

Cisco Compute Hyperconverged C240 M7 Node Family

Contents

Product overview	3
Features and benefits	4
Product specifications	5
Ordering information	7
Cisco Unified Computing Services	7
Product sustainability	7
Cisco Capital	7
Document history	8

Cisco® Compute Hyperconverged with Nutanix accelerates and simplifies the delivery of infrastructure and applications, at a global scale, through best-in-class cloud-operating models, industry-leading flexibility, and enhanced support and resiliency capabilities so you can power your hybrid multicloud future with the industry's most complete hyperconverged solution.

Product overview

Cisco Compute Hyperconverged with Nutanix

Cisco and Nutanix have partnered to introduce the industry's most complete hyperconverged solution by integrating and validating Cisco servers, storage, networking, and SaaS operations with the Nutanix hybrid multicloud platform. Cisco Compute Hyperconverged with Nutanix is built, managed, and supported holistically to deliver a more seamless experience, foster innovation, and accelerate customers' hybrid-cloud journeys.

Cisco Compute Hyperconverged C240 M7 Node family

Cisco Compute Hyperconverged C240 M7 Node family delivers performance, flexibility, and resiliency in a high-capacity solution (up to 24 disks). Physically, nodes are deployed into clusters, with a cluster consisting of one or more Cisco Compute Hyperconverged C240 M7 all-flash servers.

These servers can be interconnected and managed in two different ways:

- **UCS Managed mode:** The nodes are connected to a pair of Cisco UCS® 6400 Series or a pair of Cisco UCS 6500 Series fabric interconnects and managed as a single system using UCS Manager. The minimum number of nodes in such a cluster is three. These clusters can support both general-purpose deployments and mission-critical high-performance environments.
- **Intersight Standalone mode:** The nodes are connected to a pair of Top-of-Rack (ToR) switches and servers are centrally managed using Cisco Intersight®. While a minimum of three nodes are required to deploy a standard Nutanix cluster, we also offer an option to deploy a [single-node cluster](#) and a two-node cluster for Edge and branch locations and situations that already have a high-performance network fabric installed. Refer to the Cisco spec sheets for further detail on the use of 1-node and 2-node Nutanix clusters.

Features and benefits

Cisco Compute Hyperconverged C240 M7 All Flash and All NVMe nodes with Intel® Xeon® Scalable Processors are excellent for a wide range of enterprise workloads, including cloud computing, Virtual Desktop Infrastructure (VDI), databases, and server virtualization.

Table 1. Summary of features and benefits of Cisco Compute Hyperconverged C240 M7 All Flash and All NVMe Node

Feature	Benefit	
Memory	<ul style="list-style-type: none"> • High memory capacity • Up to 8 TB memory (32 x 256 GB DDR5 DIMMs) 	
4th Generation Intel Xeon Scalable Processors	<ul style="list-style-type: none"> • 10-nanometer (nm) processor technology • Massive processing power with up to 60 cores per socket • Larger L2 and L3 cache • Increased I/O Bandwidth with PCIe 5.0 • High-speed DDR5 memory technology for up to 4800 MT/s • Multiple built-in accelerators for new functional capabilities across AI, analytics, security, and storage • Platform level power savings to deliver sustainability goals 	
Unified network fabric (optional)	<ul style="list-style-type: none"> • Low-latency, up to 8 x 10/25/50 Gigabit Ethernet connections or up to 4 x 40/100 Gigabit Ethernet connections • Wire-once deployment model, eliminating the need to install adapters and re-cable racks and switches when changing I/O configurations • Fewer interface cards, cables, and upstream network ports to purchase, power, configure, and maintain 	
Cloud-based services and management	<p>Cisco Intersight® simplifies infrastructure operations across on-premises data centers, edge sites, and public clouds.</p> <ul style="list-style-type: none"> • Use a software-as-a-service platform that bridges applications with infrastructure • Correlate visibility and management across bare-metal servers, hypervisors, and application components • Transform operations with artificial intelligence to reach needed scale and velocity 	<p>Nutanix Cloud Platform (NCP) includes Nutanix Cloud Infrastructure (NCI), Nutanix Cloud Management (NCM), and desktop services:</p> <ul style="list-style-type: none"> • NCI unifies compute, storage and network, hypervisors and containers, in public or enterprise clouds. • NCM offers customers simplicity and ease of use to build and grow their cloud deployments and realize rapid ROI, by providing intelligent operations, self-service and orchestration, visibility, and governance. • Desktop services offer hybrid-cloud infrastructure capabilities for on-premises Virtual Desktop Infrastructure (VDI) and Desktop-as-a-Service (DaaS) use cases.
Storage	<ul style="list-style-type: none"> • All-flash and All-NVMe configurations <ul style="list-style-type: none"> ◦ Deliver high-capacity configurations for the Cisco Compute Hyperconverged Platform capacity layer • Nutanix Unified Storage provides software-defined, scale-out storage solutions for enterprise network attached storage (NAS) and object workloads for unstructured data, block storage for structured data, and backup storage. 	

Feature	Benefit
Enterprise data protection	<ul style="list-style-type: none"> • Synchronous and near synchronous replication with optional runbook automation • Multisite asynchronous replication for disaster recovery • Deduplication and compression • Disaster recovery in cloud with Nutanix cloud clusters
Security	<ul style="list-style-type: none"> • Data-at-rest encryption using self-encrypting drives and enterprise key management integration • Trusted Platform Module (TPM), a chip (microcontroller) that can securely store artifacts, including passwords, certificates, and encryption keys, which are used to authenticate the platform (node). Supports TPM 2.0. • Software-based data-at-rest encryption and micro-segmentation
Software	<ul style="list-style-type: none"> • Management software: Cisco Intersight, Nutanix Cloud Infrastructure (NCI), Nutanix Cloud Management (NCM), desktop services • Storage software: AOS Storage, Nutanix Unified Storage (NUS) – for files, objects, and volumes use cases • Hypervisor: Nutanix Acropolis Hypervisor (AHV) and VMware vSphere

Product specifications

Table 2. Specifications for Cisco Compute Hyperconverged C240 M7 All Flash and All NVMe Node

Feature	Common specifications across the C240 M7 Node family
Chassis	<ul style="list-style-type: none"> • 2RU of rack space per node
Processors	<ul style="list-style-type: none"> • One or two 4th Gen Intel Xeon Scalable Processors (Sapphire Rapids)
Chip set	<ul style="list-style-type: none"> • Intel C741 series
Memory	<ul style="list-style-type: none"> • 32 DDR5 DIMM slots: 16, 32, 64, 128 and 256 GB up to 4800 MT/s • 8 TB using 32 x 256-GB DDR5 DIMMs • 50% peak bandwidth increase over DDR4-3200, with on-die ECC; all densities are Registered DIMMs (RDIMMs))
Storage	<ul style="list-style-type: none"> • Specific drive options are available for Compute Hyperconverged C240 nodes: • C240 All Flash Node: 1.9 TB, 3.8 TB, 7.6 TB or 15.3 TB SSD disks (up to 24 drives per node) • C240 All NVMe Node: 1.9 TB, 3.8 TB, 7.6 TB and 15.3 TB NVMe disks (up to 24 drives per node) • Dual M.2 SATA SSDs with HW RAID support for hypervisor boot
PCIe	<ul style="list-style-type: none"> • Up to 8 PCIe 4.0 slots or up to 4 PCIe 5.0 slots plus 1 dedicated 12-Gbps RAID controller slot and 1 dedicated mLOM slot
Graphics Processing Units (GPUs)	<ul style="list-style-type: none"> • NVIDIA A16, A30, A40, A100-80 Tesla GPU card (optional) • NVIDIA L4, L40 GPU cards (optional)

Feature	Common specifications across the C240 M7 Node family
Network	<ul style="list-style-type: none"> • Cisco UCS Virtual Interface Card 15428 or 15238 or 15427 or 15237 (modular LAN on Motherboard) • Quad 10/25/50 G or Dual 40/100 G Ethernet VIC (Cisco UCS Virtual Interface Card 15425 or 15235) (optional) • Intel E810 dual-or quad-port Network Interface Card (Intersight Standalone Mode) • Up to 256 I/O devices programmable on demand for hypervisor and virtual machine support
Cisco Integrated Management Controller (IMC)	<ul style="list-style-type: none"> • Integrated baseboard management controller (BMC) • IPMI 2.0-compliant for management and control • One 10/100/1000 Ethernet out-of-band management interface • Command-Line Interface (CLI) and web GUI management tool for automated, lights-out management • Keyboard, Video, and Mouse (KVM) console
Advanced reliability, availability, and serviceability (RAS) features	<ul style="list-style-type: none"> • Robust reporting and analytics • Hot-swappable, front-accessible drives • Dual-redundant fans and hot-swappable, redundant power supplies for enterprise-class reliability and a convenient latching lid for easy access to internal server • Tool-free CPU insertion, enabling processor upgrades and replacements with less risk of damage • Tool-free access to all serviceable items, and color-coded indicators to guide users to hot-pluggable and serviceable items • Non-disruptive rolling upgrades using Nutanix life-cycle manager (LCM)
Front-panel connector	<ul style="list-style-type: none"> • 1 KVM console connector per node • (supplies 2 USB connectors, 1 VGA connector, and 1 serial connector)
Front-panel locator LED	<ul style="list-style-type: none"> • Helps direct administrators to specific servers in large data-center environments
Additional rear connectors	<ul style="list-style-type: none"> • 1 Gigabit Ethernet management port • 1 RS-232 serial port (RJ45 connector) • 1 Video Graphics Array (VGA) video port (DB15 connector) • 2 USB 3.0 ports
Power and cooling	<ul style="list-style-type: none"> • One or two hot-pluggable power supplies • Second power supply provides 1+1 redundancy • 1050W DC, 1200W AC, 1600W AC, or 2300W AC power supply options • 6 hot-swappable fans for front-to-rear cooling
Rail-kit options	<ul style="list-style-type: none"> • Cisco ball-bearing rail kit with optional reversible cable-management arm
Software	<ul style="list-style-type: none"> • Management software: Nutanix Cloud Infrastructure, Nutanix Cloud Management, desktop services • Storage software: AOS Storage, Nutanix Unified Storage (files, objects, and volumes) • Hypervisor: Nutanix Acropolis Hypervisor (AHV) and VMware vSphere

Ordering information

For a complete list of part numbers, refer to the [Cisco Compute Hyperconverged C240 M7 All Flash and All NVMe Node specification sheet](#).

Cisco Unified Computing Services

Cisco, Nutanix, and our industry-leading partners deliver services that accelerate your transition to Cisco Compute Hyperconverged systems. Professional services can help you create an agile infrastructure, accelerate time to value, reduce costs and risks, and maintain availability during deployment and migration. After you have deployed your system, our services can help you improve performance, availability, and resiliency as your business needs evolve.

Product sustainability

Information about Cisco's Environmental, Social, and Governance (ESG) initiatives and performance is provided in Cisco's Corporate Social Responsibility (CSR) and sustainability [reporting](#).

Table 3. Cisco environmental sustainability information

Sustainability topic		Reference
General	Information on product-material-content laws and regulations	Materials
	Information on electronic waste laws and regulations, including our products, batteries, and packaging	WEEE Compliance
	Information on product takeback and reuse program	Cisco Takeback and Reuse Program
	Sustainability inquiries	Contact: csr_inquiries@cisco.com

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

Cisco Capital

Flexible payment solutions to help you achieve your objectives

[Cisco Capital](#)® makes it easier to get the right technology to achieve your objectives, enable business transformation, and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services, and complementary third-party equipment in easy, predictable payments.

Document history

New or Revised Topic	Described In	Date
Initial release	Data Sheet	December 2023
Update for Intersight Standalone Mode	Data Sheet	February 2024

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)