



Cisco Nexus 3000 Series NX-OS Release Notes, Release 10.3(1)F

This document describes the features, issues, and exceptions of Cisco NX-OS Release 10.3(1)F software for use on Cisco Nexus 3500 and 3600 platform switches.

The new Cisco NX-OS Software Release and Image-naming Convention information is available here – [Cisco NX-OS Software Strategy and Lifecycle Guide](#).

Note: The documentation set for this product strives to use bias-free language. For the purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on RFP documentation, or language that is used by a referenced third-party product.

The following table lists the changes to this document.

Date	Description
August 19, 2022	Cisco NX-OS Release 10.3(1)F became available.

New and Enhanced Software Features

There are no new or enhanced software features introduced in Cisco NX-OS Release 10.3(1)F for Cisco Nexus 3000 series.

Hardware Features

Cisco NX-OS Release 10.3(1)F does not include any new hardware for the Cisco Nexus 3000 Series.

Release Image

Cisco Nexus 3000 Series platforms support only 64-bit image. The 64-bit Cisco NX-OS image filename begins with "nxos64-msll" (for example, nxos64-msll.10.2.3.F.bin) and this image is supported on Cisco Nexus 3600 series fixed switches and Cisco Nexus 3500-XL series switches. 32-bit image is no longer supported.

Open Issues

Bug ID	Description
CSCwc41387	Headline: Egress RACL on port-channel subinterface is not getting programmed on Nexus 3548 Symptoms: Upon application of RACL in Egress direction on Nexus 3548 port-channel sub-interface, the ACL entries are not getting programmed into hardware. Workarounds: None
CSCwc06274	Headline: PVLAN SDK resource FULL error -6 Symptoms: Problem is only seen when community vlan is converted to primary vlan in certain sequence Workarounds: Delete all the VLANs involved in the configuration and reconfigure.

Device Hardware

The following tables list the Cisco Nexus 3500 and Cisco Nexus 3600 Series hardware that Cisco NX-OS Release 10.3(1)F supports. For additional information about the supported hardware, see the Hardware Installation Guide for your Cisco Nexus 3500 and Cisco Nexus 3600 Series devices.

Cisco Nexus 3500 Switches

Product ID	Description
N3K-C3524P-XL	Cisco Nexus 3524-XL switch
N3K-C3548P-XL	Cisco Nexus 3548-XL switch

Cisco Nexus 3500 Series Fans, Fan Trays and Power Supplies

Product ID	Description
------------	-------------

N2200-PAC-400W	Cisco Nexus 2000 or 3000 400W AC power supply, forward airflow (port side exhaust)
N2200-PAC-400W-B	Cisco Nexus 2000 or 3000 400W AC power supply, reverse airflow (port side intake)
N2200-PDC-400W	Cisco Nexus 2000 or 3000 400W DC power supply, forward airflow (port side exhaust)
N3K-PDC-350W-B	Cisco Nexus 2000 or 3000 350W DC power supply, reverse airflow (port side intake)
NXA-FAN-30CFM-B	Cisco Nexus 2000 or 3000 individual fan, reverse airflow (port side intake)
NXA-FAN-30CFM-F	Cisco Nexus 2000 or 3000 individual fan, forward airflow (port side exhaust)

Cisco Nexus 3600 Switches

Product ID	Description
N3K-C3636C-R	The Cisco Nexus 3636C-R is a 1 rack unit (RU) switch with 36 100-Gigabit QSFP28 ports, 40-Gigabit QSFP, 2 management ports, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.
N3K-C36180YC-R	The Cisco Nexus 36180YC-R is a 1 rack unit (RU) switch with 48 1/10/25-Gigabit SFP ports and 6 40Gigabit QSFP/100-Gigabit QSFP28 ports, 1 management port, 1 console port, and 1 USB port. The switch supports both port-side exhaust and port-side intake airflow schemes. The switch has two power supplies, one for operations and the other for redundancy. Both power supplies must be either AC power supplies or DC power supplies.

Upgrade and Downgrade

To perform a software upgrade or downgrade, follow the instructions in the *Cisco Nexus 3500 Series NX-OS Software Upgrade and Downgrade Guide* and *Cisco Nexus 3600 Series NX-OS Software Upgrade and Downgrade Guide*.

For information about an In Service Software Upgrade (ISSU), see the [Cisco NX-OS ISSU Support Matrix](#).

MIB Support

The Cisco Management Information Base (MIB) list includes Cisco proprietary MIBs and many other Internet Engineering Task Force (IETF) standard MIBs. These standard MIBs are defined in Requests for Comments (RFCs). To find specific MIB information, you must examine the Cisco proprietary MIB structure and related IETF-standard MIBs supported by the Cisco Nexus 3000 Series switch. The MIB Support List is available at the following FTP sites:

<ftp://ftp.cisco.com/pub/mibs/supportlists/nexus3000/Nexus3000MIBSupportList.html>

Supported Optics

To determine which transceivers and cables are supported by Cisco Nexus 3000 Series switches, see the [Transceiver Module \(TMG\) Compatibility Matrix](#).

To see the transceiver specifications and installation information, see <https://www.cisco.com/c/en/us/support/interfacesmodules/transceiver-modules/products-installation-guides-list.html>.

Related Content

Cisco Nexus 3000 Series documentation: [Cisco Nexus 3000 Series switch documentation](#)

Cisco NX-OS Software Release and Image-naming Convention: [Cisco NX-OS Software Strategy and Lifecycle Guide](#)

Cisco Nexus 3000 and 9000 Series NX-API REST SDK User Guide and API Reference: [Cisco Nexus 3000 and 9000 Series NXAPI REST SDK User Guide and API Reference](#).

Licensing Information

- [Cisco NX-OS Licensing Guide](#)
- [Cisco Nexus 9000 and 3000 Series NX-OS Switch License Navigator](#)
- [Cisco Nexus Smart Licensing Using Policy User Guide](#)

Documentation Feedback

To provide technical feedback on this document, or to report an error or omission, please send your comments to nexus9k-docfeedback@cisco.com. We appreciate your feedback.

Legal Information

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2022 Cisco Systems, Inc. All rights reserved.