



Cisco Nexus 3400-S Series NX-OS Command Reference (Configuration Commands), Release 9.2(2)

First Published: 2019-07-03

Americas Headquarters

Cisco Systems, Inc.
170 West Tasman Drive
San Jose, CA 95134-1706
USA
<http://www.cisco.com>
Tel: 408 526-4000
800 553-NETS (6387)
Fax: 408 527-0883



CONTENTS

PREFACE

Preface	cxliii
Audience	cxliii
Documentation Conventions	cxliii
Documentation Feedback	cxliv
Communications, Services, and Additional Information	cxliv

CHAPTER 1

Notice	1
Notice	2

CHAPTER 2

A Commands	3
aaa accounting default	8
aaa accounting dot1x default group	9
aaa authentication dot1x default group	10
aaa authentication login ascii-authentication	11
aaa authentication login console	12
aaa authentication login default	14
aaa authentication login default fallback error local	16
aaa authentication login enable	17
aaa authentication login error-enable	18
aaa authentication login invalid-username-log	19
aaa authentication login password-aging enable	20
aaa authentication rejected	21
aaa authentication rejected in ban	22
aaa authorization commands console	23
aaa authorization commands default	24
aaa authorization ssh default group	25

aaa bypass-user	26
aaa group server ldap	27
aaa group server radius	28
aaa group server tacacs	29
aaa test-authentication	30
aaa test-radius-authentication	31
aaa user default-role	32
abort	33
abort	34
abort	35
abort	36
absolute-timeout	37
absolute start	38
accept-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l	39
access-class	41
access-list	42
access-list	43
access-list ipv6	44
access vlan	45
aclog match-log-level	46
action	47
action	48
action cli	49
action counter name value op	50
action eem test	51
action event-default	52
action forcesshut reset-reason	53
action overbudgetshut	54
action policy-default	55
action reload	56
action snmp-trap	57
action syslog msg	58

additional-paths install backup	59
additional-paths receive	60
additional-paths selection route-map	61
additional-paths send	62
address-family ipv4	63
address-family ipv4 labeled-unicast	64
address-family ipv4 labeled-unicast	65
address-family ipv4 mdt	66
address-family ipv4 mdt	67
address-family ipv4 mvpn	68
address-family ipv4 mvpn	69
address-family ipv6	70
address-family ipv6 labeled-unicast	71
address-family ipv6 labeled-unicast	72
address-family ipv6 mvpn	73
address-family ipv6 mvpn	74
address-family l2vpn evpn	75
address-family l2vpn evpn	76
address-family l2vpn vpls	77
address-family l2vpn vpls	78
address-family link-state	79
address-family link-state	80
address-family vpnv4 unicast	81
address-family vpnv4 unicast	82
address-family vpnv6 unicast	83
address-family vpnv6 unicast	84
address	85
address	86
address	87
address	88
address	89
address	90
address port-number	91
address primary	92

address secondary	93
address secondary	94
adjacency-check	95
adjacency-resolve	96
advertise-gw-ip	97
advertise-labels	98
advertise-map exist default advertise-map	99
advertise-pip	100
advertise-system-mac	101
advertise evpn multicast	102
advertise interface	103
advertise l2vpn evpn	104
advertise local-labeled-route	105
advertise virtual-rmac	106
advertisement-interval	107
advertisement-interval	108
afd queue-desired	109
affinity-group	110
affinity-group activate	111
affinity	112
affinity	113
age	114
age	115
aggregate-address	116
aggregate-address	117
alert-group user-def-cmd	118
allocate-label all	119
allocate-label option-b	120
allocate1 interface2	121
allocate2 fcoe-vlan-range	122
allocate3 shared interface3	123
allow-vni-in-ethertag	124
allow feature-set	125
allowas-in	126

allowas-in	127
allowed-locators	128
allowed-vlans	129
amt flush-routes	130
amt pseudo-interface	131
analytics cluster	132
anonymous-id	133
append-after next	134
apply profile	135
area authentication	136
area authentication	137
area default-cost	138
area default-cost	139
area filter-list route-map in	140
area filter-list route-map in	141
area nssa	142
area nssa	143
area nssa translate type7 always never supress-fa	144
area nssa translate type7 always never supress-fa	145
area range	146
area range	147
area sham-link	148
area stub	149
area stub	150
area virtual-link	151
area virtual-link	152
area virtual-link	153
area virtual-link	154
arp access-list	155
as-format asdot	156
as-override	157
assign interface shared	158
assign vlan dedicated	159
assign vrf prefix number dedicated	160

attach console module	161
attach module	162
attach module node	163
attach module port	164
auth-mechanism plain	165
authentication-check	166
authentication-check	167
authentication-check level-1	168
authentication-check level-2	169
authentication-key	170
authentication-key	171
authentication-key	172
authentication-type cleartext	173
authentication-type cleartext	174
authentication-type cleartext	175
authentication	176
authentication	177
authentication	178
authentication	179
authentication	180
authentication	181
authentication bind	182
authentication challenge	183
authentication key-chain	184
authentication key-chain	185
authentication key-chain	186
authentication key-chain	187
authentication key-chain	188
authentication key-chain	189
authentication lifetime	190
authentication text	191
authentication type md5	192
authentication window-size	193
auto-bw	194

auto-bw	195
auto-bw timers frequency	196
auto-cost reference-bandwidth	197
auto-cost reference-bandwidth	198
auto-recovery	199
auto-remap-replication-servers	200
autonomous-system	201
autoroute announce	202
autoroute metric	203
autostate	204
autovlan enable	205
awk	206

CHAPTER 3
B Commands 207

backoff	210
backup-bw	211
bandwidth	212
bandwidth	213
bandwidth	214
bandwidth	215
bandwidth	216
bandwidth	217
bandwidth	218
bandwidth	219
bandwidth	220
bandwidth kbps mbps gbps	221
banner exec	222
banner motd	223
bcm-shell module	224
bcm-shell module	225
beacon	226
begin exclude include end	227
bestpath	228
bfd-app session auto-expiry timeout	229

bfd-app session remove	230
bfd-app session src-ip dest intf	231
bfd	232
bfd	233
bfd	234
bfd	235
bfd	236
bfd	237
bfd	238
bfd authentication interop	239
bfd authentication key-id key	240
bfd echo-interface	241
bfd echo-rx-interval	242
bfd echo	243
bfd interval	244
bfd interval	245
bfd interval min_rx multiplier	246
bfd interval min_rx multiplier	247
bfd move-session target	248
bfd multihop authentication key-id key bfd multihop authentication	249
bfd multihop hosting-linecard add module	250
bfd multihop hosting-linecard add module	251
bfd multihop interval	252
bfd multihop interval min_rx multiplier	253
bfd multihop interval min_rx multiplier	254
bfd neighbor src-ip dest	255
bfd optimize subinterface	256
bfd per-link	257
bfd session-store remove client	258
bfd session-store source-ip dest-ip intf client	259
bfd session state state	260
bfd slow-timer	261
bfd startup-timer bfd startup-timer	262
bfshell	263

- bfshell cmd 264
- bfshell module 265
- bfshell module cmd 266
- binary-location 267
- bind interface 268
- bind mac-address 269
- blink 270
- bloggerd live-process-core sap 271
- bloggerd log-dump all 272
- bloggerd log-dump once log-buffer sap event-history 273
- bloggerd log-dump once pss uuid 274
- bloggerd log-throttle 275
- bloggerd log-transfer 276
- bloggerd log-transfer 277
- bloggerd parse log-buffer file 278
- bloggerd parse log-buffer file sap 279
- bloggerd parse pss file 280
- bmp-activate-server 281
- bmp-server 282
- boot-install nxos 283
- boot-order 284
- boot 285
- boot aci 286
- boot auto-copy 287
- boot kickstart 288
- boot mode docker_cluster 289
- boot mode docker_standalone 290
- boot mode lxc 291
- boot nxos 292
- boot nxos sup-1 293
- boot nxos sup-1 sup-2 294
- boot nxos sup-2 295
- boot order bootflash 296
- boot order pxe 297

boot poap enable	298
boot system	299
bootmode boot	300
bootmode extruntime	301
bootmode hitless	302
bootmode module	303
bootmode nodiagruntime	304
bootmode runtime	305
buffer-boost	306
buffer-delete	307
buffer-move	308
burst-detect enable	309
burst-detect rise-threshold bytes fall-threshold bytes2	310

CHAPTER 4**C Commands 311**

cabundle url	323
callhome	324
callhome send configuration	325
callhome send diagnostic	326
callhome test	327
callhome test inventory	328
capability additional-paths receive	329
capability additional-paths send	330
capability suppress 4-byte-as	331
capability vrf-lite	332
capture	333
capture	334
capture session	335
carrier-delay	336
catena	337
catena device-group	338
catena port-acl	339
catena port-group	340
catena vlan-group	341

cbts-member tunnel-te	342
cd	343
cdp advertise v1	344
cdp enable	345
cdp enable	346
cdp format device-id	347
cdp holdtime	348
cdp timer	349
certificate	350
cfs debug all	351
cfs distribute	352
cfs eth cos	353
cfs eth distribute	354
cfs ipv4 distribute	355
cfs ipv6 distribute	356
cfs region	357
chain	358
change-password	359
channel-group	360
channel-group	361
channel-group	362
channel-group	363
channel-group force	364
channel-group force	365
channel mode	366
channel mode active	367
chassis-family fretta	368
checkpoint	369
checkpoint	370
cipher-suite	371
class-map	372
class-map type control-plane	373
class-map type network-qos	374
class-map type psp	375

class-map type queuing	376
class-map type queuing	377
class	378
class	379
class __inline__	380
class class-default	381
class type network-qos	382
class type network-qos class-default	383
class type psp	384
class type queuing	385
clear	386
clear	387
clear	388
clear	389
clear aaa local user blocked username	390
clear access-list counters	391
clear access-list hardware counters	392
clear access-list ipsg stats	393
clear accounting log	394
clear aclqos cl-qos	395
clear aclqos fab	396
clear aclqos fc	397
clear aclqos libdrv	398
clear aclqos map	399
clear aclqos merge	400
clear aclqos pl	401
clear aclqos ppf-parse	402
clear aclqos ppf	403
clear aclqos qng-hw	404
clear aclqos qng	405
clear aclqos rl	406
clear aclqos rm	407
clear aclqos sch	408
clear aclqos stats	409

clear aclqos tbl	410
clear aclqos trace-detail	411
clear aclqos trace	412
clear aclqos uf	413
clear bfd statistics	414
clear bgp	415
clear bgp bmp stats server	417
clear bgp event-history	418
clear bgp private	419
clear bootvar log	421
clear cdp counters	422
clear checkpoint database	423
clear cli history	424
clear controller accounting log	425
clear copp statistics	426
clear cores	427
clear cores archive	428
clear counters	429
clear counters buffers	430
clear counters interface	431
clear counters interface	432
clear counters interface	433
clear counters interface all	434
clear counters interface snmp	435
clear counters tah-buffers	436
clear crypto ca trustpool timer	437
clear debug-logfile	438
clear debug logfile	439
clear dot1x all	440
clear dot1x stats interface	441
clear ecp statistics	442
clear eigrp event-history	443
clear evb hosts	444
clear evb hosts	445

clear evb statistics 446

clear fabric database dc1 vrf node-id 447

clear fabric database host all vni 448

clear fabric database host statistics 449

clear fabric database include-vrf 450

clear fabric database statistics 451

clear fabric database statistics type server-proto radius group 452

clear fabric database statistics type server-proto xmpp ip 453

clear fabric multicast event-history 454

clear fc2 455

clear fctimer session 456

clear flow cache 457

clear flow cache 458

clear flow exporter 459

clear forwarding adjacency module 460

clear forwarding cumulative counter 461

clear forwarding distribution lisp counters all 462

clear forwarding events-history 463

clear forwarding inconsistency 464

clear forwarding ipv4 multicast counters 465

clear forwarding ipv6-l3-route-history 466

clear forwarding ipv6 adjacency module 467

clear forwarding ipv6 inconsistency 468

clear forwarding ipv6 multicast counters 469

clear forwarding ipv6 route module 470

clear forwarding l2-mc-route-history 471

clear forwarding l2-oiflist-history 472

clear forwarding l2-route-history 473

clear forwarding l2mcast info l2-mc-route-history 474

clear forwarding l2mcast info l2-oiflist-history 475

clear forwarding l2mcast info l2-route-history 476

clear forwarding l2mcast info l2-xbar-history 477

clear forwarding l2mcast info statistics 478

clear forwarding l2vpn trace member-history 479

clear forwarding l3-route-history	480
clear forwarding oiflist-history	481
clear forwarding route module	482
clear forwarding trace ecmp-history	483
clear forwarding trace mfib oif-history	484
clear forwarding trace mfib oiflist-history	485
clear forwarding trace mfib platform oiflist-history	486
clear forwarding trace mfib v4-route-history	487
clear forwarding trace mfib v6-route-history	488
clear forwarding trace v4-adj-history	489
clear forwarding trace v4-pfx-history	490
clear forwarding trace v4-rmh-history	491
clear forwarding trace v6-adj-history	492
clear forwarding trace v6-pfx-history	493
clear forwarding trace v6-rmh-history	494
clear forwarding trace vobj-history	495
clear frame traffic	496
clear fs-daemon log	497
clear hardware flow ip	498
clear hardware flow ipv6	499
clear hardware flow l2	500
clear hardware ip verify	501
clear hardware profile buffer monitor	503
clear hardware profile latency monitor	504
clear hardware profile packet-drop file_instance	505
clear hardware rate-limiter	506
clear hardware rate-limiter	507
clear hsrp counters clear hsrp state-history	508
clear install all failed-standby	509
clear install failure-reason	510
clear install log-history all	511
clear install status	512
clear ip	513
clear ip adjacency statistics	514

clear ip amt tunnel	515
clear ip arp	516
clear ip arp controller-statistics	517
clear ip arp inspection log	518
clear ip arp inspection statistics vlan	519
clear ip arp multihoming-statistics	520
clear ip arp statistics	521
clear ip arp suppression-cache statistics	522
clear ip arp tunnel-statistics	523
clear ip arp vpc-statistics	524
clear ip dhcp global statistics	525
clear ip dhcp relay statistics	526
clear ip dhcp snooping binding	527
clear ip dhcp snooping statistics	528
clear ip eigrp accounting	529
clear ip eigrp event-history	530
clear ip eigrp event-history bfd	531
clear ip eigrp redistribution	532
clear ip eigrp route-map statistics redistribute	533
clear ip eigrp traffic	534
clear ip igmp event-history	535
clear ip igmp groups	536
clear ip igmp interface statistics	537
clear ip igmp snooping event-history	538
clear ip igmp snooping explicit-tracking	539
clear ip igmp snooping groups	540
clear ip igmp snooping proxy querier ports vlan	541
clear ip igmp snooping report statistics	542
clear ip igmp snooping statistics	543
clear ip interface statistics	544
clear ip lisp data-cache	545
clear ip lisp map-cache	546
clear ip lisp statistics	547
clear ip mbgp dampening	548

clear ip mbgp flap-statistics	550
clear ip mbgp peer-template	552
clear ip mfwf event-history	554
clear ip mroute	555
clear ip mroute statistics	556
clear ip msdp event-history	557
clear ip msdp peer	558
clear ip msdp policy statistics sa-policy in	559
clear ip msdp sa	560
clear ip msdp statistics	561
clear ip nat-alias address	562
clear ip nat statistics	563
clear ip nat translation	564
clear ip ospf database	566
clear ip ospf event-history	567
clear ip ospf interface	568
clear ip ospf neighbor	569
clear ip ospf policy statistics	570
clear ip ospf redistribution	572
clear ip ospf statistics	573
clear ip ospf traffic	574
clear ip pim event-history	575
clear ip pim interface statistics	576
clear ip pim policy statistics	577
clear ip pim policy statistics jp	578
clear ip pim route	579
clear ip pim statistics	580
clear ip rip policy statistics redistribute bgp	581
clear ip rip statistics	582
clear ip routing multicast event-history	583
clear ip traffic	584
clear ipv6 adjacency statistics	585
clear ipv6 amt tunnel	586
clear ipv6 dhcp-ldra statistics	587

clear ipv6 dhcp relay statistics	588
clear ipv6 eigrp route-map statistics redistribute	589
clear ipv6 icmp	590
clear ipv6 icmp vpc-statistics	591
clear ipv6 interface statistics	592
clear ipv6 lisp data-cache	593
clear ipv6 lisp statistics	594
clear ipv6 mld groups	595
clear ipv6 mroute	596
clear ipv6 neighbor	597
clear ipv6 neighbor binding	598
clear ipv6 pim event-history	599
clear ipv6 pim interface statistics	600
clear ipv6 pim policy statistics jp	601
clear ipv6 pim route	602
clear ipv6 pim statistics	603
clear ipv6 rguard statistics	604
clear ipv6 rip policy statistics redistribute bgp	605
clear ipv6 routing multicast event-history	606
clear ipv6 snooping counters	607
clear ipv6 snooping events	608
clear ipv6 snooping messages	609
clear ipv6 traffic	610
clear isis adjacency	611
clear isis dpi	612
clear isis event-history	613
clear isis ipv6 route-map statistics	614
clear isis redistribution	616
clear isis route-map statistics	617
clear isis spf-log	619
clear isis statistics	620
clear isis traffic	621
clear itd statistics	622
clear keystore	623

clear l2dbg	624
clear l2fwder statistics	625
clear l3vm event-history	626
clear lacp counters	627
clear ldap-server statistics	628
clear license	630
clear lim counters	631
clear line	632
clear lisp ddt referral-cache	633
clear lisp dynamic-eid	634
clear lisp proxy-itr	635
clear lisp site	636
clear lldp counters	637
clear lldp counters interface	638
clear logging ip access-list cache	639
clear logging logfile	640
clear logging nvram	641
clear logging onboard	642
clear logging onboard	643
clear logging session	644
clear mac address-table datapath	645
clear mac address-table dynamic	646
clear mts message statistics	647
clear mvr counters	648
clear mvr counters receiver-ports	649
clear mvr counters source-ports	650
clear nbm flow statistics	651
clear ngoam	652
clear ngoam	653
clear ngoam	654
clear ngoam	655
clear ngoam pathtrace	656
clear ntp session	657
clear ntp statistics	658

clear nvram 659

clear nxapi-server logs 660

clear openflow switch controller all 661

clear ospfv3 database 662

clear ospfv3 event-history 663

clear ospfv3 interface 664

clear ospfv3 neighbor 665

clear ospfv3 policy statistics 666

clear ospfv3 statistics 668

clear ospfv3 traffic 669

clear peer-info interface vsan 670

clear pktmgr client 671

clear pktmgr interface 672

clear plb analytics 673

clear port-security dynamic address vlan 674

clear port-security dynamic interface 675

clear processes log all 676

clear processes log all vdc-all 677

clear processes log archive 678

clear processes log pid 679

clear processes vdc log all 680

clear processes vdc log pid 681

clear ptp corrections 682

clear ptp counters interface 683

clear qos policies 684

clear qos policies force 685

clear qos statistics 686

clear queuing burst-detect 687

clear queuing pfc-queue 688

clear queuing pfc-queue interface 689

clear queuing tah-pfc-queue 690

clear radius-server statistics 691

clear radius session 693

clear rmon 694

clear route-map pbr-statistics	695
clear routing event-history	696
clear routing ip multicast mfdm pending counters	697
clear routing ip multicast rpf-source retry-cache	698
clear routing ipv6 event-history	699
clear routing ipv6 multicast	700
clear routing multicast	701
clear scheduler logfile	702
clear screen	703
clear session state name	704
clear sflow statistics	705
clear snmp counters	706
clear snmp hostconfig	707
clear sockets statistics	708
clear spanning-tree counters	709
clear spanning-tree detected-protocols	710
clear spanning-tree sps-hist	711
clear ssh hosts	712
clear statistics module-all	713
clear statistics module	714
clear sup-monitor drops session	715
clear system login failures	716
clear system reset-reason	717
clear tacacs-server statistics	718
clear tech-support lock	720
clear tech-support lock	721
clear user	722
clear veobc counters	723
clear vlan access-list counters	724
clear vlan counters	725
clear vmtracker counters	726
clear vpc statistics all	727
clear vpc statistics peer-keepalive	728
clear vpc statistics vpc	729

clear vpc transport statistics	730
clear vrrp statistics	731
clear vrrpv3 event-history	732
clear vrrpv3 statistics	733
clear vtp counters	734
cli alias name	735
cli create new-cmd	736
cli var name	737
cli var name	738
cli var name	739
cli var name	740
cli verifyrun	741
client-to-client reflection	742
clis all	743
clock-tolerance ntp oneway absolute	744
clock format 12	745
clock format show-timezone debug	746
clock format show-timezone syslog	747
clock protocol	748
clock set	749
clock summer	751
clock sync-interval	752
cluster-id	753
collect	754
collect	755
collect	756
collect	757
collect	758
collect	759
collect counter bytes	760
collect ip version	761
collect timestamp sys-uptime first	762
collect transport tcp flags	763
color	764

commit	765
commit	766
commit	767
commit verbose	768
compress-bitfields ipv6 multicast	769
compress-bitfields ipv6 multicast	770
compress-bitfields multicast	771
conf-offset	772
confederation identifier	773
confederation peers	774
config-source controller	775
configure	776
configure config-template on substitute	777
configure maintenance profile normal	778
configure profile	779
configure replace	780
configure replace abort	781
configure replace commit	782
configure session	783
configure sync	784
congestion-control dctcp ecn-threshold bytes	785
congestion-control ecn	786
congestion-control random-detect	787
congestion-control random-detect forward-nonecn	788
congestion-control random-detect global-buffer minimum-threshold maximum-threshold	789
congestion-control tail-drop	790
connect	791
connected-prefix-sid-map	792
continue	793
contract-id	794
control-plane	795
control-plane dynamic	796
control vlan	797
control vlan	798

controller-credentials username password 0	799
controller description	800
controller ip vrf	801
controller ipv4	802
controller ipv4	803
controller type l2 identifier	804
copp copy profile prefix	805
copp distributed-policing enable	806
copp profile	807
copp profile	808
copp rate-limit disable	809
copy	810
copy	812
copy licenses	813
copy licenses	814
copy recursive	815
copy running vdc-all	816
copy vdc-all	817
core-on-no-memory	818
core-on-no-memory	819
cost	820
count	821
count	822
counter name value op	823
crypto ca authenticate	824
crypto ca crt request	825
crypto ca enroll	826
crypto ca export pkcs12	827
crypto ca import certificate	828
crypto ca import pkcs12	829
crypto ca lookup	830
crypto ca remote ldap	831
crypto ca test verify	832
crypto ca trustpoint	833

[crypto ca trustpool import url](#) 834
[crypto ca trustpool import url clean](#) 835
[crypto ca trustpool policy](#) 836
[crypto cert ssh-authorize](#) 837
[crypto certificatemap mapname](#) 838
[crypto key generate rsa](#) 839
[crypto key param rsa label modulus](#) 840
[crypto key zeroize rsa](#) 841
[cryptographic-algorithm](#) 842
[customer-id](#) 843
[cut](#) 844

CHAPTER 5
D Commands 845

[dampen-igp-metric](#) 851
[dampening](#) 852
[dampening](#) 853
[dampening](#) 854
[data-pattern](#) 855
[data-pattern pad](#) 856
[data-source](#) 857
[database-mapping](#) 858
[databits](#) 859
[databits](#) 860
[datapath-id](#) 861
[datapath-id](#) 862
[db-jid](#) 863
[db-security user password](#) 864
[db-table](#) 865
[dead-interval](#) 866
[dead-interval](#) 867
[dead-interval](#) 868
[deadtime](#) 869
[deadtime](#) 870
[deadtime](#) 871

default-information originate	872
default-information originate	873
default-information originate	874
default-information originate	875
default-information originate	876
default-information originate	877
default-information originate always rd route-target	878
default-metric	879
default-metric	880
default-metric	881
default-metric	882
default-metric	883
default-miss	884
default-originate	885
default echo revision	886
default permit	887
default permit	888
default permit	889
define	890
delay-restore time	891
delay	892
delay	893
delay	894
delay peer-link	895
delay restore	896
delay restore interface-vlan	897
delay restore orphan-port	898
delay up	899
delete	900
delete ca-certificate	901
delete certificate	902
delete crl	903
demand-circuit	904
depth	905

depth	906
description	907
description	908
description	909
description	910
description	911
description	912
description	913
description	914
description	915
description	916
description	917
description	918
description	919
description	920
description	921
description	922
description	923
description	924
description	925
description	926
description	927
description	928
description	929
description	930
description	931
description	932
description	933
description	934
description	935
description	936
description	937
description	938
description	939

description	940
description	941
description	942
description	943
description	944
description	945
description	946
description	947
description	948
description	949
description	950
description	951
description	952
description description	953
dest-ipaddr	954
dest-ipaddr	955
dest-port	956
dest	957
destination-group	958
destination-profile	959
destination-profile	960
destination-profile CiscoTAC-1 alert-group	961
destination-profile CiscoTAC-1 email-addr	962
destination-profile CiscoTAC-1 http	963
destination-profile CiscoTAC-1 message-level	964
destination-profile CiscoTAC-1 message-size	965
destination-profile CiscoTAC-1 transport-method http	966
destination-profile CiscoTAC-1 transport-method email	967
destination-profile alert-group	968
destination-profile email-addr	969
destination-profile format	970
destination-profile full-txt-destination alert-group	971
destination-profile full-txt-destination email-addr	972
destination-profile full-txt-destination http	973

destination-profile full-txt-destination message-size	974
destination-profile full-txt-destination message-level	975
destination-profile full-txt-destination transport-method http	976
destination-profile full-txt-destination transport-method email	977
destination-profile http	978
destination-profile message-level	979
destination-profile message-size	980
destination-profile short-txt-destination alert-group	981
destination-profile short-txt-destination email-addr	982
destination-profile short-txt-destination http	983
destination-profile short-txt-destination message-size	984
destination-profile short-txt-destination message-level	985
destination-profile short-txt-destination transport-method http	986
destination-profile short-txt-destination transport-method email	987
destination-profile transport-method email	988
destination-profile transport-method http	989
destination-sup interface	990
destination	991
destination1 interface	992
destination	993
destination	994
destination	995
destination	996
destination	997
destination filter ip	998
destination filter ip any any	999
destination group	1000
destination interface	1001
destination ip	1002
device-group	1003
device-group	1004
device-role	1005
device-role	1006
device-role	1007

dfc-tuning-delay 1008

diagnostic bootup level 1009

diagnostic bootup level bypass 1010

diagnostic clear result module all diagnostic clear result module test 1011

diagnostic monitor interval module test all hour min second 1012

diagnostic monitor module test all 1013

diagnostic ondemand action-on-failure continue failure-count diagnostic ondemand action-on-failure stop 1014

diagnostic ondemand iteration 1015

diagnostic ondemand test-parameter module test port_lb packet-length 1016

diagnostic start module test 1017

diagnostic stop module test all 1018

diagnostic test simulation module test diagnostic test simulation module test clear 1019

diff-clean 1020

diff-clean all-users 1021

diff 1022

dir 1023

disable-connected-check 1024

disable-fka 1025

disable-peer-as-check 1026

disable-policy-batching 1027

disable 1028

discard-route external 1029

discard-route external 1030

discovery 1031

distance 1032

distance 1033

distance 1034

distance 1035

distance 1036

distance 1037

distance 1038

distribute into route-map all 1039

distribute link-state 1040

dns	1041
domain-id	1042
domain-id secondary	1043
domain-tag	1044
dont-capability-negotiate	1045
dos2nxos	1046
dot1q	1047
dot1q	1048
dot1q	1049
dot1q default dynamic	1050
dot1x default	1051
dot1x default	1052
dot1x host-mode	1053
dot1x initialize	1054
dot1x mac-auth-bypass	1055
dot1x mac-move	1056
dot1x max-reauth-req	1057
dot1x max-req	1058
dot1x pae	1059
dot1x port-control	1060
dot1x radius-accounting	1061
dot1x re-authenticate interface	1062
dot1x re-authentication	1063
dot1x re-authentication	1064
dot1x show credential	1065
dot1x start supplicant interface	1066
dot1x supplicant credential	1067
dot1x supplicant credential	1068
dot1x supplicant max-start	1069
dot1x supplicant max-start	1070
dot1x supplicant timeout auth-period	1071
dot1x supplicant timeout auth-period	1072
dot1x supplicant timeout held-period	1073
dot1x supplicant timeout held-period	1074

dot1x supplicant timeout start-period	1075
dot1x supplicant timeout start-period	1076
dot1x system-auth-control	1077
dot1x timeout inactivity-period	1078
dot1x timeout inactivity-period	1079
dot1x timeout quiet-period	1080
dot1x timeout quiet-period	1081
dot1x timeout ratelimit-period	1082
dot1x timeout re-authperiod	1083
dot1x timeout re-authperiod	1084
dot1x timeout server-timeout	1085
dot1x timeout supp-timeout	1086
dot1x timeout tx-period	1087
dot1x timeout tx-period	1088
down-bit-ignore	1089
downlink delay	1090
dpp set-qos-group	1091
drop-trigger	1092
droplist	1093
droplist	1094
dscp	1095
dscp	1096
dscp	1097
dscp	1098
dscp	1099
dscp	1100
dst-grp	1101
dual-active exclude interface-vlan	1102
duplex	1103
duplex	1104
duplicate-message throttle	1105
dynamic-capability	1106
dynamic-med-interval	1107

CHAPTER 6**E Commands 1109**

- [eapol mac-address 1116](#)
- [ebgp-multihop 1117](#)
- [echo 1118](#)
- [echo 1119](#)
- [ecp max-retries 1120](#)
- [ecp mode lan 1121](#)
- [ecp retransmission-timer-exponent 1122](#)
- [eem test 1123](#)
- [eemtest policy-add 1124](#)
- [eemtest policy-remove 1125](#)
- [egress-engineering 1126](#)
- [egress 1127](#)
- [eid-prefix 1128](#)
- [eigrp event-history cli size 1129](#)
- [eigrp file-debug 1130](#)
- [email-addr 1131](#)
- [email-contact 1132](#)
- [email 1133](#)
- [email 1134](#)
- [enable 1135](#)
- [enable 1136](#)
- [enable Cert 1137](#)
- [encapsulation dot1q 1138](#)
- [encapsulation dot1q 1139](#)
- [encrypt pause-frame 1140](#)
- [encryption decrypt type6 1141](#)
- [encryption delete type6 1142](#)
- [encryption re-encrypt obfuscated 1143](#)
- [end 1144](#)
- [endpoint 1145](#)
- [enforce-first-as 1146](#)
- [enrollment terminal 1147](#)

errdisable	1148
errdisable detect cause	1149
errdisable detect cause acl-exception	1150
errdisable port detect cause acl-exception	1151
errdisable recovery interval	1152
erspan-id	1153
ethalyzer local	1154
ethernet-segment	1155
ethernet-segment delay-restore time	1156
ethernet-tag encapsulation dot1q default static	1157
ethernet-tag encapsulation dot1q static	1158
ethernet-tag encapsulation vni default static	1159
ethernet-tag encapsulation vni static	1160
evb mac	1161
evb reinit-keep-alive	1162
evb resource-wait-delay	1163
event-history	1164
event-history acllog category all	1165
event-history acllog category all	1166
event-history acllog category fc2	1167
event-history acllog category fc2	1168
event-history acllog category mts	1169
event-history acllog category mts	1170
event-history adbm category all	1171
event-history adbm category all	1172
event-history adbm category fc2	1173
event-history adbm category fc2	1174
event-history adbm category mts	1175
event-history adbm category mts	1176
event-history callhome	1177
event-history capability	1178
event-history cli	1179
event-history copp category all	1180
event-history copp category all	1181

event-history copp category fc2	1182
event-history copp category fc2	1183
event-history copp category mts	1184
event-history copp category mts	1185
event-history dot1x	1186
event-history drap category all	1187
event-history drap category all	1188
event-history drap category mts	1189
event-history drap category mts	1190
event-history eltm category all	1191
event-history eltm category all	1192
event-history eltm category fc2	1193
event-history eltm category fc2	1194
event-history eltm category mts	1195
event-history eltm category mts	1196
event-history epp category all	1197
event-history epp category all	1198
event-history epp category fc2	1199
event-history epp category fc2	1200
event-history epp category mts	1201
event-history epp category mts	1202
event-history errors	1203
event-history ethpm	1204
event-history events	1205
event-history exceptionlog	1206
event-history fcoe_mgr category all	1208
event-history fcoe_mgr category all	1209
event-history fcoe_mgr category fc2	1210
event-history fcoe_mgr category fc2	1211
event-history fcoe_mgr category mts	1212
event-history fcoe_mgr category mts	1213
event-history hardware-telemetry	1214
event-history im category mts	1215
event-history imp category all	1216

event-history imp category all	1217
event-history imp category fc2	1218
event-history imp category fc2	1219
event-history imp category mts	1220
event-history imp category mts	1221
event-history keystore	1222
event-history lacp category all	1223
event-history lacp category all	1224
event-history lacp category fc2	1225
event-history lacp category fc2	1226
event-history lacp category mts	1227
event-history lacp category mts	1228
event-history lem-mgr category all	1229
event-history lem-mgr category all	1230
event-history lem-mgr category fc2	1231
event-history lem-mgr category fc2	1232
event-history lem-mgr category mts	1233
event-history lem-mgr category mts	1234
event-history license	1235
event-history lldp category all	1236
event-history lldp category all	1237
event-history lldp category fc2	1238
event-history lldp category fc2	1239
event-history lldp category mts	1240
event-history lldp category mts	1241
event-history m2rib category all	1242
event-history mfdm category all	1243
event-history mfdm category all	1244
event-history mfdm category fc2	1245
event-history mfdm category fc2	1246
event-history mfdm category mts	1247
event-history mfdm category mts	1248
event-history mmode category all	1249
event-history module	1250

event-history npv category all	1251
event-history npv category all	1252
event-history npv category fc2	1253
event-history npv category fc2	1254
event-history npv category mts	1255
event-history npv category mts	1256
event-history pfstat category all	1257
event-history pfstat category all	1258
event-history pfstat category fc2	1259
event-history pfstat category fc2	1260
event-history pfstat category mts	1261
event-history pfstat category mts	1262
event-history platform buffer-size	1263
event-history platform category all	1264
event-history platform category all	1265
event-history pltfm_config category all	1266
event-history pltfm_config category all	1267
event-history pltfm_config category fc2	1268
event-history pltfm_config category fc2	1269
event-history pltfm_config category mts	1270
event-history pltfm_config category mts	1271
event-history plugin	1272
event-history poap category all	1273
event-history poap category all	1274
event-history poap category fc2	1275
event-history poap category fc2	1276
event-history poap category mts	1277
event-history poap category mts	1278
event-history port-profile category all	1279
event-history port-profile category mts	1280
event-history port-resources category all	1281
event-history port-resources category all	1282
event-history port-resources category fc2	1283
event-history port-resources category fc2	1284

event-history port-resources category mts	1285
event-history port-resources category mts	1286
event-history port-security category all	1287
event-history port-security category all	1288
event-history port-security category fc2	1289
event-history port-security category fc2	1290
event-history port-security category mts	1291
event-history port-security category mts	1292
event-history port category fc2	1293
event-history port category fc2	1294
event-history port category mts	1295
event-history port category mts	1296
event-history port_client category all	1297
event-history port_client category all	1298
event-history port_client category fc2	1299
event-history port_client category fc2	1300
event-history port_client category mts	1301
event-history port_client category mts	1302
event-history san-port-channel category all	1303
event-history san-port-channel category all	1304
event-history san-port-channel category fc2	1305
event-history san-port-channel category fc2	1306
event-history san-port-channel category mts	1307
event-history san-port-channel category mts	1308
event-history sensor	1309
event-history session-mgr category all	1310
event-history session-mgr category all	1311
event-history session-mgr category mts	1312
event-history session-mgr category mts	1313
event-history sflow	1314
event-history snmp	1315
event-history spanning-tree category all	1316
event-history spm category all	1317
event-history spm category all	1318

event-history spm category fc2	1319
event-history spm category fc2	1320
event-history spm category mts	1321
event-history spm category mts	1322
event-history stripcl category all	1323
event-history stripcl category all	1324
event-history stripcl category mts	1325
event-history tamnw category all	1326
event-history tamnw category all	1327
event-history tamnw category fc2	1328
event-history tamnw category fc2	1329
event-history tamnw category mts	1330
event-history tamnw category mts	1331
event-history udld category all	1332
event-history ufdm category all	1333
event-history ufdm category all	1334
event-history ufdm category fc2	1335
event-history ufdm category fc2	1336
event-history ufdm category mts	1337
event-history ufdm category mts	1338
event-history vdc category all	1339
event-history vdc category all	1340
event-history vdc category mts	1341
event-history xbar category all	1342
event-history xbar category all	1343
event-history xbar category debug	1344
event-history xbar category debug	1345
event-history xbar category mts	1346
event-history xbar category mts	1347
event-log-size	1348
event-logging	1349
event	1350
event	1351
event application sub-system type	1352

event cli match	1353
event counter name entry-val entry-op	1354
event fanabsent time	1355
event fanbad time	1356
event fib adjacency extra	1357
event fib resource tcam usage	1358
event fib route	1359
event gold module test testing-type scheduled consecutive-failure	1360
event manager applet	1361
event manager clear counter	1362
event manager clear history events	1363
event manager environment	1364
event manager policy	1365
event manager run	1366
event memory	1367
event module-failure type module count	1368
event module status module1	1369
event neighbor-discovery	1370
event none	1371
event oir fan	1372
event oir module	1373
event oir powersupply	1374
event policy-default count	1375
event poweroverbudget	1376
event snmp oid get-type exact entry-op entry-val poll-interval	1377
event storm-control	1379
event syslog pattern	1380
event sysmgr memory major minor clear	1381
event sysmgr switchover count time	1382
event temperature threshold	1383
event test match	1384
event timer	1385
event track state	1386
evpn	1387

evpn esi multihoming 1388
 evpn multihoming core-tracking 1389
 evpn multisite border-gateway 1390
 evpn multisite dci-tracking 1391
 evpn multisite fabric-tracking 1392
 evpn storm-control level 1393
 exceptionlog module syserr devid errtype errcode phylayer ports harderror 1394
 exclude access-list 1395
 exclude access-list 1396
 exec-timeout 1397
 exec-timeout 1398
 existing-cli 1399
 exit 1400
 exit 1401
 exp 1402
 explicit-null 1403
 explicit-path 1404
 explicit-path identifier 1405
 export-gateway-ip 1406
 export map 1407
 export vrf default map 1408
 exporter-id 1409
 exporter 1410
 exporter 1411
 exporter 1412
 exporter 1413
 exporter 1414

CHAPTER 7
F Commands 1415

fabric-soo 1420
 fabric database auto-pull dci node-id 1421
 fabric database auto-pull dci vrf node-id 1422
 fabric database auto-pull vni interface 1423
 fabric database inherit-profile-map 1424

fabric database mobility-domain	1425
fabric database override-profile	1426
fabric database override-vrf-profile	1427
fabric database profile-map	1428
fabric database profile-map global	1429
fabric database refresh dot1q	1430
fabric database refresh vni	1431
fabric database static-host	1432
fabric database timer	1433
fabric database type bl-dci	1434
fabric database type cabling	1435
fabric database type host	1436
fabric database type network	1437
fabric database type partition	1438
fabric database type profile	1439
fabric forwarding admin-distance	1440
fabric forwarding anycast-gateway-mac	1441
fabric forwarding dup-host-ip-addr-detection	1442
fabric forwarding dup-host-recovery-timer recover-count	1443
fabric forwarding dup-host-unfreeze-timer unfreeze-count	1444
fabric forwarding limit-vlan-mac	1445
fabric forwarding mode anycast-gateway	1446
fabric forwarding selective-host-probe	1447
fabric multicast event-history bgp	1448
fabric multicast event-history ha	1449
fabric multicast event-history hmm	1450
fabric multicast event-history isis	1451
fabric multicast event-history m2rib	1452
fabric multicast event-history m6rib	1453
fabric multicast event-history mrrib	1454
fabric multicast event-history pim	1455
fabric multicast event-history pim6	1456
failaction	1457
failaction	1458

fast-convergence	1459
fast-convergence	1460
fast-external-falover	1461
fast-flood enable	1462
fast-flood enable	1463
fast-flood enable	1464
fast-flood interval	1465
fast-flood interval	1466
fast-flood interval	1467
fast-reload	1468
fast-reload network-os	1469
fast-reroute	1470
fast-reroute backup-prot-preempt optimize-bw	1471
fdroplateny network	1472
fcoe	1473
fcoe	1474
fcoe enable-fex	1475
fcoe fcf-priority	1476
fcoe fcmep	1477
fcoe fka-adv-period	1478
fcoe veloopback	1479
fcoe vsan	1480
fctimer D_S_TOV	1481
fctimer E_D_TOV	1482
fctimer R_A_TOV	1483
fctimer abort	1484
fctimer commit	1485
fctimer distribute	1486
feature-set	1487
feature-set	1488
feature	1489
feature analytics	1490
feature bash-shell	1491
feature bfd	1492

feature bgp	1493
feature catena	1494
feature container-tracker	1495
feature dhcp	1496
feature dot1x	1497
feature eigrp	1498
feature evb	1499
feature evmed	1500
feature fabric forwarding	1501
feature flexlink	1502
feature grpc	1503
feature hardware-telemetry	1504
feature hsrp	1505
feature icam	1506
feature imp	1507
feature interface-vlan	1508
feature isis	1509
feature itd	1510
feature lacp	1511
feature ldap	1512
feature lldp	1513
feature msdp	1514
feature mvpn	1515
feature nat	1516
feature nbm	1517
feature netconf	1518
feature ngmvpn	1519
feature ngoam	1520
feature ngoam	1521
feature npiv	1522
feature ntp	1523
feature nv overlay	1524
feature nxapi	1525
feature nxdb	1526

feature nxsdk	1527
feature openflow	1528
feature openflow	1529
feature ospf	1530
feature ospfv3	1531
feature password encryption aes	1532
feature pbr	1533
feature pim	1534
feature pim6	1535
feature plb	1536
feature poap	1537
feature poe	1538
feature pong	1539
feature port-security	1540
feature private-vlan	1541
feature privilege	1542
feature ptp	1543
feature restconf	1544
feature rip	1545
feature scheduler	1546
feature scp-server	1547
feature sflow	1548
feature sftp-server	1549
feature signature-verification	1550
feature sla responder	1551
feature sla sender	1552
feature sla twamp-server	1553
feature smart-channel	1554
feature ssh	1555
feature tacacs	1556
feature telnet	1557
feature tunnel	1558
feature udlld	1559
feature vmtracker	1560

feature vn-segment-vlan-based	1561
feature vpc	1562
feature vrrp	1563
feature vrrpv3	1564
feature vtp	1565
fec	1566
fec	1567
fec	1568
fhrp delay minimum	1569
fhrp delay reload	1570
filter	1571
filter access-group	1572
filter ip	1573
filter ipv6 access-group	1574
filter out	1575
filter tx control-packets	1576
filter vlan	1577
filter vlan include-untagged	1578
find	1579
fips debug errors debug	1580
fips mode enable	1581
flow-count	1582
flow-count	1583
flow exporter	1584
flow forward	1585
flow monitor	1586
flow record	1587
flow timeout	1588
flowcontrol hardware	1589
flowcontrol receive	1590
flush-routes	1591
flush-routes	1592
flush-routes	1593
flush-routes	1594

[flush-routes](#) 1595
[flush-routes](#) 1596
[follow](#) 1597
[format](#) 1598
[format bootflash](#) 1599
[format bootflash check-filesystem](#) 1600
[format usb1](#) 1601
[forward](#) 1602
[forwarding-adjacency](#) 1603
[fragments](#) 1604
[frequency](#) 1605
[from to](#) 1606
[from to](#) 1607
[fte event](#) 1608
[fte exporter](#) 1609
[fte monitor](#) 1610
[fte record](#) 1611
[fte system monitor](#) 1612
[ftrace](#) 1613

CHAPTER 8
G Commands 1615

[generate type7_encrypted_secret](#) 1616
[getnext](#) 1617
[global-block](#) 1618
[global ingress-replication protocol bgp](#) 1619
[global suppress-arp](#) 1620
[graceful-restart-helper](#) 1621
[graceful-restart](#) 1622
[graceful-restart](#) 1623
[graceful-restart](#) 1624
[graceful-restart](#) 1625
[graceful-restart](#) 1626
[graceful-restart](#) 1627
[graceful-restart](#) 1628

graceful-restart	1629
graceful-restart grace-period	1630
graceful-restart grace-period	1631
graceful-restart helper-disable	1632
graceful-restart helper-disable	1633
graceful-restart restart-time	1634
graceful-restart stalepath-time	1635
graceful-restart t3 manual	1636
graceful-restart t3 manual	1637
graceful-restart t3 manual	1638
graceful consistency-check	1639
grep	1640
grep	1641
grep	1642
group drop-events	1643
group latency-events	1644
guestshell	1645
gunzip	1646
gzip	1647

CHAPTER 9**H Commands 1649**

ha-policy single	1652
hardware-telemetry fte	1653
hardware-telemetry inband-telemetry	1654
hardware-telemetry postcard-telemetry	1655
hardware-telemetry sxx	1656
hardware access-list lou resource threshold	1657
hardware access-list match inner-header	1658
hardware access-list module	1659
hardware access-list team label ing-racl 9	1660
hardware access-list team region	1661
hardware access-list team region double-wide	1662
hardware access-list team region qualify udf	1663
hardware access-list team region tcp-nat	1664

hardware ecmp hash-offset	1665
hardware ecmp hash-polynomial	1666
hardware ejector enable	1667
hardware fan-zone raise-speed	1668
hardware forwarding l3 resource route non-deterministic	1669
hardware forwarding unicast trace	1670
hardware ip glean throttle	1671
hardware ip glean throttle maximum	1672
hardware ip glean throttle syslog	1673
hardware ip glean throttle timeout	1674
hardware ipv6 glean throttle	1675
hardware ipv6 glean throttle maximum	1676
hardware ipv6 glean throttle syslog	1677
hardware ipv6 glean throttle timeout	1678
hardware module boot-order reverse	1679
hardware multicast global-tx-span	1680
hardware profile buffer info poll-interval timer	1681
hardware profile buffer info port-threshold threshold	1682
hardware profile buffer monitor unicast	1683
hardware profile buffer qosgroup threshold	1684
hardware profile buffer span-threshold	1685
hardware profile ecmp auto-recovery threshold	1686
hardware profile ecmp resilient	1687
hardware profile ecmp template module	1688
hardware profile forwarding-mode	1689
hardware profile front portmode	1690
hardware profile ipv6 alpm carve-value	1691
hardware profile ipv6 lpm-entries maximum	1692
hardware profile latency monitor	1693
hardware profile module	1694
hardware profile multicast flex-stats-enable	1695
hardware profile multicast max-limit	1696
hardware profile multicast max-limit lpm-entries	1697
hardware profile multicast nlb	1698

hardware profile multicast optimization disable	1699
hardware profile multicast prefer-source-tree	1700
hardware profile multicast rpf-check-optimization	1701
hardware profile multicast service-reflect port	1702
hardware profile multicast slow-receiver port	1703
hardware profile multicast syslog-threshold	1704
hardware profile openflow	1705
hardware profile packet-drop	1706
hardware profile pbr skip-selfip	1707
hardware profile pfc mmu buffer-reservation	1708
hardware profile portmode	1709
hardware profile statistics pstat	1710
hardware profile svi flex-stats-enable	1711
hardware profile team ipv6-sup-tcam match-inner	1712
hardware profile team region	1713
hardware profile team region span qualify udf	1714
hardware profile team region spanv6-l2 qualify udf	1715
hardware profile team region spanv6 qualify udf	1716
hardware profile team resource service-template	1717
hardware profile team resource template	1718
hardware profile team syslog-threshold	1719
hardware profile ucast6 lpm-65-to-127-max-limit	1720
hardware profile ucast6 max-limit	1721
hardware profile unicast enable-host-ecmp	1722
hardware profile unicast syslog-threshold	1723
hardware qos dynamic-buffer-sharing	1724
hardware qos fc rate-shaper	1725
hardware qos pfc mc-drop	1726
hardware sample-redirect module redirect-interface	1727
head	1728
header-type 2	1729
hello-interval	1730
hello-interval	1731
hello-interval	1732

history	1733
history	1734
history	1735
history	1736
history	1737
history	1738
holdtime	1739
hop-limit maximum	1740
hop-limit minimum	1741
hop	1742
host-reachability protocol	1743
host	1744
host group permit	1745
host source group permit	1746
hostname	1747
hostname dynamic	1748
hostname dynamic	1749
hostname dynamic	1750
hsrp	1751
hsrp anycast	1752
hsrp bfd	1753
hsrp bfd all-interfaces	1754
hsrp delay minimum	1755
hsrp force state vlan	1756
hsrp ipv6	1757
hsrp mac-refresh	1758
hsrp timers extended-hold	1759
hsrp use-bia	1760
hsrp version 1	1761
http get	1762
http proxy server	1763
human	1764
human	1765
hw-module logging onboard	1766

hw-module logging onboard 1767

CHAPTER 10

I Commands 1769

icam monitor entries acl module inst 1786

icam monitor interval num_intervals 1787

icam monitor resource acl_team module inst 1788

icam monitor scale 1789

icam monitor scale 1791

icmp-echo 1792

icmpv6 cfs-queue 1793

icmpv6 library mts-queue 1794

icmpv6 mts-queue 1795

import 1796

import interface 1797

import l2vpn evpn 1798

import map 1799

import running-config 1800

import vpn unicast 1801

import vrf default map 1802

in-label allocate 1803

inband-telemetry exporter 1804

inband-telemetry flow-profile 1805

inband-telemetry monitor 1806

inband-telemetry queue-profile 1807

inband-telemetry record 1808

inband-telemetry system monitor 1809

inband-telemetry watchlist ip 1810

include-icv-indicator 1811

include profile 1812

include profile any 1813

index next-label 1814

index next 1815

ingress-mtu 1816

ingress-replication protocol bgp 1817

ingress-replication protocol static	1818
ingress	1819
ingress interface	1820
ingress interface	1821
inherit peer-policy	1822
inherit peer-policy	1823
inherit peer-session	1824
inherit peer	1825
inherit port-profile	1826
initial-delay	1827
initial-refresh skip	1828
inject-map exist-map	1829
innoshell	1830
innoshell cmd	1831
innoshell module	1832
innoshell module cmd	1833
install activate	1834
install add	1835
install all	1836
install all network-os	1837
install commit	1838
install deactivate	1839
install epld	1840
install epld	1841
install feature-set fcoe-npv	1842
install license	1843
install license	1844
install remove	1845
install reset	1846
install verify	1847
instance-id	1848
instance	1849
instance	1850
instance vlan	1851

interface	1852
interface	1853
interface	1854
interface	1855
interface	1856
interface	1857
interface	1858
interface	1859
interface	1860
interface	1861
interface	1862
interface	1863
interface	1864
interface	1865
interface	1866
interface	1867
interface	1868
interface breakout-profile	1869
interface breakout module	1870
interface breakout module	1871
interface breakout module port map	1872
interface breakout module port map	1873
interface down delay	1874
interop-enable	1875
interval	1876
interval	1877
ip	1878
ip	1879
ip	1880
ip	1881
ip	1882
ip	1883
ip	1884
ip access-class	1885

ip access-group	1886
ip access-list	1887
ip access-list match-local-traffic	1888
ip address	1889
ip address dhcp	1890
ip address ipv6 address port	1891
ip address secondary	1892
ip adjacency peer-gmac	1893
ip adjacency remote-adj	1894
ip adjacency route distance	1895
ip amt anycast-relay-prefix	1896
ip amt gateway	1897
ip amt join-policy	1898
ip amt qqic	1899
ip amt relay-advertisement-address	1900
ip amt relay	1901
ip amt state-limit	1902
ip amt tunnel-limit	1903
ip arp	1904
ip arp allow-static-arp-outside-subnet	1905
ip arp cache limit	1906
ip arp cos	1907
ip arp delete	1908
ip arp event-history size	1909
ip arp event-history size	1911
ip arp evpn timeout	1913
ip arp gratuitous hsrp duplicate	1914
ip arp gratuitous request	1915
ip arp gratuitous update	1916
ip arp inspection filter vlan	1917
ip arp inspection log-buffer entries	1918
ip arp inspection trust	1919
ip arp inspection validate	1920
ip arp inspection vlan	1921

ip arp off-list timeout	1922
ip arp rarp fabric-forwarding	1923
ip arp rarp fabric-forwarding	1924
ip arp rarp fabric-forwarding rate-limit	1925
ip arp suppression-cache	1926
ip arp suppression timeout	1927
ip arp synchronize	1928
ip arp timeout	1929
ip arp timeout	1930
ip arp unnum-svi-dup-ip-detection	1931
ip arp unnum-svi-sw-replication	1932
ip as-path access-list deny	1933
ip as-path access-list deny	1934
ip as-path access-list seq deny	1935
ip authentication	1936
ip auto-discard	1937
ip bandwidth-percent eigrp	1938
ip bandwidth eigrp	1939
ip community-list expanded deny	1940
ip community-list expanded deny	1941
ip community-list expanded seq deny	1942
ip community-list standard permit internet local-AS	1943
ip community-list standard permit internet local-AS	1944
ip community-list standard seq permit internet local-AS	1945
ip delay eigrp	1946
ip destination	1947
ip dhcp option82 suboption circuit-id	1948
ip dhcp packet strict-validation	1949
ip dhcp relay	1950
ip dhcp relay address	1951
ip dhcp relay information option	1952
ip dhcp relay information option trust	1953
ip dhcp relay information option vpn	1954
ip dhcp relay information trust-all	1955

ip dhcp relay information trusted	1956
ip dhcp relay source-interface	1957
ip dhcp relay source-interface	1958
ip dhcp relay sub-option circuit-id customized	1959
ip dhcp relay sub-option circuit-id format-type string	1960
ip dhcp relay sub-option type cisco	1961
ip dhcp smart-relay	1962
ip dhcp smart-relay global	1963
ip dhcp snooping	1964
ip dhcp snooping information option	1965
ip dhcp snooping ipsg-excluded vlan	1966
ip dhcp snooping sub-option circuit-id format-type string	1967
ip dhcp snooping trust	1968
ip dhcp snooping verify mac-address	1969
ip dhcp snooping vlan	1970
ip directed-broadcast	1971
ip distribute-list eigrp	1972
ip dns source-interface	1973
ip domain-list	1974
ip domain-lookup	1975
ip domain-name	1976
ip drop-glean	1977
ip dscp-lop	1978
ip dscp	1979
ip eigrp bfd	1980
ip eigrp event-history bfd size	1981
ip eigrp event-history errors	1982
ip eigrp event-history size	1983
ip eigrp shutdown	1984
ip extcommunity-list expanded deny	1985
ip extcommunity-list standard permit	1986
ip fabric multicast file-debug	1987
ip flow monitor input	1988
ip flow monitor input	1989

ip flow monitor input 1990

ip forward 1991

ip ftp source-interface 1992

ip hello-interval eigrp 1993

ip hold-time eigrp 1994

ip host 1995

ip host host 1996

ip http source-interface 1997

ip icmp-errors source-interface 1998

ip igmp any-query-destination 1999

ip igmp enforce-router-alert 2000

ip igmp event-history cli 2001

ip igmp event-history ha 2002

ip igmp event-history interface 2003

ip igmp event-history interface 2004

ip igmp event-history mtrace 2005

ip igmp event-history mvr 2006

ip igmp event-history nbm 2007

ip igmp event-history policy 2008

ip igmp event-history vrf 2009

ip igmp file-debug 2010

ip igmp flush-routes 2011

ip igmp group-timeout 2012

ip igmp heavy-template 2013

ip igmp host-proxy 2014

ip igmp immediate-leave 2015

ip igmp join-group 2016

ip igmp last-member-query-count 2017

ip igmp last-member-query-response-time 2018

ip igmp querier-elect strict 2019

ip igmp querier 2020

ip igmp query-interval 2021

ip igmp query-max-response-time 2022

ip igmp report-link-local-groups 2023

ip igmp report prefix-list	2024
ip igmp robustness-variable	2025
ip igmp snooping	2026
ip igmp snooping	2027
ip igmp snooping	2028
ip igmp snooping access-group	2029
ip igmp snooping disable-nve-static-router-port	2030
ip igmp snooping disable-nve-static-router-port	2031
ip igmp snooping event-history igmp-snoop-internal	2032
ip igmp snooping event-history mfdm-sum	2033
ip igmp snooping event-history mfdm	2034
ip igmp snooping event-history rib	2035
ip igmp snooping event-history vlan-events	2036
ip igmp snooping event-history vlan	2037
ip igmp snooping event-history vpc	2038
ip igmp snooping group-timeout	2039
ip igmp snooping group-timeout	2040
ip igmp snooping last-member-query-interval	2041
ip igmp snooping link-local-groups-suppression	2042
ip igmp snooping link-local-groups-suppression	2043
ip igmp snooping many-to-one-enhance	2044
ip igmp snooping max-gq-miss	2045
ip igmp snooping mrouter vpc-peer-link	2046
ip igmp snooping proxy-leave use-group-address	2047
ip igmp snooping proxy general-queries	2048
ip igmp snooping proxy general-queries	2049
ip igmp snooping report-flood all	2050
ip igmp snooping report-suppression	2051
ip igmp snooping report-suppression	2052
ip igmp snooping report prefix interface	2053
ip igmp snooping syslog-threshold	2054
ip igmp snooping v3-report-suppression	2055
ip igmp snooping v3-report-suppression	2056
ip igmp spoof-check	2057

ip igmp ssm-translate	2058
ip igmp startup-query-count	2059
ip igmp startup-query-interval	2060
ip igmp state-limit	2061
ip igmp static	2062
ip igmp suppress v3-gsq	2063
ip igmp syslog-threshold	2064
ip igmp version	2065
ip lisp alt-vrf	2066
ip lisp database-mapping dynamic priority weight	2067
ip lisp disable-spoof-alert	2068
ip lisp etr	2069
ip lisp etr accept-map-request-mapping	2070
ip lisp etr glean-mapping	2071
ip lisp etr map-cache-ttl	2072
ip lisp etr map-register-ttl	2073
ip lisp etr map-server key	2074
ip lisp hardware-forwarding	2075
ip lisp itr-etr	2076
ip lisp itr	2077
ip lisp itr map-resolver	2078
ip lisp itr send-data-probe	2079
ip lisp locator-vrf	2080
ip lisp locator reachability exclude	2081
ip lisp map-cache-limit	2082
ip lisp map-cache drop native-forward map-request priority weight	2083
ip lisp map-request-source	2084
ip lisp map-resolver	2085
ip lisp map-server	2086
ip lisp map-server try-map-cache	2087
ip lisp multicast	2088
ip lisp nat-traversal	2089
ip lisp ntr	2090
ip lisp null0-is-alt-miss	2091

ip lisp proxy-etr	2092
ip lisp proxy-itr	2093
ip lisp short-map-cache-ttl	2094
ip lisp shortest-eid-prefix-length	2095
ip lisp source-locator	2096
ip lisp translate inside outside	2097
ip lisp use-bgp-locators	2098
ip lisp use-petr priority weight	2099
ip load-sharing address	2100
ip local-proxy-arp	2101
ip local policy route-map	2102
ip mfwd event-history cli	2103
ip mfwd event-history l2	2104
ip mfwd event-history nbm	2105
ip mfwd event-history packet	2106
ip mfwd event-history vrf	2107
ip mfwd mstatic register	2108
ip mroute	2109
ip msdp description	2110
ip msdp event-history cli	2111
ip msdp event-history events	2112
ip msdp event-history routes	2113
ip msdp event-history tcp	2114
ip msdp flush-routes	2115
ip msdp group-limit source	2116
ip msdp keepalive	2117
ip msdp mesh-group	2118
ip msdp originator-id	2119
ip msdp password	2120
ip msdp peer connect-source	2121
ip msdp reconnect-interval	2122
ip msdp redistribute	2123
ip msdp sa-interval	2124
ip msdp sa-limit	2125

ip msdp sa-policy in	2126
ip msdp sa-policy out	2127
ip msdp shutdown	2128
ip mtu eigrp	2129
ip multicast multipath	2130
ip multicast multipath resilient	2131
ip multicast overlay-distributed-dr	2132
ip multicast overlay-spt-only	2133
ip multicast rpf select vrf group-list	2134
ip name-server	2135
ip nat inside	2137
ip nat inside source	2138
ip nat outside source	2140
ip nat pool netmask	2142
ip nat pool netmask	2143
ip nat translation	2144
ip nat translation creation-delay	2145
ip nat translation max-entries	2146
ip nat translation sampling-timeout	2147
ip next-hop-self eigrp	2148
ip offset-list eigrp	2149
ip ospf advertise-subnet	2150
ip ospf authentication-key	2151
ip ospf authentication	2152
ip ospf authentication key-chain	2153
ip ospf bfd	2154
ip ospf cost	2155
ip ospf dead-interval	2156
ZZZ_4621	2157
ip ospf event-history cli	2158
ip ospf event-history detail	2159
ip ospf hello-interval	2160
ip ospf message-digest-key md5	2161
ip ospf mtu-ignore	2162

ip ospf network broadcast	2163
ip ospf network point-to-point	2164
ip ospf passive-interface	2165
ip ospf prefix-attributes n-flag-clear	2166
ip ospf priority	2167
ip ospf retransmit-interval	2168
ip ospf shutdown	2169
ip ospf transmit-delay	2170
ip passive-interface eigrp	2171
ip pim anycast-rp	2172
ip pim assert-rate-limit	2173
ip pim auto-enable	2174
ip pim auto-rp listen	2175
ip pim auto-rp mapping-agent-policy	2176
ip pim auto-rp mapping-agent send-rp-discovery	2177
ip pim auto-rp rp-candidate-policy	2178
ip pim auto-rp rp-candidate send-rp-announce group-list route-map prefix-list	2179
ip pim bfd-instance	2180
ip pim bfd	2181
ip pim bidir-rp-limit	2182
ip pim border-router	2183
ip pim border	2184
ip pim bsr-candidate	2185
ip pim bsr bsr-policy	2186
ip pim bsr listen	2187
ip pim bsr rp-candidate-policy	2188
ip pim dr-delay	2189
ip pim dr-priority	2190
ip pim event-history assert	2191
ip pim event-history bidir	2192
ip pim event-history cli	2193
ip pim event-history data-register-receive	2194
ip pim event-history hello	2195
ip pim event-history join-prune-summary	2196

ip pim event-history join-prune-tw	2197
ip pim event-history join-prune	2198
ip pim event-history mrib	2199
ip pim event-history mvpn	2200
ip pim event-history nbm	2201
ip pim event-history null-register	2202
ip pim event-history packet	2203
ip pim event-history pim-library	2204
ip pim event-history rp	2205
ip pim event-history txlist	2206
ip pim event-history vpc	2207
ip pim event-history vrf	2208
ip pim evpn-border-leaf	2209
ip pim extranet	2210
ip pim file-debug	2211
ip pim flush-routes	2212
ip pim group-list	2213
ip pim hello-authentication ah-md5	2214
ip pim hello-interval	2215
ip pim isolate	2216
ip pim jp-interval	2217
ip pim jp-policy	2218
ip pim log-neighbor-changes	2219
ip pim neighbor-policy prefix-list	2220
ip pim passive	2221
ip pim pre-build-spt	2222
ip pim register-policy	2223
ip pim register-rate-limit	2224
ip pim register-source	2225
ip pim register-until-stop	2226
ip pim rp-address	2227
ip pim rp-candidate group-list route-map prefix-list	2228
ip pim sg-expiry-timer infinity	2229
ip pim sparse-mode	2230

ip pim ssm	2231
ip pim state-limit	2232
ip pim strict-rfc-compliant	2233
ip pim strict-rfc-compliant	2234
ip ping source-interface	2235
ip policy match router-address	2236
ip policy route-map	2237
ip port-unreachable	2238
ip port access-group	2239
ip port access-group	2240
ip prefix-list description	2241
ip prefix-list permit	2242
ip proxy-arp	2243
ip radius source-interface	2244
ip redirects	2245
ip rip authentication key-chain	2246
ip rip authentication mode text	2247
ip rip metric	2248
ip rip passive-interface	2249
ip rip poison-reverse	2250
ip rip route-filter route in	2251
ip rip summary-address	2252
ip route	2253
ip route static bfd	2254
ip router eigrp	2255
ip router isis	2256
ip router ospf area	2257
ip router ospf multi-area	2258
ip router rip	2259
ip routing download-on-convergence	2260
ip routing event-history	2261
ip routing multicast event-history cli	2262
ip routing multicast event-history mdt	2263
ip routing multicast event-history mfdm-debug	2264

ip routing multicast event-history mfdm-events	2265
ip routing multicast event-history mfdm-stats	2266
ip routing multicast event-history nbm	2267
ip routing multicast event-history notify-clients	2268
ip routing multicast event-history rib-summary	2269
ip routing multicast event-history rib	2270
ip routing multicast event-history urib-debug	2271
ip routing multicast event-history vrf	2272
ip routing multicast file-debug	2273
ip routing multicast holddown	2274
ip routing multicast mfdm-buffer-route-count	2275
ip routing multicast software-replicate	2276
ip routing multicast trace enable	2277
ip routing multicast trace entries	2278
ip routing multicast trace records	2279
ip secondary	2280
ip service-reflect destination to mask-len source	2281
ip service-reflect mode regular	2282
ip sla	2283
ip sla group schedule	2284
ip sla logging traps	2286
ip sla reaction-configuration react	2287
ip sla reaction-trigger	2288
ip sla reset	2289
ip sla responder	2290
ip sla responder twamp	2291
ip sla restart	2292
ip sla schedule	2293
ip sla server twamp	2295
ip source-route	2296
ip source binding vlan interface	2297
ip source icmp-errors	2298
ip split-horizon eigrp	2299
ip ssh source-interface	2300

ip summary-address eigrp ipv6 summary-address eigrp	2301
ip tacacs source-interface	2302
ip tcp mss	2303
ip tcp path-mtu-discovery	2304
ip tcp synwait-time	2305
ip telnet source-interface	2306
ip tftp source-interface	2307
ip traceroute source-interface	2308
ip ttl	2309
ip udp relay addrgroup	2310
ip udp relay subnet-broadcast	2311
ip unnumbered	2312
ip unreachable	2313
ip verify source dhcp-snooping-vlan	2314
ip verify unicast source reachable-via rx	2315
ipv6	2316
ipv6 access-class	2318
ipv6 access-list	2319
ipv6 access-list match-local-traffic	2320
ipv6 address	2321
ipv6 address dhcp	2322
ipv6 address use-link-local-only	2323
ipv6 adjacency-stale-timer	2324
ipv6 adjacency route distance	2325
ipv6 amt gateway	2326
ipv6 amt relay	2327
ipv6 destination	2328
ipv6 dhcp-ldra	2329
ipv6 dhcp-ldra attach-policy	2330
ipv6 dhcp-ldra attach-policy vlan client	2331
ipv6 dhcp guard	2332
ipv6 dhcp guard	2333
ipv6 dhcp guard policy	2334
ipv6 dhcp relay	2335

ipv6 dhcp relay address	2336
ipv6 dhcp relay address ipv6 dhcp relay address	2337
ipv6 dhcp relay option type cisco	2338
ipv6 dhcp relay option vpn	2339
ipv6 dhcp relay source-interface	2340
ipv6 dhcp relay source-interface	2341
ipv6 flow monitor input	2342
ipv6 flow monitor input	2343
ipv6 flow monitor input	2344
ipv6 forward	2345
ipv6 host	2346
ipv6 link-local	2347
ipv6 local policy route-map	2348
ipv6 mld group-timeout	2349
ipv6 mld immediate-leave	2350
ipv6 mld join-group	2351
ipv6 mld last-member-query-count	2352
ipv6 mld last-member-query-response-time	2353
ipv6 mld querier	2354
ipv6 mld query-interval	2355
ipv6 mld query-max-response-time	2356
ipv6 mld report-link-local-groups	2357
ipv6 mld report	2358
ipv6 mld robustness-variable	2359
ipv6 mld ssm-translate	2360
ipv6 mld startup-query-count	2361
ipv6 mld startup-query-interval	2362
ipv6 mld state-limit	2363
ipv6 mld static	2364
ipv6 mld version	2365
ipv6 nd cache limit	2366
ipv6 nd dad attempts	2367
ipv6 nd dadns-discover	2368
ipv6 nd hop-limit	2369

ipv6 nd mac-extract	2370
ipv6 nd managed-config-flag	2371
ipv6 nd mtu	2372
ipv6 nd ns-interval	2373
ipv6 nd off-list timeout	2374
ipv6 nd other-config-flag	2375
ipv6 nd prefix	2376
ipv6 nd prefix default	2377
ipv6 nd ra-interval	2378
ipv6 nd ra-lifetime	2379
ipv6 nd ra dns search-list sequence	2380
ipv6 nd ra dns search-list suppress	2381
ipv6 nd ra dns server sequence	2382
ipv6 nd ra dns server suppress	2383
ipv6 nd ra route suppress	2384
ipv6 nd rguard	2385
ipv6 nd rguard	2386
ipv6 nd rguard attach-policy	2387
ipv6 nd rguard policy	2388
ipv6 nd reachable-time	2389
ipv6 nd retrans-timer	2390
ipv6 nd route route-preference High Low Medium infinite	2391
ipv6 nd router-preference High Low Medium	2392
ipv6 nd solicit-na accept	2393
ipv6 nd suppress-ra	2394
ipv6 nd synchronize	2395
ipv6 neighbor	2396
ipv6 neighbor allow-static-neighbor-outside-subnet	2397
ipv6 neighbor binding	2398
ipv6 neighbor binding	2399
ipv6 neighbor binding logging	2400
ipv6 neighbor binding max-entries	2401
ipv6 neighbor tracking	2402
ipv6 pim anycast-rp	2403

ipv6 pim bidir-rp-limit	2404
ipv6 pim border	2405
ipv6 pim bsr-candidate	2406
ipv6 pim bsr bsr-policy	2407
ipv6 pim bsr listen	2408
ipv6 pim bsr rp-candidate-policy	2409
ipv6 pim dr-priority	2410
ipv6 pim event-history assert-receive	2411
ipv6 pim event-history bidir	2412
ipv6 pim event-history hello	2413
ipv6 pim event-history join-prune	2414
ipv6 pim event-history null-register	2415
ipv6 pim event-history packet	2416
ipv6 pim event-history rp	2417
ipv6 pim event-history vrf	2418
ipv6 pim flush-routes	2419
ipv6 pim hello-interval	2420
ipv6 pim isolate	2421
ipv6 pim jp-policy	2422
ipv6 pim log-neighbor-changes	2423
ipv6 pim neighbor-policy	2424
ipv6 pim passive	2425
ipv6 pim register-policy	2426
ipv6 pim register-rate-limit	2427
ipv6 pim rp-address	2428
ipv6 pim rp-candidate group	2429
ipv6 pim sparse-mode	2430
ipv6 pim ssm	2431
ipv6 pim state-limit	2432
ipv6 pim use-shared-tree-only spt-threshold infinity group-list	2433
ipv6 policy route-map	2434
ipv6 port traffic-filter	2435
ipv6 prefix-list description	2436
ipv6 prefix-list permit	2437

ipv6 queue-packets	2438
ipv6 redirects	2439
ipv6 route	2440
ipv6 route static bfd	2441
ipv6 router isis	2442
ipv6 router ospfv3 area	2443
ipv6 router ospfv3 multi-area	2444
ipv6 routing event-history size	2445
ipv6 routing multicast event-history cli	2446
ipv6 routing multicast event-history mfdm-debug	2447
ipv6 routing multicast event-history mfdm-events	2448
ipv6 routing multicast event-history mfdm-stats	2449
ipv6 routing multicast event-history rib-summary	2450
ipv6 routing multicast event-history rib	2451
ipv6 routing multicast event-history vrf	2452
ipv6 routing multicast holddown	2453
ipv6 routing multicast software-replication	2454
ipv6 snooping	2455
ipv6 snooping	2456
ipv6 snooping policy	2457
ipv6 switch-packets	2458
ipv6 traffic-filter	2459
ipv6 unreachable	2460
ipv6 verify unicast source reachable-via rx	2461
is-type	2462
ishow cli find nodes	2463
ishow cli modes	2464
ishow cli nodes	2465
ishow cli paths	2466
ishow cli tags	2467
ishow core backtrace	2468
isis authentication-check	2469
isis authentication-check level-1	2470
isis authentication-check level-2	2471

isis authentication-type cleartext	2472
isis authentication-type cleartext	2473
isis authentication key-chain	2474
isis authentication key-chain	2475
isis bfd	2476
isis circuit-type	2477
isis csnp-interval level	2478
isis event-history adjacency	2479
isis event-history cli	2480
isis event-history csnp	2481
isis event-history dis	2482
isis event-history events	2483
isis event-history graceful	2484
isis event-history ha	2485
isis event-history iih	2486
isis event-history lsp-flood	2487
isis event-history lsp-gen	2488
isis event-history mtr	2489
isis event-history perf	2490
isis event-history psnp	2491
isis event-history redist	2492
isis event-history spf-leaf	2493
isis event-history spf-tree	2494
isis event-history sr	2495
isis event-history tlv	2496
isis event-history ulib	2497
isis event-history urib	2498
isis hello-interval	2499
isis hello-interval level	2500
isis hello-multiplier	2501
isis hello-multiplier level	2502
isis hello-padding	2503
isis ipv6 bfd	2504
isis ipv6 metric	2505

isis lsp-interval	2506
isis mesh-group	2507
isis metric	2508
isis mtu-check	2509
isis mtu-check level	2510
isis network point-to-point	2511
isis passive-interface	2512
isis prefix-attributes n-flag-clear	2513
isis priority level	2514
isis retransmit-interval	2515
isis retransmit-throttle-interval	2516
isis shutdown	2517
isolate	2518
isolate	2519
isolate	2520
isolate	2521
isolate	2522
isolate	2523
isolate	2524
itd	2525
itd device-group	2526
itd session access-list refresh	2527
itd session device-group	2528
itd statistics	2529

CHAPTER 11**J Commands 2531**

job name	2532
json-pretty	2533
json-pretty	2534
json	2535
json	2536

CHAPTER 12**K Commands 2537**

key-octet-string 7 cryptographic-algorithm AES_128_CMAC	2538
---	------

key-octet-string 7 cryptographic-algorithm AES_256_CMAC	2539
key-octet-string cryptographic-algorithm AES_128_CMAC	2540
key-octet-string cryptographic-algorithm AES_256_CMAC	2541
key-server-priority	2542
key-string	2543
key-string 7	2544
key	2545
key	2546
key chain	2547
key config-key hex	2548
kill-everyone	2549
kill background	2550
kstack multicast-udp	2551
kubernetes server ip-address port	2552

CHAPTER 13
L Commands 2553

l2rib dup-host-mac-detection	2561
l2rib dup-host-mac-recovery	2562
l2rib event-history size	2563
l3vm event-history	2564
label-allocation-mode per-vrf	2565
label allocate global	2566
lACP fast-select-hot-standby	2567
lACP graceful-convergence	2568
lACP max-bundle	2569
lACP min-links	2570
lACP mode delay	2571
lACP mode delay	2572
lACP port-priority	2573
lACP rapid-transition	2574
lACP rate	2575
lACP rate	2576
lACP suspend-individual	2577
lACP system-mac	2578

lACP system-priority	2579
lACP vpc-convergence	2580
last	2581
latency	2582
latency	2583
latency quantization	2584
latency quantization	2585
layer-2 multicast lookup mac	2586
layer-2 multicast lookup mac	2587
layer2-switched flow monitor input	2588
layer3 peer-router	2589
layer3 peer-router syslog	2590
LDAP-search-map	2591
LDAP-search-map	2592
LDAP-server deadtime	2593
LDAP-server host	2594
LDAP-server host test rootDN	2596
LDAP-server port	2597
LDAP-server timeout	2598
LDAP search-map	2599
less	2600
license expiry check_interval	2601
limit-resource m4route-mem maximum equal-to-min	2602
limit-resource m6route-mem maximum	2603
limit-resource module-type	2604
limit-resource monitor-session-erspan-dst minimum maximum equal-to-min	2605
limit-resource monitor-session-inband-src minimum maximum equal-to-min	2606
limit-resource monitor-session minimum maximum equal-to-min	2607
limit-resource port-channel minimum maximum	2608
limit-resource u4route-mem maximum equal-to-min	2609
limit-resource u6route-mem maximum equal-to-min	2610
limit-resource vlan minimum maximum equal-to-min	2611
limit-resource vrf minimum maximum equal-to-min	2612
limit address-count	2613

line console	2614
line console	2615
line vty	2616
line vty	2617
link-management timers bandwidth	2618
link-state-trap	2619
link debounce	2620
link rxlos	2621
link transmit reset-skip	2622
lisp	2623
lisp ddt	2624
lisp ddt authoritative-prefix eid-prefix	2625
lisp ddt delegate eid-prefix	2626
lisp ddt map-server-peer eid-prefix	2627
lisp ddt root	2628
lisp dynamic-eid	2629
lisp dynamic-eid	2630
lisp explicit-locator-path	2631
lisp explicit-locator-path	2632
lisp extended-subnet-mode	2633
lisp geo-coordinates	2634
lisp instance-id	2635
lisp loc-reach-algorithm	2636
lisp merge-registrations site-id	2637
lisp mobility	2638
lisp mobility test-liveness	2639
lisp security	2640
lisp site	2641
lisp site	2642
lisp smr-locators	2643
lisp to	2644
list	2645
list	2646
listobject-boolean not	2647

listobject-weight weight threshold-weight	2648
listobject	2649
lldp	2650
lldp dcbx version auto	2651
lldp dcbx version cee	2652
lldp eee rx_wake_time	2653
lldp receive	2654
lldp tlv-select eee	2655
lldp tlv-select management-address v4	2656
lldp tlv-set management-address	2657
lldp tlv-set management-address ipv6	2658
lldp tlv-set vlan	2659
lldp transmit	2660
load-balance	2661
load-balance	2662
load-balance	2663
load-interval	2664
load-interval	2665
load-interval counter	2666
load-interval counter	2667
load	2668
load	2669
load	2670
load	2671
local-as	2672
local-as	2673
local-label prefix	2674
local-label prefix	2675
locator-led	2676
lockdown	2677
log-adjacency-changes	2678
log-adjacency-changes	2679
log-adjacency-changes	2680
log-adjacency-changes	2681

log-adjacency-changes	2682
log-adjacency-changes	2683
log-event-type	2684
log-neighbor-changes	2685
log-neighbor-changes	2686
log-neighbor-warnings	2687
logging	2688
logging	2689
logging abort	2690
logging console	2691
logging debug	2692
logging distribute	2693
logging drop threshold	2694
logging drop threshold	2695
logging event link enable	2696
logging event port link-status	2697
logging event port link-status	2698
logging event port link-status	2699
logging event port link-status default	2700
logging event port trunk-status	2701
logging event port trunk-status	2702
logging event port trunk-status default	2703
logging flow-mod	2704
logging flow-mod	2705
logging ip access-list cache	2706
logging ip access-list cache entries	2707
logging ip access-list detailed	2708
logging ip access-list include sgt	2709
logging level	2710
logging level	2711
logging level	2712
logging level	2713
logging level	2715
logging level	2716

logging level	2717
logging level	2718
logging level aaa	2719
logging level acllog	2720
logging level aclmgr	2721
logging level adbm	2722
logging level adjmgr	2723
logging level all	2724
logging level amt	2725
logging level arp	2726
logging level ascii-cfg	2727
logging level assoc_mgr	2728
logging level backup	2729
logging level bfd	2730
logging level bgp	2731
logging level bloggerd	2732
logging level bootvar	2733
logging level callhome	2734
logging level capability	2735
logging level catena	2736
logging level cdp	2737
logging level cert	2738
logging level cfs	2739
logging level clis	2740
logging level clk_mgr	2741
logging level confcheck	2742
logging level copp	2743
logging level core	2744
logging level cts	2745
logging level dhclient	2746
logging level dhcp_snoop	2747
logging level diagclient	2748
logging level diagmgr	2749
logging level dot1x	2750

logging level ecp	2751
logging level eigrp	2752
logging level eltm	2753
logging level epp	2754
logging level ethdstats	2755
logging level ethpm	2756
logging level ethpm link	2757
logging level evb	2758
logging level evmc	2759
logging level evmed	2760
logging level evms	2761
logging level fabric forwarding	2762
logging level fcoe_mgr	2763
logging level feature-mgr	2764
logging level fs-daemon	2765
logging level gpixm	2766
logging level hardware-telemetry	2767
logging level hsrp	2768
logging level icam	2769
logging level igmp	2770
logging level im	2771
logging level imp	2772
logging level interface-vlan	2773
logging level ip pim	2774
logging level ip sla responder	2775
logging level ip sla sender	2776
logging level ip sla twamp-server	2777
logging level ipconf	2778
logging level ipfib	2779
logging level ipqos	2780
logging level ipv6 pim	2781
logging level iscm	2782
logging level iscm	2783
logging level isis	2784

logging level keystore	2785
logging level l2fm	2786
logging level l2rib	2787
logging level l3vm	2788
logging level lacp	2789
logging level ldap	2790
logging level lem-mgr	2791
logging level license	2792
logging level lim	2793
logging level lisp	2794
logging level lldp	2795
logging level m2rib	2796
logging level mfdm	2797
logging level mfwd	2798
logging level mmode	2799
logging level module	2800
logging level monitor	2801
logging level msdp	2802
logging level mvsh	2803
logging level nat	2804
logging level nbm	2805
logging level netstack	2806
logging level nfm	2807
logging level ngoam	2808
logging level npv	2809
logging level ntp	2810
logging level nxsdk	2811
logging level openflow	2812
logging level orib	2813
logging level ospf	2814
logging level ospfv3	2815
logging level pfstat	2816
logging level pixm	2817
logging level pktmgr	2818

logging level platform	2819
logging level plbm	2820
logging level plcmgr	2821
logging level pltfm_config	2822
logging level plugin	2823
logging level poap	2824
logging level poed	2825
logging level port-profile	2826
logging level port-resources	2827
logging level port-security	2828
logging level port	2829
logging level port_client	2830
logging level port_lb	2831
logging level port link-failure	2832
logging level private-vlan	2833
logging level ptp	2834
logging level radius	2835
logging level res_mgr	2836
logging level rip	2837
logging level rpm	2838
logging level rsvp	2839
logging level sal	2840
logging level san	2841
logging level scheduler	2842
logging level security	2843
logging level session-mgr	2844
logging level sflow	2845
logging level smartc	2846
logging level smm	2847
logging level snmpd	2848
logging level snmpmib_proc	2849
logging level spanning	2850
logging level spm	2851
logging level stripcl	2852

logging level sysmgr	2853
logging level tacacs	2854
logging level tamnw	2855
logging level track	2856
logging level tunnel	2857
logging level u2rib	2858
logging level u6rib	2859
logging level udld	2860
logging level ufdm	2861
logging level urib	2862
logging level vdc_mgr	2863
logging level virtual-service	2864
logging level vlan_mgr	2865
logging level vmm	2866
logging level vmtracker	2867
logging level vpc	2868
logging level vrrp	2869
logging level vrrpv3	2870
logging level vsan	2871
logging level vshd	2872
logging level vtp	2873
logging level wwnm	2874
logging level xbar	2875
logging logfile	2876
logging message interface type ethernet	2877
logging module	2878
logging monitor	2879
logging origin-id	2880
logging rate-limit	2881
logging server	2882
logging server dns-refresh-interval	2884
logging source-interface	2885
logging timestamp	2886
login on-failure log	2887

login on-success log	2888
logout-warning	2889
low-memory exempt	2890
lshow	2891
lshow	2892
lsp-gen-interval	2893
lsp-gen-interval	2894
lsp-gen-interval	2895
lsp-mtu	2896
lsp-mtu	2897
lsp-mtu	2898
lsp	2899
lsp	2900
lsp attributes	2901

CHAPTER 14
M Commands 2903

m2rib debug ftag	2908
m2rib debug gr-route add nh	2909
m2rib debug log-size event-history	2911
m2rib debug log-size transactions	2912
m2rib debug omf enable	2913
m2rib debug pkt-recv enable	2914
m2rib debug swroute nh	2915
m2rib debug topo	2916
m2rib debug topo loop-flush-timeout	2917
mac-addr	2918
mac-address	2919
mac-address	2920
mac-address	2921
mac-address bpdu source version 2	2922
mac-address destination	2923
mac-address ipv6-extract	2924
mac-learn disable	2925
mac-learn disable	2926

mac-list permit	2927
mac access-list	2928
mac address-table aging-time	2929
mac address-table guard-vpc-peergw-mac	2930
mac address-table limit system	2931
mac address-table loop-detect port-down	2932
mac address-table multicast vlan interface	2933
mac address-table notification mac-move	2934
mac address-table notification threshold	2935
mac address-table static vlan interface	2936
mac address-table static vni	2937
mac address	2938
mac address inherit	2939
mac advert interval	2940
mac packet-classify	2941
mac packet-classify	2942
mac port access-group	2943
managed-config-flag	2944
management	2945
map-notify-group	2946
map-server key	2947
marker-packet-n3500	2948
marker-packet	2949
master ipv4	2950
match-address	2951
match	2952
match	2954
match	2955
match access-group name	2959
match address	2960
match as-number	2961
match as-number as-path-list	2962
match as-path	2963
match class-map	2964

match community	2965
match cos	2966
match cos	2967
match datalink	2968
match datalink	2969
match dscp	2970
match dscp	2971
match exception	2972
match extcommunity	2973
match interface	2974
match ip address	2975
match ip address prefix-list	2976
match ip multicast rp	2977
match ip next-hop prefix-list	2978
match ip protocol	2979
match ip route-source prefix-list	2980
match ipv4 protocol	2981
match ipv4 source address	2982
match ipv4 source address	2983
match ipv4 transport destination	2984
match ipv6	2985
match ipv6	2986
match ipv6 address	2987
match ipv6 address prefix-list	2988
match ipv6 multicast rp	2989
match ipv6 next-hop prefix-list	2990
match ipv6 protocol	2991
match ipv6 route-source prefix-list	2992
match ipv6 transport destination	2993
match metric	2994
match ospf-area	2995
match protocol	2996
match protocol arp	2997
match qos-group	2998

match qos-group2	2999
match qos-group2	3000
match qos-group	3001
match redirect	3002
match route-type	3003
match source-protocol	3004
match tag	3005
match transport destination	3006
max-backoff	3007
max-backoff	3008
max-lsa	3009
max-lsa	3010
max-lsp-lifetime	3011
max-lsp-lifetime	3012
max-lsp-lifetime	3013
max-metric router-lsa	3014
max-metric router-lsa	3015
max-ports	3016
max-ports	3017
maxas-limit	3018
maximum-paths	3019
maximum-paths	3020
maximum-paths	3021
maximum-paths	3022
maximum-paths	3023
maximum-paths	3024
maximum-paths	3025
maximum-paths	3026
maximum-paths eibgp	3027
maximum-paths mixed	3028
maximum-peers	3029
maximum-prefix	3030
maximum-prefix	3031
maximum-prefix	3032

maximum routes	3033
mdix auto	3034
mdt asm-use-shared-tree	3035
mdt data	3036
mdt data bidir-enable	3037
mdt default	3038
mdt enforce-bgp-mdt-safi	3039
mdt mtu	3040
mdt pim hello-interval	3041
mdt pim jp-interval	3042
mdt source	3043
media-type auto	3044
media-type rj45	3045
media-type sfp	3046
media	3047
medium	3048
medium broadcast	3049
medium broadcast	3050
medium p2p	3051
medium p2p	3052
member vlan	3053
member vni	3054
member vni	3055
member vni associate-vrf	3056
message-digest-key md5	3057
message-digest-key md5	3058
metric-style transition	3059
metric-type	3060
metric direct 0	3061
metric maximum-hops	3062
metric rib-scale	3063
metric version 64bit	3064
metric weights	3065
mkdir	3066

mode	3067
mode	3068
mode	3069
mode tap-aggregation	3070
module transceiver-frequency	3071
monitor erspan granularity	3072
monitor erspan origin ip-address	3073
monitor erspan switch-id	3074
monitor session	3075
monitor session shut	3076
monitor session type acl-capture	3077
monitor session type erspan-destination	3078
monitor session type erspan-source	3079
monitor session warp	3080
monitor session warp	3081
mount	3082
mount slot0	3083
move	3084
mst designated priority	3085
mst root priority	3086
mtrace	3087
mtu	3088
mtu1	3089
mtu	3090
mtu	3091
mtu	3092
mtu	3093
mtu	3094
mtu	3095
multi-topology	3096
multicast	3097
multisite border-gateway interface	3098
multisite ingress-replication	3099
mvr-config	3100

mvr-group	3101
mvr-group	3102
mvr-group	3103
mvr-group	3104
mvr-group	3105
mvr-group	3106
mvr-group	3107
mvr-group	3108
mvr-suppress-query vlan	3109
mvr-type receiver	3110
mvr-type source	3111
mvr-vlan	3112
mvr-vlan	3113

CHAPTER 15**N Commands 3115**

name-lookup	3118
name-lookup	3119
name	3120
name	3121
name	3122
nat destination	3123
nbn external-link	3124
nbn flow-policy	3125
nbn flow acceptance-mode guaranteed nbn flow acceptance-mode	3126
nbn flow asm range	3127
nbn flow bandwidth kbps mbps gbps	3128
nbn flow dscp	3129
nbn host-policy	3130
nbn mode pim-active	3131
nbn reserve unicast fabric bandwidth	3132
negotiate auto	3133
negotiate auto 25000	3134
neighbor-down fib-accelerate	3135
neighbor	3136

neighbor	3137
neighbor	3138
neighbor	3139
neighbor	3140
neighbor maximum-prefix	3141
nemo config address port interval	3142
net	3143
net	3144
net	3145
network	3146
network	3147
network	3148
network	3149
next-address exclude-address	3150
next-hop-self	3151
next-hop-self	3152
next-hop-third-party	3153
next-hop-third-party	3154
next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null	3155
next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null	3156
nexthop route-map	3157
nexthop trigger-delay critical non-critical	3158
ngoam authentication-key	3159
ngoam connect-check	3160
ngoam install acl	3161
ngoam profile	3162
ngoam xconnect hb-interval	3163
no-more	3164
no	3165
no	3166
no	3167
no	3168

no	3169
no	3170
no	3171
no	3174
no	3179
no	3183
no	3186
no	3189
no	3192
no	3195
no	3198
no	3201
no	3203
no	3204
no	3205
no	3206
node	3207
node	3208
node	3209
node ip	3210
node ip	3211
npiv enable	3212
npv auto-load-balance disruptive	3213
npv traffic-map server-interface external-interface	3214
nsf await-redis-proto-convergence	3215
ntp access-group	3216
ntp access-group match-all	3217
ntp allow private	3218
ntp authenticate	3219
ntp authentication-key md5	3220
ntp drop-aged-packet	3221
ntp logging	3222
ntp master	3223
ntp passive	3224

ntp peer	3225
ntp rts-update	3226
ntp server	3227
ntp source-interface	3228
ntp source	3229
ntp sync-retry	3230
ntp trusted-key	3231
nv overlay evpn	3232
nxapi certificate	3233
nxapi flow	3234
nxapi http port	3235
nxapi ssl ciphers weak	3236
nxapi ssl protocols	3237
nxapi use-vrf management default	3238
nxsdk enable app	3239
nxsdk service-name	3240

CHAPTER 16**O Commands 3241**

oam-channel	3243
object-group ip address	3244
object-group ip port	3245
object-group ipv6 address	3246
object-group udp relay ip address	3247
object-group udp relay ip address	3248
object-track	3249
of-port interface	3250
on-demand color	3251
openflow	3252
operation-packet-priority normal	3253
option exporter-stats timeout	3254
option interface-table timeout	3255
orib event-history	3256
orib orib_api_init	3257
ospfv3 authentication	3258

ospfv3 bfd	3259
ospfv3 cost	3260
ospfv3 dead-interval	3261
ospfv3 event-history	3262
ospfv3 event-history cli	3263
ospfv3 event-history detail	3264
ospfv3 event-history detail	3265
ospfv3 hello-interval	3266
ospfv3 instance	3267
ospfv3 mtu-ignore	3268
ospfv3 network broadcast	3269
ospfv3 network point-to-point	3270
ospfv3 passive-interface	3271
ospfv3 priority	3272
ospfv3 retransmit-interval	3273
ospfv3 shutdown	3274
ospfv3 transmit-delay	3275
other-config-flag	3276
overlay-encapsulation	3277
overwrite-vlan	3278
owner	3279

CHAPTER 17**P Commands 3281**

packet-size	3288
param-list param-list	3289
parity	3290
parity	3291
passive-interface default	3292
passive-interface default	3293
passive-interface default	3294
passive-interface default	3295
password	3296
password	3297
password	3298

password prompt username 3299

password secure-mode 3300

password strength-check 3301

path-option dynamic explicit identifier 3302

path-selection metric igp 3303

path-selection metric igp 3304

path-selection overload allow 3305

path 3306

path next-hop out-label-stack 3307

pause 3308

pause 3309

pause buffer-size2 pause-threshold2 resume-threshold2 3310

pause priority 3311

payload 3312

payload test pattern-type pad 3313

pcc 3314

pce-address ipv4 3315

peer-gateway 3316

peer-ip 3317

peer-keepalive destination 3318

peer-switch 3320

peer-type fabric 3321

peer-vtep 3322

peer ip 3323

peer ip 3324

peer local service 3325

peer local service 3326

peer vpc 3327

per-ingress-port-mtu-mode 3328

perf 3329

periodic-inventory notification 3330

periodic-inventory notification interval 3331

periodic to 3332

periodic to 3333

permit interface	3334
permit vlan	3335
permit vrf	3336
permit vsan	3337
personality	3338
personality backup	3339
personality restore	3340
phone-contact	3341
pim	3342
ping	3343
ping6	3345
platform access-list capture	3346
platform access-list fp_dnl	3347
platform access-list update	3348
platform acl tap-agg	3349
platform forwarding interface statistics mode mpls	3350
platform forwarding layer-2 fl exclude supervisor	3351
platform ip verify	3352
platform ipv6 verify	3354
platform qos	3355
platform qos	3356
platform qos	3357
platform qos	3358
platform qos	3359
platform qos	3360
platform qos	3361
platform qos	3362
platform qos	3364
platform qos	3365
platform qos	3366
platform qos	3367
platform qos	3368
platform qos	3369
platform qos	3370

platform qos buffer peak monitor counter0 class	3371
platform qos buffer peak monitor counter1 class	3372
platform qos classify ns-only	3373
platform qos eq	3374
platform qos include ipg	3375
platform qos ing	3376
platform qos ing	3377
platform qos mac ipg	3378
platform qos nodrop-PG-thresholds-FX PG-size	3379
platform qos nodrop-PG-thresholds PG-size	3380
platform qos nodrop-PG-thresholds PG-size Red-threshold Yellow-threshold Green-threshold	3381
platform qos nodrop-queue-thresholds-FX Queue-green	3382
platform qos nodrop-queue-thresholds-roc Queue-green	3383
platform qos ns	3384
platform qos q-noise percent	3385
platform rate-limiter	3386
platform rate-limiter	3388
platform rate-limiter access-list-log	3390
platform rate-limiter span-egress	3391
plb	3392
plb analytics	3393
plb device-group	3394
police	3395
police	3399
police	3401
police	3403
police police pps	3407
police police pps	3409
policy-map	3411
policy-map type control-plane	3412
policy-map type network-qos	3413
policy-map type queuing	3414
policy	3415
policy	3416

policy	3417
pop	3418
port-channel bfd destination	3419
port-channel bfd start	3420
port-channel bfd track-member-link	3421
port-channel fast-convergence	3422
port-channel hash-distribution	3423
port-channel limit	3424
port-channel load-balance	3425
port-channel load-balance1 ethernet	3426
port-channel load-balance2 resilient	3427
port-channel load-balance ethernet	3428
port-channel load-defer	3429
port-channel port hash-distribution	3430
port-channel port load-defer	3431
port-channel scale-fanout	3432
port-group	3433
port-group	3434
port-license	3435
port-license	3436
port-profile	3437
port-type	3438
port	3439
port	3440
port control	3441
port control	3442
port destination	3443
port type ethernet	3444
postcard-telemetry exporter	3445
postcard-telemetry flow-profile	3446
postcard-telemetry monitor	3447
postcard-telemetry queue-profile	3448
postcard-telemetry system monitor	3449
postcard-telemetry watchlist ip	3450

power efficient-ethernet auto	3451
power efficient-ethernet sleep threshold aggressive	3452
power inline	3453
power inline default_consumption	3454
power inline police action	3455
power inline port priority	3456
power redundancy-mode combined	3457
power redundancy-mode combined force	3458
power redundancy-mode insrc-redundant	3459
power redundancy-mode ps-redundant	3460
power reserve	3461
poweroff	3462
pps	3463
pps	3464
precision milliseconds	3465
preempt	3466
preempt	3467
preempt delay minimum	3468
preempt delay minimum reload sync preempt delay reload minimum sync preempt delay sync minimum reload preempt delay reload sync minimum preempt delay sync reload minimum preempt delay minimum sync reload preempt delay reload sync preempt delay sync reload preempt delay minimum sync preempt delay sync minimum preempt delay minimum reload preempt delay reload minimum preempt delay minimum preempt delay reload preempt delay sync preempt	3469
preference	3471
preference max	3472
preference min	3473
prefix out	3474
priority-flow-control auto-restore multiplier	3475
priority-flow-control fixed-restore multiplier	3476
priority-flow-control inn-recover interface	3477
priority-flow-control mode	3478
priority-flow-control override-interface mode off	3479
priority-flow-control recover interface	3480
priority-flow-control tah-recover interface	3481
priority-flow-control watch-dog-interval on	3482

priority-flow-control watch-dog-interval on	3483
priority-flow-control watch-dog forced on	3484
priority-flow-control watch-dog interval	3485
priority-flow-control watch-dog shutdown-multiplier	3486
priority	3487
priority2	3488
priority	3489
priority	3490
priority	3491
priority	3492
priority	3493
priority	3494
private-vlan	3495
private-vlan association	3496
private-vlan mapping	3497
private-vlan synchronize	3498
probe-interval	3499
probe-interval	3500
probe	3501
probe	3502
probe	3503
probe	3504
probe	3505
probe	3506
probe	3507
probe get	3508
probe get	3509
probe get	3510
probe get	3511
probe host	3512
probe host	3513
probe host	3514
probe host	3515
probe host	3516

probe host	3517
probe host	3518
probe port	3519
probe port	3520
probe port	3521
probe port	3522
probe port	3523
probe port	3524
probe port	3525
profile	3526
profile	3527
promiscuous-mode off	3528
propagate-sgt	3529
protection	3530
proto	3531
protocol-version	3532
protocol-version	3533
protocol	3534
protocol	3535
protocol shutdown	3536
protocol shutdown	3537
ptp	3538
ptp announce interval	3539
ptp announce timeout	3540
ptp clock-identity	3541
ptp clock-sync auto	3542
ptp clock one-step	3543
ptp convergence-time	3544
ptp correction-range	3545
ptp correction-range logging	3546
ptp correction hardware	3547
ptp cost	3548
ptp delay-request minimum interval	3549
ptp device-type boundary	3550

ptp domain	3551
ptp domain	3552
ptp domain clock-accuracy-threshold	3553
ptp domain clock-class-threshold	3554
ptp domain priority	3555
ptp grandmaster-capable	3556
ptp mean-path-delay	3557
ptp multi-domain	3558
ptp multi-domain transition-attributes priority1	3559
ptp multi-domain transition-attributes priority2	3560
ptp multicast master-only	3561
ptp neighbor propagation-delay-threshold	3562
ptp offload	3563
ptp pdelay-req-interval	3564
ptp priority1	3565
ptp priority2	3566
ptp source	3567
ptp sync interval	3568
ptp transport ipv4 ucast master	3569
ptp transport ipv4 ucast slave	3570
ptp ucast-source	3571
ptp vlan	3572
purge module running-config	3573
push	3574
pwd	3575
python	3576
python instance	3577

CHAPTER 18**Q Commands 3579**

qos copy policy-map type network-qos prefix	3580
qos copy policy-map type queuing prefix	3581
qos qos-policies statistics	3582
qos shared-policer	3583
qos statistics	3587

[qualify udf](#) 3588
[queue-limit](#) 3589
[queue-limit2](#) 3590
[queue-limit3](#) 3591
[queue-limit4](#) 3592
[queue-limit5](#) 3593
[queue-limit bytes](#) 3594

CHAPTER 19
R Commands 3595

[radius-server deadtime](#) 3600
[radius-server directed-request](#) 3601
[radius-server host key 0 6 7](#) 3602
[radius-server host test](#) 3604
[radius-server key 0 6 7](#) 3605
[radius-server pss-clean](#) 3606
[radius-server retransmit](#) 3607
[radius-server test](#) 3608
[radius-server timeout](#) 3609
[random-detect](#) 3610
[random-detect2 minimum-threshold2 maximum-threshold2](#) 3612
[random-detect2 non-ecn minimum-threshold2 maximum-threshold2 drop](#) 3613
[random-detect](#) 3614
[random-detect cos-based](#) 3616
[rate-limit](#) 3618
[rate-limit cpu direction pps action log](#) 3619
[rate-limit cpu direction pps action log](#) 3620
[rate-limit packet_in burst](#) 3621
[rate-limit packet_in burst](#) 3622
[rate-mode](#) 3623
[rd auto](#) 3624
[rd auto](#) 3625
[receiver](#) 3626
[reconnect-interval](#) 3627
[record-route](#) 3628

record-route	3629
record	3630
record	3631
record	3632
record	3633
record	3634
redistribute bgp	3635
redistribute bgp eigrp isis ospf rip static direct amt lisp route-map	3636
redistribute filter route-map	3637
redistribute filter route-map	3638
redistribute maximum-prefix	3639
redistribute maximum-prefix	3640
redistribute maximum-prefix	3641
redistribute maximum-prefix	3642
redistribute maximum-prefix	3643
redistribute route-map	3644
redistribute route-map	3645
redistribute route-map	3646
redistribute route-map	3647
redistribute route-map	3648
redistribute route-map	3649
redistribute route-map	3650
redistribute route-map	3651
redistribute route-map	3652
redistribute route-map	3653
redownload forwarding state	3654
redundancy-group	3655
reference-bandwidth	3656
reference-bandwidth	3657
register-database-mapping	3658
register-route-notifications	3659
reload	3660
reload cancel	3661
reload in	3662

reload module	3663
reload module force-dnld	3664
reload non-interruptive	3665
reload power-cycle	3666
reload sync-adjacency	3667
reload sync-adjacency	3668
reload timer	3669
reload vdc	3670
reload vdc	3671
remark	3672
remark	3673
remark	3674
remote-as	3675
remote-span	3676
remote	3677
remove-private-as	3678
reoptimize events link-up	3679
replay-protection	3680
report	3681
report	3682
report	3683
report	3684
report	3685
report	3686
report	3687
report	3688
report	3689
report	3690
report	3691
report	3692
report	3693
report	3694
report	3695
report	3696

request-data-size	3697
request-data-size	3698
request-data-size	3699
resequence access	3700
reset	3701
reset	3702
reset	3703
reset	3704
reset	3705
reset	3706
reset	3707
reset	3708
reset	3709
reset	3710
reset	3711
reset	3712
reset	3713
reset	3714
reset	3715
reset	3716
restart amt	3717
restart bgp	3718
restart eigrp	3719
restart igmp	3720
restart isis	3721
restart msdp	3722
restart ospf	3723
restart ospfv3	3724
restart pim	3725
restart pim6	3726
restart rip	3727
restart rsvp	3728
resync-database	3729
retain route-target all	3730

retain route-target all	3731
retransmit-interval	3732
retransmit-interval	3733
retransmit-interval	3734
revision	3735
revocation-check crl	3736
rewrite-evpn-rt-asn	3737
rewrite-rt-asn	3738
rfc1583compatibility	3739
rip shutdown	3740
rmdir	3741
rmon alarm absolute rising-threshold falling-threshold	3742
rmon event	3743
rmon hcalarm absolute startupalarm rising-threshold falling-threshold owner	3744
roaming-eid-prefix	3745
role feature-group name	3746
role name	3747
role priority	3748
rollback running-config checkpoint	3749
root-priority	3750
route-map	3751
route-map	3752
route-map	3753
route-map	3754
route-map out	3755
route-map pbr-statistics	3756
route-reflector-client	3757
route-reflector-client	3758
route-target both auto	3759
route-target both auto	3760
route-target export	3761
route-target export auto	3762
route-target import	3763
route-target import auto	3764

route delete dampen interval **3765**
 router-guard ip multicast **3766**
 router-guard ip multicast switchports **3767**
 router-id **3768**
 router-id **3769**
 router-id **3770**
 router-id **3771**
 router-id **3772**
 router-id **3773**
 router-preference maximum **3774**
 router bgp **3775**
 router eigrp **3776**
 router isis **3777**
 router ospf **3778**
 router ospfv3 **3779**
 router rip **3780**
 routing-context vrf **3781**
 rsakeypair **3782**
 rtr etr eid **3783**
 rule **3784**
 rule command **3785**
 rule oid **3786**
 run-script **3787**
 run2 guestshell **3788**
 run bash **3789**

CHAPTER 20
S Commands 3791

sak-expiry-time **3805**
 sampling-rate prepost **3806**
 sampling **3807**
 sap hash-algorithm HMAC-SHA-1 **3808**
 sap modelist **3809**
 sap pmk sap pmk use-dot1x **3810**
 save **3811**

scale-factor module	3812
scheduler aaa-authentication	3813
scheduler enable	3814
scheduler job name	3815
scheduler logfile size	3816
scheduler schedule name	3817
scheduler transport email	3818
scripting tcl init	3819
scripting tcl recursion-limit	3820
section	3821
secure-handoff	3822
security-level	3823
security-policy	3824
sed	3825
send-community	3826
send-community	3827
send-community extended	3828
send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l	3829
send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l	3831
send	3833
send session	3834
sender	3835
sensor-group	3836
server	3837
server	3838
server	3839
server protocol ldap	3840
server protocol radius group	3841
server protocol xmpp ip	3842
service-policy-dynamic input	3843
service-policy	3844

service-policy	3845
service-policy	3846
service-policy input	3847
service-policy type network-qos	3848
service-policy type qos	3849
service-policy type queuing	3850
service-policy type queuing	3851
service-policy type queuing	3852
service password-recovery	3853
service unsupported-transceiver	3854
session-limit	3855
session domain-lookup	3856
session protection	3857
set-attached-bit	3858
set-overload-bit	3859
set-overload-bit	3860
set	3861
set	3864
set	3865
set	3866
set	3867
set	3869
set as-path prepend last-as tag	3870
set comm-list delete	3871
set community none additive internet local-AS	3872
set cos	3873
set cos	3874
set dampening	3875
set distance	3876
set drpvec	3877
set drpvec	3883
set extcomm-list delete	3889
set extcommunity 4byteas-generic transitive additive	3890
set extcommunity color	3891

set extcommunity cost	3892
set extcommunity rt additive	3893
set forwarding-address	3894
set ieth	3895
set ieth	3898
set inner arp	3901
set inner ipv4	3903
set inner ipv4	3905
set inner ipv4	3907
set inner ipv6 src_ip	3909
set inner l2	3910
set inner l2	3912
set inner l2	3914
set inner l2 hg2	3916
set inner l2 hg2	3918
set inner l4	3920
set inner l4	3921
set inner l4	3924
set interface	3925
set interval find-new-host	3926
set interval sync-full-info	3927
set ip address prefix-list	3928
set ip default next-hop	3929
set ip default next-hop verify-availability	3930
set ip next-hop	3931
set ip next-hop peer-address	3932
set ip next-hop redist-unchanged	3933
set ip next-hop unchanged	3934
set ip next-hop verify-availability	3935
set ip precedence	3936
set ipv6 address prefix-list	3937
set ipv6 default next-hop	3938
set ipv6 default next-hop verify-availability	3939
set ipv6 next-hop	3940

set ipv6 next-hop peer-address	3941
set ipv6 next-hop redist-unchanged	3942
set ipv6 next-hop unchanged	3943
set ipv6 next-hop verify-availability	3944
set ipv6 precedence	3945
set label-index	3946
set level level-1 level-1-2 level-2	3947
set local-preference	3948
set metric	3949
set nssa-only	3950
set origin egp	3951
set origin egp igp incomplete	3952
set outer arp	3953
set outer arp	3955
set outer fcoe	3957
set outer ipv4	3959
set outer ipv4	3961
set outer ipv4	3963
set outer ipv6 src_ip	3965
set outer ipv6 src_ip	3966
set outer l2	3967
set outer l2	3969
set outer l2	3971
set outer l2 hg2	3973
set outer l4	3975
set outer l4	3976
set outer l4	3979
set path-selection advertise	3982
set pktrw	3983
set pktrw	3990
set pktrw	3997
set sb_info	4003
set sb_info	4006
set sideband	4009

set sideband	4011
set sideband	4013
set sideband	4015
set stats	4018
set tag	4021
set weight	4022
setup	4023
sflow	4024
sflow	4025
sflow data-source interface	4026
sflow data-source interface	4027
sflow extended switch	4028
shape	4029
shared-secret	4031
shut	4032
shutdown	4033
shutdown	4034
shutdown	4035
shutdown	4036
shutdown	4037
shutdown	4038
shutdown	4039
shutdown	4040
shutdown	4041
shutdown	4042
shutdown	4043
shutdown	4044
shutdown	4045
shutdown	4046
shutdown	4047
shutdown	4048
shutdown	4049
shutdown	4050
shutdown	4051

shutdown	4052
shutdown	4053
shutdown	4054
shutdown	4055
shutdown	4056
shutdown	4057
shutdown	4058
shutdown	4059
shutdown	4060
shutdown	4061
shutdown	4062
shutdown	4063
shutdown	4064
shutdown	4065
shutdown	4066
shutdown	4067
shutdown	4068
shutdown	4069
shutdown	4070
shutdown force	4071
shutdown lan	4072
shutdown lan	4073
signalling advertise explicit-null	4074
signalling hello graceful-restart	4075
signalling hello graceful-restart refresh interval	4076
signalling hello graceful-restart refresh misses	4077
signalling hello graceful-restart send recovery-time	4078
signalling hello graceful-restart send restart-time	4079
signalling hello reroute	4080
signalling initial-retransmit-delay	4081
signalling patherr state-removal	4082
signalling rate-limit	4083
signalling refresh interval	4084
signalling refresh misses	4085

signalling refresh reduction	4086
signalling refresh reduction ack-delay	4087
signalling refresh reduction bundle-max-size	4088
signing level	4089
site-id	4090
site-of-origin	4091
slave ipv4	4092
sleep	4093
sleep instance	4094
slot	4095
slot	4096
smart-channel	4097
smart-channel port-group	4098
smtp-host smtp-port reply-to from	4099
snapshot create	4100
snapshot delete	4101
snapshot delete ALL	4102
snapshot section add	4103
snapshot section delete	4104
snmp-server aaa-user cache-timeout	4105
snmp-server community	4106
snmp-server community	4107
snmp-server community use-acl	4108
snmp-server contact	4109
snmp-server context	4110
snmp-server counter cache enable	4111
snmp-server counter cache timeout	4112
snmp-server enable traps	4113
snmp-server enable traps bgp	4114
snmp-server enable traps bgp cbgp2	4115
snmp-server enable traps bgp cbgp2 threshold prefix	4116
snmp-server enable traps bgp threshold prefix	4117
snmp-server enable traps eigrp	4118
snmp-server enable traps ospf	4119

snmp-server enable traps ospf lsa	4120
snmp-server enable traps ospf rate-limit	4121
snmp-server enable traps ospfv3	4122
snmp-server enable traps ospfv3 lsa	4123
snmp-server enable traps ospfv3 lsa	4124
snmp-server enable traps ospfv3 rate-limit	4125
snmp-server enable traps storm-control trap-rate	4126
snmp-server engineID local	4127
snmp-server force-unload-feature	4128
snmp-server globalEnforcePriv	4129
snmp-server host	4130
snmp-server host filter-vrf	4131
snmp-server host source	4132
snmp-server host use-vrf	4133
snmp-server host use_vrf	4134
snmp-server load-cond-feature	4135
snmp-server load-mib	4136
snmp-server location	4137
snmp-server mib community-map context	4138
snmp-server protocol enable	4139
snmp-server source-interface informs	4140
snmp-server source-interface traps	4141
snmp-server system-shutdown	4142
snmp-server tcp-session	4143
snmp-server user	4144
snmp-server user	4145
snmp ifmib ifalias long	4147
snmp trap link-status	4148
snmp trap link-status	4149
snmp trap link-status	4150
snmp trap link-status	4151
snmp trap link-status	4152
snmp trap link-status	4153
snsr-grp sample-interval	4154

sockets local-port-range	4155
soft-reconfiguration inbound	4156
soft-reconfiguration inbound	4157
soo auto	4158
sort	4159
source-address ipv4	4160
source-group	4161
source-interface	4162
source-interface	4163
source-interface	4164
source-interface	4165
source-interface	4166
source-interface	4167
source-interface hold-down-time	4168
source	4169
source	4170
source	4171
source	4172
source	4173
source	4174
source	4175
source	4176
source	4177
source	4178
source	4179
source copy-sys	4180
source filter ip	4181
source filter ip any any	4182
source forward-drops	4183
source group permit	4184
source interface	4185
source interface	4186
source ip	4187
source vlan	4188

spanning-tree bpdupfilter	4189
spanning-tree bpduguard	4190
spanning-tree bridge-domain	4191
spanning-tree bridge assurance	4192
spanning-tree cost	4193
spanning-tree cost auto	4194
spanning-tree domain	4195
spanning-tree domain clear statistics	4196
spanning-tree fcoe	4197
spanning-tree guard	4198
spanning-tree lc-issu	4199
spanning-tree lc-issu	4200
spanning-tree link-type	4201
spanning-tree loopguard default	4202
spanning-tree mode	4203
spanning-tree mst configuration	4204
spanning-tree mst configuration	4205
spanning-tree mst cost	4206
spanning-tree mst cost auto	4207
spanning-tree mst forward-time	4208
spanning-tree mst hello-time	4209
spanning-tree mst max-age	4210
spanning-tree mst max-hops	4211
spanning-tree mst port-priority	4212
spanning-tree mst pre-standard	4213
spanning-tree mst priority	4214
spanning-tree mst root	4215
spanning-tree mst simulate pvst	4216
spanning-tree mst simulate pvst global	4217
spanning-tree pathcost method	4218
spanning-tree port-priority	4219
spanning-tree port type	4220
spanning-tree port type edge bpdupfilter default	4221
spanning-tree port type edge bpduguard default	4222

spanning-tree port type edge default	4223
spanning-tree port type edge trunk	4224
spanning-tree port type network default	4225
spanning-tree pseudo-information	4226
spanning-tree vlan	4227
spanning-tree vlan forward-time	4228
spanning-tree vlan hello-time	4229
spanning-tree vlan max-age	4230
spanning-tree vlan priority	4231
spanning-tree vlan root	4232
speed-group	4233
speed	4234
speed	4235
speed	4236
speed	4237
speed	4238
speed	4239
speed	4240
speed	4241
speed auto	4242
speed auto 100	4243
speed auto 100 1000	4244
speed auto 100 1000	4245
speed auto 100	4246
speed auto	4247
spf-interval	4248
spf-interval	4249
spf-interval	4250
spf mode incremental	4251
sport	4252
sport	4253
src-intf	4254
ssh	4255
ssh6	4256

ssh all	4257
ssh cipher-mode weak	4258
ssh idle	4259
ssh key	4260
ssh login-attempts	4261
ssh login-gracetime	4262
ssh port	4263
ssh rekey max-data max-time	4264
ssh server enable	4265
ssx exporter	4266
ssx monitor	4267
ssx record	4268
ssx system monitor	4269
ssx system system-id	4270
standby	4271
standby ip	4272
start-threshold	4273
start	4274
start	4275
start	4276
start	4277
start	4278
start	4279
start	4280
start	4281
start	4282
start	4283
start	4284
start	4285
start	4286
start	4287
start	4288
start	4289
state	4290

state enabled	4291
statistics	4292
statistics	4293
statistics	4294
statistics collection-interval	4295
statistics per-entry	4296
statistics per-entry	4297
statistics per-entry	4298
statistics per-entry	4299
stats-reporting-period	4300
status	4301
status	4302
status	4303
status	4304
status	4305
status	4306
status	4307
stop-threshold	4308
stopbits	4309
stopbits 1	4310
storm-control-cpu	4311
storm-control	4312
streetaddress	4313
stub	4314
sub-switch vlan	4315
subscription	4316
summary-address	4317
summary-address	4318
summary-address	4319
summary-address	4320
suppress-arp	4321
suppress-fib-pending	4322
suppress-fib-pending	4323
suppress-inactive	4324

suppress-inactive	4325
suppress-signaling-protocol ldp	4326
suppress mac-route	4327
switch-id	4328
switch-priority	4329
switch-profile	4330
switch-profile	4331
switch-role border-leaf	4332
switch-scope controller	4333
switch pipeline	4334
switchback	4335
switching-mode fabric-speed 40g	4336
switching-mode fast-to-slow-speed-cut-through	4337
switching-mode store-forward	4338
switchport	4339
switchport	4340
switchport access vlan	4341
switchport access vlan	4342
switchport access vlan	4343
switchport autostate exclude	4344
switchport backup interface	4345
switchport backup interface	4346
switchport backup interface multicast fast-convergence	4347
switchport backup interface multicast fast-convergence	4348
switchport backup interface preemption delay	4349
switchport backup interface preemption delay	4350
switchport backup interface preemption mode	4351
switchport backup interface preemption mode	4352
switchport beacon	4353
switchport block unicast	4354
switchport description	4355
switchport dot1q ethertype	4356
switchport dot1q ethertype	4357
switchport duplex	4358

switchport host	4359
switchport ignore bit-errors	4360
switchport isolated	4361
switchport mac-learn disable	4362
switchport mode	4363
switchport mode	4364
switchport mode	4365
switchport mode	4366
switchport mode	4367
switchport mode	4368
switchport mode monitor buffer-limit	4369
switchport mode private-vlan	4370
switchport mode private-vlan trunk	4371
switchport monitor	4372
switchport mtu	4373
switchport owner	4374
switchport port-security	4375
switchport port-security aging time	4376
switchport port-security aging type absolute	4377
switchport port-security mac-address	4378
switchport port-security mac-address sticky	4379
switchport port-security maximum	4380
switchport port-security violation	4381
switchport priority extend cos	4382
switchport private-vlan association trunk	4383
switchport private-vlan host-association	4384
switchport private-vlan mapping	4385
switchport private-vlan mapping trunk	4386
switchport private-vlan trunk allowed vlan	4387
switchport private-vlan trunk native vlan	4388
switchport promiscuous-mode off	4389
switchport speed	4390
switchport speed	4391
switchport trunk allow-multi-tag	4392

switchport trunk allowed vlan	4393
switchport trunk allowed vsan	4394
switchport trunk allowed vsan	4395
switchport trunk mode	4396
switchport trunk mode	4397
switchport trunk native vlan	4398
switchport trunk pruning vlan except add remove none all	4399
switchport virtual-ethernet-bridge	4400
switchport vlan mapping	4401
switchport vlan mapping all	4402
switchport vlan mapping all dot1q-tunnel	4403
switchport vlan mapping all dot1q-tunnel	4404
switchport vlan mapping dot1q-tunnel	4405
switchport vlan mapping dot1q-tunnel allowed-vlan	4406
switchport vlan mapping enable	4407
switchport voice vlan	4408
switchport voice vlan	4409
switchto vdc	4410
sync-peers destination	4411
sync-snmp-password	4412
sync-snmp-password	4413
sync-snmp-password	4414
system-mac	4415
system-mac	4416
system-priority	4417
system	4418
system	4419
system acl	4421
system auto-collect tech-support	4422
system cores	4423
system default interface-vlan autostate	4424
system default interface	4425
system default interface	4426
system default switchport	4427

system default switchport shutdown	4428
system default tx-credit double-queue	4429
system dot1q-tunnel transit	4430
system fabric-mode full-rate	4431
system fabric core-vlans	4432
system fabric dynamic-vlans	4433
system fast-reload stabilization-timer	4434
system hap-reset	4435
system hap-reset	4436
system health check bootflash	4437
system heartbeat	4438
system heartbeat	4439
system high-multicast-priority	4440
system inband queuing	4441
system inband queuing	4442
system interface shutdown	4443
system jumbomtu	4444
system kgdb	4445
system kgdb	4446
system login block-for	4447
system login block-for attempts within	4448
system login quiet-mode	4449
system login quiet-mode access-class	4450
system memory-thresholds minor severe critical	4451
system mode maintenance	4452
system mode maintenance always-use-custom-profile	4453
system mode maintenance maint-delay	4454
system mode maintenance on-reload reset-reason	4455
system mode maintenance snapshot-delay	4456
system mode maintenance timeout	4457
system module emon-enhanced	4458
system module failure-action shutdown	4459
system mrouting	4460
system poap	4461

system poap	4462
system pss shrink	4463
system qos	4464
system routing unknown-unicast-flood	4465
system security compliance common-criteria	4466
system shutdown fan-direction mismatch	4467
system simulate fan-presence	4468
system standby manual-boot	4469
system standby manual-boot	4470
system startup-config init	4471
system startup-config unlock	4472
system statistics	4473
system statistics	4474
system switch-mode	4475
system switchover	4476
system switchover force	4477
system timeout	4478
system trace	4479
system urpf disable	4480
system vlan long-name	4481
system vlan reserve	4482
system vrf-member-change retain-l3-config	4483
system watchdog	4484
system watchdog	4485
system watchdog kgdb	4486
system watchdog kgdb	4487

CHAPTER 21

T Commands 4489

table-map	4496
table-map	4497
table-map	4498
table-map	4499
table-map	4500
table-map	4501

table-map	4502
table-map	4503
tac-pac	4504
tac-pac	4505
tacacs-server deadline	4506
tacacs-server directed-request	4507
tacacs-server host key 0 6 7	4508
tacacs-server host test	4509
tacacs-server key 0 6 7	4510
tacacs-server test	4511
tacacs-server timeout	4512
tacacs enable	4513
tag	4514
tag happens in	4515
tahoe-python module	4516
tahoe-python module quoted	4517
tail	4518
tail	4519
tar	4520
tclsh	4521
tclsh	4522
tcp-connect	4523
telnet	4524
telnet6	4525
telnet login-attempts	4526
telnet server enable	4527
template	4528
template data timeout	4529
template peer-policy	4530
template peer-session	4531
template peer	4532
terminal	4533
terminal alias	4534
terminal ask-on-term	4535

terminal color 4536

terminal context management 4537

terminal deep-help 4538

terminal dont-ask 4539

terminal edit-mode vi 4540

terminal event-manager bypass 4541

terminal history no-exec-in-config 4542

terminal history no-exec-in-config 4543

terminal history no-exec-in-config 4544

terminal home 4545

terminal length 4546

terminal length 4547

terminal log-all 4548

terminal no 4549

terminal output xml 4550

terminal output xml 4551

terminal output xml 4552

terminal password 4553

terminal prompt 4554

terminal redirection-mode 4555

terminal session-timeout 4556

terminal sticky-mode 4557

terminal terminal-type 4558

terminal time 4559

terminal tree-update 4560

terminal verify-only 4561

terminal width 4562

terminal width 4563

threshold-percent 4564

threshold 4565

time-range 4566

timeout 4567

timeout 4568

timeout 4569

timer	4570
timer	4571
timer inactivity	4572
timers	4573
timers	4574
timers	4575
timers advertise	4576
timers basic	4577
timers bestpath-defer maximum	4578
timers bestpath-limit	4579
timers bgp	4580
timers lsa-arrival	4581
timers lsa-arrival	4582
timers lsa-group-pacing	4583
timers lsa-group-pacing	4584
timers prefix-peer-timeout	4585
timers prefix-peer-wait	4586
timers srgb cleanup	4587
timers srgb retry	4588
timers throttle lsa	4589
timers throttle lsa	4590
timers throttle spf	4591
timers throttle spf	4592
timestamp timestamp	4593
tls trust-point local remote	4594
tls trust-point local remote	4595
topology	4596
topology holddown sigerr	4597
tos	4598
tr	4599
trace buffer size	4600
traceroute	4601
traceroute6	4602
track-adjacency-nexthop	4603

track	4604
track	4605
track	4606
track	4607
track	4608
track	4609
track	4610
track	4611
track	4612
track	4613
track data	4614
track interface	4615
track interface priority	4616
track running-state track startup-state	4617
tracking enable	4618
traffic-class	4619
traffic-engineering	4620
transmit-delay	4621
transmit-delay	4622
transmit-delay	4623
transport connection-mode passive	4624
transport email	4625
transport email mail-server	4626
transport http proxy enable	4627
transport http proxy server	4628
transport http use-vrf	4629
transport udp	4630
transport udp	4631
transport udp	4632
transport udp source-port	4633
trigger forwarding distribution module	4634
trigger init	4635
trigger init in-select 10	4636
trigger init in-select 10 out-select 0	4637

trigger init in-select 10 out-select 1	4638
trigger init in-select 10 out-select 2	4639
trigger init in-select 19	4640
trigger init in-select 19 out-select 0	4641
trigger init in-select 19 out-select 1	4642
trigger init in-select 19 out-select 2	4643
trigger init in-select 6	4644
trigger init in-select 6 out-select 0	4645
trigger init in-select 6 out-select 1	4646
trigger init in-select 6 out-select 2	4647
trigger init in-select 7	4648
trigger init in-select 7 out-select 0	4649
trigger init in-select 7 out-select 1	4650
trigger init in-select 7 out-select 2	4651
trigger init in-select 8	4652
trigger init in-select 8 out-select 0	4653
trigger init in-select 8 out-select 1	4654
trigger init in-select 8 out-select 2	4655
trigger init in-select 9	4656
trigger init in-select 9 out-select 0	4657
trigger init in-select 9 out-select 1	4658
trigger init in-select 9 out-select 2	4659
trigger init ingress in-select 3 out-select 0	4660
trigger init ingress in-select 3 out-select 03	4661
trigger init ingress in-select 3 out-select 0 reverse	4662
trigger init ingress in-select 3 out-select 1	4663
trigger init ingress in-select 3 out-select 2	4664
trigger init ingress in-select 3 out-select 4	4665
trigger init ingress in-select 3 out-select 5	4666
trigger init ingress in-select 3 out-select 5 reverse	4667
trigger init ingress in-select 4 out-select 0	4668
trigger init ingress in-select 4 out-select 04	4669
trigger init ingress in-select 4 out-select 0 reverse	4670
trigger init ingress in-select 4 out-select 1	4671

trigger init ingress in-select 4 out-select 2	4672
trigger init ingress in-select 4 out-select 3	4673
trigger init ingress in-select 4 out-select 5	4674
trigger init ingress in-select 4 out-select 5 reverse	4675
trigger init ingress in-select 5 out-select 0	4676
trigger init ingress in-select 5 out-select 05	4677
trigger init ingress in-select 5 out-select 05 reverse	4678
trigger init ingress in-select 5 out-select 0 reverse	4679
trigger init ingress in-select 5 out-select 1	4680
trigger init ingress in-select 5 out-select 2	4681
trigger init ingress in-select 5 out-select 3	4682
trigger init ingress in-select 5 out-select 4	4683
trigger init ingress in-select 6 out-select 0	4684
trigger init ingress in-select 6 out-select 0 reverse	4685
trigger init ingress in-select 6 out-select 1	4686
trigger init ingress in-select 6 out-select 2	4687
trigger init ingress in-select 6 out-select 3	4688
trigger init ingress in-select 6 out-select 4	4689
trigger init ingress in-select 6 out-select 5	4690
trigger init ingress in-select 6 out-select 5 reverse	4691
trigger init ingress in-select 7 out-select 0	4692
trigger init ingress in-select 7 out-select 0 reverse	4693
trigger init ingress in-select 7 out-select 1	4694
trigger init ingress in-select 7 out-select 2	4695
trigger init ingress in-select 7 out-select 3	4696
trigger init ingress in-select 7 out-select 4	4697
trigger init ingress in-select 7 out-select 5	4698
trigger init ingress in-select 7 out-select 5 reverse	4699
trigger init lu-a2d 0	4700
trigger init lu-a2d 0 in-select 10 out-select 0	4701
trigger init lu-a2d 0 in-select 10 out-select 1	4702
trigger init lu-a2d 0 in-select 10 out-select 2	4703
trigger init lu-a2d 0 in-select 19 out-select 0	4704
trigger init lu-a2d 0 in-select 19 out-select 1	4705

trigger init lu-a2d 0 in-select 19 out-select 2	4706
trigger init lu-a2d 0 in-select 6 out-select 0	4707
trigger init lu-a2d 0 in-select 6 out-select 1	4708
trigger init lu-a2d 0 in-select 6 out-select 2	4709
trigger init lu-a2d 0 in-select 7 out-select 0	4710
trigger init lu-a2d 0 in-select 7 out-select 1	4711
trigger init lu-a2d 0 in-select 7 out-select 2	4712
trigger init lu-a2d 0 in-select 8 out-select 0	4713
trigger init lu-a2d 0 in-select 8 out-select 1	4714
trigger init lu-a2d 0 in-select 8 out-select 2	4715
trigger init lu-a2d 0 in-select 9 out-select 0	4716
trigger init lu-a2d 0 in-select 9 out-select 1	4717
trigger init lu-a2d 0 in-select 9 out-select 2	4718
trigger init lu-a2d 0 out-select 0	4719
trigger init lu-a2d 0 out-select 1	4720
trigger init lu-a2d 0 out-select 2	4721
trigger init lu-a2d 1	4722
trigger init lu-a2d 1 in-select 10	4723
trigger init lu-a2d 1 in-select 10 out-select 0	4724
trigger init lu-a2d 1 in-select 10 out-select 1	4725
trigger init lu-a2d 1 in-select 10 out-select 2	4726
trigger init lu-a2d 1 in-select 19	4727
trigger init lu-a2d 1 in-select 19 out-select 0	4728
trigger init lu-a2d 1 in-select 19 out-select 1	4729
trigger init lu-a2d 1 in-select 19 out-select 2	4730
trigger init lu-a2d 1 in-select 6	4731
trigger init lu-a2d 1 in-select 6 out-select 0	4732
trigger init lu-a2d 1 in-select 6 out-select 1	4733
trigger init lu-a2d 1 in-select 6 out-select 2	4734
trigger init lu-a2d 1 in-select 7	4735
trigger init lu-a2d 1 in-select 7 out-select 0	4736
trigger init lu-a2d 1 in-select 7 out-select 1	4737
trigger init lu-a2d 1 in-select 7 out-select 2	4738
trigger init lu-a2d 1 in-select 8	4739

trigger init lu-a2d 1 in-select 8 out-select 0	4740
trigger init lu-a2d 1 in-select 8 out-select 1	4741
trigger init lu-a2d 1 in-select 8 out-select 2	4742
trigger init lu-a2d 1 in-select 9	4743
trigger init lu-a2d 1 in-select 9 out-select 0	4744
trigger init lu-a2d 1 in-select 9 out-select 1	4745
trigger init lu-a2d 1 in-select 9 out-select 2	4746
trigger init out-select 0	4747
trigger init out-select 1	4748
trigger init out-select 2	4749
trigger reset	4750
trigger route download vrf ipv4	4751
trunk protocol	4752
trusted-port	4753
trusted-port	4754
trusted-port	4755
ttag-marker-interval	4756
ttag-marker-interval	4757
ttag-marker enable	4758
ttag-marker enable	4759
ttag-strip	4760
ttag	4761
ttag	4762
ttn-security hops	4763
tunnel destination	4764
tunnel mode	4765
tunnel path-mtu-discovery	4766
tunnel path-mtu-discovery age-timer	4767
tunnel path-mtu-discovery min-mtu	4768
tunnel source	4769
tunnel ttl	4770
tunnel use-vrf	4771

udf 4775

udld aggressive 4776

udld aggressive 4777

udld aggressive 4778

udld aggressive 4779

udld continue-on-err 4780

udld disable 4781

udld disable 4782

udld enable 4783

udld enable 4784

udld message-time 4785

udld reset 4786

udp-echo 4787

udp-jitter 4788

undebug all 4790

undebug l2rib 4791

uniq 4792

unmount 4793

unmount slot0 4794

unsuppress-map 4795

untagged cos 4796

update-source 4797

update-source 4798

update license 4799

update license 4800

urib debugs-dump-to-file 4801

use-chunking size 4802

use-compression gzip 4803

use-retry size 4804

use-vrf 4805

use-vrf 4806

use-vrf 4807

use-vrf 4808

user-jid password 4809

user max-logins	4810
user max-logins	4811
username	4812
username	4813
username	4814
username	4815
username	4816
username keypair export	4817
username keypair generate	4818
username keypair import	4819
username password	4820
username ssh-cert-dn dsa	4821
username sshkey	4822
userpassphrase	4823
userpassphrase min	4824
userpassphrase min	4825
userprofile trustedCert CRLLookup user-switch-bind user-certdn-match user-pubkey-match attribute-name search-filter base-DN	4826

CHAPTER 23**V Commands 4827**

validate-json	4830
validate-xml	4831
validate-xml	4832
vdc	4833
vdc	4834
vdc combined-hostname	4835
vdc_id	4836
vdc resource template	4837
vdc suspend	4838
vdc suspend	4839
vdp dot1q default static	4840
vdp dot1q static	4841
vdp vni default static	4842
vdp vni static	4843

verify-data	4844
verify-host	4845
verify	4846
verify profile	4847
verify verbose	4848
version	4849
version 9	4850
virtual-service	4851
virtual-service	4852
virtual-service	4853
virtual-service move name log to	4854
virtual-service reset force	4855
virtual IPv6	4856
virtual IPv6	4857
virtual ip	4858
virtual ip	4859
vlan-consistency-check	4860
vlan-pruning enable	4861
vlan	4862
vlan2	4863
vlan	4864
vlan	4865
vlan access-map	4866
vlan configuration	4867
vlan designated priority	4868
vlan filter vlan	4869
vlan root priority	4870
vmtracker connection	4871
vmtracker connection refresh	4872
vmtracker enable	4873
vmtracker fabric auto-config	4874
vn-segment	4875
vni	4876
vni	4877

vni	4878
vni default dynamic	4879
vni l2	4880
vpc	4881
vpc domain	4882
vpc orphan-port suspend	4883
vpc peer-link	4884
vpc role preempt	4885
vpn	4886
vpn id	4887
vrf	4888
vrf	4889
vrf	4890
vrf	4891
vrf	4892
vrf	4893
vrf	4894
vrf	4895
vrf	4896
vrf	4897
vrf	4898
vrf	4899
vrf	4900
vrf context	4901
vrf default static	4902
vrf member	4903
vrf member	4904
vrf static	4905
vrrp	4906
vrrp bfd	4907
vrrpv2	4908
vrrpv3	4909
vrrpv3 address-family	4910
vrrpv3 address-family	4911

[vrrs leader](#) 4912
[vrrs pathway](#) 4913
[vsh](#) 4914
[vtp](#) 4915
[vtp domain](#) 4916
[vtp file](#) 4917
[vtp mode](#) 4918
[vtp password](#) 4919
[vtp pruning](#) 4920
[vtp version](#) 4921

CHAPTER 24
W Commands 4923

[wait-igp-convergence](#) 4924
[watch](#) 4925
[watch service action apply-acl](#) 4926
[watchlist](#) 4927
[watchlist](#) 4928
[wc](#) 4929
[wedge bmc ip-addr](#) 4930
[weight](#) 4931
[weight](#) 4932
[weight](#) 4933
[weight](#) 4934
[where](#) 4935
[where detail](#) 4936
[window-size](#) 4937
[wred-queue qos-group-map queue-only](#) 4938
[write erase](#) 4939
[write erase boot](#) 4940
[write erase debug](#) 4941
[write erase poap](#) 4942
[wrr-queue qos-group-map](#) 4943
[wrr unicast-bandwidth](#) 4944
[wwn vsan vsan-wwn](#) 4945

CHAPTER 25**X Commands 4947**

- xconnect 4948
- xml 4949
- xml 4950
- xml server max-session 4951
- xml server rm-shm 4952
- xml server terminate session 4953
- xml server timeout 4954
- xml server validate 4955
- xml server xml-debug 4956
- xmlagent 4957
- xmlin 4958
- xmlin 4959
- xmlin 4960
- xmlin 4961
- xmlout 4962



Preface

This preface includes the following sections:

- [Audience, on page cxliii](#)
- [Documentation Conventions, on page cxliii](#)
- [Documentation Feedback, on page cxliv](#)
- [Communications, Services, and Additional Information, on page cxliv](#)

Audience

This publication is for network administrators who install, configure, and maintain Cisco Nexus switches.

Documentation Conventions

Command descriptions use the following conventions:

Convention	Description
bold	Bold text indicates the commands and keywords that you enter literally as shown.
<i>Italic</i>	Italic text indicates arguments for which the user supplies the values.
[x]	Square brackets enclose an optional element (keyword or argument).
[x y]	Square brackets enclosing keywords or arguments separated by a vertical bar indicate an optional choice.
{x y}	Braces enclosing keywords or arguments separated by a vertical bar indicate a required choice.
[x {y z}]	Nested set of square brackets or braces indicate optional or required choices within optional or required elements. Braces and a vertical bar within square brackets indicate a required choice within an optional element.
variable	Indicates a variable for which you supply values, in context where italics cannot be used.

Convention	Description
string	A nonquoted set of characters. Do not use quotation marks around the string or the string will include the quotation marks.

Examples use the following conventions:

Convention	Description
<code>screen font</code>	Terminal sessions and information the switch displays are in screen font.
boldface screen font	Information you must enter is in boldface screen font.
<i>italic screen font</i>	Arguments for which you supply values are in italic screen font.
<>	Nonprinting characters, such as passwords, are in angle brackets.
[]	Default responses to system prompts are in square brackets.
!, #	An exclamation point (!) or a pound sign (#) at the beginning of a line of code indicates a comment line.

Documentation Feedback

To provide technical feedback on this document, or to report an error or omission, please send your comments to . We appreciate your feedback.

Communications, Services, and Additional Information

- To receive timely, relevant information from Cisco, sign up at [Cisco Profile Manager](#).
- To get the business impact you're looking for with the technologies that matter, visit [Cisco Services](#).
- To submit a service request, visit [Cisco Support](#).
- To discover and browse secure, validated enterprise-class apps, products, solutions and services, visit [Cisco Marketplace](#).
- To obtain general networking, training, and certification titles, visit [Cisco Press](#).
- To find warranty information for a specific product or product family, access [Cisco Warranty Finder](#).

Cisco Bug Search Tool

[Cisco Bug Search Tool](#) (BST) is a web-based tool that acts as a gateway to the Cisco bug tracking system that maintains a comprehensive list of defects and vulnerabilities in Cisco products and software. BST provides you with detailed defect information about your products and software.



Notice

- [Notice, on page 2](#)

Notice



Warning

This document should be used only as a glossary reference for possible commands. The listing of a command in this document does not guarantee that the command is available or supported for your platform or application.

The command information in this reference document is auto-generated from the NX-OS source code. While we attempt to manually remove unsupported, deprecated, or internal-use commands, such commands may occasionally appear in this document. Also, with the large variety of hardware platform combinations using NX-OS software, some listed commands may not be applicable or recommended for a specific platform. Platform-based dependency information is not provided in this command reference.

We strongly encourage you to refer to the configuration guides for appropriate commands to configure and operate a feature. Command limitations, restrictions, and recommendations are documented only in the configuration guides. When in doubt, please consult your Cisco representative.



A Commands

- [aaa accounting default](#), on page 8
- [aaa accounting dot1x default group](#), on page 9
- [aaa authentication dot1x default group](#), on page 10
- [aaa authentication login ascii-authentication](#), on page 11
- [aaa authentication login console](#), on page 12
- [aaa authentication login default](#), on page 14
- [aaa authentication login default fallback error local](#), on page 16
- [aaa authentication login enable](#), on page 17
- [aaa authentication login error-enable](#), on page 18
- [aaa authentication login invalid-username-log](#), on page 19
- [aaa authentication login password-aging enable](#), on page 20
- [aaa authentication rejected](#), on page 21
- [aaa authentication rejected in ban](#), on page 22
- [aaa authorization commands console](#), on page 23
- [aaa authorization commands default](#), on page 24
- [aaa authorization ssh default group](#), on page 25
- [aaa bypass-user](#), on page 26
- [aaa group server ldap](#), on page 27
- [aaa group server radius](#), on page 28
- [aaa group server tacacs](#), on page 29
- [aaa test-authentication](#), on page 30
- [aaa test-radius-authentication](#), on page 31
- [aaa user default-role](#), on page 32
- [abort](#), on page 33
- [abort](#), on page 34
- [abort](#), on page 35
- [abort](#), on page 36
- [absolute-timeout](#), on page 37
- [absolute start](#), on page 38
- [accept-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l](#), on page 39
- [access-class](#), on page 41
- [access-list](#), on page 42

- [access-list](#), on page 43
- [access-list ipv6](#), on page 44
- [access vlan](#), on page 45
- [acllog match-log-level](#), on page 46
- [action](#), on page 47
- [action](#), on page 48
- [action cli](#), on page 49
- [action counter name value op](#), on page 50
- [action eem test](#), on page 51
- [action event-default](#), on page 52
- [action forceshut reset-reason](#), on page 53
- [action overbudgetshut](#), on page 54
- [action policy-default](#), on page 55
- [action reload](#), on page 56
- [action snmp-trap](#), on page 57
- [action syslog msg](#), on page 58
- [additional-paths install backup](#), on page 59
- [additional-paths receive](#), on page 60
- [additional-paths selection route-map](#), on page 61
- [additional-paths send](#), on page 62
- [address-family ipv4](#), on page 63
- [address-family ipv4 labeled-unicast](#), on page 64
- [address-family ipv4 labeled-unicast](#), on page 65
- [address-family ipv4 mdt](#), on page 66
- [address-family ipv4 mdt](#), on page 67
- [address-family ipv4 mvpn](#), on page 68
- [address-family ipv4 mvpn](#), on page 69
- [address-family ipv6](#), on page 70
- [address-family ipv6 labeled-unicast](#), on page 71
- [address-family ipv6 labeled-unicast](#), on page 72
- [address-family ipv6 mvpn](#), on page 73
- [address-family ipv6 mvpn](#), on page 74
- [address-family l2vpn evpn](#), on page 75
- [address-family l2vpn evpn](#), on page 76
- [address-family l2vpn vpls](#), on page 77
- [address-family l2vpn vpls](#), on page 78
- [address-family link-state](#), on page 79
- [address-family link-state](#), on page 80
- [address-family vpv4 unicast](#), on page 81
- [address-family vpv4 unicast](#), on page 82
- [address-family vpv6 unicast](#), on page 83
- [address-family vpv6 unicast](#), on page 84
- [address](#), on page 85
- [address](#), on page 86
- [address](#), on page 87
- [address](#), on page 88

- address, on page 89
- address, on page 90
- address port-number, on page 91
- address primary, on page 92
- address secondary, on page 93
- address secondary, on page 94
- adjacency-check, on page 95
- adjacency-resolve, on page 96
- advertise-gw-ip, on page 97
- advertise-labels, on page 98
- advertise-map exist default advertise-map, on page 99
- advertise-pip, on page 100
- advertise-system-mac, on page 101
- advertise evpn multicast, on page 102
- advertise interface, on page 103
- advertise l2vpn evpn, on page 104
- advertise local-labeled-route, on page 105
- advertise virtual-rmac, on page 106
- advertisement-interval, on page 107
- advertisement-interval, on page 108
- afd queue-desired, on page 109
- affinity-group, on page 110
- affinity-group activate, on page 111
- affinity, on page 112
- affinity, on page 113
- age, on page 114
- age, on page 115
- aggregate-address, on page 116
- aggregate-address, on page 117
- alert-group user-def-cmd, on page 118
- allocate-label all, on page 119
- allocate-label option-b, on page 120
- allocate1 interface2, on page 121
- allocate2 fcoe-vlan-range, on page 122
- allocate3 shared interface3, on page 123
- allow-vni-in-ethertag, on page 124
- allow feature-set, on page 125
- allowas-in, on page 126
- allowas-in, on page 127
- allowed-locators, on page 128
- allowed-vlans, on page 129
- amt flush-routes, on page 130
- amt pseudo-interface, on page 131
- analytics cluster, on page 132
- anonymous-id, on page 133
- append-after next, on page 134

- [apply profile, on page 135](#)
- [area authentication, on page 136](#)
- [area authentication, on page 137](#)
- [area default-cost, on page 138](#)
- [area default-cost, on page 139](#)
- [area filter-list route-map in, on page 140](#)
- [area filter-list route-map in, on page 141](#)
- [area nssa, on page 142](#)
- [area nssa, on page 143](#)
- [area nssa translate type7 always never supress-fa, on page 144](#)
- [area nssa translate type7 always never supress-fa, on page 145](#)
- [area range, on page 146](#)
- [area range, on page 147](#)
- [area sham-link, on page 148](#)
- [area stub, on page 149](#)
- [area stub, on page 150](#)
- [area virtual-link, on page 151](#)
- [area virtual-link, on page 152](#)
- [area virtual-link, on page 153](#)
- [area virtual-link, on page 154](#)
- [arp access-list, on page 155](#)
- [as-format asdot, on page 156](#)
- [as-override, on page 157](#)
- [assign interface shared, on page 158](#)
- [assign vlan dedicated, on page 159](#)
- [assign vrf prefix number dedicated, on page 160](#)
- [attach console module, on page 161](#)
- [attach module, on page 162](#)
- [attach module node, on page 163](#)
- [attach module port, on page 164](#)
- [auth-mechanism plain, on page 165](#)
- [authentication-check, on page 166](#)
- [authentication-check, on page 167](#)
- [authentication-check level-1, on page 168](#)
- [authentication-check level-2, on page 169](#)
- [authentication-key, on page 170](#)
- [authentication-key, on page 171](#)
- [authentication-key, on page 172](#)
- [authentication-type cleartext, on page 173](#)
- [authentication-type cleartext, on page 174](#)
- [authentication-type cleartext, on page 175](#)
- [authentication, on page 176](#)
- [authentication, on page 177](#)
- [authentication, on page 178](#)
- [authentication, on page 179](#)
- [authentication, on page 180](#)

- authentication, on page 181
- authentication bind, on page 182
- authentication challenge, on page 183
- authentication key-chain, on page 184
- authentication key-chain, on page 185
- authentication key-chain, on page 186
- authentication key-chain, on page 187
- authentication key-chain, on page 188
- authentication key-chain, on page 189
- authentication lifetime, on page 190
- authentication text, on page 191
- authentication type md5, on page 192
- authentication window-size, on page 193
- auto-bw, on page 194
- auto-bw, on page 195
- auto-bw timers frequency, on page 196
- auto-cost reference-bandwidth, on page 197
- auto-cost reference-bandwidth, on page 198
- auto-recovery, on page 199
- auto-remap-replication-servers, on page 200
- autonomous-system, on page 201
- autoroute announce, on page 202
- autoroute metric, on page 203
- autostate, on page 204
- autovlan enable, on page 205
- awk, on page 206

aaa accounting default

```
[no] aaa accounting default { group <s0> [ <s1> [ <s2> [ <s3> [ <s4> [ <s5> [ <s6> [ <s7> ] ] ] ] ] ] ] [ local1
| none ] | local [ none1 ] | none2 }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
accounting	Configure accounting methods
default	Configure default methods
group	Specify server groups to redirect the accounting logs
s0	Server group name
s1	(Optional) Server group name
s2	(Optional) Server group name
s3	(Optional) Server group name
s4	(Optional) Server group name
s5	(Optional) Server group name
s6	(Optional) Server group name
s7	(Optional) Server group name
none	(Optional) No accounting
none1	(Optional) No accounting
none2	No accounting
local	Use local accounting
local1	(Optional) Use local accounting

Command Mode

- /exec/configure

aaa accounting dot1x default group

[no] aaa accounting dot1x default group <grp_name> +

Syntax Description

aaa	Configure aaa functions
accounting	Configure accounting methods
dot1x	accounting methods for dot1x
default	default aaa methods
<i>grp_name</i>	server group name

Command Mode

- /exec/configure

aaa authentication dot1x default group

[no] aaa authentication dot1x default group <grp_name> +

Syntax Description

aaa	Configure aaa functions
authentication	Configure authentication methods
<i>grp_name</i>	server group name

Command Mode

- /exec/configure

aaa authentication login ascii-authentication

[no] aaa authentication login ascii-authentication

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
ascii-authentication	enable ascii authentication

Command Mode

- /exec/configure

none	No authentication
------	-------------------

Command Mode

- /exec/configure

aaa authentication login default

```
[no] aaa authentication login default { group <s0> [ { local1 | none | <s1> [ { local1 | none | <s2> [ { local1 | none | <s3> [ { local1 | none | <s4> [ { local1 | none | <s5> [ { local1 | none | <s6> [ { local1 | none | <s7> [ { local1 | none } ] ] ] ] ] ] ] ] ] ] ] ] ] ] | local | none }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
default	Configure default methods
group	Specify server groups
<i>s0</i>	Server group name
none	(Optional) No authentication
<i>s1</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s2</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s3</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s4</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s5</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s6</i>	(Optional) Server group name
none	(Optional) No authentication
<i>s7</i>	(Optional) Server group name
none	(Optional) No authentication
local	Use local username authentication
local1	(Optional) Use local username authentication

none	No authentication
------	-------------------

Command Mode

- /exec/configure

aaa authentication login default fallback error local

[no] aaa authentication login { default | console } fallback error local

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
default	Configure default methods
console	Configure console methods
fallback	Configure fallback behavior
error	Fallback in case all AAA servers configured for remote authentication are unreachable (Authentication error)
local	Fallback to local authentication

Command Mode

- /exec/configure

aaa authentication login enable

[no] aaa authentication login { mschap | mschapv2 | chap } enable

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
mschap	MSCHAP authentication for login
mschapv2	MSCHAP V2 authentication for login
chap	CHAP authentication for login
enable	enable the authentication for login

Command Mode

- /exec/configure

aaa authentication login error-enable

[no] aaa authentication login error-enable

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
error-enable	enable display of error message on login failures

Command Mode

- /exec/configure

aaa authentication login invalid-username-log

[no] aaa authentication login invalid-username-log

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
invalid-username-log	enable invalid username log

Command Mode

- /exec/configure

aaa authentication login password-aging enable

[no] aaa authentication login password-aging enable

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
login	Configure methods for login
password-aging	password-aging authentication for login
enable	enable password-aging notification

Command Mode

- /exec/configure

aaa authentication rejected

[no] aaa authentication rejected

Syntax Description

no	Negate a command or set its defaults
aaa	Configure aaa functions
authentication	Configure authentication methods
rejected	Set max number of fail attempts

Command Mode

- /exec/configure

aaa authentication rejected in ban

aaa authentication rejected <i1> in <i2> ban <i3>

Syntax Description

aaa	Configure aaa functions
authentication	Configure authentication methods
rejected	Set max number of fail attempts
<i>i1</i>	Fail attempts max value
in	Watch period for fail attempts
<i>i2</i>	Time period in seconds
ban	Block time period
<i>i3</i>	Time period in seconds

Command Mode

- /exec/configure

aaa authorization commands console

```
[no] aaa authorization { commands | config-commands } console { group <s0> [ { local | none | <s1> [ { local | none | <s2> [ { local | none | <s3> [ { local | none | <s4> [ { local | none | <s5> [ { local | none | <s6> [ { local | none | <s7> [ { local | none } ] ] ] ] ] ] ] ] ] ] ] ] ] ] | local | none }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authorization	Configure authorization methods
commands	Authorization for all exec-mode commands
config-commands	Authorization for config commands
console	Configure methods console
group	Specify server groups
s0	Server group name
s1	(Optional) Server group name
s2	(Optional) Server group name
s3	(Optional) Server group name
s4	(Optional) Server group name
s5	(Optional) Server group name
s6	(Optional) Server group name
s7	(Optional) Server group name
local	(Optional) Use local RBACL based authorization
none	(Optional) No authorization

Command Mode

- /exec/configure

aaa authorization commands default

```
[no] aaa authorization { commands | config-commands } default { group <s0> [ { local | none | <s1> [ { local | none | <s2> [ { local | none | <s3> [ { local | none | <s4> [ { local | none | <s5> [ { local | none | <s6> [ { local | none | <s7> [ { local | none } ] ] ] ] ] ] ] ] ] ] ] ] ] ] ] | local | none }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authorization	Configure authorization methods
commands	Authorization for all exec-mode commands
config-commands	Authorization for config commands
default	Configure default methods
group	Specify server groups
s0	Server group name
s1	(Optional) Server group name
s2	(Optional) Server group name
s3	(Optional) Server group name
s4	(Optional) Server group name
s5	(Optional) Server group name
s6	(Optional) Server group name
s7	(Optional) Server group name
local	(Optional) Use local RBACL based authorization
none	(Optional) No authorization

Command Mode

- /exec/configure

aaa authorization ssh default group

```
[no] aaa authorization { ssh-publickey | ssh-certificate } default { group <s0> [ { local1 | <s1> [ { local1 | <s2> [ { local1 | <s3> [ { local1 | <s4> [ { local1 | <s5> [ { local1 | <s6> [ { local1 | <s7> [ { local1 } ] ] ] ] ] ] ] ] ] ] ] ] ] ] ] | local }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
authorization	Configure authorization methods
ssh-publickey	Configure ssh publickey
ssh-certificate	Configure ssh certificate
default	Configure default ssh methods
group	Specify server groups
<i>s0</i>	Server group name
<i>s1</i>	(Optional) Server group name
<i>s2</i>	(Optional) Server group name
<i>s3</i>	(Optional) Server group name
<i>s4</i>	(Optional) Server group name
<i>s5</i>	(Optional) Server group name
<i>s6</i>	(Optional) Server group name
<i>s7</i>	(Optional) Server group name
local	Use local username authentication
local1	(Optional) Use local username authentication

Command Mode

- /exec/configure

aaa bypass-user

[no] aaa bypass-user <s0> { [accounting] [authorization] | [authorization] [accounting] }

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
bypass-user	Configure bypass user
s0	Enter the username
accounting	(Optional) Bypass accounting
authorization	(Optional) Bypass authorization

Command Mode

- /exec/configure

aaa group server ldap

[no] aaa group server ldap <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
group	Configure aaa server group
server	Configure aaa server group
ldap	LDAP server group name
s0	LDAP server group name

Command Mode

- /exec/configure

aaa group server radius

[no] aaa group server radius <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
group	Configure aaa server group
server	Configure aaa server group
radius	RADIUS server group name
s0	RADIUS server group name

Command Mode

- /exec/configure

aaa group server tacacs

[no] aaa group server tacacs <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
group	Configure aaa server group
server	Configure aaa server group
tacacs	TACACS+ server group name
s0	TACACS+ server group name

Command Mode

- /exec/configure

aaa test-authentication

[no] aaa test-authentication

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
test-authentication	Test aaa authentication

Command Mode

- /exec/configure

aaa test-radius-authentication

[no] aaa test-radius-authentication

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
test-radius-authentication	Test aaa radius authentication

Command Mode

- /exec/configure

aaa user default-role

[no] aaa user default-role

Syntax Description

no	(Optional) Negate a command or set its defaults
aaa	Configure aaa functions
user	Remotely authenticated user
default-role	Default role assigned by aaa-admin for remote authentication

Command Mode

- /exec/configure

abort

abort

Syntax Description

abort	Exit region configuration mode, aborting changes
-------	--

Command Mode

- /exec/configure/spanning-tree/mst/configuration

abort

abort

Syntax Description

abort	Abort the current configuration session
-------	---

Command Mode

- /exec/configure

abort

abort

Syntax Description

abort	abort itd session
-------	-------------------

Command Mode

- /exec/configure/itd-session-device-group

abort

abort

Syntax Description

abort	abort plb session
-------	-------------------

Command Mode

- /exec/configure/plb-session-device-group

absolute-timeout

{ absolute-timeout <i0> | no absolute-timeout [<i0>] }

Syntax Description

no	Negate a command or set its defaults
absolute-timeout	Configure absolute timeout
<i>i0</i>	Enter timeout in minutes, 0 to disable

Command Mode

- /exec/configure/line

absolute start

```
{ [ <seqno> ] | no } absolute { start <stime> <sday> <smonth> <syear> [ end <etime> <eday> <emonth> <eyear> ] | end <etime> <eday> <emonth> <eyear> }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
absolute	Absolute time and date
start	Starting time and date
<i>stime</i>	Starting time
<i>sday</i>	Day of the month
<i>smonth</i>	Month
<i>syear</i>	Year
end	(Optional) Ending time and date
<i>etime</i>	(Optional) Ending time
<i>eday</i>	(Optional) Day of the month
<i>emonth</i>	(Optional) Month
<i>eyear</i>	(Optional) Year

Command Mode

- /exec/configure/timerange

accept-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

```
{ { accept-lifetime [ local ] <stime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <sday> <syear> { duration <dsec> | infinite | <etime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <eday> <eyear> } } | { no accept-lifetime [ [ local ] <stime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <sday> <syear> { duration <dsec> | infinite | <etime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <eday> <eyear> } ] } }
```

Syntax Description

no	Negate a command or set its defaults
accept-lifetime	Set accept lifetime of key
local	(Optional) Specify time in local timezone
<i>stime</i>	HH:MM:SS Time to start <0-23>:<0-59>:<0-59>
<i>etime</i>	HH:MM:SS Time to end <0-23>:<0-59>:<0-59>
month_a	
month_b	
month_c	
month_d	
month_e	
month_f	
month_g	
month_h	
month_i	
month_j	
month_k	
month_l	
<i>sday</i>	Day of the month to start

accept-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

<i>eday</i>	Day of the month to end
<i>syear</i>	Year to start
<i>eyear</i>	Year to start
duration	Set key lifetime duration
<i>dsec</i>	Duration in seconds
infinite	Never Expires

Command Mode

- /exec/configure/keychain-key

access-class

[no] access-class <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
access-class	Specify IPv4 access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/line

access-list

[no] access-list <acl-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
access-list	Configure access-list for PLB service
<i>acl-name</i>	Access-list name

Command Mode

- /exec/configure/plb

access-list

[no] access-list <acl-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
access-list	ITD access-list name
<i>acl-name</i>	ITD user ACL name

Command Mode

- /exec/configure/itd

access-list ipv6

[no] access-list ipv6 <acl-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
access-list	ITD access-list name
ipv6	ipv6 access-list
<i>acl-name</i>	ITD user ACL name

Command Mode

- /exec/configure/itd

access vlan

[no] access vlan <vlan>

Syntax Description

no	(Optional) Negate a command or set its defaults
access	access
vlan	vlan
<i>vlan</i>	Vlan

Command Mode

- /exec/configure/smartc /exec/configure/smartc

aclog match-log-level

[no] aclog match-log-level <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
aclog	Configure ACL logging
match-log-level	aclog logging level
<i>level</i>	match log level

Command Mode

- /exec/configure

action

[no] action { drop [log] | forward | redirect <intf> }

Syntax Description

no	(Optional) Negate a command or set its defaults
action	Specify the action clause
drop	Drop matched packets
log	(Optional) Log matched packets
forward	Forward matched packets
redirect	Redirect matched packets to the specified interface(s)
<i>intf</i>	Interface traffic is redirected to

Command Mode

- /exec/configure/vacli

action

[no] action <label>

Syntax Description

no	Negate a command or set its defaults
action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9

Command Mode

- /exec/configure/event-manager-applet

action cli

action <label> cli [local] <vsh_cmd>

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
cli	Configure a VSH CLI action
local	(Optional) Execute the action in the same card on which the event happens
<i>vsh_cmd</i>	Enter the vsh command

Command Mode

- /exec/configure/event-manager-applet

action counter name value op

action <label> counter name <counter-name> value <counter-value> op <op-val>

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
counter	Specify the name of the counter
name	Specify the name of the counter
<i>counter-name</i>	Name of the counter
value	Specify the value to be applied to the counter
<i>counter-value</i>	Enter an integer value or a \$ prefixed name (parameter substitution)
op	Specify the operator to be applied
<i>op-val</i>	Enter the value of the operator

Command Mode

- /exec/configure/event-manager-applet

action eem test

action <label> eem test <param>

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
eem	Event Manager command
test	Do test action
<i>param</i>	Test action parameter (dummy value)

Command Mode

- /exec/configure/event-manager-applet

action event-default

action <label> event-default

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
event-default	Do default action for the event

Command Mode

- /exec/configure/event-manager-applet

action forceshut reset-reason

```
[no] action <label2> forceshut [ { module { <module> | <mod-str> } | <s0> { <santa-cruz-range> | <santa-cruz-string> } } ] reset-reason <reset_reason_string>
```

Syntax Description

no	(Optional) Negate a command or set its defaults
action	Configure the actions to be executed
<i>label2</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
forceshut	Force the entire switch to shut down
module	(Optional) Optional. Module to be forced to shut down(optional argument)
<i>module</i>	(Optional) please enter the module number
<i>mod-str</i>	(Optional) Enter the module number (integer value) or a \$ prefixed parameter name
<i>s0</i>	(Optional) Optional. Xbar to be forced to shut down(optional argument)
<i>santa-cruz-range</i>	(Optional) please enter the xbar number
<i>santa-cruz-string</i>	(Optional) Enter the xbar number (integer value) or a \$ prefixed parameter name
reset-reason	Shut down (with reset-reason)
<i>reset_reason_string</i>	please enter reset_reason_string in quotes

Command Mode

- /exec/configure/event-manager-applet

action overbudgetshut

[no] action <label> overbudgetshut [module { <module> | <mod-str> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
overbudgetshut	Shut down the specified LCs due to power over budget
module	(Optional) Optional. Module to be force-shut(optional arg)
<i>module</i>	(Optional) please enter the module number
<i>mod-str</i>	(Optional) Enter the module number (integer value) or a \$ prefixed parameter name

Command Mode

- /exec/configure/event-manager-applet

action policy-default

action <label> policy-default

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
policy-default	Do default action(s) of the policy being overridden

Command Mode

- /exec/configure/event-manager-applet

action reload

[no] action <label> reload [module { <module> | <mod-str> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
reload	Reload the system or a specific module
module	(Optional) Reload a specific module
<i>module</i>	(Optional) please enter the module number
<i>mod-str</i>	(Optional) Enter the module number (integer value) or a \$ prefixed parameter name

Command Mode

- /exec/configure/event-manager-applet

action snmp-trap

action <label> snmp-trap [intdata1 <integer-data1>] [intdata2 <integer-data2>] [strdata <string-data>]

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
snmp-trap	Send
intdata1	(Optional) Enter
<i>integer-data1</i>	(Optional) Integer
intdata2	(Optional) Enter
<i>integer-data2</i>	(Optional) Integer
strdata	(Optional) Enter
<i>string-data</i>	(Optional) String

Command Mode

- /exec/configure/event-manager-applet

action syslog msg

action <label> syslog [priority { <prio> | <prio-str> }] msg <msg-text>

Syntax Description

action	Configure the actions to be executed
<i>label</i>	Enter the label <num1>[.<num2>] for action order num2 must be 0-9
syslog	Generate a syslog message
priority	(Optional) Priority of the syslog message
<i>prio</i>	(Optional) Enter the priority
<i>prio-str</i>	(Optional) Enter a valid \$ prefixed name, for parameter substitution
msg	Enter the message for the syslog
<i>msg-text</i>	The message text

Command Mode

- /exec/configure/event-manager-applet

additional-paths install backup

[no] additional-paths install backup

Syntax Description

no	(Optional) Negate a command or set its defaults
additional-paths	Additional paths configuration
install	Install backup path
backup	Install backup path

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6
/exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv4

additional-paths receive

[no] additional-paths receive

Syntax Description

no	(Optional) Negate a command or set its defaults
additional-paths	Additional paths configuration
receive	Additional paths Receive capability

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-ipv4-mvpn
/exec/configure/router-bgp/router-bgp-af-ipv6-mvpn /exec/configure/router-bgp/router-bgp-af-vpn4
/exec/configure/router-bgp/router-bgp-af-vpn6 /exec/configure/router-bgp/router-bgp-af-ipv4-label
/exec/configure/router-bgp/router-bgp-af-ipv6-label /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

additional-paths selection route-map

[no] additional-paths selection route-map <rmap-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
additional-paths	Additional paths configuration
selection	Additional paths selection
route-map	Route-map for additional paths selection
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-ipv4
/exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-af-ipv6-label
/exec/configure/router-bgp/router-bgp-af-ipv4-mvpn /exec/configure/router-bgp/router-bgp-af-ipv6-mvpn
/exec/configure/router-bgp/router-bgp-af-ipv4-label /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

additional-paths send

[no] additional-paths send

Syntax Description

no	(Optional) Negate a command or set its defaults
additional-paths	Additional paths configuration
send	Additional paths Send capability

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-vpn4
 /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-af-ipv6-label
 /exec/configure/router-bgp/router-bgp-af-ipv4-mvpn /exec/configure/router-bgp/router-bgp-af-ipv6-mvpn
 /exec/configure/router-bgp/router-bgp-af-ipv4-label /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

address-family ipv4

[no] address-family ipv4

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv4	Configure IPv4 address-family

Command Mode

- /exec/configure/config-sr-mpls/config-sr-mpls-conn-pfxsid

address-family ipv4 labeled-unicast

{ [no | default] } address-family ipv4 labeled-unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family for peer
ipv4	Configure IPv4 address-family
labeled-unicast	Configure labeled unicast sub-address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family ipv4 labeled-unicast

[no] address-family ipv4 labeled-unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv4	Configure IPv4 address-family
labeled-unicast	Configure labeled unicast sub-address-family

Command Mode

- /exec/configure/router-bgp

address-family ipv4 mdt

{ [no | default] } address-family ipv4 mdt

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
ipv4	Configure IPv4 address-family
mdt	Configure Multicast Distribution Tree

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family ipv4 mdt

[no] address-family ipv4 mdt

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv4	Configure IPv4 address-family
mdt	Configure Multicast Distribution Tree

Command Mode

- /exec/configure/router-bgp

address-family ipv4 mvpn

[no] address-family ipv4 mvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv4	Configure IPv4 address-family
mvpn	Configure Multicast VPN

Command Mode

- /exec/configure/router-bgp

address-family ipv4 mvpn

{ [no | default] } address-family ipv4 mvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
ipv4	Configure IPv4 address-family
mvpn	Configure Multicast VPN

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family ipv6

[no] address-family ipv6

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv6	Configure IPv6 address-family

Command Mode

- /exec/configure/config-sr-mpls/config-sr-mpls-conn-pfxsid

address-family ipv6 labeled-unicast

{ [no | default] } address-family ipv6 labeled-unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family for peer
ipv6	Configure IPv6 address-family
labeled-unicast	Configure labeled unicast sub-address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family ipv6 labeled-unicast

[no] address-family ipv6 labeled-unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv6	Configure IPv6 address-family
labeled-unicast	Configure labeled unicast sub-address-family

Command Mode

- /exec/configure/router-bgp

address-family ipv6 mvpn

{ [no | default] } address-family ipv6 mvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
ipv6	Configure IPv6 address-family
mvpn	Configure Multicast VPN

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family ipv6 mvpn

[no] address-family ipv6 mvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
ipv6	Configure IPv6 address-family
mvpn	Configure Multicast VPN

Command Mode

- /exec/configure/router-bgp

address-family l2vpn evpn

[no] address-family l2vpn evpn

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
l2vpn	Configure L2VPN address-family
evpn	Configure L2VPN EVPN address-family

Command Mode

- /exec/configure/router-bgp

address-family l2vpn evpn

{ [no | default] } address-family l2vpn evpn

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
l2vpn	Configure L2VPN address-family
evpn	Configure L2VPN EVPN address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family l2vpn vpls

{ [no | default] } address-family l2vpn vpls

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
l2vpn	Configure L2VPN address-family
vpls	Configure L2VPN VPLS address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family l2vpn vpls

[no] address-family l2vpn vpls

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
l2vpn	Configure L2VPN address-family
vpls	Configure L2VPN VPLS address-family

Command Mode

- /exec/configure/router-bgp

address-family link-state

[no] address-family link-state

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
link-state	Configure link-state address-family

Command Mode

- /exec/configure/router-bgp

address-family link-state

{ [no | default] } address-family link-state

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family
link-state	Configure link-state address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family vpnv4 unicast

[no] address-family vpnv4 unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
vpnv4	Configure IPv4 VPN address-family
unicast	Configure Unicast sub-address-family

Command Mode

- /exec/configure/router-bgp

address-family vpnv4 unicast

{ [no | default] } address-family vpnv4 unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family for peer
vpnv4	Configure IPv4 VPN address-family
unicast	Configure Unicast sub-address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address-family vpnv6 unicast

[no] address-family vpnv6 unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
address-family	Configure an address-family
vpnv6	Configure IPv6 VPN address-family
unicast	Configure Unicast sub-address-family

Command Mode

- /exec/configure/router-bgp

address-family vpnv6 unicast

{ [no | default] } address-family vpnv6 unicast

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
address-family	Configure an address-family for peer
vpnv6	Configure IPv6 VPN address-family
unicast	Configure Unicast sub-address-family

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-template-neighbor /exec/configure/router-bgp/router-bgp-prefixneighbor

address

[no] address <ipv6_addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address configuration

Command Mode

- /exec/configure/if-eth-any/vrrs

address

{ address <ip_address> | no address [<ip_address>] }

Syntax Description

no	Negate a command or set its defaults
address	Add an IP address to the vr
<i>ip_address</i>	ip address

Command Mode

- /exec/configure/if-eth-any/vrrp

address

[no] address <ip_addr> [primary]

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address
primary	(Optional) Primary Address
<i>ip_addr</i>	IPv4 Address

Command Mode

- /exec/configure/if-eth-any/vrrpv3_ipv4

address

[no] address <ipv6_addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address

Command Mode

- /exec/configure/if-eth-any/vrrpv3_ipv6

address

[no] address <ip_addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address configuration
<i>ip_addr</i>	IP Address

Command Mode

- /exec/configure/if-eth-any/vrrs

address

[no] address <start-ip> <end-ip>

Syntax Description

no	(Optional) Negate a command or set its defaults
address	Address range for the pool
<i>start-ip</i>	Start IP address
<i>end-ip</i>	End IP address

Command Mode

- /exec/configure/ipnat-pool

address port-number

address { <ipv4-addr> | <ipv6-addr> } port-number <port-number> | no address

Syntax Description

no	Negate a command or set its defaults
address	Configure IPv4 or IPv6 address
<i>ipv4-addr</i>	IPv4 address of the BMP server
port-number	Configure the port for the BMP server
<i>port-number</i>	Port number value

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

address primary

[no] address <ipv6_addr> primary

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address
primary	Primary Address

Command Mode

- /exec/configure/if-eth-any/vrrpv3_ipv6

address secondary

[no] address <ip_addr> secondary

Syntax Description

no	(Optional) Negate a command or set its defaults
address	IP Address
secondary	Secondary Address
<i>ip_addr</i>	IPv4 Address

Command Mode

- /exec/configure/if-eth-any/vrrpv3_ipv4

address secondary

```
{ address <ip_address> secondary | no address <ip_address> secondary }
```

Syntax Description

no	Negate a command or set its defaults
address	Add an IP address to the vr
<i>ip_address</i>	ip address
secondary	a virtual IP address without owner

Command Mode

- /exec/configure/if-eth-any/vrrp

adjacency-check

[no] adjacency-check

Syntax Description

no	(Optional) Negate a command or set its defaults
adjacency-check	Adjacency's protocol support consistency check

Command Mode

- /exec/configure/router-isis/router-isis-af-common

adjacency-resolve

[no] adjacency-resolve

Syntax Description

no	(Optional) Negate a command or set its defaults
adjacency-resolve	Resolve L3->L2 address for ISIS adjacency

Command Mode

- /exec/configure/router-isis

advertise-gw-ip

[no | default] advertise-gw-ip

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
advertise-gw-ip	Advertise Gateway IP in Type-5 routes to neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn

advertise-labels

```
[no] advertise-labels [ vrf { <vrf-name> | <vrf-known-name> } ] [ [ for <pfx-list> [ to <peer-pfx-list> ] ] ] [ interface <intf> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise-labels	Label advertisements
vrf	(Optional) VRF Routing/Forwarding instance information
<i>vrf-name</i>	(Optional) VPN Routing/Forwarding instance name
<i>vrf-known-name</i>	(Optional) Known VRF name
for	(Optional) Prefix list specifying controls on destination prefixes
<i>pfx-list</i>	(Optional) Name of prefix list
to	(Optional) Prefix list specifying controls on LDP peers
<i>peer-pfx-list</i>	(Optional) Name of prefix list
interface	(Optional) Advertise /32 interface address
<i>intf</i>	(Optional)

Command Mode

- /exec/configure/ldp

advertise-map exist default advertise-map

{ [no] advertise-map <adv-rmap-name> { exist-map | non-exist-map } <cond-rmap-name> } | default advertise-map

Syntax Description

no	(Optional) Negate a command or set its defaults
default	Inherit values from a peer template
advertise-map	Specify route-map for conditional advertisement
exist-map	Condition route-map to advertise only when prefix in condition exists
non-exist-map	Condition route-map to advertise only when prefix in condition does not exist
<i>adv-rmap-name</i>	Route-map name
<i>cond-rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

advertise-pip

[no] advertise-pip

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise-pip	advertise physical ip for type-5 route

Command Mode

- /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

advertise-system-mac

[no] advertise-system-mac

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise-system-mac	Advertise extra EVPN RT-2 with system MAC

Command Mode

- /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

advertise evpn multicast

[no] advertise evpn multicast

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise	Advertise L2 multicast capability
evpn	evpn
multicast	L2 multicast

Command Mode

- /exec/configure

advertise interface

[no] advertise interface <interface> [<level>]

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise	Advertise interface IP
interface	Advertise interface IP
<i>interface</i>	Interface to advertise
<i>level</i>	(Optional) IS-IS level

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv4 /exec/configure/router-isis/router-isis-af-ipv6

advertise l2vpn evpn

[no] advertise l2vpn evpn

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise	Configure advertise for this AF
l2vpn	L2VPN
evpn	EVPN

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

advertise local-labeled-route

[no | default] advertise local-labeled-route

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
advertise	Advertise to peer
local-labeled-route	Advertise a route with local label to peer

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af

advertise virtual-rmac

[no] advertise virtual-rmac

Syntax Description

no	(Optional) Negate a command or set its defaults
advertise	Reachability advertisement
virtual-rmac	Advertise virtual RMAC capability

Command Mode

- /exec/configure/if-nve

advertisement-interval

[no] advertisement-interval <adv-sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
advertisement-interval	Minimum interval between sending BGP routing updates
<i>adv-sec</i>	Time in seconds

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6

advertisement-interval

{ advertisement-interval <interval_time> | no advertisement-interval [<interval_time>] }

Syntax Description

no	Negate a command or set its defaults
advertisement-interval	Set the time interval between advertisement
<i>interval_time</i>	Time interval (in seconds) between advertisements

Command Mode

- /exec/configure/if-eth-any/vrrp

afd queue-desired

[no] afd queue-desired <q-desired> { bytes | kbytes | mbytes } [ecn]

Syntax Description

no	(Optional) Negate a command or set its defaults
afd	Configure AFD parameters
queue-desired	Specify Queue Desired for AFD
bytes	Bytes
kbytes	Kilo bytes
mbytes	Mega bytes
ecn	(Optional) ECN

Command Mode

- /exec/configure/policy-map/type/queuing/class

affinity-group

```
{ affinity-group <affinity_group_id> } | { { no | default } affinity-group [ <affinity_group_id> ] }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
affinity-group	Configure an affinity group
<i>affinity_group_id</i>	Affinity Group ID

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

affinity-group activate

affinity-group activate <affinity_group_id> | no affinity-group activate [<affinity_group_id>]

Syntax Description

no	Negate a command or set its defaults
affinity-group	Configure an affinity group
activate	Activate the affinity group
<i>affinity_group_id</i>	AFFINITY Group ID

Command Mode

- /exec/configure/router-bgp

affinity

[no] affinity | affinity <hex_value> [mask <mask_value>]

Syntax Description

no	Negate a command or set its defaults
affinity	Specify attribute flags for links comprising LSP
<i>hex_value</i>	affinity value
mask	(Optional) mask on desired link attributes
<i>mask_value</i>	(Optional) affinity mask value

Command Mode

- /exec/configure/te/lsp-attr

affinity

[no] affinity | affinity <value> [mask <mask-value>]

Syntax Description

no	Negate a command or set its defaults
affinity	desired link attributes for links comprising tunnel
<i>value</i>	affinity value
mask	(Optional) mask on desired link attributes
<i>mask-value</i>	(Optional) affinity mask value

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

age

{ [no] age <age> | no age }

Syntax Description

age	Provide the age value for this POSTCARD flow-profile
<i>age</i>	flow-profile age (seconds). Default is 30.

Command Mode

- /exec/configure/config-postcard-flow-prof

age

{ [no] age <age> | no age }

Syntax Description

age	Provide the age value for this INT flow-profile
<i>age</i>	flow-profile age (seconds). Default is 30.

Command Mode

- /exec/configure/config-int-flow-prof

aggregate-address

[no] aggregate-address { <ip-addr> <ip-mask> | <ip-prefix> } [as-set | summary-only | suppress-map <suppress-rmap> | advertise-map <advertise-rmap> | attribute-map <attribute-rmap>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
aggregate-address	Configure BGP aggregate prefixes
<i>ip-addr</i>	Aggregate address
<i>ip-mask</i>	Aggregate mask
<i>ip-prefix</i>	Aggregate prefix
summary-only	(Optional) Don't advertise more specifics
as-set	(Optional) Generate AS-SET information
suppress-map	(Optional) Conditionally filter more specific routes
advertise-map	(Optional) Select attribute information from specific routes
attribute-map	(Optional) Set attribute information of aggregate
<i>advertise-rmap</i>	(Optional) Route-map name
<i>suppress-rmap</i>	(Optional) Route-map name
<i>attribute-rmap</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv4

aggregate-address

[no] aggregate-address <ipv6-prefix> [as-set | summary-only | suppress-map <suppress-rmap> | advertise-map <advertise-rmap> | attribute-map <attribute-rmap>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
aggregate-address	Configure BGP aggregate IPv6 prefixes
as-set	(Optional) Generate AS-SET information
summary-only	(Optional) Don't advertise more specifics
suppress-map	(Optional) Conditionally filter more specific routes
advertise-map	(Optional) Select attribute information from specific routes
attribute-map	(Optional) Set attribute information of aggregate
<i>advertise-rmap</i>	(Optional) Route-map name
<i>suppress-rmap</i>	(Optional) Route-map name
<i>attribute-rmap</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

alert-group user-def-cmd

[no] alert-group { Configuration | Diagnostic | Environmental | Inventory | License | Linecard-Hardware | Supervisor-Hardware | Syslog-group-port | System | Test } user-def-cmd <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
alert-group	alert group
user-def-cmd	configure a cli command for an alert group
s0	A valid CLI command
Environmental	Power,fan,temperature related events
Inventory	Inventory status events
License	Events related to licensing
Linecard-Hardware	Linecard related events
Supervisor-Hardware	Supervisor related events
Syslog-group-port	Events related to syslog messages filed by port manager
System	Software related events
Test	User generated test events
Configuration	Events related to Configuration
Diagnostic	Events related to Diagnostic

Command Mode

- /exec/configure/callhome

allocate-label all

[no] allocate-label { all | route-map <map-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
allocate-label	Configure label allocation for this AF
all	Allocate labels for all routes
route-map	Allocate labels for selected routes
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-af-ipv4

allocate-label option-b

[no] allocate-label option-b

Syntax Description

no	(Optional) Negate a command or set its defaults
allocate-label	Allow allocation of labels
option-b	Allow allocation of option B labels

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-af-ipv6

allocate1 interface2

```
allocate1 interface2 { <interface-id> [ force ] | unallocated-interfaces }
```

Syntax Description

allocate1	Assign interfaces to vdc
interface2	Assign interface range to vdc
<i>interface-id</i>	Assign interface range to vdc
force	(Optional) force
unallocated-interfaces	Best-effort trying to move all interfaces in the unallocated pool into this vdc

Command Mode

- /exec/configure/vdc

allocate2 fcoe-vlan-range

```
{ allocate2 fcoe-vlan-range [ <vlan_range> ] [ from vdc <vdc_names> ] } | { no allocate2 fcoe-vlan-range
[ <vlan_range> | { from vdc <vdc_names> } ] }
```

Syntax Description

no	Negate a command or set its defaults
allocate2	Assign interfaces to vdc
fcoe-vlan-range	vlan reserved for FCoE
<i>vlan_range</i>	(Optional) vlans reserved for FCoE
from	(Optional) which vdc will be sharing ports with the FCoE vdc
vdc	(Optional) which vdc will be sharing ports with the FCoE vdc
<i>vdc_names</i>	(Optional) which vdc will be sharing porst with the FCoE vdc

Command Mode

- /exec/configure/vdc

allocate3 shared interface3

[no] allocate3 shared interface3 <sinterface-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
allocate3	Assign interfaces to vdc
interface3	Assign interface range to vdc
<i>sinterface-id</i>	Assign interface range to vdc
shared	Shared this port using the reserved FCoE vlans

Command Mode

- /exec/configure/vdc

allow-vni-in-ethertag

[no] allow-vni-in-ethertag

Syntax Description

no	(Optional) Negate a command or set its defaults
allow-vni-in-ethertag	Allow VNI in Ethernet Tag field in EVPN route

Command Mode

- /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

allow feature-set

[no] allow feature-set <fs>

Syntax Description

no	(Optional) Negate a command or set its defaults
allow	Used to change permissions inside a vdc
feature-set	Change which feature-sets the user is able to enable inside the vdc
<i>fs</i>	installed feature-sets

Command Mode

- /exec/configure/vdc

allowas-in

[no | default] allowas-in [<allowas-in-cnt>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
allowas-in	Accept as-path with my AS present in it
<i>allowas-in-cnt</i>	(Optional) Number of occurrences of AS number, default is 3

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv4
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

allowas-in

[no | default] allowas-in [<allowas-in-cnt>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
allowas-in	Accept as-path with my AS present in it
<i>allowas-in-cnt</i>	(Optional) Number of occurrences of AS number, default is 3

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

allowed-locators

{ [no] allowed-locators { <rloc> | <rloc6> } + }

Syntax Description

no	(Optional) Negate a command or set its defaults
allowed-locators	List of locators from LISP site
<i>rloc</i>	IPv4 locator allowed in registered locator-set

Command Mode

- /exec/configure/lisp-site /exec/configure/vrf/lisp-site

allowed-vlans

allowed-vlans { <allow-vlans> | add <add-vlans> | except <except-vlans> | remove <remove-vlans> | all }

Syntax Description

allowed-vlans	Set list of allowed vlans that can be used for interface configuration
<i>allow-vlans</i>	VLAN ID 1-4094 or range(s) like: 1-5, 10 or 2-5,7-19
add	add VLANs to the current list
<i>add-vlans</i>	VLAN ID 1-4094 or range(s) like: 1-5, 10 or 2-5,7-19
except	all VLANs except the following
<i>except-vlans</i>	VLAN ID 1-4094 or range(s) like: 1-5, 10 or 2-5,7-19
remove	remove VLANs from the current list
<i>remove-vlans</i>	VLAN ID 1-4094 or range(s) like: 1-5, 10 or 2-5,7-19
all	all VLANs

Command Mode

- /exec/configure/vmt-conn

amt flush-routes

[no] amt flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
amt	AMT global configuration commands
flush-routes	Remove routes when restarting AMT

Command Mode

- /exec/configure /exec/configure/vrf

amt pseudo-interface

```
{ { amt pseudo-interface <interface> } | { no amt pseudo-interface [ <interface> ] } }
```

Syntax Description

no	Negate a command or set its defaults
amt	AMT global configuration commands
pseudo-interface	Tunnel to relay for forwarding IGMP/MLD messages
<i>interface</i>	Interface name to be used for AMT pseudo interface

Command Mode

- /exec/configure /exec/configure/vrf

analytics cluster

[no] analytics cluster <clustername> [vrf <vrfName>] [srcIf <src_intf>]

Syntax Description

no	(Optional) Negate a command or set its defaults
analytics	Feature Analytics
cluster	Analytics cluster
<i>clustername</i>	Cluster name
vrf	(Optional) VRF Name
<i>vrfName</i>	(Optional) VRF name
srcIf	(Optional) Source Interface
<i>src_intf</i>	(Optional) Source Interface

Command Mode

- /exec/configure

anonymous-id

{ [no] anonymous-id <id> }

Syntax Description

anonymous-id	anonymous identity associated with this profile
<i>id</i>	identity name

Command Mode

- /exec/configure/dot1x-cred

append-after next

```
append-after <index> { next-address [ loose | strict ] <ipaddr> | exclude-address <ipaddr> }
```

Syntax Description

append-after	Append additional entry after specified index
<i>index</i>	Previous index number
next-address	Specify the next address in the path
loose	(Optional) Target address is loose
strict	(Optional) Target address is strict
exclude-address	Exclude an address from subsequent partial path segments
<i>ipaddr</i>	Enter IP address (A.B.C.D)

Command Mode

- /exec/configure/te/expl-path

apply profile

```
[no] apply profile { <all_conf_profile_name> } [ include-profile <include-profile> ] [ { param-instance <plistinst> | include-instance <plistinst> } + ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
apply	Apply a config-profile
profile	Apply a config-profile
<i>all_conf_profile_name</i>	Enter the name of the profile
param-instance	(Optional) Enter the name of the param-instance
<i>plistinst</i>	(Optional) Enter the name of the instance
include-profile	(Optional) Enter the name of the include profile
<i>include-profile</i>	(Optional) Enter the name of the include profile
include-instance	(Optional) Enter the param-instance corresponding to the first included profile
<i>plistinst</i>	(Optional) Enter the name of the include instance

Command Mode

- /exec/configure

area authentication

[no] area <area-id-ip> authentication [message-digest]

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
authentication	Enable authentication for the area
message-digest	(Optional) Use message-digest authentication

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area authentication

```
area <area-id-ip> authentication { disable | ipsec spi <spi_id> { md5 <akey> | sha1 <akey> } } | no area
<area-id-ip> authentication { disable | ipsec spi <spi_id> }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
authentication	Enable Authentication
disable	Disable Authentication
ipsec	IPSec
spi	Security Parameter Index
<i>spi_id</i>	SPI Value
md5	Use the MD5 algorithm
<i>akey</i>	Authentication Key
sha1	Use the SHA1 algorithm
<i>akey</i>	Authentication Key

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

area default-cost

```
{ { area <area-id-ip> default-cost <cost> } | { no area <area-id-ip> default-cost [ <cost> ] } }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
default-cost	Specify default-cost for default summary LSA
<i>cost</i>	Cost value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area default-cost

```
{ { area <area-id-ip> default-cost <cost> } | { no area <area-id-ip> default-cost [ <cost> ] } }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
default-cost	Specify default-cost for default inter-area-prefix LSA
<i>cost</i>	Cost value

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

area filter-list route-map in

```
{ area <area-id-ip> filter-list route-map { <policy-name> | <rtr_pol_name> } { in | out } } | { no area
<area-id-ip> filter-list route-map { <policy-name> | <rtr_pol_name> } [ in | out ] }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
filter-list	Filter prefixes between OSPF areas
route-map	Name of filter policy
<i>policy-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy
in	Filter networks sent to this area
out	Filter networks sent from this area

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area filter-list route-map in

```
{ area <area-id-ip> filter-list route-map { <policy-name> | <rtr_pol_name> } { in | out } } | { no area
<area-id-ip> filter-list route-map { <policy-name> | <rtr_pol_name> } [ in | out ] }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
filter-list	Filter prefixes between OSPF areas
route-map	Name of filter policy
<i>policy-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy
in	Filter networks sent to this area
out	Filter networks sent from this area

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

area nssa

[no] area <area-id-ip> nssa { [no-summary] [no-redistribution] [default-information-originate [route-map <policy-name>]] } +

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
nssa	Configure area as NSSA
no-summary	(Optional) Do not send summary LSAs into NSSA area
no-redistribution	(Optional) Do not send redistributed LSAs into NSSA area
default-information-originate	(Optional) Originate Type-7 default LSA into NSSA area
route-map	(Optional) Policy to control distribution of default route
<i>policy-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area nssa

[no] area <area-id-ip> nssa { [no-summary] [no-redistribution] [default-information-originate [route-map <policy-name>]] } +

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
nssa	Configure area as NSSA
no-summary	(Optional) Do not send summary LSAs into NSSA area
no-redistribution	(Optional) Do not send redistributed LSAs into NSSA area
default-information-originate	(Optional) Originate Type-7 default LSA into NSSA area
route-map	(Optional) Policy to control distribution of default route
<i>policy-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

area nssa translate type7 always never supress-fa

```
{ area <area-id-ip> nssa translate type7 { always [ supress-fa ] | never | supress-fa } } | { no area <area-id-ip>
nssa translate type7 [ always [ supress-fa ] | never | supress-fa ] }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
nssa	Configure area as NSSA
translate	Translate LSA
type7	From Type 7 to Type 5
always	Always translate LSAs
never	Never translate LSAs
supress-fa	(Optional) Supress forwarding address in translated LSAs

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area nssa translate type7 always never supress-fa

```
{ area <area-id-ip> nssa translate type7 { always [ supress-fa ] | never | supress-fa } } | { no area <area-id-ip>
nssa translate type7 [ always [ supress-fa ] | never | supress-fa ] }
```

Syntax Description

no	Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
nssa	Configure area as NSSA
translate	Translate LSA
type7	From NSSA-external (Type 7) to AS-external (Type 5)
always	Always translate LSAs
never	Never translate LSAs
supress-fa	(Optional) Supress forwarding address in translated LSAs

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

area range

```
[no] area <area-id-ip> range { <ip-dest> <ip-mask> | <ip-prefix> } { [ not-advertise ] [ cost <conf-cost> ] }
```

+

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
range	Configure an address range for an area
<i>ip-dest</i>	IP prefix format: i.i.i.i
<i>ip-mask</i>	IP network mask format: m.m.m.m
<i>ip-prefix</i>	IP prefix format: x.x.x.x/ml
not-advertise	(Optional) Suppress advertising the specified range
cost	(Optional) Cost to use for range
<i>conf-cost</i>	(Optional) Cost value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area range

[no] area <area-id-ip> range <ipv6-prefix> { [not-advertise] [cost <conf-cost>] } +

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
range	Configure an address range for an area
not-advertise	(Optional) Suppress advertising the specified range
cost	(Optional) Cost to use for range
<i>conf-cost</i>	(Optional) Cost value

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

area sham-link

[no] area <area-id-ip> sham-link <source-address> <dest-address>

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
sham-link	Define a sham link and its parameters
<i>source-address</i>	IP addr associated with sham-link source
<i>dest-address</i>	IP addr associated with sham-link destination

Command Mode

- /exec/configure/router-ospf/vrf

area stub

[no] area <area-id-ip> stub [no-summary]

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
stub	Configure area as a stub
no-summary	(Optional) Prevent ABR from sending summary LSAs into stub area

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

area stub

[no] area <area-id-ip> stub [no-summary]

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
stub	Configure area as a stub
no-summary	(Optional) Prevent ABR from sending summary LSAs into stub area

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

area virtual-link

[no] area <area-id-ip> virtual-link <routerid>

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
virtual-link	Define a virtual link and its parameters
<i>routerid</i>	Router ID associated with virtual link neighbor

Command Mode

- /exec/configure/router-ospf/vrf

area virtual-link

[no] area <area-id-ip> virtual-link <routerid>

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
virtual-link	Define a virtual link and its parameters
<i>routerid</i>	Router ID associated with virtual link neighbor

Command Mode

- /exec/configure/router-ospf3

area virtual-link

[no] area <area-id-ip> virtual-link <routerid>

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
virtual-link	Define a virtual link and its parameters
<i>routerid</i>	Router ID associated with virtual link neighbor

Command Mode

- /exec/configure/router-ospf3/vrf

area virtual-link

[no] area <area-id-ip> virtual-link <routerid>

Syntax Description

no	(Optional) Negate a command or set its defaults
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
virtual-link	Define a virtual link and its parameters
<i>routerid</i>	Router ID associated with virtual link neighbor

Command Mode

- /exec/configure/router-ospf

arp access-list

[no] arp access-list <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
arp	ARP access-list configuration commands
access-list	Configure access list
<i>name</i>	List name

Command Mode

- /exec/configure

as-format asdot

as-format asdot | no as-format

Syntax Description

no	Negate a command or set its defaults
as-format	Configure the router's Autonomous system number (ASN) notation
asdot	Specifies the Autonomous system number (ASN) notation to asdot format

Command Mode

- /exec/configure

as-override

[no | default] as-override

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
as-override	Override matching AS-number while sending update

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv4
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn

assign interface shared

```
{ assign interface { <sdn-eth-intf-list> | <sdn-pc-intf-list> } shared | no assign interface { <sdn-eth-intf-list> | <sdn-pc-intf-list> } }
```

Syntax Description

no	Negate a command or set its defaults
assign	Assign resource
interface	Resource of interface type
<i>sdn-eth-intf-list</i>	List of Interfaces
<i>sdn-pc-intf-list</i>	List of Interfaces
shared	Share interface with controller

Command Mode

- /exec/configure/controller-type

assign vlan dedicated

{ assign vlan <sdn-id> dedicated | no assign vlan <sdn-id> }

Syntax Description

no	Negate a command or set its defaults
assign	Assign reservation
vlan	Controller VLANs
<i>sdn-id</i>	vlan ID 2-4093 or range(s): 1-5, 10 or 2-5,7-19
dedicated	Dedicated VLANs

Command Mode

- /exec/configure/controller-type

assign vrf prefix number dedicated

{ assign vrf prefix <prefix-name> number <number-of-vrfs> dedicated | no assign vrf }

Syntax Description

no	Negate a command or set its defaults
assign	Assign reservation
vrf	VRFs
prefix	VRF prefix
<i>prefix-name</i>	String description of the prefix
number	Number of VRFs
<i>number-of-vrfs</i>	VRF ID range from 1 to 4095
dedicated	Dedicated VRFs

Command Mode

- /exec/configure/controller-type

attach console module

attach console module <module>

Syntax Description

attach	Connect to a specific linecard
console	Connect to the console
module	Connect to the module console
<i>module</i>	Enter module number

Command Mode

- /exec

attach module

attach module <module>

Syntax Description

attach	Connect to a specific linecard
module	Module number of the linecard
<i>module</i>	Enter module number

Command Mode

- /exec

attach module node

attach module <module> node <i0>

Syntax Description

attach	Connect to a specific linecard
module	Module number of the linecard
<i>module</i>	Enter module number
node	Avanti node number on the linecard
<i>i0</i>	

Command Mode

- /exec

attach module port

```
attach module <module> port <i0>
```

Syntax Description

attach	Connect to a specific linecard
module	Module number of the linecard
<i>module</i>	Enter module number
port	Port number on the linecard
<i>i0</i>	

Command Mode

- /exec

auth-mechanism plain

[no] auth-mechanism { plain }

Syntax Description

no	(Optional) Negate a command or set its defaults
auth-mechanism	Set the authentication mechanism
plain	Set the authentication mechanism as plain(default)

Command Mode

- /exec/configure/ldap

authentication-check

[no] authentication-check

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication-check	Check authentication on received LSP/CSNP/PSNP's

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

authentication-check

[no] authentication-check

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication-check	Check authentication on received LSP/CSNP/PSNP's

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

authentication-check level-1

[no] authentication-check level-1

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication-check	Check authentication on received LSP/CSNP/PSNP's
level-1	Specify authentication check for level-1 LSP, CSNP and PSNP

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

authentication-check level-2

[no] authentication-check level-2

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication-check	Check authentication on received LSP/CSNP/PSNP's
level-2	Specify authentication check for level-2 LSP, CSNP and PSNP

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

authentication-key

{ [no] authentication-key <key> }

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication-key	Authentication key used by LISP site
<i>key</i>	SHA-1 password

Command Mode

- /exec/configure/lisp-site /exec/configure/vrf/lisp-site

authentication-key

{ { authentication-key <key> } | { no authentication-key [<key>] } }

Syntax Description

no	Negate a command or set its defaults
authentication-key	Configure the authentication key for the virtual-link
<i>key</i>	Authentication key

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

authentication-key

```
{ { authentication-key <key> } | { no authentication-key [ <key> ] } }
```

Syntax Description

no	Negate a command or set its defaults
authentication-key	Configure the authentication key for the sham-link
<i>key</i>	Authentication key

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

authentication-type cleartext

```
{ authentication-type { cleartext | md5 } | no authentication-type [ { cleartext | md5 } ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication-type	Set authentication type
cleartext	Cleartext
md5	HMAC-MD5

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

authentication-type cleartext

```
{ authentication-type { cleartext | md5 } <level> | no authentication-type [ { cleartext | md5 } ] <level> }
```

Syntax Description

no	Negate a command or set its defaults
authentication-type	Set authentication type
cleartext	Cleartext
md5	HMAC-MD5
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

authentication-type cleartext

```
{ authentication-type { cleartext | md5 } | no authentication-type [ { cleartext | md5 } ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication-type	Set authentication type
cleartext	Cleartext
md5	HMAC-MD5

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

authentication

authentication { disable | ipsec spi <spi_id> { md5 <akey> | sha1 <akey> } } | no authentication { disable | ipsec spi <spi_id> }

Syntax Description

no	Negate a command or set its defaults
authentication	Enable Authentication
disable	Disable Authentication
ipsec	IPSec
spi	Security Parameter Index
<i>spi_id</i>	SPI Value
md5	Use the MD5 algorithm
<i>akey</i>	Authentication Key
sha1	Use the SHA1 algorithm
<i>akey</i>	Authentication Key

Command Mode

- /exec/configure/router-ospf3/router-ospf3-vlink /exec/configure/router-ospf3/vrf/router-ospf3-vlink

authentication

```
authentication { [ text ] <secret> | md5 { key-chain <chain-name> | key-string [ 0 | 7 ] <key-name> [
compatibility ] [ timeout <sec> ] } } | no authentication
```

Syntax Description

no	Negate a command or set its defaults
authentication	Authentication
text	(Optional) Plain text authentication
<i>secret</i>	Plain text authentication string
md5	Use MD5 authentication
key-chain	Set key chain
<i>chain-name</i>	Name of key-chain
key-string	Set key string
0	(Optional) Specifies an UNENCRYPTED key string will follow
7	(Optional) Specifies a HIDDEN key string will follow
<i>key-name</i>	Key string (64 chars max)
compatibility	(Optional) Operate in compatibility mode for MD5 type-7 authentication
timeout	(Optional) Set timeout
<i>sec</i>	(Optional) (0-32767)Timeout until only accepting new key (seconds)

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

authentication

authentication { ipsec spi <spi_id> { md5 <akey> | sha1 <akey> } } | no authentication ipsec spi <spi_id>

Syntax Description

no	Negate a command or set its defaults
authentication	Enable Authentication
ipsec	IPSec
spi	Security Parameter Index
<i>spi_id</i>	SPI Value
md5	Use the MD5 algorithm
<i>akey</i>	Authentication Key
sha1	Use the SHA1 algorithm
<i>akey</i>	Authentication Key

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

authentication

[no] authentication { { key-chain <chain> } | { mode md5 } }

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication	Configures EIGRP authentication subcommands
key-chain	key-chain
<i>chain</i>	name of key-chain
mode	mode
md5	Keyed message digest

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

authentication

[no] authentication [message-digest | null]

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication	Authentication on the vlink
message-digest	(Optional) Use message-digest authentication
null	(Optional) Use null(disable) authentication

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

authentication

[no] authentication [message-digest | null]

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication	Authentication on the slink
message-digest	(Optional) Use message-digest authentication
null	(Optional) Use null(disable) authentication

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

authentication bind

```
[no] authentication { bind-first [ append-with-basedn <s1> ] | compare [ password-attribute <s0> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
authentication	Set the authentication method
bind-first	Set the authentication method to bind-first
append-with-basedn	(Optional) Change the default value (cn=\$userid)
<i>s1</i>	(Optional) append with dn value
compare	Change the default attribute
password-attribute	(Optional) Change the default password attribute (userPassword)
<i>s0</i>	(Optional) password attribute

Command Mode

- /exec/configure/ldap

authentication challenge

[no] authentication [neighbor <nbr>] challenge

Syntax Description

authentication	Configure RSVP neighbor cryptographic authentication
neighbor	(Optional) Configure RSVP neighbor
<i>nbr</i>	(Optional) RSVP Neighbor address
challenge	Perform challenge/response handshake with new RSVP neighbors

Command Mode

- /exec/configure/ip-rsvp

authentication key-chain

authentication [neighbor <nbr>] key-chain <key-chain-name> | no authentication [neighbor <nbr>] key-chain

Syntax Description

authentication	Configure RSVP neighbor cryptographic authentication
neighbor	(Optional) Configure RSVP neighbor
<i>nbr</i>	(Optional) RSVP Neighbor address
key-chain	Authentication password key-chain
<i>key-chain-name</i>	Key-chain name

Command Mode

- /exec/configure/ip-rsvp

authentication key-chain

```
{ authentication key-chain <auth-keychain> <level> | no authentication key-chain [ <auth-keychain> ] <level>
}
```

Syntax Description

no	Negate a command or set its defaults
authentication	Set authentication keychain string
key-chain	Set authentication keychain string
<i>auth-keychain</i>	authentication keychain
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

authentication key-chain

```
{ authentication key-chain <keychain> } | { no authentication key-chain [ <keychain> ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication	Authentication on the vlink
key-chain	Authentication password key-chain
<i>keychain</i>	Key-chain name

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

authentication key-chain

```
{ authentication key-chain <keychain> } | { no authentication key-chain [ <keychain> ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication	Authentication on the slink
key-chain	Authentication password key-chain
<i>keychain</i>	Key-chain name

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

authentication key-chain

```
{ authentication key-chain <auth-keychain> | no authentication key-chain [ <auth-keychain> ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication	Set authentication keychain string
key-chain	Set authentication keychain string
<i>auth-keychain</i>	authentication keychain

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

authentication key-chain

```
{ authentication key-chain <auth-keychain> | no authentication key-chain [ <auth-keychain> ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication	Set authentication keychain string
key-chain	Set authentication keychain string
<i>auth-keychain</i>	authentication keychain

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

authentication lifetime

[no] authentication [neighbor <nbr>] lifetime <time>

Syntax Description

authentication	Configure RSVP neighbor cryptographic authentication
neighbor	(Optional) Configure RSVP neighbor
<i>nbr</i>	(Optional) RSVP Neighbor address
lifetime	Maximum lifetime of neighbor authentication state
<i>time</i>	Lifetime value(in seconds)

Command Mode

- /exec/configure/ip-rsvp

authentication text

```
{ authentication text <authentication_pwd> | no authentication [ text <authentication_pwd> ] }
```

Syntax Description

no	Negate a command or set its defaults
authentication	Select authentication method
text	Set the authentication password (8 char max)
<i>authentication_pwd</i>	

Command Mode

- /exec/configure/if-eth-any/vrrp

authentication type md5

[no] authentication [neighbor <nbr>] type { md5 | sha-1 }

Syntax Description

authentication	Configure RSVP neighbor cryptographic authentication
neighbor	(Optional) Configure RSVP neighbor
<i>nbr</i>	(Optional) RSVP Neighbor address
type	Type of authentication algorithm
md5	RSA Message Digest 5 hash algorithm (default)
sha-1	NIST Secure Hash Algorithm 1

Command Mode

- /exec/configure/ip-rsvp

authentication window-size

[no] authentication [neighbor <nbr>] window-size <value>

Syntax Description

authentication	Configure RSVP neighbor cryptographic authentication
neighbor	(Optional) Configure RSVP neighbor
<i>nbr</i>	(Optional) RSVP Neighbor address
window-size	Receive window size for authenticated messages
<i>value</i>	Maximum number of messages allowed in receive window

Command Mode

- /exec/configure/ip-rsvp

auto-bw

[no] auto-bw | auto-bw [{ [collect-bw | frequency <sec>] + } | { [frequency <sec> | min-bw <min-kbps> | max-bw <max-kbps>] + }]

Syntax Description

no	Negate a command or set its defaults
auto-bw	Specify mpls tunnel should automatically change bw
collect-bw	(Optional) Just collect Bandwidth info on this tunnel
frequency	(Optional) Frequency to change tunnel BW
<i>sec</i>	(Optional) seconds between applying auto-bw
max-bw	(Optional) Set the Maximum Bandwidth for auto-bw on this tunnel
<i>max-kbps</i>	(Optional) Maximum kb/s that tunnel can be auto set to
min-bw	(Optional) Set the Minimum Bandwidth for auto-bw on this tunnel
<i>min-kbps</i>	(Optional) Min kb/s that tunnel can be auto set to

Command Mode

- /exec/configure/if-te

auto-bw

[no] auto-bw | auto-bw [{ [collect-bw | frequency <sec>] + } | { [frequency <sec> | min-bw <min-kbps> | max-bw <max-kbps>] + }]

Syntax Description

no	Negate a command or set its defaults
auto-bw	Specify automatic bandwidth configuration
collect-bw	(Optional) Just collect bandwidth info
frequency	(Optional) frequency to change LSP bandwidth
<i>sec</i>	(Optional) seconds between applying auto-bw
max-bw	(Optional) Set the maximum bandwidth for auto-bw
<i>max-kbps</i>	(Optional) Maximum bandwidth to apply (kbps)
min-bw	(Optional) Set the minimum bandwidth for auto-bw
<i>min-kbps</i>	(Optional) Minimum bandwidth to apply (kbps)

Command Mode

- /exec/configure/te/lsp-attr

auto-bw timers frequency

[no] auto-bw timers { frequency } | auto-bw timers { frequency <sec> }

Syntax Description

no	Negate a command or set its defaults
auto-bw	auto-bw parameters
timers	Enable auto-bw timers
frequency	Interval between auto-bw data collection
<i>sec</i>	Seconds between auto-bw data collection

Command Mode

- /exec/configure/te

auto-cost reference-bandwidth

auto-cost reference-bandwidth { <ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps } | no auto-cost
reference-bandwidth [<ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps]

Syntax Description

no	Negate a command or set its defaults
auto-cost	Calculate OSPF cost according to bandwidth
reference-bandwidth	Reference bandwidth used to assign OSPF cost
Mbps	(Optional) Specify rate in Mbps
Gbps	Specify rate in Gbps
<i>ref-bw-mbps</i>	Rate in Mbps (bandwidth) (Default)
<i>ref-bw-gbps</i>	Rate in Gbps (bandwidth)

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

auto-cost reference-bandwidth

auto-cost reference-bandwidth { <ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps } | no auto-cost reference-bandwidth [<ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps]

Syntax Description

no	Negate a command or set its defaults
auto-cost	Calculate OSPFv3 cost according to bandwidth
reference-bandwidth	Reference bandwidth used to assign OSPFv3 cost
Mbps	(Optional) Specify rate in Mbps
Gbps	Specify rate in Gbps
<i>ref-bw-mbps</i>	Rate in Mbps (bandwidth) (Default)
<i>ref-bw-gbps</i>	Rate in Gbps (bandwidth)

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

auto-recovery

auto-recovery [reload-delay <time-out>] | no auto-recovery [reload-delay <time-out>]

Syntax Description

no	Negate a command or set its defaults
auto-recovery	vPC settings to enable auto recovery if peer is presumed non-operational
reload-delay	(Optional) Duration to wait before assuming peer dead and restoring vpcs
<i>time-out</i>	(Optional) Time-out for restoring vPC links (in seconds)

Command Mode

- /exec/configure/vpc-domain

auto-remap-replication-servers

[no] auto-remap-replication-servers

Syntax Description

no	(Optional) Negate a command or set its defaults
auto-remap-replication-servers	Automatically re-map replication servers on every replication server add

Command Mode

- /exec/configure/if-nve

autonomous-system

{ { autonomous-system <local-as> } | { no autonomous-system [<local-as>] } }

Syntax Description

no	Negate a command or set its defaults
autonomous-system	Specify AS number for Address Family
<i>local-as</i>	Local AS number

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

autoroute announce

[no] autoroute announce

Syntax Description

no	(Optional) Negate a command or set its defaults
autoroute	parameters for IGP routing over tunnel
announce	announce tunnel to IGP

Command Mode

- /exec/configure/if-te

autoroute metric

[no] autoroute metric | autoroute metric { <value> | relative <rel-value> }

Syntax Description

no	Negate a command or set its defaults
autoroute	parameters for IGP routing over tunnel
metric	Specify mpls tunnel metric
<i>value</i>	Set tunnel metric for autoroutes
relative	Adjust tunnel metric for autoroutes relative to IGP
<i>rel-value</i>	Relative metric value

Command Mode

- /exec/configure/if-te

autostate

[no] autostate

Syntax Description

no	(Optional) Negate a command or set its defaults
autostate	Enable or disable autostate for interface-vlan

Command Mode

- /exec/configure/if-vlan

autovlan enable

[no] autovlan enable

Syntax Description

no	(Optional) Negate a command or set its defaults
autovlan	Automatic creation/deletion of VLANs
enable	Enable auto creation/deletion of VLANs

Command Mode

- /exec/configure/vmt-conn

awk

| awk <expr>

Syntax Description

	Pipe command output to filter
awk	Mini AWK
<i>expr</i>	Edition command (script)

Command Mode

- /output



B Commands

- [backoff](#), on page 210
- [backup-bw](#), on page 211
- [bandwidth](#), on page 212
- [bandwidth](#), on page 213
- [bandwidth](#), on page 214
- [bandwidth](#), on page 215
- [bandwidth](#), on page 216
- [bandwidth](#), on page 217
- [bandwidth](#), on page 218
- [bandwidth](#), on page 219
- [bandwidth](#), on page 220
- [bandwidth kbps mbps gbps](#), on page 221
- [banner exec](#), on page 222
- [banner motd](#), on page 223
- [bcm-shell module](#), on page 224
- [bcm-shell module](#), on page 225
- [beacon](#), on page 226
- [begin exclude include end](#), on page 227
- [bestpath](#), on page 228
- [bfd-app session auto-expiry timeout](#), on page 229
- [bfd-app session remove](#), on page 230
- [bfd-app session src-ip dest intf](#), on page 231
- [bfd](#), on page 232
- [bfd](#), on page 233
- [bfd](#), on page 234
- [bfd](#), on page 235
- [bfd](#), on page 236
- [bfd](#), on page 237
- [bfd](#), on page 238
- [bfd authentication interop](#), on page 239
- [bfd authentication key-id key](#), on page 240
- [bfd echo-interface](#), on page 241
- [bfd echo-rx-interval](#), on page 242

- [bfd echo](#), on page 243
- [bfd interval](#), on page 244
- [bfd interval](#), on page 245
- [bfd interval min_rx multiplier](#), on page 246
- [bfd interval min_rx multiplier](#), on page 247
- [bfd move-session target](#), on page 248
- [bfd multihop authentication key-id key bfd multihop authentication](#), on page 249
- [bfd multihop hosting-linecard add module](#), on page 250
- [bfd multihop hosting-linecard add module](#), on page 251
- [bfd multihop interval](#), on page 252
- [bfd multihop interval min_rx multiplier](#), on page 253
- [bfd multihop interval min_rx multiplier](#), on page 254
- [bfd neighbor src-ip dest](#), on page 255
- [bfd optimize subinterface](#), on page 256
- [bfd per-link](#), on page 257
- [bfd session-store remove client](#), on page 258
- [bfd session-store source-ip dest-ip intf client](#), on page 259
- [bfd session state state](#), on page 260
- [bfd slow-timer](#), on page 261
- [bfd startup-timer bfd startup-timer](#), on page 262
- [bfshell](#), on page 263
- [bfshell cmd](#), on page 264
- [bfshell module](#), on page 265
- [bfshell module cmd](#), on page 266
- [binary-location](#), on page 267
- [bind interface](#), on page 268
- [bind mac-address](#), on page 269
- [blink](#), on page 270
- [bloggerd live-process-core sap](#), on page 271
- [bloggerd log-dump all](#), on page 272
- [bloggerd log-dump once log-buffer sap event-history](#), on page 273
- [bloggerd log-dump once pss uuid](#), on page 274
- [bloggerd log-throttle](#), on page 275
- [bloggerd log-transfer](#), on page 276
- [bloggerd log-transfer](#), on page 277
- [bloggerd parse log-buffer file](#), on page 278
- [bloggerd parse log-buffer file sap](#), on page 279
- [bloggerd parse pss file](#), on page 280
- [bmp-activate-server](#), on page 281
- [bmp-server](#), on page 282
- [boot-install nxos](#), on page 283
- [boot-order](#), on page 284
- [boot](#), on page 285
- [boot aci](#), on page 286
- [boot auto-copy](#), on page 287
- [boot kickstart](#), on page 288

- [boot mode docker_cluster](#), on page 289
- [boot mode docker_standalone](#), on page 290
- [boot mode lxc](#), on page 291
- [boot nxos](#), on page 292
- [boot nxos sup-1](#), on page 293
- [boot nxos sup-1 sup-2](#), on page 294
- [boot nxos sup-2](#), on page 295
- [boot order bootflash](#), on page 296
- [boot order pxe](#), on page 297
- [boot poap enable](#), on page 298
- [boot system](#), on page 299
- [bootmode boot](#), on page 300
- [bootmode extruntime](#), on page 301
- [bootmode hitless](#), on page 302
- [bootmode module](#), on page 303
- [bootmode nodiagruntime](#), on page 304
- [bootmode runtime](#), on page 305
- [buffer-boost](#), on page 306
- [buffer-delete](#), on page 307
- [buffer-move](#), on page 308
- [burst-detect enable](#), on page 309
- [burst-detect rise-threshold bytes fall-threshold bytes2](#), on page 310

backoff

backoff <initial-backoff> <maximum-backoff> | no backoff

Syntax Description

no	Negate a command or set its defaults
backoff	Set LDP session backoff parameters
<i>initial-backoff</i>	Initial session backoff time (seconds)
<i>maximum-backoff</i>	Maximum session backoff time (seconds)

Command Mode

- /exec/configure/ldp

backup-bw

backup-bw { <kbps> } | no backup-bw

Syntax Description

no	Negate a command or set its defaults
backup-bw	Represents bw for Fast Reroute backup
<i>kbps</i>	Amount of allocatable backup bw, any lsp may use

Command Mode

- /exec/configure/if-te

bandwidth

bandwidth <bandwidth_val> | no bandwidth

Syntax Description

no	Negate a command or set its defaults
bandwidth	Set bandwidth informational parameter
<i>bandwidth_val</i>	Bandwidth in kilobits

Command Mode

- /exec/configure/if-vlan-common

bandwidth

bandwidth <bandwidth_val> | no bandwidth

Syntax Description

no	Negate a command or set its defaults
bandwidth	Set bandwidth informational parameter
<i>bandwidth_val</i>	Bandwidth in kilobits

Command Mode

- /exec/configure/if-any-tunnel

bandwidth

```
[no] bandwidth { { xxx <bw-value> [ bps | kbps | mbps | gbps ] | percent <percentage> } | { remaining percent <rem-perc> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
bandwidth	Specify bandwidth for the class
xxx	xxx
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
percent	Percentage of available bandwidth
<i>percentage</i>	Value in percentage
remaining	% of remaining bandwidth
<i>rem-perc</i>	Value in percentage

Command Mode

- /exec/configure/policy-map/type/queuing/class

bandwidth

```
bandwidth { <bandwidth_val> | inherit [ <inherit_val> ] } | no bandwidth { [ <bandwidth_val> ] | inherit [ <inherit_val> ] }
```

Syntax Description

no	Negate a command or set its defaults
bandwidth	Set bandwidth informational parameter
<i>bandwidth_val</i>	Bandwidth in kilobits
inherit	Specify that bandwidth is inherited
<i>inherit_val</i>	(Optional) Bandwidth in kilobits

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub /exec/configure/if-ethernet-p2p

bandwidth

```
bandwidth { <bandwidth_val> | inherit [ <inherit_val> ] } | no bandwidth { [ <bandwidth_val> ] | inherit [ <inherit_val> ] }
```

Syntax Description

no	Negate a command or set its defaults
bandwidth	Set bandwidth informational parameter
<i>bandwidth_val</i>	Bandwidth in kilobits
inherit	Specify that bandwidth is inherited
<i>inherit_val</i>	(Optional) Bandwidth in kilobits

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-gig-ether-sub /exec/configure/if-remote-ethernet-sub

bandwidth

bandwidth { <bandwidth_val> | inherit [<inherit_val>] } | no bandwidth { [<bandwidth_val>] | inherit [<inherit_val>] }

Syntax Description

no	Negate a command or set its defaults
bandwidth	Set bandwidth informational parameter
inherit	Specify that bandwidth is inherited

Command Mode

- /exec/configure/if-eth-port-channel /exec/configure/if-port-channel-range
/exec/configure/if-port-channel-sub /exec/configure/if-eth-port-channel-switch
/exec/configure/if-eth-port-channel-p2p

bandwidth

[no] bandwidth { { <bw-value> [bps | kbps | mbps | gbps] | percent <percentage> } | { remaining percent <rem-perc> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
bandwidth	Specify bandwidth for the class
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
percent	Percentage of available bandwidth
<i>percentage</i>	Value in percentage
remaining	% of remaining bandwidth
<i>rem-perc</i>	Value in percentage

Command Mode

- /exec/configure/policy-map/type/plc/class

bandwidth

[no] bandwidth | bandwidth { <bw> }

Syntax Description

no	Negate a command or set its defaults
bandwidth	Specify LSP bandwidth
<i>bw</i>	bandwidth requirement in kbps

Command Mode

- /exec/configure/te/lsp-attr

bandwidth

[no] bandwidth | bandwidth { <kbps> }

Syntax Description

no	Negate a command or set its defaults
bandwidth	tunnel bandwidth requirement
<i>kbps</i>	bandwidth requirement in kbps

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

bandwidth kbps mbps gbps

```
{ { bandwidth { <val_kbps> kbps | <val_mbps> mbps | <val_gbps> gbps } } | { dscp <dscp_val> } } | { no
{ bandwidth | dscp } }
```

Syntax Description

no	Negate a command or set its defaults
bandwidth	Bandwidth per flow
<i>val_kbps</i>	Per Flow Bandwidth in Kbps
kbps	Bandwidth value in Kbps
<i>val_mbps</i>	Per Flow Bandwidth in Mbps
mbps	Bandwidth value in Mbps
<i>val_gbps</i>	Per Flow Bandwidth in Gbps
gbps	Bandwidth value in Gbps
dscp	DSCP per flow
<i>dscp_val</i>	Per Flow DSCP

Command Mode

- /exec/configure/nbm-flow-policy/attr

banner exec

```
{ banner exec <lineNo> } | { no banner exec }
```

Syntax Description

no	Negate a command or set its defaults
banner	Configure banner message
exec	Configure banner exec message
<i>lineNo</i>	Delimiter char (first char is delimiter char) followed by message ending with delimiter

Command Mode

- /exec/configure

banner motd

{ banner motd <line> } | { no banner motd }

Syntax Description

no	Negate a command or set its defaults
banner	Configure banner message
motd	Configure banner motd message
<i>line</i>	Delimiter char (Very first char is delimiter char) followed by message ending with delimiter

Command Mode

- /exec/configure

bcm-shell module

bcm-shell module <module> <quoted-cmd>

Syntax Description

bcm-shell	bcm shell/cmd
module	Module number of the linecard
<i>module</i>	Enter module number
<i>quoted-cmd</i>	the command to run on bcm-shell

Command Mode

- /exec

bcm-shell module

bcm-shell module <module>

Syntax Description

bcm-shell	bcm shell/cmd
module	Module number of the linecard
<i>module</i>	Enter module number

Command Mode

- /exec

beacon

[no] beacon

Syntax Description

no	(Optional) Negate a command or set its defaults
beacon	Disable/enable the beacon for an interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

begin exclude include end

| { begin | exclude | include | end } [-i | -x] + <expr> [next <num> | prev <num>] +

Syntax Description

	Pipe command output to filter
begin	Begin with the line that matches
exclude	Exclude lines that match
include	Include lines that match
end	End with the line that matches
-i	(Optional) Ignore case difference when comparing strings
-x	(Optional) Print only lines where the match is a whole line
<i>expr</i>	Search for the expression
next	(Optional) Print <num> lines of context after every matching line
prev	(Optional) Print <num> lines of context before every matching line
<i>num</i>	(Optional) Print <num> lines of context

Command Mode

- /output

bestpath

[no] bestpath { always-compare-med | med { missing-as-worst | non-deterministic | confed } | compare-routerid | compare-neighborid | cost-community ignore | as-path { multipath-relax | ignore } | igp-metric ignore }

Syntax Description

no	(Optional) Negate a command or set its defaults
bestpath	Change default bestpath selection algorithm
always-compare-med	Compare MED on paths from different AS
med	MED
missing-as-worst	Treat missing MED as highest MED
non-deterministic	Not always pick the best-MED path among paths from same AS
compare-routerid	Compare router-id for identical EBGp paths
compare-neighborid	When more paths available than max path config, use neighborid tiebreaker
cost-community	cost community
ignore	Ignore cost communities in bestpath selection
confed	Compare MED only from paths originated from within a confederation
as-path	AS-Path
multipath-relax	Relax AS-Path restriction when choosing multipaths
ignore	Ignore AS-Path during bestpath selection
igp-metric	IGP metric for next-hop
ignore	Ignore IGP metric for next-hop during bestpath selection

Command Mode

- /exec/configure/router-bgp/vrf-cmds

bfd-app session auto-expiry timeout

bfd-app session auto-expiry { timeout <millis> | now }

Syntax Description

bfd-app	BFD application commands
auto-expiry	auto expiry start/end
session	session operation
timeout	timeout after
now	expiry reached, dont wait to timeout, do them now
<i>millis</i>	milli-secs later

Command Mode

- /exec/configure

bfd-app session remove

```
bfd-app session remove { all | intf <intf_id> | iod <iod_id> }
```

Syntax Description

bfd-app	BFD application commands
session	session operation
remove	Remove sessions
all	Remove all sessions
intf	Remove all sessions on interface
<i>intf_id</i>	Interface Id
iod	interface iod
<i>iod_id</i>	Interface iod in hex

Command Mode

- /exec/configure

bfd-app session src-ip dest intf

```
[no] bfd-app session src-ip { <src_ip> dest-ip <dest_ip> | <src_ipv6> dest-ip <dest_ipv6> } { intf <intf_id> | iod <iod_id> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd-app	BFD application commands
session	session operation
src-ip	Source ip
<i>src_ip</i>	Source ip value
dest-ip	Destination ip
<i>dest_ip</i>	Destination ip value
iod	interface iod
<i>iod_id</i>	Interface iod in hex
intf	interface
<i>intf_id</i>	Interface Id

Command Mode

- /exec/configure

bfd

[no] bfd [ipv4 | ipv6]

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
ipv4	(Optional) ipv4 sessions
ipv6	(Optional) ipv6 sessions

Command Mode

- /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd

[no | default] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
bfd	Bidirectional Fast Detection for the neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

bfd

[no] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	Enable IPv4 BFD on all ISIS interfaces

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

bfd

[no] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	Enable IPv4 BFD on all ISIS interfaces

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

bfd

[no] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	Enable BFD on all OSPF interfaces

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

bfd

[no] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	Enable BFD on all EIGRP interfaces

Command Mode

- /exec/configure/router-eigrp /exec/configure/router-eigrp/router-eigrp-vrf
/exec/configure/router-eigrp/router-eigrp-af-common

bfd

[no] bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	Enable BFD on all OSPF interfaces

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

bfd authentication interop

bfd authentication interop | no bfd authentication interop

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
authentication	Configure BFD authentication parameters
interop	Allows keys to be sent in network format to interop with non N3k/N9K switches

Command Mode

- /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd authentication key-id key

```
bfd [ { ipv4 | ipv6 } ] authentication <auth_name> key-id <key_id_val> { key <key_val> | hex-key <h_key_val> } | no bfd [ { ipv4 | ipv6 } ] authentication
```

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
authentication	Configure BFD authentication parameters
ipv4	(Optional) ipv4 sessions
ipv6	(Optional) ipv6 sessions
<i>auth_name</i>	auth algorithm
key-id	Key ID to use in BFD frames
<i>key_id_val</i>	Key ID value
key	ASCII SHA1 secret
hex-key	HEX binary SHA1 secret
<i>key_val</i>	SHA1 secret value
<i>h_key_val</i>	SHA1 secret value. e.g ABCD123

Command Mode

- /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd echo-interface

[no] bfd echo-interface <ifindex>

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
echo-interface	Configure interface used for bfd echo frames
<i>ifindex</i>	loopback interface

Command Mode

- /exec/configure

bfd echo-rx-interval

bfd [ipv4 | ipv6] echo-rx-interval <intv> | no bfd [ipv4 | ipv6] echo-rx-interval

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
ipv6	(Optional) ipv6 sessions
ipv4	(Optional) ipv4 sessions
echo-rx-interval	Configure BFD session echo rx interval
<i>intv</i>	Echo Rx Interval in milliseconds

Command Mode

- /exec/configure /exec/configure/if-ma /exec/configure/if-ma-p2p

bfd echo

[no] bfd [{ ipv4 | ipv6 }] echo

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
echo	Configure Echo function for all address families
ipv4	(Optional) ipv4 sessions
ipv6	(Optional) ipv6 sessions

Command Mode

- /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd interval

[no] bfd [ipv4 | ipv6] interval [<min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>]

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
interval	Configure BFD session interval parameters
ipv6	(Optional) ipv6 sessions
ipv4	(Optional) ipv4 sessions
<i>min_tx_mills</i>	(Optional) TX interval in milliseconds
min_rx	(Optional) Minimum RX interval
<i>min_rx_mills</i>	(Optional) RX interval in milliseconds
multiplier	(Optional) Configure detect multiplier for bfd sessions
<i>int_mult</i>	(Optional) Detect Multiplier

Command Mode

- /exec/configure

bfd interval

[no] bfd [ipv4 | ipv6] interval [<min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>]

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
interval	Configure BFD session interval parameters
ipv6	(Optional) ipv6 sessions
ipv4	(Optional) ipv4 sessions
<i>min_tx_mills</i>	(Optional) TX interval in milliseconds
min_rx	(Optional) Minimum RX interval
<i>min_rx_mills</i>	(Optional) RX interval in milliseconds
multiplier	(Optional) Configure detect multiplier for bfd sessions
<i>int_mult</i>	(Optional) Detect Multiplier

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd interval min_rx multiplier

bfd [ipv6 | ipv4] interval <min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>

Syntax Description

bfd	BFD commands
interval	Configure BFD session interval parameters
ipv6	(Optional) ipv6 sessions
ipv4	(Optional) ipv4 sessions
<i>min_tx_mills</i>	TX interval in milliseconds
min_rx	Minimum RX interval
<i>min_rx_mills</i>	RX interval in milliseconds
multiplier	Configure detect multiplier for bfd sessions
<i>int_mult</i>	Detect Multiplier

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-ma /exec/configure/if-vlan /exec/configure/if-ma-p2p

bfd interval min_rx multiplier

bfd [ipv6 | ipv4] interval <min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>

Syntax Description

bfd	BFD commands
interval	Configure BFD session interval parameters
ipv6	(Optional) ipv6 sessions
ipv4	(Optional) ipv4 sessions
<i>min_tx_mills</i>	TX interval in milliseconds
min_rx	Minimum RX interval
<i>min_rx_mills</i>	RX interval in milliseconds
multiplier	Configure detect multiplier for bfd sessions
<i>int_mult</i>	Detect Multiplier

Command Mode

- /exec/configure

bfd move-session target

bfd move-session target <target_mod> [<discr>]

Syntax Description

bfd	BFD commands
move-session	move a session
target	Target module
<i>target_mod</i>	Module number
<i>discr</i>	(Optional) Session discriminator

Command Mode

- /exec/configure/if-ma /exec/configure/if-ma-p2p

bfd multihop authentication key-id key bfd multihop authentication

```
bfd multihop authentication <auth_name> key-id <key_id_val> { key <key_val> | hex-key <h_key_val> } |
[ no | default ] bfd multihop authentication [ <auth_name> key-id <key_id_val> { key <key_val> | hex-key
<h_key_val> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
bfd	Bidirectional Fast Detection for the neighbor
multihop	For Multihop sessions
authentication	Configure BFD authentication parameters
<i>auth_name</i>	auth algorithm
key-id	Key ID to use in BFD frames
<i>key_id_val</i>	Key ID value
key	ASCII SHA1 secret
hex-key	HEX binary SHA1 secret
<i>key_val</i>	SHA1 secret value
<i>h_key_val</i>	SHA1 secret value. e.g ABCD123

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

bfd multihop hosting-linecard add module

[no] bfd multihop hosting-linecard add module <module_num>

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
multihop	Configure BFD Multihop session interval parameters
hosting-linecard	Add the linecard to hosting-linecard for multihop sessions
add	Add the linecard to hosting-linecard list for multihop sessions
module	Linecard or module number
<i>module_num</i>	Module number

Command Mode

- /exec/configure

bfd multihop hosting-linecard add module

bfd multihop hosting-linecard add module <module_num>

Syntax Description

bfd	BFD commands
multihop	Configure BFD Multihop session interval parameters
hosting-linecard	Add the linecard to hosting-linecard for multihop sessions
add	Add the linecard to hosting-linecard list for multihop sessions
module	Linecard or module number
<i>module_num</i>	Module number

Command Mode

- /exec/configure

bfd multihop interval

[no] bfd multihop interval [<min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>]

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
multihop	Configure BFD Multihop session interval parameters
interval	Configure BFD multihop session interval parameters
<i>min_tx_mills</i>	(Optional) TX interval in milliseconds
min_rx	(Optional) Minimum RX interval
<i>min_rx_mills</i>	(Optional) RX interval in milliseconds
multiplier	(Optional) Configure detect multiplier for bfd multihop sessions
<i>int_mult</i>	(Optional) Detect Multiplier

Command Mode

- /exec/configure

bfd multihop interval min_rx multiplier

bfd multihop interval <min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>

Syntax Description

bfd	BFD commands
multihop	Configure BFD Multihop session interval parameters
interval	Configure BFD multihop session interval parameters
<i>min_tx_mills</i>	TX interval in milliseconds
min_rx	Minimum RX interval
<i>min_rx_mills</i>	RX interval in milliseconds
multiplier	Configure detect multiplier for bfd multihop sessions
<i>int_mult</i>	Detect Multiplier

Command Mode

- /exec/configure

bfd multihop interval min_rx multiplier

bfd multihop interval <min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult> | { no | default } bfd multihop interval [<min_tx_mills> min_rx <min_rx_mills> multiplier <int_mult>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
bfd	Bidirectional Fast Detection for the neighbor
multihop	For Multihop sessions
interval	Configure BFD session interval parameters
<i>min_tx_mills</i>	TX interval in milliseconds
min_rx	Minimum RX interval
<i>min_rx_mills</i>	RX interval in milliseconds
multiplier	Configure detect multiplier for bfd sessions
<i>int_mult</i>	Detect Multiplier

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

bfd neighbor src-ip dest

[no] bfd neighbor src-ip { <src_ip> dest-ip <dest_ip> | <src_ipv6> dest-ip <dest_ipv6> }

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
neighbor	BFD neighbor configuration commands (simulate client)
src-ip	Source ip
<i>src_ip</i>	Source ip value
dest-ip	Destination ip
<i>dest_ip</i>	Destination ip value

Command Mode

- /exec/configure/if-ma /exec/configure/if-ma-p2p

bfd optimize subinterface

[no] bfd [ipv4] optimize subinterface

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
optimize	optimize
subinterface	optimize subinterfaces
ipv4	(Optional) ipv4 sessions

Command Mode

- /exec/configure/if-ma /exec/configure/if-ma-p2p

bfd per-link

[no] bfd [{ ipv4 | ipv6 }] per-link

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
per-link	Run BFD sessions on each port-channel link
ipv4	(Optional) ipv4 sessions
ipv6	(Optional) ipv6 sessions

Command Mode

- /exec/configure/if-eth-port-channel /exec/configure/if-port-channel-sub
/exec/configure/if-eth-port-channel-p2p

bfd session-store remove client

```
bfd session-store remove <hex_disc> client <int_cl>
```

Syntax Description

bfd	BFD commands
session-store	session store operation
remove	Remove session from session store
<i>hex_disc</i>	Session discriminator
client	Client Id
<i>int_cl</i>	client

Command Mode

- /exec/configure

bfd session-store source-ip dest-ip intf client

bfd session-store source-ip <src_ip> dest-ip <dest_ip> intf <intf_id> client <int_cl>

Syntax Description

bfd	BFD commands
session-store	Session store operation
source-ip	source ip
<i>src_ip</i>	source ip value
dest-ip	dest ip
<i>dest_ip</i>	source ip value
intf	interface
<i>intf_id</i>	Interface Id
client	Client Id
<i>int_cl</i>	client

Command Mode

- /exec/configure

bfd session state state

```
bfd session state <hex_disc> state <state_up_down>
```

Syntax Description

bfd	BFD commands
session	session related test
state	Change session state
<i>hex_disc</i>	Session discriminator
state	Change to state
<i>state_up_down</i>	UP/DOWN

Command Mode

- /exec/configure

bfd slow-timer

bfd [{ ipv4 | ipv6 }] slow-timer <int_slow_timer> | no bfd [{ ipv4 | ipv6 }] slow-timer

Syntax Description

no	Negate a command or set its defaults
bfd	BFD commands
slow-timer	Configure slow mode timer for sessions
<i>int_slow_timer</i>	Slow rate timer in milliseconds
ipv4	(Optional) ipv4 sessions
ipv6	(Optional) ipv6 sessions

Command Mode

- /exec/configure

bfd startup-timer bfd startup-timer

bfd startup-timer <int_startup_timer> | [no] bfd startup-timer

Syntax Description

no	(Optional) Negate a command or set its defaults
bfd	BFD commands
startup-timer	Configure Delayed Start Up timer for sessions
<i>int_startup_timer</i>	Start Up timer in seconds

Command Mode

- /exec/configure

bfshell

bfshell

Syntax Description

bfshell	bfshell
---------	---------

Command Mode

- /exec

bfshell cmd

bfshell cmd <cmd>

Syntax Description

bfshell	bfshell
cmd	Specify command
<i>cmd</i>	Quoted commands to be exec

Command Mode

- /exec

bfshell module

bfshell module <module>

Syntax Description

bfshell	bfshell
module	Select module
<i>module</i>	Module number

Command Mode

- /exec

bfshell module cmd

bfshell module <module> cmd <cmd>

Syntax Description

bfshell	bfshell
module	Select module
cmd	Specify command
<i>module</i>	Module number
<i>cmd</i>	Quoted commands to be exec

Command Mode

- /exec

binary-location

[no] binary-location <source-uri>

Syntax Description

no	(Optional) Negate a command or set its defaults
binary-location	the location binaries are downloaded from
<i>source-uri</i>	Location for restoration to pick up binaries

Command Mode

- /exec/configure/personality

bind interface

[no] bind interface <interface-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
bind	Bind the VFC
interface	Bind the VFC to an interface
<i>interface-name</i>	Interface name

Command Mode

- /exec/configure/if-vfc

bind mac-address

[no] bind mac-address <mac0>

Syntax Description

no	(Optional) Negate a command or set its defaults
bind	Bind the VFC
mac-address	Bind the VFC to a MAC Address
<i>mac0</i>	Enter MAC address in dotted hex format

Command Mode

- /exec/configure/if-vfc

blink

```
[no] blink { module <module> | <s0> <santa-cruz-range> | chassis | powersupply <psnum> | fan <fan_num>
}
```

Syntax Description

no	(Optional) Negate a command or set its defaults
blink	blink locator led
module	blink module led
<i>module</i>	please enter the module number
<i>s0</i>	blink a specific xbar
<i>santa-cruz-range</i>	please enter the xbar number
chassis	blink chassis led
powersupply	blink powersupply led
<i>psnum</i>	powersupply number
fan	blink Fan led
<i>fan_num</i>	fan number

Command Mode

- /exec

bloggerd live-process-core sap

bloggerd live-process-core sap <sap>

Syntax Description

bloggerd	Blogger commands
live-process-core	Dump the core of the live-process
sap	Dump core for a particular SAP
<i>sap</i>	Enter a valid SAP. Enter 0 for ALL SAPs in this VDC

Command Mode

- /exec

bloggerd log-dump all

```
[no] bloggerd log-dump { all | [ module <module> ] sap <sap_num> [ vdc <new_id> | vdc-all ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
bloggerd	Blogger commands
log-dump	Dump Log Buffer
all	Log Dump for ALL services across ALL modules in the switch on reaching threshold
module	(Optional) Enable Buffer Dump for particular Module
<i>module</i>	(Optional) Enter a valid Module Number
sap	Enable Buffer Dump for a particular sap
<i>sap_num</i>	Enter a valid SAP. Enter 0 for ALL SAPs in this VDC
vdc	(Optional) Enable Log Dump for a particular VDC. DEFAULT_VDC by default
<i>new_id</i>	(Optional) Enter a valid VDC ID
vdc-all	(Optional) Enable Log Dump for the sap on ALL VDCs

Command Mode

- /exec/configure

bloggerd log-dump once log-buffer sap event-history

```
bloggerd log-dump once log-buffer sap <sap> event-history { errors | msgs | { app-specific <uuid> instance
<buffer-instance> } }
```

Syntax Description

bloggerd	Blogger commands
log-dump	Dump Log Buffer
once	Dump Log Buffer once immediately
log-buffer	Dump Log buffer
sap	Enable Buffer Dump for a particular sap
<i>sap</i>	Enter a valid SAP. Enter 0 for ALL SAPs in this VDC
event-history	Event-History Buffers
errors	event-history errors
msgs	event-history messages
app-specific	application specific event history
<i>uuid</i>	Enter valid app's UUID
instance	Buffer Instance of the App-Specific SDWrap buffer
<i>buffer-instance</i>	Enter a valid SDWrap buffer instance for the app

Command Mode

- /exec

bloggerd log-dump once pss uuid

bloggerd log-dump once pss uuid <uuid>

Syntax Description

bloggerd	Blogger commands
log-dump	Dump Log Buffer
once	Dump Log Buffer once immediately
pss	Dump PSS
uuid	Dump PSS for a particular UUID
<i>uuid</i>	Enter a app's UUID

Command Mode

- /exec

bloggerd log-throttle

```
[no] bloggerd log-throttle [ min-rollover <min-rollover> max-rollover-per-minute <max-rollover-per-minute> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
bloggerd	Blogger commands
log-throttle	Enable Log Dump Throttling for all NxOS services
min-rollover	(Optional) Number of minimum buffer rollovers before starting to throttle. Default: 5
<i>min-rollover</i>	(Optional) Enter the minimum number of roll-overs before throttling log-dump. Default: 5
max-rollover-per-minute	(Optional) Maximum allowed buffer rollovers per minute. Default: 1
<i>max-rollover-per-minute</i>	(Optional) Enter the maximum allowed roll-overs per minute before throttling. Default: 1

Command Mode

- /exec/configure

bloggerd log-transfer

bloggerd log-transfer { <ip-addr> <path> | logflash }

Syntax Description

bloggerd	Blogger commands
log-transfer	Configure log transfer
<i>ip-addr</i>	IP addr of logging server
<i>path</i>	Path in tftp server to store logs. Eg: logOutput
logflash	Move all log-files to logflash

Command Mode

- /exec/configure

bloggerd log-transfer

[no] bloggerd log-transfer

Syntax Description

no	Negate a command or set its defaults
bloggerd	Blogger commands
log-transfer	Configure log transfer

Command Mode

- /exec/configure

bloggerd parse log-buffer file

```
bloggerd parse log-buffer { file | directory } <uri0> [ dsf_table <uri1> ]
```

Syntax Description

bloggerd	Blogger commands
parse	Parse a file
log-buffer	Parse buffer log file
directory	Enter path of directory
file	Enter file name. Please unzip file before parsing!
<i>uri0</i>	Linux path to file/directory (Eg: /bootflash/abc)
dsf_table	(Optional) Enter dsf table file name.
<i>uri1</i>	(Optional) Linux path to file/directory (Eg: /bootflash/abc)

Command Mode

- /exec

bloggerd parse log-buffer file sap

bloggerd parse log-buffer file <uri0> sap <sap-num>

Syntax Description

bloggerd	Blogger commands
parse	Parse a file
log-buffer	Parse buffer log file
file	Enter file name. Please unzip file before parsing!
<i>uri0</i>	Linux path to file (Eg: /bootflash/abc)
sap	SAP of the application which should parse the file
<i>sap-num</i>	Enter a valid SAP. Enter 0 for ALL SAPs in this VDC

Command Mode

- /exec

bloggerd parse pss file

bloggerd parse pss file <uri0>

Syntax Description

bloggerd	Blogger commands
parse	Parse a file
pss	Parse a dumped PSS File
file	Enter file name (without pss extensions). Please unzip file before parsing!
<i>uri0</i>	Linux path to file/directory (Eg: /bootflash/abc)

Command Mode

- /exec

bmp-activate-server

bmp-activate-server <server-number> | { no | default } bmp-activate-server <server-number>

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
bmp-activate-server	Activate BMP monitoring for the peer
<i>server-number</i>	Server Id

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

bmp-server

[no] bmp-server <server-number>

Syntax Description

no	(Optional) Negate a command or set its defaults
bmp-server	Configure bmp-server
<i>server-number</i>	server number value

Command Mode

- /exec/configure/router-bgp

boot-install nxos

```
{ boot-install nxos <uri0> | no boot-install nxos [ <uri0> ] }
```

Syntax Description

no	Negate a command or set its defaults
boot-install	Configure boot variables
nxos	Configure NXOS image
<i>uri0</i>	Enter NXOS image uri

Command Mode

- /exec/configure

boot-order

boot-order <new_id>

Syntax Description

boot-order	The order at which a vdc will boot up. VDCs at the same level will be started parallelly
<i>new_id</i>	The order at which a vdc will boot up. VDCs at the same level will be started parallelly

Command Mode

- /exec/configure/vdc

boot

```
{ boot <s0> <uri0> [ module [ <module> ] ] | no boot <s0> [ <uri0> [ module [ <module> ] ] ] }
```

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
<i>s0</i>	use [show boot variables] for list of keywords
<i>uri0</i>	Enter module image uri
module	(Optional) Enter module number for the image
<i>module</i>	(Optional) Enter module number

Command Mode

- /exec/configure

boot aci

```
{ boot aci <uri0> | no boot aci [ <uri0> ] }
```

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
aci	Configure ACI image
<i>uri0</i>	Enter ACI image uri

Command Mode

- /exec/configure

boot auto-copy

[no] boot auto-copy

Syntax Description

no	(Optional) Negate a command or set its defaults
boot	Configure boot variables
auto-copy	Turns on/off autocopy of bootvar images

Command Mode

- /exec/configure

boot kickstart

```
{ boot kickstart <uri0> | no boot kickstart [ <uri0> ] }
```

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
kickstart	Configure kickstart image
<i>uri0</i>	Enter Kickstart image uri

Command Mode

- /exec/configure

boot mode docker_cluster

[no] boot mode docker_cluster [dhcp <option>]

Syntax Description

no	(Optional) Negate a command or set its defaults
boot	Configure boot mode
mode	boot mode
docker_cluster	Turns on/off docker_cluster mode
dhcp	(Optional) Custom DHCP option
<i>option</i>	(Optional) Option, default is 250

Command Mode

- /exec/configure

boot mode docker_standalone

[no] boot mode docker_standalone

Syntax Description

no	(Optional) Negate a command or set its defaults
boot	Configure boot mode
mode	boot mode
docker_standalone	Turns on/off docker_standalone mode (for internal use only)

Command Mode

- /exec/configure

boot mode lxc

[no] boot mode lxc

Syntax Description

no	(Optional) Negate a command or set its defaults
boot	Configure boot mode
mode	boot mode
lxc	Turns on/off lxc mode

Command Mode

- /exec/configure

boot nxos

```
{ boot nxos <uri0> | no boot nxos [ <uri0> ] }
```

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
nxos	Configure NXOS image
<i>uri0</i>	Enter nxos image uri

Command Mode

- /exec/configure

boot nxos sup-1

{ boot nxos <uri0> sup-1 | no boot nxos <uri0> sup-1 }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
nxos	Configure NXOS image
<i>uri0</i>	Enter kickstart image uri
sup-1	Enter sup-1 to configure the 1st sup

Command Mode

- /exec/configure

boot nxos sup-1 sup-2

{ boot nxos <uri0> sup-1 sup-2 | no boot nxos <uri0> sup-1 sup-2 }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
nxos	Configure NXOS image
<i>uri0</i>	Enter kickstart image uri
sup-1	Enter sup-1 to configure the 1st sup
sup-2	Enter sup-2 to configure the 2nd sup

Command Mode

- /exec/configure

boot nxos sup-2

```
{ boot nxos <uri0> sup-2 | no boot nxos <uri0> sup-2 }
```

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
nxos	Configure NXOS image
<i>uri0</i>	Enter kickstart image uri
sup-2	Enter sup-2 to configure the 2nd sup

Command Mode

- /exec/configure

boot order bootflash

{ boot order bootflash [pxe] | no boot order bootflash [pxe] }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
order	Configure loader fallback order
bootflash	Boot from Bootflash
pxe	(Optional) Pxe Boot

Command Mode

- /exec/configure

boot order pxe

{ boot order pxe [bootflash] | no boot order pxe [bootflash] }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
order	Configure loader fallback order
pxe	Pxe Boot
bootflash	(Optional) Boot from Bootflash

Command Mode

- /exec/configure

boot poap enable

{ boot poap enable | no boot poap enable }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
poap	feature poap
enable	Enable Perpetual POAP making POAP kick in on reload even with startup-config

Command Mode

- /exec/configure

boot system

{ boot system <uri0> | no boot system [<uri0>] }

Syntax Description

no	Negate a command or set its defaults
boot	Configure boot variables
system	Configure system image
<i>uri0</i>	Enter system image uri

Command Mode

- /exec/configure

bootmode boot

[no] bootmode boot

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
boot	boot in boot mode

Command Mode

- /exec/configure

bootmode extruntime

[no] bootmode extruntime

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
extruntime	boot in runtime mode with extended diags

Command Mode

- /exec/configure

bootmode hitless

[no] bootmode hitless

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
hitless	boot in hitless mode

Command Mode

- /exec/configure

bootmode module

[no] bootmode module <module> { boot | extruntime | hitless | netboot | nodiagruntime | runtime }

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
module	set bootmode for a given module in the switch
<i>module</i>	please enter module number
boot	boot in boot mode
extruntime	boot in runtime mode with extended diags
hitless	boot in hitless mode
netboot	boot using boot netboot in runtime mode
nodiagruntime	boot in runtime mode without running any diags
runtime	boot in runtime mode with normal diags

Command Mode

- /exec/configure

bootmode nodiagruntime

[no] bootmode nodiagruntime

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
nodiagruntime	boot in runtime mode without running any diags

Command Mode

- /exec/configure

bootmode runtime

[no] bootmode runtime

Syntax Description

no	(Optional) Negate a command or set its defaults
bootmode	set bootmode for all modules in the switch
runtime	boot in runtime mode with normal diags

Command Mode

- /exec/configure

buffer-boost

[no] buffer-boost

Syntax Description

no	(Optional) Negate a command or set its defaults
buffer-boost	Enable extra buffers for this interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

buffer-delete

buffer-delete { <id-range> | <id> | all }

Syntax Description

buffer-delete	delete buffered command(s)
<i>id-range</i>	Range(whole-number) of command id(s) to be deleted from switch-profile buffer
<i>id</i>	Exact command id (x.x.x format) to be deleted from switch-profile buffer
all	delete all buffered commands

Command Mode

- /exec/configure

buffer-move

buffer-move <fromid> <toid>

Syntax Description

buffer-move	move buffered command(s)
<i>fromid</i>	Command id of command(s) to be moved in switch-profile buffer
<i>toid</i>	New command id to be assigned in switch-profile buffer

Command Mode

- /exec/configure

burst-detect enable

[no] burst-detect enable

Syntax Description

no	(Optional) Negate a command or set its defaults
burst-detect	Specify OOBST burst-detect thresholds for the class
enable	enable

Command Mode

- /exec/configure/policy-map/type/queuing/class

burst-detect rise-threshold bytes fall-threshold bytes2

[no] burst-detect rise-threshold <value-in-bytes> bytes fall-threshold <value-in-bytes> bytes2

Syntax Description

no	(Optional) Negate a command or set its defaults
burst-detect	Specify OOBST burst-detect thresholds for the class
rise-threshold	Threshold bytes(queue depth) to start monitoring burst
<i>value-in-bytes</i>	
bytes	bytes
fall-threshold	Threshold bytes(queue depth) to stop monitoring burst
<i>value-in-bytes</i>	
bytes2	bytes2

Command Mode

- /exec/configure/policy-map/type/queuing/class



C Commands

- [cabundle url](#), on page 323
- [callhome](#), on page 324
- [callhome send configuration](#), on page 325
- [callhome send diagnostic](#), on page 326
- [callhome test](#), on page 327
- [callhome test inventory](#), on page 328
- [capability additional-paths receive](#), on page 329
- [capability additional-paths send](#), on page 330
- [capability suppress 4-byte-as](#), on page 331
- [capability vrf-lite](#), on page 332
- [capture](#), on page 333
- [capture](#), on page 334
- [capture session](#), on page 335
- [carrier-delay](#), on page 336
- [catena](#), on page 337
- [catena device-group](#), on page 338
- [catena port-acl](#), on page 339
- [catena port-group](#), on page 340
- [catena vlan-group](#), on page 341
- [cbts-member tunnel-te](#), on page 342
- [cd](#), on page 343
- [cdp advertise v1](#), on page 344
- [cdp enable](#), on page 345
- [cdp enable](#), on page 346
- [cdp format device-id](#), on page 347
- [cdp holdtime](#), on page 348
- [cdp timer](#), on page 349
- [certificate](#), on page 350
- [cfs debug all](#), on page 351
- [cfs distribute](#), on page 352
- [cfs eth cos](#), on page 353
- [cfs eth distribute](#), on page 354
- [cfs ipv4 distribute](#), on page 355

- cfs ipv6 distribute, on page 356
- cfs region, on page 357
- chain, on page 358
- change-password, on page 359
- channel-group, on page 360
- channel-group, on page 361
- channel-group, on page 362
- channel-group, on page 363
- channel-group force, on page 364
- channel-group force, on page 365
- channel mode, on page 366
- channel mode active, on page 367
- chassis-family fretta, on page 368
- checkpoint, on page 369
- checkpoint, on page 370
- cipher-suite, on page 371
- class-map, on page 372
- class-map type control-plane, on page 373
- class-map type network-qos, on page 374
- class-map type psp, on page 375
- class-map type queuing, on page 376
- class-map type queuing, on page 377
- class, on page 378
- class, on page 379
- class `__inline__`, on page 380
- class class-default, on page 381
- class type network-qos, on page 382
- class type network-qos class-default, on page 383
- class type psp, on page 384
- class type queuing, on page 385
- clear, on page 386
- clear, on page 387
- clear, on page 388
- clear, on page 389
- clear aaa local user blocked username, on page 390
- clear access-list counters, on page 391
- clear access-list hardware counters, on page 392
- clear access-list ipsg stats, on page 393
- clear accounting log, on page 394
- clear aclqos cl-qos, on page 395
- clear aclqos fab, on page 396
- clear aclqos fc, on page 397
- clear aclqos libdrv, on page 398
- clear aclqos map, on page 399
- clear aclqos merge, on page 400
- clear aclqos pl, on page 401

- [clear aclqos ppf-parse](#), on page 402
- [clear aclqos ppf](#), on page 403
- [clear aclqos qng-hw](#), on page 404
- [clear aclqos qng](#), on page 405
- [clear aclqos rl](#), on page 406
- [clear aclqos rm](#), on page 407
- [clear aclqos sch](#), on page 408
- [clear aclqos stats](#), on page 409
- [clear aclqos tbl](#), on page 410
- [clear aclqos trace-detail](#), on page 411
- [clear aclqos trace](#), on page 412
- [clear aclqos uf](#), on page 413
- [clear bfd statistics](#), on page 414
- [clear bgp](#), on page 415
- [clear bgp bmp stats server](#), on page 417
- [clear bgp event-history](#), on page 418
- [clear bgp private](#), on page 419
- [clear bootvar log](#), on page 421
- [clear cdp counters](#), on page 422
- [clear checkpoint database](#), on page 423
- [clear cli history](#), on page 424
- [clear controller accounting log](#), on page 425
- [clear copp statistics](#), on page 426
- [clear cores](#), on page 427
- [clear cores archive](#), on page 428
- [clear counters](#), on page 429
- [clear counters buffers](#), on page 430
- [clear counters interface](#), on page 431
- [clear counters interface](#), on page 432
- [clear counters interface](#), on page 433
- [clear counters interface all](#), on page 434
- [clear counters interface snmp](#), on page 435
- [clear counters tah-buffers](#), on page 436
- [clear crypto ca trustpool timer](#), on page 437
- [clear debug-logfile](#), on page 438
- [clear debug logfile](#), on page 439
- [clear dot1x all](#), on page 440
- [clear dot1x stats interface](#), on page 441
- [clear ecp statistics](#), on page 442
- [clear eigrp event-history](#), on page 443
- [clear evb hosts](#), on page 444
- [clear evb hosts](#), on page 445
- [clear evb statistics](#), on page 446
- [clear fabric database dci vrf node-id](#), on page 447
- [clear fabric database host all vni](#), on page 448
- [clear fabric database host statistics](#), on page 449

- [clear fabric database include-vrf](#), on page 450
- [clear fabric database statistics](#), on page 451
- [clear fabric database statistics type server-proto radius group](#), on page 452
- [clear fabric database statistics type server-proto xmpp ip](#), on page 453
- [clear fabric multicast event-history](#), on page 454
- [clear fc2](#), on page 455
- [clear fctimer session](#), on page 456
- [clear flow cache](#), on page 457
- [clear flow cache](#), on page 458
- [clear flow exporter](#), on page 459
- [clear forwarding adjacency module](#), on page 460
- [clear forwarding cumulative counter](#), on page 461
- [clear forwarding distribution lisp counters all](#), on page 462
- [clear forwarding events-history](#), on page 463
- [clear forwarding inconsistency](#), on page 464
- [clear forwarding ipv4 multicast counters](#), on page 465
- [clear forwarding ipv6-l3-route-history](#), on page 466
- [clear forwarding ipv6 adjacency module](#), on page 467
- [clear forwarding ipv6 inconsistency](#), on page 468
- [clear forwarding ipv6 multicast counters](#), on page 469
- [clear forwarding ipv6 route module](#), on page 470
- [clear forwarding l2-mc-route-history](#), on page 471
- [clear forwarding l2-oiflist-history](#), on page 472
- [clear forwarding l2-route-history](#), on page 473
- [clear forwarding l2mcast info l2-mc-route-history](#), on page 474
- [clear forwarding l2mcast info l2-oiflist-history](#), on page 475
- [clear forwarding l2mcast info l2-route-history](#), on page 476
- [clear forwarding l2mcast info l2-xbar-history](#), on page 477
- [clear forwarding l2mcast info statistics](#), on page 478
- [clear forwarding l2vpn trace member-history](#), on page 479
- [clear forwarding l3-route-history](#), on page 480
- [clear forwarding oiflist-history](#), on page 481
- [clear forwarding route module](#), on page 482
- [clear forwarding trace ecmp-history](#), on page 483
- [clear forwarding trace mfib oif-history](#), on page 484
- [clear forwarding trace mfib oiflist-history](#), on page 485
- [clear forwarding trace mfib platform oiflist-history](#), on page 486
- [clear forwarding trace mfib v4-route-history](#), on page 487
- [clear forwarding trace mfib v6-route-history](#), on page 488
- [clear forwarding trace v4-adj-history](#), on page 489
- [clear forwarding trace v4-pfx-history](#), on page 490
- [clear forwarding trace v4-rnh-history](#), on page 491
- [clear forwarding trace v6-adj-history](#), on page 492
- [clear forwarding trace v6-pfx-history](#), on page 493
- [clear forwarding trace v6-rnh-history](#), on page 494
- [clear forwarding trace vobj-history](#), on page 495

- clear frame traffic, on page 496
- clear fs-daemon log, on page 497
- clear hardware flow ip, on page 498
- clear hardware flow ipv6, on page 499
- clear hardware flow l2, on page 500
- clear hardware ip verify, on page 501
- clear hardware profile buffer monitor, on page 503
- clear hardware profile latency monitor, on page 504
- clear hardware profile packet-drop file_instance, on page 505
- clear hardware rate-limiter, on page 506
- clear hardware rate-limiter, on page 507
- clear hsrp counters clear hsrp state-history, on page 508
- clear install all failed-standby, on page 509
- clear install failure-reason, on page 510
- clear install log-history all, on page 511
- clear install status, on page 512
- clear ip, on page 513
- clear ip adjacency statistics, on page 514
- clear ip amt tunnel, on page 515
- clear ip arp, on page 516
- clear ip arp controller-statistics, on page 517
- clear ip arp inspection log, on page 518
- clear ip arp inspection statistics vlan, on page 519
- clear ip arp multihoming-statistics, on page 520
- clear ip arp statistics, on page 521
- clear ip arp suppression-cache statistics, on page 522
- clear ip arp tunnel-statistics, on page 523
- clear ip arp vpc-statistics, on page 524
- clear ip dhcp global statistics, on page 525
- clear ip dhcp relay statistics, on page 526
- clear ip dhcp snooping binding, on page 527
- clear ip dhcp snooping statistics, on page 528
- clear ip eigrp accounting, on page 529
- clear ip eigrp event-history, on page 530
- clear ip eigrp event-history bfd, on page 531
- clear ip eigrp redistribution, on page 532
- clear ip eigrp route-map statistics redistribute, on page 533
- clear ip eigrp traffic, on page 534
- clear ip igmp event-history, on page 535
- clear ip igmp groups, on page 536
- clear ip igmp interface statistics, on page 537
- clear ip igmp snooping event-history, on page 538
- clear ip igmp snooping explicit-tracking, on page 539
- clear ip igmp snooping groups, on page 540
- clear ip igmp snooping proxy querier ports vlan, on page 541
- clear ip igmp snooping report statistics, on page 542

- clear ip igmp snooping statistics, on page 543
- clear ip interface statistics, on page 544
- clear ip lisp data-cache, on page 545
- clear ip lisp map-cache, on page 546
- clear ip lisp statistics, on page 547
- clear ip mbgp dampening, on page 548
- clear ip mbgp flap-statistics, on page 550
- clear ip mbgp peer-template, on page 552
- clear ip mfwd event-history, on page 554
- clear ip mroute, on page 555
- clear ip mroute statistics, on page 556
- clear ip msdp event-history, on page 557
- clear ip msdp peer, on page 558
- clear ip msdp policy statistics sa-policy in, on page 559
- clear ip msdp sa, on page 560
- clear ip msdp statistics, on page 561
- clear ip nat-alias address, on page 562
- clear ip nat statistics, on page 563
- clear ip nat translation, on page 564
- clear ip ospf database, on page 566
- clear ip ospf event-history, on page 567
- clear ip ospf interface, on page 568
- clear ip ospf neighbor, on page 569
- clear ip ospf policy statistics, on page 570
- clear ip ospf redistribution, on page 572
- clear ip ospf statistics, on page 573
- clear ip ospf traffic, on page 574
- clear ip pim event-history, on page 575
- clear ip pim interface statistics, on page 576
- clear ip pim policy statistics, on page 577
- clear ip pim policy statistics jp, on page 578
- clear ip pim route, on page 579
- clear ip pim statistics, on page 580
- clear ip rip policy statistics redistribute bgp, on page 581
- clear ip rip statistics, on page 582
- clear ip routing multicast event-history, on page 583
- clear ip traffic, on page 584
- clear ipv6 adjacency statistics, on page 585
- clear ipv6 amt tunnel, on page 586
- clear ipv6 dhcp-ldra statistics, on page 587
- clear ipv6 dhcp relay statistics, on page 588
- clear ipv6 eigrp route-map statistics redistribute, on page 589
- clear ipv6 icmp, on page 590
- clear ipv6 icmp vpc-statistics, on page 591
- clear ipv6 interface statistics, on page 592
- clear ipv6 lisp data-cache, on page 593

- clear ipv6 lisp statistics, on page 594
- clear ipv6 mld groups, on page 595
- clear ipv6 mroute, on page 596
- clear ipv6 neighbor, on page 597
- clear ipv6 neighbor binding, on page 598
- clear ipv6 pim event-history, on page 599
- clear ipv6 pim interface statistics, on page 600
- clear ipv6 pim policy statistics jp, on page 601
- clear ipv6 pim route, on page 602
- clear ipv6 pim statistics, on page 603
- clear ipv6 rguard statistics, on page 604
- clear ipv6 rip policy statistics redistribute bgp, on page 605
- clear ipv6 routing multicast event-history, on page 606
- clear ipv6 snooping counters, on page 607
- clear ipv6 snooping events, on page 608
- clear ipv6 snooping messages, on page 609
- clear ipv6 traffic, on page 610
- clear isis adjacency, on page 611
- clear isis dpi, on page 612
- clear isis event-history, on page 613
- clear isis ipv6 route-map statistics, on page 614
- clear isis redistribution, on page 616
- clear isis route-map statistics, on page 617
- clear isis spf-log, on page 619
- clear isis statistics, on page 620
- clear isis traffic, on page 621
- clear itd statistics, on page 622
- clear keystore, on page 623
- clear l2dbg, on page 624
- clear l2fwder statistics, on page 625
- clear l3vm event-history, on page 626
- clear lacp counters, on page 627
- clear ldap-server statistics, on page 628
- clear license, on page 630
- clear lim counters, on page 631
- clear line, on page 632
- clear lisp ddt referral-cache, on page 633
- clear lisp dynamic-eid, on page 634
- clear lisp proxy-itr, on page 635
- clear lisp site, on page 636
- clear lldp counters, on page 637
- clear lldp counters interface, on page 638
- clear logging ip access-list cache, on page 639
- clear logging logfile, on page 640
- clear logging nvram, on page 641
- clear logging onboard, on page 642

- clear logging onboard, on page 643
- clear logging session, on page 644
- clear mac address-table datapath, on page 645
- clear mac address-table dynamic, on page 646
- clear mts message statistics, on page 647
- clear mvr counters, on page 648
- clear mvr counters receiver-ports, on page 649
- clear mvr counters source-ports, on page 650
- clear nbm flow statistics, on page 651
- clear ngoam, on page 652
- clear ngoam, on page 653
- clear ngoam, on page 654
- clear ngoam, on page 655
- clear ngoam pathtrace, on page 656
- clear ntp session, on page 657
- clear ntp statistics, on page 658
- clear nvram, on page 659
- clear nxapi-server logs, on page 660
- clear openflow switch controller all, on page 661
- clear ospfv3 database, on page 662
- clear ospfv3 event-history, on page 663
- clear ospfv3 interface, on page 664
- clear ospfv3 neighbor, on page 665
- clear ospfv3 policy statistics, on page 666
- clear ospfv3 statistics, on page 668
- clear ospfv3 traffic, on page 669
- clear peer-info interface vsan, on page 670
- clear pktmgr client, on page 671
- clear pktmgr interface, on page 672
- clear plb analytics, on page 673
- clear port-security dynamic address vlan, on page 674
- clear port-security dynamic interface, on page 675
- clear processes log all, on page 676
- clear processes log all vdc-all, on page 677
- clear processes log archive, on page 678
- clear processes log pid, on page 679
- clear processes vdc log all, on page 680
- clear processes vdc log pid, on page 681
- clear ptp corrections, on page 682
- clear ptp counters interface, on page 683
- clear qos policies, on page 684
- clear qos policies force, on page 685
- clear qos statistics, on page 686
- clear queuing burst-detect, on page 687
- clear queuing pfc-queue, on page 688
- clear queuing pfc-queue interface, on page 689

- clear queuing tah-pfc-queue, on page 690
- clear radius-server statistics, on page 691
- clear radius session, on page 693
- clear rmon, on page 694
- clear route-map pbr-statistics, on page 695
- clear routing event-history, on page 696
- clear routing ip multicast mfdm pending counters, on page 697
- clear routing ip multicast rpf-source retry-cache, on page 698
- clear routing ipv6 event-history, on page 699
- clear routing ipv6 multicast, on page 700
- clear routing multicast, on page 701
- clear scheduler logfile, on page 702
- clear screen, on page 703
- clear session state name, on page 704
- clear sflow statistics, on page 705
- clear snmp counters, on page 706
- clear snmp hostconfig, on page 707
- clear sockets statistics, on page 708
- clear spanning-tree counters, on page 709
- clear spanning-tree detected-protocols, on page 710
- clear spanning-tree sps-hist, on page 711
- clear ssh hosts, on page 712
- clear statistics module-all, on page 713
- clear statistics module, on page 714
- clear sup-monitor drops session, on page 715
- clear system login failures, on page 716
- clear system reset-reason, on page 717
- clear tacacs-server statistics, on page 718
- clear tech-support lock, on page 720
- clear tech-support lock, on page 721
- clear user, on page 722
- clear veobc counters, on page 723
- clear vlan access-list counters, on page 724
- clear vlan counters, on page 725
- clear vmtracker counters, on page 726
- clear vpc statistics all, on page 727
- clear vpc statistics peer-keepalive, on page 728
- clear vpc statistics vpc, on page 729
- clear vpc transport statistics, on page 730
- clear vrrp statistics, on page 731
- clear vrrpv3 event-history, on page 732
- clear vrrpv3 statistics, on page 733
- clear vtp counters, on page 734
- cli alias name, on page 735
- cli create new-cmd, on page 736
- cli var name, on page 737

- cli var name, on page 738
- cli var name, on page 739
- cli var name, on page 740
- cli verifyrun, on page 741
- client-to-client reflection, on page 742
- clis all, on page 743
- clock-tolerance ntp oneway absolute, on page 744
- clock format 12, on page 745
- clock format show-timezone debug, on page 746
- clock format show-timezone syslog, on page 747
- clock protocol, on page 748
- clock set, on page 749
- clock summer, on page 751
- clock sync-interval, on page 752
- cluster-id, on page 753
- collect, on page 754
- collect, on page 755
- collect, on page 756
- collect, on page 757
- collect, on page 758
- collect, on page 759
- collect counter bytes, on page 760
- collect ip version, on page 761
- collect timestamp sys-uptime first, on page 762
- collect transport tcp flags, on page 763
- color, on page 764
- commit, on page 765
- commit, on page 766
- commit, on page 767
- commit verbose, on page 768
- compress-bitfields ipv6 multicast, on page 769
- compress-bitfields ipv6 multicast, on page 770
- compress-bitfields multicast, on page 771
- conf-offset, on page 772
- confederation identifier, on page 773
- confederation peers, on page 774
- config-source controller, on page 775
- configure, on page 776
- configure config-template on substitute, on page 777
- configure maintenance profile normal, on page 778
- configure profile, on page 779
- configure replace, on page 780
- configure replace abort, on page 781
- configure replace commit, on page 782
- configure session, on page 783
- configure sync, on page 784

- congestion-control dctcp ecn-threshold bytes, on page 785
- congestion-control ecn, on page 786
- congestion-control random-detect, on page 787
- congestion-control random-detect forward-nonecn, on page 788
- congestion-control random-detect global-buffer minimum-threshold maximum-threshold, on page 789
- congestion-control tail-drop, on page 790
- connect, on page 791
- connected-prefix-sid-map, on page 792
- continue, on page 793
- contract-id, on page 794
- control-plane, on page 795
- control-plane dynamic, on page 796
- control vlan, on page 797
- control vlan, on page 798
- controller-credentials username password 0, on page 799
- controller description, on page 800
- controller ip vrf, on page 801
- controller ipv4, on page 802
- controller ipv4, on page 803
- controller type l2 identifier, on page 804
- copp copy profile prefix, on page 805
- copp distributed-policing enable, on page 806
- copp profile, on page 807
- copp profile, on page 808
- copp rate-limit disable, on page 809
- copy, on page 810
- copy, on page 812
- copy licenses, on page 813
- copy licenses, on page 814
- copy recursive, on page 815
- copy running vdc-all, on page 816
- copy vdc-all, on page 817
- core-on-no-memory, on page 818
- core-on-no-memory, on page 819
- cost, on page 820
- count, on page 821
- count, on page 822
- counter name value op, on page 823
- crypto ca authenticate, on page 824
- crypto ca crl request, on page 825
- crypto ca enroll, on page 826
- crypto ca export pkcs12, on page 827
- crypto ca import certificate, on page 828
- crypto ca import pkcs12, on page 829
- crypto ca lookup, on page 830
- crypto ca remote ldap, on page 831

- [crypto ca test verify](#), on page 832
- [crypto ca trustpoint](#), on page 833
- [crypto ca trustpool import url](#), on page 834
- [crypto ca trustpool import url clean](#), on page 835
- [crypto ca trustpool policy](#), on page 836
- [crypto cert ssh-authorize](#), on page 837
- [crypto certificatemap mapname](#), on page 838
- [crypto key generate rsa](#), on page 839
- [crypto key param rsa label modulus](#), on page 840
- [crypto key zeroize rsa](#), on page 841
- [cryptographic-algorithm](#), on page 842
- [customer-id](#), on page 843
- [cut](#), on page 844

cabundle url

[no] cabundle url <source_uri>

Syntax Description

no	(Optional) Negate a command or set its defaults
cabundle	Configure cabundle
url	Configure cabundle url
<i>source_uri</i>	Select source http URL

Command Mode

- /exec/configure/trustpool

callhome

callhome

Syntax Description

callhome	Enter the callhome configuration mode
----------	---------------------------------------

Command Mode

- /exec/configure

callhome send configuration

callhome send configuration

Syntax Description

callhome	callhome commands
send	send a command callhome message
configuration	configuration type

Command Mode

- /exec

callhome send diagnostic

callhome send diagnostic

Syntax Description

callhome	callhome commands
send	send a command callhome message
diagnostic	dignostic command

Command Mode

- /exec

callhome test

callhome test

Syntax Description

callhome	callhome commands
test	send a test callhome message

Command Mode

- /exec

callhome test inventory

callhome test inventory

Syntax Description

callhome	callhome commands
test	send a test callhome message
inventory	send a dummy callhome inventory

Command Mode

- /exec

capability additional-paths receive

[no | default] capability additional-paths receive [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
capability	Advertise capability to the peer
additional-paths	Additional paths capability
receive	Additional paths Receive capability
disable	(Optional) Do not advertise additional paths Receive capability

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpn4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpn6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

capability additional-paths send

[no | default] capability additional-paths send [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
capability	Advertise capability to the peer
additional-paths	Additional paths capability
send	Additional paths Send capability
disable	(Optional) Do not advertise additional paths Send capability

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

capability suppress 4-byte-as

[no | default] capability suppress 4-byte-as

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
capability	Capability
suppress	Suppress sending out capability
4-byte-as	Suppress 4-byte AS Capability

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

capability vrf-lite

[no] capability vrf-lite [evpn]

Syntax Description

no	(Optional) Negate a command or set its defaults
capability	Capability
vrf-lite	Enable VRF-lite support
evpn	(Optional) Ethernet VPN

Command Mode

- /exec/configure/router-ospf/vrf

capture

[no] capture { buffer-drops | acl-drops | fwd-drops | blackhole }

Syntax Description

capture	Events to be logged
buffer-drops	Buffer drops
acl-drops	ACL drops
fwd-drops	Forward drops
blackhole	Blackhole

Command Mode

- /exec/configure/config-fte-event/group-drop-events

capture

[no] capture { latency exceeding-threshold <time> { nano-sec | micro-sec | milli-sec } }

Syntax Description

capture	Events to be logged
latency	Latency
exceeding-threshold	Latency threshold limit
<i>time</i>	time range <0-65535>
nano-sec	time in nano seconds
micro-sec	time in micro seconds
milli-sec	time in milli seconds

Command Mode

- /exec/configure/config-fte-event/group-latency-events

capture session

[no] capture session <session-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
capture	Enable packet capture on this filter for session
session	Session ID <1-48> for this session
<i>session-id</i>	Session ID <1-48> for this session

Command Mode

- /exec/configure/ipacl /exec/configure/ipv6acl /exec/configure/macacl /exec/configure/arpacl

carrier-delay

carrier-delay { <sec_val> | msec <msec_val> } | no carrier-delay

Syntax Description

no	Negate a command or set its defaults
carrier-delay	Specify delay for interface transitions
<i>sec_val</i>	Carrier Transitions delay seconds
msec	Carrier Transitions delay milliseconds
<i>msec_val</i>	Carrier Transitions delay milliseconds

Command Mode

- /exec/configure/if-vlan-common

catena

{ catena <instance-name> } | { no catena <instance-name> }

Syntax Description

no	Negate a command or set its defaults
catena	instance
<i>instance-name</i>	instance-name

Command Mode

- /exec/configure

catena device-group

{ catena device-group <device-grp-name> } | { no catena device-group <device-grp-name> }

Syntax Description

no	Negate a command or set its defaults
catena	instance
device-group	device group
<i>device-grp-name</i>	device-grp-name

Command Mode

- /exec/configure

catena port-acl

{ catena port-acl <port-acl-name> } | { no catena port-acl <port-acl-name> }

Syntax Description

no	Negate a command or set its defaults
catena	instance
port-acl	port acl
<i>port-acl-name</i>	port-acl-name

Command Mode

- /exec/configure

catena port-group

```
{ catena port-group <port-group-name> } | { no catena port-group <port-group-name> }
```

Syntax Description

no	Negate a command or set its defaults
catena	instance
port-group	port group
<i>port-group-name</i>	port-group-name

Command Mode

- /exec/configure

catena vlan-group

{ catena vlan-group <vlan-grp-name> } | { no catena vlan-group <vlan-grp-name> }

Syntax Description

no	Negate a command or set its defaults
catena	instance
vlan-group	vlan group
<i>vlan-grp-name</i>	vlan-grp-name

Command Mode

- /exec/configure

cbts-member tunnel-te

[no] cbts-member tunnel-te <tunnel-num>

Syntax Description

no	(Optional) Negate a command or set its defaults
cbts-member	Member Tunnel
tunnel-te	Tunnel Interface
<i>tunnel-num</i>	Tunnel Interface number

Command Mode

- /exec/configure/if-te

cd

cd <uri0>

Syntax Description

cd	Change current directory
<i>uri0</i>	Enter the name of the directory

Command Mode

- /exec

cdp advertise v1

cdp advertise { v1 | v2 } | no cdp advertise [v1 | v2]

Syntax Description

no	Negate a command or set its defaults
cdp	Configure CDP parameters
advertise	Highest CDP version supported on the switch
v1	CDP Version 1
v2	CDP Version 2

Command Mode

- /exec/configure

cdp enable

[no] cdp enable

Syntax Description

no	(Optional) Negate a command or set its defaults
cdp	Configure CDP interface parameters
enable	Enable/disable CDP on all interfaces

Command Mode

- /exec/configure

cdp enable

[no] cdp enable

Syntax Description

no	(Optional) Negate a command or set its defaults
cdp	Configure CDP interface parameters
enable	Enable/disable CDP on the interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

cdp format device-id

[no] cdp format device-id { mac-address | serial-number | system-name }

Syntax Description

no	(Optional) Negate a command or set its defaults
cdp	Configure CDP parameters
format	Device ID format for CDP
device-id	Device ID format for CDP
mac-address	Mac-address of the Chassis
serial-number	Chassis Serial Number/OUI
system-name	System name/Fully Qualified Domain Name (Default)

Command Mode

- /exec/configure

cdp holdtime

[no] cdp holdtime <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
cdp	Configure CDP parameters
holdtime	CDP hold time advertised (in seconds)
<i>i0</i>	CDP hold time advertised (in seconds)

Command Mode

- /exec/configure

cdp timer

[no] cdp timer <i>*i*>

Syntax Description

no	(Optional) Negate a command or set its defaults
cdp	Configure CDP parameters
timer	CDP refresh time interval (in seconds)
<i>i</i>	CDP refresh time interval (in seconds)

Command Mode

- /exec/configure

certificate

certificate <file-name> <host-name> | no certificate

Syntax Description

no	Negate a command or set its defaults
certificate	Specify certificate
<i>file-name</i>	.pem certificate filename
<i>host-name</i>	hostname associated with certificate

Command Mode

- /exec/configure/telemetry

cfs debug all

cfs debug all

Syntax Description

cfs	CFS parameters
debug	Internal command for debugs
all	Internal command for debugs

Command Mode

- /exec

cfs distribute

[no] cfs distribute

Syntax Description

no	(Optional) Negate a command or set its defaults
distribute	Enable fabric wide distribution

Command Mode

- /exec/configure

cfs eth cos

{ cfs eth cos <i0> | no cfs eth cos [<i0>] }

Syntax Description

no	Negate a command or set its defaults
eth	ETH configurations
cos	Configure CFS Ethernet COS value
<i>i0</i>	COS Value Range

Command Mode

- /exec/configure

cfs eth distribute

[no] cfs eth distribute

Syntax Description

no	(Optional) Negate a command or set its defaults
eth	ETH configurations
distribute	Enable CFS distribution over Ethernet

Command Mode

- /exec/configure

cfs ipv4 distribute

[no] cfs ipv4 { distribute | mcast-address <ip0> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv4	IPv4 configurations
distribute	Enable CFS distribution over IPv4
mcast-address	Configure IPv4 multicast address
<i>ip0</i>	Admin scope [239.255/16, 239.192/16-239.251/16]

Command Mode

- /exec/configure

cfs ipv6 distribute

```
[no] cfs ipv6 { distribute | mcast-address <ipv6> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	IPv6 configurations
distribute	Enable CFS distribution over IPv6
mcast-address	Configure IPv6 multicast address

Command Mode

- /exec/configure

cfs region

[no] cfs region <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
region	Regions to limit the distribution scope of application(s)
<i>i0</i>	Region Id

Command Mode

- /exec/configure

chain

```
{ chain <chain-id> } | { no chain <chain-id> }
```

Syntax Description

no	Negate a command or set its defaults
chain	chain for instance
<i>chain-id</i>	chain ID

Command Mode

- /exec/configure/catena

change-password

change-password [old-password <s1> new-password <s2>]

Syntax Description

change-password	Change your password
old-password	(Optional) Current password for the user
<i>s1</i>	(Optional) Current password for the user (clear text)
new-password	(Optional) New password for the user
<i>s2</i>	(Optional) New password for the user (clear text)

Command Mode

- /exec

channel-group

[no] channel-group

Syntax Description

no	Negate a command or set its defaults
channel-group	Configure port channel parameters

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

channel-group

channel-group <channel-id> | no channel-group

Syntax Description

no	Negate a command or set its defaults
channel-group	add to/remove from a port-channel
<i>channel-id</i>	Specify a port-channel number

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-gig-ether /exec/configure/if-fcip

channel-group

```
channel-group <channel-id> [ mode { active | passive | on } ]
```

Syntax Description

channel-group	Configure port channel parameters
mode	(Optional) Specify channeling mode
active	(Optional) Set channeling mode to ACTIVE
passive	(Optional) Set channeling mode to PASSIVE
on	(Optional) Set channeling mode to ON
<i>channel-id</i>	Specify a port-channel number

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

channel-group

[no] channel-group [<channel-id> [mode { active | passive | on }]]

Syntax Description

no	Negate a command or set its defaults
channel-group	Configure port channel parameters
mode	(Optional) Specify channeling mode
active	(Optional) Set channeling mode to ACTIVE
passive	(Optional) Set channeling mode to PASSIVE
on	(Optional) Set channeling mode to ON
<i>channel-id</i>	(Optional) Specify a port-channel number

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

channel-group force

channel-group <channel-id> force [mode { active | passive | on }] | no channel-group <channel-id> force [mode { active | passive | on }]

Syntax Description

no	Negate a command or set its defaults
channel-group	add to/remove from a port-channel
<i>channel-id</i>	Specify a port-channel number
force	Forcefully add a port
mode	(Optional) Specify channeling mode
active	(Optional) Set channeling mode to ACTIVE
passive	(Optional) Set channeling mode to PASSIVE
on	(Optional) Set channeling mode to ON

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

channel-group force

channel-group <channel-id> force

Syntax Description

channel-group	add to/remove from a san-port-channel
<i>channel-id</i>	Specify a san-port-channel number
force	Forcefully add a port

Command Mode

- /exec/configure/if-fc /exec/configure/if-gig-ether /exec/configure/if-fcip

channel mode

[no] channel mode

Syntax Description

no	Negate a command or set its defaults
channel	Set the channel mode for the san-port-channel interface
mode	Set the channel mode for the san-port-channel interface

Command Mode

- /exec/configure/if-san-port-channel

channel mode active

channel mode active | no channel mode active

Syntax Description

no	Negate a command or set its defaults
channel	Set the channel mode for the san-port-channel interface
mode	Set the channel mode for the san-port-channel interface
active	configure ACTIVE san-port-channel

Command Mode

- /exec/configure/if-san-port-channel

chassis-family fretta

[no] chassis-family fretta

Syntax Description

no	(Optional) Negate a command or set its defaults
chassis-family	Configure chassis family type
fretta	Configure chassis family type to Fretta

Command Mode

- /exec/configure

checkpoint

```
checkpoint { [ <name> ] [ description <descr_str> ] | file <file_uri> }
```

Syntax Description

checkpoint	Create configuration rollback checkpoint
<i>name</i>	(Optional) Checkpoint name
file	Create configuration rollback checkpoint to file
<i>file_uri</i>	Checkpoint file path
description	(Optional) checkpoint description for the given checkpoint
<i>descr_str</i>	(Optional) checkpoint description(can include spaces)

Command Mode

- /exec

checkpoint

[no] checkpoint <chkpoint_name>

Syntax Description

no	Negate a command or set its defaults
checkpoint	Delete configuration rollback checkpoint
<i>chkpoint_name</i>	Checkpoint name

Command Mode

- /exec

cipher-suite

[no] cipher-suite <suite>

Syntax Description

cipher-suite	Configure Cipher Suite
<i>suite</i>	Cipher Suite options

Command Mode

- /exec/configure/macsec-policy

class-map

[no] class-map [type qos] [<any_or_all>] <map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	(Optional) Specify the type of this class-map
qos	(Optional) Qos class
<i>any_or_all</i>	(Optional) Enter match-any or match-all
<i>map-name</i>	class-map name

Command Mode

- /exec/configure

class-map type control-plane

[no] class-map type control-plane [<opt_any_or_all>] <map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	Specify the type of this class-map
control-plane	Control-Plane
<i>opt_any_or_all</i>	(Optional) Enter match-any or match-all
<i>map-name</i>	Class-map name

Command Mode

- /exec/configure

class-map type network-qos

[no] class-map type network-qos [match-any] <map-name-nq>

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	Specify the type of this class-map
network-qos	Network QoS class
match-any	(Optional) Match on any criteria
<i>map-name-nq</i>	class-map name

Command Mode

- /exec/configure

class-map type psp

```
[no] class-map type psp [ <any_or_all> ] { <cmap-name-plc> | { handle <ppf_id> } } [ sequence <seq_no> ] [ client <clienttype> <clientID> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	Specify the type of this class-map
psp	PSP class
<i>any_or_all</i>	(Optional) Enter match-any or match-all
<i>cmap-name-plc</i>	class-map name
handle	Handle
<i>ppf_id</i>	PPF ID
sequence	(Optional) sequence
<i>seq_no</i>	(Optional) Sequence number
client	(Optional) set client type
<i>clienttype</i>	(Optional) cli/onep
<i>clientID</i>	(Optional) client appID

Command Mode

- /exec/configure

class-map type queuing

[no] class-map type queuing { <omap-dce-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	Specify the type of this class-map
queuing	Queuing class
<i>omap-dce-name</i>	Queuing class-map name

Command Mode

- /exec/configure

class-map type queuing

```
[no] class-map type queuing [ <any_or_all> ] { xxx <cmap-enum-name> | <cmap-dce-name> | zzz
<cmap-name-hque> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
class-map	Configure a class map
type	Specify the type of this class-map
queuing	Queuing class
<i>any_or_all</i>	(Optional) Enter match-any
<i>cmap-enum-name</i>	
xxx	xxx
zzz	zzz
<i>cmap-dce-name</i>	Queuing class-map name
<i>cmap-name-hque</i>	Hierarchical class-map name

Command Mode

- /exec/configure

class

```
[no] class [ type qos ] < cmap-name > [ insert-before [ type qos1 ] < cmap-name2 > ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Policy Criteria
type	(Optional) Specify the type of class
qos	(Optional) Match on Qos class
<i>cmap-name</i>	class map name
insert-before	(Optional) Insert this class before another class
qos1	(Optional) Insert before Qos class
<i>cmap-name2</i>	(Optional) class map name

Command Mode

- /exec/configure/policy-map

class

```
class { <cmmap-name> [ insert-before <cmmap-name2> ] | class-default } | no class { <cmmap-name> | class-default }  
}
```

Syntax Description

no	Negate a command or set its defaults
class	Attach class map to policy map
<i>cmmap-name</i>	Class-map name
insert-before	(Optional) Insert this class before another class
<i>cmmap-name2</i>	(Optional) class map name before which insertion should happen
class-default	Use class default

Command Mode

- /exec/configure/pmap

class __inline__

[no] class __inline__ [type psp] <omap-name-plc> [insert-before <omap-name2>]

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Policy Criteria
__inline__	Inline Class
type	(Optional) Specify the type of class
psp	(Optional) Match on PSP class
<i>omap-name-plc</i>	class map name
insert-before	(Optional) Insert this class before another class
<i>omap-name2</i>	(Optional) class map name

Command Mode

- /exec/configure/policy-map/type/plc

class class-default

[no] class class-default

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Policy Criteria
class-default	System default class matching otherwise unclassified packets

Command Mode

- /exec/configure/policy-map

class type network-qos

[no] class type network-qos <cmmap-name-nq>

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Match on network-qos class-map
type	Specify the type of this class-map
network-qos	Network QoS policy
<i>cmmap-name-nq</i>	Match class-map name

Command Mode

- /exec/configure/policy-map/type/uf

class type network-qos class-default

[no] class type network-qos class-default

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Match on network-qos class-map
type	Specify the type of this class-map
network-qos	Network QoS policy
class-default	System default class matching otherwise not classified cos values

Command Mode

- /exec/configure/policy-map/type/uf

class type psp

```
[no] class type psp { <omap-name-plc> | { handle1 <ppf_id1> } } [ insert-before { <omap-name2> | { handle2 <ppf_id2> } } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
class	Policy Criteria
type	Specify the type of class
psp	Match on PSP class
<i>omap-name-plc</i>	class map name
handle1	Handle1
<i>ppf_id1</i>	PPF ID1
insert-before	(Optional) Insert this class before another class
<i>omap-name2</i>	(Optional) class map name
handle2	(Optional) Handle2
<i>ppf_id2</i>	(Optional) PPF ID2

Command Mode

- /exec/configure/policy-map/type/plc

class type queuing

```
[no] class type queuing { xxx < cmap-enum-name> | < cmap-dce-name> | zzz < cmap-name-hque> } [
insert-before type queuing1 yyy < xcmap-enum-name> ]
```

Syntax Description

xxx	xxx
yyy	(Optional) yyy
zzz	zzz
no	(Optional) Negate a command or set its defaults
class	Policy Criteria
type	Specify the type of class
queuing	Match on Queuing class
<i>cmap-enum-name</i>	
<i>cmap-dce-name</i>	Queuing class-map name
<i>cmap-name-hque</i>	Hierarchical class-map name
insert-before	(Optional) Insert this class before another class
queuing1	(Optional) Insert before Queuing class
<i>xcmap-enum-name</i>	(Optional)

Command Mode

- /exec/configure/policy-map/type/queuing

clear

```
clear { { ip eigrp [ <eigrp-ptag> ] neighbors { * | <address> | <interface> } [ soft ] [ no-goodbye ] [ vrf {
<vrf-name> | <vrf-known-name> | all } ] } } | { ipv6 eigrp [ <eigrp-ptag> ] neighbors { * | <ipv6-addr> |
<interface> } [ soft ] [ no-goodbye ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
neighbors	Clear EIGRP neighbors
*	Clear all EIGRP neighbors
<i>address</i>	IP-EIGRP neighbor address
<i>interface</i>	Interface
soft	(Optional) Soft reset
no-goodbye	(Optional) No goodbye
<i>eigrp-ptag</i>	(Optional)

Command Mode

- /exec

clear

```
clear { { ip eigrp [ <eigrp-ptag> ] topology { { <address> <mask> } | { <prefix> } } [ vrf { <vrf-name> |
<vrf-known-name> | all } ] } | { ipv6 eigrp [ <eigrp-ptag> ] topology { <ipv6-prefix> } [ vrf { <vrf-name> |
<vrf-known-name> | all } ] } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
topology	Clear IP-EIGRP topology table entry
<i>address</i>	Network to display information about
<i>mask</i>	Network mask
<i>prefix</i>	IP prefix <network>/<length>, e.g., 192.168.0.0/16
<i>eigrp-ptag</i>	(Optional)

Command Mode

- /exec

clear

```
clear { { ipv6 route [ vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } ] } | { routing [ vrf { <vrf-name> | <vrf-known-name> } ] ipv6 [ unicast ] [ topology <topology-name> ] } } { <all> | { { <ipv6-addr> | <ipv6-prefix> } [ <nh-addr> <nh-interface> ] } } [ no-ufdm ]
```

Syntax Description

clear	Reset functions
route	Clear routing information
routing	Clear routing information
vrf	(Optional) Clear per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
ipv6	Clear IPv6 commands
unicast	(Optional) Clear unicast information
topology	(Optional) Clear per-topology information
<i>topology-name</i>	(Optional) Topology name
all	Clear all routes
<i>nh-interface</i>	(Optional) Interface Name
no-ufdm	(Optional) Do not tell UFDm about the change

Command Mode

- /exec

clear

```
clear { { ip route [ vrf { <vrf-name> | <vrf-known-name> | <vrf-all> } ] } | { routing [ vrf { <vrf-name> | <vrf-known-name> } ] [ ip | ipv4 ] [ unicast ] [ topology <topology-name> ] } } { <all> | { { <ip-addr> | <ip-prefix> } [ { [ <nh-addr> | <nh-addr-v6> ] [ <nh-interface> ] } | { <nh-label> } ] } } [ no-ufdm ]
```

Syntax Description

clear	Reset functions
route	Clear routing information
routing	Clear routing information
vrf	(Optional) Clear per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
vrf-all	(Optional) Display information for all VRFs
ip	Clear IP commands
ipv4	(Optional) Clear IP commands
unicast	(Optional) Clear unicast information
topology	(Optional) Clear per-topology information
<i>topology-name</i>	(Optional) Topology name
all	Clear all routes
<i>ip-addr</i>	Clear single host route
<i>ip-prefix</i>	Clear single exact match route
<i>nh-addr</i>	(Optional) Clear single path
<i>nh-label</i>	(Optional) Clear single binding label path
<i>nh-interface</i>	(Optional) Interface Name
no-ufdm	(Optional) Do not tell UFDm about the change

Command Mode

- /exec

clear aaa local user blocked username

```
clear aaa local user blocked { username <s0> | all }
```

Syntax Description

clear	Reset functions
aaa	Configure aaa functions
local	Local username
user	Local system user
blocked	Clear blocked user
username	Blocked username
<i>s0</i>	Enter the username
all	Clear all the blocked users

Command Mode

- /exec

clear access-list counters

```
clear [ <ip_ipv6_mac> ] access-list counters [ <name> ]
```

Syntax Description

clear	Reset functions
<i>ip_ipv6_mac</i>	(Optional) IP/IPv6/MAC
access-list	Clear access list statistical information
counters	Clear access list counters
<i>name</i>	(Optional) List name

Command Mode

- /exec

clear access-list hardware counters

clear access-list hardware counters [module <module>]

Syntax Description

clear	Reset functions
access-list	Clear access list statistical information
hardware	hardware information
counters	Clear access list counters
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

clear access-list ipsg stats

clear access-list ipsg stats [module <module>] [instance <instance_number>]

Syntax Description

clear	Reset functions
access-list	access-list
ipsg	ipsg
stats	Clear Statistics of IPSG drop entries
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number
instance	(Optional) ASIC Instance Number
<i>instance_number</i>	(Optional) ASIC Instance Number in Decimal

Command Mode

- /exec

clear accounting log

clear accounting log

Syntax Description

clear	Reset functions
accounting	Clear accounting log(s) in all vdc's
log	Clear the accounting log(s) in all vdc's

Command Mode

- /exec

clear aclqos cl-qos

clear aclqos cl-qos

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
cl-qos	cl-qos logs of ACLQOS

Command Mode

- /exec

clear aclqos fab

clear aclqos fab

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
fab	Fabric logs of ACLQOS

Command Mode

- /exec

clear aclqos fc

clear aclqos fc

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
fc	fc logs of ACLQOS

Command Mode

- /exec

clear aclqos libdrv

clear aclqos libdrv

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
libdrv	libdrv logs of ACLQOS

Command Mode

- /exec

clear aclqos map

clear aclqos map

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
map	map logs of ACLQOS

Command Mode

- /exec

clear aclqos merge

clear aclqos merge

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
merge	merge logs of ACLQOS

Command Mode

- /exec

clear aclqos pl

clear aclqos pl

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
pl	pl logs of ACLQOS

Command Mode

- /exec

clear aclqos ppf-parse

clear aclqos ppf-parse

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
ppf-parse	ppf-parse logs of ACLQOS

Command Mode

- /exec

clear aclqos ppf

clear aclqos ppf

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
ppf	ppf logs of ACLQOS

Command Mode

- /exec

clear aclqos qng-hw

clear aclqos qng-hw

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
qng-hw	Qng logs of ACLQOS

Command Mode

- /exec

clear aclqos qng

clear aclqos qng

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
qng	Qng logs of ACLQOS

Command Mode

- /exec

clear aclqos rl

clear aclqos rl

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
rl	RL logs of ACLQOS

Command Mode

- /exec

clear aclqos rm

clear aclqos rm

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
rm	RM logs of ACLQOS

Command Mode

- /exec

clear aclqos sch

clear aclqos sch

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
sch	Sch logs of ACLQOS

Command Mode

- /exec

clear aclqos stats

clear aclqos stats

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
stats	stats logs of ACLQOS

Command Mode

- /exec

clear aclqos tbl

clear aclqos tbl

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
tbl	tbl logs of ACLQOS

Command Mode

- /exec

clear aclqos trace-detail

clear aclqos trace-detail

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
trace-detail	detail logs of ACLQOS

Command Mode

- /exec

clear aclqos trace

clear aclqos trace

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
trace	trace logs of ACLQOS

Command Mode

- /exec

clear aclqos uf

clear aclqos uf

Syntax Description

clear	Reset functions
aclqos	Configure aclqos debug
uf	UF logs of ACLQOS

Command Mode

- /exec

clear bfd statistics

clear bfd statistics

Syntax Description

clear	Clear
bfd	bfd
statistics	statistics

Command Mode

- /exec

clear bgp

```
clear bgp { ipv4 { unicast | multicast } policy statistics { { redistribute [ { { eigrp | isis | ospf | rip } <tag> } |
static | direct | amt | lisp | hmm | am ] } | { neighbor <neighbor-id> [ default-originate | { route-map | filter-list
| prefix-list } { in | out } ] } | { dampening } | { network { <ip-addr> mask <ip-mask> | <ip-prefix> } } | {
aggregate-address { <ip-addr> <ip-mask> | <ip-prefix> } { suppress-map | advertise-map } } } | { vpnv4 |
vpnv6 } unicast policy statistics { neighbor <neighbor-id> [ { route-map | filter-list | prefix-list } { in | out
} ] } | ipv6 { unicast | multicast } policy statistics { { redistribute [ { { eigrp | isis | ospfv3 | rip } <tag> } | static
| direct | amt | lisp | hmm | am ] } | { neighbor { <neighbor-id> | <ipv6-neighbor-id> } [ default-originate | {
route-map | filter-list | prefix-list } { in | out } ] } | { dampening } | { network <ipv6-prefix> } | {
aggregate-address <ipv6-prefix> { suppress-map | advertise-map } } } }
```

Syntax Description

clear	Reset functions
ipv4	Clear IPv4 address-family
ipv6	Clear IPv6 address-family
vpnv4	Clear VPNv4 address-family
vpnv6	Clear VPNv6 address-family
bgp	Clear BGP sessions
unicast	Clear unicast address-family
multicast	Clear multicast address-family
policy	Clear policy related information
statistics	Clear Route Filter statistics
redistribute	Statistics for redistribution
isis	(Optional) ISO IS-IS
ospf	(Optional) Open Shortest Path First (OSPF)
ospfv3	(Optional) Open Shortest Path First v3
rip	(Optional) Routing Information Protocol
eigrp	(Optional) Enhanced Interior Gateway Protocol
static	(Optional) Static routes
direct	(Optional) Directly connected
amt	(Optional) AMT anycast prefix
lisp	(Optional) LISP EID-prefixes in the non-default VRF
hmm	(Optional) HMM prefix

am	(Optional) AM routes (learned via ARP)
tag	(Optional) Source protocol tag
neighbor	Clear neighbor specific counters
neighbor-id	Neighbor IPv4 address
route-map	(Optional) Neighbor route-map
prefix-list	(Optional) Neighbor prefix-list
filter-list	(Optional) Neighbor filter-list
out	(Optional) Outbound policy
in	(Optional) Inbound policy
default-originate	(Optional) Default-originate policy
dampening	Clear dampening info
network	Configured IP prefix to advertise
aggregate-address	Configured BGP aggregate prefixes
suppress-map	Statistics of suppress policy
advertise-map	Statistics of advertise policy
ip-addr	IP network advertised
mask	Configured mask of the IP prefix advertised
ip-mask	Dotted 4-octet mask
ip-prefix	IP prefix in CIDR format

Command Mode

- /exec

clear bgp bmp stats server

clear bgp bmp stats server { <server-id> | all }

Syntax Description

clear	Reset functions
bgp	Clear BGP sessions
bmp	Clear BMP
stats	Server Stats
server	BMP Server
<i>server-id</i>	Server ID
all	All BMP Servers

Command Mode

- /exec

clear bgp event-history

clear bgp event-history { <bgp-event-hist> | detail | periodic | errors | objstore | developer | all | msgs }

Syntax Description

clear	Reset functions
bgp	Clear BGP sessions
event-history	Clear event-history buffers
<i>bgp-event-hist</i>	Event History
errors	Show error logs of BGP
objstore	Show objstore logs of BGP
developer	Show developer logs of BGP
periodic	Show periodic logs of BGP
detail	Show detailed event logs
all	All event history buffers
msgs	Clear message logs of BGP

Command Mode

- /exec

clear bgp private

```
clear bgp private { all | global | threads | session | debug | io | memory | af | damp | lists | attr [ <ip-prefix> |
<ipv6-prefix> ] | rpm-info [ <rpm-name> { <ip-prefix> | <ipv6-prefix> } ] | neighbor { <neighbor-id> |
<ipv6-neighbor-id> } | slab | mqstat | ipc | rnh | rpm-attribute-cache | rpm-comm-attr-cache | peer-template
<peer-template-name> | aggregates [ summary ] | bestpath }
```

Syntax Description

clear	Reset functions
bgp	Clear BGP sessions
private	Clear internal BGP counters
all	Clear all info
global	Clear global info
threads	Clear thread info
session	Clear session info
debug	Clear debug info
io	Clear IO info
memory	Clear memory info
af	Clear AF info
damp	Clear dampening info
lists	Clear BGP internal lists
attr	Clear BGP attributes
rpm-info	Clear BGP policy outbound info
<i>ip-prefix</i>	(Optional) Clear attribute for a prefix
neighbor	Clear neighbor specific counters
<i>neighbor-id</i>	Neighbor IP address
<i>rpm-name</i>	(Optional) Route-map name
slab	Clear information about SLABs used
mqstat	Clear message queue stats
ipc	Clear ipc information
rnh	Clear recursive next hops

aggregates	Clear information about aggregates
rpm-attribute-cache	Clear rpm attribute cache statistics
rpm-comm-attr-cache	Clear rpm community attribute cache statistics
peer-template	Clear information about a peer-template
bestpath	Clear internal information about bestpath
summary	(Optional) Summary only
<i>peer-template-name</i>	Peer-template name

Command Mode

- /exec

clear bootvar log

clear bootvar log

Syntax Description

clear	Reset functions
bootvar	Clear the bootvar log
log	Clear the bootvar log

Command Mode

- /exec

clear cdp counters

```
clear cdp { counters [ interface <if0> ] | table [ interface1 <if1> ] }
```

Syntax Description

clear	Reset functions
cdp	Cisco Discovery Protocol
counters	Clear CDP counters on all interfaces
interface	(Optional) Clear CDP counters on an interface
<i>if0</i>	(Optional)
table	Clear CDP cache on all interfaces
interface1	(Optional) Clear CDP cache on an interface
<i>if1</i>	(Optional)

Command Mode

- /exec

clear checkpoint database

clear checkpoint database [user | system]

Syntax Description

clear	Reset functions
checkpoint	Clear configuration rollback checkpoint
database	Clear configuration rollback checkpoint database
user	(Optional) Clear configuration rollback checkpoint database for user checkpoints
system	(Optional) Clear configuration rollback checkpoint database for system checkpoints

Command Mode

- /exec

clear cli history

clear cli history

Syntax Description

clear	Reset functions
cli	debug cli
history	history of cli commands

Command Mode

- /exec

clear controller accounting log

clear controller <ctrl-id> accounting log

Syntax Description

clear	Show running system information
controller	Controller command
<i>ctrl-id</i>	Controller id value
accounting	Accounting
log	Clear log information

Command Mode

- /exec

clear copp statistics

clear copp statistics

Syntax Description

clear	Reset functions
copp	Clear policy information for copp
statistics	Clear statistics

Command Mode

- /exec

clear cores

clear cores

Syntax Description

clear	Reset functions
cores	clear all core dumps for the switch

Command Mode

- /exec

clear cores archive

clear cores archive [file <s0>]

Syntax Description

clear	Reset functions
cores	clear all cores for this vdc
archive	clear all core dump files for this vdc from logflash on this module
file	(Optional) delete a core file on logflash
s0	(Optional) Name of file in directory 'core

Command Mode

- /exec

clear counters

clear counters

Syntax Description

clear	Reset functions
counters	Clear counters

Command Mode

- /exec

clear counters buffers

```
clear counters buffers [ module <module> [ instance <instance> ] ] [ __readonly__ <clear_valid> ]
```

Syntax Description

clear	Reset functions
counters	Clear counters
buffers	Clear system buffer max cell usage counter
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number
instance	(Optional) ASIC Instance Number
<i>instance</i>	(Optional) ASIC Instance Number in Decimal
<u>__readonly__</u>	(Optional) Read Only
<i>clear_valid</i>	(Optional) Clear

Command Mode

- /exec

clear counters interface

clear counters interface <ifid>

Syntax Description

clear	Reset functions
counters	Clear counters
interface	Clear interface counters
<i>ifid</i>	Clear interface counters

Command Mode

- /exec

clear counters interface

clear counters interface <ifindex1>

Syntax Description

clear	Reset functions
counters	Clear counters
interface	Clear interface counters
<i>ifindex1</i>	Clear interface counters

Command Mode

- /exec

clear counters interface

clear counters interface <ifindex>

Syntax Description

clear	Reset functions
counters	Clear counters
interface	Clear interface counters
<i>ifindex</i>	Clear interface counters

Command Mode

- /exec

clear counters interface all

clear counters interface all

Syntax Description

clear	Reset functions
counters	Clear counters
interface	Clear interface counters
all	Clear all interface counters

Command Mode

- /exec

clear counters interface snmp

clear counters interface <ifindex> snmp

Syntax Description

clear	Reset functions
counters	Clear counters
interface	Clear interface counters
<i>ifindex</i>	Clear interface counters
snmp	Clear snmp interface counters

Command Mode

- /exec

clear counters tah-buffers

```
clear counters tah-buffers [ module <module> ] [ { instance <instance> | { unit <unit> slice <slice> } } ]
```

Syntax Description

clear	Reset functions
counters	Clear counters
tah-buffers	Clear system buffer max cell usage counter
instance	(Optional) ASIC Instance Number
<i>instance</i>	(Optional) ASIC Instance Number in Decimal
unit	(Optional) Asic Number
<i>unit</i>	(Optional) Asic Number on the module
slice	(Optional) slice num on asic
<i>slice</i>	(Optional) slice number on asic
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

clear crypto ca trustpool timer

clear crypto ca trustpool timer

Syntax Description

clear	Reset functions
crypto	Set crypto settings
ca	Configure certificate authority related information
trustpool	certificate trustpool
timer	clear trustpool timer

Command Mode

- /exec/

clear debug-logfile

clear debug-logfile <s0>

Syntax Description

clear	Reset functions
debug-logfile	Remove the debug logfile
<i>s0</i>	Provide name of the file

Command Mode

- /exec

clear debug logfile

clear debug logfile <s0>

Syntax Description

clear	Reset functions
debug	Debugging functions
logfile	Remove the debug logfile
<i>s0</i>	Provide name of the file

Command Mode

- /exec

clear dot1x all

```
{ clear dot1x all } | { clear dot1x interface <if> } | { clear dot1x mac <addr> }
```

Syntax Description

clear	Reset functions
dot1x	dot1x configuration commands
all	Authenticator instances on all interfaces
mac	Specific MAC address of the Supplicant
<i>if</i>	target interface
<i>addr</i>	MAC Address

Command Mode

- /exec

clear dot1x stats interface

```
{ clear dot1x stats interface <if> } | { clear dot1x stats mac <addr> }
```

Syntax Description

clear	Reset functions
dot1x	dot1x configuration commands
stats	clear stats
mac	Specific MAC address of the Supplicant
<i>if</i>	target interface
<i>addr</i>	MAC Address

Command Mode

- /exec

clear ecp statistics

clear ecp statistics

Syntax Description

clear	Reset functions
ecp	ECP (Edge Control Protocol)
statistics	Clear ECP Statistics

Command Mode

- /exec

clear eigrp event-history

clear eigrp [<eigrp-ptag>] event-history [cli | notifications | all]

Syntax Description

clear	Reset functions
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Clear the event history buffers
notifications	(Optional) EIGRP Notifications
cli	(Optional) EIGRP CLI related events
all	(Optional) All event history buffers

Command Mode

- /exec

clear evb hosts

```
clear evb { hosts | vsi } [ force-standby ] [ { [ mac <mac-addr> | interface <intf-name> | vlan <vlan-id> | vni
<vni-id> | ip <ip-addr> | ipv6 <ipv6-addr> ] + } ]
```

Syntax Description

clear	Reset functions
evb	EVB (Edge Virtual Bridge)
hosts	Clear EVB host information
vsi	Clear EVB vsi information
force-standby	(Optional) Force to clear standby entries
mac	(Optional) Clear entries by filtering MAC address
<i>mac-addr</i>	(Optional) MAC Address
interface	(Optional) Clear entries by filtering interface
<i>intf-name</i>	(Optional) Interface name
vlan	(Optional) Clear entries by filtering VLAN
<i>vlan-id</i>	(Optional) VLAN ID
vni	(Optional) Clear entries by filtering VNI
<i>vni-id</i>	(Optional) VNI
ip	(Optional) Clear entries by filtering IP address
ipv6	(Optional) Clear entries by filtering IPv6 address
<i>ip-addr</i>	(Optional) IPv4 host address

Command Mode

- /exec

clear evb hosts

clear evb { hosts | vsi } [force-standby] *

Syntax Description

clear	Reset functions
evb	EVB (Edge Virtual Bridge)
hosts	Clear EVB host information
vsi	Clear EVB vsi information
force-standby	(Optional) Force to clear standby entries
*	Clear all entries (Should be a * character)

Command Mode

- /exec

clear evb statistics

clear evb statistics

Syntax Description

clear	Reset functions
evb	EVb (Edge Virtual Bridge)
statistics	Clear EVB Statistics

Command Mode

- /exec

clear fabric database dci vrf node-id

```
clear fabric database dci vrf { <vrf-name> | <vrf-known-name> } node-id <mgmt-ip-address> [ peer-id
<peer-ip-address> ]
```

Syntax Description

clear	Reset functions
fabric	Fabric
database	Fabric Database
dci	DCI profile
vrf	Display per-VRF information
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name
node-id	management ip address of this node
<i>mgmt-ip-address</i>	IP address in CIDR format
peer-id	(Optional) management ip address of peer
<i>peer-ip-address</i>	(Optional) IP address in CIDR format

Command Mode

- /exec

clear fabric database host all vni

```
{ clear fabric database host { all | { vni <vni-id> } | { dot1q <vlan-id> } } [ re-sync ] } | { clear fabric database host vni <vni-id> re-apply } | { clear fabric database client uuid <uuid> }
```

Syntax Description

clear	Reset functions
fabric	
database	
host	Active Host to profile mapping
vni	Virtual Network Identifier
<i>vni-id</i>	
dot1q	Dot1Q Encapsulation
<i>vlan-id</i>	
re-apply	Download new config parameters and re-apply
re-sync	(Optional) Force to sync the host entry
all	Remove all entries
client	Auto-config client
uuid	Auto-config client UUID
<i>uuid</i>	UUID

Command Mode

- /exec

clear fabric database host statistics

clear fabric database host statistics

Syntax Description

clear	Reset functions
fabric	Fabric
database	Fabric Database
host	Auto-configured Hosts
statistics	Statistics

Command Mode

- /exec

clear fabric database include-vrf

clear fabric database include-vrf <vrf-name>

Syntax Description

clear	Reset functions
fabric	
database	
include-vrf	Include VRF name
<i>vrf-name</i>	VRF name

Command Mode

- /exec

clear fabric database statistics

```
clear fabric database statistics [ type { network | profile | cabling | partition | bl-dci } [ server-proto ldap { ipv6
<ipv6addr> | ip <ipaddr> | host <hostname> } [ port <portnum> ] [ vrf { <vrf-name> | <vrf-known-name> }
]]]
```

Syntax Description

clear	Reset functions
fabric	Fabric
database	Clear Fabric Database
statistics	Clear database statistics
type	(Optional) Enter database type
network	(Optional) Network Database
profile	(Optional) Port or Switch Profile Database
cabling	(Optional) Cable Management Database
partition	(Optional) Partition Database
bl-dci	(Optional) Border Leaf - DCI
server-proto	(Optional) Enter database protocol
ldap	(Optional) Use LDAP
ipv6	(Optional) IPv6 address of server
ip	(Optional) IP address of server
<i>ipaddr</i>	(Optional) Enter IP address of server
host	(Optional) Hostname of server
<i>hostname</i>	(Optional) Enter hostname of server
port	(Optional) Port
<i>portnum</i>	(Optional) Enter port number
vrf	(Optional) vrf context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear fabric database statistics type server-proto radius group

clear fabric database statistics type { network | profile | cabling | partition | bl-dci } server-proto radius group <groupname>

Syntax Description

clear	Reset functions
fabric	Fabric
database	Clear Fabric Database
statistics	Clear database statistics
type	Enter database type
network	Network Database
profile	Port or Switch Profile Database
cabling	Cable Management Database
partition	Partition Database
bl-dci	Border Leaf - DCI
server-proto	Enter database protocol
radius	Use RADIUS
group	AAA group
<i>groupname</i>	Enter AAA group name of servers

Command Mode

- /exec

clear fabric database statistics type server-proto xmpp ip

```
clear fabric database statistics type { network | profile | cabling | partition | bl-dci } server-proto xmpp { ip
<ipaddr> | host <hostname> } [ port <portnum> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
fabric	Fabric
database	Clear Fabric Database
statistics	Clear database statistics
type	Enter database type
network	Network Database
profile	Port or Switch Profile Database
cabling	Cable Management Database
partition	Partition Database
bl-dci	Border Leaf - DCI
server-proto	Enter database protocol
xmpp	Use XMPP
ip	IP address of server
<i>ipaddr</i>	Enter IP address of server
host	Hostname of server
<i>hostname</i>	Enter hostname of server
port	(Optional) Port
<i>portnum</i>	(Optional) Enter port number
vrf	(Optional) vrf context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear fabric multicast event-history

clear fabric multicast event-history [<ngmvpn-event-hist-buf-name>]

Syntax Description

clear	Reset functions
fabric	Fabric
multicast	Multicast information
event-history	Clear event history buffers
<i>ngmvpn-event-hist-buf-name</i>	(Optional) Event history buffer instance

Command Mode

- /exec

clear fc2

clear fc2 [counters]

Syntax Description

clear	Reset functions
fc2	Clear FC2 Port Counters
counters	(Optional) Clear All FC2/FCoE Port Counters

Command Mode

- /exec

clear fctimer session

clear fctimer session

Syntax Description

clear	Reset functions
fctimer	clear fctimer cfs session
session	abort an existing cfs session

Command Mode

- /exec

clear flow cache

clear flow cache [ipv4 | ipv6 | ce] [force-export]

Syntax Description

clear	Reset functions
flow	NetFlow information
cache	Clear only cache contents
ipv4	(Optional) Show ipv4 cache entries
ipv6	(Optional) Show ipv6 cache entries
ce	(Optional) Show ce cache entries
force-export	(Optional) Force the cache entries to be exported

Command Mode

- /exec

clear flow cache

clear flow cache [ipv4 | ipv6 | ce] [force-export]

Syntax Description

clear	Reset functions
flow	NetFlow information
cache	Clear only cache contents
ipv4	(Optional) Show ipv4 cache entries
ipv6	(Optional) Show ipv6 cache entries
ce	(Optional) Show ce cache entries
force-export	(Optional) Force the cache entries to be exported

Command Mode

- /exec

clear flow exporter

```
clear flow exporter { [ name ] <exportername> | all }
```

Syntax Description

clear	Reset functions
flow	NetFlow information
exporter	Clear NetFlow exporter statistics
name	(Optional) The name of the exporter
<i>exportername</i>	Specify an exporter
all	Clear all exporter statistics

Command Mode

- /exec

clear forwarding adjacency module

```
clear forwarding [ ip | ipv4 ] { adjacency } [ vrf <vrf-name> ] { <ip-addr> | all_routes } module { all_modules
| <module> } [ force-delete ] [ no-urib ]
```

Syntax Description

clear	
forwarding	forwarding information
ip	(Optional) ipv4
ipv4	(Optional) ipv4
adjacency	adjacency
vrf	(Optional) delete routes for a specific vrf
<i>vrf-name</i>	(Optional) VRF name
<i>ip-addr</i>	IPV4 source address
all_routes	delete all routes
module	module
all_modules	all module's
<i>module</i>	module number
no-urib	(Optional) Do not tell URIB about changes
force-delete	(Optional) Forcefully remove adj

Command Mode

- /exec

clear forwarding cumulative counter

clear forwarding cumulative counter [all | v4_ucast_add | v4_ucast_del | v6_ucast_add | v6_ucast_del] [module <module>]

Syntax Description

clear	clear
forwarding	forwarding information
cumulative	accumulated prefix add/delete count
counter	counter
all	(Optional) all
v4_ucast_add	(Optional) IPv4 unicast route add count
v4_ucast_del	(Optional) IPv4 unicast route delete count
v6_ucast_add	(Optional) IPv6 unicast route add count
v6_ucast_del	(Optional) IPv6 unicast route delete count
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding distribution lisp counters all

clear forwarding distribution lisp counters all

Syntax Description

clear	
forwarding	forwarding
distribution	fib distribution information
lisp	lisp application
counters	counters
all	all vrf's

Command Mode

- /exec

clear forwarding events-history

clear forwarding events-history

Syntax Description

clear	Reset functions
forwarding	forwarding
events-history	Events history

Command Mode

- /exec

clear forwarding inconsistency

clear forwarding [ipv4 | ip] [unicast] inconsistency

Syntax Description

clear	clear
forwarding	forwarding
ip	(Optional) ipv4
ipv4	(Optional) ipv4
unicast	(Optional) unicast
inconsistency	route inconsistency check

Command Mode

- /exec

clear forwarding ipv4 multicast counters

```
clear forwarding ipv4 multicast counters [ vrf { <vrf-name> | <vrf-known-name> | all } ] { [ group <gaddr>
[ source <saddr> ] ] | [ source <saddr> [ group <gaddr> ] ] } [ module <module> ]
```

Syntax Description

clear	
forwarding	fib information
vrf	(Optional) Specify VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ipv4	Ipv4
multicast	Multicast IPv4 information
counters	
group	(Optional) Multicast IPv4 Group specific info
<i>gaddr</i>	(Optional) Multicast IPv4 Group Address
source	(Optional) Multicast IPv4 Source specific info
<i>saddr</i>	(Optional) Multicast IPv4 Source Address
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding ipv6-l3-route-history

clear forwarding ipv6-l3-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
ipv6-l3-route-history	IPV6 L3 Route history

Command Mode

- /exec

clear forwarding ipv6 adjacency module

```
clear forwarding ipv6 adjacency [ vrf <vrf-name> ] { <ip-addr> | all_adj } module { all_modules | <module>
} [ force-delete ] [ no-urib ]
```

Syntax Description

clear	
forwarding	forwarding information
ipv6	ipv6
adjacency	adjacency
vrf	(Optional) delete routes for a specific vrf
<i>vrf-name</i>	(Optional) VRF name
all_adj	delete all adj
module	module
all_modules	all module's
<i>module</i>	module number
no-urib	(Optional) Do not tell URIB about changes
force-delete	(Optional) Forcefully remove adj

Command Mode

- /exec

clear forwarding ipv6 inconsistency

clear forwarding ipv6 [unicast] inconsistency

Syntax Description

clear	clear
forwarding	forwarding
ipv6	ipv6
unicast	(Optional) unicast
inconsistency	route inconsistency check

Command Mode

- /exec

clear forwarding ipv6 multicast counters

```
clear forwarding ipv6 multicast counters [ vrf { <vrf-name> | <vrf-known-name> | all } ] { [ group <gaddr>
[ source <saddr> ] ] | [ source <saddr> [ group <gaddr> ] ] } [ module <module> ]
```

Syntax Description

clear	
forwarding	fib information
vrf	(Optional) Specify VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ipv6	Ipv6
multicast	Multicast IPv6 information
counters	
group	(Optional) Multicast IPv6 Group specific info
source	(Optional) Multicast IPv6 Source specific info
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding ipv6 route module

```
clear forwarding ipv6 { route } [ vrf <vrf-name> ] { <prefix> | all_routes } module { all_modules | <module> } [ no-urib ]
```

Syntax Description

clear	
forwarding	forwarding information
ipv6	ipv6
route	route
vrf	(Optional) delete routes for a specific vrf
<i>vrf-name</i>	(Optional) VRF name
all_routes	delete all routes
module	module
all_modules	all module's
<i>module</i>	module number
no-urib	(Optional) Do not tell URIB about changes

Command Mode

- /exec

clear forwarding l2-mc-route-history

clear forwarding l2-mc-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
l2-mc-route-history	L2 MacgRoute history

Command Mode

- /exec

clear forwarding l2-oiflist-history

clear forwarding l2-oiflist-history

Syntax Description

clear	Reset functions
forwarding	forwarding
l2-oiflist-history	L2 Oiflist history

Command Mode

- /exec

clear forwarding l2-route-history

clear forwarding l2-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
l2-route-history	L2 Route history

Command Mode

- /exec

clear forwarding l2mcast info l2-mc-route-history

clear forwarding l2mcast info l2-mc-route-history [module <num>]

Syntax Description

clear	Reset functions
forwarding	forwarding
l2mcast	l2mcast
info	L2mcast Internal Info
l2-mc-route-history	L2 Macg Route history
module	(Optional) Slot
<i>num</i>	(Optional) Slot number

Command Mode

- /exec

clear forwarding l2mcast info l2-oiflist-history

clear forwarding l2mcast info l2-oiflist-history [module <num>]

Syntax Description

clear	Reset functions
forwarding	forwarding
l2mcast	l2mcast
info	L2mcast Internal Info
l2-oiflist-history	L2 oiflist history
module	(Optional) Slot
<i>num</i>	(Optional) Slot number

Command Mode

- /exec

clear forwarding l2mcast info l2-route-history

clear forwarding l2mcast info l2-route-history [module <num>]

Syntax Description

clear	Reset functions
forwarding	forwarding
l2mcast	l2mcast
info	L2mcast Internal Info
l2-route-history	L2 Route history
module	(Optional) Slot
<i>num</i>	(Optional) Slot number

Command Mode

- /exec

clear forwarding l2mcast info l2-xbar-history

clear forwarding l2mcast info l2-xbar-history [module <num>]

Syntax Description

clear	Reset functions
forwarding	forwarding
l2mcast	l2mcast
info	L2mcast Internal Info
l2-xbar-history	L2 Route history
module	(Optional) Slot
<i>num</i>	(Optional) Slot number

Command Mode

- /exec

clear forwarding l2mcast info statistics

clear forwarding l2mcast info statistics [module <num>]

Syntax Description

clear	Clear all entries
forwarding	Forwarding Information
l2mcast	Layer-2 multicast
info	L2mcast Internal Info
statistics	L2mcast Internal Info Statistics
module	(Optional) Slot
<i>num</i>	(Optional) Slot number

Command Mode

- /exec

clear forwarding l2vpn trace member-history

clear forwarding l2vpn trace member-history

Syntax Description

clear	Reset functions
forwarding	forwarding
l2vpn	L2VPN
trace	internal trace
member-history	member history

Command Mode

- /exec

clear forwarding l3-route-history

clear forwarding l3-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
l3-route-history	L3 Route history

Command Mode

- /exec

clear forwarding oiflist-history

clear forwarding oiflist-history

Syntax Description

clear	Reset functions
forwarding	forwarding
oiflist-history	Oiflist history

Command Mode

- /exec

clear forwarding route module

```
clear forwarding [ ip | ipv4 ] { route } [ vrf <vrf-name> ] { <prefix> | all_routes } module { all_modules |
<module> } [ no-urib ]
```

Syntax Description

clear	
forwarding	forwarding information
ip	(Optional) ipv4
ipv4	(Optional) ipv4
route	route
vrf	(Optional) delete routes for a specific vrf
<i>vrf-name</i>	(Optional) VRF name
<i>prefix</i>	delete specific prefix
all_routes	delete all routes
module	module
all_modules	all module's
<i>module</i>	module number
no-urib	(Optional) Do not tell URIB about changes

Command Mode

- /exec

clear forwarding trace ecmp-history

clear forwarding trace ecmp-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
ecmp-history	ECMP history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace mfib oif-history

clear forwarding trace mfib oif-history

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
mfib	mfib entries
oif-history	oif history

Command Mode

- /exec

clear forwarding trace mfib oiflist-history

clear forwarding trace mfib oiflist-history

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
mfib	mfib entries
oiflist-history	oiflist history

Command Mode

- /exec

clear forwarding trace mfib platform oiflist-history

clear forwarding trace mfib platform oiflist-history

Syntax Description

clear	Clear
forwarding	Forwarding information
trace	internal trace
mfib	mfib entries
platform	platform information
oiflist-history	Oiflist history

Command Mode

- /exec

clear forwarding trace mfib v4-route-history

clear forwarding trace mfib v4-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
mfib	clear mfib entries
v4-route-history	v4 route history

Command Mode

- /exec

clear forwarding trace mfib v6-route-history

clear forwarding trace mfib v6-route-history

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
mfib	mfib entries
v6-route-history	v6 route history

Command Mode

- /exec

clear forwarding trace v4-adj-history

clear forwarding trace v4-adj-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v4-adj-history	V4 adjacency history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace v4-pfx-history

clear forwarding trace v4-pfx-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v4-pfx-history	V4 prefix history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace v4-rnh-history

clear forwarding trace v4-rnh-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v4-rnh-history	V4 rnh history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace v6-adj-history

clear forwarding trace v6-adj-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v6-adj-history	V6 adjacency history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace v6-pfx-history

clear forwarding trace v6-pfx-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v6-pfx-history	V6 prefix history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace v6-rnh-history

clear forwarding trace v6-rnh-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
v6-rnh-history	V6 rnh history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear forwarding trace vobj-history

clear forwarding trace vobj-history [module <module>]

Syntax Description

clear	Reset functions
forwarding	forwarding
trace	internal trace
vobj-history	vobj history
module	(Optional) slot
<i>module</i>	(Optional) slot number

Command Mode

- /exec

clear frame traffic

clear frame traffic

Syntax Description

clear	Reset functions
frame	Clear layer-2 frame statistics to/from the Route Processor
traffic	Clear layer-2 frame statistics to/from the Route Processor

Command Mode

- /exec

clear fs-daemon log

clear fs-daemon log

Syntax Description

clear	Reset functions
fs-daemon	Clear the fs daemon log
log	Clear the fs daemon log

Command Mode

- /exec

clear hardware flow ip

```
clear hardware flow ip [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } | { interface
<interface> } } ] [ instance <inst> ] [ force-export ] [ module <num> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
flow	Netflow Module
ip	Internet Protocol Version 4
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface Name
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
force-export	(Optional) Force to export data to collector
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

Command Mode

- /exec

clear hardware flow ipv6

```
clear hardware flow ipv6 [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } | { interface
<interface> } } ] [ instance <inst> ] [ force-export ] [ module <num> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
flow	Netflow Module
ipv6	Internet Protocol Version 6
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface Name
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
force-export	(Optional) Force to export data to collector
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

Command Mode

- /exec

clear hardware flow l2

```
clear hardware flow l2 [ { { monitor <mname> } | { profile <prof_id> } | { vlan <vlan_id> } } ] [ instance
<inst> ] [ force-export ] [ module <num> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
flow	Netflow Module
l2	Layer 2 Protocol
monitor	(Optional) Netflow Flow Monitor
<i>mname</i>	(Optional) Netflow Flow Monitor Name
profile	(Optional) Flow Profile
<i>prof_id</i>	(Optional) Netflow Profile ID
vlan	(Optional) Vlan commands
<i>vlan_id</i>	(Optional) VLAN ID 1-4094
instance	(Optional) Instance
<i>inst</i>	(Optional) Earl Instance
force-export	(Optional) Force to export data to collector
module	(Optional) Line card module
<i>num</i>	(Optional) slot number

Command Mode

- /exec

clear hardware ip verify

```
clear hardware [ forwarding ] ip verify { all | address { source { broadcast | multicast } | class-e | destination
{ zero } | identical | reserved } | checksum | protocol | fragment | length { minimum | consistent | maximum {
max-frag | udp | max-tcp } } | tcp { tiny-frag } | version } [ module <module> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
forwarding	(Optional) Show hardware information for forwarding path
ip	IPv4 and IPv6 protocols
verify	IP packet validation checks in hardware
class-e	Class E IDS check
all	All IP packet validation checks
address	IPv4 and IPv6 Source and destination address validation
source	Check source address
broadcast	Source address is 255.255.255.255
multicast	Source address is 224.x.x.x
destination	Check destination address
zero	Destination address is 0.0.0.0
identical	Same IP SA and DA
reserved	Source address is 127.x.x.x
checksum	Verify IPv4 and IPv6 packet checksum
protocol	Verify IP protocol
fragment	Check IPv4 and IPv6 fragment with non-zero offset and DF bit active
length	Validate IPv4 packet header and payload length
minimum	Minimum IPv4 header length
consistent	Actual frame size is equal to or more than IPv4 length plus ethernet header
maximum	Check max fragment offset and payload length
max-frag	Fragment offset field value

udp	Maximum UDP length has to be less than IPv4 payload length
max-tcp	Maximum TCP length has to be less than IPv4 payload length
tcp	Validate TCP packet header
tiny-frag	Check TCP tiny fragment
version	Must be 4 for an ethertype of IPv4 (0x0800)
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec

clear hardware profile buffer monitor

clear hardware profile buffer monitor

Syntax Description

clear	Reset functions
hardware	Clear hardware profile buffer monitor data
profile	profile buffer monitor data
buffer	buffer
monitor	buffer monitor

Command Mode

- /exec

clear hardware profile latency monitor

clear hardware profile latency monitor [interface <intf-num>]

Syntax Description

clear	Reset functions
hardware	Clear hardware profile latency monitor data
profile	profile latency monitor data
latency	latency
monitor	latency monitor
interface	(Optional) clear per-interface latency monitor data
<i>intf-num</i>	(Optional) clear per-interface latency monitor data

Command Mode

- /exec

clear hardware profile packet-drop file_instance

clear hardware profile packet-drop file_instance

Syntax Description

clear	Reset functions
hardware	Change hardware usage settings
profile	Profile settings
packet-drop	Packet Drop parameters
file_instance	TCB File instances

Command Mode

- /exec

clear hardware rate-limiter

```
clear hardware rate-limiter { all | layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 <l2-opts> | <opts>
| f1 <f1-opts> | span-egress | urpf-fail } [ module <module> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
rate-limiter	Clear Rate-Limiter statistics
all	Clear all Rate-Limiter statistics
layer-3	Layer-3 control and Routed packets
<i>l3-opts</i>	
multicast	Multicast data packets
<i>mcast-opts</i>	
layer-2	Layer-2 control and Bridged packets
<i>l2-opts</i>	
<i>opts</i>	
f1	Control packets from F1 modules to supervisor
<i>f1-opts</i>	
span-egress	SPAN/ERSPAN egress packets
urpf-fail	URPF fail packets
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec

clear hardware rate-limiter

```
clear hardware rate-limiter { all | layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 <l2-opts> | <opts>
| fl <fl-opts> | span-egress | urpf-fail } [ module <module> ]
```

Syntax Description

clear	Reset functions
hardware	Show hardware information
rate-limiter	Clear Rate-Limiter statistics
all	Clear all Rate-Limiter statistics
layer-3	Layer-3 control and Routed packets
<i>l3-opts</i>	
multicast	Multicast data packets
<i>mcast-opts</i>	
layer-2	Layer-2 control and Bridged packets
<i>l2-opts</i>	
<i>opts</i>	
fl	Control packets from F1 modules to supervisor
<i>fl-opts</i>	
span-egress	SPAN/ERSPAN egress packets
urpf-fail	URPF fail packets
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec

clear hsrp counters clear hsrp state-history

clear hsrp counters [<value>] | clear hsrp state-history [interface <interface-id>] [group <group-id>]

Syntax Description

clear	Reset functions
hsrp	HSRP commands
counters	Internal counters
<i>value</i>	(Optional) Counter to be cleared
state-history	Clear Groups' state history
interface	(Optional) Groups on this interface
<i>interface-id</i>	(Optional) Interface
group	(Optional) Group number
<i>group-id</i>	(Optional) Group Number

Command Mode

- /exec

clear install all failed-standby

clear install all failed-standby

Syntax Description

clear	Reset functions
install	Clear the installer log
all	Clear the install all log
failed-standby	Clear the failed-standby log

Command Mode

- /exec

clear install failure-reason

clear install failure-reason

Syntax Description

clear	Reset functions
install	Clear the installer log
failure-reason	Clear the install failure-reason log

Command Mode

- /exec

clear install log-history all

clear install log-history { all | oldest <i0> }

Syntax Description

clear	Reset functions
install	Install related show commands
log-history	Patch installer historical logs
all	Delete complete history log
oldest	oldest Delete the oldest <n> install log-history points
<i>i0</i>	Number of log-history points to delete

Command Mode

- /exec

clear install status

clear install status

Syntax Description

clear	Reset functions
install	Clear the installer log
status	Clear the installer status log

Command Mode

- /exec

clear ip

```
clear ip { netstack mroute | mroute data-created } { <all> | <group-prefix> | <group> [ <source> ] } [ vrf {
<vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
netstack	Netstack's local cache
mroute	Clear multicast routing table
data-created	Clear all Data-created PIM ASM (S,G) routes
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all sources matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip adjacency statistics

clear ip adjacency statistics

Syntax Description

clear	Reset functions
ip	Clear IP commands
adjacency	Clear Adjacency
statistics	Clear Adjacency Statistics

Command Mode

- /exec

clear ip amt tunnel

```
clear ip amt tunnel [ <address4> <port> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

<i>clear</i>	AMT clear commands
<i>amt</i>	AMT show commands
<i>ip</i>	Display IP information
<i>tunnel</i>	Display tunnel information
<i>vrf</i>	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>address4</i>	(Optional) IP address of tunnel endpoint
<i>port</i>	(Optional) UDP port number of gateway

Command Mode

- /exec

clear ip arp

```
clear ip arp [ <interface> | <ip-address> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ force-delete ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Clear ARP table and statistics
<i>interface</i>	(Optional) ARP interface
<i>ip-address</i>	(Optional) IP address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Clear ARP entries for all vrfs
force-delete	(Optional) Clear the entries from ARP table without refresh

Command Mode

- /exec

clear ip arp controller-statistics

clear ip arp controller-statistics

Syntax Description

clear	Reset functions
ip	Display IP information
arp	Display ARP table and statistics
controller-statistics	Controller statistics

Command Mode

- /exec

clear ip arp inspection log

clear ip arp inspection log

Syntax Description

clear	Reset functions
ip	Clear ip counters
arp	Clear State of ARP features
inspection	Clear State of ARP Inspection
log	Log Buffer

Command Mode

- /exec

clear ip arp inspection statistics vlan

clear ip arp inspection statistics vlan <vlan-id>

Syntax Description

clear	Reset functions
ip	Clear ip counters
arp	Clear State of ARP features
inspection	Clear State of ARP Inspection
statistics	Statistics
vlan	Vlan range
<i>vlan-id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec

clear ip arp multihoming-statistics

```
clear ip arp multihoming-statistics [ <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Clear ARP table and statistics
<i>interface</i>	(Optional) ARP interface
multihoming-statistics	Display ARP Multihoming stats
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Clear ARP Multihoming statistics for all vrfs

Command Mode

- /exec

clear ip arp statistics

```
clear ip arp statistics [ <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Clear ARP table and statistics
<i>interface</i>	(Optional) ARP interface
statistics	Clear ARP statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Clear ARP statistics for all vrfs

Command Mode

- /exec

clear ip arp suppression-cache statistics

clear ip arp suppression-cache statistics

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Clear ARP table and statistics
suppression-cache	ARP-suppression cache
statistics	clear suppression statistics

Command Mode

- /exec

clear ip arp tunnel-statistics

clear ip arp tunnel-statistics

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Display ARP table and statistics
tunnel-statistics	Clear ARP statistics for tunneled packets

Command Mode

- /exec

clear ip arp vpc-statistics

clear ip arp vpc-statistics

Syntax Description

clear	Reset functions
ip	Clear IP commands
arp	Display ARP table and statistics
vpc-statistics	Clear ARP vPC statistics

Command Mode

- /exec

clear ip dhcp global statistics

clear ip dhcp global statistics

Syntax Description

clear	Reset functions
ip	Clear ip counters
dhcp	Clear State of DHCP features
global	Clear State of DHCP global stats
statistics	DHCP snooping statistics

Command Mode

- /exec

clear ip dhcp relay statistics

```
clear ip dhcp relay statistics [ interface <intf> | { interface <intf> serverip <ip-addr-val> [ use-vrf <vrf-name> ] } ]
```

Syntax Description

clear	Reset functions
ip	Clear ip counters
dhcp	Clear State of DHCP features
relay	Clear State of DHCP relay stats
statistics	DHCP Relay statistics
interface	(Optional) input interface
<i>intf</i>	(Optional) interface
serverip	(Optional) Helper address
<i>ip-addr-val</i>	(Optional) IP address
use-vrf	(Optional) helper address VRF membership
<i>vrf-name</i>	(Optional) VRF name

Command Mode

- /exec

clear ip dhcp snooping binding

clear ip dhcp snooping binding [{ vlan <vlan-id> mac <mac-addr> ip <ip-addr> interface <interface-id> } |

Syntax Description

clear	Reset functions
ip	Clear ip counters
dhcp	Clear State of DHCP features
snooping	Clear State of DHCP Snooping
binding	DHCP snooping bindings
vlan	(Optional) VLAN
<i>vlan-id</i>	(Optional) VLAN id
mac	(Optional) MAC address
<i>mac-addr</i>	(Optional) MAC address
ip	(Optional) IP address
<i>ip-addr</i>	(Optional) IP address
interface	(Optional) interface
<i>interface-id</i>	(Optional) interface

Command Mode

- /exec

clear ip dhcp snooping statistics

```
clear ip dhcp snooping statistics [ { vlan <vlan-id> interface <intf> } ]
```

Syntax Description

clear	Reset functions
ip	Clear ip counters
dhcp	Clear State of DHCP features
snooping	Clear State of DHCP snooping stats
statistics	DHCP snooping statistics
vlan	(Optional) VLAN
<i>vlan-id</i>	(Optional) VLAN id
interface	(Optional) input interface
<i>intf</i>	(Optional) interface

Command Mode

- /exec

clear ip eigrp accounting

clear { ip | ipv6 } eigrp [<eigrp-ptag>] accounting [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
accounting	Clear IP-EIGRP accounting statistics

Command Mode

- /exec

clear ip eigrp event-history

```
clear { ip | ipv6 } eigrp [ <eigrp-ptag> ] event-history [ fsm | packet | rib | all ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Clear the event history buffers
fsm	(Optional) FSM log of EIGRP
packet	(Optional) Packet log of EIGRP
rib	(Optional) RIB log of EIGRP
all	(Optional) All event history buffers

Command Mode

- /exec

clear ip eigrp event-history bfd

clear { ip | ipv6 } eigrp [<eigrp-ptag>] event-history bfd

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Clear the event history buffers
bfd	Show bfd log of EIGRP

Command Mode

- /exec

clear ip eigrp redistribution

```
clear { ip | ipv6 } eigrp [ <eigrp-ptag> ] redistribution [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
redistribution	Clear EIGRP redistributed information

Command Mode

- /exec

clear ip eigrp route-map statistics redistribute

```
clear ip eigrp [ <eigrp-ptag> ] route-map statistics redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> |
static | direct | amt | lisp } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
route-map	Route-map related information
statistics	Route-map statistics
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT Anycast prefix
lisp	LISP EID-prefixes

Command Mode

- /exec

clear ip eigrp traffic

```
clear { ip | ipv6 } eigrp [ <eigrp-ptag> ] traffic [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
traffic	Clear IP-EIGRP traffic statistics

Command Mode

- /exec

clear ip igmp event-history

clear ip igmp event-history [<igmp-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP related information
event-history	Clear event-history buffers
<i>igmp-event-hist-buf-name</i>	(Optional) Event hist buffer name

Command Mode

- /exec

clear ip igmp groups

```
clear ip igmp { groups | route } { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> |
<vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP related information
groups	Route information
route	Route information
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip igmp interface statistics

clear ip igmp interface statistics [<interface>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP statistics information
interface	Interface related information
statistics	Packet/internal counter statistics
<i>interface</i>	(Optional) Specific interface only

Command Mode

- /exec

clear ip igmp snooping event-history

clear ip igmp snooping event-history [<igmp-snoop-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
event-history	Clear event history buffers
<i>igmp-snoop-event-hist-buf-name</i>	(Optional) Event history buffer name

Command Mode

- /exec

clear ip igmp snooping explicit-tracking

```
clear ip igmp snooping explicit-tracking { vlan { <vlan> | all } | bridge-domain { <bdid> | all } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
explicit-tracking	Clear Explicit Host tracking information
vlan	Clear explicit tracking information for VLAN
<i>vlan</i>	Specify VLAN
bridge-domain	Clear explicit tracking information for BD
<i>bdid</i>	Specify BD
all	Clear for all vlans/BD

Command Mode

- /exec

clear ip igmp snooping groups

```
clear ip igmp snooping groups { <all> | { <group-prefix> | <group> } [ <source> ] } [ interface <if-name> ]
{ vlan { <vlan> | all } | bridge-domain { <bdid> | all } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
groups	Clear snooped groups
all	Clear all groups
<i>group-prefix</i>	Group prefix to clear
<i>group</i>	Group address to clear
<i>source</i>	(Optional) Source address to clear
interface	(Optional) Specify interface to clear group state
<i>if-name</i>	(Optional) Interface name to clear
vlan	Clear information for VLAN
<i>vlan</i>	Specify the VLAN number
bridge-domain	Clear information for BD
<i>bdid</i>	Specify the BD number
all	Clear for all VLAN/BDs

Command Mode

- /exec

clear ip igmp snooping proxy querier ports vlan

clear ip igmp snooping proxy querier ports { vlan <vlan> | bridge-domain <bdid> } <if-name> [purge]

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
proxy	Clear IGMP snooping proxy
querier	Clear IGMP snooping proxy querier
ports	Clear IGMP snooping proxy querier ports
vlan	Clear for a specific vlan
<i>vlan</i>	Specify the VLAN number
bridge-domain	Clear for a specific BD
<i>bdid</i>	Specify the BD number
<i>if-name</i>	Interface name to clear
purge	(Optional) Remove port from priority list

Command Mode

- /exec

clear ip igmp snooping report statistics

```
clear ip igmp snooping { report-policy | access-group } statistics [ vlan <vlan> ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
report-policy	IGMP Report Policy
access-group	IGMP access-group
statistics	Policy statistics
vlan	(Optional) Clear VLAN IGMP snooping policy statistics information
<i>vlan</i>	(Optional) Specify VLAN

Command Mode

- /exec

clear ip igmp snooping statistics

```
clear ip igmp snooping statistics { vlan <vlan> | bridge-domain <bidid> | all }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
igmp	Clear IGMP Snooping
snooping	Clear IGMP Snooping
statistics	Packet/internal counter statistics
vlan	Clear VLAN statistics
<i>vlan</i>	Specify VLAN
bridge-domain	Clear BD statistics
<i>bidid</i>	Specify BD
all	All VLAN/BDs

Command Mode

- /exec

clear ip interface statistics

clear ip interface statistics [<interface>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
interface	Clear IP related interface information
statistics	Clear IP interface statistics
<i>interface</i>	(Optional) Clear IP statistics for interface

Command Mode

- /exec

clear ip lisp data-cache

```
clear ip lisp data-cache [ <eid> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
lisp	LISP clear commands
data-cache	Clear EID-to-RLOC data cache mapping in this ITR
<i>eid</i>	(Optional) Clear mapping for IP destination EID
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ip lisp map-cache

```
{ { clear ip lisp map-cache [ <eid-prefix> ] [ vrf { <vrf-name> | <vrf-known-name> } ] } | { clear ipv6 lisp map-cache [ <eid-prefix6> ] [ vrf { <vrf-name> | <vrf-known-name> } ] } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ipv6	Clear IPv6 commands
lisp	LISP clear commands
map-cache	Clear an EID-to-RLOC cache mapping in this ITR
vrf	(Optional) Clear entry for particular vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>eid-prefix</i>	(Optional) Clear entry associated with IP EID-prefix

Command Mode

- /exec

clear ip lisp statistics

```
clear ip lisp statistics [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
lisp	LISP clear commands
statistics	Clear global LISP statistics
vrf	(Optional) Clear statistics for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ip mbgp dampening

```
{ { clear ip mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] dampening
[ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] dampening [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp [
vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] ipv4 { unicast | multicast }
dampening [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] all dampening } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] ipv4 { unicast | multicast } | vpv4 unicast } dampening [ <ip-prefix>
| <ip-addr> [ <ip-mask> ] ] } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] ipv6 { unicast | multicast } | vpv6 unicast } dampening [ <ipv6-prefix>
] ] } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] all dampening
} } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
bgp	Clear BGP sessions
mbgp	Clear MBGP sessions
dampening	Clear route flap dampening information
<i>ip-prefix</i>	(Optional) Clear route flap dampening for prefix
<i>ip-addr</i>	(Optional) Clear route flap dampening for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	Clear IPv4 address-family
ipv6	Clear IPv6 address-family
vpnv4	Clear VPNv4 address-family
vpnv6	Clear VPNv6 address-family
unicast	Clear unicast address-family
multicast	Clear multicast address-family
all	Clear all address-families

Command Mode

- /exec

clear ip mbgp flap-statistics

```
{ { clear ip mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] flap-statistics
[ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] ipv4 { unicast | multicast }
flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] } | { clear ip bgp [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] all flap-statistics } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast } | vpnv4 unicast } flap-statistics [ <ip-prefix>
| <ip-addr> [ <ip-mask> ] | regexp <regexp-str> ] } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] { ipv6 { unicast | multicast } | vpnv6 unicast } flap-statistics [ <ipv6-prefix>
| regexp <regexp-str> ] } | { clear bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234
} ] all flap-statistics } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
```

Syntax Description

clear	Reset functions
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ip	Clear IP commands
bgp	Clear BGP sessions
mbgp	Clear MBGP sessions
flap-statistics	Clear flap statistics
<i>ip-prefix</i>	(Optional) Clear flap statistics for one prefix
<i>ip-addr</i>	(Optional) Clear flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	Clear IPv4 address-family
ipv6	Clear IPv6 address-family
vpnv4	Clear VPNv4 address-family
vpnv6	Clear VPNv6 address-family
unicast	Clear unicast address-family
multicast	Clear multicast address-family
all	Clear all address-families
regexp	(Optional) Clear flap statistics for routes matching the regular expression

<i>regexp-str</i>	(Optional) Regular expression to match the AS paths
-------------------	---

Command Mode

- /exec

clear ip mbgp peer-template

```
{ { clear ip mbgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { <neighbor-id>
| * | <asn> | <prefix-id> peer-template <peer-template-name> } [ soft [ in | out ] | dampened-paths | flap-statistics
| no-notify ] } | { clear ip bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ]
{ <neighbor-id> | * | <asn> | <prefix-id> | peer-template <peer-template-name> } [ soft [ in | out ] |
dampened-paths | flap-statistics | no-notify ] { { ipv4 { unicast | multicast } | { vpnv4 | vpnv6 } unicast | all } {
soft [ in | out ] | dampened-paths | flap-statistics | no-notify } ] } | { clear bgp [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast | multicast | mvpn | labeled-unicast
} | ipv6 { unicast | multicast | mvpn | labeled-unicast } | { vpnv4 | vpnv6 } unicast | l2vpn vpls | l2vpn evpn |
link-state | all } { <neighbor-id> | <ipv6-neighbor-id> | * | <asn> | peer-template <peer-template-name> |
<prefix-id> | <ipv6-prefix-id> } [ soft [ in | out ] | dampened-paths | flap-statistics | no-notify ] } } [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
bgp	Clear BGP sessions
mbgp	Clear MBGP sessions
<i>neighbor-id</i>	IP address of the neighbor to clear
<i>prefix-id</i>	Clear all neighbors matching the prefix
*	Clear all neighbors (Should be a * character)
<i>asn</i>	Clear all neighbors in an AS
peer-template	Clear all neighbors in a peer-template
<i>peer-template-name</i>	Peer-template name
soft	(Optional) Soft reconfiguration
in	(Optional) Clear soft reconfiguration inbound
out	(Optional) Clear soft reconfiguration outbound
ipv4	(Optional) Clear IPv4 address-family
ipv6	Clear IPv6 address-family
vpnv4	(Optional) Clear VPNv4 address-family

vpn6	(Optional) Clear VPNv6 address-family
unicast	(Optional) Clear unicast address-family
multicast	(Optional) Clear multicast address-family
link-state	Clear link-state address-family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family
all	(Optional) Clear all address-families
dampened-paths	(Optional) Clear dampened paths for neighbor
flap-statistics	(Optional) Clear flap statistics for neighbor
no-notify	(Optional) Clear without sending notification

Command Mode

- /exec

clear ip mfwf event-history

clear ip mfwf event-history [<mfwf-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
mfwf	Clear MCASTFWD related information
event-history	Clear event-history buffers
<i>mfwf-event-hist-buf-name</i>	(Optional) Event hist buffer name

Command Mode

- /exec

clear ip mroute

```
clear ip mroute [ repopulate ] { { <all> [ shared-tree | source-tree ] } | { <group-prefix> [ shared-tree | source-tree ] } | { <group> [ <source> | shared-tree | source-tree ] } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
mroute	Clear multicast routing table
repopulate	(Optional) Clear MRIB states and request other components to repopulate mroutes
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
shared-tree	(Optional) Clear the (*,G) route associated with the group
source-tree	(Optional) Clear all (S,G) routes associated with the group
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip mroute statistics

```
clear ip mroute statistics { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> |
<vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
mroute	Clear multicast routing table
statistics	Clear statistics of multicast route
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip msdp event-history

clear ip msdp event-history [<msdp-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
msdp	MSDP global configuration commands
event-history	Clear the event-history buffer instances
<i>msdp-event-hist-buf-name</i>	(Optional) Specify the particular instance of the event-history buffer

Command Mode

- /exec

clear ip msdp peer

```
clear ip msdp peer <peer-address> [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
msdp	MSDP clear commands
peer	Clear MSDP peer connection
<i>peer-address</i>	IP address of MSDP peer
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ip msdp policy statistics sa-policy in

```
clear ip msdp policy statistics sa-policy <peer-address> { in | out } [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
msdp	MSDP global configuration commands
policy	Policy information
statistics	Policy statistics
sa-policy	Configured SA policy for MSDP peer
<i>peer-address</i>	IP address of MSDP peer for SA policy
in	Input policy
out	Output policy
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ip msdp sa

```
clear ip msdp { sa-cache | route } { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
msdp	MSDP clear commands
sa-cache	Clear contents of SA cache
route	Clear contents of SA cache
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip msdp statistics

```
clear ip msdp statistics [ <peer-address> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
msdp	MSDP clear commands
statistics	Clear statistics for peers
<i>peer-address</i>	(Optional) IP address of MSDP peer
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ip nat-alias address

```
clear ip nat-alias { address <ipaddress> | all }
```

Syntax Description

clear	Reset functions
ip	Clear ip counters
nat-alias	Clear NAT alias
address	alias address
<i>ipaddress</i>	NAT alias ip address
all	Delete all NAT alias address

Command Mode

- /exec

clear ip nat statistics

clear ip nat statistics

Syntax Description

clear	Reset functions
ip	Clear ip counters
nat	IP NAT information
statistics	Translation statistics

Command Mode

- /exec

clear ip nat translation

```
clear ip nat translation { entry-id <xlation_id> | all | inside <insideGlobalIP> <insideLocalIP> [ outside
<outsideLocalIP> <outsideGlobalIP> ] | outside <outsideLocalIP> <outsideGlobalIP> | tcp { inside
<insideGlobalIP> <insideGlobal-port> <insideLocalIP> <insideLocal-port> outside <outsideLocalIP>
<outsideLocal-port> <outsideGlobalIP> <outsideGlobal-port> } | udp { inside <insideGlobalIP>
<insideGlobal-port> <insideLocalIP> <insideLocal-port> outside <outsideLocalIP> <outsideLocal-port>
<outsideGlobalIP> <outsideGlobal-port> } | icmp { inside <insideGlobalIP> <insideGlobal-port>
<insideLocalIP> <insideLocal-port> outside <outsideLocalIP> <outsideLocal-port> <outsideGlobalIP>
<outsideGlobal-port> } }
```

Syntax Description

clear	Reset functions
ip	Clear ip counters
nat	Clear NAT
translation	Clear dynamic translation
entry-id	Dynamic xlation id
<i>xlation_id</i>	Dynamic xlation id
all	Delete all dynamic translations
inside	Inside addresses
<i>insideGlobalIP</i>	Inside global IP address
<i>insideLocalIP</i>	Inside local IP address
outside	(Optional) Outside addresses
<i>outsideLocalIP</i>	(Optional) Outside local IP address
<i>outsideGlobalIP</i>	(Optional) Outside global IP address
tcp	Transmission Control Protocol
udp	User Datagram Protocol
icmp	Internet Control Message Protocol
<i>insideGlobal-port</i>	Inside global TCP/UDP/ICMP port address
<i>insideLocal-port</i>	Inside local TCP/UDP/ICMP port address
<i>outsideLocal-port</i>	Outside local TCP/UDP port/ICMP address
<i>outsideGlobal-port</i>	Outside global TCP/UDP/ICMP port address

Command Mode

- /exec

clear ip ospf database

clear ip ospf [<tag>] database

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
database	Clear the LSDB and all neighbors

Command Mode

- /exec

clear ip ospf event-history

clear ip ospf [<tag>] event-history [adjacency | event | ha | flooding | lsa | spf | redistribution | cli | ldp | te | rib | hello | spf-trigger | objstore | all]

Syntax Description

clear	Reset functions
ip	IP events
ospf	Debug OSPF events
<i>tag</i>	(Optional) Process tag
event-history	Clear the event history buffers
adjacency	(Optional) Adjacency formation logs
event	(Optional) Internal event logs
ha	(Optional) HA and GR logs
flooding	(Optional) LSA flooding logs
lsa	(Optional) LSA generation and database logs
spf	(Optional) SPF calculation logs
redistribution	(Optional) Redistribution logs
cli	(Optional) Cli logs
ldp	(Optional) LDP related logs
te	(Optional) MPLS TE related logs
rib	(Optional) RIB related logs
hello	(Optional) HELLO related logs
spf-trigger	(Optional) SPF TRIGGER related logs
objstore	(Optional) DME OBJSTORE related logs
all	(Optional) All event history buffers

Command Mode

- /exec

clear ip ospf interface

```
clear ip ospf [ <tag> ] interface { * | <interface> }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
interface	Clear one or more interfaces
*	Clear all interfaces
<i>interface</i>	Interface to clear

Command Mode

- /exec

clear ip ospf neighbor

```
clear ip ospf [ <tag> ] neighbor { { * | <neighborid> } [ vrf { <vrf-name> | <vrf-known-name> | all } ] } |
{ <interface> } }
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbor	Clear one or more neighbors
*	Clear all neighbors
<i>neighborid</i>	Source IP address, or router ID of the neighbor
<i>interface</i>	Interface to clear all neighbors on

Command Mode

- /exec

clear ip ospf policy statistics

```
clear ip ospf [ <tag> ] policy statistics { { redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> | static |
direct | amt | lisp } } | { area <area-id-ip> filter-list { in | out } } } [ vrf { <vrf-name> | <vrf-known-name> |
all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
policy	Clear Policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	ISO Intermediate-to-Intermediate (IS-IS)
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
ospf	Open Shortest Path First (OSPFv2)
eigrp	Enhanced Interior Gateway Protocol (EIGRP)
rip	Routing Information Protocol (RIP)
static	Static
direct	Directly connected
amt	AMT anycast prefix
lisp	LISP EID-prefixes
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
filter-list	Filter prefixes between OSPF areas

in	Filter networks sent to this area
out	Filter networks sent from this area
<i>tag</i>	

Command Mode

- /exec

clear ip ospf redistribution

```
clear ip ospf [ <tag> ] redistribution [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
redistribution	Clear OSPF route redistribution

Command Mode

- /exec

clear ip ospf statistics

```
clear ip ospf [ <tag> ] statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Clear event counters

Command Mode

- /exec

clear ip ospf traffic

```
clear ip ospf [ <tag> ] traffic [ <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
ospf	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Clear packet counters
<i>interface</i>	(Optional) Interface to clear all traffic on

Command Mode

- /exec

clear ip pim event-history

clear ip pim event-history [<pim-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	PIM clear commands
event-history	Clear event history buffers
<i>pim-event-hist-buf-name</i>	(Optional) Event history buffer instance

Command Mode

- /exec

clear ip pim interface statistics

clear ip pim interface statistics [<interface> | vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	Clear PIM information
interface	Interface related information
statistics	Packet interface counter statistics
<i>interface</i>	(Optional) Interface name to clear
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip pim policy statistics

```
clear ip pim policy statistics { register-policy | bsr { bsr-policy | rp-candidate-policy } | auto-rp {
rp-candidate-policy | mapping-agent-policy } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	PIM global configuration commands
policy	Policy related information
statistics	Policy statistics
register-policy	Show statistics for register-policy
bsr	Bootstrap protocol RP-distribution policy
bsr-policy	Statistics for BSR messages
rp-candidate-policy	Statistics for RP candidate messages
auto-rp	Statistics for auto-rp messages
rp-candidate-policy	Statistics for RP candidate messages
mapping-agent-policy	Statistics for mapping agent messages
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip pim policy statistics jp

clear ip pim policy statistics { jp-policy | neighbor-policy } <interface>

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	PIM global configuration commands
policy	Policy related information
statistics	Policy statistics
jp-policy	Statistics for jp-policy
neighbor-policy	Statistics for neighbor-policy
<i>interface</i>	Interface

Command Mode

- /exec

clear ip pim route

```
clear ip pim route { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> | <vrf-known-name>
| all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	PIM clear commands
route	Route information
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching the Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip pim statistics

clear ip pim statistics [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
ip	Clear IP commands
pim	Clear PIM information
statistics	Packet global counter statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip rip policy statistics redistribute bgp

```
{ { clear ip rip policy statistics redistribute bgp <as> } | { clear ip rip policy statistics redistribute eigrp <tag>
} | { clear ip rip policy statistics redistribute isis <tag> } | { clear ip rip policy statistics redistribute rip <tag>
} | { clear ip rip policy statistics redistribute ospf <tag> } | { clear ip rip policy statistics redistribute direct }
| { clear ip rip policy statistics redistribute static } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
rip	Routing Information Protocol (RIP)
policy	Policy related information
statistics	Policy statistics
redistribute	RIP redistribute routes from other routing protocol
bgp	Border Gateway Protocol (BGP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>as</i>	Autonomous system number
isis	Intermediate-to-intermediate (ISIS)
ospf	Open Shortest Path First (OSPFv2)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected routes
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip rip statistics

```
clear { ipv6 | ip } rip statistics [ * | <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
ip	Clear IP commands
rip	Routing Information Protocol (RIP)
statistics	Clear RIP statistics
*	(Optional) RIP statistics for all interfaces
<i>interface</i>	(Optional) RIP interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ip routing multicast event-history

clear ip routing multicast event-history [<mrrib-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ip	Clear IP commands
routing	Clear event-history buffers
multicast	Clear all multicast event-history buffers
event-history	Clear event history buffers
<i>mrrib-event-hist-buf-name</i>	(Optional) Event history buffer

Command Mode

- /exec

clear ip traffic

```
clear ip traffic [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ip	Clear IP commands
traffic	Clear IP global statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ipv6 adjacency statistics

clear ipv6 adjacency statistics

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
adjacency	Clear Adjacency
statistics	Clear Adjacency Statistics

Command Mode

- /exec

clear ipv6 amt tunnel

```
clear ipv6 amt tunnel [ <address6> <port> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	AMT clear commands
amt	AMT show commands
ipv6	Display IP information
tunnel	Display tunnel information
vrf	(Optional) Display information for VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>port</i>	(Optional) UDP port number of gateway

Command Mode

- /exec

clear ipv6 dhcp-ldra statistics

clear ipv6 dhcp-ldra statistics

Syntax Description

clear	Reset functions
ipv6	IPv6
dhcp-ldra	Clear State of DHCPv6 LDRA stats
statistics	DHCPv6 LDRA statistics

Command Mode

- /exec

clear ipv6 dhcp relay statistics

```
clear ipv6 dhcp relay statistics [ interface <intf> [ [ server-ip <ip-addr-val> [ use-vrf <vrf-name> ] [ interface
<dest-interface> ] ] [ server-ip <ip-addr-val> [ interface <dest-interface> ] [ use-vrf <vrf-name> ] ] ] ]
```

Syntax Description

clear	Reset functions
ipv6	IPv6
dhcp	Clear State of DHCPv6 features
relay	Clear State of DHCPv6 relay stats
statistics	DHCPv6 Relay statistics
interface	(Optional) input interface
<i>intf</i>	(Optional) interface
server-ip	(Optional) Server address
use-vrf	(Optional) Server address VRF membership
<i>vrf-name</i>	(Optional) VRF name
interface	(Optional) Destination interface for the server address
<i>dest-interface</i>	(Optional) Destination interface

Command Mode

- /exec

clear ipv6 eigrp route-map statistics redistribute

```
clear ipv6 eigrp [ <eigrp-ptag> ] route-map statistics redistribute { bgp <as> | { eigrp | isis | ospfv3 | rip }
<tag> | static | direct | amt | lisp } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
<i>eigrp-ptag</i>	(Optional) Process tag
route-map	Route-map related information
statistics	Route-map statistics
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv4
ospfv3	Open Shortest Path First (OSPF) V3
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT Anycast prefix
lisp	LISP EID-prefixes

Command Mode

- /exec

clear ipv6 icmp

```
clear ipv6 { icmp | nd } { interface statistics [ <interface> ] | global statistics }
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
icmp	Clear ICMPv6 information
nd	Clear Neighbor Discovery interface information
interface	Clear ICMPv6 related interface information
statistics	Clear ICMPv6 interface statistics
global	Clear ICMPv6 global statistics
<i>interface</i>	(Optional) Interface to clear statistics for

Command Mode

- /exec

clear ipv6 icmp vpc-statistics

clear ipv6 icmp vpc-statistics

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
icmp	Clear ICMPv6 information
vpc-statistics	Clear ICMPv6 ND vPC statistics

Command Mode

- /exec

clear ipv6 interface statistics

clear ipv6 interface statistics [<interface>]

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
interface	Clear IPv6 related interface information
statistics	Clear IPv6 interface statistics
<i>interface</i>	(Optional) Interface to clear statistics for

Command Mode

- /exec

clear ipv6 lisp data-cache

```
clear ipv6 lisp data-cache [ <eid6> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

<i>clear</i>	Reset functions
<i>ipv6</i>	Clear IPv6 commands
<i>lisp</i>	LISP clear commands
<i>data-cache</i>	Clear EID-to-RLOC data cache mapping in this ITR
<i>eid6</i>	(Optional) Clear mapping for IPv6 destination EID
<i>vrf</i>	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ipv6 lisp statistics

```
clear ipv6 lisp statistics [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
lisp	LISP clear commands
statistics	Clear global LISP statistics
vrf	(Optional) Clear statistics for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear ipv6 mld groups

```
clear ipv6 [ icmp ] mld { groups | route } { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name>
| <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
icmp	(Optional) Clear ICMPv6 information
mld	Clear Multicast Listener Discovery information
groups	Route information
route	Route information
all	Clear all routes
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 mroute

```
clear ipv6 mroute { { <all> [ shared-tree | source-tree ] } | { <group-prefix> [ shared-tree | source-tree ] } | {
<group> [ <source> | shared-tree | source-tree ] } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
mroute	Clear multicast routing table
all	Clear all routes
shared-tree	(Optional) Clear the (*,G) route associated with the group
source-tree	(Optional) Clear all (S,G) routes associated with the group
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 neighbor

```
clear ipv6 neighbor [ [ <nbr-addr> [ <intf> ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] | vrf { <vrf-name> | <vrf-known-name> | all } | <interface> ] [ force-delete ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
neighbor	Clear ICMPv6 neighbor cache
<i>intf</i>	(Optional) Clear cache entries for given interface
<i>interface</i>	(Optional) Clear cache entries for given interface
force-delete	(Optional) Clear the cache entries without refresh
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 neighbor binding

clear ipv6 neighbor binding [mac <macaddr> | address { <ipv6-addr> | all } | policy <policy-name> |

Syntax Description

clear	Reset functions
ipv6	IPv6
<i>macaddr</i>	(Optional) 48-bit hardware address
<i>policy-name</i>	(Optional) Snooping Policy name to be cleared

Command Mode

- /exec

clear ipv6 pim event-history

clear ipv6 pim event-history [<pim6-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
pim	Clear PIM event history buffers
event-history	Clear event-history buffers
<i>pim6-event-hist-buf-name</i>	(Optional) Event-history buffer instance

Command Mode

- /exec

clear ipv6 pim interface statistics

clear ipv6 pim interface statistics [<interface>]

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
pim	Clear PIM6 information
interface	Interface related information
statistics	Packet interface counter statistics
<i>interface</i>	(Optional) Interface name to clear

Command Mode

- /exec

clear ipv6 pim policy statistics jp

clear ipv6 pim policy statistics { jp-policy | neighbor-policy } <interface>

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
pim	Clear PIM information
policy	Policy related information
statistics	Policy statistics
jp-policy	Statistics for jp-policy
neighbor-policy	Statistics for neighbor-policy
<i>interface</i>	Interface

Command Mode

- /exec

clear ipv6 pim route

```
clear ipv6 pim route { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> | <vrf-known-name>
| all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
pim	PIM6 clear commands
route	Route information
all	Clear all routes
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 pim statistics

clear ipv6 pim statistics [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
pim	Clear PIM6 information
statistics	Packet global counter statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 raguard statistics

clear ipv6 raguard statistics

Syntax Description

clear	Reset functions
ipv6	IPv6
raguard	IPV6 raguard
statistics	RA packet drop count

Command Mode

- /exec

clear ipv6 rip policy statistics redistribute bgp

```
{ { clear ipv6 rip policy statistics redistribute bgp <as> } | { clear ipv6 rip policy statistics redistribute eigrp <tag> } | { clear ipv6 rip policy statistics redistribute isis <tag> } | { clear ipv6 rip policy statistics redistribute rip <tag> } | { clear ipv6 rip policy statistics redistribute ospfv3 <tag> } | { clear ipv6 rip policy statistics redistribute direct } | { clear ipv6 rip policy statistics redistribute static } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
rip	Routing Information Protocol (RIP)
policy	Policy related information
statistics	Policy statistics
redistribute	RIP redistribute routes from other routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
isis	Intermediate-to-intermediate (ISIS)
ospfv3	Open Shortest Path First (OSPFv3)
tag	Process tag
static	Static routes
direct	Directly connected routes
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear ipv6 routing multicast event-history

clear ipv6 routing multicast event-history [<m6rib-event-hist-buf-name>]

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
routing	Clear event-history buffers
multicast	Clear all multicast event-history buffers
event-history	Clear event-history buffers
<i>m6rib-event-hist-buf-name</i>	(Optional) Event-history buffer name

Command Mode

- /exec

clear ipv6 snooping counters

clear ipv6 snooping counters [{ interface <intf> | vlan <vlanid> }]

Syntax Description

clear	Reset functions
ipv6	IPv6
<i>intf</i>	(Optional) interface
<i>vlanid</i>	(Optional) VLAN ID

Command Mode

- /exec

clear ipv6 snooping events

clear ipv6 snooping events

Syntax Description

clear	Reset functions
ipv6	IPv6

Command Mode

- /exec

clear ipv6 snooping messages

clear ipv6 snooping messages

Syntax Description

clear	Reset functions
ipv6	IPv6

Command Mode

- /exec

clear ipv6 traffic

```
clear ipv6 traffic [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
ipv6	Clear IPv6 commands
traffic	Clear IPv6 traffic statistics
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear isis adjacency

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] adjacency { * | { <interface> | system-id
<sid> } + } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
adjacency	Clear IS-IS adjacency state
*	IS-IS adjacencies on all interfaces
<i>interface</i>	IS-IS interface
system-id	Hostname or System ID
<i>sid</i>	Hostname or System ID (in the form of XXXX.XXXX.XXXX)

Command Mode

- /exec

clear isis dpi

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] dpi [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
dpi	Clear IS-IS DPI logs

Command Mode

- /exec

clear isis event-history

clear isis [<isis-tag>] event-history [<isis-event-hist-buf-name>]

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
event-history	Clear event history buffers
<i>isis-event-hist-buf-name</i>	(Optional) Clear the specific event history buffer

Command Mode

- /exec

clear isis ipv6 route-map statistics

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] ipv6 route-map statistics { { redistribute
{ bgp <as> | { <src-isis> | eigrp | ospfv3 | rip } <tag> } } | { redistribute { static | direct | amt } } | { distribute
<src-level> into <dst-level> } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ipv6	Clear IS-IS IPv6 information
statistics	Clear IS-IS route-map statistics
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
eigrp	Enhanced Interior Gateway Protocol
<i>as</i>	Autonomous system number
src-isis	IS-IS Routing for IPv6
ospfv3	Open Shortest Path First (OSPF) V3
rip	RIP for IPv6 (RIPNG)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
route-map	Route-map to constrain redistribution
distribute	Distribute routes between ISIS levels
into	from level-n into level-m
<i>src-level</i>	Route-distribution between levels

<i>dst-level</i>	Route-distribution between levels
------------------	-----------------------------------

Command Mode

- /exec

clear isis redistribution

```
clear isis [ <isis-tag> ] redistribution [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
redistribution	Clear IS-IS redistributed information

Command Mode

- /exec

clear isis route-map statistics

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ ip ] route-map statistics { { redistribute
{ bgp <as> | { <src-isis> | eigrp | ospf | rip } <tag> } } | { redistribute { static | direct | amt } } | { distribute
<src-level> into <dst-level> } } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
ip	(Optional) Clear IS-IS IPv4 information
route-map	Clear IS-IS route-map information
statistics	Clear IS-IS route-map statistics
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
eigrp	Enhanced Interior Gateway Protocol
<i>as</i>	Autonomous system number
src-isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
rip	RIP for IPv4
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
distribute	Distribute routes between ISIS levels
into	from level-n into level-m
<i>src-level</i>	Route-distribution between levels

<i>dst-level</i>	Route-distribution between levels
------------------	-----------------------------------

Command Mode

- /exec

clear isis spf-log

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] spf-log [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
spf-log	Display IS-IS SPF information

Command Mode

- /exec

clear isis statistics

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] statistics { * | <interface> } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Clear IS-IS protocol statistics
*	All IS-IS protocol statistics
<i>interface</i>	IS-IS interface

Command Mode

- /exec

clear isis traffic

```
clear isis [ <isis-tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] traffic { * | <interface> } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
isis	Clear IS-IS information
<i>isis-tag</i>	(Optional) Routing process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Clear IS-IS traffic information
*	All IS-IS traffic information
<i>interface</i>	IS-IS interface

Command Mode

- /exec

clear itd statistics

clear itd statistics <service-name>

Syntax Description

clear	Reset functions
itd	ITD service
statistics	ITD statistics
<i>service-name</i>	ITD service-name

Command Mode

- /exec

clear keystore

clear { keystore | sksd } [<index> | <name>]

Syntax Description

clear	Reset functions
keystore	Clear all records in the keystore
sksd	Clear all records in the keystore/sksd-chip
<i>index</i>	(Optional) Clear secret at index <index>
<i>name</i>	(Optional) Clear secret with name <name>

Command Mode

- /exec

clear l2dbg

```
clear l2dbg { macdb | portdb | rvtepdb | dme-events }
```

Syntax Description

clear	Clear
l2dbg	L2 debug databases
macdb	L2 debug MACDB
portdb	L2 debug PORTDB
rvtepdb	L2 debug RVTEPDB
dme-events	L2 debug ObjectstoreDB

Command Mode

- /exec

clear l2fwder statistics

clear l2fwder statistics

Syntax Description

clear	Reset functions
l2fwder	Clear L2FWDER related information
statistics	Clear the L2FWDER packet counters

Command Mode

- /exec

clear l3vm event-history

clear l3vm event-history { pss | errors | mts | reinit | cli | vrf | topology | all }

Syntax Description

clear	Reset functions
l3vm	Debug L3VM information
event-history	log debug events into event history buffer
pss	L3VM pss operation
errors	L3VM errors
mts	L3VM MTS messages
reinit	L3VM reinit events
cli	Log L3VM CLI related events
vrf	Log VRF related events
topology	Log Topology related events
all	All L3VM debugging

Command Mode

- /exec

clear lacp counters

clear lacp counters [interface <if0>]

Syntax Description

clear	Reset functions
lacp	LACP protocol
counters	LACP counters
interface	(Optional) Specify a port-channel
<i>if0</i>	(Optional)

Command Mode

- /exec

clear ldap-server statistics

```
clear ldap-server statistics <host0> [ __readonly__ { <server_state> [ <clock_time> { monitoring_statistics
<time_in_pstate> <ndead> <tt_in_dstate> } ] } } { auth_statistics <auth_failed_transactions>
<auth_succ_transactions> <auth_req_sent> <auth_req_timedout> <auth_resp_no_match>
<auth_resp_not_processed> <auth_resp_error> } { acct_statistics <acct_failed_transactions>
<acct_succ_transactions> <acct_req_sent> <acct_req_timedout> <acct_resp_no_match>
<acct_resp_not_processed> <acct_resp_error> } } ]
```

Syntax Description

clear	Reset functions
ldap-server	Clear LDAP related parameters
statistics	Clear LDAP statistics
<i>host0</i>	DNS name or IP address
<i>__readonly__</i>	(Optional)
<i>server_state</i>	(Optional) Show state of server
<i>clock_time</i>	(Optional) Show clock time in terms of hours, minutes and seconds
monitoring_statistics	(Optional) Monitoring Statistics
<i>time_in_pstate</i>	(Optional) Time in previous state
<i>ndead</i>	(Optional) Number of times dead
<i>tt_in_dstate</i>	(Optional) Total time in dead state
auth_statistics	(Optional) Authentication Statistics
acct_statistics	(Optional) Accounting Statistics
<i>auth_failed_transactions</i>	(Optional) Authentication: Failed transactions
<i>auth_succ_transactions</i>	(Optional) Authentication: Successful transactions
<i>auth_req_sent</i>	(Optional) Authentication: Requests sent
<i>auth_req_timedout</i>	(Optional) Authentication: Requests timedout
<i>auth_resp_no_match</i>	(Optional) Authentication: Responses with no matching requests
<i>auth_resp_not_processed</i>	(Optional) Authentication: Responses not processed
<i>auth_resp_error</i>	(Optional) Authentication: Responses containing errors
<i>acct_failed_transactions</i>	(Optional) Accounting: Failed transactions
<i>acct_succ_transactions</i>	(Optional) Accounting: Successful transactions

<i>acct_req_sent</i>	(Optional) Accounting: Requests sent
<i>acct_req_timeout</i>	(Optional) Accounting: Requests timeout
<i>acct_resp_no_match</i>	(Optional) Accounting: Responses with no matching requests
<i>acct_resp_not_processed</i>	(Optional) Accounting: Responses not processed
<i>acct_resp_error</i>	(Optional) Accounting: Responses containing errors

Command Mode

- /exec

clear license

```
clear license { <license-file> [ force ] | sprom | <s0> }
```

Syntax Description

clear	Reset functions
license	clear license
<i>license-file</i>	License file to be uninstalled
force	(Optional) Force license clear (don't prompt)
sprom	clear license contents in sprom
<i>s0</i>	License file to be uninstalled

Command Mode

- /exec

clear lim counters

clear lim counters [timeline]

Syntax Description

clear	Clear lim counters
lim	clear lim counters
counters	clear lim counters
timeline	(Optional) Clear all lim counters

Command Mode

- /exec

clear line

clear line <s0>

Syntax Description

clear	Reset functions
line	Kill a session on particular vty
<i>s0</i>	Enter the vty name

Command Mode

- /exec

clear lisp ddt referral-cache

```
clear lisp ddt referral-cache [ instance-id <iid> ] [ <eid-prefix> | <eid-prefix6> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
lisp	LISP clear commands
ddt	LISP Delegated Database Tree
referral-cache	Clear the DDT referral cache
vrf	(Optional) Clear entry for particular vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
instance-id	(Optional) Clear entry for specific instance-ID
<i>iid</i>	(Optional) 24-bit instance-ID value
<i>eid-prefix</i>	(Optional) Clear entry associated with IP EID-prefix

Command Mode

- /exec

clear lisp dynamic-eid

```
clear lisp dynamic-eid { <dyn-eid-name> | <dyn-eid> } [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
lisp	LISP clear commands
dynamic-eid	Clear dynamic-EID state
<i>dyn-eid</i>	IPv4 address of dynamic-EID entry
<i>dyn-eid-name</i>	Clear entries discovered for a dynamic-EID range
vrf	(Optional) Clear dynamic-EID entries for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear lisp proxy-itr

```
clear lisp proxy-itr [ <addr> | <addr6> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
lisp	LISP clear commands
proxy-itr	Clear discovered PITRs
<i>addr</i>	(Optional) IPv4 locator address of PITR
vrf	(Optional) Clear proxy-itr state for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear lisp site

```
clear lisp site <site-name> [ instance-id <iid> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

clear	Reset functions
lisp	LISP clear commands
site	Clear site registration data
<i>site-name</i>	Clear registration data for a single site
instance-id	(Optional) Clear registration for a single instance-id within a site
<i>iid</i>	(Optional) 24-bit instance-ID value
vrf	(Optional) Clear site entries for vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

clear lldp counters

clear lldp counters

Syntax Description

clear	Reset functions
lldp	Reset the lldp counters
counters	Reset the lldp traffic counters to zero

Command Mode

- /exec

clear lldp counters interface

clear lldp counters interface <if0>

Syntax Description

clear	Reset functions
lldp	Reset the lldp counters
counters	Reset the lldp traffic counters to zero
interface	Clear lldp traffic counters per interface
<i>if0</i>	Enter interface

Command Mode

- /exec

clear logging ip access-list cache

clear logging ip access-list cache

Syntax Description

clear	Reset functions
logging	Clear logging information
ip	IP configuration
access-list	Access-list
cache	logging

Command Mode

- /exec

clear logging logfile

clear logging logfile

Syntax Description

clear	Reset functions
logging	Clear logging information
logfile	Clear logfile messages

Command Mode

- /exec

clear logging nvram

clear logging nvram

Syntax Description

clear	Reset functions
logging	Clear logging information
nvram	Clear nvram logs

Command Mode

- /exec

clear logging onboard

```
clear logging onboard [ { counter-stats | epld-log | internal { <dc3_options> } | module <module> [ {
counter-stats | internal { <dc3_options> } } ] ] ]
```

Syntax Description

clear	Reset functions
logging	Clear logging information
onboard	Clear OBFL information
counter-stats	(Optional) Clear OBFL counter statistics
epld-log	(Optional) Clear EPLD log
internal	(Optional) Clear Logging Onboard Internal
module	(Optional) Clear OBFL information for Module
<i>module</i>	(Optional) Enter module number
counter-stats	(Optional) Clear OBFL counter statistics
<i>dc3_options</i>	(Optional) dc3 options

Command Mode

- /exec

clear logging onboard

clear logging onboard [{ card-boot-history | card-first-power-on | environmental-history | error-stats | exception-log | interrupt-stats | module <module> [{ environmental-history | error-stats | exception-log | interrupt-stats | obfl-logs | stack-trace | card-boot-history | card-first-power-on }] | obfl-logs | stack-trace }]

Syntax Description

clear	Reset functions
logging	Clear logging information
onboard	Clear OBFL information
environmental-history	(Optional) Clear OBFL environmental history
error-stats	(Optional) Clear OBFL error statistics
exception-log	(Optional) Clear OBFL exception log
interrupt-stats	(Optional) Clear OBFL interrupt statistics
card-boot-history	(Optional) Clear Card Boot History
card-first-power-on	(Optional) Clear Card First Power On
module	(Optional) Clear OBFL information for Module
<i>module</i>	(Optional) Enter module number
obfl-logs	(Optional) Clear OBFL (boot-uptime/device-version/obfl-history).
stack-trace	(Optional) Clear OBFL stack trace

Command Mode

- /exec

clear logging session

clear logging session

Syntax Description

clear	Reset functions
logging	Clear logging information
session	Clear logging session

Command Mode

- /exec

clear mac address-table datapath

```
clear mac address-table datapath { dynamic [ vlan <id> ] | static [ vlan <id> ] | { statistics [ interface ] } |
isis_intf_stats }
```

Syntax Description

clear	Clear
mac	MAC configuration commands
address-table	MAC Address Table
datapath	Titanium Datapath Table
dynamic	clear dynamic entries from Titanium PD Forwarding Table
static	USE WITH CAUTION!! clear static entries from Titanium PD Forwarding Table
vlan	(Optional) VLAN
<i>id</i>	(Optional) VLAN ID
statistics	Clear datapath statistics
interface	(Optional) Clear datapath interface statistics
isis_intf_stats	Statistics of ISIS Frames Tx/Rx

Command Mode

- /exec

clear mac address-table dynamic

```
clear mac address-table dynamic [ local ] [ address <mac-addr> | interface <interface-name> ] [ multicast-entries
[ not-notified ] ] [ vlan <vlan-id> | vni <vni-id> | peer-ip <peer-ipv4> ] [ instance <instance> ] [ __readonly__
<info_str> ]
```

Syntax Description

clear	Clear
mac	MAC configuration commands
address-table	MAC Address Table
dynamic	clear dynamic entries from the Layer2 Forwarding Table
local	(Optional) clear MAC Entries Learned Locally and Not on the Overlay/VXLAN
address	(Optional) address
<i>mac-addr</i>	(Optional) MAC Address
interface	(Optional) Interface
<i>interface-name</i>	(Optional) Interface name
vlan	(Optional) VLAN
<i>vlan-id</i>	(Optional) VLAN ID
vni	(Optional) VXLAN Network Identifier
<i>vni-id</i>	(Optional) VXLAN Network Identifier
peer-ip	(Optional) VXLAN Peer IP Address
<i>peer-ipv4</i>	(Optional) VXLAN Peer IP Address
instance	(Optional) Eureka Instance
<i>instance</i>	(Optional) ASIC Instance Number
multicast-entries	(Optional) clear all dynamically learnt multicast entries
not-notified	(Optional) entries that exceed the hardware notification limit
<i>__readonly__</i>	(Optional)
<i>info_str</i>	(Optional) Information

Command Mode

- /exec

clear mts message statistics

clear mts message statistics

Syntax Description

clear	Reset functions
mts	MTS statistics
message	mts messages
statistics	mts message statistics

Command Mode

- /exec

clear mvr counters

clear mvr counters

Syntax Description

clear	Reset functions
mvr	Clear MVR info
counters	Clear MVR counters

Command Mode

- /exec

clear mvr counters receiver-ports

clear mvr counters receiver-ports [<if0>]

Syntax Description

clear	Reset functions
mvr	Clear MVR info
counters	Clear MVR counters
receiver-ports	Clear MVR receiver port counters
<i>if0</i>	(Optional) Interface name

Command Mode

- /exec

clear mvr counters source-ports

clear mvr counters source-ports [<if0>]

Syntax Description

clear	Reset functions
mvr	Clear MVR info
counters	Clear MVR counters
source-ports	Clear MVR source port counters
<i>if0</i>	(Optional) Interface name

Command Mode

- /exec

clear nbm flow statistics

clear nbm flow statistics

Syntax Description

clear	Clear
nbm	Non blocking Multicast
flow	NBM flows
statistics	Clear nbm flow statistics

Command Mode

- /exec

clear ngoam

```
clear ngoam { probe { statistics { summary | { session { <handle> | all } } } } }
```

Syntax Description

clear	Reset functions
ngoam	ngoam information
probe	clear ngoam probe
statistics	clear ngoam statistics
summary	clear ngoam statistics summary
session	clear ngoam information by session handle
<i>handle</i>	specify session handle
all	clear stats for all probe sessions

Command Mode

- /exec

clear ngoam

```
clear ngoam { { interface statistics } }
```

Syntax Description

clear	Reset functions
ngoam	ngoam information
interface	probe packet interface
statistics	clear ngoam statistics

Command Mode

- /exec

clear ngoam

```
clear ngoam { loopback { { session { <ses-hdl> | all } } } | { statistics { summary | { session { <ses-hdl> | all } } } } } | database [ session <ses-hdl> ] } [ force ] }
```

Syntax Description

clear	Reset functions
ngoam	ngoam information
loopback	clear ngoam loopback
statistics	clear ngoam statistics
summary	clear ngoam statistics summary
database	clear ngoam database
session	clear ngoam information by session handle
<i>ses-hdl</i>	specify session handle
all	clear stats for all ping sessions
force	(Optional) Clear it, do not ask to confirm

Command Mode

- /exec

clear ngoam

```
clear ngoam { traceroute { { session { <handle> | all } } | { statistics { summary | { session { <handle> | all } } } } } [ force ] }
```

Syntax Description

clear	Reset functions
ngoam	ngoam information
traceroute	clear ngoam traceroute
statistics	clear ngoam statistics
summary	clear ngoam statistics summary
session	clear ngoam information by session handle
<i>handle</i>	specify session handle
all	clear stats for all traceroute sessions
force	(Optional) Clear it, do not ask to confirm

Command Mode

- /exec

clear ngoam pathtrace

```
clear ngoam pathtrace { { statistics { summary | { session { <handle> | all } } } } | { database { session { <handle> | all } } } } [ force ]
```

Syntax Description

clear	Reset functions
ngoam	ngoam information
pathtrace	clear ngoam pathtrace
database	clear ngoam pathtrace database
statistics	clear ngoam statistics
summary	clear ngoam statistics summary
session	clear ngoam information by session handle
<i>handle</i>	specify session handle
all	clear stats for all pathtrace sessions
force	(Optional) Clear it, do not ask to confirm

Command Mode

- /exec

clear ntp session

clear ntp session

Syntax Description

clear	Reset functions
ntp	Network Time Protocol
session	Clear the ntp configuration session

Command Mode

- /exec

clear ntp statistics

clear ntp statistics { all-peers | io | local | memory }

Syntax Description

clear	Reset functions
ntp	Network Time Protocol
statistics	Clear NTP Statistics
all-peers	Clear per-peer statistics counter of all peers
io	Clear input-output statistics
local	Clear counters maintained by the local NTP
memory	Clear statistics counters related to memory code

Command Mode

- /exec

clear nvram

clear nvram

Syntax Description

clear	Reset functions
nvram	purge NVRAM

Command Mode

- /exec

clear nxapi-server logs

clear nxapi-server logs

Syntax Description

clear	Reset functions
nxapi-server	Clear NX-API Server
logs	Clear NX-API Server logs

Command Mode

- /exec

clear openflow switch controller all

clear openflow switch <switch-id> controller all

Syntax Description

clear	Reset functions
openflow	Clear OpenFlow switch information
switch	Logical switch id
<i>switch-id</i>	Logical switch-id
controller	Controller
all	All

Command Mode

- /exec

clear ospfv3 database

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] database [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Clear the LSDB and all neighbors

Command Mode

- /exec

clear ospfv3 event-history

clear ospfv3 [<tag>] event-history [adjacency | event | ha | flooding | lsa | spf | redistribution | cli | hello | spf-trigger | all]

Syntax Description

clear	Reset functions
ospfv3	Debugging functions
<i>tag</i>	(Optional) Process tag
event-history	Clear the event history buffers
adjacency	(Optional) Adjacency formation logs
event	(Optional) Internal event logs
ha	(Optional) HA and GR logs
flooding	(Optional) LSA flooding logs
lsa	(Optional) LSA generation and database logs
spf	(Optional) SPF calculation logs
redistribution	(Optional) Redistribution logs
cli	(Optional) Cli logs
hello	(Optional) HELLO related logs
spf-trigger	(Optional) SPF TRIGGER related logs
all	(Optional) All event history buffers

Command Mode

- /exec

clear ospfv3 interface

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] interface { * | <interface> } [ vrf {
<vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
interface	Clear one or more interfaces
*	Clear all interfaces
<i>interface</i>	Interface to clear

Command Mode

- /exec

clear ospfv3 neighbor

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] neighbor { * | <neighborid> | <interface>
} [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbor	Clear one or more neighbors
*	Clear all neighbors
<i>neighborid</i>	Source IP address, or router ID of the neighbor
<i>interface</i>	Interface to clear all neighbors on

Command Mode

- /exec

clear ospfv3 policy statistics

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] policy statistics { { redistribute { bgp
<as> | { eigrp | isis | rip } <tag> | static | direct | amt | lisp } } | { area <area-id-ip> filter-list { in | out } } } [
vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
policy	Clear Policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
eigrp	Enhanced Interior Gateway Protocol (EIGRP)
rip	Routing Information Protocol (RIP)
isis	ISO Intermediate-to-Intermediate (IS-IS)
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
static	Static
direct	Directly connected
amt	AMT anycast prefix
lisp	LISP EID-prefixes
area	Configure area properties
<i>area-id-ip</i>	Area Id as an integer or ip address
filter-list	Filter prefixes between OSPF areas
in	Filter networks sent to this area
out	Filter networks sent from this area

<i>tag</i>	
------------	--

Command Mode

- /exec

clear ospfv3 statistics

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Clear statistics counters

Command Mode

- /exec

clear ospfv3 traffic

```
clear ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] traffic [ <interface> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
ospfv3	Clear OSPF tables
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Clear traffic counters
<i>interface</i>	(Optional) Interface to clear all traffic on

Command Mode

- /exec

clear peer-info interface vsan

```
clear peer-info interface <iface> vsan <vsan_id>
```

Syntax Description

clear	Reset functions
peer-info	clear rmid information
interface	clear peer rmid information for a port in a vsan
<i>iface</i>	
vsan	clear peer rmid information
<i>vsan_id</i>	Enter VSAN number

Command Mode

- /exec

clear pktmgr client

clear pktmgr client [<uuid>]

Syntax Description

clear	Reset functions
pktmgr	Clear Packet Manager information
client	Clear pktmgr clients counters
<i>uuid</i>	(Optional) Clear pktmgr client counters for given uuid

Command Mode

- /exec

clear pktmgr interface

clear pktmgr interface [<interface>]

Syntax Description

clear	Reset functions
pktmgr	Clear Packet Manager information
interface	Clear pktmgr related interface information
<i>interface</i>	(Optional) Interface name to display

Command Mode

- /exec

clear plb analytics

clear plb analytics <service-name>

Syntax Description

clear	Reset functions
plb	PLB service
analytics	PLB analytics
<i>service-name</i>	PLB service name

Command Mode

- /exec

clear port-security dynamic address vlan

clear port-security dynamic address <mac-address> vlan <vlanid>

Syntax Description

clear	Reset functions
port-security	Clear port-security information
dynamic	dynamic addresses
address	secure address
<i>mac-address</i>	48 bit mac address
vlan	vlan information
<i>vlanid</i>	vlan id. Enter a value between 1 and 4094

Command Mode

- /exec

clear port-security dynamic interface

clear port-security dynamic interface <if_index> [vlan <vlanid>]

Syntax Description

clear	Reset functions
port-security	Clear port-security information
dynamic	dynamic addresses
interface	interface
<i>if_index</i>	ethernet
vlan	(Optional) vlan information
<i>vlanid</i>	(Optional) vlan id. Enter a value between 1 and 4094

Command Mode

- /exec

clear processes log all

clear processes log all

Syntax Description

clear	Reset functions
processes	process-related clear commands
log	Delete log files
all	Delete all the log files

Command Mode

- /exec

clear processes log all vdc-all

clear processes log all vdc-all

Syntax Description

clear	Reset functions
processes	process-related clear commands
log	Delete log files
all	Delete all the log files
vdc-all	Delete all the log files in all vdc's

Command Mode

- /exec

clear processes log archive

clear processes log archive [file <s0>]

Syntax Description

clear	Reset functions
processes	system manager spawned processes
log	Delete log files
archive	clear all process logs for this vdc from logflash on this module
file	(Optional) delete a log file on logflash
s0	(Optional) Name of file in directory 'log

Command Mode

- /exec

clear processes log pid

clear processes log pid <i0>

Syntax Description

clear	Reset functions
processes	process-related clear commands
log	Delete log files
pid	Delete log file of a specific process
<i>i0</i>	pid of the process

Command Mode

- /exec

clear processes vdc log all

clear processes vdc <e-vdc2> log all

Syntax Description

clear	Reset functions
processes	process-related clear commands
vdc	process-related clear commands in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
log	Delete log files
all	Delete all the log files

Command Mode

- /exec

clear processes vdc log pid

clear processes vdc <e-vdc2> log pid <i1>

Syntax Description

clear	Reset functions
processes	process-related clear commands
vdc	process-related clear commands in vdc
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
log	Delete log files
pid	Delete log file of a specific process
<i>i1</i>	pid of the process

Command Mode

- /exec

clear ptp corrections

clear ptp corrections

Syntax Description

clear	Reset functions
ptp	Precision Time Protocol (IEEE 1588) Subsystem
corrections	Clear history of PTP corrections

Command Mode

- /exec

clear ptp counters interface

clear ptp counters { interface <if0> | all }

Syntax Description

clear	Reset functions
ptp	Precision Time Protocol (IEEE 1588) Subsystem
counters	Clear PTP packet counters
interface	Clear for specific interface
all	Clear for all interfaces
<i>if0</i>	

Command Mode

- /exec

clear qos policies

clear qos policies

Syntax Description

clear	Reset functions
policies	Clear default policies

Command Mode

- /exec

clear qos policies force

clear qos policies force

Syntax Description

clear	Reset functions
policies	Clear default policies
force	Clear forcefully

Command Mode

- /exec

clear qos statistics

```
clear qos statistics [ { interface [ <iface-list> ] | vlan [ <vlan-list> ] } [ input | output ] [ type <qos-or-q> ] ]
```

Syntax Description

clear	Reset functions
statistics	Clear statistics
interface	(Optional) Clear statistics on a interface
<i>iface-list</i>	(Optional) List of Interfaces
vlan	(Optional) 802.1Q vlan
<i>vlan-list</i>	(Optional) List of vlan ids
input	(Optional) Input Service policy
output	(Optional) Output Service policy
type	(Optional) Policy type
<i>qos-or-q</i>	(Optional)

Command Mode

- /exec

clear queuing burst-detect

```
clear queuing burst-detect [ interface <if_name> [ queue <queue_num> ] ] [ module <module> ]
```

Syntax Description

clear	Clear all entries
queuing	Queuing related information
burst-detect	Out of Band micro-burst queue statistics
interface	(Optional) Interface
<i>if_name</i>	(Optional) interface name
queue	(Optional) Queue number for displaying statistics
<i>queue_num</i>	(Optional) Queue number
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

clear queuing pfc-queue

clear queuing pfc-queue [interface <if_list>]

Syntax Description

clear	Reset functions
queuing	clear queuing related counters
pfc-queue	clear watchdog timers
interface	(Optional) Interface
<i>if_list</i>	(Optional) List of interfaces

Command Mode

- /exec

clear queuing pfc-queue interface

clear queuing pfc-queue interface <if_list>

Syntax Description

clear	Reset functions
queuing	clear queuing related counters
pfc-queue	clear watchdog timers
interface	Interface
<i>if_list</i>	List of interfaces

Command Mode

- /exec

clear queuing tah-pfc-queue

```
clear queuing tah-pfc-queue [ interface <if_list> ] [ module <module> ]
```

Syntax Description

clear	Clear
queuing	Queuing related information
tah-pfc-queue	PFC watchdog queuing related stats
interface	(Optional) Interface for clearing queuing stats
<i>if_list</i>	(Optional) List of interfaces
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

clear radius-server statistics

```
clear radius-server statistics <host0> [ __readonly__ { <server_state> [ <clock_time> { monitoring_statistics
<time_in_pstate> <ndead> <tt_in_dstate> } ] } { auth_statistics <auth_failed_transactions>
<auth_succ_transactions> <auth_req_sent> <auth_req_timeout> <auth_resp_no_match>
<auth_resp_not_processed> <auth_resp_error> } { acct_statistics <acct_failed_transactions>
<acct_succ_transactions> <acct_req_sent> <acct_req_timeout> <acct_resp_no_match>
<acct_resp_not_processed> <acct_resp_error> } } ]
```

Syntax Description

clear	Reset functions
radius-server	Clear RADIUS related parameters
statistics	Clear RADIUS statistics
<i>host0</i>	DNS name or IP address
<i>__readonly__</i>	(Optional)
<i>server_state</i>	(Optional) Show state of server
<i>clock_time</i>	(Optional) Show clock time in terms of hours, minutes and seconds
<i>monitoring_statistics</i>	(Optional) Monitoring Statistics
<i>time_in_pstate</i>	(Optional) Time in previous state
<i>ndead</i>	(Optional) Number of times dead
<i>tt_in_dstate</i>	(Optional) Total time in dead state
<i>auth_statistics</i>	(Optional) Authentication Statistics
<i>acct_statistics</i>	(Optional) Accounting Statistics
<i>auth_failed_transactions</i>	(Optional) Authentication: Failed transactions
<i>auth_succ_transactions</i>	(Optional) Authentication: Successful transactions
<i>auth_req_sent</i>	(Optional) Authentication: Requests sent
<i>auth_req_timeout</i>	(Optional) Authentication: Requests timeout
<i>auth_resp_no_match</i>	(Optional) Authentication: Responses with no matching requests
<i>auth_resp_not_processed</i>	(Optional) Authentication: Responses not processed
<i>auth_resp_error</i>	(Optional) Authentication: Responses containing errors
<i>acct_failed_transactions</i>	(Optional) Accounting: Failed transactions
<i>acct_succ_transactions</i>	(Optional) Accounting: Successful transactions

<i>acct_req_sent</i>	(Optional) Accounting: Requests sent
<i>acct_req_timeout</i>	(Optional) Accounting: Requests timeout
<i>acct_resp_no_match</i>	(Optional) Accounting: Responses with no matching requests
<i>acct_resp_not_processed</i>	(Optional) Accounting: Responses not processed
<i>acct_resp_error</i>	(Optional) Accounting: Responses containing errors

Command Mode

- /exec

clear radius session

clear radius session

Syntax Description

clear	Reset functions
radius	clear to be committed RADIUS config and lock in fabric
session	clear to be committed RADIUS config and lock in fabric

Command Mode

- /exec

clear rmon

clear rmon { alarms | events | logs | hcalarms | all-alarms }

Syntax Description

clear	Reset functions
rmon	Clear RMON tables
alarms	Clear all 32 bit alarms
events	Clear rmon log this also clears rmon event table
logs	Clear rmon log
hcalarms	Clear all 64 bit rmon alarms
all-alarms	Clear all 32 bit and 64 bit rmon alarms

Command Mode

- /exec

clear route-map pbr-statistics

clear route-map { <route-map-name> | <route-map-cfg-name> } pbr-statistics

Syntax Description

clear	Reset functions
route-map	Route-map used for PBR
<i>route-map-name</i>	Route-map name
<i>route-map-cfg-name</i>	Known route-map name
pbr-statistics	Statistics for policy based routing

Command Mode

- /exec

clear routing event-history

```
clear routing [ ip | ipv4 ] [ unicast ] event-history { add-route | cli | delete-route | detail | errors | general | ha |
loop-detection | modify-route | notifications | recursive-next-hop | summary | ufdm | ufdm-detail | ufdm-summary
}
```

Syntax Description

clear	Reset functions
routing	Clear routing information
ip	(Optional) Clear IP commands
ipv4	(Optional) Clear IP commands
unicast	(Optional) Clear unicast information
event-history	Clear routing event log
add-route	Add route
cli	CLI
delete-route	Delete route
detail	Detail
errors	Errors
general	General
ha	HA
loop-detection	Loop detection
modify-route	Modify route
notifications	Notification
recursive-next-hop	Recursive next hop
summary	Summary
ufdm	UFDM
ufdm-detail	UFDM Detail
ufdm-summary	UFDM Summary

Command Mode

- /exec

clear routing ip multicast mfdm pending counters

clear routing ip multicast mfdm pending counters [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
routing	Clear routing information
ip	Clear IP commands
multicast	Clear MRIB information
mfdm	Clear MFDM information
pending	Clear MFDM pending information
counters	MFDM counters
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear routing ip multicast rpf-source retry-cache

clear routing ip multicast rpf-source retry-cache [vrf { <vrf-name> | <vrf-known-name> | all }]

Syntax Description

clear	Reset functions
routing	Clear routing information
ip	Clear IP commands
multicast	Clear MRIB information
rpf-source	Clear RPF-Source information
retry-cache	Clear retry-cache information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear routing ipv6 event-history

clear routing ipv6 [unicast] event-history { am | cli | detail | errors | general | ha | lfe | recursive-next-hop | summary | ufdm | ufdm-detail | ufdm-summary }

Syntax Description

clear	Reset functions
routing	Clear routing information
ipv6	Clear IPv6 commands
unicast	(Optional) Clear unicast information
event-history	Clear routing event log
am	AM
cli	CLI
detail	Detail
errors	Errors
general	General
ha	HA
lfe	LFE
recursive-next-hop	Recursive next hop
summary	Summary
ufdm	UFDM
ufdm-detail	UFDM Detail
ufdm-summary	UFDM Summary

Command Mode

- /exec

clear routing ipv6 multicast

```
clear routing ipv6 multicast { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> |
<vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
routing	Clear routing information
ipv6	Clear IPv6 commands
multicast	Clear multicast routing table
all	Clear all routes
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear routing multicast

```
clear routing [ ip | ipv4 ] multicast { <all> | <group-prefix> | <group> [ <source> ] } [ vrf { <vrf-name> | <vrf-known-name> | all } ]
```

Syntax Description

clear	Reset functions
routing	Clear routing information
ip	(Optional) Clear IP commands
ipv4	(Optional) Clear IP commands
multicast	Clear multicast routing table
all	Clear all routes
<i>group-prefix</i>	Clear all routes within the Group prefix
<i>group</i>	Clear all routes matching Group
<i>source</i>	(Optional) Clear a (S,G) route
vrf	(Optional) Clear information for particular VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs

Command Mode

- /exec

clear scheduler logfile

clear scheduler logfile

Syntax Description

clear	Reset functions
scheduler	Scheduler clear commands
logfile	Clear scheduler log file

Command Mode

- /exec

clear screen

clear screen

Syntax Description

clear	Reset functions
screen	Clear screen

Command Mode

- /exec

clear session state name

clear session state name <s4>

Syntax Description

clear	Reset functions
session	Reset cfg session internals
state	Reset cfg session internal state
name	Reset cfg session internal state for a given name
<i>s4</i>	Enter the name of the session

Command Mode

- /exec

clear sflow statistics

clear sflow statistics

Syntax Description

clear	Reset functions
sflow	sFlow global configuration
statistics	Clear sFlow statistics

Command Mode

- /exec

clear snmp counters

clear snmp counters

Syntax Description

clear	Reset functions
snmp	Clear SNMP Tables
counters	Clear SNMP counters

Command Mode

- /exec

clear snmp hostconfig

clear snmp hostconfig

Syntax Description

clear	Reset functions
snmp	Clear SNMP Tables
hostconfig	Clear SNMP Host List

Command Mode

- /exec

clear sockets statistics

clear sockets statistics { all | tcp | tcp6 | udp | udp6 | raw | raw6 }

Syntax Description

clear	Reset functions
sockets	Clear sockets statistics
statistics	Clear sockets statistics
all	Clear TCP/UDP/RAW v4/v6 statistics
tcp	Clear TCP v4 statistics
tcp6	Clear TCP v6 statistics
udp	Clear UDP v4 statistics
udp6	Clear UDP v6 statistics
raw	Clear RAW v4 statistics
raw6	Clear RAW v6 statistics

Command Mode

- /exec

clear spanning-tree counters

clear spanning-tree counters [interface <interface-id> | vlan <vlan-id> | bridge-domain <bd-id>]

Syntax Description

clear	Reset functions
spanning-tree	Spanning Tree Subsystem
counters	Clear spanning tree statistics
interface	(Optional) Specify an interface as a target for the command
<i>interface-id</i>	(Optional) Specify an interface as a target for the command
vlan	(Optional) VLAN Switch Spanning Trees
bridge-domain	(Optional) Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	(Optional) vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	(Optional) Bridge-Domain range, Example: 2,4-5,7,9-11

Command Mode

- /exec

clear spanning-tree detected-protocols

clear spanning-tree detected-protocols [interface <interface-id>]

Syntax Description

clear	Reset functions
spanning-tree	Spanning Tree Subsystem
detected-protocols	Restart the protocol migration process
interface	(Optional) Specify an interface as a target for the command
<i>interface-id</i>	(Optional) Specify an interface as a target for the command

Command Mode

- /exec

clear spanning-tree sps-hist

clear spanning-tree sps-hist

Syntax Description

clear	Reset functions
spanning-tree	Spanning Tree Subsystem
sps-hist	Set port state stats

Command Mode

- /exec

clear ssh hosts

clear ssh hosts

Syntax Description

clear	Reset functions
ssh	Clear ssh values
hosts	Clear the list of trusted ssh hosts

Command Mode

- /exec

clear statistics module-all

clear statistics module-all

Syntax Description

clear	Clear statistics
statistics	Stats
module-all	Clear stats of all modules

Command Mode

- /exec

clear statistics module

clear statistics module <module>

Syntax Description

clear	Clear statistics
statistics	Stats
module	Clear stats of a single module
<i>module</i>	Enter module number

Command Mode

- /exec

clear sup-monitor drops session

clear sup-monitor drops session <session_number> [module <module>]

Syntax Description

clear	Clear the monitor drop counters
sup-monitor	Show Ethernet SPAN information
drops	show the drops
session	span session number
<i>session_number</i>	
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

clear system login failures

clear system login failures

Syntax Description

clear	Reset functions
system	System management commands
login	Secure Login
failures	Clear login failures in the current watch period

Command Mode

- /exec

clear system reset-reason

clear system reset-reason

Syntax Description

clear	Reset functions
system	Clear logs in system
reset-reason	Clear reset-reason logs in the system

Command Mode

- /exec

clear tacacs-server statistics

```
clear tacacs-server statistics <host0> [ __readonly__ { <server_state> [ <clock_time> { monitoring_statistics
<time_in_pstate> <ndead> <tt_in_dstate> } ] } } { auth_statistics <auth_failed_transactions>
<auth_succ_transactions> <auth_req_sent> <auth_req_timedout> <auth_resp_no_match>
<auth_resp_not_processed> <auth_resp_error> } { autho_statistics <autho_failed_transactions>
<autho_succ_transactions> <autho_req_sent> <autho_req_timedout> <autho_resp_no_match>
<autho_resp_not_processed> <autho_resp_error> } { acct_statistics <acct_failed_transactions>
<acct_succ_transactions> <acct_req_sent> <acct_req_timedout> <acct_resp_no_match>
<acct_resp_not_processed> <acct_resp_error> } ]
```

Syntax Description

clear	Reset functions
tacacs-server	Clear TACACS related parameters
statistics	Clear TACACS statistics
<i>host0</i>	DNS name or IP address
<i>__readonly__</i>	(Optional)
<i>server_state</i>	(Optional) Show state of server
<i>clock_time</i>	(Optional) Show clock time in terms of hours, minutes and seconds
monitoring_statistics	(Optional) Monitoring Statistics
<i>time_in_pstate</i>	(Optional) Time in previous state
<i>ndead</i>	(Optional) Number of times dead
<i>tt_in_dstate</i>	(Optional) Total time in dead state
auth_statistics	(Optional) Authentication Statistics
autho_statistics	(Optional) Authorization Statistics
acct_statistics	(Optional) Accounting Statistics
<i>auth_failed_transactions</i>	(Optional) Authentication: Failed transactions
<i>auth_succ_transactions</i>	(Optional) Authentication: Successful transactions
<i>auth_req_sent</i>	(Optional) Authentication: Requests sent
<i>auth_req_timedout</i>	(Optional) Authentication: Requests timedout
<i>auth_resp_no_match</i>	(Optional) Authentication: Responses with no matching requests
<i>auth_resp_not_processed</i>	(Optional) Authentication: Responses not processed
<i>auth_resp_error</i>	(Optional) Authentication: Responses containing errors

<i>autho_failed_transactions</i>	(Optional) Authorization: Failed transactions
<i>autho_succ_transactions</i>	(Optional) Authorization: Successful transactions
<i>autho_req_sent</i>	(Optional) Authorization: Requests sent
<i>autho_req_timeout</i>	(Optional) Authorization: Requests timeout
<i>autho_resp_no_match</i>	(Optional) Authorization: Responses with no matching requests
<i>autho_resp_not_processed</i>	(Optional) Authorization: Responses not processed
<i>autho_resp_error</i>	(Optional) Authorization: Responses containing errors
<i>acct_failed_transactions</i>	(Optional) Accounting: Failed transactions
<i>acct_succ_transactions</i>	(Optional) Accounting: Successful transactions
<i>acct_req_sent</i>	(Optional) Accounting: Requests sent
<i>acct_req_timeout</i>	(Optional) Accounting: Requests timeout
<i>acct_resp_no_match</i>	(Optional) Accounting: Responses with no matching requests
<i>acct_resp_not_processed</i>	(Optional) Accounting: Responses not processed
<i>acct_resp_error</i>	(Optional) Accounting: Responses containing errors

Command Mode

- /exec

clear tech-support lock

clear tech-support lock

Syntax Description

clear	Reset functions
tech-support	Gather information for troubleshooting
lock	Clear the lock which prohibits multiple show techs to run in parallel

Command Mode

- /exec

clear tech-support lock

clear tech-support lock

Syntax Description

clear	Reset functions
tech-support	Gather information for troubleshooting
lock	Clear the lock which prohibits multiple show techs to run in parallel

Command Mode

- /exec

clear user

clear user <*s0*>

Syntax Description

clear	Reset functions
user	Logout a particular user
<i>s0</i>	Enter the username

Command Mode

- /exec

clear veobc counters

clear veobc counters

Syntax Description

clear	Reset function
veobc	Reset the veobc counters
counters	Reset the veobc statistic counters to zero

Command Mode

- /exec

clear vlan access-list counters

clear vlan access-list counters [<name>]

Syntax Description

clear	Reset functions
vlan	Vlan commands
access-list	Clear access list statistical information
counters	Clear access list counters
<i>name</i>	(Optional) List name

Command Mode

- /exec

clear vlan counters

clear vlan [id <vlan-id>] counters

Syntax Description

clear	Reset functions
vlan	Vlan commands
id	(Optional) clear VLAN counters by VLAN id
<i>vlan-id</i>	(Optional) VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
counters	display counters

Command Mode

- /exec

clear vmtracker counters

clear vmtracker counters

Syntax Description

clear	Clear
vmtracker	Clear vmtracker info
counters	Clear vmtracker counter info

Command Mode

- /exec

clear vpc statistics all

clear vpc statistics all

Syntax Description

clear	Reset functions
vpc	Virtual Port Channel configuration
statistics	Statistics
all	All vPC statistics

Command Mode

- /exec

clear vpc statistics peer-keepalive

clear vpc statistics peer-keepalive

Syntax Description

clear	Reset functions
vpc	Virtual Port Channel configuration
statistics	Statistics
peer-keepalive	peer keepalive module related statistics

Command Mode

- /exec

clear vpc statistics vpc

```
clear vpc statistics { vpc <vpc_num> | peer-link }
```

Syntax Description

clear	Reset functions
vpc	Statistics for a specific vPC
statistics	Statistics
<i>vpc_num</i>	Virtual Port Channel number
peer-link	stats for peer-link

Command Mode

- /exec

clear vpc transport statistics

clear vpc transport statistics [*__readonly__* <last-clear-time>]

Syntax Description

clear	Reset functions
vpc	Virtual Port Channel configuration
transport	cfs transport
statistics	Statistics
<i>__readonly__</i>	(Optional) Read Only
<i>last-clear-time</i>	(Optional) time difference from last clear time

Command Mode

- /exec/

clear vrrp statistics

```
clear vrrp statistics [ interface <intf_num> ] [ vr <vr_id> ]
```

Syntax Description

clear	Reset functions
vrrp	Clear virtual router
statistics	Clear global virtual router statistics
interface	(Optional) Select interface
<i>intf_num</i>	(Optional)
vr	(Optional) [1-255] clear virtual router statistics
<i>vr_id</i>	(Optional)

Command Mode

- /exec

clear vrrpv3 event-history

```
clear vrrpv3 event-history { debugs | errors | msgs | all }
```

Syntax Description

clear	Reset functions
vrrpv3	VRRPv3 Clear commands
event-history	Clear event history buffers of vrrpv3
debugs	Clear debug event buffer of vrrpv3
errors	Clear errors event buffer of vrrpv3
msgs	Clear MTS event buffer of vrrpv3
all	Clear all event buffers of vrrpv3

Command Mode

- /exec

clear vrrpv3 statistics

```
clear vrrpv3 statistics [ <interface_num> [ <group_num> ] ] [ <opt_v4_or_v6> ]
```

Syntax Description

clear	Reset functions
vrrpv3	VRRPv3 Clear commands
statistics	VRRPV3 statistics
<i>interface_num</i>	(Optional) Interface
<i>group_num</i>	(Optional) Group number
<i>opt_v4_or_v6</i>	(Optional) Enter ipv4 or ipv6

Command Mode

- /exec

clear vtp counters

clear vtp counters

Syntax Description

clear	Reset functions
vtp	Clear VTP items
counters	Clear VTP counters

Command Mode

- /exec

cli alias name

{ cli alias name <s0> <line> | no cli alias name <s0> [<line>] }

Syntax Description

no	Negate a command or set its defaults
cli	Configure CLI commands
alias	Define an alias
name	Specify the alias
<i>s0</i>	Alias command
<i>line</i>	Alias definition

Command Mode

- /exec/configure

cli create new-cmd

{ cli create new-cmd <s0> | no cli create new-cmd <s0> }

Syntax Description

no	Negate a command or set its defaults
cli	Configure cli commands
create	Create a new cli
new-cmd	Specify the new cli
s0	new cli command (should include spaces)

Command Mode

- /exec/configure

cli var name

cli no var name <s0>

Syntax Description

cli	CLI commands
no	Negate a command or set its defaults
var	Unset a variable
name	Specify a variable name
s0	Variable name

Command Mode

- /exec

cli var name

{ cli var name <s0> <line> | no cli var name <s0> [<line>] }

Syntax Description

no	Negate a command or set its defaults
cli	Configure CLI commands
var	Define a variable
name	Specify a variable name
<i>s0</i>	Variable name
<i>line</i>	Variable value

Command Mode

- /exec/configure

cli var name

[no] cli var name <s0>

Syntax Description

no	Negate a command or set its defaults
cli	CLI commands
var	Unset a variable
name	Specify a variable name
s0	Variable name

Command Mode

- /exec

cli var name

cli var name <*s0*> <*line*>

Syntax Description

cli	CLI commands
var	Define a variable
name	Specify a variable name
<i>s0</i>	Variable name
<i>line</i>	Variable value

Command Mode

- /exec

cli verifyrun

[no] cli verifyrun

Syntax Description

no	(Optional) Negate a command or set its defaults
cli	CLI commands
verifyrun	Verify and run

Command Mode

- /exec

client-to-client reflection

[no] client-to-client reflection

Syntax Description

no	(Optional) Negate a command or set its defaults
client-to-client	Configure client-to-client route reflection
reflection	reflection of routes permitted

Command Mode

- /exec/configure/router-bgp/router-bgp-af

clis all

clis { no debug | undebug } all

Syntax Description

clis	dcos cli command
no	Negate a command or set its defaults
undebug	Disable Debugging functions (See also debug)
debug	Debugging functions
all	Disable

Command Mode

- /exec

clock-tolerance ntp oneway absolute

```
{ { no | default } clock-tolerance | clock-tolerance ntp oneway { absolute <abs-value> | percent <percentage> } }
```

Syntax Description

no	
<i>clock-tolerance</i>	ntp
default	Set a command to its defaults
clock-tolerance	Set acceptable clock synchronization error
ntp	Acceptable clock synchronization error due to NTP
oneway	Acceptable clock synchronization error in oneway measurement
absolute	Acceptable error in microseconds
percent	Acceptable error as percent of value measured
<i>abs-value</i>	Number in microseconds
<i>percentage</i>	Percentage of one-way delay

Command Mode

- /exec/configure/ip-sla/jitter

clock format 12

[no] clock format { 12-hours | 24-hours }

Syntax Description

no	(Optional) Negate a command or set its defaults
clock	Clock
format	Display format of clock
12-hours	12 hours display
24-hours	24 hours display

Command Mode

- /exec/configure

clock format show-timezone debug

[no] clock format show-timezone debug

Syntax Description

no	(Optional) Negate a command or set its defaults
clock	Clock
format	Display format of clock
show-timezone	Display the configured timezone
debug	Display the configured timezone in debugs

Command Mode

- /exec/configure

clock format show-timezone syslog

[no] clock format show-timezone syslog

Syntax Description

no	(Optional) Negate a command or set its defaults
clock	Clock
format	Display format of clock
show-timezone	Display the configured timezone
syslog	Display the configured timezone in syslogs

Command Mode

- /exec/configure

clock protocol

[no] clock protocol { ntp | ptp | none } [vdc <vdc-id>]

Syntax Description

no	(Optional) Negate a command or set its defaults
clock	Clock
protocol	protocol
ntp	ntp
ptp	ptp
none	none (clock can be set manually)
vdc	(Optional) vdc
<i>vdc-id</i>	(Optional) vdc-id

Command Mode

- /exec/configure

clock set

clock set <s0> <i0> { April <i1> | August <i2> | December <i3> | February <i4> | January <i5> | July <i6> | June <i7> | March <i8> | May <i9> | November <i10> | October <i11> | September <i12> }

Syntax Description

clock	Clock
set	HH:MM:SS Current Time
s0	HH:MM:SS Current Time
i0	Day of the month
April	Month of the year
i1	Enter the year (no abbreviation)
August	Month of the year
i2	Enter the year (no abbreviation)
December	Month of the year
i3	Enter the year (no abbreviation)
February	Month of the year
i4	Enter the year (no abbreviation)
January	Month of the year
i5	enter the year (no abbreviation)
July	Month of the year
i6	Enter the year (no abbreviation)
June	Month of the year
i7	Enter the year (no abbreviation)
March	Month of the year
i8	Enter the year (no abbreviation)
May	Month of the year
i9	Enter the year (no abbreviation)
November	Month of the year
i10	Enter the year (no abbreviation)

October	Month of the year
<i>i11</i>	Enter the year (no abbreviation)
September	Month of the year
<i>i12</i>	Enter the year (no abbreviation)

Command Mode

- /exec

clock summer

```
{ clock { summer-time <s0> [ <i0> <s1> <s2> <s3> <i1> <s4> <s5> <s6> [ <i2> ] ] | timezone <s7> <i3>
<i4> } | no clock { summer-time [ <s0> <i0> <s1> <s2> <s3> <i1> <s4> <s5> <s6> <i2> ] | timezone [ <s7>
<i3> <i4> ] } }
```

Syntax Description

no	Negate a command or set its defaults
clock	Clock
summer-time	Configure summer (daylight savings) time
<i>s0</i>	Name of time zone in summer, such as PDT, CDT, EDT, etc..
<i>i0</i>	(Optional) Week number to start (first week=1, last week=5)
<i>s1</i>	(Optional) Weekday to start
<i>s2</i>	(Optional) Month to start
<i>s3</i>	(Optional) HH:MM Time to start
<i>i1</i>	(Optional) Week number to end (first week=1, last week=5)
<i>s4</i>	(Optional) Weekday to end
<i>s5</i>	(Optional) Month to end
<i>s6</i>	(Optional) HH:MM Time to end
<i>i2</i>	(Optional) Offset to add in minutes
timezone	Configure time zone
<i>s7</i>	Name of time zone, such as PST, MST, CST, EST, etc..
<i>i3</i>	Hours offset from UTC
<i>i4</i>	Minutes offset from UTC

Command Mode

- /exec/configure

clock sync-interval

[no] clock sync-interval <intv>

Syntax Description

no	(Optional) Negate a command or set its defaults
clock	Clock
sync-interval	sync-interval in seconds
<i>intv</i>	interval

Command Mode

- /exec/configure

cluster-id

[no] cluster-id { <ip-cluster-id> | <int-cluster-id> }

Syntax Description

no	(Optional) Negate a command or set its defaults
cluster-id	Configure Route Reflector Cluster-ID
<i>ip-cluster-id</i>	Cluster-id as an IP address
<i>int-cluster-id</i>	Cluster-id as a 32 bit quantity

Command Mode

- /exec/configure/router-bgp/vrf-cmds

collect

[no] collect { ingress queue depth | ingress queue drops }

Syntax Description

collect	Stats type to be configured
ingress	Ingress counter
queue	Queue statistics
depth	Depth
drops	Drops

Command Mode

- /exec/configure/config-ssx-record

collect

```
{ [ no ] collect { port-id | hop-latency | queue-occupancy | queue-congestion | ingress-timestamp | egress-timestamp | egress-tx-util } }
```

Syntax Description

collect	Specify a collect field
port-id	Port Identifier
hop-latency	Latency in this hop
queue-occupancy	Queue occupancy
queue-congestion	Queue congestion
ingress-timestamp	Timestamp at ingress
egress-timestamp	Timestamp at egress
egress-tx-util	Egress utilization

Command Mode

- /exec/configure/config-int-record

collect

[no] collect { egress queue depth | egress queue drops | egress queue microburst | egress queue peak }

Syntax Description

collect	Stats type to be configured
egress	Egress counter
queue	Queue statistics
depth	Depth
drops	Drops
microburst	Microburst records
peak	Buffer peak counters

Command Mode

- /exec/configure/config-ssx-record

collect

[no] collect { egress buffer depth }

Syntax Description

collect	Stats type to be configured
egress	Egress counter
buffer	Buffer statistics
depth	Depth

Command Mode

- /exec/configure/config-ssx-record

collect

[no] collect { egress pool-group depth }

Syntax Description

collect	Stats type to be configured
egress	Egress counter
pool-group	Pool-group statistics
depth	Depth

Command Mode

- /exec/configure/config-ssx-record

collect

[no] collect { ethernet counters }

Syntax Description

collect	Stats type to be configured
ethernet	Ethernet counter
counters	Ethernet counters

Command Mode

- /exec/configure/config-ssx-record

collect counter bytes

[no] collect counter { bytes | packets } [long]

Syntax Description

collect	Specify a non-key field
counter	Counters to collect
bytes	Total number of bytes
packets	Total number of packets
long	(Optional) Long counter (64 bits)

Command Mode

- /exec/configure/nfm-record

collect ip version

[no] collect ip version

Syntax Description

collect	Specify a non-key field
ip	IP attributes
version	IPv4 or IPv6

Command Mode

- /exec/configure/nfm-record

collect timestamp sys-uptime first

[no] collect timestamp sys-uptime { first | last }

Syntax Description

collect	Specify a non-key field
timestamp	Timestamp fields
sys-uptime	System uptime
first	Time the first packet was seen
last	Time the most recent packet was seen

Command Mode

- /exec/configure/nfm-record

collect transport tcp flags

[no] collect transport tcp flags

Syntax Description

collect	Specify a non-key field
transport	Transport layer fields
tcp	TCP layer fields
flags	TCP flags

Command Mode

- /exec/configure/nfm-record

color

{ no color | color <color> }

Syntax Description

no	Negate a command or set its defaults
color	Policy Color
<i>color</i>	Policy Color

Command Mode

- /exec/configure/sr/te/pol

commit

commit

Syntax Description

commit	commit plb session
--------	--------------------

Command Mode

- /exec/configure/plb-session-device-group

commit

commit

Syntax Description

commit	Commit the current configuration session
--------	--

Command Mode

- /exec/configure

commit

commit

Syntax Description

commit	commit itd session
--------	--------------------

Command Mode

- /exec/configure/itd-session-device-group

commit verbose

commit verbose

Syntax Description

commit	Commit the current configuration session
verbose	Commit the current configuration session with more details

Command Mode

- /exec/configure

compress-bitfields ipv6 multicast

[no] compress-bitfields ipv6 multicast

Syntax Description

no	(Optional) Negate a command or set its defaults
compress-bitfields	Compress bitfields for improved memory utilization
ipv6	Use for IPv6 multicast
multicast	Use compressed bitfields for M6RIB and PIM6

Command Mode

- /exec/configure

compress-bitfields ipv6 multicast

[no] compress-bitfields ipv6 multicast

Syntax Description

no	(Optional) Negate a command or set its defaults
compress-bitfields	Compress bitfield for improved memory utilization
ipv6	Use for IPv6 multicast
multicast	Use compressed bitfields for M6RIB and PIM

Command Mode

- /exec/configure

compress-bitfields multicast

[no] compress-bitfields [ipv4] multicast

Syntax Description

no	(Optional) Negate a command or set its defaults
compress-bitfields	Compress bitfield for improved memory utilization
ipv4	(Optional) Use for IPv4 multicast
multicast	Use compressed bitfields for MRIB and PIM

Command Mode

- /exec/configure

conf-offset

[no] conf-offset <offset>

Syntax Description

conf-offset	Configure Confidentiality offset
<i>offset</i>	Confidentiality offset options

Command Mode

- /exec/configure/masec-policy

confederation identifier

[no] confederation identifier <confed-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
confederation	AS confederation parameters
identifier	Set routing domain confederation AS
<i>confed-id</i>	AS number

Command Mode

- /exec/configure/router-bgp/vrf-cmds

confederation peers

[no] confederation peers <confed-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
confederation	AS confederation parameters
peers	Peer ASs in BGP confederation
<i>confed-id</i>	AS number

Command Mode

- /exec/configure/router-bgp/vrf-cmds

config-source controller

[no] config-source controller

Syntax Description

no	(Optional) Negate a command or set its defaults
config-source	Configuration source for this NVE interface. Defaults to CLI
controller	Controller

Command Mode

- /exec/configure/if-nve

configure

configure [terminal]

Syntax Description

configure	Enter configuration mode
terminal	(Optional) Configure the system from terminal input

Command Mode

- /exec

configure config-template on substitute

[no] configure config-template <name> { on-vrf-create | on-vrf-delete } substitute <match_replace>

Syntax Description

no	(Optional) Negate a command or set its defaults
configure	Enter configuration mode
config-template	Configuration-template
<i>name</i>	Configuration-template name
on-vrf-create	Configuration-template for create action
on-vrf-delete	Configuration-template for delete action
substitute	Configuration-template substitute
<i>match_replace</i>	string in match:replace format for substitution

Command Mode

- /exec

configure maintenance profile normal

[no] configure maintenance profile { normal-mode | maintenance-mode }

Syntax Description

no	(Optional) Negate a command or set its defaults
configure	Enter configuration mode
maintenance	maintenance profile mode
profile	maintenance profile
normal-mode	Normal mode profile
maintenance-mode	Maintenance mode profile

Command Mode

- /exec

configure profile

[no] configure profile <all_conf_profile_name> [type admin]

Syntax Description

no	(Optional) Negate a command or set its defaults
configure	Enter configuration mode
profile	Configure profile
<i>all_conf_profile_name</i>	Enter the name of the configure profile
type	(Optional) config profile type
admin	(Optional) config profile admin type

Command Mode

- /exec

configure replace

```
configure replace { <uri_local> | <uri_remote> [ source-interface <intf> | vrf <vrf-known-name> ] } [ [ [
verbose ] [ debug | stop-at-first-failure ] [ commit-timeout <time> ] [ non-interactive ] ] | show-patch ]
```

Syntax Description

configure	Configure the box
replace	Perform a replace of the running-config
<i>uri_local</i>	Configuration file to use
<i>uri_remote</i>	Configuration file to use
source-interface	(Optional) Select source interface
<i>intf</i>	(Optional)
vrf	(Optional) Display per-VRF information
verbose	(Optional) Show the logs of operation
show-patch	(Optional) Show the patch to be applied
debug	(Optional) Skip errors and proceed with rollback
stop-at-first-failure	(Optional) Stop config-replace at the first error
commit-timeout	(Optional) specify config replace commit timeout value
<i>time</i>	(Optional) Timeout in seconds
non-interactive	(Optional) No user prompt in maintenance mode
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

configure replace abort

configure replace abort

Syntax Description

configure	Configure the box
replace	Perform a replace of the running-config
abort	Aborting config replace operation

Command Mode

- /exec

configure replace commit

configure replace commit

Syntax Description

configure	Configure the box
replace	Perform a replace of the running-config
commit	Commit config replace operation

Command Mode

- /exec

configure session

configure session <s0>

Syntax Description

configure	Enter configuration mode
session	Configure the system in a session
s0	Enter the name of the session

Command Mode

- /exec

configure sync

configure sync

Syntax Description

configure	Enter configuration mode
sync	Configure the system in config-sync mode

Command Mode

- /exec

congestion-control dctp ecn-threshold bytes

[no] congestion-control dctp ecn-threshold <threshold> { bytes }

Syntax Description

no	(Optional) Negate a command or set its defaults
congestion-control	Congestion Control Protocol
dctp	Data Center TCP
ecn-threshold	Explicit Congestion Notification - threshold
<i>threshold</i>	Threshold in bytes
bytes	Bytes

Command Mode

- /exec/configure/policy-map/type/uf/class

congestion-control ecn

[no] congestion-control ecn

Syntax Description

no	(Optional) Negate a command or set its defaults
congestion-control	Congestion Control Protocol
ecn	Enable ECN protocol

Command Mode

- /exec/configure/policy-map/type/uf/class

congestion-control random-detect

```
[no] congestion-control random-detect { [ threshold { burst-optimized | mesh-optimized } ] | {
minimum-threshold <min-thresh> [ packets | bytes | kbytes | mbytes ] maximum-threshold <max-thresh> [
packets1 | bytes1 | kbytes1 | mbytes1 ] drop-probability <drop-prob> } } { [ ecn ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
congestion-control	Congestion Control Protocol
random-detect	Enable WRED protocol
threshold	(Optional) Threshold
minimum-threshold	Minimum Threshold
maximum-threshold	Maximum Threshold
burst-optimized	(Optional) Threshold optimized for bursty traffic
mesh-optimized	(Optional) Threshold optimized for mesh traffic
drop-probability	Drop Probability at Maximum Threshold
<i>drop-prob</i>	Drop Probability Value
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo Bytes
mbytes	(Optional) Mega Bytes
packets1	(Optional) Packets
bytes1	(Optional) Bytes
kbytes1	(Optional) Kilo Bytes
mbytes1	(Optional) Mega Bytes
ecn	(Optional) Explicit Congestion Notification

Command Mode

- /exec/configure/policy-map/type/uf/class

congestion-control random-detect forward-nonecn

[no] congestion-control random-detect forward-nonecn

Syntax Description

no	(Optional) Negate the command
congestion-control	Congestion control protocol
random-detect	Enable WRED protocol
forward-nonecn	Forward non ECN capable traffic without WRED dropping

Command Mode

- /exec/configure

congestion-control random-detect global-buffer minimum-threshold maximum-threshold

[no] congestion-control random-detect global-buffer minimum-threshold { <min-thresh> [packets | bytes | kbytes | mbytes] } maximum-threshold { <max-thresh> [packets1 | bytes1 | kbytes1 | mbytes1] }

Syntax Description

no	(Optional) Negate the command
congestion-control	Congestion control protocol
random-detect	Enable WRED protocol
global-buffer	global buffer threshold
minimum-threshold	Specify minimum threshold for WRED
<i>min-thresh</i>	Minimum threshold value
maximum-threshold	Specify maximum threshold for WRED
<i>max-thresh</i>	Maximum threshold value
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
packets1	(Optional) Packets
bytes1	(Optional) Bytes
kbytes1	(Optional) Kilo Bytes
mbytes1	(Optional) Mega Bytes

Command Mode

- /exec/configure

congestion-control tail-drop

[no] congestion-control tail-drop [threshold { burst-optimized | mesh-optimized }]

Syntax Description

no	(Optional) Negate a command or set its defaults
congestion-control	Congestion Control Protocol
tail-drop	Enable Tail-Drop
threshold	(Optional) Threshold
burst-optimized	(Optional) Threshold optimized for bursty traffic
mesh-optimized	(Optional) Threshold optimized for mesh traffic

Command Mode

- /exec/configure/policy-map/type/uf/class

connect

[no] connect

Syntax Description

no	(Optional) Negate a command or set its defaults
connect	Connect to remote host

Command Mode

- /exec/configure/vmt-conn

connected-prefix-sid-map

[no] connected-prefix-sid-map

Syntax Description

no	(Optional) Negate a command or set its defaults
connected-prefix-sid-map	Configure connected prefix Segment Identifier mappings

Command Mode

- /exec/configure/config-sr-mps

continue

{ continue <value> } | { no continue [<value>] }

Syntax Description

no	Negate a command or set its defaults
continue	Continue on a different entry within the route-map
<i>value</i>	Route-map entry sequence number

Command Mode

- /exec/configure/route-map

contract-id

{ contract-id <s0> | no contract-id }

Syntax Description

no	Negate a command or set its defaults
contract-id	Service contract id of the customer
s0	Provide contract number (as specified in the service agreement)

Command Mode

- /exec/configure/callhome

control-plane

control-plane

Syntax Description

control-plane	Enter to control-plane sub-mode
---------------	---------------------------------

Command Mode

- /exec/configure

control-plane dynamic

control-plane dynamic

Syntax Description

control-plane	Enter to control-plane sub-mode
dynamic	dynamic mode

Command Mode

- /exec/configure

control vlan

[no] control vlan <vlan-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
control	Configure PLB control vlan
vlan	control vlan
<i>vlan-id</i>	vlan id

Command Mode

- /exec/configure/plb-inout

control vlan

[no] control vlan <vlan-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
control	ITD control vlan
vlan	control vlan
<i>vlan-id</i>	Control vlan id

Command Mode

- /exec/configure/itd-inout

controller-credentials username password 0

[no] controller-credentials username <user> password { 0 <clear> | 7 <encrypted> }

Syntax Description

no	(Optional) Negate a command or set its defaults
controller-credentials	NBM Controller login credentials
username	User ID
<i>user</i>	Enter user ID
password	Password
0	Password that follows should be in clear text
<i>clear</i>	Password in clear text
7	Password that follows should be encrypted text
<i>encrypted</i>	Encrypted password

Command Mode

- /exec/configure/nbm-controller

controller description

{ controller description <ctrlr-desc> | no controller description }

Syntax Description

no	Negate a command or set its defaults
controller	Controller command
description	Controller description
<i>ctrlr-desc</i>	String description of the controller

Command Mode

- /exec/configure/controller-type

controller ip vrf

[no] controller ip <cntlr-ip> vrf { <vrf-name> | <vrf-known-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
controller	Controller
ip	IP Address
<i>cntlr-ip</i>	IP Address of Controller
vrf	vrf context
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/nbm-controller

controller ipv4

```
[no] controller ipv4 <ipv4> [ port <tcpport> ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ security { none |
tls } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
controller	OpenFlow controller to use
ipv4	Controller ipv4 address (A.B.C.D)
<i>ipv4</i>	IP address (A.B.C.D)
port	(Optional) Controller TCP port (default is 6653)
<i>tcpport</i>	(Optional) TCP port number (default port is 6653)
vrf	(Optional) Controller VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
security	(Optional) Set security protocol
none	(Optional) Disable security protocol
tls	(Optional) Enable security protocol

Command Mode

- /exec/configure/openflow/switch/sub-switch

controller ipv4

```
[no] controller ipv4 <ipv4> [ port <tcpport> ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ security { none |
tls } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
controller	OpenFlow controller to use
ipv4	Controller ipv4 address (A.B.C.D)
<i>ipv4</i>	IP address (A.B.C.D)
port	(Optional) Controller TCP port (default is 6653)
<i>tcpport</i>	(Optional) TCP port number (default port is 6653)
vrf	(Optional) Controller VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
security	(Optional) Set security protocol
none	(Optional) Disable security protocol
tls	(Optional) Enable security protocol

Command Mode

- /exec/configure/openflow/switch

controller type l2 identifier

[no] controller type { l2-vxlan | vxlan } identifier <controller-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
controller	Controller command
type	Controller type
l2-vxlan	l2-vxlan
vxlan	vxlan
identifier	Controller identifier
<i>controller-id</i>	Controller id value

Command Mode

- /exec/configure

copp copy profile prefix

copp copy profile <profile_type> { prefix | suffix } <user_string>

Syntax Description

copp	Control-Plane Policing
copy	Make a copy of the CoPP Profile
profile	CoPP Profile
<i>profile_type</i>	CoPP Profile Types
prefix	prefix for the copied policy
suffix	suffix for the copied policy
<i>user_string</i>	Enter prefix/suffix for the copied policy

Command Mode

- /exec

copp distributed-policing enable

[no] copp distributed-policing enable

Syntax Description

no	(Optional) Negate a command or set its defaults
copp	Control-Plane Policing
distributed-policing	distributed policer
enable	enable distributed policing

Command Mode

- /exec/configure

copp profile

copp profile <profile_type>

Syntax Description

copp	Control-Plane Policing
profile	CoPP Profile
<i>profile_type</i>	CoPP Profile Types

Command Mode

- /exec/configure

copp profile

[no] copp profile [<profile_type>]

Syntax Description

no	Negate a command or set its defaults
copp	Control-Plane Policing
profile	CoPP Profile
<i>profile_type</i>	(Optional) CoPP Profile Types

Command Mode

- /exec/configure

copp rate-limit disable

[no] copp rate-limit disable

Syntax Description

no	(Optional) Negate a command or set its defaults
copp	copp
rate-limit	rate-limit
disable	Disable rate-limit on CoPP queues

Command Mode

- /exec/configure

copy

```
copy { { <src_local> { <dest_remote> [ source-interface <intf> | vrf <vrf-known-name> ] } } | { <src_remote>
{ <dest_local> [ compact ] | running-config [ echo-commands ] [ stop-at-first-failure ] | startup-config } } [
source-interface <intf> | vrf <vrf-known-name> ] | { <src_core> { <dest_remote> [ source-interface <intf> |
vrf <vrf-known-name> ] } } | { running-config-src { <dest_remote> [ source-interface <intf> | vrf
<vrf-known-name> ] } } | { startup-config-src { <dest_remote> [ source-interface <intf> | vrf
<vrf-known-name> ] } } }
```

Syntax Description

Syntax Description

copy	Copy from one file to another
<i>src_local</i>	Select source filesystem
<i>src_core</i>	Select source filesystem
<i>dest_local</i>	Select destination filesystem
<i>dest_remote</i>	Select destination filesystem
<i>src_remote</i>	Select source filesystem
vrf	(Optional) Display per-VRF information
source-interface	(Optional) Select source interface
<i>intf</i>	(Optional)
<i>vrf-known-name</i>	(Optional) Known VRF name
compact	(Optional) Compacting NXOS NBI image using scp
running-config	Copy from source to running configuration
running-config-src	Copy running configuration to destination
startup-config	Copy from source to startup configuration
startup-config-src	Copy startup configuration to destination
echo-commands	(Optional) Echo the commands before applying them (to correlate errors)
stop-at-first-failure	(Optional) Stop at first error

Command Mode

- /exec

Usage Guidelines



Note When a source or destination URI contains a reserved character such as '!' or '#', the reserved character must be entered as its percent-encoded ascii value, as described in RFC 3986. For example, the URI `!pa##word@example.com` must be entered as `%21pa%23%23word@example.com`. In this example, the reserved characters '!' (ascii 0x21) and '#' (ascii 0x23) are represented as '%21' and '%23'.

copy

```
copy { { <src_local> { <dest_local> | running-config [ echo-commands ] [ stop-at-first-failure ] | startup-config
| scheduled-config } } | { <src_core> <dest_local_core> } | { running-config-src { startup-config [ fabric ] |
<dest_local_config> } } | { startup-config-src { running-config [ echo-commands ] [ stop-at-first-failure ] |
<dest_local_config> } } | { switch-profile-cfg <dest_local_config> } }
```

Syntax Description

Syntax Description	copy	Copy from one file to another
<i>src_local</i>		Select source filesystem
<i>src_core</i>		Select source filesystem
<i>dest_local</i>		Select destination filesystem
<i>dest_local_core</i>		Select destination filesystem
<i>dest_local_config</i>		Select destination filesystem
running-config		Copy from source to running configuration
running-config-src		Copy running configuration to destination
startup-config		Copy from source to startup configuration
startup-config-src		Copy startup configuration to destination
scheduled-config		Schedule configuration at the specified source to be applied at next switch reload
switch-profile-cfg		Copy switch profile running configuration to destination
echo-commands	(Optional)	Echo the commands before applying them (to correlate errors)
stop-at-first-failure	(Optional)	Stop at first error
fabric	(Optional)	Copy from source to fabric startup configuration

Command Mode

- /exec

Usage Guidelines



Note When a source or destination URI contains a reserved character such as '!' or '#', the reserved character must be entered as its percent-encoded ascii value, as described in RFC 3986. For example, the URI `!pa##word@example.com` must be entered as `%21pa%23%23word@example.com`. In this example, the reserved characters '!' (ascii 0x21) and '#' (ascii 0x23) are represented as '%21' and '%23'.

copy licenses

copy licenses <uri0>

Syntax Description

copy	Copy from one file to another
licenses	Backup license files
<i>uri0</i>	Specify URL (with .tar extension) for backing up license files

Command Mode

- /exec

copy licenses

copy licenses <uri0>

Syntax Description

copy	Copy from one file to another
licenses	Backup license files
<i>uri0</i>	Specify URL (with .tar extension) for backing up license files

Command Mode

- /exec

copy recursive

```
copy <source> <destination> recursive [ vrf <vrf-known-name> ]
```

Syntax Description

Syntax Description	copy	Copy from one file to another
	recursive	Recursively copy files and folders
	<i>source</i>	Select source filesystem
	<i>destination</i>	Select destination filesystem
	vrf	(Optional) Display per-VRF information
	<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

Usage Guidelines



Note When a source or destination URI contains a reserved character such as '!' or '#', the reserved character must be entered as its percent-encoded ascii value, as described in RFC 3986. For example, the URI `!pa##word@example.com` must be entered as `%21pa%23%23word@example.com`. In this example, the reserved characters '!' (ascii 0x21) and '#' (ascii 0x23) are represented as '%21' and '%23'.

copy running vdc-all

```
copy { running-config-src { <dest_remote> [ source-interface <intf> | vrf <vrf-known-name> ] } |
startup-config-src { <dest_remote> [ source-interface <intf> | vrf <vrf-known-name> ] } } vdc-all
```

Syntax Description

Syntax Description	copy	Copy from one file to another
	<i>dest_remote</i>	Select destination filesystem
	vrf	(Optional) Display per-VRF information
	<i>vrf-known-name</i>	(Optional) Known VRF name
	source-interface	(Optional) Select source interface
	<i>intf</i>	(Optional)
	running-config-src	Copy running configuration to destination
	startup-config-src	Copy startup configuration to destination
	vdc-all	Perform copy for all vdc's

Command Mode

- /exec

Usage Guidelines



Note When a source or destination URI contains a reserved character such as '!' or '#', the reserved character must be entered as its percent-encoded ascii value, as described in RFC 3986. For example, the URI `!pa##word@example.com` must be entered as `%21pa%23%23word@example.com`. In this example, the reserved characters '!' (ascii 0x21) and '#' (ascii 0x23) are represented as '%21' and '%23'.

copy vdc-all

```
copy { running-config-src { startup-config | <dest_local_config> } | startup-config-src { running-config | <dest_local_config> } } vdc-all
```

Syntax Description

Syntax Description

copy	Copy from one file to another
<i>dest_local_config</i>	Select destination filesystem
running-config-src	Copy running configuration to destination
startup-config	Copy from source to startup configuration
running-config	Copy from source to running configuration
startup-config-src	Copy startup configuration to destination
vdc-all	Perform copy for all vdc's

Command Mode

- /exec

Usage Guidelines



Note When a source or destination URI contains a reserved character such as '!' or '#', the reserved character must be entered as its percent-encoded ascii value, as described in RFC 3986. For example, the URI `!pa##word@example.com` must be entered as `%21pa%23%23word@example.com`. In this example, the reserved characters '!' (ascii 0x21) and '#' (ascii 0x23) are represented as '%21' and '%23'.

core-on-no-memory

[no] core-on-no-memory

Syntax Description

no	(Optional) Negate a command or set its defaults
core-on-no-memory	Generate core dump on memory allocation failure

Command Mode

- /exec/configure/router-ospf

core-on-no-memory

[no] core-on-no-memory

Syntax Description

no	(Optional) Negate a command or set its defaults
core-on-no-memory	Generate core dump on memory allocation failure

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

cost

{ cost <cost> } | { no cost [<cost>] }

Syntax Description

no	Negate a command or set its defaults
cost	Cost associated with interface
<i>cost</i>	Cost value

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

count

[no] count <cap-count>

Syntax Description

no	(Optional) Negate the command
count	Configure Captured Transactions count
<i>cap-count</i>	Number of Captured Transactions

Command Mode

- /exec/configure/pkt-drop

count

| count

Syntax Description

	Pipe command output to filter
count	Count number of lines

Command Mode

- /output

counter name value op

counter name <counter-name> value <counter-value> op <op-val>

Syntax Description

counter	Specify the name of the counter
name	Specify the name of the counter
<i>counter-name</i>	Name of the counter
value	Specify the value to be applied to the counter
<i>counter-value</i>	Enter the value
op	Specify the operator to be applied
<i>op-val</i>	Enter the value of the operator

Command Mode

- /exec

crypto ca authenticate

[no] crypto ca authenticate <s0> [accept]

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
authenticate	Authenticate the certificate authority certificate
s0	trustpoint label
accept	(Optional) accept the certificate automatically

Command Mode

- /exec/configure

crypto ca crl request

[no] crypto ca crl request <s0> <uri0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
crl	import certificate revocation list
request	import certificate revocation list
s0	trustpoint label
uri0	Specify source file name

Command Mode

- /exec/configure

crypto ca enroll

[no] crypto ca enroll <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
enroll	Create certificate request
s0	trustpoint label

Command Mode

- /exec/configure

crypto ca export pkcs12

[no] crypto ca export <s0> pkcs12 <uri0> <s1>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
export	export rsa private key and certificates in pkcs#12
<i>s0</i>	trustpoint label
pkcs12	destination file url
<i>uri0</i>	Specify destination file name
<i>s1</i>	passphrase to encrypt the private key

Command Mode

- /exec/configure

crypto ca import certificate

[no] crypto ca import <s0> certificate

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
import	import the certificate or key
s0	trustpoint label
certificate	import the certificate

Command Mode

- /exec/configure

crypto ca import pkcs12

crypto ca import <s0> pkcs12 <uri0> <s1>

Syntax Description

crypto	Set crypto settings
ca	Configure certificate authority related information
import	import the certificate or key
<i>s0</i>	trustpoint label
pkcs12	source file url
<i>uri0</i>	source file url
<i>s1</i>	passphrase to decrypt the private key

Command Mode

- /exec/configure

crypto ca lookup

[no] crypto ca lookup { remote | local | both }

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
lookup	Choose the certstore for authentication
remote	Use remote certstore
local	Use local certstore
both	Use both local and remote certstore

Command Mode

- /exec/configure

crypto ca remote ldap

[no] crypto ca remote ldap { server-group <s0> | [crl-refresh-time <i0>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
remote	Use ca from remote certstore
ldap	Ldap certstore
crl-refresh-time	(Optional) Configure refresh-time to fetch crl from remote certstore
<i>i0</i>	(Optional) Refresh time value in hours. A value of 0 will now run the refresh routine once.
server-group	Ldap server group
<i>s0</i>	Ldap server group name

Command Mode

- /exec/configure

crypto ca test verify

[no] crypto ca test verify <uri0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
test	certificate tests
verify	verify the certificate
<i>uri0</i>	Specify certificate file name

Command Mode

- /exec/configure

crypto ca trustpoint

[no] crypto ca trustpoint <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
ca	Configure certificate authority related information
trustpoint	Configure trustpoint certificate authority
s0	trustpoint label

Command Mode

- /exec/configure

crypto ca trustpool import url

crypto ca trustpool import url <source_uri>

Syntax Description

crypto	Set crypto settings
ca	Configure certificate authority related information
trustpool	Configure trustpool related information
import	Configure import of trustpool
url	Configure URL from which trustpool will be imported
<i>source_uri</i>	Select source URL

Command Mode

- /exec

crypto ca trustpool import url clean

crypto ca trustpool import url clean

Syntax Description

crypto	Set crypto settings
ca	Configure certificate authority related information
trustpool	Configure trustpool related information
import	Configure import of trustpool
url	URL from which trustpool will be imported
clean	delete the contents of the trustpool

Command Mode

- /exec

crypto ca trustpool policy

crypto ca trustpool policy

Syntax Description

crypto	Set crypto settings
ca	Configure certificate authority related information
trustpool	Configure trustpool related information
policy	Configure trustpool policy

Command Mode

- /exec/configure

crypto cert ssh-authorize

[no] crypto cert ssh-authorize [<s0> map <s1> [<s2>] | default map <s3>]

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Configure crypto settings
cert	Configure certificate mapping filter settings
ssh-authorize	Configure mapping filter for ssh
s0	(Optional) Issuer name of the certificate
map	(Optional) Mapping filter to be applied
s1	(Optional) Name of the mapping filter which is already configured
s2	(Optional) Name of the mapping filter which is already configured
default	(Optional) Default map for ssh authorization
s3	(Optional) Name of the default mapping filter which is already configured

Command Mode

- /exec/configure

crypto certificatemap mapname

[no] crypto certificatemap mapname <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
certificatemap	Configure certificatemap filters
mapname	Create a new filter map
s0	Name of the filter map

Command Mode

- /exec/configure

crypto key generate rsa

```
[no] crypto key generate rsa [ { [ exportable ] [ modulus <i0> ] | [ label <s0> ] [ [ exportable ] [ modulus1 <i1> ] ] | modulus2 <i2> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
key	Configure key pair related information
generate	Configure key pair generation related information
rsa	Configure rsa key pair generation related information
exportable	(Optional) key-pair is exportable
modulus	(Optional) key-pair size
<i>i0</i>	(Optional) key-pair size
label	(Optional) key-pair label
<i>s0</i>	(Optional) key-pair label
exportable	(Optional) key-pair is exportable
modulus1	(Optional) key-pair size
<i>i1</i>	(Optional) key-pair size
modulus2	(Optional) key-pair size
<i>i2</i>	(Optional) key-pair size

Command Mode

- /exec/configure

crypto key param rsa label modulus

[no] crypto key param rsa label <s0> modulus <i0> [exportable]

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
key	Configure key pair related information
param	Configure key pair related information
rsa	Configure rsa key pair related information
label	key-pair label
<i>s0</i>	key-pair label
modulus	key-pair size
<i>i0</i>	key-pair size
exportable	(Optional) key-pair is exportable

Command Mode

- /exec/configure

crypto key zeroize rsa

[no] crypto key zeroize rsa <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
crypto	Set crypto settings
key	Configure key pair related information
zeroize	Delete key-pair
rsa	Delete rsa key-pair
s0	key-pair label

Command Mode

- /exec/configure

cryptographic-algorithm

[no] cryptographic-algorithm <algo>

Syntax Description

no	(Optional) Negate a command or set its defaults
cryptographic-algorithm	Set cryptographic-algorithm to be used
<i>algo</i>	Cryptographic-algorithm

Command Mode

- /exec/configure/keychain-key

customer-id

{ customer-id <s0> | no customer-id }

Syntax Description

no	Negate a command or set its defaults
customer-id	customer id
s0	Provide customer id (as specified in the service agreement)

Command Mode

- /exec/configure/callhome

cut

| cut { -b <bytes> | -c <chars> | -f <fields> | -d <delim> | -s | --help } +

Syntax Description

	Pipe command output to filter
cut	Print selected parts of lines.
-b	output only these bytes
-c	output only these characters
-d	specify other field delimiter (default is TAB).
-f	output only these fields also print any line that contains no delimiter character, unless the -s option is specified
-s	do not print lines not containing delimiters
<i>bytes</i>	{n n- n-m -m} N-th byte, N to end of line, N to M, start of line to N
<i>chars</i>	{n n- n-m -m} N-th char, N to end of line, N to M, start of line to N
<i>fields</i>	{n n- n-m -m} N-th field, N to end of line, N to M, start of line to N
<i>delim</i>	field separator char, TAB is default, use ' ' for space
--help	print help of underlying unix command

Command Mode

- /output



D Commands

- dampen-igp-metric, on page 851
- dampening, on page 852
- dampening, on page 853
- dampening, on page 854
- data-pattern, on page 855
- data-pattern pad, on page 856
- data-source, on page 857
- database-mapping, on page 858
- databits, on page 859
- databits, on page 860
- datapath-id, on page 861
- datapath-id, on page 862
- db-jid, on page 863
- db-security user password, on page 864
- db-table, on page 865
- dead-interval, on page 866
- dead-interval, on page 867
- dead-interval, on page 868
- deadtime, on page 869
- deadtime, on page 870
- deadtime, on page 871
- default-information originate, on page 872
- default-information originate, on page 873
- default-information originate, on page 874
- default-information originate, on page 875
- default-information originate, on page 876
- default-information originate, on page 877
- default-information originate always rd route-target, on page 878
- default-metric, on page 879
- default-metric, on page 880
- default-metric, on page 881
- default-metric, on page 882
- default-metric, on page 883

- default-miss, on page 884
- default-originate, on page 885
- default echo revision, on page 886
- default permit, on page 887
- default permit, on page 888
- default permit, on page 889
- define, on page 890
- delay-restore time, on page 891
- delay, on page 892
- delay, on page 893
- delay, on page 894
- delay peer-link, on page 895
- delay restore, on page 896
- delay restore interface-vlan, on page 897
- delay restore orphan-port, on page 898
- delay up, on page 899
- delete, on page 900
- delete ca-certificate, on page 901
- delete certificate, on page 902
- delete crl, on page 903
- demand-circuit, on page 904
- depth, on page 905
- depth, on page 906
- description, on page 907
- description, on page 908
- description, on page 909
- description, on page 910
- description, on page 911
- description, on page 912
- description, on page 913
- description, on page 914
- description, on page 915
- description, on page 916
- description, on page 917
- description, on page 918
- description, on page 919
- description, on page 920
- description, on page 921
- description, on page 922
- description, on page 923
- description, on page 924
- description, on page 925
- description, on page 926
- description, on page 927
- description, on page 928
- description, on page 929

- description, on page 930
- description, on page 931
- description, on page 932
- description, on page 933
- description, on page 934
- description, on page 935
- description, on page 936
- description, on page 937
- description, on page 938
- description, on page 939
- description, on page 940
- description, on page 941
- description, on page 942
- description, on page 943
- description, on page 944
- description, on page 945
- description, on page 946
- description, on page 947
- description, on page 948
- description, on page 949
- description, on page 950
- description, on page 951
- description, on page 952
- description description, on page 953
- dest-ipaddr, on page 954
- dest-ipaddr, on page 955
- dest-port, on page 956
- dest, on page 957
- destination-group, on page 958
- destination-profile, on page 959
- destination-profile, on page 960
- destination-profile CiscoTAC-1 alert-group, on page 961
- destination-profile CiscoTAC-1 email-addr, on page 962
- destination-profile CiscoTAC-1 http, on page 963
- destination-profile CiscoTAC-1 message-level, on page 964
- destination-profile CiscoTAC-1 message-size, on page 965
- destination-profile CiscoTAC-1 transport-method http, on page 966
- destination-profile CiscoTAC-1 transport-method email, on page 967
- destination-profile alert-group, on page 968
- destination-profile email-addr, on page 969
- destination-profile format, on page 970
- destination-profile full-txt-destination alert-group, on page 971
- destination-profile full-txt-destination email-addr, on page 972
- destination-profile full-txt-destination http, on page 973
- destination-profile full-txt-destination message-size, on page 974
- destination-profile full-txt-destination message-level, on page 975

- destination-profile full-txt-destination transport-method http, on page 976
- destination-profile full-txt-destination transport-method email, on page 977
- destination-profile http, on page 978
- destination-profile message-level, on page 979
- destination-profile message-size, on page 980
- destination-profile short-txt-destination alert-group, on page 981
- destination-profile short-txt-destination email-addr, on page 982
- destination-profile short-txt-destination http, on page 983
- destination-profile short-txt-destination message-size, on page 984
- destination-profile short-txt-destination message-level, on page 985
- destination-profile short-txt-destination transport-method http, on page 986
- destination-profile short-txt-destination transport-method email, on page 987
- destination-profile transport-method email, on page 988
- destination-profile transport-method http, on page 989
- destination-sup interface, on page 990
- destination, on page 991
- destination1 interface, on page 992
- destination, on page 993
- destination, on page 994
- destination, on page 995
- destination, on page 996
- destination, on page 997
- destination filter ip, on page 998
- destination filter ip any any, on page 999
- destination group, on page 1000
- destination interface, on page 1001
- destination ip, on page 1002
- device-group, on page 1003
- device-group, on page 1004
- device-role, on page 1005
- device-role, on page 1006
- device-role, on page 1007
- dfe-tuning-delay, on page 1008
- diagnostic bootup level, on page 1009
- diagnostic bootup level bypass, on page 1010
- diagnostic clear result module all diagnostic clear result module test, on page 1011
- diagnostic monitor interval module test all hour min second, on page 1012
- diagnostic monitor module test all, on page 1013
- diagnostic ondemand action-on-failure continue failure-count diagnostic ondemand action-on-failure stop, on page 1014
- diagnostic ondemand iteration, on page 1015
- diagnostic ondemand test-parameter module test port_lb packet-length, on page 1016
- diagnostic start module test, on page 1017
- diagnostic stop module test all, on page 1018
- diagnostic test simulation module test diagnostic test simulation module test clear, on page 1019
- diff-clean, on page 1020

- [diff-clean all-users](#), on page 1021
- [diff](#), on page 1022
- [dir](#), on page 1023
- [disable-connected-check](#), on page 1024
- [disable-fka](#), on page 1025
- [disable-peer-as-check](#), on page 1026
- [disable-policy-batching](#), on page 1027
- [disable](#), on page 1028
- [discard-route external](#), on page 1029
- [discard-route external](#), on page 1030
- [discovery](#), on page 1031
- [distance](#), on page 1032
- [distance](#), on page 1033
- [distance](#), on page 1034
- [distance](#), on page 1035
- [distance](#), on page 1036
- [distance](#), on page 1037
- [distance](#), on page 1038
- [distribute into route-map all](#), on page 1039
- [distribute link-state](#), on page 1040
- [dns](#), on page 1041
- [domain-id](#), on page 1042
- [domain-id secondary](#), on page 1043
- [domain-tag](#), on page 1044
- [dont-capability-negotiate](#), on page 1045
- [dos2nxos](#), on page 1046
- [dot1q](#), on page 1047
- [dot1q](#), on page 1048
- [dot1q](#), on page 1049
- [dot1q default dynamic](#), on page 1050
- [dot1x default](#), on page 1051
- [dot1x default](#), on page 1052
- [dot1x host-mode](#), on page 1053
- [dot1x initialize](#), on page 1054
- [dot1x mac-auth-bypass](#), on page 1055
- [dot1x mac-move](#), on page 1056
- [dot1x max-reauth-req](#), on page 1057
- [dot1x max-req](#), on page 1058
- [dot1x pae](#), on page 1059
- [dot1x port-control](#), on page 1060
- [dot1x radius-accounting](#), on page 1061
- [dot1x re-authenticate interface](#), on page 1062
- [dot1x re-authentication](#), on page 1063
- [dot1x re-authentication](#), on page 1064
- [dot1x show credential](#), on page 1065
- [dot1x start supplicant interface](#), on page 1066

- dot1x supplicant credential, on page 1067
- dot1x supplicant credential, on page 1068
- dot1x supplicant max-start, on page 1069
- dot1x supplicant max-start, on page 1070
- dot1x supplicant timeout auth-period, on page 1071
- dot1x supplicant timeout auth-period, on page 1072
- dot1x supplicant timeout held-period, on page 1073
- dot1x supplicant timeout held-period, on page 1074
- dot1x supplicant timeout start-period, on page 1075
- dot1x supplicant timeout start-period, on page 1076
- dot1x system-auth-control, on page 1077
- dot1x timeout inactivity-period, on page 1078
- dot1x timeout inactivity-period, on page 1079
- dot1x timeout quiet-period, on page 1080
- dot1x timeout quiet-period, on page 1081
- dot1x timeout ratelimit-period, on page 1082
- dot1x timeout re-authperiod, on page 1083
- dot1x timeout re-authperiod, on page 1084
- dot1x timeout server-timeout, on page 1085
- dot1x timeout supp-timeout, on page 1086
- dot1x timeout tx-period, on page 1087
- dot1x timeout tx-period, on page 1088
- down-bit-ignore, on page 1089
- downlink delay, on page 1090
- dpp set-qos-group, on page 1091
- drop-trigger, on page 1092
- droplist, on page 1093
- droplist, on page 1094
- dscp, on page 1095
- dscp, on page 1096
- dscp, on page 1097
- dscp, on page 1098
- dscp, on page 1099
- dscp, on page 1100
- dst-grp, on page 1101
- dual-active exclude interface-vlan, on page 1102
- duplex, on page 1103
- duplex, on page 1104
- duplicate-message throttle, on page 1105
- dynamic-capability, on page 1106
- dynamic-med-interval, on page 1107

dampen-igp-metric

dampen-igp-metric <sec> | no dampen-igp-metric

Syntax Description

no	Negate a command or set its defaults
dampen-igp-metric	Dampen IGP metric-related changes
<i>sec</i>	Time interval in seconds

Command Mode

- /exec/configure/router-bgp/router-bgp-af

dampening

```
[no] dampening [ { <half-life> <reuse-limit> <suppress-limit> <max-suppress-time> } | { route-map
<rmap-name> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
dampening	Configure route flap dampening
<i>half-life</i>	(Optional) Decay half life
<i>reuse-limit</i>	(Optional) Value to start reusing a route
<i>suppress-limit</i>	(Optional) Value to start suppressing a route
<i>max-suppress-time</i>	(Optional) Maximum suppress time for stable route
route-map	(Optional) Apply route-map to specify dampening criteria
<i>rmap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4-mdt /exec/configure/router-bgp/router-bgp-af-l2vpn-vpls

dampening

```
[no] dampening | dampening [ { <half-life> [ { <reuse> <suppress> <max-suppress> } ] restart [ <penalty> ] ] ] }
```

Syntax Description

<code>no</code>	Negate a command or set its defaults
<code>dampening</code>	configures dampening feature
<i>half-life</i>	(Optional) half-life time for the penalty
<i>reuse</i>	(Optional) Value to start reusing an interface
<i>suppress</i>	(Optional) Value to start suppressing an interface
<i>max-suppress</i>	(Optional) Maximum duration to suppress an interface
<code>restart</code>	(Optional) Enable restart penalty
<i>penalty</i>	(Optional) Penalty applied at restart

Command Mode

- /exec/configure/if-igp

dampening

```
[no] dampening [ { <half-life> <reuse-limit> <suppress-limit> <max-suppress-time> } | { route-map
<rmap-name> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
dampening	Configure route flap dampening
<i>half-life</i>	(Optional) Decay half life
<i>reuse-limit</i>	(Optional) Value to start reusing a route
<i>suppress-limit</i>	(Optional) Value to start suppressing a route
<i>max-suppress-time</i>	(Optional) Maximum suppress time for stable route
route-map	(Optional) Apply route-map to specify dampening criteria
<i>rmap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-vpnv4
/exec/configure/router-bgp/router-bgp-af-vpnv6 /exec/configure/router-bgp/router-bgp-af-link-state
/exec/configure/router-bgp/router-bgp-af-l2vpn-evpn /exec/configure/router-bgp/router-bgp-af-ipv4-mvpn
/exec/configure/router-bgp/router-bgp-af-ipv6-mvpn

data-pattern

```
{ { no | default } data-pattern | data-pattern <hex-pattern> }
```

Syntax Description

no	
default	Set a command to its defaults
data-pattern	Data Pattern
<i>hex-pattern</i>	Data Pattern in Hex

Command Mode

- /exec/configure/ip-sla/udp

data-pattern pad

```
{ data-pattern pad <pad-val> }
```

Syntax Description

data-pattern	Configure NGOAM ping payload
pad	Configure NGOAM payload test pattern pad
<i>pad-val</i>	Configure NGOAM payload test pad value

Command Mode

- /exec/configure/configngoamconnectcheck

data-source

{ data-source <type> } | { no data-source [<type>] }

Syntax Description

no	Negate a command or set its defaults
data-source	Specify the data source
<i>type</i>	

Command Mode

- /exec/configure/telemetry/sensor-group

database-mapping

```
{ [ no ] database-mapping { <eid-prefix> | <eid-prefix6> } { redistribute | { { <locator> | <locator6> } priority
<priority> weight <weight> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
database-mapping	Configure EID-prefix and locator-set for dynamic-EID
<i>eid-prefix</i>	IP EID-prefix for RLOC static mapping
<i>locator</i>	IP address of LISP-VM routers
priority	Configures which Locators from a set are preferred
<i>priority</i>	Lower priority Locator takes preference
weight	Traffic load-spreading among Locators
<i>weight</i>	Specified in a percentage from 0 to 100
redistribute	Used for redistributing into routing protocols

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

databits

[no] databits <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
databits	Set number of databits per character
<i>i0</i>	Number of data bits

Command Mode

- /exec/configure/com1

databits

[no] databits <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
databits	Set number of databits per character
<i>i0</i>	Number of data bits

Command Mode

- /exec/configure/console

datapath-id

datapath-id <datapathid-val> | no datapath-id

Syntax Description

no	Negate a command or set its defaults
datapath-id	Datapath ID
<i>datapathid-val</i>	64-bit hex value [0x1-0xffffffffffff]

Command Mode

- /exec/configure/openflow/switch/sub-switch

datapath-id

datapath-id <datapathid-val> | no datapath-id

Syntax Description

no	Negate a command or set its defaults
datapath-id	Datapath ID
<i>datapathid-val</i>	64-bit hex value [0x1-0xffffffffffffff]

Command Mode

- /exec/configure/openflow/switch

db-jid

[no] db-jid <jid> [key-type <key-type>]

Syntax Description

no	(Optional) Negate a command or set its defaults
db-jid	Jabber ID of database
<i>jid</i>	Enter Jabber ID of database
key-type	(Optional) Query key type for this database
<i>key-type</i>	(Optional)

Command Mode

- /exec/configure/fabric-db/server-xmpp

db-security user password

```
[no] db-security user <user> password { 0 <clear> | 7 <encrypted> | <password> } [ shared-secret { 10 <clear> | 7 <encrypted> | <secret> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
db-security	Database Security
user	User ID
<i>user</i>	Enter user ID
password	Password
0	Password that follows should be in clear text
<i>clear</i>	Password in clear text
7	Password that follows should be in encrypted text
<i>encrypted</i>	Encrypted password
<i>password</i>	Enter password in clear text
shared-secret	(Optional) Shared-secret
10	(Optional) Indicates that password that follows should be in clear text
<i>clear</i>	(Optional) Password in clear text
7	(Optional) Password that follows should be in encrypted text
<i>encrypted</i>	(Optional) Encrypted password
<i>secret</i>	(Optional) Enter shared-secret in clear text

Command Mode

- /exec/configure/fabric-db/server-ldap

db-table

[no] db-table <tablename> [key-type <key-type>]

Syntax Description

no	(Optional) Negate a command or set its defaults
db-table	Table name to search
<i>tablename</i>	Enter table name to search
key-type	(Optional) Query key type for this table
<i>key-type</i>	(Optional)

Command Mode

- /exec/configure/fabric-db/server-ldap

dead-interval

```
{ { dead-interval <interval> } | { no dead-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
dead-interval	Dead interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

dead-interval

```
{ { dead-interval <interval> } | { no dead-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
dead-interval	Dead interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf3/router-ospf3-vlink /exec/configure/router-ospf3/vrf/router-ospf3-vlink

dead-interval

```
{ { dead-interval <interval> } | { no dead-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
dead-interval	Dead interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

deadtime

[no] deadtime <*i0*>

Syntax Description

no	(Optional) Negate a command or set its defaults
deadtime	duration for which non-reachable server is skipped
<i>i0</i>	Length of time, in minutes

Command Mode

- /exec/configure/ldap

deadtime

[no] deadtime <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
deadtime	duration for which non-reachable server is skipped
<i>i0</i>	Length of time, in minutes

Command Mode

- /exec/configure/radius

deadtime

[no] deadtime <*i0*>

Syntax Description

no	(Optional) Negate a command or set its defaults
deadtime	duration for which non-reachable server is skipped
<i>i0</i>	Length of time, in minutes

Command Mode

- /exec/configure/tacacs+

default-information originate

[no] default-information originate [always] [route-map <map-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	RIP control distribution of default route
originate	RIP distribute a default route
always	(Optional) RIP always advertise default route
route-map	(Optional) Policy to constrain redistribution
<i>map-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-rip/router-rip-af-common /exec/configure/router-rip/router-rip-vrf-af-common

default-information originate

[no] default-information originate [always] [route-map <map-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control origination of a default route
originate	Originate a default route
always	(Optional) Always advertise default route
route-map	(Optional) Route-map to announce default routes
<i>map-name</i>	(Optional) A 'routing-rules' route-map name

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-common

default-information originate

[no] default-information originate [always] [route-map <policy-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control distribution of default route
originate	Distribute a default route
always	(Optional) Always advertise default route
route-map	(Optional) Policy to control distribution of default route
<i>policy-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

default-information originate

[no] default-information originate [always] [route-map <map>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control origination of a default route
originate	Originate a default route
always	(Optional) Always advertise default route
route-map	(Optional) Use a route-map for default route metrics
<i>map</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

default-information originate

[no] default-information originate [always] [route-map <policy-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control distribution of default route
originate	Distribute a default route
always	(Optional) Always advertise default route
route-map	(Optional) Policy to control distribution of default route
<i>policy-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

default-information originate

[no] default-information originate

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control distribution of default information
originate	Distribute a default route

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-ipv6-label
/exec/configure/router-bgp/router-bgp-af-ipv4-label

default-information originate always rd route-target

```
[no] default-information originate always rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } route-target
{ <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
default-information	Control distribution of default information
originate	Distribute a default route
always	Always advertise default route
rd	VPN Route Distinguisher
<i>ext-comm-rd-aa4nn2</i>	VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	VPN route distinguisher in aa:nn format
route-target	Specify Target VPN Extended Communities
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/router-bgp/router-bgp-af-vpnv4 /exec/configure/router-bgp/router-bgp-af-vpnv6

default-metric

[no] default-metric <metric>

Syntax Description

no	(Optional) Negate a command or set its defaults
default-metric	Set metric of redistributed routes
<i>metric</i>	Default Metric

Command Mode

- /exec/configure/router-bgp/router-bgp-af

default-metric

default-metric <metric> | no default-metric [<metric>]

Syntax Description

no	Negate a command or set its defaults
default-metric	RIP default metric
<i>metric</i>	RIP metric value

Command Mode

- /exec/configure/router-rip/router-rip-af-common /exec/configure/router-rip/router-rip-vrf-af-common

default-metric

{ default-metric <cost> } | { no default-metric [<cost>] }

Syntax Description

no	Negate a command or set its defaults
default-metric	Specify default metric for redistributed routes
<i>cost</i>	Metric value

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

default-metric

```
{ { default-metric <bw> <delay> <rel> <load> <mtu> } | { no default-metric [ <bw> <delay> <rel> <load> <mtu> ] } }
```

Syntax Description

<code>no</code>	Negate a command or set its defaults
<code>default-metric</code>	Set metric of redistributed routes
<code>bw</code>	Bandwidth in Kbits per second
<code>delay</code>	Delay metric
<code>rel</code>	Reliability metric where 255 is 100% reliable
<code>load</code>	Effective bandwidth metric (Loading) where 255 is 100% loaded
<code>mtu</code>	Maximum Transmission Unit metric of the path

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

default-metric

{ default-metric <cost> } | { no default-metric [<cost>] }

Syntax Description

no	Negate a command or set its defaults
default-metric	Specify default metric for redistributed routes
<i>cost</i>	Metric value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

default-miss

default-miss { continue-drop | continue-normal | continue-controller | drop | normal | controller } | no default-miss

Syntax Description

no	Negate a command or set its defaults
default-miss	Set continue-drop/continue-normal/continue-controller/drop/normal/controller flow action
continue-drop	cascade drop to next table
continue-normal	cascade normal to next table
continue-controller	cascade punt to next table
drop	drop packet
normal	forward to normal dataplane
controller	punt to controller

Command Mode

- /exec/configure/openflow/switch

default-originate

[no | default] default-originate [route-map <rmap-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
default-originate	Originate a default toward this peer
route-map	(Optional) Route-map to specify criteria for originating default
<i>rmap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

default echo revision

```
default echo { revision | vendor-extension }
```

Syntax Description

default	Set a command to its defaults
echo	Echo Request attributes
revision	Echo packet default revision
vendor-extension	Send Vendor Extension TLV with echo Req

Command Mode

- /exec/configure/mpls-oam

default permit

[no] default { permit | deny }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	Default Host Admission Policy
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/sender

default permit

[no] default { permit | deny }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	Default Host Admission Policy
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/receiver

default permit

[no] default { permit | deny }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	Default Host Admission Policy
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/pim

define

[no] define <paramname> [<paramtype>] [<paramdesc>]

Syntax Description

no	(Optional) Negate a command or set its defaults
define	Define a parameter
<i>paramname</i>	Enter the name of the parameter
<i>paramtype</i>	(Optional) param type
<i>paramdesc</i>	(Optional) Enter the parameter description

Command Mode

- /exec/configure/param-list

delay-restore time

[no] delay-restore time <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
delay-restore	delay-restore
time	time
<i>sec</i>	time in seconds

Command Mode

- /exec/configure/config-evpn-msite-bgw

delay

delay <microseconds> | no delay

Syntax Description

no	Negate a command or set its defaults
delay	Specify interface throughput delay
<i>microseconds</i>	Throughput delay (tens of microseconds)

Command Mode

- /exec/configure/if-vlan-common

delay

delay <delay_val> | no delay [<delay_val>]

Syntax Description

no	Negate a command or set its defaults
delay	Specify interface throughput delay
<i>delay_val</i>	Throughput delay (tens of microseconds)

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub

delay

delay <delay_val> | no delay [<delay_val>]

Syntax Description

no	Negate a command or set its defaults
delay	Specify interface throughput delay
<i>delay_val</i>	Throughput delay (tens of microseconds)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-all /exec/configure/if-ethernet-p2p /exec/configure/if-remote-ethernet-sub /exec/configure/if-port-channel-range

delay peer-link

delay peer-link <time> | no delay peer-link

Syntax Description

no	Negate a command or set its defaults
delay	Peer-link bringup delay
peer-link	Delay peer-link bringup
<i>time</i>	Delay in bringing up the peer-link (in seconds)

Command Mode

- /exec/configure/vpc-domain

delay restore

delay restore <time-out> | no delay restore

Syntax Description

no	Negate a command or set its defaults
delay	Initialization delay
restore	Delay after restoring peer-link
<i>time-out</i>	Delay in bringing up the vPC links (in seconds)

Command Mode

- /exec/configure/vpc-domain

delay restore interface-vlan

delay restore interface-vlan <time-out> | no delay restore interface-vlan

Syntax Description

no	Negate a command or set its defaults
delay	Initialization delay
restore	Delay after restoring peer-link
interface-vlan	Delay in bringing-up interface-vlan
<i>time-out</i>	Delay in bringing up the interface-vlan (in seconds)

Command Mode

- /exec/configure/vpc-domain

delay restore orphan-port

delay restore orphan-port <delay_time> | no delay restore orphan-port

Syntax Description

no	Negate a command or set its defaults
delay	Initialization delay
restore	Delay after restoring peer-link
orphan-port	Configure vPC orphan-port delay bring-up timer
<i>delay_time</i>	Specify delay time in seconds

Command Mode

- /exec/configure/vpc-domain

delay up

delay { { up <up_delay> [down <down_delay>] } | { down <down_delay> [up <up_delay>] } } | no delay

Syntax Description

no	Negate a command or set its defaults
delay	Tracking delay
up	Delay up change notification
<i>up_delay</i>	Seconds to delay
down	(Optional) Delay down change notification
<i>down_delay</i>	(Optional) Seconds to delay

Command Mode

- /exec/configure/track /exec/configure/tr-list-bool /exec/configure/tr-list-thrp /exec/configure/tr-list-thrw

delete

delete { <uri0> | <uri1> | <uri2> } [no-prompt]

Syntax Description

delete	delete a file or directory
<i>uri0</i>	Delete a file or directory
<i>uri1</i>	Delete a file or directory on expansion flash
<i>uri2</i>	Directory or filename on logflash
no-prompt	(Optional) Do not prompt for multiple deletion of files

Command Mode

- /exec

delete ca-certificate

delete ca-certificate

Syntax Description

delete	Delete the certificates
ca-certificate	Delete the ca certificates

Command Mode

- /exec/configure/trustpoint

delete certificate

delete certificate [force]

Syntax Description

delete	Delete the certificates
certificate	Delete the identity certificate
force	(Optional) Force delete the identity certificate

Command Mode

- /exec/configure/trustpoint

delete crl

delete crl

Syntax Description

delete	Delete the certificates
crl	Delete the CRL

Command Mode

- /exec/configure/trustpoint

demand-circuit

[no] demand-circuit

Syntax Description

no	(Optional) Negate a command or set its defaults
demand-circuit	OSPF Demand circuit

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

depth

{ [no] depth <cells> | no depth }

Syntax Description

depth	Provide the number of cells for this INT queue_profile
<i>cells</i>	queue_profile depth (number of cells). Default is 300

Command Mode

- /exec/configure/config-int-q-prof

depth

{ [no] depth <cells> | no depth }

Syntax Description

depth	Provide the number of cells for this POSTCARD queue_profile
cells	queue_profile depth (number of cells/packets). Default is 300

Command Mode

- /exec/configure/config-postcard-q-prof

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Exporter
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-exporter

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this INT Record
<i>line</i>	Record description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-record

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this INT Watchlist
<i>line</i>	Watchlist description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-watchlist

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this INT Monitor
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-monitor

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this INT queue_profile
<i>line</i>	queue_profile description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-q-prof

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this INT flow-profile
<i>line</i>	flow-profile description string (63 characters maximum)

Command Mode

- /exec/configure/config-int-flow-prof

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Record
<i>line</i>	Record description string (63 characters maximum)

Command Mode

- /exec/configure/config-fte-record

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this FTE Monitor
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/config-fte-monitor

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this FTE Eveny
<i>line</i>	Event description string (63 characters maximum)

Command Mode

- /exec/configure/config-fte-event

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 80 characters
<i>desc_line</i>	Description of maximum 80 characters

Command Mode

- /exec/configure/if-vfc

description

description <descr> | no description

Syntax Description

no	Negate a command or set its defaults
description	Session description (max 32 characters)
<i>descr</i>	Enter the description string(can include spaces)

Command Mode

- /exec/configure/monitor-common

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 254 characters
<i>desc_line</i>	Description of maximum 254 characters

Command Mode

- /exec/configure/if-any-tunnel

description

{ description <desc-str> | no description [<desc-str>] }

Syntax Description

no	Negate a command or set its defaults
description	Class-Map description
<i>desc-str</i>	Description of this class-map (up to 200 characters)

Command Mode

- /exec/configure/class-map

description

[no] description <desc-str>

Syntax Description

no	(Optional) Negate a command or set its defaults
description	Class-Map description
<i>desc-str</i>	Description of this class-map (up to 200 characters)

Command Mode

- /exec/configure/class-map/type/queuing

description

{ description <desc-str> | no description [<desc-str>] }

Syntax Description

no	Negate a command or set its defaults
description	Table-Map description
<i>desc-str</i>	Description of this table-map (up to 200 characters)

Command Mode

- /exec/configure/table-map

description

{ description <desc-str> | no description [<desc-str>] }

Syntax Description

no	Negate a command or set its defaults
description	Policy-Map description
<i>desc-str</i>	Description of this policy-map (up to 200 characters)

Command Mode

- /exec/configure/policy-map

description

```
{ description <desc-str> | no description [ <desc-str> ] }
```

Syntax Description

no	Negate a command or set its defaults
description	Policy-Map description
<i>desc-str</i>	Description of this policy-map (up to 200 characters)

Command Mode

- /exec/configure/policy-map/type/queuing

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Record
<i>line</i>	Record description string (63 characters maximum)

Command Mode

- /exec/configure/nfm-record

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Monitor
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/nfm-monitor

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Exporter
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/nfm-exporter

description

description [port-profile] <desc_line> | no description [port-profile] [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter port-profile description of maximum 80 characters
port-profile	(Optional) Hack for conf-sync
<i>desc_line</i>	Enter port-profile description of maximum 80 characters

Command Mode

- /exec/configure/port-profile

description

{ description <desc-str> | no description [<desc-str>] }

Syntax Description

no	Negate a command or set its defaults
description	Class-Map description
<i>desc-str</i>	Description of this class-map (up to 200 characters)

Command Mode

- /exec/configure/class-map/type/uf

description

```
{ description <desc-str> | no description [ <desc-str> ] }
```

Syntax Description

no	Negate a command or set its defaults
description	Policy-Map description
<i>desc-str</i>	Description of this policy-map (up to 200 characters)

Command Mode

- /exec/configure/policy-map/type/uf

description

description <desc> | no description

Syntax Description

no	Negate a command or set its defaults
description	Fabric Path topology description
<i>desc</i>	Description of maximum 80 characters

Command Mode

- /exec/configure/fp-topology

description

{ description <description_text> | no description [<description_text>] }

Syntax Description

no	Negate a command or set its defaults
description	Virtual service description
<i>description_text</i>	Description of this virtual service

Command Mode

- /exec/configure/virt-serv

description

[no] description <description>

Syntax Description

no	(Optional) Negate a command or set its defaults
description	Configure description for the policy
<i>description</i>	Description for the policy

Command Mode

- /exec/configure/event-manager-applet

description

[no] description

Syntax Description

no	Negate a command or set its defaults
description	Configure description for the policy

Command Mode

- /exec/configure/event-manager-applet

description

description <desc_line> | no description

Syntax Description

no	Negate a command or set its defaults
description	Interface specific description
<i>desc_line</i>	Up to 255 characters describing this interface

Command Mode

- /exec/configure/if-vlan-common

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this Flow Exporter
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/config-postcard-exporter

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this POSTCARD Watchlist
<i>line</i>	Watchlist description string (63 characters maximum)

Command Mode

- /exec/configure/config-postcard-watchlist

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this POSTCARD Monitor
<i>line</i>	Monitor description string (63 characters maximum)

Command Mode

- /exec/configure/config-postcard-monitor

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this POSTCARD queue_profile
<i>line</i>	queue_profile description string (63 characters maximum)

Command Mode

- /exec/configure/config-postcard-q-prof

description

{ [no] description <line> | no description }

Syntax Description

description	Provide a description for this POSTCARD flow-profile
<i>line</i>	flow-profile description string (63 characters maximum)

Command Mode

- /exec/configure/config-postcard-flow-prof

description

description <line> | no description

Syntax Description

no	Negate a command or set its defaults
description	Add a description for the role
<i>line</i>	Enter the description string(can include spaces)

Command Mode

- /exec/configure/role

description

{ description <line> | no description }

Syntax Description

no	Negate a command or set its defaults
description	Description of the route-map
<i>line</i>	Route-map description string

Command Mode

- /exec/configure/route-map

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 254 characters
<i>desc_line</i>	Description of maximum 254 characters

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-eth-port-channel /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub /exec/configure/if-loopback /exec/configure/if-ethernet-all /exec/configure/if-ethernet-p2p /exec/configure/if-remote-ethernet-sub /exec/configure/if-port-channel-range

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 254 characters
<i>desc_line</i>	Description of maximum 254 characters

Command Mode

- /exec/configure/if-mgmt-ether

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 254 characters
<i>desc_line</i>	Description of maximum 254 characters

Command Mode

- /exec/configure/if-nve

description

description <desc_line> | no description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
description	Enter description of maximum 80 characters
<i>desc_line</i>	Description of maximum 80 characters

Command Mode

- /exec/configure/if-overlay /exec/configure/if-te /exec/configure/if-nve

description

[no] description [<desc>] | description <desc>

Syntax Description

no	Negate a command or set its defaults
description	Group description
<i>desc</i>	(Optional) Up to 80 characters describing this group

Command Mode

- /exec/configure/if-eth-any/vrrpv3

description

{ description <line> } | { no description }

Syntax Description

no	Negate a command or set its defaults
description	Description of the VRF
<i>line</i>	VRF description string

Command Mode

- /exec/configure/vrf

description

```
{ [ no ] description <descrip-string> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
description	Provide a description string for the LISP site
<i>descrip-string</i>	Description string

Command Mode

- /exec/configure/lisp-site /exec/configure/vrf/lisp-site

description

description <describe> | no description

Syntax Description

no	Negate a command or set its defaults
description	Description for the BMP server
<i>describe</i>	Upto 80 characters describing this server

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

description

description <describe> | { no | default } description [<describe>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
description	Neighbor specific description
<i>describe</i>	Upto 80 characters describing this neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

description

```
{ [ no ] description <text> }
```

Syntax Description

description	description for this profile
<i>text</i>	description

Command Mode

- /exec/configure/dot1x-cred

description

{ description <descr> } | { no description }

Syntax Description

description	Configure description of the profile
<i>descr</i>	Description of maximum 64 characters

Command Mode

- /exec/configure/configngoamprofile

description description

[no] description | description <desc>

Syntax Description

no	(Optional) Negate a command or set its defaults
description	Pathway description
<i>desc</i>	Up to 80 characters describing this pathway

Command Mode

- /exec/configure/if-eth-any/vrrs

dest-ipaddr

```
{ dest-ipaddr { <ip-address> | <hostname> | <ipv6-address> } }
```

Syntax Description

dest-ipaddr	Destination ip address
<i>ip-address</i>	IP address, broadcast disallowed
<i>hostname</i>	IP Hostname, broadcast disallowed

Command Mode

- /exec/configure/ip-sla/tcp

dest-ipaddr

```
{ dest-ipaddr { <ip-address> | <hostname> } }
```

Syntax Description

dest-ipaddr	Destination ip address
<i>ip-address</i>	IP address, broadcast disallowed
<i>hostname</i>	IP Hostname, broadcast disallowed

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter

dest-port

{ dest-port <port> }

Syntax Description

dest-port	Destination port
<i>port</i>	udp port number

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp

dest

```
{ dest { { ip { <numeric10> | <numeric11> | unknown } } | { mac <dmac> <dot1qid> [ <intfid> ] } } }
```

Syntax Description

dest	destination node
ip	ip address
<i>numeric10</i>	Ipv4 address of remote host / VTEP
unknown	Peer vtep ip is unknown, Applicable only for channel Nv03
mac	Mac
<i>dmac</i>	Destination mac address
<i>dot1qid</i>	Encapsulation dot1q/bd on which the mac is learnt
<i>intfid</i>	(Optional) Name of the interface for ngoam ping on which dot1q is configured

Command Mode

- /exec/configure/configngoamconnectcheck

destination-group

[no] destination-group <dgrp-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-group	Create destination group
<i>dgrp-id</i>	Identifier

Command Mode

- /exec/configure/telemetry

destination-profile

[no] destination-profile <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s0	User defined destination profile name

Command Mode

- /exec/configure/callhome

destination-profile

[no] destination-profile

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Specify the default destination profile

Command Mode

- /exec/configure/telemetry

destination-profile CiscoTAC-1 alert-group

[no] destination-profile CiscoTAC-1 alert-group { All | Configuration | Diagnostic | EEM | Cisco-TAC | Environmental | Inventory | License | Linecard-Hardware | Supervisor-Hardware | Syslog-group-port | System | Test }

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
alert-group	Add alert group
All	This alert group consists of all of the callhome messages
Cisco-TAC	Events which are meant for Cisco TAC only
Environmental	Power,fan,temperature related events
Inventory	Inventory status events
License	Events related to licensing
Linecard-Hardware	Linecard related events
Supervisor-Hardware	Supervisor related events
Syslog-group-port	Events related to syslog messages filed by port manager
System	Software related events
Test	User generated test events
Configuration	Events related to Configuration
Diagnostic	Events related to Diagnostic
EEM	EEM events

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 email-addr

[no] destination-profile CiscoTAC-1 email-addr <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
email-addr	Add email addr
s0	Provide email address, example: jdow@xyz.com

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 http

[no] destination-profile CiscoTAC-1 http <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
http	Add http or https url
s0	Provide http or https url, example1: http://site.com/services/callserv example2: https://site2.com/serv/CALL

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 message-level

[no] destination-profile CiscoTAC-1 message-level <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
message-level	Callhome message level(0-lowest urgency, 9-highest urgency)
<i>i0</i>	

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 message-size

[no] destination-profile CiscoTAC-1 message-size <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
message-size	Configure maximum message size (default 5000000)
<i>i0</i>	Provide maximum possible message size

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 transport-method http

[no] destination-profile CiscoTAC-1 transport-method http

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
transport-method	Callhome message sending transport-method
http	http transport-method

Command Mode

- /exec/configure/callhome

destination-profile CiscoTAC-1 transport-method email

[no] destination-profile CiscoTAC-1 transport-method email

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
CiscoTAC-1	Configure destination profile for XML message
transport-method	Callhome message sending transport-method
email	email transport-method

Command Mode

- /exec/configure/callhome

destination-profile alert-group

[no] destination-profile <s0> alert-group { All | Configuration | Diagnostic | EEM | Cisco-TAC | Environmental | Inventory | License | Linecard-Hardware | Supervisor-Hardware | Syslog-group-port | System | Test }

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s0	User defined destination profile name
alert-group	Add alert group
All	This alert group consists of all of the callhome messages
Cisco-TAC	Events which are meant for Cisco TAC only
Environmental	Power,fan,temperature related events
Inventory	Inventory status events
License	Events related to licensing
Linecard-Hardware	Linecard related events
Supervisor-Hardware	Supervisor related events
Syslog-group-port	Events related to syslog messages filed by port manager
System	Software related events
Test	User generated test events
Configuration	Events related to Configuration
Diagnostic	Events related to Diagnostic
EEM	EEM events

Command Mode

- /exec/configure/callhome

destination-profile email-addr

[no] destination-profile <s0> email-addr <s1>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s0	User defined destination profile name
email-addr	Add email addr
s1	Provide email address, example: jdow@xyz.com

Command Mode

- /exec/configure/callhome

destination-profile format

```
destination-profile <s0> format { full-txt | short-txt | XML }
```

Syntax Description

destination-profile	Configure destination profiles
<i>s0</i>	User defined destination profile name
format	Callhome message format (default XML)
full-txt	Plain text message format
short-txt	Short text message format
XML	XML message format

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination alert-group

[no] destination-profile full-txt-destination alert-group { All | Configuration | Diagnostic | EEM | Cisco-TAC | Environmental | Inventory | License | Linecard-Hardware | Supervisor-Hardware | Syslog-group-port | System | Test }

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
alert-group	Add alert group
All	This alert group consists of all of the callhome messages
Cisco-TAC	Events which are meant for Cisco TAC only
Environmental	Power,fan,temperature related events
Inventory	Inventory status events
License	Events related to licensing
Linecard-Hardware	Linecard related events
Supervisor-Hardware	Supervisor related events
Syslog-group-port	Events related to syslog messages filed by port manager
System	Software related events
Test	User generated test events
Configuration	Events related to Configuration
Diagnostic	Events related to Diagnostic
EEM	EEM events

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination email-addr

[no] destination-profile full-txt-destination email-addr <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
email-addr	Add email addr
s0	Provide email address, example: jdow@xyz.com

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination http

[no] destination-profile full-txt-destination http <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
http	Add http or https url
s0	Provide http or https url, example1: http://site.com/services/callserv example2: https://site2.com/serv/CALL

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination message-size

[no] destination-profile full-txt-destination message-size <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
message-size	Configure maximum message size (default 2500000)
<i>i0</i>	Provide maximum possible message size

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination message-level

[no] destination-profile full-txt-destination message-level <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
message-level	Callhome message level(0-lowest urgency, 9-highest urgency)
<i>i0</i>	

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination transport-method http

[no] destination-profile full-txt-destination transport-method http

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
transport-method	Callhome message sending transport-method
http	http transport-method

Command Mode

- /exec/configure/callhome

destination-profile full-txt-destination transport-method email

[no] destination-profile full-txt-destination transport-method email

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
full-txt-destination	Configure destination profile for plain txt message
transport-method	Callhome message sending transport-method
email	email transport-method

Command Mode

- /exec/configure/callhome

destination-profile http

[no] destination-profile <s4> { http <s2> }

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s4	User defined destination profile name
http	Add http or https url
s2	Provide http or https url, example1: http://site.com/services/callserv example2: https://site2.com/serv/CALL

Command Mode

- /exec/configure/callhome

destination-profile message-level

[no] destination-profile <s0> message-level <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s0	User defined destination profile name
message-level	Callhome message level(0-lowest urgency, 9-highest urgency)
i0	

Command Mode

- /exec/configure/callhome

destination-profile message-size

[no] destination-profile <s0> message-size <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s0	User defined destination profile name
message-size	Configure maximum message size (default 2500000)
i0	Provide maximum possible message size

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination alert-group

[no] destination-profile short-txt-destination alert-group { All | Configuration | Diagnostic | EEM | Cisco-TAC | Environmental | Inventory | License | Linecard-Hardware | Supervisor-Hardware | Syslog-group-port | System | Test }

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
alert-group	Add alert group
All	This alert group consists of all of the callhome messages
Cisco-TAC	Events which are meant for Cisco TAC only
Environmental	Power,fan,temperature related events
Inventory	Inventory status events
License	Events related to licensing
Linecard-Hardware	Linecard related events
Supervisor-Hardware	Supervisor related events
Syslog-group-port	Events related to syslog messages filed by port manager
System	Software related events
Test	User generated test events
Configuration	Events related to Configuration
Diagnostic	Events related to Diagnostic
EEM	EEM events

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination email-addr

[no] destination-profile short-txt-destination email-addr <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
email-addr	Add email addr
s0	Provide email address, example: jdow@xyz.com

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination http

[no] destination-profile short-txt-destination http <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
http	Add http or https url
s0	Provide http or https url, example1: http://site.com/services/callserv example2: https://site2.com/serv/CALL

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination message-size

[no] destination-profile short-txt-destination message-size <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
message-size	Configure maximum message size (default 4000)
<i>i0</i>	

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination message-level

[no] destination-profile short-txt-destination message-level <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
message-level	Callhome message level(0-lowest urgency, 9-highest urgency)
<i>i0</i>	

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination transport-method http

[no] destination-profile short-txt-destination transport-method http

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
transport-method	Callhome message sending transport-method
http	http transport-method

Command Mode

- /exec/configure/callhome

destination-profile short-txt-destination transport-method email

[no] destination-profile short-txt-destination transport-method email

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
short-txt-destination	Configure destination profile for short txt message
transport-method	Callhome message sending transport-method
email	email transport-method

Command Mode

- /exec/configure/callhome

destination-profile transport-method email

[no] destination-profile <s5> transport-method email

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s5	User defined destination profile name
transport-method	Callhome message sending transport-method
email	email transport-method

Command Mode

- /exec/configure/callhome

destination-profile transport-method http

[no] destination-profile <s6> transport-method http

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-profile	Configure destination profiles
s6	User defined destination profile name
transport-method	Callhome message sending transport-method
http	http transport-method

Command Mode

- /exec/configure/callhome

destination-sup interface

[no] destination-sup interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination-sup	Destination configuration
interface	Configure interfaces
<i>interface</i>	

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

destination

```
{ [ no ] destination <ipaddr> } [ use-vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

destination	Destination configuration
<i>ipaddr</i>	IP Address to be configured
use-vrf	(Optional) VRF label
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure/config-ssx-exporter

destination1 interface

[no] destination1 interface <interface_range>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination1	Destination configuration
interface	Configure interfaces
<i>interface_range</i>	

Command Mode

- /exec/configure/monitor-local-dst

destination

```
{ [ no ] destination { <ipaddr> | <ipv6addr> } [ use-vrf { <vrf_name> | <vrf-known-name> } ] | no destination }
```

Syntax Description

<code>destination</code>	Specify the destination address
<code>ipaddr</code>	Destination IP address for collector
<code>use-vrf</code>	(Optional) Optional VRF label
<code>vrf_name</code>	(Optional) VRF name
<code>vrf-known-name</code>	(Optional) Known VRF name

Command Mode

- /exec/configure/config-int-exporter

destination

```
{ [ no ] destination { <ipaddr> | <ipv6addr> } [ use-vrf { <vrf_name> | <vrf-known-name> } ] | no destination }
```

Syntax Description

<code>destination</code>	Specify the destination address
<code>ipaddr</code>	Destination IP address for collector
<code>use-vrf</code>	(Optional) Optional VRF label
<code>vrf_name</code>	(Optional) VRF name
<code>vrf-known-name</code>	(Optional) Known VRF name

Command Mode

- /exec/configure/config-fte-exporter

destination

```
{ [ no ] destination { <ipaddr> | <ipv6addr> } [ use-vrf { <vrf_name> | <vrf-known-name> } ] | no destination }
```

Syntax Description

<code>destination</code>	Specify the destination address
<code>ipaddr</code>	Destination IP address for collector
<code>use-vrf</code>	(Optional) Optional VRF label
<code>vrf_name</code>	(Optional) VRF name
<code>vrf-known-name</code>	(Optional) Known VRF name

Command Mode

- /exec/configure/nfm-exporter

destination

```
{ [ no ] destination { <ipaddr> | <ipv6addr> } [ use-vrf { <vrf_name> | <vrf-known-name> } ] | no destination }
```

Syntax Description

<code>destination</code>	Specify the destination address
<code>ipaddr</code>	Destination IP address for collector
<code>use-vrf</code>	(Optional) Optional VRF label
<code>vrf_name</code>	(Optional) VRF name
<code>vrf-known-name</code>	(Optional) Known VRF name

Command Mode

- /exec/configure/config-postcard-exporter

destination

[no] destination | destination <ipaddr>

Syntax Description

no	Negate a command or set its defaults
destination	destination of tunnel
<i>ipaddr</i>	ip address (A.B.C.D)

Command Mode

- /exec/configure/if-te

destination filter ip

```
[no] destination filter ip { <ip-addr> <ip-mask> } [ ip | { { udp | tcp } { <port_num> | any } } ] [ { arp | advertise } { enable | disable } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
destination	destination ip configuration
filter	list of ips to filter
ip	destination ip
<i>ip-addr</i>	IP address in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
ip	(Optional) IP Protocol
udp	(Optional) UDP Protocol
tcp	(Optional) TCP Protocol
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
arp	(Optional) ARP
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable

Command Mode

- /exec/configure/smartc

destination filter ip any any

[no] destination filter ip any any

Syntax Description

no	(Optional) Negate a command or set its defaults
destination	destination ip configuration
filter	list of ips to filter
ip	destination ip
any	Any IP

Command Mode

- /exec/configure/smartc

destination group

[no] destination group <group_number>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination	Destination configuration
group	Configure destination group
<i>group_number</i>	

Command Mode

- /exec/configure/monitor-local-dst

destination interface

[no] destination interface <interface_range>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination	Destination configuration
interface	Configure interfaces
<i>interface_range</i>	

Command Mode

- /exec/configure/monitor-local-dst

destination ip

[no] destination ip <ipaddress>

Syntax Description

no	(Optional) Negate a command or set its defaults
destination	Destination configuration
ip	Configure remote IP address
<i>ipaddress</i>	

Command Mode

- /exec/configure/config-monitor-erspan-src

device-group

[no] device-group <group-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
device-group	PLB device group
<i>group-name</i>	Specify device-group name

Command Mode

- /exec/configure/plb

device-group

{ device-group <name> } | { no device-group <name> }

Syntax Description

no	Negate a command or set its defaults
device-group	ITD device group
<i>name</i>	ITD device group name

Command Mode

- /exec/configure/itd

device-role

[no] device-role <dev_role>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>dev_role</i>	

Command Mode

- /exec/configure/config-snoop-policy

device-role

[no] device-role <devrole>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>devrole</i>	

Command Mode

- /exec/configure/config-dhcp-guard

device-role

[no] device-role <dev_role>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>dev_role</i>	

Command Mode

- /exec/configure/config-ra-guard

dfe-tuning-delay

```
{ dfe-tuning-delay <delay-val> | no dfe-tuning-delay [ <delay-val> ] }
```

Syntax Description

no	Negate a command or set its defaults
dfe-tuning-delay	Configure DFE Tuning delay for interface
<i>delay-val</i>	DFE tuning delay value (ms)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

diagnostic bootup level

[no] diagnostic bootup level

Syntax Description

no	Negate a command or set its defaults
diagnostic	Diagnostic commands
bootup	Configure Diagnostic for bootup
level	Select diagnostic level

Command Mode

- /exec/configure

diagnostic bootup level bypass

diagnostic bootup level { bypass | complete }

Syntax Description

diagnostic	Diagnostic commands
bootup	Configure Diagnostic for bootup
level	Select diagnostic level
bypass	Skip all bootup test
complete	Complete level

Command Mode

- /exec/configure

diagnostic clear result module all diagnostic clear result module test

diagnostic clear result module all | diagnostic clear result module <module> test { <test-id> | all }

Syntax Description

diagnostic	Diagnostic commands
clear	Erase Diagnostic Test Results/Stats
result	Diagnostic test result
module	Module keyword
<i>module</i>	Module number
all	Select all
test	Diagnostic test selection
<i>test-id</i>	

Command Mode

- /exec

diagnostic monitor interval module test all hour min second

diagnostic monitor interval module <module> test { all | <name> | <test-id> } hour <hour-cntr> min <min-cntr> second <sec-cntr> | no diagnostic monitor interval module <module> test { all | <name> | <test-id> }

Syntax Description

no	Negate a command or set its defaults
diagnostic	Diagnostic commands
monitor	Configure diagnostic monitoring test
interval	Configure diagnostic monitoring tests interval
module	Module Keyword
<i>module</i>	Module number
test	Diagnostic test selection
all	Select all test ID
<i>test-id</i>	
<i>name</i>	Test name
hour	Hour of the day
<i>hour-cntr</i>	Interval in hours
min	Minute of an hour
<i>min-cntr</i>	Interval in minutes
second	Second of a minute
<i>sec-cntr</i>	Interval in seconds

Command Mode

- /exec/configure

diagnostic monitor module test all

diagnostic monitor module <module> test { all | <name> | <test-id> } | no diagnostic monitor module <module>
test { all | <name> | <test-id> }

Syntax Description

no	Negate a command or set its defaults
diagnostic	Diagnostic commands
monitor	Configure diagnostic monitoring test
module	Module Keyword
<i>module</i>	Module number
test	Diagnostic test selection
all	Select all test ID
<i>test-id</i>	
<i>name</i>	Test name

Command Mode

- /exec/configure

diagnostic ondemand action-on-failure continue failure-count diagnostic ondemand action-on-failure stop

diagnostic ondemand action-on-failure continue failure-count <failure-cnt> | diagnostic ondemand action-on-failure stop

Syntax Description

diagnostic	Diagnostic commands
ondemand	On demand diagnostic setting
action-on-failure	Set action to take if test fails
continue	Continue ondemand test until test failure limit is reached
failure-count	Continue failing tests this many times
stop	Stop ondemand tests immediately if a test fails
<i>failure-cnt</i>	Maximum number of test failures allowed

Command Mode

- /exec

diagnostic ondemand iteration

diagnostic ondemand iteration <iteration-count>

Syntax Description

diagnostic	Diagnostic commands
ondemand	On demand diagnostic setting
iteration	Set number of times to repeat ondemand test list
<i>iteration-count</i>	Number of times to repeat ondemand test list

Command Mode

- /exec

diagnostic ondemand test-parameter module test port_lb packet-length

diagnostic ondemand test-parameter module <module> test port_lb packet-length <size>

Syntax Description

diagnostic	Diagnostic commands
ondemand	Ondemand command
test-parameter	Set test parameter
module	Module keyword
<i>module</i>	Module number
test	Diagnostic test selection
port_lb	Port loop back test
packet-length	Size of the packet
<i>size</i>	Packet size for the selected module

Command Mode

- /exec

diagnostic start module test

diagnostic start module <module> test { all | <name> | <test-id> | non-disruptive | per-port } [port { iall | <port-id> }]

Syntax Description

diagnostic	Diagnostic commands
start	Starting on demand diagnostic
module	Module keyword
<i>module</i>	Module Number
test	Diagnostic test selection
all	Select all test ID
<i>name</i>	Test name
<i>test-id</i>	
non-disruptive	Select the Non-Disruptive test suite [Attribute = N]
per-port	Select the Per-Port test suite [Attribute = P]
port	(Optional) Interface port selection
iall	(Optional) Select all ports
<i>port-id</i>	(Optional)

Command Mode

- /exec

diagnostic stop module test all

```
diagnostic stop module <module> test { all | <name> | <test-id> }
```

Syntax Description

diagnostic	Diagnostic commands
stop	Stopping diagnostic
module	Module keyword
<i>module</i>	Module Number
test	Diagnostic test selection
all	Select all test ID
<i>test-id</i>	
<i>name</i>	Test name

Command Mode

- /exec

diagnostic test simulation module test diagnostic test simulation module test clear

```
diagnostic test simulation module <module> test <test-id> [ port { <port-id> | all } ] { success | fail | random-fail } | diagnostic test simulation module <module> test <test-id> clear
```

Syntax Description

diagnostic	Diagnostic commands
test	Diagnostic test selection
simulation	Simulating Diagnostic result
module	Module keyword
<i>module</i>	Module Number
test	Diagnostic test selection
<i>test-id</i>	
port	(Optional) Interface port selection
all	(Optional) Select all ports
<i>port-id</i>	(Optional)
success	pass test result
fail	fail test result
random-fail	fail test result randomly
clear	Stop simulation

Command Mode

- /exec

diff-clean

diff-clean [all-sessions]

Syntax Description

diff-clean	remove temp files created by ' diff' filters
all-sessions	(Optional) remove ' diff' temp files from all sessions (past and present!) of current user

Command Mode

- /exec

diff-clean all-users

diff-clean all-users

Syntax Description

diff-clean	remove temp files created by ' diff' filters
all-users	remove ' diff' temp files from all sessions (past and present!) of all users

Command Mode

- /exec

diff

| diff [again | echo | -c [<lines>] | -b | -B | -i | -I <regexp> | -y | --left-column | -W <columns> | -q | -s] +

Syntax Description

	Pipe command output to filter
diff	show difference between current and previous invocation (creates temp files: remove them with 'diff-clean' command and dont use it on commands with big outputs, like 'show tech!')
again	(Optional) dont create new file: use old ones, just change display options or add more filters
echo	(Optional) echo the current file (only effective if no old file)
-c	(Optional) set number of lines of context (default 3)
<i>lines</i>	(Optional) number of lines of context
-b	(Optional) Ignore changes in amount of white space
-B	(Optional) Ignore changes that just insert or delete blank lines
-i	(Optional) Ignore changes in case
-I	(Optional) Ignore changes that just insert or delete lines that match regexp
<i>regexp</i>	(Optional) regexp of lines to ignore
-y	(Optional) Use the side by side output format
--left-column	(Optional) Print only the left column of two common lines in side by side format
-W	(Optional) Use an output width of <columns> in side by side format
<i>columns</i>	(Optional) Use an output width of <columns> in side by side format
-q	(Optional) Report only whether the files differ, not the details of the differences
-s	(Optional) Report when two files are the same

Command Mode

- /output

dir

```
dir [ <uri0> | <uri1> | <uri2> ] [ __readonly__ { TABLE_dir <fsize> <timestring> <fname> } { <usage>
<bytesused> <bytesfree> <bytestotal> } ]
```

Syntax Description

<code>dir</code>	list files in a directory
<code>uri0</code>	(Optional) Directory or filename
<code>uri1</code>	(Optional) Directory or filename on expansion flash
<code>uri2</code>	(Optional) Directory or filename on log flash
<code>__readonly__</code>	(Optional) Read Only
<code>TABLE_dir</code>	(Optional) show dir
<code>fsize</code>	(Optional) filesize
<code>timestring</code>	(Optional) time string
<code>fname</code>	(Optional) filename
<code>usage</code>	(Optional) usage
<code>bytesused</code>	(Optional) bytes used
<code>bytesfree</code>	(Optional) bytes free
<code>bytestotal</code>	(Optional) bytes total

Command Mode

- /exec

disable-connected-check

[no | default] disable-connected-check

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
disable-connected-check	Disable check for directly connected peer

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

disable-fka

[no] disable-fka

Syntax Description

no	(Optional) Negate a command or set its defaults
disable-fka	Disables verifying FIP Keep Alives

Command Mode

- /exec/configure/if-vfc

disable-peer-as-check

[no | default] disable-peer-as-check

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
disable-peer-as-check	Disable checking of peer AS-number while advertising

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv4
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

disable-policy-batching

[no] disable-policy-batching [nexthop | { { ipv4 | ipv6 } prefix-list <prfxlist-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
disable-policy-batching	Disable batching evaluation of outbound policy for a peer
nexthop	(Optional) batching based on nexthop
ipv4	(Optional) IPv4 address-family
ipv6	(Optional) IPv6 address-family
prefix-list	(Optional) Apply prefix-list
<i>prfxlist-name</i>	(Optional) Name of prefix-list

Command Mode

- /exec/configure/router-bgp

disable

disable

Syntax Description

disable	disable callhome
---------	------------------

Command Mode

- /exec/configure/callhome

discard-route external

[no] discard-route { external | internal }

Syntax Description

no	(Optional) Negate a command or set its defaults
discard-route	Install discard route
external	External route
internal	Internal route

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

discard-route external

[no] discard-route { external | internal }

Syntax Description

no	(Optional) Negate a command or set its defaults
discard-route	Install discard route
external	External route
internal	Internal route

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

discovery

```
discovery { quick-start | hello { holdtime <link-hello-holdtime> | interval <link-hello-intvl> } | targeted-hello
{ accept [ from <pfx-list> ] | tgt-holdtime <tgt-hello-holdtime> | tgt-interval <tgt-hello-intvl> } |
ignore-transport-address | omit-transport-address | spoofing } | no discovery { quick-start | hello { holdtime |
interval } | targeted-hello { accept | tgt-holdtime | tgt-interval } | ignore-transport-address | omit-transport-address
| spoofing }
```

Syntax Description

no	Negate a command or set its defaults
discovery	LDP discovery
quick-start	Enable quick LDP Hello transmissions on interface up
hello	LDP discovery Hello
interval	LDP discovery Hello interval
holdtime	LDP discovery Hello holdtime
<i>link-hello-holdtime</i>	Holdtime in seconds
<i>link-hello-intvl</i>	Hello interval in seconds
targeted-hello	LDP discovery Targeted Hello
accept	Accept targeted hellos
from	(Optional) Prefix list to specify acceptable targeted hello sources
<i>pfx-list</i>	(Optional) Name of prefix list
tgt-holdtime	LDP discovery Targeted Hello holdtime
<i>tgt-hello-holdtime</i>	Holdtime in seconds
tgt-interval	LDP discovery Targeted Hello interval
<i>tgt-hello-intvl</i>	Hello interval in seconds
ignore-transport-address	
omit-transport-address	
spoofing	

Command Mode

- /exec/configure/ldp

distance

distance <admin-dist> | no distance [<admin-dist>]

Syntax Description

no	Negate a command or set its defaults
distance	OSPFv3 administrative distance
<i>admin-dist</i>	administrative distance value

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

distance

distance <distance> | no distance [<distance>]

Syntax Description

no	Negate a command or set its defaults
distance	RIP administrative distance
<i>distance</i>	RIP administrative distance

Command Mode

- /exec/configure/router-rip/router-rip-af-common /exec/configure/router-rip/router-rip-vrf-af-common

distance

distance <admin-dist> | no distance [<admin-dist>]

Syntax Description

no	Negate a command or set its defaults
distance	Administrative distance
<i>admin-dist</i>	Distance value

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv4

distance

distance <admin-dist> | no distance [<admin-dist>]

Syntax Description

no	Negate a command or set its defaults
distance	Administrative distance
<i>admin-dist</i>	Distance value

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

distance

```
{ { distance <int-distance> <ext-distance> } | { no distance [ <int-distance> <ext-distance> ] } }
```

Syntax Description

no	Negate a command or set its defaults
distance	Define an administrative distance
<i>int-distance</i>	Distance for internal routes
<i>ext-distance</i>	Distance for external routes

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

distance

distance <admin-dist> | no distance [<admin-dist>]

Syntax Description

no	Negate a command or set its defaults
distance	OSPF administrative distance
<i>admin-dist</i>	administrative distance value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

distance

distance <ebgp-dist> <ibgp-dist> <local-dist> | no distance [<ebgp-dist> <ibgp-dist> <local-dist>]

Syntax Description

no	Negate a command or set its defaults
distance	Configure administrative distance
<i>ebgp-dist</i>	Distance for EBGp routes
<i>ibgp-dist</i>	Distance for IBGP routes
<i>local-dist</i>	Distance for local routes

Command Mode

- /exec/configure/router-bgp/router-bgp-af

distribute into route-map all

```
{ { distribute <src-level> into <dst-level> { { route-map { <map-name> | <rtr_pol_name> } } | all } } | { no
distribute <src-level> into <dst-level> [ { route-map { <map-name> | <rtr_pol_name> } } | all ] } }
```

Syntax Description

no	Negate a command or set its defaults
distribute	Distribute routes between ISIS levels
<i>src-level</i>	Route-distribution between levels
<i>dst-level</i>	Route-distribution between levels
route-map	Route Map to constrain distribution
into	from level-n into level-m
<i>map-name</i>	A 'routing-rules' route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy
all	Distribute all level-n routes

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-common

distribute link-state

[no] distribute link-state [instance-id <instid>] [level <level>] [throttle <seconds>]

Syntax Description

no	(Optional) Negate a command or set its defaults
distribute	Distribute routes between ISIS levels
link-state	Distribute link-state
instance-id	(Optional) Instance ID of ISIS process
<i>instid</i>	(Optional) Instance ID of ISIS process
level	(Optional) Level to be distributed
<i>level</i>	(Optional) IS-IS level
throttle	(Optional) Throttle timer in seconds
<i>seconds</i>	(Optional) Throttle timer in seconds

Command Mode

- /exec/configure/router-isis

dns

```
[no] dns { <WORD> } { name-server { <hostname> | <ip-address> } } { [ source-ip { <source-ip-hostname> | <source-ip-address> } ] | [ source-port <src-port> ] } +
```

Syntax Description

no	(Optional)
<i>source-ip</i>	(Optional) source-port
<i>src-port</i>	(Optional)
dns	DNS Operation
<i>WORD</i>	Target IP Address or Hostname
name-server	Name Server
<i>hostname</i>	Destination hostname, broadcast disallowed
<i>ip-address</i>	Destination IP address, broadcast disallowed
<i>source-ip-hostname</i>	(Optional) source IP hostname, broadcast disallowed
<i>source-ip-address</i>	(Optional) source IP address, broadcast disallowed
source-port	(Optional) Source Port

Command Mode

- /exec/configure/ip-sla

domain-id

domain-id { <id> | { type <dtype> value <dvalue> } | Null } | no domain-id [<id> | { type <dtype> value <dvalue> } | Null]

Syntax Description

no	Negate a command or set its defaults
domain-id	OSPF domain-ID
<i>id</i>	OSPF domain ID in IP address format
type	OSPF domain ID type in Hex format
<i>dtype</i>	OSPF domain ID type in Hex format
value	OSPF domain ID ext. community value in Hex
<i>dvalue</i>	
Null	Null Domain-ID

Command Mode

- /exec/configure/router-ospf/vrf

domain-id secondary

domain-id { <id> | { type <dtype> value <dvalue> } | Null } secondary | no domain-id [<id> | { type <dtype> value <dvalue> } | Null] secondary

Syntax Description

no	Negate a command or set its defaults
domain-id	OSPF domain-ID
<i>id</i>	OSPF domain ID in IP address format
type	OSPF domain ID type in Hex format
<i>dtype</i>	OSPF domain ID type in Hex format
value	OSPF domain ID ext. community value in Hex
<i>dvalue</i>	
Null	Null Domain-ID
secondary	Secondary Domain-ID

Command Mode

- /exec/configure/router-ospf/vrf

domain-tag

[no] domain-tag <as-number>

Syntax Description

no	(Optional) Negate a command or set its defaults
domain-tag	Set OSPF process domain-tag
<i>as-number</i>	AS number

Command Mode

- /exec/configure/router-ospf/vrf

dont-capability-negotiate

[no | default] dont-capability-negotiate

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
dont-capability-negotiate	Don't negotiate capability with this neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

dos2nxos

dos2nxos <uri0>

Syntax Description

dos2nxos	DOS to NXOS text file format converter
<i>uri0</i>	Filename to be displayed

Command Mode

- /exec

dot1q

```
{ dot1q <vlan-id> [ cos <cos-val> ] } | { no dot1q }
```

Syntax Description

no	Negate a command or set its defaults
dot1q	specify flow profile to include dot1q tag
<i>vlan-id</i>	specify flow profile vlan-id
cos	(Optional) specify class of service
<i>cos-val</i>	(Optional) class of service value

Command Mode

- /exec/configure/configngoamprofileflow

dot1q

[no] dot1q <vlan-id-sh>

Syntax Description

no	(Optional) Negate a command or set its defaults
dot1q	Configure a dot1q-based static host
<i>vlan-id-sh</i>	

Command Mode

- /exec/configure/static-host

dot1q

{ dot1q <dot1q-id> [<intf-id>] } | { no dot1q }

Syntax Description

no	Negate a command or set its defaults
dot1q	Encapsulation dot1q/bd
<i>dot1q-id</i>	Encapsulation dot1q/bd value
<i>intf-id</i>	(Optional) Name of the interface for ngoam on which dot1q is configured

Command Mode

- /exec/configure/configngoamprofile

dot1q default dynamic

{ dot1q default dynamic } | { no dot1q default }

Syntax Description

no	Negate a command or set its defaults
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
dot1q	Dot1Q Encapsulation
default	Default (wildcard). Match any dot1q when there is no specific dot1q mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

dot1x default

dot1x default

Syntax Description

dot1x	dot1x configuration commands
-------	------------------------------

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x default

dot1x default

Syntax Description

dot1x	dot1x configuration commands
-------	------------------------------

Command Mode

- /exec/configure

dot1x host-mode

dot1x host-mode <host_mode> | no dot1x host-mode

Syntax Description

dot1x	dot1x configuration commands
host-mode	role of 802.1x authenticating entity
<i>host_mode</i>	Host Mode

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x initialize

{ dot1x initialize } | { dot1x initialize interface <if> }

Syntax Description

dot1x	dot1x configuration commands
initialize	Initialize State Machines for a given Interface
<i>if</i>	target interface

Command Mode

- /exec

dot1x mac-auth-bypass

dot1x mac-auth-bypass [eap] | no dot1x mac-auth-bypass

Syntax Description

no	Negate a command or set its defaults
dot1x	dot1x configuration commands
mac-auth-bypass	Configure Mac-Auth-Bypass
eap	(Optional) EAP Authentication

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x mac-move

dot1x mac-move <value> | no dot1x mac-move <value>

Syntax Description

dot1x	dot1x configuration commands
mac-move	Enable or Disable Mac-moves
<i>value</i>	Mac Move

Command Mode

- /exec/configure

dot1x max-reauth-req

dot1x max-reauth-req <count> | no dot1x max-reauth-req

Syntax Description

dot1x	dot1x configuration commands
max-reauth-req	Maximum Re-authentication Attempts Before Failing
<i>count</i>	number of retries

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x max-req

dot1x max-req <count> | no dot1x max-req

Syntax Description

dot1x	dot1x configuration commands
max-req	Maximum Retries to Initiate Authentication
<i>count</i>	number of retries

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x pae

[no] dot1x pae <pae-value>

Syntax Description

dot1x	dot1x configuration commands
pae	role of 802.1x authenticating entity
<i>pae-value</i>	role

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x port-control

[no] dot1x port-control <port-control-value>

Syntax Description

dot1x	dot1x configuration commands
port-control	port control
<i>port-control-value</i>	set the port-control value

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x radius-accounting

[no] dot1x radius-accounting

Syntax Description

dot1x	dot1x configuration commands
radius-accounting	accounting messages to RADIUS

Command Mode

- /exec/configure

dot1x re-authenticate interface

dot1x re-authenticate interface <if>

Syntax Description

dot1x	dot1x configuration commands
re-authenticate	Manually re-authenticate an Interface
<i>if</i>	target interface

Command Mode

- /exec

dot1x re-authentication

[no] dot1x re-authentication

Syntax Description

dot1x	dot1x configuration commands
re-authentication	Enable or Disable Reauthentication for this port

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x re-authentication

[no] dot1x re-authentication

Syntax Description

dot1x	dot1x configuration commands
re-authentication	Enable or Disable Reauthentication for this port

Command Mode

- /exec/configure

dot1x show credential

dot1x show credential <name>

Syntax Description

dot1x	dot1x configuration commands
credential	supplicant credential profile
<i>name</i>	profile name

Command Mode

- /exec/configure/dot1x-cred

dot1x start supplicant interface

```
{ dot1x start supplicant interface <if> } | { dot1x start supplicant interface <if> credential <name> }
```

Syntax Description

dot1x	dot1x configuration commands
start	start 802.1x client
supplicant	802.1x supplicant
<i>if</i>	target interface
credential	credential profile name
<i>name</i>	name

Command Mode

- /exec

dot1x supplicant credential

[no] dot1x supplicant credential <name>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
credential	supplicant credential profile

Command Mode

- /exec/configure

dot1x supplicant credential

[no] dot1x supplicant credential <name>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
credential	credential profile name
<i>name</i>	name

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x supplicant max-start

[no] dot1x supplicant max-start <count>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
max-start	Maximum Start Requests
<i>count</i>	number

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x supplicant max-start

[no] dot1x supplicant max-start <count>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
max-start	Maximum Start Requests
<i>count</i>	number

Command Mode

- /exec/configure

dot1x supplicant timeout auth-period

[no] dot1x supplicant timeout auth-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
auth-period	waiting period for responses from authenticator
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x supplicant timeout auth-period

[no] dot1x supplicant timeout auth-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
auth-period	waiting period for responses from authenticator
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x supplicant timeout held-period

[no] dot1x supplicant timeout held-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
held-period	waiting period for retrying, after failed authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x supplicant timeout held-period

[no] dot1x supplicant timeout held-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
held-period	waiting period for retrying, after failed authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x supplicant timeout start-period

[no] dot1x supplicant timeout start-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
start-period	Interval Between Start Requests
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x supplicant timeout start-period

[no] dot1x supplicant timeout start-period <value>

Syntax Description

dot1x	dot1x configuration commands
supplicant	802.1x supplicant
timeout	Various Timeouts
start-period	Interval Between Start Requests
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x system-auth-control

[no] dot1x system-auth-control

Syntax Description

dot1x	dot1x configuration commands
system-auth-control	Enable or Disable SysAuthControl

Command Mode

- /exec/configure

dot1x timeout inactivity-period

dot1x timeout inactivity-period <value> | no dot1x timeout inactivity-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
inactivity-period	Timeout For Session Inactivity
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x timeout inactivity-period

dot1x timeout inactivity-period <value> | no dot1x timeout inactivity-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
inactivity-period	Timeout For Session Inactivity
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout quiet-period

dot1x timeout quiet-period <value> | no dot1x timeout quiet-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
quiet-period	Timeout For Retrying Authentication After Failed Authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout quiet-period

dot1x timeout quiet-period <value> | no dot1x timeout quiet-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
quiet-period	Timeout For Retrying Authentication After Failed Authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x timeout ratelimit-period

dot1x timeout ratelimit-period <value> | no dot1x timeout ratelimit-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
ratelimit-period	Rate Limit period for EAPOL-Start
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout re-authperiod

dot1x timeout re-authperiod <value> | no dot1x timeout re-authperiod

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
re-authperiod	Timeout For Re-Authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

dot1x timeout re-authperiod

dot1x timeout re-authperiod <value> | no dot1x timeout re-authperiod

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
re-authperiod	Timeout For Re-Authentication
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout server-timeout

dot1x timeout server-timeout <value> | no dot1x timeout server-timeout

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
server-timeout	Timeout for Radius Retries
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout supp-timeout

dot1x timeout supp-timeout <value> | no dot1x timeout supp-timeout

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
supp-timeout	Timeout for Supplicant retries
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout tx-period

dot1x timeout tx-period <value> | no dot1x timeout tx-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
tx-period	Timeout For Resending Requests To Supplicant
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

dot1x timeout tx-period

dot1x timeout tx-period <value> | no dot1x timeout tx-period

Syntax Description

dot1x	dot1x configuration commands
timeout	Various Timeouts
tx-period	Timeout For Resending Requests To Supplicant
<i>value</i>	time interval in seconds

Command Mode

- /exec/configure

down-bit-ignore

{ down-bit-ignore } | { no down-bit-ignore }

Syntax Description

no	Negate a command or set its defaults
down-bit-ignore	Configure a PE router to ignore the DN bit for network summary, external and NSSA external LSA

Command Mode

- /exec/configure/router-ospf/vrf

downlink delay

downlink delay <ena-dis-flg> [timeout <time-out>] | no downlink delay

Syntax Description

no	Negate a command or set its defaults
downlink	Change downlink linkup time
delay	delay bringup of downlinks
<i>ena-dis-flg</i>	Enable/Disable downlink delay feature
timeout	(Optional) downlink ports enable delay in seconds
<i>time-out</i>	(Optional) Time out

Command Mode

- /exec/configure

dpp set-qos-group

[no] dpp set-qos-group <qos-group>

Syntax Description

no	(Optional) Negate a command or set its defaults
dpp	Dynamic Packet Prioritization
set-qos-group	QoS group to be mapped
<i>qos-group</i>	QoS Group Value

Command Mode

- /exec/configure/policy-map/type/uf/class

drop-trigger

[no] drop-trigger { ingress-admission | egress-admission | wred }

Syntax Description

no	(Optional) Negate the command
drop-trigger	Configure drop-trigger parameters
ingress-admission	Ingress Admission Drop
egress-admission	Egress Admission Drop
wred	Weighted Random Early Discard Drop

Command Mode

- /exec/configure/pkt-drop

droplist

[no] droplist <droplistname>

Syntax Description

droplist	Specify POSTCARD droplist to use
<i>droplistname</i>	Name of droplist

Command Mode

- /exec/configure/config-postcard-monitor

droplist

[no] droplist <droplistname>

Syntax Description

droplist	Specify INT droplist to use
<i>droplistname</i>	Name of droplist

Command Mode

- /exec/configure/config-int-monitor

dscp

{ [no] dscp <dscp> | no dscp }

Syntax Description

dscp	Optional DSCP
<i>dscp</i>	Differentiated services codepoint value

Command Mode

- /exec/configure/config-int-exporter

dscp

{ [no] dscp <dscp> | no dscp }

Syntax Description

dscp	Provide the dscp value for this INT flow-profile
<i>dscp</i>	flow-profile dscp (allowed values: 1, 2, 4, 8, 16, 32, 63). Default is 1

Command Mode

- /exec/configure/config-int-flow-prof

dscp

{ [no] dscp <dscp> | no dscp }

Syntax Description

dscp	Optional DSCP
<i>dscp</i>	Differentiated services codepoint value

Command Mode

- /exec/configure/nfm-exporter

dscp

[no] dscp <dscp>

Syntax Description

dscp	DSCP
<i>dscp</i>	DSCP to be configured

Command Mode

- /exec/configure/config-ssx-exporter

dscp

{ [no] dscp <dscp> | no dscp }

Syntax Description

dscp	Optional DSCP
<i>dscp</i>	Differentiated services codepostcard value

Command Mode

- /exec/configure/config-postcard-exporter

dscp

{ [no] dscp <dscp> | no dscp }

Syntax Description

dscp	Provide the dscp value for this POSTCARD flow-profile
<i>dscp</i>	flow-profile dscp (allowed values: 1, 2, 4, 8, 16, 32, 63). Default is 1

Command Mode

- /exec/configure/config-postcard-flow-prof

dst-grp

[no] dst-grp <d-grp-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
dst-grp	Associated destination group
<i>d-grp-id</i>	Identifier

Command Mode

- /exec/configure/telemetry/subscription

dual-active exclude interface-vlan

dual-active exclude interface-vlan <allow-vlans> | no dual-active exclude interface-vlan

Syntax Description

no	Negate a command or set its defaults
dual-active	Configuration when peer link is down but peer is alive
interface-vlan	Interface vlan configuration
exclude	Interface vlans to exclude from suspension when dual-active
<i>allow-vlans</i>	Set allowed interface vlans

Command Mode

- /exec/configure/vpc-domain

duplex

duplex <duplex_mode> | no duplex [<duplex_mode>]

Syntax Description

no	Negate a command or set its defaults
duplex	Enter the port duplex mode
<i>duplex_mode</i>	Interface duplex mode

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

duplex

duplex <duplex_mode> | no duplex [<duplex_mode>]

Syntax Description

no	Negate a command or set its defaults
duplex	Enter the port duplex mode
<i>duplex_mode</i>	Interface duplex mode

Command Mode

- /exec/configure/if-mgmt-ether

duplicate-message throttle

[no] duplicate-message throttle

Syntax Description

no	(Optional) Negate a command or set its defaults
duplicate-message	Configure throttling of duplicate callhome alert messages
throttle	Enable throttling of duplicate callhome alert messages

Command Mode

- /exec/configure/callhome

dynamic-capability

[no | default] dynamic-capability

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
dynamic-capability	Dynamic capability

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

dynamic-med-interval

[no] dynamic-med-interval <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
dynamic-med-interval	Sets the interval for dampening of med changes
<i>sec</i>	Time interval in seconds

Command Mode

- /exec/configure/router-bgp



E Commands

- [eapol mac-address](#), on page 1116
- [ebgp-multihop](#), on page 1117
- [echo](#), on page 1118
- [echo](#), on page 1119
- [ecp max-retries](#), on page 1120
- [ecp mode lan](#), on page 1121
- [ecp retransmission-timer-exponent](#), on page 1122
- [eem test](#), on page 1123
- [eemtest policy-add](#), on page 1124
- [eemtest policy-remove](#), on page 1125
- [egress-engineering](#), on page 1126
- [egress](#), on page 1127
- [eid-prefix](#), on page 1128
- [eigrp event-history cli size](#), on page 1129
- [eigrp file-debug](#), on page 1130
- [email-addr](#), on page 1131
- [email-contact](#), on page 1132
- [email](#), on page 1133
- [email](#), on page 1134
- [enable](#), on page 1135
- [enable](#), on page 1136
- [enable Cert](#), on page 1137
- [encapsulation dot1q](#), on page 1138
- [encapsulation dot1q](#), on page 1139
- [encrypt pause-frame](#), on page 1140
- [encryption decrypt type6](#), on page 1141
- [encryption delete type6](#), on page 1142
- [encryption re-encrypt obfuscated](#), on page 1143
- [end](#), on page 1144
- [endpoint](#), on page 1145
- [enforce-first-as](#), on page 1146
- [enrollment terminal](#), on page 1147
- [errdisable](#), on page 1148

- [errdisable detect cause](#), on page 1149
- [errdisable detect cause acl-exception](#), on page 1150
- [errdisable port detect cause acl-exception](#), on page 1151
- [errdisable recovery interval](#), on page 1152
- [erspan-id](#), on page 1153
- [ethalyzer local](#), on page 1154
- [ethernet-segment](#), on page 1155
- [ethernet-segment delay-restore time](#), on page 1156
- [ethernet-tag encapsulation dot1q default static](#), on page 1157
- [ethernet-tag encapsulation dot1q static](#), on page 1158
- [ethernet-tag encapsulation vni default static](#), on page 1159
- [ethernet-tag encapsulation vni static](#), on page 1160
- [evb mac](#), on page 1161
- [evb reinit-keep-alive](#), on page 1162
- [evb resource-wait-delay](#), on page 1163
- [event-history](#), on page 1164
- [event-history aclog category all](#), on page 1165
- [event-history aclog category all](#), on page 1166
- [event-history aclog category fc2](#), on page 1167
- [event-history aclog category fc2](#), on page 1168
- [event-history aclog category mts](#), on page 1169
- [event-history aclog category mts](#), on page 1170
- [event-history adbm category all](#), on page 1171
- [event-history adbm category all](#), on page 1172
- [event-history adbm category fc2](#), on page 1173
- [event-history adbm category fc2](#), on page 1174
- [event-history adbm category mts](#), on page 1175
- [event-history adbm category mts](#), on page 1176
- [event-history callhome](#), on page 1177
- [event-history capability](#), on page 1178
- [event-history cli](#), on page 1179
- [event-history copp category all](#), on page 1180
- [event-history copp category all](#), on page 1181
- [event-history copp category fc2](#), on page 1182
- [event-history copp category fc2](#), on page 1183
- [event-history copp category mts](#), on page 1184
- [event-history copp category mts](#), on page 1185
- [event-history dot1x](#), on page 1186
- [event-history drap category all](#), on page 1187
- [event-history drap category all](#), on page 1188
- [event-history drap category mts](#), on page 1189
- [event-history drap category mts](#), on page 1190
- [event-history eltm category all](#), on page 1191
- [event-history eltm category all](#), on page 1192
- [event-history eltm category fc2](#), on page 1193
- [event-history eltm category fc2](#), on page 1194

- event-history eltm category mts, on page 1195
- event-history eltm category mts, on page 1196
- event-history epp category all, on page 1197
- event-history epp category all, on page 1198
- event-history epp category fc2, on page 1199
- event-history epp category fc2, on page 1200
- event-history epp category mts, on page 1201
- event-history epp category mts, on page 1202
- event-history errors, on page 1203
- event-history ethpm, on page 1204
- event-history events, on page 1205
- event-history exceptionlog, on page 1206
- event-history fcoe_mgr category all, on page 1208
- event-history fcoe_mgr category all, on page 1209
- event-history fcoe_mgr category fc2, on page 1210
- event-history fcoe_mgr category fc2, on page 1211
- event-history fcoe_mgr category mts, on page 1212
- event-history fcoe_mgr category mts, on page 1213
- event-history hardware-telemetry, on page 1214
- event-history im category mts, on page 1215
- event-history imp category all, on page 1216
- event-history imp category all, on page 1217
- event-history imp category fc2, on page 1218
- event-history imp category fc2, on page 1219
- event-history imp category mts, on page 1220
- event-history imp category mts, on page 1221
- event-history keystore, on page 1222
- event-history lacp category all, on page 1223
- event-history lacp category all, on page 1224
- event-history lacp category fc2, on page 1225
- event-history lacp category fc2, on page 1226
- event-history lacp category mts, on page 1227
- event-history lacp category mts, on page 1228
- event-history lem-mgr category all, on page 1229
- event-history lem-mgr category all, on page 1230
- event-history lem-mgr category fc2, on page 1231
- event-history lem-mgr category fc2, on page 1232
- event-history lem-mgr category mts, on page 1233
- event-history lem-mgr category mts, on page 1234
- event-history license, on page 1235
- event-history lldp category all, on page 1236
- event-history lldp category all, on page 1237
- event-history lldp category fc2, on page 1238
- event-history lldp category fc2, on page 1239
- event-history lldp category mts, on page 1240
- event-history lldp category mts, on page 1241

- [event-history m2rib category all](#), on page 1242
- [event-history mfdm category all](#), on page 1243
- [event-history mfdm category all](#), on page 1244
- [event-history mfdm category fc2](#), on page 1245
- [event-history mfdm category fc2](#), on page 1246
- [event-history mfdm category mts](#), on page 1247
- [event-history mfdm category mts](#), on page 1248
- [event-history mmode category all](#), on page 1249
- [event-history module](#), on page 1250
- [event-history npv category all](#), on page 1251
- [event-history npv category all](#), on page 1252
- [event-history npv category fc2](#), on page 1253
- [event-history npv category fc2](#), on page 1254
- [event-history npv category mts](#), on page 1255
- [event-history npv category mts](#), on page 1256
- [event-history pfstat category all](#), on page 1257
- [event-history pfstat category all](#), on page 1258
- [event-history pfstat category fc2](#), on page 1259
- [event-history pfstat category fc2](#), on page 1260
- [event-history pfstat category mts](#), on page 1261
- [event-history pfstat category mts](#), on page 1262
- [event-history platform buffer-size](#), on page 1263
- [event-history platform category all](#), on page 1264
- [event-history platform category all](#), on page 1265
- [event-history pltfm_config category all](#), on page 1266
- [event-history pltfm_config category all](#), on page 1267
- [event-history pltfm_config category fc2](#), on page 1268
- [event-history pltfm_config category fc2](#), on page 1269
- [event-history pltfm_config category mts](#), on page 1270
- [event-history pltfm_config category mts](#), on page 1271
- [event-history plugin](#), on page 1272
- [event-history poap category all](#), on page 1273
- [event-history poap category all](#), on page 1274
- [event-history poap category fc2](#), on page 1275
- [event-history poap category fc2](#), on page 1276
- [event-history poap category mts](#), on page 1277
- [event-history poap category mts](#), on page 1278
- [event-history port-profile category all](#), on page 1279
- [event-history port-profile category mts](#), on page 1280
- [event-history port-resources category all](#), on page 1281
- [event-history port-resources category all](#), on page 1282
- [event-history port-resources category fc2](#), on page 1283
- [event-history port-resources category fc2](#), on page 1284
- [event-history port-resources category mts](#), on page 1285
- [event-history port-resources category mts](#), on page 1286
- [event-history port-security category all](#), on page 1287

- event-history port-security category all, on page 1288
- event-history port-security category fc2, on page 1289
- event-history port-security category fc2, on page 1290
- event-history port-security category mts, on page 1291
- event-history port-security category mts, on page 1292
- event-history port category fc2, on page 1293
- event-history port category fc2, on page 1294
- event-history port category mts, on page 1295
- event-history port category mts, on page 1296
- event-history port_client category all, on page 1297
- event-history port_client category all, on page 1298
- event-history port_client category fc2, on page 1299
- event-history port_client category fc2, on page 1300
- event-history port_client category mts, on page 1301
- event-history port_client category mts, on page 1302
- event-history san-port-channel category all, on page 1303
- event-history san-port-channel category all, on page 1304
- event-history san-port-channel category fc2, on page 1305
- event-history san-port-channel category fc2, on page 1306
- event-history san-port-channel category mts, on page 1307
- event-history san-port-channel category mts, on page 1308
- event-history sensor, on page 1309
- event-history session-mgr category all, on page 1310
- event-history session-mgr category all, on page 1311
- event-history session-mgr category mts, on page 1312
- event-history session-mgr category mts, on page 1313
- event-history sflow, on page 1314
- event-history snmp, on page 1315
- event-history spanning-tree category all, on page 1316
- event-history spm category all, on page 1317
- event-history spm category all, on page 1318
- event-history spm category fc2, on page 1319
- event-history spm category fc2, on page 1320
- event-history spm category mts, on page 1321
- event-history spm category mts, on page 1322
- event-history stripcl category all, on page 1323
- event-history stripcl category all, on page 1324
- event-history stripcl category mts, on page 1325
- event-history tamnw category all, on page 1326
- event-history tamnw category all, on page 1327
- event-history tamnw category fc2, on page 1328
- event-history tamnw category fc2, on page 1329
- event-history tamnw category mts, on page 1330
- event-history tamnw category mts, on page 1331
- event-history uddl category all, on page 1332
- event-history ufdm category all, on page 1333

- [event-history ufdm category all](#), on page 1334
- [event-history ufdm category fc2](#), on page 1335
- [event-history ufdm category fc2](#), on page 1336
- [event-history ufdm category mts](#), on page 1337
- [event-history ufdm category mts](#), on page 1338
- [event-history vdc category all](#), on page 1339
- [event-history vdc category all](#), on page 1340
- [event-history vdc category mts](#), on page 1341
- [event-history xbar category all](#), on page 1342
- [event-history xbar category all](#), on page 1343
- [event-history xbar category debug](#), on page 1344
- [event-history xbar category debug](#), on page 1345
- [event-history xbar category mts](#), on page 1346
- [event-history xbar category mts](#), on page 1347
- [event-log-size](#), on page 1348
- [event-logging](#), on page 1349
- [event](#), on page 1350
- [event](#), on page 1351
- [event application sub-system type](#), on page 1352
- [event cli match](#), on page 1353
- [event counter name entry-val entry-op](#), on page 1354
- [event fanabsent time](#), on page 1355
- [event fanbad time](#), on page 1356
- [event fib adjacency extra](#), on page 1357
- [event fib resource tcam usage](#), on page 1358
- [event fib route](#), on page 1359
- [event gold module test testing-type scheduled consecutive-failure](#), on page 1360
- [event manager applet](#), on page 1361
- [event manager clear counter](#), on page 1362
- [event manager clear history events](#), on page 1363
- [event manager environment](#), on page 1364
- [event manager policy](#), on page 1365
- [event manager run](#), on page 1366
- [event memory](#), on page 1367
- [event module-failure type module count](#), on page 1368
- [event module status module1](#), on page 1369
- [event neighbor-discovery](#), on page 1370
- [event none](#), on page 1371
- [event oir fan](#), on page 1372
- [event oir module](#), on page 1373
- [event oir powersupply](#), on page 1374
- [event policy-default count](#), on page 1375
- [event poweroverbudget](#), on page 1376
- [event snmp oid get-type exact entry-op entry-val poll-interval](#), on page 1377
- [event storm-control](#), on page 1379
- [event syslog pattern](#), on page 1380

- event sysmgr memory major minor clear, on page 1381
- event sysmgr switchover count time, on page 1382
- event temperature threshold, on page 1383
- event test match, on page 1384
- event timer, on page 1385
- event track state, on page 1386
- evpn, on page 1387
- evpn esi multihoming, on page 1388
- evpn multihoming core-tracking, on page 1389
- evpn multisite border-gateway, on page 1390
- evpn multisite dci-tracking, on page 1391
- evpn multisite fabric-tracking, on page 1392
- evpn storm-control level, on page 1393
- exceptionlog module syserr devid errtype errcode phylyer ports harderror, on page 1394
- exclude access-list, on page 1395
- exclude access-list, on page 1396
- exec-timeout, on page 1397
- exec-timeout, on page 1398
- existing-cli, on page 1399
- exit, on page 1400
- exit, on page 1401
- exp, on page 1402
- explicit-null, on page 1403
- explicit-path, on page 1404
- explicit-path identifier, on page 1405
- export-gateway-ip, on page 1406
- export map, on page 1407
- export vrf default map, on page 1408
- exporter-id, on page 1409
- exporter, on page 1410
- exporter, on page 1411
- exporter, on page 1412
- exporter, on page 1413
- exporter, on page 1414

eapol mac-address

[no] eapol mac-address { <mac_addr> | broadcast-address } [ether type <eth_type>]

Syntax Description

eapol	specify mac address and ether type for eapol packets
mac-address	mac address
<i>mac_addr</i>	mac address destination specified as a string
broadcast-address	broadcast address
ether type	(Optional) ether type
<i>eth_type</i>	(Optional) ether type specified as string

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-ethernet-p2p /exec/configure/if-eth-non-member /exec/configure/if-port-channel

ebgp-multihop

ebgp-multihop <ebgp-ttl> | { no | default } ebgp-multihop [<ebgp-ttl>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
ebgp-multihop	Specify multihop TTL for remote peer
<i>ebgp-ttl</i>	EBGP TTL value

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

echo

```
echo [ -e ] [ <line> ]
```

Syntax Description

echo	echo argument back to screen (useful for scripts)
-e	(Optional) enable interpretation of the backslash-escaped characters
<i>line</i>	(Optional) the string to echo (use quotes if string contains spaces)

Command Mode

- /exec

echo

echo { { revision { 3 | 4 } } | { vendor-extension } } | no echo { { revision } | { vendor-extension } }

Syntax Description

no	Negate a command or set its defaults
echo	Echo Request attributes
revision	Echo packet default revision
3	draft-ietf-mpls-lsp-ping-03 (rev 2)
4	RFC 4379 Compliant
vendor-extension	Send Vendor Extension TLV with echo Req

Command Mode

- /exec/configure/mpls-oam

ecp max-retries

ecp max-retries <cnt> | no ecp max-retries [<cnt>]

Syntax Description

no	Negate a command or set its defaults
ecp	ECP (Edge Control Protocol)
max-retries	Maximal number of retransmissions
<i>cnt</i>	Numer of retries. default 3

Command Mode

- /exec/configure

ecp mode lan

[no] ecp mode lan

Syntax Description

no	(Optional) Negate a command or set its defaults
ecp	ECP (Edge Control Protocol)
mode	ECP session mode
lan	Enable ECP LAN mode

Command Mode

- /exec/configure

ecp retransmission-timer-exponent

ecp retransmission-timer-exponent <exp> | no ecp retransmission-timer-exponent [<exp>]

Syntax Description

no	Negate a command or set its defaults
ecp	ECP (Edge Control Protocol)
retransmission-timer-exponent	Retransmission timer exponent
<i>exp</i>	Timer exponent. default: 14 (ex. 10 exp ~ 10 ms)

Command Mode

- /exec/configure

eem test

eem test <param>

Syntax Description

eem	Event Manager command
test	Do test action
<i>param</i>	Test action parameter (dummy value)

Command Mode

- /exec

eemtest policy-add

eemtest policy-add <name> [override <override-name>]

Syntax Description

eemtest	EEM test commands
policy-add	Add a client policy
<i>name</i>	Name of policy (cannot have underscore in first two characters)
override	(Optional) Override a system policy
<i>override-name</i>	(Optional) Name of the system policy to override - should begin with double underscore

Command Mode

- /exec

eemtest policy-remove

eemtest policy-remove <name> [override <override-name>]

Syntax Description

eemtest	EEM test commands
policy-remove	Remove a client policy
<i>name</i>	Name of policy (cannot have underscore in first two characters)
override	(Optional) Override a system policy
<i>override-name</i>	(Optional) Name of the system policy to override - should begin with double underscore

Command Mode

- /exec

egress-engineering

[no | default] egress-engineering [peer-set <peer-set-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
egress-engineering	Configure Egress Peer Engineering (EPE) for peer
peer-set	(Optional) Configure EPE Peer-Set
<i>peer-set-name</i>	(Optional) EPE Peer-Set name

Command Mode

- /exec/configure/router-bgp/router-bgp-template-neighbor
/exec/configure/router-bgp/router-bgp-neighbor-stmp /exec/configure/router-bgp/router-bgp-neighbor
/exec/configure/router-bgp/router-bgp-prefixneighbor

egress

{ egress <eid> | no egress }

Syntax Description

no	Negate a command or set its defaults
egress	Outgoing egress Interface
<i>eid</i>	Outgoing egress Interface identifier

Command Mode

- /exec/configure/configngoamconnectcheck

eid-prefix

```
{ [ no ] eid-prefix { <eid-prefix> | <eid-prefix6> } [ instance-id <iid> ] [ route-tag <tag> ] [
accept-more-specifics ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
eid-prefix	EID-prefix for LISP site
<i>eid-prefix</i>	IP EID-prefix of the site
instance-id	(Optional) Configures instance-ID for site's EID-prefix
<i>iid</i>	(Optional) 24-bit instance-ID value
route-tag	(Optional) Route tag for LISP EID-prefix routes
<i>tag</i>	(Optional) 32-bit value for tag
accept-more-specifics	(Optional) Allow more-specifics of site EID-prefix to register

Command Mode

- /exec/configure/lisp-site /exec/configure/vrf/lisp-site

eigrp event-history cli size

[no] eigrp [<eigrp-ptag>] event-history { cli } size { <size_in_text> | <size_in_Kbytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Event History of EIGRP
cli	EIGRP CLI related events
size	Configure the size of the event-hist buffer
<i>size_in_text</i>	Buffer size
<i>size_in_Kbytes</i>	Size of the file in kbytes

Command Mode

- /exec/configure

eigrp file-debug

[no] eigrp file-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	EIGRP
file-debug	Collect all debugs to a file

Command Mode

- /exec/configure

email-addr

[no] email-addr <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
email-addr	Add email addr to send output of jobs configured for this schedule
s0	Provide email address, example: jdow@xyz.com

Command Mode

- /exec/configure/schedule

email-contact

{ email-contact <*s0*> | no email-contact }

Syntax Description

no	Negate a command or set its defaults
email-contact	email address of the contact person
<i>s0</i>	Provide email address, example: <code>jdow@xyz.com</code>

Command Mode

- /exec/configure/callhome

email

[no] email

Syntax Description

no	(Optional) Negate a command or set its defaults
email	Configure pipe email

Command Mode

- /exec/configure

email

| email [-f <fromemail> | -r <replytoemail> | -S <smtphost> | -P <smtpport> | -s <subject> | -c <vrf-known-name>] + <toemail>

Syntax Description

	Pipe command output to filter
email	Email command output
-f	(Optional) From address
<i>fromemail</i>	(Optional) Email address
-r	(Optional) Reply to address
<i>replytoemail</i>	(Optional) Email address
-S	(Optional) SMTP host
<i>smtphost</i>	(Optional) IPV4/IPV6 address or DNS name
-P	(Optional) SMTP port
<i>smtpport</i>	(Optional) SMTP port number
-s	(Optional) Subject
<i>subject</i>	(Optional) Email subject
-c	(Optional) VRF
<i>vrf-known-name</i>	(Optional) VRF name
<i>toemail</i>	Recipient email address

Command Mode

- /output

enable

enable [<enable-level>]

Syntax Description

enable	Turn on privileged commands
<i>enable-level</i>	(Optional) Enable Level

Command Mode

- /exec

enable

[no] enable

Syntax Description

no	(Optional) Negate a command or set its defaults
enable	enable callhome

Command Mode

- /exec/configure/callhome

enable Cert

[no] enable { Cert-DN-match | user-server-group }

Syntax Description

no	(Optional) Negate a command or set its defaults
enable	Enable
user-server-group	Enable/Disable group validation
Cert-DN-match	Enable/Disable Cert-DN matching

Command Mode

- /exec/configure/ldap

encapsulation dot1q

encapsulation dot1q <vlan_id> | no encapsulation dot1q [<vlan_id>]

Syntax Description

no	Negate a command or set its defaults
encapsulation	Set encapsulation type for an interface
dot1q	IEEE 802.1Q Virtual LAN
<i>vlan_id</i>	IEEE 802.1Q VLAN ID required

Command Mode

- /exec/configure/if-gig-ether-sub /exec/configure/if-remote-ethernet-sub

encapsulation dot1q

encapsulation dot1q <vlan_id> | no encapsulation dot1q [<vlan_id>]

Syntax Description

no	Negate a command or set its defaults
encapsulation	Set encapsulation type for an interface
dot1q	IEEE 802.1Q Virtual LAN
<i>vlan_id</i>	IEEE 802.1Q VLAN ID required

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-port-channel-sub /exec/configure/if-ether-sub-p2p

encrypt pause-frame

[no] encrypt pause-frame

Syntax Description

encrypt	Enable/disable encryption for specific type of frames
pause-frame	Ethernet PAUSE frames

Command Mode

- /exec/configure/cts-dot1x /exec/configure/cts-manual

encryption decrypt type6

encryption decrypt type6

Syntax Description

encryption	Strong encryption for credential(s)
decrypt	Decrypts strongly encrypted secret(s) to obfuscated type(s)
type6	type6 secrets present in system

Command Mode

- /exec

encryption delete type6

encryption delete type6 [<uuid> | <name>]

Syntax Description

encryption	Strong encryption for credential(s)
delete	Deletes strongly encrypted secret(s)
type6	type6 secrets present in system
<i>uuid</i>	(Optional) uuid of the app
<i>name</i>	(Optional) Service name

Command Mode

- /exec

encryption re-encrypt obfuscated

encryption re-encrypt obfuscated

Syntax Description

encryption	Strong encryption for credential(s)
re-encrypt	Re-encrypts weekly encrypted secret(s) to strongly encrypted secret(s)
obfuscated	type-3/type-7/clear-text secrets present in system

Command Mode

- /exec

end

end

Syntax Description

end	Go to exec mode
-----	-----------------

Command Mode

- /global

endpoint

{ no endpoint | endpoint <px> }

Syntax Description

no	Negate a command or set its defaults
endpoint	Policy Endpoint
<i>px</i>	IPv4 endpoint address

Command Mode

- /exec/configure/sr/te/pol

enforce-first-as

[no] enforce-first-as

Syntax Description

no	(Optional) Negate a command or set its defaults
enforce-first-as	Enforce neighbor AS is the first AS in AS-PATH attribute (EBGP)

Command Mode

- /exec/configure/router-bgp

enrollment terminal

[no] enrollment terminal

Syntax Description

no	(Optional) Negate a command or set its defaults
enrollment	Configure trustpoint enrollment
terminal	Configure trustpoint enrollment via console

Command Mode

- /exec/configure/trustpoint

errdisable

```
errdisable { detect cause_detect { all_cause | link-flap_cause | loopback_cause } | recovery { cause_recovery
{ all_recovery | udld | loopback_recovery | bpduguard | security-violation | psecure-violation | link-flap-recovery
| storm-control | dcbx-no-ack | vpc-peerlink | failed-port-state } } } | no errdisable { detect cause_detect {
all_cause | link-flap_cause | loopback_cause } | recovery { cause_recovery { all_recovery | udld |
loopback_recovery | bpduguard | security-violation | psecure-violation | link-flap-recovery | storm-control |
dcbx-no-ack | vpc-peerlink | failed-port-state } } }
```

Syntax Description

no	Negate a command or set its defaults
errdisable	Error disable
detect	Error disable detection
cause_detect	Enable error disable detection for application
all_cause	Enable error detection on all cases
link-flap_cause	Enable error disable detection on linkstate-flapping
loopback_cause	Enable error disable detection on loopback detected by UDLD
recovery	Error disable recovery
cause_recovery	Enable error disable recovery for application
all_recovery	Enable timer to recover from all causes
udld	Enable timer to recover from udld error disabled state
loopback_recovery	Enable timer to recover from loopback error disabled state detected by UDLD
bpduguard	Enable timer to recover from BPDU Guard error disable state
security-violation	Enable timer to recover from 802.1x violation disable state
psecure-violation	Enable timer to recover from psecure violation disable state
link-flap-recovery	Enable timer to recover from linkstate flapping
storm-control	Enable timer to recover from storm control error disabled state
dcbx-no-ack	Enable timer to recover from no DCBX Acks
vpc-peerlink	Enable timer to recover from inconsistent vpc peer-link
failed-port-state	Enable timer to recover from stp set port state failure

Command Mode

- /exec/configure

errdisable detect cause

```
[no] errdisable detect cause { link-down [ num-times <i0> duration <i1> ] | trustsec-violation [ num-times
<i0> duration <i1> ] | bit-errors [ num-times <i0> duration <i1> ] | signal-loss [ num-times <i0> duration
<i1> ] | sync-loss [ num-times <i0> duration <i1> ] | link-reset [ num-times <i0> duration <i1> ] | credit-loss
[ num-times <i0> duration <i1> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
errdisable	Error Disable the port
detect	Enter detect reason
cause	Enter port down cause
link-down	Detection of excessive link down events
trustsec-violation	Detection of excessive trustsec violation events
bit-errors	Detection of excessive bit error events
signal-loss	Detection of excessive signal loss events
sync-loss	Detection of excessive sync loss events
link-reset	Detection of excessive link reset events
credit-loss	Detection of excessive credit loss events
num-times	(Optional) Enter number of flaps
<i>i0</i>	(Optional) Enter number of flaps
duration	(Optional) Enter duration in seconds
<i>i1</i>	(Optional) Enter duration in seconds

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext

errdisable detect cause acl-exception

[no] errdisable detect cause acl-exception

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure

errdisable port detect cause acl-exception

[no] errdisable port detect cause acl-exception

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/if-ethernet /exec/configure/if-ethernet-switch

errdisable recovery interval

errdisable recovery interval <val> | no errdisable recovery interval [<val>]

Syntax Description

no	Negate a command or set its defaults
errdisable	Error disable
recovery	Error disable recovery
interval	Error disable recovery timer value
<i>val</i>	timer-interval (sec)

Command Mode

- /exec/configure

erspan-id

[no] erspan-id <flow_id>

Syntax Description

no	(Optional) Negate a command or set its defaults
erspan-id	Ersparn ID for ERSPAN sessions
<i>flow_id</i>	erspan-id

Command Mode

- /exec/configure/monitor-erspan

ethalyzer local

[no] ethalyzer local [{ { {

Syntax Description

{	(Optional) inband
no	(Optional) Negate a command or set its defaults
ethalyzer	Configure cisco packet analyzer
local	start local capture of frames to Sup

Command Mode

- /exec

ethernet-segment

[no] ethernet-segment <es-num>

Syntax Description

no	(Optional) Negate a command or set its defaults
ethernet-segment	Configure Ethernet-Segment
<i>es-num</i>	ethernet-segment number

Command Mode

- /exec/configure/if-eth-port-channel-switch

ethernet-segment delay-restore time

[no] ethernet-segment delay-restore time <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
ethernet-segment	ethernet-segment
delay-restore	delay-restore
time	time
<i>sec</i>	time in seconds

Command Mode

- /exec/configure/evpn-esi-mh

ethernet-tag encapsulation dot1q default static

{ ethernet-tag encapsulation dot1q default { static <profile-name> | dynamic } } | { no ethernet-tag encapsulation dot1q default }

Syntax Description

no	Negate a command or set its defaults
ethernet-tag	Data snooping triggers
encapsulation	Encapsulation/Trigger type
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
dot1q	Dot1Q Encapsulation
default	Default (wildcard). Match any dot1q when there is no specific dot1q mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

ethernet-tag encapsulation dot1q static

{ ethernet-tag encapsulation dot1q <vlan-id> { static <profile-name> | dynamic } } | { no ethernet-tag encapsulation dot1q <vlan-id> }

Syntax Description

no	Negate a command or set its defaults
ethernet-tag	Data snooping triggers
encapsulation	Encapsulation/Trigger type
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
dot1q	Dot1Q Encapsulation
<i>vlan-id</i>	

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

ethernet-tag encapsulation vni default static

```
{ ethernet-tag encapsulation vni default { static <profile-name> | dynamic } } | { no ethernet-tag encapsulation vni default }
```

Syntax Description

no	Negate a command or set its defaults
ethernet-tag	Data snooping triggers
encapsulation	Encapsulation/Trigger type
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
vni	Virtual Network Identifier
default	Default (wildcard). Match any vni when there is no specific vni mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

ethernet-tag encapsulation vni static

```
{ ethernet-tag encapsulation vni <vni-id> { static <profile-name> | dynamic } } | { no ethernet-tag encapsulation vni <vni-id> }
```

Syntax Description

no	Negate a command or set its defaults
ethernet-tag	Data snooping triggers
encapsulation	Encapsulation/Trigger type
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
vni	Virtual Network Identifier
<i>vni-id</i>	

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

evb mac

{ evb mac <mac-addr> } | { no evb mac [<mac-addr>] }

Syntax Description

no	Negate a command or set its defaults
evb	EVB (Edge Virtual Bridge)
mac	VDP multicast MAC address
<i>mac-addr</i>	MAC Address

Command Mode

- /exec/configure

evb reinit-keep-alive

```
{ evb reinit-keep-alive <exp> } | { no evb reinit-keep-alive [ <exp> ] }
```

Syntax Description

no	Negate a command or set its defaults
evb	EVB (Edge Virtual Bridge)
reinit-keep-alive	Keepalive
<i>exp</i>	Timer exponent. (Min 22 exp ~ 40 seconds)

Command Mode

- /exec/configure

evb resource-wait-delay

{ evb resource-wait-delay <exp> } | { no evb resource-wait-delay [<exp>] }

Syntax Description

no	Negate a command or set its defaults
evb	EVB (Edge Virtual Bridge)
resource-wait-delay	Resource wait delay
<i>exp</i>	Timer exponent. (Min 22 exp ~ 40 seconds)

Command Mode

- /exec/configure

event-history

[no] event-history { detail | periodic | objstore } [size { <size_in_text> | <bytes> | disable }]

Syntax Description

no	(Optional) Negate a command or set its defaults
event-history	Configure event-history details
detail	Detailed event history buffer
periodic	Periodic events history buffer
objstore	Objstore events history buffer
size	(Optional) Set the buffer size
disable	(Optional) Disable the buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>bytes</i>	(Optional) Buffer size in bytes

Command Mode

- /exec/configure/router-bgp

event-history aclog category all

event-history aclog category all

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
category	Configure aclog event logs for category
all	Configure aclog event logs for category all events

Command Mode

- /exec

event-history aclog category all

event-history aclog no category all

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
no	Disable aclog event logs for category
category	Configure aclog event logs for category
all	Configure aclog event logs for category all events

Command Mode

- /exec

event-history aclog category fc2

```
event-history aclog category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
category	Configure aclog event logs for category
fc2	Configure aclog event logs for category FC2
rx	(Optional) Configure aclog event logs for FC2 Rx frames
brief	(Optional) Configure brief aclog event logs for FC2 Rx
detail	(Optional) Configure detail aclog event logs for FC2 Rx
tx	(Optional) Configure aclog event logs for FC2 Tx frames
brief1	(Optional) Configure brief aclog event logs for FC2 Tx
detail1	(Optional) Configure detail aclog event logs for FC2 Tx

Command Mode

- /exec

event-history aclog category fc2

```
event-history aclog no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
no	Disable aclog event logs for category
category	Configure aclog event logs for category
fc2	Configure aclog event logs for category FC2
rx	(Optional) Configure aclog event logs for FC2 Rx frames
brief	(Optional) Configure brief aclog event logs for FC2 Rx
detail	(Optional) Configure detail aclog event logs for FC2 Rx
tx	(Optional) Configure aclog event logs for FC2 Tx frames
brief1	(Optional) Configure brief aclog event logs for FC2 Tx
detail1	(Optional) Configure detail aclog event logs for FC2 Tx

Command Mode

- /exec

event-history aclog category mts

```
event-history aclog category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
category	Configure aclog event logs for category
mts	Configure aclog event logs for category mts
rx	(Optional) Configure aclog event logs for mts Rx frames
brief	(Optional) Configure brief aclog event logs for mts Rx
detail	(Optional) Configure detail aclog event logs for mts Rx
tx	(Optional) Configure aclog event logs for mts Tx frames
brief1	(Optional) Configure brief aclog event logs for mts Tx
detail1	(Optional) Configure detail aclog event logs for mts Tx

Command Mode

- /exec

event-history aclog category mts

```
event-history aclog no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
aclog	Configure aclog event logs
no	Disable aclog event logs for category
category	Configure aclog event logs for category
mts	Configure aclog event logs for category mts
rx	(Optional) Configure aclog event logs for mts Rx frames
brief	(Optional) Configure brief aclog event logs for mts Rx
detail	(Optional) Configure detail aclog event logs for mts Rx
tx	(Optional) Configure aclog event logs for mts Tx frames
brief1	(Optional) Configure brief aclog event logs for mts Tx
detail1	(Optional) Configure detail aclog event logs for mts Tx

Command Mode

- /exec

event-history adbm category all

event-history adbm no category all

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
no	Disable adbm event logs for category
category	Configure adbm event logs for category
all	Configure adbm event logs for category all events

Command Mode

- /exec

event-history adbm category all

event-history adbm category all

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
category	Configure adbm event logs for category
all	Configure adbm event logs for category all events

Command Mode

- /exec

event-history adbm category fc2

```
event-history adbm category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
category	Configure adbm event logs for category
fc2	Configure adbm event logs for category FC2
rx	(Optional) Configure adbm event logs for FC2 Rx frames
brief	(Optional) Configure brief adbm event logs for FC2 Rx
detail	(Optional) Configure detail adbm event logs for FC2 Rx
tx	(Optional) Configure adbm event logs for FC2 Tx frames
brief1	(Optional) Configure brief adbm event logs for FC2 Tx
detail1	(Optional) Configure detail adbm event logs for FC2 Tx

Command Mode

- /exec

event-history adbm category fc2

```
event-history adbm no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
no	Disable adbm event logs for category
category	Configure adbm event logs for category
fc2	Configure adbm event logs for category FC2
rx	(Optional) Configure adbm event logs for FC2 Rx frames
brief	(Optional) Configure brief adbm event logs for FC2 Rx
detail	(Optional) Configure detail adbm event logs for FC2 Rx
tx	(Optional) Configure adbm event logs for FC2 Tx frames
brief1	(Optional) Configure brief adbm event logs for FC2 Tx
detail1	(Optional) Configure detail adbm event logs for FC2 Tx

Command Mode

- /exec

event-history adbm category mts

```
event-history adbm category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
category	Configure adbm event logs for category
mts	Configure adbm event logs for category mts
rx	(Optional) Configure adbm event logs for mts Rx frames
brief	(Optional) Configure brief adbm event logs for mts Rx
detail	(Optional) Configure detail adbm event logs for mts Rx
tx	(Optional) Configure adbm event logs for mts Tx frames
brief1	(Optional) Configure brief adbm event logs for mts Tx
detail1	(Optional) Configure detail adbm event logs for mts Tx

Command Mode

- /exec

event-history adbm category mts

```
event-history adbm no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
adbm	Configure adbm event logs
no	Disable adbm event logs for category
category	Configure adbm event logs for category
mts	Configure adbm event logs for category mts
rx	(Optional) Configure adbm event logs for mts Rx frames
brief	(Optional) Configure brief adbm event logs for mts Rx
detail	(Optional) Configure detail adbm event logs for mts Rx
tx	(Optional) Configure adbm event logs for mts Tx frames
brief1	(Optional) Configure brief adbm event logs for mts Tx
detail1	(Optional) Configure detail adbm event logs for mts Tx

Command Mode

- /exec

event-history callhome

```
event-history callhome { mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] | no mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] }
```

Syntax Description

event-history	switch wide event history configuration
callhome	Configure Callhome event logs
mts	Configure callhome event logs for MTS
rx	(Optional) Configure callhome event logs for MTS Rx frames
brief	(Optional) Configure brief callhome event logs for MTS Rx
detail	(Optional) Configure detail callhome event logs for MTS Rx
tx	(Optional) Configure callhome event logs for MTS Tx frames
brief1	(Optional) Configure brief callhome event logs for MTS Tx
detail1	(Optional) Configure detail callhome event logs for MTS Tx
no	Disable callhome event logs for MTS
mts	Configure callhome event logs for MTS
rx	(Optional) Configure callhome event logs for MTS Rx frames
brief1	(Optional) Configure brief callhome event logs for MTS Rx
detail1	(Optional) Configure detail callhome event logs for MTS Rx
tx	(Optional) Configure callhome event logs for MTS Tx frames
brief2	(Optional) Configure brief callhome event logs for MTS Tx
detail2	(Optional) Configure detail callhome event logs for MTS Tx

Command Mode

- /exec

event-history capability

```
event-history capability { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] | no
category { all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] }
```

Syntax Description

event-history	switch wide event history configuration
capability	Configure capability event logs
category	Configure capability event logs for category
all	Configure capability event logs for category all events
mts	Configure capability event logs for category mts
rx	(Optional) Configure capability event logs for mts Rx frames
brief	(Optional) Configure brief capability event logs for mts Rx
detail	(Optional) Configure detail capability event logs for mts Rx
tx	(Optional) Configure capability event logs for mts Tx frames
brief1	(Optional) Configure brief capability event logs for mts Tx
detail1	(Optional) Configure detail capability event logs for mts Tx
no	Disable capability event logs for category
category	Configure capability event logs for category
all	Configure capability event logs for category all events
mts	Configure capability event logs for category mts
rx	(Optional) Configure capability event logs for mts Rx frames
brief1	(Optional) Configure brief capability event logs for mts Rx
detail1	(Optional) Configure detail capability event logs for mts Rx
tx	(Optional) Configure capability event logs for mts Tx frames
brief2	(Optional) Configure brief capability event logs for mts Tx
detail2	(Optional) Configure detail capability event logs for mts Tx

Command Mode

- /exec

event-history cli

[no] event-history cli [size { <size_in_text> | <bytes> | disable }]

Syntax Description

no	(Optional) Negate a command or set its defaults
event-history	Configure event-history details
cli	CLI event history buffer
size	(Optional) Set the buffer size
disable	(Optional) Disable the buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>bytes</i>	(Optional) Buffer size in bytes

Command Mode

- /exec/configure/router-bgp

event-history copp category all

event-history copp category all

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
category	Configure copp event logs for category
all	Configure copp event logs for category all events

Command Mode

- /exec

event-history copp category all

event-history copp no category all

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
no	Disable copp event logs for category
category	Configure copp event logs for category
all	Configure copp event logs for category all events

Command Mode

- /exec

event-history copp category fc2

```
event-history copp category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
category	Configure copp event logs for category
fc2	Configure copp event logs for category FC2
rx	(Optional) Configure copp event logs for FC2 Rx frames
brief	(Optional) Configure brief copp event logs for FC2 Rx
detail	(Optional) Configure detail copp event logs for FC2 Rx
tx	(Optional) Configure copp event logs for FC2 Tx frames
brief1	(Optional) Configure brief copp event logs for FC2 Tx
detail1	(Optional) Configure detail copp event logs for FC2 Tx

Command Mode

- /exec

event-history copp category fc2

```
event-history copp no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
no	Disable copp event logs for category
category	Configure copp event logs for category
fc2	Configure copp event logs for category FC2
rx	(Optional) Configure copp event logs for FC2 Rx frames
brief	(Optional) Configure brief copp event logs for FC2 Rx
detail	(Optional) Configure detail copp event logs for FC2 Rx
tx	(Optional) Configure copp event logs for FC2 Tx frames
brief1	(Optional) Configure brief copp event logs for FC2 Tx
detail1	(Optional) Configure detail copp event logs for FC2 Tx

Command Mode

- /exec

event-history copp category mts

```
event-history copp category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
category	Configure copp event logs for category
mts	Configure copp event logs for category mts
rx	(Optional) Configure copp event logs for mts Rx frames
brief	(Optional) Configure brief copp event logs for mts Rx
detail	(Optional) Configure detail copp event logs for mts Rx
tx	(Optional) Configure copp event logs for mts Tx frames
brief1	(Optional) Configure brief copp event logs for mts Tx
detail1	(Optional) Configure detail copp event logs for mts Tx

Command Mode

- /exec

event-history copp category mts

```
event-history copp no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
copp	Configure copp event logs
no	Disable copp event logs for category
category	Configure copp event logs for category
mts	Configure copp event logs for category mts
rx	(Optional) Configure copp event logs for mts Rx frames
brief	(Optional) Configure brief copp event logs for mts Rx
detail	(Optional) Configure detail copp event logs for mts Rx
tx	(Optional) Configure copp event logs for mts Tx frames
brief1	(Optional) Configure brief copp event logs for mts Tx
detail1	(Optional) Configure detail copp event logs for mts Tx

Command Mode

- /exec

event-history dot1x

```
event-history dot1x { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
dot1x	Configure dot1x event logs
category	Configure dot1x event logs for category
all	Configure dot1x event logs for category all events
mts	Configure dot1x event logs for category mts
rx	(Optional) Configure dot1x event logs for mts Rx frames
brief	(Optional) Configure brief dot1x event logs for mts Rx
detail	(Optional) Configure detail dot1x event logs for mts Rx
tx	(Optional) Configure dot1x event logs for mts Tx frames
brief1	(Optional) Configure brief dot1x event logs for mts Tx
detail1	(Optional) Configure detail dot1x event logs for mts Tx
no	Disable dot1x event logs for category
category	Configure dot1x event logs for category
all	Configure dot1x event logs for category all events
mts	Configure dot1x event logs for category mts
rx	(Optional) Configure dot1x event logs for mts Rx frames
brief1	(Optional) Configure brief dot1x event logs for mts Rx
detail1	(Optional) Configure detail dot1x event logs for mts Rx
tx	(Optional) Configure dot1x event logs for mts Tx frames
brief2	(Optional) Configure brief dot1x event logs for mts Tx
detail2	(Optional) Configure detail dot1x event logs for mts Tx

Command Mode

- /exec

event-history drap category all

event-history drap no category all

Syntax Description

event-history	switch wide event history configuration
drap	Configure drap event logs
no	Disable drap event logs for category
category	Configure drap event logs for category
all	Configure drap event logs for category all events

Command Mode

- /exec

event-history drap category all

event-history drap category all

Syntax Description

event-history	switch wide event history configuration
drap	Configure drap event logs
category	Configure drap event logs for category
all	Configure drap event logs for category all events

Command Mode

- /exec

event-history drap category mts

event-history drap no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
drap	Configure drap event logs
no	Disable drap event logs for category
category	Configure drap event logs for category
mts	Configure drap event logs for category mts
rx	(Optional) Configure drap event logs for mts Rx frames
brief	(Optional) Configure brief drap event logs for mts Rx
detail	(Optional) Configure detail drap event logs for mts Rx
tx	(Optional) Configure drap event logs for mts Tx frames
brief1	(Optional) Configure brief drap event logs for mts Tx
detail1	(Optional) Configure detail drap event logs for mts Tx

Command Mode

- /exec

event-history drap category mts

```
event-history drap category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
drap	Configure drap event logs
category	Configure drap event logs for category
mts	Configure drap event logs for category mts
rx	(Optional) Configure drap event logs for mts Rx frames
brief	(Optional) Configure brief drap event logs for mts Rx
detail	(Optional) Configure detail drap event logs for mts Rx
tx	(Optional) Configure drap event logs for mts Tx frames
brief1	(Optional) Configure brief drap event logs for mts Tx
detail1	(Optional) Configure detail drap event logs for mts Tx

Command Mode

- /exec

event-history eltm category all

event-history eltm no category all

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
no	Disable eltm event logs for category
category	Configure eltm event logs for category
all	Configure eltm event logs for category all events

Command Mode

- /exec

event-history eltm category all

event-history eltm category all

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
category	Configure eltm event logs for category
all	Configure eltm event logs for category all events

Command Mode

- /exec

event-history eltm category fc2

event-history eltm no category fc2 [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
no	Disable eltm event logs for category
category	Configure eltm event logs for category
fc2	Configure eltm event logs for category FC2
rx	(Optional) Configure eltm event logs for FC2 Rx frames
brief	(Optional) Configure brief eltm event logs for FC2 Rx
detail	(Optional) Configure detail eltm event logs for FC2 Rx
tx	(Optional) Configure eltm event logs for FC2 Tx frames
brief	(Optional) Configure brief eltm event logs for FC2 Tx
detail	(Optional) Configure detail eltm event logs for FC2 Tx

Command Mode

- /exec

event-history eltm category fc2

```
event-history eltm category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
category	Configure eltm event logs for category
fc2	Configure eltm event logs for category FC2
rx	(Optional) Configure eltm event logs for FC2 Rx frames
brief	(Optional) Configure brief eltm event logs for FC2 Rx
detail	(Optional) Configure detail eltm event logs for FC2 Rx
tx	(Optional) Configure eltm event logs for FC2 Tx frames
brief	(Optional) Configure brief eltm event logs for FC2 Tx
detail	(Optional) Configure detail eltm event logs for FC2 Tx

Command Mode

- /exec

event-history eltm category mts

event-history eltm category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
category	Configure eltm event logs for category
mts	Configure eltm event logs for category mts
rx	(Optional) Configure eltm event logs for mts Rx frames
brief	(Optional) Configure brief eltm event logs for mts Rx
detail	(Optional) Configure detail eltm event logs for mts Rx
tx	(Optional) Configure eltm event logs for mts Tx frames
brief	(Optional) Configure brief eltm event logs for mts Tx
detail	(Optional) Configure detail eltm event logs for mts Tx

Command Mode

- /exec

event-history eltm category mts

event-history eltm no category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
eltm	Configure eltm event logs
no	Disable eltm event logs for category
category	Configure eltm event logs for category
mts	Configure eltm event logs for category mts
rx	(Optional) Configure eltm event logs for mts Rx frames
brief	(Optional) Configure brief eltm event logs for mts Rx
detail	(Optional) Configure detail eltm event logs for mts Rx
tx	(Optional) Configure eltm event logs for mts Tx frames
brief	(Optional) Configure brief eltm event logs for mts Tx
detail	(Optional) Configure detail eltm event logs for mts Tx

Command Mode

- /exec

event-history epp category all

event-history epp category all

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
category	Configure EPP event logs for category
all	Configure EPP event logs for category all events

Command Mode

- /exec

event-history epp category all

event-history epp no category all

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
no	Disable EPP event logs for category
category	Configure EPP event logs for category
all	Configure EPP event logs for category all events

Command Mode

- /exec

event-history epp category fc2

```
event-history epp category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
category	Configure EPP event logs for category
fc2	Configure EPP event logs for category FC2
rx	(Optional) Configure EPP event logs for FC2 Rx frames
brief	(Optional) Configure brief EPP event logs for FC2 Rx
detail	(Optional) Configure detail EPP event logs for FC2 Rx
tx	(Optional) Configure EPP event logs for FC2 Tx frames
brief1	(Optional) Configure brief EPP event logs for FC2 Tx
detail1	(Optional) Configure detail EPP event logs for FC2 Tx

Command Mode

- /exec

event-history epp category fc2

```
event-history epp no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
no	Disable EPP event logs for category
category	Configure EPP event logs for category
fc2	Configure EPP event logs for category FC2
rx	(Optional) Configure EPP event logs for FC2 Rx frames
brief	(Optional) Configure brief EPP event logs for FC2 Rx
detail	(Optional) Configure detail EPP event logs for FC2 Rx
tx	(Optional) Configure EPP event logs for FC2 Tx frames
brief1	(Optional) Configure brief EPP event logs for FC2 Tx
detail1	(Optional) Configure detail EPP event logs for FC2 Tx

Command Mode

- /exec

event-history epp category mts

```
event-history epp category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
category	Configure EPP event logs for category
mts	Configure EPP event logs for category mts
rx	(Optional) Configure EPP event logs for mts Rx frames
brief	(Optional) Configure brief EPP event logs for mts Rx
detail	(Optional) Configure detail EPP event logs for mts Rx
tx	(Optional) Configure EPP event logs for mts Tx frames
brief1	(Optional) Configure brief EPP event logs for mts Tx
detail1	(Optional) Configure detail EPP event logs for mts Tx

Command Mode

- /exec

event-history epp category mts

```
event-history epp no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
epp	Configure EPP event logs
no	Disable EPP event logs for category
category	Configure EPP event logs for category
mts	Configure EPP event logs for category mts
rx	(Optional) Configure EPP event logs for mts Rx frames
brief	(Optional) Configure brief EPP event logs for mts Rx
detail	(Optional) Configure detail EPP event logs for mts Rx
tx	(Optional) Configure EPP event logs for mts Tx frames
brief1	(Optional) Configure brief EPP event logs for mts Tx
detail1	(Optional) Configure detail EPP event logs for mts Tx

Command Mode

- /exec

event-history errors

[no] event-history errors [size { <size_in_text> | <bytes> | disable }]

Syntax Description

no	(Optional) Negate a command or set its defaults
event-history	Configure event-history details
errors	Errors history buffer
size	(Optional) Set the buffer size
disable	(Optional) Disable the buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>bytes</i>	(Optional) Buffer size in bytes

Command Mode

- /exec/configure/router-bgp

event-history ethpm

```
event-history ethpm { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] } | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
ethpm	Configure ethpm event logs
category	Configure ethpm event logs for category
all	Configure ethpm event logs for category all events
mts	Configure ethpm event logs for category mts
rx	(Optional) Configure ethpm event logs for mts Rx frames
brief	(Optional) Configure brief ethpm event logs for mts Rx
detail	(Optional) Configure detail ethpm event logs for mts Rx
tx	(Optional) Configure ethpm event logs for mts Tx frames
brief1	(Optional) Configure brief ethpm event logs for mts Tx
detail1	(Optional) Configure detail ethpm event logs for mts Tx
no	Disable ethpm event logs for category
category	Configure ethpm event logs for category
all	Configure ethpm event logs for category all events
mts	Configure ethpm event logs for category mts
rx	(Optional) Configure ethpm event logs for mts Rx frames
brief1	(Optional) Configure brief ethpm event logs for mts Rx
detail1	(Optional) Configure detail ethpm event logs for mts Rx
tx	(Optional) Configure ethpm event logs for mts Tx frames
brief2	(Optional) Configure brief ethpm event logs for mts Tx
detail2	(Optional) Configure detail ethpm event logs for mts Tx

Command Mode

- /exec

event-history events

[no] event-history events [size { <size_in_text> | <bytes> | disable }]

Syntax Description

no	(Optional) Negate a command or set its defaults
event-history	Configure event-history details
events	Events history buffer
size	(Optional) Set the buffer size
disable	(Optional) Disable the buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>bytes</i>	(Optional) Buffer size in bytes

Command Mode

- /exec/configure/router-bgp

event-history exceptionlog

```
event-history exceptionlog { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] | no
category { all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
exceptionlog	Configure expl manager event logs
category	Configure exceptionlog manager event logs for category
all	Configure explog eventlogs for category all events
mts	Configure exceptionlog manager event logs for category mts
rx	(Optional) Configure exceptionlog manager event logs for mts Rx frames
brief	(Optional) Configure brief exceptionlog manager event logs for mts Rx
detail	(Optional) Configure detail exceptionlog manager event logs for mts Rx
tx	(Optional) Configure exceptionlog manager event logs for mts Tx frames
brief1	(Optional) Configure brief exceptionlog manager event logs for mts Tx
detail1	(Optional) Configure detail exceptionlog manager event logs for mts Tx
no	Disable exceptionlog manager event logs for category
category	Configure exceptionlog manager event logs for category
all	Configure explog eventlogs for category all events
mts	Configure exceptionlog manager event logs for category mts
rx	(Optional) Configure exceptionlog manager event logs for mts Rx frames
brief1	(Optional) Configure brief exceptionlog manager event logs for mts Rx
detail1	(Optional) Configure detail exceptionlog manager event logs for mts Rx
tx	(Optional) Configure exceptionlog manager event logs for mts Tx frames
brief2	(Optional) Configure brief exceptionlog manager event logs for mts Tx
detail2	(Optional) Configure detail exceptionlog manager event logs for mts Tx

Command Mode

- /exec

event-history fcoe_mgr category all

event-history fcoe_mgr category all

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
category	Configure fcoe_mgr event logs for category
all	Configure fcoe_mgr event logs for category all events

Command Mode

- /exec

event-history fcoe_mgr category all

event-history fcoe_mgr no category all

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
no	Disable fcoe_mgr event logs for category
category	Configure fcoe_mgr event logs for category
all	Configure fcoe_mgr event logs for category all events

Command Mode

- /exec

event-history fcoe_mgr category fc2

```
event-history fcoe_mgr no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
no	Disable fcoe_mgr event logs for category
category	Configure fcoe_mgr event logs for category
fc2	Configure fcoe_mgr event logs for category FC2
rx	(Optional) Configure fcoe_mgr event logs for FC2 Rx frames
brief	(Optional) Configure brief fcoe_mgr event logs for FC2 Rx
detail	(Optional) Configure detail fcoe_mgr event logs for FC2 Rx
tx	(Optional) Configure fcoe_mgr event logs for FC2 Tx frames
brief1	(Optional) Configure brief fcoe_mgr event logs for FC2 Tx
detail1	(Optional) Configure detail fcoe_mgr event logs for FC2 Tx

Command Mode

- /exec

event-history fcoe_mgr category fc2

```
event-history fcoe_mgr category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
category	Configure fcoe_mgr event logs for category
fc2	Configure fcoe_mgr event logs for category FC2
rx	(Optional) Configure fcoe_mgr event logs for FC2 Rx frames
brief	(Optional) Configure brief fcoe_mgr event logs for FC2 Rx
detail	(Optional) Configure detail fcoe_mgr event logs for FC2 Rx
tx	(Optional) Configure fcoe_mgr event logs for FC2 Tx frames
brief1	(Optional) Configure brief fcoe_mgr event logs for FC2 Tx
detail1	(Optional) Configure detail fcoe_mgr event logs for FC2 Tx

Command Mode

- /exec

event-history fcoe_mgr category mts

```
event-history fcoe_mgr no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
no	Disable fcoe_mgr event logs for category
category	Configure fcoe_mgr event logs for category
mts	Configure fcoe_mgr event logs for category mts
rx	(Optional) Configure fcoe_mgr event logs for mts Rx frames
brief	(Optional) Configure brief fcoe_mgr event logs for mts Rx
detail	(Optional) Configure detail fcoe_mgr event logs for mts Rx
tx	(Optional) Configure fcoe_mgr event logs for mts Tx frames
brief1	(Optional) Configure brief fcoe_mgr event logs for mts Tx
detail1	(Optional) Configure detail fcoe_mgr event logs for mts Tx

Command Mode

- /exec

event-history fcoe_mgr category mts

```
event-history fcoe_mgr category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
fcoe_mgr	Configure fcoe_mgr event logs
category	Configure fcoe_mgr event logs for category
mts	Configure fcoe_mgr event logs for category mts
rx	(Optional) Configure fcoe_mgr event logs for mts Rx frames
brief	(Optional) Configure brief fcoe_mgr event logs for mts Rx
detail	(Optional) Configure detail fcoe_mgr event logs for mts Rx
tx	(Optional) Configure fcoe_mgr event logs for mts Tx frames
brief1	(Optional) Configure brief fcoe_mgr event logs for mts Tx
detail1	(Optional) Configure detail fcoe_mgr event logs for mts Tx

Command Mode

- /exec

event-history hardware-telemetry

```
event-history hardware-telemetry { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] } | no category { all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
hardware-telemetry	Configure hardware-telemetry event logs
category	Configure hardware-telemetry event logs for category
all	Configure hardware-telemetry event logs for category all events
mts	Configure hardware-telemetry event logs for category mts
rx	(Optional) Configure hardware-telemetry event logs for mts Rx frames
brief	(Optional) Configure brief hardware-telemetry event logs for mts Rx
detail	(Optional) Configure detail hardware-telemetry event logs for mts Rx
tx	(Optional) Configure hardware-telemetry event logs for mts Tx frames
brief1	(Optional) Configure brief hardware-telemetry event logs for mts Tx
detail1	(Optional) Configure detail hardware-telemetry event logs for mts Tx
no	Disable hardware-telemetry event logs for category
category	Configure hw_telemetry event logs for category
all	Configure hardware-telemetry event logs for category all events
mts	Configure hardware-telemetry event logs for category mts
rx	(Optional) Configure hardware-telemetry event logs for mts Rx frames
brief1	(Optional) Configure brief hardware-telemetry event logs for mts Rx
detail1	(Optional) Configure detail hardware-telemetry event logs for mts Rx
tx	(Optional) Configure hardware-telemetry event logs for mts Tx frames
brief2	(Optional) Configure brief hardware-telemetry event logs for mts Tx
detail2	(Optional) Configure detail hardware-telemetry event logs for mts Tx

Command Mode

- /exec

event-history im category mts

event-history im no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
im	Configure im event logs
no	Disable im event logs for category
category	Configure im event logs for category
mts	Configure im event logs for category mts
rx	(Optional) Configure im event logs for mts Rx frames
brief	(Optional) Configure brief im event logs for mts Rx
detail	(Optional) Configure detail im event logs for mts Rx
tx	(Optional) Configure im event logs for mts Tx frames
brief1	(Optional) Configure brief im event logs for mts Tx
detail1	(Optional) Configure detail im event logs for mts Tx

Command Mode

- /exec

event-history imp category all

event-history imp category all

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
category	Configure imp event logs for category
all	Configure imp event logs for category all events

Command Mode

- /exec

event-history imp category all

event-history imp no category all

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
no	Disable imp event logs for category
category	Configure imp event logs for category
all	Configure imp event logs for category all events

Command Mode

- /exec

event-history imp category fc2

```
event-history imp category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
category	Configure imp event logs for category
fc2	Configure imp event logs for category FC2
rx	(Optional) Configure imp event logs for FC2 Rx frames
brief	(Optional) Configure brief imp event logs for FC2 Rx
detail	(Optional) Configure detail imp event logs for FC2 Rx
tx	(Optional) Configure imp event logs for FC2 Tx frames
brief1	(Optional) Configure brief imp event logs for FC2 Tx
detail1	(Optional) Configure detail imp event logs for FC2 Tx

Command Mode

- /exec

event-history imp category fc2

```
event-history imp no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
no	Disable imp event logs for category
category	Configure imp event logs for category
fc2	Configure imp event logs for category FC2
rx	(Optional) Configure imp event logs for FC2 Rx frames
brief	(Optional) Configure brief imp event logs for FC2 Rx
detail	(Optional) Configure detail imp event logs for FC2 Rx
tx	(Optional) Configure imp event logs for FC2 Tx frames
brief1	(Optional) Configure brief imp event logs for FC2 Tx
detail1	(Optional) Configure detail imp event logs for FC2 Tx

Command Mode

- /exec

event-history imp category mts

```
event-history imp category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
category	Configure imp event logs for category
mts	Configure imp event logs for category mts
rx	(Optional) Configure imp event logs for mts Rx frames
brief	(Optional) Configure brief imp event logs for mts Rx
detail	(Optional) Configure detail imp event logs for mts Rx
tx	(Optional) Configure imp event logs for mts Tx frames
brief1	(Optional) Configure brief imp event logs for mts Tx
detail1	(Optional) Configure detail imp event logs for mts Tx

Command Mode

- /exec

event-history imp category mts

event-history imp no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
imp	Configure imp event logs
no	Disable imp event logs for category
category	Configure imp event logs for category
mts	Configure imp event logs for category mts
rx	(Optional) Configure imp event logs for mts Rx frames
brief	(Optional) Configure brief imp event logs for mts Rx
detail	(Optional) Configure detail imp event logs for mts Rx
tx	(Optional) Configure imp event logs for mts Tx frames
brief1	(Optional) Configure brief imp event logs for mts Tx
detail1	(Optional) Configure detail imp event logs for mts Tx

Command Mode

- /exec

event-history keystore

```
event-history { keystore | sksd } { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
} | no category { all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] }
```

Syntax Description

event-history	switch wide event history configuration
keystore	Configure keystore event logs
sksd	Configure keystore/sksd event logs
category	Configure keystore event logs for category
all	Configure keystore event logs for category all events
mts	Configure keystore event logs for category mts
rx	(Optional) Configure keystore event logs for mts Rx frames
brief	(Optional) Configure brief keystore event logs for mts Rx
detail	(Optional) Configure detail keystore event logs for mts Rx
tx	(Optional) Configure keystore event logs for mts Tx frames
brief1	(Optional) Configure brief keystore event logs for mts Tx
detail1	(Optional) Configure detail keystore event logs for mts Tx
no	Disable keystore event logs for category
category	Configure keystore event logs for category
all	Configure keystore event logs for category all events
mts	Configure keystore event logs for category mts
rx	(Optional) Configure keystore event logs for mts Rx frames
brief1	(Optional) Configure brief keystore event logs for mts Rx
detail1	(Optional) Configure detail keystore event logs for mts Rx
tx	(Optional) Configure keystore event logs for mts Tx frames
brief2	(Optional) Configure brief keystore event logs for mts Tx
detail2	(Optional) Configure detail keystore event logs for mts Tx

Command Mode

- /exec

event-history lacp category all

event-history lacp category all

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
category	Configure lacp event logs for category
all	Configure lacp event logs for category all events

Command Mode

- /exec

event-history lacp category all

event-history lacp no category all

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
no	Disable lacp event logs for category
category	Configure lacp event logs for category
all	Configure lacp event logs for category all events

Command Mode

- /exec

event-history lacp category fc2

```
event-history lacp category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
category	Configure lacp event logs for category
fc2	Configure lacp event logs for category FC2
rx	(Optional) Configure lacp event logs for FC2 Rx frames
brief	(Optional) Configure brief lacp event logs for FC2 Rx
detail	(Optional) Configure detail lacp event logs for FC2 Rx
tx	(Optional) Configure lacp event logs for FC2 Tx frames
brief1	(Optional) Configure brief lacp event logs for FC2 Tx
detail1	(Optional) Configure detail lacp event logs for FC2 Tx

Command Mode

- /exec

event-history lacp category fc2

```
event-history lacp no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
no	Disable lacp event logs for category
category	Configure lacp event logs for category
fc2	Configure lacp event logs for category FC2
rx	(Optional) Configure lacp event logs for FC2 Rx frames
brief	(Optional) Configure brief lacp event logs for FC2 Rx
detail	(Optional) Configure detail lacp event logs for FC2 Rx
tx	(Optional) Configure lacp event logs for FC2 Tx frames
brief1	(Optional) Configure brief lacp event logs for FC2 Tx
detail1	(Optional) Configure detail lacp event logs for FC2 Tx

Command Mode

- /exec

event-history lacp category mts

event-history lacp no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
no	Disable lacp event logs for category
category	Configure lacp event logs for category
mts	Configure lacp event logs for category mts
rx	(Optional) Configure lacp event logs for mts Rx frames
brief	(Optional) Configure brief lacp event logs for mts Rx
detail	(Optional) Configure detail lacp event logs for mts Rx
tx	(Optional) Configure lacp event logs for mts Tx frames
brief1	(Optional) Configure brief lacp event logs for mts Tx
detail1	(Optional) Configure detail lacp event logs for mts Tx

Command Mode

- /exec

event-history lacp category mts

```
event-history lacp category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lacp	Configure lacp event logs
category	Configure lacp event logs for category
mts	Configure lacp event logs for category mts
rx	(Optional) Configure lacp event logs for mts Rx frames
brief	(Optional) Configure brief lacp event logs for mts Rx
detail	(Optional) Configure detail lacp event logs for mts Rx
tx	(Optional) Configure lacp event logs for mts Tx frames
brief1	(Optional) Configure brief lacp event logs for mts Tx
detail1	(Optional) Configure detail lacp event logs for mts Tx

Command Mode

- /exec

event-history lem-mgr category all

event-history lem-mgr no category all

Syntax Description

event-history	switch wide event history configuration
no	Disable lem-mgr event logs for category
category	Configure lem-mgr event logs for category
all	Configure lem-mgr event logs for category all events

Command Mode

- /exec

event-history lem-mgr category all

event-history lem-mgr category all

Syntax Description

event-history	switch wide event history configuration
category	Configure lem-mgr event logs for category
all	Configure lem-mgr event logs for category all events

Command Mode

- /exec

event-history lem-mgr category fc2

```
event-history lem-mgr no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
no	Disable lem-mgr event logs for category
category	Configure lem-mgr event logs for category
fc2	Configure lem-mgr event logs for category FC2
rx	(Optional) Configure lem-mgr event logs for FC2 Rx frames
brief	(Optional) Configure brief lem-mgr event logs for FC2 Rx
detail	(Optional) Configure detail lem-mgr event logs for FC2 Rx
tx	(Optional) Configure lem-mgr event logs for FC2 Tx frames
brief	(Optional) Configure brief lem-mgr event logs for FC2 Tx
detail	(Optional) Configure detail lem-mgr event logs for FC2 Tx

Command Mode

- /exec

event-history lem-mgr category fc2

```
event-history lem-mgr category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
category	Configure lem-mgr event logs for category
fc2	Configure lem-mgr event logs for category FC2
rx	(Optional) Configure lem-mgr event logs for FC2 Rx frames
brief	(Optional) Configure brief lem-mgr event logs for FC2 Rx
detail	(Optional) Configure detail lem-mgr event logs for FC2 Rx
tx	(Optional) Configure lem-mgr event logs for FC2 Tx frames
brief	(Optional) Configure brief lem-mgr event logs for FC2 Tx
detail	(Optional) Configure detail lem-mgr event logs for FC2 Tx

Command Mode

- /exec

event-history lem-mgr category mts

```
event-history lem-mgr category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
category	Configure lem-mgr event logs for category
mts	Configure lem-mgr event logs for category mts
rx	(Optional) Configure lem-mgr event logs for mts Rx frames
brief	(Optional) Configure brief lem-mgr event logs for mts Rx
detail	(Optional) Configure detail lem-mgr event logs for mts Rx
tx	(Optional) Configure lem-mgr event logs for mts Tx frames
brief	(Optional) Configure brief lem-mgr event logs for mts Tx
detail	(Optional) Configure detail lem-mgr event logs for mts Tx

Command Mode

- /exec

event-history lem-mgr category mts

```
event-history lem-mgr no category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
no	Disable lem-mgr event logs for category
category	Configure lem-mgr event logs for category
mts	Configure lem-mgr event logs for category mts
rx	(Optional) Configure lem-mgr event logs for mts Rx frames
brief	(Optional) Configure brief lem-mgr event logs for mts Rx
detail	(Optional) Configure detail lem-mgr event logs for mts Rx
tx	(Optional) Configure lem-mgr event logs for mts Tx frames
brief	(Optional) Configure brief lem-mgr event logs for mts Tx
detail	(Optional) Configure detail lem-mgr event logs for mts Tx

Command Mode

- /exec

event-history license

```
event-history license { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] } | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
license	Configure license manager event logs
category	Configure license manager event logs for category
all	Configure license manager event logs for category all events
mts	Configure license manager event logs for category mts
rx	(Optional) Configure license manager event logs for mts Rx frames
brief	(Optional) Configure brief license manager event logs for mts Rx
detail	(Optional) Configure detail license manager event logs for mts Rx
tx	(Optional) Configure license manager event logs for mts Tx frames
brief1	(Optional) Configure brief license manager event logs for mts Tx
detail1	(Optional) Configure detail license manager event logs for mts Tx
no	Disable license manager event logs for category
category	Configure license manager event logs for category
all	Configure license manager event logs for category all events
mts	Configure license manager event logs for category mts
rx	(Optional) Configure license manager event logs for mts Rx frames
brief1	(Optional) Configure brief license manager event logs for mts Rx
detail1	(Optional) Configure detail license manager event logs for mts Rx
tx	(Optional) Configure license manager event logs for mts Tx frames
brief2	(Optional) Configure brief license manager event logs for mts Tx
detail2	(Optional) Configure detail license manager event logs for mts Tx

Command Mode

- /exec

event-history lldp category all

event-history lldp category all

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
category	Configure lldp event logs for category
all	Configure lldp event logs for category all events

Command Mode

- /exec

event-history lldp category all

event-history lldp no category all

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
no	Disable lldp event logs for category
category	Configure lldp event logs for category
all	Configure lldp event logs for category all events

Command Mode

- /exec

event-history lldp category fc2

```
event-history lldp no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
no	Disable lldp event logs for category
category	Configure lldp event logs for category
fc2	Configure lldp event logs for category FC2
rx	(Optional) Configure lldp event logs for FC2 Rx frames
brief	(Optional) Configure brief lldp event logs for FC2 Rx
detail	(Optional) Configure detail lldp event logs for FC2 Rx
tx	(Optional) Configure lldp event logs for FC2 Tx frames
brief1	(Optional) Configure brief lldp event logs for FC2 Tx
detail1	(Optional) Configure detail lldp event logs for FC2 Tx

Command Mode

- /exec

event-history lldp category fc2

```
event-history lldp category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
category	Configure lldp event logs for category
fc2	Configure lldp event logs for category FC2
rx	(Optional) Configure lldp event logs for FC2 Rx frames
brief	(Optional) Configure brief lldp event logs for FC2 Rx
detail	(Optional) Configure detail lldp event logs for FC2 Rx
tx	(Optional) Configure lldp event logs for FC2 Tx frames
brief1	(Optional) Configure brief lldp event logs for FC2 Tx
detail1	(Optional) Configure detail lldp event logs for FC2 Tx

Command Mode

- /exec

event-history lldp category mts

```
event-history lldp category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
category	Configure lldp event logs for category
mts	Configure lldp event logs for category mts
rx	(Optional) Configure lldp event logs for mts Rx frames
brief	(Optional) Configure brief lldp event logs for mts Rx
detail	(Optional) Configure detail lldp event logs for mts Rx
tx	(Optional) Configure lldp event logs for mts Tx frames
brief1	(Optional) Configure brief lldp event logs for mts Tx
detail1	(Optional) Configure detail lldp event logs for mts Tx

Command Mode

- /exec

event-history lldp category mts

event-history lldp no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
lldp	Configure lldp event logs
no	Disable lldp event logs for category
category	Configure lldp event logs for category
mts	Configure lldp event logs for category mts
rx	(Optional) Configure lldp event logs for mts Rx frames
brief	(Optional) Configure brief lldp event logs for mts Rx
detail	(Optional) Configure detail lldp event logs for mts Rx
tx	(Optional) Configure lldp event logs for mts Tx frames
brief1	(Optional) Configure brief lldp event logs for mts Tx
detail1	(Optional) Configure detail lldp event logs for mts Tx

Command Mode

- /exec

event-history m2rib category all

event-history m2rib category all

Syntax Description

event-history	switch wide event history configuration
m2rib	Configure m2rib event logs
category	Configure m2rib event logs for category
all	Configure m2rib event logs for category all events

Command Mode

- /exec

event-history mfdm category all

event-history mfdm category all

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
category	Configure mfdm event logs for category
all	Configure mfdm event logs for category all events

Command Mode

- /exec

event-history mfdm category all

event-history mfdm no category all

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
no	Disable mfdm event logs for category
category	Configure mfdm event logs for category
all	Configure mfdm event logs for category all events

Command Mode

- /exec

event-history mfdm category fc2

```
event-history mfdm no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
no	Disable mfdm event logs for category
category	Configure mfdm event logs for category
fc2	Configure mfdm event logs for category FC2
rx	(Optional) Configure mfdm event logs for FC2 Rx frames
brief	(Optional) Configure brief mfdm event logs for FC2 Rx
detail	(Optional) Configure detail mfdm event logs for FC2 Rx
tx	(Optional) Configure mfdm event logs for FC2 Tx frames
brief	(Optional) Configure brief mfdm event logs for FC2 Tx
detail	(Optional) Configure detail mfdm event logs for FC2 Tx

Command Mode

- /exec

event-history mfdm category fc2

```
event-history mfdm category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
category	Configure mfdm event logs for category
fc2	Configure mfdm event logs for category FC2
rx	(Optional) Configure mfdm event logs for FC2 Rx frames
brief	(Optional) Configure brief mfdm event logs for FC2 Rx
detail	(Optional) Configure detail mfdm event logs for FC2 Rx
tx	(Optional) Configure mfdm event logs for FC2 Tx frames
brief	(Optional) Configure brief mfdm event logs for FC2 Tx
detail	(Optional) Configure detail mfdm event logs for FC2 Tx

Command Mode

- /exec

event-history mfdm category mts

event-history mfdm no category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
no	Disable mfdm event logs for category
category	Configure mfdm event logs for category
mts	Configure mfdm event logs for category mts
rx	(Optional) Configure mfdm event logs for mts Rx frames
brief	(Optional) Configure brief mfdm event logs for mts Rx
detail	(Optional) Configure detail mfdm event logs for mts Rx
tx	(Optional) Configure mfdm event logs for mts Tx frames
brief	(Optional) Configure brief mfdm event logs for mts Tx
detail	(Optional) Configure detail mfdm event logs for mts Tx

Command Mode

- /exec

event-history mfdm category mts

```
event-history mfdm category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
mfdm	Configure mfdm event logs
category	Configure mfdm event logs for category
mts	Configure mfdm event logs for category mts
rx	(Optional) Configure mfdm event logs for mts Rx frames
brief	(Optional) Configure brief mfdm event logs for mts Rx
detail	(Optional) Configure detail mfdm event logs for mts Rx
tx	(Optional) Configure mfdm event logs for mts Tx frames
brief	(Optional) Configure brief mfdm event logs for mts Tx
detail	(Optional) Configure detail mfdm event logs for mts Tx

Command Mode

- /exec

event-history mmode category all

```
event-history mmode [ no ] category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] }
```

Syntax Description

event-history	switch wide event history configuration
mmode	Configure mmode event logs
no	(Optional) Disable mmode event logs for category
category	Configure mmode event logs for category
all	Configure mmode event logs for category all events
mts	Configure mmode event logs for category mts
rx	(Optional) Configure mmode event logs for mts Rx frames
brief	(Optional) Configure brief mmode event logs for mts Rx
detail	(Optional) Configure detail mmode event logs for mts Rx
tx	(Optional) Configure mmode event logs for mts Tx frames
brief1	(Optional) Configure brief mmode event logs for mts Tx
detail1	(Optional) Configure detail mmode event logs for mts Tx

Command Mode

- /exec

event-history module

```
event-history module { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] } | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
module	Configure module event logs
category	Configure module event logs for category
all	Configure module event logs for category all events
mts	Configure module event logs for category mts
rx	(Optional) Configure module event logs for mts Rx frames
brief	(Optional) Configure brief module event logs for mts Rx
detail	(Optional) Configure detail module event logs for mts Rx
tx	(Optional) Configure module event logs for mts Tx frames
brief1	(Optional) Configure brief module event logs for mts Tx
detail1	(Optional) Configure detail module event logs for mts Tx
no	Disable module event logs for category
category	Configure module event logs for category
all	Configure module event logs for category all events
mts	Configure module event logs for category mts
rx	(Optional) Configure module event logs for mts Rx frames
brief1	(Optional) Configure brief module event logs for mts Rx
detail1	(Optional) Configure detail module event logs for mts Rx
tx	(Optional) Configure module event logs for mts Tx frames
brief2	(Optional) Configure brief module event logs for mts Tx
detail2	(Optional) Configure detail module event logs for mts Tx

Command Mode

- /exec

event-history npv category all

event-history npv no category all

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
no	Disable NPV event logs for category
category	Configure NPV event logs for category
all	Configure NPV event logs for category all events

Command Mode

- /exec

event-history npv category all

event-history npv category all

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
category	Configure NPV event logs for category
all	Configure NPV event logs for category all events

Command Mode

- /exec

event-history npv category fc2

```
event-history npv no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
no	Disable NPV event logs for category
category	Configure NPV event logs for category
fc2	Configure NPV event logs for category FC2
rx	(Optional) Configure NPV event logs for FC2 Rx frames
brief	(Optional) Configure brief NPV event logs for FC2 Rx
detail	(Optional) Configure detail NPV event logs for FC2 Rx
tx	(Optional) Configure NPV event logs for FC2 Tx frames
brief	(Optional) Configure brief NPV event logs for FC2 Tx
detail	(Optional) Configure detail NPV event logs for FC2 Tx

Command Mode

- /exec

event-history npv category fc2

```
event-history npv category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
category	Configure NPV event logs for category
fc2	Configure NPV event logs for category FC2
rx	(Optional) Configure NPV event logs for FC2 Rx frames
brief	(Optional) Configure brief NPV event logs for FC2 Rx
detail	(Optional) Configure detail NPV event logs for FC2 Rx
tx	(Optional) Configure NPV event logs for FC2 Tx frames
brief	(Optional) Configure brief NPV event logs for FC2 Tx
detail	(Optional) Configure detail NPV event logs for FC2 Tx

Command Mode

- /exec

event-history npv category mts

event-history npv category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
category	Configure NPV event logs for category
mts	Configure NPV event logs for category mts
rx	(Optional) Configure NPV event logs for mts Rx frames
brief	(Optional) Configure brief NPV event logs for mts Rx
detail	(Optional) Configure detail NPV event logs for mts Rx
tx	(Optional) Configure NPV event logs for mts Tx frames
brief	(Optional) Configure brief NPV event logs for mts Tx
detail	(Optional) Configure detail NPV event logs for mts Tx

Command Mode

- /exec

event-history npv category mts

event-history npv no category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
npv	Configure NPV event logs
no	Disable NPV event logs for category
category	Configure NPV event logs for category
mts	Configure NPV event logs for category mts
rx	(Optional) Configure NPV event logs for mts Rx frames
brief	(Optional) Configure brief NPV event logs for mts Rx
detail	(Optional) Configure detail NPV event logs for mts Rx
tx	(Optional) Configure NPV event logs for mts Tx frames
brief	(Optional) Configure brief NPV event logs for mts Tx
detail	(Optional) Configure detail NPV event logs for mts Tx

Command Mode

- /exec

event-history pfstat category all

event-history pfstat category all

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
category	Configure pfstat event logs for category
all	Configure pfstat event logs for category all events

Command Mode

- /exec

event-history pfstat category all

event-history pfstat no category all

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
no	Disable pfstat event logs for category
category	Configure pfstat event logs for category
all	Configure pfstat event logs for category all events

Command Mode

- /exec

event-history pfstat category fc2

```
event-history pfstat no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
no	Disable pfstat event logs for category
category	Configure pfstat event logs for category
fc2	Configure pfstat event logs for category FC2
rx	(Optional) Configure pfstat event logs for FC2 Rx frames
brief	(Optional) Configure brief pfstat event logs for FC2 Rx
detail	(Optional) Configure detail pfstat event logs for FC2 Rx
tx	(Optional) Configure pfstat event logs for FC2 Tx frames
brief	(Optional) Configure brief pfstat event logs for FC2 Tx
detail	(Optional) Configure detail pfstat event logs for FC2 Tx

Command Mode

- /exec

event-history pfstat category fc2

```
event-history pfstat category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
category	Configure pfstat event logs for category
fc2	Configure pfstat event logs for category FC2
rx	(Optional) Configure pfstat event logs for FC2 Rx frames
brief	(Optional) Configure brief pfstat event logs for FC2 Rx
detail	(Optional) Configure detail pfstat event logs for FC2 Rx
tx	(Optional) Configure pfstat event logs for FC2 Tx frames
brief	(Optional) Configure brief pfstat event logs for FC2 Tx
detail	(Optional) Configure detail pfstat event logs for FC2 Tx

Command Mode

- /exec

event-history pfstat category mts

```
event-history pfstat category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
category	Configure pfstat event logs for category
mts	Configure pfstat event logs for category mts
rx	(Optional) Configure pfstat event logs for mts Rx frames
brief	(Optional) Configure brief pfstat event logs for mts Rx
detail	(Optional) Configure detail pfstat event logs for mts Rx
tx	(Optional) Configure pfstat event logs for mts Tx frames
brief	(Optional) Configure brief pfstat event logs for mts Tx
detail	(Optional) Configure detail pfstat event logs for mts Tx

Command Mode

- /exec

event-history pfstat category mts

```
event-history pfstat no category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pfstat	Configure pfstat event logs
no	Disable pfstat event logs for category
category	Configure pfstat event logs for category
mts	Configure pfstat event logs for category mts
rx	(Optional) Configure pfstat event logs for mts Rx frames
brief	(Optional) Configure brief pfstat event logs for mts Rx
detail	(Optional) Configure detail pfstat event logs for mts Rx
tx	(Optional) Configure pfstat event logs for mts Tx frames
brief	(Optional) Configure brief pfstat event logs for mts Tx
detail	(Optional) Configure detail pfstat event logs for mts Tx

Command Mode

- /exec

event-history platform buffer-size

event-history platform buffer-size <i0>

Syntax Description

event-history	switch wide event history configuration
platform	Configure platform event logs
buffer-size	Configure platform event logs buffer size
<i>i0</i>	please enter buffer size

Command Mode

- /exec

event-history platform category all

```
event-history platform category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] ] }
```

Syntax Description

event-history	switch wide event history configuration
platform	Configure platform event logs
category	Configure platform event logs for category
all	Configure platform event logs for category all events
mts	Configure platform event logs for category mts
rx	(Optional) Configure platform event logs for mts Rx frames
brief	(Optional) Configure brief platform event logs for mts Rx
detail	(Optional) Configure detail platform event logs for mts Rx
tx	(Optional) Configure platform event logs for mts Tx frames
brief1	(Optional) Configure brief platform event logs for mts Tx
detail1	(Optional) Configure detail platform event logs for mts Tx

Command Mode

- /exec

event-history platform category all

```
event-history platform no category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] }
```

Syntax Description

event-history	switch wide event history configuration
platform	Configure platform event logs
no	Disable platform event logs for category
category	Configure platform event logs for category
all	Configure platform event logs for category all events
mts	Configure platform event logs for category mts
rx	(Optional) Configure platform event logs for mts Rx frames
brief	(Optional) Configure brief platform event logs for mts Rx
detail	(Optional) Configure detail platform event logs for mts Rx
tx	(Optional) Configure platform event logs for mts Tx frames
brief1	(Optional) Configure brief platform event logs for mts Tx
detail1	(Optional) Configure detail platform event logs for mts Tx

Command Mode

- /exec

event-history pltfm_config category all

event-history pltfm_config category all

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
category	Configure pltfm_config event logs for category
all	Configure pltfm_config event logs for category all events

Command Mode

- /exec

event-history pltfm_config category all

event-history pltfm_config no category all

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
no	Disable pltfm_config event logs for category
category	Configure pltfm_config event logs for category
all	Configure pltfm_config event logs for category all events

Command Mode

- /exec

event-history pltfm_config category fc2

```
event-history pltfm_config category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
category	Configure pltfm_config event logs for category
fc2	Configure pltfm_config event logs for category FC2
rx	(Optional) Configure pltfm_config event logs for FC2 Rx frames
brief	(Optional) Configure brief pltfm_config event logs for FC2 Rx
detail	(Optional) Configure detail pltfm_config event logs for FC2 Rx
tx	(Optional) Configure pltfm_config event logs for FC2 Tx frames
brief1	(Optional) Configure brief pltfm_config event logs for FC2 Tx
detail1	(Optional) Configure detail pltfm_config event logs for FC2 Tx

Command Mode

- /exec

event-history pltfm_config category fc2

```
event-history pltfm_config no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
no	Disable pltfm_config event logs for category
category	Configure pltfm_config event logs for category
fc2	Configure pltfm_config event logs for category FC2
rx	(Optional) Configure pltfm_config event logs for FC2 Rx frames
brief	(Optional) Configure brief pltfm_config event logs for FC2 Rx
detail	(Optional) Configure detail pltfm_config event logs for FC2 Rx
tx	(Optional) Configure pltfm_config event logs for FC2 Tx frames
brief1	(Optional) Configure brief pltfm_config event logs for FC2 Tx
detail1	(Optional) Configure detail pltfm_config event logs for FC2 Tx

Command Mode

- /exec

event-history pltfm_config category mts

```
event-history pltfm_config category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
category	Configure pltfm_config event logs for category
mts	Configure pltfm_config event logs for category mts
rx	(Optional) Configure pltfm_config event logs for mts Rx frames
brief	(Optional) Configure brief pltfm_config event logs for mts Rx
detail	(Optional) Configure detail pltfm_config event logs for mts Rx
tx	(Optional) Configure pltfm_config event logs for mts Tx frames
brief1	(Optional) Configure brief pltfm_config event logs for mts Tx
detail1	(Optional) Configure detail pltfm_config event logs for mts Tx

Command Mode

- /exec

event-history pltfm_config category mts

```
event-history pltfm_config no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
pltfm_config	Configure pltfm_config event logs
no	Disable pltfm_config event logs for category
category	Configure pltfm_config event logs for category
mts	Configure pltfm_config event logs for category mts
rx	(Optional) Configure pltfm_config event logs for mts Rx frames
brief	(Optional) Configure brief pltfm_config event logs for mts Rx
detail	(Optional) Configure detail pltfm_config event logs for mts Rx
tx	(Optional) Configure pltfm_config event logs for mts Tx frames
brief1	(Optional) Configure brief pltfm_config event logs for mts Tx
detail1	(Optional) Configure detail pltfm_config event logs for mts Tx

Command Mode

- /exec

event-history plugin

```
event-history plugin { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] ] } | no category
{ all | mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] ] } }
```

Syntax Description

event-history	switch wide event history configuration
plugin	Configure plugin event logs
category	Configure plugin event logs for category
all	Configure plugin event logs for category all events
mts	Configure plugin event logs for category mts
rx	(Optional) Configure plugin event logs for mts Rx frames
brief	(Optional) Configure brief plugin event logs for mts Rx
detail	(Optional) Configure detail plugin event logs for mts Rx
tx	(Optional) Configure plugin event logs for mts Tx frames
brief	(Optional) Configure brief plugin event logs for mts Tx
detail	(Optional) Configure detail plugin event logs for mts Tx
no	Disable plugin event logs for category
category	Configure plugin event logs for category
all	Configure plugin event logs for category all events
mts	Configure plugin event logs for category mts
rx	(Optional) Configure plugin event logs for mts Rx frames
brief	(Optional) Configure brief plugin event logs for mts Rx
detail	(Optional) Configure detail plugin event logs for mts Rx
tx	(Optional) Configure plugin event logs for mts Tx frames
brief	(Optional) Configure brief plugin event logs for mts Tx
detail	(Optional) Configure detail plugin event logs for mts Tx

Command Mode

- /exec

event-history poap category all

event-history poap category all

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
category	Configure poap event logs for category
all	Configure poap event logs for category all events

Command Mode

- /exec

event-history poap category all

event-history poap no category all

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
no	Disable poap event logs for category
category	Configure poap event logs for category
all	Configure poap event logs for category all events

Command Mode

- /exec

event-history poap category fc2

```
event-history poap category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
category	Configure poap event logs for category
fc2	Configure poap event logs for category FC2
rx	(Optional) Configure poap event logs for FC2 Rx frames
brief	(Optional) Configure brief poap event logs for FC2 Rx
detail	(Optional) Configure detail poap event logs for FC2 Rx
tx	(Optional) Configure poap event logs for FC2 Tx frames
brief1	(Optional) Configure brief poap event logs for FC2 Tx
detail1	(Optional) Configure detail poap event logs for FC2 Tx

Command Mode

- /exec

event-history poap category fc2

```
event-history poap no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
no	Disable poap event logs for category
category	Configure poap event logs for category
fc2	Configure poap event logs for category FC2
rx	(Optional) Configure poap event logs for FC2 Rx frames
brief	(Optional) Configure brief poap event logs for FC2 Rx
detail	(Optional) Configure detail poap event logs for FC2 Rx
tx	(Optional) Configure poap event logs for FC2 Tx frames
brief1	(Optional) Configure brief poap event logs for FC2 Tx
detail1	(Optional) Configure detail poap event logs for FC2 Tx

Command Mode

- /exec

event-history poap category mts

```
event-history poap no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
no	Disable poap event logs for category
category	Configure poap event logs for category
mts	Configure poap event logs for category mts
rx	(Optional) Configure poap event logs for mts Rx frames
brief	(Optional) Configure brief poap event logs for mts Rx
detail	(Optional) Configure detail poap event logs for mts Rx
tx	(Optional) Configure poap event logs for mts Tx frames
brief1	(Optional) Configure brief poap event logs for mts Tx
detail1	(Optional) Configure detail poap event logs for mts Tx

Command Mode

- /exec

event-history poap category mts

```
event-history poap category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
poap	Configure poap event logs
category	Configure poap event logs for category
mts	Configure poap event logs for category mts
rx	(Optional) Configure poap event logs for mts Rx frames
brief	(Optional) Configure brief poap event logs for mts Rx
detail	(Optional) Configure detail poap event logs for mts Rx
tx	(Optional) Configure poap event logs for mts Tx frames
brief1	(Optional) Configure brief poap event logs for mts Tx
detail1	(Optional) Configure detail poap event logs for mts Tx

Command Mode

- /exec

event-history port-profile category all

event-history port-profile [no] category all

Syntax Description

event-history	switch wide event history configuration
port-profile	Configure port-profile event logs
category	Configure port-profile event logs for category
no	(Optional) Disable port-profile event logs for category
all	Configure port-profile event logs for category all events

Command Mode

- /exec

event-history port-profile category mts

```
event-history port-profile [ no ] category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-profile	Configure port-profile event logs
no	(Optional) Disable port-profile event logs for category
category	Configure port-profile event logs for category
mts	Configure port-profile event logs for category mts
rx	(Optional) Configure port-profile event logs for mts Rx frames
brief	(Optional) Configure brief port-profile event logs for mts Rx
detail	(Optional) Configure detail port-profile event logs for mts Rx
tx	(Optional) Configure port-profile event logs for mts Tx frames
brief1	(Optional) Configure brief port-profile event logs for mts Tx
detail1	(Optional) Configure detail port-profile event logs for mts Tx

Command Mode

- /exec

event-history port-resources category all

event-history port-resources category all

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
category	Configure prm event logs for category
all	Configure prm event logs for category all events

Command Mode

- /exec

event-history port-resources category all

event-history port-resources no category all

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
no	Disable prm event logs for category
category	Configure prm event logs for category
all	Configure prm event logs for category all events

Command Mode

- /exec

event-history port-resources category fc2

```
event-history port-resources no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
no	Disable prm event logs for category
category	Configure prm event logs for category
fc2	Configure prm event logs for category FC2
rx	(Optional) Configure prm event logs for FC2 Rx frames
brief	(Optional) Configure brief prm event logs for FC2 Rx
detail	(Optional) Configure detail prm event logs for FC2 Rx
tx	(Optional) Configure prm event logs for FC2 Tx frames
brief1	(Optional) Configure brief prm event logs for FC2 Tx
detail1	(Optional) Configure detail prm event logs for FC2 Tx

Command Mode

- /exec

event-history port-resources category fc2

```
event-history port-resources category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
category	Configure prm event logs for category
fc2	Configure prm event logs for category FC2
rx	(Optional) Configure prm event logs for FC2 Rx frames
brief	(Optional) Configure brief prm event logs for FC2 Rx
detail	(Optional) Configure detail prm event logs for FC2 Rx
tx	(Optional) Configure prm event logs for FC2 Tx frames
brief1	(Optional) Configure brief prm event logs for FC2 Tx
detail1	(Optional) Configure detail prm event logs for FC2 Tx

Command Mode

- /exec

event-history port-resources category mts

event-history port-resources no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
no	Disable prm event logs for category
category	Configure prm event logs for category
mts	Configure prm event logs for category mts
rx	(Optional) Configure prm event logs for mts Rx frames
brief	(Optional) Configure brief prm event logs for mts Rx
detail	(Optional) Configure detail prm event logs for mts Rx
tx	(Optional) Configure prm event logs for mts Tx frames
brief1	(Optional) Configure brief prm event logs for mts Tx
detail1	(Optional) Configure detail prm event logs for mts Tx

Command Mode

- /exec

event-history port-resources category mts

```
event-history port-resources category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-resources	Configure prm event logs
category	Configure prm event logs for category
mts	Configure prm event logs for category mts
rx	(Optional) Configure prm event logs for mts Rx frames
brief	(Optional) Configure brief prm event logs for mts Rx
detail	(Optional) Configure detail prm event logs for mts Rx
tx	(Optional) Configure prm event logs for mts Tx frames
brief1	(Optional) Configure brief prm event logs for mts Tx
detail1	(Optional) Configure detail prm event logs for mts Tx

Command Mode

- /exec

event-history port-security category all

event-history port-security no category all

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
no	Disable port-security event logs for category
category	Configure port-security event logs for category
all	Configure port-security event logs for category all events

Command Mode

- /exec

event-history port-security category all

event-history port-security category all

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
category	Configure port-security event logs for category
all	Configure port-security event logs for category all events

Command Mode

- /exec

event-history port-security category fc2

event-history port-security no category fc2 [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
no	Disable port-security event logs for category
category	Configure port-security event logs for category
fc2	Configure port-security event logs for category FC2
rx	(Optional) Configure port-security event logs for FC2 Rx frames
brief	(Optional) Configure brief port-security event logs for FC2 Rx
detail	(Optional) Configure detail port-security event logs for FC2 Rx
tx	(Optional) Configure port-security event logs for FC2 Tx frames
brief1	(Optional) Configure brief port-security event logs for FC2 Tx
detail1	(Optional) Configure detail port-security event logs for FC2 Tx

Command Mode

- /exec

event-history port-security category fc2

```
event-history port-security category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
category	Configure port-security event logs for category
fc2	Configure port-security event logs for category FC2
rx	(Optional) Configure port-security event logs for FC2 Rx frames
brief	(Optional) Configure brief port-security event logs for FC2 Rx
detail	(Optional) Configure detail port-security event logs for FC2 Rx
tx	(Optional) Configure port-security event logs for FC2 Tx frames
brief1	(Optional) Configure brief port-security event logs for FC2 Tx
detail1	(Optional) Configure detail port-security event logs for FC2 Tx

Command Mode

- /exec

event-history port-security category mts

event-history port-security no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
no	Disable port-security event logs for category
category	Configure port-security event logs for category
mts	Configure port-security event logs for category mts
rx	(Optional) Configure port-security event logs for mts Rx frames
brief	(Optional) Configure brief port-security event logs for mts Rx
detail	(Optional) Configure detail port-security event logs for mts Rx
tx	(Optional) Configure port-security event logs for mts Tx frames
brief1	(Optional) Configure brief port-security event logs for mts Tx
detail1	(Optional) Configure detail port-security event logs for mts Tx

Command Mode

- /exec

event-history port-security category mts

```
event-history port-security category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port-security	Configure port-security event logs
category	Configure port-security event logs for category
mts	Configure port-security event logs for category mts
rx	(Optional) Configure port-security event logs for mts Rx frames
brief	(Optional) Configure brief port-security event logs for mts Rx
detail	(Optional) Configure detail port-security event logs for mts Rx
tx	(Optional) Configure port-security event logs for mts Tx frames
brief1	(Optional) Configure brief port-security event logs for mts Tx
detail1	(Optional) Configure detail port-security event logs for mts Tx

Command Mode

- /exec

event-history port category fc2

```
event-history port no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port	Configure port event logs
no	Disable port event logs for category
category	Configure port event logs for category
fc2	Configure port event logs for category FC2
rx	(Optional) Configure port event logs for FC2 Rx frames
brief	(Optional) Configure brief port event logs for FC2 Rx
detail	(Optional) Configure detail port event logs for FC2 Rx
tx	(Optional) Configure port event logs for FC2 Tx frames
brief1	(Optional) Configure brief port event logs for FC2 Tx
detail1	(Optional) Configure detail port event logs for FC2 Tx

Command Mode

- /exec

event-history port category fc2

```
event-history port category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port	Configure port event logs
category	Configure port event logs for category
fc2	Configure port event logs for category FC2
rx	(Optional) Configure port event logs for FC2 Rx frames
brief	(Optional) Configure brief port event logs for FC2 Rx
detail	(Optional) Configure detail port event logs for FC2 Rx
tx	(Optional) Configure port event logs for FC2 Tx frames
brief1	(Optional) Configure brief port event logs for FC2 Tx
detail1	(Optional) Configure detail port event logs for FC2 Tx

Command Mode

- /exec

event-history port category mts

event-history port no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
port	Configure port event logs
no	Disable port event logs for category
category	Configure port event logs for category
mts	Configure port event logs for category mts
rx	(Optional) Configure port event logs for mts Rx frames
brief	(Optional) Configure brief port event logs for mts Rx
detail	(Optional) Configure detail port event logs for mts Rx
tx	(Optional) Configure port event logs for mts Tx frames
brief1	(Optional) Configure brief port event logs for mts Tx
detail1	(Optional) Configure detail port event logs for mts Tx

Command Mode

- /exec

event-history port category mts

```
event-history port category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port	Configure port event logs
category	Configure port event logs for category
mts	Configure port event logs for category mts
rx	(Optional) Configure port event logs for mts Rx frames
brief	(Optional) Configure brief port event logs for mts Rx
detail	(Optional) Configure detail port event logs for mts Rx
tx	(Optional) Configure port event logs for mts Tx frames
brief1	(Optional) Configure brief port event logs for mts Tx
detail1	(Optional) Configure detail port event logs for mts Tx

Command Mode

- /exec

event-history port_client category all

event-history port_client no category all

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
no	Disable port_client event logs for category
category	Configure port_client event logs for category
all	Configure port_client event logs for category all events

Command Mode

- /exec

event-history port_client category all

event-history port_client category all

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
category	Configure port_client event logs for category
all	Configure port_client event logs for category all events

Command Mode

- /exec

event-history port_client category fc2

```
event-history port_client category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
category	Configure port_client event logs for category
fc2	Configure port_client event logs for category FC2
rx	(Optional) Configure port_client event logs for FC2 Rx frames
brief	(Optional) Configure brief port_client event logs for FC2 Rx
detail	(Optional) Configure detail port_client event logs for FC2 Rx
tx	(Optional) Configure port_client event logs for FC2 Tx frames
brief	(Optional) Configure brief port_client event logs for FC2 Tx
detail	(Optional) Configure detail port_client event logs for FC2 Tx

Command Mode

- /exec

event-history port_client category fc2

```
event-history port_client no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
no	Disable port_client event logs for category
category	Configure port_client event logs for category
fc2	Configure port_client event logs for category FC2
rx	(Optional) Configure port_client event logs for FC2 Rx frames
brief	(Optional) Configure brief port_client event logs for FC2 Rx
detail	(Optional) Configure detail port_client event logs for FC2 Rx
tx	(Optional) Configure port_client event logs for FC2 Tx frames
brief	(Optional) Configure brief port_client event logs for FC2 Tx
detail	(Optional) Configure detail port_client event logs for FC2 Tx

Command Mode

- /exec

event-history port_client category mts

```
event-history port_client category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
category	Configure port_client event logs for category
mts	Configure port_client event logs for category mts
rx	(Optional) Configure port_client event logs for mts Rx frames
brief	(Optional) Configure brief port_client event logs for mts Rx
detail	(Optional) Configure detail port_client event logs for mts Rx
tx	(Optional) Configure port_client event logs for mts Tx frames
brief	(Optional) Configure brief port_client event logs for mts Tx
detail	(Optional) Configure detail port_client event logs for mts Tx

Command Mode

- /exec

event-history port_client category mts

```
event-history port_client no category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
port_client	Configure port_client event logs
no	Disable port_client event logs for category
category	Configure port_client event logs for category
mts	Configure port_client event logs for category mts
rx	(Optional) Configure port_client event logs for mts Rx frames
brief	(Optional) Configure brief port_client event logs for mts Rx
detail	(Optional) Configure detail port_client event logs for mts Rx
tx	(Optional) Configure port_client event logs for mts Tx frames
brief	(Optional) Configure brief port_client event logs for mts Tx
detail	(Optional) Configure detail port_client event logs for mts Tx

Command Mode

- /exec

event-history san-port-channel category all

event-history san-port-channel category all

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
category	Configure pcm event logs for category
all	Configure pcm event logs for category all events

Command Mode

- /exec

event-history san-port-channel category all

event-history san-port-channel no category all

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
no	Disable pcm event logs for category
category	Configure pcm event logs for category
all	Configure pcm event logs for category all events

Command Mode

- /exec

event-history san-port-channel category fc2

```
event-history san-port-channel category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
category	Configure pcm event logs for category
fc2	Configure pcm event logs for category FC2
rx	(Optional) Configure pcm event logs for FC2 Rx frames
brief	(Optional) Configure brief pcm event logs for FC2 Rx
detail	(Optional) Configure detail pcm event logs for FC2 Rx
tx	(Optional) Configure pcm event logs for FC2 Tx frames
brief1	(Optional) Configure brief pcm event logs for FC2 Tx
detail1	(Optional) Configure detail pcm event logs for FC2 Tx

Command Mode

- /exec

event-history san-port-channel category fc2

```
event-history san-port-channel no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
no	Disable pcm event logs for category
category	Configure pcm event logs for category
fc2	Configure pcm event logs for category FC2
rx	(Optional) Configure pcm event logs for FC2 Rx frames
brief	(Optional) Configure brief pcm event logs for FC2 Rx
detail	(Optional) Configure detail pcm event logs for FC2 Rx
tx	(Optional) Configure pcm event logs for FC2 Tx frames
brief1	(Optional) Configure brief pcm event logs for FC2 Tx
detail1	(Optional) Configure detail pcm event logs for FC2 Tx

Command Mode

- /exec

event-history san-port-channel category mts

```
event-history san-port-channel category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
category	Configure pcm event logs for category
mts	Configure pcm event logs for category mts
rx	(Optional) Configure pcm event logs for mts Rx frames
brief	(Optional) Configure brief pcm event logs for mts Rx
detail	(Optional) Configure detail pcm event logs for mts Rx
tx	(Optional) Configure pcm event logs for mts Tx frames
brief1	(Optional) Configure brief pcm event logs for mts Tx
detail1	(Optional) Configure detail pcm event logs for mts Tx

Command Mode

- /exec

event-history san-port-channel category mts

event-history san-port-channel no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
san-port-channel	Configure pcm event logs
no	Disable pcm event logs for category
category	Configure pcm event logs for category
mts	Configure pcm event logs for category mts
rx	(Optional) Configure pcm event logs for mts Rx frames
brief	(Optional) Configure brief pcm event logs for mts Rx
detail	(Optional) Configure detail pcm event logs for mts Rx
tx	(Optional) Configure pcm event logs for mts Tx frames
brief1	(Optional) Configure brief pcm event logs for mts Tx
detail1	(Optional) Configure detail pcm event logs for mts Tx

Command Mode

- /exec

event-history sensor

```
event-history sensor { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] ] } } | no category
{ all | mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] ] } }
```

Syntax Description

event-history	switch wide event history configuration
sensor	Configure sensor USD event logs
category	Configure sensor USD event logs for category
all	Configure sensor USD event logs for category all events
mts	Configure sensor USD event logs for category mts
rx	(Optional) Configure sensor USD event logs for mts Rx frames
brief	(Optional) Configure brief sensor USD event logs for mts Rx
detail	(Optional) Configure detail sensor USD event logs for mts Rx
tx	(Optional) Configure sensor USD event logs for mts Tx frames
brief	(Optional) Configure brief sensor USD event logs for mts Tx
detail	(Optional) Configure detail sensor USD event logs for mts Tx
no	Disable sensor USD event logs for category
category	Configure sensor USD event logs for category
all	Configure sensor USD event logs for category all events
mts	Configure sensor USD event logs for category mts
rx	(Optional) Configure sensor USD event logs for mts Rx frames
brief	(Optional) Configure brief sensor USD event logs for mts Rx
detail	(Optional) Configure detail sensor USD event logs for mts Rx
tx	(Optional) Configure sensor USD event logs for mts Tx frames
brief	(Optional) Configure brief sensor USD event logs for mts Tx
detail	(Optional) Configure detail sensor USD event logs for mts Tx

Command Mode

- /exec

event-history session-mgr category all

event-history session-mgr no category all

Syntax Description

event-history	switch wide event history configuration
session-mgr	Configure session-mgr event logs
no	Disable session-mgr event logs for category
category	Configure session-mgr event logs for category
all	Configure session-mgr event logs for category all events

Command Mode

- /exec

event-history session-mgr category all

event-history session-mgr category all

Syntax Description

event-history	switch wide event history configuration
session-mgr	Configure session-mgr event logs
category	Configure session-mgr event logs for category
all	Configure session-mgr event logs for category all events

Command Mode

- /exec

event-history session-mgr category mts

```
event-history session-mgr no category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
session-mgr	Configure session-mgr event logs
no	Disable session-mgr event logs for category
category	Configure session-mgr event logs for category
mts	Configure session-mgr event logs for category mts
rx	(Optional) Configure session-mgr event logs for mts Rx frames
brief	(Optional) Configure brief session-mgr event logs for mts Rx
detail	(Optional) Configure detail session-mgr event logs for mts Rx
tx	(Optional) Configure session-mgr event logs for mts Tx frames
brief1	(Optional) Configure brief session-mgr event logs for mts Tx
detail1	(Optional) Configure detail session-mgr event logs for mts Tx

Command Mode

- /exec

event-history session-mgr category mts

```
event-history session-mgr category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
session-mgr	Configure session-mgr event logs
category	Configure session-mgr event logs for category
mts	Configure session-mgr event logs for category mts
rx	(Optional) Configure session-mgr event logs for mts Rx frames
brief	(Optional) Configure brief session-mgr event logs for mts Rx
detail	(Optional) Configure detail session-mgr event logs for mts Rx
tx	(Optional) Configure session-mgr event logs for mts Tx frames
brief1	(Optional) Configure brief session-mgr event logs for mts Tx
detail1	(Optional) Configure detail session-mgr event logs for mts Tx

Command Mode

- /exec

event-history sflow

```
event-history sflow { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
sflow	Configure sFlow event logs
category	Configure sFlow event logs for category
all	Configure sFlow event logs for category all events
mts	Configure sFlow event logs for category mts
rx	(Optional) Configure sFlow event logs for mts Rx frames
brief	(Optional) Configure brief sFlow event logs for mts Rx
detail	(Optional) Configure detail sFlow event logs for mts Rx
tx	(Optional) Configure sFlow event logs for mts Tx frames
brief1	(Optional) Configure brief sFlow event logs for mts Tx
detail1	(Optional) Configure detail sFlow event logs for mts Tx
no	Disable sFlow event logs for category
category	Configure sFlow event logs for category
all	Configure sFlow event logs for category all events
mts	Configure sFlow event logs for category mts
rx	(Optional) Configure sFlow event logs for mts Rx frames
brief1	(Optional) Configure brief sFlow event logs for mts Rx
detail1	(Optional) Configure detail sFlow event logs for mts Rx
tx	(Optional) Configure sFlow event logs for mts Tx frames
brief2	(Optional) Configure brief sFlow event logs for mts Tx
detail2	(Optional) Configure detail sFlow event logs for mts Tx

Command Mode

- /exec

event-history snmp

```
event-history snmp { category { all | mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ] } | no category
{ all | mts [ { rx [ { brief1 | detail1 } ] | tx [ { brief2 | detail2 } ] } ] } }
```

Syntax Description

event-history	switch wide event history configuration
snmp	Configure SNMP event logs
category	Configure SNMP event logs for category
all	Configure SNMP event logs for category all events
mts	Configure snmp event logs for category MTS
rx	(Optional) Configure snmp event logs for MTS Rx frames
brief	(Optional) Configure brief SNMP event logs for MTS Rx
detail	(Optional) Configure detail SNMP event logs for MTS Rx
tx	(Optional) Configure SNMP event logs for MTS Tx frames
brief1	(Optional) Configure brief SNMP event logs for MTS Tx
detail1	(Optional) Configure detail snmp event logs for MTS Tx
no	Disable SNMP event logs for category
category	Configure SNMP event logs for category
all	Configure SNMP event logs for category all events
mts	Configure snmp event logs for category MTS
rx	(Optional) Configure snmp event logs for MTS Rx frames
brief1	(Optional) Configure brief SNMP event logs for MTS Rx
detail1	(Optional) Configure detail SNMP event logs for MTS Rx
tx	(Optional) Configure SNMP event logs for MTS Tx frames
brief2	(Optional) Configure brief SNMP event logs for MTS Tx
detail2	(Optional) Configure detail snmp event logs for MTS Tx

Command Mode

- /exec

event-history spanning-tree category all

event-history spanning-tree category all

Syntax Description

event-history	switch wide event history configuration
spanning-tree	Configure stp event logs
category	Configure stp event logs for category
all	Configure stp event logs for category all events

Command Mode

- /exec

event-history spm category all

event-history spm category all

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
category	Configure spm event logs for category
all	Configure spm event logs for category all events

Command Mode

- /exec

event-history spm category all

event-history spm no category all

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
no	Disable spm event logs for category
category	Configure spm event logs for category
all	Configure spm event logs for category all events

Command Mode

- /exec

event-history spm category fc2

```
event-history spm category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
category	Configure spm event logs for category
fc2	Configure spm event logs for category FC2
rx	(Optional) Configure spm event logs for FC2 Rx frames
brief	(Optional) Configure brief spm event logs for FC2 Rx
detail	(Optional) Configure detail spm event logs for FC2 Rx
tx	(Optional) Configure spm event logs for FC2 Tx frames
brief1	(Optional) Configure brief spm event logs for FC2 Tx
detail1	(Optional) Configure detail spm event logs for FC2 Tx

Command Mode

- /exec

event-history spm category fc2

```
event-history spm no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
no	Disable spm event logs for category
category	Configure spm event logs for category
fc2	Configure spm event logs for category FC2
rx	(Optional) Configure spm event logs for FC2 Rx frames
brief	(Optional) Configure brief spm event logs for FC2 Rx
detail	(Optional) Configure detail spm event logs for FC2 Rx
tx	(Optional) Configure spm event logs for FC2 Tx frames
brief1	(Optional) Configure brief spm event logs for FC2 Tx
detail1	(Optional) Configure detail spm event logs for FC2 Tx

Command Mode

- /exec

event-history spm category mts

event-history spm no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
no	Disable spm event logs for category
category	Configure spm event logs for category
mts	Configure spm event logs for category mts
rx	(Optional) Configure spm event logs for mts Rx frames
brief	(Optional) Configure brief spm event logs for mts Rx
detail	(Optional) Configure detail spm event logs for mts Rx
tx	(Optional) Configure spm event logs for mts Tx frames
brief1	(Optional) Configure brief spm event logs for mts Tx
detail1	(Optional) Configure detail spm event logs for mts Tx

Command Mode

- /exec

event-history spm category mts

```
event-history spm category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
spm	Configure spm event logs
category	Configure spm event logs for category
mts	Configure spm event logs for category mts
rx	(Optional) Configure spm event logs for mts Rx frames
brief	(Optional) Configure brief spm event logs for mts Rx
detail	(Optional) Configure detail spm event logs for mts Rx
tx	(Optional) Configure spm event logs for mts Tx frames
brief1	(Optional) Configure brief spm event logs for mts Tx
detail1	(Optional) Configure detail spm event logs for mts Tx

Command Mode

- /exec

event-history stripcl category all

event-history stripcl no category all

Syntax Description

event-history	switch wide event history configuration
stripcl	Configure stripcl event logs
no	Disable stripcl event logs for category
category	Configure stripcl event logs for category
all	Configure stripcl event logs for category all events

Command Mode

- /exec

event-history stripcl category all

event-history stripcl category all

Syntax Description

event-history	switch wide event history configuration
stripcl	Configure stripcl event logs
category	Configure stripcl event logs for category
all	Configure stripcl event logs for category all events

Command Mode

- /exec

event-history stripcl category mts

```
event-history stripcl category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
stripcl	Configure stripcl event logs
category	Configure stripcl event logs for category
mts	Configure stripcl event logs for category mts
rx	(Optional) Configure stripcl event logs for mts Rx frames
brief	(Optional) Configure brief stripcl event logs for mts Rx
detail	(Optional) Configure detail stripcl event logs for mts Rx
tx	(Optional) Configure stripcl event logs for mts Tx frames
brief	(Optional) Configure brief stripcl event logs for mts Tx
detail	(Optional) Configure detail stripcl event logs for mts Tx

Command Mode

- /exec

event-history tamnw category all

event-history tamnw category all

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
category	Configure tamnw event logs for category
all	Configure tamnw event logs for category all events

Command Mode

- /exec

event-history tamnw category all

event-history tamnw no category all

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
no	Disable tamnw event logs for category
category	Configure tamnw event logs for category
all	Configure tamnw event logs for category all events

Command Mode

- /exec

event-history tamnw category fc2

```
event-history tamnw category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
category	Configure tamnw event logs for category
fc2	Configure tamnw event logs for category FC2
rx	(Optional) Configure tamnw event logs for FC2 Rx frames
brief	(Optional) Configure brief tamnw event logs for FC2 Rx
detail	(Optional) Configure detail tamnw event logs for FC2 Rx
tx	(Optional) Configure tamnw event logs for FC2 Tx frames
brief	(Optional) Configure brief tamnw event logs for FC2 Tx
detail	(Optional) Configure detail tamnw event logs for FC2 Tx

Command Mode

- /exec

event-history tamnw category fc2

```
event-history tamnw no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
no	Disable tamnw event logs for category
category	Configure tamnw event logs for category
fc2	Configure tamnw event logs for category FC2
rx	(Optional) Configure tamnw event logs for FC2 Rx frames
brief	(Optional) Configure brief tamnw event logs for FC2 Rx
detail	(Optional) Configure detail tamnw event logs for FC2 Rx
tx	(Optional) Configure tamnw event logs for FC2 Tx frames
brief	(Optional) Configure brief tamnw event logs for FC2 Tx
detail	(Optional) Configure detail tamnw event logs for FC2 Tx

Command Mode

- /exec

event-history tamnw category mts

```
event-history tamnw no category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
no	Disable tamnw event logs for category
category	Configure tamnw event logs for category
mts	Configure tamnw event logs for category mts
rx	(Optional) Configure tamnw event logs for mts Rx frames
brief	(Optional) Configure brief tamnw event logs for mts Rx
detail	(Optional) Configure detail tamnw event logs for mts Rx
tx	(Optional) Configure tamnw event logs for mts Tx frames
brief	(Optional) Configure brief tamnw event logs for mts Tx
detail	(Optional) Configure detail tamnw event logs for mts Tx

Command Mode

- /exec

event-history tamnw category mts

event-history tamnw category mts [{ rx [{ brief | detail }] | tx [{ brief | detail }] }]

Syntax Description

event-history	switch wide event history configuration
tamnw	Configure tamnw event logs
category	Configure tamnw event logs for category
mts	Configure tamnw event logs for category mts
rx	(Optional) Configure tamnw event logs for mts Rx frames
brief	(Optional) Configure brief tamnw event logs for mts Rx
detail	(Optional) Configure detail tamnw event logs for mts Rx
tx	(Optional) Configure tamnw event logs for mts Tx frames
brief	(Optional) Configure brief tamnw event logs for mts Tx
detail	(Optional) Configure detail tamnw event logs for mts Tx

Command Mode

- /exec

event-history udd category all

event-history udd category all

Syntax Description

event-history	switch wide event history configuration
udd	Configure udd event logs
category	Configure udd event logs for category
all	Configure udd event logs for category all events

Command Mode

- /exec

event-history ufdm category all

event-history ufdm category all

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
category	Configure ufdm event logs for category
all	Configure ufdm event logs for category all events

Command Mode

- /exec

event-history ufdm category all

event-history ufdm no category all

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
no	Disable ufdm event logs for category
category	Configure ufdm event logs for category
all	Configure ufdm event logs for category all events

Command Mode

- /exec

event-history ufdm category fc2

```
event-history ufdm no category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
no	Disable ufdm event logs for category
category	Configure ufdm event logs for category
fc2	Configure ufdm event logs for category FC2
rx	(Optional) Configure ufdm event logs for FC2 Rx frames
brief	(Optional) Configure brief ufdm event logs for FC2 Rx
detail	(Optional) Configure detail ufdm event logs for FC2 Rx
tx	(Optional) Configure ufdm event logs for FC2 Tx frames
brief	(Optional) Configure brief ufdm event logs for FC2 Tx
detail	(Optional) Configure detail ufdm event logs for FC2 Tx

Command Mode

- /exec

event-history ufdm category fc2

```
event-history ufdm category fc2 [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
category	Configure ufdm event logs for category
fc2	Configure ufdm event logs for category FC2
rx	(Optional) Configure ufdm event logs for FC2 Rx frames
brief	(Optional) Configure brief ufdm event logs for FC2 Rx
detail	(Optional) Configure detail ufdm event logs for FC2 Rx
tx	(Optional) Configure ufdm event logs for FC2 Tx frames
brief	(Optional) Configure brief ufdm event logs for FC2 Tx
detail	(Optional) Configure detail ufdm event logs for FC2 Tx

Command Mode

- /exec

event-history ufdm category mts

```
event-history ufdm no category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
no	Disable ufdm event logs for category
category	Configure ufdm event logs for category
mts	Configure ufdm event logs for category mts
rx	(Optional) Configure ufdm event logs for mts Rx frames
brief	(Optional) Configure brief ufdm event logs for mts Rx
detail	(Optional) Configure detail ufdm event logs for mts Rx
tx	(Optional) Configure ufdm event logs for mts Tx frames
brief	(Optional) Configure brief ufdm event logs for mts Tx
detail	(Optional) Configure detail ufdm event logs for mts Tx

Command Mode

- /exec

event-history ufdm category mts

```
event-history ufdm category mts [ { rx [ { brief | detail } ] | tx [ { brief | detail } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
ufdm	Configure ufdm event logs
category	Configure ufdm event logs for category
mts	Configure ufdm event logs for category mts
rx	(Optional) Configure ufdm event logs for mts Rx frames
brief	(Optional) Configure brief ufdm event logs for mts Rx
detail	(Optional) Configure detail ufdm event logs for mts Rx
tx	(Optional) Configure ufdm event logs for mts Tx frames
brief	(Optional) Configure brief ufdm event logs for mts Tx
detail	(Optional) Configure detail ufdm event logs for mts Tx

Command Mode

- /exec

event-history vdc category all

event-history vdc no category all

Syntax Description

event-history	switch wide event history configuration
vdc	Configure vdc_mgr event logs
no	Disable vdc_mgr event logs for category
category	Configure vdc_mgr event logs for category
all	Configure vdc_mgr event logs for category all events

Command Mode

- /exec

event-history vdc category all

event-history vdc category all

Syntax Description

event-history	switch wide event history configuration
vdc	Configure vdc_mgr event logs
category	Configure vdc_mgr event logs for category
all	Configure vdc_mgr event logs for category all events

Command Mode

- /exec

event-history vdc category mts

event-history vdc no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
vdc	Configure vdc_mgr event logs
no	Disable vdc_mgr event logs for category
category	Configure vdc_mgr event logs for category
mts	Configure vdc_mgr event logs for category mts
rx	(Optional) Configure vdc_mgr event logs for mts Rx frames
brief	(Optional) Configure brief vdc_mgr event logs for mts Rx
detail	(Optional) Configure detail vdc_mgr event logs for mts Rx
tx	(Optional) Configure vdc_mgr event logs for mts Tx frames
brief1	(Optional) Configure brief vdc_mgr event logs for mts Tx
detail1	(Optional) Configure detail vdc_mgr event logs for mts Tx

Command Mode

- /exec

event-history xbar category all

event-history xbar no category all

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
no	Disable xbar event logs for category
category	Configure xbar event logs for category
all	Configure xbar event logs for category all events

Command Mode

- /exec

event-history xbar category all

event-history xbar category all

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
category	Configure xbar event logs for category
all	Configure xbar event logs for category all events

Command Mode

- /exec

event-history xbar category debug

event-history xbar no category debug { demux | deque | flow | ha | init }

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
no	Disable xbar event logs for category
category	Configure xbar event logs for category
debug	Configure xbar event logs for category debug
demux	Configure xbar event logs for category demux
deque	Configure xbar event logs for category deque
flow	Configure xbar event logs for category flow
ha	Configure xbar event logs for category HA
init	Configure xbar event logs for category init

Command Mode

- /exec

event-history xbar category debug

event-history xbar category debug { demux | deque | flow | ha | init }

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
category	Configure xbar event logs for category
debug	Configure xbar event logs for category debug
demux	Configure xbar event logs for category demux
deque	Configure xbar event logs for category deque
flow	Configure xbar event logs for category flow
ha	Configure xbar event logs for category HA
init	Configure xbar event logs for category init

Command Mode

- /exec

event-history xbar category mts

event-history xbar no category mts [{ rx [{ brief | detail }] | tx [{ brief1 | detail1 }] }]

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
no	Disable xbar event logs for category
category	Configure xbar event logs for category
mts	Configure xbar event logs for category mts
rx	(Optional) Configure xbar event logs for mts Rx frames
brief	(Optional) Configure brief xbar event logs for mts Rx
detail	(Optional) Configure detail xbar event logs for mts Rx
tx	(Optional) Configure xbar event logs for mts Tx frames
brief1	(Optional) Configure brief xbar event logs for mts Tx
detail1	(Optional) Configure detail xbar event logs for mts Tx

Command Mode

- /exec

event-history xbar category mts

```
event-history xbar category mts [ { rx [ { brief | detail } ] | tx [ { brief1 | detail1 } ] } ]
```

Syntax Description

event-history	switch wide event history configuration
xbar	Configure xbar event logs
category	Configure xbar event logs for category
mts	Configure xbar event logs for category mts
rx	(Optional) Configure xbar event logs for mts Rx frames
brief	(Optional) Configure brief xbar event logs for mts Rx
detail	(Optional) Configure detail xbar event logs for mts Rx
tx	(Optional) Configure xbar event logs for mts Tx frames
brief1	(Optional) Configure brief xbar event logs for mts Tx
detail1	(Optional) Configure detail xbar event logs for mts Tx

Command Mode

- /exec

event-log-size

```
{ { [ eigrp ] event-log-size <size> } | { no [ eigrp ] event-log-size [ <size> ] } }
```

Syntax Description

no	Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
event-log-size	Set IP-EIGRP event log size
<i>size</i>	Event log size

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

event-logging

[no] [eigrp] event-logging

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
event-logging	Log IP-EIGRP routing events

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

event

[no] event <eventname>

Syntax Description

event	Specify FTE Event to use
<i>eventname</i>	Name of event

Command Mode

- /exec/configure/config-fte-monitor

event

[no] event

Syntax Description

no	Negate a command or set its defaults
event	Configure an event specification

Command Mode

- /exec/configure/event-manager-applet

event application sub-system type

[no] event application [tag <tag_id>] sub-system <sub-system-id> type <event-type>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
application	Application specific event
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
sub-system	Sub-system ID that will publish the application event
<i>sub-system-id</i>	Sub-system ID value
type	Event type within the specified sub-system
<i>event-type</i>	Event type value

Command Mode

- /exec/configure/event-manager-applet

event cli match

```
[no] event cli [ tag <tag_id> ] match <regex> [ count <countnum> [ time <interval> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
cli	Create a cli event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
match	Enter cli regex to be used for matching
<i>regex</i>	CLI regex, use * to wildcard a token
count	(Optional) Enter an integer to be used as count
<i>countnum</i>	(Optional) Integer count
time	(Optional) Enter time interval within which the events need to happen
<i>interval</i>	(Optional) Time interval in seconds, 0 for indefinitely

Command Mode

- /exec/configure/event-manager-applet

event counter name entry-val entry-op

[no] event counter [tag <tag_id>] name <counter-name> entry-val <entry-val> entry-op <entry-op> [exit-val <exit-val> exit-op <exit-op>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
counter	Create a counter event
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
name	Enter the name of the counter
<i>counter-name</i>	Name of the counter
entry-val	Specify the counter entry conditions
<i>entry-val</i>	Specify the value for comparison with the counter value
entry-op	Specify the operator to be used for comparison
<i>entry-op</i>	Specify the comparison operator
exit-val	(Optional) Specify the counter exit conditions
<i>exit-val</i>	(Optional) Specify the value for comparison with the counter value
exit-op	(Optional) Specify the operator to be used for comparison
<i>exit-op</i>	(Optional) Specify the comparison operator

Command Mode

- /exec/configure/event-manager-applet

event fanabsent time

[no] event fanabsent [fan <fan-number>] time <time-interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
fanabsent	Create fanabsent event specification
fan	(Optional) Optional. Enter fan number (optional arg)
<i>fan-number</i>	(Optional) Enter fan-number
time	Enter time
<i>time-interval</i>	Time in seconds fan can stay absent

Command Mode

- /exec/configure/event-manager-applet

event fanbad time

[no] event fanbad [fan <fan-number>] time <time-interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
fanbad	Create fanbad event specification
fan	(Optional) Optional. Enter fan number (optional arg)
<i>fan-number</i>	(Optional) Enter fan-number
time	Enter time
<i>time-interval</i>	Time in seconds fan can stay bad

Command Mode

- /exec/configure/event-manager-applet

event fib adjacency extra

[no] event fib adjacency extra

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
fib	FIB related event
adjacency	Adjacency related event
extra	Route extra in FIB

Command Mode

- /exec/configure/event-manager-applet

event fib resource tcam usage

[no] event fib resource tcam usage

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
fib	FIB related event
resource	Specify forwarding hardware resource related event
tcam	Specify TCAM related event
usage	Specify TCAM usage related event

Command Mode

- /exec/configure/event-manager-applet

event fib route

[no] event fib route { inconsistent | missing | extra }

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
fib	FIB related event
route	IP Route related event
inconsistent	Inconsistent route in FIB
missing	Missing route in FIB
extra	Route extra in FIB

Command Mode

- /exec/configure/event-manager-applet

event gold module test testing-type scheduled consecutive-failure

```
event gold module { <module> | all } test { <name> } [ severity { minor | moderate | major } ] testing-type {
scheduled | monitoring } consecutive-failure <cnt> | no event gold module { <module> | all } test { <name>
}
```

Syntax Description

no	Negate a command or set its defaults
event	Configure an event specification
gold	Create a 'Diagnostic' event specification
module	Module keyword
<i>module</i>	Module Number
all	Select all module ID
test	Diagnostic test selection
<i>name</i>	Test name
severity	(Optional) Severity of failure
minor	(Optional) Minor failure
moderate	(Optional) Moderate failure
major	(Optional) Major failure
testing-type	Type of Diagnostic test
scheduled	Scheduled Test
monitoring	Monitoring Test
consecutive-failure	Consecutive number of times failure has occurred
<i>cnt</i>	Failure count

Command Mode

- /exec/configure/event-manager-applet

event manager applet

[no] event manager applet <name> [module <module-id>] [override <override-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Event Manager commands
manager	Event Manager commands
applet	Create/Modify an Event Manager Policy
<i>name</i>	Name of policy (cannot have underscore in first two characters)
module	(Optional) Restrict policy to a module
<i>module-id</i>	(Optional)
override	(Optional) Override a system policy
<i>override-name</i>	(Optional) Name of the system policy to override - should begin with double underscore

Command Mode

- /exec/configure

event manager clear counter

event manager clear counter <counter-name>

Syntax Description

event	Event Manager commands
manager	Event Manager commands
clear	Clear event manager information
counter	Clear the value of a counter
<i>counter-name</i>	Name of the counter

Command Mode

- /exec

event manager clear history events

event manager clear history events

Syntax Description

event	Event Manager commands
manager	Event Manager commands
clear	Clear event manager information
history	Clear the stored/archived information
events	Clear all the stored/archived event history for this VDC

Command Mode

- /exec

event manager environment

event manager environment <varname> <varvalue> | no event manager environment <varname>

Syntax Description

no	Negate a command or set its defaults
event	Event Manager commands
manager	Event Manager commands
environment	Configure an environment variable
<i>varname</i>	Name of the environment variable
<i>varvalue</i>	Value of the environment variable

Command Mode

- /exec/configure

event manager policy

event manager policy <name>

Syntax Description

event	Event Manager commands
manager	Event Manager commands
policy	Register a script policy and activate it
<i>name</i>	Name of the script policy file

Command Mode

- /exec/configure

event manager run

```
event manager run <policy-name> [ <arg1> [ <arg2> [ <arg3> [ <arg4> [ <arg5> [ <arg6> [ <arg7> [ <arg8>
[ <arg9> [ <arg10> ]]]]]]]]]]]
```

Syntax Description

event	Event Manager commands
manager	Event Manager commands
run	Trigger/run an event manager policy manually
<i>policy-name</i>	Name of the policy to be triggered-cannot specify default system policy
<i>arg1</i>	(Optional) User specified data value 1
<i>arg2</i>	(Optional) User specified data value 2
<i>arg3</i>	(Optional) User specified data value 3
<i>arg4</i>	(Optional) User specified data value 4
<i>arg5</i>	(Optional) User specified data value 5
<i>arg6</i>	(Optional) User specified data value 6
<i>arg7</i>	(Optional) User specified data value 7
<i>arg8</i>	(Optional) User specified data value 8
<i>arg9</i>	(Optional) User specified data value 9
<i>arg10</i>	(Optional) User specified data value 10

Command Mode

- /exec

event memory

[no] event memory { minor | severe | critical }

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
memory	Create memory thresholds event specification
minor	Minor alert
severe	Severe alert
critical	Critical alert

Command Mode

- /exec/configure/event-manager-applet

event module-failure type module count

[no] event module-failure [tag <tag_id>] type <err-name> module { all | <module> } count <countnum> [time <interval>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
module-failure	Create a 'module-failure' event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
type	Enter an error type
<i>err-name</i>	
module	Enter a module number
all	All modules
<i>module</i>	Enter module number
count	Enter an integer to be used as count
<i>countnum</i>	Integer count
time	(Optional) Enter time interval within which the events need to happen
<i>interval</i>	(Optional) Time interval in seconds

Command Mode

- /exec/configure/event-manager-applet

event module status module1

[no] event module [tag <tag_id>] status { online | offline | any } module1 { all | <module> }

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
module	Create a 'module' event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
status	Status event
online	Online status
offline	Offline status
any	Online or offline status
module1	Enter a module number
all	All modules
<i>module</i>	Enter module number

Command Mode

- /exec/configure/event-manager-applet

event neighbor-discovery

[no] event [tag <tag_id>] neighbor-discovery

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
neighbor-discovery	Show CDP new neighbors

Command Mode

- /exec/configure/event-manager-applet

event none

[no] event none [tag <tag_id>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
none	Manually run policy event with none
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name

Command Mode

- /exec/configure/event-manager-applet

event oir fan

[no] event oir [tag <tag_id>] fan { insert | remove | anyoir } [<fannum>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
oir	Create Online-Insertion-Removal event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
fan	Fan OIR
insert	OIR insert
remove	OIR remove
anyoir	any OIR (Either insert or remove)
<i>fannum</i>	(Optional) Optional. Enter Fan number.

Command Mode

- /exec/configure/event-manager-applet

event oir module

[no] event oir [tag <tag_id>] module { insert | remove | anyoir } [<module>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
oir	Create Online-Insertion-Removal event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
module	Module OIR
insert	OIR insert
remove	OIR remove
anyoir	any OIR (Either insert or remove)
<i>module</i>	(Optional) Optional. Enter module number

Command Mode

- /exec/configure/event-manager-applet

event oir powersupply

[no] event oir [tag <tag_id>] powersupply { insert | remove | anyoir } [<powersupnum>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
oir	Create Online-Insertion-Removal event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
powersupply	powersupply OIR
insert	OIR insert
remove	OIR remove
anyoir	any OIR (Either insert or remove)
<i>powersupnum</i>	(Optional) Optional. Enter powersupply number

Command Mode

- /exec/configure/event-manager-applet

event policy-default count

[no] event policy-default count <countnum> [time <interval>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
policy-default	Use the event in the system policy being overridden
count	Enter an integer to be used as count
<i>countnum</i>	Integer count
time	(Optional) Enter time interval within which the events need to happen
<i>interval</i>	(Optional) Time interval in seconds

Command Mode

- /exec/configure/event-manager-applet

event poweroverbudget

[no] event poweroverbudget

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
poweroverbudget	Create poweroverbudget event specification

Command Mode

- /exec/configure/event-manager-applet

event snmp oid get-type exact entry-op entry-val poll-interval

```
[no] event snmp [ tag <tag_id> ] oid <oid-val> get-type { exact | next } entry-op { ent_gt | ent_ge | ent_eq |
ent_ne | ent_lt | ent_le } entry-val <entry-val> [ { exit-comb { or | and } exit-op { ex_gt | ex_ge | ex_eq | ex_ne
| ex_lt | ex_le } exit-val <exit-val> exit-time <exit-time-val> } | { exit-op1 { ex_gt1 | ex_ge1 | ex_eq1 | ex_ne1
| ex_lt1 | ex_le1 } exit-val1 <exit-val1> } ] poll-interval <poll-int-val>
```

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
snmp	Create a 'snmp' event specification.
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
oid	oid of data element in dot notation.
<i>oid-val</i>	oid of data element in dot notation.
get-type	The type of SNMP get operation.
exact	exact
next	next
entry-op	entry comparison operator.
ent_gt	greater than
ent_ge	greater than or equal to
ent_eq	equal to
ent_ne	not equal to
ent_lt	less than
ent_le	less than or equal to
entry-val	value to compare with the current polled value
<i>entry-val</i>	value to compare with the current polled value
exit-comb	(Optional) exit criterion combination
or	(Optional) logical OR
and	(Optional) logical AND
exit-op	(Optional) exit comparison operator.

ex_gt	(Optional) greater than
ex_ge	(Optional) greater than or equal to
ex_eq	(Optional) equal to
ex_ne	(Optional) not equal to
ex_lt	(Optional) less than
ex_le	(Optional) less than or equal to
exit-val	(Optional) value to compare with the current polled value
<i>exit-val</i>	(Optional) value to compare with the current polled value
exit-op1	(Optional) exit comparison operator.
ex_gt1	(Optional) greater than
ex_ge1	(Optional) greater than or equal to
ex_eq1	(Optional) equal to
ex_ne1	(Optional) not equal to
ex_lt1	(Optional) less than
ex_le1	(Optional) less than or equal to
exit-val1	(Optional) value to compare with the current polled value
<i>exit-val1</i>	(Optional) value to compare with the current polled value
exit-time	(Optional) exit time
<i>exit-time-val</i>	(Optional) exit time in seconds
poll-interval	polling interval
<i>poll-int-val</i>	polling interval in seconds

Command Mode

- /exec/configure/event-manager-applet

event storm-control

[no] event storm-control

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
storm-control	Create a storm control event specification

Command Mode

- /exec/configure/event-manager-applet

event syslog pattern

[no] event syslog [tag <tag_id>] [occurs <num-occurrences>] [period <period-value>] [priority [<i0> | alerts | critical | debugging | emergencies | errors | informational | notifications | warnings]] pattern <regex>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
syslog	Create a syslog event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
occurs	(Optional) Enter an integer to be used for number of occurrences
<i>num-occurrences</i>	(Optional) Integer count
period	(Optional) Enter time interval within which the events need to happen
<i>period-value</i>	(Optional) Time interval in seconds, 0 for indefinitely
priority	(Optional) Priority of the log message
<i>i0</i>	(Optional) Enter priority of the log message
alerts	(Optional) Alert log message
critical	(Optional) Critical log message
debugging	(Optional) Debugging log message
emergencies	(Optional) Emergency log message
errors	(Optional) Error log message
informational	(Optional) Informational log message
notifications	(Optional) Notifications log message
warnings	(Optional) Warning log message
pattern	Enter regex to be used for matching
<i>regex</i>	SYSLOG regex

Command Mode

- /exec/configure/event-manager-applet

event sysmgr memory major minor clear

[no] event sysmgr memory [module <module>] major <i0> minor <i1> clear <i2>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
sysmgr	system manager related events
memory	memory alert event
module	(Optional) Optional. Enter module number
<i>module</i>	(Optional) Enter module-number
major	set major memory threshold
<i>i0</i>	major memory threshold
minor	set minor memory threshold
<i>i1</i>	minor memory threshold
clear	set clear memory alert threshold
<i>i2</i>	clear memory threshold

Command Mode

- /exec/configure/event-manager-applet

event sysmgr switchover count time

[no] event sysmgr switchover count <countnum> time <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
sysmgr	System manager related events
switchover	Switchover related event
count	Number of switchovers after which event should be triggered
<i>countnum</i>	Integer count
time	Enter time interval within which the events need to happen
<i>interval</i>	Time interval in seconds

Command Mode

- /exec/configure/event-manager-applet

event temperature threshold

[no] event temperature [module <module>] [sensor <sensornum>] threshold { major | minor | any }

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
temperature	Create temperature event specification
module	(Optional) Optional. Enter module number (optional arg)
<i>module</i>	(Optional) Enter module-number
sensor	(Optional) Optional. Enter sensor number (optional arg)
<i>sensornum</i>	(Optional) Enter sensor number
threshold	Enter Major or Minor threshold
major	Major threshold
minor	Minor threshold
any	Major or Minor

Command Mode

- /exec/configure/event-manager-applet

event test match

[no] event test [tag <tag_id>] match <num> [count <countnum>] [time <interval>]

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
test	Create a 'test' event specification
match	Enter an integer to be used for matching
<i>num</i>	Integer value
count	(Optional) Enter an integer to be used as count
<i>countnum</i>	(Optional) Integer count
<i>time</i>	(Optional) <interval>
<i>interval</i>	(Optional) Time interval in seconds

Command Mode

- /exec/configure/event-manager-applet

event timer

```
[no] event timer [ tag <tag_id> ] { watchdog wtime <watchdog-time> | absolute atime <absolute-time> |
countdown ctime <countdown-time> | cron cron-entry <cron-time> } [ name <timer_name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
event	Configure an event specification
timer	Create a timer event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
name	(Optional) name of the timer
<i>timer_name</i>	(Optional) Enter the timer name
watchdog	Watchdog timer event
wtime	Time period for watchdog
<i>watchdog-time</i>	<1-1924991999[.0-999]> Enter seconds[.milliseconds] value
absolute	Absolute timer event.
atime	epoch time for absolute. Try epochconverter online tool to get value
<i>absolute-time</i>	<1-1924991999[.0-999]> Enter seconds[.milliseconds] value
countdown	Countdown timer event
ctime	Time period for countdown
<i>countdown-time</i>	<1-1924991999[.0-999]> Enter seconds[.milliseconds] value
cron	Cron timer event
cron-entry	Cron entry string
<i>cron-time</i>	format: * * * * * => min hour dom month dow

Command Mode

- /exec/configure/event-manager-applet

event track state

event track [tag <tag_id>] <object-id> state { any | up | down } | no event track [tag <tag_id>] <object-id>

Syntax Description

no	Negate a command or set its defaults
event	Configure an event specification
track	Create a 'track' event specification
tag	(Optional) event tag identifier
<i>tag_id</i>	(Optional) tag name
<i>object-id</i>	Track objects
state	State of tracking object
any	Any state
down	Down state
up	Up state

Command Mode

- /exec/configure/event-manager-applet

evpn

[no] evpn

Syntax Description

no	(Optional) Negate a command or set its defaults
evpn	Enter EVPN configuration mode

Command Mode

- /exec/configure

evpn esi multihoming

[no] evpn esi multihoming

Syntax Description

no	(Optional) unconfigure the command
evpn	VxLAN evpn feature
esi	ESI based multihoming
multihoming	Multihoming feature

Command Mode

- /exec/configure/evpn-esi-multihoming

evpn multihoming core-tracking

[no] evpn multihoming core-tracking

Syntax Description

no	(Optional) Negate a command or set its defaults
evpn	VxLAN evpn feature
multihoming	VxLAN evpn multihoming
core-tracking	core interface tracking

Command Mode

- /exec/configure/if-port-channel /exec/configure/if-routing /exec/configure/if-vlan

evpn multisite border-gateway

evpn multisite border-gateway <site-id> | no evpn multisite border-gateway

Syntax Description

no	Unconfigure the command
evpn	EVPN
multisite	Multisite
border-gateway	Border-gateway
<i>site-id</i>	Multisite Site-Id

Command Mode

- /exec/configure

evpn multisite dci-tracking

[no] evpn multisite dci-tracking

Syntax Description

no	(Optional) Negate a command or set its defaults
evpn	VxLAN evpn feature
multisite	VxLAN evpn multisite
dci-tracking	dci interface tracking

Command Mode

- /exec/configure/if-port-channel /exec/configure/if-routing /exec/configure/if-vlan /exec/configure/if-ethernet /exec/configure/if-range

evpn multisite fabric-tracking

[no] evpn multisite fabric-tracking

Syntax Description

no	(Optional) Negate a command or set its defaults
evpn	VxLAN evpn feature
multisite	VxLAN evpn multisite
fabric-tracking	fabric interface tracking

Command Mode

- /exec/configure/if-port-channel /exec/configure/if-routing /exec/configure/if-vlan /exec/configure/if-ethernet /exec/configure/if-range

evpn storm-control level

[no] evpn storm-control { broadcast | multicast | unicast } level <lev>

Syntax Description

no	(Optional) Negate a command or set its defaults
evpn	VxLAN evpn feature
storm-control	Storm-control
broadcast	Broadcast Packets
multicast	Multicast Packets
unicast	Unknown Unicast Packets
level	Traffic level
<i>lev</i>	Enter the storm suppression level

Command Mode

- /exec/configure

exceptionlog module syserr devid errtype errcode phylayer ports harderror

```
exceptionlog module <module> syserr <syserr> devid <id> errtype <type> errcode <code> phylayer <phy>
ports <list> harderror <hard> [ { desc <str> } ] [ { inband <intinband> } ]
```

Syntax Description

exceptionlog	Exception log
module	Enter a module number
<i>module</i>	Enter module number
syserr	Enter syserr
<i>syserr</i>	Syserr code
devid	Enter device id
<i>id</i>	Device id
errtype	Enter error type
<i>type</i>	Error type
errcode	Enter error code
<i>code</i>	Error code
phylayer	Enter phy layer
<i>phy</i>	Phy layer
ports	Enter failed ports
<i>list</i>	List of ports
harderror	Irrecoverable error?
<i>hard</i>	Error sub-category
desc	(Optional) Enter error description
<i>str</i>	(Optional) Error description
inband	(Optional) inband flag
<i>intinband</i>	(Optional) inband flag

Command Mode

- /exec

exclude access-list

[no] exclude access-list <acl-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
exclude	Configure access-list to exclude from redirection
access-list	PLB access-list
<i>acl-name</i>	Access-list name

Command Mode

- /exec/configure/plb

exclude access-list

[no] exclude access-list <acl-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
exclude	ACL to exclude from redirection
access-list	ITD access-list name
<i>acl-name</i>	ITD exclude ACL name

Command Mode

- /exec/configure/itd

exec-timeout

{ exec-timeout <i0> | no exec-timeout [<i0>] }

Syntax Description

no	Negate a command or set its defaults
exec-timeout	Configure exec timeout
<i>i0</i>	Enter timeout in minutes, 0 to disable

Command Mode

- /exec/configure/line

exec-timeout

{ exec-timeout <i0> | no exec-timeout [<i0>] }

Syntax Description

no	Negate a command or set its defaults
exec-timeout	Configure exec timeout
<i>i0</i>	Enter timeout in minutes, 0 to disable

Command Mode

- /exec/configure/console

existing-cli

{ existing-cli <line> | no existing-cli <line> }

Syntax Description

no	Negate a command or set its defaults
existing-cli	Specify the existing cli
<i>line</i>	existing cli definition separated by <space> <semi-colon> <space>

Command Mode

- /exec/configure/cli

exit

exit

Syntax Description

exit	Exit from command interpreter
------	-------------------------------

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http

exit

exit

Syntax Description

exit	Exit from command interpreter
------	-------------------------------

Command Mode

- /global

exp

```
[no] exp { default | <val> [ <val> [ <val> [ <val> [ <val> [ <val> [ <val> [ <val> ] ] ] ] ] ] ] ] [ default ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
exp	Set the experimental values allowed for this interface
default	Default all unconfigured exp to this interface
<i>val</i>	Enter up to 8 experimental values separated by white-spaces

Command Mode

- /exec/configure/tunnel-te/cbts-member

explicit-null

explicit-null [for <pfx-list>] [to <peer-pfx-list>] | no explicit-null

Syntax Description

no	Negate a command or set its defaults
explicit-null	Advertise Explicit Null label in place of Implicit Null
for	(Optional) Prefix list specifying controls on destination prefixes
<i>pfx-list</i>	(Optional) Name of prefix list
to	(Optional) Access-list specifying controls on LDP peers
<i>peer-pfx-list</i>	(Optional) Name of prefix list

Command Mode

- /exec/configure/ldp

explicit-path

[no] explicit-path <exp-path-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
explicit-path	Preconfigured path
<i>exp-path-name</i>	Identifying name of the explicit-path with max 128 characters

Command Mode

- /exec/configure/sr/te/pol/pref

explicit-path identifier

[no] explicit-path { identifier <id> | name <string> }

Syntax Description

no	(Optional) Negate a command or set its defaults
explicit-path	Configure explicit-path
identifier	Specify explicit path by number
<i>id</i>	Enter number
name	Specify explicit path by name
<i>string</i>	Enter name

Command Mode

- /exec/configure/te

export-gateway-ip

[no] export-gateway-ip

Syntax Description

no	(Optional) Negate a command or set its defaults
export-gateway-ip	Export Gateway IP to Type-5 EVPN routes for VRF

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

export map

[no] export map <rmap-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
export	VRF export
map	Route-map based VRF export
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

export vrf default map

[no] export vrf default [<prefix-limit>] map <rmap-name> [allow-vpn]

Syntax Description

no	(Optional) Negate a command or set its defaults
export	VRF export
vrf	Virtual Router Context
default	VRF name (default)
<i>prefix-limit</i>	(Optional) Maximum prefix limit
map	Route-map based VRF import
<i>rmap-name</i>	Route-map name
allow-vpn	(Optional) Allow re-importation of VPN imported routes

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

exporter-id

{ [no] exporter-id <id> }

Syntax Description

exporter-id	Specify details
<i>id</i>	exporter-id collector

Command Mode

- /exec/configure/config-fte-exporter

exporter

[no] exporter <exportername>

Syntax Description

exporter	Add an Exporter to use to export records
<i>exportername</i>	Name of exporter

Command Mode

- /exec/configure/config-int-monitor

exporter

[no] exporter <exportername>

Syntax Description

exporter	Add an Exporter to use to export records
<i>exportername</i>	Name of exporter

Command Mode

- /exec/configure/config-fte-monitor

exporter

[no] exporter <exportername> [collector-bucket-id <cb-id>]

Syntax Description

exporter	Add an Exporter to use to export records
<i>exportername</i>	Name of exporter
collector-bucket-id	(Optional) Collector Bucket Id
<i>cb-id</i>	(Optional) Collector Bucket Id

Command Mode

- /exec/configure/nfm-monitor

exporter

[no] exporter <exportername>

Syntax Description

exporter	Exporter to be configured
<i>exportername</i>	Exporter to be configured

Command Mode

- /exec/configure/config-ssx-monitor

exporter

[no] exporter <exportername>

Syntax Description

exporter	Add an Exporter to use to export records
<i>exportername</i>	Name of exporter

Command Mode

- /exec/configure/config-postcard-monitor



F Commands

- [fabric-soo](#), on page 1420
- [fabric database auto-pull dci node-id](#), on page 1421
- [fabric database auto-pull dci vrf node-id](#), on page 1422
- [fabric database auto-pull vni interface](#), on page 1423
- [fabric database inherit-profile-map](#), on page 1424
- [fabric database mobility-domain](#), on page 1425
- [fabric database override-profile](#), on page 1426
- [fabric database override-vrf-profile](#), on page 1427
- [fabric database profile-map](#), on page 1428
- [fabric database profile-map global](#), on page 1429
- [fabric database refresh dot1q](#), on page 1430
- [fabric database refresh vni](#), on page 1431
- [fabric database static-host](#), on page 1432
- [fabric database timer](#), on page 1433
- [fabric database type bl-dci](#), on page 1434
- [fabric database type cabling](#), on page 1435
- [fabric database type host](#), on page 1436
- [fabric database type network](#), on page 1437
- [fabric database type partition](#), on page 1438
- [fabric database type profile](#), on page 1439
- [fabric forwarding admin-distance](#), on page 1440
- [fabric forwarding anycast-gateway-mac](#), on page 1441
- [fabric forwarding dup-host-ip-addr-detection](#), on page 1442
- [fabric forwarding dup-host-recovery-timer recover-count](#), on page 1443
- [fabric forwarding dup-host-unfreeze-timer unfreeze-count](#), on page 1444
- [fabric forwarding limit-vlan-mac](#), on page 1445
- [fabric forwarding mode anycast-gateway](#), on page 1446
- [fabric forwarding selective-host-probe](#), on page 1447
- [fabric multicast event-history bgp](#), on page 1448
- [fabric multicast event-history ha](#), on page 1449
- [fabric multicast event-history hmm](#), on page 1450
- [fabric multicast event-history isis](#), on page 1451
- [fabric multicast event-history m2rib](#), on page 1452

- fabric multicast event-history m6rib, on page 1453
- fabric multicast event-history mrrib, on page 1454
- fabric multicast event-history pim, on page 1455
- fabric multicast event-history pim6, on page 1456
- failaction, on page 1457
- failaction, on page 1458
- fast-convergence, on page 1459
- fast-convergence, on page 1460
- fast-external-fallover, on page 1461
- fast-flood enable, on page 1462
- fast-flood enable, on page 1463
- fast-flood enable, on page 1464
- fast-flood interval, on page 1465
- fast-flood interval, on page 1466
- fast-flood interval, on page 1467
- fast-reload, on page 1468
- fast-reload network-os, on page 1469
- fast-reroute, on page 1470
- fast-reroute backup-prot-preempt optimize-bw, on page 1471
- fcdroplacency network, on page 1472
- fcoe, on page 1473
- fcoe, on page 1474
- fcoe enable-fex, on page 1475
- fcoe fcf-priority, on page 1476
- fcoe fcmmap, on page 1477
- fcoe fka-adv-period, on page 1478
- fcoe veloopback, on page 1479
- fcoe vsan, on page 1480
- fctimer D_S_TOV, on page 1481
- fctimer E_D_TOV, on page 1482
- fctimer R_A_TOV, on page 1483
- fctimer abort, on page 1484
- fctimer commit, on page 1485
- fctimer distribute, on page 1486
- feature-set, on page 1487
- feature-set, on page 1488
- feature, on page 1489
- feature analytics, on page 1490
- feature bash-shell, on page 1491
- feature bfd, on page 1492
- feature bgp, on page 1493
- feature catena, on page 1494
- feature container-tracker, on page 1495
- feature dhcp, on page 1496
- feature dot1x, on page 1497
- feature eigrp, on page 1498

- [feature evb](#), on page 1499
- [feature evmed](#), on page 1500
- [feature fabric forwarding](#), on page 1501
- [feature flexlink](#), on page 1502
- [feature grpc](#), on page 1503
- [feature hardware-telemetry](#), on page 1504
- [feature hsrp](#), on page 1505
- [feature icam](#), on page 1506
- [feature imp](#), on page 1507
- [feature interface-vlan](#), on page 1508
- [feature isis](#), on page 1509
- [feature itd](#), on page 1510
- [feature lacp](#), on page 1511
- [feature ldap](#), on page 1512
- [feature lldp](#), on page 1513
- [feature msdp](#), on page 1514
- [feature mvpn](#), on page 1515
- [feature nat](#), on page 1516
- [feature nbm](#), on page 1517
- [feature netconf](#), on page 1518
- [feature ngmvpn](#), on page 1519
- [feature ngoam](#), on page 1520
- [feature ngoam](#), on page 1521
- [feature npiv](#), on page 1522
- [feature ntp](#), on page 1523
- [feature nv overlay](#), on page 1524
- [feature nxapi](#), on page 1525
- [feature nxdb](#), on page 1526
- [feature nxsdk](#), on page 1527
- [feature openflow](#), on page 1528
- [feature openflow](#), on page 1529
- [feature ospf](#), on page 1530
- [feature ospfv3](#), on page 1531
- [feature password encryption aes](#), on page 1532
- [feature pbr](#), on page 1533
- [feature pim](#), on page 1534
- [feature pim6](#), on page 1535
- [feature plb](#), on page 1536
- [feature poap](#), on page 1537
- [feature poe](#), on page 1538
- [feature pong](#), on page 1539
- [feature port-security](#), on page 1540
- [feature private-vlan](#), on page 1541
- [feature privilege](#), on page 1542
- [feature ptp](#), on page 1543
- [feature restconf](#), on page 1544

- feature rip, on page 1545
- feature scheduler, on page 1546
- feature scp-server, on page 1547
- feature sflow, on page 1548
- feature sftp-server, on page 1549
- feature signature-verification, on page 1550
- feature sla responder, on page 1551
- feature sla sender, on page 1552
- feature sla twamp-server, on page 1553
- feature smart-channel, on page 1554
- feature ssh, on page 1555
- feature tacacs, on page 1556
- feature telnet, on page 1557
- feature tunnel, on page 1558
- feature udd, on page 1559
- feature vmtracker, on page 1560
- feature vn-segment-vlan-based, on page 1561
- feature vpc, on page 1562
- feature vrrp, on page 1563
- feature vrrpv3, on page 1564
- feature vtp, on page 1565
- fec, on page 1566
- fec, on page 1567
- fec, on page 1568
- fhrp delay minimum, on page 1569
- fhrp delay reload, on page 1570
- filter, on page 1571
- filter access-group, on page 1572
- filter ip, on page 1573
- filter ipv6 access-group, on page 1574
- filter out, on page 1575
- filter tx control-packets, on page 1576
- filter vlan, on page 1577
- filter vlan include-untagged, on page 1578
- find, on page 1579
- fips debug errors debug, on page 1580
- fips mode enable, on page 1581
- flow-count, on page 1582
- flow-count, on page 1583
- flow exporter, on page 1584
- flow forward, on page 1585
- flow monitor, on page 1586
- flow record, on page 1587
- flow timeout, on page 1588
- flowcontrol hardware, on page 1589
- flowcontrol receive, on page 1590

- flush-routes, on page 1591
- flush-routes, on page 1592
- flush-routes, on page 1593
- flush-routes, on page 1594
- flush-routes, on page 1595
- flush-routes, on page 1596
- follow, on page 1597
- format, on page 1598
- format bootflash, on page 1599
- format bootflash check-filesystem, on page 1600
- format usb1, on page 1601
- forward, on page 1602
- forwarding-adjacency, on page 1603
- fragments, on page 1604
- frequency, on page 1605
- from to, on page 1606
- from to, on page 1607
- fte event, on page 1608
- fte exporter, on page 1609
- fte monitor, on page 1610
- fte record, on page 1611
- fte system monitor, on page 1612
- ftrace, on page 1613

fabric-soo

```
[no] fabric-soo { <ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric-soo	Fabric Site of Origin
<i>ext-comm-soo-aa4nn2</i>	VPN extcommunity in aa4:fabric_id format
<i>ext-comm-soo-aa2nn4</i>	VPN extcommunity in aa:fabric_id format

Command Mode

- /exec/configure/router-bgp

fabric database auto-pull dci node-id

fabric database auto-pull dci node-id <mgmt-ip-address>

Syntax Description

fabric	Fabric
database	Fabric Database
auto-pull	Pull configuration
dci	DCI profile
node-id	management ip address of this node
<i>mgmt-ip-address</i>	IP address in CIDR format

Command Mode

- /exec

fabric database auto-pull dci vrf node-id

```
fabric database auto-pull dci vrf <vrf-name> node-id <mgmt-ip-address> [ peer-id <peer-ip-address> ]
```

Syntax Description

fabric	Fabric
database	Fabric Database
auto-pull	Pull configuration
dci	DCI profile
vrf	Display per-VRF information
<i>vrf-name</i>	VRF name
node-id	management ip address of this node
<i>mgmt-ip-address</i>	IP address in CIDR format
peer-id	(Optional) management ip address of peer
<i>peer-ip-address</i>	(Optional) IP address in CIDR format

Command Mode

- /exec

fabric database auto-pull vni interface

```
fabric database auto-pull { vni <vni-id> | dot1q <vlan-id> } interface <interface-id> [ { overwrite-vlan |
overwrite-bd } <ow-vlan-id> ]
```

Syntax Description

fabric	Fabric
database	Fabric Database
auto-pull	Pull configuration
vni	Pull ethernet-tag vni configuration
<i>vni-id</i>	
dot1q	Pull ethernet-tag dot1q configuration
<i>vlan-id</i>	
interface	Applied interface
<i>interface-id</i>	Name of interface
overwrite-vlan	(Optional) Overwrite the system generate vlan
overwrite-bd	(Optional) Overwrite the system generate bd
<i>ow-vlan-id</i>	(Optional)

Command Mode

- /exec

fabric database inherit-profile-map

{ fabric database inherit-profile-map <id> } | { no fabric database inherit-profile-map }

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
inherit-profile-map	Inherit a profile map. All non-global mappings will be inherited.
<i>id</i>	Profile Map ID

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-port-channel

fabric database mobility-domain

[no] fabric database mobility-domain <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
mobility-domain	Tag to identify mobility domain name
<i>name</i>	Mobility Domain Name

Command Mode

- /exec/configure

fabric database override-profile

[no] fabric database override-profile <profilename>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
override-profile	Override the network profile name
<i>profilename</i>	Enter the profile name to override network profile

Command Mode

- /exec/configure

fabric database override-vrf-profile

[no] fabric database override-vrf-profile <profilename>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
override-vrf-profile	Override the VRF (partition) profile name
<i>profilename</i>	Enter the profile name to override VRF profile

Command Mode

- /exec/configure

fabric database profile-map

[no] fabric database profile-map <id>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
profile-map	Configure a profile map
<i>id</i>	Profile Map ID

Command Mode

- /exec/configure

fabric database profile-map global

[no] fabric database profile-map global

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
profile-map	Configure a profile map
global	Global profile (apply to all interfaces)

Command Mode

- /exec/configure

fabric database refresh dot1q

fabric database refresh dot1q <vlan-id> [{ mobility-domain <name> | interface <interface-id> }]

Syntax Description

fabric	Fabric
database	Fabric Database
refresh	Refresh profile configuration
dot1q	Dot1Q Encapsulation
<i>vlan-id</i>	
interface	(Optional) Applied interface
<i>interface-id</i>	(Optional) Name of interface
mobility-domain	(Optional) Tag to identify mobility domain name
<i>name</i>	(Optional) Mobility Domain Name

Command Mode

- /exec

fabric database refresh vni

```
fabric database refresh { vni <vni-id> | include-vrf { <vrf-name> } }
```

Syntax Description

fabric	Fabric
database	Fabric Database
refresh	Refresh profile configuration
vni	Virtual Network Identifier
<i>vni-id</i>	
include-vrf	Include VRF name
<i>vrf-name</i>	VRF name

Command Mode

- /exec

fabric database static-host

[no] fabric database static-host

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Fabric Database
static-host	Configure a static host

Command Mode

- /exec/configure

fabric database timer

[no] fabric database timer { aging | cleanup | recovery | re-add } <timeout>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	
database	
timer	HMM timers
cleanup	Delay in minutes before profile is deleted
recovery	Delay in minutes before recovered profile is deleted
re-add	Delay in minutes before new client requests (after un-apply) are accepted
aging	Delay in minutes before profile is checked for aging
<i>timeout</i>	Set timeout in minutes

Command Mode

- /exec/configure

fabric database type bl-dci

[no] fabric database type bl-dci

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
bl-dci	Border Leaf - DCI

Command Mode

- /exec/configure

fabric database type cabling

[no] fabric database type cabling

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
cabling	Cable Management Database

Command Mode

- /exec/configure

fabric database type host

[no] fabric database type host

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
host	Host Database

Command Mode

- /exec/configure

fabric database type network

[no] fabric database type network

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
network	Network Database

Command Mode

- /exec/configure

fabric database type partition

[no] fabric database type partition

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
partition	Partition Database

Command Mode

- /exec/configure

fabric database type profile

[no] fabric database type profile

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
database	Configure Fabric Database
type	Configure database type
profile	Port or Switch Profile Database

Command Mode

- /exec/configure

fabric forwarding admin-distance

{ fabric forwarding admin-distance <distance> } | { no fabric forwarding admin-distance }

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
admin-distance	Administrative distance for HMM host routes
<i>distance</i>	Set the administrative distance for HMM (default is 190)

Command Mode

- /exec/configure

fabric forwarding anycast-gateway-mac

```
{ fabric forwarding anycast-gateway-mac <mac-addr> } | { no fabric forwarding anycast-gateway-mac }
```

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
anycast-gateway-mac	Anycast Gateway MAC of the Switch
<i>mac-addr</i>	MAC address

Command Mode

- /exec/configure

fabric forwarding dup-host-ip-addr-detection

```
{ fabric forwarding dup-host-ip-addr-detection <mmoves> <nsecs> | no fabric forwarding
dup-host-ip-addr-detection }
```

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
dup-host-ip-addr-detection	To detect duplicate host address in n secs
<i>mmoves</i>	Set Number of host moves to be allowed in n secs. Default is 5
<i>nsecs</i>	Set the duplicate detection timeout in secs for host moves. Default is 180

Command Mode

- /exec/configure

fabric forwarding dup-host-recovery-timer recover-count

{ fabric forwarding dup-host-recovery-timer <timeout> recover-count <count> | no fabric forwarding dup-host-recovery-timer }

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
dup-host-recovery-timer	Refresh the frozen duplicate host
<i>timeout</i>	Set the timeout in secs to refresh the duplicate host. Default is 30 secs
recover-count	Maximum number of refreshes
<i>count</i>	Set the maximum number of host refresh. Default is 5.

Command Mode

- /exec/configure

fabric forwarding dup-host-unfreeze-timer unfreeze-count

```
{ fabric forwarding dup-host-unfreeze-timer <timeout> unfreeze-count <count> | no fabric forwarding
dup-host-unfreeze-timer }
```

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
dup-host-unfreeze-timer	Refresh the frozen duplicate host
<i>timeout</i>	Set the timeout in secs to refresh the duplicate host. Default is 180 secs
unfreeze-count	Maximum number of refreshes
<i>count</i>	Set the maximum number of host refresh

Command Mode

- /exec/configure

fabric forwarding limit-vlan-mac

[no] fabric forwarding limit-vlan-mac <max-limit>

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
limit-vlan-mac	Maximum number of end-hosts allowed to have the same (vlan, MAC) mapping in a given vrf (Default is 2048)
<i>max-limit</i>	Set max-limit

Command Mode

- /exec/configure

fabric forwarding mode anycast-gateway

{ fabric forwarding mode anycast-gateway } | { no fabric forwarding mode }

Syntax Description

no	Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
mode	Forwarding Modes
anycast-gateway	Anycast Gateway Forwarding Mode

Command Mode

- /exec/configure/if-vlan /exec/configure/if-vlan-range

fabric forwarding selective-host-probe

[no] fabric forwarding selective-host-probe

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
selective-host-probe	Trigger unconditional host probe

Command Mode

- /exec/configure

fabric multicast event-history bgp

```
[no] fabric multicast event-history bgp { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
bgp	BGP events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history ha

[no] fabric multicast event-history ha { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
ha	ha events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history hmm

```
[no] fabric multicast event-history hmm { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
hmm	HMM events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history isis

[no] fabric multicast event-history isis { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
isis	ISIS events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history m2rib

[no] fabric multicast event-history m2rib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
m2rib	M2RIB events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history m6rib

[no] fabric multicast event-history m6rib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
m6rib	M6RIB events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history mrib

[no] fabric multicast event-history mrib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
mrib	MRIB events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history pim

```
[no] fabric multicast event-history pim { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
pim	PIM events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

fabric multicast event-history pim6

```
[no] fabric multicast event-history pim6 { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
fabric	Fabric
multicast	Configure multicast
event-history	Configure event-history buffer
pim6	PIM6 events for fabric multicast
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

failaction

[no] failaction { node { reassign | drop } | cluster drop } +

Syntax Description

no	(Optional) Negate a command or set its defaults
failaction	Configure failaction for PLB service
node	PLB failaction node
reassign	PLB failaction reassign
drop	PLB failaction drop
cluster	PLB failaction cluster

Command Mode

- /exec/configure/plb

failaction

```
[no] failaction { [ node { reassign | drop | least-bucket | per-bucket } ] | [ bucket { distribute } ] | [ cluster drop ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
failaction	ITD failaction
node	(Optional) ITD failaction node
reassign	(Optional) ITD failaction reassign
drop	(Optional) ITD failaction drop
least-bucket	(Optional) ITD failaction least-bucket node
per-bucket	(Optional) ITD failaction per-bucket node
bucket	(Optional) ITD failaction bucket reassign
distribute	(Optional) ITD failaction distribute reassign
cluster	(Optional) ITD failaction cluster

Command Mode

- /exec/configure/itd

fast-convergence

[no] fast-convergence

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-convergence	Configure vPC fast convergence

Command Mode

- /exec/configure/vpc-domain

fast-convergence

fast-convergence | no fast-convergence

Syntax Description

no	Negate a command or set its defaults
fast-convergence	Enable vPC fast-convergence

Command Mode

- /exec/configure/vpc-domain

fast-external-fallover

[no] fast-external-fallover

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-external-fallover	Immediately reset the session if the link to a directly connected BGP peer goes down

Command Mode

- /exec/configure/router-bgp

fast-flood enable

[no] fast-flood enable

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
enable	Turn on fast-flooding

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

fast-flood enable

[no] fast-flood enable

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
enable	Turn on fast-flooding

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

fast-flood enable

[no] fast-flood enable

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
enable	Turn on fast-flooding

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

fast-flood interval

[no] fast-flood interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
interval	Duration/interval of the fast-flood timer.
<i>interval</i>	Specify the value (ms)

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

fast-flood interval

[no] fast-flood interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
interval	Duration/interval of the fast-flood timer.
<i>interval</i>	Specify the value (ms)

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

fast-flood interval

[no] fast-flood interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-flood	Fast flood the LSP's
interval	Duration/interval of the fast-flood timer.
<i>interval</i>	Specify the value (ms)

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

fast-reload

```
fast-reload { [ nxos <uri> | trigger-gr | save-config | [ non-interruptive | nosrg ] ] + | force-all [ nxos <uri> ] +
} [ override ]
```

Syntax Description

fast-reload	fast-reload software
nxos	(Optional) boot-variable name
<i>uri</i>	(Optional) Enter image uri
non-interruptive	(Optional) Non-Interruptive image upgrade
nosrg	(Optional) nosrg
override	(Optional) Do fast-reload without impact check
trigger-gr	(Optional) Enable BGP GR for compatible peers
save-config	(Optional) Save running-config to startup-config before fast-reload
force-all	Force upgrade the system

Command Mode

- /exec

fast-reload network-os

fast-reload network-os <uri>

Syntax Description

fast-reload	fast-reload software
network-os	non-cisco OS
<i>uri</i>	Enter image uri

Command Mode

- /exec

fast-reroute

[no] fast-reroute | fast-reroute [node-protect | bw-protect] +

Syntax Description

no	Negate a command or set its defaults
fast-reroute	Specify mpls tunnel can be fast-rerouted
node-protect	(Optional) node protection desired
bw-protect	(Optional) bandwidth protection desired

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

fast-reroute backup-prot-preempt optimize-bw

[no] fast-reroute backup-prot-preempt optimize-bw | no fast-reroute timers promotion | fast-reroute timers promotion <seconds>

Syntax Description

no	(Optional) Negate a command or set its defaults
fast-reroute	fast-reroute parameters
backup-prot-preempt	Preemption algorithm for backup tunnels
optimize-bw	Reduce bandwidth wastage (default: minimize LSPs preempted)
timers	configure fast-reroute timer
promotion	Configure how often we scan for LSP backup promotion
<i>seconds</i>	seconds between promotions (0 disables promotion.)

Command Mode

- /exec/configure/te

fcdroplateny network

[no] fcdroplateny { network <i0> [vsan <i1>] | switch <i2> }

Syntax Description

no	(Optional) Negate a command or set its defaults
fcdroplateny	configure switch or network latency
network	network latency in milliseconds
<i>i0</i>	network latency in milliseconds
vsan	(Optional) VSAN id range
<i>i1</i>	(Optional)
switch	switch latency in milliseconds
<i>i2</i>	switch latency in milliseconds

Command Mode

- /exec/configure

fcoe

[no] fcoe

Syntax Description

no	(Optional) Negate a command or set its default
fcoe	FCOE Congiguration

Command Mode

- /exec/configure/vlan

fcoe

[no] fcoe

Syntax Description

no	(Optional) Negate a command or set its defaults
fcoe	create fcoe associate between fex and switch

Command Mode

- /exec/configure/fex

fcoe enable-fex

[no] fcoe enable-fex

Syntax Description

no	(Optional) Negate a command or set its defaults
fcoe	FCOE command
enable-fex	Enables FCoE over FEX HIF interfaces

Command Mode

- /exec/configure

fcoe fcf-priority

fcoe fcf-priority <i0> | no fcoe fcf-priority

Syntax Description

no	Negate a command or set its defaults
fcoe	FCOE command
fcf-priority	FCF priority specification
<i>i0</i>	Enter FCF priority

Command Mode

- /exec/configure

fcoe fcmmap

fcoe fcmmap <i0> | no fcoe fcmmap

Syntax Description

no	Negate a command or set its defaults
fcoe	FCOE command
fcmmap	FC MAP specification
<i>i0</i>	Enter FCMAP

Command Mode

- /exec/configure

fcoe fka-adv-period

fcoe fka-adv-period <i0> | no fcoe fka-adv-period

Syntax Description

no	Negate a command or set its defaults
fcoe	FCOE command
fka-adv-period	FKA Advertisement Period
<i>i0</i>	FKA Advertisement Period (in sec)

Command Mode

- /exec/configure

fcoe vloopback

fcoe vloopback | no fcoe vloopback

Syntax Description

no	Negate a command or set its defaults
fcoe	FCOE command
vloopback	VFID check for VE ports

Command Mode

- /exec/configure

fcoe vsan

fcoe vsan <tran-id> | no fcoe vsan

Syntax Description

no	Negate a command or set its default
fcoe	FCOE Congiguration
vsan	Translated VSAN Status
<i>tran-id</i>	Enter VSAN-ID being associated with VLAN-ID

Command Mode

- /exec/configure/vlan

fctimer D_S_TOV

[no] fctimer D_S_TOV <i0> [vsan <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
D_S_TOV	D_S_TOV in milliseconds(5000-10000)
<i>i0</i>	D_S_TOV in milliseconds(5000-10000)
vsan	(Optional) Specify VSAN id
<i>i1</i>	(Optional) VSAN id

Command Mode

- /exec/configure

fctimer E_D_TOV

[no] fctimer E_D_TOV <i0> [vsan <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
E_D_TOV	E_D_TOV in milliseconds(1000-4000)
<i>i0</i>	E_D_TOV in milliseconds(1000-4000)
vsan	(Optional) Specify VSAN id
<i>il</i>	(Optional) VSAN id

Command Mode

- /exec/configure

fctimer R_A_TOV

[no] fctimer R_A_TOV <i0> [vsan <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
R_A_TOV	R_A_TOV in milliseconds(5000-10000)
<i>i0</i>	R_A_TOV in milliseconds(5000-10000)
vsan	(Optional) Specify VSAN id
<i>i1</i>	(Optional) VSAN id

Command Mode

- /exec/configure

fctimer abort

[no] fctimer abort

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
abort	abort the fctimer configuration commands

Command Mode

- /exec/configure

fctimer commit

[no] fctimer commit

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
commit	commit the fctimer configuration commands

Command Mode

- /exec/configure

fctimer distribute

[no] fctimer distribute

Syntax Description

no	(Optional) Negate a command or set its defaults
fctimer	configure fibre channel timers
distribute	Enable distribution of fctimer configuration using CFS

Command Mode

- /exec/configure

feature-set

feature-set <fs>

Syntax Description

feature-set	Enable feature-set
<i>fs</i>	allow feature-set

Command Mode

- /exec/configure

feature-set

[no] feature-set <fs>

Syntax Description

no	Negate a command or set its defaults
feature-set	Enable feature-set
fs	allow feature-set

Command Mode

- /exec/configure

feature

[no] feature <arg1>

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Feature name
<i>arg1</i>	Enter feature name

Command Mode

- /exec/configure/rolefeaturegrp

feature analytics

[no] feature analytics

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
analytics	Enable/Disable Analytics!!!

Command Mode

- /exec/configure

feature bash-shell

[no] feature bash-shell

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
bash-shell	Enable/Disable bash-shell

Command Mode

- /exec/configure

feature bfd

[no] feature bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
bfd	bfd

Command Mode

- /exec/configure

feature bgp

[no] feature bgp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
bgp	Enable/Disable Border Gateway Protocol (BGP)

Command Mode

- /exec/configure

feature catena

[no] feature catena

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
catena	Enable/Disable catena

Command Mode

- /exec/configure

feature container-tracker

[no] feature container-tracker

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
container-tracker	Enable/Disable NXOS Container Tracker

Command Mode

- /exec/configure

feature dhcp

[no] feature dhcp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
dhcp	Enable/Disable DHCP Manager

Command Mode

- /exec/configure

feature dot1x

[no] feature dot1x

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
dot1x	Enable/Disable dot1x

Command Mode

- /exec/configure

feature eigrp

[no] feature eigrp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
eigrp	Enable/Disable Enhanced Interior Gateway Routing Protocol (EIGRP)

Command Mode

- /exec/configure

feature evb

[no] feature evb

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
evb	Enable/Disable Edge Virtual Bridge (EVB)

Command Mode

- /exec/configure

feature evmed

[no] feature evmed

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
evmed	Enable/Disable Generic event detectors

Command Mode

- /exec/configure

feature fabric forwarding

[no] feature fabric forwarding

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
fabric	Enable/Disable Fabric Services
forwarding	Enable/Disable Fabric Forwarding Protocol: Host Mobility Manager (HMM)

Command Mode

- /exec/configure

feature flexlink

[no] feature flexlink

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
flexlink	Enable/Disable Flexlink

Command Mode

- /exec/configure

feature grpc

[no] feature grpc

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
grpc	Enable/Disable grpc Services

Command Mode

- /exec/configure

feature hardware-telemetry

[no] feature hardware-telemetry

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
hardware-telemetry	Enable/Disable Hardware Telemetry

Command Mode

- /exec/configure

feature hsrp

[no] feature hsrp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
hsrp	Enable/Disable Hot Standby Router Protocol (HSRP)

Command Mode

- /exec/configure

feature icam

[no] feature icam

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
icam	Enable/Disable icam

Command Mode

- /exec/configure

feature imp

[no] feature imp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
imp	Enable/Disable IMP

Command Mode

- /exec/configure

feature interface-vlan

[no] feature interface-vlan

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
interface-vlan	Enable/Disable interface vlan

Command Mode

- /exec/configure

feature isis

[no] feature isis

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
isis	Enable/Disable IS-IS Unicast Routing Protocol (IS-IS)

Command Mode

- /exec/configure

feature itd

[no] feature itd

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
itd	Enable/Disable ITD

Command Mode

- /exec/configure

feature lacp

[no] feature lacp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
lacp	Enable/Disable LACP

Command Mode

- /exec/configure

feature ldap

[no] feature ldap

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ldap	Enable/Disable ldap

Command Mode

- /exec/configure

feature lldp

[no] feature lldp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
lldp	Enable/Disable LLDP

Command Mode

- /exec/configure

feature msdp

[no] feature msdp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
msdp	Enable/Disable Multicast Source Discovery Protocol (MSDP)

Command Mode

- /exec/configure

feature mvpn

[no] feature mvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
mvpn	Multicast Virtual Private Networks.

Command Mode

- /exec/configure

feature nat

[no] feature nat

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
nat	Enable/Disable NAT

Command Mode

- /exec/configure

feature nbm

[no] feature nbm

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable a feature
nbm	Enable/Disable Non Blocking Multicast (NBM) feature

Command Mode

- /exec/configure

feature netconf

[no] feature netconf

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
netconf	Enable/Disable netconf Services

Command Mode

- /exec/configure

feature ngmvpn

[no] feature ngmvpn

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ngmvpn	Enable/Disable EVPN/MVPN features

Command Mode

- /exec/configure

feature ngoam

[no] feature ngoam

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ngoam	Enable/Disable ngoam

Command Mode

- /exec/configure

feature ngoam

[no] feature ngoam

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ngoam	Enable/Disable ngoam

Command Mode

- /exec/configure

feature npiv

[no] feature npiv

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features

Command Mode

- /exec/configure

feature ntp

[no] feature ntp

Syntax Description

no	(Optional) Negate a command or set its default
feature	Command to enable/disable features
ntp	Enable/Disable NTP

Command Mode

- /exec/configure

feature nv overlay

[no] feature nv overlay

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
nv	Enable/Disable VxLAN
overlay	Enable/Disable VxLAN

Command Mode

- /exec/configure

feature nxapi

[no] feature nxapi

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
nxapi	Enable/Disable nxapi

Command Mode

- /exec/configure

feature nxdb

[no] feature nxdb

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
nxdb	Enable/Disable nxdb

Command Mode

- /exec/configure

feature nxsdk

[no] feature nxsdk

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
nxsdk	Enable/Disable nxsdk Services

Command Mode

- /exec/configure

feature openflow

[no] feature openflow

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
openflow	Enable/Disable OpenFlow agent

Command Mode

- /exec/configure

feature openflow

[no] feature openflow

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
openflow	Enable/Disable OpenFlow agent

Command Mode

- /exec/configure

feature ospf

[no] feature ospf

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ospf	Enable/Disable Open Shortest Path First Protocol (OSPF)

Command Mode

- /exec/configure

feature ospfv3

[no] feature ospfv3

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ospfv3	Enable/Disable Open Shortest Path First Version 3 Protocol (OSPFv3)

Command Mode

- /exec/configure

feature password encryption aes

[no] feature password encryption aes

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Enable the feature
password	Credential(s) for the user(s)/device(s)
encryption	Strong encryption for credential(s)
aes	Encrypt using AES encryption standard

Command Mode

- /exec/configure

feature pbr

[no] feature pbr

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
pbr	Enable/Disable Policy Based Routing(PBR)

Command Mode

- /exec/configure

feature pim

[no] feature pim

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
pim	Enable/Disable Protocol Independent Multicast (PIM)

Command Mode

- /exec/configure

feature pim6

[no] feature pim6

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
pim6	Enable/Disable Protocol Independent Multicast(PIM) for IPv6

Command Mode

- /exec/configure

feature plb

[no] feature plb

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
plb	Enable/Disable Pervasive Load Balancing feature

Command Mode

- /exec/configure

feature poap

[no] feature poap

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
poap	Enable/Disable POAP

Command Mode

- /exec/configure

feature poe

[no] feature poe

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable a feature
poe	Enable/Disable Power over Ethernet(PoE) feature

Command Mode

- /exec/configure

feature pong

[no] feature pong

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
pong	Enable/Disable Pong

Command Mode

- /exec/configure

feature port-security

[no] feature port-security

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable eth port security features
port-security	Enable/Disable port-security

Command Mode

- /exec/configure

feature private-vlan

[no] feature private-vlan

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
private-vlan	Enable/Disable private-vlan

Command Mode

- /exec/configure

feature privilege

[no] feature privilege

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
privilege	Enable/Disable IOS type privilege level support

Command Mode

- /exec/configure

feature ptp

[no] feature ptp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ptp	Enable/Disable PTP

Command Mode

- /exec/configure

feature restconf

[no] feature restconf

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
restconf	Enable/Disable restconf Services

Command Mode

- /exec/configure

feature rip

[no] feature rip

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
rip	Enable/Disable Routing Information Protocol (RIP)

Command Mode

- /exec/configure

feature scheduler

[no] feature scheduler

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
scheduler	Enable/Disable scheduler

Command Mode

- /exec/configure

feature scp-server

[no] feature scp-server

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
scp-server	Enable/Disable SCP server

Command Mode

- /exec/configure

feature sflow

[no] feature sflow

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
sflow	Enable/Disable sFlow agent

Command Mode

- /exec/configure

feature sftp-server

[no] feature sftp-server

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
sftp-server	Enable/Disable SFTP server

Command Mode

- /exec/configure

feature signature-verification

[no] feature signature-verification

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
signature-verification	Enable image signature verification

Command Mode

- /exec/configure

feature sla responder

[no] feature sla responder

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
sla	Enable/Disable SLA
responder	Enable/Disable responder part of SLA

Command Mode

- /exec/configure

feature sla sender

[no] feature sla sender

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
sla	Enable/Disable SLA
sender	Enable/Disable sender part of SLA

Command Mode

- /exec/configure

feature sla twamp-server

[no] feature sla twamp-server

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
sla	Enable/Disable SLA
twamp-server	Enable/Disable twamp-server part of SLA

Command Mode

- /exec/configure

feature smart-channel

[no] feature smart-channel

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
smart-channel	Enable/Disable smart-channel

Command Mode

- /exec/configure

feature ssh

[no] feature ssh

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
ssh	Enable/Disable ssh

Command Mode

- /exec/configure

feature tacacs

[no] feature tacacs +

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features

Command Mode

- /exec/configure

feature telnet

[no] feature telnet

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
telnet	Enable/Disable telnet

Command Mode

- /exec/configure

feature tunnel

[no] feature tunnel

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
tunnel	Enable/Disable Tunnel Manager

Command Mode

- /exec/configure

feature udd

[no] feature udd

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
udd	Enable/Disable UDLD

Command Mode

- /exec/configure

feature vmtracker

[no] feature vmtracker

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vmtracker	Enable/Disable VM Tracker feature

Command Mode

- /exec/configure

feature vn-segment-vlan-based

[no] feature vn-segment-vlan-based

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vn-segment-vlan-based	Enable/Disable VLAN based VN segment

Command Mode

- /exec/configure

feature vpc

[no] feature vpc

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vpc	Enable/Disable VPC (Virtual Port Channel)

Command Mode

- /exec/configure

feature vrrp

[no] feature vrrp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vrrp	Enable/Disable Virtual Router Redundancy Protocol (VRRP)

Command Mode

- /exec/configure

feature vrrpv3

[no] feature vrrpv3

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vrrpv3	Enable/Disable Virtual Router Redundancy Protocol (VRRP) version 3

Command Mode

- /exec/configure

feature vtp

[no] feature vtp

Syntax Description

no	(Optional) Negate a command or set its defaults
feature	Command to enable/disable features
vtp	Enable/Disable VTP

Command Mode

- /exec/configure

fec

fec <fec_val_old> | no fec [<fec_val_old>]

Syntax Description

no	Negate a command or set its defaults
fec	Forwarding error correction
<i>fec_val_old</i>	Interface FEC options

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

fec

fec <fec_val> | no fec [<fec_val>]

Syntax Description

no	Negate a command or set its defaults
fec	Forwarding error correction
<i>fec_val</i>	Interface FEC options

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

fec

fec <fec_val> | no fec [<fec_val>]

Syntax Description

no	Negate a command or set its defaults
fec	Forwarding error correction
<i>fec_val</i>	Interface FEC options

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

fhrp delay minimum

[no] fhrp delay minimum | fhrp delay minimum <delay>

Syntax Description

no	Negate a command or set its defaults
fhrp	FHRP interface configuration commands
delay	Configure FHRP delay
minimum	minimum delay
<i>delay</i>	Seconds to delay

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan

fhrp delay reload

[no] fhrp delay reload | fhrp delay reload <delay>

Syntax Description

no	Negate a command or set its defaults
fhrp	FHRP interface configuration commands
delay	Configure FHRP delay
reload	reload delay
<i>delay</i>	Seconds to delay

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan

filter

[no] filter [subject-name <s0> | altname-email <s1> | altname-upn <s2>]

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Configure mapping filter
subject-name	(Optional) Subject name of the certificate
<i>s0</i>	(Optional) Subject name
altname-email	(Optional) Email id as an alternate name
<i>s1</i>	(Optional) Email id
altname-upn	(Optional) User principal name as an alternate name
<i>s2</i>	(Optional) User principal name

Command Mode

- /exec/configure/certmap-filter

filter access-group

[no] filter access-group <acl-name> [allow-sharing]

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Filter configuration
access-group	access control group
<i>acl-name</i>	access control list name
allow-sharing	(Optional) allow up to 4 access control groups on same source interface

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

filter ip

[no] filter ip <src_ip> <src_mask> <dst_ip> <dst_mask>

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Set SPAN filter options
ip	Set SPAN IP filtering options
<i>src_ip</i>	Set source IP address
<i>src_mask</i>	Set source IP mask
<i>dst_ip</i>	Set destination IP address
<i>dst_mask</i>	Set destination IP mask

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

filter ipv6 access-group

[no] filter ipv6 access-group <acl-name> [allow-sharing]

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Filter configuration
ipv6	ipv6 access group
access-group	access control group
<i>acl-name</i>	access control list name
allow-sharing	(Optional) allow up to 4 access control groups on same source interface

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

filter out

[no | default] { filter-list <fltrlist-name> } { out | in }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
filter-list	Apply AS-PATH filter-list
<i>fltrlist-name</i>	Name of filter-list
out	Apply policy to outgoing routes
in	Apply policy to incoming routes

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

filter tx control-packets

[no] filter tx control-packets

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Set SPAN filter options
tx	Set SPAN tx filtering options
control-packets	Filter out CPU generated packets and SPAN only data packets

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

filter vlan

[no] filter vlan <vlan_mrange> [include-untagged]

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Filter configuration
vlan	Vlan type
<i>vlan_mrange</i>	
include-untagged	(Optional) Include untagged frames on port with Layer 3 subinterfaces

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

filter vlan include-untagged

[no] filter vlan include-untagged

Syntax Description

no	(Optional) Negate a command or set its defaults
filter	Filter configuration
vlan	Vlan type
include-untagged	Include untagged frames on port with Layer 3 subinterfaces

Command Mode

- /exec/configure/config-monitor

find

find <s0>

Syntax Description

find	Find a file below the current directory
s0	Enter the filename prefix to search

Command Mode

- /exec

fips debug errors debug

[no] fips debug errors { debug-lc-post-on-maint | reset-debug-lc-post-on-maint }

Syntax Description

no	(Optional) Negate a command or set its defaults
fips	Enable/Disable FIPS mode
debug	Introduce errors into FIPS tests
errors	Introduce errors
debug-lc-post-on-maint	Run the switch on debug mode for fips maintenance state
reset-debug-lc-post-on-maint	Reset the mode from debug-lc-post-on-maint

Command Mode

- /exec/

fips mode enable

[no] fips mode enable

Syntax Description

no	(Optional) Negate a command or set its defaults
fips	Enable/Disable FIPS mode
mode	FIPS mode
enable	Enable/Disable FIPS mode

Command Mode

- /exec/configure

flow-count

[no] flow-count <count>

Syntax Description

flow-count	Flow count throttle for drop events
<i>count</i>	<1-32767>

Command Mode

- /exec/configure/config-fte-event/group-drop-events

flow-count

[no] flow-count <count>

Syntax Description

flow-count	Flow count throttle for drop events
<i>count</i>	<1-32767>

Command Mode

- /exec/configure/config-fte-event/group-latency-events

flow exporter

[no] flow exporter <exportername>

Syntax Description

flow	Enable/Disable NetFlow configuration
exporter	Define a Flow Exporter
<i>exportername</i>	Name of Flow Exporter

Command Mode

- /exec/configure

flow forward

[no] flow { forward | reverse }

Syntax Description

no	(Optional) Negate a command or set its defaults
flow	Configure ngoam flow
forward	Ngoam forward flow
reverse	Ngoam reverse flow

Command Mode

- /exec/configure/configngoamprofile

flow monitor

[no] flow monitor <monitorname>

Syntax Description

flow	Enable/Disable NetFlow configuration
monitor	Define a Flow Monitor
<i>monitorname</i>	Name of Flow Monitor

Command Mode

- /exec/configure

flow record

[no] flow record <recordname>

Syntax Description

flow	Enable/Disable NetFlow configuration
record	Define a Flow Record
<i>recordname</i>	Record name

Command Mode

- /exec/configure

flow timeout

{ [no] flow timeout <time> | no flow timeout }

Syntax Description

flow	Enable/Disable NetFlow configuration
timeout	Define a Flow Timeout
<i>time</i>	Time in seconds (flush-cache-Only)

Command Mode

- /exec/configure

flowcontrol hardware

[no] flowcontrol hardware

Syntax Description

no	(Optional) Negate a command or set its defaults
flowcontrol	Set flow control
hardware	Set hardware flowcontrol

Command Mode

- /exec/configure/com1

flowcontrol receive

```
flowcontrol { receive { <rx_flowctrl> } | send { <tx_flowctrl> } } | no flowcontrol { receive [ { <rx_flowctrl>
} ] | send [ { <tx_flowctrl> } ] }
```

Syntax Description

no	Negate a command or set its defaults
flowcontrol	Configure interface flowcontrol
receive	Receive pause frames
<i>rx_flowctrl</i>	Receive flow control
send	Send pause frames
<i>tx_flowctrl</i>	Send flow control

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes on a non-graceful controlled restart

Command Mode

- /exec/configure/router-ospf3

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes in RIB during restart

Command Mode

- /exec/configure/router-rip

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes on non-graceful controlled restart

Command Mode

- /exec/configure/router-isis

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes in RIB during restart

Command Mode

- /exec/configure/router-eigrp

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes on a non-graceful controlled restart

Command Mode

- /exec/configure/router-ospf

flush-routes

[no] flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
flush-routes	Flush routes in RIB upon controlled restart

Command Mode

- /exec/configure/router-bgp

follow

follow <name> | no follow

Syntax Description

no	Negate a command or set its defaults
follow	Group to be followed
<i>name</i>	master name string to follow

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

format

format <uri>

Syntax Description

format	Format disks
<i>uri</i>	destination filesystem path

Command Mode

- /exec

format bootflash

format bootflash:

Syntax Description

format	Format disks
bootflash:	Format bootflash:

Command Mode

- /exec

format bootflash check-filesystem

format bootflash: check-filesystem

Syntax Description

format	Format disks
bootflash:	Format bootflash:
check-filesystem	Format bootflash: and fix any errors in file system

Command Mode

- /exec

format usb1

format usb1:

Syntax Description

format	Format disks
usb1:	Format usb1:

Command Mode

- /exec

forward

[no] forward

Syntax Description

no	(Optional) Negate a command or set its defaults
forward	Configure paths

Command Mode

- /exec/configure/mpls_static/ipv4/lsp/inlabel

forwarding-adjacency

[no] forwarding-adjacency | forwarding-adjacency [holdtime <msec>]

Syntax Description

no	Negate a command or set its defaults
forwarding-adjacency	Treat this tunnel as a Forwarding Adjacency
holdtime	(Optional) How long in msec to wait upon flooding a down Forwarding Adjacency
<i>msec</i>	(Optional) Holdtime on MPLS TE Down

Command Mode

- /exec/configure/if-te

fragments

[no] fragments <opt_type>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>opt_type</i>	frag_op_type

Command Mode

- /exec/configure/ipacl /exec/configure/ipv6acl

frequency

{ { no | default } frequency | frequency <seconds> }

Syntax Description

no	
default	Set a command to its defaults
frequency	Frequency of an operation
<i>seconds</i>	Frequency in seconds

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http

from to

```
[no] { { from <frm-list> to <to-val> } | { default { <value> | copy | ignore } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
from	Map values from this
<i>frm-list</i>	Original list of values which are to be mapped
to	Map values to this
<i>to-val</i>	New mapped value
default	map default values
<i>value</i>	default value to be set
copy	Do a default copy
ignore	Ignore any unspecified values

Command Mode

- /exec/configure/table-map

from to

```
{ [ no ] { { from <frm-list> to <to-val> } | { default <value> } } } | default copy
```

Syntax Description

no	(Optional) Negate a command or set its defaults
from	Map values from this
<i>frm-list</i>	Original list of values which are to be mapped
to	Map values to this
<i>to-val</i>	New mapped value
default	map default values
<i>value</i>	default value to be set
copy	Do a default copy

Command Mode

- /exec/configure/def-tmap

fte event

[no] fte event <eventname>

Syntax Description

fte	Enable/Disable FTE configuration
event	Define a FTE event
<i>eventname</i>	Event name

Command Mode

- /exec/configure/config-fte

fte exporter

[no] fte exporter <exportername>

Syntax Description

fte	Enable/Disable Flow Table Events configuration
exporter	Define a events Exporter
<i>exportername</i>	Name of event Exporter

Command Mode

- /exec/configure/config-fte

fte monitor

[no] fte monitor <monitorname>

Syntax Description

fte	Enable/Disable FTE configuration
monitor	Define a FTE Monitor
<i>monitorname</i>	Name of FTE Monitor

Command Mode

- /exec/configure/config-fte

fte record

[no] fte record <recordname>

Syntax Description

fte	Enable/Disable FTE configuration
record	Define a FTE Record
<i>recordname</i>	Record name

Command Mode

- /exec/configure/config-fte

fte system monitor

[no] fte system monitor <monitorname>

Syntax Description

fte	change fte global settings
system	global config
monitor	fte Monitor to be applied
<i>monitorname</i>	ssx Monitor to be applied

Command Mode

- /exec/configure/config-fte

ftrace

```
ftrace [ { set-opt { option <n0> <v0> | filter <f0> <v0> } { proc <p0> | buf_size <b0> } [ <s0> ] } | { reset { all | filter <f0> | trace <s0> } } | { enable { inband | kernel | lcnd <i0> | process <i0> | trace } } | { list { filters <f0> | curr_tracer | all } } | { debug { on | off } } | { dump { all | traces } } ]
```

Syntax Description

ftrace	Run ftrace tool to enable/disable kernel/process tracing
set-opt	(Optional) Set ftrace tracing options available
reset	(Optional) Reset ftrace options to defaults, disable tracing
enable	(Optional) Enable ftrace tracing with given options
list	(Optional) List ftrace available options/filters/events
debug	(Optional) Ftrace based debug trace enable/disable
dump	(Optional) Dump traces collected in ftrace circular buffer
all	(Optional) Act on all available datasets
lcnd	(Optional) Trace proc/pid specific lcnd inband driver calls
inband	(Optional) Trace inband driver + netstack functions
kernel	(Optional) Trace kernel function of sched, net, inband
process	(Optional) Trace proc/pid specific kernel function calls
trace	(Optional) Enable tracing_on in ftrace settings
option	(Optional) Name of ftrace option to be set
filter	(Optional) Set ftrace filter to be applied
proc	(Optional) Set ftrace process to be traced
buf_size	(Optional) Set ftrace buffer size limits
filters	(Optional) list available ftrace filters
curr_tracer	(Optional) Print ftrace current tracer
traces	(Optional) Dump ftrace trace buffer contents
on	(Optional) Enable ftrace based debug tracing
off	(Optional) Dump ftrace trace buffer contents
i0	(Optional) pid of process to trace
f0	(Optional) name of ftrace filter to list/set

<i>n0</i>	(Optional) name of ftrace option to be set
<i>v0</i>	(Optional) value of ftrace option/filter to be set
<i>p0</i>	(Optional) pid of ftrace proc to be set
<i>b0</i>	(Optional) value of ftrace buffer size limit to set
<i>s0</i>	(Optional) name of ftrace option to be set/reset

Command Mode

- /exec



G Commands

- [generate type7_encrypted_secret](#), on page 1616
- [getnext](#), on page 1617
- [global-block](#), on page 1618
- [global ingress-replication protocol bgp](#), on page 1619
- [global suppress-arp](#), on page 1620
- [graceful-restart-helper](#), on page 1621
- [graceful-restart](#), on page 1622
- [graceful-restart](#), on page 1623
- [graceful-restart](#), on page 1624
- [graceful-restart](#), on page 1625
- [graceful-restart](#), on page 1626
- [graceful-restart](#), on page 1627
- [graceful-restart](#), on page 1628
- [graceful-restart](#), on page 1629
- [graceful-restart grace-period](#), on page 1630
- [graceful-restart grace-period](#), on page 1631
- [graceful-restart helper-disable](#), on page 1632
- [graceful-restart helper-disable](#), on page 1633
- [graceful-restart restart-time](#), on page 1634
- [graceful-restart stalepath-time](#), on page 1635
- [graceful-restart t3 manual](#), on page 1636
- [graceful-restart t3 manual](#), on page 1637
- [graceful-restart t3 manual](#), on page 1638
- [graceful consistency-check](#), on page 1639
- [grep](#), on page 1640
- [grep](#), on page 1641
- [grep](#), on page 1642
- [group drop-events](#), on page 1643
- [group latency-events](#), on page 1644
- [guestshell](#), on page 1645
- [gunzip](#), on page 1646
- [gzip](#), on page 1647

generate type7_encrypted_secret

generate type7_encrypted_secret

Syntax Description

generate	generate
type7_encrypted_secret	Type 7 Encrypted Secret

Command Mode

- /exec

getnext

| getnext

Syntax Description

	Pipe command output to filter
getnext	return next instance instead of specified one, or first instance if none specified (if supported by feature)

Command Mode

- /output

global-block

```
{ { global-block <min-srgb-label> <max-srgb-label> } | { no global-block } }
```

Syntax Description

no	Negate a command or set its defaults
global-block	Specify global block range for Segment Routing bindings
<i>min-srgb-label</i>	Minimum label value
<i>max-srgb-label</i>	Maximum label value

Command Mode

- /exec/configure/config-sr-mpls

global ingress-replication protocol bgp

[no] global ingress-replication protocol bgp

Syntax Description

no	(Optional) Negate a command or set its defaults
global	Global configurations for nve, inherited by VNIs
ingress-replication	Configure ingress replication
protocol	Control protocol to use
bgp	Border Gateway Protocol

Command Mode

- /exec/configure/if-nve

global suppress-arp

[no] global suppress-arp

Syntax Description

no	(Optional) Negate a command or set its defaults
global	Global configurations for nve, inherited by VNIs
suppress-arp	Enable ARP suppression

Command Mode

- /exec/configure/if-nve

graceful-restart-helper

[no] graceful-restart-helper

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart-helper	Configure Graceful Restart Helper mode functionality

Command Mode

- /exec/configure/router-bgp/vrf-cmds

graceful-restart

[no] graceful-restart

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

graceful-restart

[no] graceful-restart

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

graceful-restart

[no] graceful-restart [planned-only]

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
planned-only	(Optional) Enable graceful restart only for a planned restart

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

graceful-restart

{ { [no] [eigrp] graceful-restart } | { [no] nsf } }

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
graceful-restart	Peer resync without adjacency reset
nsf	Non-stop forwarding

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

graceful-restart

[no] graceful-restart [planned-only]

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
planned-only	(Optional) Enable graceful restart only for a planned restart

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

graceful-restart

```
graceful-restart [ timers { forwarding-holding <fwdg-holdtime> | max-recovery <recovery-time> |
neighbor-liveness <peer-liveness-time> } ] | no graceful-restart [ timers { forwarding-holding | max-recovery
| neighbor-liveness } ]
```

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Configure LDP Graceful Restart
timers	(Optional) Configure Graceful Restart timers
forwarding-holding	(Optional) Forwarding State Holding time
<i>fwdg-holdtime</i>	(Optional) seconds
max-recovery	(Optional) Max-Recovery time
<i>recovery-time</i>	(Optional) seconds
neighbor-liveness	(Optional) Neighbor-Liveness time
<i>peer-liveness-time</i>	(Optional) seconds

Command Mode

- /exec/configure/ldp

graceful-restart

[no] graceful-restart

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure Graceful Restart functionality

Command Mode

- /exec/configure/router-bgp/vrf-cmds

graceful-restart

[no] graceful-restart

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

graceful-restart grace-period

[no] graceful-restart grace-period <grace-period>

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
grace-period	Configure maximum interval to restart gracefully
<i>grace-period</i>	Grace period in seconds

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

graceful-restart grace-period

[no] graceful-restart grace-period <grace-period>

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
grace-period	Configure maximum interval to restart gracefully
<i>grace-period</i>	Grace period in seconds

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

graceful-restart helper-disable

[no] graceful-restart helper-disable

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
helper-disable	Disable helper mode

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

graceful-restart helper-disable

[no] graceful-restart helper-disable

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful-restart	Configure graceful restart
helper-disable	Disable helper mode

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

graceful-restart restart-time

graceful-restart restart-time <restart-time> | no graceful-restart restart-time [<restart-time>]

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Configure Graceful Restart functionality
restart-time	Maximum time for restart advertised to peers
<i>restart-time</i>	Restart time (seconds)

Command Mode

- /exec/configure/router-bgp/vrf-cmds

graceful-restart stalepath-time

graceful-restart stalepath-time <stalepath-time> | no graceful-restart stalepath-time [<stalepath-time>]

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Configure Graceful Restart functionality
stalepath-time	Maximum time to keep a restarting peer's stale routes
<i>stalepath-time</i>	Stalepath time (seconds)

Command Mode

- /exec/configure/router-bgp/vrf-cmds

graceful-restart t3 manual

graceful-restart t3 manual <sec> | no graceful-restart t3 manual [<sec>]

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS
t3	Set the T3 (RFC 3847) graceful restart timer
manual	Change manually T3 default value
sec	Specify T3 value (secs)

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

graceful-restart t3 manual

graceful-restart t3 manual <sec> | no graceful-restart t3 manual [<sec>]

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS
t3	Set the T3 (RFC 3847) graceful restart timer
manual	Change manually T3 default value
<i>sec</i>	Specify T3 value (secs)

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

graceful-restart t3 manual

graceful-restart t3 manual <sec> | no graceful-restart t3 manual [<sec>]

Syntax Description

no	Negate a command or set its defaults
graceful-restart	Enable graceful restart for IS-IS
t3	Set the T3 (RFC 3847) graceful restart timer
manual	Change manually T3 default value
<i>sec</i>	Specify T3 value (secs)

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

graceful consistency-check

[no] graceful consistency-check

Syntax Description

no	(Optional) Negate a command or set its defaults
graceful	Enable graceful features
consistency-check	Enable graceful type-1 consistency check

Command Mode

- /exec/configure/vpc-domain

grep

| { grep | egrep } [count | ignore-case | line-number | invert-match | word-exp | line-exp | <ctx> | next <num> | prev <num>] + <expr>

Syntax Description

	Pipe command output to filter
grep	Grep - print lines matching a pattern
egrep	Egrep - print lines matching a pattern
count	(Optional) Print a total count of matching lines only
ignore-case	(Optional) Ignore case difference when comparing strings
line-number	(Optional) Print each match preceded by its line number
invert-match	(Optional) Print only lines that contain no matches for <expr>
word-exp	(Optional) Print only lines where the match is a complete word
line-exp	(Optional) Print only lines where the match is a whole line
ctx	(Optional) Print <num> lines of context on each side of every match
next	(Optional) Print <num> lines of context after every matching line
prev	(Optional) Print <num> lines of context before every matching line
num	(Optional) Print <num> lines of context
expr	Search for the expression

Command Mode

- /output

grep

| { grep | egrep } [-c | -i | -n | -v | -w | -x | <ctx> | -A <num> | -B <num>] + <expr>

Syntax Description

	Pipe command output to filter
grep	Grep - print lines matching a pattern
egrep	Egrep - print lines matching a pattern
-c	(Optional) Print a total count of matching lines only
-i	(Optional) Ignore case difference when comparing strings
-n	(Optional) Print each match preceded by its line number
-v	(Optional) Print only lines that contain no matches for <expr>
-w	(Optional) Print only lines where the match is a complete word
-x	(Optional) Print only lines where the match is a whole line
ctx	(Optional) Print <num> lines of context on each side of every match
-A	(Optional) Print <num> lines of context after every matching line
-B	(Optional) Print <num> lines of context before every matching line
num	(Optional) Print <num> lines of context
expr	Search for the expression

Command Mode

- /output

grep

| { grep | egrep } [-c | -i | -n | -v | -w | -x | <ctx> | -A <num> | -B <num>] + [--] <expr>

Syntax Description

	Pipe command output to filter
grep	Grep
egrep	Egrep
-c	(Optional) Print a total count of matching lines only
-i	(Optional) Ignore case difference when comparing strings
-n	(Optional) Print each match preceded by its line number
-v	(Optional) Print only lines that contain no matches for <expr>
-w	(Optional) Print only lines where the match is a complete word
-x	(Optional) Print only lines where the match is a whole line
ctx	(Optional) Print <num> lines of context on each side of every match
-A	(Optional) Print <num> lines of context after every matching line
-B	(Optional) Print <num> lines of context before every matching line
num	(Optional) Print <num> lines of context
--	(Optional) --
expr	Search for the expression

Command Mode

- /output

group drop-events

[no] group drop-events

Syntax Description

group	Group for which the events need to be set
drop-events	Set events for drops

Command Mode

- /exec/configure/config-fte-event

group latency-events

[no] group latency-events

Syntax Description

group	Group for which the events need to be set
latency-events	Set events for latency events

Command Mode

- /exec/configure/config-fte-event

guestshell

```
guestshell [ { enable [ { package <enable_uri> } ] } | { upgrade [ { package <upgrade_uri> } ] } | { export {
  rootfs package <export_uri> } } | { disable } | { destroy } | { reboot } | <sync_cmd_name> | { resize { rootfs
  <gsh_rootfs> | cpu <gsh_cpu> | memory <gsh_memory> } } | { run { <cmd_args> } } ]
```

Syntax Description

guestshell	Request a guest shell
enable	(Optional) Enable the guest shell service
upgrade	(Optional) Upgrade the guest shell service package to a different version
export	(Optional) Export the guest shell
<i>export_uri</i>	(Optional) Destination file or directory path
disable	(Optional) Disable the guest shell service package
destroy	(Optional) Disable and uninstall the guest shell service package
<i>sync_cmd_name</i>	(Optional) Synchronize the contents of the guest shell to standby supervisor
reboot	(Optional) Deactivate and reactivate the guest shell service
resize	(Optional) Resize the existing/default guest shell parameters
rootfs	(Optional) Guest shell root filesystem disk image
<i>gsh_rootfs</i>	(Optional) New root filesystem size (in MB)
cpu	(Optional) System CPU share allocated to guest shell
<i>gsh_cpu</i>	(Optional) New CPU share allocation (as % of system CPU)
memory	(Optional) System memory allocated to guest shell
<i>gsh_memory</i>	(Optional) New memory size (in MB)
package	(Optional) Package location
<i>enable_uri</i>	(Optional) File name for the virtual service
<i>upgrade_uri</i>	(Optional) File name for the virtual service
run	(Optional) Execute/run program in the guest shell
<i>cmd_args</i>	(Optional) Executable with optional arguments

Command Mode

- /exec

gunzip

gunzip <uri0>

Syntax Description

gunzip	Uncompresses LZ77 coded files
<i>uri0</i>	Enter filename (filename must have .gz extension)

Command Mode

- /exec

gzip

gzip <uri0>

Syntax Description

gzip	Compresses file using LZ77 coding
<i>uri0</i>	Enter filename

Command Mode

- /exec



H Commands

- [ha-policy single](#), on page 1652
- [hardware-telemetry fte](#), on page 1653
- [hardware-telemetry inband-telemetry](#), on page 1654
- [hardware-telemetry postcard-telemetry](#), on page 1655
- [hardware-telemetry ssx](#), on page 1656
- [hardware access-list lou resource threshold](#), on page 1657
- [hardware access-list match inner-header](#), on page 1658
- [hardware access-list module](#), on page 1659
- [hardware access-list tcam label ing-racl 9](#), on page 1660
- [hardware access-list tcam region](#), on page 1661
- [hardware access-list tcam region double-wide](#), on page 1662
- [hardware access-list tcam region qualify udf](#), on page 1663
- [hardware access-list tcam region tcp-nat](#), on page 1664
- [hardware ecmp hash-offset](#), on page 1665
- [hardware ecmp hash-polynomial](#), on page 1666
- [hardware ejector enable](#), on page 1667
- [hardware fan-zone raise-speed](#), on page 1668
- [hardware forwarding l3 resource route non-deterministic](#), on page 1669
- [hardware forwarding unicast trace](#), on page 1670
- [hardware ip glean throttle](#), on page 1671
- [hardware ip glean throttle maximum](#), on page 1672
- [hardware ip glean throttle syslog](#), on page 1673
- [hardware ip glean throttle timeout](#), on page 1674
- [hardware ipv6 glean throttle](#), on page 1675
- [hardware ipv6 glean throttle maximum](#), on page 1676
- [hardware ipv6 glean throttle syslog](#), on page 1677
- [hardware ipv6 glean throttle timeout](#), on page 1678
- [hardware module boot-order reverse](#), on page 1679
- [hardware multicast global-tx-span](#), on page 1680
- [hardware profile buffer info poll-interval timer](#), on page 1681
- [hardware profile buffer info port-threshold threshold](#), on page 1682
- [hardware profile buffer monitor unicast](#), on page 1683
- [hardware profile buffer qosgroup threshold](#), on page 1684

- hardware profile buffer span-threshold, on page 1685
- hardware profile ecmp auto-recovery threshold, on page 1686
- hardware profile ecmp resilient, on page 1687
- hardware profile ecmp template module, on page 1688
- hardware profile forwarding-mode, on page 1689
- hardware profile front portmode, on page 1690
- hardware profile ipv6 alpm carve-value, on page 1691
- hardware profile ipv6 lpm-entries maximum, on page 1692
- hardware profile latency monitor, on page 1693
- hardware profile module, on page 1694
- hardware profile multicast flex-stats-enable, on page 1695
- hardware profile multicast max-limit, on page 1696
- hardware profile multicast max-limit lpm-entries, on page 1697
- hardware profile multicast nlb, on page 1698
- hardware profile multicast optimization disable, on page 1699
- hardware profile multicast prefer-source-tree, on page 1700
- hardware profile multicast rpf-check-optimization, on page 1701
- hardware profile multicast service-reflect port, on page 1702
- hardware profile multicast slow-receiver port, on page 1703
- hardware profile multicast syslog-threshold, on page 1704
- hardware profile openflow, on page 1705
- hardware profile packet-drop, on page 1706
- hardware profile pbr skip-selfip, on page 1707
- hardware profile pfc mmu buffer-reservation, on page 1708
- hardware profile portmode, on page 1709
- hardware profile statistics pstat, on page 1710
- hardware profile svi flex-stats-enable, on page 1711
- hardware profile tcam ipv6-sup-tcam match-inner, on page 1712
- hardware profile tcam region, on page 1713
- hardware profile tcam region span qualify udf, on page 1714
- hardware profile tcam region spanv6-l2 qualify udf, on page 1715
- hardware profile tcam region spanv6 qualify udf, on page 1716
- hardware profile tcam resource service-template, on page 1717
- hardware profile tcam resource template, on page 1718
- hardware profile tcam syslog-threshold, on page 1719
- hardware profile ucast6 lpm-65-to-127-max-limit, on page 1720
- hardware profile ucast6 max-limit, on page 1721
- hardware profile unicast enable-host-ecmp, on page 1722
- hardware profile unicast syslog-threshold, on page 1723
- hardware qos dynamic-buffer-sharing, on page 1724
- hardware qos fc rate-shaper, on page 1725
- hardware qos pfc mc-drop, on page 1726
- hardware sample-redirect module redirect-interface, on page 1727
- head, on page 1728
- header-type 2, on page 1729
- hello-interval, on page 1730

- hello-interval, on page 1731
- hello-interval, on page 1732
- history, on page 1733
- history, on page 1734
- history, on page 1735
- history, on page 1736
- history, on page 1737
- history, on page 1738
- holdtime, on page 1739
- hop-limit maximum, on page 1740
- hop-limit minimum, on page 1741
- hop, on page 1742
- host-reachability protocol, on page 1743
- host, on page 1744
- host group permit, on page 1745
- host source group permit, on page 1746
- hostname, on page 1747
- hostname dynamic, on page 1748
- hostname dynamic, on page 1749
- hostname dynamic, on page 1750
- hsrp, on page 1751
- hsrp anycast, on page 1752
- hsrp bfd, on page 1753
- hsrp bfd all-interfaces, on page 1754
- hsrp delay minimum, on page 1755
- hsrp force state vlan, on page 1756
- hsrp ipv6, on page 1757
- hsrp mac-refresh, on page 1758
- hsrp timers extended-hold, on page 1759
- hsrp use-bia, on page 1760
- hsrp version 1, on page 1761
- http get, on page 1762
- http proxy server, on page 1763
- human, on page 1764
- human, on page 1765
- hw-module logging onboard, on page 1766
- hw-module logging onboard, on page 1767

ha-policy single

ha-policy { single-sup <hap-change> | dual-sup <sw-change> } +

Syntax Description

ha-policy	Change HA policy for this VDC
<i>hap-change</i>	Change HA policy for this VDC
single-sup	Change HA policy for this VDC for single-sup situations
dual-sup	Change HA policy for this VDC for dual-sup situations
<i>sw-change</i>	Set hap policy

Command Mode

- /exec/configure/vdc

hardware-telemetry fte

[no] hardware-telemetry fte

Syntax Description

hardware-telemetry	Hardware telemetry configuration
fte	Enable/Disable Flow Table Events configuration

Command Mode

- /exec/configure

hardware-telemetry inband-telemetry

[no] hardware-telemetry inband-telemetry

Syntax Description

hardware-telemetry	Hardware telemetry configuration
inband-telemetry	Enable/Disable inband telemetry configuration

Command Mode

- /exec/configure

hardware-telemetry postcard-telemetry

[no] hardware-telemetry postcard-telemetry

Syntax Description

hardware-telemetry	Hardware telemetry configuration
postcard-telemetry	Enable/Disable postcard telemetry configuration

Command Mode

- /exec/configure

hardware-telemetry ssx

[no] hardware-telemetry ssx

Syntax Description

hardware-telemetry	Hardware Telemetry Configurations
ssx	enable Streaming Statistics Exporter Configurations

Command Mode

- /exec/configure

hardware access-list lou resource threshold

[no] hardware access-list lou resource threshold <threshold>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
access-list	Access Control List
lou	LOU
resource	hardware resource
threshold	port expansion threshold
<i>threshold</i>	value of threshold

Command Mode

- /exec/configure

hardware access-list match inner-header

[no] hardware access-list match inner-header

Syntax Description

no	(Optional) Negate the command or set its defaults
hardware	Change hardware usage settings
access-list	Access Control List
match	Match criteria in ACL
inner-header	Match inner header fields in IPinIP/GRE packets

Command Mode

- /exec/configure

hardware access-list module

[no] hardware access-list { resource-pooling | resource pooling } module <module-number>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Show hardware information
access-list	Access Control List
resource-pooling	Enable ACL programming across TCAM banks
resource	hardware resource
pooling	Enable ACL programming across TCAM banks
module	module number
<i>module-number</i>	specify module number

Command Mode

- /exec/configure

hardware access-list tcam label ing-racl 9

[no] hardware access-list tcam label ing-racl 9

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
access-list	Access Control List
tcam	Configure tcam parameters
label	Team entry label info
ing-racl	Ingress RACL region
9	Size in bits for BD-Labels allocated to Ingress-RACL region

Command Mode

- /exec/configure

hardware access-list tcam region

[no] hardware access-list tcam region <type> <tcam_size>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
access-list	Access Control List
tcam	Configure tcam parameters
region	Configure tcam region
<i>type</i>	Region type
<i>tcam_size</i>	Enter tcam size

Command Mode

- /exec/configure

hardware access-list tcam region double-wide

[no] hardware access-list tcam region <double-wide-region> <tcam_size> double-wide

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
access-list	Access Control List
tcam	Configure tcam parameters
region	Configure tcam region
<i>double-wide-region</i>	Region type
<i>tcam_size</i>	Enter tcam size
double-wide	Double Width

Command Mode

- /exec/configure

hardware access-list tcam region qualify udf

[no] hardware access-list tcam region <udf_tcam_type> qualify { udf | v6udf } { <udf_name> } +

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
access-list	Access Control List
tcam	Configure tcam parameters
region	Configure tcam region
<i>udf_tcam_type</i>	Region type
qualify	Configure UDFs to be qualified for region
udf	Configure UDF names
v6udf	Configure IPv6 UDF names
<i>udf_name</i>	UDF name

Command Mode

- /exec/configure

hardware access-list tcam region tcp-nat

[no] hardware access-list tcam region tcp-nat <tcam_size>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
access-list	Access Control List
tcam	Configure tcam parameters
region	Configure tcam region
tcp-nat	TCP NAT region within NAT region
<i>tcam_size</i>	Enter tcam size

Command Mode

- /exec/configure

hardware ecmp hash-offset

[no] hardware ecmp hash-offset <value> [concatenation] | no hardware ecmp hash-offset

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
ecmp	ECMP configuration
hash-offset	Configure hash offset
<i>value</i>	Hash offset 0-15 non-concatenate mode, 0-63 concatenate mode
concatenation	(Optional) Configure hash concatenation

Command Mode

- /exec/configure

hardware ecmp hash-polynomial

hardware ecmp hash-polynomial <poly-type> | no hardware ecmp hash-polynomial

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
ecmp	ECMP configuration
hash-polynomial	Configure hash polynomial
<i>poly-type</i>	Polynomial type

Command Mode

- /exec/configure

hardware ejector enable

[no] hardware ejector enable

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
ejector	Card ejector functionality
enable	enabled means when both ejectors are open, card is powered down

Command Mode

- /exec/configure

hardware fan-zone raise-speed

[no] hardware fan-zone <fan_zone_id> raise-speed <speed-to-raise>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
fan-zone	Fan Zone supported in the switch
<i>fan_zone_id</i>	please enter fan zone id whose speed needs to be increased
raise-speed	Speed to be added for current fan zone speed
<i>speed-to-raise</i>	please enter additional fan speed

Command Mode

- /exec/configure

hardware forwarding l3 resource route non-deterministic

[no] hardware forwarding l3 resource route non-deterministic

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	hardware information
forwarding	forwarding information
l3	Layer-3
resource	hardware resources
route	TCAM capacity to hold prefixes
non-deterministic	extend upto 1M

Command Mode

- /exec/configure

hardware forwarding unicast trace

[no] hardware forwarding unicast trace

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
forwarding	Hardware forwarding
unicast	Hardware Unicast forwarding
trace	Debug traces

Command Mode

- /exec/configure

hardware ip glean throttle

[no] hardware ip glean throttle

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware information
ip	IP
glean	Glean
throttle	Throttle

Command Mode

- /exec/configure

hardware ip glean throttle maximum

{ hardware ip glean throttle maximum <count> } | { no hardware ip glean throttle maximum }

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ip	IP
glean	Glean
throttle	Throttle
maximum	Maximum number of entries
<i>count</i>	Count

Command Mode

- /exec/configure

hardware ip glean throttle syslog

{ hardware ip glean throttle syslog <pkt-count> } | { no hardware ip glean throttle syslog }

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ip	IP
glean	Glean
throttle	Throttle
syslog	Threshold for syslog for number of packets hitting the entry
<i>pkt-count</i>	Packet count

Command Mode

- /exec/configure

hardware ip glean throttle timeout

{ hardware ip glean throttle timeout <timeout-in-sec> } | { no hardware ip glean throttle timeout }

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ip	IP
glean	Glean
throttle	Throttle
timeout	Timeout
<i>timeout-in-sec</i>	Timeout value in seconds (should be multiple of 30, else will be rounded off to nearest boundary)

Command Mode

- /exec/configure

hardware ipv6 glean throttle

[no] hardware ipv6 glean throttle

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware information
ipv6	IPv6
glean	Glean
throttle	Throttle

Command Mode

- /exec/configure

hardware ipv6 glean throttle maximum

{ hardware ipv6 glean throttle maximum <count> } | { no hardware ipv6 glean throttle maximum }

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ipv6	IPv6
glean	Glean
throttle	Throttle
maximum	Maximum number of entries
<i>count</i>	Count

Command Mode

- /exec/configure

hardware ipv6 glean throttle syslog

{ hardware ipv6 glean throttle syslog <pkt-count> } | { no hardware ipv6 glean throttle syslog }

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ipv6	IPv6
glean	Glean
throttle	Throttle
syslog	Threshold for syslog for number of packets hitting the entry
<i>pkt-count</i>	Packet count

Command Mode

- /exec/configure

hardware ipv6 glean throttle timeout

```
{ hardware ipv6 glean throttle timeout <timeout-in-sec> } | { no hardware ipv6 glean throttle timeout }
```

Syntax Description

no	Negate a command or set its defaults
hardware	Hardware information
ipv6	IPv6
glean	Glean
throttle	Throttle
timeout	Timeout
<i>timeout-in-sec</i>	Timeout value in seconds (should be multiple of 30, else will be rounded off to nearest boundary)

Command Mode

- /exec/configure

hardware module boot-order reverse

[no] hardware module boot-order reverse

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
module	applies on all the modules
boot-order	Configure order of module power-up
reverse	reverse order of module power-up

Command Mode

- /exec/configure

hardware multicast global-tx-span

[no] hardware multicast global-tx-span

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
multicast	Change multicast setting
global-tx-span	Modify table programming to support TX multicast SPAN across slices

Command Mode

- /exec/configure

hardware profile buffer info poll-interval timer

[no] hardware profile buffer info poll-interval [module <module>] timer <msec>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
buffer	Buffer
info	Information
poll-interval	System buffer status polling interval
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number
timer	Polling timer
<i>msec</i>	Polling timer value in msec

Command Mode

- /exec/configure

hardware profile buffer info port-threshold threshold

[no] hardware profile buffer info port-threshold [module <module>] threshold <value>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
buffer	Buffer
info	Information
port-threshold	Set port egress buffer usage threshold
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number
threshold	threshold value
<i>value</i>	percentage of maximum usage

Command Mode

- /exec/configure

hardware profile buffer monitor unicast

hardware profile buffer monitor { unicast | multicast } [internal] [sampling <sampling>] [threshold <threshold>] [interface <intf-num> | sclass <sclass>] | no hardware profile buffer monitor

Syntax Description

no	Negate a command or set its defaults
hardware	Configure hardware profile buffer monitor settings
profile	profile buffer monitor settings
buffer	Buffer
monitor	buffer monitor
unicast	unicast
multicast	multicast
internal	(Optional) enable buffer monitoring internal mode
sampling	(Optional) sampling interval in nano-seconds
<i>sampling</i>	(Optional) sampling interval in nano-seconds
threshold	(Optional) histogram threshold in Kbytes with 384 Kbytes increment
<i>threshold</i>	(Optional) histogram threshold in Kbytes with 384 Kbytes increment
interface	(Optional) enable buffer monitoring on an interface
<i>intf-num</i>	(Optional) enable buffer monitoring on an interface
sclass	(Optional) enable buffer monitoring on a system class of services
<i>sclass</i>	(Optional) enable buffer monitoring on a system class of services

Command Mode

- /exec/configure

hardware profile buffer qosgroup threshold

[no] hardware profile buffer qosgroup <groupid> threshold <percentage>

Syntax Description

no	(Optional) Negate the command
hardware	N3500
profile	Profile
buffer	Buffer
qosgroup	Qos-group
<i>groupid</i>	Group-id
threshold	Threshold
<i>percentage</i>	Percentage of maximum usage

Command Mode

- /exec/configure

hardware profile buffer span-threshold

[no] hardware profile buffer span-threshold <percentage>

Syntax Description

no	(Optional) Negate the command
hardware	N3500
profile	Profile
buffer	Buffer
span-threshold	Span Threshold
<i>percentage</i>	Percentage of maximum usage

Command Mode

- /exec/configure

hardware profile ecmp auto-recovery threshold

hardware profile ecmp auto-recovery threshold <percentage> | no hardware profile ecmp auto-recovery threshold

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
ecmp	ECMP settings
auto-recovery	ECMP auto-recovery settings
threshold	ECMP table free percentage threshold for auto-recovery
<i>percentage</i>	Percentage

Command Mode

- /exec/configure

hardware profile ecmp resilient

[no] hardware profile ecmp resilient

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
ecmp	ECMP settings
resilient	Configure ECMP resilient mode

Command Mode

- /exec/configure

hardware profile ecmp template module

[no] hardware profile ecmp template [l3vpn] module <module>

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Set hardware profile
profile	Profile settings
ecmp	set the ecmp template profile
template	set the ecmp template profile
l3vpn	(Optional) set the l3vpn ecmp template profile
module	Enter module number
<i>module</i>	

Command Mode

- /exec/configure

hardware profile forwarding-mode

```
[no] hardware profile forwarding-mode { warp [ lpm-entry <lpm_warp> host-entry <host> l2-entry <l2>
mcast-entry <mcst_warp> ] | openflow-hybrid | openflow-only | normal [ lpm-entry <ipv4> mcast-entry
<mcst> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
forwarding-mode	Forwarding mode setting
warp	Warp forwarding mode setting
openflow-hybrid	Openflow hybrid forwarding mode setting
openflow-only	Openflow only forwarding mode setting
normal	Normal forwarding mode setting
lpm-entry	(Optional) 4K aligned total IPv4 entries
<i>ipv4</i>	(Optional) 4K aligned total IPv4 entries
mcast-entry	(Optional) 4K aligned total Mcast entries
<i>mcst</i>	(Optional) 4K aligned total Mcast entries
<i>lpm_warp</i>	(Optional) 4K aligned total IPv4 entries
<i>mcst_warp</i>	(Optional) 4K aligned total Mcast entries
host-entry	(Optional) 4K aligned total Host entries
<i>host</i>	(Optional) 4K aligned total Host entries
l2-entry	(Optional) 4K aligned total L2 entries
<i>l2</i>	(Optional) 4K aligned total L2 entries

Command Mode

- /exec/configure

hardware profile front portmode

hardware profile front portmode <port-mode> | no hardware profile front portmode

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
front	port 1 QSFP/SFP+ settings
portmode	QSFP or SFP+
<i>port-mode</i>	Configure QSFP/sfp+ port mode

Command Mode

- /exec/configure

hardware profile ipv6 alpm carve-value

[no] hardware profile ipv6 alpm carve-value <ipv6_alpm_carve_value>

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
ipv6	ipv6
alpm	alpm mode
carve-value	carve value
<i>ipv6_alpm_carve_value</i>	maximum entries

Command Mode

- /exec/configure

hardware profile ipv6 lpm-entries maximum

[no] hardware profile ipv6 lpm-entries maximum <ipv6_lpm_max_entry>

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
ipv6	ipv6
lpm-entries	lpm(non-host) entries
maximum	maximum limit
<i>ipv6_lpm_max_entry</i>	maximum entries

Command Mode

- /exec/configure

hardware profile latency monitor

hardware profile latency monitor [threshold-avg <threshold-avg>] [threshold-max <threshold-max>] [sampling <sampling>] | no hardware profile latency monitor

Syntax Description

no	Negate a command or set its defaults
hardware	Configure hardware profile latency monitor settings
profile	profile latency monitor settings
latency	latency
monitor	latency monitor
threshold-avg	(Optional) average latency threshold in nano-seconds
<i>threshold-avg</i>	(Optional) average latency threshold in nano-seconds
threshold-max	(Optional) maximum latency threshold in nano-seconds
<i>threshold-max</i>	(Optional) maximum latency threshold in nano-seconds
sampling	(Optional) sampling interval in seconds
<i>sampling</i>	(Optional) sampling interval in seconds

Command Mode

- /exec/configure

hardware profile module

[no] hardware profile [vxlan | mpls] module { all | <module> }

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Set hardware profile
profile	Profile settings
vxlan	(Optional) Set the hardware profile for module to vxlan
mpls	(Optional) Set the hardware profile for module to mpls
module	Enter module number
all	All modules
<i>module</i>	

Command Mode

- /exec/configure

hardware profile multicast flex-stats-enable

[no] hardware profile multicast flex-stats-enable

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
flex-stats-enable	Enable real time stats

Command Mode

- /exec/configure

hardware profile multicast max-limit

{ hardware profile multicast max-limit <mcast-ent> } | { no hardware profile multicast max-limit }

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
max-limit	maximum limit for multicast entries
<i>mcast-ent</i>	Mcast Table Entries

Command Mode

- /exec/configure

hardware profile multicast max-limit lpm-entries

[no] hardware profile multicast max-limit lpm-entries <ipv4_mcast_lpm_max_entry>

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
max-limit	maximum limit for multicast entries
lpm-entries	lpm(non-host) entries
<i>ipv4_mcast_lpm_max_entry</i>	maximum entries

Command Mode

- /exec/configure

hardware profile multicast nlb

[no] hardware profile multicast nlb

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
nlb	network load balancing for multicast entries

Command Mode

- /exec/configure

hardware profile multicast optimization disable

[no] hardware profile multicast optimization disable

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Set hardware profile
profile	Profile settings
multicast	set multicast profile
optimization	set multicast optimization profile
disable	set the multicast optimization disable profile

Command Mode

- /exec/configure

hardware profile multicast prefer-source-tree

[no] hardware profile multicast prefer-source-tree [eternity [limit <max-limit>]]

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
prefer-source-tree	prefer the source tree
eternity	(Optional) prefer source tree for eternity and not for just 2 minutes
limit	(Optional) Configure a limit for the number of hardware entries used
<i>max-limit</i>	(Optional) Number of (S,G) for which source tree is preferred

Command Mode

- /exec/configure

hardware profile multicast rpf-check-optimization

```
{ hardware profile multicast rpf-check-optimization } | { no hardware profile multicast rpf-check-optimization }  
}
```

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
rpf-check-optimization	RPF Check optimization on Monticello ASIC

Command Mode

- /exec/configure

hardware profile multicast service-reflect port

```
{ hardware profile multicast service-reflect port <port-num> } | { no hardware profile multicast service-reflect }
}
```

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
service-reflect	service-reflect settings
port	loopback port
<i>port-num</i>	loopback port-num

Command Mode

- /exec/configure

hardware profile multicast slow-receiver port

hardware profile multicast slow-receiver port <port> | no hardware profile multicast slow-receiver port <port>

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	Profile
multicast	Multicast settings
slow-receiver	Multicast slow receiver
port	Port
<i>port</i>	Port number

Command Mode

- /exec/configure

hardware profile multicast syslog-threshold

[no] hardware profile multicast syslog-threshold <percentage>

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
multicast	Multicast settings
syslog-threshold	MROUTE table syslog threshold
<i>percentage</i>	Percentage (Default is 90)

Command Mode

- /exec/configure

hardware profile openflow

```
[no] hardware profile { openflow [ agent default { drop | normal } ] | { tap-aggregation [ l2drop ] } }
```

Syntax Description

no	(Optional) Negate the command
hardware	Hardware Internal Information
profile	Profile
openflow	Openflow
tap-aggregation	Tap Aggregation
l2drop	(Optional) Drop non IP traffic ingress on mode tap interfaces
agent	(Optional) Act as Openflow Agent
default	(Optional) Specify default action for frames which don't match any flow
drop	(Optional) Drop all frames that miss MAC
normal	(Optional) [default]Flood unknown traffic

Command Mode

- /exec/configure

hardware profile packet-drop

[no] hardware profile packet-drop

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	Profile settings
packet-drop	Configure Packet Drop parameters

Command Mode

- /exec/configure

hardware profile pbr skip-selfip

[no] hardware profile pbr skip-selfip

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
pbr	PBR feature settings
skip-selfip	Configure Skipping PBR for self-ip packets

Command Mode

- /exec/configure

hardware profile pfc mmu buffer-reservation

[no] hardware profile pfc mmu buffer-reservation <percentage>

Syntax Description

no	(Optional) Negate the command
hardware	Hardware Internal Information
profile	profile settings
pfc	System level priority-flow-control settings
mmu	Hardware memory management unit configuration
buffer-reservation	Shared pool buffer reservation
<i>percentage</i>	Percentage of shared pool buffers to be reserved

Command Mode

- /exec/configure

hardware profile portmode

{ hardware profile portmode <port-mode> [2-tuple] } | no hardware profile portmode

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
portmode	QSFP port mode setting
<i>port-mode</i>	Configure QSFP port mode
2-tuple	(Optional) Display QSFP portnames in 2-tuple mode even in 10G mode

Command Mode

- /exec/configure

hardware profile statistics pstat

[no] hardware profile statistics pstat [peak]

Syntax Description

no	(Optional) Negate the command
hardware	Configure hardware profile setting
profile	profile settings
statistics	hardware stats
pstat	Enable Pstat default is instantaneous
peak	(Optional) Peak stats

Command Mode

- /exec/configure

hardware profile svi flex-stats-enable

[no] hardware profile svi flex-stats-enable

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	profile settings
svi	SVI settings
flex-stats-enable	Enable real time stats

Command Mode

- /exec/configure

hardware profile tcam ipv6-sup-tcam match-inner

```
{ hardware profile tcam ipv6-sup-tcam match-inner } | { no hardware profile tcam ipv6-sup-tcam match-inner }
}
```

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
ipv6-sup-tcam	IPv6 SUP TCAM parameters
match-inner	match inner payload for tunnel packets

Command Mode

- /exec/configure

hardware profile tcam region

```
[no] hardware profile tcam region { <tcam_compat_type> <tcam_compat_size> | ifacl <tcam_compat_size>
[ double-wide ] | nat <tcam_compat_size> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
profile	profile
tcam	Configure tcam parameters
region	Configure tcam region
ifacl	IPV4 PACL size
double-wide	(Optional) Configure tcam as double wide
nat	NAT size
<i>tcam_compat_type</i>	
<i>tcam_compat_size</i>	Enter tcam size

Command Mode

- /exec/configure

hardware profile tcam region span qualify udf

[no] hardware profile tcam region span qualify udf { <udf_name> } +

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
region	Configure tcam region
span	Configure for span region
qualify	Configure UDFs to be qualified for span region
udf	Configure UDF names
<i>udf_name</i>	UDF name

Command Mode

- /exec/configure

hardware profile tcam region spanv6-l2 qualify udf

[no] hardware profile tcam region spanv6-l2 qualify udf { <udf_name> } +

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
region	Configure tcam region
spanv6-l2	Configure for span region
qualify	Configure UDFs to be qualified for span region
udf	Configure UDF names
<i>udf_name</i>	UDF name

Command Mode

- /exec/configure

hardware profile tcam region spanv6 qualify udf

[no] hardware profile tcam region spanv6 qualify udf { <udf_name> } +

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
region	Configure tcam region
spanv6	Configure for span region
qualify	Configure UDFs to be qualified for span region
udf	Configure UDF names
<i>udf_name</i>	UDF name

Command Mode

- /exec/configure

hardware profile tcam resource service-template

[no] hardware profile tcam resource service-template { <name> } [module { <lc> | <fm> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
resource	Configure tcam hardware resources
service-template	Commit template
<i>name</i>	Select name of template
module	(Optional) Specify a module number
<i>lc</i>	(Optional) line card number
<i>fm</i>	(Optional) fabric module number

Command Mode

- /exec/configure handle auto 424

hardware profile tcam resource template

```
[no] hardware profile tcam resource template { <name> { ref-template <temp-nontahoe> | ref-template-tahoe
<temp-tahoe> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
resource	Configure tcam hardware resources
template	Configure template based tcam carving parameters
ref-template	Select a default template as reference
<i>temp-nontahoe</i>	
ref-template-tahoe	Select a default template as reference
<i>temp-tahoe</i>	
<i>name</i>	Create/Select name of custom template

Command Mode

- /exec/configure

hardware profile tcam syslog-threshold

{ hardware profile tcam syslog-threshold <percentage> } | { no hardware profile tcam syslog-threshold }

Syntax Description

no	Negate a command or set its defaults
hardware	Change hardware usage settings
profile	Profile settings
tcam	Configure tcam parameters
syslog-threshold	TCAMs syslog threshold
<i>percentage</i>	Percentage

Command Mode

- /exec/configure

hardware profile ucast6 lpm-65-to-127-max-limit

{ hardware profile ucast6 lpm-65-to-127-max-limit <unicast-ent> } | { no hardware profile ucast6 lpm-65-to-127-max-limit }

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	profile settings
ucast6	unicast ipv6 settings
lpm-65-to-127-max-limit	maximum limit for unicast ipv6 lpm-65-to-127 entries, default is 256
<i>unicast-ent</i>	Unicast ipv6 lpm-65-to-127 Table Entries

Command Mode

- /exec/configure

hardware profile ucast6 max-limit

{ hardware profile ucast6 max-limit <unicast-ent> } | { no hardware profile ucast6 max-limit }

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	profile settings
ucast6	unicast ipv6 settings
max-limit	maximum limit for unicast ipv6 entries
<i>unicast-ent</i>	Unicast ipv6 Table Entries

Command Mode

- /exec/configure

hardware profile unicast enable-host-ecmp

[no] hardware profile unicast enable-host-ecmp [arp-nd | [ipv4 [arp]] | [ipv6 [nd]]]

Syntax Description

no	(Optional) Negate the command
hardware	Change hardware usage settings
profile	profile settings
unicast	Unicast settings
enable-host-ecmp	Enable ECMP support for /32 (IPv4) and /128 (IPv6) routes
ipv4	(Optional) Enable ECMP support for /32 (IPv4 Only) Routes
ipv6	(Optional) Enable ECMP support for /128 (IPv6 Only) Routes
arp-nd	(Optional) Retain ARP (IPv4) and ND (IPv6) Routes in Host-Table
arp	(Optional) Retain ARP Entries in Host-Table
nd	(Optional) Retain ND Entries in Host-Table

Command Mode

- /exec/configure

hardware profile unicast syslog-threshold

```
{ hardware profile unicast syslog-threshold <percentage> } | { no hardware profile unicast syslog-threshold }  
}
```

Syntax Description

no	Negate the command
hardware	Change hardware usage settings
profile	profile settings
unicast	Unicast settings
syslog-threshold	Unicast Route table syslog threshold
<i>percentage</i>	Percentage

Command Mode

- /exec/configure

hardware qos dynamic-buffer-sharing

[no] hardware qos dynamic-buffer-sharing

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
qos	Configure qos related configuration
dynamic-buffer-sharing	Enable dynamic buffer sharing

Command Mode

- /exec/configure

hardware qos fc rate-shaper

[no] hardware qos fc rate-shaper [low]

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
qos	Configure qos related configuration
fc	Fibre Channel interface related configuration
rate-shaper	Rate Shaper for FC interface
low	(Optional) Configure FC interface low rate shaper

Command Mode

- /exec/configure

hardware qos pfc mc-drop

[no] hardware qos pfc mc-drop

Syntax Description

no	(Optional) Negate a command or set its defaults
hardware	Hardware Internal Information
qos	Configure qos related configuration
pfc	Priority-flow-control specific configuration
mc-drop	Multicast packets are dropped in lossless queue

Command Mode

- /exec/configure

hardware sample-redirect module redirect-interface

hardware sample-redirect module <num> redirect-interface <interface>

Syntax Description

hardware	Change hardware usage settings
sample-redirect	Redirect netflow sampled data
module	Line card module
<i>num</i>	slot number
redirect-interface	Interface for redirecting the traffic
<i>interface</i>	Interface Name

Command Mode

- /exec

head

| head [-n <lines>]

Syntax Description

	Pipe command output to filter
head	Display first lines
-n	(Optional) modify number of lines (default 10)
<i>lines</i>	(Optional) number of lines to print

Command Mode

- /output

header-type 2

[no] header-type { 2 | 3 [rfc-compliant] }

Syntax Description

no	(Optional) Negate a command or set its defaults
header-type	Set ERSPAN Source version
2	ERSPAN Source Version 2
3	ERSPAN Source Version 3
rfc-compliant	(Optional) ERSPAN V3 header rfc-compliant

Command Mode

- /exec/configure/config-monitor-erspan-src

hello-interval

```
{ { hello-interval <interval> } | { no hello-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
hello-interval	Hello interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

hello-interval

```
{ { hello-interval <interval> } | { no hello-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
hello-interval	Hello interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf3/router-ospf3-vlink /exec/configure/router-ospf3/vrf/router-ospf3-vlink

hello-interval

```
{ { hello-interval <interval> } | { no hello-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
hello-interval	Hello interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

history

```
{ no | default } history { { buckets-kept } | { distributions-of-statistics-kept } | { filter } | { hours-of-statistics-kept } | { lives-kept } | { statistics-distribution-interval } }
```

Syntax Description

no	
default	Set a command to its defaults
history	History and Distribution Data
buckets-kept	Maximum number of history buckets to collect
distributions-of-statistics-kept	Maximum number of statistics distribution buckets to capture
filter	Add operation to History when...
hours-of-statistics-kept	Maximum number of statistics hour groups to capture
lives-kept	Maximum number of history lives to collect
statistics-distribution-interval	Statistics distribution interval size

Command Mode

- /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho /exec/configure/ip-sla/http

history

```
{ no | default } history { { buckets-kept } | { distributions-of-statistics-kept } | { enhanced [ interval [
<interval-seconds> [ buckets [ <num-buckets> ] ] ] ] } | { filter } | { hours-of-statistics-kept } | { lives-kept }
| { statistics-distribution-interval } }
```

Syntax Description

no	
<i>interval</i>	(Optional) buckets
default	Set a command to its defaults
history	History and Distribution Data
buckets-kept	Maximum number of history buckets to collect
distributions-of-statistics-kept	Maximum number of statistics distribution buckets to capture
enhanced	Enable enhanced history collection
<i>interval-seconds</i>	(Optional) Interval in seconds
buckets	(Optional) Number of buckets to collect data
<i>num-buckets</i>	(Optional) Number of buckets
filter	Add operation to History when...
hours-of-statistics-kept	Maximum number of statistics hour groups to capture
lives-kept	Maximum number of history lives to collect
statistics-distribution-interval	Statistics distribution interval size

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/tcp /exec/configure/ip-sla/icmpEcho

history

```
history { { buckets-kept <num-buckets-kept> } | { distributions-of-statistics-kept <num-dist-stats> } | {
enhanced [ interval [ <interval-seconds> [ buckets [ <num-buckets> ] ] ] ] | { filter { all | failures | none |
overThreshold } } | { hours-of-statistics-kept <num-hours-of-stats> } | { lives-kept <life-size-value> } | {
statistics-distribution-interval <dist-interval> } }
```

Syntax Description

<i>interval</i>	(Optional) buckets
<i>interval-seconds</i>	(Optional) <num-buckets>
<i>life-size-value</i>	<dist-interval>
history	History and Distribution Data
buckets-kept	Maximum number of history buckets to collect
<i>num-buckets-kept</i>	Bucket size value (default 15)
distributions-of-statistics-kept	Maximum number of statistics distribution buckets to capture
<i>num-dist-stats</i>	Distribution bucket size value (default 1)
enhanced	Enable enhanced history collection
buckets	(Optional) Number of buckets to collect data
<i>num-buckets</i>	(Optional) Number of buckets
filter	Add operation to History when...
all	Collect every operation in History
failures	Collect operations that fail in History
none	Shutoff History collection
overThreshold	Collect operations that are over threshold in History
hours-of-statistics-kept	Maximum number of statistics hour groups to capture
<i>num-hours-of-stats</i>	Hour groups size value (default 2)
lives-kept	Maximum number of history lives to collect
statistics-distribution-interval	Statistics distribution interval size
<i>dist-interval</i>	Distribution interval value in msec (default 20ms), Value in usec if precision microsecond is enabled

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/tcp /exec/configure/ip-sla/icmpEcho

history

```
history { { buckets-kept <num-buckets-kept> } | { distributions-of-statistics-kept <num-dist-stats> } | { filter
{ all | failures | none | overThreshold } } | { hours-of-statistics-kept <num-hours-of-stats> } | { lives-kept
<life-size-value> } | { statistics-distribution-interval <dist-interval> } }
```

Syntax Description

<i>dist-interval</i>	<num-buckets-kept>
<i>num-hours-of-stats</i>	<life-size-value>
<i>distributions-of-statistics-kept</i>	hours-of-statistics-kept
<i>statistics-distribution-interval</i>	
history	History and Distribution Data
buckets-kept	Maximum number of history buckets to collect
<i>num-buckets-kept</i>	Bucket size value (default 15)
<i>num-dist-stats</i>	Distribution bucket size value (default 1)
filter	Add operation to History when...
all	Collect every operation in History
failures	Collect operations that fail in History
none	Shutoff History collection
overThreshold	Collect operations that are over threshold in History
hours-of-statistics-kept	Maximum number of statistics hour groups to capture
lives-kept	Maximum number of history lives to collect
<i>life-size-value</i>	Life size value (default 0)

Command Mode

- /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho /exec/configure/ip-sla/http

history

```
{ no | default } history { { distributions-of-statistics-kept } | { enhanced [ interval [ <interval-seconds> [ buckets [ <num-buckets> ] ] ] ] } | { hours-of-statistics-kept } | { statistics-distribution-interval } }
```

Syntax Description

no	
<i>interval</i>	(Optional) buckets
<i>distributions-of-statistics-kept</i>	hours-of-statistics-kept
<i>statistics-distribution-interval</i>	
default	Set a command to its defaults
history	History and Distribution Data
enhanced	Enable enhanced history collection
<i>interval-seconds</i>	(Optional) Interval in seconds
buckets	(Optional) Number of buckets to collect data
<i>num-buckets</i>	(Optional) Number of buckets
hours-of-statistics-kept	Maximum number of statistics hour groups to capture

Command Mode

- /exec/configure/ip-sla/jitter

history

```
history { { distributions-of-statistics-kept <num-dist-stats> } | { enhanced [ interval [ <interval-seconds> [
buckets [ <num-buckets> ] ] ] ] } | { hours-of-statistics-kept <num-hours-of-stats> } | {
statistics-distribution-interval <dist-interval> } }
```

Syntax Description

<i>interval</i>	(Optional) buckets
<i>num-buckets</i>	(Optional) <num-hours-of-stats>
<i>enhanced</i>	hours-of-statistics-kept
history	History and Distribution Data
distributions-of-statistics-kept	Maximum number of statistics distribution buckets to capture
<i>num-dist-stats</i>	Distribution bucket size value (default 1)
<i>interval-seconds</i>	(Optional) Interval in seconds
buckets	(Optional) Number of buckets to collect data
hours-of-statistics-kept	Maximum number of statistics hour groups to capture
<i>num-hours-of-stats</i>	Hour groups size value (default 2)
statistics-distribution-interval	Statistics distribution interval size
<i>dist-interval</i>	Distribution interval value in msec (default 20ms), Value in usec if precision microsecond is enabled

Command Mode

- /exec/configure/ip-sla/jitter

holdtime

holdtime { infinite | <secs> } | no holdtime

Syntax Description

no	Negate a command or set its defaults
holdtime	LDP session holdtime
infinite	Ignore LDP session holdtime
<i>secs</i>	Holdtime in seconds

Command Mode

- /exec/configure/ldp

hop-limit maximum

[no] hop-limit maximum <limit>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>limit</i>	Maximum hop count value allowed

Command Mode

- /exec/configure/config-ra-guard

hop-limit minimum

[no] hop-limit minimum <limit>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>limit</i>	Minimum hop count value allowed

Command Mode

- /exec/configure/config-ra-guard

hop

{ hop <val> } | { no hop }

Syntax Description

no	Negate a command or set its defaults
hop	Configure ngoam hop count
<i>val</i>	Configure ngoam service hop count value

Command Mode

- /exec/configure/configngoamprofile

host-reachability protocol

[no] host-reachability protocol { bgp | openflow | openflow-ir }

Syntax Description

no	(Optional) Negate a command or set its defaults
host-reachability	Configure host reachability advertisement
protocol	Control protocol to use
bgp	Border Gateway Protocol
openflow	OpenFlow
openflow-ir	OpenFlow-IR

Command Mode

- /exec/configure/if-nve

host

[no] { host <hostaddr> | <prefix> | <addr> <mask> }

Syntax Description

no	(Optional) Negate a command or set its defaults
host	Host address of the object-group member
<i>hostaddr</i>	A.B.C.D Host address
<i>addr</i>	A.B.C.D Network address of object-group member
<i>mask</i>	A.B.C.D wildcard
<i>prefix</i>	A.B.C.D/nn Network prefix of the object-group member

Command Mode

- /exec/configure/objgroup

host group permit

```
{ <seq> host <hostip> group <range> { permit | deny } } | { no <seq> [ host <hostip> group <range> { permit | deny } ] }
```

Syntax Description

<i>seq</i>	Sequence Number
host	Host IP Address
<i>hostip</i>	Host IP Address
group	Configure explicit group ranges
<i>range</i>	Group Prefix
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/sender

host source group permit

```
{ <seq> host <hostip> source <sourceip> group <range> { permit | deny } } | { no <seq> [ host <hostip>
source <sourceip> group <range> { permit | deny } ] }
```

Syntax Description

<i>seq</i>	Sequence Number
host	Host IP Address
<i>hostip</i>	Host IP Address value
source	Source IP Address
<i>sourceip</i>	Source IP Address value
group	Configure explicit group ranges
<i>range</i>	Group Prefix
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/receiver

hostname

{ hostname | switchname } <name> | no { hostname | switchname }

Syntax Description

no	Negate a command or set its defaults
hostname	Configure system's host name
switchname	Configure system's host name
<i>name</i>	Enter switchname

Command Mode

- /exec/configure

hostname dynamic

[no] hostname dynamic

Syntax Description

no	(Optional) Negate a command or set its defaults
hostname	Set dynamic hostname for IS-IS
dynamic	Dynamic hostname

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

hostname dynamic

[no] hostname dynamic

Syntax Description

no	(Optional) Negate a command or set its defaults
hostname	Set dynamic hostname for IS-IS
dynamic	Dynamic hostname

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

hostname dynamic

[no] hostname dynamic

Syntax Description

no	(Optional) Negate a command or set its defaults
hostname	Set dynamic hostname for IS-IS
dynamic	Dynamic hostname

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

hsrp

[no] hsrp <group-id> [ipv4]

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
<i>group-id</i>	Group number (0-255 for HSRPv1)
ipv4	(Optional) Configure IP Version 4 group

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp anycast

[no] hsrp anycast <id> { ipv4 | ipv6 | both }

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP configuration commands
anycast	Anycast related commands
<i>id</i>	Bundle number
ipv4	Associate IP Version 4 for the bundle
ipv6	Associate IP Version 6 for the bundle
both	Associate IP Version 4 and 6 for the bundle

Command Mode

- /exec/configure

hsrp bfd

[no] hsrp bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
bfd	BFD protocol

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp bfd all-interfaces

[no] hsrp bfd all-interfaces

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
bfd	BFD protocol
all-interfaces	On all interfaces

Command Mode

- /exec/configure

hsrp delay minimum

hsrp delay { minimum <min-delay> | reload <reload-delay> } + | no hsrp delay [minimum | reload]

Syntax Description

no	Negate a command or set its defaults
hsrp	HSRP interface configuration commands
delay	HSRP initialisation delay
minimum	Minimum delay
reload	Delay after reload
<i>min-delay</i>	<0-10000> Delay in seconds
<i>reload-delay</i>	<0-10000> Delay in seconds

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp force state vlan

```
hsrp force state vlan { <vlans> | all }
```

Syntax Description

hsrp	Hot Standby Router Protocol (HSRP) information
force	Move the HSRP state
state	HSRP state
vlan	HSRP state changes for these vlans
all	Include all HSRP configured VLANs
<i>vlans</i>	VLAN IDs of the VLAN for which state change will affect

Command Mode

- /exec

hsrp ipv6

[no] hsrp <group-id> ipv6

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
<i>group-id</i>	Group number
ipv6	Configure IP Version 6 group

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp mac-refresh

hsrp mac-refresh [<time>] | no hsrp mac-refresh

Syntax Description

no	Negate a command or set its defaults
hsrp	HSRP interface configuration commands
mac-refresh	Interface mac-refresh time
<i>time</i>	(Optional) Timeout value (0-10000) in sec

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp timers extended-hold

[no] hsrp timers extended-hold [<extended-hold>]

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
timers	Global Timers
extended-hold	Extended Hold
<i>extended-hold</i>	(Optional) Time in seconds

Command Mode

- /exec/configure

hsrp use-bia

[no] hsrp use-bia [scope interface]

Syntax Description

no	(Optional) Negate a command or set its defaults
hsrp	HSRP interface configuration commands
use-bia	HSRP uses interface's burned in address
scope	(Optional) Specify the scope of use-bia
interface	(Optional) Use-bia applies to all groups on this interface or sub-interface

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

hsrp version 1

hsrp version { 1 | 2 } | no hsrp version

Syntax Description

no	Negate a command or set its defaults
hsrp	HSRP interface configuration commands
version	HSRP version
1	Version 1
2	Version 2

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan-common /exec/configure/if-port-channel /exec/configure/if-sub /exec/configure/if-ethernet-all

http get

```
[no] http { get } <WORD> { [ cache { disable | enable } ] [ proxy <proxy-info> ] [ source-ip { <source-ip-hostname> | <source-ip-address> } ] [ source-port <src-port> ] [ version <http-version> ] } +
```

Syntax Description

no	(Optional)
cache	(Optional) enable
proxy	(Optional) <proxy-info>
source-ip	(Optional) <source-ip-hostname>
source-port	(Optional) <src-port>
version	(Optional) <http-version>
http	HTTP Operation
get	HTTP get operation
WORD	URL
enable	(Optional) enable download of cached entries (default)
disable	(Optional) disable download of cached entries (default)
proxy-info	(Optional) proxy information string
source-ip-hostname	(Optional) source IP hostname, broadcast disallowed
source-ip-address	(Optional) source IP address, broadcast disallowed
src-port	(Optional) Port Number (Recommended port range between 1025-65534)
http-version	(Optional) Supported HTTP versions are '1.0' and '1.1'.

Command Mode

- /exec/configure/ip-sla

http proxy server

[no] http proxy server <hostipname> [port <port-num>]

Syntax Description

no	(Optional) Negate a command or set its defaults
http	Configure http related parameters
proxy	Http Proxy related parameters
server	Server address
<i>hostipname</i>	IPV4/IPV6 address or DNS name of proxy server
port	(Optional) Http proxy server port
<i>port-num</i>	(Optional) port number

Command Mode

- /exec/configure/trustpool

human

| human

Syntax Description

	Pipe command output to filter
human	output in human format

Command Mode

- /output

human

| human

Syntax Description

	Pipe command output to filter
human	output in human format

Command Mode

- /output

hw-module logging onboard

[no] hw-module logging onboard [{ counter-stats | module <module> [{ counter-stats }] }]

Syntax Description

no	(Optional) Negate a command or set its defaults
hw-module	Enable/Disable OBFL information
logging	Enable/Disable OBFL information
onboard	Enable/Disable OBFL information
counter-stats	(Optional) Enable/Disable OBFL counter statistics
module	(Optional) Enable/Disable OBFL information for Module
<i>module</i>	(Optional) Enter module number

Command Mode

- /exec/configure

hw-module logging onboard

```
[no] hw-module logging onboard [ { environmental-history | error-stats | interrupt-stats | module <module>
[ { environmental-history | error-stats | interrupt-stats | obfl-logs | cpuhog } ] | obfl-logs | cpuhog } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
hw-module	Enable/Disable OBFL information
logging	Enable/Disable OBFL information
onboard	Enable/Disable OBFL information
environmental-history	(Optional) Enable/Disable OBFL environmental history
error-stats	(Optional) Enable/Disable OBFL error statistics
interrupt-stats	(Optional) Enable/Disable OBFL interrupt statistics
cpuhog	(Optional) Enable/Disable OBFL cpu hog events
module	(Optional) Enable/Disable OBFL information for Module
<i>module</i>	(Optional) Enter module number
obfl-logs	(Optional) Enable/Disable OBFL (boot-uptime/device-version/obfl-history)

Command Mode

- /exec/configure



I Commands

- [icam monitor entries acl module inst](#), on page 1786
- [icam monitor interval num_intervals](#), on page 1787
- [icam monitor resource acl_tcam module inst](#), on page 1788
- [icam monitor scale](#), on page 1789
- [icam monitor scale](#), on page 1791
- [icmp-echo](#), on page 1792
- [icmpv6 cfs-queue](#), on page 1793
- [icmpv6 library mts-queue](#), on page 1794
- [icmpv6 mts-queue](#), on page 1795
- [import](#), on page 1796
- [import interface](#), on page 1797
- [import l2vpn evpn](#), on page 1798
- [import map](#), on page 1799
- [import running-config](#), on page 1800
- [import vpn unicast](#), on page 1801
- [import vrf default map](#), on page 1802
- [in-label allocate](#), on page 1803
- [inband-telemetry exporter](#), on page 1804
- [inband-telemetry flow-profile](#), on page 1805
- [inband-telemetry monitor](#), on page 1806
- [inband-telemetry queue-profile](#), on page 1807
- [inband-telemetry record](#), on page 1808
- [inband-telemetry system monitor](#), on page 1809
- [inband-telemetry watchlist ip](#), on page 1810
- [include-icv-indicator](#), on page 1811
- [include profile](#), on page 1812
- [include profile any](#), on page 1813
- [index next-label](#), on page 1814
- [index next](#), on page 1815
- [ingress-mtu](#), on page 1816
- [ingress-replication protocol bgp](#), on page 1817
- [ingress-replication protocol static](#), on page 1818
- [ingress](#), on page 1819

- ingress interface, on page 1820
- ingress interface, on page 1821
- inherit peer-policy, on page 1822
- inherit peer-policy, on page 1823
- inherit peer-session, on page 1824
- inherit peer, on page 1825
- inherit port-profile, on page 1826
- initial-delay, on page 1827
- initial-refresh skip, on page 1828
- inject-map exist-map, on page 1829
- innoshell, on page 1830
- innoshell cmd, on page 1831
- innoshell module, on page 1832
- innoshell module cmd, on page 1833
- install activate, on page 1834
- install add, on page 1835
- install all, on page 1836
- install all network-os, on page 1837
- install commit, on page 1838
- install deactivate, on page 1839
- install epld, on page 1840
- install epld, on page 1841
- install feature-set fcoe-npv, on page 1842
- install license, on page 1843
- install license, on page 1844
- install remove, on page 1845
- install reset, on page 1846
- install verify, on page 1847
- instance-id, on page 1848
- instance, on page 1849
- instance, on page 1850
- instance vlan, on page 1851
- interface, on page 1852
- interface, on page 1853
- interface, on page 1854
- interface, on page 1855
- interface, on page 1856
- interface, on page 1857
- interface, on page 1858
- interface, on page 1859
- interface, on page 1860
- interface, on page 1861
- interface, on page 1862
- interface, on page 1863
- interface, on page 1864
- interface, on page 1865

- interface, on page 1866
- interface, on page 1867
- interface, on page 1868
- interface breakout-profile, on page 1869
- interface breakout module, on page 1870
- interface breakout module, on page 1871
- interface breakout module port map, on page 1872
- interface breakout module port map, on page 1873
- interface down delay, on page 1874
- interop-enable, on page 1875
- interval, on page 1876
- interval, on page 1877
- ip, on page 1878
- ip, on page 1879
- ip, on page 1880
- ip, on page 1881
- ip, on page 1882
- ip, on page 1883
- ip, on page 1884
- ip access-class, on page 1885
- ip access-group, on page 1886
- ip access-list, on page 1887
- ip access-list match-local-traffic, on page 1888
- ip address, on page 1889
- ip address dhcp, on page 1890
- ip address ipv6 address port, on page 1891
- ip address secondary, on page 1892
- ip adjacency peer-gmac, on page 1893
- ip adjacency remote-adj, on page 1894
- ip adjacency route distance, on page 1895
- ip amt anycast-relay-prefix, on page 1896
- ip amt gateway, on page 1897
- ip amt join-policy, on page 1898
- ip amt qqic, on page 1899
- ip amt relay-advertisement-address, on page 1900
- ip amt relay, on page 1901
- ip amt state-limit, on page 1902
- ip amt tunnel-limit, on page 1903
- ip arp, on page 1904
- ip arp allow-static-arp-outside-subnet, on page 1905
- ip arp cache limit, on page 1906
- ip arp cos, on page 1907
- ip arp delete, on page 1908
- ip arp event-history size, on page 1909
- ip arp event-history size, on page 1911
- ip arp evpn timeout, on page 1913

- [ip arp gratuitous hsrp duplicate](#), on page 1914
- [ip arp gratuitous request](#), on page 1915
- [ip arp gratuitous update](#), on page 1916
- [ip arp inspection filter vlan](#), on page 1917
- [ip arp inspection log-buffer entries](#), on page 1918
- [ip arp inspection trust](#), on page 1919
- [ip arp inspection validate](#), on page 1920
- [ip arp inspection vlan](#), on page 1921
- [ip arp off-list timeout](#), on page 1922
- [ip arp rarp fabric-forwarding](#), on page 1923
- [ip arp rarp fabric-forwarding](#), on page 1924
- [ip arp rarp fabric-forwarding rate-limit](#), on page 1925
- [ip arp suppression-cache](#), on page 1926
- [ip arp suppression timeout](#), on page 1927
- [ip arp synchronize](#), on page 1928
- [ip arp timeout](#), on page 1929
- [ip arp timeout](#), on page 1930
- [ip arp unnum-svi-dup-ip-detection](#), on page 1931
- [ip arp unnum-svi-sw-replication](#), on page 1932
- [ip as-path access-list deny](#), on page 1933
- [ip as-path access-list deny](#), on page 1934
- [ip as-path access-list seq deny](#), on page 1935
- [ip authentication](#), on page 1936
- [ip auto-discard](#), on page 1937
- [ip bandwidth-percent eigrp](#), on page 1938
- [ip bandwidth eigrp](#), on page 1939
- [ip community-list expanded deny](#), on page 1940
- [ip community-list expanded deny](#), on page 1941
- [ip community-list expanded seq deny](#), on page 1942
- [ip community-list standard permit internet local-AS](#), on page 1943
- [ip community-list standard permit internet local-AS](#), on page 1944
- [ip community-list standard seq permit internet local-AS](#), on page 1945
- [ip delay eigrp](#), on page 1946
- [ip destination](#), on page 1947
- [ip dhcp option82 suboption circuit-id](#), on page 1948
- [ip dhcp packet strict-validation](#), on page 1949
- [ip dhcp relay](#), on page 1950
- [ip dhcp relay address](#), on page 1951
- [ip dhcp relay information option](#), on page 1952
- [ip dhcp relay information option trust](#), on page 1953
- [ip dhcp relay information option vpn](#), on page 1954
- [ip dhcp relay information trust-all](#), on page 1955
- [ip dhcp relay information trusted](#), on page 1956
- [ip dhcp relay source-interface](#), on page 1957
- [ip dhcp relay source-interface](#), on page 1958
- [ip dhcp relay sub-option circuit-id customized](#), on page 1959

- ip dhcp relay sub-option circuit-id format-type string, on page 1960
- ip dhcp relay sub-option type cisco, on page 1961
- ip dhcp smart-relay, on page 1962
- ip dhcp smart-relay global, on page 1963
- ip dhcp snooping, on page 1964
- ip dhcp snooping information option, on page 1965
- ip dhcp snooping ipsg-excluded vlan, on page 1966
- ip dhcp snooping sub-option circuit-id format-type string, on page 1967
- ip dhcp snooping trust, on page 1968
- ip dhcp snooping verify mac-address, on page 1969
- ip dhcp snooping vlan, on page 1970
- ip directed-broadcast, on page 1971
- ip distribute-list eigrp, on page 1972
- ip dns source-interface, on page 1973
- ip domain-list, on page 1974
- ip domain-lookup, on page 1975
- ip domain-name, on page 1976
- ip drop-glean, on page 1977
- ip dscp-lop, on page 1978
- ip dscp, on page 1979
- ip eigrp bfd, on page 1980
- ip eigrp event-history bfd size, on page 1981
- ip eigrp event-history errors, on page 1982
- ip eigrp event-history size, on page 1983
- ip eigrp shutdown, on page 1984
- ip extcommunity-list expanded deny, on page 1985
- ip extcommunity-list standard permit, on page 1986
- ip fabric multicast file-debug, on page 1987
- ip flow monitor input, on page 1988
- ip flow monitor input, on page 1989
- ip flow monitor input, on page 1990
- ip forward, on page 1991
- ip ftp source-interface, on page 1992
- ip hello-interval eigrp, on page 1993
- ip hold-time eigrp, on page 1994
- ip host, on page 1995
- ip host host, on page 1996
- ip http source-interface, on page 1997
- ip icmp-errors source-interface, on page 1998
- ip igmp any-query-destination, on page 1999
- ip igmp enforce-router-alert, on page 2000
- ip igmp event-history cli, on page 2001
- ip igmp event-history ha, on page 2002
- ip igmp event-history interface, on page 2003
- ip igmp event-history interface, on page 2004
- ip igmp event-history mtrace, on page 2005

- [ip igmp event-history mvr](#), on page 2006
- [ip igmp event-history nbm](#), on page 2007
- [ip igmp event-history policy](#), on page 2008
- [ip igmp event-history vrf](#), on page 2009
- [ip igmp file-debug](#), on page 2010
- [ip igmp flush-routes](#), on page 2011
- [ip igmp group-timeout](#), on page 2012
- [ip igmp heavy-template](#), on page 2013
- [ip igmp host-proxy](#), on page 2014
- [ip igmp immediate-leave](#), on page 2015
- [ip igmp join-group](#), on page 2016
- [ip igmp last-member-query-count](#), on page 2017
- [ip igmp last-member-query-response-time](#), on page 2018
- [ip igmp querier-elect strict](#), on page 2019
- [ip igmp querier](#), on page 2020
- [ip igmp query-interval](#), on page 2021
- [ip igmp query-max-response-time](#), on page 2022
- [ip igmp report-link-local-groups](#), on page 2023
- [ip igmp report prefix-list](#), on page 2024
- [ip igmp robustness-variable](#), on page 2025
- [ip igmp snooping](#), on page 2026
- [ip igmp snooping](#), on page 2027
- [ip igmp snooping](#), on page 2028
- [ip igmp snooping access-group](#), on page 2029
- [ip igmp snooping disable-nve-static-router-port](#), on page 2030
- [ip igmp snooping disable-nve-static-router-port](#), on page 2031
- [ip igmp snooping event-history igmp-snoop-internal](#), on page 2032
- [ip igmp snooping event-history mfdm-sum](#), on page 2033
- [ip igmp snooping event-history mfdm](#), on page 2034
- [ip igmp snooping event-history rib](#), on page 2035
- [ip igmp snooping event-history vlan-events](#), on page 2036
- [ip igmp snooping event-history vlan](#), on page 2037
- [ip igmp snooping event-history vpc](#), on page 2038
- [ip igmp snooping group-timeout](#), on page 2039
- [ip igmp snooping group-timeout](#), on page 2040
- [ip igmp snooping last-member-query-interval](#), on page 2041
- [ip igmp snooping link-local-groups-suppression](#), on page 2042
- [ip igmp snooping link-local-groups-suppression](#), on page 2043
- [ip igmp snooping many-to-one-enhance](#), on page 2044
- [ip igmp snooping max-gq-miss](#), on page 2045
- [ip igmp snooping mrouter vpc-peer-link](#), on page 2046
- [ip igmp snooping proxy-leave use-group-address](#), on page 2047
- [ip igmp snooping proxy general-queries](#), on page 2048
- [ip igmp snooping proxy general-queries](#), on page 2049
- [ip igmp snooping report-flood all](#), on page 2050
- [ip igmp snooping report-suppression](#), on page 2051

- [ip igmp snooping report-suppression](#), on page 2052
- [ip igmp snooping report prefix interface](#), on page 2053
- [ip igmp snooping syslog-threshold](#), on page 2054
- [ip igmp snooping v3-report-suppression](#), on page 2055
- [ip igmp snooping v3-report-suppression](#), on page 2056
- [ip igmp spoof-check](#), on page 2057
- [ip igmp ssm-translate](#), on page 2058
- [ip igmp startup-query-count](#), on page 2059
- [ip igmp startup-query-interval](#), on page 2060
- [ip igmp state-limit](#), on page 2061
- [ip igmp static](#), on page 2062
- [ip igmp suppress v3-gsq](#), on page 2063
- [ip igmp syslog-threshold](#), on page 2064
- [ip igmp version](#), on page 2065
- [ip lisp alt-vrf](#), on page 2066
- [ip lisp database-mapping dynamic priority weight](#), on page 2067
- [ip lisp disable-spoof-alert](#), on page 2068
- [ip lisp etr](#), on page 2069
- [ip lisp etr accept-map-request-mapping](#), on page 2070
- [ip lisp etr glean-mapping](#), on page 2071
- [ip lisp etr map-cache-ttl](#), on page 2072
- [ip lisp etr map-register-ttl](#), on page 2073
- [ip lisp etr map-server key](#), on page 2074
- [ip lisp hardware-forwarding](#), on page 2075
- [ip lisp itr-etr](#), on page 2076
- [ip lisp itr](#), on page 2077
- [ip lisp itr map-resolver](#), on page 2078
- [ip lisp itr send-data-probe](#), on page 2079
- [ip lisp locator-vrf](#), on page 2080
- [ip lisp locator reachability exclude](#), on page 2081
- [ip lisp map-cache-limit](#), on page 2082
- [ip lisp map-cache drop native-forward map-request priority weight](#), on page 2083
- [ip lisp map-request-source](#), on page 2084
- [ip lisp map-resolver](#), on page 2085
- [ip lisp map-server](#), on page 2086
- [ip lisp map-server try-map-cache](#), on page 2087
- [ip lisp multicast](#), on page 2088
- [ip lisp nat-traversal](#), on page 2089
- [ip lisp ntr](#), on page 2090
- [ip lisp null0-is-alt-miss](#), on page 2091
- [ip lisp proxy-etr](#), on page 2092
- [ip lisp proxy-itr](#), on page 2093
- [ip lisp short-map-cache-ttl](#), on page 2094
- [ip lisp shortest-eid-prefix-length](#), on page 2095
- [ip lisp source-locator](#), on page 2096
- [ip lisp translate inside outside](#), on page 2097

- [ip lisp use-bgp-locators](#), on page 2098
- [ip lisp use-petr priority weight](#), on page 2099
- [ip load-sharing address](#), on page 2100
- [ip local-proxy-arp](#), on page 2101
- [ip local policy route-map](#), on page 2102
- [ip mfwf event-history cli](#), on page 2103
- [ip mfwf event-history l2](#), on page 2104
- [ip mfwf event-history nbm](#), on page 2105
- [ip mfwf event-history packet](#), on page 2106
- [ip mfwf event-history vrf](#), on page 2107
- [ip mfwf mstatic register](#), on page 2108
- [ip mroute](#), on page 2109
- [ip msdp description](#), on page 2110
- [ip msdp event-history cli](#), on page 2111
- [ip msdp event-history events](#), on page 2112
- [ip msdp event-history routes](#), on page 2113
- [ip msdp event-history tcp](#), on page 2114
- [ip msdp flush-routes](#), on page 2115
- [ip msdp group-limit source](#), on page 2116
- [ip msdp keepalive](#), on page 2117
- [ip msdp mesh-group](#), on page 2118
- [ip msdp originator-id](#), on page 2119
- [ip msdp password](#), on page 2120
- [ip msdp peer connect-source](#), on page 2121
- [ip msdp reconnect-interval](#), on page 2122
- [ip msdp redistribute](#), on page 2123
- [ip msdp sa-interval](#), on page 2124
- [ip msdp sa-limit](#), on page 2125
- [ip msdp sa-policy in](#), on page 2126
- [ip msdp sa-policy out](#), on page 2127
- [ip msdp shutdown](#), on page 2128
- [ip mtu eigrp](#), on page 2129
- [ip multicast multipath](#), on page 2130
- [ip multicast multipath resilient](#), on page 2131
- [ip multicast overlay-distributed-dr](#), on page 2132
- [ip multicast overlay-spt-only](#), on page 2133
- [ip multicast rpf select vrf group-list](#), on page 2134
- [ip name-server](#), on page 2135
- [ip nat inside](#), on page 2137
- [ip nat inside source](#), on page 2138
- [ip nat outside source](#), on page 2140
- [ip nat pool netmask](#), on page 2142
- [ip nat pool netmask](#), on page 2143
- [ip nat translation](#), on page 2144
- [ip nat translation creation-delay](#), on page 2145
- [ip nat translation max-entries](#), on page 2146

- [ip nat translation sampling-timeout](#), on page 2147
- [ip next-hop-self eigrp](#), on page 2148
- [ip offset-list eigrp](#), on page 2149
- [ip ospf advertise-subnet](#), on page 2150
- [ip ospf authentication-key](#), on page 2151
- [ip ospf authentication](#), on page 2152
- [ip ospf authentication key-chain](#), on page 2153
- [ip ospf bfd](#), on page 2154
- [ip ospf cost](#), on page 2155
- [ip ospf dead-interval](#), on page 2156
- [ZZZ_4621](#), on page 2157
- [ip ospf event-history cli](#), on page 2158
- [ip ospf event-history detail](#), on page 2159
- [ip ospf hello-interval](#), on page 2160
- [ip ospf message-digest-key md5](#), on page 2161
- [ip ospf mtu-ignore](#), on page 2162
- [ip ospf network broadcast](#), on page 2163
- [ip ospf network point-to-point](#), on page 2164
- [ip ospf passive-interface](#), on page 2165
- [ip ospf prefix-attributes n-flag-clear](#), on page 2166
- [ip ospf priority](#), on page 2167
- [ip ospf retransmit-interval](#), on page 2168
- [ip ospf shutdown](#), on page 2169
- [ip ospf transmit-delay](#), on page 2170
- [ip passive-interface eigrp](#), on page 2171
- [ip pim anycast-rp](#), on page 2172
- [ip pim assert-rate-limit](#), on page 2173
- [ip pim auto-enable](#), on page 2174
- [ip pim auto-rp listen](#), on page 2175
- [ip pim auto-rp mapping-agent-policy](#), on page 2176
- [ip pim auto-rp mapping-agent send-rp-discovery](#), on page 2177
- [ip pim auto-rp rp-candidate-policy](#), on page 2178
- [ip pim auto-rp rp-candidate send-rp-announce group-list route-map prefix-list](#), on page 2179
- [ip pim bfd-instance](#), on page 2180
- [ip pim bfd](#), on page 2181
- [ip pim bidir-rp-limit](#), on page 2182
- [ip pim border-router](#), on page 2183
- [ip pim border](#), on page 2184
- [ip pim bsr-candidate](#), on page 2185
- [ip pim bsr bsr-policy](#), on page 2186
- [ip pim bsr listen](#), on page 2187
- [ip pim bsr rp-candidate-policy](#), on page 2188
- [ip pim dr-delay](#), on page 2189
- [ip pim dr-priority](#), on page 2190
- [ip pim event-history assert](#), on page 2191
- [ip pim event-history bidir](#), on page 2192

- [ip pim event-history cli](#), on page 2193
- [ip pim event-history data-register-receive](#), on page 2194
- [ip pim event-history hello](#), on page 2195
- [ip pim event-history join-prune-summary](#), on page 2196
- [ip pim event-history join-prune-tw](#), on page 2197
- [ip pim event-history join-prune](#), on page 2198
- [ip pim event-history mrrib](#), on page 2199
- [ip pim event-history mvpn](#), on page 2200
- [ip pim event-history nbm](#), on page 2201
- [ip pim event-history null-register](#), on page 2202
- [ip pim event-history packet](#), on page 2203
- [ip pim event-history pim-library](#), on page 2204
- [ip pim event-history rp](#), on page 2205
- [ip pim event-history txlist](#), on page 2206
- [ip pim event-history vpc](#), on page 2207
- [ip pim event-history vrf](#), on page 2208
- [ip pim evpn-border-leaf](#), on page 2209
- [ip pim extranet](#), on page 2210
- [ip pim file-debug](#), on page 2211
- [ip pim flush-routes](#), on page 2212
- [ip pim group-list](#), on page 2213
- [ip pim hello-authentication ah-md5](#), on page 2214
- [ip pim hello-interval](#), on page 2215
- [ip pim isolate](#), on page 2216
- [ip pim jp-interval](#), on page 2217
- [ip pim jp-policy](#), on page 2218
- [ip pim log-neighbor-changes](#), on page 2219
- [ip pim neighbor-policy prefix-list](#), on page 2220
- [ip pim passive](#), on page 2221
- [ip pim pre-build-spt](#), on page 2222
- [ip pim register-policy](#), on page 2223
- [ip pim register-rate-limit](#), on page 2224
- [ip pim register-source](#), on page 2225
- [ip pim register-until-stop](#), on page 2226
- [ip pim rp-address](#), on page 2227
- [ip pim rp-candidate group-list route-map prefix-list](#), on page 2228
- [ip pim sg-expiry-timer infinity](#), on page 2229
- [ip pim sparse-mode](#), on page 2230
- [ip pim ssm](#), on page 2231
- [ip pim state-limit](#), on page 2232
- [ip pim strict-rfc-compliant](#), on page 2233
- [ip pim strict-rfc-compliant](#), on page 2234
- [ip ping source-interface](#), on page 2235
- [ip policy match router-address](#), on page 2236
- [ip policy route-map](#), on page 2237
- [ip port-unreachable](#), on page 2238

- ip port access-group, on page 2239
- ip port access-group, on page 2240
- ip prefix-list description, on page 2241
- ip prefix-list permit, on page 2242
- ip proxy-arp, on page 2243
- ip radius source-interface, on page 2244
- ip redirects, on page 2245
- ip rip authentication key-chain, on page 2246
- ip rip authentication mode text, on page 2247
- ip rip metric, on page 2248
- ip rip passive-interface, on page 2249
- ip rip poison-reverse, on page 2250
- ip rip route-filter route in, on page 2251
- ip rip summary-address, on page 2252
- ip route, on page 2253
- ip route static bfd, on page 2254
- ip router eigrp, on page 2255
- ip router isis, on page 2256
- ip router ospf area, on page 2257
- ip router ospf multi-area, on page 2258
- ip router rip, on page 2259
- ip routing download-on-convergence, on page 2260
- ip routing event-history, on page 2261
- ip routing multicast event-history cli, on page 2262
- ip routing multicast event-history mdt, on page 2263
- ip routing multicast event-history mfdm-debug, on page 2264
- ip routing multicast event-history mfdm-events, on page 2265
- ip routing multicast event-history mfdm-stats, on page 2266
- ip routing multicast event-history nbm, on page 2267
- ip routing multicast event-history notify-clients, on page 2268
- ip routing multicast event-history rib-summary, on page 2269
- ip routing multicast event-history rib, on page 2270
- ip routing multicast event-history urib-debug, on page 2271
- ip routing multicast event-history vrf, on page 2272
- ip routing multicast file-debug, on page 2273
- ip routing multicast holddown, on page 2274
- ip routing multicast mfdm-buffer-route-count, on page 2275
- ip routing multicast software-replicate, on page 2276
- ip routing multicast trace enable, on page 2277
- ip routing multicast trace entries, on page 2278
- ip routing multicast trace records, on page 2279
- ip secondary, on page 2280
- ip service-reflect destination to mask-len source, on page 2281
- ip service-reflect mode regular, on page 2282
- ip sla, on page 2283
- ip sla group schedule, on page 2284

- [ip sla logging traps](#), on page 2286
- [ip sla reaction-configuration react](#), on page 2287
- [ip sla reaction-trigger](#), on page 2288
- [ip sla reset](#), on page 2289
- [ip sla responder](#), on page 2290
- [ip sla responder twamp](#), on page 2291
- [ip sla restart](#), on page 2292
- [ip sla schedule](#), on page 2293
- [ip sla server twamp](#), on page 2295
- [ip source-route](#), on page 2296
- [ip source binding vlan interface](#), on page 2297
- [ip source icmp-errors](#), on page 2298
- [ip split-horizon eigrp](#), on page 2299
- [ip ssh source-interface](#), on page 2300
- [ip summary-address eigrp ipv6 summary-address eigrp](#), on page 2301
- [ip tacacs source-interface](#), on page 2302
- [ip tcp mss](#), on page 2303
- [ip tcp path-mtu-discovery](#), on page 2304
- [ip tcp synwait-time](#), on page 2305
- [ip telnet source-interface](#), on page 2306
- [ip tftp source-interface](#), on page 2307
- [ip traceroute source-interface](#), on page 2308
- [ip ttl](#), on page 2309
- [ip udp relay addrgroup](#), on page 2310
- [ip udp relay subnet-broadcast](#), on page 2311
- [ip unnumbered](#), on page 2312
- [ip unreachable](#), on page 2313
- [ip verify source dhcp-snooping-vlan](#), on page 2314
- [ip verify unicast source reachable-via rx](#), on page 2315
- [ipv6](#), on page 2316
- [ipv6 access-class](#), on page 2318
- [ipv6 access-list](#), on page 2319
- [ipv6 access-list match-local-traffic](#), on page 2320
- [ipv6 address](#), on page 2321
- [ipv6 address dhcp](#), on page 2322
- [ipv6 address use-link-local-only](#), on page 2323
- [ipv6 adjacency-stale-timer](#), on page 2324
- [ipv6 adjacency route distance](#), on page 2325
- [ipv6 amt gateway](#), on page 2326
- [ipv6 amt relay](#), on page 2327
- [ipv6 destination](#), on page 2328
- [ipv6 dhcp-ldra](#), on page 2329
- [ipv6 dhcp-ldra attach-policy](#), on page 2330
- [ipv6 dhcp-ldra attach-policy vlan client](#), on page 2331
- [ipv6 dhcp guard](#), on page 2332
- [ipv6 dhcp guard](#), on page 2333

- [ipv6 dhcp guard policy](#), on page 2334
- [ipv6 dhcp relay](#), on page 2335
- [ipv6 dhcp relay address](#), on page 2336
- [ipv6 dhcp relay address ipv6 dhcp relay address](#), on page 2337
- [ipv6 dhcp relay option type cisco](#), on page 2338
- [ipv6 dhcp relay option vpn](#), on page 2339
- [ipv6 dhcp relay source-interface](#), on page 2340
- [ipv6 dhcp relay source-interface](#), on page 2341
- [ipv6 flow monitor input](#), on page 2342
- [ipv6 flow monitor input](#), on page 2343
- [ipv6 flow monitor input](#), on page 2344
- [ipv6 forward](#), on page 2345
- [ipv6 host](#), on page 2346
- [ipv6 link-local](#), on page 2347
- [ipv6 local policy route-map](#), on page 2348
- [ipv6 mld group-timeout](#), on page 2349
- [ipv6 mld immediate-leave](#), on page 2350
- [ipv6 mld join-group](#), on page 2351
- [ipv6 mld last-member-query-count](#), on page 2352
- [ipv6 mld last-member-query-response-time](#), on page 2353
- [ipv6 mld querier](#), on page 2354
- [ipv6 mld query-interval](#), on page 2355
- [ipv6 mld query-max-response-time](#), on page 2356
- [ipv6 mld report-link-local-groups](#), on page 2357
- [ipv6 mld report](#), on page 2358
- [ipv6 mld robustness-variable](#), on page 2359
- [ipv6 mld ssm-translate](#), on page 2360
- [ipv6 mld startup-query-count](#), on page 2361
- [ipv6 mld startup-query-interval](#), on page 2362
- [ipv6 mld state-limit](#), on page 2363
- [ipv6 mld static](#), on page 2364
- [ipv6 mld version](#), on page 2365
- [ipv6 nd cache limit](#), on page 2366
- [ipv6 nd dad attempts](#), on page 2367
- [ipv6 nd dadns-discover](#), on page 2368
- [ipv6 nd hop-limit](#), on page 2369
- [ipv6 nd mac-extract](#), on page 2370
- [ipv6 nd managed-config-flag](#), on page 2371
- [ipv6 nd mtu](#), on page 2372
- [ipv6 nd ns-interval](#), on page 2373
- [ipv6 nd off-list timeout](#), on page 2374
- [ipv6 nd other-config-flag](#), on page 2375
- [ipv6 nd prefix](#), on page 2376
- [ipv6 nd prefix default](#), on page 2377
- [ipv6 nd ra-interval](#), on page 2378
- [ipv6 nd ra-lifetime](#), on page 2379

- [ipv6 nd ra dns search-list sequence](#), on page 2380
- [ipv6 nd ra dns search-list suppress](#), on page 2381
- [ipv6 nd ra dns server sequence](#), on page 2382
- [ipv6 nd ra dns server suppress](#), on page 2383
- [ipv6 nd ra route suppress](#), on page 2384
- [ipv6 nd rguard](#), on page 2385
- [ipv6 nd rguard](#), on page 2386
- [ipv6 nd rguard attach-policy](#), on page 2387
- [ipv6 nd rguard policy](#), on page 2388
- [ipv6 nd reachable-time](#), on page 2389
- [ipv6 nd retrans-timer](#), on page 2390
- [ipv6 nd route route-preference High Low Medium infinite](#), on page 2391
- [ipv6 nd router-preference High Low Medium](#), on page 2392
- [ipv6 nd solicit-na accept](#), on page 2393
- [ipv6 nd suppress-ra](#), on page 2394
- [ipv6 nd synchronize](#), on page 2395
- [ipv6 neighbor](#), on page 2396
- [ipv6 neighbor allow-static-neighbor-outside-subnet](#), on page 2397
- [ipv6 neighbor binding](#), on page 2398
- [ipv6 neighbor binding](#), on page 2399
- [ipv6 neighbor binding logging](#), on page 2400
- [ipv6 neighbor binding max-entries](#), on page 2401
- [ipv6 neighbor tracking](#), on page 2402
- [ipv6 pim anycast-rp](#), on page 2403
- [ipv6 pim bidir-rp-limit](#), on page 2404
- [ipv6 pim border](#), on page 2405
- [ipv6 pim bsr-candidate](#), on page 2406
- [ipv6 pim bsr bsr-policy](#), on page 2407
- [ipv6 pim bsr listen](#), on page 2408
- [ipv6 pim bsr rp-candidate-policy](#), on page 2409
- [ipv6 pim dr-priority](#), on page 2410
- [ipv6 pim event-history assert-receive](#), on page 2411
- [ipv6 pim event-history bidir](#), on page 2412
- [ipv6 pim event-history hello](#), on page 2413
- [ipv6 pim event-history join-prune](#), on page 2414
- [ipv6 pim event-history null-register](#), on page 2415
- [ipv6 pim event-history packet](#), on page 2416
- [ipv6 pim event-history rp](#), on page 2417
- [ipv6 pim event-history vrf](#), on page 2418
- [ipv6 pim flush-routes](#), on page 2419
- [ipv6 pim hello-interval](#), on page 2420
- [ipv6 pim isolate](#), on page 2421
- [ipv6 pim jp-policy](#), on page 2422
- [ipv6 pim log-neighbor-changes](#), on page 2423
- [ipv6 pim neighbor-policy](#), on page 2424
- [ipv6 pim passive](#), on page 2425

- [ipv6 pim register-policy](#), on page 2426
- [ipv6 pim register-rate-limit](#), on page 2427
- [ipv6 pim rp-address](#), on page 2428
- [ipv6 pim rp-candidate group](#), on page 2429
- [ipv6 pim sparse-mode](#), on page 2430
- [ipv6 pim ssm](#), on page 2431
- [ipv6 pim state-limit](#), on page 2432
- [ipv6 pim use-shared-tree-only spt-threshold infinity group-list](#), on page 2433
- [ipv6 policy route-map](#), on page 2434
- [ipv6 port traffic-filter](#), on page 2435
- [ipv6 prefix-list description](#), on page 2436
- [ipv6 prefix-list permit](#), on page 2437
- [ipv6 queue-packets](#), on page 2438
- [ipv6 redirects](#), on page 2439
- [ipv6 route](#), on page 2440
- [ipv6 route static bfd](#), on page 2441
- [ipv6 router isis](#), on page 2442
- [ipv6 router ospfv3 area](#), on page 2443
- [ipv6 router ospfv3 multi-area](#), on page 2444
- [ipv6 routing event-history size](#), on page 2445
- [ipv6 routing multicast event-history cli](#), on page 2446
- [ipv6 routing multicast event-history mfdm-debug](#), on page 2447
- [ipv6 routing multicast event-history mfdm-events](#), on page 2448
- [ipv6 routing multicast event-history mfdm-stats](#), on page 2449
- [ipv6 routing multicast event-history rib-summary](#), on page 2450
- [ipv6 routing multicast event-history rib](#), on page 2451
- [ipv6 routing multicast event-history vrf](#), on page 2452
- [ipv6 routing multicast holddown](#), on page 2453
- [ipv6 routing multicast software-replication](#), on page 2454
- [ipv6 snooping](#), on page 2455
- [ipv6 snooping](#), on page 2456
- [ipv6 snooping policy](#), on page 2457
- [ipv6 switch-packets](#), on page 2458
- [ipv6 traffic-filter](#), on page 2459
- [ipv6 unreachable](#), on page 2460
- [ipv6 verify unicast source reachable-via rx](#), on page 2461
- [is-type](#), on page 2462
- [ishow cli find nodes](#), on page 2463
- [ishow cli modes](#), on page 2464
- [ishow cli nodes](#), on page 2465
- [ishow cli paths](#), on page 2466
- [ishow cli tags](#), on page 2467
- [ishow core backtrace](#), on page 2468
- [isis authentication-check](#), on page 2469
- [isis authentication-check level-1](#), on page 2470
- [isis authentication-check level-2](#), on page 2471

- isis authentication-type cleartext, on page 2472
- isis authentication-type cleartext, on page 2473
- isis authentication key-chain, on page 2474
- isis authentication key-chain, on page 2475
- isis bfd, on page 2476
- isis circuit-type, on page 2477
- isis csnp-interval level, on page 2478
- isis event-history adjacency, on page 2479
- isis event-history cli, on page 2480
- isis event-history csnp, on page 2481
- isis event-history dis, on page 2482
- isis event-history events, on page 2483
- isis event-history graceful, on page 2484
- isis event-history ha, on page 2485
- isis event-history iih, on page 2486
- isis event-history lsp-flood, on page 2487
- isis event-history lsp-gen, on page 2488
- isis event-history mtr, on page 2489
- isis event-history perf, on page 2490
- isis event-history psnp, on page 2491
- isis event-history redist, on page 2492
- isis event-history spf-leaf, on page 2493
- isis event-history spf-tree, on page 2494
- isis event-history sr, on page 2495
- isis event-history tlv, on page 2496
- isis event-history ulib, on page 2497
- isis event-history urib, on page 2498
- isis hello-interval, on page 2499
- isis hello-interval level, on page 2500
- isis hello-multiplier, on page 2501
- isis hello-multiplier level, on page 2502
- isis hello-padding, on page 2503
- isis ipv6 bfd, on page 2504
- isis ipv6 metric, on page 2505
- isis lsp-interval, on page 2506
- isis mesh-group, on page 2507
- isis metric, on page 2508
- isis mtu-check, on page 2509
- isis mtu-check level, on page 2510
- isis network point-to-point, on page 2511
- isis passive-interface, on page 2512
- isis prefix-attributes n-flag-clear, on page 2513
- isis priority level, on page 2514
- isis retransmit-interval, on page 2515
- isis retransmit-throttle-interval, on page 2516
- isis shutdown, on page 2517

- [isolate](#), on page 2518
- [isolate](#), on page 2519
- [isolate](#), on page 2520
- [isolate](#), on page 2521
- [isolate](#), on page 2522
- [isolate](#), on page 2523
- [isolate](#), on page 2524
- [itd](#), on page 2525
- [itd device-group](#), on page 2526
- [itd session access-list refresh](#), on page 2527
- [itd session device-group](#), on page 2528
- [itd statistics](#), on page 2529

icam monitor entries acl module inst

[no] icam monitor entries acl module <module> inst <inst>

Syntax Description

no	(Optional) Negate a command or set its defaults
icam	intelligent CAM
monitor	icam monitor
entries	icam monitor entries stats
acl	icam monitor entries type ACL
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number

Command Mode

- /exec/configure

icam monitor interval num_intervals

[no] icam monitor interval <interval-hours> num_intervals <number-of-intervals>

Syntax Description

no	(Optional) Negate a command or set its defaults
icam	intelligent CAM
monitor	icam monitor
interval	icam monitor interval
<i>interval-hours</i>	icam monitor interval in hours
num_intervals	icam monitor history
<i>number-of-intervals</i>	number of intervals to keep in icam monitor history

Command Mode

- /exec/configure

icam monitor resource acl_tcam module inst

[no] icam monitor resource { acl_tcam | fib_tcam } module <module> inst <inst>

Syntax Description

no	(Optional) Negate a command or set its defaults
icam	intelligent CAM
monitor	icam monitor
resource	icam monitor resource utilization
acl_tcam	icam monitor resource type ACL TCAM
fib_tcam	icam monitor resource type FIB TCAM
module	Module Number
<i>module</i>	Enter Module Number
inst	ASIC/Forwarding Engine Instance Number
<i>inst</i>	Enter Instance Number

Command Mode

- /exec/configure

icam monitor scale

```
[no] icam monitor scale { { threshold info <ithres> warning <wthres> critical <cthes> } | { { { l2-switching
{ mac-addresses | mst-instances | mst-vports | rpvst-vports | rpvst-vlans | total-vlans-x-ports | vlans } } | {
multicast-routing { multicast-routes | igmp-groups | pim-neighbors | outgoing-interfaces } } | { unicast-routing
{ bfd-sessions | eigrp-routes | ipv4-arp | ipv4-host-routes | ipv6-host-routes | ipv4-isis-routes | ospf-nbr | ospf-lsa
| ospf-area | ospf-vrf | ospf-passive-intf } } | { vxlan { test } } } } limit <nlimit> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
icam	intelligent CAM
monitor	icam monitor
scale	icam monitor scale
l2-switching	Layer 2 switching
multicast-routing	Multicast routing
unicast-routing	Unicast routing
vxlan	VxLAN
mac-addresses	MAC addresses
mst-instances	MST instances
mst-vports	MST virtual ports
rpvst-vports	RPVST virtual ports
rpvst-vlans	RPVST VLANs
total-vlans-x-ports	Total number of VLANs x ports with switchport isolated
vlans	VLANs
multicast-routes	Multicast routes
igmp-groups	IGMP groups
pim-neighbors	PIM neighbors
outgoing-interfaces	Outgoing interfaces
bfd-sessions	BFD sessions
eigrp-routes	EIGRP routes
ipv4-arp	IPv4 ARP
ipv4-host-routes	IPv4 host routes

ipv6-host-routes	IPv6 host routes
ipv4-isis-routes	IPv4 IS-IS routes
ospf-nbr	OSPF neighbors
ospf-lsa	OSPF LSAs
ospf-area	OSPF Areas
ospf-vrf	OSPF VRFs
ospf-passive-intf	OSPF passive interfaces
test	VxLAN test
limit	Change feature limit
<i>nlimit</i>	New feature limit
threshold	Change percent threshold limit
info	Info threshold
<i>ithres</i>	Info threshold percent
warning	Warning threshold
<i>wthres</i>	Warning threshold percent
critical	Critical threshold
<i>cthres</i>	Critical threshold percent

Command Mode

- /exec/configure

icam monitor scale

[no] icam monitor scale

Syntax Description

no	(Optional) Negate a command or set its defaults
icam	intelligent CAM
monitor	icam monitor
scale	icam monitor scale

Command Mode

- /exec/configure

icmp-echo

```
[no] icmp-echo { <hostname> | <ip-address> | <ipv6-address> } { [ source-ip { <source-ip-hostname> | <source-ip-address> | <source-ipv6-address> } ] | [ source-interface <if_index> ] }
```

Syntax Description

no	(Optional)
<i>source-ip</i>	(Optional) source-interface
icmp-echo	ICMP Echo Operation
<i>hostname</i>	Destination hostname, broadcast disallowed
<i>ip-address</i>	Destination IP address, broadcast disallowed
source-interface	(Optional) Source Interface (ingress icmp packet interface)
<i>if_index</i>	(Optional) Source Interface
<i>source-ip-hostname</i>	(Optional) source IP hostname, broadcast disallowed
<i>source-ip-address</i>	(Optional) source IP address, broadcast disallowed

Command Mode

- /exec/configure/ip-sla

icmpv6 cfs-queue

{ icmpv6 cfs-queue <size> } | { no icmpv6 cfs-queue }

Syntax Description

no	Negate a command or set its defaults
icmpv6	ICMPv6 Commands
cfs-queue	cfs-queue
<i>size</i>	Size for adjacencies to be sent in CFSOE payload

Command Mode

- /exec/configure

icmpv6 library mts-queue

{ icmpv6 library mts-queue <size> } | { no icmpv6 library mts-queue }

Syntax Description

no	Negate a command or set its defaults
icmpv6	ICMPv6 Commands
library	library data queue
mts-queue	mts-queue
<i>size</i>	Size for icmpv6 data sap qlimit

Command Mode

- /exec/configure

icmpv6 mts-queue

{ icmpv6 mts-queue <size> } | { no icmpv6 mts-queue }

Syntax Description

no	Negate a command or set its defaults
icmpv6	ICMPv6 Commands
mts-queue	mts-queue
<i>size</i>	Size for icmpv6 data sap qlimit

Command Mode

- /exec/configure

import

import

Syntax Description

import	import
--------	--------

Command Mode

- /exec/configure

import interface

import interface <if0>

Syntax Description

import	import
interface	Interface configuration
<i>if0</i>	interface type and number in module/slot format

Command Mode

- /exec/configure

import l2vpn evpn

[no | default] import l2vpn evpn [route-map <import-map>] [reoriginate]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
import	Import the routes into another AF
l2vpn	L2VPN
evpn	EVPN
reoriginate	(Optional) Reoriginate the route with new RT
route-map	(Optional) Apply route-map to specify import criteria
<i>import-map</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6

import map

[no] import map <rmap-name> [evpn]

Syntax Description

no	(Optional) Negate a command or set its defaults
import	VRF import
map	Route-map based VRF import
<i>rmap-name</i>	Route-map name
evpn	(Optional) EVPN

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

import running-config

import running-config [exclude interface ethernet]

Syntax Description

import	import
running-config	running-config
exclude	(Optional) Exclude
interface	(Optional) Exclude all interfaces of this type
ethernet	(Optional) running-config excluding physical interfaces

Command Mode

- /exec/configure

import vpn unicast

[no | default] import vpn unicast [route-map <import-map>] [reoriginate]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
import	Import the routes into another AF
vpn	L3VPN
unicast	unicast
reoriginate	(Optional) Reoriginate the route with new RT
route-map	(Optional) Apply route-map to specify import criteria
<i>import-map</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn

import vrf default map

```
import vrf default [ <prefix-limit> ] map <rmap-name> | no import vrf default [ <prefix-limit> ] map
<rmap-name>
```

Syntax Description

no	Negate a command or set its defaults
import	VRF import
vrf	Virtual Router Context
default	VRF name (default)
<i>prefix-limit</i>	(Optional) Maximum prefix limit
map	Route-map based VRF import
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

in-label allocate

[no] in-label <static-inlabel> allocate [policy { <prefix> <mask> | <prefix-mask> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
in-label	Configure local label assignment and forwarding for the LSP
allocate	Allocate this label
policy	(Optional) Allocate policy-based IP prefix
<i>static-inlabel</i>	Label Value
<i>prefix</i>	(Optional) Destination prefix
<i>mask</i>	(Optional) Destination prefix mask
<i>prefix-mask</i>	(Optional) Destination prefix/mask

Command Mode

- /exec/configure/mpls_static/ipv4/lsp

inband-telemetry exporter

[no] inband-telemetry exporter <exportername>

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
exporter	Define a events Exporter
<i>exportername</i>	Name of event Exporter

Command Mode

- /exec/configure/config-int

inband-telemetry flow-profile

[no] inband-telemetry flow-profile

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
flow-profile	Define a INT flow-profile

Command Mode

- /exec/configure/config-int

inband-telemetry monitor

[no] inband-telemetry monitor <monitorname>

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
monitor	Define a INT Monitor
<i>monitorname</i>	Name of INT Monitor

Command Mode

- /exec/configure/config-int

inband-telemetry queue-profile

[no] inband-telemetry queue-profile [<queue_profilename> | queue-profile-default]

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
queue-profile	Define a INT queue_profile
<i>queue_profilename</i>	(Optional) Name of INT queue_profile
queue-profile-default	(Optional) Queue Profile Default Configuration

Command Mode

- /exec/configure/config-int

inband-telemetry record

[no] inband-telemetry record <recordname>

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
record	Define a INT Record
<i>recordname</i>	Record name

Command Mode

- /exec/configure/config-int

inband-telemetry system monitor

[no] inband-telemetry system monitor <monitorname>

Syntax Description

system	global config
inband-telemetry	int global settings
monitor	int Monitor to be applied
<i>monitorname</i>	int Monitor to be applied

Command Mode

- /exec/configure/config-int

inband-telemetry watchlist ip

[no] inband-telemetry watchlist ip <watchlistname>

Syntax Description

inband-telemetry	Enable/Disable inband telemetry configuration
watchlist	Define a INT watchlist
ip	Configure INT IP watchlist
<i>watchlistname</i>	Name of INT watchlist

Command Mode

- /exec/configure/config-int

include-icv-indicator

[no] include-icv-indicator

Syntax Description

include-icv-indicator	Include ICV Indicator paramset in MKPDU
-----------------------	---

Command Mode

- /exec/configure/macsec-policy

include profile

[no] include profile { <all_conf_profile_name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
include	Include a port-profile
profile	config-profile
<i>all_conf_profile_name</i>	Enter the name of the profile

Command Mode

- /exec/configure

include profile any

[no] include profile any

Syntax Description

no	(Optional) Negate a command or set its defaults
include	Include a port-profile
profile	config-profile
any	dynamically include profile during apply

Command Mode

- /exec/configure

index next-label

{ no index <idx> | index<idx> next-label <lbl> }

Syntax Description

no	Negate a command or set its defaults
index	Next entry index
<i>idx</i>	Index number
next-label	Label Configuration
<i>lbl</i>	MPLS Label value

Command Mode

- /exec/configure/sr/te/exp_path

index next

```
{ { index <index> { next-address [ loose | strict ] <ipaddr> | exclude-address <ipaddr> } } | { no index <index> } }
```

Syntax Description

no	Negate a command or set its defaults
index	Specify the next entry index to add, edit (or delete)
<i>index</i>	Previous index number
next-address	Specify the next address in the path
loose	(Optional) Target address is loose
strict	(Optional) Target address is strict
exclude-address	Exclude an address from subsequent partial path segments
<i>ipaddr</i>	Enter IP address (A.B.C.D)

Command Mode

- /exec/configure/te/expl-path

ingress-mtu

ingress-mtu <mtu_value> | no ingress-mtu

Syntax Description

no	Negate the command
ingress-mtu	set/reset ingress port mtu value
<i>mtu_value</i>	mtu value

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet handle auto 424

ingress-replication protocol bgp

[no] ingress-replication protocol bgp

Syntax Description

no	(Optional) Negate a command or set its defaults
ingress-replication	Configure ingress replication
protocol	Control protocol to use
bgp	Border Gateway Protocol

Command Mode

- /exec/configure/if-nve/vni

ingress-replication protocol static

[no] ingress-replication protocol static

Syntax Description

no	(Optional) Negate a command or set its defaults
ingress-replication	Configure ingress replication
protocol	Control protocol to use
static	Static End-point Configuration

Command Mode

- /exec/configure/if-nve/vni

ingress

{ ingress <ifh> | no ingress }

Syntax Description

no	Negate a command or set its defaults
ingress	Ingress interface to determine enhanced forwarding enabled
<i>ifh</i>	Name of the interface for ngoam on which fabric forwarding is configured

Command Mode

- /exec/configure/configngoamprofile

ingress interface

[no] ingress interface <interface-ref> [next-hop <ip-addr>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ingress	ITD ingress interface
interface	ITD ingress interface
<i>interface-ref</i>	
next-hop	(Optional) next hop ip address
<i>ip-addr</i>	(Optional) Next hop IPv4 address connected to ingress interface

Command Mode

- /exec/configure/itd /exec/configure/itd-inout

ingress interface

[no] ingress interface <interface-ref> [next-hop <ip-addr>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ingress	Configure ingress interface for PLB service
interface	Ingress interface
<i>interface-ref</i>	
next-hop	(Optional) next hop ip address
<i>ip-addr</i>	(Optional) Next hop IPv4 address connected to ingress intrerface

Command Mode

- /exec/configure/plb /exec/configure/plb-inout

inherit peer-policy

[no] inherit peer-policy <peer-policy-template-name> <policy-preference>

Syntax Description

no	(Optional) Negate a command or set its defaults
inherit	Inherit a template
peer-policy	Inherit a peer-policy template
<i>peer-policy-template-name</i>	Template name
<i>policy-preference</i>	Sequence number

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

inherit peer-policy

[no] inherit peer-policy <peer-policy-template-name> <policy-preference>

Syntax Description

no	(Optional) Negate a command or set its defaults
inherit	Inherit a template
peer-policy	Inherit a peer-policy template
<i>peer-policy-template-name</i>	Template name
<i>policy-preference</i>	Sequence number

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

inherit peer-session

[no] inherit peer-session <peer-session-template-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
inherit	Inherit a template
peer-session	Inherit a peer-session template
<i>peer-session-template-name</i>	Template name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

inherit peer

[no] inherit peer <peer-template-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
inherit	Inherit a template
peer	Inherit a peer template
<i>peer-template-name</i>	Peer template name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-vrf-neighbor
/exec/configure/router-bgp/router-bgp-prefixneighbor
/exec/configure/router-bgp/router-bgp-vrf-prefixneighbor

inherit port-profile

[no] inherit port-profile { <s0> | <s1> }

Syntax Description

no	(Optional) Negate a command or set its defaults
inherit	Inherit a port-profile
port-profile	Inherit a port-profile
<i>s0</i>	Enter the name of the profile
<i>s1</i>	Enter the name of the profile

Command Mode

- /exec/configure/if-any /exec/configure/if-port-channel exec/configure/if-port-channel-range /exec/configure/if-ethernet-m /exec/configure/if-ethernet-switch-m /exec/configure/if-te /exec/configure/if-pseudowire

initial-delay

[no] initial-delay <time-in-sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
initial-delay	Configure delay interval to connect to the BMP server
<i>time-in-sec</i>	Delay value

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

initial-refresh skip

[no] initial-refresh { skip | delay <time-in-sec> }

Syntax Description

no	(Optional) Negate a command or set its defaults
initial-refresh	Configure initial-refresh for the BMP server
skip	Skip sending the initial route update to the BMP server
delay	Delay after which the initial route update is sent to the BMP server
<i>time-in-sec</i>	Delay value

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

inject-map exist-map

[no] inject-map <inject-map-name> exist-map <exist-map-name> [copy-attributes]

Syntax Description

no	(Optional) Negate a command or set its defaults
inject-map	Routemap which specifies prefixes to inject
<i>inject-map-name</i>	Route-map name
exist-map	Routemap which specifies exist condition
<i>exist-map-name</i>	Route-map name
copy-attributes	(Optional) Copy attributes from aggregate

Command Mode

- /exec/configure/router-bgp/router-bgp-af

innoshell

innoshell

Syntax Description

innoshell	innoshell
-----------	-----------

Command Mode

- /exec

innoshell cmd

innoshell cmd <cmd>

Syntax Description

innoshell	innoshell
cmd	Specify command
<i>cmd</i>	Quoted commands to be exec

Command Mode

- /exec

innoshell module

innoshell module <module>

Syntax Description

innoshell	innoshell
module	Select module
<i>module</i>	Module number

Command Mode

- /exec

innoshell module cmd

innoshell module <module> cmd <cmd>

Syntax Description

innoshell	innoshell
module	Select module
cmd	Specify command
<i>module</i>	Module number
<i>cmd</i>	Quoted commands to be exec

Command Mode

- /exec

install activate

install activate <patch> + [forced]

Syntax Description

install	Install package
activate	Activate package
<i>patch</i>	Package Name
forced	(Optional) non-interactive

Command Mode

- /exec

install add

```
install add { <package-name> | <uri> } [ vrf <vrf-known-name> ] [ { gpg-key | [ activate [ upgrade | downgrade ] ] [ forced ] } ]
```

Syntax Description

install	Install package
add	Add package
<i>package-name</i>	Package name
<i>uri</i>	Enter package uri
vrf	(Optional) Display per-VRF information
<i>vrf-known-name</i>	(Optional) Known VRF name
gpg-key	(Optional) GPG-KEY
activate	(Optional) Activate package
forced	(Optional) non-interactive
upgrade	(Optional) Upgrade package
downgrade	(Optional) Downgrade package

Command Mode

- /exec

install all

```
install { all [ nxos <uri> | kickstart <uri1> | system <uri3> | serial | ignore-script-errors ] + [ force ] [ non-disruptive | no-reload | noswitchover ] [ bios | no-save ] [ bios-force ] [ non-interruptive ] [ compact ] | force-all [ nxos <uri> | serial | ignore-script-errors ] + [ non-disruptive ] [ force ] }
```

Syntax Description

install	upgrade software
all	Upgrade the system
ignore-script-errors	(Optional) Ignore script errors from dynamic confcheck
kickstart	(Optional) boot-variable name
<i>uri1</i>	(Optional) Enter image uri
system	(Optional) boot-variable name
<i>uri3</i>	(Optional) Enter image uri
no-reload	(Optional) Exit right before reload during install.
noswitchover	(Optional) Exit right before reload during install.
non-interruptive	(Optional) Non-Interruptive install.
no-save	(Optional) Config not saved. Manually save config before starting install all
bios	(Optional) BIOS Only
bios-force	(Optional) Forcefully upgrade bios.
force	(Optional) Forcefully allow ISSU with target image .
non-disruptive	(Optional) Non-Disruptive install.
compact	(Optional) Compact image to make it nexus 3k only
nxos	(Optional) boot-variable name
<i>uri</i>	(Optional) Enter image uri
serial	(Optional) Upgrade linecards in serial
force-all	Force upgrade the system

Command Mode

- /exec

install all network-os

install all network-os <uri>

Syntax Description

install	upgrade software
all	Upgrade the system
network-os	non-cisco OS
<i>uri</i>	Enter image uri

Command Mode

- /exec

install commit

install commit [<patch>]

Syntax Description

install	Install package
commit	Commit software patch
<i>patch</i>	(Optional) Package Name

Command Mode

- /exec

install deactivate

install deactivate <patch> + [forced]

Syntax Description

install	Install package
deactivate	Deactivate package
<i>patch</i>	Package Name[Note: startup configuration may get affected]
forced	(Optional) non-interactive

Command Mode

- /exec

install epld

```
install epld <uri1> { { module { <module> | all } { primary | golden } [ force ] } }
```

Syntax Description

install	upgrade software
epld	Install EPLD from EPLD image
<i>uri1</i>	Local URI containing EPLD Image
module	Enter the module number or module range
<i>module</i>	x or x-y
all	Install all the modules
primary	Upgrade primary fpga image
golden	Upgrade golden fpga image
force	(Optional) Force Install EPLD from EPLD image

Command Mode

- /exec

install epld

```
install epld <uri1> { { module { <module> | all } [ force ] } }
```

Syntax Description

install	upgrade software
epld	Install EPLD from EPLD image
<i>uri1</i>	Local URI containing EPLD Image
module	Enter the module number or module range
<i>module</i>	x or x-y
all	Install all the modules
force	(Optional) Force Install EPLD from EPLD image

Command Mode

- /exec

install feature-set fcoe-npv

[no] install feature-set fcoe-npv

Syntax Description

no	(Optional) Negate a command or set its defaults
install	install a feature-set
feature-set	install feature-set
fcoe-npv	FCOE-NPV

Command Mode

- /exec/configure

install license

install license <uri0> [<s0>] [format]

Syntax Description

install	upgrade software
license	install license
<i>uri0</i>	Specify URL for license file
<i>s0</i>	(Optional) Specify a target name for the license file
format	(Optional) Reformat the license file to remove invalid characters and formatting

Command Mode

- /exec

install license

install license <uri0> [<s0>]

Syntax Description

install	upgrade software
license	install license
<i>uri0</i>	Specify URL for license file
<i>s0</i>	(Optional) Specify a target name for the license file

Command Mode

- /exec

install remove

install remove { <patch> | inactive } [forced]

Syntax Description

install	Install package
remove	Remove package
<i>patch</i>	Package Name
inactive	All inactive except non-committed packages
forced	(Optional) Remove package

Command Mode

- /exec

install reset

```
install reset [ nxos { base | full } ]
```

Syntax Description

install	Install package
reset	Reload nxos with default packages
nxos	(Optional) Reloading with basenxos from fullnxos and vice-versa
base	(Optional) Reload with basenxos after resetting
full	(Optional) Reload with fullnxos after resetting

Command Mode

- /exec

install verify

install verify { <uri> | package <patch> }

Syntax Description

install	Install package
verify	Verify package for signature
<i>uri</i>	Enter package uri
package	Enter active/inactive package
<i>patch</i>	Package Name

Command Mode

- /exec

instance-id

[no] instance-id <iid>

Syntax Description

no	(Optional) Negate a command or set its defaults
instance-id	Configures Instance-ID for global data-mappings
<i>iid</i>	24-bit instance-ID value

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

instance

[no] instance <plistinst> [cross-check] | instance <plistinst>

Syntax Description

no	Negate a command or set its defaults
instance	Configure a parameter list instance
<i>plistinst</i>	Enter the name of the parameter list instance
cross-check	(Optional) Explicitly search for referencing config profile

Command Mode

- /exec/configure/param-list

instance

[no] instance <instance-id> [vlan <vlan-list>]

Syntax Description

no	Negate a command or set its defaults
instance	Map vlans to an MST instance
<i>instance-id</i>	MST instance id
vlan	(Optional) Range of vlans to add to the instance mapping
<i>vlan-list</i>	(Optional) vlan range ex: 1-65, 72, 200 - 300

Command Mode

- /exec/configure/spanning-tree/mst/configuration

instance vlan

instance <instance-id> vlan <vlan-list>

Syntax Description

instance	Map vlans to an MST instance
<i>instance-id</i>	MST instance id
vlan	Range of vlans to add to the instance mapping
<i>vlan-list</i>	vlan range ex: 1-65, 72, 200 - 300

Command Mode

- /exec/configure/spanning-tree/mst/configuration

interface

```
[no] interface <if_list> { [ qos-group <ucastqos-grp> ] }
```

Syntax Description

no	(Optional) Negate the command
interface	Configure capture-scope parameters
<i>if_list</i>	List of interfaces
qos-group	(Optional) Specify qos-group to be associated
<i>ucastqos-grp</i>	(Optional) Value 0-7

Command Mode

- /exec/configure/pkt-drop/profile

interface

[no] interface <interface-ref>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	egress interface
<i>interface-ref</i>	

Command Mode

- /exec/configure/catena-port-grp

interface

[no] interface <interface-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Applied interface
<i>interface-id</i>	Name of interface

Command Mode

- /exec/configure/static-host/dot1q /exec/configure/static-host/vni

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

interface <interface>

Syntax Description

interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	Configure interfaces
<i>interface</i>	Interface Name

Command Mode

- /exec/configure

interface

[no] interface <interface-ref>

Syntax Description

no	(Optional) Negate a command or set its defaults
interface	egress interface
<i>interface-ref</i>	

Command Mode

- /exec/configure/itd-port-grp

interface

{ interface <interface-range> } | { no interface }

Syntax Description

no	Negate a command or set its defaults
interface	Configure ngoam egress interface
<i>interface-range</i>	Configure ngoam egress interface

Command Mode

- /exec/configure/configngoamprofile

interface breakout-profile

interface breakout-profile <profile> | no interface breakout-profile [<profile>]

Syntax Description

no	Negate a command or set its defaults
interface	Configure interfaces
breakout-profile	Configure breakout-profile
<i>profile</i>	Breakout Profile

Command Mode

- /exec/configure

interface breakout module

```
interface breakout module <lem-aware-module> [ map <breakout_map> ]
```

Syntax Description

interface	Configure interfaces
breakout	Configuring the breakout for a module
module	High Bandwidth Module
<i>lem-aware-module</i>	High Bandwidth Module number
map	(Optional) Breakout Map
<i>breakout_map</i>	(Optional) Breakout Map to be applied to all the ports in this module

Command Mode

- /exec/configure

interface breakout module

[no] interface breakout module <lem-aware-module> [map <breakout_map>]

Syntax Description

no	Negate a command or set its defaults
interface	Configure interfaces
breakout	Configuring the breakout for a module
module	High Bandwidth Module
<i>lem-aware-module</i>	High Bandwidth Module number
map	(Optional) Breakout Map
<i>breakout_map</i>	(Optional) Breakout Map to be applied to all the ports in this module

Command Mode

- /exec/configure

interface breakout module port map

[no] interface breakout module <lem-aware-module> port <port_num> map <breakout_map>

Syntax Description

no	Negate a command or set its defaults
interface	Configure interfaces
breakout	Configuring the breakout for an interface
module	High Bandwidth Module
<i>lem-aware-module</i>	High Bandwidth Module number
port	High Bandwidth Port(HBP)
<i>port_num</i>	Parent(HBP / Front-panel) port to be broken out
map	Breakout Map
<i>breakout_map</i>	Breakout Map to be applied to the parent port

Command Mode

- /exec/configure

interface breakout module port map

```
interface breakout module <lem-aware-module> port <port_num> map <breakout_map>
```

Syntax Description

interface	Configure interfaces
breakout	ConfigurinG the breakout for an interface
module	High Bandwidth Module
<i>lem-aware-module</i>	High Bandwidth Module number
port	High Bandwidth Port(HBP)
<i>port_num</i>	Parent(HBP / Front-panel) port to be broken out
map	Breakout Map
<i>breakout_map</i>	Breakout Map to be applied to the parent port

Command Mode

- /exec/configure

interface down delay

[no] interface down delay |

Syntax Description

<i>down</i>	delay
no	Negate a command or set its defaults
interface	Add tunnel interface config
delay	Tunnel interface down delay config

Command Mode

- /exec/configure/if-te

interop-enable

[no] interop-enable

Syntax Description

no	(Optional) Negate a command or set its defaults
interop-enable	Enable interoperability with IOS XR boxes in the network

Command Mode

- /exec/configure/otv-isis

interval

[no] interval <timeinterval>

Syntax Description

interval	Time interval to be configured
<i>timeinterval</i>	time interval in increments of 100ms

Command Mode

- /exec/configure/config-ssx-record

interval

{ interval <interval> }

Syntax Description

interval	Wait
<i>interval</i>	Interval

Command Mode

- /exec/configure/configgoamconnectcheck

ip

```
{ [ no ] <seqnum> <permitdeny> { ip { <src_prefix> | <src_any> } { <dst_prefix> | <dst_any> } } } | { no <seqnum> }
```

Syntax Description

<code>no</code>	(Optional) Negate a command or set its defaults
<code>seqnum</code>	Sequence number
<code>ip</code>	ip
<code>permitdeny</code>	permitdeny
<code>src_prefix</code>	A.B.C.D/nn Source network prefix
<code>src_any</code>	Any source address
<code>dst_prefix</code>	A.B.C.D/nn Destination network prefix
<code>dst_any</code>	Any destination address

Command Mode

- /exec/configure/config-postcard-watchlist

ip

```
{ [ no ] <seqnum> <permitdeny> { ip { <src_prefix> | <src_any> } { <dst_prefix> | <dst_any> } } } | { no <seqnum> }
```

Syntax Description

<i>no</i>	(Optional) Negate a command or set its defaults
<i>seqnum</i>	Sequence number
<i>ip</i>	ip
<i>permitdeny</i>	permitdeny
<i>src_prefix</i>	A.B.C.D/nn Source network prefix
<i>src_any</i>	Any source address
<i>dst_prefix</i>	A.B.C.D/nn Destination network prefix
<i>dst_any</i>	Any destination address

Command Mode

- /exec/configure/config-int-watchlist

ip

ip [<ipaddress> | <ipprefix>] | no ip [<ipaddress> | <ipprefix>]

Syntax Description

no	Negate a command or set its defaults
ip	Enable HSRP IPv4 and set the virtual IP address
<i>ipaddress</i>	(Optional) Virtual IP address
<i>ipprefix</i>	(Optional) Virtual IP address and mask length

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4

ip

ip { <ipv6address> | autoconfig } | no ip [{ <ipv6address> | autoconfig }]

Syntax Description

no	Negate a command or set its defaults
ip	Enable HSRP IPv6 and set the virtual IP address
autoconfig	Obtain address using autoconfiguration

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv6

ip

[no] ip <ipaddr>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	ip address of redundancy group member
<i>ipaddr</i>	Redundancy-group node IP address

Command Mode

- /exec/configure/if-nve/rgrp

ip

```
[no] ip { { group <gaddr> } | { group-range <gaddr_start> to <gaddr_end> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	IP Address
group	Multicast group
<i>gaddr</i>	IPv4 group address
group-range	Multicast Group address range
<i>gaddr_start</i>	First Group address
to	Range
<i>gaddr_end</i>	Last Group address

Command Mode

- /exec/configure/nbm-flow-policy/attr

ip

```
{ { ip <dstip> <srcip> | ipv6 <dstipv6> <srcipv6> } }
```

Syntax Description

ip	ip address
<i>dstip</i>	Destination ipv4 address
<i>srcip</i>	source ipv4 address
ipv6	ipv6 address

Command Mode

- /exec/configure/configngoamccpayload

ip access-class

[no] ip access-class <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
access-class	Specify IPv4 access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/line

ip access-group

[no] ip access-group <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
access-group	Specify access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/if-set-acl-l3

ip access-list

[no] ip access-list <name> [client <clienttype> <clientID>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
access-list	Configure access list
<i>name</i>	List name
client	(Optional) set client type
<i>clienttype</i>	(Optional) CLI/ONEP
<i>clientID</i>	(Optional) client appID

Command Mode

- /exec/configure

ip access-list match-local-traffic

[no] ip access-list match-local-traffic | ip access-list match-local-traffic

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
access-list	Configure access list
match-local-traffic	Enable access-list matching for locally generated traffic

Command Mode

- /exec/configure

ip address

[no] ip address [{ <ip-addr> <ip-mask> | <ip-prefix> } [route-preference <pref>] [tag <tag>]] | ip address { <ip-addr> <ip-mask> | <ip-prefix> } [route-preference <pref>] [tag <tag>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
address	Configure IP address on interface
<i>ip-addr</i>	(Optional) IP address in format i.i.i.i
<i>ip-mask</i>	(Optional) IP network mask in format m.m.m.m
<i>ip-prefix</i>	(Optional) IP prefix and network mask length in format x.x.x.x/m
route-preference	(Optional) URIB route preference for local/direct routes
<i>pref</i>	(Optional) Local/direct route preference
tag	(Optional) URIB route tag value for local/direct routes
<i>tag</i>	(Optional) Local/direct tag value

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-mpls-tunnel /exec/configure/if-gre-tunnel /exec/configure/if-vsan /exec/configure/if-cpp

ip address dhcp

[no] ip address dhcp

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
address	Configure IP address on interface
dhcp	Configure IP address from a dhcp server

Command Mode

- /exec/configure/if-vlan /exec/configure/if-ethernet /exec/configure/if-mgmt-config /exec/configure/if-ethernet-all /exec/configure/if-sub

ip address ipv6 address port

[no] { ip address <ip4> | ipv6 address <ip6> } port <portnum> [protocol <proto> encoding <encoder>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Set destination IPv4 address
ipv6	Set destination IPv6 address
address	IP address
port	Set destination port
protocol	(Optional) Set transport protocol
encoding	(Optional) Set encoding format
<i>ip4</i>	Destination IPv4 Address
<i>portnum</i>	Destination port
<i>proto</i>	(Optional)
<i>encoder</i>	(Optional)

Command Mode

- /exec/configure/telemetry/destination-group

ip address secondary

```
[no] ip address { <ip-addr> <ip-mask> | <ip-prefix> } secondary [ route-preference <pref> ] [ tag <tag> ] | ip
address { <ip-addr> <ip-mask> | <ip-prefix> } secondary [ route-preference <pref> ] [ tag <tag> ]
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
address	Configure IP address on interface
<i>ip-addr</i>	IP address in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
<i>ip-prefix</i>	IP prefix and network mask length in format x.x.x.x/m
secondary	Configure additional IP addresses on interface
route-preference	(Optional) URIB route preference for local/direct routes
<i>pref</i>	(Optional) Local/direct route preference
tag	(Optional) URIB route tag value for local/direct routes
<i>tag</i>	(Optional) Local/direct tag value

Command Mode

- /exec/configure/if-igmp /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config
/exec/configure/if-gre-tunnel /exec/configure/if-6to4-tunnel /exec/configure/if-vsan /exec/configure/if-cpp

ip adjacency peer-gmac

[no] ip adjacency [vrf { <vrf-name> | <vrf-known-name> }] { <interface> { * | <ip-addr> } | * } peer-gmac

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
adjacency	Configure Adjmgr
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>interface</i>	Display specific interface adjacencies only
<i>ip-addr</i>	IPV4 source address
*	for all adjacencies in this context
peer-gmac	Set/clear the peer-gmac bit

Command Mode

- /exec/configure

ip adjacency remote-adj

[no] ip adjacency [vrf { <vrf-name> | <vrf-known-name> }] { <interface> { * | <ip-addr> } | * } remote-adj

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
adjacency	Configure Adjmgr
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>interface</i>	Display specific interface adjacencies only
<i>ip-addr</i>	IPV4 source address
*	for all adjacencies in this context
remote-adj	Set/clear the remote-adj bit

Command Mode

- /exec/configure

ip adjacency route distance

{ ip adjacency route distance <pref> } | { no ip adjacency route distance }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
adjacency	Configure Adjmgr
route	route
distance	admin-distance
<i>pref</i>	preference

Command Mode

- /exec/configure

ip amt anycast-relay-prefix

```
{ { ip amt anycast-relay-prefix <prefix> } | { no ip amt anycast-relay-prefix [ <prefix> ] } } | { ipv6 amt anycast-relay-prefix <prefix6> } | { no ipv6 amt anycast-relay-prefix [ <prefix6> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
anycast-relay-prefix	Configure anycast prefix for AMT relay
<i>prefix</i>	IP anycast prefix for AMT relay

Command Mode

- /exec/configure /exec/configure/vrf

ip amt gateway

[no] ip amt gateway

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
amt	AMT global configuration commands
gateway	Configures IPv4 AMT gateway functionality

Command Mode

- /exec/configure /exec/configure/vrf

ip amt join-policy

```
{ [ no ] { ip | ipv6 } amt join-policy <jroute-map> [ gateway <groute-map> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
join-policy	Configures what (S,G) are allowed to be joined
<i>jroute-map</i>	Route-map describing (S,G) entries allowed
gateway	(Optional) Configure join-policy per gateway
<i>groute-map</i>	(Optional) Route-map describing gateway or sets of gateways

Command Mode

- /exec/configure /exec/configure/vrf

ip amt qqic

[no] { ip | ipv6 } amt qqic <qqic-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
qqic	Configure Querier's Query Interval Code
<i>qqic-value</i>	QQIC value

Command Mode

- /exec/configure /exec/configure/vrf

ip amt relay-advertisement-address

```
{ { ip amt relay-advertisement-address <address> } | { no ip amt relay-advertisement-address [ <address> ] } | { ipv6 amt relay-advertisement-address <address6> } | { no ipv6 amt relay-advertisement-address [ <address6> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
relay-advertisement-address	Address to use by AMT relay
<i>address</i>	IP unicast address for AMT relay to use

Command Mode

- /exec/configure /exec/configure/vrf

ip amt relay

[no] ip amt relay

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
amt	AMT global configuration commands
relay	Configures IPv4 AMT relay functionality

Command Mode

- /exec/configure /exec/configure/vrf

ip amt state-limit

```
{ [ no ] { ip | ipv6 } amt state-limit <limit> [ gateway <route-map> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
state-limit	Configure the maximum number of (S,G) entries allowed
<i>limit</i>	Number of entries total or per AMT gateway
gateway	(Optional) Configure state limit per gateway
<i>route-map</i>	(Optional) Route-map describing gateway or sets of gateways

Command Mode

- /exec/configure /exec/configure/vrf

ip amt tunnel-limit

{ { { ip | ipv6 } amt tunnel-limit <limit> } | { no { ip | ipv6 } amt tunnel-limit [<limit>] } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
amt	AMT global configuration commands
tunnel-limit	Configure the maximum tunnels allowed
<i>limit</i>	Number of tunnels

Command Mode

- /exec/configure /exec/configure/vrf

ip arp

```
{ ip arp <ip-address> <mac-address> | no ip arp <ip-address> [ <mac-address> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
<i>ip-address</i>	IP address
<i>mac-address</i>	MAC address

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-vlan-common

ip arp allow-static-arp-outside-subnet

[no] ip arp allow-static-arp-outside-subnet

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
allow-static-arp-outside-subnet	Allow static ARP outside interface subnet

Command Mode

- /exec/configure

ip arp cache limit

```
{ { ip arp cache limit <max> } | { no ip arp cache limit } } [ syslog <rate> ]
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
cache	ARP cache parameters
limit	Limit size of ARP adjacencies cache
<i>max</i>	Maximum number of ARP entries
syslog	(Optional) Syslog messages
<i>rate</i>	(Optional) Syslogs per second

Command Mode

- /exec/configure

ip arp cos

{ ip arp cos <cosval> } | { no ip arp cos }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
cos	COS for ARP packet
<i>cosval</i>	COS value

Command Mode

- /exec/configure

ip arp delete

```
{ ip arp { delete-adj-on-mac-delete | refresh-adj-on-mac-delete <time-out> } | no ip arp {
delete-adj-on-mac-delete | refresh-adj-on-mac-delete } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
delete-adj-on-mac-delete	Delete the adjacency on MAC delete
refresh-adj-on-mac-delete	Set refresh timer for mac delete trigger
<i>time-out</i>	Refresh value in milliseconds

Command Mode

- /exec/configure/if-vlan-common

ip arp event-history size

[no] ip arp event-history { packet | event | sync-event | ip-sync-event | control | ha | errors | lcache | lcache-errors | client-event | client-errors | snmp | cli | suppression-event | suppression-errors | controller-errors | sm-trace | dme-event } size { <size_in_text> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	IP events
arp	Configure ARP parameters
event-history	log debug events into event history buffer
packet	inst packet logs
event	Internal event logs
sync-event	CFS and MCECM related event logs
ip-sync-event	L3 over vpc events
control	ARP control event logs
ha	HA and GR logs
errors	inst error logs
lcache	lcache logs
lcache-errors	lcache_error logs
client-event	Client_event logs
client-errors	Client_error logs
cli	cli logs
snmp	SNMP logs
suppression-event	ARP suppression event logs
suppression-errors	ARP suppression error logs
controller-errors	Controller MAC-IP route error logs
sm-trace	ARP State machine trace logs
dme-event	ARP DME event logs
size	Configure the size of the event-hist buffer
<i>size_in_text</i>	Buffer size

Command Mode

- /exec/configure

ip arp event-history size

[no] ip arp event-history { packet | event | sync-event | ip-sync-event | control | ha | errors | lcache | lcache-errors | client-event | client-errors | snmp | cli | suppression-event | suppression-errors | controller-errors | sm-trace | dme-event } size { <size_in_Kbytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	IP events
arp	Configure ARP parameters
event-history	log debug events into event history buffer
packet	inst packet logs
event	Internal event logs
sync-event	CFS and MCECM related event logs
ip-sync-event	L3 over vpc events
control	ARP control event logs
ha	HA and GR logs
errors	inst error logs
lcache	lcache logs
lcache-errors	lcache_error logs
client-event	Client_event logs
client-errors	Client_error logs
cli	cli logs
snmp	SNMP logs
suppression-event	ARP suppression event logs
suppression-errors	ARP suppression error logs
controller-errors	Controller MAC-IP route error logs
dme-event	ARP DME event logs
sm-trace	ARP State machine trace logs
size	Configure the size of the event-hist buffer
<i>size_in_Kbytes</i>	Size of the file in kbytes

Command Mode

- /exec/configure

ip arp evpn timeout

{ ip arp evpn timeout <time-out> } | { no ip arp evpn timeout }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
evpn	In EVPN topology
timeout	ARP timeout
<i>time-out</i>	Refresh in EVPN on host moves. supported range is (2000-30000) ms

Command Mode

- /exec/configure

ip arp gratuitous hsrp duplicate

{ ip arp gratuitous hsrp duplicate | no ip arp gratuitous hsrp duplicate }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
gratuitous	gratuitous
hsrp	hsrp
duplicate	duplicate address detection

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-vlan-common

ip arp gratuitous request

{ ip arp gratuitous request | no ip arp gratuitous request }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
gratuitous	gratuitous
request	Enable/Disable sending grat. arp request when duplicate address detected

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-vlan

ip arp gratuitous update

{ ip arp gratuitous update | no ip arp gratuitous update }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
gratuitous	gratuitous
update	Enable/Disable arp cache updates for gratuitous arp

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-vlan-common

ip arp inspection filter vlan

[no] ip arp inspection filter <arp-acl-name> vlan <vlan-range>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
inspection	Arp Inspection configuration
filter	Filter
<i>arp-acl-name</i>	Access list name
vlan	Vlan range
<i>vlan-range</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

ip arp inspection log-buffer entries

[no] ip arp inspection log-buffer { entries <number1> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
inspection	Arp Inspection configuration
log-buffer	Log Buffer Configuration
entries	Number of entries for log buffer
<i>number1</i>	Number of entries for log buffer

Command Mode

- /exec/configure

ip arp inspection trust

[no] ip arp inspection trust

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
inspection	Arp Inspection configuration
trust	Configure trust state

Command Mode

- /exec/configure/if-switching

ip arp inspection validate

[no] ip arp inspection validate { src-mac | dst-mac | ip1 } +

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
inspection	Arp Inspection configuration
validate	Validate addresses
src-mac	Validate source MAC address
dst-mac	Validate destination MAC address
ip1	Validate IP addresses

Command Mode

- /exec/configure

ip arp inspection vlan

[no] ip arp inspection vlan <vlan-id> [logging { dhcp-bindings { permit | all | inone } }]

Syntax Description

<i>logging</i>	(Optional) dhcp-bindings
no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
inspection	Arp Inspection configuration
vlan	Enable/Disable ARP Inspection on vlans
<i>vlan-id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
dhcp-bindings	(Optional) Logging of packet that match DHCP bindings
permit	(Optional) Log DHCP Binding Permitted packets
all	(Optional) Log all packets that match DHCP bindings
inone	(Optional) Do not log packets

Command Mode

- /exec/configure

ip arp off-list timeout

{ ip arp off-list timeout <time> } | { no ip arp off-list timeout }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
off-list	off-list
timeout	Expire time
<i>time</i>	Expire time value in seconds

Command Mode

- /exec/configure

ip arp rarp fabric-forwarding

[no] ip arp rarp fabric-forwarding

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
rarp	Enable/Disable forwarding of RARP messages on fabric
fabric-forwarding	Forward RARP requests to the fabric

Command Mode

- /exec/configure

ip arp rarp fabric-forwarding

[no] ip arp rarp fabric-forwarding

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
rarp	Enable/Disable forwarding of RARP messages on fabric
fabric-forwarding	Forward RARP requests to the fabric

Command Mode

- /exec/configure

ip arp rarp fabric-forwarding rate-limit

[no] ip arp rarp fabric-forwarding rate-limit <rate>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
rarp	Enable/Disable forwarding of RARP messages on fabric
fabric-forwarding	Forward RARP requests to the fabric
rate-limit	Forwarding rate of the RARP frames
<i>rate</i>	RARP frames-per-second

Command Mode

- /exec/configure

ip arp suppression-cache

```
ip arp suppression-cache { [ clear { local | remote } vlan <vlan-id> [ <ip-address> ] ] | [ download remote
vlan <vlan-id> [ <ip-address> ] ] }
```

Syntax Description

clear	(Optional) Clear ARP suppression cache entries
ip	Clear IP commands
download	(Optional) download local entries from ARP cache, remote from l2rib
arp	Clear ARP table and statistics
suppression-cache	ARP-suppression cache
local	(Optional) Local entries
remote	(Optional) Remote entries
vlan	(Optional) Vlan id
<i>vlan-id</i>	(Optional) Vlan
<i>ip-address</i>	(Optional) IP address

Command Mode

- /exec

ip arp suppression timeout

{ ip arp suppression timeout <time-out> } | { no ip arp suppression timeout }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
suppression	ARP-suppression based event
timeout	ARP timeout
<i>time-out</i>	Time-out value in seconds. Time-out = 0 indicates disabled

Command Mode

- /exec/configure

ip arp synchronize

[no] ip arp synchronize

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	ARP
synchronize	CFS synchronize

Command Mode

- /exec/configure/vpc-domain

ip arp timeout

{ ip arp timeout <time-out> } | { no ip arp timeout }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
timeout	ARP timeout
<i>time-out</i>	Time-out value in seconds

Command Mode

- /exec/configure/config-mgmt /exec/configure/if-igp

ip arp timeout

```
{ ip arp timeout <time-out> } | { no ip arp timeout }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
timeout	ARP timeout
<i>time-out</i>	Time-out value in seconds

Command Mode

- /exec/configure

ip arp unnum-svi-dup-ip-detection

[no] ip arp unnum-svi-dup-ip-detection

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
unnum-svi-dup-ip-detection	Enable duplicate IP detection across VLANs for IP unnumbered SVIs.

Command Mode

- /exec/configure/if-vlan-common

ip arp unnum-svi-sw-replication

[no] ip arp unnum-svi-sw-replication

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
arp	Configure ARP parameters
unnum-svi-sw-replication	ARP packets replication in software for unnumbered SVI

Command Mode

- /exec/configure

ip as-path access-list deny

```
{ ip as-path access-list <aspl-name> [ timeout <sec> ] { { deny | permit } <line> } } | { no ip as-path access-list <aspl-name> [ timeout <sec> ] [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
as-path	BGP autonomous system path filter
access-list	Specify an access list name
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	Known as-path access-list name
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify packets to reject
permit	Specify packets to forward
<i>line</i>	A

Command Mode

- /exec/configure

ip as-path access-list deny

```
{ ip as-path access-list <aspl-name> [ timeout <sec> ] [ { deny | permit } <line> } } | { no ip as-path access-list <aspl-name> [ timeout <sec> ] [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
as-path	BGP autonomous system path filter
access-list	Specify an access list name
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	Known as-path access-list name
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify packets to reject
permit	Specify packets to forward
<i>line</i>	A

Command Mode

- /exec/configure

ip as-path access-list seq deny

{ ip as-path access-list <aspl-name> seq <seq> [timeout <sec>] { { deny | permit } <line> } } | { no ip as-path access-list <aspl-name> seq <seq> [timeout <sec>] [{ deny | permit } <line>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
as-path	BGP autonomous system path filter
access-list	Specify an access list name
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	Known as-path access-list name
seq	Sequence number of an entry
<i>seq</i>	Sequence number
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify packets to reject
permit	Specify packets to forward
<i>line</i>	A

Command Mode

- /exec/configure

ip authentication

```
[no] { ip | ipv6 } authentication { { key-chain eigrp <eigrp-ptag> <chain> } | { mode eigrp <eigrp-ptag> md5 } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
authentication	Configures EIGRP authentication subcommands
key-chain	key-chain
<i>eigrp-ptag</i>	Process tag
<i>chain</i>	name of key-chain
mode	mode
eigrp	EIGRP interface configuration commands
md5	Keyed message digest
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip auto-discard

[no] ip auto-discard

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
auto-discard	Auto 0.0.0.0/0 discard route

Command Mode

- /exec/configure /exec/configure/vrf

ip bandwidth-percent eigrp

```
{ { { ip | ipv6 } bandwidth-percent eigrp <eigrp-ptag> <percent> } | { no { ip | ipv6 } bandwidth-percent eigrp <eigrp-ptag> [ <percent> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
bandwidth-percent	Configures IP-EIGRP bandwidth limit
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>percent</i>	Maximum bandwidth percentage that EIGRP may use
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip bandwidth eigrp

```
{ { { ip | ipv6 } bandwidth eigrp <eigrp-ptag> <bw> } | { no { ip | ipv6 } bandwidth eigrp <eigrp-ptag> [ <bw> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
bandwidth	Set bandwidth for interface used in EIGRP metric calculation
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>bw</i>	Bandwidth in kilobits
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip community-list expanded deny

```
{ ip community-list expanded <name> [ timeout <sec> ] { deny | permit } <line> } | { no ip community-list
expanded <name> [ timeout <sec> ] [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
expanded	Add an expanded community list entry
<i>name</i>	Name of expanded community list
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify community to reject
permit	Specify community to accept
<i>line</i>	Regular-expression(must

Command Mode

- /exec/configure

ip community-list expanded deny

```
{ ip community-list expanded <name> [ timeout <sec> ] { deny | permit } <line> } | { no ip community-list
expanded <name> [ timeout <sec> ] [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
expanded	Add an expanded community list entry
<i>name</i>	Name of expanded community list
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify community to reject
permit	Specify community to accept
<i>line</i>	Regular-expression(must

Command Mode

- /exec/configure

ip community-list expanded seq deny

```
{ ip community-list expanded <name> seq <seq> [ timeout <sec> ] { deny | permit } <line> } | { no ip community-list expanded <name> seq <seq> [ timeout <sec> ] [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
expanded	Add an expanded community list entry
<i>name</i>	Name of expanded community list
seq	Sequence number of an entry
<i>seq</i>	Sequence number
timeout	(Optional) Timeout to be used for checking regex cpu hog
<i>sec</i>	(Optional) No. of seconds used as timeout
deny	Specify community to reject
permit	Specify community to accept
<i>line</i>	Regular-expression(must

Command Mode

- /exec/configure

ip community-list standard permit internet local-AS

```
{ ip community-list standard <name> { permit | deny } { internet | local-AS | no-advertise | no-export | <aann> | <number> | <hex_num> } + } | { no ip community-list standard <name> [ permit | deny ] [ { internet | local-AS | no-advertise | no-export | <aann> | <number> | <hex_num> } + ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
standard	Add a standard Community list entry
<i>name</i>	Standard community list name
permit	Specify community to accept
deny	Specify community to reject
internet	Internet (well-known community)
local-AS	Do not send outside local AS (well-known community)
no-advertise	Do not advertise to any peer (well-known community)
no-export	Do not export to next AS (well-known community)
<i>aann</i>	Community number aa:nn format
<i>number</i>	Community number
<i>hex_num</i>	Community number in hex
<i>internet</i>	(Optional) local-AS

Command Mode

- /exec/configure

ip community-list standard permit internet local-AS

```
{ ip community-list standard <name> { permit | deny } { internet | local-AS | no-advertise | no-export | <aann>
| <number> | <hex_num> } + } | { no ip community-list standard <name> [ permit | deny ] [ { internet | local-AS
| no-advertise | no-export | <aann> | <number> | <hex_num> } + ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
standard	Add a standard Community list entry
<i>name</i>	Standard community list name
permit	Specify community to accept
deny	Specify community to reject
internet	Internet (well-known community)
local-AS	Do not send outside local AS (well-known community)
no-advertise	Do not advertise to any peer (well-known community)
no-export	Do not export to next AS (well-known community)
<i>aann</i>	Community number aa:nn format
<i>number</i>	Community number
<i>hex_num</i>	Community number in hex
<i>internet</i>	(Optional) local-AS

Command Mode

- /exec/configure

ip community-list standard seq permit internet local-AS

```
{ ip community-list standard <name> seq <seq> { permit | deny } { internet | local-AS | no-advertise | no-export
| <aann> | <number> | <hex_num> } + } | { no ip community-list standard <name> seq <seq> [ permit | deny
] [ { internet | local-AS | no-advertise | no-export | <aann> | <number> | <hex_num> } + ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
community-list	Add a community list entry
standard	Add a standard Community list entry
<i>name</i>	Standard community list name
seq	Sequence number of an entry
<i>seq</i>	Sequence number
permit	Specify community to accept
deny	Specify community to reject
internet	Internet (well-known community)
local-AS	Do not send outside local AS (well-known community)
no-advertise	Do not advertise to any peer (well-known community)
no-export	Do not export to next AS (well-known community)
<i>aann</i>	Community number aa:nn format
<i>number</i>	Community number
<i>hex_num</i>	Community number in hex
<i>internet</i>	(Optional) local-AS

Command Mode

- /exec/configure

ip delay eigrp

```
{ { { ip | ipv6 } delay eigrp <eigrp-ptag> <delay> [ picoseconds ] } | { no { ip | ipv6 } delay eigrp <eigrp-ptag> [ <delay> ] [ picoseconds ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
delay	Set delay for interface used in EIGRP metric calculation
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>delay</i>	Throughput delay
picoseconds	(Optional) Delay units in picoseconds
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip destination

{ ip { destination | source } <addr> } | { no ip { destination | source } }

Syntax Description

no	Negate a command or set its defaults
ip	specify flow ipv4 address
source	specify flow source ipv4 address
destination	specify flow destination ip address
<i>addr</i>	ipv4 address

Command Mode

- /exec/configure/configngoamprofileflow

ip dhcp option82 suboption circuit-id

[no] ip dhcp option82 suboption circuit-id [<format-string>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
option82	DHCP option82
suboption	DHCP option82 suboption information
circuit-id	DHCP option82 suboption circuit-id string configuration
<i>format-string</i>	(Optional) Format string

Command Mode

- /exec/configure/if-eth-phy /exec/configure/if-eth-port-channel

ip dhcp packet strict-validation

[no] ip dhcp packet strict-validation

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
packet	DHCP packet
strict-validation	DHCP packet strict validation

Command Mode

- /exec/configure/

ip dhcp relay

[no] ip dhcp relay

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	Enable DHCP relay agent

Command Mode

- /exec/configure

ip dhcp relay address

[no] ip dhcp relay address [<ip-addr-val> [use-vrf <vrf-name>]]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	Configure relay agent
address	Configure DHCP server to refer to
<i>ip-addr-val</i>	(Optional) IP address
use-vrf	(Optional) helper address VRF membership
<i>vrf-name</i>	(Optional) VRF name

Command Mode

- /exec/configure/if-igmp /exec/configure/ppm-ethernet-switch /exec/configure/ppm-port-channel-switch

ip dhcp relay information option

[no] ip dhcp relay information option

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
information	Relay agent information option
option	Insert relay information in BOOTREQUEST

Command Mode

- /exec/configure

ip dhcp relay information option trust

[no] ip dhcp relay information option trust

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
information	Relay agent information option
option	Relay agent option
trust	Enable relay trust functionality on the system

Command Mode

- /exec/configure

ip dhcp relay information option vpn

[no] ip dhcp relay information option vpn

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
information	Relay agent information option
option	Insert relay information in BOOTREQUEST
vpn	Enable relay support across VRFs

Command Mode

- /exec/configure

ip dhcp relay information trust-all

[no] ip dhcp relay information trust-all

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
information	Relay agent information option
trust-all	Enable relay trust on all the interfaces

Command Mode

- /exec/configure

ip dhcp relay information trusted

[no] ip dhcp relay information trusted

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
information	Relay agent information option
trusted	Enable relay trust on this interface

Command Mode

- /exec/configure/if-igp

ip dhcp relay source-interface

[no] ip dhcp relay source-interface

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	Configure relay agent
source-interface	Configure source interface for DHCP relay

Command Mode

- /exec/configure /exec/configure/if-igp

ip dhcp relay source-interface

ip dhcp relay source-interface <interface-name>

Syntax Description

ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	Configure relay agent
source-interface	Configure source interface for DHCP relay
<i>interface-name</i>	Source interface

Command Mode

- /exec/configure /exec/configure/if-igp

ip dhcp relay sub-option circuit-id customized

[no] ip dhcp relay sub-option circuit-id customized

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
sub-option	Relay agent information option sub-option
circuit-id	sub-option of option82
customized	circuit id customized to include vlan id, slot and port info

Command Mode

- /exec/configure

ip dhcp relay sub-option circuit-id format-type string

[no] ip dhcp relay sub-option circuit-id format-type string [format <format-string>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
sub-option	Relay agent suboption
circuit-id	Relay agent circuit-id suboption
format-type	Specify suboption format type
string	Use string format for suboption
format	(Optional) Specify format string
<i>format-string</i>	(Optional) Format string

Command Mode

- /exec/configure

ip dhcp relay sub-option type cisco

[no] ip dhcp relay sub-option type cisco

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
relay	DHCP relay agent parameters
sub-option	Relay agent suboption
type	Relay agent suboption type
cisco	Use Cisco proprietary suboptions

Command Mode

- /exec/configure

ip dhcp smart-relay

[no] ip dhcp smart-relay

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
smart-relay	Configure DHCP smart relay on interface

Command Mode

- /exec/configure/if-igp

ip dhcp smart-relay global

[no] ip dhcp smart-relay global

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
smart-relay	Configure DHCP smart relay
global	Configure DHCP smart relay globally

Command Mode

- /exec/configure

ip dhcp snooping

[no] ip dhcp snooping

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping

Command Mode

- /exec/configure/

ip dhcp snooping information option

[no] ip dhcp snooping information option

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping
information	DHCP Snooping information
option	DHCP Snooping information option

Command Mode

- /exec/configure/

ip dhcp snooping ipsg-excluded vlan

[no] ip dhcp snooping ipsg-excluded vlan <vlan-id10>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping
ipsg-excluded	exclude ipsg
vlan	DHCP Snooping ipsg excluded vlan
<i>vlan-id10</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

ip dhcp snooping sub-option circuit-id format-type string

[no] ip dhcp snooping sub-option circuit-id format-type string [format <format-string>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP snooping parameters
sub-option	suboption
circuit-id	circuit-id suboption
format-type	Specify suboption format type
string	Use string format for suboption
format	(Optional) Specify format string
<i>format-string</i>	(Optional) Format string

Command Mode

- /exec/configure

ip dhcp snooping trust

[no] ip dhcp snooping trust

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping
trust	DHCP Snooping trust config

Command Mode

- /exec/configure/if-switching

ip dhcp snooping verify mac-address

[no] ip dhcp snooping verify mac-address

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping
verify	DHCP snooping verify
mac-address	DHCP snooping verify mac-address

Command Mode

- /exec/configure/

ip dhcp snooping vlan

[no] ip dhcp snooping vlan <vlan-id10>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dhcp	Configure DHCP snooping or relay
snooping	DHCP Snooping
vlan	DHCP Snooping vlan
<i>vlan-id10</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

ip directed-broadcast

[no] ip directed-broadcast [<acl-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
directed-broadcast	IP directed-broadcast
<i>acl-name</i>	(Optional) ACL policy name

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config

ip distribute-list eigrp

```
[no] { ip | ipv6 } distribute-list eigrp <eigrp-ptag> { { route-map <map> } | { prefix-list <list> } } { in | out }
}
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
distribute-list	Filter networks in routing updates
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
route-map	Use a route-map for route filtering
<i>map</i>	Route-map name
prefix-list	Use a prefix-list for route filtering
<i>list</i>	Reference to prefix-list name
in	Filter incoming routing updates
out	Filter outgoing routing updates

Command Mode

- /exec/configure/if-igp

ip dns source-interface

[no] ip dns source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
dns	Configure dns client
source-interface	Configure source interface feature for domain-lookup
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip domain-list

[no] ip domain-list { <s0> | <s1> [use-vrf { <vrf-name> | <vrf-known-name> }] }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
domain-list	Add additional domain names
<i>s0</i>	Enter a domain
<i>s1</i>	Enter a domain
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure /exec/configure/vrf

ip domain-lookup

[no] ip domain-lookup

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
domain-lookup	Enable/Disable DNS

Command Mode

- /exec/configure

ip domain-name

[no] ip domain-name { <s0> | <s1> [use-vrf { <vrf-name> | <vrf-known-name> }] }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
domain-name	Specify default domain name
<i>s0</i>	Enter the default domain
<i>s1</i>	Enter the default domain
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure /exec/configure/vrf

ip drop-glean

[no] ip drop-glean

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
drop-glean	Installs the secondary subnet routes as Drop routes

Command Mode

- /exec/configure/if-vlan-common

ip dscp-lop

[no] ip dscp-lop | ip dscp-lop { <dscp-val> | <dscp-enum> }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
dscp-lop	Set DSCP to be used for locally originated packets for IPv4 and IPv6. Cos will not be set.
<i>dscp-val</i>	Specify DSCP value for Locally Originated packets for IPv4 and IPv6
<i>dscp-enum</i>	

Command Mode

- /exec/configure

ip dscp

[no] ip dscp <dscp_value>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Set ERSPAN IP options
dscp	Set the IP DSCP value
<i>dscp_value</i>	

Command Mode

- /exec/configure/config-monitor-erspan-src

ip eigrp bfd

[no] ip eigrp <eigrp-tag> bfd [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
eigrp	EIGRP interface configuration commands
<i>eigrp-tag</i>	Process tag
bfd	Enable BFD on this interface
disable	(Optional) Disable BFD on this interface

Command Mode

- /exec/configure/if-igp

ip eigrp event-history bfd size

[no] { ip | ipv6 } eigrp [<eigrp-ptag>] event-history bfd size { <size_in_text> | <size_in_Kbytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Event History of EIGRP
bfd	Show bfd log of EIGRP
size	Configure the size of the event-hist buffer
<i>size_in_text</i>	Buffer size
<i>size_in_Kbytes</i>	Size of the file in kbytes

Command Mode

- /exec/configure

ip eigrp event-history errors

[no] { ip | ipv6 } eigrp [<eigrp-ptag>] event-history { errors | msgs }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Event History of EIGRP
errors	Show error log of EIGRP
msgs	Show message log of EIGRP

Command Mode

- /exec/configure

ip eigrp event-history size

[no] { ip | ipv6 } eigrp [<eigrp-ptag>] event-history { fsm | packet | rib } size { <size_in_text> | <size_in_Kbytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Clear IP commands
ipv6	Clear IPv6 commands
eigrp	EIGRP clear commands
<i>eigrp-ptag</i>	(Optional) Process tag
event-history	Event History of EIGRP
fsm	FSM log of EIGRP
packet	Packet log of EIGRP
rib	RIB log of EIGRP
size	Configure the size of the event-hist buffer
<i>size_in_text</i>	Buffer size
<i>size_in_Kbytes</i>	Size of the file in kbytes

Command Mode

- /exec/configure

ip eigrp shutdown

[no] { ip | ipv6 } eigrp <eigrp-ptag> shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
shutdown	Shutdown EIGRP on this interface

Command Mode

- /exec/configure/if-igp

ip extcommunity-list expanded deny

```
{ ip extcommunity-list expanded <name> { deny | permit } <line> } | { no ip extcommunity-list expanded <name> [ { deny | permit } <line> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
extcommunity-list	Add a extcommunity list entry
expanded	Add an expanded extcommunity list entry
<i>name</i>	Name of expanded extcommunity list
deny	Specify extcommunity to reject
permit	Specify extcommunity to accept
<i>line</i>	Regular-expression(must

Command Mode

- /exec/configure

ip extcommunity-list standard permit

```
{ ip extcommunity-list standard <name> { permit | deny } { { 4byteas-generic { transitive
<ext-comm-gen-trans> | non-transitive <ext-comm-gen-nontrans> } } | { rt { <ext-comm-rt-aa2nn4> |
<ext-comm-rt-aa4nn2> } } | { soo { <ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> } } } + | { no ip
extcommunity-list standard <name> [ permit | deny ] [ { 4byteas-generic { transitive <ext-comm-gen-trans>
| non-transitive <ext-comm-gen-nontrans> } } | { rt { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } } |
{ soo { <ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> } } ] + } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
extcommunity-list	Add a extcommunity list entry
standard	Add a standard Extcommunity list entry
<i>name</i>	Standard extcommunity list name
permit	Specify extcommunity to accept
deny	Specify extcommunity to reject
4byteas-generic	Generic extended community
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
rt	Router-Target
soo	Site-Of-Origin
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
<i>ext-comm-rt-aa2nn4</i>	Extcommunity number
<i>ext-comm-rt-aa4nn2</i>	Extcommunity number
<i>ext-comm-soo-aa2nn4</i>	Extcommunity number
<i>ext-comm-soo-aa4nn2</i>	Extcommunity number

Command Mode

- /exec/configure

ip fabric multicast file-debug

[no] ip fabric multicast file-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
fabric	Config fabric
multicast	Configure multicast
file-debug	Collect all debugs to a file

Command Mode

- /exec/configure

ip flow monitor input

[no] ip flow monitor <monitorname> input

Syntax Description

ip	Configure IP features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/if-vlan-common

ip flow monitor input

[no] ip flow monitor <monitorname> input

Syntax Description

ip	Configure IP features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/if-routing /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

ip flow monitor input

[no] ip flow monitor <monitorname> input

Syntax Description

ip	Configure IP features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/vlan-config

ip forward

ip forward | no ip forward

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
forward	Enable ip forwarding on interface

Command Mode

- /exec/configure/if-vlan /exec/configure/if-vlan-range /exec/configure/if-igp

ip ftp source-interface

[no] ip ftp source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ftp	Configure FTP client
source-interface	Configure source interface feature for FTP client
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip hello-interval eigrp

```
{ { { ip | ipv6 } hello-interval eigrp <eigrp-ptag> <hello-interval> } | { no { ip | ipv6 } hello-interval eigrp <eigrp-ptag> [ <hello-interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
hello-interval	Configures IP-EIGRP hello interval
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>hello-interval</i>	Seconds between hello transmissions
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip hold-time eigrp

```
{ { { ip | ipv6 } hold-time eigrp <eigrp-ptag> <holdtime> } | { no { ip | ipv6 } hold-time eigrp <eigrp-ptag> [ <holdtime> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
hold-time	Configures IP-EIGRP hold time
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>holdtime</i>	Seconds before neighbor is considered down
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip host

[no] ip host <s0> [<ipv4_0>] | ip host <s0> <ipv4_0>

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
host	Add an entry to the ip hostname table
<i>s0</i>	Name of Host
<i>ipv4_0</i>	(Optional) Enter an IP address

Command Mode

- /exec/configure

ip host host

```
{ [ <seqnum> ] <permitdeny> { ip { <src_addr> <src_wild> | <src_prefix> | <src_any> | host <src_hostaddr>
} { <dst_addr> <dst_wild> | <dst_prefix> | <dst_any> | host <dst_hostaddr> } } } | { no <seqnum> }
```

Syntax Description

no	Negate a command or set its defaults
<i>seqnum</i>	(Optional) Sequence number
ip	ip
<i>permitdeny</i>	permitdeny
<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	A.B.C.D/nn Source network prefix
<i>src_any</i>	Any source address
host	A.B.C.D - A single source host
<i>src_hostaddr</i>	A.B.C.D - A single source host
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits
<i>dst_prefix</i>	A.B.C.D/nn Destination network prefix
<i>dst_any</i>	Any destination address
host	A.B.C.D - A single destination host
<i>dst_hostaddr</i>	A.B.C.D - A single destination host

Command Mode

- /exec/configure/catena-port-acl

ip http source-interface

[no] ip http source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
http	Configure HTTP client
source-interface	Configure source interface feature for HTTP client
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip icmp-errors source-interface

ip icmp-errors source-interface <interface> [<icmp_type>] | no ip icmp-errors source-interface [<interface> <icmp_type>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
icmp-errors	ICMP unreachable/TTL-exceeded/param-prob messages
source-interface	Configure source-address for applications
<i>interface</i>	Interface to pick source-address from
<i>icmp_type</i>	(Optional) ICMPv6 types

Command Mode

- /exec/configure /exec/configure/vrf

ip igmp any-query-destination

[no] ip igmp any-query-destination

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
any-query-destination	Allow any destination-IP for General Queries

Command Mode

- /exec/configure

ip igmp enforce-router-alert

[no] ip igmp enforce-router-alert

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
enforce-router-alert	Enforce Router Alert option check for IGMPv2 and IGMPv3 packets

Command Mode

- /exec/configure

ip igmp event-history cli

[no] ip igmp event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
cli	CLI events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history ha

[no] ip igmp event-history ha { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
ha	HA events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history interface

```
[no] ip igmp event-history { interface-debug | group-debug } { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
interface-debug	Interface-debug for IGMP
group-debug	Group-debug for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history interface

```
[no] ip igmp event-history { interface-events | group-events } { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
interface-events	Interface-events for IGMP
group-events	Group-events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history mtrace

[no] ip igmp event-history mtrace { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
mtrace	Mtrace events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history mvr

```
[no] ip igmp event-history mvr { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
mvr	MVR events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history nbm

```
[no] ip igmp event-history nbm { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
nbm	NBM events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history policy

```
[no] ip igmp event-history policy { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
policy	Policy events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp event-history vrf

```
[no] ip igmp event-history vrf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
event-history	Configure event-history buffers
vrf	VRF events for IGMP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp file-debug

[no] ip igmp file-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
file-debug	Collect all debugs to a file

Command Mode

- /exec/configure

ip igmp flush-routes

[no] ip igmp flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
flush-routes	Remove routes when restarting IGMP

Command Mode

- /exec/configure

ip igmp group-timeout

```
{ { no ip igmp group-timeout [ <time> ] } | { ip igmp group-timeout <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
group-timeout	Configures group membership timeout for IGMPv2
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igp

ip igmp heavy-template

[no] ip igmp heavy-template

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
heavy-template	IGMP heavy for IGMP scale

Command Mode

- /exec/configure

ip igmp host-proxy

```
[no] ip igmp host-proxy [ unsolicited [ <time> ] | route-map <route-map-name> [ unsolicited [ <time> ] ] |
prefix-list <prefix-list-name> [ unsolicited [ <time> ] ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
host-proxy	Configures igmp host proxy for this interface
route-map	(Optional) host proxy route-map policy
prefix-list	(Optional) host proxy prefix-list policy
unsolicited	(Optional) unsolicited joins
<i>time</i>	(Optional) Time in seconds.
<i>route-map-name</i>	(Optional) Route-map name
<i>prefix-list-name</i>	(Optional) Name of prefix-list

Command Mode

- /exec/configure/if-igp

ip igmp immediate-leave

[no] ip igmp immediate-leave

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
immediate-leave	Enable/Disable immediate leave

Command Mode

- /exec/configure/if-igp

ip igmp join-group

```
[no] ip igmp join-group { { <group> [ source <source> ] } | { route-map <route-map-name> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
join-group	Configures local group membership for router
<i>group</i>	Multicast group IP address
source	(Optional) Configures source address for IGMPv3 (S,G) Channel
<i>source</i>	(Optional) Source IP address
route-map	Join group policy
<i>route-map-name</i>	Route-map name

Command Mode

- /exec/configure/if-igp

ip igmp last-member-query-count

```
{ { no ip igmp last-member-query-count [ <count> ] } | { ip igmp last-member-query-count <count> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
last-member-query-count	Configures number of group-specific Queries sent
<i>count</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ip igmp last-member-query-response-time

```
{ { no ip igmp last-member-query-response-time [ <interval> ] } | { ip igmp last-member-query-response-time <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
last-member-query-response-time	Configures last member query response time
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ip igmp querier-elect strict

[no] ip igmp querier-elect strict

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
querier-elect	Querier election
strict	Consider subnet check for L3 igmp querier election

Command Mode

- /exec/configure

ip igmp querier

```
{ { no ip igmp { querier-timeout | query-timeout } [ <time> ] } | { ip igmp { querier-timeout | query-timeout } <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
querier-timeout	Configures querier timeout for IGMPv2
query-timeout	Configures querier timeout for IGMPv2
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igp

ip igmp query-interval

```
{ { no ip igmp query-interval [ <interval> ] } | { ip igmp query-interval <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
query-interval	Configures interval between Query transmission
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ip igmp query-max-response-time

```
{ { no ip igmp query-max-response-time [ <time> ] } | { ip igmp query-max-response-time <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
query-max-response-time	Configures MRT for query messages
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igmp

ip igmp report-link-local-groups

[no] ip igmp report-link-local-groups

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
report-link-local-groups	Send Reports for groups in 224.0.0.0/24

Command Mode

- /exec/configure/if-igp

ip igmp report prefix-list

```
{ { ip igmp { report-policy | access-group } { <route-map-name> | prefix-list <prefix-list-name> } } | { no ip igmp { report-policy | access-group } [ <route-map-name> | prefix-list <prefix-list-name> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
report-policy	IGMP Report Policy
access-group	IGMP access-group
<i>route-map-name</i>	Route-map name
prefix-list	Prefix list policy
<i>prefix-list-name</i>	Name of prefix-list

Command Mode

- /exec/configure/if-igp

ip igmp robustness-variable

```
{ { no ip igmp robustness-variable [ <value> ] } | { ip igmp robustness-variable <value> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
robustness-variable	Configures RFC defined Robustness Variable
<i>value</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ip igmp snooping

{ { no ip igmp snooping } | { ip igmp snooping } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping

```
{ { no ip igmp snooping } | { ip igmp snooping } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping

Command Mode

- /exec/configure

ip igmp snooping

```
[no] ip igmp snooping { holddown-timer <timer> | cc-mode | m2rib-max-omfs <omf-count> |
m2rib-max-omf-routes <omf-route-count> | m2rib-max-routes <route-count> | m2rib-max-buffers <buf-count>
}
```

Syntax Description

ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
no	(Optional) Negate a command or set its defaults
holddown-timer	Initial holddown period after switchover/restart
cc-mode	Enter MFDM congestion-control mode
m2rib-max-omfs	Number of OMF entries in M2RIB buffer
m2rib-max-routes	Number of route entries in M2RIB buffer
m2rib-max-omf-routes	Number of omf route entries in M2RIB buffer
m2rib-max-buffers	Number of update buffers with M2RIB
<i>timer</i>	Delay (in secs)
<i>omf-count</i>	
<i>route-count</i>	
<i>buf-count</i>	
<i>omf-route-count</i>	

Command Mode

- /exec/configure

ip igmp snooping access-group

[no] ip igmp snooping access-group <route-map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
access-group	Configures filter policy for groups mentioned in route-map
<i>route-map-name</i>	route-map name

Command Mode

- /exec/configure/vlan-config

ip igmp snooping disable-nve-static-router-port

[no] ip igmp snooping disable-nve-static-router-port

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
disable-nve-static-router-port	Disable NVE as a static router port

Command Mode

- /exec/configure

ip igmp snooping disable-nve-static-router-port

[no] ip igmp snooping disable-nve-static-router-port

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
disable-nve-static-router-port	Disable NVE as a static router port

Command Mode

- /exec/configure

ip igmp snooping event-history igmp-snoop-internal

[no] ip igmp snooping event-history igmp-snoop-internal { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
igmp-snoop-internal	Internal events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history mfdm-sum

```
[no] ip igmp snooping event-history mfdm-sum { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
mfdm-sum	MFDM-SUM events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history mfdm

```
[no] ip igmp snooping event-history mfdm { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
mfdm	MFDM events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history rib

```
[no] ip igmp snooping event-history rib { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
rib	RIB events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history vlan-events

[no] ip igmp snooping event-history vlan-events { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
vlan-events	VLAN/BD events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history vlan

[no] ip igmp snooping event-history vlan { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
vlan	VLAN/BD events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping event-history vpc

[no] ip igmp snooping event-history vpc { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
event-history	Configure event-history buffers
vpc	VPC events for IGMP-snoop
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip igmp snooping group-timeout

[no] ip igmp snooping group-timeout { <timeout> | never }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
group-timeout	Configures group membership timeout in VLAN/BD
<i>timeout</i>	Timeout in minutes
never	Never expire ports from group membership

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping group-timeout

[no] ip igmp snooping group-timeout { <timeout> | never }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
group-timeout	Configures group membership timeout in all VLAN/BDs
<i>timeout</i>	Timeout in minutes
never	Never expire ports from group membership

Command Mode

- /exec/configure

ip igmp snooping last-member-query-interval

```
{ { no ip igmp snooping last-member-query-interval [ <interval> ] } | { ip igmp snooping  
last-member-query-interval <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
last-member-query-interval	Configures interval between group-specific Query transmissions
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping link-local-groups-suppression

[no] ip igmp snooping link-local-groups-suppression

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
link-local-groups-suppression	Configures VLAN/BD link-local groups suppression

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping link-local-groups-suppression

[no] ip igmp snooping link-local-groups-suppression

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
link-local-groups-suppression	Configures Global link-local groups suppression

Command Mode

- /exec/configure

ip igmp snooping many-to-one-enhance

[no] ip igmp snooping many-to-one-enhance

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
many-to-one-enhance	Enable many to one optimization for n3500 platform

Command Mode

- /exec/configure

ip igmp snooping max-gq-miss

{ { no ip igmp snooping max-gq-miss } | { ip igmp snooping max-gq-miss <count> } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
max-gq-miss	Configure general query miss count
<i>count</i>	Max number of GQ misses allowed

Command Mode

- /exec/configure

ip igmp snooping mrouter vpc-peer-link

[no] ip igmp snooping mrouter vpc-peer-link

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
mrouter	Configures static multicast router interface
vpc-peer-link	Specify vpc-peer-link as static mrouter for all VLAN/BDS

Command Mode

- /exec/configure

ip igmp snooping proxy-leave use-group-address

```
{ { ip igmp snooping proxy-leave use-group-address } | { no ip igmp snooping proxy-leave use-group-address } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
proxy-leave	Proxy Leave
use-group-address	Use group address for proxy leave

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping proxy general-queries

[no] ip igmp snooping proxy general-queries [mrt <mrt>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
proxy	Configures IGMP snooping proxy
general-queries	Configures proxy for general-queries
mrt	(Optional) Configure max-response-time for the switch's proxy general-queries
<i>mrt</i>	(Optional) MRT in seconds

Command Mode

- /exec/configure

ip igmp snooping proxy general-queries

[no] ip igmp snooping proxy general-queries [mrt <mrt>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
proxy	Configures IGMP snooping proxy
general-queries	Configures proxy for general-queries
mrt	(Optional) Configure max-response-time for the switch's proxy general-queries
<i>mrt</i>	(Optional) MRT in seconds

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping report-flood all

```
{ { ip igmp snooping report-flood { all | interface <interface> } } | { no ip igmp snooping report-flood { all | interface <interface> } } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
report-flood	Configures Report flooding on a VLAN
interface	Specify interface for report flooding
all	Flood on ALL active ports of VLAN
<i>interface</i>	Interface name

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping report-suppression

{ { no ip igmp snooping report-suppression } | { ip igmp snooping report-suppression } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
report-suppression	Configures IGMPv1/IGMPv2 Report Suppression for the VLAN/BD

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping report-suppression

{ { no ip igmp snooping report-suppression } | { ip igmp snooping report-suppression } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
report-suppression	Configures Global IGMPv1/IGMPv2 Report Suppression

Command Mode

- /exec/configure

ip igmp snooping report prefix interface

```
{ [ no ] ip igmp snooping { report-policy | access-group } { prefix-list | route-map } <pname> interface <interface> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
report-policy	IGMP Report Policy
access-group	IGMP access-group
prefix-list	IPv4 Prefix-List Policy
route-map	Route-Map Policy
<i>pname</i>	Policy Name Name
interface	Specify interface for filtering
<i>interface</i>	Interface name

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp snooping syslog-threshold

{ ip igmp snooping syslog-threshold <percentage> } | { no ip igmp snooping syslog-threshold }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
syslog-threshold	IGMP SNOOPING table syslog threshold
<i>percentage</i>	Percentage

Command Mode

- /exec/configure

ip igmp snooping v3-report-suppression

{ { no ip igmp snooping v3-report-suppression } | { ip igmp snooping v3-report-suppression } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
snooping	Configures IGMP Snooping
v3-report-suppression	Configures Global IGMPv3 Report Suppression and Proxy Reporting

Command Mode

- /exec/configure

ip igmp snooping v3-report-suppression

```
{ { no ip igmp snooping v3-report-suppression } | { ip igmp snooping v3-report-suppression } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP configuration commands
snooping	Configures IGMP Snooping
v3-report-suppression	Configures IGMPv3 Report Suppression and Proxy Reporting for the VLAN/BD

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

ip igmp spoof-check

[no] ip igmp spoof-check

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
spoof-check	Enable spoof check for IGMP

Command Mode

- /exec/configure

ip igmp ssm-translate

[no] ip igmp ssm-translate <group> <source>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP global configuration commands
ssm-translate	Translate IGMPv1/v2 reports to (S,G) route entries
<i>group</i>	IP Multicast group range
<i>source</i>	IP Multicast address source

Command Mode

- /exec/configure /exec/configure/vrf

ip igmp startup-query-count

```
{ { no ip igmp startup-query-count [ <count> ] } | { ip igmp startup-query-count <count> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
startup-query-count	Configures number of queries sent at startup
<i>count</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ip igmp startup-query-interval

{ { no ip igmp startup-query-interval [<interval>] } | { ip igmp startup-query-interval <interval> } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
startup-query-interval	Configures query interval at startup
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igmp

ip igmp state-limit

```
{ { ip igmp state-limit <max-states> [ reserved <route-map-name> <max-reserved> ] } | { no ip igmp state-limit [ <max-states> [ reserved <route-map-name> <max-reserved> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
state-limit	Configures State limit
<i>max-states</i>	Maximum states allowed
reserved	(Optional) Reserve the states using route-map
<i>route-map-name</i>	(Optional) Route-map name
<i>max-reserved</i>	(Optional) Maximum (*,G)/(S,G) entires allowed on the interface

Command Mode

- /exec/configure/if-igp

ip igmp static

```
[no] ip igmp { static-group | static-oif } { { <group> [ source <source> ] } | { route-map <route-map-name> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
static-group	Configures static oif for a multicast forwarding entry
static-oif	Configures static oif for a multicast forwarding entry
<i>group</i>	Multicast group IP address
source	(Optional) Configures source address for IGMPv3 (S,G) Channel
<i>source</i>	(Optional) Source IP address
route-map	Static group policy
<i>route-map-name</i>	Route-map name

Command Mode

- /exec/configure/if-igp

ip igmp suppress v3-gsq

[no] ip igmp suppress v3-gsq

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
suppress	Suppress
v3-gsq	v3 GSQ

Command Mode

- /exec/configure/if-igp

ip igmp syslog-threshold

{ ip igmp syslog-threshold <percentage> } | { no ip igmp syslog-threshold }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP related events
syslog-threshold	IGMP table syslog threshold
<i>percentage</i>	Percentage

Command Mode

- /exec/configure

ip igmp version

```
{ { no ip igmp version [ <version> ] } | { ip igmp version <version> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
igmp	IGMP interface configuration commands
version	Configures IGMP version number for interface
<i>version</i>	(Optional) Version number value

Command Mode

- /exec/configure/if-igp

ip lisp alt-vrf

```
{ { [ no ] ip lisp alt-vrf { <vrf-name> | <vrf-known-name> } } | { [ no ] ipv6 lisp alt-vrf { <vrf-name> | <vrf-known-name> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
alt-vrf	Activate LISP-ALT functionality in VRF
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp database-mapping dynamic priority weight

```
{ [ no ] ip lisp database-mapping <eid-prefix> { <locator> | <locator6> | { dynamic <interface> } } priority <priority> weight <weight> } | { no ip lisp database-mapping <eid-prefix> { <locator> | <locator6> | { dynamic <interface> } } } | { [ no ] ipv6 lisp database-mapping <eid-prefix6> { <locator> | <locator6> | { dynamic <interface> } } } priority <priority> weight <weight> } | { no ipv6 lisp database-mapping <eid-prefix6> { <locator> | <locator6> | { dynamic <interface> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
database-mapping	Configures Locator addresses for an ETR
<i>eid-prefix</i>	IP EID-prefix to advertise locators for
<i>locator</i>	IP address of loopback or other ETR loopback interface
dynamic	Get locator dynamically
<i>interface</i>	Interface to learn dynamic locator
priority	Configures which Locators from a set are preferred
<i>priority</i>	Lower priority Locator takes preference
weight	Traffic load-spreading among Locators
<i>weight</i>	Specified in a percentage from 0 to 100

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp disable-spoof-alert

[no] { ip | ipv6 } lisp disable-spoof-alert

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
disable-spoof-alert	Disable spoof-alert checking for Map-Replies

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr

[no] { ip | ipv6 } lisp etr

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
etr	Configures LISP Egress Tunnel Router (ETR) parameters

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr accept-map-request-mapping

```
{ { [ no ] ip lisp etr accept-map-request-mapping [ verify ] } | { [ no ] ipv6 lisp etr accept-map-request-mapping [ verify ] } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
etr	Configures LISP Egress Tunnel Router (ETR) parameters
lisp	LISP global configuration commands
accept-map-request-mapping	Configures an ETR to cache mappings received from Map-Request messages
verify	(Optional) Send Map-Request back to Map-Request originator of a Mapping Data Record

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr glean-mapping

```
{ { [ no ] ip lisp etr glean-mapping [ verify ] } | { [ no ] ipv6 lisp etr glean-mapping } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
etr	Configures LISP Egress Tunnel Router (ETR) parameters
lisp	LISP global configuration commands
glean-mapping	Glean locator mapping from outer DA for inner DA EID
verify	(Optional) Send Map-Request to ITR to verify data gleaning

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr map-cache-ttl

```
{ [ no ] ip lisp etr map-cache-ttl <minutes> } | { no ip lisp etr map-cache-ttl } | { [ no ] ipv6 lisp etr map-cache-ttl <minutes> } | { no ipv6 lisp etr map-cache-ttl }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
etr	Configures LISP Egress Tunnel Router (ETR) parameters
lisp	LISP global configuration commands
map-cache-ttl	Configures TTL for Map-Reply messages
<i>minutes</i>	Time-to-Live in units of minutes

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr map-register-ttl

{ [no] ip lisp etr map-register-ttl <minutes> } | { no ip lisp etr map-register-ttl } | { [no] ipv6 lisp etr map-register-ttl <minutes> } | { no ipv6 lisp etr map-register-ttl }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
etr	Configures LISP Egress Tunnel Router (ETR) parameters
lisp	LISP global configuration commands
map-register-ttl	Configures TTL for Map-Register messages
<i>minutes</i>	Time-to-Live in units of minutes

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp etr map-server key

```
{ { [ no ] ip lisp etr map-server { <ms> | <ms6> } [ key-type { sha1 | sha2 } ] key <key> } | { [ no ] ipv6 lisp etr map-server { <ms> | <ms6> } [ key-type { sha1 | sha2 } ] key <key> } | { [ no ] ip lisp etr map-server { <ms> | <ms6> } proxy-reply } | { [ no ] ipv6 lisp etr map-server { <ms> | <ms6> } proxy-reply } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
etr	Configures LISP Egress Tunnel Router (ETR) parameters
map-server	To interact with Map-Server
<i>ms</i>	Address of IPv4 map-server
key-type	(Optional) Authentication key type, either sha1 or sha2
sha1	(Optional) Use sha1 authentication in Map-Register messages
sha2	(Optional) Use sha2 authentication in Map-Register messages
key	Authentication key used with Map-Server
<i>key</i>	SHA-1 password key
proxy-reply	Request Map-Server to send Map-Replies on behalf of site

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp hardware-forwarding

[no] { ip | ipv6 } lisp hardware-forwarding

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
hardware-forwarding	Enable/disable Nexus 7K hardware forwarding

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp itr-etr

[no] { ip | ipv6 } lisp itr-etr

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
itr-etr	Configures both LISP ITR and ETR functionality

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp itr

[no] { ip | ipv6 } lisp itr

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
itr	Configures LISP Ingress Tunnel Router (ITR) parameters

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp itr map-resolver

```
{ [ no ] { ip | ipv6 } lisp itr map-resolver { <mr> | <mr6> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
itr	Configures LISP Ingress Tunnel Router (ITR) parameters
map-resolver	To interact with Map-Resolver
<i>mr</i>	Address of IPv4 map-server

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp itr send-data-probe

```
{ { [ no ] ip lisp itr send-data-probe } | { [ no ] ipv6 lisp itr send-data-probe } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
itr	Configures LISP Ingress Tunnel Router (ITR) parameters
send-data-probe	Send a Data-Probe instead of Map-Request on the LISP-ALT topology

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp locator-vrf

```
{ { [ no ] ip lisp locator-vrf { <vrf-name> | <vrf-known-name> } } | { [ no ] ipv6 lisp locator-vrf { <vrf-name> | <vrf-known-name> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
locator-vrf	Configure what VRF to use for locator command references
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp locator reachability exclude

[no] { ip | ipv6 } lisp locator reachability { exclude-default | minimum-mask-length <minmask> }

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ip	Configure IP features
ipv6	Configure IPv6 features
locator	Configure locator parameters
reachability	Configure reachability parameters
exclude-default	Exclude default route to reach remote locators
minimum-mask-length	Exclude routes coarser than the given mask length
<i>minmask</i>	Minimum mask length for the routes to locators

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-cache-limit

[no] { ip | ipv6 } lisp map-cache-limit <limit> [reserve-list <prefix-list>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-cache-limit	Configures maximum size of map-cache
<i>limit</i>	Maximum number of map-cache entries
reserve-list	(Optional) EID-prefixes guaranteed to be stored in map-cache
<i>prefix-list</i>	(Optional) Reference to prefix-list name

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-cache drop native-forward map-request priority weight

```
{ { [ no ] ip lisp map-cache <eid-prefix> { drop | native-forward | map-request | { { <locator> | <locator6> }
priority <priority> weight <weight> [ down ] } } } | { [ no ] ipv6 lisp map-cache <eid-prefix6> { drop |
native-forward | map-request | { { <locator6> | <locator> } priority <priority> weight <weight> [ down ] } }
} }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-cache	Configures static EID-to-RLOC mappings for an ITR
<i>eid-prefix</i>	IP EID-prefix for RLOC static mapping
<i>locator</i>	IP address of loopback or other ETR loopback interface
priority	Configures which Locators from a set are preferred
<i>priority</i>	Lower priority Locator takes preference
weight	Traffic load-spreading among Locators
<i>weight</i>	Specified in a percentage from 0 to 100
down	(Optional) Set state to down for RLOC
drop	Drop packets that match this map-cache entry
native-forward	Natively forward packets that match his map-cache entry
map-request	Send Map-Request for LISP destination EID

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-request-source

{ [no] ip lisp map-request-source <source> } | { no ip lisp map-request-source } | { [no] ipv6 lisp map-request-source <source6> } | { no ipv6 lisp map-request-source }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-request-source	Configures source address for Map-Request message
<i>source</i>	Source address for IPv4 Map-Request message

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-resolver

{ [no] { ip | ipv6 } lisp map-resolver }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-resolver	Configures LISP Map Resolver functionality

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-server

```
{ [ no ] { ip | ipv6 } lisp map-server }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-server	Configures LISP Map Server functionality

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp map-server try-map-cache

{ [no] { ip | ipv6 } lisp map-server try-map-cache }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
map-server	Configures LISP Map Server functionality
try-map-cache	Forward Map-Request to RLOCs from map-cache when site configuration does not exist

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp multicast

[no] ip lisp multicast

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
lisp	LISP global configuration commands
multicast	Configures LISP to carry multicast traffic, when ITR or ETR function is enabled

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp nat-traversal

[no] { ip | ipv6 } lisp nat-traversal

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP interface configuration commands
nat-traversal	Send Echo messages to Map-Server to get global locator

Command Mode

- /exec/configure/if-igp

ip lisp ntr

[no] ip lisp ntr <locator>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
lisp	LISP global configuration commands
ntr	Configures LISP NAT Tunnel Router (NTR)
<i>locator</i>	Local IP address in locator namespace

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp null0-is-alt-miss

[no] { ip | ipv6 } lisp null0-is-alt-miss

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
null0-is-alt-miss	Consider a ALT route with null0 next-hop as a lookup miss

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp proxy-etr

{ { [no] ip lisp proxy-etr } | { [no] ipv6 lisp proxy-etr } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
proxy-etr	Configures a Proxy ETR (PETR)
<i>lisp</i>	

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp proxy-itr

{ { [no] ip lisp proxy-itr { <local-rloc> | <local-rloc6> } + } | { [no] ipv6 lisp proxy-itr { <local-rloc> | <local-rloc6> } + } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
proxy-itr	Configures a Proxy ITR (PTR)
<i>local-rloc</i>	Local IP address in locator namespace
<i>lisp</i>	

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp short-map-cache-ttl

{ [no] { ip | ipv6 } lisp short-map-cache-ttl }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
short-map-cache-ttl	Sets both positive and negative TTL in Map-Reply to 1 minute

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp shortest-eid-prefix-length

```
{ { [ no ] ip lisp shortest-eid-prefix-length <pl> } | { [ no ] ipv6 lisp shortest-eid-prefix-length <pl6> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
shortest-eid-prefix-length	Do not accept EID-prefixes shorter than configured value
<i>pl</i>	IPv4 EID-prefix length
<i>pl6</i>	IPv6 EID-prefix length

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp source-locator

```
{ [ no ] { ip | ipv6 } lisp source-locator <interface> [ secondary ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP interface configuration commands
source-locator	Select source locator when destination locator uses this interface
<i>interface</i>	Use primary address from interface as source locator
secondary	(Optional) Use secondary address on interface as source locator

Command Mode

- /exec/configure/if-igp

ip lisp translate inside outside

```
{ { [ no ] ip lisp translate inside <nrEID> outside <rEID> } | { [ no ] ipv6 lisp translate inside <nrEID6>
outside <rEID6> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
translate	Translate source address on ITR or destination address on ETR
inside	Site-based non-routable EID
<i>nrEID</i>	IPv4 inside address
outside	External-based routable EID
<i>rEID</i>	IPv4 outside address

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp use-bgp-locators

[no] { ip | ipv6 } lisp use-bgp-locators [route-map <imap-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
use-bgp-locators	Use next-hops from BGP as locators for map-cache entries
route-map	(Optional) Route-map applied to on-demand routes.
<i>imap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure /exec/configure/vrf

ip lisp use-petr priority weight

[no] { ip | ipv6 } lisp use-petr { <petr> | <petr6> } priority <priority> weight <weight>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
lisp	LISP global configuration commands
use-petr	Encapsulate to Proxy ETR for matching forward-native entry
<i>petr</i>	IPv4 locator address of PETR
priority	Configures which Locators from a set are preferred
<i>priority</i>	Lower priority Locator takes preference
weight	Traffic load-spreading among Locators
<i>weight</i>	Specified in a percentage from 0 to 100

Command Mode

- /exec/configure /exec/configure/vrf

ip load-sharing address

[no] ip load-sharing address { source-destination [port source-destination2 | gre | gre-outer | gtpu] | destination port2 destination2 | source } { [rotate <rotate>] | [concatenation] } + [universal-id <random-seed>] | no ip load-sharing address

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
load-sharing	ECMP load-sharing
address	Configure source/destination addresses, port numbers and hash
source-destination	Use both source and destination values for address
port	(Optional) Use source-destination value for port
gre	(Optional) Use source-destination value for gre-key
gre-outer	(Optional) Use outer IPv4 header fields for GRE tunnel hashing
gtpu	(Optional) Use GTPU TEID value for port source-destination
source-destination2	(Optional) Use both source and destination values for port
destination	Use destination address
port2	Use destination value for port
destination2	Use destination port
source	Use source address
rotate	(Optional) Offset to be used in the hash
<i>rotate</i>	(Optional) Value used for offset, default value is 32
concatenation	(Optional) Enable/Disable concatenation
universal-id	(Optional) Universal-id to randomize hash functions for load-balance
<i>random-seed</i>	(Optional) Value used to randomize hash

Command Mode

- /exec/configure

ip local-proxy-arp

{ ip local-proxy-arp [no-hw-flooding] | no ip local-proxy-arp [no-hw-flooding] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
local-proxy-arp	Configure local proxy ARP
no-hw-flooding	(Optional) Configure local proxy ARP without hardware flooding

Command Mode

- /exec/configure/if-igp /exec/configure/if-vlan-common

ip local policy route-map

ip local policy route-map <route-map-name> | no ip local policy route-map [<route-map-name> | <route-map-name>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
local	Configure local PBR feature
policy	Configure PBR feature
route-map	Route-map for PBR
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	(Optional) Route-map name
<i>route-map-name</i>	(Optional) Known route-map name

Command Mode

- /exec/configure /exec/configure/vrf

ip mfwd event-history cli

[no] ip mfwd event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfwd	Configures Global IP Multicast Forwarding
event-history	Configure event-history buffers
cli	CLI events for MCASTFWD
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip mfw event-history l2

```
[no] ip mfw event-history l2 { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfw	Configures Global IP Multicast Forwarding
event-history	Configure event-history buffers
l2	Layer2 events for MCASTFWD
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip mfwd event-history nbm

[no] ip mfwd event-history nbm { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfwd	Configures Global IP Multicast Forwarding
event-history	Configure event-history buffers
nbm	NBM events for MCASTFWD
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip mfwd event-history packet

```
[no] ip mfwd event-history packet { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfwd	Configures Global IP Multicast Forwarding
event-history	Configure event-history buffers
packet	Packet events for Multicast forwarding
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip mfwd event-history vrf

```
[no] ip mfwd event-history vrf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfwd	Configures Global IP Multicast Forwarding
event-history	Configure event-history buffers
vrf	VRF events for MCASTFWD
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip mfw mstatic register

[no] ip mfw mstatic register

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mfw	Configures Global IP Multicast Forwarding
mstatic	Static Multicast Route
register	Register

Command Mode

- /exec/configure

ip mroute

```
[no] ip mroute { <ip-addr> <ip-mask> | <ip-prefix> } { { <next-hop> | <nh-prefix> } | <interface> } [ <pref> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
mroute	Configure multicast RPF static route
<i>ip-addr</i>	IP prefix in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
<i>ip-prefix</i>	IP prefix and network mask length in format x.x.x.x/m
<i>next-hop</i>	IP next-hop address in format i.i.i.i
<i>nh-prefix</i>	IP next-hop prefix in format i.i.i.i/m
<i>interface</i>	Interface for interface static multicast routes
<i>pref</i>	(Optional) Route preference
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp description

ip msdp description <peer-address> <text> | no ip msdp description <peer-address> [<text>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
description	Configure MSDP description for peer
<i>peer-address</i>	IP address of MSDP peer
<i>text</i>	Text description

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp event-history cli

[no] ip msdp event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
event-history	Configure event-history buffer
cli	CLI logs for MSDP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip msdp event-history events

```
[no] ip msdp event-history events { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
event-history	Configure event-history buffer
events	Peer events for MSDP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip msdp event-history routes

[no] ip msdp event-history routes { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
event-history	Configure event-history buffer
routes	Route logs for MSDP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip msdp event-history tcp

```
[no] ip msdp event-history tcp { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
event-history	Configure event-history buffer
tcp	TCP logs for MSDP
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip msdp flush-routes

[no] ip msdp flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
flush-routes	Remove routes when restarting MSDP

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp group-limit source

[no] ip msdp group-limit <limit> source <sprefix>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
group-limit	Limit the number of groups per source
<i>limit</i>	Limit on number of groups
source	Sources to limit groups to
<i>sprefix</i>	Prefix to match sources against

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp keepalive

ip msdp keepalive <peer-address> <interval> <timeout> | no ip msdp keepalive <peer-address> [<interval> <timeout>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
keepalive	Configure MSDP keepalive parameters for peer
<i>peer-address</i>	IP address of MSDP peer
<i>interval</i>	Keepalive interval in seconds
<i>timeout</i>	Keepalive timeout in seconds

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp mesh-group

ip msdp mesh-group <peer-address> <name> | no ip msdp mesh-group <peer-address> [<name>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
mesh-group	Configure member of mesh-group
<i>name</i>	Name of mesh-group
<i>peer-address</i>	IP address of MSDP peer in mesh-group

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp originator-id

ip msdp originator-id <interface> | no ip msdp originator-id [<interface>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
originator-id	Configure alternative router-id for MSDP
<i>interface</i>	Use IP address of interface for originator-id

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp password

ip msdp password <peer-address> <password> | no ip msdp password <peer-address> [<password>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
password	Configure MD5 authentication password
<i>peer-address</i>	IP address of MSDP peer
<i>password</i>	MD5 password

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp peer connect-source

```
{ { ip msdp peer <peer-address> connect-source <interface> [ remote-as <asn> ] } | { no ip msdp peer
<peer-address> [ connect-source <interface> ] [ remote-as <asn> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
peer	Configure MSDP peer
<i>peer-address</i>	IP address of MSDP peer
connect-source	Configure local IP address for TCP connection
<i>interface</i>	Use IP address of interface for peer address
remote-as	(Optional) Configure remote Autonomous System Number
<i>asn</i>	(Optional) AS number

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp reconnect-interval

ip msdp reconnect-interval <interval> | no ip msdp reconnect-interval [<interval>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
reconnect-interval	Configure connection reconnect interval
<i>interval</i>	Interval in seconds

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp redistribute

[no] ip msdp redistribute [route-map <route-map-name> | prefix-list <prefix-list-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
redistribute	Configure SA policy for all MSDP peer
route-map	(Optional) route-map policy
<i>route-map-name</i>	(Optional) Route-map name
prefix-list	(Optional) Prefix list policy
<i>prefix-list-name</i>	(Optional) Name of prefix-list

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp sa-interval

ip msdp sa-interval <interval> | no ip msdp sa-interval [<interval>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
sa-interval	Configure Source-Active message transmission interval
<i>interval</i>	Interval in seconds

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp sa-limit

ip msdp sa-limit <peer-address> <limit> | no ip msdp sa-limit <peer-address> [<limit>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
sa-limit	Configure maximum (S,G) entries allowed
<i>limit</i>	Number of (S,G) entries
<i>peer-address</i>	IP address of MSDP peer in mesh-group

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp sa-policy in

```
[no] ip msdp sa-policy <peer-address> { <route-map-name> | prefix-list <prefix-list-name> | <rtr_pol_name> } in
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
sa-policy	Configure SA policy for MSDP peer
prefix-list	Prefix list policy
in	Input policy
<i>peer-address</i>	IP address of MSDP peer for SA policy
<i>route-map-name</i>	Route-map name
<i>prefix-list-name</i>	Name of prefix-list
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp sa-policy out

```
[no] ip msdp sa-policy <peer-address> { <route-map-name> | prefix-list <prefix-list-name> | <rtr_pol_name> } out
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
sa-policy	Configure SA policy for MSDP peer
prefix-list	Prefix list policy
out	Output policy
<i>peer-address</i>	IP address of MSDP peer for SA policy
<i>route-map-name</i>	Route-map name
<i>prefix-list-name</i>	Name of prefix-list
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip msdp shutdown

ip msdp shutdown <peer-address> | no ip msdp shutdown <peer-address>

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
msdp	MSDP global configuration commands
shutdown	Administratively shut down peer
<i>peer-address</i>	IP address of MSDP peer

Command Mode

- /exec/configure /exec/configure/vrf

ip mtu eigrp

{ { { ip | ipv6 } mtu eigrp <eigrp-ptag> <mtu> } | { no { ip | ipv6 } mtu eigrp <eigrp-ptag> [<mtu>] } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
mtu	Set Max Packet Size to be used by EIGRP
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>mtu</i>	Interface MTU
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip multicast multipath

[no] ip multicast multipath { none | legacy | s-g-hash [next-hop-based] | nbm }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
multicast	Configure IP multicast global parameters
multipath	Configure ECMP multicast load splitting
legacy	Configure hash based on source and group
none	Disable ECMP multicast load splitting
s-g-hash	Configure hash based on source and group address
next-hop-based	(Optional) Configure hash based on source, group, next-hop address
nbm	Configure NBM controlled RPF interface

Command Mode

- /exec/configure /exec/configure/vrf

ip multicast multipath resilient

[no] ip multicast multipath resilient

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
multicast	Configure IP multicast global parameters
multipath	Configure ECMP multicast load splitting
resilient	Configure resilient RPF interface

Command Mode

- /exec/configure /exec/configure/vrf

ip multicast overlay-distributed-dr

[no] ip multicast overlay-distributed-dr

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
multicast	Configure multicast
overlay-distributed-dr	Configure node as Distributed-DR

Command Mode

- /exec/configure

ip multicast overlay-spt-only

[no] ip multicast overlay-spt-only

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
multicast	Configure multicast
overlay-spt-only	Enable L3-Overlay spt(shortest-path-tree) only

Command Mode

- /exec/configure

ip multicast rpf select vrf group-list

```
{ { ip multicast rpf select { vrf { <vrf-name> | <vrf-known-name> } group-list <prefix> } } | { no ip multicast rpf select { vrf { <vrf-name> | <vrf-known-name> } group-list <prefix> } } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
multicast	Configure IP multicast global parameters
rpf	Configure RPF check
select	Configure VRF for RPF check
vrf	VRF for RPF lookup
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name
group-list	Group range for RPF select
<i>prefix</i>	Group range prefix

Command Mode

- /exec/configure /exec/configure/vrf

ip name-server

```
[no] ip name-server { { <ipv4_0> | <ipv6_1> } [ { <ipv4_2> | <ipv6_3> } [ { <ipv4_4> | <ipv6_5> } [ { <ipv4_6> | <ipv6_7> } [ { <ipv4_8> | <ipv6_9> } [ { <ipv4_10> | <ipv6_11> } ] ] ] ] ] | { <ipv4_12> | <ipv6_13> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] | { <ipv4_14> | <ipv6_15> } [ { <ipv4_16> | <ipv6_17> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] ] | { <ipv4_18> | <ipv6_19> } [ { <ipv4_20> | <ipv6_21> } [ { <ipv4_22> | <ipv6_23> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] ] ] | { <ipv4_24> | <ipv6_25> } [ { <ipv4_26> | <ipv6_27> } [ { <ipv4_28> | <ipv6_29> } [ { <ipv4_30> | <ipv6_31> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] ] ] ] | { <ipv4_32> | <ipv6_33> } [ { <ipv4_34> | <ipv6_35> } [ { <ipv4_36> | <ipv6_37> } [ { <ipv4_38> | <ipv6_39> } [ { <ipv4_40> | <ipv6_41> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] ] ] ] ] | { <ipv4_42> | <ipv6_43> } [ { <ipv4_44> | <ipv6_45> } [ { <ipv4_46> | <ipv6_47> } [ { <ipv4_48> | <ipv6_49> } [ { <ipv4_50> | <ipv6_51> } [ { <ipv4_52> | <ipv6_53> } [ use-vrf { <vrf-name> | <vrf-known-name> } ] ] ] ] ] ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
name-server	Specify nameserver address
<i>ipv4_0</i>	Enter an IPv4 address
<i>ipv4_2</i>	(Optional) Enter an IPv4 address
<i>ipv4_4</i>	(Optional) Enter an IPv4 address
<i>ipv4_6</i>	(Optional) Enter an IPv4 address
<i>ipv4_8</i>	(Optional) Enter an IPv4 address
<i>ipv4_10</i>	(Optional) Enter an IPv4 address
<i>ipv4_12</i>	Enter an IPv4 address
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ipv4_14</i>	Enter an IPv4 address
<i>ipv4_16</i>	(Optional) Enter an IPv4 address
<i>ipv4_18</i>	Enter an IPv4 address
<i>ipv4_20</i>	(Optional) Enter an IPv4 address
<i>ipv4_22</i>	(Optional) Enter an IPv4 address
<i>ipv4_24</i>	Enter an IPv4 address

<i>ipv4_26</i>	(Optional) Enter an IPv4 address
<i>ipv4_28</i>	(Optional) Enter an IPv4 address
<i>ipv4_30</i>	(Optional) Enter an IPv4 address
<i>ipv4_32</i>	Enter an IPv4 address
<i>ipv4_34</i>	(Optional) Enter an IPv4 address
<i>ipv4_36</i>	(Optional) Enter an IPv4 address
<i>ipv4_38</i>	(Optional) Enter an IPv4 address
<i>ipv4_40</i>	(Optional) Enter an IPv4 address
<i>ipv4_42</i>	Enter an IPv4 address
<i>ipv4_44</i>	(Optional) Enter an IPv4 address
<i>ipv4_46</i>	(Optional) Enter an IPv4 address
<i>ipv4_48</i>	(Optional) Enter an IPv4 address
<i>ipv4_50</i>	(Optional) Enter an IPv4 address
<i>ipv4_52</i>	(Optional) Enter an IPv4 address

Command Mode

- /exec/configure /exec/configure/vrf

ip nat inside

[no] ip nat { inside | outside }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
nat	NAT interface commands
inside	Inside interface for address translation
outside	Outside interface for address translation

Command Mode

- /exec/configure/if-port-channel /exec/configure/if-vlan /exec/configure/if-remote-ethernet /exec/configure/if-igp /exec/configure/if-routing

ip nat inside source

```
[no] ip nat inside source { { static <insideLocalIP> <insideGlobalIP> [ vrf <vrf-name> [ match-in-vrf ] ] [
group <group-id> [ dynamic ] ] [ no-alias ] [ add-route ] } | { static { tcp | udp } <insideLocalIP>
<insideLocalPort> <insideGlobalIP> <insideGlobalPort> [ vrf <vrf-name> [ match-in-vrf ] ] [ group <group-id>
[ dynamic ] ] [ no-alias ] [ add-route ] } | { list <acl-name> } { pool <pool-name> [ vrf <vrf-name> [
match-in-vrf ] ] [ overload ] | interface <globalAddrInterface> [ vrf <vrf-name> [ match-in-vrf ] ] overload }
[ group <group-id> dynamic ] [ add-route ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
inside	Inside address translation
source	Source address translation
static	Specify static local->global mapping
tcp	Transmission Control Protocol
udp	User Datagram Protocol
list	Specify access list describing local addresses
pool	Name pool of global addresses
interface	Specify interface for global address
vrf	(Optional) Specify vrf
match-in-vrf	(Optional) Match incoming vrf
no-alias	(Optional) Do not create alias for this NAT-address
dynamic	(Optional) Dynamic twice NAT group
<i>insideLocalIP</i>	Inside local IP address
<i>insideLocalPort</i>	Local UDP/TCP port
<i>insideGlobalIP</i>	Inside global IP address
<i>insideGlobalPort</i>	Global UDP/TCP port
group	(Optional) Specify group for the twice NAT
<i>group-id</i>	(Optional) Group ID for the twice NAT
<i>acl-name</i>	Access-list-name

<i>pool-name</i>	Pool name for global addresses
add-route	(Optional) Add a static route for outside local address
<i>vrf-name</i>	(Optional) vrf name
<i>globalAddrInterface</i>	interface type and number in module/slot format
overload	(Optional) Overload an address translation

Command Mode

- /exec/configure

ip nat outside source

```
[no] ip nat outside source { static <outsideGlobalIP> <outsideLocalIP> [ vrf <vrf-name> [ match-in-vrf ] ] [ group <group-id> [ dynamic ] ] [ no-alias ] [ add-route ] | static { tcp | udp } <outsideGlobalIP> <outsideGlobalPort> <outsideLocalIP> <outsideLocalPort> [ vrf <vrf-name> [ match-in-vrf ] ] [ group <group-id> [ dynamic ] ] [ no-alias ] [ add-route ] | list <acl-name> pool <pool-name> [ vrf <vrf-name> [ match-in-vrf ] ] [ group <group-id> dynamic ] } [ add-route ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
outside	Outside address translation
source	Source address translation
static	Specify static global->local mapping
tcp	Transmission Control Protocol
udp	User Datagram Protocol
list	Specify access list describing local addresses
pool	Name pool of global addresses
vrf	(Optional) Specify vrf
match-in-vrf	(Optional) Match incoming vrf
no-alias	(Optional) Do not create alias for this NAT-address
<i>outsideGlobalIP</i>	Outside global IP address
<i>outsideGlobalPort</i>	Outside Global UDP/TCP port
<i>outsideLocalIP</i>	Outside local IP address
<i>outsideLocalPort</i>	Outside Local UDP/TCP port
group	(Optional) Specify group for the twice NAT
dynamic	(Optional) Dynamic twice NAT group
<i>group-id</i>	(Optional) Group ID for the twice NAT
<i>acl-name</i>	Access-list-name
<i>vrf-name</i>	(Optional) vrf name
<i>pool-name</i>	Pool name for global addresses

add-route	(Optional) Add a static route for outside local address
-----------	---

Command Mode

- /exec/configure

ip nat pool netmask

```
ip nat pool <pool-name> <start-ip> <end-ip> { netmask <netmask> | prefix-length <prefix-length> } [ no-alias ] | no ip nat pool <pool-name> [ <start-ip> <end-ip> { netmask <netmask> | prefix-length <prefix-length> } ]
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
pool	Define pool of addresses
netmask	Specify the network mask
prefix-length	Specify the prefix length
no-alias	(Optional) Do not create alias for these pool addresses
<i>pool-name</i>	Pool name
<i>start-ip</i>	Start IP address
<i>end-ip</i>	End IP address
<i>netmask</i>	Network mask
<i>prefix-length</i>	Prefix length

Command Mode

- /exec/configure

ip nat pool netmask

ip nat pool <pool-name> { netmask <netmask> | prefix-length <prefix-length> } [no-alias]

Syntax Description

ip	Configure IP features
nat	NAT configuration commands
pool	Define pool of addresses
netmask	Specify the network mask
prefix-length	Specify the prefix length
no-alias	(Optional) Do not create alias for these pool addresses
<i>pool-name</i>	Pool name
<i>netmask</i>	Network mask
<i>prefix-length</i>	Prefix length

Command Mode

- /exec/configure

ip nat translation

```
[no] ip nat translation { { { tcp-timeout | udp-timeout | icmp-timeout | timeout } <timeout> } | { finrst-timeout
{ <fin_timeout> | never } | syn-timeout { <syn_timeout> | never } | timeout } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
translation	NAT translation entry configuration
tcp-timeout	Specify timeout for NAT TCP flows
udp-timeout	Specify timeout for NAT UDP flows
icmp-timeout	Specify timeout for NAT ICMP flows
finrst-timeout	Specify timeout for NAT TCP flows after a FIN or RST
syn-timeout	Specify timeout for NAT TCP flows after a SYN and no further data
timeout	Specify timeout for dynamic NAT flows
never	Never timeout
<i>timeout</i>	Timeout in seconds
<i>fin_timeout</i>	Timeout in seconds
<i>syn_timeout</i>	Timeout in seconds

Command Mode

- /exec/configure

ip nat translation creation-delay

{ ip nat translation creation-delay <batch-timeout> } | { no ip nat translation creation-delay }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
translation	NAT translation entry configuration
creation-delay	Translation entries creation delay due to batching before program to team
<i>batch-timeout</i>	0/250/500/750/1000

Command Mode

- /exec/configure

ip nat translation max-entries

ip nat translation max-entries [all-host] <max> | no ip nat translation max-entries [all-host]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
translation	NAT translation entry configuration
max-entries	Specify maximum number of NAT dynamic entries
all-host	(Optional) Specify maximum number of NAT entries for each host
<i>max</i>	Number of entries

Command Mode

- /exec/configure

ip nat translation sampling-timeout

[no] ip nat translation sampling-timeout <timeout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
nat	NAT configuration commands
translation	NAT translation entry configuration
sampling-timeout	Specify timeout after which the checking for activity is done
<i>timeout</i>	Timeout in seconds (max: 2days, recommended 900s)

Command Mode

- /exec/configure

ip next-hop-self eigrp

[no] { ip | ipv6 } next-hop-self eigrp <eigrp-ptag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
next-hop-self	Configures IP-EIGRP next-hop-self
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip offset-list eigrp

[no] { ip | ipv6 } offset-list eigrp <eigrp-ptag> { { route-map <map> } | { prefix-list <list> } } { in | out } <offset>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
offset-list	Add or subtract offset from EIGRP metrics
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
route-map	Use a route-map for offset-list selection
<i>map</i>	Route-map name
prefix-list	Use a prefix-list for offset-list selection
<i>list</i>	Reference to prefix-list name
in	Perform offset on incoming updates
out	Perform offset on outgoing updates
<i>offset</i>	Offset

Command Mode

- /exec/configure/if-igp

ip ospf advertise-subnet

[no] ip ospf advertise-subnet

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
advertise-subnet	Advertise loopback interface IP subnet in router LSA

Command Mode

- /exec/configure/if-loopback

ip ospf authentication-key

```
{ { ip ospf authentication-key <key> } | { no ip ospf authentication-key [ <key> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
authentication-key	Configure the authentication key for the interface
<i>key</i>	Authentication key

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf authentication

[no] ip ospf authentication [message-digest | null]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
authentication	Authentication on the interface
message-digest	(Optional) Use message-digest authentication
null	(Optional) Use null(disable) authentication

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf authentication key-chain

{ ip ospf authentication key-chain <keychain> } | { no ip ospf authentication key-chain [<keychain>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
authentication	Authentication on the interface
key-chain	Authentication password key-chain
<i>keychain</i>	Key-chain name

Command Mode

- /exec/configure/if-igmp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf bfd

[no] ip ospf bfd [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
bfd	Enable BFD on this interface
disable	(Optional) Disable BFD on this interface

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mgmt-config

ip ospf cost

```
{ ip ospf cost <cost> } | { no ip ospf cost [ <cost> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
cost	Cost associated with interface
<i>cost</i>	Cost value

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf dead-interval

```
{ ip ospf dead-interval <interval> } | { no ip ospf dead-interval [ <interval> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
dead-interval	Dead interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ZZZ_4621

```
[ ip ospf event-history { adjacency | event | ha | flooding | lsa | spf | redistribution | ldp | te | rib | hello | spf-trigger | objstore } size { <size_in_text> <size_in_Kbytes> } ] | [ no ip ospf event-history { adjacency | event | ha | flooding | lsa | spf | redistribution | ldp | te | rib | hello | spf-trigger | objstore } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	(Optional) IP events
ospf	(Optional) Debug OSPF events
event-history	(Optional) log debug events into event history buffer
adjacency	(Optional) Adjacency formation logs
event	(Optional) Internal event logs
ha	(Optional) HA and GR logs
flooding	(Optional) LSA flooding logs
lsa	(Optional) LSA generation and database logs
spf	(Optional) SPF calculation logs
redistribution	(Optional) Redistribution logs
ldp	(Optional) LDP related logs
te	(Optional) MPLS TE related logs
rib	(Optional) RIB related logs
hello	(Optional) HELLO related logs
spf-trigger	(Optional) SPF TRIGGER related logs
objstore	(Optional) DME OBJSTORE related logs
size	(Optional) Configure the size of the event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf

ip ospf event-history cli

[no ip ospf event-history cli] | [ip ospf event-history cli size { <size_in_text> | <size_in_Kbytes> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	(Optional) IP events
ospf	(Optional) Debug OSPF events
event-history	(Optional) log debug events into event history buffer
cli	(Optional) Cli logs
size	(Optional) Configure the size of the event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf

ip ospf event-history detail

[no ip ospf event-history detail] | [ip ospf event-history detail size { <size_in_text> | <size_in_Kbytes> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	(Optional) IP events
ospf	(Optional) Debug OSPF events
event-history	(Optional) log debug events into event history buffer
detail	(Optional) Detailed event history buffer
size	(Optional) Configure the size of the verbose event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf

ip ospf hello-interval

```
{ ip ospf hello-interval <interval> } | { no ip ospf hello-interval [ <interval> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
hello-interval	Hello interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf message-digest-key md5

```
{ { ip ospf message-digest-key <keyid> md5 <key> } | { no ip ospf message-digest-key <keyid> [ md5 <key> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
message-digest-key	Message digest authentication password (key)
<i>keyid</i>	Key ID
md5	Use MD5 algorithm
<i>key</i>	The OSPF password (key)

Command Mode

- /exec/configure/if-igmp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf mtu-ignore

[no] ip ospf mtu-ignore

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
mtu-ignore	Disable OSPF MTU mismatch detection

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf network broadcast

{ ip ospf network { broadcast | point-to-point } } | { no ip ospf network [{ broadcast | point-to-point }] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
network	Network type
broadcast	Specify OSPF broadcast multi-access network
point-to-point	Specify OSPF point-to-point network

Command Mode

- /exec/configure/if-broadcast /exec/configure/if-p2p /exec/configure/if-mgmt-config

ip ospf network point-to-point

{ ip ospf network point-to-point } | { no ip ospf network [point-to-point] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
network	Network type
point-to-point	Specify OSPF point-to-point network

Command Mode

- /exec/configure/if-loopback

ip ospf passive-interface

[default | no] ip ospf passive-interface

Syntax Description

default	(Optional) Undo a command
no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
passive-interface	Suppress routing updates on the interface

Command Mode

- /exec/configure/if-broadcast /exec/configure/if-p2p /exec/configure/if-mgmt-config

ip ospf prefix-attributes n-flag-clear

[no] ip ospf prefix-attributes n-flag-clear

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
prefix-attributes	Prefix attributes
n-flag-clear	Clear N-Flag for the interface prefixes

Command Mode

- /exec/configure/if-loopback

ip ospf priority

{ ip ospf priority <prio> } | { no ip ospf priority [<prio>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
priority	Router priority
<i>prio</i>	Router priority

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf retransmit-interval

{ ip ospf retransmit-interval <interval> } | { no ip ospf retransmit-interval [<interval>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
retransmit-interval	Packet retransmission interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip ospf shutdown

[no] ip ospf shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
shutdown	shutdown ospf on this interface

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mgmt-config

ip ospf transmit-delay

{ ip ospf transmit-delay <delay> } | { no ip ospf transmit-delay [<delay>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ospf	OSPF configuration commands
transmit-delay	Packet transmission delay
<i>delay</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip passive-interface eigrp

[default | no] { ip | ipv6 } passive-interface eigrp <eigrp-ptag>

Syntax Description

default	(Optional) Undo a command
no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
passive-interface	Suppress routing updates on an interface
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip pim anycast-rp

[no] ip pim anycast-rp <anycast-rp> <rp-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
anycast-rp	Configure an RP in an Anycast-RP set (using PIM)
<i>anycast-rp</i>	Address for the Anycast-RP address
<i>rp-addr</i>	Address of RP in the Anycast-RP set

Command Mode

- /exec/configure /exec/configure/vrf

ip pim assert-rate-limit

```
{ { ip pim assert-rate-limit <rate> } | { no ip pim assert-rate-limit [ <rate> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
assert-rate-limit	Rate limit for PIM Asserts
<i>rate</i>	Packets per second

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-enable

{ { no ip pim auto-enable } | { ip pim auto-enable } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-enable	Auto-enable configure on the vrf

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-rp listen

{ ip pim auto-rp { listen | forward } + } | { no ip pim auto-rp [{ listen | forward } +] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-rp	Auto-RP protocol RP-distribution configuration
listen	Listen to Auto-RP messages
forward	Forward Auto-RP messages

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-rp mapping-agent-policy

```
{ ip pim auto-rp mapping-agent-policy { <route-map-name> | <rtr_pol_name> } | no ip pim auto-rp
mapping-agent-policy [ <route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-rp	Auto-RP protocol RP-distribution configuration
mapping-agent-policy	Specify policy for filtering Mapping Agent messages
<i>route-map-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-rp mapping-agent send-rp-discovery

```
{ { ip pim { { auto-rp mapping-agent } | send-rp-discovery } <interface> [ scope <ttl> ] } | { no ip pim { { auto-rp mapping-agent } | send-rp-discovery } [ <interface> ] [ scope <ttl> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-rp	Auto-RP protocol RP-distribution configuration
send-rp-discovery	Configures router to send Auto-RP Discovery messages
mapping-agent	Configures router as an Auto-RP RP-mapping agent
<i>interface</i>	Use IP address of interface for Auto-RP Announce messages
scope	(Optional) Configure the scope of Auto-RP Discovery messages
<i>ttl</i>	(Optional) TTL value for scope

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-rp rp-candidate-policy

{ ip pim auto-rp rp-candidate-policy { <route-map-name> | <rtr_pol_name> } | no ip pim auto-rp rp-candidate-policy [<route-map-name> | <rtr_pol_name>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-rp	Auto-RP protocol RP-distribution configuration
rp-candidate-policy	Specify policy for filtering RP candidate messages
<i>route-map-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip pim auto-rp rp-candidate send-rp-announce group-list route-map prefix-list

```
{ { ip pim { auto-rp rp-candidate | send-rp-announce } { <interface> | <ipaddr> } { group-list <prefix> | route-map <route-map-name> | prefix-list <prefix-list-name> } { [ scope <ttl> ] | [ interval <interval> ] | [ bidir ] } + } | { no ip pim { { auto-rp rp-candidate } | send-rp-announce } [ <interface> | <ipaddr> ] [ group-list <prefix> | route-map <route-map-name> | prefix-list <prefix-list-name> ] { [ scope <ttl> ] | [ interval <interval> ] | [ bidir ] } } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
auto-rp	Auto-RP protocol RP-distribution configuration
send-rp-announce	Configures router to send Auto-RP Announce messages
rp-candidate	Configures router to be an Auto-RP candidate RP
<i>interface</i>	Use IP address of interface for Auto-RP Announce messages
<i>ipaddr</i>	IP address of RP for group
group-list	Group range list
<i>prefix</i>	Prefix of group range
route-map	Group range policy for Auto-RP Candidate RP
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy for Auto-RP Candidate RP
<i>prefix-list-name</i>	Name of prefix-list
scope	(Optional) Configure the scope of Auto-RP Announce messages
<i>ttl</i>	(Optional) TTL value for scope
interval	(Optional) Auto-RP Announce message transmission interval
<i>interval</i>	(Optional) Interval in seconds
bidir	(Optional) Group range advertised in PIM bidirectional mode

Command Mode

- /exec/configure /exec/configure/vrf

ip pim bfd-instance

[no] ip pim bfd-instance [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
bfd-instance	Configures BFD on interface
disable	(Optional) Disable BFD on interface

Command Mode

- /exec/configure/if-igp

ip pim bfd

[no] ip pim bfd

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bfd	Enable / Disable BFD for all PIM interfaces in the VRF

Command Mode

- /exec/configure /exec/configure/vrf

ip pim bidir-rp-limit

[no] ip pim bidir-rp-limit <limit>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bidir-rp-limit	Configures maximum Bidir RPs for IPv4 PIM in this VRF
<i>limit</i>	Set limit for Bidir RPs permitted in IPv4 PIM

Command Mode

- /exec/configure /exec/configure/vrf

ip pim border-router

[no] ip pim border-router

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
border-router	Configures the interface to be a boundary of a PIM-SM domain

Command Mode

- /exec/configure/if-igp

ip pim border

[no] ip pim border

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
border	Configures interface to be a boundary of a PIM domain

Command Mode

- /exec/configure/if-igp

ip pim bsr-candidate

```
{ { ip pim [ bsr ] bsr-candidate <interface> [ hash-len <hash-len> ] [ priority <priority> ] [ interval <interval> ] } | { no ip pim [ bsr ] bsr-candidate [ <interface> ] [ hash-len <hash-len> ] [ priority <priority> ] [ interval <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bsr	(Optional) Bootstrap protocol RP-distribution configuration
bsr-candidate	Configure router as a Bootstrap Router candidate
<i>interface</i>	Use IP address of interface for Bootstrap messages
hash-len	(Optional) Hash mask length used in Bootstrap messages
<i>hash-len</i>	(Optional) Hash mask length value
priority	(Optional) BSR priority used in Bootstrap messages
<i>priority</i>	(Optional) BSR priority value
interval	(Optional) Bootstrap message transmission interval
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure /exec/configure/vrf

ip pim bsr bsr-policy

```
{ ip pim bsr bsr-policy { <route-map-name> | <rtr_pol_name> } | no ip pim bsr bsr-policy [ <route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
bsr-policy	Specify policy for filtering BSR messages
<i>route-map-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip pim bsr listen

{ ip pim bsr { listen | forward } + } | { no ip pim bsr [{ listen | forward } +] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
listen	Listen to Bootstrap/Candidate-RP messages
forward	Forward Bootstrap/Candidate-RP messages

Command Mode

- /exec/configure /exec/configure/vrf

ip pim bsr rp-candidate-policy

```
{ ip pim bsr rp-candidate-policy { <route-map-name> | <rtr_pol_name> } | no ip pim bsr rp-candidate-policy
[ <route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
rp-candidate-policy	Specify policy for filtering RP candidate messages
<i>route-map-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ip pim dr-delay

```
{ { ip pim dr-delay <delay> } | { no ip pim dr-delay [ <delay> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
dr-delay	Configures delay for PIM DR election on interface
<i>delay</i>	Delay value

Command Mode

- /exec/configure/if-igp

ip pim dr-priority

```
{ { ip pim dr-priority <priority> } | { no ip pim dr-priority [ <priority> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
dr-priority	Configures priority for PIM DR election on interface
<i>priority</i>	Priority value

Command Mode

- /exec/configure/if-igp

ip pim event-history assert

```
[no] ip pim event-history assert { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
assert	Assert events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history bidir

```
[no] ip pim event-history bidir { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
bidir	Bidir events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history cli

[no] ip pim event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
cli	CLI events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history data-register-receive

```
[no] ip pim event-history data-register-receive { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
data-register-receive	Data register rcv events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history hello

```
[no] ip pim event-history hello { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
hello	Hello events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history join-prune-summary

```
[no] ip pim event-history join-prune-summary { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
join-prune-summary	JoinPrune-Summary for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history join-prune-tw

```
[no] ip pim event-history join-prune-tw { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
join-prune-tw	JoinPrune-tw for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history join-prune

```
[no] ip pim event-history join-prune { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
join-prune	Join Prune events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history mrib

```
[no] ip pim event-history mrib { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
mrib	MRIB events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history mvpn

```
[no] ip pim event-history mvpn { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
mvpn	MVPN events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history nbm

```
[no] ip pim event-history nbm { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
nbm	NBM events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history null-register

```
[no] ip pim event-history null-register { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
null-register	Null register events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history packet

[no] ip pim event-history packet { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
packet	Packet events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history pim-library

```
[no] ip pim event-history pim-library { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
pim-library	PIM library events
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history rp

[no] ip pim event-history rp { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
rp	RP events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history txlist

```
[no] ip pim event-history txlist { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
txlist	Txlist events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history vpc

[no] ip pim event-history vpc { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	Configure PIM event history
event-history	Configure event-history buffer
vpc	vPC events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim event-history vrf

```
[no] ip pim event-history vrf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
event-history	Configure event-history buffer
vrf	VRF events for PIM
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip pim evpn-border-leaf

[no] ip pim evpn-border-leaf

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
evpn-border-leaf	Configure this node as a border leaf

Command Mode

- /exec/configure

ip pim extranet

[no] ip pim extranet

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
extranet	Support for Extranet RPF lookup

Command Mode

- /exec/configure

ip pim file-debug

[no] ip pim file-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
file-debug	Collect all debugs to a file

Command Mode

- /exec/configure

ip pim flush-routes

[no] ip pim flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
flush-routes	Remove routes when restarting PIM

Command Mode

- /exec/configure /exec/configure/vrf

ip pim group-list

[no] ip pim { use-shared-tree-only | spt-threshold infinity } group-list { <route-map-name> | prefix-list <prefix-list-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
use-shared-tree-only	Use (*,G) only state, no source state is created
spt-threshold	Source-tree switching threshold
infinity	Never switch to source-tree
group-list	Specify group ranges through policy
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy
<i>prefix-list-name</i>	Name of prefix-list

Command Mode

- /exec/configure /exec/configure/vrf

ip pim hello-authentication ah-md5

```
{ ip pim hello-authentication ah-md5 <auth-key> | no ip pim hello-authentication ah-md5 [ <auth-key> ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
hello-authentication	Add AH header option to Hellos
ah-md5	Use MD5 HMAC
<i>auth-key</i>	MD5 authentication key

Command Mode

- /exec/configure/if-igp

ip pim hello-interval

```
{ { ip pim hello-interval <interval> } | { no ip pim hello-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
hello-interval	Configures the Hello interval for interface
<i>interval</i>	Interval in milliseconds

Command Mode

- /exec/configure/if-igp

ip pim isolate

[no] ip pim isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
isolate	Isolate this router from PIM perspective

Command Mode

- /exec/configure

ip pim jp-interval

[no] ip pim jp-interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
jp-interval	Join-Prune interval used between peers
<i>interval</i>	Interval in seconds

Command Mode

- /exec/configure/if-igp

ip pim jp-policy

```
{ ip pim jp-policy { <route-map-name> | prefix-list <prefix-list-name> } [ in | out ] | no ip pim jp-policy { <route-map-name> | prefix-list <prefix-list-name> } [ in | out ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
jp-policy	Specify policy for receiving Join-Prune messages
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy for static RP
<i>prefix-list-name</i>	Name of prefix-list
in	(Optional) Inbound
out	(Optional) Outbound

Command Mode

- /exec/configure/if-igp

ip pim log-neighbor-changes

[no] ip pim log-neighbor-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
log-neighbor-changes	Log up/down PIM neighbor transitions

Command Mode

- /exec/configure /exec/configure/vrf

ip pim neighbor-policy prefix-list

```
{ { ip pim neighbor-policy { <route-map-name> | prefix-list <prefix-list-name> } } | { no ip pim neighbor-policy
[ <route-map-name> | prefix-list <prefix-list-name> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
neighbor-policy	Configures a neighbor policy for filtering adjacencies
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy for neighbor
<i>prefix-list-name</i>	Name of prefix-list

Command Mode

- /exec/configure/if-igp

ip pim passive

{ ip pim passive | no ip pim passive }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
passive	Interface in passive mode. No send/rcv

Command Mode

- /exec/configure/if-igp

ip pim pre-build-spt

```
{ { { ip pim pre-build-spt [ force ] } [ route-map <route-map-name> | prefix-list <prefix-list-name> ] } | { no ip pim pre-build-spt } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
pre-build-spt	Pre construct PIM trees for all known (S,G)s
force	(Optional) Enable pre-build-spt irrespective of (*,G) state
route-map	(Optional) Route Map policy for pre-build-spt
<i>route-map-name</i>	(Optional) Route-map name
prefix-list	(Optional) Prefix List policy for pre-build-spt
<i>prefix-list-name</i>	(Optional) Name of prefix-list

Command Mode

- /exec/configure /exec/configure/vrf

ip pim register-policy

{ ip pim register-policy { <route-map-name> | prefix-list <prefix-list-name> } | no ip pim register-policy [<route-map-name> | prefix-list <prefix-list-name>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
register-policy	Specify policy for receiving Register messages
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy for Registers
<i>prefix-list-name</i>	Name of prefix-list

Command Mode

- /exec/configure /exec/configure/vrf

ip pim register-rate-limit

```
{ { ip pim register-rate-limit <rate> } | { no ip pim register-rate-limit [ <rate> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
register-rate-limit	Rate limit for PIM data registers
<i>rate</i>	Packets per second

Command Mode

- /exec/configure /exec/configure/vrf

ip pim register-source

{ { ip pim register-source { <src-interface> } } | { no ip pim register-source [<src-interface>] } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
register-source	Configure source address for Register messages
<i>src-interface</i>	Use IP address of this interface for Register messages

Command Mode

- /exec/configure /exec/configure/vrf

ip pim register-until-stop

[no] ip pim register-until-stop

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
register-until-stop	Send Data Registers till Register Stop is received

Command Mode

- /exec/configure

ip pim rp-address

```
{ { ip pim rp-address <rp-address> [ group-list <prefix> | route-map <route-map-name> | prefix-list <prefix-list-name> ] [ bidir ] [ override ] } | { no ip pim rp-address <rp-address> [ group-list <prefix> | route-map <route-map-name> | prefix-list <prefix-list-name> ] [ bidir ] [ override ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
rp-address	Configure static RP for group range
<i>rp-address</i>	IP address of router which is RP for group range
group-list	(Optional) Group range for static RP
<i>prefix</i>	(Optional) Group range prefix
route-map	(Optional) Route Map policy for static RP
<i>route-map-name</i>	(Optional) Route-map name
prefix-list	(Optional) Prefix List policy for static RP
<i>prefix-list-name</i>	(Optional) Name of prefix-list
bidir	(Optional) Group range is treated in PIM bidirectional mode
override	(Optional) RP address will override the dynamically learnt RPs

Command Mode

- /exec/configure /exec/configure/vrf

ip pim rp-candidate group-list route-map prefix-list

```
{ { ip pim [ bsr ] rp-candidate <interface> { group-list <prefix> | route-map <route-map-name> | prefix-list <prefix-list-name> } [ priority <priority> ] [ interval <interval> ] [ bidir ] } | { no ip pim [ bsr ] rp-candidate [ <interface> ] [ group-list <prefix> ] [ route-map <route-map-name> ] [ prefix-list <prefix-list-name> ] [ priority <priority> ] [ interval <interval> ] [ bidir ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
bsr	(Optional) Bootstrap protocol RP-distribution configuration
rp-candidate	Configure router as a Rendezvous Point (RP) candidate
<i>interface</i>	Use IP address of interface for Candidate-RP messages
group-list	Group range list
<i>prefix</i>	Prefix of group range
route-map	Group range policy for Candidate RP
<i>route-map-name</i>	Route-map name
prefix-list	Prefix List policy for Candidate RP
<i>prefix-list-name</i>	Name of prefix-list
priority	(Optional) RP priority used in Candidate-RP messages
<i>priority</i>	(Optional) RP priority value
interval	(Optional) Bootstrap message transmission interval
<i>interval</i>	(Optional) Interval in seconds
bidir	(Optional) Group range advertised in PIM bidirectional mode

Command Mode

- /exec/configure /exec/configure/vrf

ip pim sg-expiry-timer infinity

```
{ { ip pim [ sparse ] sg-expiry-timer { <expiry-time> | infinity } [ sg-list <route-map-name> | prefix-list <prefix-list-name> ] } | { no ip pim [ sparse ] sg-expiry-timer { <expiry-time> | infinity } [ sg-list <route-map-name> | prefix-list <prefix-list-name> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
sparse	(Optional) PIM ASM
sg-expiry-timer	Adjust expiry time for PIM ASM (S,G) routes
<i>expiry-time</i>	Expiry timer interval in seconds
infinity	Never expire (S,G) route due to data inactivity
sg-list	(Optional) Specifies route-map for (S,G)s to apply the expiry timer
<i>route-map-name</i>	(Optional) Route-map name
prefix-list	(Optional) Specifies prefix-list for (S,G)s to apply the expiry timer
<i>prefix-list-name</i>	(Optional) Name of prefix-list

Command Mode

- /exec/configure /exec/configure/vrf

ip pim sparse-mode

ip pim sparse-mode | no ip pim [sparse-mode]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
sparse-mode	Configures sparse-mode PIM on interface

Command Mode

- /exec/configure/if-igp

ip pim ssm

```
{ ip pim ssm { { range { <group> + | none } } | { route-map <route-map-name> } | { prefix-list
<prefix-list-name> } } | no ip pim ssm { { range { <group> + | none } } | { route-map <route-map-name> }
| { prefix-list <prefix-list-name> } } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
ssm	Source Specific Multicast (SSM) groups
range	Configure explicit group ranges
<i>group</i>	List of group range prefixes
route-map	Group range route-map policy for SSM range
<i>route-map-name</i>	Route-map name
prefix-list	Group range prefix-list policy for SSM range
<i>prefix-list-name</i>	Name of prefix-list
none	Remove all SSM group ranges

Command Mode

- /exec/configure /exec/configure/vrf

ip pim state-limit

```
{ { ip pim state-limit <max-states> [ reserved <route-map-name> <max-reserved> ] } | { no ip pim state-limit [ <max-states> [ reserved <route-map-name> <max-reserved> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
state-limit	Configures State limit
<i>max-states</i>	Maximum (*,G)/(S,G) entries allowed in this VRF
reserved	(Optional) Configures Reserved limit
<i>route-map-name</i>	(Optional) Route-map name
<i>max-reserved</i>	(Optional) Maximum reserved (*,G)/(S,G) entries allowed in this VRF

Command Mode

- /exec/configure /exec/configure/vrf

ip pim strict-rfc-compliant

{ { ip pim strict-rfc-compliant } | { no ip pim strict-rfc-compliant } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM interface configuration commands
strict-rfc-compliant	Dont process joins from unknown neighbors on this interface

Command Mode

- /exec/configure/if-igp

ip pim strict-rfc-compliant

{ { ip pim strict-rfc-compliant } | { no ip pim strict-rfc-compliant } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
pim	PIM global configuration commands
strict-rfc-compliant	Don't process joins from unknown neighbors

Command Mode

- /exec/configure /exec/configure/vrf

ip ping source-interface

[no] ip ping source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ping	Configure ping client
source-interface	Configure source interface feature for ping client
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip policy match router-address

[no] ip policy match router-address

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
policy	Configure PBR feature
match	Match values
router-address	Router's IP address

Command Mode

- /exec/configure

ip policy route-map

ip policy route-map <route-map-name> | no ip policy route-map [<route-map-name> | <route-map-name>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
policy	Configure PBR feature
route-map	Route-map for PBR
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	(Optional) Route-map name
<i>route-map-name</i>	(Optional) Known route-map name

Command Mode

- /exec/configure/if-igp

ip port-unreachable

[no] ip port-unreachable

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
port-unreachable	Enable sending ICMP port-unreachable

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config

ip port access-group

[no] ip port access-group <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
port	Port policy
access-group	Specify access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/system/acl

ip port access-group

[no] ip port access-group <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
port	Port policy
access-group	Specify access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/if-set-acl-l2

ip prefix-list description

{ ip prefix-list <ipv4-pfl-name> description <line> } | { no ip prefix-list <ipv4-pfl-name> description }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
prefix-list	Build a prefix list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Known prefix-list name
description	Description of the IP prefix list
<i>line</i>	IP prefix-list description string

Command Mode

- /exec/configure

ip prefix-list permit

```
{ ip prefix-list <ipv4-pfl-name> [ seq <seq> ] { permit | deny } <prefix> { [ eq <equal> ] | [ ge <greater> ] | [ le <lesser> ] } [ mask <mask> ] } | { no ip prefix-list { <ipv4-pfl-name> | <ipv4-pfl-name> } [ seq <seq> ] [ { permit | deny } <prefix> { [ eq <equal> ] | [ ge <greater> ] | [ le <lesser> ] } [ mask <mask> ] ] }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
prefix-list	Build a prefix list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Known prefix-list name
seq	(Optional) Sequence number of an entry
<i>seq</i>	(Optional) Sequence number
permit	Specify routes to forward
deny	Specify routes to reject
<i>prefix</i>	IP prefix network/length, e.g., 35.0.0.0/8
eq	(Optional) Exact prefix length to be matched
<i>equal</i>	(Optional) Exact prefix length
ge	(Optional) Minimum prefix length to be matched
<i>greater</i>	(Optional) Minimum prefix length
le	(Optional) Maximum prefix length to be matched
<i>lesser</i>	(Optional) Maximum prefix length
mask	(Optional) Explicit match mask
<i>mask</i>	(Optional) Mask to use with the prefix

Command Mode

- /exec/configure

ip proxy-arp

{ ip proxy-arp | no ip proxy-arp }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
proxy-arp	Configure proxy ARP

Command Mode

- /exec/configure/if-igp /exec/configure/if-vlan-common

ip radius source-interface

[no] ip radius source-interface | ip radius source-interface <interface>

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
radius	Radius server
source-interface	Source interface to be used to reach radius server
<i>interface</i>	Interface Description

Command Mode

- /exec/configure

ip redirects

ip redirects | no ip redirects

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
redirects	Send ICMP Redirect messages

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config

ip rip authentication key-chain

{ ip rip authentication key-chain <keychain> | no ip rip authentication key-chain [<keychain>] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
rip	RIP configuration commands
authentication	Authentication control
key-chain	Set authentication key-chain
<i>keychain</i>	Name of key-chain

Command Mode

- /exec/configure/if-igp

ip rip authentication mode text

{ ip rip authentication mode { text | md5 } | no ip rip authentication mode [{ text | md5 }] }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
rip	RIP configuration commands
authentication	RIP authentication control
mode	Set authentication mode
text	Clear text authentication
md5	Keyed message digest

Command Mode

- /exec/configure/if-igp

ip rip metric

```
{ ipv6 | ip } rip { metric-offset | offset-list } <metric> | no { ipv6 | ip } rip { metric-offset | offset-list } [ <metric> ]
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
ip	Configure IP features
rip	RIP configuration commands
metric-offset	RIP metric for interface
offset-list	RIP metric for interface
<i>metric</i>	RIP metric value

Command Mode

- /exec/configure/if-igp

ip rip passive-interface

[no] { ipv6 | ip } rip passive-interface

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
ip	Configure IP features
rip	RIP configuration commands
passive-interface	RIP passive interface

Command Mode

- /exec/configure/if-igp

ip rip poison-reverse

[no] { ipv6 | ip } rip poison-reverse

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
ip	Configure IP features
rip	RIP configuration commands
poison-reverse	RIP poison reverse (default split-horizon)

Command Mode

- /exec/configure/if-igp

ip rip route-filter route in

[no] { ipv6 | ip } rip route-filter { route-map <map> | prefix-list <list> } { in | out }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
ip	Configure IP features
rip	RIP configuration commands
route-filter	RIP route filtering
route-map	route-map policy to constrain route filtering
prefix-list	prefix-list policy to constrain route filtering
<i>map</i>	Route-map name
<i>list</i>	prefix-list name
in	inbound
out	outbound

Command Mode

- /exec/configure/if-igp

ip rip summary-address

[no] ip rip summary-address <ip-prefix> | no ipv6 rip summary-address <ipv6-prefix> | ipv6 rip summary-address <ipv6-prefix>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
rip	RIP configuration commands
summary-address	RIP summarization address
<i>ip-prefix</i>	Exact prefix

Command Mode

- /exec/configure/if-igp

ip route

```
[no] ip route { <ip-addr> <ip-mask> | <ip-prefix> } { <interface> | { { <pin-interface> <next-hop> } | { <next-hop> | <nh-prefix> } } | { <vlan-interface> } } [ vrf { <vrf-name> | <vrf-known-name> } ] [ track <object-num> ] [ name <rt-name> ] [ tag <tag-value> | <pref> ] +
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
route	Route information
<i>ip-addr</i>	IP prefix in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
<i>ip-prefix</i>	IP prefix and network mask length in format x.x.x.x/m
<i>pin-interface</i>	Pin interface
<i>next-hop</i>	IP next-hop address in format i.i.i.i
<i>nh-prefix</i>	IP next-hop prefix in format i.i.i.i/m
<i>interface</i>	Interface for interface static routes
<i>vlan-interface</i>	vlan interface
track	(Optional) Specify the Object to be Tracked
<i>object-num</i>	(Optional) Track Object Number
name	(Optional) Specify name of the next hop
<i>rt-name</i>	(Optional) Name of next hop
<i>pref</i>	(Optional) Route preference
tag	(Optional) Supply tag value with static route
<i>tag-value</i>	(Optional) 32-bit value for tag
vrf	(Optional) VRF for next-hop if different from this vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure /exec/configure/config-mgmt /exec/configure/vrf

ip route static bfd

[no] ip route static bfd <pin-interface> <next-hop>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
route	Route information
static	Static route based configuration
bfd	Enable bfd detection on static route
<i>pin-interface</i>	Interface on which bfd has to be enabled
<i>next-hop</i>	IP next-hop address in format i.i.i.i

Command Mode

- /exec/configure /exec/configure/config-mgmt /exec/configure/vrf

ip router eigrp

[no] { ip | ipv6 } router eigrp <eigrp-ptag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
router	Enable a routing process
eigrp	Configure an EIGRP routing process on interface
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip router isis

[no] ip router isis <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
router	Enable a routing process
isis	Intermediate System to Intermediate System (IS-IS)
<i>tag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip router ospf area

[no] ip router ospf <tag> area { <area-id-ip> | <area-id-int> } [secondaries none]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
router	Enable a routing process
ospf	OSPF configuration commands
<i>tag</i>	Process tag
area	Area associated with interface
<i>area-id-ip</i>	OSPF area ID in IP address format
<i>area-id-int</i>	OSPF area ID as a decimal format
secondaries	(Optional) Do not include secondary IP addresses
none	(Optional) Do not include secondary IP addresses

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip router ospf multi-area

[no] ip router ospf [<tag>] multi-area <area-id-ip>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
router	Enable a routing process
ospf	OSPF configuration commands
<i>tag</i>	(Optional) Process tag
multi-area	Multi area associated with interface
<i>area-id-ip</i>	Area Id as an integer or ip address

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ip router rip

[no] { ipv6 | ip } router rip <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
router	Enable a routing process
rip	Routing Information Protocol (RIP)
<i>tag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip routing download-on-convergence

[no] ip routing download-on-convergence

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	IP events
routing	Enable debugging for routing events
download-on-convergence	Download Routes/RNHs after Table Convergence

Command Mode

- /exec/configure

ip routing event-history

```
[no] ip routing event-history { add-route | cli | delete-route | detail | errors | general | ha | loop-detection |
modify-route | notifications | recursive-next-hop | summary | ufdm | ufdm-detail | ufdm-summary } size {
<size_in_text> | <size_in_bytes> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
event-history	Configure routing event log
add-route	Add route
cli	CLI
delete-route	Delete route
detail	Detail
errors	Errors
general	General
ha	HA
loop-detection	Loop detection
modify-route	Modify route
notifications	Notification
recursive-next-hop	Recursive next hop
summary	Summary
ufdm	UFDM
ufdm-detail	UFDM Detail
ufdm-summary	UFDM Summary
size	Size of buffer
<i>size_in_text</i>	Buffer size
<i>size_in_bytes</i>	Enter an integer value for the event history buffer

Command Mode

- /exec/configure

ip routing multicast event-history cli

[no] ip routing multicast event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
cli	CLI events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history mdt

[no] ip routing multicast event-history mdt { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mdt	MDT events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history mfdm-debug

[no] ip routing multicast event-history mfdm-debug { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mfdm-debug	MFDM debugs for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history mfdm-events

[no] ip routing multicast event-history mfdm-events { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure mfdm-stats event-history buffer
event-history	Configure event history buffers
mfdm-events	Non-periodic MFDM events in MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history mfdm-stats

[no] ip routing multicast event-history mfdm-stats { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mfdm-stats	MFDM-Stats events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history nbm

[no] ip routing multicast event-history nbm { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
nbm	NBM debugs for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history notify-clients

[no] ip routing multicast event-history notify-clients { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
notify-clients	Clients notify debugs for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history rib-summary

[no] ip routing multicast event-history rib-summary { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event-history buffers
rib-summary	RIB events for MRIB-summary
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history rib

```
[no] ip routing multicast event-history rib { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event-history buffers
rib	RIB events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history urib-debug

[no] ip routing multicast event-history urib-debug { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
urib-debug	URIB debugs for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast event-history vrf

```
[no] ip routing multicast event-history vrf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
vrf	VRF events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ip routing multicast file-debug

[no] { ip | ipv4 } routing multicast file-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv4	Configure IP features
routing	Routing information
multicast	Configure multicast
file-debug	Collect all debugs to a file

Command Mode

- /exec/configure

ip routing multicast holddown

{ ip | ipv4 } routing multicast holddown { <route-holddown-sec> | <none> } | no { ip | ipv4 } routing multicast holddown [<route-holddown-sec> | <none>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv4	Configure IP features
routing	Routing information
multicast	Configure multicast
holddown	Initial holddown period
<i>route-holddown-sec</i>	Delay in seconds
<i>none</i>	Disable holddown

Command Mode

- /exec/configure

ip routing multicast mfdm-buffer-route-count

{ ip | ipv4 } routing multicast mfdm-buffer-route-count { <size> } | no { ip | ipv4 } routing multicast mfdm-buffer-route-count [<size>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
ipv4	Configure IP features
routing	Routing information
multicast	Configure multicast
mfdm-buffer-route-count	mfdm buffer route size
<i>size</i>	size in numbers

Command Mode

- /exec/configure

ip routing multicast software-replicate

[no] ip routing multicast software-replicate [iif]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Routing information
multicast	Configure multicast
software-replicate	Enable software replication of PIM ASM leak packets
iif	(Optional) Enable software replication on incoming interface

Command Mode

- /exec/configure

ip routing multicast trace enable

[no] ip routing multicast trace enable

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
routing	Configure routing information
multicast	Configure multicast
trace	Bintrace related commands
enable	Enable bintrace

Command Mode

- /exec/configure

ip routing multicast trace entries

ip routing multicast trace entries <num-entries>

Syntax Description

ip	Configure IP features
routing	Configure routing information
multicast	Configure multicast
trace	Bintrace related commands
entries	Number of bintrace entries
<i>num-entries</i>	Update number of bintrace entries

Command Mode

- /exec/configure

ip routing multicast trace records

ip routing multicast trace records <num-rec>

Syntax Description

ip	Configure IP features
routing	Configure routing information
multicast	Configure multicast
trace	Bintrace related commands
records	Number of bintrace records per entry
<i>num-rec</i>	Update number of bintrace record per entry

Command Mode

- /exec/configure

ip secondary

ip { <ipaddress> | <ipprefix> } secondary | no ip { <ipaddress> | <ipprefix> } secondary

Syntax Description

no	Negate a command or set its defaults
ip	Enable HSRP IPv4 and set the virtual IP address
<i>ipaddress</i>	Virtual IP address
<i>ipprefix</i>	Virtual IP address and mask length
secondary	Make this IP address a secondary virtual IP address

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4

ip service-reflect destination to mask-len source

[no] ip service-reflect [<src-if>] destination <in-grp> to <out-grp> mask-len <g-mlen> source <in-out-src> [to <out-src> mask-len <s-mlen>] [sequence-number <seq-num>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
service-reflect	Service reflect config command
<i>src-if</i>	(Optional) Source Interface Name
destination	Translation information
<i>in-grp</i>	Incoming Group Address
to	
<i>out-grp</i>	Outgoing Group Address
mask-len	
<i>g-mlen</i>	Group Mask Length
source	
<i>in-out-src</i>	Source Address
to	(Optional)
<i>out-src</i>	(Optional) Outgoing Source Address
mask-len	(Optional)
<i>s-mlen</i>	(Optional) Source Mask Length
sequence-number	(Optional)
<i>seq-num</i>	(Optional) Sequence number of rule

Command Mode

- /exec/configure

ip service-reflect mode regular

```
[no] ip service-reflect mode { regular | fast-pass [ no-rewrite ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
service-reflect	Service Reflect config command
mode	Select one-pass or three-pass mode
regular	Regular mode
fast-pass	Fast Pass Mode
no-rewrite	(Optional) No Mac Rewrite

Command Mode

- /exec/configure

ip sla

[no] ip sla <index>

Syntax Description

no	(Optional)
ip	
sla	Service Level Agreement (SLA)
<i>index</i>	Entry Number

Command Mode

- /exec/configure

ip sla group schedule

```
{ no ip sla group schedule <group-id> | ip sla group schedule <group-id> { { add <operation-ids> | delete
<operation-ids> } | { <operation-ids> schedule-period <schedule-period-seconds> { [ ageout <ageout-seconds>
] [ frequency { <frequency-seconds> | range <random-frequency-range> } ] [ life { forever | <life-seconds>
} ] [ start-time { <hhmm> [ { January | February | March | April | May | June | July | August | September |
October | November | December } <day> | <day> [ January | February | March | April | May | June | July |
August | September | October | November | December ] ] | pending | now | after <hhmm> } ] } + } | reschedule
} }
```

Syntax Description

no	
add	delete
start-time	(Optional) January
October	(Optional) November
operation-ids	<schedule-period-seconds>
random-frequency-range	(Optional) <ageout-seconds>
ip	
sla	Service Level Agreement (SLA)
group	Group Configuration or Group Scheduling
schedule	Group scheduling
group-id	Group schedule entry number
delete	Delete probes from existing group
reschedule	Reschedule the group using previous config
operation-ids	Multiple probe ID's to be group scheduled
schedule-period	Group schedule period range
schedule-period-seconds	seconds
frequency	(Optional) Group operation frequency
range	(Optional) Group operation frequency-range for random scheduling
frequency-seconds	(Optional) Specify frequency in seconds
ageout	(Optional) How long to keep this Entry when inactive
ageout-seconds	(Optional) Ageout Seconds
life	(Optional) Length of time to execute in seconds

<i>life-seconds</i>	(Optional) Life seconds (default 3600)
forever	(Optional) continue running forever
after	(Optional) Start after a certain amount of time from now
<i>hhmm</i>	(Optional) Start time (hh:mm)
January	(Optional) Month of year
February	(Optional) Month of year
March	(Optional) Month of year
April	(Optional) Month of year
May	(Optional) Month of year
June	(Optional) Month of year
July	(Optional) Month of year
August	(Optional) Month of year
September	(Optional) Month of year
October	(Optional) Month of year
November	(Optional) Month of year
December	(Optional) Month of year
<i>day</i>	(Optional) Day of month
now	(Optional) Start now
pending	(Optional) Start pending

Command Mode

- /exec/configure

ip sla logging traps

[no] ip sla logging traps

Syntax Description

no	(Optional)
ip	
sla	Service Level Agreement (SLA)
logging	Enable Syslog
traps	Enable syslog traps

Command Mode

- /exec/configure

ip sla reaction-configuration react

```
[no] ip sla reaction-configuration <react-cfg-entry-num> react <monitored-element> | ip sla
reaction-configuration <react-cfg-entry-num> react <monitored-element> { [ action-type <action> ] [
threshold-value <rising-value> <falling-value> ] [ threshold-type { <neverImmed> | <consecutive> [
<consecutive-occurrences> ] | <xOfy> [ <x-value> <y-value> ] | <average> [ <n-attempts> ] } ] } +
```

Syntax Description

no	
<i>action-type</i>	(Optional) threshold-value
<i>falling-value</i>	(Optional) <neverImmed>
<i>consecutive-occurrences</i>	(Optional) <x-value>
ip	
sla	Service Level Agreement (SLA)
reaction-configuration	IP SLAs Reaction-Configuration
<i>react-cfg-entry-num</i>	Entry Number
react	Reaction variable to be configured
<i>monitored-element</i>	monitored element
<i>action</i>	(Optional)
threshold-value	(Optional) Threshold Value
<i>rising-value</i>	(Optional) Upper limit for Threshold
threshold-type	(Optional) Threshold Type
<i>neverImmed</i>	(Optional)
<i>consecutive</i>	(Optional)
<i>xOfy</i>	(Optional)
<i>average</i>	(Optional)
<i>x-value</i>	(Optional) X value
<i>y-value</i>	(Optional) Y value
<i>n-attempts</i>	(Optional) N Value

Command Mode

- /exec/configure

ip sla reaction-trigger

[no] ip sla reaction-trigger <entry-num> <target-entry>

Syntax Description

no	(Optional)
ip	
sla	Service Level Agreement (SLA)
reaction-trigger	IP SLAs Trigger Assignment
<i>entry-num</i>	Entry Number
<i>target-entry</i>	Target entry Number

Command Mode

- /exec/configure

ip sla reset

ip sla reset

Syntax Description

ip	
sla	Service Level Agreement (SLA)
reset	IP SLAs Reset

Command Mode

- /exec/configure

ip sla responder

```
[no] ip sla responder [ { tcp-connect [ ipaddress<tcp-ip> ] port <tcp-port> } | { udp-echo [ ipaddress <udp-ip> ] port <udp-port> } ]
```

Syntax Description

<i>tcp-connect</i>	(Optional) ipaddress
no	(Optional)
ip	
sla	
responder	Enable IP SLAs Responder
ipaddress	(Optional) Permanent address
port	(Optional) Permanent port
<i>tcp-port</i>	(Optional) Port Number
udp-echo	(Optional) Setup udp-echo responder
<i>udp-ip</i>	(Optional) IP Address or IP HostName
<i>udp-port</i>	(Optional) Port Number

Command Mode

- /exec/configure

ip sla responder twamp

[no] ip sla responder twamp

Syntax Description

no	(Optional)
ip	
sla	
responder	Enable IP SLAs Responder
twamp	Setup TWAMP responder

Command Mode

- /exec/configure

ip sla restart

ip sla restart <index>

Syntax Description

ip	
sla	Service Level Agreement (SLA)
restart	Restart An Active Entry
<i>index</i>	Entry Number

Command Mode

- /exec/configure

ip sla schedule

```
{ no ip sla schedule <index> | ip sla schedule <index> { [ life { <life-seconds> | forever } ] [ start-time { <hhmm> [ { January | February | March | April | May | June | July | August | September | October | November | December } <day> | <day> [ January | February | March | April | May | June | July | August | September | October | November | December ] ] | pending | now | { after <hhmm> } } ] [ ageout <ageout-seconds> ] [ recurring ] } + }
```

Syntax Description

no	
<i>life</i>	(Optional) forever
<i>August</i>	(Optional) September
<i>recurring</i>	(Optional) <life-seconds>
ip	
sla	Service Level Agreement (SLA)
schedule	Entry Scheduling
<i>index</i>	Entry Number
<i>life-seconds</i>	(Optional) Life seconds (default 3600)
forever	(Optional) continue running forever
start-time	(Optional) When to start this entry
<i>hhmm</i>	(Optional) Start time (hh:mm)
January	(Optional) Month of year
February	(Optional) Month of year
March	(Optional) Month of year
April	(Optional) Month of year
May	(Optional) Month of year
June	(Optional) Month of year
July	(Optional) Month of year
August	(Optional) Month of year
September	(Optional) Month of year
October	(Optional) Month of year
November	(Optional) Month of year

December	(Optional) Month of year
<i>day</i>	(Optional) Day of month
now	(Optional) Start now
after	(Optional) Start after a certain amount of time from now
pending	(Optional) Start pending
ageout	(Optional) How long to keep this Entry when inactive
<i>ageout-seconds</i>	(Optional) Ageout Seconds

Command Mode

- /exec/configure

ip sla server twamp

[no] ip sla server twamp

Syntax Description

no	(Optional)
ip	
sla	
server	IPSLA IPPM server configuration
twamp	IPSLA IPPM TWAMP server configuration

Command Mode

- /exec/configure

ip source-route

[no] ip source-route

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
source-route	IP source routing option

Command Mode

- /exec/configure

ip source binding vlan interface

[no] ip source binding <ipaddr1> <macaddr> vlan <vlanid> interface <interface1>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
source	IP source
binding	Static binding
<i>ipaddr1</i>	IP address
<i>macaddr</i>	MAC address
vlan	VLAN
<i>vlanid</i>	VLAN id
interface	interface
<i>interface1</i>	interface

Command Mode

- /exec/configure

ip source icmp-errors

[no] ip source <interface> icmp-errors

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
source	Configure source-address for applications
<i>interface</i>	Interface to pick source-address from
icmp-errors	ICMP unreachable/TTL-exceeded/param-prob messages

Command Mode

- /exec/configure /exec/configure/vrf

ip split-horizon eigrp

[no] { ip | ipv6 } split-horizon eigrp <eigrp-ptag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
split-horizon	Configures IP-EIGRP split-horizon on interface
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ip ssh source-interface

[no] ip ssh source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ssh	Configure ssh
source-interface	Configure source interface feature for domain-lookup
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip summary-address eigrp ipv6 summary-address eigrp

```
{ [ no ] ip summary-address eigrp <eigrp-ptag> { { <address> <mask> } | { <prefix> } } [ <distance> ] [
leak-map <leak-map> ] | [ no ] ipv6 summary-address eigrp <eigrp-ptag> <ipv6-prefix> [ <distance> ] [
leak-map <leak-map> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
ipv6	Configure IPv6 features
summary-address	Configures IP-EIGRP summary address on interface
eigrp	EIGRP interface configuration commands
<i>eigrp-ptag</i>	Process tag
<i>address</i>	IP address
<i>mask</i>	IP network mask
<i>prefix</i>	IP prefix in slash format
<i>distance</i>	(Optional) Administrative distance
leak-map	(Optional) Allow dynamic prefixes based on the leak-map
<i>leak-map</i>	(Optional) leak-map name
<i>eigrp-ptag</i>	

Command Mode

- /exec/configure/if-igp

ip tacacs source-interface

[no] ip tacacs source-interface | ip tacacs source-interface <interface>

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
tacacs	Tacacs server
source-interface	Source interface to be used to reach tacacs server
<i>interface</i>	Interface Description

Command Mode

- /exec/configure

ip tcp mss

{ { no ip tcp mss } | { ip tcp mss <bytes> } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
tcp	Global TCP parameters
mss	Maximum segment size for TCP connections in bytes
<i>bytes</i>	Maximum segment size

Command Mode

- /exec/configure /exec/configure/config-mgmt

ip tcp path-mtu-discovery

{ { ip tcp path-mtu-discovery } | { no ip tcp path-mtu-discovery } }

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
tcp	Global TCP parameters
path-mtu-discovery	Enable path-MTU discovery on TCP

Command Mode

- /exec/configure /exec/configure/config-mgmt

ip tcp synwait-time

```
{ { no ip tcp synwait-time } | { ip tcp synwait-time <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
tcp	Global TCP parameters
synwait-time	Set time to wait on new TCP connections
<i>time</i>	Wait time

Command Mode

- /exec/configure /exec/configure/config-mgmt

ip telnet source-interface

[no] ip telnet source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
telnet	Configure telnet
source-interface	Configure source interface feature for domain-lookup
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip tftp source-interface

[no] ip tftp source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
tftp	Configure TFTP client
source-interface	Configure source interface feature for TFTP client
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip traceroute source-interface

[no] ip traceroute source-interface <ifnum> [vrf { <vrf-name> | <vrf-known-name> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
traceroute	Configure traceroute client
source-interface	Configure source interface feature for traceroute
<i>ifnum</i>	Source interface
vrf	(Optional) Configure VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure

ip ttl

[no] ip ttl <ttl_value>

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Set ERSPAN IP options
ttl	Set the IP time-to-live value
<i>ttl_value</i>	

Command Mode

- /exec/configure/config-monitor-erspan-src

ip udp relay addrgroup

```
{ ip udp relay addrgroup <obj-grp-name> | no ip udp relay addrgroup }
```

Syntax Description

ip	Configure IP features
no	Negate a command or set its defaults
udp	Enable/disable UDP forwarding
relay	UDP relay agent parameters
addrgroup	UDP Relay IP Address group
<i>obj-grp-name</i>	Object grp Name

Command Mode

- /exec/configure/if-igp

ip udp relay subnet-broadcast

[no] ip udp relay subnet-broadcast

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
udp	Enable/disable UDP forwarding
relay	UDP relay agent parameters
subnet-broadcast	Enable/disable UDP forwarding for subnet-broadcast

Command Mode

- /exec/configure/if-igp

ip unnumbered

ip unnumbered <interface> | no ip unnumbered [<interface>]

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
unnumbered	Configure interface as unnumbered
<i>interface</i>	Interface with IP address

Command Mode

- /exec/configure/ppm-ethernet-switch /exec/configure/if-p2p /exec/configure/if-gre-tunnel /exec/configure/if-any-tunnel /exec/configure/if-port-channel-sub /exec/configure/if-vlan

ip unreachable

[no] ip unreachable

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
unreachables	Enable sending ICMP unreachable (other than port-unreachable)

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config

ip verify source dhcp-snooping-vlan

[no] ip verify source dhcp-snooping-vlan

Syntax Description

no	(Optional) Negate a command or set its defaults
ip	Configure IP features
verify	Configure Unicast Reverse Path Forwarding or IP Source Guard
source	IP Source Guard related commands
dhcp-snooping-vlan	Vlans on which snooping is enabled

Command Mode

- /exec/configure/if-switching

ip verify unicast source reachable-via rx

```
[no] ip verify unicast source reachable-via [ { rx | any [ allow-default ] } [ policy { <policy-name> | <acl_pol_name> } ] ] | ip verify unicast source reachable-via { rx | any [ allow-default ] } [ policy { <policy-name> | <acl_pol_name> } ]
```

Syntax Description

no	Negate a command or set its defaults
ip	Configure IP features
verify	Configure Unicast Reverse Path Forwarding or IP Source Guard
unicast	Unicast Reverse Path Forwarding
source	Validation of source address
reachable-via	Specify reachability check to apply to the source address
rx	(Optional) Source is reachable via interface on which packet was received
any	(Optional) Source is reachable via any interface
allow-default	(Optional) Loose Default Route Unicast Reverse Path Forwarding
policy	(Optional) Unicast Reverse Path Forwarding fail policy
<i>policy-name</i>	(Optional) An uRPF fail policy name
<i>acl_pol_name</i>	(Optional) An existing access-rules policy

Command Mode

- /exec/configure/if-igp

ipv6

```
{ [ <seqno> ] | no } <permitdeny> { ipv6 | <proto> | <ipv6_other_proto> } { <src_any> | { <src_addr>
<src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } {
<dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp
<dst_addrgrp_name> } } [ { { dscp { <dscp_num> | <dscp_str> } } } ] [ { flow-label <flow_num> } ] [ fragments
] [ log ] [ time-range <time_range_name> ] [ packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } ] [ { udf { <udf_name> <udf_val> <udf_mask> } + } ] + [ vlan <vlanid> | ingress_intf { <intfid>
| <intfname> } | vlan_priority <vlanpriorityid> ] + [ { udf { <udf_name> <udf_val> <udf_mask> } + } ] [
capture session <session-id> ] [ { <actionv6> <actionidv6> } ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
ipv6	Any IPV6 protocol
<i>proto</i>	A protocol number
<i>ipv6_other_proto</i>	ipv6_other_proto
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
udf	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>src_any</i>	Any
src_key_host	A single source host
src_key_addrgrp	Source address group
<i>src_addrgrp_name</i>	Address group name

<i>dst_any</i>	Any
<i>dst_key_host</i>	A single destination host
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>flow-label</i>	(Optional) Flow label
<i>flow_num</i>	(Optional) Flow label value
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>actionv6</i>	(Optional) ActionV6
<i>actionidv6</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipv6acl

ipv6 access-class

[no] ipv6 access-class <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
access-class	Specify IPv6 access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/line

ipv6 access-list

[no] ipv6 access-list <name> [client <clienttype> <clientID>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
access-list	Configure access list
<i>name</i>	List name
client	(Optional) set client type
<i>clienttype</i>	(Optional) CLI/ONEP
<i>clientID</i>	(Optional) client appID

Command Mode

- /exec/configure

ipv6 access-list match-local-traffic

[no] ipv6 access-list match-local-traffic | ipv6 access-list match-local-traffic

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
access-list	Configure access list
match-local-traffic	Enable access-list matching for locally generated traffic

Command Mode

- /exec/configure

ipv6 address

```
[no] ipv6 address [ { autoconfig [ default ] | [ <ipv6-prefix> [ eui64 ] [ route-preference <pref> ] [ tag <tag> ] [ anycast ] } ] | ipv6 address { autoconfig [ default ] | [ <ipv6-prefix> [ eui64 ] [ route-preference <pref> ] [ tag <tag> ] [ anycast ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
address	Configure IPv6 address on interface
autoconfig	(Optional) Configure IPv6 Stateless address autoconfig
default	(Optional) For SLAAC, adds default route and the nh would be fetched from RA source address
eui64	(Optional) Configure Extended Unique Identifier for the low-order 64 bits
anycast	(Optional) Configure IPv6 anycast address on interface
route-preference	(Optional) U6RIB route preference for local/direct routes
<i>pref</i>	(Optional) Local/direct route preference
tag	(Optional) U6RIB route tag value for local/direct routes
<i>tag</i>	(Optional) Local/direct tag value

Command Mode

- /exec/configure/if-igp /exec/configure/if-any-tunnel /exec/configure/if-vsan /exec/configure/if-mgmt-config

ipv6 address dhcp

[no] ipv6 address dhcp

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
address	Configure IPv6 address on interface
dhcp	Configure IPv6 address from a dhcp server

Command Mode

- /exec/configure/if-vlan /exec/configure/if-ethernet /exec/configure/if-mgmt-config /exec/configure/if-ethernet-all /exec/configure/if-sub

ipv6 address use-link-local-only

[no] ipv6 address use-link-local-only | ipv6 address use-link-local-only

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
address	Configure IPv6 address on interface
use-link-local-only	Enable IPv6 on interface using only a single link-local address

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-gre-tunnel /exec/configure/if-6to4-tunnel /exec/configure/if-vsan

ipv6 adjacency-stale-timer

```
{ { ipv6 [ icmp ] adjacency-stale-timer <stale-time> } | { no ipv6 [ icmp ] adjacency-stale-timer [ <stale-time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) Configure icmp parameters
adjacency-stale-timer	When probing for an adjacency begins
<i>stale-time</i>	Seconds after adjacency uptime

Command Mode

- /exec/configure

ipv6 adjacency route distance

{ ipv6 adjacency route distance <pref> } | { no ipv6 adjacency route distance }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
adjacency	Configure Adjmgr
route	route
distance	admin-distance
<i>pref</i>	preference

Command Mode

- /exec/configure

ipv6 amt gateway

[no] ipv6 amt gateway

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
amt	AMT global configuration commands
gateway	Configures IPv6 AMT gateway functionality

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 amt relay

[no] ipv6 amt relay

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
amt	AMT global configuration commands
relay	Configures IPv6 AMT relay functionality

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 destination

{ ipv6 { destination | source } <addr> } | { no ipv6 { destination | source } }

Syntax Description

no	Negate a command or set its defaults
ipv6	specify flow ipv6 address
source	specify flow source ipv6 address
destination	specify flow destination ipv6 address

Command Mode

- /exec/configure/configngoamprofileflow

ipv6 dhcp-ldra

[no] ipv6 dhcp-ldra

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp-ldra	Enable/disable DHCPV6 LDRA

Command Mode

- /exec/configure/

ipv6 dhcp-ldra attach-policy

[no] ipv6 dhcp-ldra attach-policy { client-facing-trusted | client-facing-untrusted | client-facing-disable | server-facing }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp-ldra	DHCPv6 LDRA
attach-policy	Apply a policy for DHCPV6 LDRA
client-facing-trusted	Client facing trusted port
client-facing-untrusted	Client facing untrusted port
client-facing-disable	Disable LDRA on port
server-facing	Server facing port

Command Mode

- /exec/configure/if-switching

ipv6 dhcp-ldra attach-policy vlan client

[no] ipv6 dhcp-ldra attach-policy vlan <vlan-id10> { client-facing-trusted | client-facing-untrusted }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp-ldra	DHCPv6 LDRA
attach-policy	Apply a policy for DHCPV6 LDRA
vlan	DHCP LDRA vlan
<i>vlan-id10</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19
client-facing-trusted	Client facing trusted
client-facing-untrusted	Client facing untrusted

Command Mode

- /exec/configure

ipv6 dhcp guard

[no] ipv6 dhcp guard [attach-policy <policy_name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>policy_name</i>	(Optional) policy name for feature DHCP Guard

Command Mode

- /exec/configure/if-switching

ipv6 dhcp guard

[no] ipv6 dhcp guard [attach-policy <policy_name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>policy_name</i>	(Optional) policy name for feature DHCP Guard

Command Mode

- /exec/configure/vlan-config

ipv6 dhcp guard policy

[no] ipv6 dhcp guard policy <policy_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>policy_name</i>	Name of the dhcp guard policy

Command Mode

- /exec/configure

ipv6 dhcp relay

[no] ipv6 dhcp relay

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	Configure DHCPv6 relay agent

Command Mode

- /exec/configure

ipv6 dhcp relay address

[no] ipv6 dhcp relay address [<ip-addr-val> [use-vrf <vrf-name>] [interface <interface-name>]] | no ipv6 dhcp relay address [<ip-addr-val> [interface <interface-name>] [use-vrf <vrf-name>]]

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	Configure DHCPv6 relay agent
address	Configure DHCPv6 server relay address
use-vrf	(Optional) server address VRF membership
<i>vrf-name</i>	(Optional) VRF name
interface	(Optional) Destination interface for the relay address
<i>interface-name</i>	(Optional) Destination interface

Command Mode

- /exec/configure/if-igp

ipv6 dhcp relay address ipv6 dhcp relay address

ipv6 dhcp relay address <ip-addr-val> [use-vrf <vrf-name>] [interface <interface-name>] | ipv6 dhcp relay address <ip-addr-val> [interface <interface-name>] [use-vrf <vrf-name>]

Syntax Description

ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	Configure DHCPv6 relay agent
address	Configure DHCPv6 server relay address
use-vrf	(Optional) server address VRF membership
<i>vrf-name</i>	(Optional) VRF name
interface	(Optional) Destination interface for the relay address
<i>interface-name</i>	(Optional) Destination interface

Command Mode

- /exec/configure/if-igmp /exec/configure/ppm-ethernet-switch /exec/configure/ppm-port-channel-switch

ipv6 dhcp relay option type cisco

[no] ipv6 dhcp relay option type cisco

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	DHCPv6 relay agent parameters
option	Relay agent option
type	Relay agent option type
cisco	Use Cisco proprietary options

Command Mode

- /exec/configure

ipv6 dhcp relay option vpn

[no] ipv6 dhcp relay option vpn

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	DHCPv6 relay agent parameters
option	Insert DHCPv6 relay information in Relay forward
vpn	Enable DHCPv6 relay support across VRFs

Command Mode

- /exec/configure

ipv6 dhcp relay source-interface

ipv6 dhcp relay source-interface <interface-name>

Syntax Description

ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	Configure DHCPv6 relay agent
source-interface	Configure source interface for DHCPv6 relay
<i>interface-name</i>	Source interface

Command Mode

- /exec/configure /exec/configure/if-igp

ipv6 dhcp relay source-interface

[no] ipv6 dhcp relay source-interface

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
dhcp	Configure DHCPv6 relay
relay	Configure DHCPv6 relay agent
source-interface	Configure source interface for DHCPv6 relay

Command Mode

- /exec/configure /exec/configure/if-igp

ipv6 flow monitor input

[no] ipv6 flow monitor <monitorname> input

Syntax Description

ipv6	Configure IPv6 features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/if-routing /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

ipv6 flow monitor input

[no] ipv6 flow monitor <monitorname> input

Syntax Description

ipv6	Configure IPv6 features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/vlan-config

ipv6 flow monitor input

[no] ipv6 flow monitor <monitorname> input

Syntax Description

ipv6	Configure IPv6 features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/if-vlan-common

ipv6 forward

ipv6 forward | no ipv6 forward

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
forward	Enable ipv6 forwarding on interface

Command Mode

- /exec/configure/if-vlan /exec/configure/if-vlan-range

ipv6 host

[no] ipv6 host <s0> [<ipv6_0>] | ipv6 host <s0> <ipv6_0>

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
host	Add an entry to the ip hostname table
<i>s0</i>	Name of Host

Command Mode

- /exec/configure

ipv6 link-local

[no] ipv6 link-local [<ipv6-addr>] | ipv6 link-local <ipv6-addr>

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
link-local	Change format of link-local address

Command Mode

- /exec/configure/if-vlan /exec/configure/if-mgmt-config /exec/configure/if-gre-tunnel /exec/configure/if-6to4-tunnel /exec/configure/if-igp /exec/configure/if-vsan

ipv6 local policy route-map

ipv6 local policy route-map <route-map-name> | no ipv6 local policy route-map [<route-map-name> | <route-map-name>]

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
local	Configure local PBR feature
policy	Configure PBR feature
route-map	Route-map for PBR
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	(Optional) Route-map name
<i>route-map-name</i>	(Optional) Known route-map name

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 mld group-timeout

```
{ { no ipv6 [ icmp ] mld group-timeout [ <time> ] } | { ipv6 [ icmp ] mld group-timeout <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
group-timeout	Configures group membership timeout
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld immediate-leave

[no] ipv6 [icmp] mld immediate-leave

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
immediate-leave	Enable/Disable immediate leave

Command Mode

- /exec/configure/if-igp

ipv6 mld join-group

```
[no] ipv6 [ icmp ] mld join-group { { <group> [ source <source> ] } | { route-map <route-map-name> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
join-group	Configures local group membership for router
source	(Optional) Configures source address for MLDv2 (S,G) channel
route-map	Join group policy
<i>route-map-name</i>	route-map name

Command Mode

- /exec/configure/if-igp

ipv6 mld last-member-query-count

```
{ { no ipv6 [ icmp ] mld last-member-query-count [ <count> ] } | { ipv6 [ icmp ] mld last-member-query-count <count> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
last-member-query-count	Configures number of group-specific Queries sent
<i>count</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ipv6 mld last-member-query-response-time

```
{ { no ipv6 [ icmp ] mld last-member-query-response-time [ <interval> ] } | { ipv6 [ icmp ] mld  
last-member-query-response-time <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
last-member-query-response-time	Configures last member query response time
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld querier

```
{ { no ipv6 [ icmp ] mld { querier-timeout | query-timeout } [ <time> ] } | { ipv6 [ icmp ] mld { querier-timeout | query-timeout } <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
query-timeout	Configures querier timeout for MLDv1
querier-timeout	Configures querier timeout for MLDv1
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld query-interval

```
{ { no ipv6 [ icmp ] mld query-interval [ <interval> ] } | { ipv6 [ icmp ] mld query-interval <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
query-interval	Configures interval between Query transmission
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld query-max-response-time

```
{ { no ipv6 [ icmp ] mld query-max-response-time [ <time> ] } | { ipv6 [ icmp ] mld query-max-response-time <time> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
query-max-response-time	Configures MRT for query messages
<i>time</i>	(Optional) Time in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld report-link-local-groups

[no] ipv6 [icmp] mld report-link-local-groups

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
report-link-local-groups	Send Reports for groups in ff02::/16

Command Mode

- /exec/configure/if-igp

ipv6 mld report

```
{ { ipv6 [ icmp ] mld { report-policy | access-group } <route-map-name> } | { no ipv6 [ icmp ] mld {
report-policy | access-group } [ <route-map-name> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
report-policy	ICMPv6 MLD Report Policy
access-group	ICMPv6 MLD access-group
<i>route-map-name</i>	Route-map name

Command Mode

- /exec/configure/if-igp

ipv6 mld robustness-variable

```
{ { no ipv6 [ icmp ] mld robustness-variable [ <value> ] } | { ipv6 [ icmp ] mld robustness-variable <value> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
robustness-variable	Configures RFC defined Robustness Variable
<i>value</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ipv6 mld ssm-translate

[no] ipv6 [icmp] mld ssm-translate <group> <source>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) Configure icmp parameters
mld	Multicast Listener Discovery commands
ssm-translate	Translate MLDv1 reports to (S,G) route entries

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 mld startup-query-count

```
{ { no ipv6 [ icmp ] mld startup-query-count [ <count> ] } | { ipv6 [ icmp ] mld startup-query-count <count> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
startup-query-count	Configures number of queries sent at startup
<i>count</i>	(Optional) Count value

Command Mode

- /exec/configure/if-igp

ipv6 mld startup-query-interval

```
{ { no ipv6 [ icmp ] mld startup-query-interval [ <interval> ] } | { ipv6 [ icmp ] mld startup-query-interval <interval> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
startup-query-interval	Configures query interval at startup
<i>interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ipv6 mld state-limit

```
{ { ipv6 [ icmp ] mld state-limit <max-states> [ reserved <route-map-name> <max-reserved> ] } | { no ipv6 [ icmp ] mld state-limit [ <max-states> [ reserved <route-map-name> <max-reserved> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
state-limit	Configures State limit
<i>max-states</i>	Maximum states allowed
reserved	(Optional) Reserve the states using route-map
<i>route-map-name</i>	(Optional) Route-map name
<i>max-reserved</i>	(Optional) Maximum (*,G)/(S,G) entires allowed on the interface

Command Mode

- /exec/configure/if-igp

ipv6 mld static

```
[no] ipv6 [ icmp ] mld { static-group | static-oif } { { <group> [ source <source> ] } | { route-map
<route-map-name> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
mld	Multicast Listener Discovery commands
static-group	Configures static oif for a multicast forwarding entry
static-oif	Configures static oif for a multicast forwarding entry
source	(Optional) Configures source address for MLDv2 (S,G) Channel
route-map	Static group policy
<i>route-map-name</i>	route-map name

Command Mode

- /exec/configure/if-igp

ipv6 mld version

```
{ { no ipv6 mld version [ <version> ] } | { ipv6 mld version <version> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
mld	Multicast Listener Discovery commands
version	Configures MLD version number for interface
<i>version</i>	(Optional) Version number value

Command Mode

- /exec/configure/if-igp

ipv6 nd cache limit

```
{ { ipv6 nd cache limit <max> } | { no ipv6 nd cache limit } } [ syslog <rate> ]
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
cache	ND cache parameters
limit	Limit size of ND adjacencies cache
<i>max</i>	Max no of ND adjacencies configured
syslog	(Optional) Syslog messages
<i>rate</i>	(Optional) Syslogs per second

Command Mode

- /exec/configure

ipv6 nd dad attempts

ipv6 nd dad attempts <attempt> | no ipv6 nd dad attempts

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
dad	Duplicate Address Detection
attempts	Set IPv6 Duplicate Address Detection Transmits
<i>attempt</i>	Number of attempts

Command Mode

- /exec/configure/if-igp

ipv6 nd dadns-discover

{ ipv6 nd dadns-discover <dadns_interval> } | { no ipv6 nd dadns-discover }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
dadns-discover	Discover host from DADNS
<i>dadns_interval</i>	Interval in milliseconds

Command Mode

- /exec/configure/if-igp

ipv6 nd hop-limit

```
{ { ipv6 nd hop-limit <hop-limit> } | { no ipv6 nd hop-limit [ <hop-limit> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
hop-limit	Sent in RA messages, tells hosts what hop-limit to use when originating IPv6 packets
<i>hop-limit</i>	Hop limit in IPv6 header

Command Mode

- /exec/configure/if-igp

ipv6 nd mac-extract

[no] ipv6 nd mac-extract [exclude nud-phase]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
mac-extract	Extract next hop MAC address embedded in IPV6 address
exclude	(Optional) Exclude
nud-phase	(Optional) during NUD phase

Command Mode

- /exec/configure/if-igp

ipv6 nd managed-config-flag

[no] ipv6 nd managed-config-flag

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
managed-config-flag	Sent in RA messages, tells hosts to use stateful address auto-configuration to obtain address information

Command Mode

- /exec/configure/if-igp

ipv6 nd mtu

```
{ { ipv6 nd mtu <mtu> } | { no ipv6 nd mtu [ <mtu> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
mtu	Sent in RA messages, tells hosts what MTU to use on this link
<i>mtu</i>	MTU in bytes

Command Mode

- /exec/configure/if-igp

ipv6 nd ns-interval

```
{ { ipv6 nd ns-interval <interval> [ <retry-count> ] } | { no ipv6 nd ns-interval [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ns-interval	Retransmission interval between sending Neighbor-Solicitation messages
<i>interval</i>	Interval in milliseconds
<i>retry-count</i>	(Optional) NS Retry count

Command Mode

- /exec/configure/if-igp

ipv6 nd off-list timeout

{ ipv6 nd off-list timeout <time> } | { no ipv6 nd off-list timeout }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	Display Neighbor Discovery interface information
off-list	off-list
timeout	Expire time
<i>time</i>	Expire time value in seconds

Command Mode

- /exec/configure

ipv6 nd other-config-flag

[no] ipv6 nd other-config-flag

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
other-config-flag	Sent in RA messages, tells hosts to use stateful auto-configuration to obtain non-address related information

Command Mode

- /exec/configure/if-igp

ipv6 nd prefix

```
{ { ipv6 nd prefix <prefix> [ { <val-life> | infinite } { <perf-life> | infinite } [ [ no-autoconfig ] [ no-onlink ] [ no-rtr-address ] [ off-link ] ] | no-advertise ] } | { no ipv6 nd prefix <prefix> } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
prefix	IPv6 Prefix to advertise in RA
<i>val-life</i>	(Optional) Valid Lifetime (secs)
infinite	(Optional) Infinite Valid Lifetime
no-advertise	(Optional) Do not advertise prefix
<i>perf-life</i>	(Optional) Preferred Lifetime (secs)
infinite	(Optional) Infinite Preferred Lifetime
no-autoconfig	(Optional) Do not use prefix for autoconfiguration
no-onlink	(Optional) Do not use prefix for onlink determination
no-rtr-address	(Optional) Do not send full router address in prefix advert
off-link	(Optional) Prefix is offlink

Command Mode

- /exec/configure/if-igp

ipv6 nd prefix default

```
{ { ipv6 nd prefix default [ { <val-life> | infinite } { <perf-life> | infinite } [ [ no-autoconfig ] [ no-onlink ] [ no-rtr-address ] [ off-link ] ] ] no-advertise } } | { no ipv6 nd prefix default } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
prefix	IPv6 Prefix to advertise in RA
default	Specify prefix default parameters
<i>val-life</i>	(Optional) Valid Lifetime (secs)
infinite	(Optional) Infinite Valid Lifetime
no-advertise	(Optional) Do not advertise prefix
<i>perf-life</i>	(Optional) Preferred Lifetime (secs)
infinite	(Optional) Infinite Preferred Lifetime
no-autoconfig	(Optional) Do not use prefix for autoconfiguration
no-onlink	(Optional) Do not use prefix for onlink determination
no-rtr-address	(Optional) Do not send full router address in prefix advert
off-link	(Optional) Prefix is offlink

Command Mode

- /exec/configure/if-igp

ipv6 nd ra-interval

```
ipv6 nd ra-interval <interval> [ min <min-interval> ] | no ipv6 nd ra-interval [ <interval> ] [ min <min-interval> ]
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra-interval	Interval between sending Router-Advertisement messages
<i>interval</i>	Interval in seconds
min	(Optional) Minimum interval between sending RA messages
<i>min-interval</i>	(Optional) Interval in seconds

Command Mode

- /exec/configure/if-igp

ipv6 nd ra-lifetime

```
{ { ipv6 nd ra-lifetime <lifetime> } | { no ipv6 nd ra-lifetime [ <lifetime> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra-lifetime	Sent in RA messages, Router Lifetime of a default router, 0 means this router will not be the default router
<i>lifetime</i>	Lifetime in seconds

Command Mode

- /exec/configure/if-igp

ipv6 nd ra dns search-list sequence

[no] ipv6 nd ra dns search-list <dnssl> [{ <dnssl_life> | infinite }] sequence <seqno>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra	Router Advertisement
dns	Domain Name System
search-list	DNS Search List
<i>dnssl</i>	Configure DNS Search List to advertise in RA
<i>dnssl_life</i>	(Optional) Configure IPv6 DNS Search list life time
infinite	(Optional) Configure IPv6 DNS Search list life time with infinite
sequence	Sequence of Search List
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/if-igp

ipv6 nd ra dns search-list suppress

[no] ipv6 nd ra dns search-list suppress

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra	Router Advertisement
dns	Domain Name System
search-list	DNS Search List
suppress	Disable sending DNSSL in Router-Advertisement messages

Command Mode

- /exec/configure/if-igp

ipv6 nd ra dns server sequence

[no] ipv6 nd ra dns server <ipv6_addr> [{ <rdnss_life> | infinite }] sequence <seqno>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra	Router Advertisement
dns	Domain Name System
server	Domain Name System Server
<i>rdnss_life</i>	(Optional) Configure IPv6 DNS Server life time
infinite	(Optional) Configure IPv6 DNS Server life time with infinite
sequence	Sequence of Server
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/if-igp

ipv6 nd ra dns server suppress

[no] ipv6 nd ra dns server suppress

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra	Router Advertisement
dns	Domain Name System
server	Domain Name System Server
suppress	Disable sending RDNSS in Router-Advertisement messages

Command Mode

- /exec/configure/if-igp

ipv6 nd ra route suppress

[no] ipv6 nd ra route suppress

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
ra	Router Advertisement
route	Route Information Option in RFC 4191
suppress	Disable sending Route Information Options in RA messages

Command Mode

- /exec/configure/if-igp

ipv6 nd rguard

[no] ipv6 nd rguard

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	Configure IPv6 ND
rguard	Configure RA guard

Command Mode

- /exec/configure/if-switching

ipv6 nd raguard

[no] ipv6 nd raguard [attach-policy <policy_name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>policy_name</i>	(Optional) policy name for ipv6 raguard

Command Mode

- /exec/configure/vlan-config

ipv6 nd raguard attach-policy

[no] ipv6 nd raguard attach-policy <policy_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>policy_name</i>	policy name for feature RA guard

Command Mode

- /exec/configure/if-switching

ipv6 nd raguard policy

[no] ipv6 nd raguard policy <policy_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>policy_name</i>	Name of the raguard policy

Command Mode

- /exec/configure

ipv6 nd reachable-time

```
{ { ipv6 nd reachable-time <time> } | { no ipv6 nd reachable-time [ <time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
reachable-time	Sent in RA messages, advertised time when a node considers a neighbor up after receiving a reachability confirmation
<i>time</i>	Time in milliseconds

Command Mode

- /exec/configure/if-igp

ipv6 nd retrans-timer

```
{ { ipv6 nd retrans-timer <time> } | { no ipv6 nd retrans-timer [ <time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
retrans-timer	Sent in RA messages, advertised time between NS messages
<i>time</i>	Time in milliseconds

Command Mode

- /exec/configure/if-igp

ipv6 nd route route-preference High Low Medium infinite

```
{ { ipv6 nd route <prefix> route-preference { High | Low | Medium } { <lifetime> | infinite } [ {
verify-reachability } ] } | { no ipv6 nd route { <prefix> | all } route-preference } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
route	Route Information Option in RFC 4191
route-preference	Route preference value
High	High router preference
Low	Low router preference
Medium	Medium router preference
<i>lifetime</i>	Lifetime (secs)
infinite	Infinite lifetime of prefix
verify-reachability	(Optional) Verify if route is present in Route table
all	Remove all the Router Preference prefixes

Command Mode

- /exec/configure/if-igp

ipv6 nd router-preference High Low Medium

```
{ { ipv6 nd router-preference { High | Low | Medium } } | { no ipv6 nd router-preference } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
router-preference	Set default router preference value
High	High default router preference
Low	Low default router preference
Medium	Medium default router preference

Command Mode

- /exec/configure/if-igp

ipv6 nd solicit-na accept

```
{ ipv6 nd solicit-na { { accept [ no-probe | <interval> ] | [ no-accept ] } | { accept1 [ no-probe1 | <interval1> ] | [ no-accept1 ] } } } | { no ipv6 nd solicit-na }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
solicit-na	Solicited Neighbor Advertisemen
accept	Accept Solicit NA without incomplete entry
no-probe	(Optional) Do not probe, create a Reachable Entry
<i>interval</i>	(Optional) Probe Interval in Seconds
no-accept	(Optional) Do not accept Solicit NA without incomplete entry
accept1	Accept Solicit NA without incomplete entry
no-probe1	(Optional) Do not probe, create a Reachable Entry
<i>interval1</i>	(Optional) Probe Interval in Seconds
no-accept1	(Optional) Do not accept Solicit NA without incomplete entry

Command Mode

- /exec/configure

ipv6 nd suppress-ra

[no] ipv6 nd suppress-ra [mtu]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	ICMPv6 Neighbor Discovery commands
suppress-ra	Disable sending Router-Advertisement messages
mtu	(Optional) Disable sending MTU in Router-Advertisement messages

Command Mode

- /exec/configure/if-igp

ipv6 nd synchronize

ipv6 nd synchronize [pull | push]

Syntax Description

ipv6	Configure IPv6 features
nd	Display Neighbor Discovery interface information
synchronize	CFS synchronize
pull	(Optional) Initiate CFS pull request
push	(Optional) Initiate CFS push message

Command Mode

- /exec

ipv6 neighbor

[no] ipv6 neighbor <ipv6-addr> [<mac-addr>] | ipv6 neighbor <ipv6-addr> <mac-addr>

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
neighbor	Configure IPv6 address to layer-2 address mapping
<i>mac-addr</i>	(Optional) Layer-2 MAC address

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config /exec/configure/if-vlan-common

ipv6 neighbor allow-static-neighbor-outside-subnet

[no] ipv6 neighbor allow-static-neighbor-outside-subnet

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
neighbor	Configure IPv6 address to layer-2 address mapping
allow-static-neighbor-outside-subnet	Allow static neighbor outside interface subnet

Command Mode

- /exec/configure

ipv6 neighbor binding

[no] ipv6 neighbor binding { { reachable-lifetime { infinite | <reach-secs> } } | { stale-lifetime { infinite | <stale-secs> } } } | { down-lifetime { infinite | <down-secs> } } } +

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>reach-secs</i>	Seconds
<i>stale-secs</i>	Seconds
<i>down-secs</i>	Seconds

Command Mode

- /exec/configure

ipv6 neighbor binding

```
[no] ipv6 neighbor binding { { vlan <vlanid> { <ipv6addr1> } } interface <intf> [ <mac-address> [ tracking
{ default | disable | enable [ retry-interval { default | <interval> } ] } ] [ reachable-lifetime { default | infinite
| <reach-secs> } ] ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>vlanid</i>	Number of entries
<i>intf</i>	Interface
<i>mac-address</i>	(Optional) 48-bit hardware address / <cr> for any mac address
<i>interval</i>	(Optional) seconds
<i>reach-secs</i>	(Optional) seconds

Command Mode

- /exec/configure

ipv6 neighbor binding logging

[no] ipv6 neighbor binding logging

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features

Command Mode

- /exec/configure

ipv6 neighbor binding max-entries

```
{ ipv6 neighbor binding max-entries <box-lim> { [ vlan-limit <vlan-lim> ] | [ port-limit <port-lim> ] | [ mac-limit <mac-lim> ] } + | no ipv6 neighbor binding max-entries [ <box-lim> { [ vlan-limit <vlan-lim> ] | [ port-limit <port-lim> ] | [ mac-limit <mac-lim> ] } + ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>box-lim</i>	Number of entries
<i>vlan-lim</i>	(Optional) Number of entries
<i>port-lim</i>	(Optional) Number of entries
<i>mac-lim</i>	(Optional) Number of entries

Command Mode

- /exec/configure

ipv6 neighbor tracking

[no] ipv6 neighbor tracking [retry-interval <interval>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>interval</i>	(Optional) Seconds

Command Mode

- /exec/configure

ipv6 pim anycast-rp

[no] ipv6 pim anycast-rp <anycast-rp> <rp-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
anycast-rp	Configure an RP in an Anycast-RP set (using PIM6)

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim bidir-rp-limit

[no] ipv6 pim bidir-rp-limit <limit>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bidir-rp-limit	Configures maximum Bidir RPs for IPv6 PIM in this VRF
<i>limit</i>	Set limit for Bidir RPs permitted in IPv6 PIM

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim border

[no] ipv6 pim border

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
border	Configures interface to be a boundary of a PIM6 domain

Command Mode

- /exec/configure/if-igp

ipv6 pim bsr-candidate

```
{ { ipv6 pim [ bsr ] bsr-candidate <interface> [ hash-len <hash-len> ] [ priority <priority> ] } | { no ipv6 pim [ bsr ] bsr-candidate [ <interface> ] [ hash-len <hash-len> ] [ priority <priority> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bsr	(Optional) Bootstrap protocol RP-distribution configuration
bsr-candidate	Configure router as a Bootstrap Router candidate
<i>interface</i>	Use IPV6 address of interface for Bootstrap messages
hash-len	(Optional) Hash mask length used in Bootstrap messages
<i>hash-len</i>	(Optional) Hash mask length value
priority	(Optional) BSR priority used in Bootstrap messages
<i>priority</i>	(Optional) BSR priority value

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim bsr bsr-policy

```
{ ipv6 pim bsr bsr-policy { <route-map-name> | <rtr_pol_name> } | no ipv6 pim bsr bsr-policy [ <route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
bsr-policy	Specify policy for filtering BSR messages
<i>route-map-name</i>	A route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim bsr listen

{ ipv6 pim bsr { listen | forward } + } | { no ipv6 pim bsr [{ listen | forward } +] }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
listen	Listen to Bootstrap/Candidate-RP messages
forward	Forward Bootstrap/Candidate-RP messages

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim bsr rp-candidate-policy

```
{ ipv6 pim bsr rp-candidate-policy { <route-map-name> | <rtr_pol_name> } | no ipv6 pim bsr
rp-candidate-policy [ <route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bsr	Bootstrap protocol RP-distribution configuration
rp-candidate-policy	Specify policy for filtering RP candidate messages
<i>route-map-name</i>	A route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim dr-priority

```
{ { ipv6 pim dr-priority <priority> } | { no ipv6 pim dr-priority [ <priority> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
dr-priority	Configures priority for PIM6 DR election on interface
<i>priority</i>	Priority value

Command Mode

- /exec/configure/if-igp

ipv6 pim event-history assert-receive

[no] ipv6 pim event-history assert-receive { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
assert-receive	Assert-receive events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history bidir

```
[no] ipv6 pim event-history bidir { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
bidir	Bidir events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history hello

```
[no] ipv6 pim event-history hello { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
hello	Hello events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history join-prune

```
[no] ipv6 pim event-history join-prune { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
join-prune	Join/Prune events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history null-register

[no] ipv6 pim event-history null-register { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
null-register	Reg events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history packet

```
[no] ipv6 pim event-history packet { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
packet	Packet events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history rp

[no] ipv6 pim event-history rp { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
rp	RP events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim event-history vrf

```
[no] ipv6 pim event-history vrf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
event-history	Configure event-history buffer
vrf	VRF events for PIM6
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 pim flush-routes

[no] ipv6 pim flush-routes

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
flush-routes	Remove routes when restarting PIM6

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim hello-interval

```
{ { ipv6 pim hello-interval { <interval-min> | <interval-max> } } | { no ipv6 pim hello-interval [ <interval-min> | <interval-max> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
hello-interval	Configures the Hello interval for interface
<i>interval-min</i>	Interval in milliseconds
<i>interval-max</i>	Interval in milliseconds

Command Mode

- /exec/configure/if-igp

ipv6 pim isolate

[no] ipv6 pim isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
isolate	Isolate this router from IPV6 PIM perspective

Command Mode

- /exec/configure

ipv6 pim jp-policy

```
{ ipv6 pim jp-policy { <route-map-name> | <rtr_pol_name> } [ in | out ] | no ipv6 pim jp-policy [ <route-map-name> | <rtr_pol_name> ] [ in | out ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
jp-policy	Specify policy for receiving Join-Prune messages
<i>route-map-name</i>	A route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy
in	(Optional) Inbound
out	(Optional) Outbound

Command Mode

- /exec/configure/if-igp

ipv6 pim log-neighbor-changes

[no] ipv6 pim log-neighbor-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
log-neighbor-changes	Log up/down PIM6 neighbor transitions

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim neighbor-policy

{ ipv6 pim neighbor-policy <route-map-name> | no ipv6 pim neighbor-policy [<route-map-name>] }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
neighbor-policy	Configures a neighbor policy for filtering adjacencies
<i>route-map-name</i>	A route-map name

Command Mode

- /exec/configure/if-igp

ipv6 pim passive

[no] ipv6 pim passive

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
passive	Interface in passive mode. No send/rcv

Command Mode

- /exec/configure/if-igp

ipv6 pim register-policy

```
{ ipv6 pim register-policy { <route-map-name> | <rtr_pol_name> } | no ipv6 pim register-policy [
<route-map-name> | <rtr_pol_name> ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
register-policy	Specify policy for receiving Register messages
<i>route-map-name</i>	A route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim register-rate-limit

```
{ { ipv6 pim register-rate-limit <rate> } | { no ipv6 pim register-rate-limit [ <rate> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
register-rate-limit	Rate limit for PIM data registers
<i>rate</i>	Packets per second

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim rp-address

```
{ { ipv6 pim rp-address <rp-address> [ group-list <prefix> | route-map <route-map-name> | prefix-list
<prefix-list-name> ] [ bidir ] [ override ] } | { no ipv6 pim rp-address <rp-address> [ group-list <prefix> |
route-map <route-map-name> | prefix-list <prefix-list-name> ] [ bidir ] [ override ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
rp-address	Configure static RP for group range
group-list	(Optional) Group range for static RP
route-map	(Optional) Route Map policy for static RP
<i>route-map-name</i>	(Optional) route-map name
prefix-list	(Optional) Prefix List policy for static RP
<i>prefix-list-name</i>	(Optional) prefix-list name
bidir	(Optional) Group range is treated in PIM6 bidirectional mode
override	(Optional) Overrides the dynamically learnt RPs

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim rp-candidate group

```
{ { ipv6 pim [ bsr ] rp-candidate <interface> { group-list <prefix> | route-map <route-map-name> } [ priority <priority> ] [ interval <interval> ] [ bidir ] } | { no ipv6 pim [ bsr ] rp-candidate [ <interface> ] [ group-list <prefix> ] [ route-map <route-map-name> ] [ priority <priority> ] [ interval <interval> ] [ bidir ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
bsr	(Optional) Bootstrap protocol RP-distribution configuration
rp-candidate	Configure router as a Rendezvous Point (RP) candidate
<i>interface</i>	IPv6 address of interface for Candidate-RP messages
group-list	Group range list
route-map	Group range policy for Candidate RP
<i>route-map-name</i>	route-map name
priority	(Optional) RP priority used in Candidate-RP messages
<i>priority</i>	(Optional) RP priority value
interval	(Optional) Bootstrap message transmission interval
<i>interval</i>	(Optional) Interval in seconds
bidir	(Optional) Group range advertised in PIM6 bidirectional mode

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim sparse-mode

ipv6 pim sparse-mode | no ipv6 pim [sparse-mode]

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 interface configuration commands
sparse-mode	Configures sparse-mode PIMv6 on interface

Command Mode

- /exec/configure/if-igp

ipv6 pim ssm

```
{ ipv6 pim ssm { { range { <group> + | none } } | { route-map <route-map-name> } } | no ipv6 pim ssm { { range { <group> + | none } } | { route-map <route-map-name> } } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
ssm	Source Specific Multicast (SSM) groups
range	Configure explicit group ranges
none	Remove all SSM group ranges
route-map	Group range policy for SSM range
<i>route-map-name</i>	A route-map name

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim state-limit

```
{ { ipv6 pim state-limit <max-states> [ reserved <route-map-name> <max-reserved> ] } | { no ipv6 pim
state-limit [ <max-states> [ reserved <route-map-name> <max-reserved> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
state-limit	Configures State limit
<i>max-states</i>	Maximum (*,G)/(S,G) entries allowed in this VRF
reserved	(Optional) Configures Reserved limit
<i>route-map-name</i>	(Optional) Route-map name
<i>max-reserved</i>	(Optional) Maximum reserved (*,G)/(S,G) entries allowed in this VRF

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 pim use-shared-tree-only spt-threshold infinity group-list

{ ipv6 pim { use-shared-tree-only | spt-threshold infinity } group-list <route-map-name> } | { no ipv6 pim { use-shared-tree-only | spt-threshold infinity } [group-list <route-map-name>] }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
pim	PIM6 global configuration commands
use-shared-tree-only	Use (*,G) only state, no source state is created
spt-threshold	Source-tree switching threshold
infinity	Never switch to source-tree
group-list	Specify group ranges through policy
<i>route-map-name</i>	Route-map name

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 policy route-map

```
ipv6 policy route-map <route-map-name> | no ipv6 policy route-map [ <route-map-name> | <route-map-name> ]
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
policy	Configure PBR feature
route-map	Route-map for PBR
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	(Optional) Route-map name
<i>route-map-name</i>	(Optional) Known route-map name

Command Mode

- /exec/configure/if-igp

ipv6 port traffic-filter

[no] ipv6 port traffic-filter <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
port	Port policy
traffic-filter	Specify access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/if-set-acl-l2

ipv6 prefix-list description

```
{ ipv6 prefix-list <ipv6-pfl-name> description <line> } | { no ipv6 prefix-list <ipv6-pfl-name> description }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
prefix-list	Build a prefix list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Known prefix-list name
description	Description of the IPv6 prefix list
<i>line</i>	IPv6 prefix-list description string

Command Mode

- /exec/configure

ipv6 prefix-list permit

```
{ ipv6 prefix-list <ipv6-pfl-name> [ seq <seq> ] { permit | deny } <prefix> { [ eq <equal> ] | [ ge <greater> ] | [ le <lesser> ] } } | { no ipv6 prefix-list { <ipv6-pfl-name> | <ipv6-pfl-name> } [ seq <seq> ] [ { permit | deny } <prefix> { [ eq <equal> ] | [ ge <greater> ] | [ le <lesser> ] } ] }
```

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
prefix-list	Build a prefix list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Known prefix-list name
seq	(Optional) Sequence number of an entry
<i>seq</i>	(Optional) Sequence number
permit	Specify routes to forward
deny	Specify routes to reject
eq	(Optional) Exact prefix length to be matched
<i>equal</i>	(Optional) Exact prefix length
ge	(Optional) Minimum prefix length to be matched
<i>greater</i>	(Optional) Minimum prefix length
le	(Optional) Maximum prefix length to be matched
<i>lesser</i>	(Optional) Maximum prefix length

Command Mode

- /exec/configure

ipv6 queue-packets

[no] ipv6 queue-packets

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
queue-packets	Queue 1 packet when triggered NS is sent

Command Mode

- /exec/configure

ipv6 redirects

ipv6 [nd] redirects | no ipv6 [nd] redirects

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
nd	(Optional) ICMPv6 Neighbor Discovery commands
redirects	Enable sending ICMPv6 Redirect messages

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-config

ipv6 route

```
[no] ipv6 route <ipv6-prefix> { <interface> | { { <link-local> <interface-link-local> } | { <pin-interface>
<next-hop> } | { <next-hop> | <nh-prefix> } | { <vlan-interface> } } [ vrf { <vrf-name> | <vrf-known-name>
} ] ] [ track <object-num> ] [ name <rt-name> ] [ <pref> | tag <tag-value> ] +
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
route	Configure IPv6 unicast static route
<i>interface</i>	Interface for interface static routes
<i>vlan-interface</i>	vlan interface
name	(Optional) Specify name of the next hop
<i>rt-name</i>	(Optional) Name of next hop
<i>pin-interface</i>	Pin interface
<i>interface-link-local</i>	Interface for interface static routes
track	(Optional) Specify the Object to be Tracked
<i>object-num</i>	(Optional) Track Object Number
vrf	(Optional) VRF for next-hop if different from this vrf
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>pref</i>	(Optional) Route preference
tag	(Optional) Supply tag value with static route
<i>tag-value</i>	(Optional) 32-bit value for tag

Command Mode

- /exec/configure /exec/configure/vrf

ipv6 route static bfd

[no] ipv6 route static bfd <pin-interface> <next-hop>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IP features
route	Route information
static	Static route based configuration
bfd	Enable bfd detection on static route
<i>pin-interface</i>	Interface on which bfd has to be enabled

Command Mode

- /exec/configure /exec/configure/config-mgmt /exec/configure/vrf

ipv6 router isis

[no] ipv6 router isis <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
router	Enable a routing process
isis	Intermediate System to Intermediate System (IS-IS)
<i>tag</i>	Process tag

Command Mode

- /exec/configure/if-igp

ipv6 router ospfv3 area

[no] ipv6 router ospfv3 <tag> area { <area-id-ip> | <area-id-int> } [secondaries none]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
router	Enable a routing process
ospfv3	OSPFv3 configuration commands
<i>tag</i>	Process tag
area	Area associated with interface
<i>area-id-ip</i>	OSPFv3 area ID in IP address format
<i>area-id-int</i>	OSPFv3 area ID as a decimal format
secondaries	(Optional) Do not include secondary IPv6 addresses
none	(Optional) Do not include secondary IPv6 addresses

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ipv6 router ospfv3 multi-area

[no] ipv6 router ospfv3 [<tag>] multi-area <area-id-ip>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
router	Enable a routing process
ospfv3	OSPFv3 configuration commands
<i>tag</i>	(Optional) Process tag
multi-area	Multi-Area associated with interface
<i>area-id-ip</i>	Area Id as an integer or ip address

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ipv6 routing event-history size

[no] ipv6 routing event-history { am | cli | detail | errors | general | ha | lfe | recursive-next-hop | summary | ufdm | ufdm-detail | ufdm-summary } size { <size_in_text> | <size_in_bytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
event-history	Configure routing event log
am	AM
cli	CLI
detail	Detail
errors	Errors
general	General
ha	HA
lfe	LFE
recursive-next-hop	Recursive next hop
summary	Summary
ufdm	UFDM
ufdm-detail	UFDM Detail
ufdm-summary	UFDM Summary
size	Size of buffer
<i>size_in_text</i>	Buffer size
<i>size_in_bytes</i>	Enter an integer value for the event history buffer

Command Mode

- /exec/configure

ipv6 routing multicast event-history cli

[no] ipv6 routing multicast event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
cli	CLI events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history mfdm-debug

```
[no] ipv6 routing multicast event-history mfdm-debug { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mfdm-debug	MFDM events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history mfdm-events

```
[no] ipv6 routing multicast event-history mfdm-events { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mfdm-events	Non-periodic MFDM events in MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history mfdm-stats

[no] ipv6 routing multicast event-history mfdm-stats { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
mfdm-stats	MFDM-stats events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history rib-summary

```
[no] ipv6 routing multicast event-history rib-summary { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event-history buffers
rib-summary	RIB events for MRIB-summary
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history rib

[no] ipv6 routing multicast event-history rib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
rib	RIB events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast event-history vrf

[no] ipv6 routing multicast event-history vrf { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
event-history	Configure event history buffers
vrf	VRF events for MRIB
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

ipv6 routing multicast holddown

ipv6 routing multicast holddown { <route-holddown-sec> | <none> } | no ipv6 routing multicast holddown [<route-holddown-sec> | <none>]

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
holddown	Initial holddown period
<i>route-holddown-sec</i>	Delay in seconds
<i>none</i>	Disable holddown

Command Mode

- /exec/configure

ipv6 routing multicast software-replication

[no] ipv6 routing multicast software-replication

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
routing	Routing information
multicast	Configure multicast
software-replication	Enable software replication of PIM ASM leak packets

Command Mode

- /exec/configure

ipv6 snooping

[no] ipv6 snooping [attach-policy <policy_name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>policy_name</i>	(Optional) policy name for ipv6 snooping

Command Mode

- /exec/configure/if-switching

ipv6 snooping

[no] ipv6 snooping [attach-policy <policy_name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>policy_name</i>	(Optional) policy name for ipv6 snooping

Command Mode

- /exec/configure/vlan-config

ipv6 snooping policy

[no] ipv6 snooping policy <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
<i>name</i>	Name of the snooping policy

Command Mode

- /exec/configure

ipv6 switch-packets

[no] ipv6 switch-packets [lla]

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
switch-packets	Switch ND packets received on core ports
lla	(Optional) Switch ND packets targeted to Link local address on core ports

Command Mode

- /exec/configure

ipv6 traffic-filter

[no] ipv6 traffic-filter <name> <inout>

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
traffic-filter	Specify access control for packets
<i>name</i>	List name
<i>inout</i>	Traffic direction

Command Mode

- /exec/configure/if-set-acl-l3

ipv6 unreachable

[no] ipv6 [icmp] unreachable

Syntax Description

no	(Optional) Negate a command or set its defaults
ipv6	Configure IPv6 features
icmp	(Optional) ICMPv6 commands
unreachables	Enable sending ICMPv6 Unreachable messages (port-unreachables are always rate-limit enabled)

Command Mode

- /exec/configure/if-igp

ipv6 verify unicast source reachable-via rx

[no] ipv6 verify unicast source reachable-via [{ rx | any [allow-default] }] | ipv6 verify unicast source reachable-via { rx | any [allow-default] }

Syntax Description

no	Negate a command or set its defaults
ipv6	Configure IPv6 features
verify	Unicast Reverse Path Forwarding
unicast	Unicast Reverse Path Forwarding
source	Validation of source address
reachable-via	Specify reachability check to apply to the source address
rx	(Optional) Source is reachable via interface on which packet was received
any	(Optional) Source is reachable via any interface
allow-default	(Optional) Loose Default Route Unicast Reverse Path Forwarding

Command Mode

- /exec/configure/if-igp

is-type

is-type <is-type> | no is-type [<is-type>]

Syntax Description

no	Negate a command or set its defaults
is-type	IS type for this IS-IS process
<i>is-type</i>	IS-IS IS type

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

ishow cli find nodes

ishow cli find nodes [<component>] [recurse]

Syntax Description

ishow	Show internal information
cli	Show CLI information
find	
nodes	display
<i>component</i>	(Optional) display
recurse	(Optional) go

Command Mode

- /exec

ishow cli modes

ishow cli modes

Syntax Description

ishow	Show internal information
cli	Show CLI information
modes	show

Command Mode

- /exec

ishow cli nodes

ishow cli nodes [<mode>]

Syntax Description

ishow	Show internal information
cli	Show CLI information
nodes	show
<i>mode</i>	(Optional) mode

Command Mode

- /exec

ishow cli paths

ishow cli paths <component> [<type>]

Syntax Description

ishow	Show internal information
cli	Show CLI information
paths	show
<i>component</i>	component
<i>type</i>	(Optional)

Command Mode

- /exec

ishow cli tags

ishow cli tags

Syntax Description

ishow	Show internal information
cli	Show CLI information
tags	

Command Mode

- /exec

ishow core backtrace

ishow core <pid> backtrace

Syntax Description

ishow	Show internal information
core	display info from core file
<i>pid</i>	PID from 'show cores
backtrace	display backtrace -- needs enough space to unzip the core file!

Command Mode

- /exec

isis authentication-check

[no] isis authentication-check

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
authentication-check	Check authentication on received hellos

Command Mode

- /exec/configure/if-igp

isis authentication-check level-1

[no] isis authentication-check level-1

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
authentication-check	Check authentication on received hellos
level-1	Configure authentication check for level-1 IIHs

Command Mode

- /exec/configure/if-igp

isis authentication-check level-2

[no] isis authentication-check level-2

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
authentication-check	Check authentication on received hellos
level-2	Configure authentication check for level-2 IIHs

Command Mode

- /exec/configure/if-igp

isis authentication-type cleartext

```
{ isis authentication-type { cleartext | md5 } <level> | no isis authentication-type [ { cleartext | md5 } ] <level>
}
```

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
authentication-type	Set hello authentication type
cleartext	Cleartext
md5	HMAC-MD5
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/if-ma

isis authentication-type cleartext

```
{ isis authentication-type { cleartext | md5 } | no isis authentication-type [ { cleartext | md5 } ] }
```

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
authentication-type	Set hello authentication type
cleartext	Cleartext
md5	HMAC-MD5

Command Mode

- /exec/configure/if-p2p

isis authentication key-chain

```
{ isis authentication key-chain <auth-keychain> <level> | no isis authentication key-chain [ <auth-keychain> ] <level> }
```

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
authentication	Set hello authentication keychain
key-chain	Set hello authentication keychain
<i>auth-keychain</i>	authentication keychain
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/if-ma

isis authentication key-chain

```
{ isis authentication key-chain <auth-keychain> | no isis authentication key-chain [ <auth-keychain> ] }
```

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
authentication	Set hello authentication keychain
key-chain	Set hello authentication keychain
<i>auth-keychain</i>	authentication keychain

Command Mode

- /exec/configure/if-p2p

isis bfd

[no] isis bfd [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
bfd	Interface BFD configuration
disable	(Optional) Disable BFD on interface

Command Mode

- /exec/configure/if-igp

isis circuit-type

isis circuit-type <circuit-type> | no isis circuit-type [<circuit-type>]

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
circuit-type	Configure circuit type for interface
<i>circuit-type</i>	IS-IS circuit type
<i>isis</i>	

Command Mode

- /exec/configure/if-igp

isis csnp-interval level

[no] isis csnp-interval <sec> { level-1 | level-2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
csnp-interval	Set CSNP interval in seconds
<i>sec</i>	CSNP interval value
level-1	Specify interval for level-1 CSNPs
level-2	Specify interval for level-2 CSNPs

Command Mode

- /exec/configure/if-igp

isis event-history adjacency

[no] isis event-history adjacency { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
adjacency	Adjacency events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history cli

[no] isis event-history cli { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
cli	CLI events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history csnp

[no] isis event-history csnp { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
csnp	CSNP events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history dis

[no] isis event-history dis { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
dis	Dis events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history events

[no] isis event-history events { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
events	Events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history graceful

[no] isis event-history graceful { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
graceful	Graceful Restart events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history ha

[no] isis event-history ha { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
ha	HA events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history iih

[no] isis event-history iih { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
iih	IIH events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history lsp-flood

[no] isis event-history lsp-flood { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
lsp-flood	LSP-flood events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history lsp-gen

[no] isis event-history lsp-gen { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
lsp-gen	LSP-Gen events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history mtr

[no] isis event-history mtr { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
mtr	MTR events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history perf

[no] isis event-history perf { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
perf	Performance events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history psnp

[no] isis event-history psnp { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
psnp	PSNP events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history redist

[no] isis event-history redist { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
redist	Redist events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history spf-leaf

```
[no] isis event-history spf-leaf { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
spf-leaf	Shortest path first events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history spf-tree

[no] isis event-history spf-tree { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
spf-tree	SPF-Tree events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history sr

[no] isis event-history sr { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
sr	SR events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history tlv

```
[no] isis event-history tlv { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
tlv	TLV events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history ulib

[no] isis event-history ulib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
ulib	ULIB events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis event-history urib

[no] isis event-history urib { size { <size_in_text> | <size_in_kbytes> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	Event-history buffers for IS-IS
event-history	Configure event-history buffers
urib	URIB events for IS-IS
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure/router-isis

isis hello-interval

[no] isis hello-interval <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
hello-interval	Set Hello interval in seconds
<i>sec</i>	Hello interval value

Command Mode

- /exec/configure/if-igp

isis hello-interval level

[no] isis hello-interval <sec> { level-1 | level-2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
hello-interval	Set Hello interval in seconds
<i>sec</i>	Hello interval value
level-1	Specify hello-interval for level-1 IIHs
level-2	Specify hello-interval for level-2 IIHs

Command Mode

- /exec/configure/if-igp

isis hello-multiplier

[no] isis hello-multiplier <multi>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
hello-multiplier	Set multiplier for Hello holding time
<i>multi</i>	Hello multiplier value

Command Mode

- /exec/configure/if-igp

isis hello-multiplier level

[no] isis hello-multiplier <multi> { level-1 | level-2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
hello-multiplier	Set multiplier for Hello holding time
<i>multi</i>	Hello multiplier value
level-1	Specify hello multiplier for level-1 IIHs
level-2	Specify hello multiplier for level-2 IIHs

Command Mode

- /exec/configure/if-igp

isis hello-padding

{ isis hello-padding | no isis hello-padding [always] }

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
hello-padding	Pad IS-IS hello PDUs to full MTU
always	(Optional) Pad every hello

Command Mode

- /exec/configure/if-igp

isis ipv6 bfd

[no] isis ipv6 bfd [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
ipv6	Enable BFD for ipv6
bfd	Interface BFD configuration
disable	(Optional) Disable BFD on interface

Command Mode

- /exec/configure/if-igp

isis ipv6 metric

[no] isis ipv6 metric <metric> <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
metric	Configure metric for IPV6 topology
ipv6	Configure metric for IPV6 topology
<i>metric</i>	Default metric
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/if-igp /exec/configure/router-isis/router-isis-af-ipv6

isis lsp-interval

[no] isis lsp-interval <msec>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
lsp-interval	Set LSP transmission interval
<i>msec</i>	LSP transmission interval (milliseconds)

Command Mode

- /exec/configure/if-igp

isis mesh-group

```
{ isis mesh-group { blocked | <mesh-id> } | no isis mesh-group [ { blocked | <mesh-id> } ] }
```

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
mesh-group	Set IS-IS mesh group
<i>mesh-id</i>	Mesh group number
blocked	Block LSPs on this interface

Command Mode

- /exec/configure/if-igp

isis metric

[no] isis metric <metric> <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
metric	Configure the metric for interface
<i>metric</i>	Default metric
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/if-igp /exec/configure/if-mpls-tunnel

isis mtu-check

[no] isis mtu-check

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
mtu-check	Check mtu on received hellos, if its padded

Command Mode

- /exec/configure/if-p2p

isis mtu-check level

[no] isis mtu-check { level-1 | level-2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
mtu-check	Check mtu on received hellos, if its padded
level-1	Configure mtu-check for level-1
level-2	Configure mtu-check for level-2

Command Mode

- /exec/configure/if-ma

isis network point-to-point

[no] isis network point-to-point [use-allIS-mac]

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
network	Change interface medium to p2p
point-to-point	Change interface medium to p2p
use-allIS-mac	(Optional) use allISs MAC for Tx packets

Command Mode

- /exec/configure/if-igp /exec/configure/if-mpls-tunnel

isis passive-interface

isis passive-interface <level> | no isis passive-interface <level> | default isis passive-interface [<level_obsolete>]

Syntax Description

no	Negate a command or set its defaults
isis	IS-IS configuration commands
passive-interface	Suppress IS-IS PDU
default	Undo a command
<i>level</i>	Level to suppress
<i>level_obsolete</i>	(Optional) Level to suppress

Command Mode

- /exec/configure/if-igp

isis prefix-attributes n-flag-clear

[no] isis prefix-attributes n-flag-clear

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
prefix-attributes	Segment routing attribute
n-flag-clear	Clear N flag for prefix

Command Mode

- /exec/configure/if-igp

isis priority level

[no] isis priority <priority> { level-1 | level-2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
priority	Set priority for DIS election
<i>priority</i>	Priority value
level-1	Specify priority for level-1 routing
level-2	Specify priority for level-2 routing

Command Mode

- /exec/configure/if-igp

isis retransmit-interval

[no] isis retransmit-interval <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
retransmit-interval	Set per-LSP retransmission interval
<i>sec</i>	Interval between retransmissions of the same LSP (seconds)

Command Mode

- /exec/configure/if-igp

isis retransmit-throttle-interval

[no] isis retransmit-throttle-interval <msec>

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
retransmit-throttle-interval	Set interface LSP retransmission interval
<i>msec</i>	Delay between retransmitted LSPs (milliseconds)

Command Mode

- /exec/configure/if-igp

isis shutdown

[no] isis shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
isis	IS-IS configuration commands
shutdown	Graceful shutdown IS-IS functionality on the interface

Command Mode

- /exec/configure/if-igp

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate this router from RIP perspective

Command Mode

- /exec/configure/router-rip

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate router, ISIS perspective (set overload)

Command Mode

- /exec/configure/router-isis

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate this router from OSPFV3 perspective

Command Mode

- /exec/configure/router-ospf3

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate this router from EIGRP perspective

Command Mode

- /exec/configure/router-eigrp

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate this router from OSPF perspective

Command Mode

- /exec/configure/router-ospf

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate this router from BGP perspective

Command Mode

- /exec/configure/router-bgp

isolate

[no] isolate

Syntax Description

no	(Optional) Negate a command or set its defaults
isolate	Isolate fabric spine (set overload)

Command Mode

- /exec/configure/l2mp-isis

itd

{ itd <service-name> } | { no itd <service-name> }

Syntax Description

no	Negate a command or set its defaults
itd	ITD service
<i>service-name</i>	ITD service-name

Command Mode

- /exec/configure

itd device-group

{ itd device-group <svc-name> } | { no itd device-group <svc-name> }

Syntax Description

no	Negate a command or set its defaults
itd	ITD service
device-group	ITD device group
<i>svc-name</i>	service-name

Command Mode

- /exec/configure

itd session access-list refresh

itd session access-list <acl-name> refresh

Syntax Description

itd	ITD service
session	ITD session
access-list	ITD include access-list
<i>acl-name</i>	acl-name
refresh	Refresh ITD policies based on access-list changes

Command Mode

- /exec/configure

itd session device-group

{ itd session device-group <svc-name> } | { no itd session device-group <svc-name> }

Syntax Description

no	Negate a command or set its defaults
itd	ITD service
session	ITD session
device-group	ITD device group
<i>svc-name</i>	service-name

Command Mode

- /exec/configure

itd statistics

{ itd statistics <service-name> } | { no itd statistics <service-name> }

Syntax Description

no	Negate a command or set its defaults
itd	ITD service
statistics	ITD statistics
<i>service-name</i>	ITD service-name

Command Mode

- /exec/configure



J Commands

- [job name](#), on page 2532
- [json-pretty](#), on page 2533
- [json-pretty](#), on page 2534
- [json](#), on page 2535
- [json](#), on page 2536

job name

[no] job name <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
job	Assign a job to the schedule
name	Assign a job to the schedule
s0	Specify the job name

Command Mode

- /exec/configure/schedule

json-pretty

| json-pretty

Syntax Description

	Pipe command output to filter
json-pretty	output in json pretty print format

Command Mode

- /output

json-pretty

| json-pretty

Syntax Description

	Pipe command output to filter
json-pretty	output in json pretty print format

Command Mode

- /output

json

| json

Syntax Description

	Pipe command output to filter
json	output in json format

Command Mode

- /output

json

| json

Syntax Description

	Pipe command output to filter
json	output in json format

Command Mode

- /output



K Commands

- [key-octet-string 7 cryptographic-algorithm AES_128_CMAC](#), on page 2538
- [key-octet-string 7 cryptographic-algorithm AES_256_CMAC](#), on page 2539
- [key-octet-string cryptographic-algorithm AES_128_CMAC](#), on page 2540
- [key-octet-string cryptographic-algorithm AES_256_CMAC](#), on page 2541
- [key-server-priority](#), on page 2542
- [key-string](#), on page 2543
- [key-string 7](#), on page 2544
- [key](#), on page 2545
- [key](#), on page 2546
- [key chain](#), on page 2547
- [key config-key hex](#), on page 2548
- [kill-everyone](#), on page 2549
- [kill background](#), on page 2550
- [kstack multicast-udp](#), on page 2551
- [kubernetes server ip-address port](#), on page 2552

key-octet-string 7 cryptographic-algorithm AES_128_CMAC

```
{ key-octet-string 7 <keystring> cryptographic-algorithm AES_128_CMAC }
```

Syntax Description

key-octet-string	Set key octet string
7	Encryption Type - Proprietary
<i>keystring</i>	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_128_CMAC	cryptographic-algorithm AES-128-CMAC

Command Mode

- /exec/configure/macseckeychain-key

key-octet-string 7 cryptographic-algorithm AES_256_CMAC

```
{ key-octet-string 7 <keystring> cryptographic-algorithm AES_256_CMAC }
```

Syntax Description

key-octet-string	Set key octet string
7	Encryption Type - Proprietary
<i>keystring</i>	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_256_CMAC	cryptographic-algorithm AES-256-CMAC

Command Mode

- /exec/configure/macseckeychain-key

key-octet-string cryptographic-algorithm AES_128_CMAC

```
{ key-octet-string [ 0 ] <keystring> cryptographic-algorithm AES_128_CMAC | no key-octet-string [ 0 ]
<keystring> cryptographic-algorithm AES_128_CMAC }
```

Syntax Description

no	Negate a command or set its defaults
key-octet-string	Set key octet string
0	(Optional) Encryption Type - No Encryption(default)
<i>keystring</i>	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_128_CMAC	cryptographic-algorithm AES-128-CMAC

Command Mode

- /exec/configure/macseckeychain-key

key-octet-string cryptographic-algorithm AES_256_CMAC

```
{ key-octet-string [ 0 ] <keystring> cryptographic-algorithm AES_256_CMAC | no key-octet-string [ 0 ]  
<keystring> cryptographic-algorithm AES_256_CMAC }
```

Syntax Description

no	Negate a command or set its defaults
key-octet-string	Set key octet string
0	(Optional) Encryption Type - No Encryption(default)
<i>keystring</i>	key octet string
cryptographic-algorithm	Select CMAC algorithm for authentication
AES_256_CMAC	cryptographic-algorithm AES-256-CMAC

Command Mode

- /exec/configure/macseckeychain-key

key-server-priority

[no] key-server-priority <pri>

Syntax Description

key-server-priority	Configure Key-Server priority
<i>pri</i>	key-server priority value

Command Mode

- /exec/configure/masec-policy

key-string

{ key-string [0] <keystring> | no key-string }

Syntax Description

no	Negate a command or set its defaults
key-string	Set key string
0	(Optional) Encryption Type - No Encryption(default)
<i>keystring</i>	key string

Command Mode

- /exec/configure/keychain-key

key-string 7

```
{ key-string 7 <keystring> }
```

Syntax Description

key-string	Set key string
7	Encryption Type - Proprietary
<i>keystring</i>	key string

Command Mode

- /exec/configure/keychain-key

key

[no] key <macsec_keyid>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Configure a macsec key
<i>macsec_keyid</i>	MACsec Key identifier ranging from 1 octet to 32

Command Mode

- /exec/configure/macseckeychain

key

[no] key <keyid>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Configure a key
<i>keyid</i>	Key identifier

Command Mode

- /exec/configure/keychain

key chain

[no] key chain <keychain>

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Key Management
chain	Keychain Management
<i>keychain</i>	key-chain name

Command Mode

- /exec/configure

key config-key hex

[no] key config-key { hex | ascii } [<master-key>]

Syntax Description

no	(Optional) Negate a command or set its defaults
key	Encryption key for strong encryption
config-key	Master-key for strong encryption of secrets in config
hex	Key followed should be in hex format
ascii	Key followed should be in ascii format
<i>master-key</i>	(Optional) Enter the Master-key

Command Mode

- /exec

kill-everyone

[no] [eigrp] kill-everyone

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
kill-everyone	Kill all adjacencies on SIA

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

kill background

kill background <pid>

Syntax Description

kill	terminate processes
background	kill background processes (started with 'source background <file>' command)
<i>pid</i>	background script to terminate, by process-id or just a regex matching any line from 'show background' command

Command Mode

- /exec

kstack multicast-udp

```
{ { no kstack multicast-udp } | { kstack multicast-udp { enable | disable } } }
```

Syntax Description

no	Negate a command or set its defaults
kstack	Enable/Disable kstack feature
multicast-udp	Clone UDP dest Multicast packets to kstack
enable	
disable	

Command Mode

- /exec/configure /exec/configure/config-mgmt

kubernetes server ip-address port

[no] kubernetes server ip-address <ip-addr> port <s0> [vrf <vrf-name>] | no kubernetes server

Syntax Description

no	(Optional) Negate a command or set its defaults
kubernetes	kubernetes
server	kubernetes server
ip-address	IP address of the kubernetes host
<i>ip-addr</i>	ip address of kubernetes Host
port	Port number of the host
<i>s0</i>	port number
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name

Command Mode

- /exec/configure



L Commands

- [l2rib dup-host-mac-detection](#), on page 2561
- [l2rib dup-host-mac-recovery](#), on page 2562
- [l2rib event-history size](#), on page 2563
- [l3vm event-history](#), on page 2564
- [label-allocation-mode per-vrf](#), on page 2565
- [label allocate global](#), on page 2566
- [lacp fast-select-hot-standby](#), on page 2567
- [lacp graceful-convergence](#), on page 2568
- [lacp max-bundle](#), on page 2569
- [lacp min-links](#), on page 2570
- [lacp mode delay](#), on page 2571
- [lacp mode delay](#), on page 2572
- [lacp port-priority](#), on page 2573
- [lacp rapid-transition](#), on page 2574
- [lacp rate](#), on page 2575
- [lacp rate](#), on page 2576
- [lacp suspend-individual](#), on page 2577
- [lacp system-mac](#), on page 2578
- [lacp system-priority](#), on page 2579
- [lacp vpc-convergence](#), on page 2580
- [last](#), on page 2581
- [latency](#), on page 2582
- [latency](#), on page 2583
- [latency quantization](#), on page 2584
- [latency quantization](#), on page 2585
- [layer-2 multicast lookup mac](#), on page 2586
- [layer-2 multicast lookup mac](#), on page 2587
- [layer2-switched flow monitor input](#), on page 2588
- [layer3 peer-router](#), on page 2589
- [layer3 peer-router syslog](#), on page 2590
- [ldap-search-map](#), on page 2591
- [ldap-search-map](#), on page 2592
- [ldap-server deadtime](#), on page 2593

- [ldap-server host](#), on page 2594
- [ldap-server host test rootDN](#), on page 2596
- [ldap-server port](#), on page 2597
- [ldap-server timeout](#), on page 2598
- [ldap search-map](#), on page 2599
- [less](#), on page 2600
- [license expiry check_interval](#), on page 2601
- [limit-resource m4route-mem maximum equal-to-min](#), on page 2602
- [limit-resource m6route-mem maximum](#), on page 2603
- [limit-resource module-type](#), on page 2604
- [limit-resource monitor-session-erspan-dst minimum maximum equal-to-min](#), on page 2605
- [limit-resource monitor-session-inband-src minimum maximum equal-to-min](#), on page 2606
- [limit-resource monitor-session minimum maximum equal-to-min](#), on page 2607
- [limit-resource port-channel minimum maximum](#), on page 2608
- [limit-resource u4route-mem maximum equal-to-min](#), on page 2609
- [limit-resource u6route-mem maximum equal-to-min](#), on page 2610
- [limit-resource vlan minimum maximum equal-to-min](#), on page 2611
- [limit-resource vrf minimum maximum equal-to-min](#), on page 2612
- [limit address-count](#), on page 2613
- [line console](#), on page 2614
- [line console](#), on page 2615
- [line vty](#), on page 2616
- [line vty](#), on page 2617
- [link-management timers bandwidth](#), on page 2618
- [link-state-trap](#), on page 2619
- [link debounce](#), on page 2620
- [link rxlos](#), on page 2621
- [link transmit reset-skip](#), on page 2622
- [lisp](#), on page 2623
- [lisp ddt](#), on page 2624
- [lisp ddt authoritative-prefix eid-prefix](#), on page 2625
- [lisp ddt delegate eid-prefix](#), on page 2626
- [lisp ddt map-server-peer eid-prefix](#), on page 2627
- [lisp ddt root](#), on page 2628
- [lisp dynamic-eid](#), on page 2629
- [lisp dynamic-eid](#), on page 2630
- [lisp explicit-locator-path](#), on page 2631
- [lisp explicit-locator-path](#), on page 2632
- [lisp extended-subnet-mode](#), on page 2633
- [lisp geo-coordinates](#), on page 2634
- [lisp instance-id](#), on page 2635
- [lisp loc-reach-algorithm](#), on page 2636
- [lisp merge-registrations site-id](#), on page 2637
- [lisp mobility](#), on page 2638
- [lisp mobility test-liveness](#), on page 2639
- [lisp security](#), on page 2640

- lisp site, on page 2641
- lisp site, on page 2642
- lisp smr-locators, on page 2643
- lisp to, on page 2644
- list, on page 2645
- list, on page 2646
- listobject-boolean not, on page 2647
- listobject-weight weight threshold-weight, on page 2648
- listobject, on page 2649
- lldp, on page 2650
- lldp dcbx version auto, on page 2651
- lldp dcbx version cee, on page 2652
- lldp eee rx_wake_time, on page 2653
- lldp receive, on page 2654
- lldp tlv-select eee, on page 2655
- lldp tlv-select management-address v4, on page 2656
- lldp tlv-set management-address, on page 2657
- lldp tlv-set management-address ipv6, on page 2658
- lldp tlv-set vlan, on page 2659
- lldp transmit, on page 2660
- load-balance, on page 2661
- load-balance, on page 2662
- load-balance, on page 2663
- load-interval, on page 2664
- load-interval, on page 2665
- load-interval counter, on page 2666
- load-interval counter, on page 2667
- load, on page 2668
- load, on page 2669
- load, on page 2670
- load, on page 2671
- local-as, on page 2672
- local-as, on page 2673
- local-label prefix, on page 2674
- local-label prefix, on page 2675
- locator-led, on page 2676
- lockdown, on page 2677
- log-adjacency-changes, on page 2678
- log-adjacency-changes, on page 2679
- log-adjacency-changes, on page 2680
- log-adjacency-changes, on page 2681
- log-adjacency-changes, on page 2682
- log-adjacency-changes, on page 2683
- log-event-type, on page 2684
- log-neighbor-changes, on page 2685
- log-neighbor-changes, on page 2686

- [log-neighbor-warnings](#), on page 2687
- [logging](#), on page 2688
- [logging](#), on page 2689
- [logging abort](#), on page 2690
- [logging console](#), on page 2691
- [logging debug](#), on page 2692
- [logging distribute](#), on page 2693
- [logging drop threshold](#), on page 2694
- [logging drop threshold](#), on page 2695
- [logging event link enable](#), on page 2696
- [logging event port link-status](#), on page 2697
- [logging event port link-status](#), on page 2698
- [logging event port link-status](#), on page 2699
- [logging event port link-status default](#), on page 2700
- [logging event port trunk-status](#), on page 2701
- [logging event port trunk-status](#), on page 2702
- [logging event port trunk-status default](#), on page 2703
- [logging flow-mod](#), on page 2704
- [logging flow-mod](#), on page 2705
- [logging ip access-list cache](#), on page 2706
- [logging ip access-list cache entries](#), on page 2707
- [logging ip access-list detailed](#), on page 2708
- [logging ip access-list include sgt](#), on page 2709
- [logging level](#), on page 2710
- [logging level](#), on page 2711
- [logging level](#), on page 2712
- [logging level](#), on page 2713
- [logging level](#), on page 2715
- [logging level](#), on page 2716
- [logging level](#), on page 2717
- [logging level](#), on page 2718
- [logging level aaa](#), on page 2719
- [logging level acllog](#), on page 2720
- [logging level aclmgr](#), on page 2721
- [logging level adbm](#), on page 2722
- [logging level adjmgr](#), on page 2723
- [logging level all](#), on page 2724
- [logging level amt](#), on page 2725
- [logging level arp](#), on page 2726
- [logging level ascii-cfg](#), on page 2727
- [logging level assoc_mgr](#), on page 2728
- [logging level backup](#), on page 2729
- [logging level bfd](#), on page 2730
- [logging level bgp](#), on page 2731
- [logging level bloggerd](#), on page 2732
- [logging level bootvar](#), on page 2733

- [logging level callhome](#), on page 2734
- [logging level capability](#), on page 2735
- [logging level catena](#), on page 2736
- [logging level cdp](#), on page 2737
- [logging level cert](#), on page 2738
- [logging level cfs](#), on page 2739
- [logging level clis](#), on page 2740
- [logging level clk_mgr](#), on page 2741
- [logging level confcheck](#), on page 2742
- [logging level copp](#), on page 2743
- [logging level core](#), on page 2744
- [logging level cts](#), on page 2745
- [logging level dhclient](#), on page 2746
- [logging level dhcp_snoop](#), on page 2747
- [logging level diagclient](#), on page 2748
- [logging level diagmgr](#), on page 2749
- [logging level dot1x](#), on page 2750
- [logging level ecp](#), on page 2751
- [logging level eigrp](#), on page 2752
- [logging level eltm](#), on page 2753
- [logging level epp](#), on page 2754
- [logging level ethdstats](#), on page 2755
- [logging level ethpm](#), on page 2756
- [logging level ethpm link](#), on page 2757
- [logging level evb](#), on page 2758
- [logging level evmc](#), on page 2759
- [logging level evmed](#), on page 2760
- [logging level evms](#), on page 2761
- [logging level fabric forwarding](#), on page 2762
- [logging level fcoe_mgr](#), on page 2763
- [logging level feature-mgr](#), on page 2764
- [logging level fs-daemon](#), on page 2765
- [logging level gpixm](#), on page 2766
- [logging level hardware-telemetry](#), on page 2767
- [logging level hsrp](#), on page 2768
- [logging level icam](#), on page 2769
- [logging level igmp](#), on page 2770
- [logging level im](#), on page 2771
- [logging level imp](#), on page 2772
- [logging level interface-vlan](#), on page 2773
- [logging level ip pim](#), on page 2774
- [logging level ip sla responder](#), on page 2775
- [logging level ip sla sender](#), on page 2776
- [logging level ip sla twamp-server](#), on page 2777
- [logging level ipconf](#), on page 2778
- [logging level ipfib](#), on page 2779

- [logging level ipqos](#), on page 2780
- [logging level ipv6 pim](#), on page 2781
- [logging level iscm](#), on page 2782
- [logging level iscm](#), on page 2783
- [logging level isis](#), on page 2784
- [logging level keystore](#), on page 2785
- [logging level l2fm](#), on page 2786
- [logging level l2rib](#), on page 2787
- [logging level l3vm](#), on page 2788
- [logging level lacp](#), on page 2789
- [logging level ldap](#), on page 2790
- [logging level lem-mgr](#), on page 2791
- [logging level license](#), on page 2792
- [logging level lim](#), on page 2793
- [logging level lisp](#), on page 2794
- [logging level lldp](#), on page 2795
- [logging level m2rib](#), on page 2796
- [logging level mfdm](#), on page 2797
- [logging level mfwd](#), on page 2798
- [logging level mmode](#), on page 2799
- [logging level module](#), on page 2800
- [logging level monitor](#), on page 2801
- [logging level msdp](#), on page 2802
- [logging level mvsh](#), on page 2803
- [logging level nat](#), on page 2804
- [logging level nbm](#), on page 2805
- [logging level netstack](#), on page 2806
- [logging level nfm](#), on page 2807
- [logging level ngoam](#), on page 2808
- [logging level npv](#), on page 2809
- [logging level ntp](#), on page 2810
- [logging level nxsdk](#), on page 2811
- [logging level openflow](#), on page 2812
- [logging level orib](#), on page 2813
- [logging level ospf](#), on page 2814
- [logging level ospfv3](#), on page 2815
- [logging level pfstat](#), on page 2816
- [logging level pixm](#), on page 2817
- [logging level pktmgr](#), on page 2818
- [logging level platform](#), on page 2819
- [logging level plbm](#), on page 2820
- [logging level plcmgr](#), on page 2821
- [logging level pltfm_config](#), on page 2822
- [logging level plugin](#), on page 2823
- [logging level poap](#), on page 2824
- [logging level poed](#), on page 2825

- logging level port-profile, on page 2826
- logging level port-resources, on page 2827
- logging level port-security, on page 2828
- logging level port, on page 2829
- logging level port_client, on page 2830
- logging level port_lb, on page 2831
- logging level port link-failure, on page 2832
- logging level private-vlan, on page 2833
- logging level ptp, on page 2834
- logging level radius, on page 2835
- logging level res_mgr, on page 2836
- logging level rip, on page 2837
- logging level rpm, on page 2838
- logging level rsvp, on page 2839
- logging level sal, on page 2840
- logging level san, on page 2841
- logging level scheduler, on page 2842
- logging level security, on page 2843
- logging level session-mgr, on page 2844
- logging level sflow, on page 2845
- logging level smartc, on page 2846
- logging level smm, on page 2847
- logging level snmpd, on page 2848
- logging level snmpmib_proc, on page 2849
- logging level spanning, on page 2850
- logging level spm, on page 2851
- logging level stripcl, on page 2852
- logging level sysmgr, on page 2853
- logging level tacacs, on page 2854
- logging level tamnw, on page 2855
- logging level track, on page 2856
- logging level tunnel, on page 2857
- logging level u2rib, on page 2858
- logging level u6rib, on page 2859
- logging level udld, on page 2860
- logging level ufdm, on page 2861
- logging level urib, on page 2862
- logging level vdc_mgr, on page 2863
- logging level virtual-service, on page 2864
- logging level vlan_mgr, on page 2865
- logging level vmm, on page 2866
- logging level vmtracker, on page 2867
- logging level vpc, on page 2868
- logging level vrrp, on page 2869
- logging level vrrpv3, on page 2870
- logging level vsan, on page 2871

- [logging level vshd, on page 2872](#)
- [logging level vtp, on page 2873](#)
- [logging level wwnm, on page 2874](#)
- [logging level xbar, on page 2875](#)
- [logging logfile, on page 2876](#)
- [logging message interface type ethernet, on page 2877](#)
- [logging module, on page 2878](#)
- [logging monitor, on page 2879](#)
- [logging origin-id, on page 2880](#)
- [logging rate-limit, on page 2881](#)
- [logging server, on page 2882](#)
- [logging server dns-refresh-interval, on page 2884](#)
- [logging source-interface, on page 2885](#)
- [logging timestamp, on page 2886](#)
- [login on-failure log, on page 2887](#)
- [login on-success log, on page 2888](#)
- [logout-warning, on page 2889](#)
- [low-memory exempt, on page 2890](#)
- [lshow, on page 2891](#)
- [lshow, on page 2892](#)
- [lsp-gen-interval, on page 2893](#)
- [lsp-gen-interval, on page 2894](#)
- [lsp-gen-interval, on page 2895](#)
- [lsp-mtu, on page 2896](#)
- [lsp-mtu, on page 2897](#)
- [lsp-mtu, on page 2898](#)
- [lsp, on page 2899](#)
- [lsp, on page 2900](#)
- [lsp attributes, on page 2901](#)

l2rib dup-host-mac-detection

{ no l2rib dup-host-mac-detection } | { l2rib dup-host-mac-detection <num-of-moves> <duration> }

Syntax Description

no	Negate a command or set its defaults
l2rib	Layer 2 routing information base
dup-host-mac-detection	Set Duplicate-Host-MAC-Detection parameters
<i>num-of-moves</i>	Number of host moves to be allowed
<i>duration</i>	Duplicate detection timeout in secs for host moves

Command Mode

- /exec/configure

l2rib dup-host-mac-recovery

{ no l2rib dup-host-mac-recovery } | { l2rib dup-host-mac-recovery <timeout> <retry-count> }

Syntax Description

no	Negate a command or set its defaults
l2rib	Layer 2 routing information base
dup-host-mac-recovery	Set Duplicate-Host-MAC-Recovery (Unfreeze) parameters
<i>timeout</i>	Unfreeze timeout (secs)
<i>retry-count</i>	Unfreeze retry count

Command Mode

- /exec/configure

l2rib event-history size

```
l2rib event-history { client-tbl | ead-pl | errors | mac | mac-ip | misc-obj | rmac | topology | tx-infra | server }
size { default | medium | high | very-high }
```

Syntax Description

l2rib	Layer 2 routing information base
event-history	Set event-history size for L2RIB
client-tbl	L2RIB Client, Producer, Consumer Tables Event Logs
ead-pl	L2RIB EAD, Path-List Objects Event Logs
errors	L2RIB Error Logs
mac	L2RIB MAC Object Event Logs
mac-ip	L2RIB MAC Object Event Logs
misc-obj	L2RIB IMET, Flood-List, ARP-Signal, Peer ID, Startup-Routes Objects Event Logs
rmac	L2RIB Router MAC Object Event Logs
topology	L2RIB Topology Object Event Logs
tx-infra	L2RIB TxList, TxSend, TxThread Event Logs
server	L2RIB Sysmgr, PSS, HA Logs
size	Size
default	Default (Low)
medium	Medium
high	High
very-high	Very High

Command Mode

- /exec/configure

l3vm event-history

```
[no] l3vm event-history { pss | errors | mts | reinit | cli | vrf | topology } { size { <size_in_text> | <size_in_Kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
l3vm	Debug L3VM information
event-history	log debug events into event history buffer
pss	L3VM pss operation
errors	L3VM errors
mts	L3VM MTS messages
reinit	L3VM reinit events
cli	Log L3VM CLI related events
vrf	Log VRF related events
topology	Log Topology related events
size	Configure the size of the event-hist buffer
<i>size_in_text</i>	Buffer size
<i>size_in_Kbytes</i>	Size of the file in kbytes

Command Mode

- /exec

label-allocation-mode per-vrf

[no] label-allocation-mode per-vrf

Syntax Description

no	(Optional) Negate a command or set its defaults
label-allocation-mode	Configure label allocation mode
per-vrf	per VRF label allocation mode

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

label allocate global

[no] label allocate global { all-routes | host-routes | prefix-list <pfx-list> }

Syntax Description

no	(Optional) Negate a command or set its defaults
label	LDP label configuration
allocate	Allocate local labels
global	Specify default VPN Routing/Forwarding instance
all-routes	Allocate local labels for all routes
host-routes	Allocate local labels for host routes only (default)
prefix-list	Specify a prefix-list for local label filtering
<i>pfx-list</i>	IP prefix-list for destination prefixes

Command Mode

- /exec/configure/ldp

lacp fast-select-hot-standby

lacp fast-select-hot-standby | no lacp fast-select-hot-standby

Syntax Description

no	Negate a command or set its defaults
lacp	Set LACP parameters for the interface
fast-select-hot-standby	Configure fast select for hot standby ports. Enabling this feature will allow fast selection of hot standby port when last active port in the port-channel is going down.

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

lACP graceful-convergence

lACP graceful-convergence | no lACP graceful-convergence

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
graceful-convergence	Configure port-channel lACP graceful convergence. Disable this only with lACP ports connected to Non-Nexus peer. Disabling this with Nexus peer can lead to port suspension

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

lACP max-bundle

lACP max-bundle <max-bundle-number> | no lACP max-bundle [<max-bundle-number>]

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
max-bundle	Configure the port-channel max-bundle
<i>max-bundle-number</i>	Enter the max-bundle number

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel
/exec/configure/if-eth-port-channel-p2p

lACP min-links

lACP min-links <min-links-number> | no lACP min-links [<min-links-number>]

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
min-links	Configure the port-channel min-links
<i>min-links-number</i>	Enter the min-link number

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

lacp mode delay

[no] lacp mode delay

Syntax Description

no	(Optional) Negate a command or set its defaults
lacp	Set LACP parameters for the interface
mode	Enter the LACP mode
delay	Configure delayed lacp on the port-channel

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel
/exec/configure/if-eth-port-channel-p2p

lACP mode delay

[no] lACP mode delay

Syntax Description

no	(Optional) Negate a command or set its defaults
lACP	Set LACP parameters for the interface
mode	Enter the LACP mode
delay	Configure delayed lACP on the port-channel

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel
/exec/configure/if-eth-port-channel-p2p

lacp port-priority

lacp port-priority <port-pri> | no lacp port-priority

Syntax Description

no	Negate a command or set its defaults
lacp	Set LACP parameters for the interface
port-priority	Set LACP port priority
<i>port-pri</i>	Enter port priority

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

lacp rapid-transition

lacp rapid-transition | no lacp rapid-transition

Syntax Description

no	Negate a command or set its defaults
lacp	Set LACP parameters for the interface
rapid-transition	Optimizes LACP timers for rapid transition from P->I, I->P state

Command Mode

- /exec/configure

lACP rate

[no] lACP rate

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
rate	Configure rate at which PDUs are sent by LACP

Command Mode

- /exec/configure/if-ethernet /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-ethernet-m /exec/configure/if-ethernet-switch-m /exec/configure/if-remote-ethernet /exec/configure/if-remote-ethernet-switch

lacp rate

lacp rate <rate_type>

Syntax Description

lacp	Set LACP parameters for the interface
rate	Configure rate at which PDUs are sent by LACP
<i>rate_type</i>	Rate type

Command Mode

- /exec/configure/if-ethernet /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-ethernet-m /exec/configure/if-ethernet-switch-m /exec/configure/if-remote-ethernet /exec/configure/if-remote-ethernet-switch

lacp suspend-individual

lacp suspend-individual | no lacp suspend-individual

Syntax Description

no	Negate a command or set its defaults
lacp	Set LACP parameters for the interface
suspend-individual	Configure lacp port-channel state. Disabling this will cause lacp to put the port to individual state and not suspend the port in case it does not get LACP BPDU from the peer ports in the port-channel

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

lACP system-mac

lACP system-mac <mac-address> [role <role>] | no lACP system-mac

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
system-mac	Configure the MAC address to be used for the LACP Protocol exchanges
<i>mac-address</i>	MAC-address(FORMAT :xxxx.xxxx.xxxx)
role	(Optional) Configure the role for this Switch
<i>role</i>	(Optional) Role played by the Switch

Command Mode

- /exec/configure

lacp system-priority

lacp system-priority <sys-pri> | no lacp system-priority

Syntax Description

no	Negate a command or set its defaults
lacp	Set LACP parameters for the interface
system-priority	Set LACP system priority
<i>sys-pri</i>	Enter System Priority

Command Mode

- /exec/configure

lACP vPC-convergence

lACP vPC-convergence | no lACP vPC-convergence

Syntax Description

no	Negate a command or set its defaults
lACP	Set LACP parameters for the interface
vPC-convergence	Enable lACP convergence for vPC port channels.

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel
/exec/configure/if-eth-port-channel-p2p

last

| last [<lines>]

Syntax Description

	Pipe command output to filter
last	Display last lines
<i>lines</i>	(Optional) number of lines to print

Command Mode

- /output

latency

{ [no] latency <lat> | no latency }

Syntax Description

latency	Provide the latency value for this POSTCARD queue_profile
<i>lat</i>	queue_profile latency (nano seconds). Default is 2048 ns

Command Mode

- /exec/configure/config-postcard-q-prof

latency

{ [no] latency <lat> | no latency }

Syntax Description

latency	Provide the latency value for this INT queue_profile
<i>lat</i>	queue_profile latency (nano seconds). Default is 2048 ns

Command Mode

- /exec/configure/config-int-q-prof

latency quantization

{ [no] latency quantization <lat> | no latency quantization }

Syntax Description

latency	Provide the latency value for this POSTCARD flow-profile
quantization	Provide the latency value for this POSTCARD flow-profile
<i>lat</i>	flow-profile latency quantization. This value will be converted to a power of 2 (nanoseconds). For example, value of 11 will be converted to 2 power 11 which is 2048. This means that if the difference between ingress timestamp and egress timestamp is more than 2048 nanosec at any popostcard in the path, one upstream report or local report will be generated per flow. The allowed values are in range 0-31. Default is 11.

Command Mode

- /exec/configure/config-postcard-flow-prof

latency quantization

{ [no] latency quantization <lat> | no latency quantization }

Syntax Description

latency	Provide the latency value for this INT flow-profile
quantization	Provide the latency value for this INT flow-profile
<i>lat</i>	flow-profile latency quantization. This value will be converted to a power of 2 (nanoseconds). For example, value of 11 will be converted to 2 power 11 which is 2048. This means that if the difference between ingress timestamp and egress timestamp is more than 2048 nanosec at any point in the path, one upstream report or local report will be generated per flow. The allowed values are in range 0-28 Default is 11.

Command Mode

- /exec/configure/config-int-flow-prof

layer-2 multicast lookup mac

[no] layer-2 multicast lookup mac

Syntax Description

no	(Optional) Negate a command or set its defaults
layer-2	set layer2 multicast lkup mode
multicast	set layer2 multicast lkup mode
lookup	lkup type can be either mac or ip based
mac	set mac based multicast lkup mode

Command Mode

- /exec/configure/vlan-config /exec/configure/bdomain

layer-2 multicast lookup mac

[no] layer-2 multicast lookup mac

Syntax Description

no	(Optional) Negate a command or set its defaults
layer-2	set layer2 multicast lkup mode
multicast	set layer2 multicast lkup mode
lookup	lkup type can be either mac or ip based
mac	set mac based multicast lkup mode

Command Mode

- /exec/configure

layer2-switched flow monitor input

[no] layer2-switched flow monitor <monitorname> input

Syntax Description

layer2-switched	Configure L2 features
flow	NetFlow related commands
monitor	Apply a Flow Monitor to this interface
<i>monitorname</i>	Name of Flow Monitor
input	Apply Flow Monitor on input traffic

Command Mode

- /exec/configure/if-switching

layer3 peer-router

layer3 peer-router | no layer3 peer-router

Syntax Description

no	Negate a command or set its defaults
layer3	Enable layer 3 functionality
peer-router	no change for TTL of packets destined to the peer

Command Mode

- /exec/configure/vpc-domain

layer3 peer-router syslog

layer3 peer-router syslog [interval <syslog-interval>] | no layer3 peer-router syslog

Syntax Description

no	Negate a command or set its defaults
layer3	Enable layer 3 functionality
peer-router	no change for TTL of packets destined to the peer
syslog	print layer 3 protocol syslog
interval	(Optional) how frequent to print the syslog
<i>syslog-interval</i>	(Optional) how many seconds to print a syslog

Command Mode

- /exec/configure/vpc-domain

ldap-search-map

[no] ldap-search-map

Syntax Description

no	Negate a command or set its defaults
ldap-search-map	Set one of the configured search-map as active

Command Mode

- /exec/configure/ldap

ldap-search-map

ldap-search-map <s0>

Syntax Description

ldap-search-map	Set one of the configured search-map as active
<i>s0</i>	Name of the search-map

Command Mode

- /exec/configure/ldap

ldap-server deadtime

[no] ldap-server deadtime <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
ldap-server	Configure LDAP related parameters
deadtime	Global LDAP server deadtime period in seconds
<i>i0</i>	LDAP server deadtime period in minutes (default 0 mins -disabled)

Command Mode

- /exec/configure

ldap-server host

```
[no] ldap-server host { <hostipname> } [ { enable-ssl | port <i1> [ timeout <i2> ] | rootDN <s0> [ password
{ 7 <s1> { { [ port1 <i3> [ timeout1 <i4> ] } } | [ timeout5 <i9> ] } } | <s2> { { [ port2 <i5> [ timeout2 <i6>
] } } | [ timeout4 <i8> ] } } } ] | timeout3 <i7> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ldap-server	Configure LDAP related parameters
host	LDAP server's DNS name or IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name
enable-ssl	(Optional) LDAP server enable ssl
port	(Optional) LDAP server's port (default: global config)
<i>i1</i>	(Optional) port number
timeout	(Optional) LDAP server timeout period in seconds
<i>i2</i>	(Optional) LDAP server timeout in seconds (default: global config)
rootDN	(Optional) LDAP server root DN
<i>s0</i>	(Optional) root DN
password	(Optional) LDAP server root password
7	(Optional) LDAP root password (encrypted)
<i>s1</i>	(Optional) password (encrypted)
port1	(Optional) LDAP server's port (default: global config)
<i>i3</i>	(Optional) port number
timeout1	(Optional) LDAP server timeout period in seconds
<i>i4</i>	(Optional) LDAP server timeout in seconds (default: global config)
<i>s2</i>	(Optional) password (clear text)
port2	(Optional) LDAP server's port (default: global config)
<i>i5</i>	(Optional) port number
timeout2	(Optional) LDAP server timeout period in seconds
<i>i6</i>	(Optional) LDAP server timeout in seconds (default: global config)
timeout3	(Optional) LDAP server timeout period in seconds

<i>i7</i>	(Optional) LDAP server timeout in seconds (default: global config)
timeout4	(Optional) LDAP server timeout period in seconds
<i>i8</i>	(Optional) LDAP server timeout in seconds (default: global config)
timeout5	(Optional) LDAP server timeout period in seconds
<i>i9</i>	(Optional) LDAP server timeout in seconds (default: global config)

Command Mode

- /exec/configure

ldap-server host test rootDN

```
[no] ldap-server host { <hostipname> } test rootDN <r1> { { [ username <s0> { [ password { [ 7 <s2> | <s1> ] } [ idle-time <i1> ] ] | [ idle-time <i1> ] } ] } | { [ password { [ 7 <s2> | <s1> ] } [ idle-time <i1> ] ] } | { [ idle-time <i1> ] } }
```

Syntax Description

<i>username</i>	(Optional) <s0>
no	(Optional) Negate a command or set its defaults
ldap-server	Configure LDAP related parameters
host	LDAP server's IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name
test	Parameters to send test packets
7	(Optional) LDAP test password (encrypted)
<i>s0</i>	(Optional) user name
password	(Optional) user password in test packets
<i>s1</i>	(Optional) test password
<i>s2</i>	(Optional) test password (encrypted)
rootDN	rootDN in test packets
<i>r1</i>	root DN
idle-time	(Optional) time interval for monitoring the server
<i>i1</i>	(Optional) time period in minutes

Command Mode

- /exec/configure

ldap-server port

[no] ldap-server port <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
ldap-server	Configure LDAP related parameters
port	Global LDAP server's port (default 389)
<i>i0</i>	port number

Command Mode

- /exec/configure

ldap-server timeout

[no] ldap-server timeout <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
ldap-server	Configure LDAP related parameters
timeout	Global LDAP server timeout period in seconds
<i>i0</i>	LDAP server timeout period in seconds (default 5 sec)

Command Mode

- /exec/configure

ldap search-map

[no] ldap search-map <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
ldap	Configure information about ldap
search-map	Configure the search-map
s0	Search Map Name

Command Mode

- /exec/configure

less

| less [-d | -E] +

Syntax Description

	Pipe command output to filter
less	Filter for paging
-d	(Optional) dumb terminal
-E	(Optional) quit at end of file

Command Mode

- /output

license expiry check_interval

license expiry check_interval <i0>

Syntax Description

license	Enter the license configuration mode
expiry	Configure the expiry check interval
check_interval	Configure the expiry check interval
<i>i0</i>	Specify the license expiry check interval in seconds

Command Mode

- /exec

limit-resource m4route-mem maximum equal-to-min

```
{ limit-resource m4route-mem [ minimum { <min> | <min-hi> } ] maximum { <max-lo> | <max> | <max-hi>
| equal-to-min } } | { no limit-resource m4route-mem [ [ minimum { <min> | <min-hi> } ] maximum {
<max-lo> | <max> | <max-hi> | equal-to-min } ] }
```

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
m4route-mem	set ipv4 route memory limits
minimum	(Optional) minimum route memory to allocate
<i>min</i>	(Optional) minimum route memory value
<i>min-hi</i>	(Optional) minimum route memory value
maximum	maximum route memory to allocate
<i>max-lo</i>	maximum route memory value
<i>max</i>	maximum route memory value
<i>max-hi</i>	maximum route memory value
equal-to-min	maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

Usage Guidelines



Note

You can set only one value for the resource maximum or minimum limits. If you specify a minimum limit, the maximum limit is ignored, but that value is displayed for both the minimum and maximum limits. If you specify only a maximum limit, that value is displayed for both the minimum and maximum limits.

limit-resource m6route-mem maximum

```
{ limit-resource m6route-mem [ minimum { <min> | <min-hi> } ] maximum { <max-lo> | <max> | <max-hi>
} } | { no limit-resource m6route-mem [ [ minimum { <min> | <min-hi> } ] maximum { <max-lo> | <max>
| <max-hi> } ] }
```

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
m6route-mem	set ipv6 route memory limits
minimum	(Optional) minimum route memory to allocate
<i>min</i>	(Optional) minimum route memory value
<i>min-hi</i>	(Optional) minimum route memory value
maximum	maximum route memory to allocate
<i>max-lo</i>	maximum route memory value
<i>max</i>	maximum route memory value
<i>max-hi</i>	maximum route memory value

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

Usage Guidelines



Note You can set only one value for the resource maximum or minimum limits. If you specify a minimum limit, the maximum limit is ignored, but that value is displayed for both the minimum and maximum limits. If you specify only a maximum limit, that value is displayed for both the minimum and maximum limits.

limit-resource module-type

{ limit-resource module-type <card-type> + } | { no limit-resource module-type }

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
module-type	Controls which type of modules are allowed in this vdc
<i>card-type</i>	Allowed module types

Command Mode

- /exec/configure/vdc

limit-resource monitor-session-erspan-dst minimum maximum equal-to-min

```
{ limit-resource monitor-session-erspan-dst minimum <min-val> maximum { <max-val> | equal-to-min } }
| { no limit-resource monitor-session-erspan-dst [ minimum <min-val> maximum { <max-val> | equal-to-min
} ] }
```

Syntax Description

limit-resource	Resource configuration
monitor-session-erspan-dst	Monitor erspan destination session
minimum	minimum monitor erspan-dst session to allocate
<i>min-val</i>	minimum monitor erspan-dst session value
maximum	maximum monitor erspan-dst session to allocate
<i>max-val</i>	maximum monitor erspan-dst session value
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit-resource monitor-session-inband-src minimum maximum equal-to-min

```
{ limit-resource monitor-session-inband-src minimum <min-val> maximum { <max-val> | equal-to-min } }
| { no limit-resource monitor-session-inband-src [ minimum <min-val> maximum { <max-val> | equal-to-min
} ] }
```

Syntax Description

limit-resource	Resource configuration
monitor-session-inband-src	Monitor inband source
minimum	minimum monitor inband source to allocate
<i>min-val</i>	minimum monitor inband source value
maximum	maximum monitor inband source to allocate
<i>max-val</i>	maximum monitor inband source value
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit-resource monitor-session minimum maximum equal-to-min

```
{ limit-resource monitor-session minimum <min-val> maximum { <max-val> | equal-to-min } } | { no
limit-resource monitor-session [ minimum <min-val> maximum { <max-val> | equal-to-min } ] }
```

Syntax Description

limit-resource	Resource configuration
monitor-session	Monitor local/erspan-source session
minimum	minimum monitor local session to allocate
<i>min-val</i>	minimum monitor local session value
maximum	maximum monitor local session to allocate
<i>max-val</i>	maximum monitor local session value
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit-resource port-channel minimum maximum

limit-resource port-channel minimum <min-val> maximum { <max-val> | equal-to-min } | no limit-resource port-channel [minimum <min-val> maximum { <max-val> | equal-to-min }]

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
port-channel	set port-channel limits
minimum	minimum port-channels to allocate
<i>min-val</i>	
maximum	maximum port-channels to allocate
<i>max-val</i>	
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit-resource u4route-mem maximum equal-to-min

```
{ limit-resource u4route-mem [ minimum { <min-lo> | <min> | <min-hi> } ] maximum { <max-lo> | <max>
| <max-hi> | equal-to-min } } | { no limit-resource u4route-mem [ [ minimum { <min-lo> | <min> | <min-hi>
} ] maximum { <max-lo> | <max> | <max-hi> | equal-to-min } ] }
```

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
u4route-mem	set ipv4 route memory limits
minimum	(Optional) minimum route memory to allocate
<i>min-lo</i>	(Optional) minimum route memory value
<i>min</i>	(Optional) minimum route memory value
<i>min-hi</i>	(Optional) minimum route memory value
maximum	maximum route memory to allocate
<i>max-lo</i>	maximum route memory value
<i>max</i>	maximum route memory value
<i>max-hi</i>	maximum route memory value
equal-to-min	maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

Usage Guidelines



Note You can set only one value for the resource maximum or minimum limits. If you specify a minimum limit, the maximum limit is ignored, but that value is displayed for both the minimum and maximum limits. If you specify only a maximum limit, that value is displayed for both the minimum and maximum limits.

limit-resource u6route-mem maximum equal-to-min

```
{ limit-resource u6route-mem [ minimum { <min-lo> | <min> | <min-hi> } ] maximum { <max-lo> | <max>
| <max-hi> | equal-to-min } } | { no limit-resource u6route-mem [ [ minimum { <min-lo> | <min> | <min-hi>
} ] maximum { <max-lo> | <max> | <max-hi> | equal-to-min } ] }
```

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
u6route-mem	set ipv6 route memory limits
minimum	(Optional) minimum route memory to allocate
<i>min-lo</i>	(Optional) minimum route memory value
<i>min</i>	(Optional) minimum route memory value
<i>min</i>	(Optional) minimum route memory value
<i>min-hi</i>	(Optional) minimum route memory value
maximum	maximum route memory to allocate
<i>max-lo</i>	maximum route memory value
<i>max</i>	maximum route memory value
<i>max-hi</i>	maximum route memory value
equal-to-min	maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

Usage Guidelines



Note You can set only one value for the resource maximum or minimum limits. If you specify a minimum limit, the maximum limit is ignored, but that value is displayed for both the minimum and maximum limits. If you specify only a maximum limit, that value is displayed for both the minimum and maximum limits.

limit-resource vlan minimum maximum equal-to-min

{ limit-resource vlan minimum <min-val> maximum { <max-val> | equal-to-min } } | { no limit-resource vlan [minimum <min-val> maximum { <max-val> | equal-to-min }] }

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
vlan	set VLAN limits
minimum	minimum VLANs to allocate
<i>min-val</i>	minimum VLANs value
maximum	maximum VLANs to allocate
<i>max-val</i>	maximum VLANs value
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit-resource vrf minimum maximum equal-to-min

```
{ limit-resource vrf minimum <number1> maximum { <number2> | equal-to-min } } | { no limit-resource vrf [ minimum <number1> maximum { <number2> | equal-to-min } ] }
```

Syntax Description

no	Negate a command or set its defaults
limit-resource	Resource configuration
vrf	set vrf resource limits
minimum	minimum vrf resources to allocate
<i>number1</i>	minimum vrf resource value
maximum	maximum vrf resources to allocate
<i>number2</i>	maximum vrf resource value
equal-to-min	set maximum value equal to min

Command Mode

- /exec/configure/vdc-template /exec/configure/vdc

limit address-count

[no] limit address-count <addr_count>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>addr_count</i>	maximum value

Command Mode

- /exec/configure/config-snoop-policy

line console

[no] line console

Syntax Description

no	(Optional) Negate a command or set its defaults
line	Configure a terminal line
console	Primary terminal line

Command Mode

- /exec/configure

line console

[no] line console

Syntax Description

no	(Optional) Negate a command or set its defaults
line	Configure a terminal line
console	Primary terminal line

Command Mode

- /exec/configure

line vty

line vty

Syntax Description

line	Configure a terminal line
vty	Virtual terminal line

Command Mode

- /exec/configure

line vty

[no] line vty

Syntax Description

no	Negate a command or set its defaults
line	Configure a terminal line
vty	Virtual terminal line

Command Mode

- /exec/configure

link-management timers bandwidth

[no] link-management timers { bandwidth-hold | periodic-flooding } | link-management timers { bandwidth-hold <bw_seconds> | periodic-flooding <flood_seconds> }

Syntax Description

no	Negate a command or set its defaults
link-management	Link Management configuration
timers	Link Management timers configuration
bandwidth-hold	Link Management bandwidth hold timer
<i>bw_seconds</i>	seconds
periodic-flooding	Link Management periodic flooding interval
<i>flood_seconds</i>	seconds [0 to disable, minimum set to 30]

Command Mode

- /exec/configure/te

link-state-trap

[no] link-state-trap

Syntax Description

no	(Optional) Negate a command or set its defaults
link-state-trap	Enable/disable link state change traps

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-fcip /exec/configure/if-iscsi

link debounce

```
link debounce { [ link-up [ time <time_val_link_up> ] ] | [ time <time_val> ] } | no link debounce [ link-up ]
```

Syntax Description

no	Negate a command or set its defaults
link	Configure link
debounce	Configure link debounce timer
link-up	(Optional) Timer for the link-up event
time	(Optional) Link debounce time
<i>time_val</i>	(Optional) Timer value (in milliseconds)
<i>time_val_link_up</i>	(Optional) Timer value (in milliseconds)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

link rxlos

link rxlos [algo <algo_val>] | no link rxlos [algo <algo_val>]

Syntax Description

no	Negate a command or set its defaults
link	Configure link
rxlos	Configure link rxlos algo
algo	(Optional) Link rxlos algo control
<i>algo_val</i>	(Optional) rxlos control options

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-sub

link transmit reset-skip

{ link transmit reset-skip | no link transmit reset-skip }

Syntax Description

no	Negate a command or set its defaults
link	Configure link
transmit	Configure link transmit for interface
reset-skip	Configure link transmit for interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

lisp

```
{ lisp-lig | lig } { version | self | self6 | <hostname> | { <eid> | <eid6> } } [ source { <seid> | <seid6> } ] [ to
{ <mr-hostname> | { <mr> | <mr6> } } ] [ count <count> ] [ probe ] [ vrf { <vrf-name> | <vrf-known-name>
} ]
```

Syntax Description

lisp-lig	LISP Internet Groper
lig	LISP Internet Groper
<i>eid</i>	LIG on a IPv4 Endpoint ID (EID)
version	Display Internet Draft version lig supports
self	Test if IPv4 EID-prefix registered in mapping database
self6	Test if IPv6 EID-prefix registered in mapping database
<i>hostname</i>	DNS name for Endpoint ID (EID)
source	(Optional) Provide source EID for Map-Request
<i>seid</i>	(Optional) Source IPv4 Endpoint ID (EID)
to	(Optional) Where to send the Map-Request
<i>mr-hostname</i>	(Optional) DNS name for Map-Resolver
<i>mr</i>	(Optional) Map-Resolver IPv4 address to send Map-Request to
count	(Optional) Map-Requests to send before Map-Reply returned
<i>count</i>	(Optional) Number of Map-Requests
probe	(Optional) RLOC-probe each locator
vrf	(Optional) LIGing for specific VRF
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

lisp ddt

```
{ [ no ] lisp ddt }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ddt	Configures a LISP-DDT mapping system functionality

Command Mode

- /exec/configure /exec/configure/vrf

lisp ddt authoritative-prefix eid-prefix

```
{ [ no ] lisp ddt authoritative-prefix eid-prefix { <eid-prefix> | <eid-prefix6> } } | { [ no ] lisp ddt
authoritative-prefix instance-id <iid> [ eid-prefix { <eid-prefix> | <eid-prefix6> } ] } | { [ no ] lisp ddt
authoritative-prefix <star> } | { [ no ] lisp ddt authoritative-prefix instance-id { <iidp> | <range> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ddt	Configure LISP-DDT parameters
authoritative-prefix	Configure EID-prefix this LISP-DDT node is authoritative for
instance-id	Instance ID of VPN for EID-prefix
<i>iid</i>	Instance-ID value
star	Authoritative prefix on root for all address space
<i>iidp</i>	Instance-ID in prefix format
<i>range</i>	Instance-ID range in 'x-y' format where y > x
eid-prefix	Authoritative IPv4 or IPv6 EID-prefix
<i>eid-prefix</i>	EID-prefix in IPv4 slash format

Command Mode

- /exec/configure /exec/configure/vrf

lisp ddt delegate eid-prefix

```
{ [ no ] lisp ddt delegate { <node> | <node6> } { eid-prefix { <eid-prefix> | <eid-prefix6> } } [ priority
<priority> weight <weight> ] [ public-key <key> ] [ map-server ] } | { [ no ] lisp ddt delegate { <node> |
<node6> } instance-id <iid> [ eid-prefix { <eid-prefix> | <eid-prefix6> } ] [ priority <priority> weight <weight>
] [ public-key <key> ] [ map-server ] } | { [ no ] lisp ddt delegate { <node> | <node6> } instance-id { <iidp>
| <range> } [ priority <priority> weight <weight> ] [ public-key <key> ] [ map-server ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ddt	Configure LISP-DDT parameters
delegate	Configure LISP-DDT child in delegation hierarchy
<i>node</i>	IPv4 locator address of DDT node
instance-id	Instance ID of VPN for EID-prefix
<i>iid</i>	Instance-ID value
<i>iidp</i>	Instance-ID in prefix format
<i>range</i>	Instance-ID range in 'x-y' format where y > x
eid-prefix	Child delegation for IPv4 or IPv6 EID-prefix
<i>eid-prefix</i>	EID-prefix in IPv4 slash format
priority	(Optional) Configures which Locators from a set are preferred
<i>priority</i>	(Optional) Lower priority Locator takes preference
weight	(Optional) Traffic load-spreading among Locators
<i>weight</i>	(Optional) Specified in a percentage from 0 to 100
map-server	(Optional) Child delegate is a Map-Server
public-key	(Optional) DDT child's public key this DDT-node supplies for referrals
<i>key</i>	(Optional) RSA public-key

Command Mode

- /exec/configure /exec/configure/vrf

lisp ddt map-server-peer eid-prefix

```
{ [ no ] lisp ddt map-server-peer { <node> | <node6> } { eid-prefix { <eid-prefix> | <eid-prefix6> } } [ priority <priority> weight <weight> ] [ public-key <key> ] } | { [ no ] lisp ddt map-server-peer { <node> | <node6> } instance-id <iid> [ eid-prefix { <eid-prefix> | <eid-prefix6> } ] [ priority <priority> weight <weight> ] [ public-key <key> ] } | { [ no ] lisp ddt map-server-peer { <node> | <node6> } instance-id { <iidp> | <range> } [ priority <priority> weight <weight> ] [ public-key <key> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ddt	Configure LISP-DDT parameters
map-server-peer	Configure other map-server peers
<i>node</i>	IPv4 locator address of DDT node
instance-id	Instance ID of VPN for EID-prefix
<i>iid</i>	Instance-ID value
<i>iidp</i>	Instance-ID in prefix format
<i>range</i>	Instance-ID range in 'x-y' format where y > x
eid-prefix	Child delegation for IPv4 or IPv6 EID-prefix
<i>eid-prefix</i>	EID-prefix in IPv4 slash format
priority	(Optional) Configures which Locators from a set are preferred
<i>priority</i>	(Optional) Lower priority Locator takes preference
weight	(Optional) Traffic load-spreading among Locators
<i>weight</i>	(Optional) Specified in a percentage from 0 to 100
public-key	(Optional) DDT child's public key this DDT-node supplies for referrals
<i>key</i>	(Optional) RSA public-key

Command Mode

- /exec/configure /exec/configure/vrf

lisp ddt root

[no] lisp ddt root { <root> | <root6> } [public-key <key>]

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
ddt	Configure LISP-DDT parameters
root	Configure LISP-DDT root of tree in Map-Resolver
<i>root</i>	IPv4 locator address of DDT root
public-key	(Optional) DDT root's public key used to verify signed Map-Referrals
<i>key</i>	(Optional) RSA public-key

Command Mode

- /exec/configure /exec/configure/vrf

lisp dynamic-eid

```
{ [ no ] lisp dynamic-eid <dyn-eid-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
dynamic-eid	Configure dynamic-EIDs for roaming
<i>dyn-eid-name</i>	Name your dynamic-EID

Command Mode

- /exec/configure

lisp dynamic-eid

```
{ [ no ] lisp dynamic-eid <dyn-eid-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
dynamic-eid	Configure dynamic-EIDs for roaming
<i>dyn-eid-name</i>	Name your dynamic-EID

Command Mode

- /exec/configure/vrf

lisp explicit-locator-path

[no] lisp explicit-locator-path <elp-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
explicit-locator-path	Configures a LISP Explicit Locator Path (ELP)
<i>elp-name</i>	Name of LISP ELP

Command Mode

- /exec/configure/vrf

lisp explicit-locator-path

```
{ [ no ] lisp explicit-locator-path <elp-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
explicit-locator-path	Configures a LISP Explicit Locator Path (ELP)
<i>elp-name</i>	Name of LISP ELP

Command Mode

- /exec/configure

lisp extended-subnet-mode

{ [no] lisp extended-subnet-mode }

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP interface configuration commands
extended-subnet-mode	Create dynamic-EID state when EIDs reside on their home subnet

Command Mode

- /exec/configure/if-igp

lisp geo-coordinates

[no] lisp geo-coordinates <latitude> <longitude> [<altitude>]

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
geo-coordinates	Configure Geo Coordinates for this router
<i>latitude</i>	Latitude in DMS format: 'degree-min-sec-N' or 'degree-min-sec-S'
<i>longitude</i>	Longitude in DMS format: 'degree-min-sec-E' or 'degree-min-sec-W' format
<i>altitude</i>	(Optional) Altitude in meters above sea-level

Command Mode

- /exec/configure /exec/configure/vrf

lisp instance-id

[no] lisp instance-id <iid>

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
instance-id	Configures Instance-ID for global data-mappings
<i>iid</i>	24-bit instance-ID value

Command Mode

- /exec/configure /exec/configure/vrf

lisp loc-reach-algorithm

```
[no] lisp loc-reach-algorithm { count-tcp | echo-nonce | { rloc-probing [ map-request-on-failure ] } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
loc-reach-algorithm	Configure locator reachability algorithm
count-tcp	Count TCP SYNs and ACKs
echo-nonce	Request for nonce to echo back in data-plane
rloc-probing	Probe each high-priority RLOC with Map-Request as last resort
map-request-on-failure	(Optional) Send Map-Request to database mapping system when any RLOC for a map-cache entry becomes RLOC-probing unreachable

Command Mode

- /exec/configure /exec/configure/vrf

lisp merge-registrations site-id

[no] lisp merge-registrations site-id <site-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
merge-registrations	ETRs merge registrations from Map-Notify messages
site-id	Configure site-id value for each xTR at site
<i>site-id</i>	Site-ID to group xTRs together

Command Mode

- /exec/configure /exec/configure/vrf

lisp mobility

[no] lisp mobility <dyn-eid-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP interface configuration commands
mobility	Configures to allow EID mobility on interface
<i>dyn-eid-name</i>	Name of the dynamic-EID to use

Command Mode

- /exec/configure/if-igp

lisp mobility test-liveness

[no] lisp mobility test-liveness

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP interface configuration commands
mobility	Configures to allow EID mobility on interface
test-liveness	Ping discovered dyn-eid hosts on this interface periodically to determine host liveness

Command Mode

- /exec/configure/if-igp

lisp security

[no] lisp security [strong]

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
security	Configure LISP-SEC on ITR or PITR
strong	(Optional) Reject Map-Replies without LISP-SEC signatures included

Command Mode

- /exec/configure /exec/configure/vrf

lisp site

```
{ [ no ] lisp site <site-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
site	Configures LISP sites in a map-server
<i>site-name</i>	Name your LISP site

Command Mode

- /exec/configure/vrf

lisp site

```
{ [ no ] lisp site <site-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
site	Configures LISP sites in a map-server
<i>site-name</i>	Name your LISP site

Command Mode

- /exec/configure

lisp smr-locators

[no] lisp smr-locators

Syntax Description

no	(Optional) Negate a command or set its defaults
lisp	LISP global configuration commands
smr-locators	Send SMR to all RLOCs in locator-set for map-cache entry

Command Mode

- /exec/configure

lisp to

```
{ lisp-rig | rig } [ instance-id <iid> ] { <hostname> | { <eid> | <eid6> } } to { <ddt-hostname> | { <ddt> | <ddt6> } }
```

Syntax Description

lisp-rig	LISP-DDT Referral Internet Groper
rig	LISP-DDT Referral Internet Groper
instance-id	(Optional) Instance-ID of VPN EID resides in
<i>iid</i>	(Optional) 24-bit instance-ID value
<i>eid</i>	RIG on a IPv4 Endpoint ID (EID)
<i>hostname</i>	DNS name for Endpoint ID (EID)
to	Where to send the Map-Request
<i>ddt-hostname</i>	DNS name for DDT-node
<i>ddt</i>	DDT-node IPv4 address to send Map-Request to

Command Mode

- /exec

list

list [<index>]

Syntax Description

list	Re-list all or part of the explicit path entries
<i>index</i>	(Optional) List starting at entry index number

Command Mode

- /exec/configure/te/expl-path

list

list

Syntax Description

list	Re-list all of the attribute list entries
------	---

Command Mode

- /exec/configure/te/lsp-attr

listobject-boolean not

listobject-boolean <object-id> not

Syntax Description

listobject-boolean	Configure Object as member of tracking list
<i>object-id</i>	Tracked object
not	Negate Up status

Command Mode

- /exec/configure/tr-list-bool

listobject-weight weight threshold-weight

```
listobject-weight { <object-id> weight <weight-val> } | threshold-weight { weight-thresh { weightup
<up-weight> [ weightdown <down-weight> ] | weightdown <down-weight> [ weightup <up-weight> ] } } |
no threshold-weight weight-thresh
```

Syntax Description

no	Negate a command or set its defaults
listobject-weight	Configure Object as member of tracking list
<i>object-id</i>	Tracked Object
weight	Assign a weight to object
<i>weight-val</i>	Assign a weight to object
threshold-weight	Threshold parameters
weight-thresh	Weight threshold
weightup	Up threshold
<i>up-weight</i>	Up threshold weight
weightdown	(Optional) Down threshold
<i>down-weight</i>	(Optional) Down threshold weight

Command Mode

- /exec/configure/tr-list-thrw

listobject

[no] listobject <object-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
listobject	Configure Object as member of tracking list
<i>object-id</i>	Tracked Object

Command Mode

- /exec/configure/tr-list-thrw /exec/configure/tr-list-thrp /exec/configure/tr-list-bool

lldp

```
[no] lldp { holdtime <i0> | reinit <i1> | timer <i2> | portid-subtype <i3> | tlv-select { management-address |
port-description | port-vlan | power-management | system-capabilities | system-description | system-name |
dcbxp } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure global LLDP parameters
holdtime	Specify the holdtime (in sec) to be sent in packets
<i>i0</i>	holdtime in sec
reinit	Delay (in sec) for LLDP initialisation on any interface
<i>i1</i>	reinit in sec
timer	Specify the rate at which LLDP packets are sent (in sec)
<i>i2</i>	rate of packets in sec
portid-subtype	config portid subtype for LLDP TLV and SNMP MIBs
<i>i3</i>	0: long interface name (default), 1: short interface name
tlv-select	Selection of LLDP to send
management-address	Management Address TLV
port-description	Port Description TLV
port-vlan	Port Vlan ID TLV
power-management	IEEE 802.3 DTE Power via MDI TLV
system-capabilities	System Capabilities TLV
system-description	System Description TLV
system-name	System Name TLV
dcbxp	DCBXP TLVs

Command Mode

- /exec/configure

lldp dcbx version auto

lldp dcbx version auto

Syntax Description

lldp	Configure LLDP parameters
dcbx	Configure DCBX parameters
version	Change the DCBX protocol version
auto	Auto-detect the DCBX version

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp dcbx version cee

[no] lldp dcbx version { cee | ieee }

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure LLDP parameters
dcbx	Configure DCBX parameters
version	Change the DCBX protocol version
cee	The CEE version of DCBX
ieee	The IEEE 802.1 version of DCBX

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp eee rx_wake_time

[no] lldp eee { rx_wake_time <i0> | tx_wake_time <i1> }

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure LLDP parameters
eee	Configure LLDP EEE parameters
rx_wake_time	Specify the EEE rx wake time
<i>i0</i>	EEE rx wake time
tx_wake_time	Specify the EEE tx wake time
<i>i1</i>	EEE tx wake time

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp receive

[no] lldp receive

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
receive	Enable LLDP reception on interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp tlv-select eee

[no] lldp tlv-select eee

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
tlv-select	Configure EEE parameter
eee	Enable/Disable LLDP EEE TLV

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp tlv-select management-address v4

[no] lldp tlv-select management-address { v4 | v6 }

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure global LLDP parameters
tlv-select	Selection of LLDP to send
management-address	Management Address TLV
v4	Management Address TLV v4
v6	Management Address TLV v6

Command Mode

- /exec/configure

lldp tlv-set management-address

[no] lldp tlv-set management-address <ip-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
tlv-set	LLDP TLV configuration for interface
management-address	Management address to be sent in management-tlv of LLDPDU.
<i>ip-addr</i>	IP address in dotted decimal format i.i.i.i

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp tlv-set management-address ipv6

[no] lldp tlv-set management-address <ipv6-addr> ipv6

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
tlv-set	LLDP TLV configuration for interface
management-address	Management address to be sent in management-tlv of LLDPDU.
ipv6	IPV6

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp tlv-set vlan

[no] lldp tlv-set vlan [<vlan-id>]

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
tlv-set	LLDP TLV configuration for interface
vlan	VLAN-id whose SVI IP address should be used as management address in management-tlv of LLDPDU. Default is native VLAN.
<i>vlan-id</i>	(Optional) vlan-id within range of 1-4094

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

lldp transmit

[no] lldp transmit

Syntax Description

no	(Optional) Negate a command or set its defaults
lldp	Configure Interface LLDP parameters
transmit	Enable LLDP transmission on interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-gig-ether-all /exec/configure/if-gig-ether /exec/configure/if-eth-base /exec/configure/if-mgmt-ether

load-balance

```
[no] load-balance { [ method { src { ip | ip-l4port <src-protocol> range <src-x> <src-y> } | dst { ip-dst | ip-l4port <dst-protocol> range <dst-x> <dst-y> } } | buckets <num> | mask-position <mask> ] + }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
load-balance	ITD Loadbalance
method	(Optional) ITD Loadbalance method
src	(Optional) Source based parameters
dst	(Optional) Destination based parameters
ip	(Optional) IP
ip-l4port	(Optional) IP and L4 port
<i>src-protocol</i>	(Optional) Protocol
range	(Optional) Match only packets in the range of port numbers
<i>src-x</i>	(Optional)
<i>src-y</i>	(Optional)
ip-dst	(Optional) IP
<i>dst-protocol</i>	(Optional) Protocol
<i>dst-x</i>	(Optional)
<i>dst-y</i>	(Optional)
buckets	(Optional) Used to create the buckets for traffic distribution, and it should be in powers of 2
<i>num</i>	(Optional) Loadbalance bucket number
mask-position	(Optional) Loadbalance mask position
<i>mask</i>	(Optional) Loadbalance mask position number range 0-31 for IPv4 and 0-127 for IPv6

Command Mode

- /exec/configure/itd

load-balance

```
[no] load-balance { [ method { src { ip | ip-l4port <src-protocol> range <src-x> <src-y> } | dst { ip-dst | ip-l4port <dst-protocol> range <dst-x> <dst-y> } } | buckets <num> | mask-position <mask> ] + }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
load-balance	Loadbalance
method	(Optional) Loadbalance method
src	(Optional) Source based parameters
dst	(Optional) Destination based parameters
ip	(Optional) IP
ip-l4port	(Optional) IP and L4 port
<i>src-protocol</i>	(Optional) Protocol
range	(Optional) Match only packets in the range of port numbers
<i>src-x</i>	(Optional)
<i>src-y</i>	(Optional)
ip-dst	(Optional) IP
<i>dst-protocol</i>	(Optional) Protocol
<i>dst-x</i>	(Optional)
<i>dst-y</i>	(Optional)
buckets	(Optional) Used to create the buckets for traffic distribution, and it should be in powers of 2
<i>num</i>	(Optional) Loadbalance bucket number
mask-position	(Optional) Loadbalance mask position
<i>mask</i>	(Optional) Loadbalance mask position number range 0-31 for IPv4 and 0-127 for IPv6

Command Mode

- /exec/configure/smarte

load-balance

```
[no] load-balance { [ method { src { ip | ip-l4port <src-protocol> range <src-x> <src-y> } | dst { ip-dst | ip-l4port <dst-protocol> range <dst-x> <dst-y> } } | buckets <num> | mask-position <mask> ] + }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
load-balance	PLB Loadbalance options
method	(Optional) Loadbalance method
src	(Optional) Source based parameters
dst	(Optional) Destination based parameters
ip	(Optional) IP
ip-l4port	(Optional) IP and L4 port
<i>src-protocol</i>	(Optional) Protocol
range	(Optional) Match only packets in the range of port numbers
<i>src-x</i>	(Optional)
<i>src-y</i>	(Optional)
ip-dst	(Optional) IP
<i>dst-protocol</i>	(Optional) Protocol
<i>dst-x</i>	(Optional)
<i>dst-y</i>	(Optional)
buckets	(Optional) Used to create the buckets for traffic distribution, and it should be in powers of 2
<i>num</i>	(Optional) Loadbalance bucket number
mask-position	(Optional) Loadbalance mask position
<i>mask</i>	(Optional) Loadbalance mask position number range 0-23 for IPv4 and 0-127 for IPv6

Command Mode

- /exec/configure/plb

load-interval

load-interval <interval> | no load-interval [<interval1>]

Syntax Description

no	Negate a command or set its defaults
load-interval	Specify interval for load calculation for an interface
<i>interval</i>	Load interval delay in seconds
<i>interval1</i>	(Optional) Load interval delay in seconds

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

load-interval

load-interval <interval> | no load-interval [<interval1>]

Syntax Description

no	Negate a command or set its defaults
load-interval	Specify interval for load calculation for an interface
<i>interval</i>	Load interval delay in seconds
<i>interval1</i>	(Optional) Load interval delay in seconds

Command Mode

- /exec/configure/if-vlan-common

load-interval counter

load-interval counter <counter_val> <interval> | no load-interval counter <counter_val> [<interval1>]

Syntax Description

no	Negate a command or set its defaults
load-interval	Specify interval for load calculation for an interface
counter	Specify counter for this load interval
<i>interval</i>	Load interval delay in seconds
<i>counter_val</i>	Specify counter for this load interval
<i>interval1</i>	(Optional) Load interval delay in seconds

Command Mode

- /exec/configure/if-vlan-common

load-interval counter

load-interval counter <counter_val> <interval> | no load-interval counter <counter_val> [<interval1>]

Syntax Description

no	Negate a command or set its defaults
load-interval	Specify interval for load calculation for an interface
counter	Specify counter for this load interval
<i>counter_val</i>	Specify counter for this load interval
<i>interval</i>	Load interval delay in seconds
<i>interval1</i>	(Optional) Load interval delay in seconds

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

load

load <uri0>

Syntax Description

load	Load system image
<i>uri0</i>	Enter image URI

Command Mode

- /exec

load

load <uri0> [<s0>]

Syntax Description

load	Load system image
<i>uri0</i>	Enter image URI
<i>s0</i>	(Optional) Options

Command Mode

- /exec

load

load <uri0> [<s0>]

Syntax Description

load	Load system image
<i>uri0</i>	Enter image URI
<i>s0</i>	(Optional) Options

Command Mode

- /exec

load

load <uri0> [<s0>]

Syntax Description

load	Load system image
<i>uri0</i>	Enter image URI
<i>s0</i>	(Optional) Options

Command Mode

- /exec

local-as

```
{ local-as <asn> [ no-prepend [ replace-as [ dual-as ] ] ] } | { { no | default } local-as [ <asn> ] }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
local-as	Specify the local-as number for the eBGP neighbor
<i>asn</i>	Autonomous System Number
no-prepend	(Optional) Do not prepend the local-as number to updates from the eBGP neighbor
replace-as	(Optional) Prepend only the local-as number to updates to eBGP neighbor
dual-as	(Optional) Connect using either the local-as number or the real as

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

local-as

local-as <asn> | no local-as [<asn>]

Syntax Description

no	Negate a command or set its defaults
local-as	Specify the local-as for this vrf
<i>asn</i>	AS number

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf

local-label prefix

```
[no] { [ vrf { <vrf-name> | <vrf-known-name> } ] local-label <static-inlabel> prefix { <prefix> <mask> | <prefix-mask> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	(Optional) VPN Routing/Forwarding instance name
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
local-label	Configure local label assignment and forwarding
<i>static-inlabel</i>	Label Value
prefix	For a given prefix
<i>prefix</i>	Destination prefix
<i>mask</i>	Destination prefix mask
<i>prefix-mask</i>	Destination prefix/mask

Command Mode

- /exec/configure/mpls_static/ipv4

local-label prefix

```
[no] { [ vrf { <vrf-name> | <vrf-known-name> } ] local-label <static-inlabel> prefix { <ipv6-prefix-mask> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	(Optional) VPN Routing/Forwarding instance name
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
local-label	Configure local label assignment and forwarding
<i>static-inlabel</i>	Label Value
prefix	For a given prefix

Command Mode

- /exec/configure/mpls_static/ipv6

locator-led

[no] locator-led { chassis | module <module> | fan <fan_num> }

Syntax Description

no	(Optional) Negate a command or set its defaults
locator-led	blink locator led on device
chassis	blink chassis led
module	blink module led
<i>module</i>	please enter the module number
fan	blink Fan led
<i>fan_num</i>	fan number

Command Mode

- /exec

lockdown

[no] lockdown

Syntax Description

no	(Optional) Negate a command or set its defaults
lockdown	Lockdown the LSP--disable reoptimization

Command Mode

- /exec/configure/te/lsp-attr

log-adjacency-changes

[no] log-adjacency-changes [detail]

Syntax Description

no	(Optional) Negate a command or set its defaults
log-adjacency-changes	Log changes in adjacency state
detail	(Optional) Notify all state changes

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

log-adjacency-changes

[no] log-adjacency-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
log-adjacency-changes	Log changes in adjacency state

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

log-adjacency-changes

{ [no] log-adjacency-changes } | { [no] [eigrp] log-neighbor-changes }

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
log-adjacency-changes	Log changes in adjacency state
log-neighbor-changes	Enable/Disable IP-EIGRP neighbor logging

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

log-adjacency-changes

[no] log-adjacency-changes [detail]

Syntax Description

no	(Optional) Negate a command or set its defaults
log-adjacency-changes	Log changes in adjacency state
detail	(Optional) Notify all state changes

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

log-adjacency-changes

[no] log-adjacency-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
log-adjacency-changes	Log changes in adjacency state

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

log-adjacency-changes

[no] log-adjacency-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
log-adjacency-changes	Log changes in adjacency state

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

log-event-type

[no] [eigrp] log-event-type [dual] [xmit] [transport]

Syntax Description

no	(Optional) Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
log-event-type	Set event types logged
dual	(Optional) Log DUAL events
xmit	(Optional) Log transmission events
transport	(Optional) Log transport events

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

log-neighbor-changes

[no] log-neighbor-changes

Syntax Description

no	(Optional) Negate a command or set its defaults
log-neighbor-changes	Log a message for neighbor up/down event

Command Mode

- /exec/configure/router-bgp/vrf-cmds

log-neighbor-changes

[no | default] log-neighbor-changes [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
log-neighbor-changes	Log message for neighbor up/down event
disable	(Optional) Disable logging of neighbor up/down event

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

log-neighbor-warnings

```
{ { [ eigrp ] log-neighbor-warnings [ <interval> ] } | { no [ eigrp ] log-neighbor-warnings [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
log-neighbor-warnings	Enable/Disable IP-EIGRP neighbor warnings
<i>interval</i>	(Optional) Neighbor warning interval in seconds

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

logging

[no] logging { neighbor-changes |

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Enable LDP logging
neighbor-changes	Log LDP neighbor state changes

Command Mode

- /exec/configure/ldp

logging

```
[no] logging { lsp { path-errors | preemption | reservation-errors | setups | teardowns } | tunnel { lsp-selection | path change } } | logging { lsp { path-errors | preemption | reservation-errors | setups | teardowns } | tunnel { lsp-selection | path change } }
```

Syntax Description

no	Negate a command or set its defaults
logging	Trap logging configuration
lsp	LSP-specific traps logging configuration
path-errors	Log LSP Path Error traps
preemption	Log LSP Preemption traps
reservation-errors	Log LSP Reservation Error traps
setups	Log LSP Establishment Traps
teardowns	Log LSP Teardown Traps
tunnel	Tunnel-specific traps logging configuration
lsp-selection	Log Tunnel LSP Selection traps
path	Log Tunnel Path-related traps
change	Log Tunnel Path change traps

Command Mode

- /exec/configure/te

logging abort

logging abort

Syntax Description

logging	Modify message logging facilities
abort	Flushes cached data without committing and releases the lock

Command Mode

- /exec/configure

logging console

[no] logging console [<i0>]

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
console	Set console logging
<i>i0</i>	(Optional) 0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging debug

logging debug

Syntax Description

logging	Exec logging commands
debug	Debug logging

Command Mode

- /exec

logging distribute

[no] logging distribute

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
distribute	Enables/disables fabric distribution using cfs.

Command Mode

- /exec/configure

logging drop threshold

[no] logging drop { threshold-packets <threshold-in-packets> | threshold-bytes <threshold-in-bytes> } [level <level-value>]

Syntax Description

no	Negate a command or set its defaults
logging	set logging for copp class
drop	logging for copp drops
threshold-packets	threshold value for dropped packets
threshold-bytes	threshold value for dropped bytes
level	(Optional) syslog level
<i>level-value</i>	(Optional) specify the logging level between 1-7

Command Mode

- /exec/configure/pmap/class

logging drop threshold

```
logging drop { threshold-packets <threshold-in-packets> | threshold-bytes <threshold-in-bytes> } [ level <level-value> ]
```

Syntax Description

logging	set logging for copp class
drop	logging for copp drops
threshold-packets	threshold value for dropped packets
threshold-bytes	threshold value for dropped bytes
level	(Optional) syslog level
<i>level-value</i>	(Optional) specify the logging level between 1-7

Command Mode

- /exec/configure/pmap/class

logging event link enable

[no] logging event { link-status | trunk-status } { enable | default }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Configure logging for interface
event	Interface events
link-status	UPDOWN and CHANGE messages
trunk-status	TRUNK status messages
enable	To enable logging overriding port level configuration
default	default logging configuration used by interfaces not explicitly configured

Command Mode

- /exec/configure

logging event port link-status

logging event port link-status [default] | no logging event port link-status

Syntax Description

no	Negate a command or set its defaults
logging	Configure logging for interface
event	Interface events
port	Port level events
link-status	UPDOWN and CHANGE messages
default	(Optional) Use the global default value

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-port-channel-sub /exec/configure/if-gig-ether-sub /exec/configure/if-loopback /exec/configure/if-remote-ethernet-sub /exec/configure/if-ether-sub-p2p

logging event port link-status

logging event port link-status

Syntax Description

logging	Configure logging for interface
event	Interface events
port	Port level events
link-status	UPDOWN and CHANGE messages

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging event port link-status

[no] logging event port link-status

Syntax Description

no	Negate a command or set its defaults
logging	Configure logging for interface
event	Interface events
port	Port level events
link-status	UPDOWN and CHANGE messages

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging event port link-status default

logging event port link-status default

Syntax Description

logging	Configure logging for interface
event	Interface events
port	Port level events
link-status	UPDOWN and CHANGE messages
default	Use the global default value

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging event port trunk-status

[no] logging event port trunk-status

Syntax Description

no	Negate a command or set its defaults
logging	Configure logging for interface
event	Interface events
port	Port level events
trunk-status	TRUNK status messages

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging event port trunk-status

logging event port trunk-status

Syntax Description

logging	Configure logging for interface
event	Interface events
port	Port level events
trunk-status	TRUNK status messages

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging event port trunk-status default

logging event port trunk-status default

Syntax Description

logging	Configure logging for interface
event	Interface events
port	Port level events
trunk-status	TRUNK status messages
default	Use the global default value

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel

logging flow-mod

[no] logging flow-mod

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Enable logging
flow-mod	Enable logging for flow-modify

Command Mode

- /exec/configure/openflow/switch/sub-switch

logging flow-mod

[no] logging flow-mod

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Enable logging
flow-mod	Enable logging for flow-modify

Command Mode

- /exec/configure/openflow/switch

logging ip access-list cache

[no] logging ip access-list cache { { interval <seconds> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
ip	IP configuration
access-list	Access-list
cache	logging
interval	Log-update interval (in sec)
<i>seconds</i>	Log-update interval in seconds

Command Mode

- /exec/configure

logging ip access-list cache entries

[no] logging ip access-list cache { { entries <num_entries> } | { threshold <num_packets> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
ip	IP configuration
access-list	Access-list
cache	logging
entries	Maximum number of log entries cached in software
<i>num_entries</i>	Number of entries
threshold	Log-update threshold
<i>num_packets</i>	Log-update threshold (number of hits)

Command Mode

- /exec/configure

logging ip access-list detailed

[no] logging ip access-list detailed

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Enable detailed logging
ip	configured IP
access-list	Access-list
detailed	Detailed ACL information

Command Mode

- /exec/configure

logging ip access-list include sgt

[no] logging ip access-list include sgt

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
ip	IP configuration
access-list	Access-list
include	Include additional fields in syslogs
sgt	Include source group tag info in syslogs

Command Mode

- /exec/configure

logging level

[no] logging level { port-channel <loglevel> | port_channel <loglevel> | eth_port_channel <loglevel> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port-channel	Set level for port-channel syslog messages
port_channel	Set level for port-channel syslog messages
eth_port_channel	Set level for port-channel syslog messages
<i>loglevel</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { { ipv6 icmp } | icmpv6 } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ipv6	Configure IPv6 features
icmp	ICMPv6 Commands
icmpv6	ICMPv6 Commands
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { { routing ipv6 multicast } | m6rib } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
routing	Configure routing information
ipv6	Configure IPv6 features
multicast	Set syslog filter level for MRIB
m6rib	Set syslog filter level for MRIB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

```
{ logging level { auth <i1> | authpriv <i2> | cron <i3> | daemon <i4> | ftp <i5> | kernel <i6> | local0 <i7> |
local1 <i8> | local2 <i9> | local3 <i10> | local4 <i11> | local5 <i12> | local6 <i13> | local7 <i14> | lpr <i15>
| mail <i16> | news <i17> | syslog <i18> | user <i19> | uucp <i20> } | no logging level { auth [ <i1> ] | authpriv
[ <i2> ] | cron [ <i3> ] | daemon [ <i4> ] | ftp [ <i5> ] | kernel [ <i6> ] | local0 [ <i7> ] | local1 [ <i8> ] | local2
[ <i9> ] | local3 [ <i10> ] | local4 [ <i11> ] | local5 [ <i12> ] | local6 [ <i13> ] | local7 [ <i14> ] | lpr [ <i15>
] | mail [ <i16> ] | news [ <i17> ] | syslog [ <i18> ] | user [ <i19> ] | uucp [ <i20> ] } }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
auth	Set level for Authorization System
<i>i1</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
authpriv	Set level for Authorization (Private) system
<i>i2</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
cron	Set level for Cron/at facility
<i>i3</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
daemon	Set level for System daemons
<i>i4</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
ftp	Set level for File Transfer System
<i>i5</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
kernel	Set level for kernel
<i>i6</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local0	Set level for Local use daemons
<i>i7</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local1	Set level for Local use daemons
<i>i8</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local2	Set level for Local use daemons
<i>i9</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local3	Set level for Local use daemons

<i>i10</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local4	Set level for Local use daemons
<i>i11</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local5	Set level for Local use daemons
<i>i12</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local6	Set level for Local use daemons
<i>i13</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
local7	Set level for Local use daemons
<i>i14</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
lpr	Set level for Line Printer System
<i>i15</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
mail	Set level for Mail system
<i>i16</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
news	Set level for USENET news
<i>i17</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
syslog	Set level for Internal Syslog Messages
<i>i18</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
user	Set level for User Process
<i>i19</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
uucp	Set level for Unix-to-Unix copy system
<i>i20</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { { routing [ip | ipv4] multicast } | mrib } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
routing	Configure routing information
ip	(Optional) Configure IP features
ipv4	(Optional) Configure IP features
multicast	Set syslog filter level for MRIB
mrib	Set syslog filter level for MRIB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { { otv isis } | isis_otv } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
otv	Set syslog filter level for OTV
isis	Set syslog filter level for IS-IS
isis_otv	Show OTV ISIS logging configuration
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { xml server | xmlma } <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
xml	xml agent
server	xml agent server
xmlma	xml master agent. Same as combination of keywords xml server
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level

[no] logging level { { fabricpath isis } | isis_l2mp | isis_fabricpath } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
fabricpath	fabricpath configuration
isis	Set logging level for fabricpath IS-IS
isis_l2mp	Set fabricpath logging configuration
isis_fabricpath	Set fabricpath logging configuration
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level aaa

logging level aaa <i0> | no logging level aaa [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
aaa	Set level for aaa syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level aclog

logging level aclog <i0> | no logging level aclog [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
aclog	Set level for aclog syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level aclmgr

[no] logging level aclmgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
aclmgr	Set level for aclmgr syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level adbm

[no] logging level adbm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
adbm	Set level for adbm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level adjmgr

[no] logging level adjmgr <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
adjmgr	Set syslog filter level for Adjacency Manager
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level all

{ logging level { all <i0> } | no logging level { all [<i0>] } }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
all	Set level for all facilities
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level amt

[no] logging level amt <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
amt	Set syslog filter level for AMT
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level arp

```
{ logging level arp <level> } | { no logging level arp [ <level> ] }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
arp	Set syslog filter level for ARP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ascii-cfg

[no] logging level ascii-cfg <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ascii-cfg	Set logging level for ascii-cfg
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level assoc_mgr

[no] logging level assoc_mgr <i0> | no logging level assoc_mgr [<i0>]

Syntax Description

no	(Optional) Negate a command or set its default
logging	Show logging configuration and contents of logfile
level	Show facility logging configuration
assoc_mgr	Show Association Manager Logging Configuration
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level backup

[no] logging level { backup | flexlink } <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
backup	Set level for Switchport Backup syslog messages
flexlink	Set level for Switchport Backup syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level bfd

[no] logging level bfd <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
bfd	Set level for bfd syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level bgp

[no] logging level bgp <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
bgp	Set syslog filter level for BGP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level bloggerd

[no] logging level bloggerd <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
bloggerd	Set level for BloggerD syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level bootvar

[no] logging level bootvar <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
bootvar	Set level for bootvar
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level callhome

logging level callhome <i0> | no logging level callhome [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
callhome	Callhome syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level capability

[no] logging level capability <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
capability	Set syslog level for mig utils daemon
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level catena

[no] logging level catena <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
catena	Set level for catena syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level cdp

logging level cdp <i0> | no logging level cdp [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
cdp	Set level for CDP syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level cert

[no] logging level { cert-enroll <i0> | cert_enroll <i1> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
cert-enroll	Cert-enroll syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
cert_enroll	Cert-enroll syslog level
<i>il</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level cfs

[no] logging level cfs <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level clis

[no] logging level clis <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
clis	Set syslog filter level for CLIS
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level clk_mgr

[no] logging level clk_mgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
clk_mgr	Set level for clock manager syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level confcheck

```
{ logging level confcheck <i0> | no logging level confcheck [ <i0> ] }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level copp

logging level copp <i0> | no logging level copp [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
copp	Set level for copp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level core

{ logging level core <i0> | no logging level core [<i0>] }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
core	core daemon syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level cts

[no] logging level cts <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
cts	Set level for cts syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level dhclient

[no] logging level dhclient <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
dhclient	Set level for dhcp client syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level dhcp_snoop

logging level dhcp_snoop <level> | no logging level dhcp_snoop [<level>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
dhcp_snoop	Set level for dhcp snoop syslog messages
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level diagclient

[no] logging level diagclient <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
diagclient	Set level for GOLD DiagClient syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level diagmgr

[no] logging level diagmgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
diagmgr	Set level for GOLD DiagMgr syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level dot1x

[no] logging level dot1x <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
dot1x	Set level for dot1x syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ecp

[no] logging level ecp <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ecp	Set syslog filter level for ECP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level eigrp

[no] logging level eigrp [<eigrp-ptag>] <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
eigrp	Set syslog filter level for EIGRP
<i>eigrp-ptag</i>	(Optional) Process tag
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level eltm

logging level eltm <i0> | no logging level eltm

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
eltm	Set level for eltm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level epp

[no] logging level epp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
epp	Set level for EPP syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ethdstats

[no] logging level { ethdstats <i0> | eth_dstats <i0> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ethdstats	delta statistics syslog level
eth_dstats	delta statistics syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ethpm

[no] logging level ethpm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ethpm	Set level for ethpm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ethpm link

[no] logging level ethpm { link-up | link-down } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ethpm	Set level for ethpm syslog messages
link-up	Configure logging level for link up syslog messages
link-down	Configure logging level for link down syslog messages
<i>level</i>	Logging Level

Command Mode

- /exec/configure

logging level evb

[no] logging level evb <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
evb	Set syslog filter level for EVB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level evmc

[no] logging level evmc <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
evmc	Set level for evmc syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level evmed

[no] logging level evmed <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
evmed	Set level for evmed syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level evms

[no] logging level evms <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
evms	Set level for evms syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level fabric forwarding

[no] logging level fabric forwarding <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
fabric	Fabric
forwarding	Fabric Forwarding Protocol: Host Mobility Manager (HMM)
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level fcoe_mgr

[no] logging level fcoe_mgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
fcoe_mgr	Set level for fcoe_mgr syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level feature-mgr

```
{ logging level feature-mgr <i0> | no logging level feature-mgr [ <i0> ] }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
feature-mgr	Set feature manager syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level fs-daemon

{ logging level fs-daemon <i0> | no logging level fs-daemon [<i0>] }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
fs-daemon	fs daemon syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level gpixm

[no] logging level gpixm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
gpixm	Set level for global-pixm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level hardware-telemetry

[no] logging level hardware-telemetry <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
hardware-telemetry	Set level for hardware-telemetry syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level hsrp

[no] logging level hsrp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
hsrp	Set level for hsrp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level icam

[no] logging level icam <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
icam	Set level for icam syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level igmp

[no] logging level [ip] igmp <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	(Optional) Configure IP features
igmp	IGMP global configuration commands
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level im

[no] logging level { im <i0> | ifmgr <i0> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
im	Set level for im syslog messages
ifmgr	Set level for im syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level imp

[no] logging level imp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
imp	Set level for imp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level interface-vlan

[no] logging level interface-vlan <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
interface-vlan	Set level for interface vlan syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ip pim

[no] logging level ip pim <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	Configure IP features
pim	Set syslog filter level for PIM
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ip sla responder

[no] logging level ip sla responder <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	
sla	Service Level Agreement (SLA)
responder	Set level for sla-responder syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ip sla sender

[no] logging level ip sla sender <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	
sla	Service Level Agreement (SLA)
sender	Set level for sla-sender syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ip sla twamp-server

[no] logging level ip sla twamp-server <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	
sla	Service Level Agreement (SLA)
twamp-server	Set level for sla-twamp-server syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ipconf

[no] logging level ipconf { ipv6 <i0> | <i1> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ipconf	Set level for ipconf syslog messages
ipv6	Set level for ipconf syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
<i>i1</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ipfib

logging level ipfib <i0> | no logging level ipfib

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ipfib	Set level for ipfib syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ipqos

[no] logging level { ipqos | IPQOSMGR } <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ipv6 pim

[no] logging level ipv6 pim <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ipv6	Configure IPv6 features
pim	Set syslog filter level for PIM6
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level iscm

[no] logging level iscm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
iscm	Set level for iscm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level iscm

[no] logging level iscm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
iscm	Set level for iscm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level isis

[no] logging level isis <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
isis	Set syslog filter level for IS-IS
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level keystore

logging level { keystore | sksd } <i0> | no logging level { keystore | sksd } [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
keystore	Keystore syslog level
sksd	Keystore/sksd syslog level
<i>i0</i>	

Command Mode

- /exec/configure

logging level l2fm

logging level l2fm <i0> | no logging level l2fm

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
l2fm	Set level for l2fm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level l2rib

[no] logging level l2rib <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
l2rib	l2rib syslog
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level l3vm

[no] logging level l3vm <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
l3vm	Set syslog filter level for L3VM
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level lacp

[no] logging level lacp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
lacp	Set level for lacp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ldap

logging level ldap <i0> | no logging level ldap [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ldap	Set level for ldap syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level lem-mgr

[no] logging level lem-mgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level license

logging level { license | licmgr } <i0> | no logging level { license | licmgr } [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
license	Licensing syslog level
licmgr	Licensing syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level lim

[no] logging level lim <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
lim	Set level for lim syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level lisp

[no] logging level lisp <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
lisp	Set logging level for LISP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level lldp

[no] logging level lldp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
lldp	Set level for lldp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level m2rib

[no] logging level m2rib <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
m2rib	Set level for m2rib syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level mfdm

logging level mfdm <i0> | no logging level mfdm

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
mfdm	Set level for mfdm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level mfwd

[no] logging level { mfwd | mcastfwd } <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
mfwd	Configures Global IP Multicast Forwarding
mcastfwd	Configures Global IP Multicast Forwarding
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level mmode

[no] logging level mmode <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
mmode	Set level for maintenance mode syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level module

[no] logging level module <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
module	Set level for module(linecard) manager syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level monitor

[no] logging level monitor <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
monitor	Set level for ethernet span syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level msdp

[no] logging level [ip] msdp <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ip	(Optional) Configure IP features
msdp	Set syslog filter level for MSDP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level mvsh

[no] logging level mvsh <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
mvsh	Set level for mvsh syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level nat

logging level nat <i0> | no logging level nat [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
nat	Set level for NAT syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level nbm

logging level nbm <i0> | no logging level nbm

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
nbm	Set level for nbm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level netstack

```
{ logging level netstack <level> } | { no logging level netstack [ <level> ] }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
netstack	Set syslog filter level for Netstack
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level nfm

[no] logging level nfm <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
nfm	Set level for nfm syslog messages
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ngoam

[no] logging level ngoam <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ngoam	Set level for oam logging messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure handle function sdstub_syslog sdwrap args-legacy

logging level npv

[no] logging level npv <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
npv	Set level for NPV syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ntp

[no] logging level ntp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ntp	Set syslog filter level for NTP
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level nxsdk

[no] logging level nxsdk <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
nxsdk	NXOS SDK
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level openflow

[no] logging level openflow <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
openflow	Set level for OpenFlow agent syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level orib

[no] logging level orib <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
orib	Set syslog filter level for ORIB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ospf

[no] logging level ospf <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ospf	Set syslog filter level for OSPF
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ospfv3

[no] logging level ospfv3 <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ospfv3	Set syslog filter level for OSPFv3
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level pfstat

logging level pfstat <i0> | no logging level pfstat

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
pfstat	Set level for pfstat syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level pixm

[no] logging level pixm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
pixm	Set level for vdc-local-pixm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level pktmgr

[no] logging level pktmgr <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
pktmgr	Set syslog filter level for Packet manager
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level platform

[no] logging level platform <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
platform	platform manager syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level plbm

[no] logging level plbm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
plbm	Set level for plbm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level plcmgr

[no] logging level { plcmgr | ipplc } <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level pltfm_config

[no] logging level pltfm_config <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
pltfm_config	Set level for pltfm_config syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level plugin

{ logging level plugin <i0> | no logging level plugin [<i0>] }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
plugin	Set level for plugin syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level poap

[no] logging level poap <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
poap	Set level for poap syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level poed

[no] logging level poed <i0> | no logging level poed [<i0>]

Syntax Description

no	(Optional) Negate a command or set its default
logging	Show logging configuration and contents of logfile
level	Show facility logging configuration
poed	Show PoE Daemon Logging Configuration
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port-profile

logging level port-profile <i0> | no logging level port-profile [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port-profile	Set level for port-profile syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port-resources

[no] logging level port-resources <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port-resources	Set level for prn syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port-security

logging level port-security <i0> | no logging level port-security [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port-security	Set level for port-security syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port

[no] logging level port <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port	Set level for port syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port_client

[no] logging level port_client <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port_client	Set level for port_client syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port_lb

[no] logging level { port_lb <i0> | diag_port_lb <i0> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port_lb	Set level for Diagnostic Port Loopback Test syslog messages
diag_port_lb	Set level for Diagnostic Port Loopback Test syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level port link-failure

[no] logging level port link-failure <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
port	Set level for port syslog messages
link-failure	Configure logging level for link failure syslog messages
<i>level</i>	Logging Level

Command Mode

- /exec/configure

logging level private-vlan

[no] logging level private-vlan <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
private-vlan	Set level for private VLAN syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ptp

[no] logging level ptp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ptp	Set level for ptp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level radius

logging level radius <i0> | no logging level radius [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
radius	RADIUS syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level res_mgr

[no] logging level res_mgr <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
res_mgr	Set level for res_mgr syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level rip

[no] logging level rip <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
rip	Set syslog filter level for RIP
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level rpm

[no] logging level rpm <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
rpm	Set syslog filter level for RPM
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level rsvp

[no] logging level rsvp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
rsvp	Set level for RSVP syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level sal

[no] logging level sal <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
sal	Set level for sal syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level san

[no] logging level { san-port-channel <loglevel> | port_channel <loglevel> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
san-port-channel	Set level for san-port-channel syslog messages
port_channel	Set level for san-port-channel syslog messages
<i>loglevel</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level scheduler

[no] logging level scheduler <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
scheduler	Set logging level for scheduler
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level security

logging level { security | securityd } <i0> | no logging level { security | securityd } [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
security	Security syslog level
securityd	Security syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level session-mgr

logging level session-mgr <i0> | no logging level session-mgr [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
session-mgr	Set level for session-manager syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level sflow

[no] logging level sflow <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
sflow	Set level for sFlow syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level smartc

[no] logging level smartc <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
smartc	Set level for smartc syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level smm

[no] logging level smm <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
smm	Set logging level for Shared Memory Manager
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level snmpd

[no] logging level snmpd <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
snmpd	Set level for SNMP syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level snmpmib_proc

[no] logging level snmpmib_proc <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
snmpmib_proc	Set level for snmpmib_proc syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level spanning

[no] logging level { spanning-tree } <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
spanning-tree	Set level for stp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level spm

[no] logging level spm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
spm	Set level for spm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level stripcl

[no] logging level stripcl <log-level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
stripcl	Set level for stripcl syslog messages
<i>log-level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level sysmgr

{ logging level sysmgr <i0> | no logging level sysmgr [<i0>] }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level tacacs

logging level tacacs <i0> | no logging level tacacs [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
tacacs	TACACS+ syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level tamnw

[no] logging level tamnw <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
tamnw	Set level for tamnw syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level track

[no] logging level track <*i0*>

Syntax Description

logging	Modify message logging facilities
level	Facility parameter for syslog messages
track	Set level for track syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level tunnel

logging level tunnel <i0> | no logging level tunnel [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
tunnel	Set level for tunnel syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level u2rib

[no] logging level u2rib <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
u2rib	Set level for u2rib syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level u6rib

[no] logging level u6rib <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
u6rib	Set syslog filter level for U6RIB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level udd

[no] logging level udd <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
udd	Set level for udd syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level ufdm

[no] logging level ufdm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
ufdm	Set level for ufdm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level urib

[no] logging level urib <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
urib	Set syslog filter level for URIB
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vdc_mgr

[no] logging level vdc_mgr <i0>

Syntax Description

logging	Modify message logging facilities
level	Facility parameter for syslog messages
vdc_mgr	Set level for vdc_mgr syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level virtual-service

[no] logging level virtual-service <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
virtual-service	Set level for virtual service syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vlan_mgr

logging level vlan_mgr <i0> | no logging level vlan_mgr [<i0>]

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vlan_mgr	Set level for VLAN syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vmm

[no] logging level vmm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vmm	Set level for vmm syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vmtracker

[no] logging level vmtracker <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vmtracker	Set level for vmtracker syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vpc

[no] logging level vpc <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vpc	Set level for vPC syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vrrp

[no] logging level { vrrp-cfg <cfg_level_num> | vrrp-eng <eng_level_num> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vrrp-cfg	Set level for vrrp configuration
<i>cfg_level_num</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
vrrp-eng	Set level for vrrp engine
<i>eng_level_num</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vrrpv3

[no] logging level { vrrpv3 <level> }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vrrpv3	Set level for vrrpv3 configuration
<i>level</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vsan

{ logging level vsan <i0> | no logging level vsan [<i1>] }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
<i>i1</i>	(Optional) 0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vshd

[no] logging level vshd <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level vtp

[no] logging level vtp <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
vtp	Set level for vtp syslog messages
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level wwnm

[no] logging level wwnm <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
wwnm	Set WWN Manager syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging level xbar

[no] logging level xbar <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
level	Facility parameter for syslog messages
xbar	xbar syslog level
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging logfile

```
{ logging logfile <s0> <i0> [ size <i1> ] | no logging logfile [ <s0> <i0> [ size <i1> ] ] }
```

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
logfile	Set File logging
<i>s0</i>	Enter the logfile name
<i>i0</i>	0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
size	(Optional) Set logfile size
<i>i1</i>	(Optional) Enter the logfile size in bytes

Command Mode

- /exec/configure

logging message interface type ethernet

logging message interface type ethernet <info> | no logging message interface type ethernet <info>

Syntax Description

no	Negate a command or set its defaults
logging	Configure logging for interface
message	Interface events
interface	Interface level events
type	Interface type
ethernet	Ethernet interfaces
<i>info</i>	Field Names to be added to interface syslog

Command Mode

- /exec/configure

logging module

[no] logging module [<i0>]

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
module	Set module(linecard) logging
<i>i0</i>	(Optional) 0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging monitor

[no] logging monitor [<i0>]

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
monitor	Set terminal line(monitor) logging level
<i>i0</i>	(Optional) 0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug

Command Mode

- /exec/configure

logging origin-id

```
[no] logging origin-id { hostname | ip <ip0> | string <s0> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
origin-id	Enable origin information for Remote Syslog Server
hostname	Use hostname as origin-id of logging messages
ip	Use ip address as origin-id of logging messages
<i>ip0</i>	Hostname/IPv4/IPv6 address
string	Use text string as origin-id of logging messages
<i>s0</i>	Enter string to append to the front of syslog msgs

Command Mode

- /exec/configure

logging rate-limit

[no] logging rate-limit

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
rate-limit	Enables rate limit for log messages

Command Mode

- /exec/configure

logging server

```
[no] logging server <host0> [ [ <i1> ] ] [ port <port> ] [ secure [ trustpoint client-identity <trustpoint-label> ] ] [ use-vrf { <vrf-name> | <vrf-known-name> } ] facility { auth | authpriv | cron | daemon | ftp | kernel | local0 | local1 | local2 | local3 | local4 | local5 | local6 | local7 | lpr | mail | news | syslog | user | uucp } ] + ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
server	Enable forwarding to Remote Syslog Server
<i>host0</i>	Hostname/IPv4/IPv6 address of the Remote Syslog Server
<i>i1</i>	(Optional) 0-emerg 1-alert 2-crit 3-err 4-warn 5-notif 6-inform 7-debug
port	(Optional) Destination Port when forwarding to remote server
<i>port</i>	(Optional) Range from 1 - 65535(Default 514)
secure	(Optional) Enable secure connection to remote server
trustpoint	(Optional) Trustpoint configuration
client-identity	(Optional) Client Identity certificate for mutual authentication
<i>trustpoint-label</i>	(Optional) trustpoint to use for client certificate authentication
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
facility	(Optional) Facility to use when forwarding to server
auth	(Optional) Use auth facility
authpriv	(Optional) Use authpriv facility
cron	(Optional) Use Cron/at facility
daemon	(Optional) Use daemon facility
ftp	(Optional) Use file transfer system facility
kernel	(Optional) Use kernel facility
local0	(Optional) Use local0 facility
local1	(Optional) Use local1 facility
local2	(Optional) Use local2 facility

local3	(Optional) Use local3 facility
local4	(Optional) Use local4 facility
local5	(Optional) Use local5 facility
local6	(Optional) Use local6 facility
local7	(Optional) Use local7 facility
lpr	(Optional) Use lpr facility
mail	(Optional) Use mail facility
news	(Optional) Use USENET news facility
syslog	(Optional) Use syslog facility
user	(Optional) Use user facility
uucp	(Optional) Use Unix-to-Unix copy system facility

Command Mode

- /exec/configure

logging server dns-refresh-interval

[no] logging server dns-refresh-interval <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
server	Enable forwarding to Remote Syslog Server
dns-refresh-interval	DNS refresh interval for remote syslog server hostnames
<i>i0</i>	Configure DNS Refresh interval from 10 minutes to 24 hours Default:60 (will cancel any existing timers)

Command Mode

- /exec/configure

logging source-interface

{ logging source-interface <interface> | no logging source-interface }

Syntax Description

no	Negate a command or set its defaults
logging	Modify message logging facilities
source-interface	Enable Source-Interface for Remote Syslog Server
<i>interface</i>	Source interface name

Command Mode

- /exec/configure

logging timestamp

[no] logging timestamp { microseconds | milliseconds | seconds }

Syntax Description

no	(Optional) Negate a command or set its defaults
logging	Modify message logging facilities
timestamp	Set logging timestamp granularity
microseconds	Timestamp in micro-seconds
milliseconds	Timestamp in milli-seconds
seconds	Timestamp in seconds (Default)

Command Mode

- /exec/configure

login on-failure log

[no] login on-failure log

Syntax Description

no	(Optional) Negate a command or set its defaults
login	login
on-failure	Set options for failed login attempt
log	Generate syslogs on failure logins

Command Mode

- /exec/configure

login on-success log

[no] login on-success log

Syntax Description

no	(Optional) Negate a command or set its defaults
login	login
on-success	Set options for successful login attempt
log	Generate syslogs on successful logins

Command Mode

- /exec/configure

logout-warning

{ logout-warning <i0> | no logout-warning [<i0>] }

Syntax Description

no	Negate a command or set its defaults
logout-warning	Configure logout warning
<i>i0</i>	Enter logout warning time in seconds

Command Mode

- /exec/configure/line

low-memory exempt

[no | default] low-memory exempt

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
low-memory	Behaviour
exempt	Do

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

Ishow

Ishow

Syntax Description

Ishow	display this instance of credential
-------	-------------------------------------

Command Mode

- /exec/configure/dot1x-cred

Ishow

Ishow

Syntax Description

Ishow	local show: displays config of current interface
-------	--

Command Mode

- /exec/configure/if-igp

lsp-gen-interval

lsp-gen-interval <max-wait> [<initial-wait> <second-wait>] | no lsp-gen-interval <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
lsp-gen-interval	Configure LSP generation interval
<i>max-wait</i>	Maximum wait between trigger and LSP generation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and LSP generation (milli-secs)
<i>second-wait</i>	(Optional) Second wait used in LSP generation (milli-secs) during backoff

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

lsp-gen-interval

lsp-gen-interval <level> <max-wait> [<initial-wait> <second-wait>] | no lsp-gen-interval <level> <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
lsp-gen-interval	Configure LSP generation interval
<i>level</i>	IS-IS level
<i>max-wait</i>	Maximum wait between trigger and LSP generation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and LSP generation (milli-secs)
<i>second-wait</i>	(Optional) Second wait used in LSP generation (milli-secs) during backoff

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

lsp-gen-interval

lsp-gen-interval <max-wait> [<initial-wait> <second-wait>] | no lsp-gen-interval <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
lsp-gen-interval	Configure LSP generation interval
<i>max-wait</i>	Maximum wait between trigger and LSP generation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and LSP generation (milli-secs)
<i>second-wait</i>	(Optional) Second wait used in LSP generation (milli-secs) during backoff

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

lsp-mtu

lsp-mtu <mtu> | no lsp-mtu [<mtu>]

Syntax Description

no	Negate a command or set its defaults
lsp-mtu	Set LSP MTU
<i>mtu</i>	Maximum LSP size in bytes

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

lsp-mtu

lsp-mtu <mtu> | no lsp-mtu [<mtu>]

Syntax Description

no	Negate a command or set its defaults
lsp-mtu	Set LSP MTU
<i>mtu</i>	Maximum LSP size in bytes

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

lsp-mtu

lsp-mtu <mtu> | no lsp-mtu [<mtu>]

Syntax Description

no	Negate a command or set its defaults
lsp-mtu	Set LSP MTU
<i>mtu</i>	Maximum LSP size in bytes

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

lsp

[no] lsp <lsp-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
lsp	Configure the name for the label-switched path
<i>lsp-name</i>	Name for this LSP

Command Mode

- /exec/configure/mpls_static/ipv6

lsp

[no] lsp <lsp-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
lsp	Configure the name for the label-switched path
<i>lsp-name</i>	Name for this LSP

Command Mode

- /exec/configure/mpls_static/ipv4

Isp attributes

[no] lsp attributes <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
lsp	Configure LSP parameters
attributes	Configure LSP attributes
<i>name</i>	Name of LSP attribute list

Command Mode

- /exec/configure/te



M Commands

- [m2rib debug ftag](#), on page 2908
- [m2rib debug gr-route add nh](#), on page 2909
- [m2rib debug log-size event-history](#), on page 2911
- [m2rib debug log-size transactions](#), on page 2912
- [m2rib debug omf enable](#), on page 2913
- [m2rib debug pkt-recv enable](#), on page 2914
- [m2rib debug swroute nh](#), on page 2915
- [m2rib debug topo](#), on page 2916
- [m2rib debug topo loop-flush-timeout](#), on page 2917
- [mac-addr](#), on page 2918
- [mac-address](#), on page 2919
- [mac-address](#), on page 2920
- [mac-address](#), on page 2921
- [mac-address bpd source version 2](#), on page 2922
- [mac-address destination](#), on page 2923
- [mac-address ipv6-extract](#), on page 2924
- [mac-learn disable](#), on page 2925
- [mac-learn disable](#), on page 2926
- [mac-list permit](#), on page 2927
- [mac access-list](#), on page 2928
- [mac address-table aging-time](#), on page 2929
- [mac address-table guard-vpc-peergw-mac](#), on page 2930
- [mac address-table limit system](#), on page 2931
- [mac address-table loop-detect port-down](#), on page 2932
- [mac address-table multicast vlan interface](#), on page 2933
- [mac address-table notification mac-move](#), on page 2934
- [mac address-table notification threshold](#), on page 2935
- [mac address-table static vlan interface](#), on page 2936
- [mac address-table static vni](#), on page 2937
- [mac address](#), on page 2938
- [mac address inherit](#), on page 2939
- [mac advert interval](#), on page 2940
- [mac packet-classify](#), on page 2941

- [mac packet-classify](#), on page 2942
- [mac port access-group](#), on page 2943
- [managed-config-flag](#), on page 2944
- [management](#), on page 2945
- [map-notify-group](#), on page 2946
- [map-server key](#), on page 2947
- [marker-packet-n3500](#), on page 2948
- [marker-packet](#), on page 2949
- [master ipv4](#), on page 2950
- [match-address](#), on page 2951
- [match](#), on page 2952
- [match](#), on page 2954
- [match](#), on page 2955
- [match access-group name](#), on page 2959
- [match address](#), on page 2960
- [match as-number](#), on page 2961
- [match as-number as-path-list](#), on page 2962
- [match as-path](#), on page 2963
- [match class-map](#), on page 2964
- [match community](#), on page 2965
- [match cos](#), on page 2966
- [match cos](#), on page 2967
- [match datalink](#), on page 2968
- [match datalink](#), on page 2969
- [match dscp](#), on page 2970
- [match dscp](#), on page 2971
- [match exception](#), on page 2972
- [match extcommunity](#), on page 2973
- [match interface](#), on page 2974
- [match ip address](#), on page 2975
- [match ip address prefix-list](#), on page 2976
- [match ip multicast rp](#), on page 2977
- [match ip next-hop prefix-list](#), on page 2978
- [match ip protocol](#), on page 2979
- [match ip route-source prefix-list](#), on page 2980
- [match ipv4 protocol](#), on page 2981
- [match ipv4 source address](#), on page 2982
- [match ipv4 source address](#), on page 2983
- [match ipv4 transport destination](#), on page 2984
- [match ipv6](#), on page 2985
- [match ipv6](#), on page 2986
- [match ipv6 address](#), on page 2987
- [match ipv6 address prefix-list](#), on page 2988
- [match ipv6 multicast rp](#), on page 2989
- [match ipv6 next-hop prefix-list](#), on page 2990
- [match ipv6 protocol](#), on page 2991

- [match ipv6 route-source prefix-list](#), on page 2992
- [match ipv6 transport destination](#), on page 2993
- [match metric](#), on page 2994
- [match ospf-area](#), on page 2995
- [match protocol](#), on page 2996
- [match protocol arp](#), on page 2997
- [match qos-group](#), on page 2998
- [match qos-group2](#), on page 2999
- [match qos-group2](#), on page 3000
- [match qos-group](#), on page 3001
- [match redirect](#), on page 3002
- [match route-type](#), on page 3003
- [match source-protocol](#), on page 3004
- [match tag](#), on page 3005
- [match transport destination](#), on page 3006
- [max-backoff](#), on page 3007
- [max-backoff](#), on page 3008
- [max-lsa](#), on page 3009
- [max-lsa](#), on page 3010
- [max-lsp-lifetime](#), on page 3011
- [max-lsp-lifetime](#), on page 3012
- [max-lsp-lifetime](#), on page 3013
- [max-metric router-lsa](#), on page 3014
- [max-metric router-lsa](#), on page 3015
- [max-ports](#), on page 3016
- [max-ports](#), on page 3017
- [maxas-limit](#), on page 3018
- [maximum-paths](#), on page 3019
- [maximum-paths](#), on page 3020
- [maximum-paths](#), on page 3021
- [maximum-paths](#), on page 3022
- [maximum-paths](#), on page 3023
- [maximum-paths](#), on page 3024
- [maximum-paths](#), on page 3025
- [maximum-paths](#), on page 3026
- [maximum-paths eibgp](#), on page 3027
- [maximum-paths mixed](#), on page 3028
- [maximum-peers](#), on page 3029
- [maximum-prefix](#), on page 3030
- [maximum-prefix](#), on page 3031
- [maximum-prefix](#), on page 3032
- [maximum routes](#), on page 3033
- [mdix auto](#), on page 3034
- [mdt asm-use-shared-tree](#), on page 3035
- [mdt data](#), on page 3036
- [mdt data bidir-enable](#), on page 3037

- [mdt default](#), on page 3038
- [mdt enforce-bgp-mdt-safi](#), on page 3039
- [mdt mtu](#), on page 3040
- [mdt pim hello-interval](#), on page 3041
- [mdt pim jp-interval](#), on page 3042
- [mdt source](#), on page 3043
- [media-type auto](#), on page 3044
- [media-type rj45](#), on page 3045
- [media-type sfp](#), on page 3046
- [media](#), on page 3047
- [medium](#), on page 3048
- [medium broadcast](#), on page 3049
- [medium broadcast](#), on page 3050
- [medium p2p](#), on page 3051
- [medium p2p](#), on page 3052
- [member vlan](#), on page 3053
- [member vni](#), on page 3054
- [member vni](#), on page 3055
- [member vni associate-vrf](#), on page 3056
- [message-digest-key md5](#), on page 3057
- [message-digest-key md5](#), on page 3058
- [metric-style transition](#), on page 3059
- [metric-type](#), on page 3060
- [metric direct 0](#), on page 3061
- [metric maximum-hops](#), on page 3062
- [metric rib-scale](#), on page 3063
- [metric version 64bit](#), on page 3064
- [metric weights](#), on page 3065
- [mkdir](#), on page 3066
- [mode](#), on page 3067
- [mode](#), on page 3068
- [mode](#), on page 3069
- [mode tap-aggregation](#), on page 3070
- [module transceiver-frequency](#), on page 3071
- [monitor erspan granularity](#), on page 3072
- [monitor erspan origin ip-address](#), on page 3073
- [monitor erspan switch-id](#), on page 3074
- [monitor session](#), on page 3075
- [monitor session shut](#), on page 3076
- [monitor session type acl-capture](#), on page 3077
- [monitor session type erspan-destination](#), on page 3078
- [monitor session type erspan-source](#), on page 3079
- [monitor session warp](#), on page 3080
- [monitor session warp](#), on page 3081
- [mount](#), on page 3082
- [mount slot0](#), on page 3083

- [move](#), on page 3084
- [mst designated priority](#), on page 3085
- [mst root priority](#), on page 3086
- [mtrace](#), on page 3087
- [mtu](#), on page 3088
- [mtu1](#), on page 3089
- [mtu](#), on page 3090
- [mtu](#), on page 3091
- [mtu](#), on page 3092
- [mtu](#), on page 3093
- [mtu](#), on page 3094
- [mtu](#), on page 3095
- [multi-topology](#), on page 3096
- [multicast](#), on page 3097
- [multisite border-gateway interface](#), on page 3098
- [multisite ingress-replication](#), on page 3099
- [mvr-config](#), on page 3100
- [mvr-group](#), on page 3101
- [mvr-group](#), on page 3102
- [mvr-group](#), on page 3103
- [mvr-group](#), on page 3104
- [mvr-group](#), on page 3105
- [mvr-group](#), on page 3106
- [mvr-group](#), on page 3107
- [mvr-group](#), on page 3108
- [mvr-suppress-query vlan](#), on page 3109
- [mvr-type receiver](#), on page 3110
- [mvr-type source](#), on page 3111
- [mvr-vlan](#), on page 3112
- [mvr-vlan](#), on page 3113

m2rib debug ftag

```
m2rib debug ftag { add | del | mod } <ftag-id> <topo-id> { [ UCAST ] [ MCAST ] [ ACTIVE ] [ INACTIVE ] } + [ <proto> ] [ vampire-tap ]
```

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
ftag	Configure M2RIB's ftag db
add	Add an ftag
mod	Modify an ftag flags
del	Delete an ftag
<i>ftag-id</i>	ftag id
<i>topo-id</i>	topo id
<i>proto</i>	(Optional) Protocol owner id
UCAST	(Optional) Broadcast ftag
MCAST	(Optional) Multicast ftag
ACTIVE	(Optional) Active ftag
INACTIVE	(Optional) Inactive ftag
vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI

Command Mode

- /exec

m2rib debug gr-route add nh

```
m2rib debug gr-route { add | del } <vlan> { { <v4-source> <v4-group> } | { <v6-source> <v6-group> } } {
nh-if <if-name> | nh-sw <switch-id> } { [ WC_SRC ][ WC_GRP ][ NH_EXCLUDE ][ FLOOD_TO_VLAN
] [ LOCAL ][ REMOTE ][ IGNORE_STAR ] } + [ proto <proto> ] [ route-type <route-type> ] [ vampire-tap
]
```

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
gr-route	Perform group route operations on m2rib
add	Add a route next-hop
del	Delete a route next-hop
proto	(Optional) Protocol owning this next-hop
route-type	(Optional) Route type of this next-hop
nh-if	next-hop interface
nh-sw	next-hop switch
vlan	vlan key
v4-source	IPv4 Multicast traffic source
v4-group	IPv4 Multicast Group address
if-name	Specify the next hop interface
switch-id	Specify the next hop switch id
WC_SRC	(Optional) Source is wildcarded
WC_GRP	(Optional) Group is wildcarded
NH_EXCLUDE	(Optional) Next-hop excluded from ltl+1
FLOOD_TO_VLAN	(Optional) Broadcast (flood-to-vlan) special group
LOCAL	(Optional) Local members exist
REMOTE	(Optional) Remote members exist
IGNORE_STAR	(Optional) Do not combine with router-port oif list
proto	(Optional) Protocol owner id
route-type	(Optional) Route type

vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI
-------------	---

Command Mode

- /exec

m2rib debug log-size event-history

m2rib debug log-size event-history { <size> | small | medium | large }

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
log-size	Set log sizes
event-history	Set event-history size
<i>size</i>	Buffer size in KB
small	Set to default small log size
medium	Set to default medium log size
large	Set to default large log size

Command Mode

- /exec/configure

m2rib debug log-size transactions

```
m2rib debug log-size transactions { { received | u2rib | mfdm | pixm | eltm } [ error-log ] | announced } {
<size> | small | medium | large } <size_bytes>
```

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
log-size	Set log sizes
transactions	Set transaction log sizes
received	Set received transaction log size
announced	Set announced transaction log size
u2rib	Set U2RIB transaction log size
mfdm	Set MFDM transaction log size
pixm	Set PIXM transaction log size
eltn	Set ELTM transaction log size
error-log	(Optional) errors only log
<i>size</i>	Size in number of transactions
small	Set number of transactions default small log size (0 disables limits)
medium	Set number of transactions default medium log size
large	Set number of transactions default large log size
<i>size_bytes</i>	Max log size in number of bytes

Command Mode

- /exec/configure

m2rib debug omf enable

m2rib debug omf { enable | disable } <from-vlan> <to-vlan> [vampire-tap]

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
omf	Enable or disable Optimized Multicast Flood (OMF)
enable	Enable OMF
disable	Disable OMF
<i>from-vlan</i>	from vlan
<i>to-vlan</i>	to vlan
vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI

Command Mode

- /exec

m2rib debug pkt-recv enable

m2rib debug pkt-recv { enable | disable } <from-vlan> <to-vlan> <proto> [vampire-tap]

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
pkt-recv	Enable or disable protocol packet reception
enable	Enable packet receive
disable	Disable packet receive
<i>from-vlan</i>	from vlan
<i>to-vlan</i>	to vlan
<i>proto</i>	Protocol id
vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI

Command Mode

- /exec

m2rib debug swroute nh

m2rib debug swroute { add | mod | del } <ftag> <switch-id> nh <if-name> [proto <proto>] [route-type <route-type>] [vampire-tap]

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
swroute	Perform route operations on m2rib
add	Add a route next-hop
mod	Modify a route's next-hop
del	Delete a route next-hop
nh	next-hop
proto	(Optional) Protocol owning this next-hop
route-type	(Optional) Route type of this next-hop
<i>ftag</i>	ftag key
<i>switch-id</i>	switch id
<i>if-name</i>	Specify the next hop interface
<i>proto</i>	(Optional) Protocol owner id
<i>route-type</i>	(Optional) Route type
vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI

Command Mode

- /exec

m2rib debug topo

m2rib debug topo { create | del | add-vlans | del-vlans } <topo-id> <from-vlan> <to-vlan> [<proto>] [vampire-tap]

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
topo	Configure M2RIB's topo db
create	Create a topo in m2rib
del	Delete a topo in m2rib
add-vlans	Add vlans to an existing topo
del-vlans	Delete vlans from an existing topo
<i>topo-id</i>	topo id
<i>from-vlan</i>	from vlan
<i>to-vlan</i>	to vlan
<i>proto</i>	(Optional) Protocol owner id
vampire-tap	(Optional) Send a copy of all M2RIB generated messages to CLI

Command Mode

- /exec

m2rib debug topo loop-flush-timeout

m2rib debug topo [<topo-id>] loop-flush-timeout <timeout>

Syntax Description

m2rib	Configure m2rib
debug	Configure m2rib debug
topo	configure M2RIB's topology db
<i>topo-id</i>	(Optional) topo id
loop-flush-timeout	configure the loop flush timer value
<i>timeout</i>	Loop flush timeout value in ms

Command Mode

- /exec/configure

mac-addr

```
{ mac-addr <dstmac> <smac> [ dot1q <dot1q-id> ] }
```

Syntax Description

mac-addr	Mac
<i>dstmac</i>	Destination mac address
<i>smac</i>	Source mac address
dot1q	(Optional) Encapsulation dot1q/bd
<i>dot1q-id</i>	(Optional) Encapsulation dot1q/bd on which the mac is learnt

Command Mode

- /exec/configure/configngoamccpayload

mac-address

mac-address <mac_address_val> | no mac-address [<mac_address_val>]

Syntax Description

no	Negate a command or set its defaults
mac-address	Configure interface mac address (1)
<i>mac_address_val</i>	Static Router MAC address (1)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-ether-sub /exec/configure/if-eth-non-member /exec/configure/if-remote-ethernet-sub /exec/configure/if-port-channel /exec/configure/if-port-channel-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-ethernet-p2p

mac-address

mac-address <macaddress> | no mac-address [<macaddress>]

Syntax Description

no	Negate a command or set its defaults
mac-address	Virtual MAC address
<i>macaddress</i>	MAC address(FORMAT:xxxx.xxxx.xxxx)

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

mac-address

mac-address <mac-addr> | no mac-address

Syntax Description

no	Negate a command or set its defaults
mac-address	Manually set interface MAC address
<i>mac-addr</i>	MAC address

Command Mode

- /exec/configure/if-vlan-common

mac-address bpdu source version 2

[no] mac-address bpdu source version 2

Syntax Description

no	(Optional) Negate a command or set its defaults
mac-address	change vpc mac address
bpdu	bpdu
source	source
version	version
2	use version 2 bpdu source mac-address

Command Mode

- /exec/configure/vpc-domain

mac-address destination

{ mac-address { destination | source } <addr> } | { no mac-address { destination | source } }

Syntax Description

no	Negate a command or set its defaults
mac-address	specify flow mac address
source	specify flow source mac address
destination	specify flow destination mac address
<i>addr</i>	mac address

Command Mode

- /exec/configure/configngoamprofileflow

mac-address ipv6-extract

mac-address ipv6-extract | no mac-address ipv6-extract

Syntax Description

no	Negate a command or set its defaults
mac-address	Configure interface mac address (3)
ipv6-extract	Extract mac-address (3) from the IPv6 address configured on the interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-ether-sub /exec/configure/if-eth-non-member /exec/configure/if-remote-ethernet-sub /exec/configure/if-port-channel-sub /exec/configure/if-port-channel

mac-learn disable

mac-learn disable | no mac-learn disable

Syntax Description

no	Negate a command or set its defaults
mac-learn	Mac Learning disable/enable
disable	Mac Learning disable to use switch as a HUB. Do a clear mac address-table dynamic after disabling mac learning

Command Mode

- /exec/configure

mac-learn disable

mac-learn disable | no mac-learn disable

Syntax Description

no	Negate a command or set its defaults
mac-learn	Mac Learning disable/enable on vlan
disable	Mac Learning disable on vlan

Command Mode

- /exec/configure/vlan-config

mac-list permit

```
{ mac-list <name> [ seq <seq> ] { permit | deny } <mac-addr> [ <mac-mask> ] } | { no mac-list <name> [ seq <seq> ] [ { permit | deny } <mac-addr> [ <mac-mask> ] ] }
```

Syntax Description

no	Negate a command or set its defaults
mac-list	Build a mac list
<i>name</i>	Name of prefix list
seq	(Optional) Sequence number of an entry
<i>seq</i>	(Optional) Sequence number
permit	Specify routes to forward
deny	Specify routes to reject
<i>mac-addr</i>	MAC address
<i>mac-mask</i>	(Optional) MAC Mask. Default Mask is ffff.ffff.ffff

Command Mode

- /exec/configure

mac access-list

[no] mac access-list <name> [client <clienttype> <clientID>]

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC configuration commands
access-list	Configure access list
<i>name</i>	List name
client	(Optional) set client type
<i>clienttype</i>	(Optional) CLI/ONEP
<i>clientID</i>	(Optional) client appID

Command Mode

- /exec/configure

mac address-table aging-time

mac address-table aging-time { 0 | <seconds> } [{ vlan <vlan-id> }] [__readonly__ <info_str>] | no mac address-table aging-time [[0 | <seconds>]]

Syntax Description

no	Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
aging-time	Aging time
0	0 disables aging
<i>seconds</i>	Aging time in seconds.
vlan	(Optional) VLAN
<i>vlan-id</i>	(Optional) VLAN ID
__readonly__	(Optional)
<i>info_str</i>	(Optional) Information

Command Mode

- /exec/configure

mac address-table guard-vpc-peergw-mac

[no] mac address-table guard-vpc-peergw-mac

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
guard-vpc-peergw-mac	Prevent vPC Peer gateway MAC Spoofing

Command Mode

- /exec/configure

mac address-table limit system

```
mac address-table limit { system | vlan <id> } [ <limitcount> ] [ actiondrop ] [ __readonly__ <info_str> ] |
no mac address-table limit { system | vlan <id> } [ <limitcount> ] [ actiondrop ]
```

Syntax Description

no	Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
limit	Restrict number of Mac addresses learnt
system	System-wide
vlan	VLAN
<i>id</i>	List of VLAN ids
<i>limitcount</i>	(Optional) Mac address limit count
actiondrop	(Optional) Drop packets instead of flooding
__readonly__	(Optional)
<i>info_str</i>	(Optional) Information

Command Mode

- /exec/configure

mac address-table loop-detect port-down

mac address-table loop-detect port-down | no mac address-table loop-detect port-down

Syntax Description

no	Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
loop-detect	Action for Mac loop detection
port-down	Take port-down action for mac loop detection

Command Mode

- /exec/configure

mac address-table multicast vlan interface

[no] mac address-table multicast <mac-address> { vlan <vlan> | bridge-domain <bdid> } interface [vsi] <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
multicast	mcast mac OIF Static Entry
<i>mac-address</i>	mcast MAC Address, not in Unicast IP Range
vlan	VLAN
<i>vlan</i>	VLAN
bridge-domain	BD
<i>bdid</i>	BD
interface	Interface
vsi	(Optional) Specify if this interface is a VSI
<i>interface</i>	Interface name

Command Mode

- /exec/configure

mac address-table notification mac-move

mac address-table notification mac-move | no mac address-table notification mac-move

Syntax Description

no	Negate a command
mac	MAC configuration commands
address-table	MAC Address Table
notification	Notify of mac-move
mac-move	MAC move notification on syslog

Command Mode

- /exec/configure

mac address-table notification threshold

mac address-table notification threshold [limit <percentage> interval <seconds>] | no mac address-table notification threshold

Syntax Description

no	Negate a command
mac	MAC configuration commands
address-table	MAC Address Table
notification	Notify of mac-move
threshold	MAC Address Table threshold notification
limit	(Optional) Specify the percentage limit beyond which notifications are enabled
<i>percentage</i>	(Optional) Percentage of MAC Table Consumption
interval	(Optional) Minimum time in seconds between two notifications
<i>seconds</i>	(Optional) Interval time in seconds

Command Mode

- /exec/configure

mac address-table static vlan interface

```
mac address-table static <mac-address> vlan <vlan-id> { interface <interface-name> | drop } [ auto-learn ] [
__readonly__ <info_str> ] | no mac address-table static <mac-address> vlan <vlan-id>
```

Syntax Description

no	Negate a command or set its defaults
mac	MAC configuration commands
address-table	MAC Address Table
static	Static Entry
<i>mac-address</i>	MAC Address
vlan	VLAN
<i>vlan-id</i>	VLAN ID
interface	Interface
<i>interface-name</i>	Interface name
drop	Drop all traffic
auto-learn	(Optional) Allow moving this MAC address
__readonly__	(Optional)
<i>info_str</i>	(Optional) Information

Command Mode

- /exec/configure

mac address-table static vni

mac address-table static <mac-address> vni <vni-id>

Syntax Description

mac	MAC configuration commands
address-table	MAC Address Table
static	Static Entry
<i>mac-address</i>	MAC Address
vni	Virtual Network Identifier
<i>vni-id</i>	VNI ID

Command Mode

- /exec/configure

mac address

[no] mac address { <macaddr> }

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	Configure vMAC address options for Pathway
address	Pathway will use a specified vMAC address
<i>macaddr</i>	48-bit MAC address in HEX

Command Mode

- /exec/configure/if-eth-any/vrrs

mac address inherit

mac address inherit

Syntax Description

mac	Configure vMAC address options for Pathway
address	Pathway will use a specified vMAC address
inherit	Pathway will inherit vMAC

Command Mode

- /exec/configure/if-eth-any/vrrs

mac advert interval

[no] mac advert interval | mac advert interval <macint>

Syntax Description

no	Negate a command or set its defaults
mac	Configure vMAC address options for Pathway
advert	Specify vMAC unsolicited advertisements
interval	Specify interval between vMAC unsolicited advertisements
<i>macint</i>	Advertisement Interval in seconds

Command Mode

- /exec/configure/if-eth-any/vrrs

mac packet-classify

[no] mac packet-classify

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC
packet-classify	Force mac classification of packets

Command Mode

- /exec/configure/vlan

mac packet-classify

[no] mac packet-classify

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC configuration commands
packet-classify	Force mac classification of packets

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-remote-ethernet-switch
/exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-all

mac port access-group

[no] mac port access-group <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
mac	MAC configuration commands
port	Port policy
access-group	Specify access control for packets
<i>name</i>	List name

Command Mode

- /exec/configure/if-set-acl-l2

managed-config-flag

[no] managed-config-flag <state>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>state</i>	

Command Mode

- /exec/configure/config-ra-guard

management

[no] management

Syntax Description

no	(Optional) Negate a command or set its defaults
management	Allow in-band management access to VLAN Interface IP address

Command Mode

- /exec/configure/if-vlan-common

map-notify-group

```
{ [ no ] map-notify-group { <addr> | <addr6> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
map-notify-group	Group address to send and receive site specific Map-Notify messages
<i>addr</i>	IPv4 group address

Command Mode

- /exec/configure/lisp-dynamic-oid /exec/configure/vrf/lisp-dynamic-oid

map-server key

```
{ { [ no ] map-server { <ms> | <ms6> } [ key-type { sha1 | sha2 } ] key <key> } | { [ no ] map-server { <ms> | <ms6> } proxy-reply } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
map-server	To interact with Map-Server
<i>ms</i>	Address of IPv4 map-server
key-type	(Optional) Authentication key type, either sha1 or sha2
sha1	(Optional) Use sha1 authentication in Map-Register messages
sha2	(Optional) Use sha2 authentication in Map-Register messages
key	Authentication key used with Map-Server
<i>key</i>	SHA-1 password key
proxy-reply	Request Map-Server to send Map-Replies on behalf of dynamic-EID

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

marker-packet-n3500

[no] marker-packet-n3500 [<interval> | seconds <interval1> | milliseconds <interval2>]

Syntax Description

no	(Optional) Negate a command or set its defaults
marker-packet-n3500	Enable/Disable send marker packet
<i>interval</i>	(Optional) range between <1-4> second
seconds	(Optional) Configure interval in secs
<i>interval1</i>	(Optional) range between <1-4> second
milliseconds	(Optional) Interval in milli second.
<i>interval2</i>	(Optional) range between <100-900> msec, increments in multiples of 100

Command Mode

- /exec/configure/config-monitor-erspan-src

marker-packet

[no] marker-packet [<interval>]

Syntax Description

no	(Optional) Negate a command or set its defaults
marker-packet	Enable/Disable send marker packet
<i>interval</i>	(Optional)

Command Mode

- /exec/configure/config-monitor-erspan-src

master ipv4

[no] master ipv4 <ip>

Syntax Description

no	(Optional) Negate a command or set its defaults
master	master
ipv4	ipv4
<i>ip</i>	IPv4 address (A.B.C.D) of slave

Command Mode

- /exec/configure/ptp-ucast-slave

match-address

[no] match-address

Syntax Description

no	(Optional) Negate a command or set its defaults
match-address	Match addresses in advertisement packets

Command Mode

- /exec/configure/if-eth-any/vrrpv3

match

```
[no] match { { access-group name <acl-name> } | [ not ] { dscp { <dscp-list> | { <dscp-enum> } + } | { {
packet length <len-list> | ip rtp <port-list> } [ replace ] } | { cos <cos-list> } | { qos-group <qos-group-list>
} | { precedence { <precedence-list> | { <prec-enum> } + } } | { protocol <protocol-enum> } | { mpls
experimental topmost <exp-list> } | { ip roce <port-list> } } }
```

Syntax Description

<i>dscp-list</i>	<dscp-enum>
<i>cos-list</i>	
<i>precedence-list</i>	<prec-enum>
no	(Optional) Negate a command or set its defaults
replace	(Optional) Replace current ip rtp / packet length configuration
match	Classification criteria
not	(Optional) Negate this match result
access-group	Access group
name	Named Access List
<i>acl-name</i>	Access List name
dscp	DSCP in IP(v4) and IPv6 packets
<i>dscp-enum</i>	
cos	IEEE 802.1Q Class of Service
qos-group	Qos-group
<i>qos-group-list</i>	List of qos-group values
precedence	Precedence in IP(v4) and IPv6 packets
<i>prec-enum</i>	
protocol	Protocol
<i>protocol-enum</i>	
packet	Packet
length	Length of IP datagram
<i>len-list</i>	List of IP packet length
ip	IP

rtp	Real Time Protocol
<i>port-list</i>	UDP port list that are using RTP
mpls	Match on MPLS label
experimental	Match on MPLS Experimental label
topmost	Match on topmost MPLS label
ip	IP
roce	Roce protocol. port to be used 3804
<i>port-list</i>	UDP port list that are using RoCE
<i>exp-list</i>	List of MPLS exp values

Command Mode

- /exec/configure/class-map

match

```
[no] match { [ not ] { { discard-class <discard-class-list> } | { class-map <cmmap-name> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
not	(Optional) Negate this match result
discard-class	Discard class
<i>discard-class-list</i>	List of discard-class values
class-map	Class map
<i>cmmap-name</i>	Match class-map name

Command Mode

- /exec/configure/class-map

match

```
[no] match { { access-group name <acl-name> } | [ not ] { { cos <cos-value> } | any | { eth-src <mac_src>
<mac_src_wild> } | { eth-dest <mac_dest> <mac_dest_wild> } | { eth-type <eth-value> } | { vlan
<vlan-number> } | { ip-tos <tos-value> <tos-mask> } | { ip-protocol <ip-protocol-value> } | { ip-src-addr
<ip-s-addr> <ip-s-mask> } | { ip-dst-addr <ip-d-addr> <ip-d-mask> } | { tcp-src-port <tcp-src-port-addr> } |
{ tcp-dst-port <tcp-dest-port-addr> } | { udp-src-port <udp-src-port-addr> } | { udp-dst-port
<udp-dest-port-addr> } | { input-interface <ifnum> } | { ipv6-src-addr <ipv6-s-addr> <ipv6-s-mask> } | {
ipv6-dst-addr <ipv6-d-addr> <ipv6-d-mask> } | { ipv6-protocol <ipv6-protocol-value> } | { ipv6-flowlabel
<ipv6-flowlabel-value> } | { icmpv6-type <icmpv6-type-value> } | { icmpv6-code <icmpv6-code-value> } |
{ ipv4-dscp <ipv4-dscp-list> } | { ipv6-dscp <ipv6-dscp-list> } | { dscp { <dscp-list> | <dscp-enum> } + } |
{ precedence { <precedence-list> | <prec-enum> } + } | { discard-class <discard-class-list> } | { qos-group
<qos-group-list> } | { class-map <cmap-name-plc> } | { protocol <protocol-enum> } | { packet length <len-list>
} | { ip rtp <port-list> } | { mpls experimental topmost <exp-list> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
not	(Optional) Negate this match result
access-group	Access group
name	Named Access List
<i>acl-name</i>	Access List name
cos	IEEE 802.1Q class of service
dscp	DSCP in IP(v4) and IPv6 packets
<i>dscp-list</i>	List of DSCP values
<i>dscp-enum</i>	
precedence	Precedence in IP(v4) and IPv6 packets
<i>precedence-list</i>	List of precedence values
<i>prec-enum</i>	
discard-class	Discard class
<i>discard-class-list</i>	List of discard-class values
qos-group	Qos-group
<i>qos-group-list</i>	List of qos-group values
class-map	Class map
<i>cmap-name-plc</i>	Match class-map name

protocol	Protocol
<i>protocol-enum</i>	
packet	Packet
length	Length of IP datagram
<i>len-list</i>	list of IP packet length
ip	IP
rtp	Real Time Protocol
<i>port-list</i>	UDP port list that are using RTP
mpls	Match on MPLS label
experimental	Match on MPLS Experimental label
topmost	Match on topmost MPLS label
<i>exp-list</i>	List of MPLS exp values
any	Match on Any Filter
eth-dest	Match on Layer 2 destination MAC address
eth-src	Match on Layer 2 source MAC address
eth-type	Match on Ether type
vlan	Match on 802.1Q vlan
ip-tos	Match on IPv4 TOS
ip-protocol	Match on IP protocol
ip-src-addr	Match on IPv4 source address
ip-dst-addr	Match on IPv4 destination address
ipv6-src-addr	Match on IPv6 source address
ipv6-dst-addr	Match on IPv6 destination address
tcp-src-port	Match on TCP source port
tcp-dst-port	Match on TCP source port
udp-src-port	Match on UDP source port
udp-dst-port	Match on UDP source port
input-interface	Match on physical input interface
ipv6-protocol	Match on IPv6 Protocol Value

<i>ipv6-flowlabel</i>	Match on IPv6 Flowlabel
<i>icmpv6-type</i>	Match on ICMPv6 Message Type
<i>icmpv6-code</i>	Match on ICMPv6 Message Code
<i>ipv4-dscp</i>	Match on DSCP for IPV4 Packets
<i>ipv6-dscp</i>	Match on DSCP for IPV6 Packets
<i>cos-value</i>	class of service Value
<i>mac_src</i>	Source MAC address
<i>mac_src_wild</i>	Source MAC mask
<i>mac_dest</i>	Destination MAC address
<i>mac_dest_wild</i>	Destination MAC mask
<i>eth-value</i>	Ethernet type
<i>vlan-number</i>	Vlan number
<i>tos-value</i>	IPv4 TOS
<i>tos-mask</i>	IPV4 TOS Mask for DSCP
<i>ip-protocol-value</i>	IPV4 protocol
<i>ip-s-addr</i>	IPV4 address in format a.b.c.d
<i>ip-d-addr</i>	IPV4 address in format a.b.c.d
<i>ip-s-mask</i>	IPV4 address Mask in format a.b.c.d
<i>ip-d-mask</i>	IPV4 address Mask in format a.b.c.d
<i>tcp-src-port-addr</i>	Transport layer port number
<i>tcp-dest-port-addr</i>	Transport layer port number
<i>udp-src-port-addr</i>	Transport layer port number
<i>udp-dest-port-addr</i>	Transport layer port number
<i>ifnum</i>	Physical interface Name and Number
<i>ipv6-protocol-value</i>	IPv6 Protocol Value
<i>ipv6-flowlabel-value</i>	IPv6 Flowlabel
<i>icmpv6-type-value</i>	ICMPv6 Message Type
<i>icmpv6-code-value</i>	ICMPv6 Message Code
<i>ipv4-dscp-list</i>	List of IPV4 DSCP values

<i>ipv6-dscp-list</i>	List of IPV6 DSCP values
-----------------------	--------------------------

Command Mode

- /exec/configure/class-map/type/plc

match access-group name

[no] match access-group name <acs-grp-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
access-group	Match with given access group
name	Name of the access group
<i>acs-grp-name</i>	Match parameter for class-map

Command Mode

- /exec/configure/cmap

match address

[no] match <ip_ipv6_mac> address <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Specify the match clause
<i>ip_ipv6_mac</i>	IP/IPv6/MAC
address	Match an access list
<i>name</i>	List name

Command Mode

- /exec/configure/vacl

match as-number

[no] match as-number [{ <asnum> | <asnum_range> } +] { <asnum_trail> | <asnum_range_trail> }

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
as-number	Match BGP peer AS number
<i>asnum</i>	(Optional) <AA4> ,
<i>asnum_range</i>	(Optional) <AA4>-<AA4> ,
<i>asnum_trail</i>	<AA4> ,
<i>asnum_range_trail</i>	<AA4>-<AA4> ,

Command Mode

- /exec/configure/route-map

match as-number as-path-list

match as-number as-path-list <aspl-name> + | no match as-number as-path-list { <aspl-name> | <aspl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
as-number	Match BGP peer AS number
as-path-list	AS-path access-list
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	Known as-path access-list name

Command Mode

- /exec/configure/route-map

match as-path

match as-path <aspl-name> + | no match as-path { <aspl-name> | <aspl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
as-path	Match BGP AS path list
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	AS path access list name
<i>aspl-name</i>	Known as-path access-list name

Command Mode

- /exec/configure/route-map

match class-map

[no] match class-map < cmap-name >

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
class-map	Class map
<i>cmap-name</i>	class map name

Command Mode

- /exec/configure/class-map/type/queuing

match community

[no] match community <name> + [exact-match]

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
community	Match BGP community list
<i>name</i>	Community list name
exact-match	(Optional) Do exact matching of communities

Command Mode

- /exec/configure/route-map

match cos

[no] match cos <cos-list>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
cos	IEEE 802.1Q class of service
<i>cos-list</i>	List of class-of-service values

Command Mode

- /exec/configure/class-map/type/uf

match cos

[no] match cos <cos-list>

Syntax Description

<i>cos-list</i>	
no	(Optional) Negate a command or set its defaults
match	Classification criteria
cos	IEEE 802.1Q Class of Service

Command Mode

- /exec/configure/class-map/type/queuing

match datalink

[no] match datalink { mac source-address | mac destination-address | ethertype | vlan }

Syntax Description

match	Specify a key field
datalink	datalink (Layer 2) attributes
mac	MAC Address
source-address	Source MAC Address
destination-address	Destination MAC Address
ethertype	Ethertype
vlan	VLAN ID

Command Mode

- /exec/configure/nfm-record

match datalink

[no] match datalink { mac source-address | mac destination-address | ethertype }

Syntax Description

match	Specify a key field
datalink	datalink (Layer 2) attributes
mac	MAC Address
source-address	Source MAC Address
destination-address	Destination MAC Address
ethertype	Ethertype

Command Mode

- /exec/configure/config-fte-record

match dscp

[no] match dscp { <dscp-list> | <dscp-enum> } +

Syntax Description

<i>dscp-list</i>	<dscp-enum>
no	(Optional) Negate a command or set its defaults
match	Classification criteria
dscp	DSCP in IP(v4) and IPv6 packets
<i>dscp-enum</i>	

Command Mode

- /exec/configure/color-cmap

match dscp

[no] match dscp { <dscp-list> } +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
dscp	DSCP in IP(v4) packets
<i>dscp-list</i>	List of DSCP values

Command Mode

- /exec/configure/class-map/type/queuing

match exception

```
[no] match exception { { ip | ipv6 } { option | { icmp { redirect | unreachable } } | muncast } } | ttl-failure
| glean | mtu-failure | nat-flow | sflow | { multicast { rpf-failure | sg-rpf-failure | dest-miss | ipv6-rpf-failure |
ipv6-sg-rpf-failure | ipv6-dest-miss } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
exception	Match exception packets
ip	ipv4 match criteria
ipv6	ipv6 match criteria
option	Match ip/ipv6 option exception packets
icmp	Icmp redirect packets
redirect	Send redirected packets back to sender
unreachable	Send unreachable packets back to sender
muncast	IP unicast packets with multicast MAC
ttl-failure	Failed in ttl
mtu-failure	mtu-failure
glean	Glean packets
multicast	multicast packets
rpf-failure	multicast rpf check failure
sg-rpf-failure	multicast sg rpf check failure
dest-miss	L3 multicast destination lookup failure
ipv6-rpf-failure	IPv6 multicast rpf check failure
ipv6-sg-rpf-failure	IPv6 multicast sg rpf check failure
ipv6-dest-miss	IPv6 L3 multicast destination lookup failure
nat-flow	ipv4 software nat flow packets
sflow	sflow packets

Command Mode

- /exec/configure/cmap

match extcommunity

[no] match extcommunity <name> + [exact-match]

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
extcommunity	Match BGP community list
<i>name</i>	Extended Community list name
exact-match	(Optional) Do exact matching of extended communities

Command Mode

- /exec/configure/route-map

match interface

[no] match interface <name> +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
interface	Match first hop interface of route
<i>name</i>	Interface name

Command Mode

- /exec/configure/route-map

match ip address

[no] match ip address <name> +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
ip	Configure IP features
address	Match address of route or match packet
<i>name</i>	IP access-list name (for use in route-maps for PBR only)

Command Mode

- /exec/configure/route-map

match ip address prefix-list

match ip address prefix-list <ipv4-pfl-name> + | no match ip address prefix-list { <ipv4-pfl-name> | <ipv4-pfl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ip	Configure IP features
address	Match address of route or match packet
prefix-list	Match entries of prefix-lists
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ip multicast rp

```
{ match ip multicast { { rp <iprp> [ rp-type <iprptype> ] } | { group <gprefix> } | { source <ipsrc> } } + } |
{ match ip multicast { { rp <iprp> [ rp-type <iprptype> ] } | { group-range <gaddr_start> to <gaddr_end> }
| { source <ipsrc> } } + } | { no match ip multicast }
```

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ip	Configure IP features
multicast	Match multicast attributes
rp	Rendezvous point
<i>iprp</i>	IPv4 rendezvous prefix
rp-type	(Optional) Multicast rendezvous point type
<i>iprptype</i>	(Optional) IPv4 rendezvous point type
group	Multicast Group prefix
<i>gprefix</i>	IPv4 group prefix
group-range	Multicast Group address range
<i>gaddr_start</i>	First Group address
to	Range
<i>gaddr_end</i>	Last Group address
source	Multicast source address
<i>ipsrc</i>	IPv4 source prefix

Command Mode

- /exec/configure/route-map

match ip next-hop prefix-list

match ip next-hop prefix-list <ipv4-pfl-name> + | no match ip next-hop prefix-list { <ipv4-pfl-name> | <ipv4-pfl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ip	Configure IP features
next-hop	Match next-hop address of route
prefix-list	Match entries of prefix-lists
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ip protocol

[no] match ip { protocol | tos }

Syntax Description

match	Specify a key field
ip	IP attributes
protocol	Protocol
tos	TOS

Command Mode

- /exec/configure/nfm-record

match ip route-source prefix-list

match ip route-source prefix-list <ipv4-pfl-name> + | no match ip route-source prefix-list { <ipv4-pfl-name> | <ipv4-pfl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ip	Configure IP features
route-source	Match advertising source address of route
prefix-list	Match entries of prefix-lists
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Name of prefix-list
<i>ipv4-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ipv4 protocol

[no] match ipv4 { protocol | tos }

Syntax Description

match	Specify a key field
ipv4	IPv4 attributes
protocol	Protocol
tos	TOS

Command Mode

- /exec/configure/config-fte-record

match ipv4 source address

[no] match ipv4 { source | destination } address

Syntax Description

match	Specify a key field
ipv4	IPv4 attributes
source	Source Address
destination	Destination Address
address	Address

Command Mode

- /exec/configure/config-fte-record

match ipv4 source address

[no] match ipv4 { source | destination } address

Syntax Description

match	Specify a key field
ipv4	IPv4 attributes
source	Source Address
destination	Destination Address
address	Address

Command Mode

- /exec/configure/nfm-record

match ipv4 transport destination

[no] match ipv4 transport { destination-port | source-port }

Syntax Description

match	Specify a key field
ipv4	IPv4 attributes
transport	Transport layer fields
destination-port	Transport destination port
source-port	Transport source port

Command Mode

- /exec/configure/config-fte-record

match ipv6

```
[no] match ipv6 { { { source | destination } address } | { flow-label | options } }
```

Syntax Description

match	Specify a key field
ipv6	IPv6 attributes
source	Source Address
destination	Destination Address
address	Address
flow-label	Flow label
options	Options

Command Mode

- /exec/configure/nfm-record

match ipv6

```
[no] match ipv6 { { { source | destination } address } | { flow-label } }
```

Syntax Description

match	Specify a key field
ipv6	IPv6 attributes
source	Source Address
destination	Destination Address
address	Address
flow-label	Flow label

Command Mode

- /exec/configure/config-fte-record

match ipv6 address

[no] match ipv6 address <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
ipv6	Configure IPv6 features
address	Match address of route or match packet
<i>name</i>	IPv6 access-list name (for use in route-maps for PBR only)

Command Mode

- /exec/configure/route-map

match ipv6 address prefix-list

match ipv6 address prefix-list <ipv6-pfl-name> + | no match ipv6 address prefix-list { <ipv6-pfl-name> | <ipv6-pfl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ipv6	Configure IPv6 features
address	Match address of route or match packet
prefix-list	Match entries of prefix-lists
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ipv6 multicast rp

```
{ match ipv6 multicast { { rp <ipv6rp> [ rp-type <ipv6rptype> ] } | { group <gprefix> } | { source <ipv6src> } } + } | { match ipv6 multicast { { rp <ipv6rp> [ rp-type <ipv6rptype> ] } | { group-range <gaddr_start> to <gaddr_end> } | { source <ipv6src> } } + } | { no match ipv6 multicast }
```

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ipv6	Configure IPv6 features
multicast	Match multicast attributes
rp	Rendezvous point
rp-type	(Optional) Multicast rendezvous point type
<i>ipv6rptype</i>	(Optional) IPv6 rendezvous point type
group	Multicast group address
group-range	Multicast Group address range
to	Range
source	Multicast source address

Command Mode

- /exec/configure/route-map

match ipv6 next-hop prefix-list

match ipv6 next-hop prefix-list <ipv6-pfl-name> + | no match ipv6 next-hop prefix-list { <ipv6-pfl-name> | <ipv6-pfl-name> } +

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ipv6	Configure IPv6 features
next-hop	Match next-hop address of route
prefix-list	Match entries of prefix-lists
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ipv6 protocol

[no] match ipv6 { protocol | tos }

Syntax Description

match	Specify a key field
ipv6	IPv6 attributes
protocol	Protocol
tos	TOS

Command Mode

- /exec/configure/config-fte-record

match ipv6 route-source prefix-list

```
match ipv6 route-source prefix-list <ipv6-pfl-name> + | no match ipv6 route-source prefix-list {
<ipv6-pfl-name> | <ipv6-pfl-name> } +
```

Syntax Description

no	Negate a command or set its defaults
match	Match values from routing table
ipv6	Configure IPv6 features
route-source	Match advertising source address of route
prefix-list	Match entries of prefix-lists
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Name of prefix-list
<i>ipv6-pfl-name</i>	Known prefix-list name

Command Mode

- /exec/configure/route-map

match ipv6 transport destination

[no] match ipv6 transport { destination-port | source-port }

Syntax Description

match	Specify a key field
ipv6	IPv6 attributes
transport	Transport layer fields
destination-port	Transport destination port
source-port	Transport source port

Command Mode

- /exec/configure/config-fte-record

match metric

[no] match metric { <measure> [<plus-minus> <deviation>] } +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
metric	Match metric of route
<i>plus-minus</i>	(Optional) +-
<i>measure</i>	Metric value
<i>deviation</i>	(Optional) Deviation value

Command Mode

- /exec/configure/route-map

match ospf-area

[no] match ospf-area <area> +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
ospf-area	Match ospf area
<i>area</i>	area id

Command Mode

- /exec/configure/route-map

match protocol

[no] match protocol { fcoe | iscsi | tcp }

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
protocol	Protocol
fcoe	FCoE
iscsi	ISCSI
tcp	TCP

Command Mode

- /exec/configure/class-map/type/uf

match protocol arp

```
[no] match protocol { arp | mpls [ router-alert | exp <exp_value> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
protocol	Protocol
arp	IP ARP
mpls	Multi-protocol Label Switching
router-alert	(Optional) Match packets with router-alert label set to 1 for OTV Overlay frames
exp	(Optional) Match packets on MPLS exp bits
<i>exp_value</i>	(Optional) Exp bits value

Command Mode

- /exec/configure/cmap

match qos-group

[no] match qos-group { <qos-group-list> } +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
qos-group	QoS Group
<i>qos-group-list</i>	List of qos-group values

Command Mode

- /exec/configure/class-map/type/queuing

match qos-group2

[no] match qos-group2 { <qos-group-list> }

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
qos-group2	QoS Group
<i>qos-group-list</i>	

Command Mode

- /exec/configure/class-map/type/queuing

match qos-group2

[no] match qos-group2 <qos-group-list>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
qos-group2	QoS Group
<i>qos-group-list</i>	

Command Mode

- /exec/configure/class-map/type/uf

match qos-group

[no] match qos-group <qos-group-list>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
qos-group	QoS Group
<i>qos-group-list</i>	List of qos-group values

Command Mode

- /exec/configure/class-map/type/uf

match redirect

[no] match redirect <opt_match_redirect>

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Classification criteria
redirect	Match redirected packets
<i>opt_match_redirect</i>	Match criteria for redirected packets

Command Mode

- /exec/configure/cmap

match route-type

[no] match route-type { external | internal | level-1 | level-2 | local | nssa-external | type-1 | type-2 | inter-area | intra-area } +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
route-type	Match route-type of route
external	external route (BGP, EIGRP and OSPF type 1/2)
internal	internal route (including OSPF intra/inter area)
level-1	IS-IS level-1 route
level-2	IS-IS level-2 route
local	locally generated route
nssa-external	nssa-external route (OSPF type 1/2)
type-1	OSPF external type 1 route
type-2	OSPF external type 2 route
inter-area	OSPF inter area route
intra-area	OSPF intra area route

Command Mode

- /exec/configure/route-map

match source-protocol

[no] match source-protocol <src_prot> +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
source-protocol	Match source protocol
<i>src_prot</i>	Protocol instance name

Command Mode

- /exec/configure/route-map

match tag

[no] match tag <tagid> +

Syntax Description

no	(Optional) Negate a command or set its defaults
match	Match values from routing table
tag	Match tag of route
<i>tagid</i>	Tag value

Command Mode

- /exec/configure/route-map

match transport destination

[no] match transport { destination-port | source-port }

Syntax Description

match	Specify a key field
transport	Transport layer fields
destination-port	Transport destination port
source-port	Transport source port

Command Mode

- /exec/configure/nfm-record

max-backoff

max-backoff <maxbackoff-val> | no max-backoff

Syntax Description

no	Negate a command or set its defaults
max-backoff	OpenFlow controller maximum backoff timer (default is 8 seconds)
<i>maxbackoff-val</i>	max backoff timer value in secs

Command Mode

- /exec/configure/openflow/switch

max-backoff

max-backoff <maxbackoff-val> | no max-backoff

Syntax Description

no	Negate a command or set its defaults
max-backoff	OpenFlow controller maximum backoff timer (default is 8 seconds)
<i>maxbackoff-val</i>	max backoff timer value in secs

Command Mode

- /exec/configure/openflow/switch/sub-switch

max-lsa

[no] max-lsa <maximum-number> [<threshold>] [warning-only | [ignore-time <ignore-time-minutes>] [ignore-count <ignore-count-number>] [reset-time <reset-time-minutes>]]

Syntax Description

no	(Optional) Negate a command or set its defaults
max-lsa	Feature to limit the number of non-self-originated LSAs
<i>maximum-number</i>	Set maximum number of non self-generated LSAs
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Log a warning message when limit is exceeded
ignore-time	(Optional) Set time during which all adjacencies are suppressed
<i>ignore-time-minutes</i>	(Optional) ignore-time in minutes
ignore-count	(Optional) Set count on how many times adjacencies can be suppressed
<i>ignore-count-number</i>	(Optional) ignore-count
reset-time	(Optional) Set number of minutes after which ignore-count is reset to zero
<i>reset-time-minutes</i>	(Optional) reset-time in minutes

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

max-lsa

[no] max-lsa <maximum-number> [<threshold>] [warning-only | [ignore-time <ignore-time-minutes>] [ignore-count <ignore-count-number>] [reset-time <reset-time-minutes>]]

Syntax Description

no	(Optional) Negate a command or set its defaults
max-lsa	Feature to limit the number of non-self-originated LSAs
<i>maximum-number</i>	Set maximum number of non self-generated LSAs
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Log a warning message when limit is exceeded
ignore-time	(Optional) Set time during which all adjacencies are suppressed
<i>ignore-time-minutes</i>	(Optional) ignore-time in minutes
ignore-count	(Optional) Set count on how many times adjacencies can be suppressed
<i>ignore-count-number</i>	(Optional) ignore-count
reset-time	(Optional) Set number of minutes after which ignore-count is reset to zero
<i>reset-time-minutes</i>	(Optional) reset-time in minutes

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

max-lsp-lifetime

max-lsp-lifetime <lifetime> | no max-lsp-lifetime [<lifetime>]

Syntax Description

no	Negate a command or set its defaults
max-lsp-lifetime	Set maximum LSP lifetime
<i>lifetime</i>	Maximum LSP lifetime in seconds

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

max-lsp-lifetime

max-lsp-lifetime <lifetime> | no max-lsp-lifetime [<lifetime>]

Syntax Description

no	Negate a command or set its defaults
max-lsp-lifetime	Set maximum LSP lifetime
<i>lifetime</i>	Maximum LSP lifetime in seconds

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

max-lsp-lifetime

max-lsp-lifetime <lifetime> | no max-lsp-lifetime [<lifetime>]

Syntax Description

no	Negate a command or set its defaults
max-lsp-lifetime	Set maximum LSP lifetime
<i>lifetime</i>	Maximum LSP lifetime in seconds

Command Mode

- exec/configure/l2mp-isis/l2mp-isis-vrf-common

max-metric router-lsa

```
[no] max-metric router-lsa [ external-lsa [ <max-metric-extlsa> ] ] [ stub-prefix-lsa ] [ on-startup [ <timeout> ] ] [ wait-for bgp <as> ] ] [ inter-area-prefix-lsa [ <max-metric-sumlsa> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
max-metric	Maximize the cost metric
router-lsa	Router LSA
external-lsa	(Optional) External LSAs
<i>max-metric-extlsa</i>	(Optional) Max metric value for external LSAs
stub-prefix-lsa	(Optional) Advertise Max metric for Stub links as well
on-startup	(Optional) Effective only at startup
<i>timeout</i>	(Optional) Wait period in seconds after startup
wait-for	(Optional) Wait for an event to advertise normal metric
bgp	(Optional) BGP Convergence
<i>as</i>	(Optional) ASN of BGP to wait for
inter-area-prefix-lsa	(Optional) Inter-area-prefix LSAs
<i>max-metric-sumlsa</i>	(Optional) Max metric value for summary LSAs

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

max-metric router-lsa

```
[no] max-metric router-lsa [ external-lsa [ <max-metric-extlsa> ] ] [ include-stub ] [ on-startup [ <timeout> ]
[ wait-for bgp <as> ] ] [ summary-lsa [ <max-metric-sumlsa> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
max-metric	Maximize the cost metric
router-lsa	Router LSA
external-lsa	(Optional) External LSAs
<i>max-metric-extlsa</i>	(Optional) Max metric value for external LSAs
include-stub	(Optional) Advertise Max metric for Stub links as well
on-startup	(Optional) Effective only at startup
<i>timeout</i>	(Optional) Wait period in seconds after startup
wait-for	(Optional) Wait for an event to advertise normal metric
bgp	(Optional) BGP Convergence
<i>as</i>	(Optional) ASN of BGP to wait for
summary-lsa	(Optional) Summary LSAs
<i>max-metric-sumlsa</i>	(Optional) Max metric value for summary LSAs

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

max-ports

[no] [vmware] max-ports

Syntax Description

no	Negate a command or set its defaults
vmware	(Optional) VMware configuration
max-ports	Max ports on which this profile can be inherited

Command Mode

- /exec/configure/port-profile

max-ports

[vmware] max-ports <i0>

Syntax Description

vmware	(Optional) VMware configuration
max-ports	Max ports on which this profile can be inherited
<i>i0</i>	Enter the max-number of ports

Command Mode

- /exec/configure/port-profile

maxas-limit

maxas-limit <as-limit> | no maxas-limit [<as-limit>]

Syntax Description

no	Negate a command or set its defaults
maxas-limit	Allow AS-PATH attribute from EBGP neighbor imposing a limit on number of ASes
<i>as-limit</i>	Number of ASes in the AS-PATH attribute

Command Mode

- /exec/configure/router-bgp/vrf-cmds

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Maximum paths per destination
<i>max-paths</i>	Maximum paths per destination

Command Mode

- /exec/configure/router-ospf

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	RIP set maximum paths per route
<i>max-paths</i>	Maximum paths per prefix

Command Mode

- /exec/configure/router-rip/router-rip-af-common /exec/configure/router-rip/router-rip-vrf-af-common

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Set maximum paths per destination
<i>max-paths</i>	Maximum paths per destination

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv4

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Set maximum paths per destination
<i>max-paths</i>	Maximum paths per destination

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Maximum paths per destination
<i>max-paths</i>	Maximum paths per destination

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

maximum-paths

```
{ { maximum-paths <num-paths> } | { no maximum-paths [ <num-paths> ] } }
```

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Forward packets over multiple paths
<i>num-paths</i>	Number of paths

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

maximum-paths

maximum-paths [ibgp] <mpath-count> | no maximum-paths [ibgp] [<mpath-count>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Forward packets over multipath paths
ibgp	(Optional) Configure multipath for IBGP paths
<i>mpath-count</i>	Number of parallel paths

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

maximum-paths

maximum-paths <max-paths> | no maximum-paths [<max-paths>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Set maximum paths per destination
<i>max-paths</i>	Maximum paths per destination

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common /exec/configure/l2mp-isis/l2mp-isis-l2-topo

maximum-paths eibgp

maximum-paths eibgp <mpath-count> | no maximum-paths eibgp [<mpath-count>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Forward packets over multipath paths
eibgp	Configure multipath for both EBGP and IBGP paths
<i>mpath-count</i>	Number of parallel paths

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6
/exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-af-ipv6

maximum-paths mixed

maximum-paths mixed <mpath-count> | no maximum-paths mixed [<mpath-count>]

Syntax Description

no	Negate a command or set its defaults
maximum-paths	Forward packets over multipath paths
mixed	Configure multipath for local and remote paths
<i>mpath-count</i>	Number of parallel paths

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6
/exec/configure/router-bgp/router-bgp-af-vpn4 /exec/configure/router-bgp/router-bgp-af-vpn6
/exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

maximum-peers

{ maximum-peers <limit> | no maximum-peers [<limit>] }

Syntax Description

no	Negate a command or set its defaults
maximum-peers	Maximum number of peers for this prefix
<i>limit</i>	Max. peers limit

Command Mode

- exec/configure/router-bgp/router-bgp-neighbor-prefix

maximum-prefix

```
{ { maximum-prefix <value> [ <threshold> ] [ warning-only ] [ restart <time1> ] [ restart-count <count> ] [
reset-time <time2> ] [ dampened ] } | { no maximum-prefix [ <value> [ <threshold> ] [ warning-only ] [ restart
<time1> ] [ restart-count <count> ] [ reset-time <time2> ] [ dampened ] } }
```

Syntax Description

no	Negate a command or set its defaults
maximum-prefix	Maximum number of IP prefixes acceptable in aggregate
<i>value</i>	Number of IP prefixes for maximum-prefix limit
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Only give warning message when limit is exceeded
restart	(Optional) Duration for which a prefix source is ignored
<i>time1</i>	(Optional) Restart interval in minutes
restart-count	(Optional) Number of times sessions are auto-restarted
<i>count</i>	(Optional) Number of times
reset-time	(Optional) Duration after which restart history is cleared
<i>time2</i>	(Optional) Reset time in minutes
dampened	(Optional) Exponentially increase restart time interval

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

maximum-prefix

```
maximum-prefix <limit> [ <percent> ] [ restart <restart-time> | warning-only ] | { no | default } maximum-prefix
[ <limit> [ <percent> ] [ restart <restart-time> | warning-only ] ]
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
maximum-prefix	Maximum number of prefixes from this neighbor
<i>limit</i>	Max. prefix limit
<i>percent</i>	(Optional) Threshold percentage at which to generate a warning
restart	(Optional) Restart bgp connection after limit is exceeded
<i>restart-time</i>	(Optional) Restart interval in minutes
warning-only	(Optional) Only give a warning message when limit is exceeded

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

maximum-prefix

maximum-prefix <limit> [<percent>] [restart <restart-time> | warning-only] | { no | default } maximum-prefix [<limit> [<percent>] [restart <restart-time> | warning-only]]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
maximum-prefix	Maximum number of prefixes from this neighbor
<i>limit</i>	Max. prefix limit
<i>percent</i>	(Optional) Threshold percentage at which to generate a warning
restart	(Optional) Restart bgp connection after limit is exceeded
<i>restart-time</i>	(Optional) Restart interval in minutes
warning-only	(Optional) Only give a warning message when limit is exceeded

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

maximum routes

[no] maximum routes <limit> [{ <warnlevel> [reinstall <threshold>] } | warning-only]

Syntax Description

no	(Optional) Negate a command or set its defaults
maximum	Set a limit
routes	Maximum number of routes allowed in this routing table
<i>limit</i>	Maximum number of routes allowed
<i>warnlevel</i>	(Optional) Threshold value (%) at which to generate a warning msg
reinstall	(Optional) Reinstall previous rejected route due to over maximum route limit
<i>threshold</i>	(Optional) Threshold value (%) at which to reinstall routes back to VRF
warning-only	(Optional) Only give a warning message if limit is exceeded

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

mdix auto

{ mdix auto | no mdix [auto] }

Syntax Description

no	Negate a command or set its defaults
mdix	Enable auto mdix mode
auto	Enable auto mdix mode

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

mdt asm-use-shared-tree

[no] mdt asm-use-shared-tree

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
asm-use-shared-tree	Use (*,G) only state, no remote source state is created

Command Mode

- /exec/configure/vrf

mdt data

[no] mdt data <prefix> [threshold <value> | immediate-switch] [route-map <policy-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
data	Configure settings for Data MDT
<i>prefix</i>	List of group range prefixes
threshold	(Optional) Data MDT switching threshold
immediate-switch	(Optional) Move to data mdt immediately if remote receiver exists
<i>value</i>	(Optional) Threshold in kilobits per sec
route-map	(Optional) Specify policy for creating Data MDTs
<i>policy-name</i>	(Optional) A route-map name

Command Mode

- /exec/configure/vrf

mdt data bidir-enable

[no] mdt data bidir-enable

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
data	Configure settings for Data MDT
bidir-enable	Allow creation of data mdts for bidir customers

Command Mode

- /exec/configure/vrf

mdt default

mdt default <mdt-default> | no mdt default [<mdt-default>]

Syntax Description

no	Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
default	The default group
<i>mdt-default</i>	IP multicast group address

Command Mode

- /exec/configure/vrf

mdt enforce-bgp-mdt-safi

[no] mdt enforce-bgp-mdt-safi

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
enforce-bgp-mdt-safi	Depend on BGP MDT SAFI for auto-discovery

Command Mode

- /exec/configure/vrf

mdt mtu

[no] mdt mtu <mtu-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
mtu	The MTU
<i>mtu-value</i>	MTU value

Command Mode

- /exec/configure/vrf

mdt pim hello-interval

[no] mdt pim hello-interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
pim	PIM protocol related parameters
hello-interval	Hello interval used between peers
<i>interval</i>	Interval in milliseconds

Command Mode

- /exec/configure/vrf

mdt pim jp-interval

[no] mdt pim jp-interval <interval>

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
pim	PIM protocol related parameters
jp-interval	Join-Prune interval used between peers
<i>interval</i>	Interval in seconds

Command Mode

- /exec/configure/vrf

mdt source

[no] mdt source <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
mdt	Backbone Multicast Distribution Tree
source	Source interface to be used in the backbone network
<i>interface</i>	Use IP address of this interface

Command Mode

- /exec/configure/vrf

media-type auto

media-type auto

Syntax Description

media-type	Select the media-type link
auto	Select mgmt port as auto

Command Mode

- /exec/configure/if-mgmt-ether

media-type rj45

media-type rj45

Syntax Description

media-type	Select the media-type link
rj45	Select mgmt port rj45

Command Mode

- /exec/configure/if-mgmt-ether

media-type sfp

media-type sfp

Syntax Description

media-type	Select the media-type link
sfp	Select mgmt port sfp

Command Mode

- /exec/configure/if-mgmt-ether

media

media <vlanshowinfo-media-type> | no media

Syntax Description

no	Negate a command or set its defaults
media	Media type of the VLAN
<i>vlanshowinfo-media-type</i>	Select media type

Command Mode

- /exec/configure/vlan

medium

medium <medium-type> | no medium <medium-type>

Syntax Description

no	Negate a command or set its defaults
medium	Configure Interface medium mode
<i>medium-type</i>	

Command Mode

- /exec/configure/if-vlan-common

medium broadcast

{ medium broadcast | no medium broadcast }

Syntax Description

no	Negate a command or set its defaults
medium	Configure Interface medium mode
broadcast	Broadcast medium

Command Mode

- /exec/configure/if-ethernet-p2p-switch /exec/configure/if-ethernet-p2p /exec/configure/if-ethernet-all /exec/configure/if-eth-l3-non-member /exec/configure/if-port-channel /exec/configure/if-remote-ethernet-sub /exec/configure/if-eth-port-channel-p2p /exec/configure/if-ethernet-p2p-m

medium broadcast

{ medium broadcast | no medium broadcast }

Syntax Description

no	Negate a command or set its defaults
medium	Configure Interface medium mode
broadcast	Broadcast medium

Command Mode

- /exec/configure/ppm-ethernet-switch /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-ethernet-all

medium p2p

{ medium p2p | no medium p2p }

Syntax Description

no	Negate a command or set its defaults
medium	Configure Interface medium mode
p2p	Point-to-Point medium

Command Mode

- /exec/configure/if-ethernet-p2p-switch /exec/configure/if-ethernet-p2p /exec/configure/if-ethernet-all /exec/configure/if-eth-l3-non-member /exec/configure/if-port-channel /exec/configure/if-remote-ethernet-sub /exec/configure/if-eth-port-channel-p2p /exec/configure/if-ethernet-p2p-m

medium p2p

{ medium p2p | no medium p2p }

Syntax Description

no	Negate a command or set its defaults
medium	Configure Interface medium mode
p2p	Point-to-Point medium

Command Mode

- /exec/configure/ppm-ethernet-switch /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub /exec/configure/if-ethernet-all

member vlan

{ member vlan <vlan-range> } | { no member vlan [<vlan-range>] }

Syntax Description

no	Negate a command or set its defaults
member	Set fabricpath topology VLAN membership
vlan	Configure VLANs for Fabricpath Topology
<i>vlan-range</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure/fp-topology

member vni

{ member vni <vni-range> } | { no member vni [<vni-range>] }

Syntax Description

no	Negate a command or set its defaults
member	Set fabricpath topology VNI membership
vni	Configure VNIs for L2MP Topology
<i>vni-range</i>	vni range, Example: 4096, 4099-5013, 5019

Command Mode

- /exec/configure/fp-topology

member vni

[no] member vni <vni-range>

Syntax Description

no	(Optional) Negate a command or set its defaults
member	NVE VN-Segment Membership
vni	Virtual Network Identifier
<i>vni-range</i>	vni range, Example: 5000 or 5001-5008

Command Mode

- /exec/configure/if-nve

member vni associate-vrf

[no] member vni <vni-range> associate-vrf

Syntax Description

no	(Optional) Negate a command or set its defaults
member	NVE VN-Segment Membership
vni	Virtual Network Identifier
<i>vni-range</i>	vni range, Example: 5000 or 5001-5008
associate-vrf	Associate vni with a vrf

Command Mode

- /exec/configure/if-nve

message-digest-key md5

```
{ { message-digest-key <keyid> md5 <key> } | { no message-digest-key [ <keyid> md5 <key> ] } }
```

Syntax Description

no	Negate a command or set its defaults
message-digest-key	Message digest authentication password (key)
<i>keyid</i>	Key ID
md5	Use MD5 algorithm
<i>key</i>	The OSPF password (key)

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

message-digest-key md5

```
{ { message-digest-key <keyid> md5 <key> } | { no message-digest-key [ <keyid> md5 <key> ] } }
```

Syntax Description

no	Negate a command or set its defaults
message-digest-key	Message digest authentication password (key)
<i>keyid</i>	Key ID
md5	Use MD5 algorithm
<i>key</i>	OSPF password (key)

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

metric-style transition

[no] metric-style { transition }

Syntax Description

no	(Optional) Negate a command or set its defaults
metric-style	Configure metric style used in advertised LSPs
transition	Use both narrow and wide metric style

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

metric-type

[no] metric-type <metric-type>

Syntax Description

no	(Optional) Negate a command or set its defaults
metric-type	Identifying name of metric with max 128 characters
<i>metric-type</i>	Supported metric-types te,igp

Command Mode

- /exec/configure/sr/te/color

metric direct 0

[no] metric direct 0

Syntax Description

no	(Optional) Negate a command or set its defaults
metric	Cost of direct routes
direct	Cost of direct routes
0	direct route cost is zero to be compatible with IOS

Command Mode

- /exec/configure/router-rip

metric maximum-hops

{ { metric maximum-hops <hops> } | { no metric maximum-hops [<hops>] } }

Syntax Description

no	Negate a command or set its defaults
metric	Modify EIGRP routing metrics and parameters
maximum-hops	Advertise EIGRP routes greater than <hops> as unreachable
<i>hops</i>	Hop count

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

metric rib-scale

{ { metric rib-scale <rib-scale> } | { no metric rib-scale [<rib-scale>] } }

Syntax Description

no	Negate a command or set its defaults
metric	Modify EIGRP routing metrics and parameters
rib-scale	Defines RIB scaling value
<i>rib-scale</i>	Rib scale

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

metric version 64bit

{ { metric version 64bit } | { no metric version [64bit] } }

Syntax Description

no	Negate a command or set its defaults
metric	Modify EIGRP routing metrics and parameters
version	Modify EIGRP metric version
64bit	64 bit metric version

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

metric weights

```
{ { metric weights <tos> <k1> <k2> <k3> <k4> <k5> [ <k6> ] } | { no metric weights [ <tos> <k1> <k2> <k3> <k4> <k5> [ <k6> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
metric	Modify EIGRP routing metrics and parameters
weights	Modify EIGRP metric coefficients
<i>tos</i>	Type Of Service (Only TOS 0 supported)
<i>k1</i>	K1
<i>k2</i>	K2
<i>k3</i>	K3
<i>k4</i>	K4
<i>k5</i>	K5
<i>k6</i>	(Optional) K6

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

mkdir

mkdir <uri0>

Syntax Description

mkdir	Create new directory
<i>uri0</i>	Directory name

Command Mode

- /exec

mode

[no] mode <mode-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
mode	Hot-standby mode
<i>mode-id</i>	Node Mode

Command Mode

- /exec/configure/itd-dg-node

mode

[no] mode <vmode>

Syntax Description

no	(Optional) Negate a command or set its defaults
mode	Operational mode of the VLAN
<i>vmode</i>	

Command Mode

- /exec/configure/vlan

mode

[no] mode <mode-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
mode	Configure Hot-standby mode for a node
<i>mode-id</i>	Mode of node

Command Mode

- /exec/configure/plb-dg-node

mode tap-aggregation

[no] mode tap-aggregation [{ vlan <vlan_id> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
mode	Configure the interface operational mode
tap-aggregation	Disable/Enable tap aggregation on the interface
vlan	(Optional) vlan that is to be tagged in outgoing packets
<i>vlan_id</i>	(Optional) Vlan ID

Command Mode

- /exec/configure/if-switching

module transceiver-frequency

[no] module <module> transceiver-frequency { <xcvr_frequency> }

Syntax Description

no	(Optional) Negate a command or set its defaults
module	Configure for module
<i>module</i>	Enter module number
transceiver-frequency	Configure X2 transceiver frequency type
<i>xcvr_frequency</i>	Enter transceiver frequency type

Command Mode

- /exec/configure

monitor erspan granularity

[no] monitor erspan granularity { 100_us | 100_ns | 1588 | ns }

Syntax Description

no	(Optional) Negate a command or set its defaults
monitor	Configure Ethernet SPAN sessions
erspan	Configure Ethernet ERSPAN sessions
granularity	Configure granularity for ERSPAN Type III sessions
100_us	100 microseconds
100_ns	100 nanoseconds
1588	1588 in seconds/nanoseconds
ns	nanoseconds

Command Mode

- /exec/configure

monitor erspan origin ip-address

[no] monitor erspan origin ip-address <ip> [global]

Syntax Description

no	(Optional) Negate a command or set its defaults
monitor	Configure Ethernet SPAN sessions
erspan	Configure Ethernet ERSPAN sessions
origin	Configure the erspan origin ip address
ip-address	Configure global origin IP address
<i>ip</i>	
global	(Optional) Configure in default VDC across all VDCs

Command Mode

- /exec/configure

monitor erspan switch-id

[no] monitor erspan switch-id <switch_id>

Syntax Description

no	(Optional) Negate a command or set its defaults
monitor	Configure Ethernet SPAN sessions
erspan	Configure Ethernet ERSPAN sessions
switch-id	Configure the erspan switch-id
<i>switch_id</i>	erspan-switch-id

Command Mode

- /exec/configure

monitor session

monitor session <session_number> [type local]

Syntax Description

monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
<i>session_number</i>	
type	(Optional) Specify a session type
local	(Optional) Create a local session

Command Mode

- /exec/configure

monitor session shut

[no] monitor session { all | <session_range> } [shut] | monitor session { all | <session_range> } shut

Syntax Description

no	Negate a command or set its defaults
monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
all	All sessions
<i>session_range</i>	
shut	(Optional) Shut the selected session

Command Mode

- /exec/configure

monitor session type acl-capture

monitor session <session_number> type acl-capture

Syntax Description

monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
<i>session_number</i>	
type	Specify a session type
acl-capture	Create an acl-capture session

Command Mode

- /exec/configure

monitor session type erspan-destination

monitor session <session_number> type erspan-destination

Syntax Description

monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
<i>session_number</i>	
type	Specify a session type
erspan-destination	Create an erspan destination session

Command Mode

- /exec/configure

monitor session type erspan-source

monitor session <session_number> type erspan-source

Syntax Description

monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
<i>session_number</i>	
type	Specify a session type
erspan-source	Create an erspan source session

Command Mode

- /exec/configure

monitor session warp

[no] monitor session warp

Syntax Description

no	Negate a command or set its defaults
monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
warp	Configure Warp span mode

Command Mode

- /exec/configure

monitor session warp

monitor session warp [type local]

Syntax Description

monitor	Configure Ethernet SPAN sessions
session	Configure session preferences
warp	Create warp session
type	(Optional) Specify a session type
local	(Optional) Create a local session

Command Mode

- /exec/configure

mount

mount { usb1: | usb2: }

Syntax Description

mount	mount expansion flash or USB storage
usb1:	mount USB drive in port 1
usb2:	mount USB drive in port 2

Command Mode

- /exec

mount slot0

mount slot0:

Syntax Description

mount	mount expansion flash or USB storage
slot0:	mount expansion flash

Command Mode

- /exec

move

move <uri0> <uri1>

Syntax Description

move	Move files
<i>uri0</i>	Source file path
<i>uri1</i>	Destination file path

Command Mode

- /exec

mst designated priority

mst <mst-id> designated priority <prio> | no mst <mst-id> designated priority [<prio>]

Syntax Description

no	Negate a command or set its defaults
mst	Multiple spanning tree configuration
<i>mst-id</i>	MST instance range, example: 0-3,5,7-9
designated	Set the designated bridge priority for the spanning tree
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure/spanning-tree/pseudo

mst root priority

mst <mst-id> root priority <prio> | no mst <mst-id> root priority [<prio>]

Syntax Description

no	Negate a command or set its defaults
mst	Multiple spanning tree configuration
<i>mst-id</i>	MST instance range, example: 0-3,5,7-9
root	Set the root bridge priority for the spanning tree
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure/spanning-tree/pseudo

mtrace

mtrace <source> [<receiver>] [<group>] [vrf <vrf-known-name>]

Syntax Description

mtrace	Trace
<i>source</i>	IP
<i>receiver</i>	(Optional) IP
<i>group</i>	(Optional) IP
vrf	(Optional) VRF
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

mtu

mtu <mtu_val> | no mtu [<mtu_val>]

Syntax Description

no	Negate a command or set its defaults
mtu	Configure mtu for the port
<i>mtu_val</i>	

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub /exec/configure/if-sub /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

mtu1

[no] mtu1 <value>

Syntax Description

no	(Optional) Negate a command or set its defaults
mtu1	MTU for the CoS
<i>value</i>	MTU value

Command Mode

- /exec/configure/policy-map/type/uf/class

mtu

mtu <mtu_value> | no mtu

Syntax Description

no	Negate a command or set its defaults
mtu	Set the MTU size for SPAN packets
<i>mtu_value</i>	

Command Mode

- /exec/configure/monitor-local-src

mtu

mtu <mtu_value> | no mtu

Syntax Description

no	Negate a command or set its defaults
mtu	Set the MTU size for ERSPAN packets
<i>mtu_value</i>	

Command Mode

- /exec/configure/monitor-erspan-src

mtu

mtu <mtu-val> | no mtu [<mtu-val>]

Syntax Description

no	Negate a command or set its defaults
mtu	Configure MTU
<i>mtu-val</i>	Bytes

Command Mode

- /exec/configure/if-any-tunnel

mtu

[no] mtu <value>

Syntax Description

no	(Optional) Negate a command or set its defaults
mtu	MTU for the CoS
<i>value</i>	MTU value

Command Mode

- /exec/configure/policy-map/type/uf/class

mtu

[no] mtu <mtu>

Syntax Description

mtu	MTU
<i>mtu</i>	MTU port to be configured

Command Mode

- /exec/configure/config-ssx-exporter

mtu

mtu <mtu_val> | no mtu

Syntax Description

no	Negate a command or set its defaults
mtu	Set the interface Maximum Transmission Unit (MTU)
<i>mtu_val</i>	MTU size in bytes

Command Mode

- /exec/configure/if-vlan-common

multi-topology

[no] multi-topology [transition]

Syntax Description

no	(Optional) Negate a command or set its defaults
multi-topology	Enable multitopoloy for IPV6
transition	(Optional) Configure multitopology transition mode

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

multicast

[no] multicast <mode_enum>

Syntax Description

no	(Optional) Negate a command or set its defaults
multicast	Enable multicast best-effort
<i>mode_enum</i>	

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

multisite border-gateway interface

[no] multisite border-gateway interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
multisite	VxLAN Multisite
border-gateway	VxLAN Multisite Border-gateway
interface	NVE Multisite Border-gateway Interface
<i>interface</i>	

Command Mode

- /exec/configure/if-nve

multisite ingress-replication

[no] multisite ingress-replication

Syntax Description

no	(Optional) Negate a command or set its defaults
multisite	multisite ingress replication
ingress-replication	Configure ingress replication

Command Mode

- /exec/configure/if-nve/vni

mvr-config

[no] mvr-config

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-config	Enable IGMP MVR

Command Mode

- /exec/configure

mvr-group

```
[no] mvr-group { { <ip-addr> <ip-mask> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR interface config
<i>ip-addr</i>	Group IP Address
<i>ip-mask</i>	IP network mask in format m.m.m.m
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-group

```
[no] mvr-group { { <ip-addr> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR Group
<i>ip-addr</i>	Group IP Address
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/igmp-mvr-global

mvr-group

```
[no] mvr-group { { <ip-addr> count <count> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR Group
<i>ip-addr</i>	Group IP Address
count	Number of contiguous groups
<i>count</i>	Number of contiguous groups
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/igmp-mvr-global

mvr-group

```
[no] mvr-group { { <ip-addr> <ip-mask> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR Group
<i>ip-addr</i>	Group IP Address
<i>ip-mask</i>	IP network mask in format m.m.m.m
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/igmp-mvr-global

mvr-group

```
[no] mvr-group { { <ip-prefix> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR Group
<i>ip-prefix</i>	IP prefix and network mask length in format x.x.x.x/m
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/igmp-mvr-global

mvr-group

```
[no] mvr-group { { <ip-addr> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR interface config
<i>ip-addr</i>	Group IP Address
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-group

```
[no] mvr-group { { <ip-addr> count <count> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR interface config
<i>ip-addr</i>	Group IP Address
count	Number of contiguous groups
<i>count</i>	Number of contiguous groups
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-group

```
[no] mvr-group { { <ip-prefix> } [ { vlan <vlan-id> } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-group	MVR interface config
<i>ip-prefix</i>	IP prefix and network mask length in format x.x.x.x/m
vlan	(Optional) Global default MVR vlan
<i>vlan-id</i>	(Optional) Enter MVR Vlan

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-suppress-query vlan

{ { mvr-suppress-query vlan <vlan-range> } | { no mvr-suppress-query } }

Syntax Description

no	Negate a command or set its defaults
mvr-suppress-query	Suppress IGMP General query forwarding from vlans
vlan	MVR Vlan Id or ranges
<i>vlan-range</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure/igmp-mvr-global

mvr-type receiver

[no] mvr-type receiver

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-type	MVR interface config
receiver	Mvr receiver port

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-type source

[no] mvr-type source

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-type	MVR interface config
source	Mvr source port

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

mvr-vlan

[no] mvr-vlan <vlan-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
mvr-vlan	Global default MVR vlan
<i>vlan-id</i>	Enter MVR Vlan

Command Mode

- /exec/configure/igmp-mvr-global

mvr-vlan

{ { no mvr-vlan <vlan-id> } | { mvr-vlan <vlan-id> } }

Syntax Description

no	Negate a command or set its defaults
mvr-vlan	Interface MVR Config
<i>vlan-id</i>	Enter MVR Vlan

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch



N Commands

- [name-lookup](#), on page 3118
- [name-lookup](#), on page 3119
- [name](#), on page 3120
- [name](#), on page 3121
- [name](#), on page 3122
- [nat destination](#), on page 3123
- [nbm external-link](#), on page 3124
- [nbm flow-policy](#), on page 3125
- [nbm flow acceptance-mode guaranteed nbm flow acceptance-mode](#), on page 3126
- [nbm flow asm range](#), on page 3127
- [nbm flow bandwidth kbps mbps gbps](#), on page 3128
- [nbm flow dscp](#), on page 3129
- [nbm host-policy](#), on page 3130
- [nbm mode pim-active](#), on page 3131
- [nbm reserve unicast fabric bandwidth](#), on page 3132
- [negotiate auto](#), on page 3133
- [negotiate auto 25000](#), on page 3134
- [neighbor-down fib-accelerate](#), on page 3135
- [neighbor](#), on page 3136
- [neighbor](#), on page 3137
- [neighbor](#), on page 3138
- [neighbor](#), on page 3139
- [neighbor](#), on page 3140
- [neighbor maximum-prefix](#), on page 3141
- [nemo config address port interval](#), on page 3142
- [net](#), on page 3143
- [net](#), on page 3144
- [net](#), on page 3145
- [network](#), on page 3146
- [network](#), on page 3147
- [network](#), on page 3148
- [network](#), on page 3149
- [next-address exclude-address](#), on page 3150

- next-hop-self, on page 3151
- next-hop-self, on page 3152
- next-hop-third-party, on page 3153
- next-hop-third-party, on page 3154
- next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null, on page 3155
- next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null, on page 3156
- nexthop route-map, on page 3157
- nexthop trigger-delay critical non-critical, on page 3158
- ngoam authentication-key, on page 3159
- ngoam connect-check, on page 3160
- ngoam install acl, on page 3161
- ngoam profile, on page 3162
- ngoam xconnect hb-interval, on page 3163
- no-more, on page 3164
- no, on page 3165
- no, on page 3166
- no, on page 3167
- no, on page 3168
- no, on page 3169
- no, on page 3170
- no, on page 3171
- no, on page 3174
- no, on page 3179
- no, on page 3183
- no, on page 3186
- no, on page 3189
- no, on page 3192
- no, on page 3195
- no, on page 3198
- no, on page 3201
- no, on page 3203
- no, on page 3204
- no, on page 3205
- no, on page 3206
- node, on page 3207
- node, on page 3208
- node, on page 3209
- node ip, on page 3210
- node ip, on page 3211
- npiv enable, on page 3212
- npv auto-load-balance disruptive, on page 3213
- npv traffic-map server-interface external-interface, on page 3214
- nsf await-redis-proto-convergence, on page 3215
- ntp access-group, on page 3216

- [ntp access-group match-all](#), on page 3217
- [ntp allow private](#), on page 3218
- [ntp authenticate](#), on page 3219
- [ntp authentication-key md5](#), on page 3220
- [ntp drop-aged-packet](#), on page 3221
- [ntp logging](#), on page 3222
- [ntp master](#), on page 3223
- [ntp passive](#), on page 3224
- [ntp peer](#), on page 3225
- [ntp rts-update](#), on page 3226
- [ntp server](#), on page 3227
- [ntp source-interface](#), on page 3228
- [ntp source](#), on page 3229
- [ntp sync-retry](#), on page 3230
- [ntp trusted-key](#), on page 3231
- [nv overlay evpn](#), on page 3232
- [nxapi certificate](#), on page 3233
- [nxapi flow](#), on page 3234
- [nxapi http port](#), on page 3235
- [nxapi ssl ciphers weak](#), on page 3236
- [nxapi ssl protocols](#), on page 3237
- [nxapi use-vrf management default](#), on page 3238
- [nxsdk enable app](#), on page 3239
- [nxsdk service-name](#), on page 3240

name-lookup

[no] name-lookup

Syntax Description

no	(Optional) Negate a command or set its defaults
name-lookup	Display OSPF router ids as DNS names

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

name-lookup

[no] name-lookup

Syntax Description

no	(Optional) Negate a command or set its defaults
name-lookup	Enable Name Lookup for OSPF Neighbors

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

name

name [<name>] | no name

Syntax Description

no	Negate a command or set its defaults
name	Redundancy name string
<i>name</i>	(Optional) name string

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

name

name <name-val> | no name [<name-val>]

Syntax Description

no	Negate a command or set its defaults
name	Set configuration name
<i>name-val</i>	Configuration name

Command Mode

- /exec/configure/spanning-tree/mst/configuration

name

name <vlan-name> | no name

Syntax Description

no	Negate a command or set its defaults
name	Ascii name of the VLAN
<i>vlan-name</i>	The ascii name for the VLAN

Command Mode

- /exec/configure/vlan

nat destination

{ nat destination } | { no nat destination }

Syntax Description

no	Negate a command or set its defaults
nat	Network Address Translation
destination	Destination NAT

Command Mode

- /exec/configure/plb

nbm external-link

[no] nbm external-link

Syntax Description

nbm	Non Blocking Multicast
external-link	link connected to external router. Configuring this will flap the interface

Command Mode

- /exec/configure/if-igp

nbm flow-policy

[no] nbm flow-policy

Syntax Description

no	(Optional) Negate a command or set its defaults
nbm	Non Blocking Multicast
flow-policy	Flow Policy Characteristics

Command Mode

- /exec/configure

nbm flow acceptance-mode guaranteed nbm flow acceptance-mode

{ nbm flow acceptance-mode { guaranteed | best-fit } } | [no] nbm flow acceptance-mode

Syntax Description

nbm	Non Blocking Multicast
flow	Flow Characteristics
acceptance-mode	Flow Acceptance Mode
guaranteed	New flows are guaranteed to be accepted
best-fit	New flows are best-fit among fabric links

Command Mode

- /exec/configure

nbm flow asm range

[no] nbm flow asm range <group> +

Syntax Description

nbm	Non Blocking Multicast
flow	Flow Characteristics
asm	Any-Source Multicast (ASM) groups
range	Configure explicit group ranges
<i>group</i>	List of group range prefixes

Command Mode

- /exec/configure

nbm flow bandwidth kbps mbps gbps

```
{ nbm flow bandwidth { <val_kbps> kbps | <val_mbps> mbps | <val_gbps> gbps } } | { no nbm flow bandwidth }
```

Syntax Description

nbm	Non Blocking Multicast
flow	Flow Characteristics
bandwidth	Bandwidth per flow
<i>val_kbps</i>	Per Flow Bandwidth in Kbps
kbps	Bandwidth value in Kbps
<i>val_mbps</i>	Per Flow Bandwidth in Mbps
mbps	Bandwidth value in Mbps
<i>val_gbps</i>	Per Flow Bandwidth in Gbps
gbps	Bandwidth value in Gbps

Command Mode

- /exec/configure

nbm flow dscp

```
{ nbm flow dscp <val_dscp> } | { no nbm flow dscp }
```

Syntax Description

nbm	Non Blocking Multicast
flow	Flow Characteristics
dscp	DSCP for the flow
<i>val_dscp</i>	Integer value

Command Mode

- /exec/configure

nbm host-policy

[no] nbm host-policy

Syntax Description

no	(Optional) Negate a command or set its defaults
nbm	Non Blocking Multicast
host-policy	NBM SW Host Admission Policy

Command Mode

- /exec/configure

nbm mode pim-active

[no] nbm mode pim-active [__readonly__ <output>]

Syntax Description

no	(Optional) Negate a command or set its defaults
nbm	Non Blocking Multicast
mode	Set pmn mode
pim-active	Bandwidth engine running in fabric
__readonly__	(Optional)
<i>output</i>	(Optional)

Command Mode

- /exec/configure

nbm reserve unicast fabric bandwidth

nbm reserve unicast fabric bandwidth <percentage> | no nbm reserve unicast fabric bandwidth

Syntax Description

no	Negate a command or set its defaults
nbm	Non Blocking Multicast
reserve	reserve bandwidth
unicast	unicast
fabric	fabric
bandwidth	percentage of bandwidth for unicast flow
<i>percentage</i>	percentage value

Command Mode

- /exec/configure

negotiate auto

negotiate auto | no negotiate auto

Syntax Description

no	Negate a command or set its defaults
negotiate	Configure link negotiation parameters
auto	Configure auto-negotiation

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

negotiate auto 25000

[no] negotiate auto 25000

Syntax Description

no	(Optional) Negate a command or set its defaults
negotiate	Configure link negotiation parameters
auto	Configure auto-negotiation
25000	Force auto-negotiate to only 25000 and change fec to auto

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

neighbor-down fib-accelerate

[no] neighbor-down fib-accelerate

Syntax Description

no	(Optional) Negate a command or set its defaults
neighbor-down	Handle BGP neighbor down event, due to various reasons
fib-accelerate	Accelerate the hardware updates for IP/IPv6 adjacencies for neighbor

Command Mode

- /exec/configure/router-bgp/vrf-cmds

neighbor

neighbor [vrf { <vrf-name> | <vrf-known-name> }] <ipaddr> { implicit-withdraw | labels accept <pfx-list> | targeted } | no neighbor [vrf { <vrf-name> | <vrf-known-name> }] <ipaddr> [implicit-withdraw | labels accept | targeted]

Syntax Description

no	Negate a command or set its defaults
neighbor	Configure neighbor parameters
vrf	(Optional) VRF Routing/Forwarding instance information
<i>vrf-name</i>	(Optional) VPN Routing/Forwarding instance name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ipaddr</i>	IP address for LDP neighbor
implicit-withdraw	Enable LDP Implicit Withdraw Label
labels	Configure label binding exchange controls
accept	Specify label bindings to accept
<i>pfx-list</i>	Name of prefix list
targeted	Establish targeted session

Command Mode

- /exec/configure/ldp

neighbor

[no] neighbor { <neighbor-id> | <ipv6-neighbor-id> } [remote-as <asn>]

Syntax Description

no	(Optional) Negate a command or set its defaults
neighbor	Configure a BGP neighbor
<i>neighbor-id</i>	IP address of the neighbor
remote-as	(Optional) Specify Autonomous System Number of the neighbor
<i>asn</i>	(Optional) Autonomous System Number

Command Mode

- /exec/configure/router-bgp

neighbor

[no] neighbor { <neighbor-id> | <ipv6-neighbor-id> } [remote-as <asn>]

Syntax Description

no	(Optional) Negate a command or set its defaults
neighbor	Configure a BGP neighbor
<i>neighbor-id</i>	IP address of the neighbor
remote-as	(Optional) Specify Autonomous System Number of the neighbor
<i>asn</i>	(Optional) Autonomous System Number

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf

neighbor

```
[no] neighbor { <neighbor-prefix> | <ipv6-neighbor-prefix> } [ remote-as [ <asn> | route-map <rmap-name> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
neighbor	Configure a BGP neighbor
<i>neighbor-prefix</i>	IP prefix for neighbors
remote-as	(Optional) Specify Autonomous System Number of the neighbor
<i>asn</i>	(Optional) Autonomous System Number
route-map	(Optional) Route-map to match prefix peer AS number
<i>rmap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp

neighbor

```
[no] neighbor { <neighbor-prefix> | <ipv6-neighbor-prefix> } [ remote-as [ <asn> | route-map <rmap-name> ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
neighbor	Configure a BGP neighbor
<i>neighbor-prefix</i>	IP prefix for neighbors
remote-as	(Optional) Specify Autonomous System Number of the neighbor
<i>asn</i>	(Optional) Autonomous System Number
route-map	(Optional) Route-map to match prefix peer AS number
<i>rmap-name</i>	(Optional) Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-vrf

neighbor maximum-prefix

```
{ { neighbor <address> { <interface> | maximum-prefix <value> [ warning-only ] } } | { no neighbor <address>
[ <interface> | maximum-prefix <value> [ warning-only ] ] } } | { { neighbor maximum-prefix <value> [
<threshold> ] [ warning-only ] [ restart <time1> ] [ restart-count <count> ] [ reset-time <time2> ] [ dampened
] } | { no neighbor maximum-prefix [ <value> [ <threshold> ] [ warning-only ] [ restart <time1> ] [ restart-count
<count> ] ] } }
```

Syntax Description

no	Negate a command or set its defaults
neighbor	Specify a neighbor router
<i>interface</i>	Interface
<i>address</i>	Neighbor address
maximum-prefix	Maximum number of IP prefixes acceptable from a neighbor
<i>value</i>	Number of IP prefixes for maximum-prefix limit
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Only give warning message when limit is exceeded
restart	(Optional) Duration for which a prefix source is ignored
<i>time1</i>	(Optional) Restart interval in minutes
restart-count	(Optional) Number of times sessions are auto-restarted
<i>count</i>	(Optional) Number of times
reset-time	(Optional) Duration after which restart history is cleared
<i>time2</i>	(Optional) Reset time in minutes
dampened	(Optional) Exponentially increase restart time interval

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

nemo config address port interval

[no] nemo config address <ip_address> port <portnum> interval <interval-num>

Syntax Description

no	(Optional) Negate a command or set its defaults
nemo	Nemo switch onboarding enabler
config	Configure Nemo for switch onboarding
address	IP address of the Nemo platform
<i>ip_address</i>	IP Address
port	Port number of the Nemo platform
<i>portnum</i>	Port number
interval	Config interval in millisecond
<i>interval-num</i>	Config interval in millisecond

Command Mode

- /exec/configure

net

[no] net <net>

Syntax Description

no	(Optional) Negate a command or set its defaults
net	Configure Network Entity Title for IS-IS
<i>net</i>	NET in form of XX.XXXX.XXXX[.00]

Command Mode

- /exec/configure/otv-isis

net

[no] net <net>

Syntax Description

no	(Optional) Negate a command or set its defaults
net	Configure Network Entity Title for IS-IS
<i>net</i>	NET in form of XX.XXXX.XXXX[.00]

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

net

[no] net <net>

Syntax Description

no	(Optional) Negate a command or set its defaults
net	Configure Network Entity Title for IS-IS
<i>net</i>	NET in form of XX.XXXX.XXXX[.00]

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

network

[no] network { { <address> <mask> } | <prefix> }

Syntax Description

no	(Optional) Negate a command or set its defaults
network	Enable routing on an IP network
<i>address</i>	Network number
<i>mask</i>	EIGRP wild card bits
<i>prefix</i>	IP prefix in slash format

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-ipv4

network

[no] network { <ip-dest> <ip-mask> | <ip-prefix> }

Syntax Description

no	(Optional) Negate a command or set its defaults
network	RIP IP network
<i>ip-dest</i>	IP addr format
<i>ip-mask</i>	IP network mask format
<i>ip-prefix</i>	Exact prefix

Command Mode

- /exec/configure/router-rip/router-rip-af-ipv4 /exec/configure/router-rip/router-rip-vrf-af-ipv4

network

[no] network { <ip-addr> mask <ip-mask> | <ip-prefix> } [route-map <rmap-name> | summarize | evpn] +

Syntax Description

no	(Optional) Negate a command or set its defaults
network	Configure an IP prefix to advertise
<i>ip-addr</i>	IP network to advertise
mask	Configure the mask of the IP prefix to advertise
<i>ip-mask</i>	Dotted 4-octet mask
<i>ip-prefix</i>	IP prefix in CIDR format
route-map	(Optional) Apply route-map to modify attributes
<i>rmap-name</i>	(Optional) Route-map name
summarize	(Optional) Summarize more specific prefixes from routing table
evpn	(Optional) Only advertise route towards evpn side

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv4

network

[no] network <ipv6-prefix> [route-map <rmap-name> | summarize] +

Syntax Description

no	(Optional) Negate a command or set its defaults
network	Configure an IPv6 prefix to advertise
route-map	(Optional) Apply route-map to modify attributes
<i>rmap-name</i>	(Optional) Route-map name
summarize	(Optional) Summarize more specific prefixes from routing table

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

next-address exclude-address

```
{ next-address [ loose | strict ] <ipaddr> | exclude-address <ipaddr> }
```

Syntax Description

next-address	Specify the next address in the path
loose	(Optional) Target address is loose
strict	(Optional) Target address is strict
exclude-address	Exclude an address from subsequent partial path segments
<i>ipaddr</i>	Enter IP address (A.B.C.D)

Command Mode

- /exec/configure/te/expl-path

next-hop-self

[no | default] next-hop-self

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
next-hop-self	Set our peering address as nexthop

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt

next-hop-self

[no | default] next-hop-self

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
next-hop-self	Set our peering address as nexthop

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6

next-hop-third-party

[no | default] next-hop-third-party

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
next-hop-third-party	Compute a third-party nexthop if possible

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt

next-hop-third-party

[no | default] next-hop-third-party

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
next-hop-third-party	Compute a third-party nexthop if possible

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null

```
[no] { next-hop [ backup <interface> ] <next-hop> out-label { <static-outlabel> | explicit-null | implicit-null } | next-hop auto-resolve out-label { <static-outlabel> | explicit-null | implicit-null } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
next-hop	Nexthop
<i>next-hop</i>	Destination IPv4 next hop
<i>static-outlabel</i>	Label Value
<i>interface</i>	(Optional) Back up interface
out-label	Output label
explicit-null	IETF MPLS IPv4 explicit null label (0)
implicit-null	IETF MPLS implicit null label (3)
auto-resolve	auto resolve the destination path
backup	(Optional) Backup destination

Command Mode

- /exec/configure/mpls_static/ipv4/input

next-hop out-label explicit-null implicit-null next-hop auto-resolve out-label explicit-null implicit-null

```
[no] { next-hop [ backup <interface> ] <ipv6-next-hop> out-label { <static-outlabel> | explicit-null | implicit-null } | next-hop auto-resolve out-label { <static-outlabel> | explicit-null | implicit-null } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
next-hop	Nexthop
<i>static-outlabel</i>	Label Value
<i>interface</i>	(Optional) Back up interface
out-label	Output label
explicit-null	IETF MPLS IPv6 explicit null label (2)
implicit-null	IETF MPLS implicit null label (3)
auto-resolve	auto resolve the destination path
backup	(Optional) Backup destination

Command Mode

- /exec/configure/mpls_static/ipv6/input

nexthop route-map

[no] nexthop route-map <rmap-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
nexthop	Nexthop tracking
route-map	Route map for valid nexthops
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn
/exec/configure/router-bgp/router-bgp-af-link-state /exec/configure/router-bgp/router-bgp-af-ipv4-mvpn
/exec/configure/router-bgp/router-bgp-af-ipv6-mvpn /exec/configure/router-bgp/router-bgp-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-af-l2vpn-vpls

nexthop trigger-delay critical non-critical

```
{ nexthop trigger-delay critical <criticaldelay> non-critical <noncriticaldelay> } | { no nexthop trigger-delay }
```

Syntax Description

no	Negate a command or set its defaults
nexthop	Nexthop tracking
trigger-delay	Set the delay to trigger nexthop tracking
critical	Nexthop changes affecting reachability
non-critical	Other nexthop changes
<i>noncriticaldelay</i>	Delay value (milliseconds)
<i>criticaldelay</i>	Delay value (milliseconds)

Command Mode

- /exec/configure/router-bgp/router-bgp-af /exec/configure/router-bgp/router-bgp-af-ipv4-mdt /exec/configure/router-bgp/router-bgp-af-ipv4-vpnv4 /exec/configure/router-bgp/router-bgp-af-ipv4-vpnv6 /exec/configure/router-bgp/router-bgp-af-link-state /exec/configure/router-bgp/router-bgp-af-l2vpn-vpls /exec/configure/router-bgp/router-bgp-af-ipv4-mvpn /exec/configure/router-bgp/router-bgp-af-ipv6-mvpn /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn

ngoam authentication-key

{ ngoam authentication-key <value> } | { no ngoam authentication-key [<value>] }

Syntax Description

no	Negate a command or set its defaults
ngoam	Configure ngoam
authentication-key	Ngoam authentication-key
<i>value</i>	authentication key

Command Mode

- /exec/configure

ngoam connect-check

[no] ngoam connect-check <id>

Syntax Description

no	(Optional) Negate a command or set its defaults
ngoam	Configure ngoam
connect-check	Configure ngoam oam connectivity check
<i>id</i>	connect check id

Command Mode

- /exec/configure

ngoam install acl

[no] ngoam install acl

Syntax Description

no	(Optional) Negate a command or set its defaults
ngoam	Configure ngoam
install	Ngoam install
acl	Ngoam install acl

Command Mode

- /exec/configure

ngoam profile

[no] ngoam profile <profile-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
ngoam	Configure ngoam
profile	Configure ngoam oam profile
<i>profile-id</i>	ngoam profile id

Command Mode

- /exec/configure

ngoam xconnect hb-interval

{ ngoam xconnect hb-interval <ms> } | { no ngoam xconnect hb-interval [<ms>] }

Syntax Description

no	Negate a command or set its defaults
ngoam	Configure ngoam
xconnect	Configure xconnect parameters
hb-interval	Configure xconnect heartbeat interval
<i>ms</i>	interval in ms, 3 failures triggers failure default is 190

Command Mode

- /exec/configure

no-more

| no-more

Syntax Description

	Pipe command output to filter
no-more	Turn-off pagination for command output

Command Mode

- /output

no

{ [<seqno>] | no } { <addr> <wild> | <prefix> | host <hostaddr> }

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>addr</i>	A.B.C.D Network address of object-group member
<i>wild</i>	A.B.C.D wildcard
<i>prefix</i>	A.B.C.D/nn Network prefix of the object-group member
host	Host address of the object-group member
<i>hostaddr</i>	A.B.C.D Host address

Command Mode

- /exec/configure/ipgroup

no

[no] { userprofile | trustedCert | CRLLookup | user-switch-bind | user-certdn-match | user-pubkey-match }

Syntax Description

no	Negate a command or set its defaults
userprofile	Delete the userprofile
trustedCert	Delete the trustedCert
CRLLookup	Delete the CRLLookup
user-switch-bind	Delete the user-switch-bind
user-certdn-match	Delete the certificate matching
user-pubkey-match	Delete the pubkey matching

Command Mode

- /exec/configure/ldap/search

no

[no] <seqno>

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/arpacl /exec/configure/ipgroup /exec/configure/ipv6group /exec/configure/portgroup /exec/configure/timerange

no

[no] <seqno>

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/macac1

no

[no] <seqno>

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/mplsac1

no

[no] <seqno>

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	Sequence number

Command Mode

- /exec/configure/ipacl /exec/configure/ipv6acl

no

```
{ [ <seqno> ] | no } <permitdeny> { { { { ethertype <ethertypeid> } | { ip | <proto> | <ip_other_proto> } {
<src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp
<src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host>
} | { dst_key_addrgrp <dst_addrgrp_name> } } { { [ [ fragments ] | [ log ] [ time-range <time_range_name>
] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str>
} } | { ttl <ttl_num> } | { udf { <udf_name> <udf_val> <udf_mask> } + } ] } + | { [ [ fragments ] | [ log ] [
time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } |
{ tos { <tos_num> | <tos_str> } } | { precedence { <prec_num> | <prec_str> } } | { ttl <ttl_num> } | { udf {
<udf_name> <udf_val> <udf_mask> } + } ] } + } [ capture session <session-id> ] } } [ vlan <vlanid> |
ingress_intf { <intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + [ { udf { <udf_name> <udf_val>
<udf_mask> } + } ] } | { udf { <udf_name> <udf_val> <udf_mask> } + } } { [ <action> <actionid> ] } + [
log ]
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
ethertype	Configure match based on ethertype
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
<i>ethertypeid</i>	Configure the ethertype value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
ip	Any IP protocol
<i>proto</i>	A protocol number
<i>ip_other_proto</i>	ip_other_proto
<i>src_any</i>	Any
<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	Source network prefix

<i>src_key_host</i>	A single source host
<i>src_host</i>	Source address
<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits
<i>dst_prefix</i>	Destination network prefix
<i>dst_key_host</i>	A single destination host
<i>dst_host</i>	Destination address
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>tos</i>	(Optional) Match packets with given TOS value
<i>tos_num</i>	(Optional) Type of service value
<i>tos_str</i>	(Optional) Type of service label
<i>precedence</i>	(Optional) Match packets with given precedence value
<i>prec_num</i>	(Optional) Precedence value
<i>prec_str</i>	(Optional) Precedence label
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length

<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>ttl</i>	(Optional) Match Packets with a given TTL value
<i>ttl_num</i>	(Optional)
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>udf</i>	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipacl

no

```
{ [ <seqno> ] | no } <permitdeny> { { ethertype <ethertypeid> } | { <proto_tcp> { { { <src_any> | {
<src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name>
} } [ { { <src_port_op> { <src_port0> | <src_port0_str> } } | { <src_port_range> { <src_port1> |
<src_port1_str> } } { <src_port2> | <src_port2_str> } } } | src_portgroup <src_port_group> } } ] { <dst_any> | {
<dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name>
} } [ { { <dst_port_op> { <dst_port0> | <dst_port0_str> } } | { <dst_port_range> { <dst_port1> |
<dst_port1_str> } } { <dst_port2> | <dst_port2_str> } } } | dst_portgroup <dst_port_group> } } ] [ { [ urg | ack |
psh | rst | syn | fin | established | [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0>
| <plen_range> <plen1> <plen2> } } | { dscp { <dscp_num> | <dscp_str> } } } | { http-method { <opt_num> |
<opt_str> } } } | { tcp-option-length <tcp_opt_len> } | { tcp-flags-mask <tcp_flags_mask> } | { ttl <ttl_num>
} } ] + | { [ urg | ack | psh | rst | syn | fin | established | [ log ] [ time-range <time_range_name> ] | packet-length
{ <plen_op> <plen0> | <plen_range> <plen1> <plen2> } } | { tos { <tos_num> | <tos_str> } } | { precedence
{ <prec_num> | <prec_str> } } } | { ttl <ttl_num> } } ] + } [ { udf { <udf_name> <udf_val> <udf_mask> } +
} ] ] | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | {
src_key_addrgrp <src_addrgrp_name> } } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } } { [ [ fragments ] | [ log ] [ time-range
<time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } } | { dscp {
<dscp_num> | <dscp_str> } } | { ttl <ttl_num> } } | { udf { <udf_name> <udf_val> <udf_mask> } + } ] ] + |
{ [ [ fragments ] | [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range>
<plen1> <plen2> } } | { tos { <tos_num> | <tos_str> } } } | { precedence { <prec_num> | <prec_str> } } | { ttl
<ttl_num> } } | { udf { <udf_name> <udf_val> <udf_mask> } + } ] ] + } } } [ vlan <vlanid> | ingress_intf
{ <intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + { [ [ urg | ack | psh | rst | syn | fin | established |
[ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } } | { dscp { <dscp_num> | <dscp_str> } } } | { http-method { <opt_num> | <opt_str> } } ] ] + | { [ urg |
ack | psh | rst | syn | fin | established | [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op>
<plen0> | <plen_range> <plen1> <plen2> } } | { tos { <tos_num> | <tos_str> } } } | { precedence { <prec_num>
| <prec_str> } } } | { ttl <ttl_num> } } ] + } [ { udf { <udf_name> <udf_val> <udf_mask> } + } ] [ capture
session <session-id> ] [ [ <action> <actionid> ] ] + [ log ]
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
ethertype	Configure match based on ethertype
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
<i>ethertypeid</i>	Configure the ethertype value
<i>vlanid</i>	(Optional) VLAN number

<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>proto_tcp</i>	Protocol
<i>src_any</i>	Any
<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	Source network prefix
<i>src_key_host</i>	A single source host
<i>src_host</i>	Source address
<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>src_port_op</i>	(Optional) Port operator
<i>src_port_range</i>	(Optional) Port range
<i>src_port0</i>	(Optional) Port number
<i>src_port0_str</i>	(Optional) TCP port
<i>src_port1</i>	(Optional) Port number
<i>src_port1_str</i>	(Optional) TCP port
<i>src_port2</i>	(Optional) Port number
<i>src_port2_str</i>	(Optional) TCP port
<i>src_portgroup</i>	(Optional) src port group
<i>src_port_group</i>	(Optional) Port group name
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits
<i>dst_prefix</i>	Destination network prefix
<i>dst_key_host</i>	A single destination host
<i>dst_host</i>	Destination address
<i>dst_key_addrgrp</i>	Destination address group

<i>dst_addrgrp_name</i>	Address group name
<i>dst_port_op</i>	(Optional) Port operator
<i>dst_port_range</i>	(Optional) Port range
<i>dst_port0</i>	(Optional) Port number
<i>dst_port0_str</i>	(Optional) TCP port
<i>dst_port1</i>	(Optional) Port number
<i>dst_port1_str</i>	(Optional) TCP port
<i>dst_port2</i>	(Optional) Port number
<i>dst_port2_str</i>	(Optional) TCP port
<i>dst_portgroup</i>	(Optional) dst port group
<i>dst_port_group</i>	(Optional) Port group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>tos</i>	(Optional) Match packets with given TOS value
<i>tos_num</i>	(Optional) Type of service value
<i>tos_str</i>	(Optional) Type of service label
<i>precedence</i>	(Optional) Match packets with given precedence value
<i>prec_num</i>	(Optional) Precedence value
<i>prec_str</i>	(Optional) Precedence label
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length

<i>plen2</i>	(Optional) Higher packet length
<i>ttl</i>	(Optional) Match Packets with a given TTL value
<i>ttl_num</i>	(Optional)
<i>tcp-option-length</i>	(Optional) Specify TCP Options size
<i>tcp_opt_len</i>	(Optional) TCP option length (multiples of 4 bytes)
<i>tcp-flags-mask</i>	(Optional) Specify TCP Flags
<i>tcp_flags_mask</i>	(Optional) TCP flags mask
<i>http-method</i>	(Optional) Match packets based on http-method
<i>opt_num</i>	(Optional) http_option value
<i>opt_str</i>	(Optional) http_option_param
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>urg</i>	(Optional) Match on the URG bit
<i>ack</i>	(Optional) Match on the ACK bit
<i>psh</i>	(Optional) Match on the PSH bit
<i>rst</i>	(Optional) Match on the RST bit
<i>syn</i>	(Optional) Match on the SYN bit
<i>fin</i>	(Optional) Match on the FIN bit
<i>established</i>	(Optional) Match established connections
<i>udf</i>	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session

<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipacl

no

```
{ [ <seqno> ] | no } <permitdeny> { { ethertype <ethertypeid> } | { <proto_udp> { { { <src_any> | {
<src_addr><src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name>
} } [ { { <src_port_op> { <src_port0> | <src_port0_str> } } | { <src_port_range> { <src_port1> |
<src_port1_str> } { <src_port2> | <src_port2_str> } } | src_portgroup <src_port_group> } ] { <dst_any> | {
<dst_addr><dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name>
} } [ { { <dst_port_op> { <dst_port0> | <dst_port0_str> } } | { <dst_port_range> { <dst_port1> |
<dst_port1_str> } { <dst_port2> | <dst_port2_str> } } | dst_portgroup <dst_port_group> } ] { { [ [ log ] [
time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } |
{ dscp { <dscp_num> | <dscp_str> } } | { ttl <ttl_num> } ] } + | { [ [ log ] [ time-range <time_range_name>
] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { tos { <tos_num> | <tos_str> }
} | { precedence { <prec_num> | <prec_str> } } | { ttl <ttl_num> } ] } + | { udf { <udf_name> <udf_val>
<udf_mask> } + } ] [ nve vni <vni-id> ] } | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | {
src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild>
} | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } { { [ [ fragments
] | [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } | { dscp { <dscp_num> | <dscp_str> } } | { ttl <ttl_num> } | { udf { <udf_name> <udf_val>
<udf_mask> } + } ] } + | { [ [ fragments ] | [ log ] [ time-range <time_range_name> ] | packet-length {
<plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence {
<prec_num> | <prec_str> } } | { ttl <ttl_num> } | { udf { <udf_name> <udf_val> <udf_mask> } + } ] } + }
} ] [ nve vni <vni-id> ] } } [ vlan <vlanid> | ingress_intf { <intfid> | <intfname> } | vlan_priority
<vlanpriorityid> ] + { { [ [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> |
<plen_range> <plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str> } } | { ttl <ttl_num> } ] } + | { [ [ log
] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2>
} | { tos { <tos_num> | <tos_str> } } | { precedence { <prec_num> | <prec_str> } } | { ttl <ttl_num> } ] } + }
] [ udf { <udf_name> <udf_val> <udf_mask> } + } ] # 2293 ../feature/acl_mgr/cli/aclmgr.cmd [ capture
session <session-id> ] { [ <action> <actionid> ] } + [ log ]
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
ethertype	Configure match based on ethertype
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
<i>ethertypeid</i>	Configure the ethertype value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name

<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>proto_udp</i>	Protocol
<i>src_any</i>	Any
<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	Source network prefix
<i>src_key_host</i>	A single source host
<i>src_host</i>	Source address
<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>src_port_op</i>	(Optional) Port operator
<i>src_port_range</i>	(Optional) Port range
<i>src_port0</i>	(Optional) Port number
<i>src_port0_str</i>	(Optional) UDP port
<i>src_port1</i>	(Optional) Port number
<i>src_port1_str</i>	(Optional) UDP port
<i>src_port2</i>	(Optional) Port number
<i>src_port2_str</i>	(Optional) UDP port
<i>src_portgroup</i>	(Optional) src port group
<i>src_port_group</i>	(Optional) Port group name
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits
<i>dst_prefix</i>	Destination network prefix
<i>dst_key_host</i>	A single destination host
<i>dst_host</i>	Destination address
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dst_port_op</i>	(Optional) Port operator

<i>dst_port_range</i>	(Optional) Port range
<i>dst_port0</i>	(Optional) Port number
<i>dst_port0_str</i>	(Optional) UDP port
<i>dst_port1</i>	(Optional) Port number
<i>dst_port1_str</i>	(Optional) UDP port
<i>dst_port2</i>	(Optional) Port number
<i>dst_port2_str</i>	(Optional) UDP port
<i>dst_portgroup</i>	(Optional) dst port group
<i>dst_port_group</i>	(Optional) Port group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>tos</i>	(Optional) Match packets with given TOS value
<i>tos_num</i>	(Optional) Type of service value
<i>tos_str</i>	(Optional) Type of service label
<i>precedence</i>	(Optional) Match packets with given precedence value
<i>prec_num</i>	(Optional) Precedence value
<i>prec_str</i>	(Optional) Precedence label
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>ttl</i>	(Optional) Match Packets with a given TTL value

<i>ttl_num</i>	(Optional)
<i>nve</i>	(Optional) VNI ID <0-16777215>
<i>vni</i>	(Optional) VNI ID <0-16777215>
<i>vni-id</i>	(Optional) VNI ID <0-16777215>
<i>udf</i>	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipacl

no

```
{ [ <seqno> ] | no } <permitdeny> <proto_igmp> { { { <src_any> | { <src_addr> <src_wild> } | <src_prefix>
| { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr>
<dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } } [
[ log ] [ time-range <time_range_name> ] | <igmp_num> | packet-length { <plen_op> <plen0> | <plen_range>
<plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str> } } ] + [ [ log ] [ time-range <time_range_name> ]
| <igmp_str> | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { dscp { <dscp_num>
| <dscp_str> } } ] + [ [ log ] [ time-range <time_range_name> ] | <igmp_num> | packet-length { <plen_op>
<plen0> | <plen_range> <plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence { <prec_num>
| <prec_str> } } ] + [ [ log ] [ time-range <time_range_name> ] | <igmp_str> | packet-length { <plen_op>
<plen0> | <plen_range> <plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence { <prec_num>
| <prec_str> } } ] + } } | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host>
} | { src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } { { [ fragments ] | [ log ] [ time-range
<time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { dscp {
<dscp_num> | <dscp_str> } } | { ttl <ttl_num> } } ] + | { [ fragments ] | [ log ] [ time-range
<time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { tos {
<tos_num> | <tos_str> } } | { precedence { <prec_num> | <prec_str> } } | { ttl <ttl_num> } } ] + } } [ capture
session <session-id> ] { [ <action> <actionid> ] } + [ log ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>proto_igmp</i>	Protocol
<i>src_any</i>	Any
<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	Source network prefix
<i>src_key_host</i>	A single source host
<i>src_host</i>	Source address
<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits

<i>dst_prefix</i>	Destination network prefix
<i>dst_key_host</i>	A single destination host
<i>dst_host</i>	Destination address
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>tos</i>	(Optional) Match packets with given TOS value
<i>tos_num</i>	(Optional) Type of service value
<i>tos_str</i>	(Optional) Type of service label
<i>precedence</i>	(Optional) Match packets with given precedence value
<i>prec_num</i>	(Optional) Precedence value
<i>prec_str</i>	(Optional) Precedence label
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>ttl</i>	(Optional) Match Packets with a given TTL value
<i>ttl_num</i>	(Optional)
<i>igmp_num</i>	(Optional) IGMP message type
<i>igmp_str</i>	(Optional) IGMP type
<i>capture</i>	(Optional) Enable packet capture on this filter for session

<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipacl

no

```
{ [ <seqno> ] | no } <permitdeny> { { { ethertype <ethertypeid> } | { <proto_icmp> { { { <src_any> | {
<src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name>
} } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp
<dst_addrgrp_name> } } } { [ [ log ] [ time-range <time_range_name> ] | { <icmp_type> [ <icmp_code> ] |
packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str>
} } } ] + [ [ log ] [ time-range <time_range_name> ] | <icmp_str> | packet-length { <plen_op> <plen0> |
<plen_range> <plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str> } } ] + [ [ log ] [ time-range
<time_range_name> ] | { <icmp_type> [ <icmp_code> ] | packet-length { <plen_op> <plen0> | <plen_range>
<plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence { <prec_num> | <prec_str> } } ] + [ [
log ] [ time-range <time_range_name> ] | <icmp_str> | packet-length { <plen_op> <plen0> | <plen_range>
<plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence { <prec_num> | <prec_str> } } ] + }
| { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp
<src_addrgrp_name> } } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host>
} | { dst_key_addrgrp <dst_addrgrp_name> } } } { [ [ fragments ] [ log ] [ time-range <time_range_name>
] | packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { dscp { <dscp_num> | <dscp_str>
} } } | { ttl <ttl_num> } } ] + [ [ fragments ] [ log ] [ time-range <time_range_name> ] | packet-length {
<plen_op> <plen0> | <plen_range> <plen1> <plen2> } | { tos { <tos_num> | <tos_str> } } | { precedence {
<prec_num> | <prec_str> } } | { ttl <ttl_num> } } ] + } } } [ vlan <vlanid> | ingress_intf { <intfid> |
<intfname> } | vlan_priority <vlanpriorityid> ] + [ capture session <session-id> ] { [ <action> <actionid> ]
} + [ log ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
ethertype	Configure match based on ethertype
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
<i>ethertypeid</i>	Configure the ethertype value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>proto_icmp</i>	Protocol
<i>src_any</i>	Any

<i>src_addr</i>	Source network address
<i>src_wild</i>	Source wildcard bits
<i>src_prefix</i>	Source network prefix
<i>src_key_host</i>	A single source host
<i>src_host</i>	Source address
<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination network address
<i>dst_wild</i>	Destination wildcard bits
<i>dst_prefix</i>	Destination network prefix
<i>dst_key_host</i>	A single destination host
<i>dst_host</i>	Destination address
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>tos</i>	(Optional) Match packets with given TOS value
<i>tos_num</i>	(Optional) Type of service value
<i>tos_str</i>	(Optional) Type of service label
<i>precedence</i>	(Optional) Match packets with given precedence value
<i>prec_num</i>	(Optional) Precedence value
<i>prec_str</i>	(Optional) Precedence label
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length

<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>ttl</i>	(Optional) Match Packets with a given TTL value
<i>ttl_num</i>	(Optional)
<i>icmp_type</i>	(Optional) ICMP message type
<i>icmp_code</i>	(Optional) ICMP message code
<i>icmp_str</i>	(Optional) ICMP label
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>action</i>	(Optional) Action
<i>actionid</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipacl

no

```
{ [ <seqno> ] | no } <permitdeny> <proto_tcp> { { { <src_any> | { <src_addr> <src_wild> } | <src_prefix>
| { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } [ { { <src_port_op> { <src_port0>
| <src_port0_str> } } | { <src_port_range> { <src_port1> | <src_port1_str> } { <src_port2> | <src_port2_str>
} } | src_portgroup <src_port_group> } ] { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } [ { { <dst_port_op> { <dst_port0>
| <dst_port0_str> } } | { <dst_port_range> { <dst_port1> | <dst_port1_str> } { <dst_port2> | <dst_port2_str>
} } | dst_portgroup <dst_port_group> } ] [ { { dscp { <dscp_num> | <dscp_str> } } ] [ { flow-label
<flow_num> } ] [ log ] [ time-range <time_range_name> ] [ urg | ack | psh | rst | syn | fin | established ] | {
tcp-flags-mask <tcp_flags_mask> } | [ packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2>
} ] ] + } | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> } | {
src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } { [ { dscp { <dscp_num> | <dscp_str>
} } ] [ { flow-label <flow_num> } ] [ fragments ] [ log ] [ time-range <time_range_name> ] [ packet-length
{ <plen_op> <plen0> | <plen_range> <plen1> <plen2> } ] [ { udf { <udf_name> <udf_val> <udf_mask> }
+ } ] ] + } } [ vlan <vlanid> | ingress_intf { <intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + [
capture session <session-id> ] [ { <actionv6> <actionidv6> } ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>proto_tcp</i>	Protocol
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
udf	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>src_any</i>	Any
src_key_host	A single source host

<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>src_port_op</i>	(Optional) Port operator
<i>src_port_range</i>	(Optional) Port range
<i>src_port0</i>	(Optional) Port number
<i>src_port0_str</i>	(Optional) TCP port
<i>src_port1</i>	(Optional) Port number
<i>src_port1_str</i>	(Optional) TCP port
<i>src_port2</i>	(Optional) Port number
<i>src_port2_str</i>	(Optional) TCP port
<i>src_portgroup</i>	(Optional) src port group
<i>src_port_group</i>	(Optional) Port group name
<i>dst_any</i>	Any
<i>dst_key_host</i>	A single destination host
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dst_port_op</i>	(Optional) Port operator
<i>dst_port_range</i>	(Optional) Port range
<i>dst_port0</i>	(Optional) Port number
<i>dst_port0_str</i>	(Optional) TCP port
<i>dst_port1</i>	(Optional) Port number
<i>dst_port1_str</i>	(Optional) TCP port
<i>dst_port2</i>	(Optional) Port number
<i>dst_port2_str</i>	(Optional) TCP port
<i>dst_portgroup</i>	(Optional) dst port group
<i>dst_port_group</i>	(Optional) Port group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label

flow-label	(Optional) Flow label
<i>flow_num</i>	(Optional) Flow label value
fragments	(Optional) Check non-initial fragments
log	(Optional) Log matches against this entry
time-range	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
packet-length	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
tcp-flags-mask	Specify TCP Flags
<i>tcp_flags_mask</i>	TCP flags mask
urg	(Optional) Match on the URG bit
ack	(Optional) Match on the ACK bit
psh	(Optional) Match on the PSH bit
rst	(Optional) Match on the RST bit
syn	(Optional) Match on the SYN bit
fin	(Optional) Match on the FIN bit
established	(Optional) Match established connections
capture	(Optional) Enable packet capture on this filter for session
session	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>actionv6</i>	(Optional) ActionV6
<i>actionidv6</i>	(Optional) redirect: Ethernet1/1,port-channell set-erspan-dscp: <1-63> set-erspan-gre-PROTO: <1-65535>

Command Mode

- /exec/configure/ipv6acl

no

```
{ [ <seqno> ] no } <permitdeny> <proto_udp> { { { <src_any> | { <src_addr> <src_wild> } | <src_prefix>
| { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } [ { { <src_port_op> { <src_port0>
| <src_port0_str> } } | { <src_port_range> { <src_port1> | <src_port1_str> } { <src_port2> | <src_port2_str>
} } | src_portgroup <src_port_group> } ] { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } [ { { <dst_port_op> { <dst_port0>
| <dst_port0_str> } } | { <dst_port_range> { <dst_port1> | <dst_port1_str> } { <dst_port2> | <dst_port2_str>
} } | dst_portgroup <dst_port_group> } ] [ { { dscp { <dscp_num> | <dscp_str> } } ] [ { flow-label <flow_num>
} ] [ log ] [ time-range <time_range_name> ] [ packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } ] + } [ nve vni <vni-id> ] | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | {
src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild>
} | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } { { dscp {
<dscp_num> | <dscp_str> } } ] [ { flow-label <flow_num> } ] [ fragments ] [ log ] [ time-range
<time_range_name> ] [ packet-length { <plen_op> <plen0> | <plen_range> <plen1> <plen2> } ] [ { udf {
<udf_name> <udf_val> <udf_mask> } + } ] + } ] [ nve vni <vni-id> ] [ vlan <vlanid> | ingress_intf {
<intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + [ capture session <session-id> ] { [ <actionv6>
<actionidv6> ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>proto_udp</i>	Protocol
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
udf	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>src_any</i>	Any
src_key_host	A single source host

<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>src_port_op</i>	(Optional) Port operator
<i>src_port_range</i>	(Optional) Port range
<i>src_port0</i>	(Optional) Port number
<i>src_port0_str</i>	(Optional) UDP port
<i>src_port1</i>	(Optional) Port number
<i>src_port1_str</i>	(Optional) UDP port
<i>src_port2</i>	(Optional) Port number
<i>src_port2_str</i>	(Optional) UDP port
<i>src_portgroup</i>	(Optional) src port group
<i>src_port_group</i>	(Optional) Port group name
<i>dst_any</i>	Any
<i>dst_key_host</i>	A single destination host
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dst_port_op</i>	(Optional) Port operator
<i>dst_port_range</i>	(Optional) Port range
<i>dst_port0</i>	(Optional) Port number
<i>dst_port0_str</i>	(Optional) UDP port
<i>dst_port1</i>	(Optional) Port number
<i>dst_port1_str</i>	(Optional) UDP port
<i>dst_port2</i>	(Optional) Port number
<i>dst_port2_str</i>	(Optional) UDP port
<i>dst_portgroup</i>	(Optional) dst port group
<i>dst_port_group</i>	(Optional) Port group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label

flow-label	(Optional) Flow label
<i>flow_num</i>	(Optional) Flow label value
fragments	(Optional) Check non-initial fragments
log	(Optional) Log matches against this entry
time-range	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
packet-length	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
capture	(Optional) Enable packet capture on this filter for session
session	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
nve	(Optional) VNI ID <0-16777215>
vni	(Optional) VNI ID <0-16777215>
<i>vni-id</i>	(Optional) VNI ID <0-16777215>
<i>actionv6</i>	(Optional) ActionV6
<i>actionidv6</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipv6acl

no

```
{ [ <seqno> ] | no } <permitdeny> <proto_sctp> { { { <src_any> | { <src_addr> <src_wild> } | <src_prefix>
| { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } [ { { <src_port_op> { <src_port0>
| <src_port0_str> } } | { <src_port_range> { <src_port1> | <src_port1_str> } { <src_port2> | <src_port2_str>
} } | src_portgroup <src_port_group> } ] { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } [ { { <dst_port_op> { <dst_port0>
| <dst_port0_str> } } | { <dst_port_range> { <dst_port1> | <dst_port1_str> } { <dst_port2> | <dst_port2_str>
} } | dst_portgroup <dst_port_group> } ] [ { dscp { <dscp_num> | <dscp_str> } } ] [ { flow-label <flow_num>
} ] [ log ] [ time-range <time_range_name> ] [ packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } ] ] + } | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> }
| { src_key_addrgrp <src_addrgrp_name> } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } [ { dscp { <dscp_num> | <dscp_str>
} } ] [ { flow-label <flow_num> } ] [ fragments ] [ log ] [ time-range <time_range_name> ] [ packet-length
{ <plen_op> <plen0> | <plen_range> <plen1> <plen2> } ] [ { udf { <udf_name> <udf_val> <udf_mask> }
+ } ] ] + [ vlan <vlanid> | ingress_intf { <intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + [ capture
session <session-id> ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>proto_sctp</i>	Protocol
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
udf	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>src_any</i>	Any
src_key_host	A single source host

<i>src_key_addrgrp</i>	Source address group
<i>src_addrgrp_name</i>	Address group name
<i>src_port_op</i>	(Optional) Port operator
<i>src_port_range</i>	(Optional) Port range
<i>src_port0</i>	(Optional) Port number
<i>src_port0_str</i>	(Optional) SCTP port
<i>src_port1</i>	(Optional) Port number
<i>src_port1_str</i>	(Optional) SCTP port
<i>src_port2</i>	(Optional) Port number
<i>src_port2_str</i>	(Optional) SCTP port
<i>src_portgroup</i>	(Optional) src port group
<i>src_port_group</i>	(Optional) Port group name
<i>dst_any</i>	Any
<i>dst_key_host</i>	A single destination host
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dst_port_op</i>	(Optional) Port operator
<i>dst_port_range</i>	(Optional) Port range
<i>dst_port0</i>	(Optional) Port number
<i>dst_port0_str</i>	(Optional) SCTP port
<i>dst_port1</i>	(Optional) Port number
<i>dst_port1_str</i>	(Optional) SCTP port
<i>dst_port2</i>	(Optional) Port number
<i>dst_port2_str</i>	(Optional) SCTP port
<i>dst_portgroup</i>	(Optional) dst port group
<i>dst_port_group</i>	(Optional) Port group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label

flow-label	(Optional) Flow label
<i>flow_num</i>	(Optional) Flow label value
fragments	(Optional) Check non-initial fragments
log	(Optional) Log matches against this entry
time-range	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
packet-length	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
capture	(Optional) Enable packet capture on this filter for session
session	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session

Command Mode

- /exec/configure/ipv6acl

no

```
{ [ <seqno> ] no } <permitdeny> <proto_icmpv6> { { { { <src_any> | { <src_addr> <src_wild> } |
<src_prefix> | { src_key_host <src_host> } | { src_key_addrgrp <src_addrgrp_name> } } } { <dst_any> | {
<dst_addr> <dst_wild> } | <dst_prefix> | { dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name>
} } } { [ { <icmpv6_type> [ <icmpv6_code> ] } | { dscp { <dscp_num> | <dscp_str> } } | { flow-label
<flow_num> } ] [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range>
<plen1> <plen2> } } ] + [ [ <icmpv6_str> | { dscp { <dscp_num> | <dscp_str> } } | { flow-label <flow_num>
} ] [ log ] [ time-range <time_range_name> ] | packet-length { <plen_op> <plen0> | <plen_range> <plen1>
<plen2> } } ] + } | { { <src_any> | { <src_addr> <src_wild> } | <src_prefix> | { src_key_host <src_host> }
| { src_key_addrgrp <src_addrgrp_name> } } } { <dst_any> | { <dst_addr> <dst_wild> } | <dst_prefix> | {
dst_key_host <dst_host> } | { dst_key_addrgrp <dst_addrgrp_name> } } } { [ { dscp { <dscp_num> | <dscp_str>
} } ] [ { flow-label <flow_num> } ] [ fragments ] [ log ] [ time-range <time_range_name> ] [ packet-length
{ <plen_op> <plen0> | <plen_range> <plen1> <plen2> } ] [ { udf { <udf_name> <udf_val> <udf_mask>
+ } } ] + } } [ vlan <vlanid> | ingress_intf { <intfid> | <intfname> } | vlan_priority <vlanpriorityid> ] + [
capture session <session-id> ] { [ <actionv6> <actionidv6> ] } }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>proto_icmpv6</i>	Protocol
vlan	(Optional) Configure match based on vlan
ingress_intf	(Optional) Configure match based on ingress interface
vlan_priority	(Optional) Configure match based on priority
udf	(Optional) User defined field match
<i>udf_name</i>	(Optional) UDF name
<i>udf_val</i>	(Optional) UDF value to match
<i>udf_mask</i>	(Optional) Mask to apply to UDF value
<i>vlanid</i>	(Optional) VLAN number
<i>intfid</i>	(Optional) Interface index
<i>intfname</i>	(Optional) Interface name
<i>vlanpriorityid</i>	(Optional) Vlan Priority
<i>src_any</i>	Any
src_key_host	A single source host
src_key_addrgrp	Source address group

<i>src_addrgrp_name</i>	Address group name
<i>dst_any</i>	Any
<i>dst_key_host</i>	A single destination host
<i>dst_key_addrgrp</i>	Destination address group
<i>dst_addrgrp_name</i>	Address group name
<i>dscp</i>	(Optional) Match packets with given dscp value
<i>dscp_num</i>	(Optional) Differentiated services codepoint value
<i>dscp_str</i>	(Optional) Differentiated services codepoint label
<i>flow-label</i>	(Optional) Flow label
<i>flow_num</i>	(Optional) Flow label value
<i>fragments</i>	(Optional) Check non-initial fragments
<i>log</i>	(Optional) Log matches against this entry
<i>time-range</i>	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
<i>packet-length</i>	(Optional) Match packets based on layer 3 packet length
<i>plen_op</i>	(Optional) Packet-length operator
<i>plen_range</i>	(Optional) Packet-length range
<i>plen0</i>	(Optional) Packet length
<i>plen1</i>	(Optional) Lower packet length
<i>plen2</i>	(Optional) Higher packet length
<i>icmpv6_type</i>	(Optional) ICMPv6 message type
<i>icmpv6_code</i>	(Optional) ICMPv6 message code
<i>icmpv6_str</i>	(Optional) ICMPv6 label
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>actionv6</i>	(Optional) ActionV6
<i>actionidv6</i>	(Optional) redirect: Ethernet1/1,port-channel1 set-erspan-dscp: <1-63> set-erspan-gre-proto: <1-65535>

Command Mode

- /exec/configure/ipv6acl

no

```
{ { [ <seqno> ] | no } <permitdeny> { { [ <arp_request> ] req_ip { <sender1_ip_any> | { { <sender1_host>
<sender1_ip> | { <sender1_net_ip> <sender1_ip_mask> } } } } mac { <sender1_mac_any> | { {
<sender1_mac_host> <sender1_mac> | { <sender1_net_mac> <sender1_mac_mask> } } } } | {
<arp_response> resp_ip { <sender2_ip_any> | { { <sender2_host> <sender2_ip> | { <sender2_net_ip>
<sender2_ip_mask> } } } } { <target_ip_any> | { { <target_host> <target_ip> | { <target_net_ip>
<target_ip_mask> } } } } mac { <sender2_mac_any> | { { <sender2_mac_host> <sender2_mac> | {
<sender2_net_mac> <sender2_mac_mask> } } } } [ { <target_mac_any> | { { <target_mac_host> <target_mac>
| { <target_net_mac> <target_mac_mask> } } } } ] } [ <arp_log> ] [ capture session <session-id> ] }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
req_ip	Any IP protocol
resp_ip	Any IP protocol
<i>arp_request</i>	(Optional) ARP_Request
<i>arp_response</i>	ARP_Response
<i>sender1_ip_any</i>	Any
<i>sender1_host</i>	Host
<i>sender1_ip</i>	IP address <a.b.c.d>
<i>sender1_net_ip</i>	IP address <a.b.c.d>
<i>sender1_ip_mask</i>	IP mask <a.b.c.d>
<i>sender2_ip_any</i>	Any
<i>sender2_host</i>	Host
<i>sender2_ip</i>	IP address <a.b.c.d>
<i>sender2_net_ip</i>	IP address <a.b.c.d>
<i>sender2_ip_mask</i>	IP mask <a.b.c.d>
<i>target_ip_any</i>	Any
<i>target_host</i>	Host
<i>target_ip</i>	IP address <a.b.c.d>
<i>target_net_ip</i>	IP address <a.b.c.d>

<i>target_ip_mask</i>	IP mask <a.b.c.d>
<i>mac</i>	MAC configuration commands
<i>sender1_mac_any</i>	Any
<i>sender1_mac_host</i>	Host
<i>sender1_mac</i>	MAC address EEEE.EEEE.EEEE
<i>sender1_net_mac</i>	MAC address EEEE.EEEE.EEEE
<i>sender1_mac_mask</i>	MAC mask EEEE.EEEE.EEEE
<i>sender2_mac_any</i>	Any
<i>sender2_mac_host</i>	Host
<i>sender2_mac</i>	MAC address EEEE.EEEE.EEEE
<i>sender2_net_mac</i>	MAC address EEEE.EEEE.EEEE
<i>sender2_mac_mask</i>	MAC mask EEEE.EEEE.EEEE
<i>target_mac_any</i>	(Optional) Any
<i>target_mac_host</i>	(Optional) Host
<i>target_mac</i>	(Optional) MAC address EEEE.EEEE.EEEE
<i>target_net_mac</i>	(Optional) MAC address EEEE.EEEE.EEEE
<i>target_mac_mask</i>	(Optional) MAC mask EEEE.EEEE.EEEE
<i>arp_log</i>	(Optional) Log
<i>capture</i>	(Optional) Enable packet capture on this filter for session
<i>session</i>	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session

Command Mode

- /exec/configure/arpacl

no

{ [<seqno>] | no } { <addr> <wild> | <prefix> | host <hostaddr> }

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
host	Host address of the object-group member

Command Mode

- /exec/configure/ipv6group

no

```
{ [ <seqno> ] | no } { <_port_op> <port0_num> | <_port_range> <port1_num> <port2_num> }
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>_port_op</i>	Port operator
<i>_port_range</i>	Port range
<i>port0_num</i>	Port number
<i>port1_num</i>	Port number
<i>port2_num</i>	Port number

Command Mode

- /exec/configure/portgroup

no

```
{ [ <seqno> ] | no } <permitdeny> { <src_any> | { <src_addr> <src_wild> } } { <dst_any> | { <dst_addr>
<dst_wild> } } [ <mac_proto> | <mac_proto_str> ] [ vlan <vlan> | cos <cos> ] + [ time-range
<time_range_name> ] [ capture session <session-id> ] { [ <macaction> <macactionid> ] } +
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
<i>permitdeny</i>	Permit/deny
<i>src_any</i>	Any
<i>src_addr</i>	Source MAC address
<i>src_wild</i>	Source wildcard bits
<i>dst_any</i>	Any
<i>dst_addr</i>	Destination MAC address
<i>dst_wild</i>	Destination wildcard bits
<i>mac_proto</i>	(Optional) MAC protocol number
<i>mac_proto_str</i>	(Optional) MAC protocol name
vlan	(Optional) VLAN number
cos	(Optional) CoS value
<i>vlan</i>	(Optional) VLAN number
<i>cos</i>	(Optional) CoS value
time-range	(Optional) Specify a time range
<i>time_range_name</i>	(Optional) Time range name
capture	(Optional) Enable packet capture on this filter for session
session	(Optional) Session ID <1-48> for this session
<i>session-id</i>	(Optional) Session ID <1-48> for this session
<i>macaction</i>	(Optional) MAC ACL Action
<i>macactionid</i>	(Optional) redirect: Ethernet1/1,port-channel1

Command Mode

- /exec/configure/macacl

no

no

Syntax Description

no	Negate a command or set its defaults
----	--------------------------------------

Command Mode

- /exec/configure/vsan-db

node

[no] node [ip <ip-addr> | IPv6 <ip-addrv6>]

Syntax Description

no	(Optional) Negate a command or set its defaults
node	ITD node
ip	(Optional) ITD node IPv4 address
<i>ip-addr</i>	(Optional) ITD node IP4 prefix in format i.i.i.i
IPv6	(Optional) ITD node IPv6 address

Command Mode

- /exec/configure/itd-device-group

node

[no] node [ip <ip-addr> | IPv6 <ip-addrv6>]

Syntax Description

no	(Optional) Negate a command or set its defaults
node	Catena device-group node
ip	(Optional) Catena device-group node IPv4 address
<i>ip-addr</i>	(Optional) Catena device-group node IP4 prefix in format i.i.i.i
IPv6	(Optional) Catena device-group node IPv6 address

Command Mode

- /exec/configure/catena-device-grp

node

[no] node [ip <ip-addr> | IPv6 <ip-addrv6>]

Syntax Description

no	(Optional) Negate a command or set its defaults
node	ITD node
ip	(Optional) ITD node IPv4 address
<i>ip-addr</i>	(Optional) ITD node IP4 prefix in format i.i.i.i
IPv6	(Optional) ITD node IPv6 address

Command Mode

- /exec/configure/itd-session-device-group

node ip

[no] node { ip <ip-addr> | IPv6 <ip-addrv6> }

Syntax Description

no	(Optional) Negate a command or set its defaults
node	Configure nodes for PLB device group
ip	node IPv4 address
<i>ip-addr</i>	IP4 prefix in format i.i.i.i
IPv6	node IPv6 address

Command Mode

- /exec/configure/plb-session-device-group

node ip

[no] node { ip <ip-addr> | IPv6 <ip-addrv6> }

Syntax Description

no	(Optional) Negate a command or set its defaults
node	Configure nodes for PLB device group
ip	node IPv4 address
<i>ip-addr</i>	IP4 prefix in format i.i.i.i
IPv6	node IPv6 address

Command Mode

- /exec/configure/plb-device-group

npiv enable

[no] npiv enable

Syntax Description

no	(Optional) Negate a command or set its defaults
enable	Enable/Disable Nx port Id Virtualization (NPIV)

Command Mode

- /exec/configure

npv auto-load-balance disruptive

[no] npv auto-load-balance disruptive

Syntax Description

no	(Optional) Negate a command or set its defaults
npv	Config commands for FC N_port Virtualizer
auto-load-balance	configure auto load balancing among preferred external links
disruptive	enable disruptive auto load balancing among external links

Command Mode

- /exec/configure

npv traffic-map server-interface external-interface

[no] npv traffic-map server-interface <if1> external-interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
npv	Config commands for FC N_port Virtualizer
traffic-map	Configure NPV traffic engineering
server-interface	Configure server interface based traffic engineering
<i>if1</i>	
external-interface	Configure preferred external interface(s)
<i>interface</i>	

Command Mode

- /exec/configure

nsf await-redist-proto-convergence

{ [no] nsf await-redist-proto-convergence }

Syntax Description

no	(Optional) Negate a command or set its defaults
nsf	Non-stop forwarding
await-redist-proto-convergence	Specify whether EIGRP should wait for other protocols to converge before advertising routes

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

ntp access-group

[no] ntp access-group { peer | serve-only | serve | query-only } <acl-name>

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
access-group	NTP access-group
peer	access-group peer
serve	access-group serve
serve-only	access-group serve-only
query-only	access-group query-only
<i>acl-name</i>	Name of access list

Command Mode

- /exec/configure

ntp access-group match-all

[no] ntp access-group match-all

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
access-group	NTP access-group
match-all	Scan ACLs present in all ntp access groups

Command Mode

- /exec/configure

ntp allow private

```
[no] ntp allow { private | control [ rate-limit <delay> ] }
```

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
allow	Enable/Disable the packets
private	Enable/Disable Private mode packets
control	Enable/Disable Control mode packets
rate-limit	(Optional) Rate-limit the control packets
<i>delay</i>	(Optional) Rate-limit delay (Default 3)

Command Mode

- /exec/configure

ntp authenticate

[no] ntp authenticate

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
authenticate	Enable/Disable authentication

Command Mode

- /exec/configure

ntp authentication-key md5

[no] ntp authentication-key <number> md5 <md5> [0 | 7]

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
authentication-key	NTP authentication key
<i>number</i>	authentication key number (range 1-65535)
md5	use md5 authentication scheme
<i>md5</i>	MD5 string
0	(Optional) clear text
7	(Optional) encrypted

Command Mode

- /exec/configure

ntp drop-aged-packet

[no] ntp drop-aged-packet

Syntax Description

no	(Optional) Negate a command or set its defaults
ntp	NTP Configuration
drop-aged-packet	Enable or disable Riviera Timestamp Check.

Command Mode

- /exec/configure

ntp logging

[no] ntp logging

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
logging	Enable/Disable logging of NTPD Events

Command Mode

- /exec/configure

ntp master

[no] ntp master [<stratum-no>]

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
master	Act as NTP master clock
<i>stratum-no</i>	(Optional) Stratum number

Command Mode

- /exec/configure

ntp passive

[no] ntp passive

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
passive	NTP passive command

Command Mode

- /exec/configure

ntp peer

```
[no] ntp peer <host0> [ prefer | key <keyid> | use-vrf { <vrf-name> | <vrf-known-name> } | minpoll <minpoll> | maxpoll <maxpoll> ] +
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ntp	NTP Configuration
peer	NTP Peer address
<i>host0</i>	Hostname/IP address of the NTP Peer
prefer	(Optional) Preferred Server
key	(Optional) Keyid to be used while communicating to this server
<i>keyid</i>	(Optional) Value of keyid 1-65535
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
minpoll	(Optional) Minimum interval to poll a peer
<i>minpoll</i>	(Optional) Poll interval in secs to a power of 2 [default 4]
maxpoll	(Optional) Maximum interval to poll a peer
<i>maxpoll</i>	(Optional) Poll interval in secs to a power of 2 [default 6]

Command Mode

- /exec/configure

ntp rts-update

[no] ntp rts-update

Syntax Description

no	(Optional) Negate a command or set its defaults
ntp	NTP Configuration
rts-update	Enable or disable RTS update to linecards.

Command Mode

- /exec/configure

ntp server

[no] ntp server <host0> [prefer | key <keyid> | use-vrf { <vrf-name> | <vrf-known-name> } | minpoll <minpoll> | maxpoll <maxpoll>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
ntp	NTP Configuration
server	NTP server address
<i>host0</i>	Hostname/IP address of the NTP Server
prefer	(Optional) Preferred Server
key	(Optional) Keyid to be used while communicating to this server
<i>keyid</i>	(Optional) Value of keyid 1-65535
use-vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
minpoll	(Optional) Minimum interval to poll a server
<i>minpoll</i>	(Optional) Poll interval in secs to a power of 2 [default 4]
maxpoll	(Optional) Maximum interval to poll a server
<i>maxpoll</i>	(Optional) Poll interval in secs to a power of 2 [default 6]

Command Mode

- /exec/configure

ntp source-interface

[no] ntp source-interface <interface>

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
source-interface	Source interface sending NTP packets
<i>interface</i>	Source interface

Command Mode

- /exec/configure

ntp source

[no] ntp source <ip-addr>

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP Configuration
source	Source of NTP packets
<i>ip-addr</i>	IPv4/IPv6 address

Command Mode

- /exec/configure

ntp sync-retry

ntp sync-retry

Syntax Description

ntp	NTP configuration
sync-retry	Retry synchronization with configured servers

Command Mode

- /exec

ntp trusted-key

[no] ntp trusted-key <number>

Syntax Description

no	(Optional) Negate a command or set its default
ntp	NTP configuration
trusted-key	NTP trusted-key
<i>number</i>	trusted-key number

Command Mode

- /exec/configure

nv overlay evpn

[no] nv overlay evpn

Syntax Description

no	(Optional) Negate a command or set its defaults
nv	Command to enable/disable features
overlay	Command to enable/disable features
evpn	Enable/Disable Ethernet VPN (EVPN)

Command Mode

- /exec/configure

nxapi certificate

```
{ nxapi certificate { { httpskey { keyfile <uri0> | <line> } } | { httpsCRT { certfile <uri1> | <line1> } } | { enable } } }
```

Syntax Description

nxapi	Configure nxapi
certificate	Https certificate configuration
httpskey	Https private key
httpsCRT	Https certificate
keyfile	Https key file
certfile	Https certificate file
enable	Enable the current certificate
<i>uri0</i>	File containing https private key for the user
<i>line</i>	nxapi https private key
<i>uri1</i>	File containing https certificate
<i>line1</i>	nxapi https certificate

Command Mode

- /exec/configure

nxapi flow

{ [no] nxapi flow }

Syntax Description

no	(Optional) Negate a command or set its defaults
nxapi	Configure nxapi
flow	allow frontend to access /sys/flow/

Command Mode

- /exec/configure

nxapi http port

{ nxapi { http | https } port <s0> } | { no nxapi { http | https } } | { no nxapi { http | https } port <s0> }

Syntax Description

no	Negate a command or set its defaults
nxapi	Configure nxapi
http	Http configuration
https	Https configuration
port	Port number
s0	Port number. Please do not use well-known protocol ports

Command Mode

- /exec/configure

nxapi ssl ciphers weak

```
{ [ no ] nxapi ssl ciphers weak }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
nxapi	Configure nxapi
ssl	Configure ssl parameters
ciphers	Configure allowed ciphers for ssl
weak	Allow weak ciphers

Command Mode

- /exec/configure

nxapi ssl protocols

{ nxapi ssl protocols <prot_string> } | { no nxapi ssl protocols }

Syntax Description

no	Negate a command or set its defaults
nxapi	Configure nxapi
ssl	Configure ssl parameters
protocols	Configure allowed ssl protocols
<i>prot_string</i>	String of supported protocols, Ex: TLSv1 TLSv1.1 TLSv1.2

Command Mode

- /exec/configure

nxapi use-vrf management default

```
{ nxapi use-vrf { management | default | <vrf_name> } } | { no nxapi use-vrf { management | default | <vrf_name> } }
```

Syntax Description

no	Negate a command or set its defaults
nxapi	Configure nxapi
use-vrf	vrf to be used for nxapi communication
management	management vrf
default	default vrf
<i>vrf_name</i>	name of the vrf

Command Mode

- /exec/configure

nxsdk enable app

[no] nxsdk enable app <app-index>

Syntax Description

no	(Optional) Negate a command or set its defaults
nxsdk	NXOS SDK
enable	Command to enable/disable nxsdk application
app	Enable/disable application
<i>app-index</i>	Application index

Command Mode

- /exec

nxsdk service-name

```
{ [ no ] nxsdk service-name <service-name> }
```

Syntax Description

nxsdk	NXOS SDK
service-name	Complete path and name of file to execute
<i>service-name</i>	Service name

Command Mode

- /exec/configure



0 Commands

- [oam-channel](#), on page 3243
- [object-group ip address](#), on page 3244
- [object-group ip port](#), on page 3245
- [object-group ipv6 address](#), on page 3246
- [object-group udp relay ip address](#), on page 3247
- [object-group udp relay ip address](#), on page 3248
- [object-track](#), on page 3249
- [of-port interface](#), on page 3250
- [on-demand color](#), on page 3251
- [openflow](#), on page 3252
- [operation-packet-priority normal](#), on page 3253
- [option exporter-stats timeout](#), on page 3254
- [option interface-table timeout](#), on page 3255
- [orib event-history](#), on page 3256
- [orib orib_api_init](#), on page 3257
- [ospfv3 authentication](#), on page 3258
- [ospfv3 bfd](#), on page 3259
- [ospfv3 cost](#), on page 3260
- [ospfv3 dead-interval](#), on page 3261
- [ospfv3 event-history](#), on page 3262
- [ospfv3 event-history cli](#), on page 3263
- [ospfv3 event-history detail](#), on page 3264
- [ospfv3 event-history detail](#), on page 3265
- [ospfv3 hello-interval](#), on page 3266
- [ospfv3 instance](#), on page 3267
- [ospfv3 mtu-ignore](#), on page 3268
- [ospfv3 network broadcast](#), on page 3269
- [ospfv3 network point-to-point](#), on page 3270
- [ospfv3 passive-interface](#), on page 3271
- [ospfv3 priority](#), on page 3272
- [ospfv3 retransmit-interval](#), on page 3273
- [ospfv3 shutdown](#), on page 3274
- [ospfv3 transmit-delay](#), on page 3275

- [other-config-flag](#), on page 3276
- [overlay-encapsulation](#), on page 3277
- [overwrite-vlan](#), on page 3278
- [owner](#), on page 3279

oam-channel

{ oam-channel <val> } | { no oam-channel }

Syntax Description

oam-channel	oam-channel used
<i>val</i>	2 - nvo3 tissa

Command Mode

- /exec/configure/configngoamprofile

object-group ip address

[no] object-group ip address <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
object-group	Configure ACL object groups
ip	IP Object groups
address	Address object group
<i>name</i>	object-group name

Command Mode

- /exec/configure

object-group ip port

[no] object-group ip port <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
object-group	Configure ACL object groups
ip	IP Object groups
port	IP port object group (can be used in IPv4 and IPv6 access-lists)
<i>name</i>	object-group name

Command Mode

- /exec/configure

object-group ipv6 address

[no] object-group ipv6 address <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
object-group	Configure ACL object groups
ipv6	IPv6 Object groups
address	Address object group
<i>name</i>	object-group name

Command Mode

- /exec/configure

object-group udp relay ip address

[no] object-group udp relay ip address <obj-grp-name>

Syntax Description

no	Negate a command or set its defaults
object-group	Configure object groups
udp	Configure UDP
relay	Configure UDP Relay
ip	IP Object groups
address	Address object group
<i>obj-grp-name</i>	object-group name

Command Mode

- /exec/configure

object-group udp relay ip address

object-group udp relay ip address <obj-grp-name>

Syntax Description

object-group	Configure object groups
udp	Configure UDP
relay	Configure UDP Relay
ip	IP Object groups
address	Address object group
<i>obj-grp-name</i>	object-group name

Command Mode

- /exec/configure

object-track

[no] object-track <object-number> [decrement <value>]

Syntax Description

no	(Optional) Negate a command or set its defaults
object-track	Associates track object to VRRP group
<i>object-number</i>	Set the object number to the group
decrement	(Optional) Decrements vrrp group priority when tracked object goes down
<i>value</i>	(Optional) Set the value to decrement from priority

Command Mode

- /exec/configure/if-eth-any/vrrpv3

of-port interface

[no] of-port interface <ifname>

Syntax Description

no	(Optional) Negate a command or set its defaults
of-port	Add interfaces to openflow switch
interface	Interface
<i>ifname</i>	interface name

Command Mode

- /exec/configure/openflow/switch

on-demand color

[no] on-demand color <color>

Syntax Description

no	(Optional) Negate a command or set its defaults
on-demand	Configure on-demand color
color	Color
<i>color</i>	Color

Command Mode

- /exec/configure/sr/te

openflow

[no] openflow

Syntax Description

no	(Optional) Negate a command or set its defaults
openflow	OpenFlow configuration

Command Mode

- /exec/configure

operation-packet-priority normal

{ { no | default } operation-packet-priority | operation-packet-priority { normal | high } }

Syntax Description

no	
default	Set a command to its defaults
operation-packet-priority	Set operation packet properties
high	Priority high
normal	Priority normal

Command Mode

- /exec/configure/ip-sla/jitter

option exporter-stats timeout

{ [no] option exporter-stats timeout <time> | no option exporter-stats timeout }

Syntax Description

option	Version 9 Option Templates and Data
exporter-stats	Exporter Statistics Option
timeout	Option resend time
<i>time</i>	Time in seconds

Command Mode

- /exec/configure/nfm-exporter-v9

option interface-table timeout

{ [no] option interface-table timeout <time> | no option interface-table timeout }

Syntax Description

option	Version 9 Option Templates and Data
interface-table	Interface Table Option
timeout	Option resend time
<i>time</i>	Time in seconds

Command Mode

- /exec/configure/nfm-exporter-v9

orib event-history

```
[no] orib event-history { cli | ipc | uroute | mroute | mroute_only | uhw | mhw | ha | internal } { size { <size_in_text> | <size_in_kbytes> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
orib	Display ORIB information
event-history	ORIB event logs
cli	ORIB cli logs
ipc	ORIB ipc logs
uroute	ORIB unicast route logs
mroute	ORIB multicast route logs
mroute_only	ORIB multicast route logs without mhw
uhw	ORIB unicast platform logs
mhw	ORIB multicast platform logs
ha	ORIB ha logs
internal	ORIB internal logs
size	Configure size
<i>size_in_text</i>	Buffer size
<i>size_in_kbytes</i>	Size in kbytes

Command Mode

- /exec/configure

orib orib_api_init

```
{ orib orib_api_init <client-name> } | { orib orib_api_close } | { orib orib_add_route <client-name> <mac>
[ <nh> | <nh6> ] <if-name> } | { orib orib_delete_route <client-name> <mac> [ <nh> | <nh6> ] <if-name> }
```

Syntax Description

orib	Use ORIB API routines from OTV process
orib_api_init	Call orib_api_init() from the OTV process
orib_api_close	Call orib_api_close() from the OTV process
orib_add_route	Call orib_add_route() from OTV process
orib_delete_route	Call orib_delete_route() from OTV process
<i>client-name</i>	Client name registered to ORIB process
<i>mac</i>	VLAN-ID/MAC Address tuple in vvvv-aaaa.bbbb.cccc format
<i>nh</i>	(Optional) Next-hop IPv4 address
<i>if-name</i>	Next-hop interface (iod)

Command Mode

- /exec

ospfv3 authentication

```
ospfv3 authentication { disable | ipsec spi <spi_id> { md5 <akey> | sha1 <akey> } } | no ospfv3 authentication
{ disable | ipsec spi <spi_id> }
```

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
authentication	Enable Authentication
disable	Disable Authentication
ipsec	IPSec
spi	Security Parameter Index
<i>spi_id</i>	SPI Value
md5	Use the MD5 algorithm
<i>akey</i>	Authentication Key
sha1	Use the SHA1 algorithm
<i>akey</i>	Authentication Key

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 bfd

[no] ospfv3 bfd [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
bfd	Enable BFD on this interface
disable	(Optional) Disable BFD on this interface

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mgmt-config

ospfv3 cost

{ ospfv3 cost <cost> } | { no ospfv3 cost [<cost>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
cost	Cost associated with interface
<i>cost</i>	Cost value

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 dead-interval

{ ospfv3 dead-interval <interval> } | { no ospfv3 dead-interval [<interval>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
dead-interval	Dead interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 event-history

```
[ no ospfv3 event-history { adjacency | event | ha | flooding | lsa | spf | redistribution | hello | spf-trigger } ] |
[ ospfv3 event-history { adjacency | event | ha | flooding | lsa | spf | redistribution | hello | spf-trigger } size {
<size_in_text> | <size_in_Kbytes> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	(Optional) Debugging functions
event-history	(Optional) log debug events into event history buffer
adjacency	(Optional) Adjacency formation logs
event	(Optional) Internal event logs
ha	(Optional) HA and GR logs
flooding	(Optional) LSA flooding logs
lsa	(Optional) LSA generation and database logs
spf	(Optional) SPF calculation logs
redistribution	(Optional) Redistribution logs
hello	(Optional) HELLO related logs
spf-trigger	(Optional) SPF TRIGGER related logs
size	(Optional) Configure the size of the event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf3

ospfv3 event-history cli

[no ospfv3 event-history cli] | [ospfv3 event-history cli size { <size_in_text> | <size_in_Kbytes> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	(Optional) Debugging functions
event-history	(Optional) log debug events into event history buffer
cli	(Optional) Cli logs
size	(Optional) Configure the size of the event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf3

ospfv3 event-history detail

[no] ospfv3 event-history detail

Syntax Description

no	Negate a command or set its defaults
ospfv3	Debugging functions
event-history	log debug events into event history buffer
detail	Detailed event history buffer

Command Mode

- /exec/configure/router-ospf3

ospfv3 event-history detail

[no ospfv3 event-history detail] | [ospfv3 event-history detail size { <size_in_text> | <size_in_Kbytes> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	(Optional) Debugging functions
event-history	(Optional) log debug events into event history buffer
detail	(Optional) Detailed event history buffer
size	(Optional) Configure the size of the event-hist buffer
<i>size_in_text</i>	(Optional) Buffer size
<i>size_in_Kbytes</i>	(Optional) Size of the file in kbytes

Command Mode

- /exec/configure/router-ospf3

ospfv3 hello-interval

```
{ ospfv3 hello-interval <interval> } | { no ospfv3 hello-interval [ <interval> ] }
```

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
hello-interval	Hello interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 instance

{ ospfv3 instance <instance-id> } | { no ospfv3 instance [<instance-id>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
instance	Instance identifier
<i>instance-id</i>	Instance identifier value

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 mtu-ignore

[no] ospfv3 mtu-ignore

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
mtu-ignore	Disable OSPF MTU mismatch detection

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 network broadcast

```
{ ospfv3 network { broadcast | point-to-point } } | { no ospfv3 network [ { broadcast | point-to-point } ] }
```

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
network	Network type
broadcast	Specify OSPF broadcast multi-access network
point-to-point	Specify OSPF point-to-point network

Command Mode

- /exec/configure/if-broadcast /exec/configure/if-p2p /exec/configure/if-mgmt-config

ospfv3 network point-to-point

{ ospfv3 network point-to-point } | { no ospfv3 network [point-to-point] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
network	Network type
point-to-point	Specify OSPF point-to-point network

Command Mode

- /exec/configure/if-loopback

ospfv3 passive-interface

[default | no] ospfv3 passive-interface

Syntax Description

default	(Optional) Undo a command
no	(Optional) Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
passive-interface	Suppress routing updates on the interface

Command Mode

- /exec/configure/if-broadcast /exec/configure/if-p2p /exec/configure/if-mgmt-config

ospfv3 priority

{ ospfv3 priority <prio> } | { no ospfv3 priority [<prio>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
priority	Router priority
<i>prio</i>	Router priority

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

ospfv3 retransmit-interval

{ ospfv3 retransmit-interval <interval> } | { no ospfv3 retransmit-interval [<interval>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
retransmit-interval	Packet retransmission interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel
/exec/configure/if-mgmt-config

ospfv3 shutdown

[no] ospfv3 shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
shutdown	Shutdown ospf on this interface

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mgmt-config

ospfv3 transmit-delay

{ ospfv3 transmit-delay <delay> } | { no ospfv3 transmit-delay [<delay>] }

Syntax Description

no	Negate a command or set its defaults
ospfv3	OSPFv3 configuration commands
transmit-delay	Packet transmission delay
<i>delay</i>	(seconds)

Command Mode

- /exec/configure/if-igp /exec/configure/if-gre-tunnel /exec/configure/if-mpls-tunnel /exec/configure/if-mgmt-config

other-config-flag

[no] other-config-flag <state>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>state</i>	

Command Mode

- /exec/configure/config-ra-guard

overlay-encapsulation

overlay-encapsulation <encap-type> [tunnel-control-frames [<layer2-prot>]] | no overlay-encapsulation

Syntax Description

no	Negate a command or set its defaults
overlay-encapsulation	NVE Overlay Encapsulation
<i>encap-type</i>	Configure encapsulation type
tunnel-control-frames	(Optional) tunnel protocol
<i>layer2-prot</i>	(Optional) configure specific protocol

Command Mode

- /exec/configure/if-nve

overwrite-vlan

[no] overwrite-vlan <ow-vlan-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
overwrite-vlan	Overwrite the system generated vlan
<i>ow-vlan-id</i>	

Command Mode

- /exec/configure/static-host/vni

owner

{ { no | default } owner | owner <text> }

Syntax Description

no	
default	Set a command to its defaults
owner	Owner of Entry
<i>text</i>	Owner String

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http



P Commands

- [packet-size](#), on page 3288
- [param-list param-list](#), on page 3289
- [parity](#), on page 3290
- [parity](#), on page 3291
- [passive-interface default](#), on page 3292
- [passive-interface default](#), on page 3293
- [passive-interface default](#), on page 3294
- [passive-interface default](#), on page 3295
- [password](#), on page 3296
- [password](#), on page 3297
- [password](#), on page 3298
- [password prompt username](#), on page 3299
- [password secure-mode](#), on page 3300
- [password strength-check](#), on page 3301
- [path-option dynamic explicit identifier](#), on page 3302
- [path-selection metric igp](#), on page 3303
- [path-selection metric igp](#), on page 3304
- [path-selection overload allow](#), on page 3305
- [path](#), on page 3306
- [path next-hop out-label-stack](#), on page 3307
- [pause](#), on page 3308
- [pause](#), on page 3309
- [pause buffer-size2 pause-threshold2 resume-threshold2](#), on page 3310
- [pause priority](#), on page 3311
- [payload](#), on page 3312
- [payload test pattern-type pad](#), on page 3313
- [pcc](#), on page 3314
- [pce-address ipv4](#), on page 3315
- [peer-gateway](#), on page 3316
- [peer-ip](#), on page 3317
- [peer-keepalive destination](#), on page 3318
- [peer-switch](#), on page 3320
- [peer-type fabric](#), on page 3321

- [peer-vtep](#), on page 3322
- [peer ip](#), on page 3323
- [peer ip](#), on page 3324
- [peer local service](#), on page 3325
- [peer local service](#), on page 3326
- [peer vpc](#), on page 3327
- [per-ingress-port-mtu-mode](#), on page 3328
- [perf](#), on page 3329
- [periodic-inventory notification](#), on page 3330
- [periodic-inventory notification interval](#), on page 3331
- [periodic to](#), on page 3332
- [periodic to](#), on page 3333
- [permit interface](#), on page 3334
- [permit vlan](#), on page 3335
- [permit vrf](#), on page 3336
- [permit vsan](#), on page 3337
- [personality](#), on page 3338
- [personality backup](#), on page 3339
- [personality restore](#), on page 3340
- [phone-contact](#), on page 3341
- [pim](#), on page 3342
- [ping](#), on page 3343
- [ping6](#), on page 3345
- [platform access-list capture](#), on page 3346
- [platform access-list fp_dnl](#), on page 3347
- [platform access-list update](#), on page 3348
- [platform acl tap-agg](#), on page 3349
- [platform forwarding interface statistics mode mpls](#), on page 3350
- [platform forwarding layer-2 fl exclude supervisor](#), on page 3351
- [platform ip verify](#), on page 3352
- [platform ipv6 verify](#), on page 3354
- [platform qos](#), on page 3355
- [platform qos](#), on page 3356
- [platform qos](#), on page 3357
- [platform qos](#), on page 3358
- [platform qos](#), on page 3359
- [platform qos](#), on page 3360
- [platform qos](#), on page 3361
- [platform qos](#), on page 3362
- [platform qos](#), on page 3364
- [platform qos](#), on page 3365
- [platform qos](#), on page 3366
- [platform qos](#), on page 3367
- [platform qos](#), on page 3368
- [platform qos](#), on page 3369
- [platform qos](#), on page 3370

- platform qos buffer peak monitor counter0 class, on page 3371
- platform qos buffer peak monitor counter1 class, on page 3372
- platform qos classify ns-only, on page 3373
- platform qos eq, on page 3374
- platform qos include ipg, on page 3375
- platform qos ing, on page 3376
- platform qos ing, on page 3377
- platform qos mac ipg, on page 3378
- platform qos nodrop-PG-thresholds-FX PG-size, on page 3379
- platform qos nodrop-PG-thresholds PG-size, on page 3380
- platform qos nodrop-PG-thresholds PG-size Red-threshold Yellow-threshold Green-threshold, on page 3381
- platform qos nodrop-queue-thresholds-FX Queue-green, on page 3382
- platform qos nodrop-queue-thresholds-roc Queue-green, on page 3383
- platform qos ns, on page 3384
- platform qos q-noise percent, on page 3385
- platform rate-limiter, on page 3386
- platform rate-limiter, on page 3388
- platform rate-limiter access-list-log, on page 3390
- platform rate-limiter span-egress, on page 3391
- plb, on page 3392
- plb analytics, on page 3393
- plb device-group, on page 3394
- police, on page 3395
- police, on page 3399
- police, on page 3401
- police, on page 3403
- police police pps, on page 3407
- police police pps, on page 3409
- policy-map, on page 3411
- policy-map type control-plane, on page 3412
- policy-map type network-qos, on page 3413
- policy-map type queuing, on page 3414
- policy, on page 3415
- policy, on page 3416
- policy, on page 3417
- pop, on page 3418
- port-channel bfd destination, on page 3419
- port-channel bfd start, on page 3420
- port-channel bfd track-member-link, on page 3421
- port-channel fast-convergence, on page 3422
- port-channel hash-distribution, on page 3423
- port-channel limit, on page 3424
- port-channel load-balance, on page 3425
- port-channel load-balance1 ethernet, on page 3426
- port-channel load-balance2 resilient, on page 3427

- [port-channel load-balance ethernet](#), on page 3428
- [port-channel load-defer](#), on page 3429
- [port-channel port hash-distribution](#), on page 3430
- [port-channel port load-defer](#), on page 3431
- [port-channel scale-fanout](#), on page 3432
- [port-group](#), on page 3433
- [port-group](#), on page 3434
- [port-license](#), on page 3435
- [port-license](#), on page 3436
- [port-profile](#), on page 3437
- [port-type](#), on page 3438
- [port](#), on page 3439
- [port](#), on page 3440
- [port control](#), on page 3441
- [port control](#), on page 3442
- [port destination](#), on page 3443
- [port type ethernet](#), on page 3444
- [postcard-telemetry exporter](#), on page 3445
- [postcard-telemetry flow-profile](#), on page 3446
- [postcard-telemetry monitor](#), on page 3447
- [postcard-telemetry queue-profile](#), on page 3448
- [postcard-telemetry system monitor](#), on page 3449
- [postcard-telemetry watchlist ip](#), on page 3450
- [power efficient-ethernet auto](#), on page 3451
- [power efficient-ethernet sleep threshold aggressive](#), on page 3452
- [power inline](#), on page 3453
- [power inline default_consumption](#), on page 3454
- [power inline police action](#), on page 3455
- [power inline port priority](#), on page 3456
- [power redundancy-mode combined](#), on page 3457
- [power redundancy-mode combined force](#), on page 3458
- [power redundancy-mode insrc-redundant](#), on page 3459
- [power redundancy-mode ps-redundant](#), on page 3460
- [power reserve](#), on page 3461
- [poweroff](#), on page 3462
- [pps](#), on page 3463
- [pps](#), on page 3464
- [precision milliseconds](#), on page 3465
- [preempt](#), on page 3466
- [preempt](#), on page 3467
- [preempt delay minimum](#), on page 3468
- [preempt delay minimum reload sync preempt delay reload minimum sync preempt delay sync minimum reload preempt delay reload sync minimum preempt delay sync reload minimum preempt delay minimum sync reload preempt delay reload sync preempt delay sync reload preempt delay minimum sync preempt delay sync minimum preempt delay minimum reload preempt delay reload minimum preempt delay minimum preempt delay reload preempt delay sync preempt](#), on page 3469

- preference, on page 3471
- preference max, on page 3472
- preference min, on page 3473
- prefix out, on page 3474
- priority-flow-control auto-restore multiplier, on page 3475
- priority-flow-control fixed-restore multiplier, on page 3476
- priority-flow-control inn-recover interface, on page 3477
- priority-flow-control mode, on page 3478
- priority-flow-control override-interface mode off, on page 3479
- priority-flow-control recover interface, on page 3480
- priority-flow-control tah-recover interface, on page 3481
- priority-flow-control watch-dog-interval on, on page 3482
- priority-flow-control watch-dog-interval on, on page 3483
- priority-flow-control watch-dog forced on, on page 3484
- priority-flow-control watch-dog interval, on page 3485
- priority-flow-control watch-dog shutdown-multiplier, on page 3486
- priority, on page 3487
- priority2, on page 3488
- priority, on page 3489
- priority, on page 3490
- priority, on page 3491
- priority, on page 3492
- priority, on page 3493
- priority, on page 3494
- private-vlan, on page 3495
- private-vlan association, on page 3496
- private-vlan mapping, on page 3497
- private-vlan synchronize, on page 3498
- probe-interval, on page 3499
- probe-interval, on page 3500
- probe, on page 3501
- probe, on page 3502
- probe, on page 3503
- probe, on page 3504
- probe, on page 3505
- probe, on page 3506
- probe, on page 3507
- probe get, on page 3508
- probe get, on page 3509
- probe get, on page 3510
- probe get, on page 3511
- probe host, on page 3512
- probe host, on page 3513
- probe host, on page 3514
- probe host, on page 3515
- probe host, on page 3516

- [probe host, on page 3517](#)
- [probe host, on page 3518](#)
- [probe port, on page 3519](#)
- [probe port, on page 3520](#)
- [probe port, on page 3521](#)
- [probe port, on page 3522](#)
- [probe port, on page 3523](#)
- [probe port, on page 3524](#)
- [probe port, on page 3525](#)
- [profile, on page 3526](#)
- [profile, on page 3527](#)
- [promiscuous-mode off, on page 3528](#)
- [propagate-sgt, on page 3529](#)
- [protection, on page 3530](#)
- [proto, on page 3531](#)
- [protocol-version, on page 3532](#)
- [protocol-version, on page 3533](#)
- [protocol, on page 3534](#)
- [protocol, on page 3535](#)
- [protocol shutdown, on page 3536](#)
- [protocol shutdown, on page 3537](#)
- [ptp, on page 3538](#)
- [ptp announce interval, on page 3539](#)
- [ptp announce timeout, on page 3540](#)
- [ptp clock-identity, on page 3541](#)
- [ptp clock-sync auto, on page 3542](#)
- [ptp clock one-step, on page 3543](#)
- [ptp convergence-time, on page 3544](#)
- [ptp correction-range, on page 3545](#)
- [ptp correction-range logging, on page 3546](#)
- [ptp correction hardware, on page 3547](#)
- [ptp cost, on page 3548](#)
- [ptp delay-request minimum interval, on page 3549](#)
- [ptp device-type boundary, on page 3550](#)
- [ptp domain, on page 3551](#)
- [ptp domain, on page 3552](#)
- [ptp domain clock-accuracy-threshold, on page 3553](#)
- [ptp domain clock-class-threshold, on page 3554](#)
- [ptp domain priority, on page 3555](#)
- [ptp grandmaster-capable, on page 3556](#)
- [ptp mean-path-delay, on page 3557](#)
- [ptp multi-domain, on page 3558](#)
- [ptp multi-domain transition-attributes priority1, on page 3559](#)
- [ptp multi-domain transition-attributes priority2, on page 3560](#)
- [ptp multicast master-only, on page 3561](#)
- [ptp neighbor propagation-delay-threshold, on page 3562](#)

- [ptp offload](#), on page 3563
- [ptp pdelay-req-interval](#), on page 3564
- [ptp priority1](#), on page 3565
- [ptp priority2](#), on page 3566
- [ptp source](#), on page 3567
- [ptp sync interval](#), on page 3568
- [ptp transport ipv4 ucast master](#), on page 3569
- [ptp transport ipv4 ucast slave](#), on page 3570
- [ptp ucast-source](#), on page 3571
- [ptp vlan](#), on page 3572
- [purge module running-config](#), on page 3573
- [push](#), on page 3574
- [pwd](#), on page 3575
- [python](#), on page 3576
- [python instance](#), on page 3577

packet-size

{ packet-size <packetsize> }

Syntax Description

packet-size	Packet
<i>packetsize</i>	Size

Command Mode

- /exec/configure/configngoamconnectcheck

param-list param-list

[no] param-list <plistname> [cross-check] | param-list <plistname>

Syntax Description

no	(Optional) Negate a command or set its defaults
param-list	Configure a parameter list
<i>plistname</i>	Enter the name of the parameter list
cross-check	(Optional) Explicitly search for referencing config profile

Command Mode

- /exec/configure

parity

[no] parity <parity-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
parity	Set terminal parity
<i>parity-value</i>	terminal parity value

Command Mode

- /exec/configure/console

parity

[no] parity { even | none | odd }

Syntax Description

no	(Optional) Negate a command or set its defaults
parity	Set terminal parity
even	Even parity
none	No parity
odd	Odd parity

Command Mode

- /exec/configure/com1

passive-interface default

[no] passive-interface default

Syntax Description

no	(Optional) Negate a command or set its defaults
passive-interface	Suppress routing updates on the interface
default	interfaces passive by default

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

passive-interface default

[no] passive-interface default <level>

Syntax Description

no	(Optional) Negate a command or set its defaults
passive-interface	Suppress IS-IS PDU
default	Undo a command
<i>level</i>	IS-IS level

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

passive-interface default

[no] passive-interface default

Syntax Description

no	(Optional) Negate a command or set its defaults
passive-interface	Suppress routing updates on the interface
default	interfaces passive by default

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

passive-interface default

[no] passive-interface default

Syntax Description

no	(Optional) Negate a command or set its defaults
passive-interface	Suppress routing updates on the interface
default	interfaces passive by default

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

password

password <password-string> | { no | default } password [<password-string>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
password	Configure a password for neighbor
<i>password-string</i>	Neighbor password

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-neighbor-stmp
- /exec/configure/router-bgp/router-bgp-vrf-neighbor
- /exec/configure/router-bgp/router-bgp-template-neighbor
- /exec/configure/router-bgp/router-bgp-prefixneighbor
- /exec/configure/router-bgp/router-bgp-vrf-prefixneighbor

password

```
password [ vrf { <vrf-name> | <vrf-known-name> } ] { required [ req-for <req-pfx-list> ] | { fallback | option
<seq-num> opt-for <opt-pfx-list> } { key-chain <name> } } | no password [ vrf { <vrf-name> |
<vrf-known-name> } ] { required | fallback | option <seq-num> }
```

Syntax Description

no	Negate a command or set its defaults
password	Configure LDP password
vrf	(Optional) VRF Routing/Forwarding instance information
<i>vrf-name</i>	(Optional) VPN Routing/Forwarding instance name
<i>vrf-known-name</i>	(Optional) Known VRF name
required	Password is required for the peer
req-for	(Optional) Prefix list specifying control on LDP peers
<i>req-pfx-list</i>	(Optional) Prefix list for LDP peers
fallback	Specifies a fallback password will follow
option	LDP password option
<i>seq-num</i>	Sequence number of the LDP password option
opt-for	Prefix list specifying control on LDP peers
<i>opt-pfx-list</i>	Prefix list for LDP peers
key-chain	Specifies a key-chain name will follow
<i>name</i>	Key-chain name

Command Mode

- /exec/configure/ldp

password

{ [no] password <passwd> }

Syntax Description

password	password
<i>passwd</i>	password

Command Mode

- /exec/configure/dot1x-cred

password prompt username

[no] password prompt username

Syntax Description

no	(Optional) Negate a command or set its defaults
password	Password for the user
prompt	Enable prompt for password
username	Enable prompt for password on username command

Command Mode

- /exec/configure

password secure-mode

[no] password secure-mode

Syntax Description

no	(Optional) Negate a command or set its defaults
password	Password for the user
secure-mode	Enable secure mode for changing password

Command Mode

- /exec/configure

password strength-check

[no] password strength-check

Syntax Description

no	(Optional) Negate a command or set its defaults
password	Password for the user
strength-check	Strength check of password

Command Mode

- /exec/configure

path-option dynamic explicit identifier

```
[no] path-option [ protect ] <pref> | path-option <pref> dynamic [ attributes <attr-name> | { bandwidth <kbps> | lockdown } + ] | path-option [ protect ] <pref> explicit { identifier <id-num> | name <name> } [ { attributes <attr-name> | verbatim } | { bandwidth <kbps> | lockdown | verbatim } + ]
```

Syntax Description

no	Negate a command or set its defaults
path-option	a primary or fallback path setup option
protect	(Optional) a path protection setup option
<i>pref</i>	preference for this path option
dynamic	setup based on dynamically calculated path
explicit	setup based on preconfigured path
identifier	Specify an IP explicit path by number
<i>id-num</i>	Number of ip explicit path
name	Specify an IP explicit path by name
<i>name</i>	Name of ip explicit path
attributes	(Optional) Specify an LSP attribute list
<i>attr-name</i>	(Optional) Name of LSP attribute list
verbatim	(Optional) send out path as is, with no checking
bandwidth	(Optional) override the bandwidth configured on the tunnel
<i>kbps</i>	(Optional) bandwidth requirement in kbps
lockdown	(Optional) not a candidate for reoptimization
<i>kbps</i>	(Optional) bandwidth requirement in kbps
lockdown	(Optional) not a candidate for reoptimization

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

path-selection metric igp

[no] path-selection metric | path-selection metric { igp | te }

Syntax Description

no	Negate a command or set its defaults
path-selection	Path Selection Configuration
metric	Metric type for path calculation
igp	Use IGP Metric
te	Use TE Metric

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

path-selection metric igp

path-selection metric { igp | te } | no path-selection metric

Syntax Description

no	Negate a command or set its defaults
path-selection	Path Selection Configuration
metric	Metric Type Configuration
igp	Use IGP metric
te	Use TE metric (*Default)

Command Mode

- /exec/configure/te

path-selection overload allow

[no] path-selection overload allow | path-selection overload allow { head [middle] [tail] | middle [tail] | tail }

Syntax Description

no	Negate a command or set its defaults
path-selection	Path Selection Configuration
overload	Overload Node Configuration
allow	Allow overloaded nodes in CSPFs
head	Allow overloaded head node in TE CSPF
middle	(Optional) Allow overloaded middle node in TE CSPF
tail	(Optional) Allow overloaded tail node in TE CSPF

Command Mode

- /exec/configure/te

path

path <dn> [depth { <level> | unbounded }] [query-condition <query>] [filter-condition <filter>] | no path <dn>

Syntax Description

no	Negate a command or set its defaults
path	Create a sensor path
depth	(Optional) Specify a retrieval depth
query-condition	(Optional) Specify a query condition
filter-condition	(Optional) Specify a filter condition
<i>dn</i>	Distinguished Name
unbounded	(Optional) Retrieve entire tree
<i>level</i>	(Optional) Retrieval depth
<i>query</i>	(Optional) query condition
<i>filter</i>	(Optional) Filter Condition

Command Mode

- /exec/configure/telemetry/sensor-group

path next-hop out-label-stack

```
{ no path <path-num> | path <path-num> next-hop <next-hop> out-label-stack { <static-outlabel> + |
implicit-null } }
```

Syntax Description

no	Negate a command or set its defaults
path	Configure an outgoing path for the LSP
<i>path-num</i>	Path identifier
next-hop	Nexthop
<i>next-hop</i>	Destination IPv4 next hop
out-label-stack	Series of output labels
<i>static-outlabel</i>	Label Value
implicit-null	IETF MPLS implicit null label (3)

Command Mode

- /exec/configure/mpls_static/ipv4/lsp/inlabel/forw

pause

```
[no] pause { no-drop | receive1 | { delayed-drop <timeout> } | { [ buffer-size <size-in-bytes> pause-threshold
<xoff-bytes> resume-threshold <xon-bytes> ] pfc-cos <pfc-cos-list> [ receive ] } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
pause	PAUSE charecteristics (CBFC)
no-drop	NO-DROP
delayed-drop	Enable delayed-drop for the CoS
<i>timeout</i>	Timer value for delayed drop
buffer-size	(Optional) Ingress buffer size in bytes
pause-threshold	(Optional) Buffer limit for pausing in bytes
resume-threshold	(Optional) Buffer limit at which to resume in bytes
pfc-cos	CoS values to assert PFC on
receive	(Optional) Enable only PFC receive for the list of pfc-cos values
receive1	Enable only PFC receive
<i>pfc-cos-list</i>	List of class-of-service values

Command Mode

- /exec/configure/policy-map/type/uf/class

pause

[no] pause { buffer-size <size-in-bytes> pause-threshold <xoff-bytes> resume-threshold <xon-bytes> }

Syntax Description

no	(Optional) Negate a command or set its defaults
pause	PAUSE characteristics (CBFC)
buffer-size	Ingress buffer size in bytes
pause-threshold	Buffer limit for pausing in bytes
resume-threshold	Buffer limit at which to resume in bytes

Command Mode

- /exec/configure/policy-map/type/queuing/class

pause buffer-size2 pause-threshold2 resume-threshold2

[no] pause buffer-size2 <size-in-bytes> pause-threshold2 <xoff-bytes> resume-threshold2 <xon-bytes>

Syntax Description

no	(Optional) Negate a command or set its defaults
pause	PAUSE characteristics (CBFC)
buffer-size2	Ingress buffer size in bytes
pause-threshold2	Buffer limit for pausing in bytes
resume-threshold2	Buffer limit at which to resume in bytes

Command Mode

- /exec/configure/policy-map/type/queuing/class

pause priority

[no] pause { priority-group <priority-group-number> }

Syntax Description

no	(Optional) Negate a command or set its defaults
pause	PAUSE characteristics (CBFC)
priority-group	ingress priority-group to which the traffic is mapped and pause limits are applied
<i>priority-group-number</i>	Priority group value

Command Mode

- /exec/configure/policy-map/type/queuing/class

payload

[no] payload

Syntax Description

no	(Optional) Negate a command or set its defaults
payload	Configure ngoam connectivity check payload

Command Mode

- /exec/configure/configngoamconnectcheck

payload test pattern-type pad

{ payload { test pattern-type <test-id> | pad <pad-val> } } | { no payload { test pattern-type | pad } }

Syntax Description

no	Negate a command or set its defaults
payload	Configure ngoam payload
test	Configure ngoam payload test
pattern-type	Configure ngoam payload test pattern
<i>test-id</i>	Configure ngoam payload test pattern id
pad	Configure ngoam payload test pattern pad
<i>pad-val</i>	Configure ngoam payload test pad value

Command Mode

- /exec/configure/configngoamprofile

pcc

[no] pcc

Syntax Description

no	(Optional) Negate a command or set its defaults
pcc	PCC related configuration

Command Mode

- /exec/configure/sr/te

pce-address ipv4

[no] pce-address ipv4 <ip-address> [precedence <precedence>]

Syntax Description

no	(Optional) Negate a command or set its defaults
pce-address	Configure the address of the PCE
ipv4	Configure v4 address of the PCE
precedence	(Optional) Precedence of the PCE
<i>ip-address</i>	PCE address
<i>precedence</i>	(Optional) Path-option preference

Command Mode

- /exec/configure/sr/te/pcc

peer-gateway

peer-gateway [exclude-vlan <vlan-list>] | no peer-gateway

Syntax Description

no	Negate a command or set its defaults
peer-gateway	Enable L3 forwarding for packets destined to peer's gateway mac-address
exclude-vlan	(Optional) Specify VLANs to be excluded from peer-gateway functionality
<i>vlan-list</i>	(Optional) Specify the list of vlans

Command Mode

- /exec/configure/vpc-domain

peer-ip

[no] peer-ip <addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer-ip	Static IP Address Configuration
<i>addr</i>	Remote Peer IP Address

Command Mode

- /exec/configure/if-nve/vni/ingr-rep

peer-keepalive destination

```
peer-keepalive destination <dst-ip> [ [ source <src-ip> | udp-port <udp-port-num> | vrf { <vrf-name> |
<vrf-known-name> } | { interval <interval-ms> timeout <time-out> } | tos-byte <tos-byte-value> | hold-timeout
<hold-time-out> ] + ] [ source <src-ip> | udp-port <udp-port-num> | vrf { <vrf-name> | <vrf-known-name>
} | { interval <interval-ms> timeout <time-out> } | tos { <tos-value> | min-delay | max-throughput |
max-reliability | min-monetary-cost | normal } | hold-timeout <hold-time-out> ] + ] [ source <src-ip> | udp-port
<udp-port-num> | vrf { <vrf-name> | <vrf-known-name> } | { interval <interval-ms> timeout <time-out> } |
precedence { <prec-vlaue> | network | internet | critical | flash-override | flash | immediate | priority | routine
} | hold-timeout <hold-time-out> ] + ]
```

Syntax Description

peer-keepalive	Keepalive/Hello with peer switch
destination	specify destination ip address of peer switch
<i>dst-ip</i>	IPv4 address (A.B.C.D) of destination
source	(Optional) source interface for hello
<i>src-ip</i>	(Optional) IPv4 address (A.B.C.D) of source
udp-port	(Optional) enter UDP port number used for hello
<i>udp-port-num</i>	(Optional) udp port number for hellos
vrf	(Optional) vrf to be used for hello messages
<i>vrf-name</i>	(Optional) vrf to be used for hellos
<i>vrf-known-name</i>	(Optional) Known VRF name
interval	(Optional) enter interval in milleseconds
<i>interval-ms</i>	(Optional) Enter interval in milleseconds
timeout	(Optional) enter timeout in seconds
<i>time-out</i>	(Optional) enter timeout in seconds
precedence	(Optional) Precedence
<i>prec-vlaue</i>	(Optional) Precedence value
network	(Optional) network (7)
internet	(Optional) internet (6)
critical	(Optional) critical (5)
flash-override	(Optional) flash-override (4)
flash	(Optional) flash (3)

immediate	(Optional) immediate (2)
priority	(Optional) priority (1)
routine	(Optional) routine (0)
tos	(Optional) Type of Service
<i>tos-value</i>	(Optional) Enter 4-bit TOS value
min-delay	(Optional) min-delay (8)
max-throughput	(Optional) max-throughput (4)
max-reliability	(Optional) max-reliability (2)
min-monetary-cost	(Optional) min-monetary-cost (1)
normal	(Optional) normal (0)
tos-byte	(Optional) Type of Service Byte
<i>tos-byte-value</i>	(Optional) Enter 8-bit TOS value
hold-timeout	(Optional) hold timeout to ignore stale peer alive messages
<i>hold-time-out</i>	(Optional) Enter hold-timeout in seconds

Command Mode

- /exec/configure/vpc-domain

peer-switch

[no] peer-switch

Syntax Description

no	(Optional) Negate a command or set its defaults
peer-switch	Enable peer switch on vPC pair switches

Command Mode

- /exec/configure/vpc-domain

peer-type fabric

peer-type { fabric-external | fabric-border-leaf } | { no | default } peer-type

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
peer-type	Neighbor facing
fabric-external	Fabric external
fabric-border-leaf	Fabric Border Leaf

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

peer-vtep

[no] peer-vtep <addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer-vtep	Configure tunnel End Point
<i>addr</i>	Remote VTEP IP Address

Command Mode

- /exec/configure/if-nve/vni

peer ip

[no] peer ip <ip-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer	PLB peer
ip	PLB peer ip
<i>ip-addr</i>	NICE node IPv4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-inout

peer ip

[no] peer ip <ip-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer	ITD peer
ip	ITD peer ip
<i>ip-addr</i>	NICE node IP prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-inout

peer local service

[no] peer local service <service-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer	Peer cli for sandwich mode failure notification
local	Peer involved in sandwich mode
service	Peer service involved in sandwich mode
<i>service-name</i>	Peer service name

Command Mode

- /exec/configure/plb

peer local service

[no] peer local service <service-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer	Peer cli for sandwich mode failure notification
local	Peer involved in sandwich mode
service	Peer service involved in sandwich mode
<i>service-name</i>	Peer service name string

Command Mode

- /exec/configure/itd

peer vpc

[no] peer <svc-name> vpc <num>

Syntax Description

no	(Optional) Negate a command or set its defaults
peer	smart channel peer
vpc	vpc
<i>svc-name</i>	peer smart channel name
<i>num</i>	VPC number to assign to smart-channel

Command Mode

- /exec/configure/smartc

per-ingress-port-mtu-mode

[no] per-ingress-port-mtu-mode

Syntax Description

no	(Optional) Negate the command
per-ingress-port-mtu-mode	per-ingress-port mtu mode

Command Mode

- /exec/configure handle auto 424

perf

```
perf [ { record { context-switch | profile } { system | process <i0> } [ <s1> ] } | { stop { all | <s0> } } | { list } | { create-archive <s2> } | { remove { all | <s3> } } ]
```

Syntax Description

perf	Run perf tool to collect or process event data
record	(Optional) Record events to a file for later analysis
stop	(Optional) Stop a perf record.
list	(Optional) List recorded datasets
create-archive	(Optional) Create an archive of dataset for download
remove	(Optional) Remove recorded dataset(s)
all	(Optional) Act on all recorded datasets
context-switch	(Optional) Record context-switch events
profile	(Optional) Record periodic runtime samples
system	(Optional) Record events for all processes on all CPUS
process	(Optional) Record events for a specific process with the given pid
<i>i0</i>	(Optional) pid of process to record events
<i>s0</i>	(Optional) id of perf record session to stop
<i>s1</i>	(Optional) id to use for perf record session
<i>s2</i>	(Optional) id of perf dataset to create an archive
<i>s3</i>	(Optional) id of perf dataset to remove

Command Mode

- /exec

periodic-inventory notification

[no] periodic-inventory notification

Syntax Description

no	(Optional) Negate a command or set its defaults
periodic-inventory	Configure periodic software inventory message dispatch
notification	Enable periodic software inventory message dispatch

Command Mode

- /exec/configure/callhome

periodic-inventory notification interval

periodic-inventory notification { interval <i0> | timeofday <s0> }

Syntax Description

periodic-inventory	Configure periodic software inventory message dispatch
notification	Enable periodic software inventory message dispatch
interval	Configure the time period for periodic inventory
<i>i0</i>	Time period in days (default is 7 days)
timeofday	Configure the timeofday for periodic inventory in HH:MM format
<i>s0</i>	Time period in HH:MM format

Command Mode

- /exec/configure/callhome

periodic to

{ [<seqno>] | no } periodic { { Monday | Tuesday | Wednesday | Thursday | Friday | Saturday | Sunday } + | daily | weekdays | weekend } <stime> to <etime>

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
periodic	Periodic time and date
Monday	Monday
Tuesday	Tuesday
Wednesday	Wednesday
Thursday	Thursday
Friday	Friday
Saturday	Saturday
Sunday	Sunday
daily	Every day of the week
weekdays	Monday thru Friday
weekend	Saturday and Sunday
<i>stime</i>	Starting time
to	Ending day and time
<i>etime</i>	Ending time

Command Mode

- /exec/configure/timerange

periodic to

```
{ [ <seqno> ] | no } periodic { Monday | Tuesday | Wednesday | Thursday | Friday | Saturday | Sunday }
<stime> to { <eday> } <etime>
```

Syntax Description

<i>seqno</i>	(Optional) Sequence number
no	Negate a command or set its defaults
periodic	Periodic time and date
Monday	Monday
Tuesday	Tuesday
Wednesday	Wednesday
Thursday	Thursday
Friday	Friday
Saturday	Saturday
Sunday	Sunday
<i>eday</i>	Day of the week
<i>stime</i>	Starting time
to	Ending day and time
<i>etime</i>	Ending time

Command Mode

- /exec/configure/timerange

permit interface

[no] permit interface <if0>

Syntax Description

no	(Optional) Negate a command or set its defaults
permit	Permit access to interfaces (applicable if interface policy is 'deny')
interface	Enter the range of interfaces accessible the role
<i>if0</i>	Enter the interface range

Command Mode

- /exec/configure/role/interface

permit vlan

[no] permit vlan <vlan-mrange>

Syntax Description

no	(Optional) Negate a command or set its defaults
permit	Permit access to vlans (applicable if vlan policy is 'deny')
vlan	Enter the range of vlans accessible the role
<i>vlan-mrange</i>	Enter the vlan range

Command Mode

- /exec/configure/role/vlan

permit vrf

[no] permit vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
permit	Permit access to vrf (applicable if vrf policy is 'deny')
vrf	Enter the range of vrf accessible the role
<i>vrf-name</i>	Enter the vrf name

Command Mode

- /exec/configure/role/vrf

permit vsan

[no] permit vsan <vsan-mrange>

Syntax Description

no	(Optional) Negate a command or set its defaults
permit	Permit access to vsans (applicable if vsan policy is 'deny')
vsan	Enter the range of vsans accessible the role
<i>vsan-mrange</i>	Enter the vsan range

Command Mode

- /exec/configure/role/vsan

personality

[no] personality

Syntax Description

no	(Optional) Negate a mode
personality	Config Personality

Command Mode

- /exec/configure

personality backup

```
personality backup { <uri_local> | <uri_remote> [ password <password> ] [ vrf <vrf-known-name> ] }
```

Syntax Description

personality	personality
backup	backup personality
password	(Optional) The password for personality backups
vrf	(Optional) The VRF for personality backups
<i>uri_local</i>	Personality backup local destination
<i>uri_remote</i>	Personality backup remote destination
<i>password</i>	(Optional) Password for SCP username
<i>vrf-known-name</i>	(Optional) VRF name

Command Mode

- /exec

personality restore

```
personality restore <uri> [ user-name <user> ] [ password <password> ] [ hostname <hostname> ] [ vrf
<vrf_name> ]
```

Syntax Description

personality	Personality
restore	Restore the personality file
<i>uri</i>	Personality file
user-name	(Optional) The username for downloads
<i>user</i>	(Optional) The username
password	(Optional) The password for downloads
<i>password</i>	(Optional) The password
hostname	(Optional) The hostname for downloads
<i>hostname</i>	(Optional) The hostname
vrf	(Optional) The VRF for downloads
<i>vrf_name</i>	(Optional) The VRF name

Command Mode

- /exec

phone-contact

{ phone-contact <s0> | no phone-contact }

Syntax Description

no	Negate a command or set its defaults
phone-contact	Contact person's phone number
s0	Phone number in international format(such as +1-800-123-4567)

Command Mode

- /exec/configure/callhome

pim

[no] pim

Syntax Description

no	(Optional) Negate a command or set its defaults
pim	Policies for a Remote Receiver

Command Mode

- /exec/configure/nbm-host-policy

ping

```
ping [ { { <alpha> | <numeric> [ loopback interface <interface> ] } | { multicast <group> interface <interface>
[ loopback ] } } [ [ source-interface <src-intf> | vrf { <vrf-name> | <vrf-known-name> } ] [ count { <count>
| unlimited } | packet-size <packetsize> | vrf { <vrf-name> | <vrf-known-name> } | interval <interval> | source
{ <alpha> | <numeric1> } | df-bit | timeout <timeout> } + [ [ count { <count> | unlimited } | packet-size
<packetsize> | source-interface <src-intf> | interval <interval> | df-bit | timeout <timeout> } + ] ]
```

Syntax Description

ping	Test
count	(Optional) Number
unlimited	(Optional) Unlimited
<i>count</i>	(Optional) Number
packet-size	(Optional) Packet
<i>packetsize</i>	(Optional) Size
source-interface	(Optional) Select source interface
<i>src-intf</i>	(Optional) Specify interface
interval	(Optional) Wait
<i>interval</i>	(Optional) Interval
<i>numeric</i>	(Optional) IP address of remote system
<i>numeric1</i>	(Optional) IP
<i>alpha</i>	(Optional) Enter
multicast	(Optional) Multicast
<i>group</i>	(Optional) Multicast
interface	(Optional) Interface
<i>interface</i>	(Optional) Interface
loopback	(Optional) Receive
source	(Optional) Source
df-bit	(Optional) Enable
timeout	(Optional) Specify
<i>timeout</i>	(Optional) Timeout
vrf	(Optional) Display per-VRF information

<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec

ping6

```
ping6 { { <host> | <hostname> } | { multicast <group> } } [ [ { count { <count> | unlimited } } | { packet-size <packetsize> } ] | [ source { <host1> | <hostname> } ] | vrf { <vrf-name> | <vrf-known-name> } | timeout <timeout> | { interval <interval> } ] + [ [ { count { <count> | unlimited } } | { packet-size <packetsize> } ] | { source-interface <src-intf> } | timeout <timeout> | { interval <interval> } ] + ]
```

Syntax Description

ping6	Test
count	(Optional) Number
<i>count</i>	(Optional) Number
unlimited	(Optional) unlimited
packet-size	(Optional) Packet
<i>packetsize</i>	(Optional) Size
source-interface	(Optional) Select source interface
<i>src-intf</i>	(Optional) Specify interface
interval	(Optional) Wait
<i>interval</i>	(Optional) Interval
<i>hostname</i>	Enter
multicast	Multicast
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
source	(Optional) Source
timeout	(Optional) Specify
<i>timeout</i>	(Optional) Timeout

Command Mode

- /exec

platform access-list capture

[no] { platform | hardware } access-list capture

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
access-list	Access Control List
capture	Configure ACL capture

Command Mode

- /exec/configure

platform access-list fp_dnl

[no] { platform | hardware } access-list fp_dnl

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
access-list	Access control list
fp_dnl	Fabric path - do not learn mac from broadcast

Command Mode

- /exec/configure

platform access-list update

[no] { platform | hardware } access-list update { { atomic [strict] } | { default-result permit } }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
access-list	Access Control List
update	Configure atomic/non-atomic update and default-result
atomic	Enable atomic update of access-list in hardware
strict	(Optional) Strict check on TCAM size for using multiple features
default-result	Default access-list result during non-atomic hardware update
permit	Permit all packets during non-atomic update

Command Mode

- /exec/configure

platform acl tap-agg

[no] { platform | hardware } acl tap-agg

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
acl	Configure acl related configuration
tap-agg	Enable tap-aggregation feature on this pltfm

Command Mode

- /exec/configure

platform forwarding interface statistics mode mpls

```
[no] { platform | hardware } forwarding interface statistics mode { mpls | default } [ module <module-num> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
forwarding	Hardware forwarding
interface	Interface
statistics	Statistics
mode	Statistics mode
mpls	Mpls mode
default	Default mode
module	(Optional) Specify a module number
<i>module-num</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform forwarding layer-2 f1 exclude supervisor

[no] { platform | hardware } forwarding layer-2 f1 exclude supervisor

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
forwarding	Forwarding information
layer-2	L2 only mode
f1	N7K-F132XP-15 module
exclude	Exclude supervisor from getting copies of ARP and multicast packets
supervisor	Supervisor module

Command Mode

- /exec/configure

platform ip verify

```
[no] { platform | hardware } ip verify { address { source { broadcast | multicast } | class-e | destination { zero
} | identical | reserved } | checksum | protocol | fragment | length { minimum | consistent | maximum { max-frag
| udp | max-tcp } } | tcp { tiny-frag } | version | syslog }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
ip	IP
verify	Enable IPv4 and some IPv6 packet validation checks in hardware
address	IPv4 Source and destination address validation
source	Check source address
broadcast	Source address is 255.255.255.255
multicast	Source address is 224.x.x.x
destination	Check destination address
zero	Destination address is 0.0.0.0
class-e	Class E IDS check
identical	Same IP SA and DA
reserved	Source address is 127.x.x.x
checksum	Verify IPv4 and IPv6 packet checksum
protocol	Verify IP protocol
fragment	Check IPv4 and IPv6 fragment with non-zero offset and DF bit active
length	Validate IPv4 packet header and payload length
minimum	Minimum IPv4 header length
consistent	Actual frame size is equal to or more than IPv4 length plus ethernet header
maximum	Check max fragment offset and payload length
max-frag	Fragment offset field value
udp	Maximum UDP length has to be less than IPv4 payload length

max-tcp	Maximum TCP length has to be less than IPv4 payload length
tcp	Validate TCP packet header
tiny-frag	Check TCP tiny fragment
version	Must be 4 for an ethertype of IPv4 (0x0800)
syslog	Syslog Messages logging configuration for IDS check drops

Command Mode

- /exec/configure

platform ipv6 verify

```
[no] { platform | hardware } ipv6 verify { length { consistent | maximum { max-frag | udp | max-tcp } } | tcp
{ tiny-frag } | version }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
ipv6	IPv6
verify	Enable IPv6 packet validation checks in hardware
length	Validate IPv6 packet header and payload length
consistent	Actual frame size is equal to or more than IPv6 length plus ethernet header
maximum	Check max fragment offset and payload length
max-frag	Fragment offset field value
udp	Maximum UDP length has to be less than IPv6 payload length
max-tcp	Maximum TCP length has to be less than IPv6 payload length
tcp	Validate TCP packet header
tiny-frag	Check TCP tiny fragment
version	Must be 6 for an ethertype of IPv6 (0x86DD)

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { burst-detect max-records <val> }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
burst-detect	Set OOBST burst monitor configs
max-records	Set OOBST burst monitor max records
<i>val</i>	maximum number of records to monitor

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { afd profile <prof-opts> [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
afd	Approximate Fair Dropping
profile	AFD profiles
<i>prof-opts</i>	
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { min-buffer qos-group <buff-prof-opts> [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
min-buffer	minimum/reserved buffer selection
qos-group	Qos Group
<i>buff-prof-opts</i>	
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { ns-mcq3-alias qos-group <qos-grp-val> [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure QoS related configuration
ns-mcq3-alias	Select qos-group to which to divert qos-group-3 Multicast traffic
qos-group	Qos Group
<i>qos-grp-val</i>	QoS group value
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { ing-pg-hdrm-reserve percent <percent-val> [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
ing-pg-hdrm-reserve	Set Ingress PG Headroom reservation
percent	PG Headroom reservation percent
<i>percent-val</i>	percent of PG Headroom to reserve
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { burst-detect rise-threshold <val> bytes fall-threshold <val> bytes }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
burst-detect	Set OOBST burst monitor configs
rise-threshold	Threshold bytes(queue depth) to start monitoring burst
<i>val</i>	Value in bytes
bytes	Bytes
fall-threshold	Threshold bytes(queue depth) to stop monitoring burst
<i>val</i>	Value in bytes
bytes	Bytes

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { oq-drops type <sel> [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
oq-drops	per output queue drops
type	type of drops - occ/wred/both
<i>sel</i>	
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { oq-stats [ { q0 | q1 | q2 | q3 | q4 | q5 | q6 | q7 | q8 | q9 } ] [ { counter0 | counter1 | counter2 | counter3 | counter4 | counter5 | counter6 | counter7 | counter8 | counter9 } ] type { all | <sel1> [ <sel2> ] } [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
oq-stats	per output queue statistics
q0	(Optional) queueing statistics for qos-group q0 (default)
q1	(Optional) queueing statistics for qos-group q1
q2	(Optional) queueing statistics for qos-group q2
q3	(Optional) queueing statistics for qos-group q3
q4	(Optional) queueing statistics for qos-group q4
q5	(Optional) queueing statistics for qos-group q5
q6	(Optional) queueing statistics for qos-group q6
q7	(Optional) queueing statistics for qos-group q7
q8	(Optional) queueing statistics for qos-group q8 (cpu)
q9	(Optional) queueing statistics for qos-group q9 (span)
counter0	(Optional) use per-port counter 0
counter1	(Optional) use per-port counter 1
counter2	(Optional) use per-port counter 2
counter3	(Optional) use per-port counter 3
counter4	(Optional) use per-port counter 4
counter5	(Optional) use per-port counter 5
counter6	(Optional) use per-port counter 6
counter7	(Optional) use per-port counter 7
counter8	(Optional) use per-port counter 8

counter9	(Optional) use per-port counter 9
type	type of statistics
all	aggregated occ-drops + wred-drops + ecn-stats
<i>sel1</i>	
<i>sel2</i>	(Optional)
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { dynamic-packet-prioritization age-period <period> usec [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
dynamic-packet-prioritization	Dynamic Packet Prioritization
age-period	Aging Period
<i>period</i>	Aging Period
usec	micro seconds
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { dynamic-packet-prioritization max-num-pkts <pkts> [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
dynamic-packet-prioritization	Dynamic Packet Prioritization
max-num-pkts	Maximum number of packets prioritized
<i>pkts</i>	Number of packets
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { etrap age-period <period> usec [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
etrap	Elephant Trap
age-period	Aging Period
<i>period</i>	Aging Period
usec	micro seconds
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { etrap byte-count <count> [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
etrap	Elephant Trap
byte-count	Number of bytes to become elephant flow
<i>count</i>	Number of bytes
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { etrap bandwidth-threshold <bw> bytes [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
etrap	Elephant Trap
bandwidth-threshold	Bandwidth threshold for elephant flow
<i>bw</i>	Number of bytes
bytes	Bytes
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

[no] { platform | hardware } qos { buffer input peak <sel> [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
buffer	buffer config for EX platforms
input	input buffer
peak	peak counter type
<i>sel</i>	
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos

```
[no] { platform | hardware } qos { [ cpu-pg-size <cpu-size> ] [ lcpu-pg-size <lcpu-size> ] [ span-pg-size <span-size> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
cpu-pg-size	(Optional) Configure CPU Pool Group thresholds
<i>cpu-size</i>	(Optional) Pool Group size
lcpu-pg-size	(Optional) Configure LCPU Pool Group thresholds
<i>lcpu-size</i>	(Optional) Pool Group size
span-pg-size	(Optional) Configure SPAN Pool Group thresholds
<i>span-size</i>	(Optional) Pool Group size

Command Mode

- /exec/configure

platform qos buffer peak monitor counter0 class

[no] { platform | hardware } qos buffer peak monitor counter0 class <classes>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
buffer	buffer config
peak	Configure peak control
monitor	monitor peak
counter0	selecting counter 0 for assigning classes
class	class(es) to monitor
<i>classes</i>	qos-group

Command Mode

- /exec/configure

platform qos buffer peak monitor counter1 class

[no] { platform | hardware } qos buffer peak monitor counter1 class { <classes> | none }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
buffer	buffer config
peak	Configure peak control
monitor	monitor peak
counter1	selecting counter 1 for assigning classes
class	class(es) to monitor
<i>classes</i>	qos-group
none	none

Command Mode

- /exec/configure

platform qos classify ns-only

[no] { platform | hardware } qos classify ns-only

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Quality Of Service
classify	Configure qos classification
ns-only	Enable qos classification on NS only in hardware

Command Mode

- /exec/configure

platform qos eoq

```
[no] { platform | hardware } qos eoq { stats-class qos-group { all | <qos-grp-val> } [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure QoS related configuration
eoq	Extended Output Queue(EOQ) related configuration
stats-class	Select class for which to report the statistics
qos-group	Qos Group
<i>qos-grp-val</i>	QoS group value
all	all Qos Groups
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos include ipg

```
[no] { platform | hardware } qos include { ipg [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
include	include specific configuration param
ipg	Select whether to include IPG in Shaping/Policing
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos ing

```
[no] { platform | hardware } qos { ing-pg-no-min [ pgmin <pgmin> ] [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
ing-pg-no-min	Enable PG Min
pgmin	(Optional) Set PG Min Value
<i>pgmin</i>	(Optional) PG Min Value
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos ing

[no] { platform | hardware } qos { ing-pg-share [module <module>] }

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
ing-pg-share	Select Ingress PG Shared Buffer Usage
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos mac ipg

{ platform | hardware } qos mac ipg <val> | no { platform | hardware } qos mac ipg [<val>]

Syntax Description

no	Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
mac	MAC
ipg	Mac IPG Value
<i>val</i>	new Mac IPG value in byte

Command Mode

- /exec/configure

platform qos nodrop-PG-thresholds-FX PG-size

[no] { platform | hardware } qos nodrop-PG-thresholds-FX PG-size <pg-total>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
nodrop-PG-thresholds-FX	Configure No-drop Pool Group thresholds for FX platforms
PG-size	Configure No-drop Pool Group size
<i>pg-total</i>	Pool Group size

Command Mode

- /exec/configure

platform qos nodrop-PG-thresholds PG-size

[no] { platform | hardware } qos nodrop-PG-thresholds PG-size <pg-total>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
nodrop-PG-thresholds	Configure No-drop Pool Group thresholds
PG-size	Configure No-drop Pool Group size
<i>pg-total</i>	Pool Group size

Command Mode

- /exec/configure

platform qos nodrop-PG-thresholds PG-size Red-threshold Yellow-threshold Green-threshold

[no] { platform | hardware } qos nodrop-PG-thresholds PG-size <pg-total> Red-threshold <pg-red> Yellow-threshold <pg-yellow> Green-threshold <pg-green>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
nodrop-PG-thresholds	Configure No-drop Pool Group thresholds for EX platforms
PG-size	Configure No-drop Pool Group size
<i>pg-total</i>	Pool Group size
Red-threshold	Configure No-drop PG red threshold
<i>pg-red</i>	PG red threshold
Yellow-threshold	Configure No-drop PG yellow threshold
<i>pg-yellow</i>	PG yellow threshold
Green-threshold	Configure No-drop PG green threshold
<i>pg-green</i>	PG green threshold

Command Mode

- /exec/configure

platform qos nodrop-queue-thresholds-FX Queue-green

[no] { platform | hardware } qos nodrop-queue-thresholds-FX Queue-green <q-green>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
nodrop-queue-thresholds-FX	Configure No-drop PG's Queue thresholds for FX platforms
Queue-green	Configure No-drop PG Queue green threshold
<i>q-green</i>	PG Queue green threshold

Command Mode

- /exec/configure

platform qos nodrop-queue-thresholds-roc Queue-green

[no] { platform | hardware } qos nodrop-queue-thresholds-roc Queue-green <q-green>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
nodrop-queue-thresholds-roc	Configure No-drop PG's Queue thresholds
Queue-green	Configure No-drop PG Queue green threshold
<i>q-green</i>	PG Queue green threshold

Command Mode

- /exec/configure

platform qos ns

```
[no] { platform | hardware } qos { ns-buffer-profile <buff-prof-opts> [ module <module> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
ns-buffer-profile	NorthStar buffer absorption profiles
<i>buff-prof-opts</i>	
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

platform qos q-noise percent

[no] { platform | hardware } qos q-noise percent <noise>

Syntax Description

no	(Optional) Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
qos	Configure qos related configuration
q-noise	Configure noise thresholds
percent	Noise threshold in percentage of dynamic/static queue_max
<i>noise</i>	Noise percent

Command Mode

- /exec/configure

platform rate-limiter

```
{ platform | hardware } rate-limiter { layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 { <l2-opts> } |
<opts> | fl <f1-opts> } { <pps> [ burst <burst> ] | disable } [ module <module> [ port <start> <end> ] ] | no
{ platform | hardware } rate-limiter { layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 { <l2-opts> } |
<opts> | fl <f1-opts> } [ disable ] [ <pps> ] [ burst <burst> ] [ module <module> [ port <start> <end> ] ]
```

Syntax Description

no	Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
rate-limiter	Configure Rate-Limiter for packets forwarded
layer-3	Layer-3 control and Routed packets
<i>l3-opts</i>	
multicast	Multicast data packets
<i>mcast-opts</i>	
layer-2	Layer-2 control and Bridged packets
<i>l2-opts</i>	
<i>opts</i>	
<i>pps</i>	value in packets per sec
fl	Control packets from F1 modules to supervisor
<i>f1-opts</i>	
disable	Disable the rate-limiter
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
port	(Optional) Port range
<i>start</i>	(Optional) Port start index
<i>end</i>	(Optional) Port end index
burst	(Optional) Modify burst parameter
<i>burst</i>	(Optional) value of burst size

Command Mode

- /exec/configure

platform rate-limiter

```
{ platform | hardware } rate-limiter { layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 { <l2-opts> } |
<opts> | fl <f1-opts> } { <pps> [ burst <burst> ] | disable } [ module <module> [ port <start> <end> ] ] | no
{ platform | hardware } rate-limiter { layer-3 { <l3-opts> | multicast <mcast-opts> } | layer-2 { <l2-opts> } |
<opts> | fl <f1-opts> } [ disable ] [ <pps> ] [ burst <burst> ] [ module <module> [ port <start> <end> ] ]
```

Syntax Description

no	Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
rate-limiter	Configure Rate-Limiter for packets forwarded
layer-3	Layer-3 control and Routed packets
<i>l3-opts</i>	
multicast	Multicast data packets
<i>mcast-opts</i>	
layer-2	Layer-2 control and Bridged packets
<i>l2-opts</i>	
<i>opts</i>	
<i>pps</i>	value in kbits per sec
fl	Control packets from F1 modules to supervisor
<i>f1-opts</i>	
disable	Disable the rate-limiter
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
port	(Optional) Port range
<i>start</i>	(Optional) Port start index
<i>end</i>	(Optional) Port end index
burst	(Optional) Modify burst parameter
<i>burst</i>	(Optional) value of burst size

Command Mode

- /exec/configure

platform rate-limiter access-list-log

```
{ platform | hardware } rate-limiter access-list-log { <pps> [ burst <burst> ] | disable } [ module <module> [ port <start> <end> ] ] | no { platform | hardware } rate-limiter access-list-log [ disable ] [ <pps> ] [ burst <burst> ] [ module <module> [ port <start> <end> ] ]
```

Syntax Description

no	Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
rate-limiter	Configure Rate-Limiter for packets forwarded
access-list-log	Packets copied to supervisor for access-list logging
<i>pps</i>	value in packets per sec
disable	Disable the rate-limiter
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
port	(Optional) Port range
<i>start</i>	(Optional) Port start index
<i>end</i>	(Optional) Port end index
burst	(Optional) Modify burst parameter
<i>burst</i>	(Optional) value of burst size

Command Mode

- /exec/configure

platform rate-limiter span-egress

```
{ platform | hardware } rate-limiter span-egress <rate> [ module <module> ] | no { platform | hardware }
rate-limiter span-egress [ <rate> ] [ module <module> ]
```

Syntax Description

no	Negate a command or set its defaults
platform	Platform configuration commands
hardware	Hardware Internal Information
rate-limiter	Configure Rate-Limiter for packets forwarded
span-egress	SPAN/ERSPAN egress packets
<i>rate</i>	value in kbit per sec
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number

Command Mode

- /exec/configure

plb

[no] plb [<svc-name>] [service <service-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
plb	Configure PLB
<i>svc-name</i>	(Optional) Specify PLB service name [Deprecated]
service	(Optional) Configure PLB service [Preferred]
<i>service-name</i>	(Optional) Specify PLB service name

Command Mode

- /exec/configure

plb analytics

[no] plb analytics <service-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
plb	Configure PLB
analytics	Enable PLB service analytics
<i>service-name</i>	PLB service name

Command Mode

- /exec/configure

plb device-group

[no] plb device-group <group-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
plb	Configure PLB
device-group	Configure PLB device group
<i>group-name</i>	Specify device-group name

Command Mode

- /exec/configure

police

```
[no] police { { [ cir ] { <cir-val> [ bps | kbps | mbps | gbps | pps ] | percent <cir-perc> } [ [ bc ] {
<committed-burst> [ bytes | kbytes | mbytes | ms | us | packets ] } ] [ pir { <pir-val> [ bps2 | kbps2 | mbps2 |
gbps2 | pps2 ] | percent <pir-perc> } [ [ be ] { <extended-burst> [ bytes2 | kbytes2 | mbytes2 | ms2 | us2 |
packets2 ] } ] ] [ conform { transmit | set-prec-transmit { <prec-val> | <prec-enum> } | set-dscp-transmit {
<dscp-val> | <dscp-enum> } | set-cos-transmit <cos-val> | set-discard-class-transmit <disc-class-val> |
set-qos-transmit <qos-grp-val> | set-mpls-exp-imposition-transmit <exp-value-imp> |
set-mpls-exp-topmost-transmit <exp-value-top> } ] [ exceed { transmit1 | drop1 | set <exc-frm-field>
<exc-to-field> table cir-markdown-map | set-prec-transmit1 { <prec-val1> | <prec-enum1> } | set-dscp-transmit1
{ <dscp-val1> | <dscp-enum1> } | set-cos-transmit1 <cos-val1> | set-discard-class-transmit1 <disc-class-val1>
| set-qos-transmit1 <qos-grp-val1> | set-mpls-exp-imposition-transmit1 <exp-value-imp1> |
set-mpls-exp-topmost-transmit1 <exp-value-top1> } ] [ violate { drop2 | set <vio-frm-field> <vio-to-field>
table2 pir-markdown-map | set-prec-transmit2 { <prec-val2> | <prec-enum2> } | set-dscp-transmit2 {
<dscp-val2> | <dscp-enum2> } | set-cos-transmit2 <cos-val2> | set-discard-class-transmit2 <disc-class-val2>
| set-qos-transmit2 <qos-grp-val2> | set-mpls-exp-imposition-transmit2 <exp-value-imp2> |
set-mpls-exp-topmost-transmit2 <exp-value-top2> } ] } | aggregate <policer-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
police	police
cir	(Optional) Specify committed information rate
bc	(Optional) Specify committed burst
percent	Specify rate as percentage of interface data-rate
<i>cir-perc</i>	Percentage
<i>pir-perc</i>	(Optional) Percentage
pir	(Optional) Specify peak information rate
be	(Optional) Specify extended burst (for 1R3C meter)
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
pps	(Optional) Packets per second
bps2	(Optional) Bits per second
kbps2	(Optional) Kilo Bits per second
mbps2	(Optional) Mega Bits per second

gbps2	(Optional) Giga Bits per second
pps2	(Optional) Packets per second
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
us	(Optional) Micro second(s)
ms	(Optional) Milli second(s)
packets	(Optional) Packets
bytes2	(Optional) Bytes
kbytes2	(Optional) Kilo Bytes
mbytes2	(Optional) Mega Bytes
ms2	(Optional) Milli seconds
us2	(Optional) Micro seconds
packets2	(Optional) Packets
conform	(Optional) Specify a conform action
exceed	(Optional) Specify a exceed action
violate	(Optional) Specify a violate action
transmit	(Optional) Transmit packet
transmit1	(Optional) Transmit packet
drop1	(Optional) Drop packet
drop2	(Optional) Drop packet
set-prec-transmit	(Optional) Set precedence and send it
set-prec-transmit1	(Optional) Set precedence and send it
set-prec-transmit2	(Optional) Set precedence and send it
<i>prec-val</i>	(Optional) Precedence value
<i>prec-val1</i>	(Optional) Precedence value
<i>prec-val2</i>	(Optional) Precedence value
<i>prec-enum</i>	(Optional)
<i>prec-enum1</i>	(Optional)

<i>prec-enum2</i>	(Optional)
set-dscp-transmit	(Optional) Set dscp and send it
set-dscp-transmit1	(Optional) Set dscp and send it
set-dscp-transmit2	(Optional) Set dscp and send it
<i>dscp-val</i>	(Optional) DSCP value
<i>dscp-val1</i>	(Optional) DSCP value
<i>dscp-val2</i>	(Optional) DSCP value
<i>dscp-enum</i>	(Optional)
<i>dscp-enum1</i>	(Optional)
<i>dscp-enum2</i>	(Optional)
set-cos-transmit	(Optional) Set cos and send it
set-cos-transmit1	(Optional) Set cos and send it
set-cos-transmit2	(Optional) Set cos and send it
<i>cos-val</i>	(Optional) new cos value
<i>cos-val1</i>	(Optional) new cos value
<i>cos-val2</i>	(Optional) new cos value
set-discard-class-transmit	(Optional) Set discard class and send it
set-discard-class-transmit1	(Optional) Set discard class and send it
set-discard-class-transmit2	(Optional) Set discard class and send it
<i>disc-class-val</i>	(Optional) new discard-class value
<i>disc-class-val1</i>	(Optional) new discard-class value
<i>disc-class-val2</i>	(Optional) new discard-class value
set-qos-transmit	(Optional) Set qos-group and send it
set-qos-transmit1	(Optional) Set qos-group and send it
set-qos-transmit2	(Optional) Set qos-group and send it
<i>qos-grp-val</i>	(Optional) QoS group value
<i>qos-grp-val1</i>	(Optional) QoS group value
<i>qos-grp-val2</i>	(Optional) QoS group value
set-mpls-exp-imposition-transmit	(Optional) set-mpls-exp-imposition-transmit

set-mpls-exp-imposition-transmit1	(Optional) set-mpls-exp-imposition-transmit
set-mpls-exp-imposition-transmit2	(Optional) set-mpls-exp-imposition-transmit
<i>exp-value-imp</i>	(Optional) MPLS imposition value
<i>exp-value-imp1</i>	(Optional) MPLS imposition value
<i>exp-value-imp2</i>	(Optional) MPLS imposition value
set-mpls-exp-topmost-transmit	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit1	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit2	(Optional) Set MPLS topmost label
<i>exp-value-top</i>	(Optional) MPLS topmost value
<i>exp-value-top1</i>	(Optional) MPLS topmost value
<i>exp-value-top2</i>	(Optional) MPLS topmost value
set	(Optional) Set a particular value using table or markdown map
<i>exc-frm-field</i>	(Optional)
<i>exc-to-field</i>	(Optional)
<i>vio-frm-field</i>	(Optional)
<i>vio-to-field</i>	(Optional)
table	(Optional) Set using the table-map
table2	(Optional) Set using the table-map
cir-markdown-map	(Optional) Markdown map table name for exceed action
pir-markdown-map	(Optional) Markdown map table name for violate action
aggregate	Choose aggregate policer for current class
<i>policer-name</i>	Enter aggregate-policer name

Command Mode

- /exec/configure/policy-map/class

police

```
[no] police [ { [ cir ] { <cir-val> [ <opt_kbps_mbps_gbps_pps_cir> ] | percent <cir-perc> } } { [ [ bc ]
<bc-val> [ <opt_kbytes_mbytes_gbytes_bc> ] } ] } { [ { pir { <pir> [ <opt_kbps_mbps_gbps_pps_pir> ] |
percent1 <pir-perc> } } [ [ be ] <be-val> [ <opt_kbytes_mbytes_gbytes_be> ] ] } ] } { [ { conform {
<opt_drop_transmit_conform> | { set-cos-transmit <set-cos-val> } | { set-dscp-transmit { <set-dscp-val> |
<opt_set_dscp> } } | { set-prec-transmit { <set-prec-val> | <opt_set_prec> } } } ] [ { exceed {
<opt_drop_transmit_exceed> | { set dscp1 dscp2 table cir-markdown-map } } ] [ { violate {
<opt_drop_transmit_violate> | { set1 dscp3 dscp4 table1 pir-markdown-map } } } ] ] ] }
```

Syntax Description

no	Negate a command or set its defaults
police	Police
cir	(Optional) Specify committed information rate
<i>opt_kbps_mbps_gbps_pps_cir</i>	(Optional) Units
percent	(Optional) Specify rate as percentage of interface data-rate
pir	(Optional) Specify peak information rate
<i>opt_kbps_mbps_gbps_pps_pir</i>	(Optional) Units
percent1	(Optional) Specify rate as percentage of interface data-rate
be	(Optional) Specify extended burst
<i>opt_kbytes_mbytes_gbytes_be</i>	(Optional) Units
bc	(Optional) Specify committed burst
<i>opt_kbytes_mbytes_gbytes_bc</i>	(Optional) Units
conform	(Optional) Specify a conform action
<i>opt_drop_transmit_conform</i>	(Optional) Set the action
set-cos-transmit	(Optional) Set conform action cos val
<i>set-cos-val</i>	(Optional) 802.1Q Class of Service value
set-dscp-transmit	(Optional) Set conform action dscp val
<i>set-dscp-val</i>	(Optional) DSCP value
<i>opt_set_dscp</i>	(Optional)
set-prec-transmit	(Optional) Set conform action precedence val
<i>set-prec-val</i>	(Optional) IP Precedence value
<i>opt_set_prec</i>	(Optional)

exceed	(Optional) Specify a exceed action
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional) Set exceed action to cir-markdown-map
dscp1	(Optional) Exceed from field
dscp2	(Optional) Exceed to field
table	(Optional) To specify table name
cir-markdown-map	(Optional) Well known markdown map
violate	(Optional) Specify a violate action
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional) Set violate action to pir-markdown-map
dscp3	(Optional) Violate from field
dscp4	(Optional) Violate to field
table1	(Optional) To specify table name
pir-markdown-map	(Optional) Well known markdown map

Command Mode

- /exec/configure/pmap/class

exceed	(Optional) Specify a exceed action
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional) Set exceed action to cir-markdown-map
dscp1	(Optional) Exceed from field
dscp2	(Optional) Exceed to field
table	(Optional) To specify table name
cir-markdown-map	(Optional) Well known markdown map
violate	(Optional) Specify a violate action
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional) Set violate action to pir-markdown-map
dscp3	(Optional) Violate from field
dscp4	(Optional) Violate to field
table1	(Optional) To specify table name
pir-markdown-map	(Optional) Well known markdown map

Command Mode

- /exec/configure/pmap/class

police

```
[no] police { { [ cir ] { <cir-val> [ bps | kbps | mbps | gbps ] | percent <cir-perc> } [ [ bc ] { <committed-burst>
[ bytes | kbytes | mbytes | ms | us ] } ] [ pir { <pir-val> [ bps2 | kbps2 | mbps2 | gbps2 | pps2 ] | percent <pir-perc>
} [ [ be ] { <extended-burst> [ bytes2 | kbytes2 | mbytes2 | ms2 | us2 | packets2 ] } ] ] [ conform { transmit |
set-prec-transmit { <prec-val> | <prec-enum> } | set-dscp-transmit { <dscp-val> | <dscp-enum> } |
set-cos-transmit <cos-val> | set-discard-class-transmit <disc-class-val> | set-qos-transmit <qos-grp-val> |
set-mpls-exp-imposition-transmit <exp-value-imp> | set-mpls-exp-topmost-transmit <exp-value-top> } [
exceed { drop1 | set <exc-frm-field> <exc-to-field> table cir-markdown-map | set-prec-transmit1 { <prec-val1>
| <prec-enum1> } | set-dscp-transmit1 { <dscp-val1> | <dscp-enum1> } | set-cos-transmit1 <cos-val1> |
set-discard-class-transmit1 <disc-class-val1> | set-qos-transmit1 <qos-grp-val1> |
set-mpls-exp-imposition-transmit1 <exp-value-imp1> | set-mpls-exp-topmost-transmit1 <exp-value-top1> }
] [ violate { drop2 | set <vio-frm-field> <vio-to-field> table2 pir-markdown-map | set-prec-transmit2 {
<prec-val2> | <prec-enum2> } | set-dscp-transmit2 { <dscp-val2> | <dscp-enum2> } | set-cos-transmit2
<cos-val2> | set-discard-class-transmit2 <disc-class-val2> | set-qos-transmit2 <qos-grp-val2> |
set-mpls-exp-imposition-transmit2 <exp-value-imp2> | set-mpls-exp-topmost-transmit2 <exp-value-top2> }
] ] } | aggregate <policer-name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
police	police
cir	(Optional) Specify committed information rate
bc	(Optional) Specify committed burst
percent	Specify rate as percentage of interface data-rate
<i>cir-perc</i>	Percentage
<i>pir-perc</i>	(Optional) Percentage
pir	(Optional) Specify peak information rate
be	(Optional) Specify extended burst (for 1R3C meter)
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
bps2	(Optional) Bits per second
kbps2	(Optional) Kilo Bits per second
mbps2	(Optional) Mega Bits per second
gbps2	(Optional) Giga Bits per second

pps2	(Optional) Packets per second
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
us	(Optional) Micro second(s)
ms	(Optional) Milli second(s)
bytes2	(Optional) Bytes
kbytes2	(Optional) Kilo Bytes
mbytes2	(Optional) Mega Bytes
ms2	(Optional) Milli seconds
us2	(Optional) Micro seconds
packets2	(Optional) Packets
conform	(Optional) Specify a conform action
exceed	(Optional) Specify a exceed action
violate	(Optional) Specify a violate action
transmit	(Optional) Transmit packet
drop1	(Optional) Drop packet
drop2	(Optional) Drop packet
set-prec-transmit	(Optional) Set precedence and send it
set-prec-transmit1	(Optional) Set precedence and send it
set-prec-transmit2	(Optional) Set precedence and send it
<i>prec-val</i>	(Optional) Precedence value
<i>prec-val1</i>	(Optional) Precedence value
<i>prec-val2</i>	(Optional) Precedence value
<i>prec-enum</i>	(Optional)
<i>prec-enum1</i>	(Optional)
<i>prec-enum2</i>	(Optional)
set-dscp-transmit	(Optional) Set dscp and send it
set-dscp-transmit1	(Optional) Set dscp and send it

set-dscp-transmit2	(Optional) Set dscp and send it
<i>dscp-val</i>	(Optional) DSCP value
<i>dscp-val1</i>	(Optional) DSCP value
<i>dscp-val2</i>	(Optional) DSCP value
<i>dscp-enum</i>	(Optional)
<i>dscp-enum1</i>	(Optional)
<i>dscp-enum2</i>	(Optional)
set-cos-transmit	(Optional) Set cos and send it
set-cos-transmit1	(Optional) Set cos and send it
set-cos-transmit2	(Optional) Set cos and send it
<i>cos-val</i>	(Optional) new cos value
<i>cos-val1</i>	(Optional) new cos value
<i>cos-val2</i>	(Optional) new cos value
set-discard-class-transmit	(Optional) Set discard class and send it
set-discard-class-transmit1	(Optional) Set discard class and send it
set-discard-class-transmit2	(Optional) Set discard class and send it
<i>disc-class-val</i>	(Optional) new discard-class value
<i>disc-class-val1</i>	(Optional) new discard-class value
<i>disc-class-val2</i>	(Optional) new discard-class value
set-qos-transmit	(Optional) Set qos-group and send it
set-qos-transmit1	(Optional) Set qos-group and send it
set-qos-transmit2	(Optional) Set qos-group and send it
<i>qos-grp-val</i>	(Optional) QoS group value
<i>qos-grp-val1</i>	(Optional) QoS group value
<i>qos-grp-val2</i>	(Optional) QoS group value
set-mpls-exp-imposition-transmit	(Optional) set-mpls-exp-imposition-transmit
set-mpls-exp-imposition-transmit1	(Optional) set-mpls-exp-imposition-transmit
set-mpls-exp-imposition-transmit2	(Optional) set-mpls-exp-imposition-transmit
<i>exp-value-imp</i>	(Optional) MPLS imposition value

<i>exp-value-imp1</i>	(Optional) MPLS imposition value
<i>exp-value-imp2</i>	(Optional) MPLS imposition value
set-mpls-exp-topmost-transmit	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit1	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit2	(Optional) Set MPLS topmost label
<i>exp-value-top</i>	(Optional) MPLS topmost value
<i>exp-value-top1</i>	(Optional) MPLS topmost value
<i>exp-value-top2</i>	(Optional) MPLS topmost value
set	(Optional) Set a particular value using table or markdown map
<i>exc-frm-field</i>	(Optional)
<i>exc-to-field</i>	(Optional)
<i>vio-frm-field</i>	(Optional)
<i>vio-to-field</i>	(Optional)
table	(Optional) Set using the table-map
table2	(Optional) Set using the table-map
cir-markdown-map	(Optional) Markdown map table name for exceed action
pir-markdown-map	(Optional) Markdown map table name for violate action
aggregate	Choose aggregate policer for current class
<i>policer-name</i>	Enter aggregate-policer name

Command Mode

- /exec/configure/policy-map/class

police police pps

```

police { [ cir ] { <cir-val> [ <opt_kbps_mbps_gbps_pps_cir> ] | percent <cir-perc> } } { [ { [ bc ] <bc-val>
[ <opt_kbytes_mbytes_gbytes_bc> ] } ] } { [ { pir { <pir> [ <opt_kbps_mbps_gbps_pps_pir> ] | percent1
<pir-perc> } } [ { [ be ] <be-val> [ <opt_kbytes_mbytes_gbytes_be> ] } ] ] } { [ { conform {
<opt_drop_transmit_conform> | { set-cos-transmit <set-cos-val> } | { set-dscp-transmit { <set-dscp-val> |
<opt_set_dscp> } } | { set-prec-transmit { <set-prec-val> | <opt_set_prec> } } } ] [ { exceed {
<opt_drop_transmit_exceed> | { set dscp1 dscp2 table cir-markdown-map } } ] [ { violate {
<opt_drop_transmit_violate> | { set1 dscp3 dscp4 table1 pir-markdown-map } } } ] ] } | police { pps {
<pps-val> } }

```

Syntax Description

police	Police
cir	(Optional) Specify committed information rate
<i>opt_kbps_mbps_gbps_pps_cir</i>	(Optional) Units
percent	Specify rate as percentage of interface data-rate
pir	(Optional) Specify peak information rate
<i>opt_kbps_mbps_gbps_pps_pir</i>	(Optional) Units
percent1	(Optional) Specify rate as percentage of interface data-rate
be	(Optional) Specify extended burst
<i>opt_kbytes_mbytes_gbytes_be</i>	(Optional) Units
bc	(Optional) Specify committed burst
<i>opt_kbytes_mbytes_gbytes_bc</i>	(Optional) Units
conform	(Optional) Specify a conform action
<i>opt_drop_transmit_conform</i>	(Optional) Set the action
set-cos-transmit	(Optional) Set conform action cos val
<i>set-cos-val</i>	(Optional) 802.1Q Class of Service value
set-dscp-transmit	(Optional) Set conform action dscp val
<i>set-dscp-val</i>	(Optional) DSCP value
<i>opt_set_dscp</i>	(Optional)
set-prec-transmit	(Optional) Set conform action precedence val
<i>set-prec-val</i>	(Optional) IP Precedence value
<i>opt_set_prec</i>	(Optional)

exceed	(Optional) Specify a exceed action
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional) Set exceed action to cir-markdown-map
dscp1	(Optional) Exceed from field
dscp2	(Optional) Exceed to field
table	(Optional) To specify table name
cir-markdown-map	(Optional) Well known markdown map
violate	(Optional) Specify a violate action
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional) Set violate action to pir-markdown-map
dscp3	(Optional) Violate from field
dscp4	(Optional) Violate to field
table1	(Optional) To specify table name
pir-markdown-map	(Optional) Well known markdown map
pps	Specify PPS rate limit

Command Mode

- /exec/configure/pmap/class

police police pps

```

police { [ cir ] { <cir-val> [ <opt_kbps_mbps_gbps_pps_cir> ] | percent <cir-perc> } } { [ { [ bc ] <bc-val>
[ <opt_kbytes_mbytes_gbytes_bc> ] } ] } { [ { pir { <pir> [ <opt_kbps_mbps_gbps_pps_pir> ] | percent1
<pir-perc> } } [ { [ be ] <be-val> [ <opt_kbytes_mbytes_gbytes_be> ] } ] ] } { [ { conform {
<opt_drop_transmit_conform> | { set-cos-transmit <set-cos-val> } | { set-dscp-transmit { <set-dscp-val> |
<opt_set_dscp> } } | { set-prec-transmit { <set-prec-val> | <opt_set_prec> } } } ] [ { exceed {
<opt_drop_transmit_exceed> | { set dscp1 dscp2 table cir-markdown-map } } ] [ { violate {
<opt_drop_transmit_violate> | { set1 dscp3 dscp4 table1 pir-markdown-map } } } ] ] } | police { pps {
<pps-val> } }

```

Syntax Description

police	Police
cir	(Optional) Specify committed information rate
<i>opt_kbps_mbps_gbps_pps_cir</i>	(Optional) Units
percent	Specify rate as percentage of interface data-rate
pir	(Optional) Specify peak information rate
<i>opt_kbps_mbps_gbps_pps_pir</i>	(Optional) Units
percent1	(Optional) Specify rate as percentage of interface data-rate
be	(Optional) Specify extended burst
<i>opt_kbytes_mbytes_gbytes_be</i>	(Optional) Units
bc	(Optional) Specify committed burst
<i>opt_kbytes_mbytes_gbytes_bc</i>	(Optional) Units
conform	(Optional) Specify a conform action
<i>opt_drop_transmit_conform</i>	(Optional) Set the action
set-cos-transmit	(Optional) Set conform action cos val
<i>set-cos-val</i>	(Optional) 802.1Q Class of Service value
set-dscp-transmit	(Optional) Set conform action dscp val
<i>set-dscp-val</i>	(Optional) DSCP value
<i>opt_set_dscp</i>	(Optional)
set-prec-transmit	(Optional) Set conform action precedence val
<i>set-prec-val</i>	(Optional) IP Precedence value
<i>opt_set_prec</i>	(Optional)

exceed	(Optional) Specify a exceed action
<i>opt_drop_transmit_exceed</i>	(Optional) Set the action
set	(Optional) Set exceed action to cir-markdown-map
dscp1	(Optional) Exceed from field
dscp2	(Optional) Exceed to field
table	(Optional) To specify table name
cir-markdown-map	(Optional) Well known markdown map
violate	(Optional) Specify a violate action
<i>opt_drop_transmit_violate</i>	(Optional) Set the action
set1	(Optional) Set violate action to pir-markdown-map
dscp3	(Optional) Violate from field
dscp4	(Optional) Violate to field
table1	(Optional) To specify table name
pir-markdown-map	(Optional) Well known markdown map
pps	Specify PPS rate limit

Command Mode

- /exec/configure/pmap/class

policy-map

[no] policy-map [type qos] [match-first] <pmap-name-qos>

Syntax Description

no	(Optional) Negate a command or set its defaults
policy-map	Configure a policy map
type	(Optional) Specify the type of this policy-map
qos	(Optional) Qos policy
match-first	(Optional) Take the action for the first class that matches
<i>pmap-name-qos</i>	Policy-map name (alphanumeric)

Command Mode

- /exec/configure

policy-map type control-plane

[no] policy-map type control-plane <pmap-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
policy-map	Configure a policy map
type	Specify the type of this policy-map
control-plane	Control-Plane
<i>pmap-name</i>	Policy-map name (alphanumeric)

Command Mode

- /exec/configure

policy-map type network-qos

[no] policy-map type network-qos <pmap-name-nq>

Syntax Description

no	(Optional) Negate a command or set its defaults
policy-map	Configure a policy map
type	Specify the type of this policy-map
network-qos	Network QoS policy
<i>pmap-name-nq</i>	Policy-map name

Command Mode

- /exec/configure

policy-map type queuing

[no] policy-map type queuing [match-first] <pmap-name-que>

Syntax Description

no	(Optional) Negate a command or set its defaults
policy-map	Configure a policy map
type	Specify the type of this policy-map
queuing	Queuing policy
match-first	(Optional) Take the action for the first class that matches
<i>pmap-name-que</i>	Policy-map name (alphanumeric)

Command Mode

- /exec/configure

policy

[no] policy { <cfg-pol-name> | <unknown-pol-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
policy	NBM Flow policy
<i>cfg-pol-name</i>	Policy name
<i>unknown-pol-name</i>	Policy name

Command Mode

- /exec/configure/nbm-flow-policy

policy

policy { { dynamic identity <device-id> } | { static sgt <sgt> [trusted] } } | no policy static | no policy dynamic

Syntax Description

policy	Enable and define policy to be applied
dynamic	apply to authorization server for policy
identity	specify identity of peer for authorization request
<i>device-id</i>	peer's device-id
static	configure static policy
sgt	SGT tag for pkts from this device
<i>sgt</i>	sgt value
trusted	(Optional) specify trust state of the link

Command Mode

- /exec/configure/cts-manual

policy

[no] policy <pol-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
policy	Identifying name for policy with max 128 characters
<i>pol-name</i>	Configure Policy name

Command Mode

- /exec/configure/sr/te

pop

pop [<name>]

Syntax Description

pop	pop mode from stack or restore from name
<i>name</i>	(Optional) name

Command Mode

- /global

port-channel bfd destination

port-channel bfd destination <dest-ip> | no port-channel bfd destination [<dest-ip>]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
bfd	BFD parameters
destination	Configure IP address of BFD peer
<i>dest-ip</i>	BFD peer IPv4 address

Command Mode

- /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

port-channel bfd start

port-channel bfd start <start-timer-value> | no port-channel bfd start [<start-timer-value>]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
bfd	BFD parameters
start	Start timer timeout value
<i>start-timer-value</i>	BFD start timer timeout value in seconds (default off)

Command Mode

- /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

port-channel bfd track-member-link

port-channel bfd track-member-link | no port-channel bfd track-member-link

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
bfd	Enable BFD
track-member-link	Enable per-member-link BFD on the port-channel interface

Command Mode

- /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

port-channel fast-convergence

port-channel fast-convergence | no port-channel fast-convergence

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
fast-convergence	Enable/Disable port-channel fast convergene

Command Mode

- /exec/configure

port-channel hash-distribution

port-channel hash-distribution <type> | no port-channel hash-distribution [<type>]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
hash-distribution	Configure port-channel hash-distribution
<i>type</i>	adaptive/fixed (default adaptive)

Command Mode

- /exec/configure/

port-channel limit

port-channel limit | no port-channel limit

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure the maximum number of supported vPCs
limit	limit to 244 vPCs

Command Mode

- /exec/configure/vpc-domain

port-channel load-balance

```
port-channel load-balance <bndl_hash> <bndl_sel> [ rotate <po-lb-rotate-range> ] [ concatenation ] [ module
<module> | fex all ] [ symmetric ] | no port-channel load-balance [ <bndl_hash> <bndl_sel> [ rotate
<po-lb-rotate-range> ] [ concatenation ] [ module <module> | fex all ] [ symmetric ] ]
```

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
load-balance	Configure port-channel load balance
<i>bndl_hash</i>	bundle hash
<i>bndl_sel</i>	bundle select
rotate	(Optional) offset the hash-input
<i>po-lb-rotate-range</i>	(Optional) offset the hash-input
concatenation	(Optional) enable/disable concatenation
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
fex	(Optional) FEX devices
all	(Optional) Permit all FEX to configure port-channel LB
symmetric	(Optional) symmetric load balancing

Command Mode

- /exec/configure

port-channel load-balance1 ethernet

port-channel load-balance1 ethernet <algorithm> [symmetric] | no port-channel load-balance1 ethernet [<algorithm> [symmetric]]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
load-balance1	Configure port-channel load balance
ethernet	Ethernet port-channel
<i>algorithm</i>	Configure port-channel load balance
symmetric	(Optional) symmetric load balancing

Command Mode

- /exec/configure

port-channel load-balance2 resilient

port-channel load-balance2 resilient | no port-channel load-balance2 resilient

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
load-balance2	Configure port-channel load balance
resilient	Configure port-channel load balance resilient mode

Command Mode

- /exec/configure

port-channel load-balance ethernet

port-channel load-balance ethernet <algorithm> [module <module>] | no port-channel load-balance ethernet [<algorithm> [module <module>]]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
load-balance	Configure port-channel load balance
ethernet	Ethernet port-channel
module	(Optional) Specify a module number
<i>module</i>	(Optional) Specify a module number
<i>algorithm</i>	Configure port-channel load balance

Command Mode

- /exec/configure

port-channel load-defer

port-channel load-defer <load-defer-timeout> | no port-channel load-defer [<load-defer-timeout>]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
load-defer	Load defer time interval
<i>load-defer-timeout</i>	Load defer time interval in seconds (default 120 seconds)

Command Mode

- /exec/configure/

port-channel port hash-distribution

port-channel port hash-distribution <type> | no port-channel port hash-distribution [<type>]

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
port	Configure port-channel port hash-distribution
hash-distribution	Configure port-channel port hash-distribution
<i>type</i>	adaptive/fixed (default adaptive)

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

port-channel port load-defer

port-channel port load-defer | no port-channel port load-defer

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
port	Configure port-channel load-defer for member ports
load-defer	Configure port-channel load-defer

Command Mode

- /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel /exec/configure/if-eth-port-channel-p2p

port-channel scale-fanout

port-channel scale-fanout | no port-channel scale-fanout

Syntax Description

no	Negate a command or set its defaults
port-channel	Configure port channel parameters
scale-fanout	Enable/disable port-channel scale-fanout when ports span more than 16 ASIC units

Command Mode

- /exec/configure

port-group

{ port-group <name> } | { no port-group <name> }

Syntax Description

no	Negate a command or set its defaults
port-group	smart channel port group
<i>name</i>	smart channel port group name

Command Mode

- /exec/configure/smarte

port-group

{ port-group <name> } | { no port-group <name> }

Syntax Description

no	Negate a command or set its defaults
port-group	catena port group
<i>name</i>	catena port group name

Command Mode

- /exec/configure/catena

port-license

[no] port-license [acquire]

Syntax Description

no	(Optional) Negate a command or set its defaults
port-license	Enable port activation license
acquire	(Optional) Acquire port activation license

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext

port-license

[no] port-license [acquire]

Syntax Description

no	(Optional) Negate a command or set its defaults
port-license	Enable port activation license
acquire	(Optional) Acquire port activation license

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext

port-profile

```
[no] port-profile [ type <typeval> ] { <profilename> | <s0> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
port-profile	Configure a port-profile
<i>profilename</i>	Enter the name of the profile
<i>s0</i>	Enter the name of the profile
type	(Optional) configure type of the profile
<i>typeval</i>	(Optional)

Command Mode

- /exec/configure

port-type

[no] port-type <type>

Syntax Description

no	(Optional) Negate a command or set its defaults
port-type	Identifies if port is fabric-facing or not
<i>type</i>	Facing port-type

Command Mode

- /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-all

port

{ port <sport> <dport> }

Syntax Description

port	L4 port info
<i>sport</i>	Source port
<i>dport</i>	Destination port

Command Mode

- /exec/configure/configngoamccpayload

port

{ no port | port <value> }

Syntax Description

no	
port	Port on which to listen
<i>value</i>	Max port value

Command Mode

- /exec/configure/config-twamp-srvr

port control

[no] port control <port-control-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
port	ITD port
control	control
<i>port-control-name</i>	Port control name

Command Mode

- /exec/configure/itd-inout

port control

[no] port control <port-control-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
port	Configure PLB port control
control	control
<i>port-control-name</i>	Port control name

Command Mode

- /exec/configure/plb-inout

port destination

{ port { destination | source } <port> } | { no port { destination | source } }

Syntax Description

no	Negate a command or set its defaults
port	specify flow port address
source	specify flow source port address
destination	specify flow destination port address
<i>port</i>	port number

Command Mode

- /exec/configure/configngoamprofileflow

port type ethernet

[no] port <port-range> type { ethernet | fc }

Syntax Description

no	(Optional) Negate a command or set its defaults
port	Configure a port
<i>port-range</i>	Enter a port range
type	Configure a port type
ethernet	Ethernet Port
fc	FC Port

Command Mode

- /exec/configure/slot

postcard-telemetry exporter

[no] postcard-telemetry exporter <exportername>

Syntax Description

postcard-telemetry	Enable/Disable postcard telemetry configuration
exporter	Define a events Exporter
<i>exportername</i>	Name of event Exporter

Command Mode

- /exec/configure/config-postcard

postcard-telemetry flow-profile

[no] postcard-telemetry flow-profile

Syntax Description

postcard-telemetry	Enable/Disable postcard telemetry configuration
flow-profile	Define a POSTCARD flow-profile

Command Mode

- /exec/configure/config-postcard

postcard-telemetry monitor

[no] postcard-telemetry monitor <monitorname>

Syntax Description

postcard-telemetry	Enable/Disable postcard telemetry configuration
monitor	Define a POSTCARD Monitor
<i>monitorname</i>	Name of POSTCARD Monitor

Command Mode

- /exec/configure/config-postcard

postcard-telemetry queue-profile

[no] postcard-telemetry queue-profile <queue_profilename>

Syntax Description

postcard-telemetry	Enable/Disable postcard telemetry configuration
queue-profile	Define a POSTCARD queue_profile
<i>queue_profilename</i>	Name of POSTCARD queue_profile

Command Mode

- /exec/configure/config-postcard

postcard-telemetry system monitor

[no] postcard-telemetry system monitor <monitorname>

Syntax Description

system	global config
postcard-telemetry	postcard global settings
monitor	postcard Monitor to be applied
<i>monitorname</i>	postcard Monitor to be applied

Command Mode

- /exec/configure/config-postcard

postcard-telemetry watchlist ip

[no] postcard-telemetry watchlist ip <watchlistname>

Syntax Description

postcard-telemetry	Enable/Disable postcard telemetry configuration
watchlist	Define a POSTCARD watchlist
ip	Configure POSTCARD IP watchlist
<i>watchlistname</i>	Name of POSTCARD watchlist

Command Mode

- /exec/configure/config-postcard

power efficient-ethernet auto

[no] power efficient-ethernet auto

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure EEE for the port
efficient-ethernet	Configure Energy Efficient Ethernet (EEE)
auto	Auto negotiate EEE

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

power efficient-ethernet sleep threshold aggressive

[no] power efficient-ethernet sleep threshold aggressive

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure EEE for the port
efficient-ethernet	Configure Energy Efficient Ethernet (EEE)
sleep	EEE LPI sleep configuration
threshold	EEE LPI sleep threshold
aggressive	Enable/ Disable EEE LPI aggressive sleep mode

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

power inline

```
{ power inline { <port-mode-never> | <port-mode> [ max <wattage> ] } } | { no power inline { <port-mode-never> | <port-mode> } }
```

Syntax Description

no	Negate a command or set its defaults
power	Power over Ethernet
<i>port-mode-never</i>	configure POE port mode
<i>port-mode</i>	configure POE port mode
max	(Optional) Configure the max power per interface
<i>wattage</i>	(Optional) milli-watts

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

power inline default_consumption

{ power inline default_consumption <wattage> } | { no power inline default_consumption }

Syntax Description

no	Negate a command or set its defaults
power	Power over Ethernet
default_consumption	POE port default consumption
<i>wattage</i>	milli-watts

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

power inline police action

{ power inline police action <police-action> } | { no power inline police action }

Syntax Description

no	Negate a command or set its defaults
power	Power over Ethernet
police	Configure POE port police parameters
action	Configure action in port when power allocation exceeds
<i>police-action</i>	configure POE port action

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

power inline port priority

{ power inline port priority <port-priority> } | { no power inline port priority <port-priority> }

Syntax Description

no	Negate a command or set its defaults
power	Power over Ethernet
port	Configure POE port parameters
priority	Configure the priority for the port
<i>port-priority</i>	configure POE port priority

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

power redundancy-mode combined

[no] power redundancy-mode combined

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure power supply
redundancy-mode	Configure power supply redundancy mode
combined	Configure power supply redundancy mode as combined

Command Mode

- /exec/configure

power redundancy-mode combined force

[no] power redundancy-mode combined force

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure power supply
redundancy-mode	Configure power supply redundancy mode
combined	Configure power supply redundancy mode as combined
force	Force combined mode without prompting

Command Mode

- /exec/configure

power redundancy-mode insrc-redundant

[no] power redundancy-mode insrc-redundant

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure power supply
redundancy-mode	Configure power supply redundancy mode
insrc-redundant	Configure power supply redundancy mode as grid/AC input source redundant

Command Mode

- /exec/configure

power redundancy-mode ps-redundant

[no] power redundancy-mode ps-redundant

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure power supply
redundancy-mode	Configure power supply redundancy mode
ps-redundant	Configure power supply redundancy mode as PS redundant

Command Mode

- /exec/configure

power reserve

[no] power reserve <percentage>

Syntax Description

no	(Optional) Negate a command or set its defaults
power	Configure power supply
reserve	Override default power reservation
<i>percentage</i>	please enter a percentage

Command Mode

- /exec/configure

poweroff

[no] poweroff { module <lem-aware-module> | <s0> <santa-cruz-range> }

Syntax Description

no	(Optional) Negate a command or set its defaults
poweroff	Power off a module in the switch
module	enter a module number
<i>lem-aware-module</i>	please enter the module number
<i>s0</i>	Power off a specific xbar
<i>santa-cruz-range</i>	please enter the xbar number

Command Mode

- /exec/configure

pps

pps <pps> <burst> | no pps [<pps>] [<burst>]

Syntax Description

no	Negate a command or set its defaults
pps	OSPF packets per second
<i>pps</i>	Packets per second value
<i>burst</i>	Burst value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

pps

pps <pps> <burst> | no pps [<pps>] [<burst>]

Syntax Description

no	Negate a command or set its defaults
pps	OSPFv3 packets per second
<i>pps</i>	Packets per second value
<i>burst</i>	Burst value

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

precision milliseconds

{ { no | default } precision | precision { milliseconds | microseconds } }

Syntax Description

no	
<i>precision</i>	milliseconds
default	Set a command to its defaults
precision	Set precision of measurement
microseconds	Precision microseconds
milliseconds	Precision milliseconds

Command Mode

- /exec/configure/ip-sla/jitter

preempt

[no] preempt | preempt

Syntax Description

no	Negate a command or set its defaults
preempt	Enable preemption of lower priority Master

Command Mode

- /exec/configure/if-eth-any/vrrpv3

preempt

[no] preempt

Syntax Description

no	(Optional) Negate a command or set its defaults
preempt	Enable preemption of lower priority master

Command Mode

- /exec/configure/if-eth-any/vrrp

preempt delay minimum

[no] preempt delay | preempt delay minimum <secs>

Syntax Description

no	Negate a command or set its defaults
preempt	Enable preemption of lower priority Master
delay	Wait before preempting
minimum	Delay at least this long
<i>secs</i>	Seconds to delay

Command Mode

- /exec/configure/if-eth-any/vrrpv3

preempt delay minimum reload sync preempt delay reload minimum sync preempt delay sync minimum reload preempt delay reload sync minimum preempt delay sync reload minimum preempt delay minimum sync reload preempt delay reload sync preempt delay sync reload preempt delay minimum sync preempt delay sync minimum preempt delay minimum reload preempt delay reload minimum preempt delay minimum preempt delay reload preempt delay sync preempt

preempt delay minimum reload sync preempt delay reload minimum sync preempt delay sync minimum reload preempt delay reload sync minimum preempt delay sync reload preempt delay reload sync preempt delay sync reload preempt delay minimum sync preempt delay sync minimum preempt delay minimum reload preempt delay reload minimum preempt delay minimum preempt delay reload preempt delay sync preempt

preempt delay minimum <min-delay> reload <rel-delay> sync <sync-delay> | preempt delay reload <rel-delay> minimum <min-delay> sync <sync-delay> | preempt delay sync <sync-delay> minimum <min-delay> reload <rel-delay> | preempt delay reload <rel-delay> sync <sync-delay> minimum <min-delay> | preempt delay sync <sync-delay> reload <rel-delay> minimum <min-delay> | preempt delay minimum <min-delay> sync <sync-delay> reload <rel-delay> | preempt delay reload <rel-delay> sync <sync-delay> | preempt delay sync <sync-delay> reload <rel-delay> | preempt delay minimum <min-delay> sync <sync-delay> | preempt delay sync <sync-delay> minimum <min-delay> reload <rel-delay> | preempt delay minimum <min-delay> reload <rel-delay> | preempt delay reload <rel-delay> minimum <min-delay> | preempt delay minimum <min-delay> | preempt delay reload <rel-delay> | preempt delay sync <sync-delay> | preempt | no preempt | no preempt delay [{ minimum [<min-delay>] [[reload [<rel-delay>]] [sync [<sync-delay>]]] [sync [<sync-delay>]] [reload [<rel-delay>]]] | reload [<rel-delay>] [[minimum [<min-delay>]] [sync [<sync-delay>]]] [sync [<sync-delay>]] [minimum [<min-delay>]]] | sync [<sync-delay>] [[reload [<rel-delay>]] [minimum [<min-delay>]]] [minimum [<min-delay>]] [[minimum [<min-delay>]] [reload [<rel-delay>]]] }]

Syntax Description

no	Negate a command or set its defaults
preempt	Overthrow lower priority Active routers
delay	Wait before preempting
minimum	Delay at least this long
<i>min-delay</i>	Number of seconds for minimum delay
reload	Delay after reload
<i>rel-delay</i>	Number of seconds for reload delay
sync	Wait for IP redundancy clients
<i>sync-delay</i>	Number of seconds for sync delay

Command Mode

preempt delay minimum reload sync preempt delay reload minimum sync preempt delay sync minimum reload preempt delay reload sync minimum preempt
delay sync reload minimum preempt delay minimum sync reload preempt delay reload sync preempt delay sync reload preempt delay minimum sync preempt
delay sync minimum preempt delay minimum reload preempt delay reload minimum preempt delay minimum preempt delay reload preempt delay sync preempt

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

preference

[no] preference <pref>

Syntax Description

no	(Optional) Negate a command or set its defaults
preference	Policy path-option preference entry
<i>pref</i>	Path-option preference

Command Mode

- /exec/configure/sr/te/pol

preference max

[no] preference max <pref-val>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>pref-val</i>	maximum value

Command Mode

- /exec/configure/config-dhcp-guard

preference min

[no] preference min <pref-val>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>pref-val</i>	maximum value

Command Mode

- /exec/configure/config-dhcp-guard

prefix out

[no | default] { prefix-list <prfxlist-name> } { out | in }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
prefix-list	Apply prefix-list
<i>prfxlist-name</i>	Name of prefix-list
out	Apply policy to outgoing routes
in	Apply policy to incoming routes

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

priority-flow-control auto-restore multiplier

[no] priority-flow-control auto-restore multiplier { <val> }

Syntax Description

no	(Optional) Negate the command
priority-flow-control	pfm related commands
auto-restore	auto restore
multiplier	Auto restore multiplier
<i>val</i>	Auto multiplier value

Command Mode

- /exec/configure

priority-flow-control fixed-restore multiplier

[no] priority-flow-control fixed-restore multiplier { <val> }

Syntax Description

no	(Optional) Negate the command
priority-flow-control	pfc related commands
fixed-restore	fixed restore
multiplier	Fixed restore multiplier
<i>val</i>	Fixed multiplier value

Command Mode

- /exec/configure

priority-flow-control inn-recover interface

priority-flow-control inn-recover interface <if_list>

Syntax Description

priority-flow-control	Change PFC settings
inn-recover	Recover PFC queue from stuck state
interface	Interface
<i>if_list</i>	List of interfaces

Command Mode

- /exec

priority-flow-control mode

[no] priority-flow-control mode { auto | on | off } [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
priority-flow-control	Enable/Disable PFC
mode	PFC Mode
auto	Set Auto Mode
on	Force PFC to On
off	Force PFC to Off
force	(Optional) Force apply PFC config

Command Mode

- /exec/configure/if-switching /exec/configure/if-routing /exec/configure/if-port-channel /exec/configure/if-port-channel-sub

priority-flow-control override-interface mode off

[no] priority-flow-control override-interface mode off

Syntax Description

no	(Optional) Negate a command or set its defaults
priority-flow-control	Global priority-flow-control settings
override-interface	Overrides interface priority-flow-control mode
mode	Priority-flow-control mode
off	Off

Command Mode

- /exec/configure

priority-flow-control recover interface

```
priority-flow-control recover interface <if_list> [ qos-group <qgrp-num> ] [ module <module_idx> ] [ instance <inst> ]
```

Syntax Description

priority-flow-control	Change PFC settings
recover	Recover PFC queue from stuck state
interface	Interface
<i>if_list</i>	List of interfaces
qos-group	(Optional) No-drop class to be recovered
<i>qgrp-num</i>	(Optional) qos-group number of the no-drop class
module	(Optional) Slot/module
<i>module_idx</i>	(Optional) Slot/module number
instance	(Optional) ASIC Instance Number
<i>inst</i>	(Optional) ASIC Instance Number in Decimal

Command Mode

- /exec

priority-flow-control tah-recover interface

priority-flow-control tah-recover interface <if_list> [qos-group <qos>] [module <module>]

Syntax Description

priority-flow-control	Change PFC settings
tah-recover	Recover PFC queue from stuck state
interface	Interface
<i>if_list</i>	List of interfaces
qos-group	(Optional) No-drop class to be recovered
<i>qos</i>	(Optional) qos-group number of the no-drop class
module	(Optional) Slot/module
<i>module</i>	(Optional) Slot/module number

Command Mode

- /exec

priority-flow-control watch-dog-interval on

```
[no] priority-flow-control watch-dog-interval { on [ disable-action ] [ interface-multiplier <multiplier-val> ]
| off }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
priority-flow-control	Enable/Disable PFC
watch-dog-interval	Watch dog interval
on	PFC watch-dog interval to On
disable-action	(Optional) Only generate syslog for stuck queue, no action
interface-multiplier	(Optional) Shutdown multiplier value
<i>multiplier-val</i>	(Optional) Shutdown multiplier value
off	PFC watch-dog interval to Off

Command Mode

- /exec/configure/if-switching /exec/configure/if-routing /exec/configure/if-port-channel /exec/configure/if-port-channel-sub

priority-flow-control watch-dog-interval on

[no] priority-flow-control watch-dog-interval { on | off }

Syntax Description

no	(Optional) Negate the command
priority-flow-control	Enable/Disable PFC
watch-dog-interval	Watch dog interval
on	Enable PFC watch-dog interval globally
off	Disable PFC watch-dog interval globally

Command Mode

- /exec/configure

priority-flow-control watch-dog forced on

[no] priority-flow-control watch-dog forced { on | off }

Syntax Description

no	(Optional) Negate the command
priority-flow-control	pfc related commands
watch-dog	watch dog interval
forced	Force enable watch-dog behaviour globally
on	Enable PFC watch-dog globally
off	Disable PFC watch-dog globally

Command Mode

- /exec/configure

priority-flow-control watch-dog interval

[no] priority-flow-control watch-dog interval <interval-val>

Syntax Description

no	(Optional) Negate the command
priority-flow-control	pfm related commands
watch-dog	watch dog interval
interval	Poll interval
<i>interval-val</i>	Watch dog interval value in ms

Command Mode

- /exec/configure

priority-flow-control watch-dog shutdown-multiplier

[no] priority-flow-control watch-dog shutdown-multiplier { <val> }

Syntax Description

no	(Optional) Negate the command
priority-flow-control	pfc related commands
watch-dog	watch dog interval
shutdown-multiplier	Shutdown multiplier
<i>val</i>	Shutdown multiplier

Command Mode

- /exec/configure

priority

```
{ priority <priority_value> [ forwarding-threshold lower <lower-value> upper <upper-value> ] | no priority
[ forwarding-threshold ] }
```

Syntax Description

no	Negate a command or set its defaults
priority	Configure the vr priority
<i>priority_value</i>	Configure the vr priority
forwarding-threshold	(Optional) Set forwarding threshold
lower	(Optional) Set lower threshold value
<i>lower-value</i>	(Optional) Lower threshold value
upper	(Optional) Set upper threshold value
<i>upper-value</i>	(Optional) Upper threshold value

Command Mode

- /exec/configure/if-eth-any/vrrp

priority2

[no] priority2 [level2 <value>]

Syntax Description

no	(Optional) Negate a command or set its defaults
priority2	Configure traffic class priority
level2	(Optional) Specify level of priority
<i>value</i>	(Optional) Strict-priority level (1=hi 2=med 3=lo)

Command Mode

- /exec/configure/policy-map/type/queuing/class

priority

priority <priority> [forwarding-threshold lower <lower-value> upper <upper-value>] | no priority [forwarding-threshold]

Syntax Description

no	Negate a command or set its defaults
priority	Priority level
<i>priority</i>	Priority value
forwarding-threshold	(Optional) Set forwarding threshold
lower	(Optional) Set lower threshold value
<i>lower-value</i>	(Optional) Lower threshold value
upper	(Optional) Set upper threshold value
<i>upper-value</i>	(Optional) Upper threshold value

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

priority

priority <value> | no priority

Syntax Description

no	Negate a command or set its defaults
priority	Configure Bundle priority
<i>value</i>	Priority value

Command Mode

- /exec/configure/anycast

priority

[no] priority [level <value>]

Syntax Description

no	(Optional) Negate a command or set its defaults
priority	Configure traffic class priority
level	(Optional) Specify level of priority
<i>value</i>	(Optional) Value of level, lower the number higher the priority

Command Mode

- /exec/configure/policy-map/type/queuing/class

priority

[no] priority | priority <val>

Syntax Description

no	Negate a command or set its defaults
priority	Priority of this VRRP group
<i>val</i>	Priority level

Command Mode

- /exec/configure/if-eth-any/vrrpv3

priority

[no] priority | priority <setup_prio> [<hold_prio>]

Syntax Description

no	Negate a command or set its defaults
priority	Specify LSP priority
<i>setup_prio</i>	setup priority
<i>hold_prio</i>	(Optional) hold priority

Command Mode

- /exec/configure/te/lsp-attr

priority

[no] priority | priority <setup_pri> [<hold_pri>]

Syntax Description

no	Negate a command or set its defaults
priority	tunnel priority
<i>setup_pri</i>	setup priority
<i>hold_pri</i>	(Optional) hold priority

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

private-vlan

[no] private-vlan <pvlan-type>

Syntax Description

no	(Optional) Negate a command or set its defaults
private-vlan	Configure a private VLAN
<i>pvlan-type</i>	PVLAN Type

Command Mode

- /exec/configure/vlan

private-vlan association

```
{ private-vlan association [ { add | remove } ] <secondary_vlans> } | { no private-vlan association [ <secondary_vlans> ] }
```

Syntax Description

private-vlan	Configure a private VLAN
association	Add association between private VLANs
add	(Optional) Add a VLAN to private VLAN list
remove	(Optional) Remove a VLAN from private VLAN list
no	Negate a command or set its defaults
<i>secondary_vlans</i>	VLAN IDs of the private VLANs to be configured

Command Mode

- /exec/configure/vlan

private-vlan mapping

```
{ private-vlan mapping [ { add | remove } ] <secondary_vlans> } | { no private-vlan mapping [ <secondary_vlans> ] }
```

Syntax Description

private-vlan	Configure a private VLAN
mapping	Set the private VLAN interface mapping
add	(Optional) Add a VLAN to private VLAN list
remove	(Optional) Remove a VLAN from private VLAN list
no	Negate a command or set its defaults
<i>secondary_vlans</i>	Secondary VLAN IDs of the private VLAN interface mapping

Command Mode

- /exec/configure/if-vlan

private-vlan synchronize

private-vlan synchronize

Syntax Description

private-vlan	Set private-vlan synchronization
synchronize	Synchronize vlans

Command Mode

- /exec/configure/spanning-tree/mst/configuration

probe-interval

probe-interval <probeinterval-val> | no probe-interval

Syntax Description

no	Negate a command or set its defaults
probe-interval	OpenFlow controller probe interval timer (default is 180 seconds)
<i>probeinterval-val</i>	probe interval timer value in secs

Command Mode

- /exec/configure/openflow/switch/sub-switch

probe-interval

probe-interval <probeinterval-val> | no probe-interval

Syntax Description

no	Negate a command or set its defaults
probe-interval	OpenFlow controller probe interval timer (default is 180 seconds)
<i>probeinterval-val</i>	probe interval timer value in secs

Command Mode

- /exec/configure/openflow/switch

probe

```
{ probe <probe-id-icmp> [ frequency <freq-num> | timeout <timeout> | retry-down-count <count> |
retry-up-count <up-count> | ip <ip-addr> ] + } | { no probe }
```

Syntax Description

no	Negate a command or set its defaults
probe	Catena probe
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/catena-device-grp

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node-standby

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/itd-device-group

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count
ip	(Optional) Configure ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count
ip	(Optional) Configure ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node-standby

probe

[no] probe <probe-id-icmp> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id-icmp</i>	Service mode
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/plb-device-group

probe get

[no] probe <probe-id-http> get [<url-name> | cache | frequency <freq-num> | timeout <timeout> |
 retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-http</i>	Service mode
get	Host name/Target address
<i>url-name</i>	(Optional) Specify only the user input text/filename. http://<node-ip>/<user input>
cache	(Optional) Use cache
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node

probe get

```
{ probe <probe-id-http> get [ <url-name> | cache | frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr> ] + } | { no probe }
```

Syntax Description

no	Negate a command or set its defaults
probe	Catena probe
<i>probe-id-http</i>	Service mode
get	Host name/Target address
<i>url-name</i>	(Optional) Specify only the user input text/filename. http://<node-ip>/<user input>
cache	(Optional) Use cache
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/catena-device-grp

probe get

[no] probe <probe-id-http> get [<url-name> | cache | frequency <freq-num> | timeout <timeout> |
 retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-http</i>	Service mode
get	Host name/Target address
<i>url-name</i>	(Optional) Specify only the user input text/filename. http://<node-ip>/<user input>
cache	(Optional) Use cache
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node-standby

probe get

[no] probe <probe-id-http> get [<url-name> | cache | frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-http</i>	Service mode
get	Host name/Target address
<i>url-name</i>	(Optional) Specify only the user input text/filename. http://<node-ip>/<user input>
cache	(Optional) Use cache
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/itd-device-group

probe host

```
{ probe <probe-id-dns> host <host-name> [ frequency <freq-num> | timeout <timeout> | retry-down-count
<count> | retry-up-count <up-count> | ip <ip-addr> ] + } | { no probe }
```

Syntax Description

no	Negate a command or set its defaults
probe	Catena probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/catena-device-grp

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency
<i>freq-num</i>	(Optional) Frequency
timeout	(Optional) Timeout
<i>timeout</i>	(Optional) Timeout
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node-standby

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/itd-device-group

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	PLB probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared down
<i>up-count</i>	(Optional) Count
ip	(Optional) Configure ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node-standby

probe host

[no] probe <probe-id-dns> host <host-name> [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	PLB probe
<i>probe-id-dns</i>	Service mode
host	Host name/Target address
<i>host-name</i>	DNS Target IP Address or Hostname
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/plb-device-group

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id</i>	Service mode
port	TCP/UDP Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count
ip	(Optional) Configure ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node-standby

probe port

```
{ probe <probe-id> port <port-num> [ control <status> ] [ frequency <freq-num> | timeout <timeout> |
retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr> ] + } | { no probe }
```

Syntax Description

no	Negate a command or set its defaults
probe	Catena probe
<i>probe-id</i>	Service mode
port	Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/catena-device-grp

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id</i>	Service mode
port	Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id</i>	Service mode
port	Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count
ip	(Optional) ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/itd-dg-node-standby

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	ITD probe
<i>probe-id</i>	Service mode
port	Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Frequency in seconds
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Timeout in seconds
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Retry-count when node goes down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Retry-count when node comes back up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/itd-device-group

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count> | ip <ip-addr>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for PLB device group node
<i>probe-id</i>	Service mode
port	TCP/UDP Port
<i>port-num</i>	Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count
ip	(Optional) Configure ip address for probe
<i>ip-addr</i>	(Optional) IP4 prefix in format i.i.i.i

Command Mode

- /exec/configure/plb-dg-node

probe port

[no] probe <probe-id> port <port-num> [control <status>] [frequency <freq-num> | timeout <timeout> | retry-down-count <count> | retry-up-count <up-count>] +

Syntax Description

no	(Optional) Negate a command or set its defaults
probe	Configure probe for node
<i>probe-id</i>	Service mode
port	Port
<i>port-num</i>	TCP/UDP Port number
control	(Optional) control protocol
<i>status</i>	(Optional) control protocol status
frequency	(Optional) Configure probe frequency for a node
<i>freq-num</i>	(Optional) Frequency in seconds
timeout	(Optional) Configure probe timeout for a node
<i>timeout</i>	(Optional) Timeout in seconds
retry-down-count	(Optional) Configure retry-count before node declared down
<i>count</i>	(Optional) Count
retry-up-count	(Optional) Configure retry-count after node declared up
<i>up-count</i>	(Optional) Count

Command Mode

- /exec/configure/plb-device-group

profile

{ profile <pid> | no profile }

Syntax Description

no	Negate a command or set its defaults
profile	NGOAM profile to use
<i>pid</i>	NGOAM profile id

Command Mode

- /exec/configure/configngoamconnectcheck

profile

[no] profile <profile-name>

Syntax Description

no	(Optional) Negate the command
profile	Packet Drop Profile
<i>profile-name</i>	Profile name

Command Mode

- /exec/configure/pkt-drop

promiscuous-mode off

promiscuous-mode { off | on } | no promiscuous-mode [{ off | on }]

Syntax Description

no	Negate a command or set its defaults
promiscuous-mode	Configure promiscuous mode for the port
off	Disable promiscuous mode
on	Enable promiscuous mode

Command Mode

- /exec/configure/if-port-channel /exec/configure/if-ethernet-all /exec/configure/if-eth-base

propagate-sgt

[no] propagate-sgt

Syntax Description

propagate-sgt	Enable SGT propagation from this port (the default use the no form to disable)
---------------	--

Command Mode

- /exec/configure/cts-dot1x /exec/configure/cts-manual

protection

[no] protection | protection [fast-reroute [bw-protect]]

Syntax Description

no	Negate a command or set its defaults
protection	Enable failure protection
fast-reroute	(Optional) Enable fast-reroute failure protection
bw-protect	(Optional) Enable BW protection

Command Mode

- /exec/configure/te/lsp-attr

proto

{ proto <proto-id> }

Syntax Description

proto	Protocol
<i>proto-id</i>	IANA Protocol id

Command Mode

- /exec/configure/configngoamccpayload

protocol-version

protocol-version { <10> | <13> | negotiate } | no protocol-version

Syntax Description

no	Negate a command or set its defaults
protocol-version	Set OpenFlow protocol version
10	Use only OF 1.0 protocol to connect to controller
13	Use only OF 1.3 protocol to connect to controller
negotiate	Negotiate protocol with controller

Command Mode

- /exec/configure/openflow/switch

protocol-version

protocol-version { <10> | <13> | negotiate } | no protocol-version

Syntax Description

no	Negate a command or set its defaults
protocol-version	Set OpenFlow protocol version
10	Use only OF 1.0 protocol to connect to controller
13	Use only OF 1.3 protocol to connect to controller
negotiate	Negotiate protocol with controller

Command Mode

- /exec/configure/openflow/switch/sub-switch

protocol

{ protocol <num> } | { no protocol }

Syntax Description

no	Negate a command or set its defaults
protocol	specify flow protocol number
<i>num</i>	flow protocol number

Command Mode

- /exec/configure/configngoamprofileflow

protocol

[no] protocol <proto> [prefix-list <pflist-name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>proto</i>	
<i>pflist-name</i>	(Optional) Name of the prefix-list to be matched

Command Mode

- /exec/configure/config-snoop-policy

protocol shutdown

[no] protocol shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
protocol	OSPF protocol
shutdown	shutdown the OSPF protocol instance

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

protocol shutdown

[no] protocol shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
protocol	OSPF protocol
shutdown	Shutdown the OSPF protocol instance

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

ptp

[no] ptp

Syntax Description

no	(Optional) Negate a command or set its defaults
ptp	Precision Time Protocol (IEEE 1588) Subsystem

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp announce interval

```
[no] ptp announce interval { <log-seconds> | smpte-2059-2 <smpte-log-seconds> | aes67 <aes-log-seconds>
}
```

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
announce	announce
interval	interval
<i>log-seconds</i>	log seconds
smpte-2059-2	SMPTE-2059-2
<i>smpte-log-seconds</i>	SMPTE-2059-2 log seconds
aes67	AES67-2015
<i>aes-log-seconds</i>	AES67-2015 log seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp announce timeout

[no] ptp announce timeout { <val> | smpte-2059-2 <smpte-val> | aes67 <aes-val> }

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
announce	announce
timeout	timeout
smpte-2059-2	SMPTE-2059-2
aes67	AES67-2015
<i>val</i>	
<i>smpte-val</i>	SMPTE-2059-2 val
<i>aes-val</i>	AES67-2015 val

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp clock-identity

ptp clock-identity <mac-address> | no ptp clock-identity

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
clock-identity	clock-identity
<i>mac-address</i>	Mac Address

Command Mode

- /exec/configure

ptp clock-sync auto

[no] ptp clock-sync auto

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
clock-sync	clock-sync
auto	auto adjust frequency

Command Mode

- /exec/configure

ptp clock one-step

[no] ptp { clock-mode | clock-operation } one-step

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
clock-mode	Set the PTP Clock mode
clock-operation	Set the PTP Clock Operation
one-step	One step

Command Mode

- /exec/configure

ptp convergence-time

[no] ptp convergence-time [<val>]

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
convergence-time	Convergence time for Grandmaster capable node, default 10 seconds
<i>val</i>	(Optional) convergence-time

Command Mode

- /exec/configure

ptp correction-range

[no] ptp correction-range <threshold-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
correction-range	set correction range threshold value
<i>threshold-value</i>	correction threshold (ns) [-value, +value], default 100000 (100 us)

Command Mode

- /exec/configure

ptp correction-range logging

[no] ptp correction-range logging

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
correction-range	set correction range threshold value
logging	enable logging for corrections exceeding threshold value

Command Mode

- /exec/configure

ptp correction hardware

[no] ptp correction hardware

Syntax Description

no	(Optional) Negate a command or set its defaults
ptp	Precision Time Protocol (IEEE 1588) Subsystem
correction	Corrections for PTP
hardware	Frequency correction from hardware or software

Command Mode

- /exec/configure

ptp cost

[no] ptp cost <cost>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
cost	Cost associated with the interface
<i>cost</i>	Cost

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp delay-request minimum interval

[no] ptp delay-request minimum interval { <log-seconds> | smpte-2059-2 <smpte-log-seconds> | aes67 <aes-log-seconds> }

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
delay-request	delay-request
minimum	minimum
interval	interval
smpte-2059-2	SMPTE-2059-2
aes67	AES67-2015
<i>log-seconds</i>	log seconds
<i>smpte-log-seconds</i>	SMPTE-2059-2 log seconds
<i>aes-log-seconds</i>	AES67-2015 log seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp device-type boundary

[no] ptp device-type { boundary-clock | generalized-ptp }

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
device-type	ptp device-type
boundary-clock	boundary-clock
generalized-ptp	Generalized PTP

Command Mode

- /exec/configure

ptp domain

[no] ptp domain <domain-val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp domain to be associated with interface
<i>domain-val</i>	Enter configured domain value, default 0

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp domain

[no] ptp domain <domain-val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp clock domain
<i>domain-val</i>	Enter domain value

Command Mode

- /exec/configure

ptp domain clock-accuracy-threshold

[no] ptp domain <domain-val> clock-accuracy-threshold <threshold-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp clock domain
<i>domain-val</i>	Domain value, default is 0
clock-accuracy-threshold	Domain clock accuracy threshold
<i>threshold-value</i>	Domain clock accuracy threshold value, default is 254

Command Mode

- /exec/configure

ptp domain clock-class-threshold

[no] ptp domain <domain-val> clock-class-threshold <threshold-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp clock domain
<i>domain-val</i>	Domain value, default is 0
clock-class-threshold	Domain clock class threshold
<i>threshold-value</i>	Domain clock class threshold value, default is 248

Command Mode

- /exec/configure

ptp domain priority

[no] ptp domain <domain-val> priority <priority-val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
domain	ptp clock domain
<i>domain-val</i>	Domain value, default is 0
priority	Domain priority
<i>priority-val</i>	Domain priority value, default is 255

Command Mode

- /exec/configure

ptp grandmaster-capable

ptp grandmaster-capable | no ptp grandmaster-capable [convergence-time <val>]

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
grandmaster-capable	Grandmaster capability
convergence-time	(Optional) Convergence time in seconds
<i>val</i>	(Optional) convergence

Command Mode

- /exec/configure

ptp mean-path-delay

[no] ptp mean-path-delay <threshold-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
mean-path-delay	set mean-path-delay threshold value
<i>threshold-value</i>	mean-path-delay threshold (ns), default 1000000000 (1 sec)

Command Mode

- /exec/configure

ptp multi-domain

ptp multi-domain | no ptp multi-domain

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
multi-domain	Configure ptp multi-domain

Command Mode

- /exec/configure

ptp multi-domain transition-attributes priority1

[no] ptp multi-domain transition-attributes priority1 <priority1-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
multi-domain	Configure ptp multi-domain
transition-attributes	ptp multi-domain priority domain conversion attributes
priority1	domain conversion priority1 value
<i>priority1-value</i>	Enter domain priority1 value, default 255

Command Mode

- /exec/configure

ptp multi-domain transition-attributes priority2

[no] ptp multi-domain transition-attributes priority2 <priority2-value>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
multi-domain	Configure ptp multi-domain
transition-attributes	ptp multi-domain priority domain conversion attributes
priority2	domain conversion priority2 value
<i>priority2-value</i>	Enter domain priority2 value, default 255

Command Mode

- /exec/configure

ptp multicast master-only

[no] ptp multicast master-only

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
multicast	multicast
master-only	master only

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp neighbor propagation-delay-threshold

[no] ptp neighbor propagation-delay-threshold <nseconds>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
neighbor	ptp neighbor
propagation-delay-threshold	GPTP propagation delay threshold
<i>nseconds</i>	Interval in nano-seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp offload

[no] ptp offload

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
offload	Allows increasing number of PTP sessions per system by offloading some timers to linecard

Command Mode

- /exec/configure

ptp pdelay-req-interval

[no] ptp pdelay-req-interval <val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
pdelay-req-interval	Log mean peer delay request interval
<i>val</i>	value

Command Mode

- /exec/configure

ptp priority1

[no] ptp priority1 <val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
priority1	priority1
<i>val</i>	priority1

Command Mode

- /exec/configure

ptp priority2

[no] ptp priority2 <val>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
priority2	priority1
<i>val</i>	priority2

Command Mode

- /exec/configure

ptp source

```
[no] ptp source <src-ip> [ vrf { <vrf-name> | <vrf-cfg-name> } ]
```

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
source	source IP address
<i>src-ip</i>	IPv4 address (A.B.C.D) of source
vrf	(Optional) vrf to be used for hello messages
<i>vrf-name</i>	(Optional) vrf to be used for hellos
<i>vrf-cfg-name</i>	(Optional) Configurable VRF name

Command Mode

- /exec/configure

ptp sync interval

[no] ptp sync interval { <log-seconds> | smpte-2059-2 <smpte-log-seconds> | aes67 <aes-log-seconds> }

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
sync	sync
interval	interval
smpte-2059-2	SMPTE-2059-2
aes67	AES67-2015
<i>log-seconds</i>	log seconds
<i>smpte-log-seconds</i>	SMPTE-2059-2 log seconds
<i>aes-log-seconds</i>	AES67-2015 log seconds

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp transport ipv4 ucast master

[no] ptp transport ipv4 ucast master

Syntax Description

no	(Optional) Negate a command or set its defaults
ptp	Precision Time Protocol (IEEE 1588) Subsystem
transport	unicast support
ipv4	ipv4
ucast	ipv4 unicast
master	master mode

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp transport ipv4 ucast slave

[no] ptp transport ipv4 ucast slave

Syntax Description

no	(Optional) Negate a command or set its defaults
ptp	Precision Time Protocol (IEEE 1588) Subsystem
transport	unicast support
ipv4	ipv4
ucast	ipv4 unicast
slave	slave mode

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp ucast-source

```
[no] ptp ucast-source <src-ip> [ vrf { <vrf-name> | <vrf-cfg-name> } ]
```

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
ucast-source	source IP address for ucast messages
<i>src-ip</i>	IPv4 address (A.B.C.D) of source
vrf	(Optional) vrf to be used for hello messages
<i>vrf-name</i>	(Optional) vrf to be used for hellos
<i>vrf-cfg-name</i>	(Optional) Configurable VRF name

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ptp vlan

[no] ptp vlan <vlan>

Syntax Description

ptp	Precision Time Protocol (IEEE 1588) Subsystem
vlan	vlan
<i>vlan</i>	vlan

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

purge module running-config

purge module <module> running-config

Syntax Description

purge	Deletes unused data
module	Purge configuration for non-existent modules
<i>module</i>	Enter module number
running-config	purge running configuration for non-existent modules

Command Mode

- /exec

push

push [<name>]

Syntax Description

push	push current mode to stack or save it under name
<i>name</i>	(Optional) name

Command Mode

- /global

pwd

pwd

Syntax Description

pwd	View current directory
-----	------------------------

Command Mode

- /exec

python

python [<uri> [<pyargs>] +]

Syntax Description

python	run a python command/script, or enter python mode (if no arg)
<i>uri</i>	(Optional) path to a python file
<i>pyargs</i>	(Optional) python command line arguments (maximum 32)

Command Mode

- /exec

python instance

[no] python instance <inst> [<uri> [<pyargs>] +] | python instance <inst> <uri> [<pyargs>] +

Syntax Description

no	Negate a command or set its defaults
python	run a python command/script, or enter python mode (if no arg)
instance	label with an instance number
<i>inst</i>	instance number
<i>uri</i>	(Optional) path to a python file
<i>pyargs</i>	(Optional) python command line arguments (maximum 32)

Command Mode

- /exec/configure



Q Commands

- [qos copy policy-map type network-qos prefix, on page 3580](#)
- [qos copy policy-map type queuing prefix, on page 3581](#)
- [qos qos-policies statistics, on page 3582](#)
- [qos shared-policer, on page 3583](#)
- [qos statistics, on page 3587](#)
- [qualify udf, on page 3588](#)
- [queue-limit, on page 3589](#)
- [queue-limit2, on page 3590](#)
- [queue-limit3, on page 3591](#)
- [queue-limit4, on page 3592](#)
- [queue-limit5, on page 3593](#)
- [queue-limit bytes, on page 3594](#)

qos copy policy-map type network-qos prefix

qos copy policy-map type network-qos <pmap-nq-enum-name-dc3> { prefix | suffix } <ix-name>

Syntax Description

copy	Copy (Clone) template
policy-map	Configure a policy map
type	Specify the type of this policy-map
network-qos	Network QoS policy
<i>pmap-nq-enum-name-dc3</i>	
prefix	Policy map name prefix
suffix	Policy map name suffix
<i>ix-name</i>	Suffix/Prefix name, max size counted together with policy name

Command Mode

- /exec

qos copy policy-map type queuing prefix

qos copy policy-map type queuing <pmap-name-que-temp> { prefix | suffix } <ix-name>

Syntax Description

copy	Copy (Clone) template
policy-map	Configure a policy map
type	Specify the type of this policy-map
queuing	Queuing policy
<i>pmap-name-que-temp</i>	Policy-map name
prefix	Policy map name prefix
suffix	Policy map name suffix
<i>ix-name</i>	Suffix/Prefix name, max size counted together with policy name

Command Mode

- /exec

qos qos-policies statistics

[no] qos qos-policies statistics

Syntax Description

no	(Optional) Negate a command or set its defaults
qos-policies	All qos type policies
statistics	statistics

Command Mode

- /exec/configure

qos shared-policer

```
{ qos shared-policer [ type qos ] <policer-name> { [ cir ] { <cir-val> [ bps | kbps | mbps | gbps | pps ] | percent
<cir-perc> } [ [ bc ] { <committed-burst> [ bytes | kbytes | mbytes | ms | us | packets ] } ] [ pir { <pir-val> [
bps2 | kbps2 | mbps2 | gbps2 | pps2 ] | percent <pir-perc> } [ [ be ] { <extended-burst> [ bytes2 | kbytes2 |
mbytes2 | ms2 | us2 | packets2 ] } ] ] [ conform { transmit | set-prec-transmit { <prec-val> | <prec-enum> } |
set-dscp-transmit { <dscp-val> | <dscp-enum> } | set-cos-transmit <cos-val> | set-discard-class-transmit
<disc-class-val> | set-qos-transmit <qos-grp-val> | set-mpls-exp-imposition-transmit <exp-value-imp> |
set-mpls-exp-topmost-transmit <exp-value-top> } ] [ exceed { transmit1 | drop1 | set <exc-frm-field>
<exc-to-field> table cir-markdown-map | set-prec-transmit1 { <prec-val1> | <prec-enum1> } | set-dscp-transmit1
{ <dscp-val1> | <dscp-enum1> } | set-cos-transmit1 <cos-val1> | set-discard-class-transmit1 <disc-class-val1>
| set-qos-transmit1 <qos-grp-val1> | set-mpls-exp-imposition-transmit1 <exp-value-imp1> |
set-mpls-exp-topmost-transmit1 <exp-value-top1> } ] [ violate { drop2 | set <vio-frm-field> <vio-to-field>
table2 pir-markdown-map | set-prec-transmit2 { <prec-val2> | <prec-enum2> } | set-dscp-transmit2 {
<dscp-val2> | <dscp-enum2> } | set-cos-transmit2 <cos-val2> | set-discard-class-transmit2 <disc-class-val2>
| set-qos-transmit2 <qos-grp-val2> | set-mpls-exp-imposition-transmit2 <exp-value-imp2> |
set-mpls-exp-topmost-transmit2 <exp-value-top2> } ] } | no qos shared-policer [ type qos ] <policer-name>
}
```

Syntax Description

no	Negate a command or set its defaults
shared-policer	Shared policer
<i>policer-name</i>	Shared policer name
type	(Optional) Specify the type of shared-policer
qos	QoS Global Commands
cir	(Optional) Specify committed information rate
bc	(Optional) Specify committed burst
percent	Specify rate as percentage of interface data-rate
<i>cir-perc</i>	Percentage
<i>pir-perc</i>	(Optional) Percentage
pir	(Optional) Specify peak information rate
be	(Optional) Specify extended burst (for 1R3C meter)
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
pps	(Optional) Packets per second

bps2	(Optional) Bits per second
kbps2	(Optional) Kilo Bits per second
mbps2	(Optional) Mega Bits per second
gbps2	(Optional) Giga Bits per second
pps2	(Optional) Packets per second
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
us	(Optional) Micro second(s)
ms	(Optional) Milli second(s)
packets	(Optional) Packets
bytes2	(Optional) Bytes
kbytes2	(Optional) Kilo Bytes
mbytes2	(Optional) Mega Bytes
ms2	(Optional) Milli seconds
us2	(Optional) Micro seconds
packets2	(Optional) Packets
conform	(Optional) Specify a conform action
exceed	(Optional) Specify a exceed action
violate	(Optional) Specify a violate action
transmit	(Optional) Transmit packet
transmit1	(Optional) Transmit packet
drop1	(Optional) Drop packet
drop2	(Optional) Drop packet
set-prec-transmit	(Optional) Set precedence and send it
set-prec-transmit1	(Optional) Set precedence and send it
set-prec-transmit2	(Optional) Set precedence and send it
<i>prec-val</i>	(Optional) Precedence value
<i>prec-val1</i>	(Optional) Precedence value

<i>prec-val2</i>	(Optional) Precedence value
<i>prec-enum</i>	(Optional)
<i>prec-enum1</i>	(Optional)
<i>prec-enum2</i>	(Optional)
set-dscp-transmit	(Optional) Set dscp and send it
set-dscp-transmit1	(Optional) Set dscp and send it
set-dscp-transmit2	(Optional) Set dscp and send it
<i>dscp-val</i>	(Optional) DSCP value
<i>dscp-val1</i>	(Optional) DSCP value
<i>dscp-val2</i>	(Optional) DSCP value
<i>dscp-enum</i>	(Optional)
<i>dscp-enum1</i>	(Optional)
<i>dscp-enum2</i>	(Optional)
set-cos-transmit	(Optional) Set cos and send it
set-cos-transmit1	(Optional) Set cos and send it
set-cos-transmit2	(Optional) Set cos and send it
<i>cos-val</i>	(Optional) new cos value
<i>cos-val1</i>	(Optional) new cos value
<i>cos-val2</i>	(Optional) new cos value
set-discard-class-transmit	(Optional) Set discard class and send it
set-discard-class-transmit1	(Optional) Set discard class and send it
set-discard-class-transmit2	(Optional) Set discard class and send it
<i>disc-class-val</i>	(Optional) new discard-class value
<i>disc-class-val1</i>	(Optional) new discard-class value
<i>disc-class-val2</i>	(Optional) new discard-class value
set-qos-transmit	(Optional) Set qos-group and send it
set-qos-transmit1	(Optional) Set qos-group and send it
set-qos-transmit2	(Optional) Set qos-group and send it
<i>qos-grp-val</i>	(Optional) QoS group value

<i>qos-grp-val1</i>	(Optional) QoS group value
<i>qos-grp-val2</i>	(Optional) QoS group value
set-mpls-exp-imposition-transmit	(Optional) set-mpls-exp-imposition-transmit
set-mpls-exp-imposition-transmit1	(Optional) set-mpls-exp-imposition-transmit
set-mpls-exp-imposition-transmit2	(Optional) set-mpls-exp-imposition-transmit
<i>exp-value-imp</i>	(Optional) MPLS imposition value
<i>exp-value-imp1</i>	(Optional) MPLS imposition value
<i>exp-value-imp2</i>	(Optional) MPLS imposition value
set-mpls-exp-topmost-transmit	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit1	(Optional) Set MPLS topmost label
set-mpls-exp-topmost-transmit2	(Optional) Set MPLS topmost label
<i>exp-value-top</i>	(Optional) MPLS topmost value
<i>exp-value-top1</i>	(Optional) MPLS topmost value
<i>exp-value-top2</i>	(Optional) MPLS topmost value
set	(Optional) Set a particular value using table or markdown map
<i>exc-frm-field</i>	(Optional)
<i>exc-to-field</i>	(Optional)
<i>vio-frm-field</i>	(Optional)
<i>vio-to-field</i>	(Optional)
table	(Optional) Set using the table-map
table2	(Optional) Set using the table-map
cir-markdown-map	(Optional) Markdown map table name for exceed action
pir-markdown-map	(Optional) Markdown map table name for violate action

Command Mode

- /exec/configure

qos statistics

[no] qos statistics

Syntax Description

no	(Optional) Negate a command or set its defaults
statistics	statistics

Command Mode

- /exec/configure

qualify udf

[no] <udf_tcam_type> qualify udf { <udf_name> } +

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>udf_tcam_type</i>	Region type
qualify	Configure UDFs to be qualified for span region
udf	Configure UDF names
<i>udf_name</i>	UDF name

Command Mode

- /exec/configure/tcam-templ

queue-limit

[no] queue-limit [cos <cos-val>] { <q-size> [packets | bytes | kbytes | mbytes | ms | us] | percent <perc-q-size> | dynamic <alpha> }

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit	Configure queue size for the class
cos	(Optional) IEEE 802.1Q Class of Service
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
percent	Specify queue size in Percentage
<i>perc-q-size</i>	Queue size in percentage of total tx/rx buffer size
dynamic	Queue size in dynamic alpha factor
<i>alpha</i>	0-1/128, 1-1/64, 2-1/32, 3-1/16, 4-1/8, 5-1/4, 6-1/2, 7-1, 8-2, 9-4, 10-8
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

queue-limit2

```
[no] queue-limit2 [ cos2 <cos-val> ] { <q-size> [ packets | bytes | kbytes | mbytes | ms | us ] | percent2
<perc-q-size> | dynamic2 <alpha> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit2	Configure queue size for the class
cos2	(Optional) IEEE 802.1Q Class of Service
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
percent2	Specify queue size in Percentage
<i>perc-q-size</i>	Queue size in percentage of total tx/rx buffer size
dynamic2	Queue size in dynamic alpha factor
<i>alpha</i>	0-1/128, 1-1/64, 2-1/32, 3-1/16, 4-1/8, 5-1/4, 6-1/2, 7-1, 8-2, 9-4, 10-8
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

queue-limit3

```
[no] queue-limit3 [ cos3 <cos-val> ] { <q-size> [ packets | bytes | kbytes | mbytes | ms | us ] | percent3
<perc-q-size> | dynamic3 <alpha> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit3	Configure queue size for the class
cos3	(Optional) IEEE 802.1Q Class of Service
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
percent3	Specify queue size in Percentage
<i>perc-q-size</i>	Queue size in percentage of total tx/rx buffer size
dynamic3	Queue size in dynamic alpha factor
<i>alpha</i>	0-1/8, 1-1/4, 2-1/2, 3-3/4, 4-9/8, 5-15/8, 6-3, 7-5, 8-8, 9-14, 10-18
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

queue-limit4

```
[no] queue-limit4 [ cos4 <cos-val> ] { <q-size> [ packets | bytes | kbytes | mbytes | ms | us ] | percent4
<perc-q-size> | dynamic4 <alpha> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit4	Configure queue size for the class
cos4	(Optional) IEEE 802.1Q Class of Service
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
percent4	Specify queue size in Percentage
<i>perc-q-size</i>	Queue size in percentage of total tx/rx buffer size
dynamic4	Queue size in dynamic alpha factor
<i>alpha</i>	0-3/2, 1-3, 2-6, 3-11, 4-20, 5-33, 6-50, 7-66, 8-80
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

queue-limit5

```
[no] queue-limit5 [ cos5 <cos-val> ] { <q-size> [ packets | bytes | kbytes | mbytes | ms | us ] | percent5
<perc-q-size> | dynamic5 <alpha> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit5	Configure queue size for the class
cos5	(Optional) IEEE 802.1Q Class of Service
<i>cos-val</i>	(Optional) 802.1Q Class of Service value
percent5	Specify queue size in Percentage
<i>perc-q-size</i>	Queue size in percentage of total tx/rx buffer size
dynamic5	Queue size in dynamic alpha factor
<i>alpha</i>	1-1/16, 2-1/8, 3-1/4, 4-1/2, 5-1, 6-2, 7-4, 8-8
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

queue-limit bytes

[no] queue-limit { <q-size> bytes }

Syntax Description

no	(Optional) Negate a command or set its defaults
queue-limit	Configure queue size for the class
bytes	Bytes

Command Mode

- /exec/configure/policy-map/type/uf/class



R Commands

- [radius-server deadtime](#), on page 3600
- [radius-server directed-request](#), on page 3601
- [radius-server host key 0 6 7](#), on page 3602
- [radius-server host test](#), on page 3604
- [radius-server key 0 6 7](#), on page 3605
- [radius-server pss-clean](#), on page 3606
- [radius-server retransmit](#), on page 3607
- [radius-server test](#), on page 3608
- [radius-server timeout](#), on page 3609
- [random-detect](#), on page 3610
- [random-detect2 minimum-threshold2 maximum-threshold2](#), on page 3612
- [random-detect2 non-ecn minimum-threshold2 maximum-threshold2 drop](#), on page 3613
- [random-detect](#), on page 3614
- [random-detect cos-based](#), on page 3616
- [rate-limit](#), on page 3618
- [rate-limit cpu direction pps action log](#), on page 3619
- [rate-limit cpu direction pps action log](#), on page 3620
- [rate-limit packet_in burst](#), on page 3621
- [rate-limit packet_in burst](#), on page 3622
- [rate-mode](#), on page 3623
- [rd auto](#), on page 3624
- [rd auto](#), on page 3625
- [receiver](#), on page 3626
- [reconnect-interval](#), on page 3627
- [record-route](#), on page 3628
- [record-route](#), on page 3629
- [record](#), on page 3630
- [record](#), on page 3631
- [record](#), on page 3632
- [record](#), on page 3633
- [record](#), on page 3634
- [redistribute bgp](#), on page 3635
- [redistribute bgp eigrp isis ospf rip static direct amt lisp route-map](#), on page 3636

- redistribute filter route-map, on page 3637
- redistribute filter route-map, on page 3638
- redistribute maximum-prefix, on page 3639
- redistribute maximum-prefix, on page 3640
- redistribute maximum-prefix, on page 3641
- redistribute maximum-prefix, on page 3642
- redistribute maximum-prefix, on page 3643
- redistribute route-map, on page 3644
- redistribute route-map, on page 3645
- redistribute route-map, on page 3646
- redistribute route-map, on page 3647
- redistribute route-map, on page 3648
- redistribute route-map, on page 3649
- redistribute route-map, on page 3650
- redistribute route-map, on page 3651
- redistribute route-map, on page 3652
- redistribute route-map, on page 3653
- redownload forwarding state, on page 3654
- redundancy-group, on page 3655
- reference-bandwidth, on page 3656
- reference-bandwidth, on page 3657
- register-database-mapping, on page 3658
- register-route-notifications, on page 3659
- reload, on page 3660
- reload cancel, on page 3661
- reload in, on page 3662
- reload module, on page 3663
- reload module force-dnld, on page 3664
- reload non-interruptive, on page 3665
- reload power-cycle, on page 3666
- reload sync-adjacency, on page 3667
- reload sync-adjacency, on page 3668
- reload timer, on page 3669
- reload vdc, on page 3670
- reload vdc, on page 3671
- remark, on page 3672
- remark, on page 3673
- remark, on page 3674
- remote-as, on page 3675
- remote-span, on page 3676
- remote, on page 3677
- remove-private-as, on page 3678
- reoptimize events link-up, on page 3679
- replay-protection, on page 3680
- report, on page 3681
- report, on page 3682

- report, on page 3683
- report, on page 3684
- report, on page 3685
- report, on page 3686
- report, on page 3687
- report, on page 3688
- report, on page 3689
- report, on page 3690
- report, on page 3691
- report, on page 3692
- report, on page 3693
- report, on page 3694
- report, on page 3695
- report, on page 3696
- request-data-size, on page 3697
- request-data-size, on page 3698
- request-data-size, on page 3699
- resequence access, on page 3700
- reset, on page 3701
- reset, on page 3702
- reset, on page 3703
- reset, on page 3704
- reset, on page 3705
- reset, on page 3706
- reset, on page 3707
- reset, on page 3708
- reset, on page 3709
- reset, on page 3710
- reset, on page 3711
- reset, on page 3712
- reset, on page 3713
- reset, on page 3714
- reset, on page 3715
- reset, on page 3716
- restart amt, on page 3717
- restart bgp, on page 3718
- restart eigrp, on page 3719
- restart igmp, on page 3720
- restart isis, on page 3721
- restart msdp, on page 3722
- restart ospf, on page 3723
- restart ospfv3, on page 3724
- restart pim, on page 3725
- restart pim6, on page 3726
- restart rip, on page 3727
- restart rsvp, on page 3728

- resync-database, on page 3729
- retain route-target all, on page 3730
- retain route-target all, on page 3731
- retransmit-interval, on page 3732
- retransmit-interval, on page 3733
- retransmit-interval, on page 3734
- revision, on page 3735
- revocation-check srl, on page 3736
- rewrite-evpn-rt-asn, on page 3737
- rewrite-rt-asn, on page 3738
- rfc1583compatibility, on page 3739
- rip shutdown, on page 3740
- rmdir, on page 3741
- rmon alarm absolute rising-threshold falling-threshold, on page 3742
- rmon event, on page 3743
- rmon hcalarm absolute startupalarm rising-threshold falling-threshold owner, on page 3744
- roaming-eid-prefix, on page 3745
- role feature-group name, on page 3746
- role name, on page 3747
- role priority, on page 3748
- rollback running-config checkpoint, on page 3749
- root-priority, on page 3750
- route-map, on page 3751
- route-map, on page 3752
- route-map, on page 3753
- route-map, on page 3754
- route-map out, on page 3755
- route-map pbr-statistics, on page 3756
- route-reflector-client, on page 3757
- route-reflector-client, on page 3758
- route-target both auto, on page 3759
- route-target both auto, on page 3760
- route-target export, on page 3761
- route-target export auto, on page 3762
- route-target import, on page 3763
- route-target import auto, on page 3764
- route delete dampen interval, on page 3765
- router-guard ip multicast, on page 3766
- router-guard ip multicast switchports, on page 3767
- router-id, on page 3768
- router-id, on page 3769
- router-id, on page 3770
- router-id, on page 3771
- router-id, on page 3772
- router-id, on page 3773
- router-preference maximum, on page 3774

- [router bgp](#), on page 3775
- [router eigrp](#), on page 3776
- [router isis](#), on page 3777
- [router ospf](#), on page 3778
- [router ospfv3](#), on page 3779
- [router rip](#), on page 3780
- [routing-context vrf](#), on page 3781
- [rsa-keypair](#), on page 3782
- [rtr etr eid](#), on page 3783
- [rule](#), on page 3784
- [rule command](#), on page 3785
- [rule oid](#), on page 3786
- [run-script](#), on page 3787
- [run2 guestshell](#), on page 3788
- [run bash](#), on page 3789

radius-server deadtime

[no] radius-server deadtime <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
deadtime	duration for which non-reachable server is skipped
<i>i0</i>	Length of time, in minutes

Command Mode

- /exec/configure

radius-server directed-request

[no] radius-server directed-request

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
directed-request	enable direct authentication requests to server

Command Mode

- /exec/configure

radius-server host key 0 6 7

```
{ { [ no ] radius-server host <hostipname> { { key { 0 <s0> | 6 <s6> | 7 <s1> | <s2> } [ pac ] [ auth-port <i0>
[ acct-port <i1> ] ] } | { [ auth-port1 <i2> ] [ acct-port1 <i3> ] } } [ { authentication [ accounting [ timeout
<i4> ] [ retransmit <i5> ] ] } | { [ accounting1 ] [ timeout1 <i6> ] [ retransmit1 <i7> ] } } ] | { no radius-server
host <hostipname> key } }
```

Syntax Description

<i>key</i>	0
no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
host	RADIUS server's DNS name or its IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name
key	RADIUS shared secret
pac	(Optional) Secure Radius Enable
0	RADIUS shared secret(clear text)
<i>s0</i>	RADIUS shared secret(clear text)
accounting	(Optional) Use for accounting
retransmit	(Optional) RADIUS server retransmit count
<i>i5</i>	(Optional) RADIUS server retransmit count
timeout	(Optional) RADIUS server timeout period in seconds
<i>i4</i>	(Optional) RADIUS server timeout period in seconds
retransmit1	(Optional) RADIUS server retransmit count
<i>i7</i>	(Optional) RADIUS server retransmit count
auth-port	(Optional) RADIUS server's port for authentication
<i>i0</i>	(Optional) port number
timeout1	(Optional) RADIUS server timeout period in seconds
<i>i6</i>	(Optional) RADIUS server timeout period in seconds
acct-port	(Optional) RADIUS server's port for accounting
<i>i1</i>	(Optional) port number
accounting1	(Optional) Use for accounting

authentication	(Optional) Use for authentication
6	Radius shared secret(type-6 encrypted)
<i>s6</i>	Tadius shared secret(encrypted)
7	RADIUS shared secret(encrypted)
<i>s1</i>	RADIUS shared secret(encrypted)
auth-port1	(Optional) RADIUS server's port for authentication
<i>i2</i>	(Optional) port number
<i>s2</i>	RADIUS shared secret(clear text)
acct-port1	(Optional) RADIUS server's port for accounting
<i>i3</i>	(Optional) port number

Command Mode

- /exec/configure

radius-server host test

```
[no] radius-server host { <hostipname> } test { { username <s0> { [ password <s1> [ idle-time <i1> ] ] } | [ idle-time <i1> ] } } | { password <s1> [ idle-time <i1> ] } | { idle-time <i1> } }
```

Syntax Description

<i>username</i>	<s0>
no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
host	RADIUS server's DNS name or its IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name
test	Parameters to send test packets
<i>s0</i>	user name
password	(Optional) user password in test packets
<i>s1</i>	(Optional) user password
idle-time	(Optional) time interval for monitoring the server
<i>i1</i>	(Optional) time period in minutes

Command Mode

- /exec/configure

radius-server key 0 6 7

```
{ { [ no ] radius-server key { 0 <s0> | 6 <s6> | 7 <s1> | <s2> } } | { no radius-server key } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
key	Global RADIUS server shared secret
0	default RADIUS shared secret(clear text)
<i>s0</i>	default RADIUS shared secret(clear text)
6	default RADIUS shared secret(type-6 encrypted)
<i>s6</i>	default RADIUS shared secret(type-6 encrypted)
7	default RADIUS shared secret(encrypted)
<i>s1</i>	default RADIUS shared secret(encrypted)
<i>s2</i>	default RADIUS shared secret(clear text)

Command Mode

- /exec/configure

radius-server pss-clean

[no] radius-server pss-clean

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
pss-clean	Erase PSS

Command Mode

- /exec/configure

radius-server retransmit

[no] radius-server retransmit <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
retransmit	Global RADIUS server retransmit count
<i>i0</i>	Global RADIUS server retransmit count

Command Mode

- /exec/configure

radius-server test

```
[no] radius-server test { { username <s0> { [ password <s1> [ idle-time <i1> ] ] | [ idle-time <i1> ] } } | { password <s1> [ idle-time <i1> ] } | { idle-time <i1> } }
```

Syntax Description

<i>username</i>	<s0>
no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
test	Parameters to send test packets
<i>s0</i>	user name
password	(Optional) user password in test packets
<i>s1</i>	(Optional) user password
idle-time	(Optional) time interval for monitoring the server
<i>i1</i>	(Optional) time period in minutes

Command Mode

- /exec/configure

radius-server timeout

[no] radius-server timeout <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
radius-server	Configure RADIUS related parameters
timeout	Global RADIUS server timeout period in seconds
<i>i0</i>	RADIUS server timeout period in seconds

Command Mode

- /exec/configure

random-detect

```
[no] random-detect [ { minimum-threshold <min-thresh> { packets | bytes | kbytes | mbytes }
maximum-threshold <max-thresh> { packets1 | bytes1 | kbytes1 | mbytes1 } drop-probability <drop-prob>
weight <weight> [ cap-average ] } | threshold { burst-optimized | mesh-optimized } ] [ ecn ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
random-detect	Configure WRED parameters
threshold	(Optional) Threshold
burst-optimized	(Optional) Threshold optimized for bursty traffic
mesh-optimized	(Optional) Threshold optimized for mesh traffic
minimum-threshold	(Optional) Specify minimum threshold for WRED
maximum-threshold	(Optional) Specify maximum threshold for WRED
<i>max-thresh</i>	(Optional) Maximum threshold value
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
packets1	(Optional) Packets
bytes1	(Optional) Bytes
kbytes1	(Optional) Kilo Bytes
mbytes1	(Optional) Mega Bytes
drop-probability	(Optional) Drop Probability at Maximum Threshold
<i>drop-prob</i>	(Optional) Drop Probability Value
weight	(Optional) Queue length weight
<i>weight</i>	(Optional) Queue length weight
cap-average	(Optional) If average queue length is more, replace average queue length with current queue length
ecn	(Optional) ECN

Command Mode

- /exec/configure/policy-map/type/queuing/class

random-detect2 minimum-threshold2 maximum-threshold2

```
[no] random-detect2 minimum-threshold2 <min-thresh2> { packets2 | bytes2 | kbytes2 | mbytes2 }
maximum-threshold2 <max-thresh2> { packets3 | bytes3 | kbytes3 | mbytes3 } [ drop-probability2 <drop-prob2>
weight2 <weight2> [ cap-average2 ] ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
random-detect2	Configure WRED parameters
minimum-threshold2	Specify minimum threshold for WRED
maximum-threshold2	Specify maximum threshold for WRED
packets2	Packets
bytes2	Bytes
kbytes2	Kilo Bytes
mbytes2	Mega Bytes
packets3	Packets
bytes3	Bytes
kbytes3	Kilo Bytes
mbytes3	Mega Bytes
drop-probability2	(Optional) Drop Probability at Maximum Threshold
<i>drop-prob2</i>	(Optional) Drop Probability Value
weight2	(Optional) Queue length weight
<i>weight2</i>	(Optional) Queue length weight
cap-average2	(Optional) If average queue length is more, replace average queue length with current queue length

Command Mode

- /exec/configure/policy-map/type/queuing/class

random-detect2 non-ecn minimum-threshold2 maximum-threshold2 drop

```
[no] random-detect2 non-ecn minimum-threshold2 <min-thresh2> { packets2 | bytes2 | kbytes2 | mbytes2 }
maximum-threshold2 <max-thresh2> { packets3 | bytes3 | kbytes3 | mbytes3 } { drop-probability2 <drop-prob2>
}
```

Syntax Description

no	(Optional) Negate a command or set its defaults
random-detect2	Configure WRED parameters
non-ecn	Configure WRED parameters for non-ecn
minimum-threshold2	Specify minimum threshold for WRED
maximum-threshold2	Specify maximum threshold for WRED
packets2	Packets
bytes2	Bytes
kbytes2	Kilo Bytes
mbytes2	Mega Bytes
packets3	Packets
bytes3	Bytes
kbytes3	Kilo Bytes
mbytes3	Mega Bytes
drop-probability2	Drop Probability at Maximum Threshold
<i>drop-prob2</i>	Drop Probability Value

Command Mode

- /exec/configure/policy-map/type/queuing/class

random-detect

```
[no] random-detect { cos <cos-list> [ minimum-threshold ] { <min-thresh> [ packets | bytes | kbytes | mbytes
| ms | us ] | percent <min-percent-of-qsize> } [ maximum-threshold ] { <max-thresh> [ packets1 | bytes1 |
kbytes1 | mbytes1 | ms1 | us1 ] | percent1 <max-percent-of-qsize> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
random-detect	Configure WRED parameters
cos	Parameters for each cos value
<i>cos-list</i>	List of class-of-service values
minimum-threshold	(Optional) Specify minimum threshold for WRED
maximum-threshold	(Optional) Specify maximum threshold for WRED
<i>max-thresh</i>	Maximum threshold value
percent	Specify thresholds in percent
percent1	Specify thresholds in percent
<i>min-percent-of-qsize</i>	Minimum threshold percent of queue size
<i>max-percent-of-qsize</i>	Maximum threshold percent of queue size
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)
packets1	(Optional) Packets
bytes1	(Optional) Bytes
kbytes1	(Optional) Kilo Bytes
mbytes1	(Optional) Mega Bytes
ms1	(Optional) Milli second(s)
us1	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

random-detect cos-based

[no] random-detect cos-based [aggregate [minimum-threshold] { <min-thresh> [packets | bytes | kbytes | mbytes | ms | us] | percent <min-percent-of-qsize> } [maximum-threshold] { <max-thresh> [packets1 | bytes1 | kbytes1 | mbytes1 | ms1 | us1] | percent1 <max-percent-of-qsize> }]

Syntax Description

no	(Optional) Negate a command or set its defaults
random-detect	Configure WRED parameters
cos-based	Configure WRED parameters for cos-based mode
aggregate	(Optional) Configure WRED parameters to same value for all sub-classes
minimum-threshold	(Optional) Specify minimum threshold for WRED
maximum-threshold	(Optional) Specify maximum threshold for WRED
<i>max-thresh</i>	(Optional) Maximum threshold value
percent	(Optional) Specify thresholds in percent
percent1	(Optional) Specify thresholds in percent
<i>min-percent-of-qsize</i>	(Optional) Minimum threshold percent of queue size
<i>max-percent-of-qsize</i>	(Optional) Maximum threshold percent of queue size
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes
ms	(Optional) Milli second(s)
us	(Optional) Micro second(s)
packets1	(Optional) Packets
bytes1	(Optional) Bytes
kbytes1	(Optional) Kilo Bytes
mbytes1	(Optional) Mega Bytes
ms1	(Optional) Milli second(s)
us1	(Optional) Micro second(s)

Command Mode

- /exec/configure/policy-map/type/queuing/class

rate-limit

rate-limit { auto | <rate_value> } | no rate-limit

Syntax Description

no	Negate a command or set its defaults
rate-limit	Set the Rate limit for SPAN packets
auto	Set the Rate limit using auto value
<i>rate_value</i>	Enter the percentage of the maximum rate for SPAN packets

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

rate-limit cpu direction pps action log

[no] rate-limit cpu direction { input | output | both } pps <pps-val> action log

Syntax Description

no	(Optional) Negate a command or set its defaults
rate-limit	set packet per second rate limit
cpu	Supervisor CPU limits
direction	input/output direction
input	set max input packet rate
output	set max output packet rate
both	set max input and output packet rate
pps	packet per second
<i>pps-val</i>	pps value
action	log action
log	write a syslog message if PPS hits rate-limit

Command Mode

- /exec/configure

rate-limit cpu direction pps action log

[no] rate-limit cpu direction { input | output | both } pps <pps-val> action log

Syntax Description

no	(Optional) Negate a command or set its defaults
rate-limit	set packet per second rate limit
cpu	Supervisor CPU limits
direction	input/output direction
input	set max input packet rate
output	set max output packet rate
both	set max input and output packet rate
pps	packet per second
<i>pps-val</i>	pps value
action	log action
log	write a syslog message if PPS hits rate-limit

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-eth-any /exec/configure/if-mgmt-config

rate-limit packet_in burst

rate-limit packet_in <packetin-val> burst <burst-val> | no rate-limit

Syntax Description

no	Negate a command or set its defaults
rate-limit	OpenFlow rate limit to controller
packet_in	packet in rate (pps)
<i>packetin-val</i>	packets per second
burst	Maximum number of packets to controller (pps)
<i>burst-val</i>	packets per second

Command Mode

- /exec/configure/openflow/switch/sub-switch

rate-limit packet_in burst

rate-limit packet_in <packetin-val> burst <burst-val> | no rate-limit

Syntax Description

no	Negate a command or set its defaults
rate-limit	OpenFlow rate limit to controller
packet_in	packet in rate (pps)
<i>packetin-val</i>	packets per second
burst	Maximum number of packets to controller (pps)
<i>burst-val</i>	packets per second

Command Mode

- /exec/configure/openflow/switch

rate-mode

rate-mode <ratemode> [force] | no rate-mode [<ratemode>] [force]

Syntax Description

no	Negate a command or set its defaults
rate-mode	Enter the rate mode
force	(Optional) This option will shutdown all ports in port-group momentarily
<i>ratemode</i>	Interface port speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

rd auto

```
{ rd { auto | <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } } | { no rd [ { auto | <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] }
```

Syntax Description

no	Negate a command or set its defaults
rd	VPN Route Distinguisher
auto	Generate RD automatically
<i>ext-comm-rd-aa4nn2</i>	VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	VPN route distinguisher in aa:nn format

Command Mode

- /exec/configure/evpn/evi

rd auto

```
{ rd { auto | <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } } | { no rd [ { auto | <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] }
```

Syntax Description

no	Negate a command or set its defaults
rd	VPN Route Distinguisher
auto	Generate RD automatically
<i>ext-comm-rd-aa4nn2</i>	VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	VPN route distinguisher in aa:nn format

Command Mode

- /exec/configure/vrf

receiver

[no] receiver

Syntax Description

no	(Optional) Negate a command or set its defaults
receiver	Policies for a Local Receiver

Command Mode

- /exec/configure/nbm-host-policy

reconnect-interval

reconnect-interval <interval> | no reconnect-interval [<interval>]

Syntax Description

no	Negate a command or set its defaults
reconnect-interval	Configure connection reconnect interval
<i>interval</i>	Interval in seconds

Command Mode

- /exec/configure/router-bgp/vrf-cmds

record-route

[no] record-route

Syntax Description

no	(Optional) Negate a command or set its defaults
record-route	Record the route used by the LSP

Command Mode

- /exec/configure/te/lsp-attr

record-route

[no] record-route

Syntax Description

no	(Optional) Negate a command or set its defaults
record-route	record the route used by the tunnel

Command Mode

- /exec/configure/if-te /exec/configure/tunnel-te/cbts-member

record

[no] record <recordname>

Syntax Description

record	Specify POSTCARD Record to use
<i>recordname</i>	Name of record

Command Mode

- /exec/configure/config-postcard-monitor

record

[no] record <recordname>

Syntax Description

record	Specify INT Record to use
<i>recordname</i>	Name of record

Command Mode

- /exec/configure/config-int-monitor

record

[no] record <recordname>

Syntax Description

record	Specify FTE Record to use
<i>recordname</i>	Name of record

Command Mode

- /exec/configure/config-fte-monitor

record

[no] record <recordname>

Syntax Description

record	Specify Flow Record to use
<i>recordname</i>	Name of record

Command Mode

- /exec/configure/nfm-monitor

record

[no] record <recordname>

Syntax Description

record	Record to be monitored
<i>recordname</i>	Record name to be configured

Command Mode

- /exec/configure/config-ssx-monitor

redistribute bgp

```
{ redistribute { { bgp <as> } | { eigrp | isis | ospfv3 | rip } <ptag> | static | direct | amt | lisp } route-map {
<policy-name> | <rtr_pol_name> } } | { no redistribute { { bgp <as> } | { eigrp | isis | ospfv3 | rip } <ptag> |
static | direct | amt | lisp } [ route-map { <policy-name> | <rtr_pol_name> } ] }
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
eigrp	Enhanced Interior Gateway Protocol (EIGRP)
isis	ISO Intermediate-to-Intermediate (IS-IS)
ospfv3	Open Shortest Path First (OSPFv3)
rip	Routing Information Protocol (RIP)
ptag	Process Tag
static	Static
direct	Directly connected
amt	AMT anycast prefix
lisp	LISP EID-prefixes
route-map	Policy to constrain redistribution
policy-name	Route-map name
rtr_pol_name	An existing routing-rules policy

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

redistribute bgp eigrp isis ospf rip static direct amt lisp route-map

```
{ redistribute { bgp <as> | { eigrp | isis | ospf | rip } <ptag> | static | direct | amt | lisp } route-map {
<policy-name> | <rtr_pol_name> } } | { no redistribute { bgp <as> | { eigrp | isis | ospf | rip } <ptag> | static
| direct | amt | lisp } [ route-map { <policy-name> | <rtr_pol_name> } ] }
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	ISO Intermediate-to-Intermediate (IS-IS)
ospf	Open Shortest Path First (OSPFv2)
eigrp	Enhanced Interior Gateway Protocol (EIGRP)
rip	Routing Information Protocol (RIP)
<i>ptag</i>	Protocol Tag
static	Static
direct	Directly connected
amt	AMT anycast prefix
lisp	LISP EID-prefixes
route-map	Policy to constrain redistribution
<i>policy-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

redistribute filter route-map

[no] redistribute filter route-map { <map-name> | <rtr_pol_name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
filter	Filter redistributed routes
route-map	Route-map to constrain redistribution
<i>map-name</i>	A 'routing-rules' route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

redistribute filter route-map

[no] redistribute filter route-map { <map-name> | <rtr_pol_name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
filter	Filter redistributed routes
route-map	Route-map to constrain redistribution
<i>map-name</i>	A 'routing-rules' route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

redistribute maximum-prefix

```
{ redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout> ] ] } | { no redistribute maximum-prefix }
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
maximum-prefix	Maximum number of prefixes redistributed to protocol
<i>maximum</i>	Maximum number of IP prefixes redistributed
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Log a warning message when limit is exceeded
withdraw	(Optional) Withdraw all redistributed routes
<i>retries</i>	(Optional) Number of times to retry to get the redistributed routes again
<i>timeout</i>	(Optional) Timeout between each retries

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

redistribute maximum-prefix

```
redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout> ] ] | no redistribute maximum-prefix [ <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout> ] ] ]
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
maximum-prefix	Max number of prefixes redistributed
<i>maximum</i>	max number
<i>threshold</i>	(Optional) Threshold in %, at which message is generated
warning-only	(Optional) Warning msg is logged when max is reached
withdraw	(Optional) Withdraw all redistributed routes
<i>retries</i>	(Optional) No of times to retry to get redist routes again
<i>timeout</i>	(Optional) Time between the retries

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-ipv4

redistribute maximum-prefix

```
redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout> ] ] | no redistribute maximum-prefix [ <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout> ] ] ]
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
maximum-prefix	Max number of prefixes redistributed
<i>maximum</i>	max number
<i>threshold</i>	(Optional) Threshold in %, at which message is generated
warning-only	(Optional) Warning msg is logged when max is reached
withdraw	(Optional) Withdraw all redistributed routes
<i>retries</i>	(Optional) No of times to retry to get redist routes again
<i>timeout</i>	(Optional) Time between the retries

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

redistribute maximum-prefix

```
redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout>
] ] | no redistribute maximum-prefix [ <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries>
<timeout> ] ] ]
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
maximum-prefix	Max number of prefixes redistributed
<i>maximum</i>	max number
<i>threshold</i>	(Optional) Threshold in %, at which message is generated
warning-only	(Optional) Warning msg is logged when threshold is reached
withdraw	(Optional) Withdraw all redistributed routes
<i>retries</i>	(Optional) Number of attempts to receive redistributed routes after max is reached
<i>timeout</i>	(Optional) Retry interval

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

redistribute maximum-prefix

```
{ redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries> <timeout>
]] } | { no redistribute maximum-prefix <maximum> [ <threshold> ] [ warning-only | withdraw [ <retries>
<timeout> ] ] }
```

Syntax Description

no	Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
maximum-prefix	Maximum number of prefixes redistributed to protocol
<i>maximum</i>	Maximum number of IP prefixes redistributed
<i>threshold</i>	(Optional) Threshold value (%) at which to generate a warning message
warning-only	(Optional) Log a warning message when limit is exceeded
withdraw	(Optional) Withdraw all redistributed routes
<i>retries</i>	(Optional) Number of times to retry to get the redistributed routes again
<i>timeout</i>	(Optional) Timeout between each retries

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> | static | direct | amt } route-map { <map-name>
| <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
eigrp	Enhanced Interior Gateway Protocol
rip	RIP for IPv4
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
route-map	Route-map to constrain redistribution
<i>map-name</i>	A 'routing-rules' route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-af-ipv4

redistribute route-map

[no] redistribute { bgp <as> | { eigrp | isis | ospfv3 | rip } <tag> | static | direct | amt | lisp } route-map <map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	RIP redistribute routes from other routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
isis	Intermediate-to-intermediate (ISIS)
rip	Routing Information Protocol (RIP)
ospfv3	Open Shortest Path First (OSPFv3)
tag	Process tag
static	Static routes
direct	Directly connected routes
amt	AMT anycast prefix
lisp	LISP EID-prefixes
route-map	Policy to constrain redistribution
map-name	Route-map name

Command Mode

- /exec/configure/router-rip/router-rip-af-ipv6 /exec/configure/router-rip/router-rip-vrf-af-ipv6

redistribute route-map

[no] redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> | static | direct | amt | lisp } route-map <map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	RIP redistribute routes from other routing protocol
bgp	Border Gateway Protocol (BGP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
as	Autonomous system number
isis	Intermediate-to-intermediate (ISIS)
rip	Routing Information Protocol (RIP)
ospf	Open Shortest Path First (OSPFv2)
tag	Process tag
static	Static routes
direct	Directly connected routes
amt	AMT anycast prefix
lisp	LISP EID-prefixes
route-map	Policy to constrain redistribution
map-name	Route-map name

Command Mode

- /exec/configure/router-rip/router-rip-af-ipv4 /exec/configure/router-rip/router-rip-vrf-af-ipv4

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> | static | direct | amt } route-map { <map-name>
| <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
eigrp	Enhanced Interior Gateway Protocol
rip	RIP for IPv4
tag	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
route-map	Route-map to constrain redistribution
map-name	A 'routing-rules' route-map name
rtr_pol_name	An existing routing-rules policy

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-ipv4

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospfv3 | rip } <tag> | static | direct | amt } route-map { <map-name>
| <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv6
ospfv3	Open Shortest Path First (OSPF) V3
eigrp	Enhanced Interior Gateway Protocol
rip	RIP for IPv6 (RIPNG)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
route-map	Route-map to constrain redistribution
<i>map-name</i>	A 'routing-rules' route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospf | rip } <tag> | static | direct | amt | lisp } route-map {
<map-name> | <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
isis	IS-IS Routing for IPv4
ospf	Open Shortest Path First (OSPF)
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
tag	Process tag
static	Static routes
direct	Directly connected
lisp	LISP EID-prefixes
amt	AMT Anycast prefix
route-map	Route-map to constrain redistribution
map-name	Route-map name
rtr_pol_name	An existing routing-rules policy

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-ipv4

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospfv3 | rip } <tag> | static | direct | amt | lisp } route-map {
<map-name> | <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous system number
isis	IS-IS Routing for IPv4
ospfv3	Open Shortest Path First (OSPF) V3
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>tag</i>	Process tag
static	Static routes
direct	Directly connected
amt	AMT Anycast prefix
lisp	LISP EID-prefixes
route-map	Route-map to constrain redistribution
<i>map-name</i>	Route-map name
<i>rtr_pol_name</i>	An existing routing-rules policy

Command Mode

- /exec/configure/router-eigrp/router-eigrp-af-ipv6

redistribute route-map

[no] redistribute { static | direct | amt | lisp | am | hmm | { { eigrp | isis | ospf | rip } <tag> } } route-map <rmap-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Configure redistribution
static	Static routes
direct	Directly connected
isis	ISO IS-IS
ospf	Open Shortest Path First (OSPF)
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Protocol
amt	AMT anycast prefix
lisp	LISP EID-prefixes in the non-default VRF
am	AM routes (learned via ARP)
hmm	HMM prefix
route-map	Route-map applied to redistributed routes
<i>rmap-name</i>	Route-map name
<i>tag</i>	Source protocol tag

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv4

redistribute route-map

```
[no] redistribute { static | direct | amt | lisp | am | hmm | { { eigrp | isis | ospfv3 | rip } <tag> } } route-map
<rmap-name>
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Configure redistribution
static	Static routes
direct	Directly connected
isis	ISO IS-IS
ospfv3	Open Shortest Path First, version 3 (OSPFv3)
rip	Routing Information Protocol (RIP)
eigrp	Enhanced Interior Gateway Protocol
amt	AMT anycast prefix
lisp	LISP EID-prefixes in the non-default VRF
hmm	HMM prefix
am	AM routes (learned via ARP)
route-map	Route-map applied to redistributed routes
<i>rmap-name</i>	Route-map name
<i>tag</i>	Source protocol tag

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

redistribute route-map

```
[no] redistribute { bgp <as> | { eigrp | isis | ospfv3 | rip } <tag> | static | direct | amt } route-map { <map-name> | <rtr_pol_name> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
redistribute	Redistribute information from another routing protocol
bgp	Border Gateway Protocol (BGP)
as	Autonomous system number
isis	IS-IS Routing for IPv6
ospfv3	Open Shortest Path First (OSPF) V3
eigrp	Enhanced Interior Gateway Protocol
rip	RIP for IPv6 (RIPNG)
tag	Process tag
static	Static routes
direct	Directly connected
amt	AMT anycast prefix
route-map	Route-map to constrain redistribution
map-name	A 'routing-rules' route-map name
rtr_pol_name	An existing routing-rules policy

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-af-ipv6

redownload forwarding state

redownload forwarding [ipv4 | ipv6 | all] state

Syntax Description

redownload	redownload
forwarding	forwarding
ipv4	(Optional) ipv4
ipv6	(Optional) ipv6
all	(Optional) both ipv4 and ipv6
state	state

Command Mode

- /exec

redundancy-group

[no] redundancy-group

Syntax Description

no	(Optional) Negate a command or set its defaults
redundancy-group	Configure a redundancy-group node

Command Mode

- /exec/configure/if-nve

reference-bandwidth

[no] reference-bandwidth { <ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps }

Syntax Description

no	(Optional) Negate a command or set its defaults
reference-bandwidth	Change reference bandwidth used for setting interface metric
<i>ref-bw-mbps</i>	Bandwidth in Mbps (Default)
Mbps	(Optional) Specify in Mbps
<i>ref-bw-gbps</i>	Bandwidth in Gbps
Gbps	Specify in Gbps

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

reference-bandwidth

[no] reference-bandwidth { <ref-bw-mbps> [Mbps] | <ref-bw-gbps> Gbps }

Syntax Description

no	(Optional) Negate a command or set its defaults
reference-bandwidth	Change reference bandwidth used for setting interface metric
<i>ref-bw-mbps</i>	Bandwidth in Mbps (Default)
Mbps	(Optional) Specify in Mbps
<i>ref-bw-gbps</i>	Bandwidth in Gbps
Gbps	Specify in Gbps

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common /exec/configure/l2mp-isis/l2mp-isis-l2-topo

register-database-mapping

{ [no] register-database-mapping }

Syntax Description

no	(Optional) Negate a command or set its defaults
register-database-mapping	Register database-mapping EID-prefix to Map-Server

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

register-route-notifications

{ [no] register-route-notifications }

Syntax Description

no	(Optional) Negate a command or set its defaults
register-route-notifications	Register more-specific routes of the database-mapping EID-prefix to Map-Server

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

reload

reload

Syntax Description

reload	reboot the entire box
--------	-----------------------

Command Mode

- /exec

reload cancel

reload cancel

Syntax Description

reload	reboot the entire box
cancel	Cancel scheduling of the reload

Command Mode

- /exec

reload in

reload in <secs>

Syntax Description

reload	reboot the entire box
in	Schedule a reload after some time
<i>secs</i>	Reload after n seconds

Command Mode

- /exec

reload module

reload module <lem-aware-module>

Syntax Description

reload	reboot the entire box
module	reboot a specific module
<i>lem-aware-module</i>	please enter the module number

Command Mode

- /exec

reload module force-dnld

reload module <module> force-dnld

Syntax Description

reload	reboot the entire box
module	reboot a specific module
<i>module</i>	please enter the module number
force-dnld	reboot a specific module to force NetBoot and image download

Command Mode

- /exec

reload non-interruptive

reload non-interruptive

Syntax Description

reload	reboot the entire box
non-interruptive	Reboot without interruption

Command Mode

- /exec

reload power-cycle

reload power-cycle

Syntax Description

reload	reboot the entire box
power-cycle	Power cycle ADM

Command Mode

- /exec

reload sync-adjacency

reload sync-adjacency

Syntax Description

reload	reload with sync adjacency
sync-adjacency	Reload with ARP/ND sync adjacency

Command Mode

- /exec

reload sync-adjacency

reload sync-adjacency

Syntax Description

reload	reboot the entire box
sync-adjacency	Reload with sync adjacency

Command Mode

- /exec

reload timer

reload timer <secs>

Syntax Description

reload	reboot the entire box
timer	reboot after a delay <5-3600> seconds
<i>secs</i>	delay in seconds

Command Mode

- /exec

reload vdc

reload vdc <d-vdc>

Syntax Description

vdc	Restart the current vdc
reload	Power cycle
<i>d-vdc</i>	Enter Virtual Device Context <vdc-id>

Command Mode

- /exec

reload vdc

reload vdc

Syntax Description

vdc	Restart the current vdc
reload	Power cycle

Command Mode

- /exec

remark

```
{ [ <seqno> ] | no } remark <comment>
```

Syntax Description

<code>no</code>	Negate a command or set its defaults
<code>seqno</code>	(Optional) Sequence number
<code>remark</code>	Access list entry comment
<code>comment</code>	Comment, up to 100 characters

Command Mode

- `/exec/configure/arpacl /exec/configure/timerange`

remark

{ [<seqno>] | no } remark <comment>

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	(Optional) Sequence number
remark	Access list entry comment
<i>comment</i>	Comment, up to 100 characters

Command Mode

- /exec/configure/ipacl /exec/configure/ipv6acl

remark

```
{ [ <seqno> ] | no } remark <comment>
```

Syntax Description

no	Negate a command or set its defaults
<i>seqno</i>	(Optional) Sequence number
remark	Access list entry comment
<i>comment</i>	Comment, up to 100 characters

Command Mode

- /exec/configure/macacl

remote-as

```
{ remote-as <asn> } | { { no | default } remote-as [ <asn> ] }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
remote-as	Specify Autonomous System Number of the neighbor
<i>asn</i>	Autonomous System Number

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

remote-span

[no] remote-span

Syntax Description

no	(Optional) Negate a command or set its defaults
remote-span	Enable remote span VLAN

Command Mode

- /exec/configure/vlan

remote

```
remote { { ip address { <ipaddress> } | hostname <host_name> } [ port <port_no> ] [ vrf { <vrf-name> |
<vrf-known-name> } ] | port <port_no> | vrf { <vrf-name> | <vrf-known-name> } } | no remote { ip address
| hostname | port }
```

Syntax Description

no	Negate a command or set its defaults
remote	Configure remote machine information
ip	Configure IP features
address	Configure IP address
<i>ipaddress</i>	Enter ipv4 address information
hostname	Configure remote host name
<i>host_name</i>	Enter name of the remote host
port	(Optional) Configure remote host tcp port
<i>port_no</i>	(Optional) Configure the host tcp port number
vrf	(Optional) vrf via which the vCenter Server is reachable
<i>vrf-name</i>	(Optional) Specify the vrf-name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure/vmt-conn

remove-private-as

[no | default] remove-private-as [all | replace-as]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
remove-private-as	Remove private AS number from outbound updates
all	(Optional) All
replace-as	(Optional) Replace

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

reoptimize events link-up

[no] reoptimize events link-up | no reoptimize timers { delay { cleanup | installation } | frequency } | reoptimize timers { delay { cleanup <clean_sec> | installation <inst_sec> } | frequency <freq_sec> }

Syntax Description

no	(Optional) Negate a command or set its defaults
reoptimize	Reoptimization parameters
events	Reoptimization triggers
link-up	Reoptimize tunnels on link up events
timers	Reoptimization timers
delay	Delay reoptimization action
cleanup	Delay cleanup of reoptimized LSP
<i>clean_sec</i>	seconds to delay cleanup of replaced tunnel LSP
installation	Delay replacement of current LSP by reoptimized LSP
<i>inst_sec</i>	seconds to delay replacement of tunnel LSP
frequency	Interval between reoptimization scans
<i>freq_sec</i>	seconds between reoptimizations (0 disables reoptimization)

Command Mode

- /exec/configure/te

replay-protection

[no] replay-protection

Syntax Description

replay-protection	Enable replay-protection (the default use the no form to disable)
-------------------	---

Command Mode

- /exec/configure/cts-dot1x /exec/configure/cts-manual

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/outsel2

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/insel6

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/insel7

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/insel8

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtaah/inse19

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/insel10

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/inse119

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/outsel0

report

report [detail]

Syntax Description

report	Show trigger report summary
detail	(Optional) Show detailed trigger report

Command Mode

- /exec/elamtah/outsell

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/eramns/se13

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/elamns/sel4

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/eramns/se15

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/elamns/sel6

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/elamns/se17

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/elamns/outse10

report

report

Syntax Description

report	Show trigger report
--------	---------------------

Command Mode

- /exec/elanms/outse15

request-data-size

{ { no | default } request-data-size | request-data-size <bytes-in-payload> }

Syntax Description

no	
default	Set a command to its defaults
request-data-size	Request data size
<i>bytes-in-payload</i>	Number of bytes in payload

Command Mode

- /exec/configure/ip-sla/jitter

request-data-size

{ { no | default } request-data-size | request-data-size <bytes-in-payload> }

Syntax Description

no	
default	Set a command to its defaults
request-data-size	Request data size
<i>bytes-in-payload</i>	Number of bytes in payload

Command Mode

- /exec/configure/ip-sla/udp

request-data-size

{ { no | default } request-data-size | request-data-size <bytes-in-payload> }

Syntax Description

no	
default	Set a command to its defaults
request-data-size	Request data size
<i>bytes-in-payload</i>	Number of bytes in payload

Command Mode

- /exec/configure/ip-sla/icmpEcho

resequence access

```
resequence { { <ip_ipv6_mac_arp> access-list } | time-range } <name> <number> <increment>
```

Syntax Description

resequence	Resequence a list with sequence numbers
<i>ip_ipv6_mac_arp</i>	IP/IPv6/MAC/ARP
access-list	Resequence an access list
time-range	Resequence a time-range
<i>name</i>	List name
<i>number</i>	Starting sequence number
<i>increment</i>	Step to increment the sequence number

Command Mode

- /exec/configure

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamta/insel7

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamtah/insel6

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamta/insel8

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamtah/insel9

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamtah/insel10

reset

reset

Syntax Description

reset	Reset Trigger Filters
-------	-----------------------

Command Mode

- /exec/elamtah/insel19

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elamta/outsel0

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elamtah/outsel1

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elamta/outsel2

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elanms/se13

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elamns/sel4

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elanms/se15

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elamns/sel6

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elanms/se17

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elanms/outsel0

reset

reset

Syntax Description

reset	Reset Trigger conditions
-------	--------------------------

Command Mode

- /exec/elanms/outse15

restart amt

restart amt

Syntax Description

restart	Manually restart a component
amt	Restart the AMT multicast routing protocol

Command Mode

- /exec

restart bgp

restart bgp <as>

Syntax Description

restart	Manually restart a component
bgp	Border Gateway Protocol (BGP)
<i>as</i>	Autonomous

Command Mode

- /exec

restart eigrp

restart eigrp <eigrp-ptag>

Syntax Description

restart	Manually restart a component
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec

restart igmp

restart igmp

Syntax Description

restart	Manually restart a component
igmp	Restart the IGMP multicast routing protocol

Command Mode

- /exec

restart isis

restart isis <tag>

Syntax Description

restart	Manually restart a component
isis	Intermediate System to Intermediate System (IS-IS)
<i>tag</i>	Routing process tag

Command Mode

- /exec

restart msdp

restart msdp

Syntax Description

restart	Manually restart a component
msdp	Restart the MSDP multicast routing protocol

Command Mode

- /exec

restart ospf

restart ospf <tag>

Syntax Description

restart	Manually restart a component
ospf	Open Shortest Path First (OSPF)
<i>tag</i>	Process tag

Command Mode

- /exec

restart ospfv3

restart ospfv3 <tag>

Syntax Description

restart	Manually restart a component
ospfv3	Open Shortest Path First (OSPF) (Version 3)
<i>tag</i>	Process tag

Command Mode

- /exec

restart pim

restart pim

Syntax Description

restart	Manually restart a component
pim	Restart the PIM multicast routing protocol

Command Mode

- /exec

restart pim6

restart pim6

Syntax Description

restart	Manually restart a component
pim6	Restart the PIM6 multicast routing protocol

Command Mode

- /exec

restart rip

restart rip <tag>

Syntax Description

restart	Manually restart a component
rip	Routing Information Protocol (RIP)
<i>tag</i>	Process ID

Command Mode

- /exec

restart rsvp

restart rsvp

Syntax Description

restart	Manually restart a process
rsvp	RSVP process

Command Mode

- /exec

resync-database

resync-database

Syntax Description

resync-database	Re-synchronize switch-profile database
-----------------	--

Command Mode

- /exec/configure

retain route-target all

[no] retain route-target { all | route-map <rmap-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
retain	Retain the routes based on Target VPN Extended Communities
route-target	Specify Target VPN Extended Communities
all	All the routes regardless of Target-VPN community
route-map	Apply route-map to filter routes
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-l2vpn-vpls

retain route-target all

[no] retain route-target { all | route-map <rmap-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
retain	Retain the routes based on Target VPN Extended Communities
route-target	Specify Target VPN Extended Communities
all	All the routes regardless of Target-VPN community
route-map	Apply route-map to filter routes
<i>rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-af-vpnv4 /exec/configure/router-bgp/router-bgp-af-vpnv6
/exec/configure/router-bgp/router-bgp-af-link-state /exec/configure/router-bgp/router-bgp-af-l2vpn-evpn
/exec/configure/router-bgp/router-bgp-af-ipv4-mvpn /exec/configure/router-bgp/router-bgp-af-ipv6-mvpn

retransmit-interval

{ { retransmit-interval <interval> } | { no retransmit-interval [<interval>] } }

Syntax Description

no	Negate a command or set its defaults
retransmit-interval	Packet retransmission interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf3/router-ospf3-vlink /exec/configure/router-ospf3/vrf/router-ospf3-vlink

retransmit-interval

{ { retransmit-interval <interval> } | { no retransmit-interval [<interval>] } }

Syntax Description

no	Negate a command or set its defaults
retransmit-interval	Packet retransmission interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

retransmit-interval

{ { retransmit-interval <interval> } | { no retransmit-interval [<interval>] } }

Syntax Description

no	Negate a command or set its defaults
retransmit-interval	Packet retransmission interval
<i>interval</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

revision

revision <rev-id> | no revision [<rev-id>]

Syntax Description

no	Negate a command or set its defaults
revision	Set configuration revision number
<i>rev-id</i>	Configuration revision number

Command Mode

- /exec/configure/spanning-tree/mst/configuration

revocation-check crl

[no] revocation-check { crl [none] | none }

Syntax Description

no	(Optional) Negate a command or set its defaults
revocation-check	Configure trustpoint revocation check methods
crl	Configure revocation check using crl
none	(Optional) Configure revocation check using none
none	Configure revocation check using none

Command Mode

- /exec/configure/trustpoint

rewrite-evpn-rt-asn

[no | default] rewrite-evpn-rt-asn

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
rewrite-evpn-rt-asn	Auto generate RTs for EBGp neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn

rewrite-rt-asn

[no | default] rewrite-rt-asn

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
rewrite-rt-asn	Auto generate RTs for EBGP neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

rfc1583compatibility

[no] rfc1583compatibility

Syntax Description

no	(Optional) Negate a command or set its defaults
rfc1583compatibility	Configure 1583 compatibility for external path preferences

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

rip shutdown

[no] rip shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
rip	RIP configuration commands
shutdown	Shutdown RIP on this interface

Command Mode

- /exec/configure/if-igp

rmdir

rmdir { <uri0> | <uri1> }

Syntax Description

rmdir	Delete a directory
<i>uri0</i>	Delete a directory
<i>uri1</i>	Delete a directory on expansion flash

Command Mode

- /exec

rmon alarm absolute rising-threshold falling-threshold

```
rmon alarm <i0> <s0> <i1> { absolute | delta } rising-threshold <i2> [ <i3> ] falling-threshold <i4> [ <i5> ]
[ owner <s1> ] | no rmon alarm <i0>
```

Syntax Description

no	Negate a command or set its defaults
rmon	Remote Monitoring
alarm	Configure an RMON alarm
<i>i0</i>	Alarm number
<i>s0</i>	MIB object to monitor
<i>i1</i>	Sample interval
absolute	Test each sample directly
delta	Test delta between samples
rising-threshold	Configure the rising threshold
<i>i2</i>	Rising threshold value
<i>i3</i>	(Optional) Event to fire on rising threshold crossing
falling-threshold	Configure the falling threshold
<i>i4</i>	Falling threshold value
<i>i5</i>	(Optional) Event to fire on falling threshold crossing
owner	(Optional) Specify an owner for the alarm
<i>s1</i>	(Optional) Alarm owner

Command Mode

- /exec/configure

rmon event

rmon event <i0> [log] [trap <s0>] [description <s1>] [owner <s2>] | no rmon event <i0>

Syntax Description

no	Negate a command or set its defaults
rmon	Remote Monitoring
event	Configure an RMON event
<i>i0</i>	Event number
log	(Optional) Generate RMON log when the event fires
trap	(Optional) Generate SNMP trap when event fires
<i>s0</i>	(Optional) SNMP community string
description	(Optional) Specify a description of the event
<i>s1</i>	(Optional) Event description
owner	(Optional) Specify an owner for the event
<i>s2</i>	(Optional) Event owner

Command Mode

- /exec/configure

rmon hcalarm absolute startupalarm rising-threshold falling-threshold owner

rmon hcalarm <i0> <s0> <i1> { absolute | delta } startupalarm <i2> rising-threshold <i3> <i4> falling-threshold <i5> <i6> owner <s1> | no rmon hcalarm <i0>

Syntax Description

no	Negate a command or set its defaults
rmon	Remote Monitoring
hcalarm	Configure an High Capacity RMON alarm
<i>i0</i>	Alarm number
<i>s0</i>	MIB object to monitor
<i>i1</i>	Sample interval
absolute	Test each sample directly
delta	Test delta between samples
startupalarm	Configure alarm type
<i>i2</i>	Startup alarm type, rising(1) falling(2) risingorfalling(3)
rising-threshold	Configure the rising threshold
<i>i3</i>	Rising threshold value in bytes
<i>i4</i>	Event to fire on rising threshold crossing
falling-threshold	Configure the falling threshold
<i>i5</i>	Falling threshold value in bytes
<i>i6</i>	Event to fire on falling threshold crossing
owner	Specify an owner for the alarm
<i>s1</i>	Alarm owner

Command Mode

- /exec/configure

roaming-eid-prefix

```
{ [ no ] roaming-eid-prefix { <eid-prefix> | <eid-prefix6> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
roaming-eid-prefix	Configures what EID-prefixes allowed to roam
<i>eid-prefix</i>	IPv4 roaming EID-prefix

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

role feature-group name

[no] role feature-group name <arg6>

Syntax Description

no	(Optional) Negate a command or set its defaults
role	Configure roles
feature-group	Configure role feature-group
name	Feature-group name
<i>arg6</i>	Enter feature-group name

Command Mode

- /exec/configure

role name

[no] role name <arg2>

Syntax Description

no	(Optional) Negate a command or set its defaults
role	Configure roles
name	Enter the role name
<i>arg2</i>	Enter the role name

Command Mode

- /exec/configure

role priority

role priority <priority_value> | no role priority

Syntax Description

no	Negate a command or set its defaults
role	Role related configuration
priority	Configure priority to be used during vPC role (primary/secondary) election
<i>priority_value</i>	specify priority value

Command Mode

- /exec/configure/vpc-domain

rollback running-config checkpoint

```
rollback running-config { checkpoint <chkpoint_name> | file <file_uri> } [ best-effort | stop-at-first-failure | atomic ] [ verbose ]
```

Syntax Description

rollback	Rollback configuration
running-config	Rollback running configuration
checkpoint	Rollback running configuration to checkpoint
<i>chkpoint_name</i>	Checkpoint name
file	Rollback running configuration to configuration file
<i>file_uri</i>	Checkpoint file path
best-effort	(Optional) Skip errors and proceed with rollback
stop-at-first-failure	(Optional) Stop rollback at the first error
atomic	(Optional) Stop rollback and revert to original configuration (default)
verbose	(Optional) Show the execution log

Command Mode

- /exec

root-priority

[no] root-priority <root-pri>

Syntax Description

no	(Optional) Negate a command or set its defaults
root-priority	Set priority with which nodes becomes root
<i>root-pri</i>	Root priority value per topology

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common /exec/configure/l2mp-isis/l2mp-isis-l2-topo

route-map

[no] route-map { <rtmap-name> | <rtmap-name> } [permit | deny] <seq>

Syntax Description

no	Negate a command or set its defaults
route-map	Create route-map or enter route-map command mode
<i>rtmap-name</i>	Route-map name
<i>rtmap-name</i>	Known route-map name
permit	(Optional) Route map permits set operations
deny	(Optional) Route map denies set operations
<i>seq</i>	Sequence to insert to/delete from existing route-map entry

Command Mode

- /exec/configure

route-map

route-map <rtmap-name> [permit | deny]

Syntax Description

route-map	Create route-map or enter route-map command mode
<i>rtmap-name</i>	Route-map name
permit	(Optional) Route map permits set operations
deny	(Optional) Route map denies set operations

Command Mode

- /exec/configure

route-map

route-map <rtmap-name> [permit | deny] <seq>

Syntax Description

route-map	Create route-map or enter route-map command mode
<i>rtmap-name</i>	Route-map name
permit	(Optional) Route map permits set operations
deny	(Optional) Route map denies set operations
<i>seq</i>	Sequence to insert to/delete from existing route-map entry

Command Mode

- /exec/configure

route-map

[no] route-map { <rtmap-name> | <rtmap-name> } [permit | deny]

Syntax Description

no	Negate a command or set its defaults
route-map	Create route-map or enter route-map command mode
<i>rtmap-name</i>	Route-map name
<i>rtmap-name</i>	Known route-map name
permit	(Optional) Route map permits set operations
deny	(Optional) Route map denies set operations

Command Mode

- /exec/configure

route-map out

[no | default] route-map <rmap-name> { out | in }

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
route-map	Apply route-map to neighbor
<i>rmap-name</i>	Route-map name
out	Apply policy to outgoing routes
in	Apply policy to incoming routes

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
 /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

route-map pbr-statistics

```
route-map <route-map-name> pbr-statistics | no route-map { <route-map-name> | <route-map-name> }
pbr-statistics
```

Syntax Description

no	Negate a command or set its defaults
route-map	Create route-map or enter route-map command mode
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	Route-map name
<i>route-map-name</i>	Known route-map name
pbr-statistics	Statistics for policy based routing

Command Mode

- /exec/configure

route-reflector-client

[no | default] route-reflector-client

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
route-reflector-client	Configure a neighbor as Route reflector client

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

route-reflector-client

[no | default] route-reflector-client

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
route-reflector-client	Configure a neighbor as Route reflector client

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

route-target both auto

```
{ route-target both { auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } [ evpn | mvpn ] } | { no route-target
both [ auto [ evpn | mvpn ] | <ext-comm-rt-aa2nn4> [ evpn | mvpn ] | <ext-comm-rt-aa4nn2> [ evpn | mvpn
]] }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
both	Export And Import Target-VPN community
auto	Generate route target automatically
evpn	(Optional) Specify Target for EVPN routes
mvpn	(Optional) Specify Target for MVPN routes
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

route-target both auto

```
{ route-target both { auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } } | { no route-target both { auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
auto	Generate RT automatically
both	Export and Import Target-VPN community
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/evpn/evi

route-target export

```
{ route-target export { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } [ evpn | mvpn ] } | { no route-target
export { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } [ evpn | mvpn ] }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
export	Export Target-VPN community
evpn	(Optional) Specify Target for EVPN routes
mvpn	(Optional) Specify Target for MVPN routes
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

route-target export auto

```
{ route-target export { auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } } | { no route-target export {
auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
auto	Generate RT automatically
export	Export Target-VPN community
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/evpn/evi

route-target import

```
{ route-target import { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } [ evpn | mvpn ] } | { no route-target
import { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } [ evpn | mvpn ] }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
import	Import Target-VPN community
evpn	(Optional) Specify Target for EVPN routes
mvpn	(Optional) Specify Target for MVPN routes
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/vrf-af-ipv4 /exec/configure/vrf-af-ipv6

route-target import auto

```
{ route-target import { auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } } | { no route-target import
{ auto | <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } }
```

Syntax Description

no	Negate a command or set its defaults
route-target	Specify Target VPN Extended Communities
import	Import Target-VPN community
auto	Generate RT automatically
<i>ext-comm-rt-aa4nn2</i>	RT extcommunity in aa4:nn or ip:nn format
<i>ext-comm-rt-aa2nn4</i>	RT extcommunity in aa:nn format

Command Mode

- /exec/configure/evpn/evi

route delete dampen interval

[no] route delete dampen interval <time>

Syntax Description

no	(Optional) Negate a command or set its defaults
route	Display routing information
delete	Dampen route delete update to hardware
dampen	Dampen update to hardware
interval	Dampen interval
<i>time</i>	Dampen interval in seconds

Command Mode

- /exec/configure

router-guard ip multicast

[no] router-guard ip multicast [vlan <vlan_id>]

Syntax Description

no	(Optional) Negate a command or set its defaults
router-guard	Configures router guard for all interfaces
ip	Configure IP features
multicast	router-guard for multicast packet processing
vlan	(Optional) Configures router guard for specified vlan only(only in trunk ports)
<i>vlan_id</i>	(Optional) Specify vlan-id

Command Mode

- /exec/configure/if-switching

router-guard ip multicast switchports

[no] router-guard ip multicast switchports

Syntax Description

no	(Optional) Negate a command or set its defaults
router-guard	Configures router guard for all interfaces
ip	Configure IP features
multicast	router-guard for multicast packet processing
switchports	configures on all switchports globally

Command Mode

- /exec/configure

router-id

[no] router-id { <interface> | <rid> }

Syntax Description

no	(Optional) Negate a command or set its defaults
router-id	Router-ID
<i>interface</i>	Interface to provide IP address for router-id
<i>rid</i>	IP address to become router-id

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv4

router-id

{ { router-id <id> } | { no router-id [<id>] } }

Syntax Description

no	Negate a command or set its defaults
router-id	Set OSPFv3 process router-id
<i>id</i>	Router ID Value

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

router-id

```
{ { [ eigrp ] router-id <id> } | { no [ eigrp ] router-id [ <id> ] } }
```

Syntax Description

no	Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
router-id	router-id for this EIGRP process
<i>id</i>	EIGRP Router-ID in IP address format

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

router-id

```
{ { router-id <id> } | { no router-id [ <id> ] } }
```

Syntax Description

no	Negate a command or set its defaults
router-id	Set OSPF process router-id
<i>id</i>	Router ID Value

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

router-id

```
router-id [ vrf { <vrf-name> | <vrf-known-name> } ] <interface> [ force ] | no router-id [ { vrf { <vrf-name> | <vrf-known-name> } | <interface> [ force ] } ]
```

Syntax Description

no	Negate a command or set its defaults
router-id	Select interface to prefer for LDP identifier address
vrf	(Optional) VRF Routing/Forwarding instance information
<i>vrf-name</i>	(Optional) VPN Routing/Forwarding instance name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>interface</i>	
force	(Optional) Forcibly change the LDP router id

Command Mode

- /exec/configure/ldp

router-id

[no] router-id <router-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
router-id	Specify the IP address to use as router-id
<i>router-id</i>	Manually configured router identifier

Command Mode

- /exec/configure/router-bgp/vrf-cmds

router-preference maximum

[no] router-preference maximum <prefopts>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>prefopts</i>	

Command Mode

- /exec/configure/config-ra-guard

router bgp

[no] router bgp <as>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
bgp	Border Gateway Protocol (BGP)
as	Autonomous

Command Mode

- /exec/configure

router eigrp

[no] router eigrp <eigrp-ptag>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
eigrp	Enhanced Interior Gateway Routing Protocol (EIGRP)
<i>eigrp-ptag</i>	Process tag

Command Mode

- /exec/configure

router isis

[no] router isis <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
isis	Intermediate System to Intermediate System (IS-IS)
<i>tag</i>	Routing process tag

Command Mode

- /exec/configure

router ospf

[no] router ospf <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
ospf	Open Shortest Path First (OSPF)
<i>tag</i>	Process tag

Command Mode

- /exec/configure

router ospfv3

[no] router ospfv3 <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
ospfv3	Open Shortest Path First (OSPF) (Version 3)
<i>tag</i>	Process tag

Command Mode

- /exec/configure

router rip

[no] router rip <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
router	Enable a routing process
rip	Routing Information Protocol (RIP)
<i>tag</i>	Process ID

Command Mode

- /exec/configure

routing-context vrf

routing-context vrf <vrf-known-name>

Syntax Description

routing-context	Set the routing context
vrf	The new routing-context VRF
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec

rsakeypair

[no] rsakeypair <s0> [<i0>]

Syntax Description

no	(Optional) Negate a command or set its defaults
rsakeypair	Configure trustpoint rsa key-pair details
s0	key-pair label
i0	(Optional) key-pair size

Command Mode

- /exec/configure/trustpoint

rtr etr eid

[no] { rtr | etr | eid } { <locator> | <locator6> } [strict | probe] + <seq>

Syntax Description

no	(Optional) Negate a command or set its defaults
rtr	Configure RTR in ELP ordered list
etr	Configure ETR in ELP ordered list
eid	Configure EID in ELP ordered list
<i>locator</i>	IPv4 locator for RTR/ETR or EID
strict	(Optional) ELP hop must be used in Explicit Locator Path
probe	(Optional) RLOC-probe next-hop in ELP
<i>seq</i>	Sequence to insert or delete RTR/ETR/EID ELP entry

Command Mode

- /exec/configure/lisp-elp /exec/configure/vrf/lisp-elp

rule

```
rule <number> { <action> } { { <permission> [ <featuretype> <name> ] } } | no rule <number>
```

Syntax Description

<code>no</code>	Negate a command or set its defaults
<code>rule</code>	Enter the rule number
<i>number</i>	Enter the rule number
<i>action</i>	Action
<i>permission</i>	Permission
<i>featuretype</i>	(Optional) Feature type
<i>name</i>	(Optional) Enter the access entity name

Command Mode

- /exec/configure/role

rule command

rule <number> { <action> } { command <cmd_line> } | no rule <number>

Syntax Description

no	Negate a command or set its defaults
rule	Enter the rule number
<i>number</i>	Enter the rule number
<i>action</i>	Action
command	Command line
<i>cmd_line</i>	Enter the command (use space+' ' for command separator) e.g. config t role *

Command Mode

- /exec/configure/role

rule oid

rule <number> <action> <permission> oid <snmp_oid> | no rule <number>

Syntax Description

no	Negate a command or set its defaults
rule	Enter the rule number
<i>number</i>	Enter the rule number
<i>action</i>	Action
<i>permission</i>	Permission
oid	SNMP oid (up to 32 elements)
<i>snmp_oid</i>	Enter snmp oid instance name

Command Mode

- /exec/configure/role

run-script

run-script <uri0>

Syntax Description

run-script	Run shell scripts
<i>uri0</i>	Enter script file name

Command Mode

- /exec

run2 guestshell

```
run2 guestshell [ { <cmd_args> } ]
```

Syntax Description

run2	execute/run program
guestshell	The guest shell Linux-bash
<i>cmd_args</i>	(Optional) The command to execute

Command Mode

- /exec

run bash

run bash [<cmd>]

Syntax Description

run	execute/run program
bash	linux-bash
<i>cmd</i>	(Optional) the command to execute

Command Mode

- /exec



S Commands

- [sak-expiry-time](#), on page 3805
- [sampling-rate prepost](#), on page 3806
- [sampling](#), on page 3807
- [sap hash-algorithm HMAC-SHA-1](#), on page 3808
- [sap modelist](#), on page 3809
- [sap pmk sap pmk use-dot1x](#), on page 3810
- [save](#), on page 3811
- [scale-factor module](#), on page 3812
- [scheduler aaa-authentication](#), on page 3813
- [scheduler enable](#), on page 3814
- [scheduler job name](#), on page 3815
- [scheduler logfile size](#), on page 3816
- [scheduler schedule name](#), on page 3817
- [scheduler transport email](#), on page 3818
- [scripting tcl init](#), on page 3819
- [scripting tcl recursion-limit](#), on page 3820
- [section](#), on page 3821
- [secure-handoff](#), on page 3822
- [security-level](#), on page 3823
- [security-policy](#), on page 3824
- [sed](#), on page 3825
- [send-community](#), on page 3826
- [send-community](#), on page 3827
- [send-community extended](#), on page 3828
- [send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l](#), on page 3829
- [send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l](#), on page 3831
- [send](#), on page 3833
- [send session](#), on page 3834
- [sender](#), on page 3835
- [sensor-group](#), on page 3836

- server, on page 3837
- server, on page 3838
- server, on page 3839
- server protocol ldap, on page 3840
- server protocol radius group, on page 3841
- server protocol xmpp ip, on page 3842
- service-policy-dynamic input, on page 3843
- service-policy, on page 3844
- service-policy, on page 3845
- service-policy, on page 3846
- service-policy input, on page 3847
- service-policy type network-qos, on page 3848
- service-policy type qos, on page 3849
- service-policy type queuing, on page 3850
- service-policy type queuing, on page 3851
- service-policy type queuing, on page 3852
- service password-recovery, on page 3853
- service unsupported-transceiver, on page 3854
- session-limit, on page 3855
- session domain-lookup, on page 3856
- session protection, on page 3857
- set-attached-bit, on page 3858
- set-overload-bit, on page 3859
- set-overload-bit, on page 3860
- set, on page 3861
- set, on page 3864
- set, on page 3865
- set, on page 3866
- set, on page 3867
- set, on page 3869
- set as-path prepend last-as tag, on page 3870
- set comm-list delete, on page 3871
- set community none additive internet local-AS, on page 3872
- set cos, on page 3873
- set cos, on page 3874
- set dampening, on page 3875
- set distance, on page 3876
- set drpvec, on page 3877
- set drpvec, on page 3883
- set extcomm-list delete, on page 3889
- set extcommunity 4byteas-generic transitive additive, on page 3890
- set extcommunity color, on page 3891
- set extcommunity cost, on page 3892
- set extcommunity rt additive, on page 3893
- set forwarding-address, on page 3894
- set ieth, on page 3895

- [set ieth, on page 3898](#)
- [set inner arp, on page 3901](#)
- [set inner ipv4, on page 3903](#)
- [set inner ipv4, on page 3905](#)
- [set inner ipv4, on page 3907](#)
- [set inner ipv6 src_ip, on page 3909](#)
- [set inner l2, on page 3910](#)
- [set inner l2, on page 3912](#)
- [set inner l2, on page 3914](#)
- [set inner l2 hg2, on page 3916](#)
- [set inner l2 hg2, on page 3918](#)
- [set inner l4, on page 3920](#)
- [set inner l4, on page 3921](#)
- [set inner l4, on page 3924](#)
- [set interface, on page 3925](#)
- [set interval find-new-host, on page 3926](#)
- [set interval sync-full-info, on page 3927](#)
- [set ip address prefix-list, on page 3928](#)
- [set ip default next-hop, on page 3929](#)
- [set ip default next-hop verify-availability, on page 3930](#)
- [set ip next-hop, on page 3931](#)
- [set ip next-hop peer-address, on page 3932](#)
- [set ip next-hop redist-unchanged, on page 3933](#)
- [set ip next-hop unchanged, on page 3934](#)
- [set ip next-hop verify-availability, on page 3935](#)
- [set ip precedence, on page 3936](#)
- [set ipv6 address prefix-list, on page 3937](#)
- [set ipv6 default next-hop, on page 3938](#)
- [set ipv6 default next-hop verify-availability, on page 3939](#)
- [set ipv6 next-hop, on page 3940](#)
- [set ipv6 next-hop peer-address, on page 3941](#)
- [set ipv6 next-hop redist-unchanged, on page 3942](#)
- [set ipv6 next-hop unchanged, on page 3943](#)
- [set ipv6 next-hop verify-availability, on page 3944](#)
- [set ipv6 precedence, on page 3945](#)
- [set label-index, on page 3946](#)
- [set level level-1 level-1-2 level-2, on page 3947](#)
- [set local-preference, on page 3948](#)
- [set metric, on page 3949](#)
- [set nssa-only, on page 3950](#)
- [set origin egp, on page 3951](#)
- [set origin egp igp incomplete, on page 3952](#)
- [set outer arp, on page 3953](#)
- [set outer arp, on page 3955](#)
- [set outer fcoe, on page 3957](#)
- [set outer ipv4, on page 3959](#)

- [set outer ipv4, on page 3961](#)
- [set outer ipv4, on page 3963](#)
- [set outer ipv6 src_ip, on page 3965](#)
- [set outer ipv6 src_ip, on page 3966](#)
- [set outer l2, on page 3967](#)
- [set outer l2, on page 3969](#)
- [set outer l2, on page 3971](#)
- [set outer l2 hg2, on page 3973](#)
- [set outer l4, on page 3975](#)
- [set outer l4, on page 3976](#)
- [set outer l4, on page 3979](#)
- [set path-selection advertise, on page 3982](#)
- [set pktrw, on page 3983](#)
- [set pktrw, on page 3990](#)
- [set pktrw, on page 3997](#)
- [set sb_info, on page 4003](#)
- [set sb_info, on page 4006](#)
- [set sideband, on page 4009](#)
- [set sideband, on page 4011](#)
- [set sideband, on page 4013](#)
- [set sideband, on page 4015](#)
- [set stats, on page 4018](#)
- [set tag, on page 4021](#)
- [set weight, on page 4022](#)
- [setup, on page 4023](#)
- [sflow, on page 4024](#)
- [sflow, on page 4025](#)
- [sflow data-source interface, on page 4026](#)
- [sflow data-source interface, on page 4027](#)
- [sflow extended switch, on page 4028](#)
- [shape, on page 4029](#)
- [shared-secret, on page 4031](#)
- [shut, on page 4032](#)
- [shutdown, on page 4033](#)
- [shutdown, on page 4034](#)
- [shutdown, on page 4035](#)
- [shutdown, on page 4036](#)
- [shutdown, on page 4037](#)
- [shutdown, on page 4038](#)
- [shutdown, on page 4039](#)
- [shutdown, on page 4040](#)
- [shutdown, on page 4041](#)
- [shutdown, on page 4042](#)
- [shutdown, on page 4043](#)
- [shutdown, on page 4044](#)
- [shutdown, on page 4045](#)

- shutdown, on page 4046
- shutdown, on page 4047
- shutdown, on page 4048
- shutdown, on page 4049
- shutdown, on page 4050
- shutdown, on page 4051
- shutdown, on page 4052
- shutdown, on page 4053
- shutdown, on page 4054
- shutdown, on page 4055
- shutdown, on page 4056
- shutdown, on page 4057
- shutdown, on page 4058
- shutdown, on page 4059
- shutdown, on page 4060
- shutdown, on page 4061
- shutdown, on page 4062
- shutdown, on page 4063
- shutdown, on page 4064
- shutdown, on page 4065
- shutdown, on page 4066
- shutdown, on page 4067
- shutdown, on page 4068
- shutdown, on page 4069
- shutdown, on page 4070
- shutdown force, on page 4071
- shutdown lan, on page 4072
- shutdown lan, on page 4073
- signalling advertise explicit-null, on page 4074
- signalling hello graceful-restart, on page 4075
- signalling hello graceful-restart refresh interval, on page 4076
- signalling hello graceful-restart refresh misses, on page 4077
- signalling hello graceful-restart send recovery-time, on page 4078
- signalling hello graceful-restart send restart-time, on page 4079
- signalling hello reroute, on page 4080
- signalling initial-retransmit-delay, on page 4081
- signalling patherr state-removal, on page 4082
- signalling rate-limit, on page 4083
- signalling refresh interval, on page 4084
- signalling refresh misses, on page 4085
- signalling refresh reduction, on page 4086
- signalling refresh reduction ack-delay, on page 4087
- signalling refresh reduction bundle-max-size, on page 4088
- signing level, on page 4089
- site-id, on page 4090
- site-of-origin, on page 4091

- [slave ipv4](#), on page 4092
- [sleep](#), on page 4093
- [sleep instance](#), on page 4094
- [slot](#), on page 4095
- [slot](#), on page 4096
- [smart-channel](#), on page 4097
- [smart-channel port-group](#), on page 4098
- [smtp-host smtp-port reply-to from](#), on page 4099
- [snapshot create](#), on page 4100
- [snapshot delete](#), on page 4101
- [snapshot delete ALL](#), on page 4102
- [snapshot section add](#), on page 4103
- [snapshot section delete](#), on page 4104
- [snmp-server aaa-user cache-timeout](#), on page 4105
- [snmp-server community](#), on page 4106
- [snmp-server community](#), on page 4107
- [snmp-server community use-acl](#), on page 4108
- [snmp-server contact](#), on page 4109
- [snmp-server context](#), on page 4110
- [snmp-server counter cache enable](#), on page 4111
- [snmp-server counter cache timeout](#), on page 4112
- [snmp-server enable traps](#), on page 4113
- [snmp-server enable traps bgp](#), on page 4114
- [snmp-server enable traps bgp cbgp2](#), on page 4115
- [snmp-server enable traps bgp cbgp2 threshold prefix](#), on page 4116
- [snmp-server enable traps bgp threshold prefix](#), on page 4117
- [snmp-server enable traps eigrp](#), on page 4118
- [snmp-server enable traps ospf](#), on page 4119
- [snmp-server enable traps ospf lsa](#), on page 4120
- [snmp-server enable traps ospf rate-limit](#), on page 4121
- [snmp-server enable traps ospfv3](#), on page 4122
- [snmp-server enable traps ospfv3 lsa](#), on page 4123
- [snmp-server enable traps ospfv3 lsa](#), on page 4124
- [snmp-server enable traps ospfv3 rate-limit](#), on page 4125
- [snmp-server enable traps storm-control trap-rate](#), on page 4126
- [snmp-server engineID local](#), on page 4127
- [snmp-server force-unload-feature](#), on page 4128
- [snmp-server globalEnforcePriv](#), on page 4129
- [snmp-server host](#), on page 4130
- [snmp-server host filter-vrf](#), on page 4131
- [snmp-server host source](#), on page 4132
- [snmp-server host use-vrf](#), on page 4133
- [snmp-server host use_vrf](#), on page 4134
- [snmp-server load-cond-feature](#), on page 4135
- [snmp-server load-mib](#), on page 4136
- [snmp-server location](#), on page 4137

- snmp-server mib community-map context, on page 4138
- snmp-server protocol enable, on page 4139
- snmp-server source-interface informs, on page 4140
- snmp-server source-interface traps, on page 4141
- snmp-server system-shutdown, on page 4142
- snmp-server tcp-session, on page 4143
- snmp-server user, on page 4144
- snmp-server user, on page 4145
- snmp ifmib ifalias long, on page 4147
- snmp trap link-status, on page 4148
- snmp trap link-status, on page 4149
- snmp trap link-status, on page 4150
- snmp trap link-status, on page 4151
- snmp trap link-status, on page 4152
- snmp trap link-status, on page 4153
- snsr-grp sample-interval, on page 4154
- sockets local-port-range, on page 4155
- soft-reconfiguration inbound, on page 4156
- soft-reconfiguration inbound, on page 4157
- soo auto, on page 4158
- sort, on page 4159
- source-address ipv4, on page 4160
- source-group, on page 4161
- source-interface, on page 4162
- source-interface, on page 4163
- source-interface, on page 4164
- source-interface, on page 4165
- source-interface, on page 4166
- source-interface, on page 4167
- source-interface hold-down-time, on page 4168
- source, on page 4169
- source, on page 4170
- source, on page 4171
- source, on page 4172
- source, on page 4173
- source, on page 4174
- source, on page 4175
- source, on page 4176
- source, on page 4177
- source, on page 4178
- source, on page 4179
- source copy-sys, on page 4180
- source filter ip, on page 4181
- source filter ip any any, on page 4182
- source forward-drops, on page 4183
- source group permit, on page 4184

- source interface, on page 4185
- source interface, on page 4186
- source ip, on page 4187
- source vlan, on page 4188
- spanning-tree bpdudfilter, on page 4189
- spanning-tree bpduguard, on page 4190
- spanning-tree bridge-domain, on page 4191
- spanning-tree bridge assurance, on page 4192
- spanning-tree cost, on page 4193
- spanning-tree cost auto, on page 4194
- spanning-tree domain, on page 4195
- spanning-tree domain clear statistics, on page 4196
- spanning-tree fcoe, on page 4197
- spanning-tree guard, on page 4198
- spanning-tree lc-issu, on page 4199
- spanning-tree lc-issu, on page 4200
- spanning-tree link-type, on page 4201
- spanning-tree loopguard default, on page 4202
- spanning-tree mode, on page 4203
- spanning-tree mst configuration, on page 4204
- spanning-tree mst configuration, on page 4205
- spanning-tree mst cost, on page 4206
- spanning-tree mst cost auto, on page 4207
- spanning-tree mst forward-time, on page 4208
- spanning-tree mst hello-time, on page 4209
- spanning-tree mst max-age, on page 4210
- spanning-tree mst max-hops, on page 4211
- spanning-tree mst port-priority, on page 4212
- spanning-tree mst pre-standard, on page 4213
- spanning-tree mst priority, on page 4214
- spanning-tree mst root, on page 4215
- spanning-tree mst simulate pvst, on page 4216
- spanning-tree mst simulate pvst global, on page 4217
- spanning-tree pathcost method, on page 4218
- spanning-tree port-priority, on page 4219
- spanning-tree port type, on page 4220
- spanning-tree port type edge bpdudfilter default, on page 4221
- spanning-tree port type edge bpduguard default, on page 4222
- spanning-tree port type edge default, on page 4223
- spanning-tree port type edge trunk, on page 4224
- spanning-tree port type network default, on page 4225
- spanning-tree pseudo-information, on page 4226
- spanning-tree vlan, on page 4227
- spanning-tree vlan forward-time, on page 4228
- spanning-tree vlan hello-time, on page 4229
- spanning-tree vlan max-age, on page 4230

- [spanning-tree vlan priority](#), on page 4231
- [spanning-tree vlan root](#), on page 4232
- [speed-group](#), on page 4233
- [speed](#), on page 4234
- [speed](#), on page 4235
- [speed](#), on page 4236
- [speed](#), on page 4237
- [speed](#), on page 4238
- [speed](#), on page 4239
- [speed](#), on page 4240
- [speed](#), on page 4241
- [speed auto](#), on page 4242
- [speed auto 100](#), on page 4243
- [speed auto 100 1000](#), on page 4244
- [speed auto 100 1000](#), on page 4245
- [speed auto 100](#), on page 4246
- [speed auto](#), on page 4247
- [spf-interval](#), on page 4248
- [spf-interval](#), on page 4249
- [spf-interval](#), on page 4250
- [spf mode incremental](#), on page 4251
- [sport](#), on page 4252
- [sport](#), on page 4253
- [src-intf](#), on page 4254
- [ssh](#), on page 4255
- [ssh6](#), on page 4256
- [ssh all](#), on page 4257
- [ssh cipher-mode weak](#), on page 4258
- [ssh idle](#), on page 4259
- [ssh key](#), on page 4260
- [ssh login-attempts](#), on page 4261
- [ssh login-gracetime](#), on page 4262
- [ssh port](#), on page 4263
- [ssh rekey max-data max-time](#), on page 4264
- [ssh server enable](#), on page 4265
- [ssx exporter](#), on page 4266
- [ssx monitor](#), on page 4267
- [ssx record](#), on page 4268
- [ssx system monitor](#), on page 4269
- [ssx system system-id](#), on page 4270
- [standby](#), on page 4271
- [standby ip](#), on page 4272
- [start-threshold](#), on page 4273
- [start](#), on page 4274
- [start](#), on page 4275
- [start](#), on page 4276

- start, on page 4277
- start, on page 4278
- start, on page 4279
- start, on page 4280
- start, on page 4281
- start, on page 4282
- start, on page 4283
- start, on page 4284
- start, on page 4285
- start, on page 4286
- start, on page 4287
- start, on page 4288
- start, on page 4289
- state, on page 4290
- state enabled, on page 4291
- statistics, on page 4292
- statistics, on page 4293
- statistics, on page 4294
- statistics collection-interval, on page 4295
- statistics per-entry, on page 4296
- statistics per-entry, on page 4297
- statistics per-entry, on page 4298
- statistics per-entry, on page 4299
- stats-reporting-period, on page 4300
- status, on page 4301
- status, on page 4302
- status, on page 4303
- status, on page 4304
- status, on page 4305
- status, on page 4306
- status, on page 4307
- stop-threshold, on page 4308
- stopbits, on page 4309
- stopbits 1, on page 4310
- storm-control-cpu, on page 4311
- storm-control, on page 4312
- streetaddress, on page 4313
- stub, on page 4314
- sub-switch vlan, on page 4315
- subscription, on page 4316
- summary-address, on page 4317
- summary-address, on page 4318
- summary-address, on page 4319
- summary-address, on page 4320
- suppress-arp, on page 4321
- suppress-fib-pending, on page 4322

- [suppress-fib-pending](#), on page 4323
- [suppress-inactive](#), on page 4324
- [suppress-inactive](#), on page 4325
- [suppress-signaling-protocol ldp](#), on page 4326
- [suppress mac-route](#), on page 4327
- [switch-id](#), on page 4328
- [switch-priority](#), on page 4329
- [switch-profile](#), on page 4330
- [switch-profile](#), on page 4331
- [switch-role border-leaf](#), on page 4332
- [switch-scope controller](#), on page 4333
- [switch pipeline](#), on page 4334
- [switchback](#), on page 4335
- [switching-mode fabric-speed 40g](#), on page 4336
- [switching-mode fast-to-slow-speed-cut-through](#), on page 4337
- [switching-mode store-forward](#), on page 4338
- [switchport](#), on page 4339
- [switchport](#), on page 4340
- [switchport access vlan](#), on page 4341
- [switchport access vlan](#), on page 4342
- [switchport access vlan](#), on page 4343
- [switchport autostate exclude](#), on page 4344
- [switchport backup interface](#), on page 4345
- [switchport backup interface](#), on page 4346
- [switchport backup interface multicast fast-convergence](#), on page 4347
- [switchport backup interface multicast fast-convergence](#), on page 4348
- [switchport backup interface preemption delay](#), on page 4349
- [switchport backup interface preemption delay](#), on page 4350
- [switchport backup interface preemption mode](#), on page 4351
- [switchport backup interface preemption mode](#), on page 4352
- [switchport beacon](#), on page 4353
- [switchport block unicast](#), on page 4354
- [switchport description](#), on page 4355
- [switchport dot1q ethertype](#), on page 4356
- [switchport dot1q ethertype](#), on page 4357
- [switchport duplex](#), on page 4358
- [switchport host](#), on page 4359
- [switchport ignore bit-errors](#), on page 4360
- [switchport isolated](#), on page 4361
- [switchport mac-learn disable](#), on page 4362
- [switchport mode](#), on page 4363
- [switchport mode](#), on page 4364
- [switchport mode](#), on page 4365
- [switchport mode](#), on page 4366
- [switchport mode](#), on page 4367
- [switchport mode](#), on page 4368

- [switchport mode monitor buffer-limit](#), on page 4369
- [switchport mode private-vlan](#), on page 4370
- [switchport mode private-vlan trunk](#), on page 4371
- [switchport monitor](#), on page 4372
- [switchport mtu](#), on page 4373
- [switchport owner](#), on page 4374
- [switchport port-security](#), on page 4375
- [switchport port-security aging time](#), on page 4376
- [switchport port-security aging type absolute](#), on page 4377
- [switchport port-security mac-address](#), on page 4378
- [switchport port-security mac-address sticky](#), on page 4379
- [switchport port-security maximum](#), on page 4380
- [switchport port-security violation](#), on page 4381
- [switchport priority extend cos](#), on page 4382
- [switchport private-vlan association trunk](#), on page 4383
- [switchport private-vlan host-association](#), on page 4384
- [switchport private-vlan mapping](#), on page 4385
- [switchport private-vlan mapping trunk](#), on page 4386
- [switchport private-vlan trunk allowed vlan](#), on page 4387
- [switchport private-vlan trunk native vlan](#), on page 4388
- [switchport promiscuous-mode off](#), on page 4389
- [switchport speed](#), on page 4390
- [switchport speed](#), on page 4391
- [switchport trunk allow-multi-tag](#), on page 4392
- [switchport trunk allowed vlan](#), on page 4393
- [switchport trunk allowed vsan](#), on page 4394
- [switchport trunk allowed vsan](#), on page 4395
- [switchport trunk mode](#), on page 4396
- [switchport trunk mode](#), on page 4397
- [switchport trunk native vlan](#), on page 4398
- [switchport trunk pruning vlan except add remove none all](#), on page 4399
- [switchport virtual-ethernet-bridge](#), on page 4400
- [switchport vlan mapping](#), on page 4401
- [switchport vlan mapping all](#), on page 4402
- [switchport vlan mapping all dot1q-tunnel](#), on page 4403
- [switchport vlan mapping all dot1q-tunnel](#), on page 4404
- [switchport vlan mapping dot1q-tunnel](#), on page 4405
- [switchport vlan mapping dot1q-tunnel allowed-vlan](#), on page 4406
- [switchport vlan mapping enable](#), on page 4407
- [switchport voice vlan](#), on page 4408
- [switchport voice vlan](#), on page 4409
- [switchto vdc](#), on page 4410
- [sync-peers destination](#), on page 4411
- [sync-snmp-password](#), on page 4412
- [sync-snmp-password](#), on page 4413
- [sync-snmp-password](#), on page 4414

- [system-mac, on page 4415](#)
- [system-mac, on page 4416](#)
- [system-priority, on page 4417](#)
- [system, on page 4418](#)
- [system, on page 4419](#)
- [system acl, on page 4421](#)
- [system auto-collect tech-support, on page 4422](#)
- [system cores, on page 4423](#)
- [system default interface-vlan autostate, on page 4424](#)
- [system default interface, on page 4425](#)
- [system default interface, on page 4426](#)
- [system default switchport, on page 4427](#)
- [system default switchport shutdown, on page 4428](#)
- [system default tx-credit double-queue, on page 4429](#)
- [system dot1q-tunnel transit, on page 4430](#)
- [system fabric-mode full-rate, on page 4431](#)
- [system fabric core-vlans, on page 4432](#)
- [system fabric dynamic-vlans, on page 4433](#)
- [system fast-reload stabilization-timer, on page 4434](#)
- [system hap-reset, on page 4435](#)
- [system hap-reset, on page 4436](#)
- [system health check bootflash, on page 4437](#)
- [system heartbeat, on page 4438](#)
- [system heartbeat, on page 4439](#)
- [system high-multicast-priority, on page 4440](#)
- [system inband queuing, on page 4441](#)
- [system inband queuing, on page 4442](#)
- [system interface shutdown, on page 4443](#)
- [system jumbomtu, on page 4444](#)
- [system kgdb, on page 4445](#)
- [system kgdb, on page 4446](#)
- [system login block-for, on page 4447](#)
- [system login block-for attempts within, on page 4448](#)
- [system login quiet-mode, on page 4449](#)
- [system login quiet-mode access-class, on page 4450](#)
- [system memory-thresholds minor severe critical, on page 4451](#)
- [system mode maintenance, on page 4452](#)
- [system mode maintenance always-use-custom-profile, on page 4453](#)
- [system mode maintenance maint-delay, on page 4454](#)
- [system mode maintenance on-reload reset-reason, on page 4455](#)
- [system mode maintenance snapshot-delay, on page 4456](#)
- [system mode maintenance timeout, on page 4457](#)
- [system module emon-enhanced, on page 4458](#)
- [system module failure-action shutdown, on page 4459](#)
- [system mrouting, on page 4460](#)
- [system poap, on page 4461](#)

- [system poap](#), on page 4462
- [system pss shrink](#), on page 4463
- [system qos](#), on page 4464
- [system routing unknown-unicast-flood](#), on page 4465
- [system security compliance common-criteria](#), on page 4466
- [system shutdown fan-direction mismatch](#), on page 4467
- [system simulate fan-presence](#), on page 4468
- [system standby manual-boot](#), on page 4469
- [system standby manual-boot](#), on page 4470
- [system startup-config init](#), on page 4471
- [system startup-config unlock](#), on page 4472
- [system statistics](#), on page 4473
- [system statistics](#), on page 4474
- [system switch-mode](#), on page 4475
- [system switchover](#), on page 4476
- [system switchover force](#), on page 4477
- [system timeout](#), on page 4478
- [system trace](#), on page 4479
- [system urpf disable](#), on page 4480
- [system vlan long-name](#), on page 4481
- [system vlan reserve](#), on page 4482
- [system vrf-member-change retain-l3-config](#), on page 4483
- [system watchdog](#), on page 4484
- [system watchdog](#), on page 4485
- [system watchdog kgdb](#), on page 4486
- [system watchdog kgdb](#), on page 4487

sak-expiry-time

[no] sak-expiry-time <ts>

Syntax Description

sak-expiry-time	Time in seconds to force SAK rekey
<i>ts</i>	time in seconds

Command Mode

- /exec/configure/macsec-policy

sampling-rate prepost

[no] sampling-rate { pre-trigger <pre-sample-rate> } { post-trigger <post-sample-rate> }

Syntax Description

no	(Optional) Negate the command
sampling-rate	Configure sampling-rate parameters
pre-trigger	Pre-trigger parameters
<i>pre-sample-rate</i>	Transactions to be captured out of 16 samples (1-16)
post-trigger	Post-trigger parameters
<i>post-sample-rate</i>	Transactions to be captured out of 16 samples (1-16)

Command Mode

- /exec/configure/pkt-drop

sampling

sampling <sampling_range> | no sampling

Syntax Description

no	Negate a command or set its defaults
sampling	Set the sampling range for SPAN packets.
<i>sampling_range</i>	Sampling range: N = every Nth packet will be spanned

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

sap hash-algorithm HMAC-SHA-1

{ [no] sap hash-algorithm HMAC-SHA-1 } | { sap hash-algorithm HMAC-MD5 }

Syntax Description

sap	Specify preferred SAP negotiation parameters
hash-algorithm	Hashing Algorithm to use during SAP protocol
HMAC-SHA-1	use HMAC-SHA-1 for hashing (default is HMAC-MD5)
HMAC-MD5	use HMAC-MD5 for hashing

Command Mode

- /exec/configure/cts-dot1x /exec/configure/cts-manual

sap modelist

[no] sap modelist <mode_opt>

Syntax Description

sap	Specify preferred SAP negotiation parameters
modelist	encryption mode
<i>mode_opt</i>	modelist options

Command Mode

- /exec/configure/cts-dot1x

sap pmk sap pmk use-dot1x

```
sap pmk <pmk> [ left-zero-padded ] [ modelist <mode_opt> ] | sap pmk use-dot1x [ modelist <mode_opt> ]
| no sap
```

Syntax Description

sap	Specify preferred SAP negotiation parameters
pmk	pairwise master key
<i>pmk</i>	32 byte value specified as a string
left-zero-padded	(Optional) Pad with zeros on the left if PMK length is less than 32 bytes
modelist	(Optional) encryption mode
<i>mode_opt</i>	(Optional) modelist options
<i>modelist</i>	(Optional) <mode_opt>
use-dot1x	Use pmk generated after dot1x authentication. Use dot1x commands to configure dot1x on this port

Command Mode

- /exec/configure/cts-manual

save

save <uri0>

Syntax Description

save	Save the current configuration session to uri
<i>uri0</i>	Enter the complete uri where the session is to be stored

Command Mode

- /exec/configure

scale-factor module

[no] scale-factor <sf-value> module <module-number>

Syntax Description

no	(Optional) Negate a command or set its defaults
scale-factor	Scale factor
<i>sf-value</i>	Specify scale factor value from 0.10 to 2.00
module	Module
<i>module-number</i>	specify module number

Command Mode

- /exec/configure/ctrl-plane

scheduler aaa-authentication

```
{ scheduler aaa-authentication { password { 0 <s0> | 7 <s1> | <s2> } | username <s3> password { 01 <s4> | 71 <s5> | <s6> } } | no scheduler aaa-authentication { password [ { 0 <s0> | 7 <s1> | <s2> } ] | username <s3> password [ { 01 <s4> | 71 <s5> | <s6> } ] } }
```

Syntax Description

no	Negate a command or set its defaults
scheduler	Config commands for scheduler
aaa-authentication	Password for AAA authentication(of logged in user)
password	Specify the password of logged in user(for AAA authentication)
0	Password (clear text) of logged in user
s0	password (clear text) of logged in user
7	Encrypted password of logged in user
s1	Encrypted password (for AAA authentication)
s2	Password (clear text) of logged in user
username	logged in user name
s3	user name (for AAA authentication)
password	Specify the password of logged in user(for AAA authentication)
01	Password (clear text) of logged in user
s4	password (clear text) of logged in user
71	Encrypted password of logged in user
s5	Encrypted password (for AAA authentication)
s6	Password (clear text) of logged in user

Command Mode

- /exec/configure

scheduler enable

[no] scheduler enable

Syntax Description

no	(Optional) Negate a command or set its defaults
scheduler	Config commands for scheduler
enable	Command to enable/disable features

Command Mode

- /exec/configure

scheduler job name

[no] scheduler job name <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
scheduler	Config commands for scheduler
job	Define a job
name	Specify a name for the job
s0	Name of the job

Command Mode

- /exec/configure

scheduler logfile size

{ scheduler logfile size <i0> | no scheduler logfile size [<i0>] }

Syntax Description

no	Negate a command or set its defaults
scheduler	Config commands for scheduler
logfile	Scheduler log file configuration
size	Specify the log file size
<i>i0</i>	Size of the file in KB

Command Mode

- /exec/configure

scheduler schedule name

[no] scheduler schedule name <s0>

Syntax Description

no	(Optional) Negate a command or set its defaults
scheduler	Config commands for scheduler
schedule	Define a schedule
name	Specify a name for the schedule
s0	Name of the schedule

Command Mode

- /exec/configure

scheduler transport email

```
{ scheduler transport email { from <s0> | reply-to <s1> | smtp-server <host0> [ port <i1> ] } | no scheduler transport email { from | reply-to | smtp-server } }
```

Syntax Description

no	Negate a command or set its defaults
scheduler	Config commands for scheduler
transport	Configure transport related configuration
email	Configure email transport related configuration
from	Configure from email address
<i>s0</i>	Provide from email address, example: SJ-9500-1@xyz.com
reply-to	Configure replyto email address
<i>s1</i>	Provide reply-to email address, example: admin@xyz.com
smtp-server	Configure SMTP server address
<i>host0</i>	SMTP server(DNS name or IPv4 or IPv6 address)
port	(Optional) Configure SMTP server port (default:25)
<i>i1</i>	(Optional) SMTP server port

Command Mode

- /exec/configure

scripting tcl init

scripting tcl init <uri0> | no scripting tcl init

Syntax Description

no	Negate a command or set its defaults
scripting	Configure scripting parameters
tcl	Specify scripting parameter for tcl
init	Specify init parameters
<i>uri0</i>	Tcl init script name

Command Mode

- /exec

scripting tcl recursion-limit

scripting tcl recursion-limit <limit> | no scripting tcl recursion-limit

Syntax Description

no	Negate a command or set its defaults
scripting	Configure scripting parameters
tcl	Specify scripting parameter for tcl
recursion-limit	Specify recursion-limit
<i>limit</i>	Specify limit

Command Mode

- /exec

section

| section <pattern>

Syntax Description

	Pipe command output to filter
section	show lines that include the pattern as well as the subsequent lines that are more indented than matching line
<i>pattern</i>	the pattern (regular expression) to match

Command Mode

- /output

secure-handoff

{ [no] secure-handoff }

Syntax Description

no	(Optional) Negate a command or set its defaults
secure-handoff	Confirm dynamic-eid discovery by probing for remote host

Command Mode

- /exec/configure/lisp-dynamic-eid /exec/configure/vrf/lisp-dynamic-eid

security-level

[no] security-level <seclvl>

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>seclvl</i>	

Command Mode

- /exec/configure/config-snoop-policy

security-policy

[no] security-policy <policy>

Syntax Description

security-policy	Configure Security policy
<i>policy</i>	Security Policy options

Command Mode

- /exec/configure/masec-policy

sed

| sed [-n] + <expr>

Syntax Description

	Pipe command output to filter
sed	Stream Editor
-n	(Optional) suppress automatic printing of pattern space
<i>expr</i>	Edition command (script)

Command Mode

- /output

send-community

[no | default] send-community [both | standard]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
send-community	Send Community attribute to this neighbor
both	(Optional) Send Standard and Extended Community attributes
standard	(Optional) Send Standard Community attribute

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

send-community

[no | default] send-community [both | extended | standard]

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
send-community	Send Community attribute to this neighbor
both	(Optional) Send Standard and Extended Community attributes
extended	(Optional) Send Extended Community attribute
standard	(Optional) Send Standard Community attribute

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

send-community extended

[no | default] send-community extended

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
send-community	Send Community attribute to this neighbor
extended	Send Extended Community attribute

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-evpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-link-state
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label


```
send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b
month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l
```

send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

```
{ { send-lifetime [ local ] <stime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g
| month_h | month_i | month_j | month_k | month_l } <sday> <syyear> { duration <dsec> | infinite | <etime>
{ month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j |
month_k | month_l } <eday> <eyear> } } | { no send-lifetime [ [ local ] <stime> { month_a | month_b | month_c
| month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <sday> <syyear>
{ duration <dsec> | infinite | <etime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g
| month_h | month_i | month_j | month_k | month_l } <eday> <eyear> } ] } }
```

Syntax Description

no	Negate a command or set its defaults
send-lifetime	Set send lifetime of macsec key
local	(Optional) Specify time in local timezone
<i>stime</i>	HH:MM:SS Time to start <0-23>:<0-59>:<0-59>
<i>etime</i>	HH:MM:SS Time to end <0-23>:<0-59>:<0-59>
month_a	
month_b	
month_c	
month_d	
month_e	
month_f	
month_g	
month_h	
month_i	
month_j	
month_k	
month_l	
<i>sday</i>	Day of the month to start

send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

<i>eday</i>	Day of the month to end
<i>syear</i>	Year to start
<i>eyear</i>	Year to end
duration	Set key lifetime duration
<i>dsec</i>	Duration in seconds
infinite	Never Expires

Command Mode

- /exec/configure/macseckeychain-key

```
send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b
month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l
```

send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

```
{ { send-lifetime [ local ] <stime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g
| month_h | month_i | month_j | month_k | month_l } <sday> <syyear> { duration <dsec> | infinite | <etime>
{ month_a | month_b | month_c | month_d | month_e | month_f | month_g | month_h | month_i | month_j |
month_k | month_l } <eday> <eyear> } } | { no send-lifetime [ [ local ] <stime> { month_a | month_b | month_c
| month_d | month_e | month_f | month_g | month_h | month_i | month_j | month_k | month_l } <sday> <syyear>
{ duration <dsec> | infinite | <etime> { month_a | month_b | month_c | month_d | month_e | month_f | month_g
| month_h | month_i | month_j | month_k | month_l } <eday> <eyear> } ] } }
```

Syntax Description

no	Negate a command or set its defaults
send-lifetime	Set send lifetime of key
local	(Optional) Specify time in local timezone
<i>stime</i>	HH:MM:SS Time to start <0-23>:<0-59>:<0-59>
<i>etime</i>	HH:MM:SS Time to end <0-23>:<0-59>:<0-59>
month_a	
month_b	
month_c	
month_d	
month_e	
month_f	
month_g	
month_h	
month_i	
month_j	
month_k	
month_l	
<i>sday</i>	Day of the month to start

send-lifetime month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l duration infinite month_a month_b month_c month_d month_e month_f month_g month_h month_i month_j month_k month_l

<i>eday</i>	Day of the month to end
<i>syear</i>	Year to start
<i>eyear</i>	Year to end
duration	Set key lifetime duration
<i>dsec</i>	Duration in seconds
infinite	Never Expires

Command Mode

- /exec/configure/keychain-key

send

send <line>

Syntax Description

send	Send message to open sessions
<i>line</i>	Send message (a line) to all open sessions

Command Mode

- /exec

send session

send session <s0> <line>

Syntax Description

send	Send message to open sessions
session	Send message to specific session
<i>s0</i>	Specify pts/tty device type
<i>line</i>	Enter a one line message

Command Mode

- /exec

sender

[no] sender

Syntax Description

no	(Optional) Negate a command or set its defaults
sender	Policies for a Sender

Command Mode

- /exec/configure/nbm-host-policy

sensor-group

[no] sensor-group <sgrp-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
sensor-group	Create a sensor group
<i>sgrp-id</i>	Identifier

Command Mode

- /exec/configure/telemetry

server

[no] server { <hostname> }

Syntax Description

no	(Optional) Negate a command or set its defaults
server	TACACS+ server name or IP address
<i>hostname</i>	IPV4/IPV6 address or DNS name

Command Mode

- /exec/configure/tacacs+

server

[no] server <host0>

Syntax Description

no	(Optional) Negate a command or set its defaults
server	LDAP server name
<i>host0</i>	LDAP server name

Command Mode

- /exec/configure/ldap

server

[no] server <hostipname>

Syntax Description

no	(Optional) Negate a command or set its defaults
server	RADIUS server name or IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name

Command Mode

- /exec/configure/radius

server protocol ldap

```
[no] server protocol ldap { ipv6 <ipv6addr> | ip <ipaddr> | host <hostname> } [ port <portnum> ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ enable-ssl ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
server	Configure database server
protocol	Configure database protocol
ldap	Use LDAP
ipv6	IPv6 address of server
ip	IP address of server
<i>ipaddr</i>	Enter IP address of server
host	Hostname of server
<i>hostname</i>	Enter hostname of server
port	(Optional) Port
<i>portnum</i>	(Optional) Enter port number
vrf	(Optional) vrf context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
enable-ssl	(Optional) LDAP server enable ssl

Command Mode

- /exec/configure/fabric-db

server protocol radius group

[no] server protocol radius group <groupname>

Syntax Description

no	(Optional) Negate a command or set its defaults
server	Configure database server
protocol	Configure database protocol
radius	Use RADIUS
group	AAA group
<i>groupname</i>	Enter AAA group name of servers

Command Mode

- /exec/configure/fabric-db

server protocol xmpp ip

```
[no] server protocol xmpp { ip <ipaddr> | host <hostname> } [ port <portnum> ] [ vrf { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
server	Configure database server
protocol	Configure database protocol
xmpp	Use XMPP
ip	IP address of server
<i>ipaddr</i>	Enter IP address of server
host	Hostname of server
<i>hostname</i>	Enter hostname of server
port	(Optional) Port
<i>portnum</i>	(Optional) Enter port number
vrf	(Optional) vrf context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

Command Mode

- /exec/configure/fabric-db

service-policy-dynamic input

[no] service-policy-dynamic input <policy_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy-dynamic	Attach a policy to control-plane interface
input	Input the policy name
<i>policy_name</i>	Name of the policy

Command Mode

- /exec/configure/ctrl-plane-dyn

service-policy

[no] service-policy [type qos] <inp-or-out> <pmap-name-qos> [no-stats]

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Configure service policy for an interface
type	(Optional) Specify the type of this policy
qos	(Optional) Qos policy
<i>inp-or-out</i>	
<i>pmap-name-qos</i>	Policy-map name __nil__ You must create a policy-map before using this command
no-stats	(Optional) Disable statistics for this policy

Command Mode

- /exec/configure/vlan

service-policy

[no] service-policy [type qos] <inp-or-out> <pmap-name-qos> [no-stats]

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Configure service policy for an interface
type	(Optional) Specify the type of this policy
qos	(Optional) Qos policy
<i>inp-or-out</i>	
<i>pmap-name-qos</i>	Policy-map name __nil__ You must create a policy-map before using this command
no-stats	(Optional) Disable statistics for this policy

Command Mode

- /exec/configure/if-set-qos /exec/configure/if-remote-ethernet /exec/configure/if-remote-ethernet-switch /exec/configure/if-fc /exec/configure/if-san-port-channel

service-policy

[no] service-policy [type qos] <pmap-name-qos>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Configure hierarchial policy-map
type	(Optional) Specify the type of this policy
qos	(Optional) Qos policy
<i>pmap-name-qos</i>	Policy-map name

Command Mode

- /exec/configure/policy-map/class

service-policy input

[no] service-policy input <policy_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Attach a policy to control-plane interface
input	Input the policy name
<i>policy_name</i>	Name of the policy

Command Mode

- /exec/configure/ctrl-plane

service-policy type network-qos

[no] service-policy type network-qos <pmap-name-nq>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Policy Map
type	Specify the type of this policy-map
network-qos	Network QoS policy
<i>pmap-name-nq</i>	Policy-map name

Command Mode

- /exec/configure/system/qos

service-policy type qos

[no] service-policy type qos <inp-only> <pmap-name-qos>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Policy Map
type	Specify the type of this policy-map
qos	System-level QoS policy
<i>inp-only</i>	
<i>pmap-name-qos</i>	Policy-map name __nil__ You must create a policy-map before using this command

Command Mode

- /exec/configure/system/qos

service-policy type queuing

[no] service-policy type queuing <pmap-name-que>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Set the inner policy-map
type	Specify the type of this policy
queuing	Queuing policy
<i>pmap-name-que</i>	Policy-map name __nil__ You must create a policy-map before using this command

Command Mode

- /exec/configure/policy-map/type/queuing/class

service-policy type queuing

[no] service-policy type queuing <inp-or-out> <pmap-name-que> [no-stats]

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Configure service policy for an interface
type	Specify the type of this policy
queuing	Queuing policy
<i>inp-or-out</i>	
<i>pmap-name-que</i>	Policy-map name
no-stats	(Optional) Disable statistics for this policy

Command Mode

- /exec/configure/if-set-que

service-policy type queuing

[no] service-policy type queuing <inp-or-out> <pmap-name-que>

Syntax Description

no	(Optional) Negate a command or set its defaults
service-policy	Policy Map
type	Specify the type of this policy-map
queuing	DCE Queuing policy
<i>inp-or-out</i>	
<i>pmap-name-que</i>	Policy-map name

Command Mode

- /exec/configure/system/qos

service password-recovery

[no] service password-recovery

Syntax Description

no	(Optional) Negate a command or set its defaults
service	Service
password-recovery	Configure password-recovery option of console

Command Mode

- /exec/configure

service unsupported-transceiver

[no] service unsupported-transceiver

Syntax Description

no	(Optional) Negate a command or set its defaults
service	Serviceability Commands
unsupported-transceiver	Configure support for transceivers not supported by Cisco

Command Mode

- /exec/configure

session-limit

[no] session-limit <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
session-limit	Set the max no of concurrent vsh sessions
<i>i0</i>	Max concurrent vsh sessions

Command Mode

- /exec/configure/line

session domain-lookup

session domain-lookup | no session domain-lookup

Syntax Description

session	Configure session preferences
no	Negate a command or set its defaults
domain-lookup	Session

Command Mode

- /exec

session protection

```
[no] session protection [ vrf { <vrf-name> | <vrf-known-name> } ] [ for <pfx-list> ] [ duration { <secs> | infinite } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
session	Configure session parameters
protection	Configure session protection parameters
vrf	(Optional) VRF Routing/Forwarding instance information
<i>vrf-name</i>	(Optional) VPN Routing/Forwarding instance name
<i>vrf-known-name</i>	(Optional) Known VRF name
for	(Optional) Prefix list to specify LDP peers
<i>pfx-list</i>	(Optional) Prefix list for LDP peers
duration	(Optional) Period to sustain session protection after loss of link discovery
<i>secs</i>	(Optional) Holdup time in seconds
infinite	(Optional) Protect session forever after loss of link discovery

Command Mode

- /exec/configure/ldp

set-attached-bit

[no] set-attached-bit

Syntax Description

no	(Optional) Negate a command or set its defaults
set-attached-bit	Configure L1 L2 router to set/unset attached bit in its L1 LSP

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-ipv6

set-overload-bit

```
[no] set-overload-bit | [ no ] set-overload-bit { always | on-startup { <secs> | [ <seconds> ] wait-for bgp <as>
} } [ suppress { [ interlevel ] [ external ] } ]
```

Syntax Description

no	Negate a command or set its defaults
set-overload-bit	Signal other routers not to use us for transit
always	Set the overload bit unconditionally
on-startup	Set the overload bit on IS-IS startup
<i>secs</i>	Clear the overload bit after an elapsed time in seconds
wait-for	Clear the overload bit when notified by a specific protocol
bgp	Border Gateway Protocol (BGP)
<i>seconds</i>	(Optional) Clear the overload bit after an elapsed time in seconds
<i>as</i>	Autonomous system number
suppress	(Optional) Suppress route redistribution if overload bit set
interlevel	(Optional) Suppress interlevel route redistribution
external	(Optional) Suppress external route redistribution

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

set-overload-bit

```
{ no set-overload-bit | [ no ] set-overload-bit { always | on-startup { <secs> | <seconds> } } }
```

Syntax Description

no	Negate a command or set its defaults
set-overload-bit	Signal other routers not to use us for transit
always	Set the overload bit unconditionally
on-startup	Set the overload bit on IS-IS startup
<i>secs</i>	Clear the overload bit after an elapsed time in seconds
<i>seconds</i>	Clear the overload bit after an elapsed time in seconds

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

set

```
[no] set { { cos <cos-val> } | { eth-src-mac-addr <src-mac-addr> } | { eth-dest-mac-addr <dest-mac-addr> }
| { vlan <vlan-number> } | { ip-tos <ip-tos-value> <ip-tos-mask> } | { out-interface <iface-list> } | { dscp [
tunnel ] { <dscp-val> | <dscp-enum> } } | { precedence [ prec-tunnel ] { <prec-val> | <prec-enum> } } | {
discard-class <dis-class-val> } | { qos-group <qos-grp-val> } | { { { cos1 cos2 } | { dscp1 dscp2 } | { prec1
prec2 } | { dis-class1 dis-class2 } | { dscp3 mpls-exp-imposition } | { mpls-exp-topmost dscp4 } | {
mpls-exp-topmost1 mpls-exp-topmost2 } } } | { mpls experimental { { topmost <exp-value> } | { imposition
<exp-value-imp> } } } | action-strip-vlan | action-drop-pkt | divert-action | copy-action | action-decrement-ttl
| forward-normal | goto-pmap <pmap-table-handle> }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
cos	IEEE 802.1Q class of service
cos1	IEEE 802.1Q class of service
cos2	IEEE 802.1Q class of service
<i>cos-val</i>	802.1Q Class of Service value
eth-dest-mac-addr	Action on Layer 2 destination MAC address
eth-src-mac-addr	Action on Layer 2 source MAC address
<i>src-mac-addr</i>	Layer 2 MAC Address
<i>dest-mac-addr</i>	Layer 2 MAC Address
vlan	Set the VLAN ID
<i>vlan-number</i>	VLAN NUMBER
ip-tos	Set the IPv4 TOS
<i>ip-tos-value</i>	IPv4 TOS Value
<i>ip-tos-mask</i>	IPV4 TOS Mask
out-interface	Output to a Specified Interface
<i>iface-list</i>	Physical Interface Name and Number or List
action-strip-vlan	Perform the action STRIP-VLAN-ID
action-drop-pkt	Perform the action Drop the Packet
divert-action	Divert the packets to Controller
copy-action	Copy the packets to Controller

action-decrement-ttl	Decrement TTL on the Packet
forward-normal	Forward the packets normally
goto-pmap	Goto pmap/table
<i>pmap-table-handle</i>	Pmap-table handle
dscp	DSCP in IP(v4) and IPv6 packets
dscp1	DSCP in IP(v4) and IPv6 packets
dscp2	DSCP in IP(v4) and IPv6 packets
tunnel	(Optional) Set DSCP in tunnel encapsulation
<i>dscp-val</i>	DSCP value
<i>dscp-enum</i>	
precedence	Precedence in IP(v4) and IPv6 packets
prec1	Precedence in IP(v4) and IPv6 packets
prec2	Precedence in IP(v4) and IPv6 packets
prec-tunnel	(Optional) Set Precedence in tunnel encapsulation
<i>prec-val</i>	IP Precedence value
<i>prec-enum</i>	
discard-class	Discard class
dis-class1	Discard class
dis-class2	Discard class
<i>dis-class-val</i>	Discard class value
qos-group	Qos-group
<i>qos-grp-val</i>	Qos-group value
mpls	Set MPLS label
experimental	Set MPLS experimental label
topmost	Set MPLS topmost label
imposition	Push the label and set new one on top
<i>exp-value</i>	MPLS value
<i>exp-value-imp</i>	MPLS value
dscp3	DSCP in IP(v4) and IPv6 packets

mpls-exp-imposition	mpls-exp-imposition
mpls-exp-topmost	mpls-exp-topmost
dscp4	DSCP in IP(v4) and IPv6 packets
mpls-exp-topmost1	mpls-exp-topmost
mpls-exp-topmost2	mpls-exp-topmost

Command Mode

- /exec/configure/policy-map/type/plc/class

set

```
[no] set { { cos [ inner ] <cos-val> } | { dscp [ tunnel ] { <dscp-val> | <opt_set_dscp> } } | { precedence [ tunnel1 ] { <prec-val> | <opt_set_prec> } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
cos	IEEE 802.1Q class of service
inner	(Optional) Set inner 802.1Q class of service in QinQ environment
<i>cos-val</i>	802.1Q Class of Service value
dscp	DSCP in IP(v4) and IPv6 packets
tunnel	(Optional) Set DSCP in tunnel encapsulation
<i>dscp-val</i>	DSCP value
<i>opt_set_dscp</i>	
precedence	Precedence in IP(v4) and IPv6 packets
tunnel1	(Optional) Set DSCP in tunnel encapsulation
<i>prec-val</i>	IP Precedence value
<i>opt_set_prec</i>	

Command Mode

- /exec/configure/pmap/class

set

set <paramname> <paramval>

Syntax Description

set	Set the parameter value
<i>paramname</i>	Enter the name of the parameter
<i>paramval</i>	Enter the parameter value

Command Mode

- /exec/configure/param-inst

set

```
[no] set { { dlb-disable } | { precedence [ prec-tunnel ] { <prec-val> | <prec-enum> } } | { dscp [ tunnel ] { <dscp-val> | <dscp-enum> } } | { cos <cos-val> } | { qos-group <qos-grp-val> } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
dlb-disable	Disable Dynamic Load Balancing
precedence	Precedence in IP(v4) and IPv6 packets
prec-tunnel	(Optional) Set Precedence in tunnel encapsulation
<i>prec-val</i>	IP Precedence value
<i>prec-enum</i>	
dscp	DSCP in IP(v4) and IPv6 packets
tunnel	(Optional) Set DSCP in tunnel encapsulation
<i>dscp-val</i>	DSCP value
<i>dscp-enum</i>	
cos	IEEE 802.1Q Class of Service
<i>cos-val</i>	802.1Q Class of Service value
qos-group	Qos-group
<i>qos-grp-val</i>	

Command Mode

- /exec/configure/policy-map/class

set

```
[no] set { { discard-class <dis-class-val> } | { { cos1 cos2 } | { dscp1 dscp2 } | { prec1 prec2 } | { dis-class1
dis-class2 } | { dscp3 mpls-exp-imposition } | { mpls-exp-topmost dscp4 } | { mpls-exp-topmost1
mpls-exp-topmost2 } } table <table-map-name> } | { mpls experimental { { topmost <exp-value> } | {
imposition <exp-value-imp> } } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
cos1	IEEE 802.1Q class of service
cos2	IEEE 802.1Q class of service
dscp1	DSCP in IP(v4) and IPv6 packets
dscp2	DSCP in IP(v4) and IPv6 packets
prec1	Precedence in IP(v4) and IPv6 packets
prec2	Precedence in IP(v4) and IPv6 packets
discard-class	Discard class
dis-class1	Discard class
dis-class2	Discard class
<i>dis-class-val</i>	Discard class value
table	Table defining mapping from input to output
<i>table-map-name</i>	Table-map name
mpls	Set MPLS label
experimental	Set MPLS experimental label
topmost	Set MPLS topmost label
imposition	Push the label and set new one on top
<i>exp-value</i>	MPLS value
<i>exp-value-imp</i>	MPLS value
dscp3	DSCP in IP(v4) and IPv6 packets
mpls-exp-imposition	mpls-exp-imposition
mpls-exp-topmost	mpls-exp-topmost

dscp4	DSCP in IP(v4) and IPv6 packets
mpls-exp-topmost1	mpls-exp-topmost
mpls-exp-topmost2	mpls-exp-topmost

Command Mode

- /exec/configure/policy-map/class

set

[no] set { load-sharing per-packet }

Syntax Description

set	Set attribute
load-sharing	Load sharing across ECMP by set out-of-order bit
per-packet	per MiM packet
no	(Optional) Negate a command or set its defaults

Command Mode

- /exec/configure/policy-map/class

set as-path prepend last-as tag

```
{ set as-path { prepend { last-as <lastas> | <as> + } | tag } } | { no set as-path { prepend [ last-as [ <lastas> ] | <as> + ] | tag } }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
as-path	Prepend string for a BGP AS-path attribute
prepend	Prepend to the AS-Path
last-as	Prepend last AS to the as-path
<i>lastas</i>	number of last-AS prepends
<i>as</i>	AS number
tag	Set the tag as an AS-path attribute
<i>as</i>	(Optional)

Command Mode

- /exec/configure/route-map

set comm-list delete

```
{ { set comm-list <name> delete } | { no set comm-list } }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
comm-list	set BGP community list (for deletion)
<i>name</i>	Community list name
delete	Delete matching communities

Command Mode

- /exec/configure/route-map

set community none additive internet local-AS

```
{ set community { none | { additive | internet | local-AS | no-advertise | no-export | <hex_num> | <number>
| <community> } + } } | { no set community [ { none | { additive | internet | local-AS | no-advertise | no-export
| <hex_num> | <number> | <community> } + } ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
community	Set BGP community attribute
additive	Add to existing community
internet	Internet (well-known community)
local-AS	Do not send outside local AS (well-known community)
no-advertise	Do not advertise to any peer (well-known community)
no-export	Do not export to next AS (well-known community)
none	No community attribute
<i>number</i>	Community number
<i>hex_num</i>	Community number in hex
<i>community</i>	Community number aa:nn format
<i>additive</i>	(Optional) internet

Command Mode

- /exec/configure/route-map

set cos

[no] set cos <cos-val>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
cos	IEEE 802.1Q Class of Service
<i>cos-val</i>	802.1Q Class of Service value

Command Mode

- /exec/configure/policy-map/type/queuing/class

set cos

[no] set cos <cos-val>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set attribute
cos	IEEE 802.1Q class of service
<i>cos-val</i>	802.1Q Class of Service value

Command Mode

- /exec/configure/policy-map/type/uf/class

set dampening

```
{ set dampening <halflife> <reuse> <supress> <duration> } | { no set dampening [ <halflife> <reuse> <supress> <duration> ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
dampening	Set BGP route flap dampening parameters
<i>halflife</i>	half-life time for the penalty
<i>reuse</i>	penalty to start reusing a route
<i>supress</i>	penalty to start suppressing a route
<i>duration</i>	Maximum duration to suppress a stable route

Command Mode

- /exec/configure/route-map

set distance

```
{ set distance <external-dist> [ <internal-dist> [ <local-dist> ] ] } | { no set distance }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
distance	Set the Administrative distance of route
<i>external-dist</i>	Administrative distance for IGP or EBGP routes
<i>internal-dist</i>	(Optional) Administrative distance for internal routes
<i>local-dist</i>	(Optional) Administrative distance for local routes

Command Mode

- /exec/configure/route-map

set drpvec

```

set drpvec { parse_err <parse_err> | outer_ids_g0 <outer_ids_g0> | outer_ids_g1 <outer_ids_g1> | outer_ids_g2
<outer_ids_g2> | outer_ids_g3 <outer_ids_g3> | outer_ids_g4 <outer_ids_g4> | outer_ids_g5 <outer_ids_g5>
| outer_ids_g6 <outer_ids_g6> | outer_ids_g7 <outer_ids_g7> | outer_xlate_miss <outer_xlate_miss> |
infra_encap_src_tep_miss <infra_encap_src_tep_miss> | infra_encap_type_mismatch
<infra_encap_type_mismatch> | uc_tenant_mytep_route_miss <uc_tenant_mytep_route_miss> |
uc_tenant_mytep_bridge_miss <uc_tenant_mytep_bridge_miss> | arp_nd_ucast_miss <arp_nd_ucast_miss>
| mc_dvif_miss <mc_dvif_miss> | shard_override_vlan_xlate_miss <shard_override_vlan_xlate_miss> |
fcf_check_failed <fcf_check_failed> | ttl_expired <ttl_expired> | security_group_deny <security_group_deny>
| mc_iic <mc_iic> | mc_gipo_miss <mc_gipo_miss> | vif_miss <vif_miss> | missing_vntag <missing_vntag>
| vlan_xlate_miss <vlan_xlate_miss> | ip_mtu_check_failure <ip_mtu_check_failure> | uc_rpf_failure
<uc_rpf_failure> | mc_rpf_failure <mc_rpf_failure> | l3_binding_failure <l3_binding_failure> |
nsh_not_allowed <nsh_not_allowed> | src_vlan_mbr <src_vlan_mbr> | nsh_src_sw_chk_failed
<nsh_src_sw_chk_failed> | l2mp_iic_failed <l2mp_iic_failed> | l2mp_on_ce_bd <l2mp_on_ce_bd> |
l2mp_encap_from_edge <l2mp_encap_from_edge> | l2mp_noencap_from_core <l2mp_noencap_from_core>
| outer_ttl_expired <outer_ttl_expired> | incorrect_vntag_type <incorrect_vntag_type> | l2mp_ftag_comp_miss
<l2mp_ftag_comp_miss> | ipv6_uc_link_local_cross_bd <ipv6_uc_link_local_cross_bd> |
ipv6_mc_sa_local_da_global_svi <ipv6_mc_sa_local_da_global_svi> | ipv6_mc_sa_local_da_global_l3if
<ipv6_mc_sa_local_da_global_l3if> | routing_disabled <routing_disabled> | fc_lookup_miss <fc_lookup_miss>
| no_sgt_from_core <no_sgt_from_core> | ip_self_fwd_failure <ip_self_fwd_failure> | acl_drop <acl_drop>
| smac_miss <smac_miss> | secure_mac_move <secure_mac_move> | non_secure_mac <non_secure_mac>
| l2_binding_failure <l2_binding_failure> | inner_ids_g0 <inner_ids_g0> | inner_ids_g1 <inner_ids_g1> |
inner_ids_g2 <inner_ids_g2> | inner_ids_g3 <inner_ids_g3> | inner_ids_g4 <inner_ids_g4> | inner_ids_g5
<inner_ids_g5> | inner_ids_g6 <inner_ids_g6> | inner_ids_g7 <inner_ids_g7> | infra_encap_src_tep_drop
<infra_encap_src_tep_drop> | split_horizon_check <split_horizon_check> | mc_fib_miss <mc_fib_miss> |
mc_l2_miss <mc_l2_miss> | uc_df_check_failure <uc_df_check_failure> | uc_pc_cfg_table_drop
<uc_pc_cfg_table_drop> | illegal_expl_null <illegal_expl_null> | mpls_lookup_miss <mpls_lookup_miss>
| outer_cbl_check <outer_cbl_check> | null_shard_with_e_bit_set <null_shard_with_e_bit_set> | lb_drop
<lb_drop> | nat_fragment <nat_fragment> | illegal_dce_pkt <illegal_dce_pkt> | dci_vnid_xlate_miss
<dci_vnid_xlate_miss> | dci_sclass_xlate_miss <dci_sclass_xlate_miss> | dci_2nd_uc_transit
<dci_2nd_uc_transit> } +

```

Syntax Description

set	Setup Trigger
drpvec	All drop vector fields
parse_err	Parse_Err
<i>parse_err</i>	Parse_Err
outer_ids_g0	Outer_Ids_G0
<i>outer_ids_g0</i>	Outer_Ids_G0
outer_ids_g1	Outer_Ids_G1
<i>outer_ids_g1</i>	Outer_Ids_G1
outer_ids_g2	Outer_Ids_G2

<i>outer_ids_g2</i>	Outer_Ids_G2
<i>outer_ids_g3</i>	Outer_Ids_G3
<i>outer_ids_g3</i>	Outer_Ids_G3
<i>outer_ids_g4</i>	Outer_Ids_G4
<i>outer_ids_g4</i>	Outer_Ids_G4
<i>outer_ids_g5</i>	Outer_Ids_G5
<i>outer_ids_g5</i>	Outer_Ids_G5
<i>outer_ids_g6</i>	Outer_Ids_G6
<i>outer_ids_g6</i>	Outer_Ids_G6
<i>outer_ids_g7</i>	Outer_Ids_G7
<i>outer_ids_g7</i>	Outer_Ids_G7
<i>outer_xlate_miss</i>	Outer_Xlate_Miss
<i>outer_xlate_miss</i>	Outer_Xlate_Miss
<i>infra_encap_src_tep_miss</i>	Infra_Encap_Src_Tep_Miss
<i>infra_encap_src_tep_miss</i>	Infra_Encap_Src_Tep_Miss
<i>infra_encap_type_mismatch</i>	Infra_Encap_Type_Mismatch
<i>infra_encap_type_mismatch</i>	Infra_Encap_Type_Mismatch
<i>uc_tenant_mytep_route_miss</i>	Uc_Tenant_Mytep_Route_Miss
<i>uc_tenant_mytep_route_miss</i>	Uc_Tenant_Mytep_Route_Miss
<i>uc_tenant_mytep_bridge_miss</i>	Uc_Tenant_Mytep_Bridge_Miss
<i>uc_tenant_mytep_bridge_miss</i>	Uc_Tenant_Mytep_Bridge_Miss
<i>arp_nd_ucast_miss</i>	Arp_Nd_Ucast_Miss
<i>arp_nd_ucast_miss</i>	Arp_Nd_Ucast_Miss
<i>mc_dvif_miss</i>	Mc_Dvif_Miss
<i>mc_dvif_miss</i>	Mc_Dvif_Miss
<i>shard_override_vlan_xlate_miss</i>	Shard_Override_Vlan_Xlate_Miss
<i>shard_override_vlan_xlate_miss</i>	Shard_Override_Vlan_Xlate_Miss
<i>fcf_check_failed</i>	Fcf_Check_Failed
<i>fcf_check_failed</i>	Fcf_Check_Failed

ttl_expired	Ttl_Expired
<i>ttl_expired</i>	Ttl_Expired
security_group_deny	Security_Group_Deny
<i>security_group_deny</i>	Security_Group_Deny
mc_iic	Mc_Iic
<i>mc_iic</i>	Mc_Iic
mc_gipo_miss	Mc_Gipo_Miss
<i>mc_gipo_miss</i>	Mc_Gipo_Miss
vif_miss	Vif_Miss
<i>vif_miss</i>	Vif_Miss
missing_vntag	Missing_Vntag
<i>missing_vntag</i>	Missing_Vntag
vlan_xlate_miss	Vlan_Xlate_Miss
<i>vlan_xlate_miss</i>	Vlan_Xlate_Miss
ip_mtu_check_failure	Ip_Mtu_Check_Failure
<i>ip_mtu_check_failure</i>	Ip_Mtu_Check_Failure
uc_rpf_failure	Uc_Rpf_Failure
<i>uc_rpf_failure</i>	Uc_Rpf_Failure
mc_rpf_failure	Mc_Rpf_Failure
<i>mc_rpf_failure</i>	Mc_Rpf_Failure
l3_binding_failure	L3_Binding_Failure
<i>l3_binding_failure</i>	L3_Binding_Failure
nsh_not_allowed	Nsh_Not_Allowed
<i>nsh_not_allowed</i>	Nsh_Not_Allowed
src_vlan_mbr	Src_Vlan_Mbr
<i>src_vlan_mbr</i>	Src_Vlan_Mbr
nsh_src_sw_chk_failed	Nsh_Src_Sw_Chk_Failed
<i>nsh_src_sw_chk_failed</i>	Nsh_Src_Sw_Chk_Failed
l2mp_iic_failed	L2Mp_Iic_Failed

<i>l2mp_iic_failed</i>	L2Mp_Iic_Failed
<i>l2mp_on_ce_bd</i>	L2Mp_On_Ce_Bd
<i>l2mp_on_ce_bd</i>	L2Mp_On_Ce_Bd
<i>l2mp_encap_from_edge</i>	L2Mp_Encap_From_Edge
<i>l2mp_encap_from_edge</i>	L2Mp_Encap_From_Edge
<i>l2mp_noencap_from_core</i>	L2Mp_Noencap_From_Core
<i>l2mp_noencap_from_core</i>	L2Mp_Noencap_From_Core
<i>outer_ttl_expired</i>	Outer_Ttl_Expired
<i>outer_ttl_expired</i>	Outer_Ttl_Expired
<i>incorrect_vntag_type</i>	Incorrect_Vntag_Type
<i>incorrect_vntag_type</i>	Incorrect_Vntag_Type
<i>l2mp_ftag_comp_miss</i>	L2Mp_Ftag_Comp_Miss
<i>l2mp_ftag_comp_miss</i>	L2Mp_Ftag_Comp_Miss
<i>ipv6_uc_link_local_cross_bd</i>	Ipv6_Uc_Link_Local_Cross_Bd
<i>ipv6_uc_link_local_cross_bd</i>	Ipv6_Uc_Link_Local_Cross_Bd
<i>ipv6_mc_sa_local_da_global_svi</i>	Ipv6_Mc_Sa_Local_Da_Global_Svi
<i>ipv6_mc_sa_local_da_global_svi</i>	Ipv6_Mc_Sa_Local_Da_Global_Svi
<i>ipv6_mc_sa_local_da_global_l3if</i>	Ipv6_Mc_Sa_Local_Da_Global_L3If
<i>ipv6_mc_sa_local_da_global_l3if</i>	Ipv6_Mc_Sa_Local_Da_Global_L3If
<i>routing_disabled</i>	Routing_Disabled
<i>routing_disabled</i>	Routing_Disabled
<i>fc_lookup_miss</i>	Fc_Lookup_Miss
<i>fc_lookup_miss</i>	Fc_Lookup_Miss
<i>no_sgt_from_core</i>	No_Sgt_From_Core
<i>no_sgt_from_core</i>	No_Sgt_From_Core
<i>ip_self_fwd_failure</i>	Ip_Self_Fwd_Failure
<i>ip_self_fwd_failure</i>	Ip_Self_Fwd_Failure
<i>acl_drop</i>	Acl_Drop
<i>acl_drop</i>	Acl_Drop

smac_miss	Smac_Miss
<i>smac_miss</i>	Smac_Miss
secure_mac_move	Secure_Mac_Move
<i>secure_mac_move</i>	Secure_Mac_Move
non_secure_mac	Non_Secure_Mac
<i>non_secure_mac</i>	Non_Secure_Mac
l2_binding_failure	L2_Binding_Failure
<i>l2_binding_failure</i>	L2_Binding_Failure
inner_ids_g0	Inner_Ids_G0
<i>inner_ids_g0</i>	Inner_Ids_G0
inner_ids_g1	Inner_Ids_G1
<i>inner_ids_g1</i>	Inner_Ids_G1
inner_ids_g2	Inner_Ids_G2
<i>inner_ids_g2</i>	Inner_Ids_G2
inner_ids_g3	Inner_Ids_G3
<i>inner_ids_g3</i>	Inner_Ids_G3
inner_ids_g4	Inner_Ids_G4
<i>inner_ids_g4</i>	Inner_Ids_G4
inner_ids_g5	Inner_Ids_G5
<i>inner_ids_g5</i>	Inner_Ids_G5
inner_ids_g6	Inner_Ids_G6
<i>inner_ids_g6</i>	Inner_Ids_G6
inner_ids_g7	Inner_Ids_G7
<i>inner_ids_g7</i>	Inner_Ids_G7
infra_encap_src_tep_drop	Infra_Encap_Src_Tep_Drop
<i>infra_encap_src_tep_drop</i>	Infra_Encap_Src_Tep_Drop
split_horizon_check	Split_Horizon_Check
<i>split_horizon_check</i>	Split_Horizon_Check
mc_fib_miss	Mc_Fib_Miss

<i>mc_fib_miss</i>	Mc_Fib_Miss
<i>mc_l2_miss</i>	Mc_L2_Miss
<i>mc_l2_miss</i>	Mc_L2_Miss
<i>uc_df_check_failure</i>	Uc_Df_Check_Failure
<i>uc_df_check_failure</i>	Uc_Df_Check_Failure
<i>uc_pc_cfg_table_drop</i>	Uc_Pc_Cfg_Table_Drop
<i>uc_pc_cfg_table_drop</i>	Uc_Pc_Cfg_Table_Drop
<i>illegal_expl_null</i>	Illegal_Expl_Null
<i>illegal_expl_null</i>	Illegal_Expl_Null
<i>mpls_lookup_miss</i>	Mpls_Lookup_Miss
<i>mpls_lookup_miss</i>	Mpls_Lookup_Miss
<i>outer_cbl_check</i>	Outer_Cbl_Check
<i>outer_cbl_check</i>	Outer_Cbl_Check
<i>null_shard_with_e_bit_set</i>	Null_Shard_With_E_Bit_Set
<i>null_shard_with_e_bit_set</i>	Null_Shard_With_E_Bit_Set
<i>lb_drop</i>	Lb_Drop
<i>lb_drop</i>	Lb_Drop
<i>nat_fragment</i>	Nat_Fragment
<i>nat_fragment</i>	Nat_Fragment
<i>illegal_dce_pkt</i>	Illegal_Dce_Pkt
<i>illegal_dce_pkt</i>	Illegal_Dce_Pkt
<i>dci_vnid_xlate_miss</i>	Dci_Vnid_Xlate_Miss
<i>dci_vnid_xlate_miss</i>	Dci_Vnid_Xlate_Miss
<i>dci_sclass_xlate_miss</i>	Dci_Sclass_Xlate_Miss
<i>dci_sclass_xlate_miss</i>	Dci_Sclass_Xlate_Miss
<i>dci_2nd_uc_transit</i>	Dci_2nd_Uc_Transit
<i>dci_2nd_uc_transit</i>	Dci_2nd_Uc_Transit

Command Mode

- /exec/elamtah/outsel

set drpvec

```
set drpvec { parse_err <parse_err> | outer_ids_g0 <outer_ids_g0> | outer_ids_g1 <outer_ids_g1> | outer_ids_g2
<outer_ids_g2> | outer_ids_g3 <outer_ids_g3> | outer_ids_g4 <outer_ids_g4> | outer_ids_g5 <outer_ids_g5>
| outer_ids_g6 <outer_ids_g6> | outer_ids_g7 <outer_ids_g7> | outer_xlate_miss <outer_xlate_miss> |
infra_encap_src_tep_miss <infra_encap_src_tep_miss> | infra_encap_type_mismatch
<infra_encap_type_mismatch> | uc_tenant_mytep_route_miss <uc_tenant_mytep_route_miss> |
uc_tenant_mytep_bridge_miss <uc_tenant_mytep_bridge_miss> | arp_nd_ucast_miss <arp_nd_ucast_miss>
| mc_dvif_miss <mc_dvif_miss> | shard_override_vlan_xlate_miss <shard_override_vlan_xlate_miss> |
fcf_check_failed <fcf_check_failed> | ttl_expired <ttl_expired> | security_group_deny <security_group_deny>
| mc_iic <mc_iic> | mc_gipo_miss <mc_gipo_miss> | vif_miss <vif_miss> | missing_vntag <missing_vntag>
| vlan_xlate_miss <vlan_xlate_miss> | ip_mtu_check_failure <ip_mtu_check_failure> | uc_rpf_failure
<uc_rpf_failure> | mc_rpf_failure <mc_rpf_failure> | l3_binding_failure <l3_binding_failure> |
nsh_not_allowed <nsh_not_allowed> | src_vlan_mbr <src_vlan_mbr> | nsh_src_sw_chk_failed
<nsh_src_sw_chk_failed> | l2mp_iic_failed <l2mp_iic_failed> | l2mp_on_ce_bd <l2mp_on_ce_bd> |
l2mp_encap_from_edge <l2mp_encap_from_edge> | l2mp_noencap_from_core <l2mp_noencap_from_core>
| outer_ttl_expired <outer_ttl_expired> | incorrect_vntag_type <incorrect_vntag_type> | l2mp_ftag_comp_miss
<l2mp_ftag_comp_miss> | ipv6_uc_link_local_cross_bd <ipv6_uc_link_local_cross_bd> |
ipv6_mc_sa_local_da_global_svi <ipv6_mc_sa_local_da_global_svi> | ipv6_mc_sa_local_da_global_l3if
<ipv6_mc_sa_local_da_global_l3if> | routing_disabled <routing_disabled> | fc_lookup_miss <fc_lookup_miss>
| no_sgt_from_core <no_sgt_from_core> | ip_self_fwd_failure <ip_self_fwd_failure> | acl_drop <acl_drop>
| smac_miss <smac_miss> | secure_mac_move <secure_mac_move> | non_secure_mac <non_secure_mac>
| l2_binding_failure <l2_binding_failure> | inner_ids_g0 <inner_ids_g0> | inner_ids_g1 <inner_ids_g1> |
inner_ids_g2 <inner_ids_g2> | inner_ids_g3 <inner_ids_g3> | inner_ids_g4 <inner_ids_g4> | inner_ids_g5
<inner_ids_g5> | inner_ids_g6 <inner_ids_g6> | inner_ids_g7 <inner_ids_g7> | infra_encap_src_tep_drop
<infra_encap_src_tep_drop> | split_horizon_check <split_horizon_check> | mc_fib_miss <mc_fib_miss> |
mc_l2_miss <mc_l2_miss> | uc_df_check_failure <uc_df_check_failure> | uc_pc_cfg_table_drop
<uc_pc_cfg_table_drop> | illegal_expl_null <illegal_expl_null> | mpls_lookup_miss <mpls_lookup_miss>
| outer_cbl_check <outer_cbl_check> | null_shard_with_e_bit_set <null_shard_with_e_bit_set> | lb_drop
<lb_drop> | nat_fragment <nat_fragment> | illegal_dce_pkt <illegal_dce_pkt> | dci_vnid_xlate_miss
<dci_vnid_xlate_miss> | dci_sclass_xlate_miss <dci_sclass_xlate_miss> | dci_2nd_uc_transit
<dci_2nd_uc_transit> } +
```

Syntax Description

set	Setup Trigger
drpvec	All drop vector fields
parse_err	Parse_Err
<i>parse_err</i>	Parse_Err
outer_ids_g0	Outer_Ids_G0
<i>outer_ids_g0</i>	Outer_Ids_G0
outer_ids_g1	Outer_Ids_G1
<i>outer_ids_g1</i>	Outer_Ids_G1
outer_ids_g2	Outer_Ids_G2

<i>outer_ids_g2</i>	Outer_Ids_G2
<i>outer_ids_g3</i>	Outer_Ids_G3
<i>outer_ids_g3</i>	Outer_Ids_G3
<i>outer_ids_g4</i>	Outer_Ids_G4
<i>outer_ids_g4</i>	Outer_Ids_G4
<i>outer_ids_g5</i>	Outer_Ids_G5
<i>outer_ids_g5</i>	Outer_Ids_G5
<i>outer_ids_g6</i>	Outer_Ids_G6
<i>outer_ids_g6</i>	Outer_Ids_G6
<i>outer_ids_g7</i>	Outer_Ids_G7
<i>outer_ids_g7</i>	Outer_Ids_G7
<i>outer_xlate_miss</i>	Outer_Xlate_Miss
<i>outer_xlate_miss</i>	Outer_Xlate_Miss
<i>infra_encap_src_tep_miss</i>	Infra_Encap_Src_Tep_Miss
<i>infra_encap_src_tep_miss</i>	Infra_Encap_Src_Tep_Miss
<i>infra_encap_type_mismatch</i>	Infra_Encap_Type_Mismatch
<i>infra_encap_type_mismatch</i>	Infra_Encap_Type_Mismatch
<i>uc_tenant_mytep_route_miss</i>	Uc_Tenant_Mytep_Route_Miss
<i>uc_tenant_mytep_route_miss</i>	Uc_Tenant_Mytep_Route_Miss
<i>uc_tenant_mytep_bridge_miss</i>	Uc_Tenant_Mytep_Bridge_Miss
<i>uc_tenant_mytep_bridge_miss</i>	Uc_Tenant_Mytep_Bridge_Miss
<i>arp_nd_ucast_miss</i>	Arp_Nd_Ucast_Miss
<i>arp_nd_ucast_miss</i>	Arp_Nd_Ucast_Miss
<i>mc_dvif_miss</i>	Mc_Dvif_Miss
<i>mc_dvif_miss</i>	Mc_Dvif_Miss
<i>shard_override_vlan_xlate_miss</i>	Shard_Override_Vlan_Xlate_Miss
<i>shard_override_vlan_xlate_miss</i>	Shard_Override_Vlan_Xlate_Miss
<i>fcf_check_failed</i>	Fcf_Check_Failed
<i>fcf_check_failed</i>	Fcf_Check_Failed

ttl_expired	Ttl_Expired
<i>ttl_expired</i>	Ttl_Expired
security_group_deny	Security_Group_Deny
<i>security_group_deny</i>	Security_Group_Deny
mc_iic	Mc_Iic
<i>mc_iic</i>	Mc_Iic
mc_gipo_miss	Mc_Gipo_Miss
<i>mc_gipo_miss</i>	Mc_Gipo_Miss
vif_miss	Vif_Miss
<i>vif_miss</i>	Vif_Miss
missing_vntag	Missing_Vntag
<i>missing_vntag</i>	Missing_Vntag
vlan_xlate_miss	Vlan_Xlate_Miss
<i>vlan_xlate_miss</i>	Vlan_Xlate_Miss
ip_mtu_check_failure	Ip_Mtu_Check_Failure
<i>ip_mtu_check_failure</i>	Ip_Mtu_Check_Failure
uc_rpf_failure	Uc_Rpf_Failure
<i>uc_rpf_failure</i>	Uc_Rpf_Failure
mc_rpf_failure	Mc_Rpf_Failure
<i>mc_rpf_failure</i>	Mc_Rpf_Failure
l3_binding_failure	L3_Binding_Failure
<i>l3_binding_failure</i>	L3_Binding_Failure
nsh_not_allowed	Nsh_Not_Allowed
<i>nsh_not_allowed</i>	Nsh_Not_Allowed
src_vlan_mbr	Src_Vlan_Mbr
<i>src_vlan_mbr</i>	Src_Vlan_Mbr
nsh_src_sw_chk_failed	Nsh_Src_Sw_Chk_Failed
<i>nsh_src_sw_chk_failed</i>	Nsh_Src_Sw_Chk_Failed
l2mp_iic_failed	L2Mp_Iic_Failed

<i>l2mp_iic_failed</i>	L2Mp_Iic_Failed
<i>l2mp_on_ce_bd</i>	L2Mp_On_Ce_Bd
<i>l2mp_on_ce_bd</i>	L2Mp_On_Ce_Bd
<i>l2mp_encap_from_edge</i>	L2Mp_Encap_From_Edge
<i>l2mp_encap_from_edge</i>	L2Mp_Encap_From_Edge
<i>l2mp_noencap_from_core</i>	L2Mp_Noencap_From_Core
<i>l2mp_noencap_from_core</i>	L2Mp_Noencap_From_Core
<i>outer_ttl_expired</i>	Outer_Ttl_Expired
<i>outer_ttl_expired</i>	Outer_Ttl_Expired
<i>incorrect_vntag_type</i>	Incorrect_Vntag_Type
<i>incorrect_vntag_type</i>	Incorrect_Vntag_Type
<i>l2mp_ftag_comp_miss</i>	L2Mp_Ftag_Comp_Miss
<i>l2mp_ftag_comp_miss</i>	L2Mp_Ftag_Comp_Miss
<i>ipv6_uc_link_local_cross_bd</i>	Ipv6_Uc_Link_Local_Cross_Bd
<i>ipv6_uc_link_local_cross_bd</i>	Ipv6_Uc_Link_Local_Cross_Bd
<i>ipv6_mc_sa_local_da_global_svi</i>	Ipv6_Mc_Sa_Local_Da_Global_Svi
<i>ipv6_mc_sa_local_da_global_svi</i>	Ipv6_Mc_Sa_Local_Da_Global_Svi
<i>ipv6_mc_sa_local_da_global_l3if</i>	Ipv6_Mc_Sa_Local_Da_Global_L3If
<i>ipv6_mc_sa_local_da_global_l3if</i>	Ipv6_Mc_Sa_Local_Da_Global_L3If
<i>routing_disabled</i>	Routing_Disabled
<i>routing_disabled</i>	Routing_Disabled
<i>fc_lookup_miss</i>	Fc_Lookup_Miss
<i>fc_lookup_miss</i>	Fc_Lookup_Miss
<i>no_sgt_from_core</i>	No_Sgt_From_Core
<i>no_sgt_from_core</i>	No_Sgt_From_Core
<i>ip_self_fwd_failure</i>	Ip_Self_Fwd_Failure
<i>ip_self_fwd_failure</i>	Ip_Self_Fwd_Failure
<i>acl_drop</i>	Acl_Drop
<i>acl_drop</i>	Acl_Drop

smac_miss	Smac_Miss
<i>smac_miss</i>	Smac_Miss
secure_mac_move	Secure_Mac_Move
<i>secure_mac_move</i>	Secure_Mac_Move
non_secure_mac	Non_Secure_Mac
<i>non_secure_mac</i>	Non_Secure_Mac
l2_binding_failure	L2_Binding_Failure
<i>l2_binding_failure</i>	L2_Binding_Failure
inner_ids_g0	Inner_Ids_G0
<i>inner_ids_g0</i>	Inner_Ids_G0
inner_ids_g1	Inner_Ids_G1
<i>inner_ids_g1</i>	Inner_Ids_G1
inner_ids_g2	Inner_Ids_G2
<i>inner_ids_g2</i>	Inner_Ids_G2
inner_ids_g3	Inner_Ids_G3
<i>inner_ids_g3</i>	Inner_Ids_G3
inner_ids_g4	Inner_Ids_G4
<i>inner_ids_g4</i>	Inner_Ids_G4
inner_ids_g5	Inner_Ids_G5
<i>inner_ids_g5</i>	Inner_Ids_G5
inner_ids_g6	Inner_Ids_G6
<i>inner_ids_g6</i>	Inner_Ids_G6
inner_ids_g7	Inner_Ids_G7
<i>inner_ids_g7</i>	Inner_Ids_G7
infra_encap_src_tep_drop	Infra_Encap_Src_Tep_Drop
<i>infra_encap_src_tep_drop</i>	Infra_Encap_Src_Tep_Drop
split_horizon_check	Split_Horizon_Check
<i>split_horizon_check</i>	Split_Horizon_Check
mc_fib_miss	Mc_Fib_Miss

<i>mc_fib_miss</i>	Mc_Fib_Miss
<i>mc_l2_miss</i>	Mc_L2_Miss
<i>mc_l2_miss</i>	Mc_L2_Miss
<i>uc_df_check_failure</i>	Uc_Df_Check_Failure
<i>uc_df_check_failure</i>	Uc_Df_Check_Failure
<i>uc_pc_cfg_table_drop</i>	Uc_Pc_Cfg_Table_Drop
<i>uc_pc_cfg_table_drop</i>	Uc_Pc_Cfg_Table_Drop
<i>illegal_expl_null</i>	Illegal_Expl_Null
<i>illegal_expl_null</i>	Illegal_Expl_Null
<i>mpls_lookup_miss</i>	Mpls_Lookup_Miss
<i>mpls_lookup_miss</i>	Mpls_Lookup_Miss
<i>outer_cbl_check</i>	Outer_Cbl_Check
<i>outer_cbl_check</i>	Outer_Cbl_Check
<i>null_shard_with_e_bit_set</i>	Null_Shard_With_E_Bit_Set
<i>null_shard_with_e_bit_set</i>	Null_Shard_With_E_Bit_Set
<i>lb_drop</i>	Lb_Drop
<i>lb_drop</i>	Lb_Drop
<i>nat_fragment</i>	Nat_Fragment
<i>nat_fragment</i>	Nat_Fragment
<i>illegal_dce_pkt</i>	Illegal_Dce_Pkt
<i>illegal_dce_pkt</i>	Illegal_Dce_Pkt
<i>dci_vnid_xlate_miss</i>	Dci_Vnid_Xlate_Miss
<i>dci_vnid_xlate_miss</i>	Dci_Vnid_Xlate_Miss
<i>dci_sclass_xlate_miss</i>	Dci_Sclass_Xlate_Miss
<i>dci_sclass_xlate_miss</i>	Dci_Sclass_Xlate_Miss
<i>dci_2nd_uc_transit</i>	Dci_2nd_Uc_Transit
<i>dci_2nd_uc_transit</i>	Dci_2nd_Uc_Transit

Command Mode

- /exec/elamtah/outsel2

set extcomm-list delete

```
{ { set extcomm-list <name> delete } | { no set extcomm-list [ <name> delete ] } }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
extcomm-list	set BGP extcommunity list (for deletion)
<i>name</i>	Extended Community list name
delete	Delete matching extcommunities

Command Mode

- /exec/configure/route-map

set extcommunity 4byteas-generic transitive additive

```
{ set extcommunity 4byteas-generic { { transitive <ext-comm-gen-trans> | non-transitive
<ext-comm-gen-nontrans> } + [ additive ] | additive | none } } | { no set extcommunity 4byteas-generic [ {
transitive <ext-comm-gen-trans> | non-transitive <ext-comm-gen-nontrans> } + [ additive ] | additive | none
] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
extcommunity	Set BGP extcommunity attribute
4byteas-generic	Generic extended community
additive	(Optional) Add to existing generic extcommunity
none	No extcommunity generic attribute
transitive	Transitive extended community
non-transitive	Non-Transitive extended community
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-trans</i>	(Optional) <ext-comm-gen-nontrans>

Command Mode

- /exec/configure/route-map

set extcommunity color

```
{ set extcommunity color <color-value> } | { no set extcommunity color [ <color-value> ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
extcommunity	Set BGP extcommunity attribute
color	Color Extended Community
<i>color-value</i>	Color Community value

Command Mode

- /exec/configure/route-map

set extcommunity cost

```
{ set extcommunity cost { [ igp | pre-bestpath ] <comm-id> <cost-value> } + } | { no set extcommunity cost
[ [ igp | pre-bestpath ] <comm-id> <cost-value> ] + }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
extcommunity	Set BGP extcommunity attribute
cost	Cost
igp	(Optional) Compare following IGP cost comparison
pre-bestpath	(Optional) Compare before all other steps in bestpath calculation
<i>comm-id</i>	Community ID
<i>cost-value</i>	Cost Community value
<i>comm-id</i>	(Optional) <cost-value>

Command Mode

- /exec/configure/route-map

set extcommunity rt additive

```
{ set extcommunity rt { { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } + [ additive ] | additive } } | {
no set extcommunity rt [ { <ext-comm-rt-aa2nn4> | <ext-comm-rt-aa4nn2> } + [ additive ] | additive ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
extcommunity	Set BGP extcommunity attribute
rt	Route-Target
additive	(Optional) Add to existing rt extcommunity
<i>ext-comm-rt-aa2nn4</i>	Extcommunity number
<i>ext-comm-rt-aa4nn2</i>	Extcommunity number
<i>ext-comm-rt-aa2nn4</i>	(Optional) <ext-comm-rt-aa4nn2>

Command Mode

- /exec/configure/route-map

set forwarding-address

[no] set forwarding-address

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
forwarding-address	Set the forwarding address

Command Mode

- /exec/configure/route-map

set ieth

```
set ieth { sof <sof_val> | hdr_type <hdr_type> | ext_hd <ext_hd> | opcode <opcode> | src_idx <src_idx> |
dst_idx <dst_idx> | src_chip <src_chip> | src_port <src_port> | dst_chip <dst_chip> | dst_port <dst_port> |
outer_bd <outer_bd> | bd <bd> | traceroute <traceroute> | dont_lrn <dont_lrn> | span <span> | alt_if_prof
<alt_if_prof> | ttl_bypass <ttl_bypass> | src_is_tunl <src_is_tunl> | dst_is_tunl <dst_is_tunl> | l2_tunl <l2_tunl>
| sup_tx <sup_tx> | sup_code <sup_code> | cos_de <cos_de> | tclass <tclass> | src_is_peer <src_is_peer> |
pkt_hash <pkt_hash> } +
```

Syntax Description

set	Setup Trigger
ieth	All iETH Hdr Fields
sof	Start of Frame
<i>sof_val</i>	Start of Frame
hdr_type	Header Type
<i>hdr_type</i>	Header Type
ext_hd	Ext hd
<i>ext_hd</i>	Ext hd
opcode	Opcode
<i>opcode</i>	Opcode
src_idx	Source Index
<i>src_idx</i>	Source Index
dst_idx	Destination Index
<i>dst_idx</i>	Destination Index
src_chip	Source Chip
<i>src_chip</i>	Source Chip
src_port	Source Port
<i>src_port</i>	Source Port
dst_chip	Destination Chip
<i>dst_chip</i>	Destination Chip
dst_port	Destination Port
<i>dst_port</i>	Destination Port

outer_bd	Outer BD
<i>outer_bd</i>	Outer BD
bd	BD
<i>bd</i>	BD
traceroute	Trace Route
<i>traceroute</i>	Trace Route
dont_lrn	Don't Learn
<i>dont_lrn</i>	Don't Learn
span	Span
<i>span</i>	Span
alt_if_prof	Alternate IF Profile
<i>alt_if_prof</i>	Alternate IF Profile
ttn_bypass	TTL Bypass
<i>ttn_bypass</i>	TTL Bypass
src_is_tunl	Source is Tunnel
<i>src_is_tunl</i>	Source is Tunnel
dst_is_tunl	Destination is Tunnel
<i>dst_is_tunl</i>	Destination is Tunnel
l2_tunl	L2 Tunnel
<i>l2_tunl</i>	L2 Tunnel
sup_tx	Sup Tx
<i>sup_tx</i>	Sup Tx
sup_code	Sup Code
<i>sup_code</i>	Sup Code
cos_de	Cos De
<i>cos_de</i>	Cos De
tclass	Tclass
<i>tclass</i>	Tclass
src_is_peer	Source is Peer

<i>src_is_peer</i>	Source is Peer
<i>pkt_hash</i>	Packet Hash
<i>pkt_hash</i>	Packet Hash

Command Mode

- /exec/elamtah/inse18

set ieth

```
set ieth { sof <sof_val> | hdr_type <hdr_type> | ext_hd <ext_hd> | opcode <opcode> | src_idx <src_idx> |
dst_idx <dst_idx> | src_chip <src_chip> | src_port <src_port> | dst_chip <dst_chip> | dst_port <dst_port> |
outer_bd <outer_bd> | bd <bd> | traceroute <traceroute> | dont_lrn <dont_lrn> | span <span> | alt_if_prof
<alt_if_prof> | ttl_bypass <ttl_bypass> | src_is_tunl <src_is_tunl> | dst_is_tunl <dst_is_tunl> | l2_tunl <l2_tunl>
| sup_tx <sup_tx> | sup_code <sup_code> | cos_de <cos_de> | tclass <tclass> | src_is_peer <src_is_peer> |
pkt_hash <pkt_hash> } +
```

Syntax Description

set	Setup Trigger
ieth	All iETH Hdr Fields
sof	Start of Frame
<i>sof_val</i>	Start of Frame
hdr_type	Header Type
<i>hdr_type</i>	Header Type
ext_hd	Ext hd
<i>ext_hd</i>	Ext hd
opcode	Opcode
<i>opcode</i>	Opcode
src_idx	Source Index
<i>src_idx</i>	Source Index
dst_idx	Destination Index
<i>dst_idx</i>	Destination Index
src_chip	Source Chip
<i>src_chip</i>	Source Chip
src_port	Source Port
<i>src_port</i>	Source Port
dst_chip	Destination Chip
<i>dst_chip</i>	Destination Chip
dst_port	Destination Port
<i>dst_port</i>	Destination Port

outer_bd	Outer BD
<i>outer_bd</i>	Outer BD
bd	BD
<i>bd</i>	BD
traceroute	Trace Route
<i>traceroute</i>	Trace Route
dont_lrn	Don't Learn
<i>dont_lrn</i>	Don't Learn
span	Span
<i>span</i>	Span
alt_if_prof	Alternate IF Profile
<i>alt_if_prof</i>	Alternate IF Profile
tth_bypass	TTL Bypass
<i>tth_bypass</i>	TTL Bypass
src_is_tunl	Source is Tunnel
<i>src_is_tunl</i>	Source is Tunnel
dst_is_tunl	Destination is Tunnel
<i>dst_is_tunl</i>	Destination is Tunnel
l2_tunl	L2 Tunnel
<i>l2_tunl</i>	L2 Tunnel
sup_tx	Sup Tx
<i>sup_tx</i>	Sup Tx
sup_code	Sup Code
<i>sup_code</i>	Sup Code
cos_de	Cos De
<i>cos_de</i>	Cos De
tclass	Tclass
<i>tclass</i>	Tclass
src_is_peer	Source is Peer

<i>src_is_peer</i>	Source is Peer
<i>pkt_hash</i>	Packet Hash
<i>pkt_hash</i>	Packet Hash

Command Mode

- /exec/elamtah/insel10

set inner arp

```
set inner arp { target-ip-addr <tipaddr> | target-mac-addr <tmac> | source-ip-addr <sipaddr> | source-mac-addr
<smac> | opcode <opcode_val> | prot-addr-len <prot_addr_len> | hw-addr-len <hw_addr_len> | protocol-type
<prot_type> | hardware-type <hw_type> | ether-type <etype> | payload-len <pyld_len> } +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
arp	ARP Fields
target-ip-addr	ARP Target IP Address
<i>tipaddr</i>	ARP Target IP Address
target-mac-addr	ARP Target MAC Address
<i>tmac</i>	ARP Target MAC Address
source-ip-addr	ARP Source IP Address
<i>sipaddr</i>	ARP Source IP Address
source-mac-addr	ARP Source MAC Address
<i>smac</i>	ARP Source MAC Address
opcode	ARP Opcode
<i>opcode_val</i>	ARP Opcode
prot-addr-len	ARP Protocol Address Length
<i>prot_addr_len</i>	ARP Protocol Address Length
hw-addr-len	ARP Hardware Address Length
<i>hw_addr_len</i>	ARP Hardware Address Length
protocol-type	ARP Protocol Type
<i>prot_type</i>	ARP Protocol Type
hardware-type	ARP Hardware Type
<i>hw_type</i>	ARP Hardware Type
ether-type	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP
<i>etype</i>	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP
payload-len	ARP Payload Length

<i>pyld_len</i>	ARP Payload Length
-----------------	--------------------

Command Mode

- /exec/elamta/insel7

set inner ipv4

```
set inner ipv4 { pyld-len <pyld_len> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val>
| packet-len <pkt_len> | more- frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> |
checksum <csum> | src_ip <sip> | dst_ip <dip> } +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
ipv4	IPv4 Fields
pyld-len	Payload Length
<i>pyld_len</i>	Payload Length
version	Version
<i>ver</i>	Version
header-len	Header Length
<i>hlen</i>	Header Length
dscp	Diff. Serv. Code Point
<i>dscp_val</i>	Diff. Serv. Code Point
ecn	Explicit Congestion Ntn
<i>ecn_val</i>	Explicit Congestion Ntn
packet-len	Packet Total Length
<i>pkt_len</i>	Packet Total Length
more-frags	More Fragments Available
<i>mf</i>	More Fragments Available
fragment-off	Fragments Offset
<i>fragoff</i>	Fragments Offset
ttl	Time to Live
<i>ttl_val</i>	Time to Live
next-protocol	Next Protocol
<i>nproto</i>	Next Protocol
checksum	Checksum

<i>csum</i>	Checksum
<i>src_ip</i>	Source IP Address
<i>sip</i>	Source IP Address
<i>dst_ip</i>	Destination IP Address
<i>dip</i>	Destination IP Address

Command Mode

- /exec/elamtah/insel7

set inner ipv4

set { inner | outer } ipv4 [{ l3-type <l3_type> | pyld-len <pyld_len> | v6-vld <v6_vld> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val> | packet-len <pkt_len> | more-frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> | checksum <csum> | src_ip <sip> | dst_ip <dip> }] +

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
outer	Mask and Match By Outer Packet Fields
ipv4	IPv4 Fields
l3-type	(Optional) L3 Packet Type
<i>l3_type</i>	(Optional) L3 Packet Type
pyld-len	(Optional) Payload Length
<i>pyld_len</i>	(Optional) Payload Length
v6-vld	(Optional) IPv6 Valid Information
<i>v6_vld</i>	(Optional) IPv6 Valid Information
version	(Optional) Version
<i>ver</i>	(Optional) Version
header-len	(Optional) Header Length
<i>hlen</i>	(Optional) Header Length
dscp	(Optional) Diff. Serv. Code Point
<i>dscp_val</i>	(Optional) Diff. Serv. Code Point
ecn	(Optional) Explicit Congestion Ntn
<i>ecn_val</i>	(Optional) Explicit Congestion Ntn
packet-len	(Optional) Packet Total Length
<i>pkt_len</i>	(Optional) Packet Total Length
more-frags	(Optional) More Fragments Available
<i>mf</i>	(Optional) More Fragments Available
fragment-off	(Optional) Fragments Offset
<i>fragoff</i>	(Optional) Fragments Offset

<code>ttl</code>	(Optional) Time to Live
<code>ttl_val</code>	(Optional) Time to Live
<code>next-protocol</code>	(Optional) Next(L4) Protocol
<code>nproto</code>	(Optional) Next(L4) Protocol
<code>checksum</code>	(Optional) Checksum
<code>csum</code>	(Optional) Checksum
<code>src_ip</code>	(Optional) Source IP Address
<code>sip</code>	(Optional) Source IP Address
<code>dst_ip</code>	(Optional) Destination IP Address
<code>dip</code>	(Optional) Destination IP Address

Command Mode

- /exec/elanms/sel6

set inner ipv4

```
set inner ipv4 [ { l3-type <l3_type> | pyld-len <pyld_len> | v6-vld <v6_vld> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val> | packet-len <pkt_len> | more-frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> | checksum <csum> | src_ip <sip> | dst_ip <dip> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
ipv4	IPv4 Fields
l3-type	(Optional) L3 Packet Type
<i>l3_type</i>	(Optional) L3 Packet Type
pyld-len	(Optional) Payload Length
<i>pyld_len</i>	(Optional) Payload Length
v6-vld	(Optional) IPv6 Valid Information
<i>v6_vld</i>	(Optional) IPv6 Valid Information
version	(Optional) Version
<i>ver</i>	(Optional) Version
header-len	(Optional) Header Length
<i>hlen</i>	(Optional) Header Length
dscp	(Optional) Diff. Serv. Code Point
<i>dscp_val</i>	(Optional) Diff. Serv. Code Point
ecn	(Optional) Explicit Congestion Ntn
<i>ecn_val</i>	(Optional) Explicit Congestion Ntn
packet-len	(Optional) Packet Total Length
<i>pkt_len</i>	(Optional) Packet Total Length
more-frags	(Optional) More Fragments Available
<i>mf</i>	(Optional) More Fragments Available
fragment-off	(Optional) Fragments Offset
<i>fragoff</i>	(Optional) Fragments Offset
ttl	(Optional) Time to Live

<i>ttl_val</i>	(Optional) Time to Live
next-protocol	(Optional) Next(L4) Protocol
<i>nproto</i>	(Optional) Next(L4) Protocol
checksum	(Optional) Checksum
<i>csum</i>	(Optional) Checksum
src_ip	(Optional) Source IP Address
<i>sip</i>	(Optional) Source IP Address
dst_ip	(Optional) Destination IP Address
<i>dip</i>	(Optional) Destination IP Address

Command Mode

- /exec/elanms/sel4

set inner ipv6 src_ip

set inner ipv6 { src_ip <src_ip> | dst_ip <dst_ip> } +

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
ipv6	IPv6 Fields
src_ip	Source IP Address
dst_ip	Destination IP Address

Command Mode

- /exec/elamtah/insel7

set inner l2

```
set inner l2 [ { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id> | cos
<cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif> |
vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
l2	All Layer 2 Fields
snap_vld	(Optional) SNAP Header Information Valid
<i>snap_vld</i>	(Optional) SNAP Header Information Valid
cntag_vld	(Optional) CNTag Information Valid
<i>cntag_vld</i>	(Optional) CNTag Information Valid
qtag_vld	(Optional) VLAN Tag Information Valid
<i>qtag_vld</i>	(Optional) VLAN Tag Information Valid
vlan	(Optional) VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	(Optional) VLAN Id
cos	(Optional) Class of Service
<i>cos_val</i>	(Optional) Class of Service Type
cfi	(Optional) CFI Setting
<i>cfi_vld</i>	(Optional) CFI Setting Valid
vntag_vld	(Optional) VNTAG Information Valid
<i>vntag_vld</i>	(Optional) VNTAG Information Valid
vntag_svif	(Optional) VNTAG Source vif
<i>vntag_svif</i>	(Optional) VNTAG Source vif
vntag_dvif	(Optional) VNTAG Destination vif
<i>vntag_dvif</i>	(Optional) VNTAG Destination vif
vntag_looped	(Optional) VNTAG Header Looped Valid
<i>vntag_loop</i>	(Optional) VNTAG Header Looped Valid
vntag_pointer	(Optional) VNTAG Header Pointer Valid

<i>vntag_p</i>	(Optional) VNTAG Header Pointer Valid
<i>src_mac</i>	(Optional) Source MAC Address
<i>smac</i>	(Optional) Source MAC Address Value
<i>dst_mac</i>	(Optional) Destination MAC Address
<i>dmac</i>	(Optional) Destination MAC Address Value

Command Mode

- /exec/elamns/sel4

set inner l2

```
set inner l2 { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id> | cos
<cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif> |
vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
l2	All Layer 2 Fields
snap_vld	SNAP Header Information Valid
<i>snap_vld</i>	SNAP Header Information Valid
cntag_vld	CNTag Information Valid
<i>cntag_vld</i>	CNTag Information Valid
qtag_vld	VLAN Tag Information Valid
<i>qtag_vld</i>	VLAN Tag Information Valid
vlan	VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	VLAN Id
cos	Class of Service
<i>cos_val</i>	Class of Service Type
cfi	CFI Setting
<i>cfi_vld</i>	CFI Setting Valid
vntag_vld	VNTAG Information Valid
<i>vntag_vld</i>	VNTAG Information Valid
vntag_svif	VNTAG Source vif
<i>vntag_svif</i>	VNTAG Source vif
vntag_dvif	VNTAG Destination vif
<i>vntag_dvif</i>	VNTAG Destination vif
vntag_looped	VNTAG Header Looped Valid
<i>vntag_loop</i>	VNTAG Header Looped Valid
vntag_pointer	VNTAG Header Pointer Valid

<i>vntag_p</i>	VNTAG Header Pointer Valid
<i>src_mac</i>	Source MAC Address
<i>smac</i>	Source MAC Address Value
<i>dst_mac</i>	Destination MAC Address
<i>dmac</i>	Destination MAC Address Value

Command Mode

- /exec/elamtah/inse17

set inner l2

```
set { inner | outer } l2 [ { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id>
| cos <cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif>
| vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
outer	Mask and Match By Outer Packet Fields
l2	All Layer 2 Fields
snap_vld	(Optional) SNAP Header Information Valid
<i>snap_vld</i>	(Optional) SNAP Header Information Valid
cntag_vld	(Optional) CNTag Information Valid
<i>cntag_vld</i>	(Optional) CNTag Information Valid
qtag_vld	(Optional) VLAN Tag Information Valid
<i>qtag_vld</i>	(Optional) VLAN Tag Information Valid
vlan	(Optional) VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	(Optional) VLAN Id
cos	(Optional) Class of Service
<i>cos_val</i>	(Optional) Class of Service Type
cfi	(Optional) CFI Setting
<i>cfi_vld</i>	(Optional) CFI Setting Valid
vntag_vld	(Optional) VNTAG Information Valid
<i>vntag_vld</i>	(Optional) VNTAG Information Valid
vntag_svif	(Optional) VNTAG Source vif
<i>vntag_svif</i>	(Optional) VNTAG Source vif
vntag_dvif	(Optional) VNTAG Destination vif
<i>vntag_dvif</i>	(Optional) VNTAG Destination vif
vntag_looped	(Optional) VNTAG Header Looped Valid
<i>vntag_loop</i>	(Optional) VNTAG Header Looped Valid

<code>vntag_pointer</code>	(Optional) VNTAG Header Pointer Valid
<code>vntag_p</code>	(Optional) VNTAG Header Pointer Valid
<code>src_mac</code>	(Optional) Source MAC Address
<code>smac</code>	(Optional) Source MAC Address Value
<code>dst_mac</code>	(Optional) Destination MAC Address
<code>dmac</code>	(Optional) Destination MAC Address Value

Command Mode

- /exec/elanms/sel5

set inner l2 hg2

```
set { inner | outer } l2 hg2 [ { hg2_vid <hg2_vlan> | hg2_ppd_type <hg2_ppd_type> | hg2_mirror <hg2_mirror>
| hg2_opcode <hg2_opcode> | hg2_dstpid <hg2_dpid> | hg2_dstmod <hg2_dmod> | hg2_srcpid <hg2_spid>
| hg2_srcmod <hg2_smod> | hg2_l3vld <hg2_l3_vld> | hg2_tc <hg2_tc> | hg2_dp <hg2_dp> | hg2_mcast
<hg2_mcast_vld> | hg2-vld <hg2_vld> | hg2-cos <hg2_cos> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
outer	Mask and Match By Outer Packet Fields
l2	All Layer 2 Fields
hg2	High Gig2 Fields
hg2_vid	(Optional) High Gig2 VLAN Tag
<i>hg2_vlan</i>	(Optional) High Gig2 VLAN Tag Information
hg2_ppd_type	(Optional) High Gig2 Packet Processing Descriptor
<i>hg2_ppd_type</i>	(Optional) High Gig2 Packet Processing Descriptor
hg2_mirror	(Optional) High Gig2 Packet Mirror Information
<i>hg2_mirror</i>	(Optional) High Gig2 Packet Mirror Information
hg2_opcode	(Optional) High Gig2 Packet Type
<i>hg2_opcode</i>	(Optional) High Gig2 Packet Type
hg2_dstpid	(Optional) High Gig2 Destination Port ID
<i>hg2_dpid</i>	(Optional) High Gig2 Destination Port ID
hg2_dstmod	(Optional) High Gig2 Destination Module ID
<i>hg2_dmod</i>	(Optional) High Gig2 Destination Module ID
hg2_srcpid	(Optional) High Gig2 Source Port ID
<i>hg2_spid</i>	(Optional) High Gig2 Source Port ID
hg2_srcmod	(Optional) High Gig2 Souce Module ID
<i>hg2_smod</i>	(Optional) High Gig2 Souce Module ID
hg2_l3vld	(Optional) High Gig2 Packet L3 Switched
<i>hg2_l3_vld</i>	(Optional) High Gig2 Packet L3 Switched

<code>hg2_tc</code>	(Optional) High Gig2 Packet Traffic Class
<code>hg2_tc</code>	(Optional) High Gig2 Packet Traffic Class
<code>hg2_dp</code>	(Optional) High Gig2 Drop Precedence
<code>hg2_dp</code>	(Optional) High Gig2 Drop Precedence
<code>hg2_mcast</code>	(Optional) High Gig2 MultiCast Forwarding Information
<code>hg2_mcast_vld</code>	(Optional) High Gig2 Multicast Forwarding Information
<code>hg2-vld</code>	(Optional) High Gig2 Valid Information
<code>hg2_vld</code>	(Optional) High Gig2 Valid Information
<code>hg2-cos</code>	(Optional) High Gig2 CoS Information
<code>hg2_cos</code>	(Optional) High Gig2 CoS Information

Command Mode

- /exec/elanms/sel5

set inner l2 hg2

```
set inner l2 hg2 [ { hg2_vid <hg2_vlan> | hg2_ppd_type <hg2_ppd_type> | hg2_mirror <hg2_mirror> |
hg2_opcode <hg2_opcode> | hg2_dstpid <hg2_dpid> | hg2_dstmod <hg2_dmod> | hg2_srcpid <hg2_spid>
| hg2_srcmod <hg2_smod> | hg2_l3vld <hg2_l3_vld> | hg2_tc <hg2_tc> | hg2_dp <hg2_dp> | hg2_mcast
<hg2_mcast_vld> | hg2-vld <hg2_vld> | hg2-cos <hg2_cos> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
l2	All Layer 2 Fields
hg2	High Gig2 Fields
hg2_vid	(Optional) High Gig2 VLAN Tag
<i>hg2_vlan</i>	(Optional) High Gig2 VLAN Tag Information
hg2_ppd_type	(Optional) High Gig2 Packet Processing Descriptor
<i>hg2_ppd_type</i>	(Optional) High Gig2 Packet Processing Descriptor
hg2_mirror	(Optional) High Gig2 Packet Mirror Information
<i>hg2_mirror</i>	(Optional) High Gig2 Packet Mirror Information
hg2_opcode	(Optional) High Gig2 Packet Type
<i>hg2_opcode</i>	(Optional) High Gig2 Packet Type
hg2_dstpid	(Optional) High Gig2 Destination Port ID
<i>hg2_dpid</i>	(Optional) High Gig2 Destination Port ID
hg2_dstmod	(Optional) High Gig2 Destination Module ID
<i>hg2_dmod</i>	(Optional) High Gig2 Destination Module ID
hg2_srcpid	(Optional) High Gig2 Source Port ID
<i>hg2_spid</i>	(Optional) High Gig2 Source Port ID
hg2_srcmod	(Optional) High Gig2 Souce Module ID
<i>hg2_smod</i>	(Optional) High Gig2 Souce Module ID
hg2_l3vld	(Optional) High Gig2 Packet L3 Switched
<i>hg2_l3_vld</i>	(Optional) High Gig2 Packet L3 Switched
hg2_tc	(Optional) High Gig2 Packet Traffic Class

<i>hg2_tc</i>	(Optional) High Gig2 Packet Traffic Class
<i>hg2_dp</i>	(Optional) High Gig2 Drop Precedence
<i>hg2_dp</i>	(Optional) High Gig2 Drop Precedence
<i>hg2_mcast</i>	(Optional) High Gig2 MultiCast Forwarding Information
<i>hg2_mcast_vld</i>	(Optional) High Gig2 Multicast Forwarding Information
<i>hg2-vld</i>	(Optional) High Gig2 Valid Information
<i>hg2_vld</i>	(Optional) High Gig2 Valid Information
<i>hg2-cos</i>	(Optional) High Gig2 CoS Information
<i>hg2_cos</i>	(Optional) High Gig2 CoS Information

Command Mode

- /exec/elanms/sel4

set inner l4

```
set { inner | outer } l4 [ { src-port <sport> | dst-port <dport> | packet-len <pkt_len> | checksum <csum> | flags
<flag_val> } ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
outer	Mask and Match By Outer Packet Fields
l4	L4 Fields
src-port	(Optional) Source Port Information
<i>sport</i>	(Optional) Source Port
dst-port	(Optional) Destination Port Information
<i>dport</i>	(Optional) Destination Port
packet-len	(Optional) Packet Length
<i>pkt_len</i>	(Optional) Packet Length
checksum	(Optional) Checksum
<i>csum</i>	(Optional) Checksum
flags	(Optional) L4 Flags
<i>flag_val</i>	(Optional) L4 Flags

Command Mode

- /exec/elanms/se17

set inner l4

```
set inner l4 { l4-type <l4_type> | src-port <sport> | dst-port <dport> | packet-len <pkt_len> | checksum <csum>
| flags <flag_val> | tn-nonce <tn_nonce> | tn-lsb <tn_lsb> | tn-nonce-info <tn_nonce_info> | tn-lsb-info
<tn_lsb_info> | vnid <vnid_val> | nd-type <nd_type> | nd-code <nd_code> | nd-flags <nd_flags> | nd-ip
<nd_ip> | nonce-lb <nonce_lb> | nonce-dl <nonce_dl> | nonce-e <nonce_e> | nonce-sp <nonce_sp> | nonce-dp
<nonce_dp> | nonce-dre <nonce_dre> | sclass <sclass> | lsb-m <lsb_m> | lsb-lb-tag <lsb_lb_tag> | lsb-lb-metric
<lsb_lb_metric> } +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
l4	L4 Fields
l4-type	L4 Type - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
<i>l4_type</i>	L4 Type Value - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
src-port	Source Port Information
<i>sport</i>	Source Port
dst-port	Destination Port Information
<i>dport</i>	Destination Port
packet-len	Packet Length
<i>pkt_len</i>	Packet Length
checksum	Checksum
<i>csum</i>	Checksum
flags	L4 Flags
<i>flag_val</i>	L4 Flags
tn-nonce	Nonce valid
<i>tn_nonce</i>	Nonce valid
tn-lsb	Lsb valid
<i>tn_lsb</i>	Lsb valid
tn-nonce-info	Nonce Info
<i>tn_nonce_info</i>	Nonce Info
tn-lsb-info	Lsb Info

<i>tn_lsb_info</i>	Lsb Info
<i>vnid</i>	Virtual Network Id
<i>vnid_val</i>	Virtual Network Id
<i>nd-type</i>	ND Type
<i>nd_type</i>	ND Type
<i>nd-code</i>	ND Code
<i>nd_code</i>	ND Code
<i>nd-flags</i>	ND Flags
<i>nd_flags</i>	ND Flags
<i>nd-ip</i>	ND IP
<i>nonce-lb</i>	Nonce Load Balance
<i>nonce_lb</i>	Nonce Load Balance
<i>nonce-dl</i>	Nonce Don't Learn
<i>nonce_dl</i>	Nonce Don't Learn
<i>nonce-e</i>	Nonce Exception
<i>nonce_e</i>	Nonce Exception
<i>nonce-sp</i>	Nonce Src Policy applied
<i>nonce_sp</i>	Nonce Src Policy applied
<i>nonce-dp</i>	Nonce Dst Policy applied
<i>nonce_dp</i>	Nonce Dst Policy applied
<i>nonce-dre</i>	Nonce Congestion Est.
<i>nonce_dre</i>	Nonce Congestion Est.
<i>sclass</i>	Nonce Src Class
<i>sclass</i>	Nonce Src Class
<i>lsb-m</i>	Lsb Marker
<i>lsb_m</i>	Lsb Marker
<i>lsb-lb-tag</i>	Lsb LB Tag
<i>lsb_lb_tag</i>	Lsb LB Tag
<i>lsb-lb-metric</i>	Lsb LB Metric

<i>lsb_lb_metric</i>	Lsb LB Metric
----------------------	---------------

Command Mode

- /exec/elamtah/inse17

set inner l4

```
set inner l4 [ { src-port <sport> | dst-port <dport> | packet-len <pkt_len> | checksum <csum> | flags <flag_val>
} ] +
```

Syntax Description

set	Setup Trigger
inner	Mask and Match By Inner Packet Fields
l4	L4 Fields
src-port	(Optional) Source Port Information
<i>sport</i>	(Optional) Source Port
dst-port	(Optional) Destination Port Information
<i>dport</i>	(Optional) Destination Port
packet-len	(Optional) Packet Length
<i>pkt_len</i>	(Optional) Packet Length
checksum	(Optional) Checksum
<i>csum</i>	(Optional) Checksum
flags	(Optional) L4 Flags
<i>flag_val</i>	(Optional) L4 Flags

Command Mode

- /exec/elanms/set4

set interface

[no] set interface <iiface>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
interface	Output interface
<i>iface</i>	Interface name

Command Mode

- /exec/configure/route-map

set interval find-new-host

[no] set interval find-new-host <val>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set vmtracker options
interval	Set the polling interval
find-new-host	Set interval for the new host searching timer
<i>val</i>	The host search interval value in seconds (0 to disable)

Command Mode

- /exec/configure/vmt-conn

set interval sync-full-info

[no] set interval sync-full-info <val>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set vmtracker options
interval	Set the polling interval
sync-full-info	Set interval for syncing complete info from host
<i>val</i>	The sync info interval value in seconds (0 to disable)

Command Mode

- /exec/configure/vmt-conn

set ip address prefix-list

[no] set ip address prefix-list <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
address	Specify IP address
prefix-list	IP prefix-list
<i>name</i>	Name of prefix list

Command Mode

- /exec/configure/route-map

set ip default next-hop

[no] set ip default next-hop [recursive] { load-share | <addr1> + [load-share] }

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
recursive	(Optional) Use recursive lookup
default	Set default next-hop
next-hop	Next hop address
<i>addr1</i>	IP address of next hop
load-share	Enables load sharing

Command Mode

- /exec/configure/route-map

set ip default next-hop verify-availability

[no] set ip default next-hop verify-availability { <addr> [track <object_id>] } [load-share]

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
default	Set default next-hop
next-hop	Next hop address
verify-availability	Verify the reachability of the tracked object
<i>addr</i>	IP address of next hop
track	(Optional) The tracking method is track
<i>object_id</i>	(Optional) Object number that the tracking subsystem is tracking
load-share	(Optional) Enables load sharing

Command Mode

- /exec/configure/route-map

set ip next-hop

```
[no] set ip next-hop [ recursive ] { [ <addr1> + ] { { [ drop-on-fail ] [ load-share ] [ force-order ] } | { [ drop-on-fail ] [ force-order ] [ load-share ] } | { [ load-share ] [ drop-on-fail ] [ force-order ] } | { [ load-share ] [ force-order ] [ drop-on-fail ] } | { [ force-order ] [ drop-on-fail ] [ load-share ] } | { [ force-order ] [ load-share ] [ drop-on-fail ] } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
recursive	(Optional) Use recursive lookup
next-hop	Next hop address
<i>addr1</i>	(Optional) IP address of next hop
load-share	(Optional) Enables load sharing
force-order	(Optional) Maintains next-hop order as per cli config
drop-on-fail	(Optional) Drop packets when next-hop unreachable

Command Mode

- /exec/configure/route-map

set ip next-hop peer-address

[no] set ip next-hop peer-address

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
next-hop	Next hop address
peer-address	Use peer address (for BGP only)

Command Mode

- /exec/configure/route-map

set ip next-hop redistrib-unchanged

[no] set ip next-hop redistrib-unchanged

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
next-hop	Next hop address
redistrib-unchanged	Use unchanged address during redistribution (for BGP session only)

Command Mode

- /exec/configure/route-map

set ip next-hop unchanged

[no] set ip next-hop unchanged

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
next-hop	Next hop address
unchanged	Use unchanged address (for eBGP session only)

Command Mode

- /exec/configure/route-map

set ip next-hop verify-availability

[no] set ip next-hop verify-availability { <addr> [track <object_id>] } [load-share]

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
next-hop	Next hop address
verify-availability	Verify the reachability of the tracked object
<i>addr</i>	IP address of next hop
track	(Optional) The tracking method is track
<i>object_id</i>	(Optional) Object number that the tracking subsystem is tracking
load-share	(Optional) Enables load sharing

Command Mode

- /exec/configure/route-map

set ip precedence

```
{ set ip precedence { <value> | <name> } } | { no set ip precedence [ <value> | <name> ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
ip	Configure IP features
precedence	Set precedence field
<i>value</i>	Precedence value
<i>name</i>	Precedence value

Command Mode

- /exec/configure/route-map

set ipv6 address prefix-list

[no] set ipv6 address prefix-list <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
address	Specify IP address
prefix-list	IPv6 prefix-list
<i>name</i>	Name of prefix list

Command Mode

- /exec/configure/route-map

set ipv6 default next-hop

[no] set ipv6 default next-hop [recursive] { load-share | <addr1> + [load-share] }

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
recursive	(Optional) Use recursive lookup
default	Set default next-hop
next-hop	Next hop address
load-share	Enables load sharing
<i>addr1</i>	

Command Mode

- /exec/configure/route-map

set ipv6 default next-hop verify-availability

[no] set ipv6 default next-hop verify-availability { <addr> [track <object_id>] } [load-share]

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop address
default	Set default next-hop
verify-availability	Verify the reachability of the tracked object
track	(Optional) The tracking method is track
<i>object_id</i>	(Optional) Object number that the tracking subsystem is tracking
load-share	(Optional) Enables load sharing

Command Mode

- /exec/configure/route-map

set ipv6 next-hop

```
[no] set ipv6 next-hop { [ <addr> + ] { { [ drop-on-fail ] [ load-share ] [ force-order ] } | { [ drop-on-fail ] [ force-order ] [ load-share ] } | { [ load-share ] [ drop-on-fail ] [ force-order ] } | { [ load-share ] [ force-order ] [ drop-on-fail ] } | { [ force-order ] [ drop-on-fail ] [ load-share ] } | { [ force-order ] [ load-share ] [ drop-on-fail ] } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop ipv6 address
load-share	(Optional) Enables load sharing
force-order	(Optional) Enables Next-hop ordering as per cli
drop-on-fail	(Optional) Drop packets when next-hop unreachable
<i>addr</i>	(Optional)

Command Mode

- /exec/configure/route-map

set ipv6 next-hop peer-address

[no] set ipv6 next-hop peer-address

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop address
peer-address	Use peer address (for BGP only)

Command Mode

- /exec/configure/route-map

set ipv6 next-hop redist-unchanged

[no] set ipv6 next-hop redist-unchanged

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop address
redist-unchanged	Use unchanged address during redistribution (for BGP session only)

Command Mode

- /exec/configure/route-map

set ipv6 next-hop unchanged

[no] set ipv6 next-hop unchanged

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop address
unchanged	Use unchanged address (for eBGP session only)

Command Mode

- /exec/configure/route-map

set ipv6 next-hop verify-availability

```
[no] set ipv6 next-hop verify-availability { <addr> [ track <object_id> ] } [ load-share ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
next-hop	Next hop address
verify-availability	Verify the reachability of the tracked object
track	(Optional) The tracking method is track
<i>object_id</i>	(Optional) Object number that the tracking subsystem is tracking
load-share	(Optional) Enables load sharing

Command Mode

- /exec/configure/route-map

set ipv6 precedence

```
{ set ipv6 precedence { <value> | <name> } } | { no set ipv6 precedence [ <value> | <name> ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
ipv6	Configure IPv6 features
precedence	Set precedence field
<i>value</i>	Precedence value
<i>name</i>	Precedence value

Command Mode

- /exec/configure/route-map

set label-index

{ { set label-index <value> } | { no set label-index [<value>] } }

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
label-index	Set Segment Routing (SR) label index of route
<i>value</i>	Segment Routing (SR) label index

Command Mode

- /exec/configure/route-map

set level level-1 level-1-2 level-2

{ set level { level-1 | level-1-2 | level-2 } } | { no set level [level-1 | level-1-2 | level-2] }

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
level	Where to import route
level-1	Import into a level-1 area
level-1-2	Import into level-1 and level-2
level-2	Import into level-2 sub-domain

Command Mode

- /exec/configure/route-map

set local-preference

{ set local-preference <pref> | no set local-preference [<pref>] }

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
local-preference	BGP local preference path attribute
<i>pref</i>	Preference value

Command Mode

- /exec/configure/route-map

set metric

```
{ set metric <metric0> [ <metric1> <metric2> <metric3> <metric4> ] } | { no set metric [ <metric0> [ <metric1> <metric2> <metric3> <metric4> ] ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
metric	Set metric for destination routing protocol
<i>metric0</i>	[+/-] Metric value or Bandwidth in Kbits per second
<i>metric1</i>	(Optional) IGRP delay metric
<i>metric2</i>	(Optional) IGRP reliability metric where 255 is 100% reliable
<i>metric3</i>	(Optional) IGRP Effective bandwidth metric (Loading) 255 is 100%
<i>metric4</i>	(Optional) IGRP MTU of the path

Command Mode

- /exec/configure/route-map

set nssa-only

[no] set nssa-only

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
nssa-only	OSPF NSSA Areas

Command Mode

- /exec/configure/route-map

set origin egp

{ set origin egp <as> } | { no set origin egp <as> }

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
origin	BGP origin code
egp	remote EGP
as	AS number

Command Mode

- /exec/configure/route-map

set origin egp igp incomplete

```
{ set origin { egp | igp | incomplete } } | { no set origin [ { egp | igp | incomplete } ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
origin	BGP origin code
egp	remote EGP
igp	local IGP
incomplete	unknown heritage

Command Mode

- /exec/configure/route-map

set outer arp

```
set outer arp { target-ip-addr <tipaddr> | target-mac-addr <tmac> | source-ip-addr <sipaddr> | source-mac-addr
<smac> | opcode <opcode_val> | prot-addr-len <prot_addr_len> | hw-addr-len <hw_addr_len> | protocol-type
<prot_type> | hardware-type <hw_type> | ether-type <etype> | payload-len <pyld_len> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
arp	ARP Fields
target-ip-addr	ARP Target IP Address
<i>tipaddr</i>	ARP Target IP Address
target-mac-addr	ARP Target MAC Address
<i>tmac</i>	ARP Target MAC Address
source-ip-addr	ARP Source IP Address
<i>sipaddr</i>	ARP Source IP Address
source-mac-addr	ARP Source MAC Address
<i>smac</i>	ARP Source MAC Address
opcode	ARP Opcode
<i>opcode_val</i>	ARP Opcode
prot-addr-len	ARP Protocol Address Length
<i>prot_addr_len</i>	ARP Protocol Address Length
hw-addr-len	ARP Hardware Address Length
<i>hw_addr_len</i>	ARP Hardware Address Length
protocol-type	ARP Protocol Type
<i>prot_type</i>	ARP Protocol Type
hardware-type	ARP Hardware Type
<i>hw_type</i>	ARP Hardware Type
ether-type	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP
<i>etype</i>	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP
payload-len	ARP Payload Length

<i>pyld_len</i>	ARP Payload Length
-----------------	--------------------

Command Mode

- /exec/elamta/insel6

set outer arp

```
set { outer | inner } arp { target-ip-addr <tipaddr> | target-mac-addr <tmac> | source-ip-addr <sipaddr> |
source-mac-addr <smac> | opcode <opcode_val> | prot-addr-len <prot_addr_len> | hw-addr-len <hw_addr_len>
| protocol-type <prot_type> | hardware-type <hw_type> | ether-type <etype> | payload-len <pyld_len> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
inner	Mask and Match By Inner Packet Fields
arp	ARP Fields
target-ip-addr	ARP Target IP Address
<i>tipaddr</i>	ARP Target IP Address
target-mac-addr	ARP Target MAC Address
<i>tmac</i>	ARP Target MAC Address
source-ip-addr	ARP Source IP Address
<i>sipaddr</i>	ARP Source IP Address
source-mac-addr	ARP Source MAC Address
<i>smac</i>	ARP Source MAC Address
opcode	ARP Opcode
<i>opcode_val</i>	ARP Opcode
prot-addr-len	ARP Protocol Address Length
<i>prot_addr_len</i>	ARP Protocol Address Length
hw-addr-len	ARP Hardware Address Length
<i>hw_addr_len</i>	ARP Hardware Address Length
protocol-type	ARP Protocol Type
<i>prot_type</i>	ARP Protocol Type
hardware-type	ARP Hardware Type
<i>hw_type</i>	ARP Hardware Type
ether-type	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP
<i>etype</i>	ARP Ether Type - 0x0806 -> ARP 0x8035 -> RARP

payload-len	ARP Payload Length
<i>pyld_len</i>	ARP Payload Length

Command Mode

- /exec/elamtah/inse19

set outer fcoe

```
set outer fcoe { pyld-len <pyld_len> | ether-type <etype> | esof <esof> | r_ctl <r_ctl> | d_id <d_id> | cs_ctl
<cs_ctl> | s_id <s_id> | fc_type <fc_type> | f_ctl <f_ctl> | df_ctl <df_ctl> | ox_id <ox_id> | rx_id <rx_id> |
pyld0 <pyld0> | pyld1 <pyld1> | pyld2 <pyld2> | pyld3 <pyld3> | vft_vld <vft_vld> | vft_type <vft_type> |
vft_prio <vft_prio> | vft_vfid <vft_vfid> | vft_hopct <vft_hopct> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
fcoe	FCoE Fields
pyld-len	Payload Length
<i>pyld_len</i>	Payload Length
ether-type	FCoE Ether Type - 0x8906
<i>etype</i>	FCoE Ether Type - 0x8906
esof	ESOF
<i>esof</i>	ESOF Value
r_ctl	R_CTL
<i>r_ctl</i>	R_CTL value
d_id	D_ID
<i>d_id</i>	D_ID value
cs_ctl	CS_CTL
<i>cs_ctl</i>	CS_CTL value
s_id	S_ID
<i>s_id</i>	S_ID value
fc_type	FC_TYPE
<i>fc_type</i>	FC_TYPE value
f_ctl	F_CTL
<i>f_ctl</i>	F_CTL value
df_ctl	DF_CTL
<i>df_ctl</i>	DF_CTL value

<code>ox_id</code>	OxID
<code>ox_id</code>	OxID value
<code>rx_id</code>	RxID
<code>rx_id</code>	RxID value
<code>pyld0</code>	First 4 bytes of payload
<code>pyld0</code>	First 4 bytes of payload value
<code>pyld1</code>	Second 4 bytes of payload
<code>pyld1</code>	Second 4 bytes of payload value
<code>pyld2</code>	Third 4 bytes of payload
<code>pyld2</code>	Third 4 bytes of payload value
<code>pyld3</code>	Fourth 4 bytes of payload
<code>pyld3</code>	Fourth 4 bytes of payload value
<code>vft_vld</code>	VFT_VLD
<code>vft_vld</code>	VFT_VLD value
<code>vft_type</code>	VFT_TYPE
<code>vft_type</code>	VFT_TYPE value
<code>vft_prio</code>	VFT_PRIO
<code>vft_prio</code>	VFT_PRIO value
<code>vft_vfid</code>	VFT_VFID
<code>vft_vfid</code>	VFT_VFID value
<code>vft_hopct</code>	VFT_HOPCT
<code>vft_hopct</code>	VFT_HOPCT value

Command Mode

- `/exec/elamtah/insel6`

set outer ipv4

```
set outer ipv4 { pyld-len <pyld_len> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val>
| packet-len <pkt_len> | more-frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> |
checksum <csum> | src_ip <sip> | dst_ip <dip> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
ipv4	IPv4 Fields
pyld-len	Payload Length
<i>pyld_len</i>	Payload Length
version	Version
<i>ver</i>	Version
header-len	Header Length
<i>hlen</i>	Header Length
dscp	Diff. Serv. Code Point
<i>dscp_val</i>	Diff. Serv. Code Point
ecn	Explicit Congestion Ntn
<i>ecn_val</i>	Explicit Congestion Ntn
packet-len	Packet Total Length
<i>pkt_len</i>	Packet Total Length
more-frags	More Fragments Available
<i>mf</i>	More Fragments Available
fragment-off	Fragments Offset
<i>fragoff</i>	Fragments Offset
ttl	Time to Live
<i>ttl_val</i>	Time to Live
next-protocol	Next Protocol
<i>nproto</i>	Next Protocol
checksum	Checksum

<i>csum</i>	Checksum
<i>src_ip</i>	Source IP Address
<i>sip</i>	Source IP Address
<i>dst_ip</i>	Destination IP Address
<i>dip</i>	Destination IP Address

Command Mode

- /exec/elamtah/insel6

set outer ipv4

set { outer | inner } ipv4 { pyld-len <pyld_len> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val> | packet-len <pkt_len> | more- frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> | checksum <csum> | src_ip <sip> | dst_ip <dip> } +

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
inner	Mask and Match By Inner Packet Fields
ipv4	IPv4 Fields
pyld-len	Payload Length
<i>pyld_len</i>	Payload Length
version	Version
<i>ver</i>	Version
header-len	Header Length
<i>hlen</i>	Header Length
dscp	Diff. Serv. Code Point
<i>dscp_val</i>	Diff. Serv. Code Point
ecn	Explicit Congestion Ntn
<i>ecn_val</i>	Explicit Congestion Ntn
packet-len	Packet Total Length
<i>pkt_len</i>	Packet Total Length
more- frags	More Fragments Available
<i>mf</i>	More Fragments Available
fragment-off	Fragments Offset
<i>fragoff</i>	Fragments Offset
ttl	Time to Live
<i>ttl_val</i>	Time to Live
next-protocol	Next Protocol
<i>nproto</i>	Next Protocol

checksum	Checksum
<i>csum</i>	Checksum
src_ip	Source IP Address
<i>sip</i>	Source IP Address
dst_ip	Destination IP Address
<i>dip</i>	Destination IP Address

Command Mode

- /exec/elamta/insel9

set outer ipv4

```
set outer ipv4 [ { l3-type <l3_type> | pyld-len <pyld_len> | v6-vld <v6_vld> | version <ver> | header-len <hlen> | dscp <dscp_val> | ecn <ecn_val> | packet-len <pkt_len> | more-frags <mf> | fragment-off <fragoff> | ttl <ttl_val> | next-protocol <nproto> | checksum <csum> | src_ip <sip> | dst_ip <dip> } ] +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
ipv4	IPv4 Fields
l3-type	(Optional) L3 Packet Type
<i>l3_type</i>	(Optional) L3 Packet Type
pyld-len	(Optional) Payload Length
<i>pyld_len</i>	(Optional) Payload Length
v6-vld	(Optional) IPv6 Valid Information
<i>v6_vld</i>	(Optional) IPv6 Valid Information
version	(Optional) Version
<i>ver</i>	(Optional) Version
header-len	(Optional) Header Length
<i>hlen</i>	(Optional) Header Length
dscp	(Optional) Diff. Serv. Code Point
<i>dscp_val</i>	(Optional) Diff. Serv. Code Point
ecn	(Optional) Explicit Congestion Ntn
<i>ecn_val</i>	(Optional) Explicit Congestion Ntn
packet-len	(Optional) Packet Total Length
<i>pkt_len</i>	(Optional) Packet Total Length
more-frags	(Optional) More Fragments Available
<i>mf</i>	(Optional) More Fragments Available
fragment-off	(Optional) Fragments Offset
<i>fragoff</i>	(Optional) Fragments Offset
ttl	(Optional) Time to Live

<i>ttl_val</i>	(Optional) Time to Live
next-protocol	(Optional) Next(L4) Protocol
<i>nproto</i>	(Optional) Next(L4) Protocol
checksum	(Optional) Checksum
<i>csum</i>	(Optional) Checksum
src_ip	(Optional) Source IP Address
<i>sip</i>	(Optional) Source IP Address
dst_ip	(Optional) Destination IP Address
<i>dip</i>	(Optional) Destination IP Address

Command Mode

- /exec/elanms/sel3

set outer ipv6 src_ip

set { outer | inner } ipv6 { src_ip <src_ip> | dst_ip <dst_ip> } +

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
inner	Mask and Match By Inner Packet Fields
ipv6	IPv6 Fields
src_ip	Source IP Address
dst_ip	Destination IP Address

Command Mode

- /exec/elamtah/inse19

set outer ipv6 src_ip

```
set outer ipv6 { src_ip <sip> | dst_ip <dip> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
ipv6	IPv6 Fields
src_ip	Source IP Address
dst_ip	Destination IP Address

Command Mode

- /exec/elamtah/insel6

set outer l2

```
set { outer | inner } l2 { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id>
| cos <cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif>
| vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
inner	Mask and Match By Inner Packet Fields
l2	All Layer 2 Fields
snap_vld	SNAP Header Information Valid
<i>snap_vld</i>	SNAP Header Information Valid
cntag_vld	CNTag Information Valid
<i>cntag_vld</i>	CNTag Information Valid
qtag_vld	VLAN Tag Information Valid
<i>qtag_vld</i>	VLAN Tag Information Valid
vlan	VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	VLAN Id
cos	Class of Service
<i>cos_val</i>	Class of Service Type
cfi	CFI Setting
<i>cfi_vld</i>	CFI Setting Valid
vntag_vld	VNTAG Information Valid
<i>vntag_vld</i>	VNTAG Information Valid
vntag_svif	VNTAG Source vif
<i>vntag_svif</i>	VNTAG Source vif
vntag_dvif	VNTAG Destination vif
<i>vntag_dvif</i>	VNTAG Destination vif
vntag_looped	VNTAG Header Looped Valid
<i>vntag_loop</i>	VNTAG Header Looped Valid

<i>vntag_pointer</i>	VNTAG Header Pointer Valid
<i>vntag_p</i>	VNTAG Header Pointer Valid
<i>src_mac</i>	Source MAC Address
<i>smac</i>	Source MAC Address Value
<i>dst_mac</i>	Destination MAC Address
<i>dmac</i>	Destination MAC Address Value

Command Mode

- /exec/elamta/insel8

set outer l2

```
set outer l2 { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id> | cos
<cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif> |
vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
l2	All Layer 2 Fields
snap_vld	SNAP Header Information Valid
<i>snap_vld</i>	SNAP Header Information Valid
cntag_vld	CNTag Information Valid
<i>cntag_vld</i>	CNTag Information Valid
qtag_vld	VLAN Tag Information Valid
<i>qtag_vld</i>	VLAN Tag Information Valid
vlan	VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	VLAN Id
cos	Class of Service
<i>cos_val</i>	Class of Service Type
cfi	CFI Setting
<i>cfi_vld</i>	CFI Setting Valid
vntag_vld	VNTAG Information Valid
<i>vntag_vld</i>	VNTAG Information Valid
vntag_svif	VNTAG Source vif
<i>vntag_svif</i>	VNTAG Source vif
vntag_dvif	VNTAG Destination vif
<i>vntag_dvif</i>	VNTAG Destination vif
vntag_looped	VNTAG Header Looped Valid
<i>vntag_loop</i>	VNTAG Header Looped Valid
vntag_pointer	VNTAG Header Pointer Valid

<i>vntag_p</i>	VNTAG Header Pointer Valid
<i>src_mac</i>	Source MAC Address
<i>smac</i>	Source MAC Address Value
<i>dst_mac</i>	Destination MAC Address
<i>dmac</i>	Destination MAC Address Value

Command Mode

- /exec/elamtah/insel6

set outer l2

```
set outer l2 [ { snap_vld <snap_vld> | cntag_vld <cntag_vld> | qtag_vld <qtag_vld> | vlan <vlan_id> | cos
<cos_val> | cfi <cfi_vld> | vntag_vld <vntag_vld> | vntag_svif <vntag_svif> | vntag_dvif <vntag_dvif> |
vntag_looped <vntag_loop> | vntag_pointer <vntag_p> | src_mac <smac> | dst_mac <dmac> } ] +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
l2	All Layer 2 Fields
snap_vld	(Optional) SNAP Header Information Valid
<i>snap_vld</i>	(Optional) SNAP Header Information Valid
cntag_vld	(Optional) CNTag Information Valid
<i>cntag_vld</i>	(Optional) CNTag Information Valid
qtag_vld	(Optional) VLAN Tag Information Valid
<i>qtag_vld</i>	(Optional) VLAN Tag Information Valid
vlan	(Optional) VLAN Id (Present only in case of FEX)
<i>vlan_id</i>	(Optional) VLAN Id
cos	(Optional) Class of Service
<i>cos_val</i>	(Optional) Class of Service Type
cfi	(Optional) CFI Setting
<i>cfi_vld</i>	(Optional) CFI Setting Valid
vntag_vld	(Optional) VNTAG Information Valid
<i>vntag_vld</i>	(Optional) VNTAG Information Valid
vntag_svif	(Optional) VNTAG Source vif
<i>vntag_svif</i>	(Optional) VNTAG Source vif
vntag_dvif	(Optional) VNTAG Destination vif
<i>vntag_dvif</i>	(Optional) VNTAG Destination vif
vntag_looped	(Optional) VNTAG Header Looped Valid
<i>vntag_loop</i>	(Optional) VNTAG Header Looped Valid
vntag_pointer	(Optional) VNTAG Header Pointer Valid

<i>vntag_p</i>	(Optional) VNTAG Header Pointer Valid
<i>src_mac</i>	(Optional) Source MAC Address
<i>smac</i>	(Optional) Source MAC Address Value
<i>dst_mac</i>	(Optional) Destination MAC Address
<i>dmac</i>	(Optional) Destination MAC Address Value

Command Mode

- /exec/elanms/se13

set outer l2 hg2

```
set outer l2 hg2 [ { hg2_vid <hg2_vlan> | hg2_ppd_type <hg2_ppd_type> | hg2_mirror <hg2_mirror> |
hg2_opcode <hg2_opcode> | hg2_dstpid <hg2_dpid> | hg2_dstmod <hg2_dmod> | hg2_srcpid <hg2_spid>
| hg2_srcmod <hg2_smod> | hg2_l3vld <hg2_l3_vld> | hg2_tc <hg2_tc> | hg2_dp <hg2_dp> | hg2_mcast
<hg2_mcast_vld> | hg2-vld <hg2_vld> | hg2-cos <hg2_cos> } ] +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
l2	All Layer 2 Fields
hg2	High Gig2 Fields
hg2_vid	(Optional) High Gig2 VLAN Tag
<i>hg2_vlan</i>	(Optional) High Gig2 VLAN Tag Information
hg2_ppd_type	(Optional) High Gig2 Packet Processing Descriptor
<i>hg2_ppd_type</i>	(Optional) High Gig2 Packet Processing Descriptor
hg2_mirror	(Optional) High Gig2 Packet Mirror Information
<i>hg2_mirror</i>	(Optional) High Gig2 Packet Mirror Information
hg2_opcode	(Optional) High Gig2 Packet Type
<i>hg2_opcode</i>	(Optional) High Gig2 Packet Type
hg2_dstpid	(Optional) High Gig2 Destination Port ID
<i>hg2_dpid</i>	(Optional) High Gig2 Destination Port ID
hg2_dstmod	(Optional) High Gig2 Destination Module ID
<i>hg2_dmod</i>	(Optional) High Gig2 Destination Module ID
hg2_srcpid	(Optional) High Gig2 Source Port ID
<i>hg2_spid</i>	(Optional) High Gig2 Source Port ID
hg2_srcmod	(Optional) High Gig2 Souce Module ID
<i>hg2_smod</i>	(Optional) High Gig2 Souce Module ID
hg2_l3vld	(Optional) High Gig2 Packet L3 Switched
<i>hg2_l3_vld</i>	(Optional) High Gig2 Packet L3 Switched
hg2_tc	(Optional) High Gig2 Packet Traffic Class

<i>hg2_tc</i>	(Optional) High Gig2 Packet Traffic Class
<i>hg2_dp</i>	(Optional) High Gig2 Drop Precedence
<i>hg2_dp</i>	(Optional) High Gig2 Drop Precedence
<i>hg2_mcast</i>	(Optional) High Gig2 MultiCast Forwarding Information
<i>hg2_mcast_vld</i>	(Optional) High Gig2 Multicast Forwarding Information
<i>hg2-vld</i>	(Optional) High Gig2 Valid Information
<i>hg2_vld</i>	(Optional) High Gig2 Valid Information
<i>hg2-cos</i>	(Optional) High Gig2 CoS Information
<i>hg2_cos</i>	(Optional) High Gig2 CoS Information

Command Mode

- /exec/elamns/sel3

set outer l4

```
set outer l4 [ { src-port <sport> | dst-port <dport> | packet-len <pkt_len> | checksum <csum> | flags <flag_val>
} ] +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
l4	L4 Fields
src-port	(Optional) Source Port Information
<i>sport</i>	(Optional) Source Port
dst-port	(Optional) Destination Port Information
<i>dport</i>	(Optional) Destination Port
packet-len	(Optional) Packet Length
<i>pkt_len</i>	(Optional) Packet Length
checksum	(Optional) Checksum
<i>csum</i>	(Optional) Checksum
flags	(Optional) L4 Flags
<i>flag_val</i>	(Optional) L4 Flags

Command Mode

- /exec/elanms/sel3

set outer l4

```
set outer l4 { l4-type <l4_type> | src-port <sport> | dst-port <dport> | packet-len <pkt_len> | checksum <csum>
| flags <flag_val> | tn-nonce <tn_nonce> | tn-lsb <tn_lsb> | tn-nonce-info <tn_nonce_info> | tn-lsb-info
<tn_lsb_info> | vnid <vnid_val> | nd-type <nd_type> | nd-code <nd_code> | nd-flags <nd_flags> | nd-ip
<nd_ip> | nonce-lb <nonce_lb> | nonce-dl <nonce_dl> | nonce-e <nonce_e> | nonce-sp <nonce_sp> | nonce-dp
<nonce_dp> | nonce-dre <nonce_dre> | sclass <sclass> | lsb-m <lsb_m> | lsb-lb-tag <lsb_lb_tag> | lsb-lb-metric
<lsb_lb_metric> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
l4	L4 Fields
l4-type	L4 Type - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
<i>l4_type</i>	L4 Type Value - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
src-port	Source Port Information
<i>sport</i>	Source Port
dst-port	Destination Port Information
<i>dport</i>	Destination Port
packet-len	Packet Length
<i>pkt_len</i>	Packet Length
checksum	Checksum
<i>csum</i>	Checksum
flags	L4 Flags 123
<i>flag_val</i>	L4 Flags
tn-nonce	Nonce valid
<i>tn_nonce</i>	Nonce valid
tn-lsb	Lsb valid
<i>tn_lsb</i>	Lsb valid
tn-nonce-info	Nonce Info
<i>tn_nonce_info</i>	Nonce Info
tn-lsb-info	Lsb Info

<i>tn_lsb_info</i>	Lsb Info
<i>vnid</i>	Virtual Network Id
<i>vnid_val</i>	Virtual Network Id
<i>nd-type</i>	ND Type
<i>nd_type</i>	ND Type
<i>nd-code</i>	ND Code
<i>nd_code</i>	ND Code
<i>nd-flags</i>	ND Flags
<i>nd_flags</i>	ND Flags
<i>nd-ip</i>	ND IP
<i>nonce-lb</i>	Nonce Load Balance
<i>nonce_lb</i>	Nonce Load Balance
<i>nonce-dl</i>	Nonce Don't Learn
<i>nonce_dl</i>	Nonce Don't Learn
<i>nonce-e</i>	Nonce Exception
<i>nonce_e</i>	Nonce Exception
<i>nonce-sp</i>	Nonce Src Policy applied
<i>nonce_sp</i>	Nonce Src Policy applied
<i>nonce-dp</i>	Nonce Dst Policy applied
<i>nonce_dp</i>	Nonce Dst Policy applied
<i>nonce-dre</i>	Nonce Congestion Est.
<i>nonce_dre</i>	Nonce Congestion Est.
<i>sclass</i>	Nonce Src Class
<i>sclass</i>	Nonce Src Class
<i>lsb-m</i>	Lsb Marker
<i>lsb_m</i>	Lsb Marker
<i>lsb-lb-tag</i>	Lsb LB Tag
<i>lsb_lb_tag</i>	Lsb LB Tag
<i>lsb-lb-metric</i>	Lsb LB Metric

<i>lsb_lb_metric</i>	Lsb LB Metric
----------------------	---------------

Command Mode

- /exec/elamtaH/inse16

set outer l4

```
set { outer | inner } l4 { l4-type <l4_type> | src-port <sport> | dst-port <dport> | packet-len <pkt_len> |
checksum <csum> | flags <flag_val> | tn-nonce <tn_nonce> | tn-lsb <tn_lsb> | tn-nonce-info <tn_nonce_info>
| tn-lsb-info <tn_lsb_info> | vnid <vnid_val> | nd-type <nd_type> | nd-code <nd_code> | nd-flags <nd_flags>
| nd-ip <nd_ip> | nonce-lb <nonce_lb> | nonce-dl <nonce_dl> | nonce-e <nonce_e> | nonce-sp <nonce_sp> |
nonce-dp <nonce_dp> | nonce-dre <nonce_dre> | sclass <sclass> | lsb-m <lsb_m> | lsb-lb-tag <lsb_lb_tag> |
lsb-lb-metric <lsb_lb_metric> } +
```

Syntax Description

set	Setup Trigger
outer	Mask and Match By Outer Packet Fields
inner	Mask and Match By Inner Packet Fields
l4	L4 Fields
l4-type	L4 Type - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
<i>l4_type</i>	L4 Type Value - 0:TCP 1:UDP 2:IVXLAN 3:VXLAN 4:NVGRE 7:ND
src-port	Source Port Information
<i>sport</i>	Source Port
dst-port	Destination Port Information
<i>dport</i>	Destination Port
packet-len	Packet Length
<i>pkt_len</i>	Packet Length
checksum	Checksum
<i>csum</i>	Checksum
flags	L4 Flags 123
<i>flag_val</i>	L4 Flags
tn-nonce	Nonce valid
<i>tn_nonce</i>	Nonce valid
tn-lsb	Lsb valid
<i>tn_lsb</i>	Lsb valid
tn-nonce-info	Nonce Info
<i>tn_nonce_info</i>	Nonce Info

tn-lsb-info	Lsb Info
<i>tn_lsb_info</i>	Lsb Info
vnid	Virtual Network Id
<i>vnid_val</i>	Virtual Network Id
nd-type	ND Type
<i>nd_type</i>	ND Type
nd-code	ND Code
<i>nd_code</i>	ND Code
nd-flags	ND Flags
<i>nd_flags</i>	ND Flags
nd-ip	ND IP
nonce-lb	Nonce Load Balance
<i>nonce_lb</i>	Nonce Load Balance
nonce-dl	Nonce Don't Learn
<i>nonce_dl</i>	Nonce Don't Learn
nonce-e	Nonce Exception
<i>nonce_e</i>	Nonce Exception
nonce-sp	Nonce Src Policy applied
<i>nonce_sp</i>	Nonce Src Policy applied
nonce-dp	Nonce Dst Policy applied
<i>nonce_dp</i>	Nonce Dst Policy applied
nonce-dre	Nonce Congestion Est.
<i>nonce_dre</i>	Nonce Congestion Est.
sclass	Nonce Src Class
<i>sclass</i>	Nonce Src Class
lsb-m	Lsb Marker
<i>lsb_m</i>	Lsb Marker
lsb-lb-tag	Lsb LB Tag
<i>lsb_lb_tag</i>	Lsb LB Tag

lsb-lb-metric	Lsb LB Metric
<i>lsb_lb_metric</i>	Lsb LB Metric

Command Mode

- /exec/elamtah/inse110

set path-selection advertise

[no] set path-selection { all | best2 | backup | multipaths | best-external | group-best } advertise

Syntax Description

no	(Optional) Negate a command or set its defaults
set	Set values in destination routing protocol
path-selection	Path selection criteria for BGP
all	Specifies all BGP paths
best2	Specifies best 2 BGP paths
backup	Specifies best + backup BGP paths
multipaths	Specifies multipaths BGP paths
best-external	Specifies best-external BGP paths TBD
group-best	Specifies group-best BGP paths TBD
advertise	Advertise add paths to its peers if receive capability enabled

Command Mode

- /exec/configure/route-map

set pktrw

```
set pktrw { spare <spare> | cap_access <cap_access> | bounce <bounce> | dst_vnic_if <dst_vnic_if> | src_vnic_if
<src_vnic_if> | pif_block_type <pif_block_type> | epg_out <epg_out> | epg_in <epg_in> | sup_qnum
<sup_qnum> | sup_code <sup_code> | ecn_coi <ecn_coi> | ecn_cio <ecn_cio> | ttl_coi <ttl_coi> | ttl_cio
<ttl_coi> | qos_map_idx <qos_map_idx> | lat_update <lat_update> | lat_index <lat_index> | dclass <dclass>
| sclass <sclass> | ol_fb_metric <ol_fb_metric> | ol_fb_vpath <ol_fb_vpath> | ol_dre <ol_dre> | ol_vpath
<ol_vpath> | ol_dp <ol_dp> | ol_sp <ol_sp> | ol_e <ol_e> | ol_dl <ol_dl> | ol_lb <ol_lb> | ol_mark <ol_mark>
| ol_udp_sp <ol_udp_sp> | ol_ecn <ol_ecn> | nat_idx <nat_idx> | nat_vld <nat_vld> | dst_addr1 <dst_addr1>
| dst_addr0 <dst_addr0> | adj_vld <adj_vld> | encap_l2_idx <encap_l2_idx> | encap_pcid <encap_pcid> |
encap_idx <encap_idx> | encap_vld <encap_vld> | my_pcid <my_pcid> | my_tep_idx <my_tep_idx> | fwd_op
<fwd_op> | orig_encap_type <orig_encap_type> | pkt_type <pkt_type> | len_type <len_type> | cap_1588
<cap_1588> | pktid <pktid> | srcid <srcid> | tstamp <tstamp> | pktfmt1_inner <pktfmt1_inner> | pktfmt1_l3
<pktfmt1_l3> | pktfmt1_l3_type <pktfmt1_l3_type> | pktfmt1_mpls_null <pktfmt1_mpls_null> | pktfmt1_snap
<pktfmt1_snap> | pktfmt1_cntag <pktfmt1_cntag> | pktfmt1_ttag <pktfmt1_ttag> | pktfmt1_cmd_dgt
<pktfmt1_cmd_dgt> | pktfmt1_cmd_sgt <pktfmt1_cmd_sgt> | pktfmt1_cdce <pktfmt1_cdce> | pktfmt1_trill
<pktfmt1_trill> | pktfmt1_qtag2 <pktfmt1_qtag2> | pktfmt1_qtag1 <pktfmt1_qtag1> | pktfmt1_qtag0
<pktfmt1_qtag0> | pktfmt1_ivntag <pktfmt1_ivntag> | pktfmt1_vntag <pktfmt1_vntag> | pktfmt1_ce
<pktfmt1_ce> | pktfmt1_ieth <pktfmt1_ieth> | pktfmt1_higig2 <pktfmt1_higig2> | pktfmt0_inner
<pktfmt0_inner> | pktfmt0_l3 <pktfmt0_l3> | pktfmt0_l3_type <pktfmt0_l3_type> | pktfmt0_mpls_null
<pktfmt0_mpls_null> | pktfmt0_snap <pktfmt0_snap> | pktfmt0_cntag <pktfmt0_cntag> | pktfmt0_ttag
<pktfmt0_ttag> | pktfmt0_cmd_dgt <pktfmt0_cmd_dgt> | pktfmt0_cmd_sgt <pktfmt0_cmd_sgt> | pktfmt0_cdce
<pktfmt0_cdce> | pktfmt0_trill <pktfmt0_trill> | pktfmt0_qtag2 <pktfmt0_qtag2> | pktfmt0_qtag1
<pktfmt0_qtag1> | pktfmt0_qtag0 <pktfmt0_qtag0> | pktfmt0_ivntag <pktfmt0_ivntag> | pktfmt0_vntag
<pktfmt0_vntag> | pktfmt0_ce <pktfmt0_ce> | pktfmt0_ieth <pktfmt0_ieth> | pktfmt0_higig2 <pktfmt0_higig2>
} +
```

Syntax Description

set	Setup Trigger
pktrw	All pktrw fields
spare	Spare
<i>spare</i>	Spare
cap_access	Cap_Access
<i>cap_access</i>	Cap_Access
bounce	Bounce
<i>bounce</i>	Bounce
dst_vnic_if	Dst_Vnic_If
<i>dst_vnic_if</i>	Dst_Vnic_If
src_vnic_if	Src_Vnic_If
<i>src_vnic_if</i>	Src_Vnic_If

pif_block_type	Pif_Block_Type
<i>pif_block_type</i>	Pif_Block_Type
epg_out	Epg_Out
<i>epg_out</i>	Epg_Out
epg_in	Epg_In
<i>epg_in</i>	Epg_In
sup_qnum	Sup_Qnum
<i>sup_qnum</i>	Sup_Qnum
sup_code	Sup_Code
<i>sup_code</i>	Sup_Code
ecn_coi	Ecn_Coi
<i>ecn_coi</i>	Ecn_Coi
ecn_cio	Ecn_Cio
<i>ecn_cio</i>	Ecn_Cio
ttl_coi	Ttl_Coi
<i>ttl_coi</i>	Ttl_Coi
ttl_cio	Ttl_Cio
<i>ttl_cio</i>	Ttl_Cio
qos_map_idx	Qos_Map_Idx
<i>qos_map_idx</i>	Qos_Map_Idx
lat_update	Lat_Update
<i>lat_update</i>	Lat_Update
lat_index	Lat_Index
<i>lat_index</i>	Lat_Index
dclass	Dclass
<i>dclass</i>	Dclass
sclass	Sclass
<i>sclass</i>	Sclass
ol_fb_metric	Ol_Fb_Metric

<i>ol_fb_metric</i>	Ol_Fb_Metric
<i>ol_fb_vpath</i>	Ol_Fb_Vpath
<i>ol_fb_vpath</i>	Ol_Fb_Vpath
<i>ol_dre</i>	Ol_Dre
<i>ol_dre</i>	Ol_Dre
<i>ol_vpath</i>	Ol_Vpath
<i>ol_vpath</i>	Ol_Vpath
<i>ol_dp</i>	Ol_Dp
<i>ol_dp</i>	Ol_Dp
<i>ol_sp</i>	Ol_Sp
<i>ol_sp</i>	Ol_Sp
<i>ol_e</i>	Ol_E
<i>ol_e</i>	Ol_E
<i>ol_dl</i>	Ol_Dl
<i>ol_dl</i>	Ol_Dl
<i>ol_lb</i>	Ol_Lb
<i>ol_lb</i>	Ol_Lb
<i>ol_mark</i>	Ol_Mark
<i>ol_mark</i>	Ol_Mark
<i>ol_udp_sp</i>	Ol_Udp_Sp
<i>ol_udp_sp</i>	Ol_Udp_Sp
<i>ol_ecn</i>	Ol_Ecn
<i>ol_ecn</i>	Ol_Ecn
<i>nat_idx</i>	Nat_Idx
<i>nat_idx</i>	Nat_Idx
<i>nat_vld</i>	Nat_Vld
<i>nat_vld</i>	Nat_Vld
<i>dst_addr1</i>	Dst_Addr1
<i>dst_addr1</i>	Dst_Addr1

dst_addr0	Dst_Addr0
<i>dst_addr0</i>	Dst_Addr0
adj_vld	Adj_Vld
<i>adj_vld</i>	Adj_Vld
encap_l2_idx	Encap_L2_Idx
<i>encap_l2_idx</i>	Encap_L2_Idx
encap_pcid	Encap_Pcid
<i>encap_pcid</i>	Encap_Pcid
encap_idx	Encap_Idx
<i>encap_idx</i>	Encap_Idx
encap_vld	Encap_Vld
<i>encap_vld</i>	Encap_Vld
my_pcid	My_Pcid
<i>my_pcid</i>	My_Pcid
my_tep_idx	My_Tep_Idx
<i>my_tep_idx</i>	My_Tep_Idx
fwd_op	Fwd_Op
<i>fwd_op</i>	Fwd_Op
orig_encap_type	Orig_Encap_Type
<i>orig_encap_type</i>	Orig_Encap_Type
pkt_type	Pkt_Type
<i>pkt_type</i>	Pkt_Type
len_type	Len_Type
<i>len_type</i>	Len_Type
cap_1588	Cap_1588
<i>cap_1588</i>	Cap_1588
pktid	Pktid
<i>pktid</i>	Pktid
srcid	Srcid

<i>srcid</i>	Srcid
tstamp	Tstamp
<i>tstamp</i>	Tstamp
pktfmt1_inner	Pktfmt1_Inner
<i>pktfmt1_inner</i>	Pktfmt1_Inner
pktfmt1_l3	Pktfmt1_L3
<i>pktfmt1_l3</i>	Pktfmt1_L3
pktfmt1_l3_type	Pktfmt1_L3_Type
<i>pktfmt1_l3_type</i>	Pktfmt1_L3_Type
pktfmt1_mpls_null	Pktfmt1_Mpls_Null
<i>pktfmt1_mpls_null</i>	Pktfmt1_Mpls_Null
pktfmt1_snap	Pktfmt1_Snap
<i>pktfmt1_snap</i>	Pktfmt1_Snap
pktfmt1_cntag	Pktfmt1_Cntag
<i>pktfmt1_cntag</i>	Pktfmt1_Cntag
pktfmt1_ttag	Pktfmt1_Ttag
<i>pktfmt1_ttag</i>	Pktfmt1_Ttag
pktfmt1_cmd_dgt	Pktfmt1_Cmd_Dgt
<i>pktfmt1_cmd_dgt</i>	Pktfmt1_Cmd_Dgt
pktfmt1_cmd_sgt	Pktfmt1_Cmd_Sgt
<i>pktfmt1_cmd_sgt</i>	Pktfmt1_Cmd_Sgt
pktfmt1_cdce	Pktfmt1_Cdce
<i>pktfmt1_cdce</i>	Pktfmt1_Cdce
pktfmt1_trill	Pktfmt1_Trill
<i>pktfmt1_trill</i>	Pktfmt1_Trill
pktfmt1_qtag2	Pktfmt1_Qtag2
<i>pktfmt1_qtag2</i>	Pktfmt1_Qtag2
pktfmt1_qtag1	Pktfmt1_Qtag1
<i>pktfmt1_qtag1</i>	Pktfmt1_Qtag1

pktfmt1_qtag0	Pktfmt1_Qtag0
<i>pktfmt1_qtag0</i>	Pktfmt1_Qtag0
pktfmt1_ivntag	Pktfmt1_Ivntag
<i>pktfmt1_ivntag</i>	Pktfmt1_Ivntag
pktfmt1_vntag	Pktfmt1_Vntag
<i>pktfmt1_vntag</i>	Pktfmt1_Vntag
pktfmt1_ce	Pktfmt1_Ce
<i>pktfmt1_ce</i>	Pktfmt1_Ce
pktfmt1_ieth	Pktfmt1_Ieth
<i>pktfmt1_ieth</i>	Pktfmt1_Ieth
pktfmt1_higig2	Pktfmt1_Higig2
<i>pktfmt1_higig2</i>	Pktfmt1_Higig2
pktfmt0_inner	Pktfmt0_Inner
<i>pktfmt0_inner</i>	Pktfmt0_Inner
pktfmt0_l3	Pktfmt0_L3
<i>pktfmt0_l3</i>	Pktfmt0_L3
pktfmt0_l3_type	Pktfmt0_L3_Type
<i>pktfmt0_l3_type</i>	Pktfmt0_L3_Type
pktfmt0_mpls_null	Pktfmt0_Mpls_Null
<i>pktfmt0_mpls_null</i>	Pktfmt0_Mpls_Null
pktfmt0_snap	Pktfmt0_Snap
<i>pktfmt0_snap</i>	Pktfmt0_Snap
pktfmt0_cntag	Pktfmt0_Cntag
<i>pktfmt0_cntag</i>	Pktfmt0_Cntag
pktfmt0_ttag	Pktfmt0_Ttag
<i>pktfmt0_ttag</i>	Pktfmt0_Ttag
pktfmt0_cmd_dgt	Pktfmt0_Cmd_Dgt
<i>pktfmt0_cmd_dgt</i>	Pktfmt0_Cmd_Dgt
pktfmt0_cmd_sgt	Pktfmt0_Cmd_Sgt

<i>pktfmt0_cmd_sgt</i>	Pktfmt0_Cmd_Sgt
pktfmt0_cdce	Pktfmt0_Cdce
<i>pktfmt0_cdce</i>	Pktfmt0_Cdce
pktfmt0_trill	Pktfmt0_Trill
<i>pktfmt0_trill</i>	Pktfmt0_Trill
pktfmt0_qtag2	Pktfmt0_Qtag2
<i>pktfmt0_qtag2</i>	Pktfmt0_Qtag2
pktfmt0_qtag1	Pktfmt0_Qtag1
<i>pktfmt0_qtag1</i>	Pktfmt0_Qtag1
pktfmt0_qtag0	Pktfmt0_Qtag0
<i>pktfmt0_qtag0</i>	Pktfmt0_Qtag0
pktfmt0_ivntag	Pktfmt0_Ivntag
<i>pktfmt0_ivntag</i>	Pktfmt0_Ivntag
pktfmt0_vntag	Pktfmt0_Vntag
<i>pktfmt0_vntag</i>	Pktfmt0_Vntag
pktfmt0_ce	Pktfmt0_Ce
<i>pktfmt0_ce</i>	Pktfmt0_Ce
pktfmt0_ieth	Pktfmt0_Ieth
<i>pktfmt0_ieth</i>	Pktfmt0_Ieth
pktfmt0_higig2	Pktfmt0_Higig2
<i>pktfmt0_higig2</i>	Pktfmt0_Higig2

Command Mode

- /exec/elamtah/outsel0

set pktrw

```
set pktrw { spare <spare> | cap_access <cap_access> | bounce <bounce> | dst_vnic_if <dst_vnic_if> | src_vnic_if
<src_vnic_if> | pif_block_type <pif_block_type> | epg_out <epg_out> | epg_in <epg_in> | sup_qnum
<sup_qnum> | sup_code <sup_code> | ecn_coi <ecn_coi> | ecn_cio <ecn_cio> | ttl_coi <ttl_coi> | ttl_cio
<ttl_cio> | qos_map_idx <qos_map_idx> | lat_update <lat_update> | lat_index <lat_index> | dclass <dclass>
| sclass <sclass> | ol_fb_metric <ol_fb_metric> | ol_fb_vpath <ol_fb_vpath> | ol_dre <ol_dre> | ol_vpath
<ol_vpath> | ol_dp <ol_dp> | ol_sp <ol_sp> | ol_e <ol_e> | ol_dl <ol_dl> | ol_lb <ol_lb> | ol_mark <ol_mark>
| ol_udp_sp <ol_udp_sp> | ol_ecn <ol_ecn> | nat_idx <nat_idx> | nat_vld <nat_vld> | dst_addr1 <dst_addr1>
| dst_addr0 <dst_addr0> | adj_vld <adj_vld> | encap_l2_idx <encap_l2_idx> | encap_pcid <encap_pcid> |
encap_idx <encap_idx> | encap_vld <encap_vld> | my_pcid <my_pcid> | my_tep_idx <my_tep_idx> | fwd_op
<fwd_op> | orig_encap_type <orig_encap_type> | pkt_type <pkt_type> | len_type <len_type> | cap_1588
<cap_1588> | pktid <pktid> | srcid <srcid> | tstamp <tstamp> | pktfmt1_inner <pktfmt1_inner> | pktfmt1_l3
<pktfmt1_l3> | pktfmt1_l3_type <pktfmt1_l3_type> | pktfmt1_mpls_null <pktfmt1_mpls_null> | pktfmt1_snap
<pktfmt1_snap> | pktfmt1_cntag <pktfmt1_cntag> | pktfmt1_ttag <pktfmt1_ttag> | pktfmt1_cmd_dgt
<pktfmt1_cmd_dgt> | pktfmt1_cmd_sgt <pktfmt1_cmd_sgt> | pktfmt1_cdce <pktfmt1_cdce> | pktfmt1_trill
<pktfmt1_trill> | pktfmt1_qtag2 <pktfmt1_qtag2> | pktfmt1_qtag1 <pktfmt1_qtag1> | pktfmt1_qtag0
<pktfmt1_qtag0> | pktfmt1_ivntag <pktfmt1_ivntag> | pktfmt1_vntag <pktfmt1_vntag> | pktfmt1_ce
<pktfmt1_ce> | pktfmt1_ieth <pktfmt1_ieth> | pktfmt1_higig2 <pktfmt1_higig2> | pktfmt0_inner
<pktfmt0_inner> | pktfmt0_l3 <pktfmt0_l3> | pktfmt0_l3_type <pktfmt0_l3_type> | pktfmt0_mpls_null
<pktfmt0_mpls_null> | pktfmt0_snap <pktfmt0_snap> | pktfmt0_cntag <pktfmt0_cntag> | pktfmt0_ttag
<pktfmt0_ttag> | pktfmt0_cmd_dgt <pktfmt0_cmd_dgt> | pktfmt0_cmd_sgt <pktfmt0_cmd_sgt> | pktfmt0_cdce
<pktfmt0_cdce> | pktfmt0_trill <pktfmt0_trill> | pktfmt0_qtag2 <pktfmt0_qtag2> | pktfmt0_qtag1
<pktfmt0_qtag1> | pktfmt0_qtag0 <pktfmt0_qtag0> | pktfmt0_ivntag <pktfmt0_ivntag> | pktfmt0_vntag
<pktfmt0_vntag> | pktfmt0_ce <pktfmt0_ce> | pktfmt0_ieth <pktfmt0_ieth> | pktfmt0_higig2 <pktfmt0_higig2>
} +
```

Syntax Description

set	Setup Trigger
pktrw	All pktrw fields
spare	Spare
<i>spare</i>	Spare
cap_access	Cap_Access
<i>cap_access</i>	Cap_Access
bounce	Bounce
<i>bounce</i>	Bounce
dst_vnic_if	Dst_Vnic_If
<i>dst_vnic_if</i>	Dst_Vnic_If
src_vnic_if	Src_Vnic_If
<i>src_vnic_if</i>	Src_Vnic_If

pif_block_type	Pif_Block_Type
<i>pif_block_type</i>	Pif_Block_Type
epg_out	Epg_Out
<i>epg_out</i>	Epg_Out
epg_in	Epg_In
<i>epg_in</i>	Epg_In
sup_qnum	Sup_Qnum
<i>sup_qnum</i>	Sup_Qnum
sup_code	Sup_Code
<i>sup_code</i>	Sup_Code
ecn_coi	Ecn_Coi
<i>ecn_coi</i>	Ecn_Coi
ecn_cio	Ecn_Cio
<i>ecn_cio</i>	Ecn_Cio
ttl_coi	Ttl_Coi
<i>ttl_coi</i>	Ttl_Coi
ttl_cio	Ttl_Cio
<i>ttl_cio</i>	Ttl_Cio
qos_map_idx	Qos_Map_Idx
<i>qos_map_idx</i>	Qos_Map_Idx
lat_update	Lat_Update
<i>lat_update</i>	Lat_Update
lat_index	Lat_Index
<i>lat_index</i>	Lat_Index
dclass	Dclass
<i>dclass</i>	Dclass
sclass	Sclass
<i>sclass</i>	Sclass
ol_fb_metric	Ol_Fb_Metric

<i>ol_fb_metric</i>	Ol_Fb_Metric
<i>ol_fb_vpath</i>	Ol_Fb_Vpath
<i>ol_fb_vpath</i>	Ol_Fb_Vpath
<i>ol_dre</i>	Ol_Dre
<i>ol_dre</i>	Ol_Dre
<i>ol_vpath</i>	Ol_Vpath
<i>ol_vpath</i>	Ol_Vpath
<i>ol_dp</i>	Ol_Dp
<i>ol_dp</i>	Ol_Dp
<i>ol_sp</i>	Ol_Sp
<i>ol_sp</i>	Ol_Sp
<i>ol_e</i>	Ol_E
<i>ol_e</i>	Ol_E
<i>ol_dl</i>	Ol_Dl
<i>ol_dl</i>	Ol_Dl
<i>ol_lb</i>	Ol_Lb
<i>ol_lb</i>	Ol_Lb
<i>ol_mark</i>	Ol_Mark
<i>ol_mark</i>	Ol_Mark
<i>ol_udp_sp</i>	Ol_Udp_Sp
<i>ol_udp_sp</i>	Ol_Udp_Sp
<i>ol_ecn</i>	Ol_Ecn
<i>ol_ecn</i>	Ol_Ecn
<i>nat_idx</i>	Nat_Idx
<i>nat_idx</i>	Nat_Idx
<i>nat_vld</i>	Nat_Vld
<i>nat_vld</i>	Nat_Vld
<i>dst_addr1</i>	Dst_Addr1
<i>dst_addr1</i>	Dst_Addr1

dst_addr0	Dst_Addr0
<i>dst_addr0</i>	Dst_Addr0
adj_vld	Adj_Vld
<i>adj_vld</i>	Adj_Vld
encap_l2_idx	Encap_L2_Idx
<i>encap_l2_idx</i>	Encap_L2_Idx
encap_pcid	Encap_Pcid
<i>encap_pcid</i>	Encap_Pcid
encap_idx	Encap_Idx
<i>encap_idx</i>	Encap_Idx
encap_vld	Encap_Vld
<i>encap_vld</i>	Encap_Vld
my_pcid	My_Pcid
<i>my_pcid</i>	My_Pcid
my_tep_idx	My_Tep_Idx
<i>my_tep_idx</i>	My_Tep_Idx
fwd_op	Fwd_Op
<i>fwd_op</i>	Fwd_Op
orig_encap_type	Orig_Encap_Type
<i>orig_encap_type</i>	Orig_Encap_Type
pkt_type	Pkt_Type
<i>pkt_type</i>	Pkt_Type
len_type	Len_Type
<i>len_type</i>	Len_Type
cap_1588	Cap_1588
<i>cap_1588</i>	Cap_1588
pktid	Pktid
<i>pktid</i>	Pktid
srcid	Srcid

<i>srcid</i>	Srcid
tstmp	Tstmp
<i>tstmp</i>	Tstmp
pktfmt1_inner	Pktfmt1_Inner
<i>pktfmt1_inner</i>	Pktfmt1_Inner
pktfmt1_l3	Pktfmt1_L3
<i>pktfmt1_l3</i>	Pktfmt1_L3
pktfmt1_l3_type	Pktfmt1_L3_Type
<i>pktfmt1_l3_type</i>	Pktfmt1_L3_Type
pktfmt1_mpls_null	Pktfmt1_Mpls_Null
<i>pktfmt1_mpls_null</i>	Pktfmt1_Mpls_Null
pktfmt1_snap	Pktfmt1_Snap
<i>pktfmt1_snap</i>	Pktfmt1_Snap
pktfmt1_cntag	Pktfmt1_Cntag
<i>pktfmt1_cntag</i>	Pktfmt1_Cntag
pktfmt1_ttag	Pktfmt1_Ttag
<i>pktfmt1_ttag</i>	Pktfmt1_Ttag
pktfmt1_cmd_dgt	Pktfmt1_Cmd_Dgt
<i>pktfmt1_cmd_dgt</i>	Pktfmt1_Cmd_Dgt
pktfmt1_cmd_sgt	Pktfmt1_Cmd_Sgt
<i>pktfmt1_cmd_sgt</i>	Pktfmt1_Cmd_Sgt
pktfmt1_cdce	Pktfmt1_Cdce
<i>pktfmt1_cdce</i>	Pktfmt1_Cdce
pktfmt1_trill	Pktfmt1_Trill
<i>pktfmt1_trill</i>	Pktfmt1_Trill
pktfmt1_qtag2	Pktfmt1_Qtag2
<i>pktfmt1_qtag2</i>	Pktfmt1_Qtag2
pktfmt1_qtag1	Pktfmt1_Qtag1
<i>pktfmt1_qtag1</i>	Pktfmt1_Qtag1

pktfmt1_qtag0	Pktfmt1_Qtag0
<i>pktfmt1_qtag0</i>	Pktfmt1_Qtag0
pktfmt1_ivntag	Pktfmt1_Ivntag
<i>pktfmt1_ivntag</i>	Pktfmt1_Ivntag
pktfmt1_vntag	Pktfmt1_Vntag
<i>pktfmt1_vntag</i>	Pktfmt1_Vntag
pktfmt1_ce	Pktfmt1_Ce
<i>pktfmt1_ce</i>	Pktfmt1_Ce
pktfmt1_ieth	Pktfmt1_Ieth
<i>pktfmt1_ieth</i>	Pktfmt1_Ieth
pktfmt1_higig2	Pktfmt1_Higig2
<i>pktfmt1_higig2</i>	Pktfmt1_Higig2
pktfmt0_inner	Pktfmt0_Inner
<i>pktfmt0_inner</i>	Pktfmt0_Inner
pktfmt0_l3	Pktfmt0_L3
<i>pktfmt0_l3</i>	Pktfmt0_L3
pktfmt0_l3_type	Pktfmt0_L3_Type
<i>pktfmt0_l3_type</i>	Pktfmt0_L3_Type
pktfmt0_mpls_null	Pktfmt0_Mpls_Null
<i>pktfmt0_mpls_null</i>	Pktfmt0_Mpls_Null
pktfmt0_snap	Pktfmt0_Snap
<i>pktfmt0_snap</i>	Pktfmt0_Snap
pktfmt0_cntag	Pktfmt0_Cntag
<i>pktfmt0_cntag</i>	Pktfmt0_Cntag
pktfmt0_ttag	Pktfmt0_Ttag
<i>pktfmt0_ttag</i>	Pktfmt0_Ttag
pktfmt0_cmd_dgt	Pktfmt0_Cmd_Dgt
<i>pktfmt0_cmd_dgt</i>	Pktfmt0_Cmd_Dgt
pktfmt0_cmd_sgt	Pktfmt0_Cmd_Sgt

<i>pktfmt0_cmd_sgt</i>	Pktfmt0_Cmd_Sgt
pktfmt0_cdce	Pktfmt0_Cdce
<i>pktfmt0_cdce</i>	Pktfmt0_Cdce
pktfmt0_trill	Pktfmt0_Trill
<i>pktfmt0_trill</i>	Pktfmt0_Trill
pktfmt0_qtag2	Pktfmt0_Qtag2
<i>pktfmt0_qtag2</i>	Pktfmt0_Qtag2
pktfmt0_qtag1	Pktfmt0_Qtag1
<i>pktfmt0_qtag1</i>	Pktfmt0_Qtag1
pktfmt0_qtag0	Pktfmt0_Qtag0
<i>pktfmt0_qtag0</i>	Pktfmt0_Qtag0
pktfmt0_ivntag	Pktfmt0_Ivntag
<i>pktfmt0_ivntag</i>	Pktfmt0_Ivntag
pktfmt0_vntag	Pktfmt0_Vntag
<i>pktfmt0_vntag</i>	Pktfmt0_Vntag
pktfmt0_ce	Pktfmt0_Ce
<i>pktfmt0_ce</i>	Pktfmt0_Ce
pktfmt0_ieth	Pktfmt0_Ieth
<i>pktfmt0_ieth</i>	Pktfmt0_Ieth
pktfmt0_higig2	Pktfmt0_Higig2
<i>pktfmt0_higig2</i>	Pktfmt0_Higig2

Command Mode

- /exec/elamtah/outsel1

set pktrw

```
set pktrw { mcast <mcast> | sup_redir <sured> | bcm_proxy <bcm_proxy> | excep_case <excep> | transit
<trans> | vpc_df <vpc_df> | src_tep_idx <src_tep> | lat_update <lat_update> | lat_idx <lat_idx> | src_class
<sclass> | ol_fb_met <ol_fb_met> | ol_fb_vpath <ol_fb_vpath> | ol_dre <ol_dre> | ol_vpath <ol_vpath> |
ol_dp <ol_dp> | ol_sp <ol_sp> | ol_e <ol_e> | ol_dl <ol_dl> | ol_lb <ol_lb> | ol_mark <ol_mark> | ol_udp_sp
<ol_udp_sp> | ol_ftag <ol_ftag> | ol_segid <ol_segid> | ol_ttl <ol_ttl> | ol_ecn <ol_ecn> | ol_dscp <ol_dscp>
| ol_de <ol_de> | ol_cos <ol_cos> | ol_mac <ol_mac> | ol_encap_idx <ol_encap> | ol_vpc <ol_vpc> | ol_idx
<ol_idx> | ttl <ttl> | dscp <dscp> | vlan1 <vlan1> | ecn_coi <ecn_coi> | ecn_cio <ecn_cio> | ttl_coi <ttl_coi>
| ttl_cio <ttl_cio> | adj_idx <adj_idx> | vntag_svif <vntag_svif> | de <de> | cos <cos> | vlan0 <vlan0> | adj_vld
<adj_vld> | uc_routed <uc_routed> | loopback <lpb> | ecn <ecn> | hg2_vid <hg2_vlan> | hg2_ppd <hg2_ppd>
| hg2_tc_sup_copy <hg2_tcscopy> | hg2_tc <hg2_tc> | hg2_lbid <hg2_lbid> | hg2_opc <hg2_opc> | hg2_dstpid
<hg2_dpид> | hg2_srcpid <hg2_spид> | hg2_dstmod <hg2_dmod> | hg2_srcmod <hg2_smod> | op_inner
<op_inner> | op_qtag <op_qtag> | op_vntag <op_vntag> | op_outer <op_outer> | pkt_type <pkt_type> | drop
<drp> | pkt_tstmp <pkt_tstmp> | tstmp <tstmp> | cap_tstmp <cap_tstmp> | len_info <len_info> | len_type
<len_type> | pktid <pktid> | srcid <srcid> | pktfmt1 <pktfmt1> | pktfmt0 <pktfmt0> | hg2_cos <hg2_cos> }
+
```

Syntax Description

set	Setup Trigger
pktrw	All packet re-write fields
mcast	mcast
<i>mcast</i>	Mcast
sup_redir	Sup Redirect
<i>sured</i>	Sup Redirect
bcm_proxy	Broadcom Proxy
<i>bcm_proxy</i>	Broadcom Proxy
excep_case	Excep_case
<i>excep</i>	Excep_case
transit	Transit
<i>trans</i>	Transit
vpc_df	VPC_df
<i>vpc_df</i>	VPC_df
src_tep_idx	Src TEP Index
<i>src_tep</i>	Src TEP Index
lat_update	Lat Update

<i>lat_update</i>	Lat Update
lat_idx	Lat Index
<i>lat_idx</i>	Lat Index
src_class	Source Class
<i>sclass</i>	Source Class
ol_fb_met	Ol_fb_metric
<i>ol_fb_met</i>	Ol_fb_metric
ol_fb_vpath	Ol_fb_vpath
<i>ol_fb_vpath</i>	Ol_fb_vpath
ol_dre	Ol_dre
<i>ol_dre</i>	Ol_dre
ol_vpath	Ol_vpath
<i>ol_vpath</i>	Ol_vpath
ol_dp	Ol_dp
<i>ol_dp</i>	Ol_dp
ol_sp	Ol_sp
<i>ol_sp</i>	Ol_sp
ol_e	Ol_e
<i>ol_e</i>	Ol_e
ol_dl	Ol_dl
<i>ol_dl</i>	Ol_dl
ol_lb	Ol_lb
<i>ol_lb</i>	Ol_lb
ol_mark	Ol_mark
<i>ol_mark</i>	Ol_mark
ol_udp_sp	Ol_UDP_sp
<i>ol_udp_sp</i>	Ol UDP Source Port
ol_ftag	Ol_ftag
<i>ol_ftag</i>	Ol_ftag

ol_segid	Ol_segid
<i>ol_segid</i>	Ol_segid
ol_ttl	Ol_TTL
<i>ol_ttl</i>	Ol_TTL
ol_ecn	Ol_ecn
<i>ol_ecn</i>	Ol_ecn
ol_dscp	Ol_dscp
<i>ol_dscp</i>	Ol_dscp
ol_de	Ol_de
<i>ol_de</i>	Ol_de
ol_cos	Ol_cos
<i>ol_cos</i>	Ol_cos
ol_mac	Ol_mac
<i>ol_mac</i>	Ol_mac
ol_encap_idx	Ol_encap_idx
<i>ol_encap</i>	Ol_encap_idx
ol_vpc	Ol_VPC
<i>ol_vpc</i>	Ol_VPC
ol_idx	Ol_idx
<i>ol_idx</i>	Ol_idx
ttl	TTL
<i>ttl</i>	TTL
dscp	DSCP
<i>dscp</i>	DSCP
vlan1	Vlan1
<i>vlan1</i>	Vlan1
ecn_coi	ecn_coi
<i>ecn_coi</i>	ecn_coi
ecn_cio	ecn_cio

<i>ecn_cio</i>	ecn_cio
ttl_coi	ttl_coi
<i>ttl_coi</i>	ttl_coi
ttl_cio	ttl_cio
<i>ttl_cio</i>	ttl_cio
adj_idx	adj_idx
<i>adj_idx</i>	adj_idx
vntag_svif	vntag_svif
<i>vntag_svif</i>	vntag_svif
de	de
<i>de</i>	de
cos	cos
<i>cos</i>	cos
vlan0	vlan0
<i>vlan0</i>	vlan0
adj_vld	adj_vld
<i>adj_vld</i>	adj_vld
uc_routed	uc_routed
<i>uc_routed</i>	uc_routed
loopback	loopback
<i>lpb</i>	loopback
ecn	ecn
<i>ecn</i>	ecn
hg2_vid	High Gig2 VLAN Tag
<i>hg2_vlan</i>	High Gig2 VLAN Tag Information
hg2_cos	High Gig2 CoS Information
<i>hg2_cos</i>	High Gig2 CoS Information
hg2_ppd	High Gig2 Packet Processing Descriptor
<i>hg2_ppd</i>	High Gig2 Packet Processing Descriptor

hg2_tc_sup_copy	High Gig2 Traffic Class SUP Copy
<i>hg2_tcscopy</i>	High Gig2 Traffic Class SUP Copy
hg2_tc	High Gig2 Packet Traffic Class
<i>hg2_tc</i>	High Gig2 Packet Traffic Class
hg2_lbid	High Gig2 Packet Ibid
<i>hg2_lbid</i>	High Gig2 Packet Ibid
hg2_opc	High Gig2 Packet Type
<i>hg2_opc</i>	High Gig2 Packet Type
hg2_dstpid	High Gig2 Destination Port ID
<i>hg2_dpid</i>	High Gig2 Destination Port ID
hg2_dstmod	High Gig2 Destination Module ID
<i>hg2_dmod</i>	High Gig2 Destination Module ID
hg2_srcpid	High Gig2 Source Port ID
<i>hg2_spid</i>	High Gig2 Source Port ID
hg2_srcmod	High Gig2 Souce Module ID
<i>hg2_smod</i>	High Gig2 Souce Module ID
op_inner	Op_inner
<i>op_inner</i>	Op_inner
op_outer	Op_outer
<i>op_outer</i>	Op_outer
op_qtag	Op_qtag
<i>op_qtag</i>	Op_qtag
op_vntag	Op_vntag
<i>op_vntag</i>	Op_vntag
pkt_type	Pkt_type
<i>pkt_type</i>	Pkt_type
drop	Drop
<i>drp</i>	Drop
pkt_tstamp	Packet timestamp

<i>pkt_tstamp</i>	Packet timestamp
tstamp	Timestamp
<i>tstamp</i>	Timestamp
cap_tstamp	Capture Timestamp
<i>cap_tstamp</i>	Capture Timestamp
len_info	Len_info
<i>len_info</i>	Len_info
len_type	Len_type
<i>len_type</i>	Len_type
pktid	Pkt_id
<i>pktid</i>	Pkt_id
srcid	Src_id
<i>srcid</i>	Src_id
pktfmt1	Pktfmt1
<i>pktfmt1</i>	Pktfmt1
pktfmt0	Pktfmt0
<i>pktfmt0</i>	Pktfmt0

Command Mode

- /exec/elanms/outsel0

set sb_info

```
set sb_info { oslice_vec <oslice_vec> | srvc_oslice_vec <srvc_oslice_vec> | is_tcp <is_tcp> | srvc_class
<srvc_class> | cpu_oclass <cpu_oclass> | set_v <set_v> | set_idx <set_idx> | set_last <set_last> | bd <bd> |
src_is_l3_if <src_is_l3_if> | src_is_vpc_peer <src_is_vpc_peer> | is_my_tep <is_my_tep> | src_sh_group
<src_sh_group> | ftag <ftag> | rpf_fail <rpf_fail> | post_route_flood <post_route_flood> | pkt_hash <pkt_hash>
| bpdu <bpdu> | met0_v <met0_v> | met0_idx <met0_idx> | met0_last <met0_last> | met1_v <met1_v> |
met1_idx <met1_idx> | met1_last <met1_last> | ip_clen <ip_clen> | ip_clen <ip_clen> | sod_cap <sod_cap>
| sod_en <sod_en> } +
```

Syntax Description

set	Setup Trigger
sb_info	All sb_info fields
oslice_vec	Oslice_Vec
<i>oslice_vec</i>	Oslice_Vec
srvc_oslice_vec	srvc_oslice_vec
<i>srvc_oslice_vec</i>	srvc_oslice_vec
is_tcp	is_tcp
<i>is_tcp</i>	is_tcp
srvc_class	srvc_class
<i>srvc_class</i>	srvc_class
cpu_oclass	cpu_oclass
<i>cpu_oclass</i>	cpu_oclass
set_v	set_v
<i>set_v</i>	set_v
set_idx	set_idx
<i>set_idx</i>	set_idx
set_last	set_last
<i>set_last</i>	set_last
bd	bd
<i>bd</i>	bd
src_is_l3_if	src_is_l3_if
<i>src_is_l3_if</i>	src_is_l3_if

src_is_vpc_peer	src_is_vpc_peer
<i>src_is_vpc_peer</i>	src_is_vpc_peer
is_my_tep	is_my_tep
<i>is_my_tep</i>	is_my_tep
src_sh_group	src_sh_group
<i>src_sh_group</i>	src_sh_group
ftag	ftag
<i>ftag</i>	ftag
rpf_fail	rpf_fail
<i>rpf_fail</i>	rpf_fail
post_route_flood	post_route_flood
<i>post_route_flood</i>	post_route_flood
pkt_hash	pkt_hash
<i>pkt_hash</i>	pkt_hash
bpdu	bpdu
<i>bpdu</i>	bpdu
met0_v	met0_v
<i>met0_v</i>	met0_v
met0_idx	met0_idx
<i>met0_idx</i>	met0_idx
met0_last	met0_last
<i>met0_last</i>	met0_last
met1_v	met1_v
<i>met1_v</i>	met1_v
met1_idx	met1_idx
<i>met1_idx</i>	met1_idx
met1_last	met1_last
<i>met1_last</i>	met1_last
ip_clen	ip_clen

<i>ip_clen</i>	ip_clen
sod_cap	sod_cap
<i>sod_cap</i>	sod_cap
sod_en	sod_en
<i>sod_en</i>	sod_en

Command Mode

- /exec/elamtah/outse10

set sb_info

```
set sb_info { oslice_vec <oslice_vec> | srvc_oslice_vec <srvc_oslice_vec> | is_tcp <is_tcp> | srvc_class
<srvc_class> | cpu_oclass <cpu_oclass> | set_v <set_v> | set_idx <set_idx> | set_last <set_last> | bd <bd> |
src_is_l3_if <src_is_l3_if> | src_is_vpc_peer <src_is_vpc_peer> | is_my_tep <is_my_tep> | src_sh_group
<src_sh_group> | ftag <ftag> | rpf_fail <rpf_fail> | post_route_flood <post_route_flood> | pkt_hash <pkt_hash>
| bpdu <bpdu> | met0_v <met0_v> | met0_idx <met0_idx> | met0_last <met0_last> | met1_v <met1_v> |
met1_idx <met1_idx> | met1_last <met1_last> | ip_clen <ip_clen> | ip_clen <ip_clen> | sod_cap <sod_cap>
| sod_en <sod_en> } +
```

Syntax Description

set	Setup Trigger
sb_info	All sb_info fields
oslice_vec	Oslice_Vec
<i>oslice_vec</i>	Oslice_Vec
srvc_oslice_vec	srvc_oslice_vec
<i>srvc_oslice_vec</i>	srvc_oslice_vec
is_tcp	is_tcp
<i>is_tcp</i>	is_tcp
srvc_class	srvc_class
<i>srvc_class</i>	srvc_class
cpu_oclass	cpu_oclass
<i>cpu_oclass</i>	cpu_oclass
set_v	set_v
<i>set_v</i>	set_v
set_idx	set_idx
<i>set_idx</i>	set_idx
set_last	set_last
<i>set_last</i>	set_last
bd	bd
<i>bd</i>	bd
src_is_l3_if	src_is_l3_if
<i>src_is_l3_if</i>	src_is_l3_if

src_is_vpc_peer	src_is_vpc_peer
<i>src_is_vpc_peer</i>	src_is_vpc_peer
is_my_tep	is_my_tep
<i>is_my_tep</i>	is_my_tep
src_sh_group	src_sh_group
<i>src_sh_group</i>	src_sh_group
ftag	ftag
<i>ftag</i>	ftag
rpf_fail	rpf_fail
<i>rpf_fail</i>	rpf_fail
post_route_flood	post_route_flood
<i>post_route_flood</i>	post_route_flood
pkt_hash	pkt_hash
<i>pkt_hash</i>	pkt_hash
bpdu	bpdu
<i>bpdu</i>	bpdu
met0_v	met0_v
<i>met0_v</i>	met0_v
met0_idx	met0_idx
<i>met0_idx</i>	met0_idx
met0_last	met0_last
<i>met0_last</i>	met0_last
met1_v	met1_v
<i>met1_v</i>	met1_v
met1_idx	met1_idx
<i>met1_idx</i>	met1_idx
met1_last	met1_last
<i>met1_last</i>	met1_last
ip_clen	ip_clen

<i>ip_clen</i>	ip_clen
sod_cap	sod_cap
<i>sod_cap</i>	sod_cap
sod_en	sod_en
<i>sod_en</i>	sod_en

Command Mode

- /exec/elamtah/outsel2

set sideband

```
set sideband { cpu_oport <cpu_oport> | span_idx <span_idx> | ovector_idx <ovector_idx> | iclass <iclass> |
oclass <oclass> | opcode <opcode> | ecncapable <ecncapable> | nodrop <nodrop> | storefwd <storefwd> |
spantransit <spantransit> | rr <rr> | ecnmark <ecnmark> | gbw_tagged <gbw_tagged> | gbw_color <gbw_color>
| bnce <bnce> | spanslc <spanslc> | segrate <segrate> | mark <mark> } +
```

Syntax Description

set	Setup Trigger
sideband	All sideband fields
cpu_oport	Cpu_Oport
<i>cpu_oport</i>	Cpu_Oport
span_idx	Span_Idx
<i>span_idx</i>	Span_Idx
ovector_idx	Ovector_Idx
<i>ovector_idx</i>	Ovector_Idx
iclass	Iclass
<i>iclass</i>	Iclass
oclass	Oclass
<i>oclass</i>	Oclass
opcode	Opcode
<i>opcode</i>	Opcode
ecncapable	Ecncapable
<i>ecncapable</i>	Ecncapable
nodrop	Nodrop
<i>nodrop</i>	Nodrop
storefwd	Storefwd
<i>storefwd</i>	Storefwd
spantransit	Spantransit
<i>spantransit</i>	Spantransit
rr	Rr

<i>rr</i>	Rr
ecnmark	Ecnmark
<i>ecnmark</i>	Ecnmark
gbw_tagged	Gbw_Tagged
<i>gbw_tagged</i>	Gbw_Tagged
gbw_color	Gbw_Color
<i>gbw_color</i>	Gbw_Color
bnce	Bnce
<i>bnce</i>	Bnce
spanslc	Spanslc
<i>spanslc</i>	Spanslc
segrate	Segrate
<i>segrate</i>	Segrate
mark	Mark
<i>mark</i>	Mark

Command Mode

- /exec/elamta/outsel2

set sideband

```
set sideband { cpu_oport <cpu_oport> | span_idx <span_idx> | ovector_idx <ovector_idx> | iclass <iclass> |
oclass <oclass> | opcode <opcode> | ecncapable <ecncapable> | nodrop <nodrop> | storefwd <storefwd> |
spantransit <spantransit> | rr <rr> | ecnmark <ecnmark> | gbw_tagged <gbw_tagged> | gbw_color <gbw_color>
| bnce <bnce> | spanslc <spanslc> | segrate <segrate> | mark <mark> } +
```

Syntax Description

set	Setup Trigger
sideband	All sideband fields
cpu_oport	Cpu_Oport
<i>cpu_oport</i>	Cpu_Oport
span_idx	Span_Idx
<i>span_idx</i>	Span_Idx
ovector_idx	Ovector_Idx
<i>ovector_idx</i>	Ovector_Idx
iclass	Iclass
<i>iclass</i>	Iclass
oclass	Oclass
<i>oclass</i>	Oclass
opcode	Opcode
<i>opcode</i>	Opcode
ecncapable	Ecncapable
<i>ecncapable</i>	Ecncapable
nodrop	Nodrop
<i>nodrop</i>	Nodrop
storefwd	Storefwd
<i>storefwd</i>	Storefwd
spantransit	Spantransit
<i>spantransit</i>	Spantransit
rr	Rr

<i>rr</i>	Rr
ecnmark	Ecnmark
<i>ecnmark</i>	Ecnmark
gbw_tagged	Gbw_Tagged
<i>gbw_tagged</i>	Gbw_Tagged
gbw_color	Gbw_Color
<i>gbw_color</i>	Gbw_Color
bnce	Bnce
<i>bnce</i>	Bnce
spanslc	Spanslc
<i>spanslc</i>	Spanslc
segrate	Segrate
<i>segrate</i>	Segrate
mark	Mark
<i>mark</i>	Mark

Command Mode

- /exec/elamta/outsel0

set sideband

```
set sideband { cpu_oport <cpu_oport> | span_idx <span_idx> | ovector_idx <ovector_idx> | iclass <iclass> |
oclass <oclass> | opcode <opcode> | ecncapable <ecncapable> | nodrop <nodrop> | storefwd <storefwd> |
spantransit <spantransit> | rr <rr> | ecnmark <ecnmark> | gbw_tagged <gbw_tagged> | gbw_color <gbw_color>
| bnce <bnce> | spanslc <spanslc> | segrate <segrate> | mark <mark> } +
```

Syntax Description

set	Setup Trigger
sideband	All sideband fields
cpu_oport	Cpu_Oport
<i>cpu_oport</i>	Cpu_Oport
span_idx	Span_Idx
<i>span_idx</i>	Span_Idx
ovector_idx	Ovector_Idx
<i>ovector_idx</i>	Ovector_Idx
iclass	Iclass
<i>iclass</i>	Iclass
oclass	Oclass
<i>oclass</i>	Oclass
opcode	Opcode
<i>opcode</i>	Opcode
ecncapable	Ecncapable
<i>ecncapable</i>	Ecncapable
nodrop	Nodrop
<i>nodrop</i>	Nodrop
storefwd	Storefwd
<i>storefwd</i>	Storefwd
spantransit	Spantransit
<i>spantransit</i>	Spantransit
rr	Rr

<i>rr</i>	Rr
ecnmark	Ecnmark
<i>ecnmark</i>	Ecnmark
gbw_tagged	Gbw_Tagged
<i>gbw_tagged</i>	Gbw_Tagged
gbw_color	Gbw_Color
<i>gbw_color</i>	Gbw_Color
bnce	Bnce
<i>bnce</i>	Bnce
spanslc	Spanslc
<i>spanslc</i>	Spanslc
segrate	Segrate
<i>segrate</i>	Segrate
mark	Mark
<i>mark</i>	Mark

Command Mode

- /exec/elamta/outsell

set sideband

```
set sideband { span_vec <span_vec> | bounce <bnc> | mclast <mclast> | mcastcurptr <mccurptr> | mcastcurptr_v
<mccurptr_v> | srcport <sport> | vlan <vlan> | segwgt <segwgt> | segid <segid> | seglocal <seglcl> | gbw_color
<gbw_color> | gbw_tag <gbw_tagg> | fwddrp <fwddrp> | l2fld <l2fld> | nodrp <nodrp> | ovrlyidx <ovrlyidx>
| ecncap <ecncap> | cpu <cpu> | store_fwd <stfwd> | mcast <mcast> | oclass <ocls> | iclass <icls> | odest_v
<odest_v> | odest <odest> | ovec <ovec> | span_trans <span_trans> | lbtype <lbtype> | lbena <lbena> | tdmid
<tdmid> | pktid <pktid> | srcid <srcid> | eoferror <eoferr> | eofbytes <eofby> | eof <eof> | sof <sof> } +
```

Syntax Description

set	Setup Trigger
sideband	All sideband fields
span_vec	SPAN vector
<i>span_vec</i>	SPAN vector
bounce	Bounce
<i>bnc</i>	Bounce
mclast	Mclast
<i>mclast</i>	Mclast
mcastcurptr	Mcast cur ptr
<i>mccurptr</i>	Mcast cur ptr
mcastcurptr_v	Mcast cur ptr v
<i>mccurptr_v</i>	Mcast cur ptr v
srcport	Source Port
<i>sport</i>	Source Port
vlan	Vlan
<i>vlan</i>	Vlan
segwgt	Segwgt
<i>segwgt</i>	Segwgt
segid	Segid
<i>segid</i>	Segid
seglocal	Seglocal
<i>seglcl</i>	Seglocal

gbw_color	GBW color
<i>gbw_color</i>	GBW color
gbw_tag	GBW tagged
<i>gbw_tagg</i>	GBW tagged
fwddrp	Forward drop
<i>fwddrp</i>	Forward drop
l2fld	L2 Flood
<i>l2fld</i>	L2 Flood
nodrp	No drop
<i>nodrp</i>	No drop
ovrlyidx	Overlay index
<i>ovrlyidx</i>	Overlay index
ecncap	ECN Capable
<i>ecncap</i>	ECN Capable
cpu	CPU
<i>cpu</i>	CPU
store_fwd	Store_fwd
<i>stfwd</i>	Store_fwd
mcast	Multicast
<i>mcast</i>	Multicast
oclass	Output class
<i>ocls</i>	Output class
iclass	Input class
<i>icls</i>	Input class
odest_v	Odest_v
<i>odest_v</i>	Odest_v
odest	Odest
<i>odest</i>	Odest
ovec	Ovector

<i>ovec</i>	Ovector
<i>span_trans</i>	SPAN transit
<i>span_trans</i>	SPAN transit
<i>lbtype</i>	Lbtype
<i>lbtype</i>	Lbtype
<i>lbena</i>	Lbenable
<i>lbena</i>	Lbenable
<i>tdmid</i>	Tdmid
<i>tdmid</i>	Tdmid
<i>pktid</i>	Pkt_id
<i>pktid</i>	Pkt_id
<i>srcid</i>	Src_id
<i>srcid</i>	Src_id
<i>eoferror</i>	EOF error
<i>eoferr</i>	EOF erro
<i>eofbytes</i>	EOF bytes
<i>eofby</i>	EOF bytes
<i>eof</i>	EOF
<i>eof</i>	EOF
<i>sof</i>	SOF
<i>sof</i>	SOF

Command Mode

- /exec/elanms/outsel5

set stats

```
set stats { vld0 <vld0> | atomic0 <atomic0> | mode0 <mode0> | index0 <index0> | vld1 <vld1> | atomic1
<atomic1> | mode1 <mode1> | index1 <index1> | vld2 <vld2> | atomic2 <atomic2> | mode2 <mode2> | index2
<index2> | vld3 <vld3> | atomic3 <atomic3> | mode3 <mode3> | index3 <index3> | vld4 <vld4> | atomic4
<atomic4> | mode4 <mode4> | index4 <index4> | vld5 <vld5> | atomic5 <atomic5> | mode5 <mode5> | index5
<index5> | vld6 <vld6> | atomic6 <atomic6> | mode6 <mode6> | index6 <index6> | vld7 <vld7> | atomic7
<atomic7> | mode7 <mode7> | index7 <index7> } +
```

Syntax Description

set	Setup Trigger
stats	All stats fields
vld0	Vld0
<i>vld0</i>	Vld0
atomic0	Atomic0
<i>atomic0</i>	Atomic0
mode0	Mode0
<i>mode0</i>	Mode0
index0	Index0
<i>index0</i>	Index0
vld1	Vld1
<i>vld1</i>	Vld1
atomic1	Atomic1
<i>atomic1</i>	Atomic1
mode1	Mode1
<i>mode1</i>	Mode1
index1	Index1
<i>index1</i>	Index1
vld2	Vld2
<i>vld2</i>	Vld2
atomic2	Atomic2
<i>atomic2</i>	Atomic2

mode2	Mode2
<i>mode2</i>	Mode2
index2	Index2
<i>index2</i>	Index2
vld3	Vld3
<i>vld3</i>	Vld3
atomic3	Atomic3
<i>atomic3</i>	Atomic3
mode3	Mode3
<i>mode3</i>	Mode3
index3	Index3
<i>index3</i>	Index3
vld4	Vld4
<i>vld4</i>	Vld4
atomic4	Atomic4
<i>atomic4</i>	Atomic4
mode4	Mode4
<i>mode4</i>	Mode4
index4	Index4
<i>index4</i>	Index4
vld5	Vld5
<i>vld5</i>	Vld5
atomic5	Atomic5
<i>atomic5</i>	Atomic5
mode5	Mode5
<i>mode5</i>	Mode5
index5	Index5
<i>index5</i>	Index5
vld6	Vld6

<i>vld6</i>	Vld6
atomic6	Atomic6
<i>atomic6</i>	Atomic6
mode6	Mode6
<i>mode6</i>	Mode6
index6	Index6
<i>index6</i>	Index6
vld7	Vld7
<i>vld7</i>	Vld7
atomic7	Atomic7
<i>atomic7</i>	Atomic7
mode7	Mode7
<i>mode7</i>	Mode7
index7	Index7
<i>index7</i>	Index7

Command Mode

- /exec/elamtah/outsel2

set tag

```
{ { set tag <value> } | { no set tag [ <value> ] } }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
tag	Tag value for destination routing protocol
<i>value</i>	Tag value

Command Mode

- /exec/configure/route-map

set weight

```
{ set weight <count> | no set weight [ <count> ] }
```

Syntax Description

no	Negate a command or set its defaults
set	Set values in destination routing protocol
weight	BGP weight for routing table
<i>count</i>	Weight value

Command Mode

- /exec/configure/route-map

setup

setup

Syntax Description

setup	Run the basic SETUP command facility
-------	--------------------------------------

Command Mode

- /exec

sflow

```
sflow { [ sampling-rate <rate> ] | [ max-sampled-size <pkt-size> ] | [ counter-poll-interval <interval> ] | [ max-datagram-size <dgram-size> ] | [ collector-ip <dst-ip> vrf { <vrf-name> | <vrf-known-name> } ] [ source <src-ip> ] | [ collector-port <dst-port> ] | [ agent-ip <agent-ip> ] }
```

Syntax Description

sflow	change sFlow global settings
sampling-rate	(Optional) sFlow Sampling Rate
<i>rate</i>	(Optional)
max-sampled-size	(Optional) sFlow Sampled Size
<i>pkt-size</i>	(Optional) sFlow Sampled Size
counter-poll-interval	(Optional) sFlow Counter Poll Interval
<i>interval</i>	(Optional) sFlow Counter Poll Interval
max-datagram-size	(Optional) sFlow Datagram Size
<i>dgram-size</i>	(Optional) sFlow Datagram Size
collector-ip	(Optional) sFlow Collector IP address
<i>dst-ip</i>	(Optional) sFlow Collector IP address
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
source	(Optional) Source IP address to send to sFlow Collector
<i>src-ip</i>	(Optional) Source IP address to send to sFlow Collector
collector-port	(Optional) sFlow Collector UDP port
<i>dst-port</i>	(Optional) sFlow Collector UDP port
agent-ip	(Optional) sFlow Agent IP address
<i>agent-ip</i>	(Optional) sFlow Agent IP address

Command Mode

- /exec/configure

sflow

[no] sflow { sampling-rate | max-sampled-size | counter-poll-interval | max-datagram-size | collector-ip | collector-port | agent-ip }

Syntax Description

no	Negate a command or set its defaults
sflow	change sFlow global settings
sampling-rate	sFlow Sampling Rate
max-sampled-size	sFlow Sampled Size
counter-poll-interval	sFlow Counter Poll Interval
max-datagram-size	sFlow Datagram Size
collector-ip	sFlow Collector IP address
collector-port	sFlow Collector UDP port
agent-ip	sFlow Agent IP address

Command Mode

- /exec/configure

sflow data-source interface

sflow data-source interface { <ifnum> | <pcifnum> }

Syntax Description

sflow	change sFlow global settings
data-source	sFlow Data Source
interface	sFlow Data Source Interface
<i>ifnum</i>	sFlow Data Source Interface
<i>pcifnum</i>	sFlow Data Source Interface

Command Mode

- /exec/configure

sflow data-source interface

[no] sflow data-source interface { <ifnum> | <pcifnum> }

Syntax Description

no	Negate a command or set its defaults
sflow	change sFlow global settings
data-source	sFlow Data Source
interface	sFlow Data Source Interface
<i>ifnum</i>	sFlow Data Source Interface
<i>pcifnum</i>	sFlow Data Source Interface

Command Mode

- /exec/configure

sflow extended switch

[no] sflow extended switch

Syntax Description

no	(Optional) Negate a command or set its defaults
sflow	change sFlow global settings
extended	sFlow extended flow records
switch	sFlow extended switch flow

Command Mode

- /exec/configure

shape

```
[no] shape { { { [ average ] { <avg-rate> [ bps | kbps | mbps | gbps ] | percent <percentage> } } | { min { <min-rate> [ bps2 | kbps2 | mbps2 | gbps2 | pps2 ] | percent2 <percentage2> } max { <max-rate> [ bps3 | kbps3 | mbps3 | gbps3 | pps3 ] | percent3 <percentage3> } } } | { { kbps4 | pps4 } { <max-rate4> [ min2 <min-rate4> ] } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
shape	shape
average	(Optional) Configure average shape rate
min	Configure minimum shape rate
max	Configure maximum shape rate
bps	(Optional) Bits per second
kbps	(Optional) Kilo bits per second
mbps	(Optional) Mega bits per second
gbps	(Optional) Giga bits per second
bps2	(Optional) Bits per second
kbps2	(Optional) Kilo Bits per second
mbps2	(Optional) Mega Bits per second
gbps2	(Optional) Giga Bits per second
pps2	(Optional) Packets per second
bps3	(Optional) Bits per second
kbps3	(Optional) Kilo Bits per second
mbps3	(Optional) Mega Bits per second
gbps3	(Optional) Giga Bits per second
pps3	(Optional) Packets per second
percent	Specify rate as percentage of interface data-rate
percent2	Specify rate as percentage of interface data-rate
percent3	Specify rate as percentage of interface data-rate
<i>percentage</i>	Percentage

<i>percentage2</i>	Percentage
<i>percentage3</i>	Percentage
<i>kbits4</i>	Kilo Bits per second
<i>pps4</i>	Packets per second
<i>min2</i>	(Optional) Min guaranteed bandwidth

Command Mode

- /exec/configure/policy-map/type/queuing/class

shared-secret

```
[no] shared-secret { 10 <clear> | 7 <encrypted> | <secret> } [ user <user> password { 0 <clear> | 7 <encrypted> | <password> } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
shared-secret	Shared-secret
<i>secret</i>	Enter shared-secret in clear text
10	password in clear text
<i>clear</i>	Password in clear text
7	Password that follows should be in encrypted text
<i>encrypted</i>	Encrypted password
user	(Optional) User Name
<i>user</i>	(Optional) Enter user name
password	(Optional) Password
<i>password</i>	(Optional) Enter password in clear text
0	(Optional) Password that follows should be in clear text
<i>clear</i>	(Optional) Password in clear text
7	(Optional) Password that follows should be in encrypted text
<i>encrypted</i>	(Optional) Encrypted password

Command Mode

- /exec/configure/fabric-db/server-radius

shut

[no] shut

Syntax Description

no	(Optional) Negate a command or set its defaults
shut	Shut a monitor session

Command Mode

- /exec/configure/monitor-common

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	

Command Mode

- /exec/configure/smartc /exec/configure/smartc

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown this instance of RIP

Command Mode

- /exec/configure/router-rip /exec/configure/router-rip/router-rip-vrf

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Change the admin status of the bundle

Command Mode

- /exec/configure/anycast

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	

Command Mode

- /exec/configure/catena /exec/configure/catena

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown tunnel interface(s)

Command Mode

- /exec/configure/if-any-tunnel

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	OpenFlow switch shutdown

Command Mode

- /exec/configure/openflow/switch

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	OpenFlow switch shutdown

Command Mode

- /exec/configure/openflow/switch/sub-switch

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown this IS-IS process

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	shutdown the OSPF protocol instance

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate the command
shutdown	Enable Transient Capture Buffer

Command Mode

- /exec/configure/pkt-drop

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown this instance of EIGRP

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable or disable a VR

Command Mode

- /exec/configure/if-eth-any/vrrp

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface

Command Mode

- /exec/configure/if-vlan-common

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown Segment Routing

Command Mode

- /exec/configure/config-sr-mpls

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown VLAN switching

Command Mode

- /exec/configure/vlan

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface

Command Mode

- /exec/configure/if-mgmt-ether

shutdown

[no] shutdown [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	(Optional) Enable/disable an interface

Command Mode

- /exec/configure/if-ethernet /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-eth-port-channel /exec/configure/if-ethernet-all /exec/configure/if-ethernet-p2p /exec/configure/if-remote-ethernet-sub /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub /exec/configure/if-port-channel-range

shutdown

[no] shutdown [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	(Optional) Enable/disable an interface

Command Mode

- /exec/configure/if-ethernet /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-eth-port-channel /exec/configure/if-ethernet-all /exec/configure/if-ethernet-p2p /exec/configure/if-remote-ethernet-sub /exec/configure/if-ether-sub /exec/configure/if-ether-sub-p2p /exec/configure/if-port-channel-sub

shutdown

[no] shutdown [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	(Optional) Enable/disable an interface

Command Mode

- /exec/configure/if-nve

shutdown

[no] shutdown [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	(Optional) Enable/disable an interface

Command Mode

- /exec/configure/if-loopback

shutdown

[no] shutdown [force]

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	(Optional) Enable/disable an interface

Command Mode

- /exec/configure/if-cpp /exec/configure/if-fv /exec/configure/if-fa /exec/configure/if-svc
/exec/configure/if-fc-tunnel /exec/configure/if-sme /exec/configure/if-ioa /exec/configure/if-overlay
/exec/configure/if-te

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface

Command Mode

- /exec/configure/if-gig-ether /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-vsan /exec/configure/if-iscsi /exec/configure/if-fcip /exec/configure/if-sme /exec/configure/if-ioa /exec/configure/if-san-port-channel

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface

Command Mode

- /exec/configure/if-vfc /exec/configure/if-vfc-port-channel

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown the OSPF protocol instance

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Disable MPLS forwarding for IP

Command Mode

- /exec/configure/ldp

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	

Command Mode

- /exec/configure/itd /exec/configure/itd-inout

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shut down VRRPv3

Command Mode

- /exec/configure/vrrpv3

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shut down the group

Command Mode

- /exec/configure/if-eth-any/vrrpv3

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shut down the pathway

Command Mode

- /exec/configure/if-eth-any/vrrs

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown current VRF

Command Mode

- /exec/configure/vrf

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Administratively shutdown BGP protocol

Command Mode

- /exec/configure/router-bgp

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Administratively shutdown this BMP server

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

shutdown

[no | default] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
shutdown	Administratively shutdown this neighbor

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

shutdown

shutdown | no shutdown

Syntax Description

no	Negate a command or set its defaults
shutdown	suspend vPC locally

Command Mode

- /exec/configure/vpc-domain

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown PLB service

Command Mode

- /exec/configure/plb /exec/configure/plb-inout

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown MPLS Traffic Engineering

Command Mode

- /exec/configure/te

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Disable current explicit-path

Command Mode

- /exec/configure/te/expl-path

shutdown

[no] shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Shutdown the CBTS member LSP

Command Mode

- /exec/configure/tunnel-te/cbts-member

shutdown force

[no] shutdown force

Syntax Description

no	(Optional) Negate a command or set its defaults
shutdown	Enable/disable an interface
force	Enable/disable an interface

Command Mode

- /exec/configure/if-mgmt-ether

shutdown lan

shutdown lan

Syntax Description

shutdown	Enable/disable an interface
lan	Shut all LAN VLANs on interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

shutdown lan

[no] shutdown lan

Syntax Description

no	Negate a command or set its defaults
shutdown	Enable/disable an interface
lan	Shut all LAN VLANs on interface

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

signalling advertise explicit-null

[no] signalling advertise explicit-null | signalling advertise explicit-null [<acl>]

Syntax Description

no	Negate a command or set its defaults
signalling	Traffic Engineering Signalling Parameters
advertise	Signalling advertisement parameters
explicit-null	Advertise explicit-null label in signalling messages
<i>acl</i>	(Optional) Access list

Command Mode

- /exec/configure/te

signalling hello graceful-restart

[no] signalling hello graceful-restart

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
graceful-restart	RSVP Graceful restart commands

Command Mode

- /exec/configure/ip-rsvp

signalling hello graceful-restart refresh interval

[no] signalling hello graceful-restart refresh interval <value>

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
graceful-restart	RSVP Graceful restart commands
refresh	Configure RSVP Hello refresh behavior for Graceful Restart
interval	Time between sending Hello Requests for Graceful Restart
<i>value</i>	Hello interval in msec

Command Mode

- /exec/configure/ip-rsvp

signalling hello graceful-restart refresh misses

[no] signalling hello graceful-restart refresh misses <value>

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
graceful-restart	RSVP Graceful restart commands
refresh	Configure RSVP Hello refresh behavior for Graceful Restart
misses	Number of Hello misses for Graceful Restart
<i>value</i>	Number of missed Hello Acks which triggers neighbor down

Command Mode

- /exec/configure/ip-rsvp

signalling hello graceful-restart send recovery-time

[no] signalling hello graceful-restart send recovery-time <value>

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
graceful-restart	RSVP Graceful restart commands
send	Configure the restart-time in outgoing Hello msgs
recovery-time	Configure the recovery-time in outgoing GR Hello msgs
<i>value</i>	recovery-time in msec

Command Mode

- /exec/configure/ip-rsvp

signalling hello graceful-restart send restart-time

[no] signalling hello graceful-restart send restart-time <value>

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
graceful-restart	RSVP Graceful restart commands
send	Configure the restart-time in outgoing Hello msgs
restart-time	Configure the restart-time in outgoing GR Hello msgs
<i>value</i>	restart-time in msec

Command Mode

- /exec/configure/ip-rsvp

signalling hello reroute

[no] signalling hello reroute

Syntax Description

signalling	Configure RSVP Signalling information
hello	RSVP Hello configuration commands
reroute	RSVP Reroute commands

Command Mode

- /exec/configure/ip-rsvp

signalling initial-retransmit-delay

[no] signalling initial-retransmit-delay <msec>

Syntax Description

signalling	Configure RSVP Signalling information
initial-retransmit-delay	RSVP Initial retransmit delay
<i>msec</i>	Initial retransmit delay in millisec

Command Mode

- /exec/configure/ip-rsvp

signalling patherr state-removal

[no] signalling patherr state-removal

Syntax Description

signalling	Configure RSVP Signalling information
patherr	Configure Path-Error processing
state-removal	Setup automatic removal of path-state

Command Mode

- /exec/configure/ip-rsvp

signalling rate-limit

```
[no] signalling rate-limit { [ interval <msec> ] [ limit <messages> ] } | { [ limit <messages> ] [ interval <msec> ] }
```

Syntax Description

signalling	Configure RSVP Signalling information
rate-limit	Configure rate-limiting
interval	(Optional) Configure scheduling interval
<i>msec</i>	(Optional) Interval in millisecc
limit	(Optional) Configure message limit per scheduling interval
<i>messages</i>	(Optional) Message limit value

Command Mode

- /exec/configure/ip-rsvp

signalling refresh interval

[no] signalling refresh interval <seconds>

Syntax Description

signalling	Configure RSVP Signalling information
refresh	Configure RSVP signaling refresh parameters
interval	Set signaling refresh interval
<i>seconds</i>	Signaling refresh interval in seconds

Command Mode

- /exec/configure/ip-rsvp

signalling refresh misses

[no] signalling refresh misses <value>

Syntax Description

signalling	Configure RSVP Signalling information
refresh	Configure RSVP signaling refresh parameters
misses	Set refresh misses tolerated before expiring a state
<i>value</i>	Refresh miss value

Command Mode

- /exec/configure/ip-rsvp

signalling refresh reduction

[no] signalling refresh reduction

Syntax Description

signalling	Configure RSVP Signalling information
refresh	Configure RSVP signaling refresh parameters
reduction	Enable, disable or set refresh reduction parameters

Command Mode

- /exec/configure/ip-rsvp

signalling refresh reduction ack-delay

[no] signalling refresh reduction ack-delay <msec>

Syntax Description

signalling	Configure RSVP Signalling information
refresh	Configure RSVP signaling refresh parameters
reduction	Enable, disable or set refresh reduction parameters
ack-delay	Set delay for sending ACK messages
<i>msec</i>	ACK delay value in millisecc

Command Mode

- /exec/configure/ip-rsvp

signalling refresh reduction bundle-max-size

[no] signalling refresh reduction bundle-max-size <value>

Syntax Description

signalling	Configure RSVP Signalling information
refresh	Configure RSVP signaling refresh parameters
reduction	Enable, disable or set refresh reduction parameters
bundle-max-size	Set bundle-maximum-size
<i>value</i>	Bundle size in bytes, use zero to disable bundling

Command Mode

- /exec/configure/ip-rsvp

signing level

{ [no] signing level { none | cisco | unsigned } | no signing level }

Syntax Description

no	(Optional) Negate a command or set its defaults
signing	Virtual service package signing settings
level	Package signing level allowed for virtual service installation
none	Most restrictive, don't allow package installation
cisco	Allow only Cisco signed packages
unsigned	Least restrictive, allow unsigned and all signing methods

Command Mode

- /exec/configure/virt-serv-global

site-id

{ site-id <s0> | no site-id }

Syntax Description

no	Negate a command or set its defaults
site-id	site id of the network where switch is deployed
s0	Provide site id

Command Mode

- /exec/configure/callhome

site-of-origin

```
{ site-of-origin { <ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> } } | { no site-of-origin [ {  
<ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> } ] }
```

Syntax Description

no	Negate a command or set its defaults
site-of-origin	Site of Origin
<i>ext-comm-soo-aa2nn4</i>	Extcommunity number
<i>ext-comm-soo-aa4nn2</i>	Extcommunity number

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-ether

slave ipv4

[no] slave ipv4 <ip>

Syntax Description

no	(Optional) Negate a command or set its defaults
slave	slave
ipv4	ipv4
<i>ip</i>	IPv4 address (A.B.C.D) of slave

Command Mode

- /exec/configure/ptp-ucast-master

sleep

sleep <i0>

Syntax Description

sleep	Sleep for the specified number of seconds
<i>i0</i>	Enter the number of seconds to sleep

Command Mode

- /exec

sleep instance

[no] sleep instance <inst> [<i0>] | sleep instance <inst> <i0>

Syntax Description

no	Negate a command or set its defaults
sleep	Sleep for the specified number of seconds
instance	Label with an instance number
<i>inst</i>	Instance number
<i>i0</i>	(Optional) Enter the number of seconds to sleep

Command Mode

- /exec/configure

slot

slot <module> { quoted <quoted-cmd> | <cmd> }

Syntax Description

slot	run commands on specific linecard (or set slot for commands that take optional slot number)
<i>module</i>	the slot number (aka module number)
quoted	enter the command with quotes -> pipe redirection and semi-colon are local
<i>quoted-cmd</i>	the command(s) to run on lc separated by <space> <semi-colon> <space>
<i>cmd</i>	the command(s) to run on lc separated by <space> <semi-colon> <space>

Command Mode

- /exec

slot

slot <module>

Syntax Description

slot	Configure a slot
<i>module</i>	the slot number (aka module number)

Command Mode

- /exec/configure

smart-channel

{ smart-channel <service-name> } | { no smart-channel <service-name> }

Syntax Description

no	Negate a command or set its defaults
smart-channel	L2 service
<i>service-name</i>	L2 service-name

Command Mode

- /exec/configure

smart-channel port-group

{ smart-channel port-group <svc-name> } | { no smart-channel port-group <svc-name> }

Syntax Description

no	Negate a command or set its defaults
smart-channel	service
port-group	port group
<i>svc-name</i>	service-name

Command Mode

- /exec/configure

smtp-host smtp-port reply-to from

```
{ smtp-host { <ipv4> | <ipv6> | <host> } [ smtp-port <port> ] | smtp-port <port> | reply-to <reply> | from <from> |
```

Syntax Description

}	
smtp-host	SMTP server host
<i>ipv4</i>	IPV4 address
<i>host</i>	DNS name
smtp-port	(Optional) SMTP server port
<i>port</i>	(Optional) Port for SMTP server
reply-to	Reply to email address
<i>reply</i>	Provide reply-to email address
from	From email address
<i>from</i>	Provide from email address

Command Mode

- /exec/configure/email

snapshot create

snapshot create <snapshot-name> <snapshot-description>

Syntax Description

snapshot	Create/Delete a snapshot
create	Create a snapshot of running state of selected features
<i>snapshot-name</i>	Name of a snapshot
<i>snapshot-description</i>	Description of a snapshot

Command Mode

- /exec

snapshot delete

snapshot delete <snapshot-name>

Syntax Description

snapshot	Create/Delete a snapshot
delete	Delete a single snapshot or all snapshots
<i>snapshot-name</i>	Name of a snapshot

Command Mode

- /exec

snapshot delete ALL

snapshot delete ALL

Syntax Description

snapshot	Create/Delete a snapshot
delete	Delete a single snapshot or all snapshots
ALL	Delete all snapshots present on the switch

Command Mode

- /exec

snapshot section add

snapshot section add <name> <command> <row-id> <key1> [<key2>]

Syntax Description

snapshot	Create/Delete a snapshot
section	Add/Delete a snapshot section
add	Add a snapshot section
<i>name</i>	Name of a section
<i>command</i>	show' command to generate XML output
<i>row-id</i>	tag of each row entry of the 'show' XML output
<i>key1</i>	first key to distinguish among row entries with
<i>key2</i>	(Optional) second key to distinguish among row entries with

Command Mode

- /exec

snapshot section delete

snapshot section delete <name>

Syntax Description

snapshot	Create/Delete a snapshot
section	Add/Delete a snapshot section
delete	Delete a snapshot section
<i>name</i>	Name of a section

Command Mode

- /exec

snmp-server aaa-user cache-timeout

[no] snmp-server aaa-user cache-timeout <timeout>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
aaa-user	set duration for which aaa-cached snmp user exists
cache-timeout	timeout for AAA cache
<i>timeout</i>	timeout for which aaa-cached user exists(in secs)

Command Mode

- /exec/configure

snmp-server community

```
{ no snmp-server community <community_name> { use-ipv4acl [ <ipv4_acl_name> ] use-ipv6acl [
<ipv6_acl_name> ] | use-ipv4acl [ <ipv4_acl_name> ] | use-ipv6acl [ <ipv6_acl_name> ] } | snmp-server
community <community_name> { use-ipv4acl <ipv4_acl_name> use-ipv6acl <ipv6_acl_name> | use-ipv4acl
<ipv4_acl_name> | use-ipv6acl <ipv6_acl_name> } }
```

Syntax Description

no	Negate a command or set its defaults
snmp-server	Configure snmp server
community	set community string and access privs
<i>community_name</i>	SNMP community string
use-ipv4acl	Specify IPv4 ACL, the ACL name specified after must be IPv4 ACL.
<i>ipv4_acl_name</i>	(Optional) IPv4 ACL name to filter snmp requests
use-ipv6acl	Specify IPv6 ACL, the ACL name specified after must be IPv6 ACL.
<i>ipv6_acl_name</i>	(Optional) IPv6 ACL name to filter snmp requests

Command Mode

- /exec/configure

snmp-server community

[no] snmp-server community <s0> [{ group <s1> | ro | rw }]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
community	set community string and access privs
<i>s0</i>	SNMP community string
group	(Optional) Group to which the community belongs
<i>s1</i>	(Optional) Group to which the community belongs
ro	(Optional) Read-only access with this community string
rw	(Optional) Read-write access with this community string

Command Mode

- /exec/configure

snmp-server community use-acl

[no] snmp-server community <community_name> use-acl <acl_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
community	set community string and access privs
<i>community_name</i>	SNMP community string
use-acl	acl name to filter snmp requests
<i>acl_name</i>	acl name to filter snmp requests

Command Mode

- /exec/configure

snmp-server contact

[no] snmp-server contact [<line>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
contact	modify sysContact
<i>line</i>	(Optional) modify sysContact

Command Mode

- /exec/configure

snmp-server context

```
[no] snmp-server context <context_name> [ instance <instance-name> ] [ vrf { <vrf-name> | <vrf-known-name> } ] [ topology <topology-name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
context	SNMP context to be mapped
<i>context_name</i>	name of the SNMP context
instance	(Optional) Protocol instance associated with the SNMP context
<i>instance-name</i>	(Optional) Name of the protocol instance
vrf	(Optional) VRF associated with the SNMP context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
topology	(Optional) Topology associated with the SNMP context
<i>topology-name</i>	(Optional) name of the Topology

Command Mode

- /exec/configure

snmp-server counter cache enable

[no] snmp-server counter cache enable

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
counter	Configure port counter configuration
cache	port stats cache
enable	enable port stats cache

Command Mode

- /exec/configure

snmp-server counter cache timeout

[no] snmp-server counter cache timeout <timeout>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
counter	Configure port counter configuration
cache	Port stats cache
timeout	Timeout for port stats cache
<i>timeout</i>	Timeout for which cached port stats exists(in secs)

Command Mode

- /exec/configure

snmp-server enable traps

[no] snmp-server enable traps [<trap_arg> [<trap_sub_category> +]]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
<i>trap_arg</i>	(Optional) Enable __left__ traps
<i>trap_sub_category</i>	(Optional) Enter the trap

Command Mode

- /exec/configure

snmp-server enable traps bgp

[no] snmp-server enable traps bgp [{ state-changes [<subsystem> +] }]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
bgp	Enable SNMP BGP traps
state-changes	(Optional) Traps for FSM state changes
<i>subsystem</i>	(Optional) subsystem within BGP for SNMP traps

Command Mode

- /exec/configure

snmp-server enable traps bgp cbgp2

[no] snmp-server enable traps bgp cbgp2 [{ state-changes [<subsystem> +] }]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
bgp	Enable SNMP BGP traps
cbgp2	Enable SNMP CISCO-BGP-MIBv2 traps
state-changes	(Optional) Traps for FSM state changes
<i>subsystem</i>	(Optional) subsystem within BGP for SNMP traps

Command Mode

- /exec/configure

snmp-server enable traps bgp cbgp2 threshold prefix

[no] snmp-server enable traps bgp cbgp2 threshold prefix

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
bgp	Enable SNMP BGP traps
cbgp2	Enable SNMP CISCO-BGP-MIBv2 traps
threshold	Traps for threshold events
prefix	CISCO specific trap for prefix threshold events

Command Mode

- /exec/configure

snmp-server enable traps bgp threshold prefix

[no] snmp-server enable traps bgp threshold prefix

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
bgp	Enable SNMP BGP traps
threshold	Traps for threshold events
prefix	CISCO specific trap for prefix threshold events

Command Mode

- /exec/configure

snmp-server enable traps eigrp

[no] snmp-server enable traps eigrp [<eigrp-ptag>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
eigrp	Enable SNMP EIGRP traps
<i>eigrp-ptag</i>	(Optional) Process tag

Command Mode

- /exec/configure

snmp-server enable traps ospf

[no] snmp-server enable traps ospf [<tag>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospf	Enable SNMP OSPF traps
<i>tag</i>	(Optional) Process tag

Command Mode

- /exec/configure

snmp-server enable traps ospf lsa

[no] snmp-server enable traps ospf [<tag>] lsa

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospf	Enable SNMP OSPF traps
<i>tag</i>	(Optional) Process tag
lsa	Allow sending LSA traps

Command Mode

- /exec/configure

snmp-server enable traps ospf rate-limit

```
{ { no snmp-server enable traps ospf [ <tag> ] rate-limit [ <window> <rate> ] } | { snmp-server enable traps ospf [ <tag> ] rate-limit <window> <rate> } }
```

Syntax Description

no	Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospf	Enable SNMP OSPF traps
<i>tag</i>	(Optional) Process tag
rate-limit	Trap rate limit values
<i>window</i>	(Optional) Rate limit window size in seconds
<i>rate</i>	(Optional) Max number of traps sent in window time
<i>tag</i>	(Optional)

Command Mode

- /exec/configure

snmp-server enable traps ospfv3

[no] snmp-server enable traps ospfv3 [<tag>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospfv3	Enable SNMP OSPFv3 traps
<i>tag</i>	(Optional) Process tag

Command Mode

- /exec/configure

snmp-server enable traps ospfv3 lsa

[no] snmp-server enable traps ospfv3 lsa

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospfv3	Enable SNMP OSPFv3 traps
lsa	Enable SNMP OSPFv3 LSA traps

Command Mode

- /exec/configure

snmp-server enable traps ospfv3 lsa

[no] snmp-server enable traps ospfv3 <tag> lsa

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospfv3	Enable SNMP OSPFv3 traps
<i>tag</i>	Process tag
lsa	Enable SNMP OSPFv3 LSA traps

Command Mode

- /exec/configure

snmp-server enable traps ospfv3 rate-limit

```
{ { no snmp-server enable traps ospfv3 [ <tag> ] rate-limit } | { snmp-server enable traps ospfv3 [ <tag> ]
rate-limit <swindow> <rate> } }
```

Syntax Description

no	Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
ospfv3	Enable SNMP OSPFv3 traps
<i>tag</i>	(Optional) Process tag
rate-limit	Trap rate limit values
<i>swindow</i>	Rate limit window size in seconds
<i>rate</i>	Max number of traps sent in window time
<i>tag</i>	(Optional)

Command Mode

- /exec/configure

snmp-server enable traps storm-control trap-rate

[no] snmp-server enable traps storm-control trap-rate <rate-per-minute>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
enable	Enable SNMP Traps
traps	Enable SNMP traps
storm-control	Enable storm-control traps
trap-rate	Number of traps per minute
<i>rate-per-minute</i>	per Minute (0 means no upper rate)

Command Mode

- /exec/configure

snmp-server engineID local

snmp-server engineID local <engineId> | no snmp-server engineID local [<engineId>]

Syntax Description

no	Negate a command or set its defaults
snmp-server	Configure snmp server
engineID	Configure a local SNMPv3 engineID
local	engineID of the local agent
<i>engineId</i>	engine ID should be an even number of hexadecimal characters, which ranges from 10 to 64 where every two hexadecimal characters should be separated by colon. Including colons-

Command Mode

- /exec/configure

snmp-server force-unload-feature

snmp-server force-unload-feature <feature_name>

Syntax Description

snmp-server	Configure snmp server
force-unload-feature	unload mibs of conditional feature forcefully
<i>feature_name</i>	conditional feature name

Command Mode

- /exec/configure

snmp-server globalEnforcePriv

[no] snmp-server globalEnforcePriv

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
globalEnforcePriv	globally enforce privacy for all the users

Command Mode

- /exec/configure

snmp-server host

```
[no] snmp-server host <host0> { <s6> | [ informs | traps ] } { version { 1 <s0> | 2c <s1> | 3 { auth <s2> | noauth <s3> | priv <s4> } } } | <s5> } } [ udp-port <i1> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
host	Specify hosts to receive SNMP notifications
<i>host0</i>	IPv4 or IPv6 address or DNS Name of SNMP notification host
informs	(Optional) Send Inform messages to this host
traps	(Optional) Send Traps messages to this host
version	SNMP version to use for notification messages
1	Use SNMPv1
<i>s0</i>	SNMP community string or SNMPv3 user name
udp-port	(Optional) The notification host's UDP port number
<i>i1</i>	(Optional) The notification host's UDP port number
2c	Use SNMPv2c
<i>s1</i>	SNMP community string or SNMPv3 user name
3	Use SNMPv3
auth	Use the SNMPv3 authNoPriv Security Level
<i>s2</i>	SNMP community string or SNMPv3 user name
noauth	Use the SNMPv3 noAuthNoPriv Security Level
<i>s3</i>	SNMP community string or SNMPv3 user name
priv	Use the SNMPv3 authPriv Security Level
<i>s4</i>	SNMP community string or SNMPv3 user name
<i>s5</i>	SNMP community string or SNMPv3 user name
<i>s6</i>	SNMP community string or SNMPv3 user name

Command Mode

- /exec/configure

snmp-server host filter-vrf

[no] snmp-server host <host0> filter-vrf { <vrf-name> | <vrf-known-name> } [udp-port <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
host	Specify hosts to receive SNMP notifications
<i>host0</i>	IPv4 or IPv6 address or DNS Name of SNMP notification host
filter-vrf	Filters notifications to the notification host receiver based on the configured VRF
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name
udp-port	(Optional) The notification host's UDP port number
<i>i1</i>	(Optional) The notification host's UDP port number

Command Mode

- /exec/configure

snmp-server host source

[no] snmp-server host <host0> { source-interface <ifName> } [udp-port <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
host	Specify hosts to send SNMP notifications
<i>host0</i>	IPv4 or IPv6 address or DNS Name of SNMP notification host
source-interface	Source interface to be used for sending out SNMP notifications to this host
<i>ifName</i>	Source interface name
udp-port	(Optional) The notification host's UDP port number
<i>i1</i>	(Optional) The notification host's UDP port number

Command Mode

- /exec/configure

snmp-server host use-vrf

[no] snmp-server host <host0> use-vrf { <vrf-name> | <vrf-known-name> } [udp-port <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
host	Specify hosts to receive SNMP notifications
<i>host0</i>	IPv4 or IPv6 address or DNS Name of SNMP notification host
use-vrf	Configures SNMP to use the selected VRF to communicate with the host receiver
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name
udp-port	(Optional) The notification host's UDP port number
<i>i1</i>	(Optional) The notification host's UDP port number

Command Mode

- /exec/configure

snmp-server host use_vrf

[no] snmp-server host <host0> { use_vrf <s0> | filter_vrf <s1> } [udp-port <i1>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
host	Specify hosts to receive SNMP notifications
<i>host0</i>	IPv4 or IPv6 address or DNS Name of SNMP notification host
use_vrf	Configures SNMP to use the selected VRF to communicate with the host receiver
<i>s0</i>	VRF name
filter_vrf	Filters notifications to the notification host receiver based on the configured VRF
<i>s1</i>	VRF name
udp-port	(Optional) The notification host's UDP port number
<i>i1</i>	(Optional) The notification host's UDP port number

Command Mode

- /exec/configure

snmp-server load-cond-feature

[no] snmp-server load-cond-feature <feature_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
load-cond-feature	load or unload mibs of conditional feature
<i>feature_name</i>	conditional feature name

Command Mode

- /exec/configure

snmp-server load-mib

[no] snmp-server load-mib <mib_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
load-mib	load a given mib
<i>mib_name</i>	mib module name

Command Mode

- /exec/configure

snmp-server location

[no] snmp-server location [<line>]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
location	modify sysLocation
<i>line</i>	(Optional) modify sysLocation

Command Mode

- /exec/configure

snmp-server mib community-map context

[no] snmp-server mib community-map <community_name> context <context_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
mib	mib access parameters
community-map	SNMP community
<i>community_name</i>	SNMP community string
context	SNMP context to be mapped
<i>context_name</i>	name of the SNMP context

Command Mode

- /exec/configure

snmp-server protocol enable

[no] snmp-server protocol enable

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
protocol	snmp protocol operations
enable	Enable/Disable snmp protocol operations

Command Mode

- /exec/configure

snmp-server source-interface informs

[no] snmp-server source-interface { informs } <ifName>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
source-interface	Source interface to be used for sending out SNMP notifications
<i>ifName</i>	Source interface name
informs	SNMP Inform notifications for which this source interface needs to be used

Command Mode

- /exec/configure

snmp-server source-interface traps

[no] snmp-server source-interface { traps } <ifName>

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
source-interface	Source interface to be used for sending out SNMP notifications
<i>ifName</i>	Source interface name
traps	SNMP Trap notifications for which this source interface needs to be used

Command Mode

- /exec/configure

snmp-server system-shutdown

[no] snmp-server system-shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
system-shutdown	Configure snmp-server for reload(2)

Command Mode

- /exec/configure

snmp-server tcp-session

[no] snmp-server tcp-session [auth]

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
tcp-session	Enable one time authentication for snmp over tcp session.
auth	(Optional) Enable one time authentication for snmp over tcp session.

Command Mode

- /exec/configure

snmp-server user

```
{ no snmp-server user <user_name> { use-ipv4acl [ <ipv4_acl_name> ] use-ipv6acl [ <ipv6_acl_name> ] |
use-ipv4acl [ <ipv4_acl_name> ] | use-ipv6acl [ <ipv6_acl_name> ] } | snmp-server user <user_name> {
use-ipv4acl <ipv4_acl_name> use-ipv6acl <ipv6_acl_name> | use-ipv4acl <ipv4_acl_name> | use-ipv6acl
<ipv6_acl_name> } }
```

Syntax Description

no	Negate a command or set its defaults
snmp-server	Configure snmp server
user	Define a user who can access the SNMP engine
<i>user_name</i>	Name of the user
use-ipv4acl	Specify IPv4 ACL, the ACL name specified after must be IPv4 ACL.
<i>ipv4_acl_name</i>	(Optional) IPv4 ACL name to filter snmp requests
use-ipv6acl	Specify IPv6 ACL, the ACL name specified after must be IPv6 ACL.
<i>ipv6_acl_name</i>	(Optional) IPv6 ACL name to filter snmp requests

Command Mode

- /exec/configure

snmp-server user

```
[no] snmp-server user <s0> { enforcePriv | { [ <s1> ] { [ auth { md5 | sha } <s2> { { priv [ aes-128 ] { <s3>
[ localizedkey ] [ { auto | engineID <s4> } ] } } | { [ localizedkey1 ] [ { auto | engineID1 <s5> } ] } } } }
}
```

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp-server	Configure snmp server
user	Define a user who can access the SNMP engine
s0	Name of the user
enforcePriv	Enforce privacy for the user
s1	(Optional) Group name (ignored for notif target user)
auth	(Optional) authentication parameters for the user
md5	(Optional) Use HMAC MD5 algorithm for authentication
sha	(Optional) Use HMAC SHA algorithm for authentication
s2	(Optional) authentication password for user
priv	(Optional) encryption parameters for the user
aes-128	(Optional) Use 128-bit AES algorithm for privacy
s3	(Optional) privacy password for user
localizedkey	(Optional) specifies whether the passwords are in localized key format
auto	(Optional) specifies whether the user is auto created (volatile)
engineID	(Optional) engineID for configuring notif target user (for V3 informs)
s4	(Optional) Specifies notification target's SNMP engineID. Should be an octet of either Decimal (range: 0 to 255) or Hexadecimal (range: 0 to FF) value, each octet being separated by colon. Hexadecimal value should have prefix of 0x or 0X. Including colons-
localizedkey1	(Optional) specifies whether the passwords are in localized key format
auto1	(Optional) specifies whether the user is auto created (volatile)
engineID1	(Optional) engineID for configuring notif target user (for V3 informs)
s5	(Optional) Specifies notification target's SNMP engineID. Should be an octet of either Decimal (range: 0 to 255) or Hexadecimal (range: 0 to FF) value, each octet being separated by colon. Hexadecimal value should have prefix of 0x or 0X. Including colons-

Command Mode

- /exec/configure

snmp ifmib ifalias long

[no] snmp ifmib ifalias long

Syntax Description

no	(Optional) Negate a command or set its defaults
snmp	Configure snmp
ifmib	Configure snmp interface mib feature
ifalias	Configure snmp interface alias attribute for interface mib
long	Enable long description up to 256 characters for interface alias

Command Mode

- /exec/configure

snmp trap link-status

snmp trap link-status | no snmp trap link-status

Syntax Description

no	Negate a command or set its defaults
snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-mgmt-ether

snmp trap link-status

snmp trap link-status | no snmp trap link-status

Syntax Description

no	Negate a command
snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-any-tunnel

snmp trap link-status

snmp trap link-status | no snmp trap link-status

Syntax Description

no	Negate a command or set its defaults
snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-vlan-common

snmp trap link-status

snmp trap link-status | no snmp trap link-status

Syntax Description

no	Negate a command or set its defaults
snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-ether-sub /exec/configure/if-port-channel-sub /exec/configure/if-gig-ether-sub /exec/configure/if-remote-ethernet-sub /exec/configure/if-ether-sub-p2p

snmp trap link-status

snmp trap link-status

Syntax Description

snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-port-channel-range

snmp trap link-status

[no] snmp trap link-status

Syntax Description

no	Negate a command or set its defaults
snmp	Modify SNMP interface parameters
trap	Allow a specific SNMP trap
link-status	Allow SNMP LINKUP and LINKDOWN traps

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base /exec/configure/if-port-channel /exec/configure/if-port-channel-range

snsr-grp sample-interval

snsr-grp <sn-grp-id> sample-interval <cadence> | no snsr-grp <sn-grp-id>

Syntax Description

no	Negate a command or set its defaults
snsr-grp	Associated sensor group
sample-interval	Cadence Time in milliseconds(0 for events)
<i>sn-grp-id</i>	Identifier
<i>cadence</i>	Cadence Time in milliseconds

Command Mode

- /exec/configure/telemetry/subscription

sockets local-port-range

{ { no sockets local-port-range } | { sockets local-port-range <start-port> <end-port> } }

Syntax Description

no	Negate a command or set its defaults
sockets	Negate a command or set its defaults
local-port-range	Define local port range for Kstack. Note: This CLI requires switch to be reloaded
<i>start-port</i>	Start port of local port range
<i>end-port</i>	End port of local port range

Command Mode

- /exec/configure /exec/configure/config-mgmt

soft-reconfiguration inbound

```
{ soft-reconfiguration inbound [ always ] } | { no soft-reconfiguration inbound } | { default soft-reconfiguration inbound }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
soft-reconfiguration	Soft reconfiguration
inbound	Allow inbound soft reconfiguration
always	(Optional) Always perform inbound soft reconfiguration

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mvpn
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-mvpn

soft-reconfiguration inbound

{ soft-reconfiguration inbound [always] } | { no soft-reconfiguration inbound } | { default soft-reconfiguration inbound }

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
soft-reconfiguration	Soft reconfiguration
inbound	Allow inbound soft reconfiguration
always	(Optional) Always perform inbound soft reconfiguration

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt

soo auto

```
{ [ no ] soo { auto | <ext-comm-soo-aa2nn4> | <ext-comm-soo-aa4nn2> } } | { default soo }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
default	Inherit values from a peer template
soo	Specify Site-of-origin extcommunity
auto	Generate SOO automatically
<i>ext-comm-soo-aa4nn2</i>	VPN extcommunity in aa4:nn or ip:nn format
<i>ext-comm-soo-aa2nn4</i>	VPN extcommunity in aa:nn format

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv4
- /exec/configure/router-bgp/router-bgp-vrf-neighbor/router-bgp-vrf-neighbor-af-ipv6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

sort

| sort [-b | -d | -f | -g | -i | -M | -n | -r | -k <key> | -t <delim> | -u] +

Syntax Description

	Pipe command output to filter
sort	Stream Sorter
-b	(Optional) ignore leading blanks
-d	(Optional) consider only blanks and alphanumeric characters
-f	(Optional) fold lower case to upper case characters
-g	(Optional) compare according to general numerical value
-i	(Optional) consider only printable characters
-M	(Optional) month sort
-n	(Optional) compare according to string numerical value
-r	(Optional) reverse the result of comparisons
-k	(Optional) provide a key
-t	(Optional) use different separator instead of non-blank to blank transition
-u	(Optional) remove duplicate lines
<i>key</i>	(Optional) key in format POS1[,POS2] with POS = <field-nb>[.<char-pos>][<ordering>]
<i>delim</i>	(Optional) field delimiter char

Command Mode

- /output

source-address ipv4

[no] source-address ipv4 [<ip-address>]

Syntax Description

no	(Optional) Negate a command or set its defaults
source-address	Configure the source address to be used for PCE connection
ipv4	Configure v4 source address for PCC
<i>ip-address</i>	(Optional) Source address

Command Mode

- /exec/configure/sr/te/pcc

source-group

[no] source-group <source> <group>

Syntax Description

no	(Optional) Negate a command or set its defaults
source-group	Source Group
<i>source</i>	Configure source address
<i>group</i>	Configure group address

Command Mode

- /exec/configure/if-nve

source-interface

[no] source-interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
source-interface	Configure source interface to reach http server
<i>interface</i>	Interface

Command Mode

- /exec/configure/trustpool

source-interface

source-interface <interface> | no source-interface

Syntax Description

no	Negate a command or set its defaults
source-interface	NVE Source-Interface
<i>interface</i>	

Command Mode

- /exec/configure/if-nve

source-interface

source-interface <interface> | no source-interface

Syntax Description

no	Negate a command or set its defaults
source-interface	Source interface
<i>interface</i>	Interface name

Command Mode

- /exec/configure/telemetry/destination-profile

source-interface

[no] source-interface | source-interface <interface>

Syntax Description

no	Negate a command or set its defaults
source-interface	Source interface to be used to reach radius server
<i>interface</i>	Interface (default is mgmt)

Command Mode

- /exec/configure/radius

source-interface

[no] source-interface | source-interface <interface>

Syntax Description

no	Negate a command or set its defaults
source-interface	Source interface to be used to reach tacacs server
<i>interface</i>	Interface (default is mgmt)

Command Mode

- /exec/configure/tacacs+

source-interface

[no] source-interface <interface>

Syntax Description

no	(Optional) Negate a command or set its defaults
source-interface	PLB probe Source-Interface
<i>interface</i>	source interface for probe

Command Mode

- /exec/configure/plb

source-interface hold-down-time

[no] source-interface hold-down-time <sec>

Syntax Description

no	(Optional) Negate a command or set its defaults
source-interface	NVE Source-Interface
hold-down-time	Hold source loopback down time
<i>sec</i>	time in seconds

Command Mode

- /exec/configure/if-nve

source

{ [no] source <intf> | no source }

Syntax Description

source	Source Interface for this destination
<i>intf</i>	Interface

Command Mode

- /exec/configure/config-postcard-exporter

source

{ [no] source <intf> | no source }

Syntax Description

source	Source Interface for this destination
<i>intf</i>	Interface

Command Mode

- /exec/configure/config-int-exporter

source

```
{ [ no ] source { <ipaddr> | <ipv6addr> } }
```

Syntax Description

source	Specify details
<i>ipaddr</i>	Source IP address for collector

Command Mode

- /exec/configure/config-fte-exporter

source

{ [no] source <intf> | no source }

Syntax Description

source	Source Interface for this destination
<i>intf</i>	Interface

Command Mode

- /exec/configure/nfm-exporter

source

source <srcip> | no source

Syntax Description

no	Negate a command or set its defaults
source	Source address for connection to controllers
<i>srcip</i>	IP address of source

Command Mode

- /exec/configure/openflow/switch

source

```
[no] source { { unicast-queue interface <if_list> qos-group <qos-grp> } | { { ingress | egress } { interface <if_list> } } }
```

Syntax Description

no	(Optional) Negate the command
source	Configure Packet Drop Scope
unicast-queue	Specify Capture scope as queue basis
interface	Specify interface associated to particular Queue
<i>if_list</i>	List of interfaces
qos-group	Specify the Qos-grp to be associated
<i>qos-grp</i>	Value 0-7
ingress	Specify Capture scope as Ingress
egress	Specify Capture scope as Egress
interface	Configure the Entity Interface
<i>if_list</i>	List of interfaces

Command Mode

- /exec/configure/pkt-drop

source

[no] source <ipaddr>

Syntax Description

source	Source configuration
<i>ipaddr</i>	IP Address to be configured

Command Mode

- /exec/configure/config-ssx-exporter

source

source [background] <file> [<args>] +

Syntax Description

source	run a script (python, tcl,...) from bootflash:scripts
background	(Optional) run the script in the background, see also 'show background' and 'kill background'
<i>file</i>	the script file to run
<i>args</i>	(Optional) argument to be passed to script

Command Mode

- /exec

source

| source <file> [<args>] +

Syntax Description

	Pipe command output to filter
source	run a script (python, tcl,...) from bootflash:scripts
<i>file</i>	the script file to run
<i>args</i>	(Optional) argument to be passed to script

Command Mode

- /output

source

source { <ipaddr> } | no source

Syntax Description

no	Negate a command or set its defaults
source	source of tunnel packets
<i>ipaddr</i>	ip address (A.B.C.D)

Command Mode

- /exec/configure/if-te

source

{ source { <numeric1> | <numeric2> } | no source }

Syntax Description

no	Negate a command or set its defaults
source	Source
<i>numeric1</i>	IP

Command Mode

- /exec/configure/configngoamconnectcheck

source copy-sys

source copy-sys

Syntax Description

source	run a script (python, tcl,...) from bootflash:scripts
copy-sys	copy the system provided example scripts of /sys to bootflash:scripts

Command Mode

- /exec

source filter ip

```
[no] source filter ip { <ip-addr> <ip-mask> } [ ip | { { udp | tcp } { <port_num> | any } } ] [ { arp | advertise } { enable | disable } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
source	source ip configuration
filter	source filters
ip	source ip
<i>ip-addr</i>	IP address in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
ip	(Optional) IP Protocol
udp	(Optional) UDP Protocol
tcp	(Optional) TCP Protocol
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
arp	(Optional) ARP
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable

Command Mode

- /exec/configure/smarte

source filter ip any any

[no] source filter ip any any

Syntax Description

no	(Optional) Negate a command or set its defaults
source	source ip configuration
filter	source filters
ip	source ip
any	Any IP

Command Mode

- /exec/configure/smartc

source forward-drops

[no] source forward-drops <src_dir> [priority-low]

Syntax Description

no	(Optional) Negate a command or set its defaults
source	Source configuration
forward-drops	Forwarding drops
priority-low	(Optional) Drop span session is low priority relative to span acl and vlan sessions
<i>src_dir</i>	Source direction

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

source group permit

```
{ <seq> source <sourceip> group <range> { permit | deny } } | { no <seq> [ source <sourceip> group <range>
{ permit | deny } ] }
```

Syntax Description

<i>seq</i>	Sequence Number
source	Source IP Address
<i>sourceip</i>	Source IP Address value
group	Configure explicit group ranges
<i>range</i>	Group Prefix
permit	Admission Permitted
deny	Admission Denied

Command Mode

- /exec/configure/nbm-host-policy/pim

source interface

[no] source { interface <interface_range> } [<src_dir>] [allow-pfc]

Syntax Description

no	(Optional) Negate a command or set its defaults
source	Source configuration
interface	Configure interfaces
<i>interface_range</i>	
<i>src_dir</i>	(Optional) Source direction
allow-pfc	(Optional) Enable SPAN on PFC frames

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

source interface

[no] source { interface <interface> } [<src_dir>]

Syntax Description

no	(Optional) Negate a command or set its defaults
source	Source configuration
interface	Configure interfaces
<i>interface</i>	
<i>src_dir</i>	(Optional) Source direction

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

source ip

[no] source ip <ipaddress>

Syntax Description

no	(Optional) Negate a command or set its defaults
source	Source IP address configuration
ip	Configure source IP address
<i>ipaddress</i>	

Command Mode

- /exec/configure/config-monitor-erspan-dst

source vlan

[no] source { vlan <vlan_range> | vsan <vsan_range> } [<src_dir>]

Syntax Description

no	(Optional) Negate a command or set its defaults
source	Source configuration
vlan	Vlan type
vsan	Vsan type
<i>vlan_range</i>	
<i>vsan_range</i>	
<i>src_dir</i>	(Optional) Source direction

Command Mode

- /exec/configure/monitor-local-src /exec/configure/config-monitor
/exec/configure/config-monitor-erspan-src

spanning-tree bpdudfilter

spanning-tree bpdudfilter <port-bpdudfilter> | no spanning-tree bpdudfilter [<port-bpdudfilter>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
bpdudfilter	Don't send or receive BPDUs on this interface
<i>port-bpdudfilter</i>	Don't send or receive BPDUs on this interface

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree bpduguard

spanning-tree bpduguard <port-bpduguard> | no spanning-tree bpduguard [<port-bpduguard>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
bpduguard	Don't accept BPDUs on this interface
<i>port-bpduguard</i>	Don't accept BPDUs on this interface

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree bridge-domain

[no] spanning-tree bridge-domain <bd-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11

Command Mode

- /exec/configure

spanning-tree bridge assurance

[no] spanning-tree bridge assurance

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
bridge	Spanning tree bridge options
assurance	Enable Bridge Assurance on all network ports

Command Mode

- /exec/configure

spanning-tree cost

spanning-tree [vlan <vlan-id> | bridge-domain <bd-id>] cost <port-cost> | no spanning-tree [vlan <vlan-id> | bridge-domain <bd-id>] cost [<port-cost>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	(Optional) VLAN Switch Spanning Trees
bridge-domain	(Optional) Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	(Optional) vlan range, Example: 1,3-5,7,9-11
<i>vlan-id</i>	(Optional) vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	(Optional) Bridge-Domain range, Example: 2,4-5,7,9-11
cost	Change an interface's spanning tree port path cost
<i>port-cost</i>	port path cost

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree cost auto

[no] spanning-tree [vlan <vlan-id> | bridge-domain <bd-id>] cost auto

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	(Optional) VLAN Switch Spanning Trees
bridge-domain	(Optional) Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	(Optional) vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	(Optional) Bridge-Domain range, Example: 2,4-5,7,9-11
cost	Change an interface's spanning tree port path cost
auto	Determine cost based on media speed of this interface

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree domain

spanning-tree domain { enable | disable | <domain-id> } | no spanning-tree domain [enable]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
domain	Spanning Tree Domain
enable	Enable Spanning Tree Domain
disable	Disable Spanning Tree Domain
<i>domain-id</i>	Domain Identifier

Command Mode

- /exec/configure

spanning-tree domain clear statistics

spanning-tree domain clear statistics

Syntax Description

spanning-tree	Spanning Tree Subsystem
domain	Spanning Tree Domain
clear	Clear
statistics	Clear Statistics

Command Mode

- /exec/configure

spanning-tree fcoe

[no] spanning-tree fcoe

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
fcoe	Enable STP for FCoE VLANs

Command Mode

- /exec/configure

spanning-tree guard

spanning-tree guard <guard-type> | no spanning-tree guard [<guard-type>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
guard	Change an interface's spanning tree guard mode
<i>guard-type</i>	Change an interface's spanning tree guard mode

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree lc-issu

spanning-tree lc-issu <issu-type> | no spanning-tree lc-issu [<issu-type>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
lc-issu	Configure Linecard ISSU type
<i>issu-type</i>	ISSU Type

Command Mode

- /exec/configure

spanning-tree lc-issu

spanning-tree lc-issu <port-issu-type> | no spanning-tree lc-issu [<port-issu-type>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
lc-issu	Configure Linecard ISSU type
<i>port-issu-type</i>	ISSU Type

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree link-type

spanning-tree link-type <link-type-val> | no spanning-tree link-type [<link-type-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
link-type	Specify a link type for spanning tree tree protocol use
<i>link-type-val</i>	Specify a link type for spanning tree tree protocol use

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree loopguard default

[no] spanning-tree loopguard default

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
loopguard	Spanning tree loopguard options
default	Enable loopguard by default on all ports

Command Mode

- /exec/configure

spanning-tree mode

spanning-tree mode <stp-mode> | no spanning-tree mode [<stp-mode>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mode	Spanning Tree operating mode
<i>stp-mode</i>	Spanning Tree operating mode

Command Mode

- /exec/configure

spanning-tree mst configuration

spanning-tree mst configuration

Syntax Description

spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
configuration	Enter MST configuration submenu

Command Mode

- /exec/configure

spanning-tree mst configuration

[no] spanning-tree mst configuration

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
configuration	Enter MST configuration submode

Command Mode

- /exec/configure

spanning-tree mst cost

spanning-tree mst <mst-id> cost <port-cost> | no spanning-tree mst <mst-id> cost [<port-cost>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree
<i>mst-id</i>	MST instance list, example 0,2-4,6,8-12
cost	Change an interface's spanning tree port path cost
<i>port-cost</i>	port path cost

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree mst cost auto

[no] spanning-tree mst <mst-id> cost auto

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree
<i>mst-id</i>	MST instance list, example 0,2-4,6,8-12
cost	Change an interface's spanning tree port path cost
auto	Determine cost based on media speed of this interface

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree mst forward-time

spanning-tree mst forward-time <fwd-time> | no spanning-tree mst forward-time [<fwd-time>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
forward-time	Set the forward delay for the spanning tree
<i>fwd-time</i>	number of seconds for the forward delay timer

Command Mode

- /exec/configure

spanning-tree mst hello-time

spanning-tree mst hello-time <hello-time-val> | no spanning-tree mst hello-time [<hello-time-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
hello-time	Set the hello interval for the spanning tree
<i>hello-time-val</i>	number of seconds between generation of config bpdu

Command Mode

- /exec/configure

spanning-tree mst max-age

spanning-tree mst max-age <max-age-val> | no spanning-tree mst max-age [<max-age-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
max-age	Set the max age interval for the spanning tree
<i>max-age-val</i>	maximum number of seconds the information in a bpdu is valid

Command Mode

- /exec/configure

spanning-tree mst max-hops

spanning-tree mst max-hops <max-hops-val> | no spanning-tree mst max-hops [<max-hops-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
max-hops	Set the max hops value for the spanning tree
<i>max-hops-val</i>	maximum number of hops a BPDU is valid

Command Mode

- /exec/configure

spanning-tree mst port-priority

spanning-tree mst <mst-id> port-priority <port-prio> | no spanning-tree mst <mst-id> port-priority [<port-prio>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree
<i>mst-id</i>	MST instance list, example 0,2-4,6,8-12
port-priority	Change an interface's spanning tree port priority
<i>port-prio</i>	Spanning-tree port priority

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree mst pre-standard

[no] spanning-tree mst pre-standard

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree
pre-standard	Force pre-standard MST BPDU transmission on port

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree mst priority

spanning-tree mst <mst-id> priority <prio> | no spanning-tree mst <mst-id> priority [<prio>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
<i>mst-id</i>	MST instance range, example: 0-3,5,7-9
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure

spanning-tree mst root

```
spanning-tree mst <mst-id> root <root-type> [ diameter <diameter-val> [ hello-time <hello-time-val> ] ] | no
spanning-tree mst <mst-id> root [ <root-type> [ diameter <diameter-val> [ hello-time <hello-time-val> ] ] ]
```

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
<i>mst-id</i>	MST instance range, example: 0-3,5,7-9
diameter	(Optional) Network diameter of this spanning tree
<i>diameter-val</i>	(Optional) Maximum number of bridges between any two end nodes
root	configure switch as root
<i>root-type</i>	configure switch as root
hello-time	(Optional) Set the hello interval for the spanning tree
<i>hello-time-val</i>	(Optional) number of seconds between generation of config bpdu

Command Mode

- /exec/configure

spanning-tree mst simulate pvst

[no] spanning-tree mst simulate pvst [<simpvst-disable>]

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree
simulate	Enable spanning tree simulation
pvst	Enable PVST simulation
<i>simpvst-disable</i>	(Optional) Disable PVST simulation on this interface

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree mst simulate pvst global

[no] spanning-tree mst simulate pvst global

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
mst	Multiple spanning tree configuration
simulate	Enable spanning tree simulation
pvst	Enable PVST simulation
global	Enable PVST Simulation by default on all ports

Command Mode

- /exec/configure

spanning-tree pathcost method

spanning-tree pathcost method <method-val> | no spanning-tree pathcost method [<method-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
pathcost	Spanning tree pathcost options
method	Method to calculate default port path cost
<i>method-val</i>	Method to calculate default port path cost

Command Mode

- /exec/configure

spanning-tree port-priority

spanning-tree [vlan <vlan-id> | bridge-domain <bd-id>] port-priority <port-prio> | no spanning-tree [vlan <vlan-id> | bridge-domain <bd-id>] port-priority [<port-prio>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	(Optional) VLAN Switch Spanning Trees
bridge-domain	(Optional) Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	(Optional) vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	(Optional) Bridge-Domain range, Example: 2,4-5,7,9-11
port-priority	Change an interface's spanning tree port priority
<i>port-prio</i>	Spanning-tree port priority

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree port type

spanning-tree port type <port-type> | no spanning-tree port type [<port-type>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
<i>port-type</i>	Specify a port type for spanning tree protocol use

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree port type edge bpdufilter default

[no] spanning-tree port type edge bpdufilter default

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
edge	Consider the interface as edge port (enable portfast)
bpdufilter	Enable edge port (portfast) bpdu filter on this switch
default	Enable bpdu filter by default on all edge (portfast) ports

Command Mode

- /exec/configure

spanning-tree port type edge bpduguard default

[no] spanning-tree port type edge bpduguard default

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
edge	Consider the interface as edge port (enable portfast)
bpduguard	Enable edge port (portfast) bpduguard on this switch
default	Enable bpduguard by default on all edge (portfast) ports

Command Mode

- /exec/configure

spanning-tree port type edge default

[no] spanning-tree port type edge default

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
edge	Consider the interface as edge port (enable portfast)
default	Select edge port type by default on all access ports

Command Mode

- /exec/configure

spanning-tree port type edge trunk

spanning-tree port type edge trunk | no spanning-tree port type edge trunk

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
edge	Consider the interface as edge port (enable portfast)
trunk	Consider the interface as edge port (enable portfast) even in trunk mode

Command Mode

- /exec/configure/if-switching /exec/configure/if-ethernet-switch-m

spanning-tree port type network default

[no] spanning-tree port type network default

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
port	Spanning tree port options
type	Specify a port type for spanning tree protocol use
network	Consider the interface as inter-switch link
default	Select network port type by default on all ports

Command Mode

- /exec/configure

spanning-tree pseudo-information

spanning-tree pseudo-information

Syntax Description

spanning-tree	Spanning Tree Subsystem
pseudo-information	configure spanning tree pseudo information

Command Mode

- /exec/configure

spanning-tree vlan

[no] spanning-tree vlan <vlan-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11

Command Mode

- /exec/configure

spanning-tree vlan forward-time

spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } forward-time <fwd-time> | no spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } forward-time [<fwd-time>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
forward-time	Set the forward delay for the spanning tree
<i>fwd-time</i>	number of seconds for the forward delay timer

Command Mode

- /exec/configure

spanning-tree vlan hello-time

```
spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } hello-time <hello-time-val> | no spanning-tree {
vlan <vlan-id> | bridge-domain <bd-id> } hello-time [ <hello-time-val> ]
```

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
hello-time	Set the hello interval for the spanning tree
<i>hello-time-val</i>	number of seconds between generation of config bpdu

Command Mode

- /exec/configure

spanning-tree vlan max-age

spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } max-age <max-age-val> | no spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } max-age [<max-age-val>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
max-age	Set the max age interval for the spanning tree
<i>max-age-val</i>	maximum number of seconds the information in a bpdu is valid

Command Mode

- /exec/configure

spanning-tree vlan priority

spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } priority <prio> | no spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } priority [<prio>]

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure

spanning-tree vlan root

```
spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } root <root-type> [ diameter <diameter-val> [
hello-time <hello-time-val> ] ] | no spanning-tree { vlan <vlan-id> | bridge-domain <bd-id> } root [ <root-type>
[ diameter <diameter-val> [ hello-time <hello-time-val> ] ] ]
```

Syntax Description

no	Negate a command or set its defaults
spanning-tree	Spanning Tree Subsystem
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
diameter	(Optional) Network diameter of this spanning tree
<i>diameter-val</i>	(Optional) Maximum number of bridges between any two end nodes
root	configure switch as root
<i>root-type</i>	configure switch as root
hello-time	(Optional) Set the hello interval for the spanning tree
<i>hello-time-val</i>	(Optional) number of seconds between generation of config bpdu

Command Mode

- /exec/configure

speed-group

speed-group <gspeed_val> | no speed-group [<gspeed_val>]

Syntax Description

no	Negate a command or set its defaults
speed-group	port group speed
<i>gspeed_val</i>	Interface port speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

speed

speed { <speed_val> }

Syntax Description

speed	Enter the port speed
<i>speed_val</i>	Interface port speed

Command Mode

- /exec/configure/if-mgmt-ether

speed

[no] speed <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
speed	Set the transmit and receive speeds
<i>i0</i>	Transmit and receive speeds

Command Mode

- /exec/configure/com1

speed

[no] speed <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
speed	Set the transmit and receive speeds
<i>i0</i>	Transmit and receive speeds

Command Mode

- /exec/configure/console

speed

speed { <speed_val> }

Syntax Description

speed	Enter the port speed
<i>speed_val</i>	Interface port speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

speed

speed { <speed_val> }

Syntax Description

speed	Enter the port speed
<i>speed_val</i>	Interface port speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-ethernet-p2p

speed

speed { <speed_val> }

Syntax Description

speed	Enter the port speed
<i>speed_val</i>	Interface port speed

Command Mode

- /exec/configure/if-port-channel

speed

```
[no] speed [ { <speed_val> | auto [ 100 [ 1000 ] ] } ]
```

Syntax Description

no	Negate a command or set its defaults
speed	Enter the port speed
<i>speed_val</i>	(Optional) Interface port speed
auto	(Optional) auto negotiate speed
100	(Optional) 100 Mbps speed
1000	(Optional) 1000 Mbps speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

speed

```
[no] speed [ { <speed_val> | auto [ 100 [ 1000 ] ] } ]
```

Syntax Description

no	Negate a command or set its defaults
speed	Enter the port speed
<i>speed_val</i>	(Optional) Interface port speed
auto	(Optional) auto negotiate speed
100	(Optional) 100 Mbps speed
1000	(Optional) 1000 Mbps speed

Command Mode

- /exec/configure/if-mgmt-ether

speed auto

speed auto

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

speed auto 100

speed auto 100

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed
100	100 Mbps speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

speed auto 100 1000

speed auto 100 1000

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed
100	100 Mbps speed
1000	1000 Mbps speed

Command Mode

- /exec/configure/if-mgmt-ether

speed auto 100 1000

speed auto 100 1000

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed
100	100 Mbps speed
1000	1000 Mbps speed

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

speed auto 100

speed auto 100

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed
100	100 Mbps speed

Command Mode

- /exec/configure/if-mgmt-ether

speed auto

speed auto

Syntax Description

speed	Enter the port speed
auto	auto negotiate speed

Command Mode

- /exec/configure/if-mgmt-ether

spf-interval

spf-interval <max-wait> [<initial-wait> <second-wait>] | no spf-interval <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
spf-interval	Configure SPF interval
<i>max-wait</i>	Maximum wait between trigger and SPF computation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and SPF computation (milli-secs)
<i>second-wait</i>	(Optional) Second wait between trigger and SPF computation (milli-secs)

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

spf-interval

spf-interval <level> <max-wait> [<initial-wait> <second-wait>] | no spf-interval <level> <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
spf-interval	Configure SPF interval
<i>level</i>	IS-IS level
<i>max-wait</i>	Maximum wait between trigger and SPF computation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and SPF computation (milli-secs)
<i>second-wait</i>	(Optional) Second wait between trigger and SPF computation (milli-secs)

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common

spf-interval

spf-interval <max-wait> [<initial-wait> <second-wait>] | no spf-interval <max-wait> [<initial-wait> <second-wait>]

Syntax Description

no	Negate a command or set its defaults
spf-interval	Configure SPF interval
<i>max-wait</i>	Maximum wait between trigger and SPF computation (milli-secs)
<i>initial-wait</i>	(Optional) Initial wait between trigger and SPF computation (milli-secs)
<i>second-wait</i>	(Optional) Second wait between trigger and SPF computation (milli-secs)

Command Mode

- /exec/configure/otv-isis/otv-isis-vrf-common

spf mode incremental

[no] spf mode incremental

Syntax Description

no	(Optional) Negate a command or set its defaults
spf	Configure route computation related settings
mode	Set the mode of spf computation
incremental	If possible, recompute only parts of the SPT

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

sport

{ sport <sva1> } | { no sport }

Syntax Description

no	Negate a command or set its defaults
sport	Configure ngoam Udp source port range
<i>sva1</i>	Udp source port range, max span 1024, Example: 2000-3000,400,500

Command Mode

- /exec/configure/configngoamprofile

sport

{ sport < sval > | no sport }

Syntax Description

no	Negate a command or set its defaults
sport	Outer UDP source port
<i>sval</i>	Source port

Command Mode

- /exec/configure/configngoamconnectcheck

src-intf

```
{ src-intf <src_if> }
```

Syntax Description

src-intf	Interface on which the host with src ip of the payload is connected
<i>src_if</i>	Interface

Command Mode

- /exec/configure/configngoamccpayload

ssh

```
{ ssh <s0> [ [ vrf { <vrf-name> | <vrf-known-name> } ] [ source-ip <s1> ] ] [ source-interface <intf> ] ] }
| { ssh <s0> [ [ source-ip <s1> ] [ vrf { <vrf-name> | <vrf-known-name> } ] ] [ source-interface <intf> ] ]
}
```

Syntax Description

ssh	SSH to another system
vrf	(Optional) Display per-VRF information
source-ip	(Optional) ip address to bind
source-interface	(Optional) Select source interface
<i>s0</i>	Enter hostname or user@hostname
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>s1</i>	(Optional) Enter source ip address to bind
<i>intf</i>	(Optional)

Command Mode

- /exec

ssh6

```
{ ssh6 <s0> [ [ vrf { <vrf-name> | <vrf-known-name> } ] [ source-ip <s2> ] [ interface <s1> ] ] | [
source-interface <intf> ] ] } | { ssh6 <s0> [ [ source-ip <s2> ] [ vrf { <vrf-name> | <vrf-known-name> } ] [
interface <s1> ] ] | [ source-interface <intf> ] ] }
```

Syntax Description

ssh6	SSH to another system using IPv6 addressing
vrf	(Optional) vrf to use
source-ip	(Optional) ip address to bind
source-interface	(Optional) Select source interface
interface	(Optional) interface to bind
s0	Enter hostname or user@hostname
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
s2	(Optional) Enter source ip address to bind
s1	(Optional) Enter interface to bind
intf	(Optional)

Command Mode

- /exec

ssh all

[no] ssh { kexalgos | ciphers | macs | keytypes } all

Syntax Description

no	(Optional) Negate a command or set its defaults
ssh	SSH to another system
kexalgos	key exchange methods that are used to generate per-connection keys
ciphers	ciphers to encrypt the connection
macs	message authentication codes used to detect traffic modification
keytypes	public key algorithms that the server can use to authenticate itself to the client
all	enable algorithms supported in current version of SSH

Command Mode

- /exec/configure/

ssh cipher-mode weak

```
{ { ssh cipher-mode weak } | { no ssh cipher-mode [ weak ] } }
```

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
cipher-mode	Set Cipher-mode for ssh
weak	Enable Weak Ciphers

Command Mode

- /exec/configure/

ssh idle

```
{ ssh { idle-timeout <i0> } [ keepalive-count <i1> ] | no ssh idle-timeout }
```

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
idle-timeout	SSH Client session idle timeout value
<i>i0</i>	Idle timeout value in seconds, 0 to disable, default is 0
keepalive-count	(Optional) Maximum count of SSH Keepalive packets to be sent to the ssh client
<i>i1</i>	(Optional) Count of SSH Keepalive packets sent to client, default is 0

Command Mode

- /exec/configure/

ssh key

```
{ ssh key { dsa [ force ] | rsa [ { <i0> | <oldrange> } [ force ] ] | ecdsa { <i0> } [ force ] } | no ssh key [ { dsa
[ force ] | rsa [ { <i0> | <oldrange> } [ force ] ] | ecdsa [ { <i0> } [ force ] ] ] }
```

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
key	Generate SSH Key
dsa	Generate DSA keys
force	(Optional) Force the generation of keys even if previous ones are present
rsa	Generate RSA keys
<i>i0</i>	(Optional) Enter number of bits (in multiples of 8)
<i>oldrange</i>	(Optional) Enter number of bits
force	(Optional) Force the generation of keys even if previous ones are present
ecdsa	Generate ECDSA keys
<i>i0</i>	Enter key size in bits (256, 384 or 521)
force	(Optional) Force the generation of keys even if previous ones are present

Command Mode

- /exec/configure

ssh login-attempts

```
{ { ssh login-attempts <d0> } | { no ssh login-attempts [ <d0> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
login-attempts	Set maximum login attempts from ssh
<i>d0</i>	Specify max-attempt number

Command Mode

- /exec/configure/

ssh login-gracetime

```
{ { ssh login-gracetime <d0> } | { no ssh login-gracetime [ <d0> ] } }
```

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
login-gracetime	Set login gracetime for ssh connection
<i>d0</i>	Specify grace time in seconds

Command Mode

- /exec/configure/

ssh port

{ ssh port { <port_number> } | no ssh port }

Syntax Description

no	Negate a command or set its defaults
ssh	SSH to another system
port	Set port number for ssh
<i>port_number</i>	Specify port number

Command Mode

- /exec/configure/

ssh rekey max-data max-time

[no] ssh rekey max-data <data> max-time <time>

Syntax Description

no	(Optional) Negate a command or set its defaults
ssh	SSH to another system
rekey	Renegotiate ssh key
max-data	data units are Kilo(K), Mega(M) and Giga(G)
<i>data</i>	Max data transmitted before key renegotiation
max-time	time units are Seconds(S), Minutes(M) and Hours(H)
<i>time</i>	Max time lapsed before key renegotiation

Command Mode

- /exec/configure/

ssh server enable

[no] ssh server enable

Syntax Description

no	(Optional) Negate a command or set its defaults
ssh	Configure SSH parameters
server	Configure SSH Server parameters
enable	Enable SSH server

Command Mode

- /exec/configure

ssx exporter

[no] ssx exporter <exportername>

Syntax Description

ssx	change ssx settings
exporter	ssx Exporter to be configured
<i>exportername</i>	ssx Exporter to be configured

Command Mode

- /exec/configure/config-ssx

ssx monitor

[no] ssx monitor <monitorname>

Syntax Description

ssx	change ssx settings
monitor	ssx Monitor to be configured
<i>monitorname</i>	ssx Monitor to be configured

Command Mode

- /exec/configure/config-ssx

ssx record

[no] ssx record <recordname>

Syntax Description

ssx	change ssx settings
record	ssx Record to be configured
<i>recordname</i>	ssx Record to be configured

Command Mode

- /exec/configure/config-ssx

ssx system monitor

[no] ssx system monitor <monitorname>

Syntax Description

ssx	change ssx settings
system	global config
monitor	ssx Monitor to be applied
<i>monitorname</i>	ssx Monitor to be applied

Command Mode

- /exec/configure/config-ssx

ssx system system-id

[no] ssx system system-id <systemid>

Syntax Description

ssx	change ssx settings
system	global config
system-id	ssx system-id to be applied
<i>systemid</i>	ssx system-id to be applied, default 0

Command Mode

- /exec/configure/config-ssx

standby

[no] standby [ip <ip-addr-first> | IPv6 <ip-addrv6-first>]

Syntax Description

no	(Optional) Negate a command or set its defaults
standby	Standby node
ip	(Optional) ip address for standby node
<i>ip-addr-first</i>	(Optional) ITD node IPv4 address
IPv6	(Optional) IPv6 address

Command Mode

- /exec/configure/itd-dg-node

standby ip

[no] standby { ip <ip-addr-first> | IPv6 <ip-addrv6-first> }

Syntax Description

no	(Optional) Negate a command or set its defaults
standby	Configure standby node for a primary node
ip	Standby node IPv4 address
<i>ip-addr-first</i>	IP4 prefix in format i.i.i.i
IPv6	Standby node IPv6 address

Command Mode

- /exec/configure/plb-dg-node

start-threshold

[no] start-threshold <start-threshold-rate>

Syntax Description

no	(Optional) Negate the command
start-threshold	Configure Start-threshold parameters in bytes
<i>start-threshold-rate</i>	Specify start threshold-rate

Command Mode

- /exec/configure/pkt-drop/profile

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamns/outse15

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel6

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel7

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel8

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel9

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel10

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/insel19

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/outse0

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/outsel1

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamtah/outsel2

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elanms/se13

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamns/sel4

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamns/se15

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamns/sel6

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elanms/se17

start

start

Syntax Description

start	Start Trigger
-------	---------------

Command Mode

- /exec/elamns/outse0

state

state <vstate> | no state

Syntax Description

no	Negate a command or set its defaults
state	Operational state of the VLAN
<i>vstate</i>	

Command Mode

- /exec/configure/vlan

state enabled

[no] state enabled

Syntax Description

no	(Optional) Negate a command or set its defaults
state	Port-profile state
enabled	Enable/ disable the port-profile

Command Mode

- /exec/configure/port-profile

statistics

[no] statistics

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/ipv6acl

statistics

[no] statistics

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/ipacl /exec/configure/vacl

statistics

[no] statistics

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/macac1

statistics collection-interval

statistics collection-interval <interval-val> | no statistics collection-interval

Syntax Description

no	Negate a command or set its defaults
statistics	Statistics related commands
collection-interval	How often to retrieve statistics
<i>interval-val</i>	Collection interval in seconds (0 = do not collect)

Command Mode

- /exec/configure/openflow/switch

statistics per-entry

[no] statistics per-entry

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/ipv6acl

statistics per-entry

[no] statistics per-entry

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/ipacl /exec/configure/vacl

statistics per-entry

[no] statistics per-entry

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/mplsac1

statistics per-entry

[no] statistics per-entry

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/macac1

stats-reporting-period

stats-reporting-period <time-in-sec> | no stats-reporting-period

Syntax Description

no	Negate a command or set its defaults
stats-reporting-period	Interval after which statistics are sent to the BMP server
<i>time-in-sec</i>	Delay value

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elamns/outsel5

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/eramns/se13

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elamns/sel4

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elanms/se15

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elamns/sel6

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elanms/se17

status

status

Syntax Description

status	Status of Trigger
--------	-------------------

Command Mode

- /exec/elamns/outse10

stop-threshold

[no] stop-threshold <stop-threshold-rate>

Syntax Description

no	(Optional) Negate the command
stop-threshold	Configure Stop-threshold parameters in bytes
<i>stop-threshold-rate</i>	

Command Mode

- /exec/configure/pkt-drop/profile

stopbits

[no] stopbits <stopbits-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
stopbits	Set async line stopbits
<i>stopbits-value</i>	async line stopbits value

Command Mode

- /exec/configure/console

stopbits 1

[no] stopbits { 1 | 2 }

Syntax Description

no	(Optional) Negate a command or set its defaults
stopbits	Set async line stopbits
1	One stop bit
2	Two stop bits

Command Mode

- /exec/configure/com1

storm-control-cpu

storm-control-cpu { { arp rate } <pps> } | no storm-control-cpu arp

Syntax Description

no	Negate a command or set its defaults
storm-control-cpu	Configure Interface storm control cpu
arp	arp storm control
rate	Set allowed arp traffic rate on this interface
<i>pps</i>	value in packets per sec

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-non-member /exec/configure/if-port-channel

storm-control

```
storm-control { { { broadcast blevel | multicast mlevel | unicast ulevel | port plevel } { pps <pps_val> | <level> } } } | action { shutdown | trap } } | no storm-control { { { broadcast blevel | multicast mlevel | unicast ulevel | port plevel } { pps [ <pps_val> ] | [ <level> ] } } } | action [ shutdown | trap ] }
```

Syntax Description

no	Negate a command or set its defaults
storm-control	Configure Interface storm control
broadcast	Broadcast address storm control
multicast	Multicast address storm control
unicast	Unicast address storm control
port	Port level storm control
blevel	Set allowed broadcast traffic level on this interface
mlevel	Set allowed multicast traffic level on this interface
ulevel	Set allowed unicast traffic level on this interface
plevel	Set allowed Port traffic level on this interface
<i>level</i>	Enter the storm suppression level
pps	Storm-control level is specified in packets per second
<i>pps_val</i>	Enter the storm suppression level in pps
action	Action on storm control
shutdown	Shutdown (Err-Disable) port
trap	Generate SNMP trap

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-l2-non-member /exec/configure/if-eth-port-channel-switch

streetaddress

{ streetaddress <line> | no streetaddress }

Syntax Description

no	Negate a command or set its defaults
streetaddress	Configure replacement part shipping address.
<i>line</i>	Provide street address (white spaces are fine)

Command Mode

- /exec/configure/callhome

stub

```
{ { [ eigrp ] stub [ { [ direct | connected | static | summary ] [ redistributed ] } + [ leak-map <leak-map> ] | {
receive-only } ] } } | { no [ eigrp ] stub [ { [ direct | connected | static | summary ] [ redistributed ] } + [ leak-map
<leak-map> ] | { receive-only } ] } }
```

Syntax Description

no	Negate a command or set its defaults
eigrp	(Optional) EIGRP router configuration commands
stub	Set IP-EIGRP as stubbed router
direct	(Optional) Do advertise connected routes
connected	(Optional) Do advertise connected routes
static	(Optional) Do advertise static routes
summary	(Optional) Do advertise summary routes
redistributed	(Optional) Do advertise redistributed routes
leak-map	(Optional) Allow dynamic prefixes based on the leak-map
<i>leak-map</i>	(Optional) leak-map name
receive-only	(Optional) Set IP-EIGRP as receive only neighbor

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

sub-switch vlan

sub-switch <subswitch-id> vlan <vlan-id> | no sub-switch <subswitch-id>

Syntax Description

no	Negate a command or set its defaults
sub-switch	Logical sub-switch id
<i>subswitch-id</i>	Logical subswitch-id(2 to 10)
vlan	VLAN-id or VLAN-range
<i>vlan-id</i>	VLAN-id or VLAN-range

Command Mode

- /exec/configure/openflow/switch

subscription

[no] subscription <sub-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
subscription	Create a Subscription
<i>sub-id</i>	Identifier

Command Mode

- /exec/configure/telemetry

summary-address

summary-address { <ip-addr> <ip-mask> | <ip-prefix> } <level> | no summary-address { <ip-addr> <ip-mask> | <ip-prefix> } [<level>]

Syntax Description

no	Negate a command or set its defaults
summary-address	Configure IP address summaries
<i>ip-addr</i>	IP summary address
<i>ip-mask</i>	IP summary mask
<i>ip-prefix</i>	IP summary prefix
<i>level</i>	Level to summarize into

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-ipv4

summary-address

summary-address <ipv6-prefix> <level> | no summary-address <ipv6-prefix> [<level>]

Syntax Description

no	Negate a command or set its defaults
summary-address	Configure IP address summaries
<i>level</i>	Level to summarize into

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

summary-address

[no] summary-address <ipv6-prefix> [tag <tagval> | not-advertise]

Syntax Description

no	(Optional) Negate a command or set its defaults
summary-address	Configure route summarization for redistribution
tag	(Optional) 32-bit tag value
<i>tagval</i>	(Optional) 32-bit tag value
not-advertise	(Optional) Suppress advertising the specified summary

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

summary-address

[no] summary-address { <ip-dest> <ip-mask> | <ip-prefix> } [tag <tagval> | not-advertise]

Syntax Description

no	(Optional) Negate a command or set its defaults
summary-address	Configure route summarization for redistribution
<i>ip-dest</i>	IP prefix format: i.i.i.i
<i>ip-mask</i>	IP network mask format: m.m.m.m
<i>ip-prefix</i>	IP prefix format: x.x.x.x/ml
tag	(Optional) 32-bit tag value
<i>tagval</i>	(Optional) 32-bit tag value
not-advertise	(Optional) Suppress advertising the specified summary

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

suppress-arp

[no] suppress-arp [disable]

Syntax Description

no	(Optional) Negate a command or set its defaults
suppress-arp	Enable ARP suppression
disable	(Optional) Override the global ARP suppression config

Command Mode

- /exec/configure/if-nve/vni

suppress-fib-pending

[no] suppress-fib-pending

Syntax Description

no	(Optional) Negate a command or set its defaults
suppress-fib-pending	Advertise only routes that are programmed in hardware to peers

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

suppress-fib-pending

[no] suppress-fib-pending

Syntax Description

no	(Optional) Negate a command or set its defaults
suppress-fib-pending	Advertise only routes that are programmed in hardware to peers

Command Mode

- /exec/configure/router-bgp

suppress-inactive

[no | default] suppress-inactive

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
suppress-inactive	Advertise only active routes to peer

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

suppress-inactive

[no] suppress-inactive

Syntax Description

no	(Optional) Negate a command or set its defaults
suppress-inactive	Advertise only active routes to peers

Command Mode

- /exec/configure/router-bgp/router-bgp-af

suppress-signaling-protocol ldp

[no | default] suppress-signaling-protocol ldp

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
suppress-signaling-protocol	Suppress VPLS BGP AD protocol
ldp	LDP signaling

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-l2vpn-vpls

suppress mac-route

[no] suppress mac-route

Syntax Description

no	(Optional) Negate a command or set its defaults
suppress	Suppress MAC only route advertisement
mac-route	MAC route

Command Mode

- /exec/configure/if-nve

switch-id

switch-id <asid> | no switch-id

Syntax Description

no	Negate a command or set its defaults
switch-id	Configure Switch ID
<i>asid</i>	Anycast Switch ID

Command Mode

- /exec/configure/anycast

switch-priority

{ switch-priority <i0> | no switch-priority }

Syntax Description

no	Negate a command or set its defaults
switch-priority	Priority of the switch(0-highest 7-lowest)
<i>i0</i>	Priority of the switch(0-highest 7-lowest)

Command Mode

- /exec/configure/callhome

switch-profile

switch-profile <s0>

Syntax Description

switch-profile	Enter switch-profile configuration mode
<i>s0</i>	Enter the name of the switch-profile

Command Mode

- /exec/configure

switch-profile

[no] switch-profile <s0> { profile-only { local | all } | local-config | all-config }

Syntax Description

no	Negate a command or set its defaults
switch-profile	Enter switch-profile configuration mode
s0	Enter the name of the switch-profile
profile-only	Deletion of profile only and no other configuration
local	Deletion of profile only and no other configurations in local switch
all	Deletion of profile only and no other configurations from all the peers
local-config	Deletion of profile and local configuration
all-config	Deletion of profile, local and peer configurations

Command Mode

- /exec/configure

switch-role border-leaf

[no] switch-role border-leaf

Syntax Description

switch-role	Switch Role
border-leaf	Border Leaf

Command Mode

- /exec/configure/nbm-controller

switch-scope controller

{ switch-scope controller <controller-id> | no switch-scope controller }

Syntax Description

no	Negate a command or set its defaults
switch-scope	switch-scope
controller	Controller command
<i>controller-id</i>	Controller id

Command Mode

- /exec

switch pipeline

switch <switch-id> pipeline <pipeline-id> | no switch <switch-id>

Syntax Description

no	Negate a command or set its defaults
switch	Switch
<i>switch-id</i>	Logical switch-id
pipeline	Select forwarding profile, use 'show openflow hardware capabilities' for choices
<i>pipeline-id</i>	Pipeline id

Command Mode

- /exec/configure/openflow

switchback

switchback

Syntax Description

switchback	switchback to default vdc
------------	---------------------------

Command Mode

- /exec

switching-mode fabric-speed 40g

[no] switching-mode fabric-speed 40g

Syntax Description

no	(Optional) Negate a command or set its defaults
switching-mode	Configure the operating switching-mode of asics
fabric-speed	fabric speed settings
40g	fabric speed at 40g instead of 42g

Command Mode

- /exec/configure

switching-mode fast-to-slow-speed-cut-through

[no] switching-mode fast-to-slow-speed-cut-through

Syntax Description

no	(Optional) Negate a command or set its defaults
switching-mode	Configure the operating switching-mode of asics
fast-to-slow-speed-cut-through	Operate in fast-to-slow speed cut-through mode

Command Mode

- /exec/configure

switching-mode store-forward

[no] switching-mode store-forward

Syntax Description

no	(Optional) Negate a command or set its defaults
switching-mode	Configure the operating switching-mode of asics
store-forward	Operate in store and forward mode

Command Mode

- /exec/configure

switchport

[no] switchport

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-non-member /exec/configure/if-ethernet /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

switchport

switchport

Syntax Description

switchport	Configure switchport parameters
------------	---------------------------------

Command Mode

- /exec/configure/if-eth-non-member /exec/configure/if-ethernet-all /exec/configure/if-port-channel /exec/configure/if-ethernet-p2p

switchport access vlan

switchport access vlan <vlan-id-access> | no switchport access vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
access	Set access mode characteristics of the interface
vlan	Set VLAN when interface is in access mode
<i>vlan-id-access</i>	VLAN ID of the VLAN when this port is in access mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch

switchport access vlan

switchport access vlan <vlan-id-access> | no switchport access vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
access	Set access mode characteristics of the interface
vlan	Set VLAN when interface is in access mode
<i>vlan-id-access</i>	VLAN ID of the VLAN when this port is in access mode

Command Mode

- /exec/configure/if-ethernet-all

switchport access vlan

switchport access vlan <vlan-id-access> | no switchport access vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
access	Set access mode characteristics of the interface
vlan	Set VLAN when interface is in access mode
<i>vlan-id-access</i>	VLAN ID of the VLAN when this port is in access mode

Command Mode

- /exec/configure/if-eth-port-channel-switch

switchport autostate exclude

```
switchport autostate exclude [ vlan { <exclude-vlans> | add <add-vlans> | except <except-vlans> | remove
<remove-vlans> | all | none } ] | no switchport autostate exclude [ dummy ] [ vlan { <exclude-vlans> | add
<add-vlans> } ]
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
autostate	Include or exclude this port from vlan link up calculation
exclude	Exclude this port from vlan link up calculation
vlan	(Optional) VLAN Id
<i>exclude-vlans</i>	(Optional) VLAN IDs of the VLANs to auto-state exclude on this interface
add	(Optional) add VLANs to except list
<i>add-vlans</i>	(Optional) VLAN IDs of the VLANs to auto-state exclude on this interface
except	(Optional) List of VLANs to excepted from auto-state exclude
<i>except-vlans</i>	(Optional) VLAN IDs of the VLANs to auto-state exclude on this interface
remove	(Optional) remove VLANs from except list
<i>remove-vlans</i>	(Optional) VLAN IDs of the VLANs to auto-state exclude on this interface
all	(Optional) Exclude all VLANs
none	(Optional) Exclude no VLANs
dummy	(Optional) Hidden Keyword

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-gig-ether /exec/configure/if-port-channel-range /exec/configure/if-eth-port-channel-switch /exec/configure/if-remote-ethernet-switch

switchport backup interface

[no] switchport backup interface <if0> [__readonly__ <from_snmp>]

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
<i>__readonly__</i>	(Optional) Read Only
<i>from_snmp</i>	(Optional) Configuration comes from SNMP

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface

[no] switchport backup interface <if0> [__readonly__ <from_snmp>]

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
__readonly__	(Optional) Read Only
<i>from_snmp</i>	(Optional) Configuration comes from SNMP

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface multicast fast-convergence

[no] switchport backup interface <if0> multicast fast-convergence

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
multicast	multicast parameters
fast-convergence	configure fast convergence on backup interface

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface multicast fast-convergence

[no] switchport backup interface <if0> multicast fast-convergence

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
multicast	multicast parameters
fast-convergence	configure fast convergence on backup interface

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface preemption delay

{ switchport backup interface <if0> preemption delay <delay_secs> } | { no switchport backup interface <if0> preemption delay }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
preemption	preemption parameters
delay	preemption parameters
<i>preemption</i>	delay
<i>delay_secs</i>	preemption delay in seconds

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface preemption delay

{ switchport backup interface <if0> preemption delay <delay_secs> } | { no switchport backup interface <if0> preemption delay }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
preemption	preemption parameters
delay	preemption parameters
<i>preemption</i>	delay
<i>delay_secs</i>	preemption delay in seconds

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface preemption mode

{ switchport backup interface <if0> preemption mode <preempt_mode> } | { no switchport backup interface <if0> preemption mode }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
preemption	preemption parameters
mode	set the preemption mode
<i>preemption</i>	mode
<i>preempt_mode</i>	preemption mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport backup interface preemption mode

{ switchport backup interface <if0> preemption mode <preempt_mode> } | { no switchport backup interface <if0> preemption mode }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
backup	Set backup for the interface
interface	Specify an interface as backup
<i>if0</i>	Enter interface name
preemption	preemption parameters
mode	set the preemption mode
<i>preemption</i>	mode
<i>preempt_mode</i>	preemption mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-port-channel-switch

switchport beacon

[no] switchport beacon

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
beacon	Disable/enable the beacon for an interface

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-legacy-eth

switchport block unicast

switchport block { unicast | multicast } | no switchport block { unicast | multicast }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
block	Block specified outbound traffic for all VLANs
unicast	Block unknown unicast traffic
multicast	Block flood multicast traffic

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport description

switchport description <desc_line> | no switchport description [<desc_line>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
description	Enter description of maximum 254 characters
<i>desc_line</i>	Description of maximum 254 characters

Command Mode

- /exec/configure/if-iscsi /exec/configure/if-fcip /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-gig-ether /exec/configure/if-fa /exec/configure/if-fv /exec/configure/if-san-port-channel /exec/configure/if-sme /exec/configure/if-ioa /exec/configure/if-gig-ether-sub /exec/configure/if-vfc /exec/configure/if-vfc-port-channel

switchport dot1q ethertype

switchport dot1q ethertype { 0x8100 | 0x88A8 | 0x9100 | <any> } | no switchport dot1q ethertype [<any>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
dot1q	Configure dot1q EtherType value
ethertype	Configure dot1q EtherType value
0x8100	Default EtherType for 802.1q frames
0x88A8	EtherType for 802.1ad double tagged frames
0x9100	EtherType for QinQ frames
<i>any</i>	Any EtherType

Command Mode

- /exec/configure/if-eth-port-channel-switch

switchport dot1q ethertype

switchport dot1q ethertype { 0x8100 | 0x88A8 | 0x9100 | <any> } | no switchport dot1q ethertype [<any>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
dot1q	Configure dot1q EtherType value
ethertype	Configure dot1q EtherType value
0x8100	Default EtherType for 802.1q frames
0x88A8	EtherType for 802.1ad double tagged frames
0x9100	EtherType for QinQ frames
<i>any</i>	Any EtherType

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all

switchport duplex

{ switchport duplex { auto | full | half } | no switchport duplex [{ auto | full | half }] }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
duplex	Enter the port duplex mode
auto	auto negotiate duplex mode
full	full duplex mode
half	half duplex mode

Command Mode

- /exec/configure/if-legacy-eth /exec/configure/if-mgmt-ether

switchport host

[no] switchport host

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
host	Set port host

Command Mode

- /exec/configure/if-eth-12-non-member /exec/configure/if-ethernet-switch
/exec/configure/if-ethernet-switch-m /exec/configure/if-ethernet-all

switchport ignore bit-errors

{ switchport ignore bit-errors | no switchport ignore bit-errors }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
ignore	Enter parameter to be ignored
bit-errors	ignore bit-errors

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext

switchport isolated

[no] switchport isolated

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
isolated	Disable loop-free detection.

Command Mode

- /exec/configure/if-eth-12-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mac-learn disable

switchport mac-learn disable | no switchport mac-learn disable

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mac-learn	Disable/enable mac learning on interface
disable	Disable mac learning on all VLANs on interface

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mode

{ switchport mode { <port_mode> } | no switchport mode }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	port mode

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mode

{ switchport mode { <port_mode> } | no switchport mode }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	port mode

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mode

switchport mode <port_mode> | no switchport mode [<port_mode>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	Port mode

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext

switchport mode

switchport mode <port_mode> | no switchport mode [<port_mode>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	Port mode

Command Mode

- /exec/configure/if-fcip

switchport mode

switchport mode <port_mode> | no switchport mode [<port_mode>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	Port mode

Command Mode

- /exec/configure/if-san-port-channel

switchport mode

switchport mode <port_mode> | no switchport mode [<port_mode>]

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
<i>port_mode</i>	Port mode

Command Mode

- /exec/configure/if-vfc /exec/configure/if-vfc-port-channel

switchport mode monitor buffer-limit

switchport mode monitor buffer-limit { <value> [packets | bytes | kbytes | mbytes] } | no switchport mode monitor buffer-limit

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
monitor	Configures an interface as span-destination
buffer-limit	Set buffer limit for span destination
<i>value</i>	Limit in terms of packets
packets	(Optional) Packets
bytes	(Optional) Bytes
kbytes	(Optional) Kilo bytes
mbytes	(Optional) Mega bytes

Command Mode

- /exec/configure/if-eth-12-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mode private-vlan

```
{ switchport mode private-vlan <port_mode> } | { no switchport mode private-vlan [ <port_mode> ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
private-vlan	Set the private VLAN configuration
<i>port_mode</i>	private vlan mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-remote-ethernet-switch

switchport mode private-vlan trunk

```
{ switchport mode private-vlan trunk <trunk_mode> } | { no switchport mode private-vlan trunk [ <trunk_mode> ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mode	Enter the port mode
private-vlan	Set the private VLAN configuration
trunk	private-vlan trunk
<i>trunk_mode</i>	private vlan trunk mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch /exec/configure/if-remote-ethernet-switch

switchport monitor

switchport monitor [ingress [learning]] | no switchport monitor

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
monitor	Configures an interface as span-destination
ingress	(Optional) Enables the forwarding on incoming packets
learning	(Optional) Enables mac-learning

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport mtu

{ switchport mtu <i0> | no switchport mtu [<i0>] }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
mtu	Configure mtu for the port
<i>i0</i>	Enter mtu

Command Mode

- /exec/configure/if-gig-ether-sub /exec/configure/if-legacy-eth

switchport owner

{ switchport owner { <owner_str> } | no switchport owner }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
owner	Specify the owner of an interface
<i>owner_str</i>	Owner of maximum 80 characters

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-vfc /exec/configure/if-vfc-port-channel

switchport port-security

[no] switchport port-security

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command

Command Mode

- /exec/configure/if-switching

switchport port-security aging time

[no] switchport port-security aging time <value>

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
aging	Port-security aging commands
time	Port-security aging time
<i>value</i>	Aging time in minutes. Enter a value between 1 and 1440

Command Mode

- /exec/configure/if-switching

switchport port-security aging type absolute

[no] switchport port-security aging type { absolute | inactivity }

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
aging	Port-security aging commands
type	Type of timers
absolute	Absolute Timer
inactivity	Inactivity Timer

Command Mode

- /exec/configure/if-switching

switchport port-security mac-address

[no] switchport port-security mac-address <mac-address> [vlan <vlanid>]

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
mac-address	MAC address
<i>mac-address</i>	48 bit mac address format HHHH.HHHH.HHHH
vlan	(Optional) Vlan on which the mac address should be secured
<i>vlanid</i>	(Optional) vlan id. Enter a value between 1 and 4094

Command Mode

- /exec/configure/if-switching

switchport port-security mac-address sticky

[no] switchport port-security mac-address sticky

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
mac-address	MAC address
sticky	Sticky MAC address

Command Mode

- /exec/configure/if-switching

switchport port-security maximum

[no] switchport port-security maximum <value> [vlan <vlanid>]

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
maximum	Max secure addresses
<i>value</i>	Maximum addresses 1 to 1025
vlan	(Optional) Vlan on which the mac address should be secured
<i>vlanid</i>	(Optional) vlan id. Enter a value between 1 and 4094

Command Mode

- /exec/configure/if-switching

switchport port-security violation

[no] switchport port-security violation { protect | restrict | shutdown }

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
port-security	Port security related command
violation	Security violation mode
protect	security violation protect mode
restrict	security violation restrict mode
shutdown	security violation shutdown mode

Command Mode

- /exec/configure/if-switching

switchport priority extend cos

{ switchport priority extend { cos <cos-value> | trust } | no switchport priority extend }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
priority	CoS Priority parameter
extend	Enter priority extend mode
cos	Switch will send CDP packet to instruct phone to mark data traffic with CoS value
<i>cos-value</i>	Trust CoS value to be sent to the IP Phone
trust	Switch will send CDP packet to instruct phone to trust tagged data traffic

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all

switchport private-vlan association trunk

```
{ switchport private-vlan association trunk <primary-vlan> <secondary-vlan> } | { no switchport private-vlan
association trunk [ <primary-vlan> [ <secondary-vlan> ] ] }
```

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
association	private vlan trunk association
trunk	private-vlan trunk secondary
no	Negate a command or set its defaults
<i>primary-vlan</i>	Primary VLAN ID
<i>secondary-vlan</i>	Secondary VLAN ID

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport private-vlan host-association

{ switchport private-vlan host-association <primary-vlan> <secondary-vlan> } | { no switchport private-vlan host-association }

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
host-association	Set the private VLAN host association
no	Negate a command or set its defaults
<i>primary-vlan</i>	Primary VLAN ID
<i>secondary-vlan</i>	Secondary VLAN ID

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport private-vlan mapping

```
{ switchport private-vlan mapping <primary-vlan> [ { add | remove } ] <secondary_vlans> } | { no switchport private-vlan mapping [ <primary-vlan> <secondary_vlans> ] }
```

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
mapping	Set the private VLAN access/trunk promiscuous mapping
add	(Optional) Add a VLAN to private VLAN list
remove	(Optional) Remove a VLAN from private VLAN list
no	Negate a command or set its defaults
<i>primary-vlan</i>	Primary private VLAN
<i>secondary_vlans</i>	Secondary VLAN IDs

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport private-vlan mapping trunk

```
{ switchport private-vlan mapping trunk <primary-vlan> [ { add | remove } ] <secondary_vlans> } | { no
switchport private-vlan mapping trunk [ <primary-vlan> [ <secondary_vlans> ] ] }
```

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
mapping	Set the private VLAN access/trunk promiscuous mapping
add	(Optional) Add a VLAN to private VLAN list
remove	(Optional) Remove a VLAN from private VLAN list
no	Negate a command or set its defaults
trunk	private-vlan trunk promiscuous
<i>primary-vlan</i>	Primary private VLAN
<i>secondary_vlans</i>	Secondary VLAN IDs

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport private-vlan trunk allowed vlan

switchport private-vlan trunk allowed vlan { <allowed-vlans> | add <add-vlans> | except <except-vlans> | remove <remove-vlans> | all | none } | no switchport private-vlan trunk allowed vlan <no-allowed-vlans>

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
trunk	Set the private vlan trunking configuration
allowed	Set allowed VLANs when interface is in private-vlan trunking mode
vlan	VLAN status
<i>allowed-vlans</i>	VLAN IDs of the allowed VLANs when interface is in private-vlan trunking mode
add	add VLANs to the current list
<i>add-vlans</i>	VLAN IDs of the allowed VLANs when interface is in private-vlan trunking mode
except	all VLANs except the following
<i>except-vlans</i>	VLAN IDs of disallowed VLANs when this port is in trunking mode
remove	remove VLANs from the current list
<i>remove-vlans</i>	VLAN IDs of disallowed VLANs when this port is in trunking mode
all	all VLANs
none	no VLANs
no	Negate a command or set its defaults
<i>no-allowed-vlans</i>	VLAN IDs of disallowed VLANs when this port is in trunking mode

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport private-vlan trunk native vlan

{ switchport private-vlan trunk native vlan <native-vlan> } | { no switchport private-vlan trunk native vlan }

Syntax Description

switchport	Configure switchport parameters
private-vlan	Set the private VLAN configuration
no	Negate a command or set its defaults
trunk	Set the private vlan trunking configuration
native	Set the private vlan trunking native configuration
vlan	VLAN status
<i>native-vlan</i>	native vlan id

Command Mode

- /exec/configure/if-switching /exec/configure/if-eth-port-channel-switch

switchport promiscuous-mode off

switchport promiscuous-mode { off | on }

Syntax Description

switchport	Configure switchport parameters
promiscuous-mode	Configure promiscuous mode for the port
off	Disable promiscuous mode
on	Enable promiscuous mode

Command Mode

- /exec/configure/if-gig-ether-sub /exec/configure/if-legacy-eth

switchport speed

```
{ switchport speed { 1000 | 2000 | 4000 | 8000 | 10000 | 16000 | 32000 | auto [ max { 20001 | 40001 | 80001
| 160001 | 320001 } ] } | no switchport speed [ { 1000 | 2000 | 4000 | 8000 | 10000 | 16000 | 32000 | auto [
max { 20001 | 40001 | 80001 | 160001 | 320001 } ] } ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
speed	Enter the port speed
1000	1000 Mbps speed
2000	2000 Mbps speed
4000	4000 Mbps speed
8000	8000 Mbps speed
10000	10000 Mbps speed
16000	16000 Mbps speed
32000	32000 Mbps speed
auto	auto negotiate speed
max	(Optional) Maximum speed
20001	(Optional) Maximum speed is 2000
40001	(Optional) Maximum speed is 4000
80001	(Optional) Maximum speed is 8000
160001	(Optional) Maximum speed is 16000
320001	(Optional) Maximum speed is 32000

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-san-port-channel

switchport speed

{ switchport speed { 10 | 100 | 1000 | auto } | no switchport speed [{ 10 | 100 | 1000 | auto }] }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
speed	Enter the port speed
10	10 Mbps speed
100	100 Mbps speed
1000	1000 Mbps speed
auto	auto negotiate speed

Command Mode

- /exec/configure/if-mgmt-ether

switchport trunk allow-multi-tag

switchport trunk allow-multi-tag | no switchport trunk allow-multi-tag

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
allow-multi-tag	Allows Multiple Q-Tags

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport trunk allowed vlan

switchport trunk allowed vlan { <allow-vlans> | add <add-vlans> | except <except-vlans> | remove <remove-vlans> | all | none } | no switchport trunk allowed vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
allowed	Set allowed VLAN characteristics when interface is in trunking mode
vlan	Set allowed VLANs when interface is in trunking mode
<i>allow-vlans</i>	VLAN IDs of the allowed VLANs when this port in trunking mode
add	add VLANs to the current list
<i>add-vlans</i>	VLAN IDs of the allowed VLANs when this port in trunking mode
all	all VLANs
except	all VLANs except the following
<i>except-vlans</i>	VLAN IDs of the allowed VLANs when this port in trunking mode
none	no VLANs
remove	remove VLANs from the current list
<i>remove-vlans</i>	VLAN IDs of the allowed VLANs when this port in trunking mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport trunk allowed vsan

```
{ switchport trunk allowed vsan { add <i0> | all | <i1> [ no-warning ] } | no switchport trunk allowed vsan [
{ add <i0> | all | <i1> } ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
allowed	Configure allowed list for interface(s)
vsan	Configure allowed list for interface(s)
add	give VSAN id range to add to allowed vsan list
<i>i0</i>	VSAN id range
all	add all the vsans to allowed vsan list
<i>il</i>	VSAN id range
no-warning	(Optional) Avoid displaying a warning message and user prompt for this command

Command Mode

- /exec/configure/if-fc /exec/configure/if-san-port-channel /exec/configure/if-fcip /exec/configure/if-svc /exec/configure/if-bay /exec/configure/if-ext

switchport trunk allowed vsan

```
{ switchport trunk allowed vsan { add <i0> | all | <i1> [ no-warning ] } | no switchport trunk allowed vsan [
{ add <i0> | all | <i1> } ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
allowed	Configure allowed list for interface(s)
vsan	Configure allowed list for interface(s)
add	give VSAN id range to add to allowed vsan list
<i>i0</i>	VSAN id range
all	add all the vsans to allowed vsan list
<i>i1</i>	VSAN id range
no-warning	(Optional) Avoid displaying a warning message and user prompt for this command

Command Mode

- /exec/configure/if-vfc

switchport trunk mode

{ switchport trunk mode { <trunk_mode> } | no switchport trunk mode [{ <trunk_mode> }] }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
mode	Configure trunking mode
<i>trunk_mode</i>	Trunk mode

Command Mode

- /exec/configure/if-fc /exec/configure/if-bay /exec/configure/if-ext /exec/configure/if-fcip /exec/configure/if-san-port-channel

switchport trunk mode

```
{ switchport trunk mode { <trunk_mode> } | no switchport trunk mode [ { <trunk_mode> } ] }
```

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
mode	Configure trunking mode
<i>trunk_mode</i>	Trunk mode

Command Mode

- /exec/configure/if-vfc /exec/configure/if-vfc-port-channel

switchport trunk native vlan

switchport trunk native vlan <vlan-id-native> | no switchport trunk native vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
native	Set trunking native characteristics when interface is in trunking mode
vlan	Set native VLAN when interface is in trunking mode
<i>vlan-id-native</i>	VLAN ID of the native VLAN when this port is in trunking mode

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport trunk pruning vlan except add remove none all

{ no switchport trunk pruning vlan [<vlan-ids>] | switchport trunk pruning vlan <vlan-ids> | switchport trunk pruning vlan except <vlan-ids> | switchport trunk pruning vlan add <vlan-ids> | switchport trunk pruning vlan remove <vlan-ids> | switchport trunk pruning vlan none | switchport trunk pruning vlan all }

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
trunk	Configure trunking parameters on an interface
pruning	Set pruning VLAN characteristics when interface is in trunking mode
vlan	Enter VLANs
add	add VLANs to the current list
remove	remove VLANs from the current list
except	all VLANs except the following
none	no VLANs
all	all VLANs
<i>vlan-ids</i>	(Optional) Enter VLANs

Command Mode

- /exec/configure/if-switching

switchport virtual-ethernet-bridge

switchport virtual-ethernet-bridge | no switchport virtual-ethernet-bridge

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
virtual-ethernet-bridge	Enable hair-pin forwarding

Command Mode

- /exec/configure/if-eth-l2-non-member /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping

[no] switchport vlan mapping <vlan-id-orig> [inner <vlan-id-inner>] <vlan-id-translated>

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
<i>vlan-id-orig</i>	VLAN ID 1-3967
inner	(Optional) inner vlanid
<i>vlan-id-inner</i>	(Optional) Inner VLAN ID
<i>vlan-id-translated</i>	Translated VLAN ID

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping all

[no] switchport vlan mapping all

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
all	all VLANs

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all /exec/configure/if-eth-port-channel-switch

switchport vlan mapping all dot1q-tunnel

[no] switchport vlan mapping all dot1q-tunnel

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
all	all VLANs
dot1q-tunnel	selective dot1q-tunnel

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping all dot1q-tunnel

[no] switchport vlan mapping all dot1q-tunnel <vlan-id-translated>

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
all	all VLANs
dot1q-tunnel	selective dot1q-tunnel
<i>vlan-id-translated</i>	Translated VLAN ID

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping dot1q-tunnel

[no] switchport vlan mapping <vlan-id-orig2> dot1q-tunnel <vlan-id-translated>

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
<i>vlan-id-orig2</i>	VLAN ID 1-4094 or Vlan range(s): 1-5, 10 or 2-5,7-19 for Selective dot1q-tunnel
dot1q-tunnel	selective dot1q-tunnel
<i>vlan-id-translated</i>	Translated VLAN ID

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping dot1q-tunnel allowed-vlan

[no] switchport vlan mapping dot1q-tunnel allowed-vlan <vlan-id-list>

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
dot1q-tunnel	selective dot1q-tunnel
allowed-vlan	Set allowed VLAN characteristics when interface is in trunking mode
<i>vlan-id-list</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport vlan mapping enable

[no] switchport vlan mapping enable

Syntax Description

no	(Optional) Negate a command or set its defaults
switchport	Configure switchport parameters
vlan	Set VLAN translation mapping
mapping	VLAN translation mapping
enable	enable/disable VLAN translation

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch
/exec/configure/if-remote-ethernet-switch /exec/configure/if-ethernet-all
/exec/configure/if-eth-port-channel-switch

switchport voice vlan

switchport voice vlan { <vlan-id-voice> | dot1p | untagged } | no switchport voice vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
voice	Set voice mode characteristics of the interface
vlan	Set VLAN for VoIP traffic
<i>vlan-id-voice</i>	VLAN ID of the VLAN configured for VoIP traffic
dot1p	Switch will send CDP packets to instruct IP phone to send voice traffic in 802.1p frames
untagged	Switch will send CDP packets to instruct IP phone to send voice traffic untagged

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-ethernet-p2p-switch /exec/configure/if-remote-ethernet-switch

switchport voice vlan

switchport voice vlan { <vlan-id-voice> | dot1p | untagged } | no switchport voice vlan

Syntax Description

no	Negate a command or set its defaults
switchport	Configure switchport parameters
voice	Set voice mode characteristics of the interface
vlan	Set VLAN for VoIP traffic
<i>vlan-id-voice</i>	VLAN ID of the VLAN configured for VoIP traffic
dot1p	Switch will send CDP packets to instruct IP phone to send voice traffic in 802.1p frames
untagged	Switch will send CDP packets to instruct IP phone to send voice traffic untagged

Command Mode

- /exec/configure/if-ethernet-all

switchto vdc

```
switchto vdc <e-vdc2> [ force ] [ bypass ] [ __readonly__ <vdc_id> <invalid_vdc_id> <noauth_vdc_id>
<no_first> ]
```

Syntax Description

switchto	Goto specific Virtual Device Context <vdc-name> <vdc-id>
vdc	Manage Virtual Device Context
<i>e-vdc2</i>	Enter Virtual Device Context <vdc-id>
<i>__readonly__</i>	(Optional) Read Only
force	(Optional) force
<i>vdc_id</i>	(Optional) Enter Virtual Device Context <vdc-id>
<i>invalid_vdc_id</i>	(Optional) Enter Virtual Device Context <vdc-id>
<i>noauth_vdc_id</i>	(Optional) Enter Virtual Device Context <vdc-id>
<i>no_first</i>	(Optional) Enter Virtual Device Context <vdc-id>
bypass	(Optional) Enter Virtual Device Context <vdc-id>

Command Mode

- /exec/

sync-peers destination

sync-peers destination <dst-ip> [source <src-ip> | vrf <vrf-name>] + | no sync-peers destination [<dst-ip> [source <src-ip>]]

Syntax Description

no	Negate a command or set its defaults
sync-peers	Specify peers to whom configuration needs to be synced
destination	Specify destination ip address of peer switch
<i>dst-ip</i>	IPv4 address (A.B.C.D) of destination
source	(Optional) Source interface for sending out configs
<i>src-ip</i>	(Optional) IPv4 address (A.B.C.D) of source
vrf	(Optional) vrf to be used default/management
<i>vrf-name</i>	(Optional) vrf to be used

Command Mode

- /exec/configure

sync-snmp-password

sync-snmp-password <s0> <s1> <s2>

Syntax Description

sync-snmp-password	sync snmp password
<i>s0</i>	password
<i>s1</i>	user
<i>s2</i>	snmp client host

Command Mode

- /exec

sync-snmp-password

sync-snmp-password <s0>

Syntax Description

sync-snmp-password	sync snmp password
<i>s0</i>	password

Command Mode

- /exec

sync-snmp-password

[no] sync-snmp-password <*s0*>

Syntax Description

no	(Optional) Negate a command or set its defaults
sync-snmp-password	sync snmp password
<i>s0</i>	password

Command Mode

- /exec/configure

system-mac

system-mac <sysmac> | no system-mac

Syntax Description

no	Negate a command or set its defaults
system-mac	Configure system mac address
<i>sysmac</i>	specify system mac address

Command Mode

- /exec/configure/vpc-domain

system-mac

[no] system-mac <mac-addr>

Syntax Description

no	(Optional) Negate a command or set its defaults
system-mac	Mac Address
<i>mac-addr</i>	specify system mac address

Command Mode

- /exec/configure/if-eth-port-channel/ethernet-segment

system-priority

system-priority <syspri> | no system-priority <syspri>

Syntax Description

no	Negate a command or set its defaults
system-priority	Configure system priority
<i>syspri</i>	specify system priority

Command Mode

- /exec/configure/vpc-domain

system

[no] system { default switchport { mode F | trunk model { auto | off | on } } | delayed-traps { enable mode2 FX | timer <i0> } }

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
switchport	Configure default values for switchport attributes
mode	Enter the port mode
F	F system default port mode
trunk	Configure trunking parameters as a default
model	Configure trunking mode
auto	Autosense trunking
off	Disable trunking
on	Enable trunking
delayed-traps	Configure system delayed trap values
enable	Configure system delayed trap state
mode2	Configure system delayed trap state
FX	Configure system delayed trap state
timer	Configure system delayed trap timeout value
<i>i0</i>	Configure number of minutes

Command Mode

- /exec/configure

system

```
[no] system { { routing { hierarchical def-max-mode l3 64b-alpm | non-hierarchical [ max-mode l3-nh [
64b-alpm-nh ] ] | max-mode host | max-mode-tor { l2 | l3 | l2-l3 } | template-overlay-host-scale |
template-lpm-heavy | template-lpm-scale-v6-64 | template-dual-stack-host-scale | template-service-provider
| template-multicast-heavy | template-multicast-ext-heavy | template-vxlan-scale | template-mpls-heavy |
template-internet-peering | template-multicast-nbm | template-l3-heavy } } | { non-hierarchical-routing [
max-l3-mode ] } } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
routing	Layer-3 routing
hierarchical	Host routing on LC and LPM routing in FM
non-hierarchical	Disable mode of host routing on LC and LPM routing in Fabric modules
non-hierarchical-routing	Disable mode of host routing on LC and LPM routing in Fabric modules
def-max-mode	Maximum scale to be enabled
max-mode	(Optional) Maximum scale to be enabled
max-mode-tor	Maximum scale to be enabled
l2	Max Layer-2 records and fewer Layer-3 host routes
l3	Layer-3 longest-prefix-match (LPM) routes
l2-l3	Balance of both Layer-2 records and Layer-3 host routes
l3-nh	(Optional) Layer-3 longest-prefix-match (LPM) routes
64b-alpm	IPv6 routes with masks /64 or shorter
64b-alpm-nh	(Optional) IPv6 routes with masks /64 or shorter
max-l3-mode	(Optional) Enable ALPM mode (Mode-4 in T2)
host	host routes
template-internet-peering	Internet Peering
template-overlay-host-scale	Overlay Host Scale
template-lpm-heavy	LPM Heavy
template-lpm-scale-v6-64	LPM Scale V6 64
template-dual-stack-host-scale	Dual Stack Host Scale

template-service-provider	Service Provider
template-multicast-heavy	Multicast Heavy Scale
template-multicast-ext-heavy	Multicast Extended Heavy Scale
template-multicast-nbm	Multicast NBM Scale
template-l3-heavy	L3 Heavy Scale profile for Tofino chipset
template-mpls-heavy	MPLS Heavy Scale
template-vxlan-scale	Vxlan Scale

Command Mode

- /exec/configure

system acl

[no] system acl

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System management commands
acl	ACL parameters

Command Mode

- /exec/configure

system auto-collect tech-support

system [no] auto-collect tech-support [timeout <time>]

Syntax Description

system	System management commands
no	(Optional) Negate a command or set its defaults
auto-collect	Auto collection of information
tech-support	Collect tech-support in case of service causing supervisor reset
timeout	(Optional) Collect tech-support timeout
<i>time</i>	(Optional) Timeout in seconds

Command Mode

- /exec

system cores

```
{ system cores { { <uri0> } | { <uri1> vrf <vrf-known-name> } } | no system cores [ { { <uri0> } | { <uri1> vrf <vrf-known-name> } } ] }
```

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
cores	Copy cores to destination
<i>uri0</i>	Select destination filesystem
<i>uri1</i>	Select destination filesystem
vrf	Enter the vrf name
<i>vrf-known-name</i>	VRF name

Command Mode

- /exec/configure

system default interface-vlan autostate

[no] system default interface-vlan autostate

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
interface-vlan	Configure interface-vlan
default	Configure system default values
autostate	Enable or disable autostate for entire system

Command Mode

- /exec/configure

system default interface

```
{ system default interface { congestion { timeout <i0> mode { core | edge } | mode { core | edge } } | pause
{ timeout <i1> mode1 { core | edge } | mode1 { core | edge } } } | no system default interface { congestion {
timeout <i0> mode { core | edge } | mode { core | edge } } | pause { timeout <i1> mode1 { core | edge } |
mode1 { core | edge } } } }
```

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
interface	Configure system default interface values
congestion	Configure system timeout values for congestion drop
pause	Configure system timeout values for pause frame
timeout	Configure system timeout values
<i>i0</i>	Configure number of milliseconds
<i>i1</i>	Configure number of milliseconds
mode	Configure mode
mode1	Configure mode
core	Enter the port type
edge	Enter the port type

Command Mode

- /exec/configure

system default interface

```
{ system default interface { congestion { timeout <i0> mode { core | edge } | mode { core | edge } } | pause
{ timeout <i1> mode1 { core | edge } | mode1 { core | edge } } } | no system default interface { congestion {
timeout <i0> mode { core | edge } | mode { core | edge } } | pause { timeout <i1> mode1 { core | edge } |
mode1 { core | edge } } } }
```

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
interface	Configure system default interface values
congestion	Configure system timeout values for congestion drop
pause	Configure system timeout values for pause frame
timeout	Configure system timeout values
<i>i0</i>	Configure number of milliseconds
<i>i1</i>	Configure number of milliseconds
mode	Configure mode
mode1	Configure mode
core	Enter the port type
edge	Enter the port type

Command Mode

- /exec/configure

system default switchport

{ [no] system default switchport }

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
switchport	Configure switchport

Command Mode

- /exec/configure

system default switchport shutdown

{ [no] system default switchport shutdown }

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
switchport	Configure switchport
shutdown	Configure admin state

Command Mode

- /exec/configure

system default tx-credit double-queue

[no] system default tx-credit double-queue

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
default	Configure system default values
tx-credit	Configure default values for tx credit queue type
double-queue	Configure tx credit queue as double queue

Command Mode

- /exec/configure

system dot1q-tunnel transit

[no] system dot1q-tunnel transit

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
dot1q-tunnel	Dot1Q tunnel
transit	Transit box for multi-tag Ethernet Frames

Command Mode

- /exec/configure

system fabric-mode full-rate

[no] system fabric-mode full-rate

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
fabric-mode	Configure the operating mode of the fabrics
full-rate	Operates fabrics in Full Rate Mode

Command Mode

- /exec/configure

system fabric core-vlans

{ system fabric core-vlans <id> | no system fabric core-vlans }

Syntax Description

no	Negate a command or set its defaults
system	System management commands
fabric	Manage fabric dynamic vlan ranges
core-vlans	Configure the dynamic core vlan range
<i>id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

system fabric dynamic-vlans

{ system fabric dynamic-vlans <id> | no system fabric dynamic-vlans }

Syntax Description

no	Negate a command or set its defaults
system	System management commands
fabric	Manage fabric dynamic vlan ranges
dynamic-vlans	Configure the dynamic server and core vlan range
<i>id</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

system fast-reload stabilization-timer

system fast-reload stabilization-timer <time>

Syntax Description

system	System management commands
fast-reload	fast-reload software
stabilization-timer	Network stabilization time in seconds before fast-reload can be executed after the previous reload
<i>time</i>	time in secs

Command Mode

- /exec/configure

system hap-reset

system hap-reset

Syntax Description

system	System management commands
hap-reset	enables resetting of local or remote sup on ha failures

Command Mode

- /exec

system hap-reset

system no hap-reset

Syntax Description

system	System management commands
no	Negate a command or set its defaults
hap-reset	enables resetting of local or remote sup on ha failures

Command Mode

- /exec

system health check bootflash

system health check bootflash [fix-errors]

Syntax Description

system	System management commands
health	system health exec commands
check	run consistency check on compact flash
bootflash	check internal bootflash
fix-errors	(Optional) fix bootflash errors

Command Mode

- /exec

system heartbeat

system no heartbeat

Syntax Description

system	System management commands
no	Negate a command or set its defaults
heartbeat	enables heartbeat

Command Mode

- /exec

system heartbeat

system heartbeat

Syntax Description

system	System management commands
heartbeat	enables heartbeat

Command Mode

- /exec

system high-multicast-priority

[no] system high-multicast-priority

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
high-multicast-priority	high priority to multicast

Command Mode

- /exec/configure

system inband queuing

```
[no] system inband queuing [ { [ round-robin ] [ bpdw weight <weight-val> ] [ q0 weight <weight-val> ] [ q1 weight <weight-val> ] [ q0 no-drop ] [ q1 no-drop ] [ pick_packets ] [ bpdw map <q-index> ] [ arp map <q-index> ] [ q0 map <q-index> ] [ q1 map <q-index> ] } ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System-related show commands
inband	System Inband configuration
queuing	System Inband Queueing Algorithm
round-robin	(Optional) Simple Round-Robin
bpdw	(Optional) bpdw queue
arp	(Optional) arp queue
q0	(Optional) q0 queue (cos 4,5,6,7)
q1	(Optional) q1 queue (cos 0,1,2,3)
weight	(Optional) weight associated with the queue
no-drop	(Optional) set no drop option on queue
<i>weight-val</i>	(Optional) weights
pick_packets	(Optional) enable packet rx
map	(Optional) map to queue
<i>q-index</i>	(Optional) queue index

Command Mode

- /exec/configure

system inband queuing

system inband queuing { clear-pm-counters | clear-klm-counters | clear-all-counters | enable-timestamp | disable-timestamp }

Syntax Description

system	System-related show commands
inband	System Inband configuration
queuing	System Inband Queueing Algorithm
clear-pm-counters	clear user space inband queue counters
clear-klm-counters	clear KLM VDC inband queue counters
clear-all-counters	clear all inband queue counters
enable-timestamp	enable timestamping in klm vdc
disable-timestamp	disable timestamping in klm vdc

Command Mode

- /exec

system interface shutdown

[no] system interface shutdown [exclude fex-fabric]

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
interface	Configure system interface config
shutdown	Configure interface shutdown
exclude	(Optional) exclude
fex-fabric	(Optional) fex-fabric

Command Mode

- /exec/configure

system jumbomtu

{ system jumbomtu <mtu> | no system jumbomtu [<mtu>] }

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
jumbomtu	Configure system jumbomtu
<i>mtu</i>	Enter jumbomtu

Command Mode

- /exec/configure

system kgdb

system no kgdb

Syntax Description

system	System management commands
no	Negate a command or set its defaults
kgdb	enables kgdb

Command Mode

- /exec

system kgdb

system kgdb

Syntax Description

system	System management commands
kgdb	enables kgdb

Command Mode

- /exec

system login block-for

[no] system login block-for

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
login	Enable secure login checking
block-for	Set quiet-mode active time period

Command Mode

- /exec/configure

system login block-for attempts within

system login block-for <i1> attempts <i2> within <i3>

Syntax Description

system	System configuration commands
login	Enable secure login checking
block-for	Set quiet-mode active time period
<i>i1</i>	Time period in seconds
attempts	Set max number of fail attempts
<i>i2</i>	Fail attempts max value
within	Watch period for fail attempts
<i>i3</i>	Time period in seconds

Command Mode

- /exec/configure

system login quiet-mode

[no] system login quiet-mode

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
login	Enable secure login checking
quiet-mode	Set quiet-mode options

Command Mode

- /exec/configure

system login quiet-mode access-class

system login quiet-mode access-class <access-list>

Syntax Description

system	System configuration commands
login	Enable secure login checking
quiet-mode	Set quiet-mode options
access-class	Set access class
<i>access-list</i>	Access-list name

Command Mode

- /exec/configure

system memory-thresholds minor severe critical

[no] system memory-thresholds minor <minor> severe <severe> critical <crit>

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
memory-thresholds	Set memory thresholds on the card
minor	enter minor threshold
<i>minor</i>	please enter minor memory threshold as % memory
severe	enter severe treshold
<i>severe</i>	please enter severe memory threshold as % memory
critical	enter critical treshold
<i>crit</i>	please enter critical memory threshold as % memory

Command Mode

- /exec/configure

system mode maintenance

[no] system mode maintenance [dont-generate-profile] [non-interactive] | system mode maintenance [dont-generate-profile | shutdown] [non-interactive]

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
dont-generate-profile	(Optional) do not generate the maintenance/normal-mode profile
shutdown	(Optional) issue shutdown instead of isolate (default)
non-interactive	(Optional) do operation non interactively in background

Command Mode

- /exec/configure

system mode maintenance always-use-custom-profile

[no] system mode maintenance always-use-custom-profile

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
always-use-custom-profile	always use custom profile when entering maintenance mode

Command Mode

- /exec/configure

system mode maintenance maint-delay

[no] system mode maintenance maint-delay <delay-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
maint-delay	delay to allow protocol reroute before releasing CLI
<i>delay-value</i>	delay value in seconds

Command Mode

- /exec/configure

system mode maintenance on-reload reset-reason

[no] system mode maintenance on-reload reset-reason <reason>

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
on-reload	on reload maintenance mode configuration
reset-reason	reset reason
<i>reason</i>	

Command Mode

- /exec/configure

system mode maintenance snapshot-delay

[no] system mode maintenance snapshot-delay <delay-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
snapshot-delay	delay after which after_maintenance snapshot will be taken
<i>delay-value</i>	delay value in seconds

Command Mode

- /exec/configure

system mode maintenance timeout

[no] system mode maintenance timeout <timer-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System configuration commands
mode	system mode commands
maintenance	system maintenance mode
timeout	restart maintenance mode timer with a new value
<i>timer-value</i>	timer value in minutes

Command Mode

- /exec/configure

system module emon-enhanced

[no] system module emon-enhanced

Syntax Description

no	(Optional) Negate a command or set its defaults
system	system Internal Information
module	module commands
emon-enhanced	Configure emon enhanced support

Command Mode

- /exec/configure

system module failure-action shutdown

[no] system module failure-action shutdown

Syntax Description

no	(Optional) Negate a command or set its defaults
system	system Internal Information
module	module commands
failure-action	Configure module action on failure
shutdown	action on failure - shutdown

Command Mode

- /exec/configure

system mrouting

[no] system mrouting [performance-mode | disable-2nd-update | disable-l2-update]

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
mrouting	Layer-3 mrouting
performance-mode	(Optional) Multicast Performance Mode
disable-2nd-update	(Optional) Disable 2nd route update
disable-l2-update	(Optional) Disable l2 route update

Command Mode

- /exec/configure

system poap

system poap

Syntax Description

system	System management commands
poap	Re-enable POAP on every write erase+reload

Command Mode

- /exec

system poap

system no poap

Syntax Description

system	System management commands
no	Negate a command or set its defaults
poap	This will set a boot flag, that will allow disabling POAP permanently even when the system starts with no configuration

Command Mode

- /exec

system pss shrink

system pss shrink

Syntax Description

system	System management commands
pss	PSS commands
shrink	shrink pss files

Command Mode

- /exec

system qos

system qos

Syntax Description

system	System management commands
qos	QoS parameters

Command Mode

- /exec/configure

system routing unknown-unicast-flood

[no] system routing unknown-unicast-flood

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
routing	Layer-3 routing
unknown-unicast-flood	Hardware flood post-routed traffic on SVI if dest-mac->layer2-port binding unknown

Command Mode

- /exec/configure

system security compliance common-criteria

[no] system security compliance common-criteria

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management commands
security	Security Management commands
compliance	Compliant with the mode configured
common-criteria	Enable/Disable common-criteria mode

Command Mode

- /exec/configure

system shutdown fan-direction mismatch

system shutdown fan-direction mismatch | no system shutdown fan-direction mismatch

Syntax Description

no	Negate a command or set its defaults
system	System management commands
shutdown	Shutdown management commands
fan-direction	Fan-direction check
mismatch	Mismatch in check

Command Mode

- /exec/configure

system simulate fan-presence

system simulate fan-presence | no system simulate fan-presence

Syntax Description

no	Negate a command or set its defaults
system	System management commands
simulate	Simulate Fan Presence
fan-presence	Simulate Fan Presence

Command Mode

- /exec/configure

system standby manual-boot

system standby manual-boot

Syntax Description

system	System management commands
standby	System standby management commands
manual-boot	No action taken to force-download standby sup

Command Mode

- /exec

system standby manual-boot

system no standby manual-boot

Syntax Description

system	System management commands
no	Negate a command or set its defaults
standby	System standby manual boot
manual-boot	No action taken to force-download standby sup

Command Mode

- /exec

system startup-config init

system startup-config init

Syntax Description

system	System management commands
startup-config	System startup-config commands
init	Initialize the startup-configuration

Command Mode

- /exec

system startup-config unlock

system startup-config unlock <i0>

Syntax Description

system	System management commands
startup-config	System startup-config commands
unlock	Unlock startup-config
<i>i0</i>	Startup-config lock id

Command Mode

- /exec

system statistics

system statistics

Syntax Description

system	System management commands
statistics	enables sysmgr statistics

Command Mode

- /exec

system statistics

system no statistics

Syntax Description

system	System management commands
no	Negate a command or set its defaults
statistics	disable the sysmgr statistics

Command Mode

- /exec

system switch-mode

```
system switch-mode { <mode> }
```

Syntax Description

system	System management commands
switch-mode	change switch operational mode
<i>mode</i>	switch mode

Command Mode

- /exec/configure

system switchover

system switchover

Syntax Description

system	System management commands
switchover	Switch over to the standby supervisor

Command Mode

- /exec

system switchover force

system switchover force

Syntax Description

system	System management commands
switchover	Switch over to the standby supervisor
force	Force switch over to the standby supervisor

Command Mode

- /exec

system timeout

```
{ system timeout { congestion-drop { <i0> mode <port_mode> | default mode <port_mode> } | no-credit-drop
{ <i1> mode1 <port_mode1> | default mode1 <port_mode1> } } | no system timeout no-credit-drop mode1
<port_mode1> }
```

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
timeout	Configure system timeout values
congestion-drop	Configure system timeout values for congestion drop
<i>i0</i>	Configure number of milliseconds
default	Default timeout value for congestion-drop
mode	Enter the port mode
<i>port_mode</i>	Port mode
no-credit-drop	Configure system timeout values for no credit drop
<i>il</i>	Configure number of milliseconds
default	Default timeout value for no-credit-drop
mode1	Enter the port mode
<i>port_mode1</i>	Port mode

Command Mode

- /exec/configure

system trace

{ system trace <i0> | no system trace [<i0>] }

Syntax Description

no	Negate a command or set its defaults
system	System configuration commands
trace	To configure system trace level
<i>i0</i>	Select the mask

Command Mode

- /exec/configure

system urpf disable

[no] system urpf disable

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System Management Commands
urpf	Manage urpf enable/disable
disable	disable

Command Mode

- /exec/configure

system vlan long-name

[no] system vlan long-name

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System management commands
vlan	Vlan commands
long-name	Configure 128 character VLAN names

Command Mode

- /exec/configure

system vlan reserve

system vlan <start-val> reserve | no system vlan <start-val> reserve

Syntax Description

system	system wide configuration
no	Select default reserved vlans group vlan 3968-4094
vlan	Vlan commands
<i>start-val</i>	minimum VLANs value
reserve	reservation

Command Mode

- /exec/configure

system vrf-member-change retain-l3-config

[no] system vrf-member-change retain-l3-config

Syntax Description

no	(Optional) Negate a command or set its defaults
system	System management commands
vrf-member-change	vrf member change
retain-l3-config	retain L3 configuration

Command Mode

- /exec/configure

system watchdog

system no watchdog

Syntax Description

system	System management commands
no	Negate a command or set its defaults
watchdog	enables watchdog

Command Mode

- /exec

system watchdog

system watchdog

Syntax Description

system	System management commands
watchdog	enables watchdog

Command Mode

- /exec

system watchdog kgdb

system no watchdog kgdb

Syntax Description

system	System management commands
no	Negate a command or set its defaults
watchdog	enables watchdog
kgdb	enter kgdb on watchdog failure

Command Mode

- /exec

system watchdog kgdb

system watchdog kgdb

Syntax Description

system	System management commands
watchdog	enables watchdog
kgdb	enter kgdb on watchdog failure

Command Mode

- /exec



T Commands

- [table-map](#), on page 4496
- [table-map](#), on page 4497
- [table-map](#), on page 4498
- [table-map](#), on page 4499
- [table-map](#), on page 4500
- [table-map](#), on page 4501
- [table-map](#), on page 4502
- [table-map](#), on page 4503
- [tac-pac](#), on page 4504
- [tac-pac](#), on page 4505
- [tacacs-server deadtime](#), on page 4506
- [tacacs-server directed-request](#), on page 4507
- [tacacs-server host key 0 6 7](#), on page 4508
- [tacacs-server host test](#), on page 4509
- [tacacs-server key 0 6 7](#), on page 4510
- [tacacs-server test](#), on page 4511
- [tacacs-server timeout](#), on page 4512
- [tacacs enable](#), on page 4513
- [tag](#), on page 4514
- [tag happens in](#), on page 4515
- [tahoe-python module](#), on page 4516
- [tahoe-python module quoted](#), on page 4517
- [tail](#), on page 4518
- [tail](#), on page 4519
- [tar](#), on page 4520
- [tclsh](#), on page 4521
- [tclsh](#), on page 4522
- [tcp-connect](#), on page 4523
- [telnet](#), on page 4524
- [telnet6](#), on page 4525
- [telnet login-attempts](#), on page 4526
- [telnet server enable](#), on page 4527
- [template](#), on page 4528

- [template data timeout](#), on page 4529
- [template peer-policy](#), on page 4530
- [template peer-session](#), on page 4531
- [template peer](#), on page 4532
- [terminal](#), on page 4533
- [terminal alias](#), on page 4534
- [terminal ask-on-term](#), on page 4535
- [terminal color](#), on page 4536
- [terminal context management](#), on page 4537
- [terminal deep-help](#), on page 4538
- [terminal dont-ask](#), on page 4539
- [terminal edit-mode vi](#), on page 4540
- [terminal event-manager bypass](#), on page 4541
- [terminal history no-exec-in-config](#), on page 4542
- [terminal history no-exec-in-config](#), on page 4543
- [terminal history no-exec-in-config](#), on page 4544
- [terminal home](#), on page 4545
- [terminal length](#), on page 4546
- [terminal length](#), on page 4547
- [terminal log-all](#), on page 4548
- [terminal no](#), on page 4549
- [terminal output xml](#), on page 4550
- [terminal output xml](#), on page 4551
- [terminal output xml](#), on page 4552
- [terminal password](#), on page 4553
- [terminal prompt](#), on page 4554
- [terminal redirection-mode](#), on page 4555
- [terminal session-timeout](#), on page 4556
- [terminal sticky-mode](#), on page 4557
- [terminal terminal-type](#), on page 4558
- [terminal time](#), on page 4559
- [terminal tree-update](#), on page 4560
- [terminal verify-only](#), on page 4561
- [terminal width](#), on page 4562
- [terminal width](#), on page 4563
- [threshold-percent](#), on page 4564
- [threshold](#), on page 4565
- [time-range](#), on page 4566
- [timeout](#), on page 4567
- [timeout](#), on page 4568
- [timeout](#), on page 4569
- [timer](#), on page 4570
- [timer](#), on page 4571
- [timer inactivity](#), on page 4572
- [timers](#), on page 4573
- [timers](#), on page 4574

- [timers](#), on page 4575
- [timers advertise](#), on page 4576
- [timers basic](#), on page 4577
- [timers bestpath-defer maximum](#), on page 4578
- [timers bestpath-limit](#), on page 4579
- [timers bgp](#), on page 4580
- [timers lsa-arrival](#), on page 4581
- [timers lsa-arrival](#), on page 4582
- [timers lsa-group-pacing](#), on page 4583
- [timers lsa-group-pacing](#), on page 4584
- [timers prefix-peer-timeout](#), on page 4585
- [timers prefix-peer-wait](#), on page 4586
- [timers srgb cleanup](#), on page 4587
- [timers srgb retry](#), on page 4588
- [timers throttle lsa](#), on page 4589
- [timers throttle lsa](#), on page 4590
- [timers throttle spf](#), on page 4591
- [timers throttle spf](#), on page 4592
- [timestamp timestamp](#), on page 4593
- [tls trust-point local remote](#), on page 4594
- [tls trust-point local remote](#), on page 4595
- [topology](#), on page 4596
- [topology holddown sigerr](#), on page 4597
- [tos](#), on page 4598
- [tr](#), on page 4599
- [trace buffer size](#), on page 4600
- [traceroute](#), on page 4601
- [traceroute6](#), on page 4602
- [track-adjacency-nexthop](#), on page 4603
- [track](#), on page 4604
- [track](#), on page 4605
- [track](#), on page 4606
- [track](#), on page 4607
- [track](#), on page 4608
- [track](#), on page 4609
- [track](#), on page 4610
- [track](#), on page 4611
- [track](#), on page 4612
- [track](#), on page 4613
- [track data](#), on page 4614
- [track interface](#), on page 4615
- [track interface priority](#), on page 4616
- [track running-state track startup-state](#), on page 4617
- [tracking enable](#), on page 4618
- [traffic-class](#), on page 4619
- [traffic-engineering](#), on page 4620

- transmit-delay, on page 4621
- transmit-delay, on page 4622
- transmit-delay, on page 4623
- transport connection-mode passive, on page 4624
- transport email, on page 4625
- transport email mail-server, on page 4626
- transport http proxy enable, on page 4627
- transport http proxy server, on page 4628
- transport http use-vrf, on page 4629
- transport udp, on page 4630
- transport udp, on page 4631
- transport udp, on page 4632
- transport udp source-port, on page 4633
- trigger forwarding distribution module, on page 4634
- trigger init, on page 4635
- trigger init in-select 10, on page 4636
- trigger init in-select 10 out-select 0, on page 4637
- trigger init in-select 10 out-select 1, on page 4638
- trigger init in-select 10 out-select 2, on page 4639
- trigger init in-select 19, on page 4640
- trigger init in-select 19 out-select 0, on page 4641
- trigger init in-select 19 out-select 1, on page 4642
- trigger init in-select 19 out-select 2, on page 4643
- trigger init in-select 6, on page 4644
- trigger init in-select 6 out-select 0, on page 4645
- trigger init in-select 6 out-select 1, on page 4646
- trigger init in-select 6 out-select 2, on page 4647
- trigger init in-select 7, on page 4648
- trigger init in-select 7 out-select 0, on page 4649
- trigger init in-select 7 out-select 1, on page 4650
- trigger init in-select 7 out-select 2, on page 4651
- trigger init in-select 8, on page 4652
- trigger init in-select 8 out-select 0, on page 4653
- trigger init in-select 8 out-select 1, on page 4654
- trigger init in-select 8 out-select 2, on page 4655
- trigger init in-select 9, on page 4656
- trigger init in-select 9 out-select 0, on page 4657
- trigger init in-select 9 out-select 1, on page 4658
- trigger init in-select 9 out-select 2, on page 4659
- trigger init ingress in-select 3 out-select 0, on page 4660
- trigger init ingress in-select 3 out-select 03, on page 4661
- trigger init ingress in-select 3 out-select 0 reverse, on page 4662
- trigger init ingress in-select 3 out-select 1, on page 4663
- trigger init ingress in-select 3 out-select 2, on page 4664
- trigger init ingress in-select 3 out-select 4, on page 4665
- trigger init ingress in-select 3 out-select 5, on page 4666

- [trigger init ingress in-select 3 out-select 5 reverse](#), on page 4667
- [trigger init ingress in-select 4 out-select 0](#), on page 4668
- [trigger init ingress in-select 4 out-select 04](#), on page 4669
- [trigger init ingress in-select 4 out-select 0 reverse](#), on page 4670
- [trigger init ingress in-select 4 out-select 1](#), on page 4671
- [trigger init ingress in-select 4 out-select 2](#), on page 4672
- [trigger init ingress in-select 4 out-select 3](#), on page 4673
- [trigger init ingress in-select 4 out-select 5](#), on page 4674
- [trigger init ingress in-select 4 out-select 5 reverse](#), on page 4675
- [trigger init ingress in-select 5 out-select 0](#), on page 4676
- [trigger init ingress in-select 5 out-select 05](#), on page 4677
- [trigger init ingress in-select 5 out-select 05 reverse](#), on page 4678
- [trigger init ingress in-select 5 out-select 0 reverse](#), on page 4679
- [trigger init ingress in-select 5 out-select 1](#), on page 4680
- [trigger init ingress in-select 5 out-select 2](#), on page 4681
- [trigger init ingress in-select 5 out-select 3](#), on page 4682
- [trigger init ingress in-select 5 out-select 4](#), on page 4683
- [trigger init ingress in-select 6 out-select 0](#), on page 4684
- [trigger init ingress in-select 6 out-select 0 reverse](#), on page 4685
- [trigger init ingress in-select 6 out-select 1](#), on page 4686
- [trigger init ingress in-select 6 out-select 2](#), on page 4687
- [trigger init ingress in-select 6 out-select 3](#), on page 4688
- [trigger init ingress in-select 6 out-select 4](#), on page 4689
- [trigger init ingress in-select 6 out-select 5](#), on page 4690
- [trigger init ingress in-select 6 out-select 5 reverse](#), on page 4691
- [trigger init ingress in-select 7 out-select 0](#), on page 4692
- [trigger init ingress in-select 7 out-select 0 reverse](#), on page 4693
- [trigger init ingress in-select 7 out-select 1](#), on page 4694
- [trigger init ingress in-select 7 out-select 2](#), on page 4695
- [trigger init ingress in-select 7 out-select 3](#), on page 4696
- [trigger init ingress in-select 7 out-select 4](#), on page 4697
- [trigger init ingress in-select 7 out-select 5](#), on page 4698
- [trigger init ingress in-select 7 out-select 5 reverse](#), on page 4699
- [trigger init lu-a2d 0](#), on page 4700
- [trigger init lu-a2d 0 in-select 10 out-select 0](#), on page 4701
- [trigger init lu-a2d 0 in-select 10 out-select 1](#), on page 4702
- [trigger init lu-a2d 0 in-select 10 out-select 2](#), on page 4703
- [trigger init lu-a2d 0 in-select 19 out-select 0](#), on page 4704
- [trigger init lu-a2d 0 in-select 19 out-select 1](#), on page 4705
- [trigger init lu-a2d 0 in-select 19 out-select 2](#), on page 4706
- [trigger init lu-a2d 0 in-select 6 out-select 0](#), on page 4707
- [trigger init lu-a2d 0 in-select 6 out-select 1](#), on page 4708
- [trigger init lu-a2d 0 in-select 6 out-select 2](#), on page 4709
- [trigger init lu-a2d 0 in-select 7 out-select 0](#), on page 4710
- [trigger init lu-a2d 0 in-select 7 out-select 1](#), on page 4711
- [trigger init lu-a2d 0 in-select 7 out-select 2](#), on page 4712

- [trigger init lu-a2d 0 in-select 8 out-select 0](#), on page 4713
- [trigger init lu-a2d 0 in-select 8 out-select 1](#), on page 4714
- [trigger init lu-a2d 0 in-select 8 out-select 2](#), on page 4715
- [trigger init lu-a2d 0 in-select 9 out-select 0](#), on page 4716
- [trigger init lu-a2d 0 in-select 9 out-select 1](#), on page 4717
- [trigger init lu-a2d 0 in-select 9 out-select 2](#), on page 4718
- [trigger init lu-a2d 0 out-select 0](#), on page 4719
- [trigger init lu-a2d 0 out-select 1](#), on page 4720
- [trigger init lu-a2d 0 out-select 2](#), on page 4721
- [trigger init lu-a2d 1](#), on page 4722
- [trigger init lu-a2d 1 in-select 10](#), on page 4723
- [trigger init lu-a2d 1 in-select 10 out-select 0](#), on page 4724
- [trigger init lu-a2d 1 in-select 10 out-select 1](#), on page 4725
- [trigger init lu-a2d 1 in-select 10 out-select 2](#), on page 4726
- [trigger init lu-a2d 1 in-select 19](#), on page 4727
- [trigger init lu-a2d 1 in-select 19 out-select 0](#), on page 4728
- [trigger init lu-a2d 1 in-select 19 out-select 1](#), on page 4729
- [trigger init lu-a2d 1 in-select 19 out-select 2](#), on page 4730
- [trigger init lu-a2d 1 in-select 6](#), on page 4731
- [trigger init lu-a2d 1 in-select 6 out-select 0](#), on page 4732
- [trigger init lu-a2d 1 in-select 6 out-select 1](#), on page 4733
- [trigger init lu-a2d 1 in-select 6 out-select 2](#), on page 4734
- [trigger init lu-a2d 1 in-select 7](#), on page 4735
- [trigger init lu-a2d 1 in-select 7 out-select 0](#), on page 4736
- [trigger init lu-a2d 1 in-select 7 out-select 1](#), on page 4737
- [trigger init lu-a2d 1 in-select 7 out-select 2](#), on page 4738
- [trigger init lu-a2d 1 in-select 8](#), on page 4739
- [trigger init lu-a2d 1 in-select 8 out-select 0](#), on page 4740
- [trigger init lu-a2d 1 in-select 8 out-select 1](#), on page 4741
- [trigger init lu-a2d 1 in-select 8 out-select 2](#), on page 4742
- [trigger init lu-a2d 1 in-select 9](#), on page 4743
- [trigger init lu-a2d 1 in-select 9 out-select 0](#), on page 4744
- [trigger init lu-a2d 1 in-select 9 out-select 1](#), on page 4745
- [trigger init lu-a2d 1 in-select 9 out-select 2](#), on page 4746
- [trigger init out-select 0](#), on page 4747
- [trigger init out-select 1](#), on page 4748
- [trigger init out-select 2](#), on page 4749
- [trigger reset](#), on page 4750
- [trigger route download vrf ipv4](#), on page 4751
- [trunk protocol](#), on page 4752
- [trusted-port](#), on page 4753
- [trusted-port](#), on page 4754
- [trusted-port](#), on page 4755
- [ttag-marker-interval](#), on page 4756
- [ttag-marker-interval](#), on page 4757
- [ttag-marker enable](#), on page 4758

- [ttag-marker enable](#), on page 4759
- [ttag-strip](#), on page 4760
- [ttag](#), on page 4761
- [ttag](#), on page 4762
- [ttl-security hops](#), on page 4763
- [tunnel destination](#), on page 4764
- [tunnel mode](#), on page 4765
- [tunnel path-mtu-discovery](#), on page 4766
- [tunnel path-mtu-discovery age-timer](#), on page 4767
- [tunnel path-mtu-discovery min-mtu](#), on page 4768
- [tunnel source](#), on page 4769
- [tunnel ttl](#), on page 4770
- [tunnel use-vrf](#), on page 4771

table-map

[no] table-map <policy-name> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Policy for filtering/modifying OSPFV3 routes before sending them to RIB
<i>policy-name</i>	Route-map name
filter	(Optional) To block the OSPFV3 routes from being sent to RIB

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

table-map

[no] table-map <table-map-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Configure a table map
<i>table-map-name</i>	Table map name

Command Mode

- /exec/configure

table-map

table-map <default-tmap-enum-name>

Syntax Description

table-map	Configure a table map
<i>default-tmap-enum-name</i>	

Command Mode

- /exec/configure

table-map

[no] table-map <policy-name> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Table-map policy used to filter routes and tune attributes before downloading to RIB
filter	(Optional) Filter the routes based on policy results
<i>policy-name</i>	A 'routing-rules' route-map name

Command Mode

- /exec/configure/router-isis/router-isis-vrf-common /exec/configure/router-isis/router-isis-af-ipv4

table-map

[no] table-map <policy-name> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Table-map policy used to filter routes and tune attributes before downloading to RIB
filter	(Optional) Filter the routes based on policy results
<i>policy-name</i>	A 'routing-rules' route-map name

Command Mode

- /exec/configure/router-isis/router-isis-af-ipv6

table-map

[no] table-map <map> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Configure Table Map information
<i>map</i>	Route-map name
filter	(Optional) Filter routes which are rejected by route-map

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

table-map

[no] table-map <policy-name> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Policy for filtering/modifying OSPF routes before sending them to RIB
<i>policy-name</i>	Route-map name
filter	(Optional) To block the OSPF routes from being sent to RIB

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

table-map

[no] table-map <rmap-name> [filter]

Syntax Description

no	(Optional) Negate a command or set its defaults
table-map	Apply table-map to filter routes downloaded into URIB
<i>rmap-name</i>	Route-map name
filter	(Optional) Selective route download

Command Mode

- /exec/configure/router-bgp/router-bgp-af

tac-pac

```
tac-pac [ <uri0> [ vrf <vrf-known-name> ] ]
```

Syntax Description

<code>tac-pac</code>	save tac info in a compressed .gz file at specific location
<code>uri0</code>	(Optional) Select destination filesystem
<code>vrf</code>	(Optional) Display per-VRF information
<code>vrf-known-name</code>	(Optional) Known VRF name

Command Mode

- /exec

tac-pac

tac-pac [<uri0>]

Syntax Description

tac-pac	save tac info in a compressed .gz file at specific location
<i>uri0</i>	(Optional) Select destination filesystem

Command Mode

- /exec

tacacs-server deadtime

[no] tacacs-server deadtime <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
deadtime	duration for which non-reachable server is skipped
<i>i0</i>	Length of time, in minutes

Command Mode

- /exec/configure

tacacs-server directed-request

[no] tacacs-server directed-request

Syntax Description

no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
directed-request	enable direct authentication requests to server

Command Mode

- /exec/configure

tacacs-server host key 0 6 7

```
{ { [ no ] tacacs-server host { <hostipname> } { { key { 0 <s0> | 6 <s6> | 7 <s1> | <s2> } [ port <i1> ] [
timeout <i2> ] [ single-connection ] } | { [ port1 <i3> ] [ timeout1 <i4> ] [ single-connection ] } | { [
single-connection ] } } } | { no tacacs-server host <hostipname> key } }
```

Syntax Description

<i>key</i>	0
no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
host	TACACS+ server's DNS name or its IP address
<i>hostipname</i>	IPV4/IPV6 address or DNS name
key	TACACS+ shared secret
0	TACACS+ shared secret(clear text)
<i>s0</i>	TACACS+ shared secret(clear text)
port	(Optional) TACACS+ server port
<i>i1</i>	(Optional) TACACS+ server port
timeout	(Optional) TACACS+ server timeout period in seconds
<i>i2</i>	(Optional) TACACS+ server timeout period in seconds
single-connection	(Optional) Use single connection for this Tacacs+ server
6	TACACS+ shared secret(type-6 encrypted)
<i>s6</i>	TACACS+ shared secret(encrypted)
7	TACACS+ shared secret(encrypted)
<i>s1</i>	TACACS+ shared secret(encrypted)
port1	(Optional) TACACS+ server port
<i>i3</i>	(Optional) TACACS+ server port
timeout1	(Optional) TACACS+ server timeout period in seconds
<i>i4</i>	(Optional) TACACS+ server timeout period in seconds
<i>s2</i>	TACACS+ shared secret(clear text)

Command Mode

- /exec/configure

tacacs-server host test

```
[no] tacacs-server host <hostipnam> test { { username <s0> { [ password <s1> [ idle-time <i1> ] ] [ idle-time <i1> ] } } | { password <s1> [ idle-time <i1> ] } | { idle-time <i1> } }
```

Syntax Description

<i>username</i>	<s0>
no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
host	TACACS+ server's DNS name or its IP address
<i>hostipnam</i>	IPV4/IPV6 address or DNS name
test	Parameters to send test packets
<i>s0</i>	user name
password	(Optional) user password in test packets
<i>s1</i>	(Optional) user password
idle-time	(Optional) time interval for monitoring the server
<i>i1</i>	(Optional) time period in minutes

Command Mode

- /exec/configure

tacacs-server key 0 6 7

```
{ { [ no ] tacacs-server key { 0 <s0> [ timeout <i0> ] | 6 <s6> [ timeout6 <i6> ] | 7 <s1> [ timeout1 <i1> ] | <s2> [ timeout2 <i2> ] } } } | { no tacacs-server key } }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
key	Global TACACS+ server shared secret
0	default TACACS+ shared secret(clear text)
<i>s0</i>	default TACACS+ shared secret(clear text)
timeout	(Optional) Global TACACS+ server timeout period in seconds
<i>i0</i>	(Optional) Global TACACS+ server timeout period in seconds
6	default TACACS+ shared secret(type-6 encrypted)
<i>s6</i>	default TACACS+ shared secret(type-6 encrypted)
timeout6	(Optional) Global TACACS+ server timeout period in seconds
<i>i6</i>	(Optional) Global TACACS+ server timeout period in seconds
7	default TACACS+ shared secret(encrypted)
<i>s1</i>	default TACACS+ shared secret(encrypted)
timeout1	(Optional) Global TACACS+ server timeout period in seconds
<i>i1</i>	(Optional) Global TACACS+ server timeout period in seconds
<i>s2</i>	default TACACS+ shared secret(clear text)
timeout2	(Optional) Global TACACS+ server timeout period in seconds
<i>i2</i>	(Optional) Global TACACS+ server timeout period in seconds

Command Mode

- /exec/configure

tacacs-server test

```
[no] tacacs-server test { { username <s0> { [ password <s1> [ idle-time <i1> ] ] | [ idle-time <i1> ] } } | { password <s1> [ idle-time <i1> ] } | { idle-time <i1> } }
```

Syntax Description

<i>username</i>	<s0>
no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
test	Parameters to send test packets
<i>s0</i>	user name
password	(Optional) user password in test packets
<i>s1</i>	(Optional) user password
idle-time	(Optional) time interval for monitoring the server
<i>i1</i>	(Optional) time period in minutes

Command Mode

- /exec/configure

tacacs-server timeout

[no] tacacs-server timeout <i0>

Syntax Description

no	(Optional) Negate a command or set its defaults
tacacs-server	Configure TACACS+ server related parameters
timeout	Global TACACS+ server timeout period in seconds
<i>i0</i>	Global TACACS+ server timeout period in seconds

Command Mode

- /exec/configure

tacacs enable

[no] tacacs + enable

Syntax Description

no	(Optional) Negate a command or set its defaults
enable	Enable tacacs+

Command Mode

- /exec/configure

tag

```
{ { no | default } tag | tag <text> }
```

Syntax Description

no	
default	Set a command to its defaults
tag	User defined tag
<i>text</i>	Tag string line

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http

tag happens in

```
[no] tag <tag_id> <op> <tag_id> [ <op> <tag_id> [ <op> <tag_id> ] ] happens <threshold> in <interval> |
no tag
```

Syntax Description

no	(Optional) Negate a command or set its defaults
tag	event tag identifier
<i>tag_id</i>	tag name
<i>op</i>	boolean operator
happens	The number of occurrences before raising the event
<i>threshold</i>	Occurs value
in	Number of occurrences must occur within this time period
<i>interval</i>	Enter seconds value

Command Mode

- /exec/configure/event-manager-applet

tahoe-python module

tahoe-python module <module>

Syntax Description

tahoe-python	enter python mode for tahoe systems
module	Module number of the linecard
<i>module</i>	Enter module number

Command Mode

- /exec

tahoe-python module quoted

tahoe-python module <module> quoted <quoted-cmd>

Syntax Description

tahoe-python	enter python mode for tahoe systems
module	Module number of the linecard
<i>module</i>	Enter module number
quoted	enter the command with quotes Add multiple commands separated by semi-colon
<i>quoted-cmd</i>	the command(s) to run in tahoe python

Command Mode

- /exec

tail

tail <uri0> [<i1>]

Syntax Description

tail	Display the last part of a file
<i>uri0</i>	Filename to be displayed
<i>i1</i>	(Optional) Enter the number of lines to be displayed

Command Mode

- /exec

tail

| tail [-n <lines>]

Syntax Description

	Pipe command output to filter
tail	Display last lines
-n	(Optional) modify number of lines (default 10)
<i>lines</i>	(Optional) number of lines to print

Command Mode

- /output

tar

```
tar { create <new-archive-file> [ gz-compress | bz2-compress | uncompressed ] + [ remove | absolute | verbose ] + <files> + | append <archive-file> [ remove | absolute | verbose ] + <files> + | extract <archive-file> [ screen | to <dest-dir> | keep-old | verbose ] + | list <archive-file> }
```

Syntax Description

tar	archiving operations
create	create an archive (merge several files together)
append	append some files to an existing archive
extract	extract files from archive (unmerge them)
verbose	(Optional) display files while merging/extracting
gz-compress	(Optional) compress archive with gzip, the default -> .tar.gz
bz2-compress	(Optional) compress archive with bzip2 -> .tar.bz2
uncompressed	(Optional) dont compress archive -> .tar
remove	(Optional) remove files after adding them to the archive
absolute	(Optional) don't strip leading '/'s from file names
keep-old	(Optional) don't replace existing files when extracting
screen	(Optional) extract files to screen
list	shows the list of files which are part of the archive
<i>new-archive-file</i>	the name of the archive (extension will be added if none of tar/tgz/tar.gz/tar.bz2/tbz2/tar.Z specified)
<i>archive-file</i>	the name of the archive (extension will be added if none of tar/tgz/tar.gz/tar.bz2/tbz2/tar.Z specified)
<i>files</i>	name of file to be added into archive
to	(Optional) extract to specific directory (default is bootflash)
<i>dest-dir</i>	(Optional) destination dir where to extract to (created if not exist), default is bootflash

Command Mode

- /exec

tclsh

tclsh

Syntax Description

tclsh	Execute tclsh
-------	---------------

Command Mode

- /exec

tclsh

tclsh <file> [<args>] +

Syntax Description

tclsh	source tclsh script
<i>file</i>	the file to run
<i>args</i>	(Optional) args to tcl script

Command Mode

- /exec

tcp-connect

```
[no] tcp-connect { <hostname> | <ip-address> | <ipv6-address> } <dest-port> { [ control { disable | enable } ] [ source-ip { <source-ip-hostname> | <source-ip-address> | <source-ipv6-address> } ] [ source-port <src-port> ] } +
```

Syntax Description

no	(Optional)
<i>control</i>	(Optional) enable
<i>source-ip-address</i>	(Optional) <source-ipv6-address>
tcp-connect	TCP Connect Operation
<i>hostname</i>	Destination hostname, broadcast disallowed
<i>ip-address</i>	Destination IP address, broadcast disallowed
<i>dest-port</i>	Port Number (Recommended port range between 1025-65534)
enable	(Optional) Enable control packets exchange (default)
disable	(Optional) Disable control packets exchange
source-ip	(Optional) Source address
<i>source-ip-hostname</i>	(Optional) source IP hostname, broadcast disallowed
source-port	(Optional) Source Port
<i>src-port</i>	(Optional) Port Number (Recommended port range between 1025-65534)

Command Mode

- /exec/configure/ip-sla

telnet

```
{ telnet { <so> | <host> } } [ <i0> ] [ [ source { <host_src> | <interface> } ] [ vrf { <vrf-name> | <vrf-known-name> } ] ]
```

Syntax Description

telnet	Telnet to another system
<i>so</i>	Enter hostname
<i>host</i>	Enter a valid IPv4 address
source	(Optional) Set source address in IPv4 header
<i>host_src</i>	(Optional) Set IPV4 address as source
<i>interface</i>	(Optional) Set interface to send IPv4 packet
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>i0</i>	(Optional) Enter the port number

Command Mode

- /exec

telnet6

```
{ telnet6 { <s1> | <host1> } } [ <i0> ] [ [ source { <host1_src> | <interface> } ] [ vrf { <vrf-name> | <vrf-known-name> } ] ]
```

Syntax Description

telnet6	Telnet6 to another system using IPv6 addressing
<i>s1</i>	Enter hostname
source	(Optional) Set source address in IPv6 header
<i>interface</i>	(Optional) Set interface to send IPv6 packet
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>i0</i>	(Optional) Enter the port number

Command Mode

- /exec

telnet login-attempts

```
{ { telnet login-attempts <d0> } | { no telnet login-attempts [ <d0> ] } }
```

Syntax Description

no	Negate a command or set its defaults
telnet	telnet login
login-attempts	Set maximum login attempts
<i>d0</i>	Specify max-attempt number

Command Mode

- /exec/configure/

telnet server enable

[no] telnet server enable

Syntax Description

no	(Optional) Negate a command or set its defaults
telnet	Enable telnet
server	Enable telnet
enable	Enable telnet

Command Mode

- /exec/configure

template

template <res-mgr-template-known-name-all>

Syntax Description

template	Change the template for this vdc
<i>res-mgr-template-known-name-all</i>	Resource template for this vdc

Command Mode

- /exec/configure/vdc

template data timeout

{ [no] template data timeout <time> | no template data timeout }

Syntax Description

template	Version 9 Template
data	Data
timeout	Template Data resend time
<i>time</i>	Time in seconds

Command Mode

- /exec/configure/nfm-exporter-v9

template peer-policy

[no] template peer-policy <peer-policy-template-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
template	Enter template command mode
peer-policy	Template configuration for policy parameters
<i>peer-policy-template-name</i>	Name of peer-policy template

Command Mode

- /exec/configure/router-bgp

template peer-session

[no] template peer-session <peer-session-template-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
template	Enter template command mode
peer-session	Template configuration for session parameters
<i>peer-session-template-name</i>	Name of peer-session template

Command Mode

- /exec/configure/router-bgp

template peer

[no] template peer <peer-template-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
template	Enter template command mode
peer	Template configuration for peer parameters
<i>peer-template-name</i>	Neighbor template name

Command Mode

- /exec/configure/router-bgp

terminal

terminal { monitor | no { monitor1 | monitor-force } }

Syntax Description

terminal	Set terminal line parameters
monitor	Copy Syslog output to the current terminal line
no	Negate a command or set its defaults
monitor1	Copy Syslog output to the current terminal line
monitor-force	Copy Syslog output to the current terminal line

Command Mode

- /exec

terminal alias

[no] terminal alias [persist] [<alias-name> [<command>]]

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
alias	show aliases (if no arguments) create 'exec' aliases (not persistent). Persistent aliases are in config mode, see 'cli alias
persist	(Optional) add terminal alias to <username>.rc.cli file (auto-executed at login time)
<i>alias-name</i>	(Optional) Name of the alias. (if last argument: shows the value of that alias) Command lines can start with an alias and it will be expanded before parsing. An alias can also be used right after a pipe. The substitution text can contain things like '\$1 \$2' and those \$<number> will be substituted by correspondingly numbered token from the command line starting the counting after the alias.
<i>command</i>	(Optional) Value of the alias (what the alias will be substituted with)

Command Mode

- /exec

terminal ask-on-term

[no] terminal ask-on-term <term>

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
ask-on-term	ask backend driven question on given terminal
<i>term</i>	the terminal (/dev/ptsX)

Command Mode

- /exec

terminal color

[no] terminal color [persist]

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
color	enable colorization of prompt(green if last command ok, red if error), command line (blue), output (default color)
persist	(Optional) add command to <username>.rc.cli file (auto-execed at login time)

Command Mode

- /exec

terminal context management

[no] terminal context management

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
context	set the vrf context
management	vrf context management

Command Mode

- /exec

terminal deep-help

[no] terminal deep-help

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
deep-help	enable cli syntax and list

Command Mode

- /exec

terminal dont-ask

[no] terminal dont-ask [persist]

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
dont-ask	Don't ask 'are you sure' questions, take default answer instead
persist	(Optional) add command to <username>.rc.cli file (auto-execed at login time)

Command Mode

- /exec

terminal edit-mode vi

[no] terminal edit-mode vi [persist]

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
edit-mode	set command line edition keys (vi or emacs emacs is default)
vi	edit like in vi by default in insert-mode, use ~ for command-mode
persist	(Optional) add command to <username>.rc.cli file (auto-execed at login time)

Command Mode

- /exec

terminal event-manager bypass

terminal [<noarg>] event-manager bypass

Syntax Description

terminal	Set terminal line parameters
<i>noarg</i>	(Optional)
event-manager	Event manager cli event
bypass	Bypass event manager cli event publish

Command Mode

- /exec

terminal history no-exec-in-config

[no] terminal history no-exec-in-config

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
history	configure terminal history properties
no-exec-in-config	don't recall exec commands while in config mode

Command Mode

- /exec

terminal history no-exec-in-config

[no] terminal history no-exec-in-config

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
history	configure terminal history properties
no-exec-in-config	don't recall exec commands while in config mode

Command Mode

- /exec

terminal history no-exec-in-config

[no] terminal history no-exec-in-config

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
history	configure terminal history properties
no-exec-in-config	don't recall exec commands while in config mode

Command Mode

- /exec

terminal home

terminal home

Syntax Description

terminal	Set terminal line parameters
home	go back to line 1 position 1 without erasing the screen (to be used in cli command loops)

Command Mode

- /exec

terminal length

terminal length <i0>

Syntax Description

terminal	Set terminal line parameters
length	Set number of lines on a screen
<i>i0</i>	Number of lines on screen (0 for no pausing)

Command Mode

- /exec/configure/console

terminal length

terminal length <i0>

Syntax Description

terminal	Set terminal line parameters
length	Set number of lines on a screen
<i>i0</i>	Number of lines on screen (0 for no pausing)

Command Mode

- /exec

terminal log-all

[no] terminal log-all

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Configure terminal settings
log-all	Accounting log all commands including the show commands

Command Mode

- /exec/configure

terminal no

terminal no { length | terminal-type | width }

Syntax Description

terminal	Set terminal line parameters
no	Negate a command or set its defaults
length	Set number of lines on a screen
terminal-type	Set the terminal type
width	Set width of the display terminal

Command Mode

- /exec

terminal output xml

[no] terminal output xml

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
output	how output of show commands should be formatted
xml	xml output

Command Mode

- /exec

terminal output xml

[no] terminal output xml

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
output	how output of show commands should be formatted
xml	xml output

Command Mode

- /exec

terminal output xml

[no] terminal output xml <namespace-version>

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
output	how output of show commands should be formatted
xml	xml output
<i>namespace-version</i>	enter the version for xml output

Command Mode

- /exec

terminal password

terminal password <password> | no terminal password [<password>]

Syntax Description

no	Negate a command or set its defaults
terminal	Set terminal line parameters
password	set a password to be used in copy scp/ftp commands use online help on the argument to disable echo so you don't need to type control-x-e twice (to toggle echo), echo will be re-enabled after carriage-return
<i>password</i>	Enter the password (online help that you just did disabled echo so type your password and press return

Command Mode

- /exec

terminal prompt

[no] terminal prompt [fix [<name>] [with-cr] | mode | { fq-command | command } | status | exec-time | time | no-echo] +

Syntax Description

no	(Optional) Negate a command or set its defaults
terminal	Set terminal line parameters
prompt	configure how the prompt should look like
fix	(Optional) set the prompt to a fix name (default _prompt_)
with-cr	(Optional) add a carriage return at the end of the prompt
<i>name</i>	(Optional) name to use as a fix prompt
mode	(Optional) include the cli mode name (ex: config-if) into the prompt
fq-command	(Optional) include the fully qualified command just executed (formatted like in accounting log)
command	(Optional) include the previous command (not including the mode and mode instance)
status	(Optional) include the status of previous command (0=success)
exec-time	(Optional) include the time it took to execute previous command
time	(Optional) include the time when prompt was printed
no-echo	(Optional) dont echo the typed characters

Command Mode

- /exec

terminal redirection-mode

terminal redirection-mode <mode>

Syntax Description

terminal	Set terminal line parameters
redirection-mode	Set the redirection mode
<i>mode</i>	

Command Mode

- /exec

terminal session-timeout

terminal session-timeout <i0>

Syntax Description

terminal	Set terminal line parameters
session-timeout	Set session timeout
<i>i0</i>	Enter timeout in minutes, 0 to disable

Command Mode

- /exec

terminal sticky-mode

terminal [<noarg>] sticky-mode

Syntax Description

terminal	Set terminal line parameters
<i>noarg</i>	(Optional)
sticky-mode	Search for the command match in current mode only

Command Mode

- /exec

terminal terminal-type

terminal terminal-type <*s0*>

Syntax Description

terminal	Set terminal line parameters
terminal-type	Set the terminal type
<i>s0</i>	Terminal type

Command Mode

- /exec

terminal time

terminal time [<name>] [delta]

Syntax Description

terminal	Set terminal line parameters
time	save the current time under a variable
<i>name</i>	(Optional) the variable to store the time in
delta	(Optional) print the delta time to the currently saved time value

Command Mode

- /exec

terminal tree-update

terminal tree-update

Syntax Description

terminal	Set terminal line parameters
tree-update	Updates the main parse tree

Command Mode

- /exec

terminal verify-only

terminal [<noarg>] verify-only [username <user>]

Syntax Description

terminal	Set terminal line parameters
<i>noarg</i>	(Optional)
verify-only	Verify command and do not execute
username	(Optional) Username for aaa authorization
<i>user</i>	(Optional) Username for aaa authorization

Command Mode

- /exec

terminal width

terminal width <*i0*>

Syntax Description

terminal	Set terminal line parameters
width	Set width of the display terminal
<i>i0</i>	Number of characters on a screen line

Command Mode

- /exec/configure/console

terminal width

terminal width <i0>

Syntax Description

terminal	Set terminal line parameters
width	Set width of the display terminal
<i>i0</i>	Number of characters on a screen line

Command Mode

- /exec

threshold-percent

```
threshold-percent { percent-threshold { percentup <up-percentage> [ percentdown<down-percentage> ] |
percentdown<down-percentage> [ percentup <up-percentage> ] } } | no threshold-percent { percent-threshold
}
```

Syntax Description

no	Negate a command or set its defaults
threshold-percent	Threshold parameters
percent-threshold	Percentage threshold
percentup	Up threshold
<i>up-percentage</i>	Up threshold percentage

Command Mode

- /exec/configure/tr-list-thrp

threshold

{ { no | default } threshold | threshold <milliseconds> }

Syntax Description

no	
default	Set a command to its defaults
threshold	Operation threshold
<i>milliseconds</i>	Millisecond threshold value

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http

time-range

[no] time-range <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
time-range	Define time range entries
<i>name</i>	Time range name

Command Mode

- /exec/configure

timeout

{ { no | default } timeout |

Syntax Description

no	
default	Set a command to its defaults
timeout	Timeout of an operation

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/fabricPathEcho
/exec/configure/ip-sla/http

timeout

{ no timeout | timeout <value> }

Syntax Description

no	
timeout	Inactivity timeout period
<i>value</i>	Session inactivity timeout in seconds (default 900)

Command Mode

- /exec/configure/config-twamp-ref

timeout

{ timeout <timeout> }

Syntax Description

timeout	Specify
<i>timeout</i>	Timeout

Command Mode

- /exec/configure/configngoamconnectcheck

timer

[no] timer <cap-timer-usec>

Syntax Description

no	(Optional) Negate the command
timer	Configure Packet Drop Timer parameters
<i>cap-timer-usec</i>	

Command Mode

- /exec/configure/pkt-drop

timer

timer <value> | no timer

Syntax Description

no	Negate a command or set its defaults
timer	Configure Bundle timer value
<i>value</i>	Hello timer value

Command Mode

- /exec/configure/anycast

timer inactivity

{ no timer inactivity | timer inactivity <value> }

Syntax Description

no	
timer	Timer configurations
inactivity	Inactivity timer
<i>value</i>	Max number of inactive seconds (default 900)

Command Mode

- /exec/configure/config-twamp-srvr

timers

```
[no] timers { nsf { route-hold <hold-interval> | converge <converge-interval> | signal <signal-interval> } |
active-time [ <max-active-time> | disabled ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
timers	Set EIGRP timers
nsf	EIGRP NSF timer
route-hold	EIGRP hold time for routes learned from nsf peer
<i>hold-interval</i>	Seconds
active-time	EIGRP time limit for active state
<i>max-active-time</i>	(Optional) EIGRP active-state time limit in minutes
disabled	(Optional) disable EIGRP time limit for active state
converge	EIGRP time limit for convergence after switchover
<i>converge-interval</i>	Seconds
signal	EIGRP time limit for signaling NSF restart
<i>signal-interval</i>	Seconds

Command Mode

- /exec/configure/router-eigrp/router-eigrp-vrf-common /exec/configure/router-eigrp/router-eigrp-af-common

timers

```
timers { <hello-time> { <hold-time> | msec-hold <msec-hold> } | msec-hello <msec-hello> { <hold-time> | msec-hold <msec-hold> } } | no timers
```

Syntax Description

no	Negate a command or set its defaults
timers	Hello and hold timers
<i>hello-time</i>	Hello interval in seconds
<i>hold-time</i>	Hold time in seconds
msec-hold	Specify hold interval in milliseconds
<i>msec-hold</i>	Hold interval in milliseconds
msec-hello	Specify hello interval in milliseconds
<i>msec-hello</i>	Hello interval in milliseconds

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

timers

timers <keepalive-interval> <hold-time> | { no | default } timers [<keepalive-interval> <hold-time>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
timers	Configure keepalive and hold timers
<i>keepalive-interval</i>	Keepalive interval (seconds)
<i>hold-time</i>	Holdtime (seconds)

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

timers advertise

[no] timers advertise | timers advertise <val>

Syntax Description

no	Negate a command or set its defaults
timers	Set the VRRP timers
advertise	Set the advertise timer
<i>val</i>	Advertisement interval in milliseconds

Command Mode

- /exec/configure/if-eth-any/vrrpv3

timers basic

timers basic <update> <invalid> <holddown> <garbage> | no timers basic [<update> <invalid> <holddown> <garbage>]

Syntax Description

no	Negate a command or set its defaults
timers	RIP set timers
basic	RIP set basic timers
<i>update</i>	RIP update period
<i>invalid</i>	RIP route timeout period
<i>holddown</i>	RIP route holddown period
<i>garbage</i>	RIP route garbage period

Command Mode

- /exec/configure/router-rip/router-rip-af-common /exec/configure/router-rip/router-rip-vrf-af-common

timers bestpath-defer maximum

[no] timers bestpath-defer <bestpath-defer-time> maximum <bestpath-defer-time-max>

Syntax Description

no	(Optional) Negate a command or set its defaults
timers	Configure bgp related timers
bestpath-defer	Configure bestpath defer timer value for batch prefix processing
<i>bestpath-defer-time</i>	Bestpath defer time (mseconds)
maximum	Configure bestpath defer timer maximum value
<i>bestpath-defer-time-max</i>	Maximum bestpath defer time (mseconds)

Command Mode

- /exec/configure/router-bgp/router-bgp-af

timers bestpath-limit

timers bestpath-limit <bestpath-timeout> [always] | no timers bestpath-limit [<bestpath-timeout>]

Syntax Description

no	Negate a command or set its defaults
timers	Configure bgp related timers
bestpath-limit	Configure timeout for first bestpath after restart
<i>bestpath-timeout</i>	Bestpath timeout (seconds)
always	(Optional) Configure update-delay-always option

Command Mode

- /exec/configure/router-bgp/vrf-cmds

timers bgp

[no] timers bgp <keepalive-interval> <hold-time>

Syntax Description

no	(Optional) Negate a command or set its defaults
timers	Configure bgp related timers
bgp	Configure different bgp keepalive and holdtimes
<i>keepalive-interval</i>	Keepalive interval (seconds)
<i>hold-time</i>	Holdtime (seconds)

Command Mode

- /exec/configure/router-bgp/vrf-cmds

timers lsa-arrival

```
{ { timers lsa-arrival <interval> } | { no timers lsa-arrival [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
lsa-arrival	Minimum interval between arrival of a LSA
<i>interval</i>	Interval value (milliseconds)

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

timers lsa-arrival

```
{ { timers lsa-arrival <interval> } | { no timers lsa-arrival [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
lsa-arrival	Minimum interval between arrival of a LSA
<i>interval</i>	Interval value (millisecond)

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

timers lsa-group-pacing

{ { timers lsa-group-pacing <interval> } | { no timers lsa-group-pacing [<interval>] } }

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
lsa-group-pacing	LSA group refresh/maxage interval
<i>interval</i>	Interval value (seconds)

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

timers lsa-group-pacing

```
{ { timers lsa-group-pacing <interval> } | { no timers lsa-group-pacing [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
lsa-group-pacing	LSA group refresh/maxage interval
<i>interval</i>	Interval value (seconds)

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

timers prefix-peer-timeout

timers prefix-peer-timeout <prefixpeer-timeout> | no timers prefix-peer-timeout [<prefixpeer-timeout>]

Syntax Description

no	Negate a command or set its defaults
timers	Configure bgp related timers
prefix-peer-timeout	Configure how long state for a prefix peer is maintained
<i>prefixpeer-timeout</i>	Prefix Peer timeout (seconds)

Command Mode

- /exec/configure/router-bgp/vrf-cmds

timers prefix-peer-wait

timers prefix-peer-wait <prefixpeer-wait> | no timers prefix-peer-wait [<prefixpeer-wait>]

Syntax Description

no	Negate a command or set its defaults
timers	Configure bgp related timers
prefix-peer-wait	Configure wait timer for a prefix peer
<i>prefixpeer-wait</i>	Prefix peer wait timer (seconds)

Command Mode

- /exec/configure/router-bgp/vrf-cmds

timers srgb cleanup

```
{ { timers srgb cleanup <interval> } | { no timers srgb cleanup [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
srgb	Configure SRGB related timer constants
cleanup	Interval for which SR will wait for SRGB cleanup ACK from clients
<i>interval</i>	Interval value (seconds)

Command Mode

- /exec/configure/config-sr-mpls

timers srgb retry

```
{ { timers srgb retry <interval> } | { no timers srgb retry [ <interval> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
srgb	Configure SRGB related timer constants
retry	Interval for which SR will retry SRGB allocation with ULIB
<i>interval</i>	Interval value (seconds)

Command Mode

- /exec/configure/config-sr-mpls

timers throttle lsa

```
{ { timers throttle lsa <start-time> <hold-time> <max-time> } | { no timers throttle lsa [ <start-time>
<hold-time> <max-time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
throttle	Set rate-limiting values (milliseconds)
lsa	Set rate-limiting for LSA generation
<i>start-time</i>	Start interval (milliseconds)
<i>hold-time</i>	Hold interval (milliseconds)
<i>max-time</i>	Max interval (milliseconds)

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

timers throttle lsa

```
{ { timers throttle lsa <start-time> <hold-time> <max-time> } | { no timers throttle lsa [ <start-time>
<hold-time> <max-time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
throttle	Set rate-limiting values (milliseconds)
lsa	Set rate-limiting for LSA generation
<i>start-time</i>	Start interval (milliseconds)
<i>hold-time</i>	Hold interval (milliseconds)
<i>max-time</i>	Max interval (milliseconds)

Command Mode

- /exec/configure/router-ospf3 /exec/configure/router-ospf3/vrf

timers throttle spf

```
{ { timers throttle spf <start-time> <hold-time> <max-time> } | { no timers throttle spf [ <start-time>
<hold-time> <max-time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
throttle	Configure timer related constants
spf	OSPF SPF timers
<i>start-time</i>	Initial SPF schedule delay in milliseconds
<i>hold-time</i>	Minimum hold time between SPF calculations
<i>max-time</i>	Maximum wait time between SPF calculations

Command Mode

- /exec/configure/router-ospf3/router-ospf3-af-ipv6 /exec/configure/router-ospf3/vrf/router-ospf3-af-ipv6

timers throttle spf

```
{ { timers throttle spf <start-time> <hold-time> <max-time> } | { no timers throttle spf [ <start-time>
<hold-time> <max-time> ] } }
```

Syntax Description

no	Negate a command or set its defaults
timers	Configure timer related constants
throttle	Configure timer related constants
spf	OSPF SPF timers
<i>start-time</i>	Initial SPF schedule delay in milliseconds
<i>hold-time</i>	Minimum hold time between SPF calculations
<i>max-time</i>	Maximum wait time between SPF calculations

Command Mode

- /exec/configure/router-ospf /exec/configure/router-ospf/vrf

timestamp timestamp

timestamp { ingress id <ingress-source-id> | egress id <egress-source-id> } | timestamp { ingress id <ingress-source-id> egress id <egress-source-id> } | no timestamp

Syntax Description

no	Negate a command or set its defaults
timestamp	Configure packet timestamping
ingress	ingress direction
egress	egress direction
id	source identifier inserted in timestamp
<i>ingress-source-id</i>	Ingress source id value
<i>egress-source-id</i>	Egress source id value

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

tls trust-point local remote

tls trust-point local <tp_local> remote <tp_remote> | no tls trust-point

Syntax Description

no	Negate a command or set its defaults
tls	OpenFlow switch tls
trust-point	Configure local and remote trustpoints
local	Configure local trustpoint
<i>tp_local</i>	Local trustpoint name
remote	Configure remote trustpoint
<i>tp_remote</i>	Remote trustpoint name

Command Mode

- /exec/configure/openflow/switch

tls trust-point local remote

tls trust-point local <tp_local> remote <tp_remote> | no tls trust-point

Syntax Description

no	Negate a command or set its defaults
tls	OpenFlow switch tls
trust-point	Configure local and remote trustpoints
local	Configure local trustpoint
<i>tp_local</i>	Local trustpoint name
remote	Configure remote trustpoint
<i>tp_remote</i>	Remote trustpoint name

Command Mode

- /exec/configure/openflow/switch/sub-switch

topology

[no] topology <tpg-id>

Syntax Description

no	(Optional) Negate a command or set its defaults
topology	Configure Layer-2 Topology for IS-IS
<i>tpg-id</i>	L2 Topology ID 1-63

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

topology holddown sigerr

[no] topology holddown sigerr | topology holddown sigerr <sec>

Syntax Description

no	Negate a command or set its defaults
topology	Topology Database Configuration
holddown	Topology Database hold down timers
sigerr	Link hold down time for signalling errors
<i>sec</i>	Hold down time in seconds

Command Mode

- /exec/configure/te

tos

{ { no | default } tos | tos <tos-value> }

Syntax Description

no	
default	Set a command to its defaults
tos	Type of Service
<i>tos-value</i>	Type of Service Value

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/http

tr

```
| tr [ -c | -d | -s | -t ] + <SET1> [ <SET2> ]
```

Syntax Description

	Pipe command output to filter
tr	Translate, squeeze, and/or delete characters
-c	(Optional) first complement SET1
-d	(Optional) delete characters in SET1, do not translate
-s	(Optional) replace each sequence of a repeated character from SET1 with single occurrence of that character
-t	(Optional) first truncate SET1 to length of SET2
<i>SET1</i>	character SET1: CHAR1-CHAR2 = all characters from CHAR1 to CHAR2 in ascending order special chars: (tab) (new line) [:alnum:] [:alpha:] [:digit:] [:graph:] (printable, no space) [:print:] (printable, with space) [:lower:] [:upper:] [:space:] (tab or space)
<i>SET2</i>	(Optional) character SET2 (for translation length is extended to length of SET1 by repeating last char, excess chars are ignored): format same as SET1 [CHAR*] = copies of CHAR until length of SET1 [CHAR*REPEAT] = REPEAT copies of CHAR

Command Mode

- /output

trace buffer size

trace buffer { error | warning | event } size <size>

Syntax Description

trace	MPLS static trace
buffer	MPLS static trace buffer
error	MPLS static error trace
warning	MPLS static warning trace
event	MPLS static event trace
size	trace buffer size in Kbytes
<i>size</i>	trace buffer size in Kbytes

Command Mode

- /exec/configure/mpls_static

traceroute

```
traceroute { <host> | <hostname> } [ port <portnumber> ] [ [ source-interface <src-intf> ] | [ source { <host> | <hostname> | <interface> } ] ] [ vrf { <vrf-name> | <vrf-known-name> } ] ] ]
```

Syntax Description

traceroute	Traceroute
<i>host</i>	IP address of remote system
<i>hostname</i>	Hostname of remote system
port	(Optional) Set destination port
<i>portnumber</i>	(Optional) Enter destination port number
source	(Optional) Set source address in IP header
<i>interface</i>	(Optional) Interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
source-interface	(Optional) Select source interface
<i>src-intf</i>	(Optional) Specify interface

Command Mode

- /exec

tracert6

```
tracert6 { <host> | <hostname> } [ [ source { <host> | <hostname> | <interface> } ] [ vrf { <vrf-name> | <vrf-known-name> } ] ] [ source-interface <src-intf> ] ]
```

Syntax Description

tracert6	Tracert6
<i>hostname</i>	Hostname of remote system
source	(Optional) Set source address in IPv6 header
<i>interface</i>	(Optional) Interface
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
source-interface	(Optional) Select source interface
<i>src-intf</i>	(Optional) Specify interface

Command Mode

- /exec

track-adjacency-nexthop

[no] track-adjacency-nexthop

Syntax Description

no	(Optional) Negate a command or set its defaults
track-adjacency-nexthop	Track next-hop for same-site Overlay adjacencies

Command Mode

- /exec/configure/otv-isis

track

```
track <object-id> { list threshold <weight-val> }
```

Syntax Description

track	Object tracking configuration command
<i>object-id</i>	Tracked Object
list	Object tracking list
threshold	threshold type
<i>weight-val</i>	threshold weight type

Command Mode

- /exec/configure

track

[no] track <object-number> [decrement <value>]

Syntax Description

no	(Optional) Negate a command or set its defaults
track	Associates track object to HSRP group
<i>object-number</i>	Set the object number to the group
decrement	(Optional) Decrements when tracked object goes down
<i>value</i>	(Optional) Set the value to decrement from priority

Command Mode

- /exec/configure/if-eth-any/hsrp_ipv4 /exec/configure/if-eth-any/hsrp_ipv6

track

track <object-number> | no track

Syntax Description

no	Negate a command or set its defaults
track	Associates track object to Anycast Bundle
<i>object-number</i>	Set the object number

Command Mode

- /exec/configure/anycast

track

track <object-id>

Syntax Description

track	Object tracking deletion command
<i>object-id</i>	Tracked Object

Command Mode

- /exec/configure

track

[no] track <object-id> [force]

Syntax Description

no	Negate a command or set its defaults
track	Object tracking deletion command
<i>object-id</i>	Tracked Object
force	(Optional) Completely remove the object

Command Mode

- /exec/configure

track

```
track <object-id> { { ip_v4 route <route-prefix> reachability [ hmm ] } | { ip_v6 routev6 <v6route-prefix> reachability [ hmm ] } }
```

Syntax Description

track	Object tracking configuration command
<i>object-id</i>	Tracked Object
ip_v4	IPv4 protocol
route	IPv4 route
<i>route-prefix</i>	Specify ipv4 route prefix
ip_v6	IPv6 protocol
routev6	IPv6 route
reachability	Route reachability state
hmm	(Optional) Track routes owned by hmm

Command Mode

- /exec/configure

track

```
track <object-id> { ip_v4 sla <sla-id> [ sla_reachability | sla_state ] }
```

Syntax Description

track	Object tracking configuration command
<i>object-id</i>	Tracked Object
ip_v4	IPv4 protocol
sla	IP Service Level Agreement
<i>sla-id</i>	Entry number
sla_reachability	(Optional) Reachability
sla_state	(Optional) return code state

Command Mode

- /exec/configure

track

```
track <object-id> { list { boolean <bool-val> } }
```

Syntax Description

track	Object tracking configuration command
<i>object-id</i>	Tracked Object
list	Object tracking list
boolean	boolean list type
<i>bool-val</i>	boolean list type

Command Mode

- /exec/configure

track

```
track <object-id> { list threshold <percentage-val> }
```

Syntax Description

track	Object tracking configuration command
<i>object-id</i>	Tracked Object
list	Object tracking list
threshold	threshold type
<i>percentage-val</i>	threshold percentage type

Command Mode

- /exec/configure

track

track <track-obj> | no track <track-obj>

Syntax Description

no	Negate a command or set its defaults
track	Tracking object to suspend vPC if object goes down
<i>track-obj</i>	Tracked object

Command Mode

- /exec/configure/vpc-domain

track data

[no] track data <loc-uri>

Syntax Description

no	(Optional) Negate a command or set its defaults
data	User files to preserve
track	Track file uri
<i>loc-uri</i>	Enter file uri

Command Mode

- /exec/configure/personality

track interface

```
track <object-id> interface <ifnum> { line-protocol | ipv4 routing | ipv6 routingv6 }
```

Syntax Description

track	Object tracking configuration commands
<i>object-id</i>	Tracked Object
interface	Interface to track
<i>ifnum</i>	Interface type and number
line-protocol	Track interface line-protocol
ipv4	IPv4 parameters
routing	Track interface ipv4 routing
ipv6	IPv6 parameters
routingv6	Track interface ipv6 routing

Command Mode

- /exec/configure

track interface priority

```
{ { track { { interface <intf_num> priority <priority_value> } | { <object-num> [ decrement <decrement-value> ] } } } | { no track [ { { interface <intf_num> priority <priority_value> } | { <object-num> [ decrement <decrement-value> ] } } ] } }
```

Syntax Description

no	Negate a command or set its defaults
track	Track the availability of another interface/object
interface	Select the tracked interface(Native tracking)
<i>intf_num</i>	
priority	Vr priority used when the tracked interface is down
<i>priority_value</i>	
<i>object-num</i>	Set the object number to the group(Object tracking)
decrement	(Optional) Decrements priority when tracked object goes down
<i>decrement-value</i>	(Optional) Set the value to decrement from priority

Command Mode

- /exec/configure/if-eth-any/vrrp

track running-state track startup-state

[no] track running-state | [no] track startup-state

Syntax Description

no	(Optional) Negate a command or set its defaults
track	Track file uri
running-state	active patches, third-party RPMs, and running-config
startup-state	committed patches, third-party RPMs, and startup-config

Command Mode

- /exec/configure/personality

tracking enable

```
[no] tracking { enable [ reachable-lifetime { <reach_secs> | infinite } ] | disable [ stale-lifetime { <stale_secs> | infinite } ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
<i>reach_secs</i>	(Optional) Seconds
<i>stale_secs</i>	(Optional) Seconds
infinite	(Optional) Keep entry in chosen state forever

Command Mode

- /exec/configure/config-snoop-policy

traffic-class

```
{ { no | default } traffic-class | traffic-class <traffic-class> }
```

Syntax Description

no	
default	Set a command to its defaults
traffic-class	Traffic Class
<i>traffic-class</i>	Traffic Class Value

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp
/exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/http

traffic-engineering

[no] traffic-engineering

Syntax Description

no	(Optional) Negate a command or set its defaults
traffic-engineering	Configure Traffic Engineering related configurations

Command Mode

- /exec/configure/sr

transmit-delay

```
{ { transmit-delay <delay> } | { no transmit-delay [ <delay> ] } }
```

Syntax Description

no	Negate a command or set its defaults
transmit-delay	Packet transmission delay
<i>delay</i>	(seconds)

Command Mode

- /exec/configure/router-ospf3/router-ospf3-vlink /exec/configure/router-ospf3/vrf/router-ospf3-vlink

transmit-delay

```
{ { transmit-delay <delay> } | { no transmit-delay [ <delay> ] } }
```

Syntax Description

no	Negate a command or set its defaults
transmit-delay	Packet transmission delay
<i>delay</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/router-ospf-vlink /exec/configure/router-ospf/vrf/router-ospf-vlink

transmit-delay

```
{ { transmit-delay <delay> } | { no transmit-delay [ <delay> ] } }
```

Syntax Description

no	Negate a command or set its defaults
transmit-delay	Packet transmission delay
<i>delay</i>	(seconds)

Command Mode

- /exec/configure/router-ospf/vrf/router-ospf-slink

transport connection-mode passive

[no | default] transport connection-mode passive

Syntax Description

no	(Optional) Negate a command or set its defaults
default	(Optional) Inherit values from a peer template
transport	BGP transport connection
connection-mode	Specify type of connection
passive	Allow passive connection setup only

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor /exec/configure/router-bgp/router-bgp-neighbor-stmp
/exec/configure/router-bgp/router-bgp-vrf-neighbor
/exec/configure/router-bgp/router-bgp-template-neighbor

transport email

```
{ transport email { from <s0> | reply-to <s1> | smtp-server { <hostipv4> | <hostipv6> | <hostname> } [ port <i1> ] [ use-vrf <s2> ] } | no transport email smtp-server | no transport email { from | reply-to } }
```

Syntax Description

no	Negate a command or set its defaults
transport	Configure transport related configuration
email	Configure email transport related configuration
from	Configure from email address
<i>s0</i>	Provide from email address, example: SJ-9500-1@xyz.com
reply-to	Configure replyto email address
<i>s1</i>	Provide reply-to email address, example: admin@xyz.com
smtp-server	Configure SMTP server address
<i>hostname</i>	SMTP server(DNS name or IPv4 or IPv6 address)
<i>hostipv4</i>	IPV4 address of SMTP server
port	(Optional) Configure SMTP server port (default:25)
<i>i1</i>	(Optional) SMTP server port
use-vrf	(Optional) Configure vrf name
<i>s2</i>	(Optional) vrf name

Command Mode

- /exec/configure/callhome

transport email mail-server

```
{ [ no ] transport email mail-server { <hostipv4> | <hostipv6> | <hostname> } [ port <i1> ] [ priority <i2> ]
[ use-vrf <s2> ] }
```

Syntax Description

no	(Optional) Negate a command or set its defaults
transport	Configure transport related configuration
email	Configure email transport related configuration
mail-server	Configure SMTP server address (for supporting multiple SMTP-servers)
<i>hostname</i>	SMTP server(DNS name or IPv4 or IPv6 address)
<i>hostipv4</i>	IPV4 address of SMTP server
port	(Optional) Configure SMTP server port (default:25)
<i>i1</i>	(Optional) SMTP server port
use-vrf	(Optional) Configure vrf name
<i>s2</i>	(Optional) vrf name
priority	(Optional) Configure SMTP server priority (1-100) (default:50)
<i>i2</i>	(Optional) SMTP server priority

Command Mode

- /exec/configure/callhome

transport http proxy enable

[no] transport http proxy enable

Syntax Description

no	(Optional) Negate a command or set its defaults
transport	Configure transport related configuration
http	Configure transport option for http urls
proxy	Configure proxy for http transport
enable	Enable the usage of proxy server for messages sent over http(s)

Command Mode

- /exec/configure/callhome

transport http proxy server

```
{ transport http proxy server { <hostname> } [ port <i1> ] } | { no transport http proxy server }
```

Syntax Description

no	Negate a command or set its defaults
transport	Configure transport related configuration
http	Configure transport option for http urls
proxy	Configure proxy for http transport
server	Configure proxy server address and port
<i>hostname</i>	Proxy server name or IP address(DNS name or IPv4 or IPv6 address)
port	(Optional) Configure Proxy server port (default:8080)
<i>i1</i>	(Optional) Proxy server port

Command Mode

- /exec/configure/callhome

transport http use-vrf

transport http use-vrf <s2> | no transport http use-vrf

Syntax Description

no	Negate a command or set its defaults
transport	Configure transport related configuration
http	Configure transport option for http urls
use-vrf	Configure vrf name
s2	vrf name

Command Mode

- /exec/configure/callhome

transport udp

[no] transport udp { src-port <srcport> dst-port <dstport> | dst-port <dstport> src-port <srcport> | src-port <srcport> | dst-port <dstport> }

Syntax Description

transport	Transport configurations
udp	UDP Port
src-port	Src UDP port
<i>srcport</i>	UDP port to be configured, default 49153
dst-port	Dest UDP port
<i>dstport</i>	UDP port to be configured for destination, default 49153

Command Mode

- /exec/configure/config-ssx-exporter

transport udp

```
{ [ no ] transport udp <portnumber> | no transport udp }
```

Syntax Description

transport	Transport Destination Port
udp	Destination UDP Port
<i>portnumber</i>	Destination UDP Port

Command Mode

- /exec/configure/config-int-exporter

transport udp

{ [no] transport udp <portnumber> | no transport udp }

Syntax Description

transport	Transport Destination Port
udp	Destination UDP Port
<i>portnumber</i>	Destination UDP Port

Command Mode

- /exec/configure/nfm-exporter

transport udp source-port

```
{ [ no ] transport udp source-port <intf> }
```

Syntax Description

transport	Transport protocol config
udp	UDP Port
source-port	source-port
<i>intf</i>	UDP port to be configured

Command Mode

- /exec/configure/config-fte-exporter

trigger forwarding distribution module

trigger forwarding distribution module <module>

Syntax Description

trigger	Trigger
forwarding	Trigger related to forwarding
distribution	Trigger distribution of forwarding data to LCs
module	distribute to a particular module
<i>module</i>	module number

Command Mode

- /exec

trigger init

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 10

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 10 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
10	{outer l4, inner l4, ieth}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 10 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 10 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 10 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 10 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 10 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 10 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 19

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 19 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
19	{udf_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 19 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 19 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
19	{udf_vec}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 19 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 19 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
19	{udf_vec}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 19 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 19 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
19	{udf_vec}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 6

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 6 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
6	{outer I2, outer I3, outer I4}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 6 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 6 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
6	{outer l2, outer l3, outer l4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 6 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 6 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
6	{outer I2, outer I3, outer I4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 6 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 6 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
6	{outer l2, outer l3, outer l4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 7

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 7 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
7	{inner I2, inner I3, inner I4}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 7 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 7 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 7 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 7 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 7 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 7 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 8

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 8 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
8	{outer I2, inner I2, ieth}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 8 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 8 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 8 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 8 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 8 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 8 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 9

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 9 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
9	{outer I3, inner I3}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 9 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] in-select 9 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
9	{outer l3, inner l3}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 9 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] in-select 9 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init in-select 9 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] in-select 9 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init ingress in-select 3 out-select 0

trigger init { ingress | egress } in-select 3 out-select 0

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
3	outerl2-outerl3-outerl4

Command Mode

- /exec/elanms

trigger init ingress in-select 3 out-select 03

trigger init { ingress | egress } in-select 3 out-select 03

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
03	pkt_lsb
3	outerl2-outerl3-outerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 3 out-select 0 reverse

trigger init { ingress | egress } in-select 3 out-select 0 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
3	outerl2-outerl3-outerl4
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 3 out-select 1

trigger init { ingress | egress } in-select 3 out-select 1

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
1	pkt_fifo_lsb
3	outerl2-outerl3-outerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 3 out-select 2

trigger init { ingress | egress } in-select 3 out-select 2

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
2	pkt_fifo_msb
3	outerl2-outerl3-outerl4

Command Mode

- /exec/elanms

trigger init ingress in-select 3 out-select 4

trigger init { ingress | egress } in-select 3 out-select 4

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
4	pkt_msb
3	outerl2-outerl3-outerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 3 out-select 5

trigger init { ingress | egress } in-select 3 out-select 5

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
3	outer12-outer13-outer14

Command Mode

- /exec/elanms

trigger init ingress in-select 3 out-select 5 reverse

trigger init { ingress | egress } in-select 3 out-select 5 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
3	outer12-outer13-outer14
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 4 out-select 0

trigger init { ingress | egress } in-select 4 out-select 0

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
4	inner12-inner13-inner14

Command Mode

- /exec/elanms

trigger init ingress in-select 4 out-select 04

trigger init { ingress | egress } in-select 4 out-select 04

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
04	pkt_msb
4	innerl2-innerl3-innerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 4 out-select 0 reverse

trigger init { ingress | egress } in-select 4 out-select 0 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
4	inner12-inner13-inner14
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 4 out-select 1

trigger init { ingress | egress } in-select 4 out-select 1

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
1	pkt_fifo_lsb
4	innerl2-innerl3-innerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 4 out-select 2

trigger init { ingress | egress } in-select 4 out-select 2

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
2	pkt_fifo_msb
4	inner12-inner13-inner14

Command Mode

- /exec/elanms

trigger init ingress in-select 4 out-select 3

trigger init { ingress | egress } in-select 4 out-select 3

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
3	pkt_lsb
4	innerl2-innerl3-innerl4

Command Mode

- /exec/alamns

trigger init ingress in-select 4 out-select 5

trigger init { ingress | egress } in-select 4 out-select 5

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
4	inner12-inner13-inner14

Command Mode

- /exec/elanms

trigger init ingress in-select 4 out-select 5 reverse

trigger init { ingress | egress } in-select 4 out-select 5 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
4	innerl2-innerl3-innerl4
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 5 out-select 0

trigger init { ingress | egress } in-select 5 out-select 0

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
5	outerl2-innerl2

Command Mode

- /exec/elanms

trigger init ingress in-select 5 out-select 05

trigger init { ingress | egress } in-select 5 out-select 05

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
05	sideband
5	outerl2-innerl2

Command Mode

- /exec/alamns

trigger init ingress in-select 5 out-select 05 reverse

trigger init { ingress | egress } in-select 5 out-select 05 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
05	sideband
5	outerl2-innerl2
reverse	Program reverse ELAM

Command Mode

- /exec/elanms

trigger init ingress in-select 5 out-select 0 reverse

trigger init { ingress | egress } in-select 5 out-select 0 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
5	outerl2-innerl2
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 5 out-select 1

trigger init { ingress | egress } in-select 5 out-select 1

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
1	pkt_fifo_lsb
5	outerl2-innerl2

Command Mode

- /exec/elanms

trigger init ingress in-select 5 out-select 2

trigger init { ingress | egress } in-select 5 out-select 2

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
2	pkt_fifo_msb
5	outerl2-innerl2

Command Mode

- /exec/alamns

trigger init ingress in-select 5 out-select 3

trigger init { ingress | egress } in-select 5 out-select 3

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
3	pkt_lsb
5	outerl2-innerl2

Command Mode

- /exec/elanms

trigger init ingress in-select 5 out-select 4

trigger init { ingress | egress } in-select 5 out-select 4

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
4	pkt_msb
5	outerl2-innerl2

Command Mode

- /exec/alamns

trigger init ingress in-select 6 out-select 0

trigger init { ingress | egress } in-select 6 out-select 0

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
6	outer13-inner13

Command Mode

- /exec/elanms

trigger init ingress in-select 6 out-select 0 reverse

trigger init { ingress | egress } in-select 6 out-select 0 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
6	outerl3-innerl3
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 6 out-select 1

trigger init { ingress | egress } in-select 6 out-select 1

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
1	pkt_fifo_lsb
6	outer13-inner13

Command Mode

- /exec/elanms

trigger init ingress in-select 6 out-select 2

trigger init { ingress | egress } in-select 6 out-select 2

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
2	pkt_fifo_msb
6	outer13-inner13

Command Mode

- /exec/alamns

trigger init ingress in-select 6 out-select 3

trigger init { ingress | egress } in-select 6 out-select 3

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
3	pkt_lsb
6	outer13-inner13

Command Mode

- /exec/elanms

trigger init ingress in-select 6 out-select 4

trigger init { ingress | egress } in-select 6 out-select 4

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
4	pkt_msb
6	outerl3-innerl3

Command Mode

- /exec/alamns

trigger init ingress in-select 6 out-select 5

trigger init { ingress | egress } in-select 6 out-select 5

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
6	outer13-inner13

Command Mode

- /exec/elanms

trigger init ingress in-select 6 out-select 5 reverse

trigger init { ingress | egress } in-select 6 out-select 5 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
6	outerl3-innerl3
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 7 out-select 0

trigger init { ingress | egress } in-select 7 out-select 0

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
7	outerl4-innerl4

Command Mode

- /exec/elanms

trigger init ingress in-select 7 out-select 0 reverse

trigger init { ingress | egress } in-select 7 out-select 0 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
0	pktrw
7	outerl4-innerl4
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init ingress in-select 7 out-select 1

trigger init { ingress | egress } in-select 7 out-select 1

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
1	pkt_fifo_lsb
7	outerl4-innerl4

Command Mode

- /exec/elanms

trigger init ingress in-select 7 out-select 2

trigger init { ingress | egress } in-select 7 out-select 2

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
2	pkt_fifo_msb
7	outer14-inner14

Command Mode

- /exec/alamns

trigger init ingress in-select 7 out-select 3

trigger init { ingress | egress } in-select 7 out-select 3

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
3	pkt_lsb
7	outer14-inner14

Command Mode

- /exec/elanms

trigger init ingress in-select 7 out-select 4

trigger init { ingress | egress } in-select 7 out-select 4

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
4	pkt_msb
7	outer14-inner14

Command Mode

- /exec/alamns

trigger init ingress in-select 7 out-select 5

trigger init { ingress | egress } in-select 7 out-select 5

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
7	outer14-inner14

Command Mode

- /exec/elanms

trigger init ingress in-select 7 out-select 5 reverse

trigger init { ingress | egress } in-select 7 out-select 5 reverse

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
ingress	Ingress Fields
egress	Egress Fields
in-select	in-select
out-select	out-select
5	sideband
7	outerl4-innerl4
reverse	Program reverse ELAM

Command Mode

- /exec/elamns

trigger init lu-a2d 0

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] lu-a2d 0 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 10 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 10 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 10 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 10 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 10 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 10 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 19 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 19 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
19	{udf_vec}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 19 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 19 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
19	{udf_vec}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 19 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 19 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
19	{udf_vec}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 6 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 6 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
6	{outer l2, outer l3, outer l4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 6 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 6 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
6	{outer I2, outer I3, outer I4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 6 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 6 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
6	{outer l2, outer l3, outer l4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 7 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 7 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 7 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 7 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 7 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 7 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 8 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 8 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 8 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 8 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 8 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 8 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 9 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 9 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 9 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 9 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
9	{outer 13, inner 13}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 in-select 9 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 in-select 9 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
out-select	out-select
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] lu-a2d 0 out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
out-select	out-select
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 0 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 0 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
0	Trigger at LUD
out-select	out-select
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] lu-a2d 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 10

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 10 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
10	{outer l4, inner l4, ieth}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 10 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 10 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 10 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 10 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 10 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 10 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
10	{outer l4, inner l4, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 19

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 19 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
19	{udf_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 19 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 19 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
19	{udf_vec}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 19 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 19 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
19	{udf_vec}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 19 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 19 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
19	{udf_vec}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 6

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 6 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
6	{outer l2, outer l3, outer l4}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 6 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 6 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
6	{outer I2, outer I3, outer I4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 6 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 6 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
6	{outer l2, outer l3, outer l4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamta

trigger init lu-a2d 1 in-select 6 out-select 2

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] lu-a2d 1 in-select 6 out-select 2 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
6	{outer I2, outer I3, outer I4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 7

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 7 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
7	{inner l2, inner l3, inner l4}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 7 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 7 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 7 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 7 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 7 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 7 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
7	{inner l2, inner l3, inner l4}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 8

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 8 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
8	{outer l2, inner l2, ieth}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 8 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 8 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 8 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 8 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamta

trigger init lu-a2d 1 in-select 8 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 8 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
8	{outer l2, inner l2, ieth}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 9

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 9 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
9	{outer 13, inner 13}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 9 out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 9 out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 9 out-select 1

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 9 out-select 1 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
9	{outer 13, inner 13}
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init lu-a2d 1 in-select 9 out-select 2

trigger init [asic <asic-no>] [slice <slice-no>] lu-a2d 1 in-select 9 out-select 2 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
lu-a2d	Trigger at LUA/LUD
1	Trigger at LUA
in-select	in-select
out-select	out-select
9	{outer I3, inner I3}
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init out-select 0

trigger init [asic <asic-no>] [slice <slice-no>] out-select 0 [use-src-id <src-id>]

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
out-select	out-select
0	{header_vec, sideband, sb_info}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init out-select 1

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] out-select 1 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
out-select	out-select
1	{header_vec, sideband, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger init out-select 2

```
trigger init [ asic <asic-no> ] [ slice <slice-no> ] out-select 2 [ use-src-id <src-id> ]
```

Syntax Description

trigger	Define A Trigger
init	Initialize Trigger
asic	(Optional) ASIC instance
<i>asic-no</i>	(Optional) ASIC instance number
slice	(Optional) ASIC slice
<i>slice-no</i>	(Optional) ASIC slice number
out-select	out-select
2	{sideband, sb_info, stats, lux_drop_vec}
use-src-id	(Optional) Capture on ethernet interface
<i>src-id</i>	(Optional) interface index

Command Mode

- /exec/elamtah

trigger reset

trigger reset

Syntax Description

trigger	Define A Trigger
reset	Reset triggers

Command Mode

- /exec/elanms

trigger route download vrf ipv4

```
trigger route download vrf <vrf-name> { ipv4 <route4> | ipv6 <route6> } [ module <slot-num> ]
```

Syntax Description

trigger	Trigger
route	IP route related
download	Download
vrf	vrf
<i>vrf-name</i>	vrf name
ipv4	ipv4
<i>route4</i>	ipv4 prefix
ipv6	ipv6
module	(Optional) Module
<i>slot-num</i>	(Optional) Slot number of the module

Command Mode

- /exec

trunk protocol

[no] trunk protocol [enable]

Syntax Description

no	(Optional) Negate a command or set its defaults
trunk	Configure Switch wide trunk protocol
protocol	enable trunk protocol
enable	(Optional) enable trunk protocol

Command Mode

- /exec/configure

trusted-port

[no] trusted-port

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/config-ra-guard

trusted-port

[no] trusted-port

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/config-snoop-policy

trusted-port

[no] trusted-port

Syntax Description

no	(Optional) Negate a command or set its defaults
----	---

Command Mode

- /exec/configure/config-dhcp-guard

ttag-marker-interval

[no] ttag-marker-interval <seconds>

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag-marker-interval	Marker packet interval
<i>seconds</i>	Interval in seconds

Command Mode

- /exec/configure

ttag-marker-interval

[no] ttag-marker-interval <seconds>

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag-marker-interval	Marker packet interval
<i>seconds</i>	Interval in seconds

Command Mode

- /exec/configure

ttag-marker enable

[no] ttag-marker enable

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag-marker	Enable/Disable marker packet on interface
enable	Enable/Disable marker packet on interface

Command Mode

- /exec/configure/if-ethernet-switch /exec/configure/if-eth-l2-non-member
/exec/configure/if-eth-port-channel /exec/configure/if-ethernet-all

ttag-marker enable

[no] ttag-marker enable

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag-marker	Enable/Disable marker packet on interface
enable	Enable/Disable marker packet on interface

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ttag-strip

[no] ttag-strip

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag-strip	strip ttag from egress packet on this interface

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ttag

[no] ttag

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag	enable ingress packet with ttag on this interface

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ttag

[no] ttag

Syntax Description

no	(Optional) Negate a command or set its defaults
ttag	hardware ttag timestamp

Command Mode

- /exec/configure/if-eth-base /exec/configure/if-ethernet-all

ttl-security hops

ttl-security hops <ebgp-ttl> | { no | default } ttl-security hops [<ebgp-ttl>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
ttl-security	Enable TTL Security Mechanism
hops	Specify hop count for remote peer
<i>ebgp-ttl</i>	EBGP hop count value

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

tunnel destination

tunnel destination { { <ip-addr> | <ip-prefix> | { <ip-addr> <ip-mask> } } | <ipv6-addr> } | no tunnel destination
 [<ip-addr> | <ip-prefix> | { <ip-addr> <ip-mask> } | <ipv6-addr>]

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
destination	destination of tunnel packets
<i>ip-addr</i>	IPv4 address (A.B.C.D)
<i>ip-prefix</i>	IPv4 mask (A.B.C.D/LEN)
<i>ip-mask</i>	IPv4 mask A.B.C.D

Command Mode

- /exec/configure/if-gre-tunnel

tunnel mode

tunnel mode { { gre [ip | ipv6] } | { ipip [ip | ipv6] } | { ipip decapsulate-any [ip | ipv6] } | { ipv6ip [decapsulate-any] } | { ipv6ipv6 [decapsulate-any] } } | no tunnel mode

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
mode	tunnel encapsulation method
gre	generic route encapsulation protocol
ipip	IP in IP protocol
decapsulate-any	decapsulate any
ip	(Optional) over IP
ipv6	(Optional) over IPv6
ipv6ip	IPv6 in IPv4 protocol
ipv6ipv6	IPv6 in IPv6 protocol

Command Mode

- /exec/configure/if-any-tunnel

tunnel path-mtu-discovery

[no] tunnel path-mtu-discovery

Syntax Description

no	(Optional) Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
path-mtu-discovery	Enable Path MTU Discovery on tunnel

Command Mode

- /exec/configure/if-any-tunnel

tunnel path-mtu-discovery age-timer

tunnel path-mtu-discovery age-timer { <age-time> | infinite } | no tunnel path-mtu-discovery age-timer [{ <age-time> | infinite }]

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
path-mtu-discovery	Enable Path MTU Discovery on tunnel
age-timer	Set PMTUD aging timer
<i>age-time</i>	Aging time
infinite	Disable pathmtu aging timer

Command Mode

- /exec/configure/if-any-tunnel

tunnel path-mtu-discovery min-mtu

tunnel path-mtu-discovery min-mtu <mtu> | no tunnel path-mtu-discovery min-mtu [<mtu>]

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
path-mtu-discovery	Enable Path MTU Discovery on tunnel
min-mtu	Min pmtud mtu allowed
<i>mtu</i>	Bytes

Command Mode

- /exec/configure/if-any-tunnel

tunnel source

tunnel source { <intf> | <ip-prefix> | { <ip-addr> [<ip-mask>] } | <ipv6-addr> | direct } | no tunnel source [<intf> | <ip-prefix> | { <ip-addr> [<ip-mask>] } | <ipv6-addr> | direct]

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
source	source of tunnel packets
<i>intf</i>	interface
<i>ip-addr</i>	IPv4 address (A.B.C.D)
<i>ip-prefix</i>	IPv4 address (A.B.C.D/LEN)
<i>ip-mask</i>	(Optional) IPv4 mask A.B.C.D
direct	all directly connected IP

Command Mode

- /exec/configure/if-gre-tunnel

tunnel ttl

tunnel ttl <ttl_val> | no tunnel ttl [<ttl_val>]

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
ttl	set time to live
<i>ttl_val</i>	time to live value

Command Mode

- /exec/configure/if-any-tunnel

tunnel use-vrf

```
tunnel use-vrf { <vrf-name> | <vrf-known-name> } | no tunnel use-vrf [ { <vrf-name> | <vrf-known-name> } ]
```

Syntax Description

no	Negate a command or set its defaults
tunnel	protocol-over-protocol tunneling
use-vrf	set tunnel vrf membership
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/if-any-tunnel



U Commands

- [udf](#), on page 4775
- [udld aggressive](#), on page 4776
- [udld aggressive](#), on page 4777
- [udld aggressive](#), on page 4778
- [udld aggressive](#), on page 4779
- [udld continue-on-err](#), on page 4780
- [udld disable](#), on page 4781
- [udld disable](#), on page 4782
- [udld enable](#), on page 4783
- [udld enable](#), on page 4784
- [udld message-time](#), on page 4785
- [udld reset](#), on page 4786
- [udp-echo](#), on page 4787
- [udp-jitter](#), on page 4788
- [undebg all](#), on page 4790
- [undebg l2rib](#), on page 4791
- [uniq](#), on page 4792
- [unmount](#), on page 4793
- [unmount slot0](#), on page 4794
- [unsuppress-map](#), on page 4795
- [untagged cos](#), on page 4796
- [update-source](#), on page 4797
- [update-source](#), on page 4798
- [update license](#), on page 4799
- [update license](#), on page 4800
- [urib debugs-dump-to-file](#), on page 4801
- [use-chunking size](#), on page 4802
- [use-compression gzip](#), on page 4803
- [use-retry size](#), on page 4804
- [use-vrf](#), on page 4805
- [use-vrf](#), on page 4806
- [use-vrf](#), on page 4807
- [use-vrf](#), on page 4808

- [user-jid password](#), on page 4809
- [user max-logins](#), on page 4810
- [user max-logins](#), on page 4811
- [username](#), on page 4812
- [username](#), on page 4813
- [username](#), on page 4814
- [username](#), on page 4815
- [username](#), on page 4816
- [username keypair export](#), on page 4817
- [username keypair generate](#), on page 4818
- [username keypair import](#), on page 4819
- [username password](#), on page 4820
- [username ssh-cert-dn dsa](#), on page 4821
- [username sshkey](#), on page 4822
- [userpassphrase](#), on page 4823
- [userpassphrase min](#), on page 4824
- [userpassphrase min](#), on page 4825
- [userprofile trustedCert CRLLookup user-switch-bind user-certdn-match user-pubkey-match attribute-name search-filter base-DN](#), on page 4826

udf

```
udf <udf_name> { packet-start | { header { outer | inner } { 13 | 14 } } } <offset> <length> | no udf <udf_name>
[ { packet-start | { header { outer | inner } { 13 | 14 } } } <offset> <length> ]
```

Syntax Description

no	Negate the command
udf	Define the User Defined Field (UDF)
<i>udf_name</i>	Name of the UDF to configure
packet-start	Offset base from packet-start
header	Offset base configuration
outer	Offset base: from outer header
inner	Offset base: from inner header
13	Offset base: from 13 header
14	Offset base: from 14 header
<i>offset</i>	Enter Offset in bytes for UDF (from offset base)
<i>length</i>	Enter Length in bytes for UDF (from offset)

Command Mode

- /exec/configure

udld aggressive

[no] udld aggressive

Syntax Description

no	Negate a command or set its defaults
udld	UDLD protocol
aggressive	Enable UDLD aggressive mode on all fiber optic ports

Command Mode

- /exec/configure

udld aggressive

udld aggressive

Syntax Description

udld	UDLD protocol
aggressive	Enable UDLD aggressive mode on all fiber optic ports

Command Mode

- /exec/configure

udld aggressive

udld aggressive

Syntax Description

udld	UDLD protocol
aggressive	Enable UDLD aggressive mode for interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld aggressive

[no] udld aggressive

Syntax Description

no	Negate a command or set its defaults
udld	UDLD protocol
aggressive	Enable UDLD aggressive mode for interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld continue-on-err

[no] udld continue-on-err

Syntax Description

no	(Optional) Negate a command or set its defaults
udld	UDLD protocol
continue-on-err	Force UDLD continue without disabling the port

Command Mode

- /exec

udld disable

udld disable

Syntax Description

udld	UDLD protocol
disable	Disable UDLD for fiber interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld disable

[no] udld disable

Syntax Description

no	Negate a command or set its defaults
udld	UDLD protocol
disable	Disable UDLD for fiber interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld enable

udld enable

Syntax Description

udld	UDLD protocol
enable	Enable UDLD for non-fiber interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld enable

[no] udld enable

Syntax Description

no	Negate a command or set its defaults
udld	UDLD protocol
enable	Enable UDLD for non-fiber interface(s)

Command Mode

- /exec/configure/if-ethernet-all /exec/configure/if-eth-base

udld message-time

udld message-time <i0> | no udld message-time

Syntax Description

no	Negate a command or set its defaults
udld	UDLD protocol
message-time	Setting the time in seconds between UDLD probe messages
<i>i0</i>	Enter the message timer value [default = 15]

Command Mode

- /exec/configure

udld reset

udld reset

Syntax Description

udld	UDLD protocol
reset	Reset all ports shut down by UDLD

Command Mode

- /exec/configure

udp-echo

```
[no] udp-echo { <hostname> | <ip-address> } <port> { [ control { disable | enable } ] [ source-ip { <source-ip-hostname> | <source-ip-address> } ] [ source-port <source-port-number> ] } +
```

Syntax Description

no	(Optional)
<i>control</i>	(Optional) enable
<i>source-ip-address</i>	(Optional) <source-port-number>
udp-echo	UDP Echo Operation
<i>hostname</i>	Destination hostname, broadcast disallowed
<i>ip-address</i>	Destination IP address, broadcast disallowed
<i>port</i>	Port Number (Recommended port range between 1025-65534)
enable	(Optional) Enable control packets exchange (default)
disable	(Optional) Disable control packets exchange
source-ip	(Optional) Source address
<i>source-ip-hostname</i>	(Optional) source IP hostname, broadcast disallowed
source-port	(Optional) Source Port
<i>source-port-number</i>	(Optional) Port Number (Recommended port range between 1025-65534)

Command Mode

- /exec/configure/ip-sla

udp-jitter

```
[no] udp-jitter { <hostname> | <ip-address> } <dest-port> { { [ codec { g711alaw | g711ulaw | g729a } { [ advantage-factor <advantage-num> ] [ codec-interval <codec-int> ] [ codec-numpackets <codec-numpack> ] [ codec-size <codec-bytes> ] } } + } [ control { disable | enable } ] [ source-ip { <source-ip-hostname> | <source-ip-address> } ] [ source-port <src-port> ] } + | { [ interval <packet-interval> ] [ num-packets <num-packets> ] [ control { disable | enable } ] [ source-ip { <source-ip-hostname> | <source-ip-address> } ] [ source-port <src-port> ] } } + }
```

Syntax Description

no	(Optional)
<i>codec</i>	(Optional) g711alaw
<i>codec-numpackets</i>	(Optional) codec-size
<i>source-port</i>	(Optional) interval
<i>codec-numpack</i>	(Optional) <codec-bytes>
<i>source-ip-hostname</i>	(Optional) <source-ip-address>
udp-jitter	UDP Jitter Operation
<i>hostname</i>	Destination hostname, broadcast disallowed
<i>ip-address</i>	Destination IP address, broadcast disallowed
<i>dest-port</i>	Port Number (Recommended port range between 1025-65534)
g711alaw	(Optional) G.711 A Law 64000 bps
g711ulaw	(Optional) G.711 U Law 64000 bps
g729a	(Optional) G.729 8000 bps
advantage-factor	(Optional) Advantage Factor
codec-interval	(Optional) Inter Packet Interval
codec-size	(Optional) Number of bytes in payload
<i>advantage-num</i>	(Optional) Advantage Factor
<i>codec-int</i>	(Optional) Delay
<i>codec-bytes</i>	(Optional) Number of bytes in payload
<i>packet-interval</i>	(Optional) Delay (default 20)
<i>num-packets</i>	(Optional) Number of Packets (default 10)
interval	(Optional) Inter Packet Interval

num-packets	(Optional) Number of Packets to be transmitted
control	(Optional) Enable or disable control packets
enable	(Optional) Enable control packets exchange (default)
disable	(Optional) Disable control packets exchange
source-ip	(Optional) Source address
<i>source-ip-hostname</i>	(Optional) source IP hostname, broadcast disallowed
<i>source-ip-address</i>	(Optional) source IP address, broadcast disallowed
source-port	(Optional) Source Port
<i>src-port</i>	(Optional) Port Number (Recommended port range between 1025-65534)

Command Mode

- /exec/configure/ip-sla

undebug all

undebug all

Syntax Description

undebug	Disable Debugging functions (See also debug)
all	Disable all debugging

Command Mode

- /exec

undebg l2rib

undebg l2rib

Syntax Description

undebg	Disable Debugging functions (See also debug)
l2rib	L2RIB debug commands

Command Mode

- /exec

uniq

| uniq [-c | -d | -f <nb-of-fields> | -s <nb-of-chars> | -u | -w <nb-chars-to-compare> | -i] +

Syntax Description

	Pipe command output to filter
uniq	Discard all but one of successive identical lines
-c	(Optional) prefix lines by the number of occurrences
-d	(Optional) only print duplicate lines
-f	(Optional) avoid comparing the first N fields
-s	(Optional) avoid comparing the first N characters
-u	(Optional) only print unique lines
-w	(Optional) compare no more than N characters in lines
-i	(Optional) ignore differences in case when comparing
<i>nb-of-fields</i>	(Optional) number of initial fields to ignore
<i>nb-of-chars</i>	(Optional) number of initial chars to ignore
<i>nb-chars-to-compare</i>	(Optional) max number of chars to compare

Command Mode

- /output

unmount

unmount { usb1: | usb2: }

Syntax Description

unmount	unmount expansion flash or USB storage
usb1:	Unmount USB drive in port 1
usb2:	Unmount USB drive in port 2

Command Mode

- /exec

unmount slot0

unmount slot0:

Syntax Description

unmount	unmount expansion flash or USB storage
slot0:	Unmount expansion flash

Command Mode

- /exec

unsuppress-map

unsuppress-map <unsupp-rmap-name> | { no | default } unsuppress-map [<unsupp-rmap-name>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
unsuppress-map	Route-map to selectively unsuppress suppressed routes
<i>unsupp-rmap-name</i>	Route-map name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpn4
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpn6
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

untagged cos

untagged cos <ucos-value> | no untagged cos

Syntax Description

no	Negate a command or set its defaults
untagged	default to use for untagged packets on interface
cos	IEEE 802.1Q class of service for QoS classification
<i>ucos-value</i>	COS value

Command Mode

- /exec/configure/if-set-qos

update-source

update-source <interface> | { no | default } update-source [<interface>]

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
update-source	Specify source of BGP session and updates
<i>interface</i>	Interface name

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor-sess

update-source

update-source <interface> | no update-source

Syntax Description

no	Negate a command or set its defaults
update-source	Specify source of BMP session and messages
<i>interface</i>	Interface name

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

update license

```
update license <uri0> { <license-file> [ force ] | <s0> }
```

Syntax Description

update	Update license
license	Update a license file
<i>uri0</i>	Specify URL for the new license file
<i>license-file</i>	License file to be updated
force	(Optional) Force update license (don't prompt)
<i>s0</i>	License file to be updated

Command Mode

- /exec

update license

```
update license <uri0> { <license-file> [ force ] | <s0> }
```

Syntax Description

update	Update license
license	Update a license file
<i>uri0</i>	Specify URL for the new license file
<i>license-file</i>	License file to be updated
force	(Optional) Force update license (don't prompt)
<i>s0</i>	License file to be updated

Command Mode

- /exec

urib debugs-dump-to-file

urib debugs-dump-to-file

Syntax Description

urib	Unicast Routing Information Base
debugs-dump-to-file	Dump all urib debugs to a file

Command Mode

- /exec

use-chunking size

use-chunking size <kbytes> | no use-chunking

Syntax Description

no	Negate a command or set its defaults
use-chunking	Enable chunking
size	Chunk size
<i>kbytes</i>	Specify chunking size in kilobytes

Command Mode

- /exec/configure/telemetry/destination-group

use-compression gzip

use-compression { gzip } | no use-compression

Syntax Description

no	Negate a command or set its defaults
use-compression	Specify the destination compression method
gzip	GZIP compression algorithm

Command Mode

- /exec/configure/telemetry/destination-profile

use-retry size

use-retry size <mbytes> | no use-retry

Syntax Description

no	Negate a command or set its defaults
use-retry	Specify send retry details
size	Retry buffer size
<i>mbytes</i>	Buffer size in Mega bytes

Command Mode

- /exec/configure/telemetry/destination-profile

use-vrf

use-vrf { default | <vrf-cfg-name> } | no use-vrf

Syntax Description

no	Negate a command or set its defaults
use-vrf	Specify the destination vrf
default	Known VRF name
<i>vrf-cfg-name</i>	Configurable VRF name

Command Mode

- /exec/configure/telemetry/destination-profile

use-vrf

[no] use-vrf { <vrf-name> | <vrf-known-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
use-vrf	Display per-VRF information
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/ldap

use-vrf

[no] use-vrf { management | default | <vrf_name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
use-vrf	vrf to be used to contact servers in this group
management	management vrf
default	default vrf
<i>vrf_name</i>	name of the vrf

Command Mode

- /exec/configure/radius

use-vrf

[no] use-vrf { management | default | <vrf_name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
use-vrf	vrf to be used to contact servers in this group
management	management vrf
default	default vrf
<i>vrf_name</i>	name of the vrf

Command Mode

- /exec/configure/tacacs+

user-jid password

[no] user-jid <jid> password [0 <clear> | 7 <encrypted> | <password>]

Syntax Description

no	(Optional) Negate a command or set its defaults
user-jid	User Jabber ID
<i>jid</i>	Enter user Jabber ID
password	Password
0	(Optional) Password that follows should be in clear text
<i>clear</i>	(Optional) Password in clear text
7	(Optional) Password that follows should be in encrypted text
<i>encrypted</i>	(Optional) Encrypted password
<i>password</i>	(Optional) Enter password in clear text

Command Mode

- /exec/configure/fabric-db/server-xmpp

user max-logins

user max-logins <limit>

Syntax Description

user	Configure system-wide user settings
max-logins	maximum simultaneous logins
<i>limit</i>	login session maximum

Command Mode

- /exec/configure

user max-logins

[no] user max-logins [<limit>]

Syntax Description

no	Negate a command or set its defaults
user	Configure system-wide user settings
max-logins	maximum simultaneous logins
<i>limit</i>	(Optional) login session maximum

Command Mode

- /exec/configure

username

```
[no] username <s0> { sshkey2 { file <uri0> | <line> } }
```

Syntax Description

<code>no</code>	(Optional) Negate a command or set its defaults
<code>username</code>	Configure user information.
<code>s0</code>	user name
<code>sshkey2</code>	Update ssh key for the user for ssh authentication
<code>file</code>	ssh key file
<code>uri0</code>	file containing host public key for the user
<code>line</code>	ssh key for the user

Command Mode

- /exec/configure

username

```
{ username <s0> [ password { 0 <s2> | 5 <s3> | <s4> } ] [ expire <s5> [ past ] ] [ priv-lvl <p> ] } | { username
<s0> [ password { 0 <s2> | 5 <s3> | <s4> } ] [ priv-lvl <p> ] [ expire <s5> [ past ] ] } | { username <s0> [
expire <s5> [ past ] ] [ password { 0 <s2> | 5 <s3> | <s4> } ] [ priv-lvl <p> ] } | { username <s0> [ expire
<s5> [ past ] ] [ priv-lvl <p> ] [ password { 0 <s2> | 5 <s3> | <s4> } ] } | { username <s0> [ priv-lvl <p> ] [
password { 0 <s2> | 5 <s3> | <s4> } ] [ expire <s5> [ past ] ] } | { username <s0> [ priv-lvl <p> ] [ expire
<s5> [ past ] ] [ password { 0 <s2> | 5 <s3> | <s4> } ] } | { no username <s7> [ priv-lvl <p> ] }
```

Syntax Description

no	Negate a command or set its defaults
username	Configure user information.
<i>s0</i>	user name
password	(Optional) Password for the user
0	(Optional) Indicates that the password that follows should be in clear text
<i>s2</i>	(Optional) Password for the user (clear text)
5	(Optional) Indicates that the password that follows should be encrypted
<i>s3</i>	(Optional) strongly encrypted password
<i>s4</i>	(Optional) Password for the user (clear text)
expire	(Optional) Expiry date for this user account(in YYYY-MM-DD format)
<i>s5</i>	(Optional) Expiry in YYYY-MM-DD format
past	(Optional) Expiry date is in past
<i>s7</i>	user name
priv-lvl	(Optional) privilege level which the user is to be assigned to
<i>p</i>	(Optional) privilege level

Command Mode

- /exec/configure

username

```
{ username <s0> [ password { 0 <s2> | 5 <s3> | <s4> } ] [ expire <s5> [ past ] ] [ role <s6> ] } | { username
<s0> [ password { 0 <s2> | 5 <s3> | <s4> } ] [ role <s6> ] [ expire <s5> [ past ] ] } | { username <s0> [ expire
<s5> [ past ] ] [ password { 0 <s2> | 5 <s3> | <s4> } ] [ role <s6> ] } | { username <s0> [ expire <s5> [ past
] ] [ role <s6> ] [ password { 0 <s2> | 5 <s3> | <s4> } ] } | { username <s0> [ role <s6> ] [ password { 0 <s2>
| 5 <s3> | <s4> } ] [ expire <s5> [ past ] ] } | { username <s0> [ role <s6> ] [ expire <s5> [ past ] ] [ password
{ 0 <s2> | 5 <s3> | <s4> } ] } | { no username <s7> [ role <s8> ] }
```

Syntax Description

no	Negate a command or set its defaults
username	Configure user information.
<i>s0</i>	user name
password	(Optional) Password for the user
0	(Optional) Indicates that the password that follows should be in clear text
<i>s2</i>	(Optional) Password for the user (clear text)
5	(Optional) Indicates that the password that follows should be encrypted
<i>s3</i>	(Optional) strongly encrypted password
<i>s4</i>	(Optional) Password for the user (clear text)
expire	(Optional) Expiry date for this user account(in YYYY-MM-DD format)
<i>s5</i>	(Optional) Expiry in YYYY-MM-DD format
past	(Optional) Expiry date is in past
role	(Optional) role which the user is to be assigned to
<i>s6</i>	(Optional) role name
<i>s7</i>	user name
<i>s8</i>	(Optional) role name

Command Mode

- /exec/configure

username

```
{ username <s0> { shelltype { vsh | bash } } }
```

Syntax Description

username	Configure user information.
<i>s0</i>	user name
shelltype	Choose shell type for login
vsh	use vsh shell
bash	use bash shell

Command Mode

- /exec/configure

username

```
{ [ no ] username <name> }
```

Syntax Description

username	user name
<i>name</i>	user name

Command Mode

- /exec/configure/dot1x-cred

username keypair export

```
{ username <s0> keypair export <s1> { dsa | rsa | ecdsa } [ force ] }
```

Syntax Description

username	Configure user information.
keypair	Use existing ssh keypair
export	Export keypair to Bootflash/Remote directory
force	(Optional) Force the export of keys even if the destination files are present
dsa	Use DSA Keys
rsa	Use RSA Keys
ecdsa	Use ECDSA Keys
<i>s0</i>	user name
<i>s1</i>	Enter filename to export to

Command Mode

- /exec/configure

username keypair generate

```
{ username <s0> keypair generate { dsa [ force ] | rsa [ <i0> | <oldrange> ] [ force ] | ecdsa { <i0> } [ force ] } | no username <s0> keypair generate [ { dsa [ force ] | rsa [ <i0> | <oldrange> ] [ force ] | ecdsa [ { <i0> } [ force ] ] } ] }
```

Syntax Description

no	Negate a command or set its defaults
username	Configure user information.
<i>s0</i>	user name
generate	Generate ssh key pairs
keypair	Generate SSH User Keys
dsa	Generate DSA keys
force	(Optional) Force the generation of keys even if previous ones are present
rsa	Generate RSA keys
<i>i0</i>	(Optional) Enter number of bits (in multiples of 8)
<i>oldrange</i>	(Optional) Enter number of bits
ecdsa	Generate ECDSA keys
<i>i0</i>	Enter key size in bits (256, 384 or 521)
force	(Optional) Force the generation of keys even if previous ones are present

Command Mode

- /exec/configure

username keypair import

```
{ username <s0> keypair import <s1> { dsa | rsa | ecdsa } [ force ] }
```

Syntax Description

username	Configure user information.
keypair	Use existing ssh keypair
import	Import keypair from Bootflash/Remote directory
force	(Optional) Force the generation of keys even if previous ones are present
dsa	Use DSA Keys
rsa	Use RSA Keys
ecdsa	Use ECDSA Keys
<i>s0</i>	user name
<i>s1</i>	Enter filename to import

Command Mode

- /exec/configure

username password

[no] username <user> password { 0 <pass1> | 5 <pass2> | <pass3> }

Syntax Description

no	(Optional) Negate a command or set its defaults
username	Configure user name
<i>user</i>	Username
password	Password for user
0	Indicates that the password that follows should be in clear text
<i>pass1</i>	Password for the user (clear text)
5	Indicates that the password that follows should be encrypted
<i>pass2</i>	strongly encrypted password
<i>pass3</i>	Password for the user (clear text)

Command Mode

- /exec/configure/vmt-conn

username ssh-cert-dn dsa

[no] username <s1> ssh-cert-dn <s2> { dsa | rsa }

Syntax Description

no	(Optional) Negate a command or set its defaults
username	Configure user information.
<i>s1</i>	user name
ssh-cert-dn	Update cert dn
<i>s2</i>	distinguished name to be used
dsa	Use dsa algorithm
rsa	Use rsa algorithm

Command Mode

- /exec/configure

username sshkey

```
{ username <s0> sshkey { file <uri0> | <line> } | no username <s0> sshkey }
```

Syntax Description

username	Configure user information.
<i>s0</i>	user name
sshkey	Update ssh key for the user for ssh authentication
file	ssh key file
<i>uri0</i>	file containing host public key for the user
<i>line</i>	ssh key for the user
no	Negate a command or set its defaults

Command Mode

- /exec/configure

userpassphrase

[no] userpassphrase { min-length | max-length | length }

Syntax Description

no	Negate a command or set its defaults
userpassphrase	user passphrase
min-length	passphrase minimum length
max-length	passphrase maximum length
length	passphrase min and max length

Command Mode

- /exec/configure

userpassphrase min

[no] userpassphrase { min-length <min-len> | max-length <max-len> } +

Syntax Description

no	Negate a command or set its defaults
userpassphrase	user passphrase
min-length	passphrase minimum length
max-length	passphrase maximum length
<i>min-len</i>	minimum length of passphrase
<i>max-len</i>	maximum length of passphrase

Command Mode

- /exec/configure

userpassphrase min

userpassphrase { min-length <min-len> | max-length <max-len> } +

Syntax Description

userpassphrase	user passphrase
min-length	passphrase minimum length
max-length	passphrase maximum length
<i>min-len</i>	minimum length of passphrase
<i>max-len</i>	maximum length of passphrase

Command Mode

- /exec/configure

userprofile trustedCert CRLLookup user-switch-bind user-certdn-match user-pubkey-match attribute-name search-filter base-DN

{ userprofile | trustedCert | CRLLookup | user-switch-bind | user-certdn-match | user-pubkey-match }
attribute-name <s0> search-filter <s1> base-DN <s2>

Syntax Description

userprofile	Set the userprofile
trustedCert	Set the trustedCert
CRLLookup	Set the CRLLookup
user-switch-bind	Set the user-switch-bind
user-certdn-match	Set the certificate matching
user-pubkey-match	Set the pubkey matching
attribute-name	LDAP attribute-name
<i>s0</i>	Search Map attribute-name
search-filter	LDAP search-filter
<i>s1</i>	Search Map search-filter
base-DN	LDAP base-DN
<i>s2</i>	Search Map base-DN Name

Command Mode

- /exec/configure/ldap/search



V Commands

- [validate-json](#), on page 4830
- [validate-xml](#), on page 4831
- [validate-xml](#), on page 4832
- [vdc](#), on page 4833
- [vdc](#), on page 4834
- [vdc combined-hostname](#), on page 4835
- [vdc_id](#), on page 4836
- [vdc resource template](#), on page 4837
- [vdc suspend](#), on page 4838
- [vdc suspend](#), on page 4839
- [vdp dot1q default static](#), on page 4840
- [vdp dot1q static](#), on page 4841
- [vdp vni default static](#), on page 4842
- [vdp vni static](#), on page 4843
- [verify-data](#), on page 4844
- [verify-host](#), on page 4845
- [verify](#), on page 4846
- [verify profile](#), on page 4847
- [verify verbose](#), on page 4848
- [version](#), on page 4849
- [version 9](#), on page 4850
- [virtual-service](#), on page 4851
- [virtual-service](#), on page 4852
- [virtual-service](#), on page 4853
- [virtual-service move name log to](#), on page 4854
- [virtual-service reset force](#), on page 4855
- [virtual IPv6](#), on page 4856
- [virtual IPv6](#), on page 4857
- [virtual ip](#), on page 4858
- [virtual ip](#), on page 4859
- [vlan-consistency-check](#), on page 4860
- [vlan-pruning enable](#), on page 4861
- [vlan](#), on page 4862

- [vlan2](#), on page 4863
- [vlan](#), on page 4864
- [vlan](#), on page 4865
- [vlan access-map](#), on page 4866
- [vlan configuration](#), on page 4867
- [vlan designated priority](#), on page 4868
- [vlan filter vlan](#), on page 4869
- [vlan root priority](#), on page 4870
- [vmtracker connection](#), on page 4871
- [vmtracker connection refresh](#), on page 4872
- [vmtracker enable](#), on page 4873
- [vmtracker fabric auto-config](#), on page 4874
- [vn-segment](#), on page 4875
- [vni](#), on page 4876
- [vni](#), on page 4877
- [vni](#), on page 4878
- [vni default dynamic](#), on page 4879
- [vni l2](#), on page 4880
- [vpc](#), on page 4881
- [vpc domain](#), on page 4882
- [vpc orphan-port suspend](#), on page 4883
- [vpc peer-link](#), on page 4884
- [vpc role preempt](#), on page 4885
- [vpn](#), on page 4886
- [vpn id](#), on page 4887
- [vrf](#), on page 4888
- [vrf](#), on page 4889
- [vrf](#), on page 4890
- [vrf](#), on page 4891
- [vrf](#), on page 4892
- [vrf](#), on page 4893
- [vrf](#), on page 4894
- [vrf](#), on page 4895
- [vrf](#), on page 4896
- [vrf](#), on page 4897
- [vrf](#), on page 4898
- [vrf](#), on page 4899
- [vrf](#), on page 4900
- [vrf context](#), on page 4901
- [vrf default static](#), on page 4902
- [vrf member](#), on page 4903
- [vrf member](#), on page 4904
- [vrf static](#), on page 4905
- [vrrp](#), on page 4906
- [vrrp bfd](#), on page 4907
- [vrrpv2](#), on page 4908

- vrrpv3, on page 4909
- vrrpv3 address-family, on page 4910
- vrrpv3 address-family, on page 4911
- vrrs leader, on page 4912
- vrrs pathway, on page 4913
- vsh, on page 4914
- vtp, on page 4915
- vtp domain, on page 4916
- vtp file, on page 4917
- vtp mode, on page 4918
- vtp password, on page 4919
- vtp pruning, on page 4920
- vtp version, on page 4921

validate-json

| validate-json

Syntax Description

	Pipe command output to filter
validate-json	validate json output according to .xsd definitions

Command Mode

- /output

validate-xml

| validate-xml

Syntax Description

	Pipe command output to filter
validate-xml	validate an xml output according to .xsd definitions

Command Mode

- /output

validate-xml

| validate-xml

Syntax Description

	Pipe command output to filter
validate-xml	validate an xml output according to .xsd definitions

Command Mode

- /output

vdc

[no] vdc <e-vdc> [force]

Syntax Description

no	Negate a command or set its defaults
vdc	Manage Virtual Device Context
<i>e-vdc</i>	Enter Virtual Device Context <vdc-id>
force	(Optional) Force ungraceful cleanup

Command Mode

- /exec/configure

vdc

```
vdc <e-vdc> [ id <new_id> ] [ type <vtype> ]
```

Syntax Description

vdc	Manage Virtual Device Context
<i>e-vdc</i>	Enter Virtual Device Context <vdc-id>
id	(Optional) force this vdc into a specific id
<i>new_id</i>	(Optional) force this vdc into a specific id
type	(Optional) Create vdc with a special set of services
<i>vtype</i>	(Optional) type of vdc

Command Mode

- /exec/configure

vdc combined-hostname

[no] vdc combined-hostname

Syntax Description

no	(Optional) Negate a command or set its defaults
vdc	Manage Virtual Device Context
combined-hostname	The hostname of non-default vdc's will be <default vdc name>-<nondefault vdc name>

Command Mode

- /exec/configure

vdc_id

[no] vdc_id <id>

Syntax Description

no	Negate a command or set its defaults
vdc_id	Manage Virtual Device Context
<i>id</i>	Enter Virtual Device Context <vdc-id>

Command Mode

- /exec/configure

vdc resource template

[no] vdc resource template { <name> | <res-mgr-template-known-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
vdc	Manage Virtual Device Context
resource	Configure resource template
template	Configure resource template
<i>name</i>	Resource template name
<i>res-mgr-template-known-name</i>	Resource template name

Command Mode

- /exec/configure

vdc suspend

vdc <en-vdc> suspend

Syntax Description

vdc	Manage Virtual Device Context
<i>en-vdc</i>	Enter Virtual Device Context <vdc-id>
suspend	Put the vdc in a paused state. When resumed vdc will come up with its startup config

Command Mode

- /exec/configure

vdc suspend

[no] vdc <en-vdc> suspend

Syntax Description

vdc	Manage Virtual Device Context
<i>en-vdc</i>	Enter Virtual Device Context <vdc-id>
suspend	Put the vdc in a paused stated. When resumed vdc will use its startup config

Command Mode

- /exec/configure

vdp dot1q default static

```
{ vdp dot1q default { static <profile-name> | dynamic } } | { no vdp dot1q default }
```

Syntax Description

no	Negate a command or set its defaults
vdp	VDP protocol triggers
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
dot1q	Dot1Q Encapsulation
default	Default (wildcard). Match any dot1q when there is no specific dot1q mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

vdp dot1q static

```
{ vdp dot1q <vlan-id> { static <profile-name> | dynamic } } | { no vdp dot1q <vlan-id> }
```

Syntax Description

no	Negate a command or set its defaults
vdp	VDP protocol triggers
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
dot1q	Dot1Q Encapsulation
<i>vlan-id</i>	

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

vdp vni default static

```
{ vdp vni default { static <profile-name> | dynamic } } | { no vdp vni default }
```

Syntax Description

no	Negate a command or set its defaults
vdp	VDP protocol triggers
vni	Virtual Network Identifier
static	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
default	Default (wildcard). Match any vni when there is no specific vni mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

vdp vni static

{ vdp vni <vni-id> { static <profile-name> | dynamic } } | { no vdp vni <vni-id> }

Syntax Description

no	Negate a command or set its defaults
vdp	VDP protocol triggers
vni	Virtual Network Identifier
<i>vni-id</i>	
static	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

verify-data

{ { no | default } verify-data | verify-data }

Syntax Description

no	
default	Set a command to its defaults
verify-data	Verify data

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/icmpEcho

verify-host

{ verify-host | no verify-host }

Syntax Description

no	Negate a command or set its defaults
verify-host	Verify host reachability - payload info mandatory

Command Mode

- /exec/configure/configngoamconnectcheck

verify

verify

Syntax Description

verify	Verify the current configuration session
--------	--

Command Mode

- /exec/configure

verify profile

verify profile <all_conf_profile_name> [__readonly__ TABLE_profile_name <missing_param>]

Syntax Description

verify	Verify the instance with a configuration profile
profile	Name of the configuration profile
<i>all_conf_profile_name</i>	Enter the name of configuration profile
<i>__readonly__</i>	(Optional)
<i>TABLE_profile_name</i>	(Optional)
<i>missing_param</i>	(Optional)

Command Mode

- /exec/configure/param-inst

verify verbose

verify verbose

Syntax Description

verify	Verify the current configuration session
verbose	Verify the current configuration session with more details

Command Mode

- /exec/configure

version

[no] version <s0> [<s1>] [<s2>] [<s3>] [<s4>]

Syntax Description

no	(Optional) Negate a command or set its defaults
version	Version info
s0	Version
s1	(Optional) Version1
s2	(Optional) Version2
s3	(Optional) Version3
s4	(Optional) Version4

Command Mode

- /exec/configure

version 9

version 9

Syntax Description

version	Specify the export version
9	Version 9 Export

Command Mode

- /exec/configure/nfm-exporter

virtual-service

[no] virtual-service <virt_serv_name>

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual-service	Configure a virtual service
<i>virt_serv_name</i>	Virtual service name

Command Mode

- /exec/configure

virtual-service

[no] virtual-service

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual-service	Virtual service global settings

Command Mode

- /exec/configure

virtual-service

```
virtual-service { { install name <virt_serv_name> package <file_uri> [ media <target_media> ] } | { upgrade
name <virt_serv_name> package <file_uri> } | { uninstall name <virt_serv_name> } }
```

Syntax Description

virtual-service	Virtualization manager actions
install	Add a virtual service to install database
upgrade	Upgrade a virtual service package to a different version
name	Name of the virtual service
<i>virt_serv_name</i>	Virtual service name
package	Package location
<i>file_uri</i>	File name (with .ova extension) for the virtual service
media	(Optional) Target media to use to explode the virtual service package
<i>target_media</i>	(Optional) Target media
uninstall	Remove a virtual service from the install database

Command Mode

- /exec

virtual-service move name log to

virtual-service move name <virt_serv_name> { log | core } to <dir_uri>

Syntax Description

virtual-service	Virtualization service actions
move	Move a virtual service log or core files
name	Name of the virtual service
<i>virt_serv_name</i>	Name of existing virtual service
log	Move log files
core	Move core files
to	Destination directory to move log or core files to
<i>dir_uri</i>	Destination directory name

Command Mode

- /exec

virtual-service reset force

virtual-service reset force

Syntax Description

virtual-service	Virtualization service actions
reset	Virtualization reset commands
force	Force a non-recoverable reset of all virtualization files

Command Mode

- /exec

virtual IPv6

```
[no] virtual IPv6 { <ip-addr> { <prefix> | <netmask> } } [ ip | { { udp | tcp } { <port_num> | any } } ] [ {
advertise } { enable | disable } [ active ] [ device-group <dgrp_name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual	ITD virtual ip configuration
IPv6	ITD virtual IPv6
<i>prefix</i>	IPv6 prefix length
ip	(Optional) IP Protocol
udp	(Optional) UDP Protocol
tcp	(Optional) TCP Protocol
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable
active	(Optional) Advertise route on at least one node active
device-group	(Optional) device-group
<i>dgrp_name</i>	(Optional) VIP device-group name

Command Mode

- /exec/configure/itd

virtual IPv6

```
[no] virtual IPv6 { <ip-addr> { <prefix> | <netmask> } } [ ip | { { udp | tcp } { <port_num> | any } } ] [ { arp
| advertise } { enable | disable } ] [ device-group <group-name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual	Configure Virtual IP of server nodes for redirection
IPv6	IPv6 address
<i>prefix</i>	IPV6 prefix length
ip	(Optional) IP address
udp	(Optional) UDP port
tcp	(Optional) TCP port
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
arp	(Optional) ARP
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable
device-group	(Optional) Specify device group mapped to VIP
<i>group-name</i>	(Optional) Device-group name mapped to VIP

Command Mode

- /exec/configure/plb

virtual ip

```
[no] virtual ip { <ip-addr> <ip-mask> } [ ip | { { udp | tcp } { <port_num> | any } } ] [ { advertise } { enable | disable } [ active ] ] [ device-group <dgrp_name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual	ITD virtual ip configuration
ip	ITD virtual ip
<i>ip-addr</i>	IP address in format i.i.i.i
<i>ip-mask</i>	IP network mask in format m.m.m.m
ip	(Optional) IP Protocol
udp	(Optional) UDP Protocol
tcp	(Optional) TCP Protocol
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable
active	(Optional) Advertise route on at least one node active
device-group	(Optional) device-group
<i>dgrp_name</i>	(Optional) VIP device-group name

Command Mode

- /exec/configure/itd

virtual ip

```
[no] virtual ip { <ip-addr> <ip-mask> } [ ip | { { udp | tcp } { <port_num> | any } } ] [ { arp | advertise } { enable | disable } ] [ device-group <group-name> ]
```

Syntax Description

no	(Optional) Negate a command or set its defaults
virtual	Configure Virtual IP of server nodes for redirection
ip	IPv4 address
<i>ip-addr</i>	IPv4 prefix in format i.i.i.i
<i>ip-mask</i>	IPv4 prefix mask in format m.m.m.m
ip	(Optional) IPv4 address
udp	(Optional) UDP port
tcp	(Optional) TCP port
<i>port_num</i>	(Optional) Port Number
any	(Optional) Any Port Number
arp	(Optional) ARP
advertise	(Optional) advertise
enable	(Optional) Enable
disable	(Optional) Disable
device-group	(Optional) Specify device group mapped to VIP
<i>group-name</i>	(Optional) Device-group name mapped to VIP

Command Mode

- /exec/configure/plb

vlan-consistency-check

[no] vlan-consistency-check

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan-consistency-check	enable vlan consistency check

Command Mode

- /exec/configure/evpn-esi-mh

vlan-pruning enable

vlan-pruning enable | no vlan-pruning enable

Syntax Description

no	Negate a command or set its defaults
vlan-pruning	Configure Vlan-pruning feature
enable	Set the mode for vlan-pruning

Command Mode

- /exec/configure/l2mp-isis/l2mp-isis-vrf-common

vlan

vlan <vlans> | no vlan

Syntax Description

no	Negate a command or set its defaults
vlan	Set allowed fabricpath VLANs for a given anycast bundle
<i>vlans</i>	VLAN IDs of the allowed fabricpath VLANs in the anycast bundle

Command Mode

- /exec/configure/anycast

vlan2

[no] vlan2 <vlan-id-create-delete>

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan2	Vlan commands
<i>vlan-id-create-delete</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

vlan

[no] vlan <vlan-range>

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan	add vlan to vlan group
<i>vlan-range</i>	range of vlans

Command Mode

- /exec/configure/itd-vlan-grp

vlan

[no] vlan <vlan-range>

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan	vlan
<i>vlan-range</i>	range of vlans

Command Mode

- /exec/configure/smarte /exec/configure/smarte

vlan access-map

[no] vlan access-map <name> [<seqno>]

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan	Vlan commands
<i>name</i>	List name
access-map	Configure a VLAN access map
<i>seqno</i>	(Optional) Sequence number

Command Mode

- /exec/configure

vlan configuration

[no] vlan configuration <vlan-id-create-delete>

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan	Vlan commands
configuration	vlan feature configuration mode
<i>vlan-id-create-delete</i>	VLAN ID 1-4094 or range(s): 1-5, 10 or 2-5,7-19

Command Mode

- /exec/configure

vlan designated priority

{ vlan <vlan-id> | bridge-domain <bd-id> } designated priority <prio> | no { vlan <vlan-id> | bridge-domain <bd-id> } designated priority [<prio>]

Syntax Description

no	Negate a command or set its defaults
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
designated	Set the designated bridge priority for the spanning tree
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure/spanning-tree/pseudo

vlan filter vlan

[no] vlan filter <name> { vlan-list <vlans> | vlan-list-include-reserved <vlans-include-reserved> }

Syntax Description

no	(Optional) Negate a command or set its defaults
vlan	Vlan commands
filter	Specify access control for packets
<i>name</i>	List name
vlan-list	Specify list of VLANs to apply access control
<i>vlans</i>	List of VLANs
vlan-list-include-reserved	Specify list of VLANs to apply access control
<i>vlans-include-reserved</i>	List of VLANs

Command Mode

- /exec/configure

vlan root priority

```
{ vlan <vlan-id> | bridge-domain <bd-id> } root priority <prio> | no { vlan <vlan-id> | bridge-domain <bd-id> } root priority [ <prio> ]
```

Syntax Description

no	Negate a command or set its defaults
vlan	VLAN Switch Spanning Trees
bridge-domain	Bridge-Domain Switch Spanning Trees
<i>vlan-id</i>	vlan range, Example: 1,3-5,7,9-11
<i>bd-id</i>	Bridge-Domain range, Example: 2,4-5,7,9-11
root	Set the root bridge priority for the spanning tree
priority	Set the bridge priority for the spanning tree
<i>prio</i>	bridge priority in increments of 4096

Command Mode

- /exec/configure/spanning-tree/pseudo

vmtracker connection

[no] vmtracker connection <connection-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vmtracker	Configure vmtracker parameters
connection	Specify a host to connect
<i>connection-name</i>	VM host name

Command Mode

- /exec/configure

vmtracker connection refresh

[no] vmtracker connection <connection-name> refresh

Syntax Description

no	(Optional) Negate a command or set its defaults
vmtracker	Configure vmtracker parameters
connection	Specify a host to connect
<i>connection-name</i>	VM host name
refresh	Refresh all host related information

Command Mode

- /exec/configure

vmtracker enable

[no] vmtracker enable

Syntax Description

no	(Optional) Negate a command or set its defaults
vmtracker	Configure vmtracker feature
enable	Enable vmtracker feature on interface

Command Mode

- /exec/configure/if-switching

vmtracker fabric auto-config

[no] vmtracker fabric auto-config

Syntax Description

no	(Optional) Negate a command or set its defaults
vmtracker	Configure vmtracker parameters
fabric	Enable VM Tracker Fabric parameters
auto-config	Enable VM Tracker Fabric AutoConfiguration

Command Mode

- /exec/configure

vn-segment

vn-segment { <segment-id> | <zero-segment-id> } | no vn-segment

Syntax Description

no	Negate a command or set its defaults
vn-segment	VN Segment id of the VLAN
<i>segment-id</i>	segment-id
<i>zero-segment-id</i>	segment-id

Command Mode

- /exec/configure/vlan

vni

[no] vni <vni-id-sh>

Syntax Description

no	(Optional) Negate a command or set its defaults
vni	Configure a vni-based static host
<i>vni-id-sh</i>	

Command Mode

- /exec/configure/static-host

vni

{ vni <id> } | { no vni [<id>] }

Syntax Description

no	Negate a command or set its defaults
vni	Virtual Network Identifier
<i>id</i>	vni, Example: 4096,6099

Command Mode

- /exec/configure/vrf

vni

{ vni <vni-id> | no vni }

Syntax Description

no	Negate a command or set its defaults
vni	Vni
<i>vni-id</i>	Configure vni id

Command Mode

- /exec/configure/configngoamconnectcheck

vni default dynamic

{ vni default dynamic } | { no vni default }

Syntax Description

no	Negate a command or set its defaults
dynamic	Dynamic Profile Map: Retrieve profile name from the external server
vni	Virtual Network Identifier
default	Default (wildcard). Match any vni when there is no specific vni mapping configured

Command Mode

- /exec/configure/profile-map /exec/configure/profile-map-global

vni l2

[no] vni <vni_id> l2

Syntax Description

no	(Optional) Negate a command or set its defaults
vni	Configure Ethernet VPN ID
<i>vni_id</i>	Specify VNI ID
l2	Layer-2 VNI

Command Mode

- /exec/configure/evpn

vpc

vpc [<vpc_num>] | no vpc [<vpc_num>]

Syntax Description

no	Negate a command or set its defaults
vpc	Virtual Port Channel configuration
<i>vpc_num</i>	(Optional) specify a Virtual Port Channel number

Command Mode

- /exec/configure/if-eth-port-channel-switch

vpc domain

vpc domain <domain_id> | no vpc domain <domain_id>

Syntax Description

no	Negate a command or set its defaults
vpc	Virtual Port Channel configuration
domain	Specify domain
<i>domain_id</i>	domain id

Command Mode

- /exec/configure

vpc orphan-port suspend

[no] vpc orphan-port suspend

Syntax Description

no	(Optional) Negate a command or set its defaults
vpc	Virtual Port Channel configuration
orphan-port	orphan-port (non-vpc port)
suspend	suspend - when vPC secondary peerlink goes down

Command Mode

- /exec/configure/if-eth-phy /exec/configure/if-eth-port-channel-switch /exec/configure/if-eth-port-channel

vpc peer-link

vpc peer-link | no vpc peer-link

Syntax Description

no	Negate a command or set its defaults
vpc	Virtual Port Channel configuration
peer-link	specify if this link is used for peer communication

Command Mode

- /exec/configure/if-eth-port-channel-switch

vpc role preempt

vpc role preempt

Syntax Description

vpc	Virtual Port Channel configuration
role	vPC role related command
preempt	Enable/Trigger preemption of lower priority master

Command Mode

- /exec

vpn

[no] vpn <otv-isis-vpn-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vpn	Configure IS-IS VPN name eg: Overlay<x>
<i>otv-isis-vpn-name</i>	Overlay name

Command Mode

- /exec/configure/otv-isis

vpn id

vpn id <vpn-id> | no vpn id [<vpn-id>]

Syntax Description

no	Negate a command or set its defaults
vpn	Configure VPN ID in rfc2685 format
id	Configure VPN ID in rfc2685 format
<i>vpn-id</i>	OUI:VPN-Index, format (hex) <3 bytes OUI:4 bytes VPN-Index>

Command Mode

- /exec/configure/vrf

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Configure RIP VRF information
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-rip

vrf

[no] vrf [<name>]

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Catena service vrf
<i>name</i>	(Optional) Catena Service VRF name

Command Mode

- /exec/configure/catena-device-grp

vrf

[no] vrf { <vrf-name> | <vrf-known-name> }

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	set vrf membership
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/config-monitor-erspan-src

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Configure ISIS VRF information
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-isis

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Display per-VRF information
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-ospf3

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Configure VRF information
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-eigrp

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Display per-VRF information
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-ospf

vrf

{ vrf <name> } | { no vrf <name> }

Syntax Description

no	Negate a command or set its defaults
vrf	ITD service vrf
<i>name</i>	ITD Service VRF name

Command Mode

- /exec/configure/itd

vrf

[no] vrf <vrf-cfg-name>

Syntax Description

<i>vrf-cfg-name</i>	VRF name
vrf	Virtual Router Context
no	(Optional) Negate a command or set its defaults

Command Mode

- /exec/configure/router-bgp/router-bgp-bmp-server

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Virtual Router Context
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/router-bgp

vrf

[no] vrf <vrf-name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrf	Configure vrf for PLB service
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/plb

vrf

{ { no | default } vrf |

Syntax Description

no	
default	Set a command to its defaults
vrf	Configure IP SLAs for a VPN Routing/Forwarding instance

Command Mode

- /exec/configure/ip-sla/udp /exec/configure/ip-sla/jitter /exec/configure/ip-sla/tcp /exec/configure/ip-sla/icmpEcho /exec/configure/ip-sla/dns /exec/configure/ip-sla/http

vrf

```
{ { vrf { <vrf-name> | <vrf-known-name> } } | no vrf }
```

Syntax Description

no	Negate a command or set its defaults
vrf	Display per-VRF information
<i>vrf-name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/configngoamconnectcheck

vrf context

vrf context <vrf-name> | no vrf context { <vrf-name> | <vrf-name> }

Syntax Description

no	Negate a command or set its defaults
vrf	Configure VRF parameters
context	Create VRF and enter VRF mode
<i>vrf-name</i>	VRF name
<i>vrf-name</i>	VRF name
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure

vrf default static

```
{ vrf default { static <profile-name> | dynamic } } | { no vrf default }
```

Syntax Description

no	Negate a command or set its defaults
vrf	VRF name
default	Default (wildcard). Match any vrf when there is no specific vrf mapping configured
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server

Command Mode

- /exec/configure/profile-map-global

vrf member

vrf member <vrf-name> | no vrf member [<vrf-name>]

Syntax Description

no	Negate a command or set its defaults
vrf	Configure VRF parameters
member	Set interface's VRF membership
<i>vrf-name</i>	VRF name

Command Mode

- /exec/configure/if-igp /exec/configure/if-mgmt-ether

vrf member

vrf member { <vrf_name> | <vrf-known-name> } | no vrf member [<vrf_name> | <vrf-known-name>]

Syntax Description

no	Negate a command or set its defaults
vrf	Configure VPN Routing/Forwarding table
member	Set route's VRF membership
<i>vrf_name</i>	VRF name
<i>vrf-known-name</i>	Known VRF name

Command Mode

- /exec/configure/track

vrf static

{ vrf <vrf-name> { static <profile-name> | dynamic } } | { no vrf <vrf-name> }

Syntax Description

no	Negate a command or set its defaults
vrf	VRF name
<i>vrf-name</i>	VRF name
static	Static Profile Map: Configure profile name via CLI
<i>profile-name</i>	Static Profile Map: Configure profile name via CLI
dynamic	Dynamic Profile Map: Retrieve profile name from the external server

Command Mode

- /exec/configure/profile-map-global

vrrp

[no] vrrp <vr_id>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrp	VRRP configuration commands
<i>vr_id</i>	IPv4 VR group number

Command Mode

- /exec/configure/if-legacy-eth /exec/configure/if-ethernet /exec/configure/if-port-channel /exec/configure/if-vlan-common /exec/configure/if-eth-any

vrrp bfd

```
{ vrrp bfd <peer_intf_ip> | no vrrp bfd [ <peer_intf_ip> ] }
```

Syntax Description

vrrp	VRRP configuration commands
bfd	BFD protocol
<i>peer_intf_ip</i>	Neighbor IP address
no	Negate a command or set its defaults

Command Mode

- /exec/configure/if-eth-any/vrrp

vrrpv2

[no] vrrpv2

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrpv2	Enable VRRPv2 compatibility mode

Command Mode

- /exec/configure/if-eth-any/vrrpv3

vrrpv3

[no] vrrpv3

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrpv3	VRRPv3 configuration commands

Command Mode

- /exec/configure

vrrpv3 address-family

[no] vrrpv3 <group_id> address-family <opt_v6>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrpv3	Configure VRRPv3 group parameters
address-family	IPV6 address family
<i>opt_v6</i>	Enter ipv6
<i>group_id</i>	VRRP Group ID

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan

vrrpv3 address-family

[no] vrrpv3 <group_id> address-family <opt_v4>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrpv3	Configure VRRPv3 group parameters
address-family	IPV4 address family
<i>opt_v4</i>	Enter ipv4
<i>group_id</i>	VRRP Group ID

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan

vrrs leader

[no] vrrs leader <tag>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrs	VRRS-related commands
leader	Name of VRRS tag for which this group is the leader
<i>tag</i>	VRRS tag to lead

Command Mode

- /exec/configure/if-eth-any/vrrpv3

vrrs pathway

[no] vrrs pathway <name>

Syntax Description

no	(Optional) Negate a command or set its defaults
vrrs	VRRS Interface configuration commands
pathway	Configure a VRRS pathway
<i>name</i>	Name of the VRRS tag to associate with pathway

Command Mode

- /exec/configure/if-eth-any /exec/configure/if-vlan

vsh

| vsh

Syntax Description

	Pipe command output to filter
vsh	the shell that understands cli command

Command Mode

- /output

vtp

[no] vtp

Syntax Description

no	(Optional) Negate a command or set its defaults
vtp	Enable VTP on this interface

Command Mode

- /exec/configure/if-switching

vtp domain

vtp domain <domain_name>

Syntax Description

vtp	Configure global VTP state
domain	Set the name of the VTP administrative domain
<i>domain_name</i>	The ascii name for the VTP administrative domain

Command Mode

- /exec/configure

vtp file

vtp file <file_name> | no vtp file

Syntax Description

no	Negate a command or set its defaults
vtp	Configure global VTP state
file	Set the name of the VTP file name
<i>file_name</i>	URI for vlan.dat

Command Mode

- /exec/configure

vtp mode

vtp mode <mode-name> | no vtp mode

Syntax Description

no	Negate a command or set its defaults
vtp	Configure global VTP state
mode	Configure VTP device mode
<i>mode-name</i>	

Command Mode

- /exec/configure

vtp password

vtp password <password_name> | no vtp password

Syntax Description

no	Negate a command or set its defaults
vtp	Configure global VTP state
password	Set the password for the VTP administrative domain
<i>password_name</i>	The ascii password for the VTP administrative domain

Command Mode

- /exec/configure

vtp pruning

vtp pruning | no vtp pruning

Syntax Description

no	Negate a command or set its defaults
vtp	Configure global VTP state
pruning	Set the administrative domain to permit pruning

Command Mode

- /exec/configure

vtp version

vtp version <version_num> | no vtp version

Syntax Description

no	Negate a command or set its defaults
vtp	Configure global VTP state
version	Set the administrative domain to VTP version
<i>version_num</i>	Set the administrative domain to VTP version

Command Mode

- /exec/configure



W Commands

- [wait-igp-convergence](#), on page 4924
- [watch](#), on page 4925
- [watch service action apply-acl](#), on page 4926
- [watchlist](#), on page 4927
- [watchlist](#), on page 4928
- [wc](#), on page 4929
- [wedge bmc ip-addr](#), on page 4930
- [weight](#), on page 4931
- [weight](#), on page 4932
- [weight](#), on page 4933
- [weight](#), on page 4934
- [where](#), on page 4935
- [where detail](#), on page 4936
- [window-size](#), on page 4937
- [wred-queue qos-group-map queue-only](#), on page 4938
- [write erase](#), on page 4939
- [write erase boot](#), on page 4940
- [write erase debug](#), on page 4941
- [write erase poap](#), on page 4942
- [wrr-queue qos-group-map](#), on page 4943
- [wrr unicast-bandwidth](#), on page 4944
- [wwn vsan vsan-wwn](#), on page 4945

wait-igp-convergence

[no] wait-igp-convergence

Syntax Description

no	(Optional) Negate a command or set its defaults
wait-igp-convergence	Delay initial bestpath until redistributed IGP's have converged

Command Mode

- /exec/configure/router-bgp/router-bgp-af-ipv4 /exec/configure/router-bgp/router-bgp-vrf-af-ipv4
/exec/configure/router-bgp/router-bgp-af-ipv6 /exec/configure/router-bgp/router-bgp-vrf-af-ipv6

watch

watch [differences] [interval <time>] <watch_cmd>

Syntax Description

watch	execute a program periodically
differences	(Optional) highlight the differences
interval	(Optional) watch interval
<i>time</i>	(Optional) interval in seconds
<i>watch_cmd</i>	enter the command you want to watch

Command Mode

- /exec

watch service action apply-acl

[no] watch service <service-name> action apply-acl <acl-name> | no watch service

Syntax Description

no	(Optional) Negate a command or set its defaults
watch	Watch a pod/service
service	The pod or service to watch
<i>service-name</i>	Name of the service/pod to watch
action	Action to be applied
apply-acl	Change ACL config
<i>acl-name</i>	Name of the acl to apply

Command Mode

- /exec/configure/kubernetes

watchlist

[no] watchlist <watchlistname>

Syntax Description

watchlist	Specify POSTCARD watchlist to use
<i>watchlistname</i>	Name of watchlist

Command Mode

- /exec/configure/config-postcard-monitor

watchlist

[no] watchlist <watchlistname>

Syntax Description

watchlist	Specify INT watchlist to use
<i>watchlistname</i>	Name of watchlist

Command Mode

- /exec/configure/config-int-monitor

WC

| wc [-c | -l | -w]

Syntax Description

	Pipe command output to filter
wc	Count words, lines, characters
-c	(Optional) Output character count
-l	(Optional) Output line count
-w	(Optional) Output word count

Command Mode

- /output

wedge bmc ip-addr

[no] wedge bmc ip-addr { <ip> | <ip_v6> }

Syntax Description

no	(Optional) Negate a command or set its defaults
wedge	Configure wedge Board Management controller ip address
bmc	Board Management Controller ip address
ip-addr	BMC ip address
<i>ip</i>	ip address

Command Mode

- /exec/configure

weight

```
{ weight <weight> } | { { no | default } weight [ <weight> ] }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
weight	Set default weight for routes from this neighbor
<i>weight</i>	Default weight

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-mdt

weight

[no] weight <weight-value>

Syntax Description

no	(Optional) Negate a command or set its defaults
weight	weight for traffic distribution
<i>weight-value</i>	weight value

Command Mode

- /exec/configure/itd-dg-node

weight

```
{ weight <weight> } | { { no | default } weight [ <weight> ] }
```

Syntax Description

no	Negate a command or set its defaults
default	Inherit values from a peer template
weight	Set default weight for routes from this neighbor
<i>weight</i>	Default weight

Command Mode

- /exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv4
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-vpnv6
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv4-label
/exec/configure/router-bgp/router-bgp-neighbor/router-bgp-neighbor-af-ipv6-label

weight

weight <weight-value> | no weight

Syntax Description

no	Negate a command or set its defaults
weight	Configure weight of node for traffic distribution
<i>weight-value</i>	weight value

Command Mode

- /exec/configure/plb-dg-node

where

where

Syntax Description

where	shows the cli context you are in
-------	----------------------------------

Command Mode

- /global

where detail

where detail

Syntax Description

where	shows the cli context you are in
detail	shows each entry on separate line

Command Mode

- /global

window-size

[no] window-size <size>

Syntax Description

window-size	Configure Window size
<i>size</i>	window size value

Command Mode

- /exec/configure/macsec-policy

wred-queue qos-group-map queue-only

[no] wred-queue qos-group-map queue-only { <qid> }

Syntax Description

no	(Optional) Negate the command
wred-queue	Enable queue based ECN marking for specific qos-group
queue-only	Enable queue based ECN marking
qos-group-map	Qid value
<i>qid</i>	Provide qos-group value

Command Mode

- /exec/configure

write erase

write erase

Syntax Description

write	Write current configuration
erase	Destroys the configuration on persistent media

Command Mode

- /exec

Usage Guidelines

You can erase the configuration on your device to return to the configuration defaults. In this context, **configuration** refers to the startup configuration as displayed by the **show startup** command. No other internal application or process states are cleared. To remove all application persistency files such as patch rpms, third party rpms, and application configuration in the /etc directory other than configuration, use the **install reset** command.

write erase boot

write erase boot

Syntax Description

write	Write current configuration
erase	Destroys the configuration on persistent media
boot	Destroys boot configuration on persistent media

Command Mode

- /exec

write erase debug

write erase debug

Syntax Description

write	Write current configuration
erase	Destroys the configuration on persistent media
debug	Destroys debug configuration on persistent media

Command Mode

- /exec

write erase poap

write erase poap

Syntax Description

write	Write current configuration
erase	Destroys the configuration on persistent media
poap	Removes System-wide POAP disable configuration on persistent media

Command Mode

- /exec

wrr-queue qos-group-map

[no] wrr-queue qos-group-map <qid> { <cos> } +

Syntax Description

no	(Optional) Negate the command
wrr-queue	Map traffic priority (QG) values to L3 Multicast Queues
qos-group-map	Qid value
<i>qid</i>	Provide qid value
<i>cos</i>	Provide qos-group-map value

Command Mode

- /exec/configure

wrr unicast-bandwidth

[no] wrr unicast-bandwidth <bw>

Syntax Description

no	(Optional) Negate the command
wrr	Configure Unicast Traffic Bandwidth Percentage
unicast-bandwidth	Specify rate as percentage of interface data-rate
<i>bw</i>	Value in percentage (Default is set to 50)

Command Mode

- /exec/configure

wwn vsan vsan-wwn

wwn vsan <i0> vsan-wwn <wwn1> | no

Syntax Description

<i>vsan</i>	<i0>
no	Negate a command or set its defaults
wwn	Set secondary base MAC addr and range for additional WWNs
<i>i0</i>	Enter the vsan id
vsan-wwn	vsan-wwn for vsan in interop mode 4
<i>wwn1</i>	Enter wwn for vsan in interop mode 4

Command Mode

- /exec/configure



X Commands

- [xconnect](#), on page 4948
- [xml](#), on page 4949
- [xml](#), on page 4950
- [xml server max-session](#), on page 4951
- [xml server rm-shm](#), on page 4952
- [xml server terminate session](#), on page 4953
- [xml server timeout](#), on page 4954
- [xml server validate](#), on page 4955
- [xml server xml-debug](#), on page 4956
- [xmlagent](#), on page 4957
- [xmlin](#), on page 4958
- [xmlin](#), on page 4959
- [xmlin](#), on page 4960
- [xmlin](#), on page 4961
- [xmlout](#), on page 4962

xconnect

xconnect | no xconnect

Syntax Description

no	Negate a command or set its defaults
xconnect	Enable cross connect on this VLAN

Command Mode

- /exec/configure/vlan

xml

| xml

Syntax Description

	Pipe command output to filter
xml	output in xml format (according to .xsd definitions)

Command Mode

- /output

xml

| xml

Syntax Description

	Pipe command output to filter
xml	output in xml format (according to .xsd definitions)

Command Mode

- /output

xml server max-session

[no] xml server max-session <number>

Syntax Description

no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml agent server
max-session	configure maximum number of xml sessions allowed
<i>number</i>	number of the sessions

Command Mode

- /exec/configure

xml server rm-shm

xml server rm-shm

Syntax Description

xml	xml agent
server	xml agent server
rm-shm	remove shm. SHOULD BE USED WITH CAUTION

Command Mode

- /exec/configure

xml server terminate session

xml server terminate session <session_id>

Syntax Description

xml	xml agent
server	xml agent server
terminate	command to terminate an XML session
session	terminate an XML session
<i>session_id</i>	sessions number

Command Mode

- /exec

xml server timeout

[no] xml server timeout <value> [<session_id>]

Syntax Description

no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml agent server
timeout	configure xml agent session timeout
<i>value</i>	timeout in seconds
<i>session_id</i>	(Optional) xml agent session id

Command Mode

- /exec/configure

xml server validate

[no] xml server validate { all | <session_id> }

Syntax Description

no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml agent server
validate	command to validate an XML session
all	all sessions
<i>session_id</i>	session number

Command Mode

- /exec/configure

xml server xml-debug

[no] xml server xml-debug

Syntax Description

no	(Optional) Negate a command or set its defaults
xml	xml agent
server	xml server
xml-debug	xml server xml-debug

Command Mode

- /exec/configure

xmlagent

xmlagent

Syntax Description

xmlagent	to run xmlagent
----------	-----------------

Command Mode

- /exec

xmlin

xmlin

Syntax Description

xmlin	Convert CLI commands to their XML formats
-------	---

Command Mode

- /exec

xmlin

| xmlin

Syntax Description

	Pipe command output to filter
xmlin	Convert CLI show commands to their XML formats

Command Mode

- /output

xmlin

xmlin

Syntax Description

xmlin	Convert CLI commands to their XML formats
-------	---

Command Mode

- /exec

xmlin

| xmlin

Syntax Description

	Pipe command output to filter
xmlin	Convert CLI show commands to their XML formats

Command Mode

- /output

xmlout

| xmlout

Syntax Description

	Pipe command output to filter
xmlout	output in xml format (according to the latest .xsd version)

Command Mode

- /output