



Release Notes for Cisco Catalyst IE9300 Rugged Series Switches, and Cisco Catalyst ESS9300 Embedded Series Switch, Cisco IOS XE Dublin 17.10.x

First Published: 2022-12-01

Last Modified: 2023-01-16

Cisco Catalyst IE9300 Rugged Series Switches and Cisco Catalyst ESS9300 Embedded Series Switch

This document provides release information for the following Catalyst IE switches:

- Cisco Catalyst IE9310 GE Fiber
- Cisco Catalyst IE9320 GE Fiber
- Cisco Catalyst ESS9300 Embedded Series Switch

Cisco Catalyst IE9300 Rugged Series Switches provide rugged and secure switching infrastructure for harsh environments. It is suitable for industrial Ethernet applications, including manufacturing, utility substations, intelligent transportation systems (ITSs), rail transportation, and other similar deployments.

The switch fulfills the need for a high-density SFP, rack-, or wall-mount switch that can function as a software-defined (SD)-Access fabric edge. It provides end-to-end architectural uniformity in the Cisco Digital Network Architecture (DNA) for Internet of Things (IoT) connected communities and extended enterprises.

In industrial environments, the switch can be connected to any Ethernet-enabled industrial communication devices. These devices include programmable logic controllers (PLCs), human-machine interfaces (HMIs), drives, sensors, and input and output (I/O) devices.

The Cisco Catalyst ESS9300 Embedded Series Switch is a Small Form Factor (SFF) Ruggedized Gige Embedded platform for tactical, outdoor, and mobile environments. The compact design simplifies integration and offers the system integrator the ability to use the ESS9300 in a wide variety of applications. The Cisco ESS 9300 consists of one switch card. There are no cooling plates sold with it. It is up to the system integrator to design a thermal solution. The ESS-9300-10X-E board supports up to 10 ports of 10 GE fiber. Thermal power is 35 Watts.



Note The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on standards documentation, or language that is used by a referenced third-party product.

New Features for Cisco Catalyst IE9300 Rugged Series Switches and Cisco Catalyst ESS9300 Embedded Series Switch

The following features apply to all versions of the IE9310 GE Fiber, IE9320 GE Fiber switches and the Cisco Catalyst ESS9300 Embedded Series Switch unless otherwise noted. The features are new in this release for the switches.

Table 1: Cisco Catalyst IE9300 Rugged Series Switches

Feature Name	License Level	Description	Supported Switches
Precision Time Protocol alarms	Network Essentials	PTP alarms can help you manage and monitor PTP on the switch. You can configure the PTP alarms to trigger the external alarm relay output and send system messages to a syslog server.	<ul style="list-style-type: none"> • IE-9310-26S2C-A • IE-9310-26S2C-E • IE-9320-26S2C-A • IE-9320-26S2C-E
Layer 2 Network Address Translation	Network Essentials	One-to-one Layer 2 NAT (Network Address Translation) is a service that allows the assignment of a unique public IP address to an existing private IP address (end device). Layer 2 NAT enables the end device to communicate on both the private and public subnets.	<ul style="list-style-type: none"> • IE-9310-26S2C-A • IE-9310-26S2C-E • IE-9320-26S2C-A • IE-9320-26S2C-E

Table 2: Cisco Catalyst ESS9300 Embedded Series Switch

Feature Name	License Level	Description	Supported Switches
Network Advantage License	Network Advantage	Release 17.10.1 offers the Network Advantage License level for the Cisco Catalyst ESS9300 Embedded Series Switch. Note Only MACsec 256 bit feature is supported.	Cisco Catalyst ESS9300 Embedded Series Switch

The following table describes the features available in Network Essentials for the Cisco Catalyst IE 9300 and ESS9300 Embedded Series Switch:

Table 3: Network Essentials

Layer 2 Switching	IEEE 802.1Q VLAN Trunking, 802.1W Spanning Tree Rapid Reconfiguration, 802.1ab LLDP (Link Layer Discovery Protocol), 802.1s - Multiple Spanning Tree Protocol (MSTP) Standard Compliance, 802.1s VLAN Multiple Spanning Trees, 802.1Q Tunneling, 802.3 standard, Unidirectional Link Detection (UDLD), Cisco Discovery Protocol, unicast MAC filter, VLAN Trunk Protocol (VTP) v2 and v3, EtherChannel, voice VLAN, Per-VLAN Spanning Tree Plus (PVST+), and Rapid STP (RSTP)
Multicast	IGMPv1, v2, v3 snooping, IGMP filtering, IGMP querier
Management	Web UI, MIB, SmartPort, Simple Network Management Protocol (SNMP), syslog, Dynamic Host Configuration Protocol (DHCP) server, Switched Port Analyzer (SPAN) session (1), Full Flexible NetFlow (FnF), Network Time Protocol (NTP)
Security	Zeroization, secure boot, port security, IEEE 802.1X, DHCP snooping, dynamic Address Resolution Protocol (ARP) inspection, IP Source Guard, private VLAN. MAC authentication bypass, 802.1X multidomain authentication, storm control - unicast, multicast, broadcast, Secure Copy (SCP), Secure Shell (SSH), SNMPv3, TACACS+, RADIUS server/client, MAC address notification, Bridge Protocol Data Unit (BPDU) guard, hardware physical alarm inputs (2), and relay output (1)
Quality of service (QoS)	Ingress policing, rate limit, egress queuing/shaping, autoQoS

Layer 2 IPv6	IPv6 host support, HTTP over IPv6, SNMP over IPv6
Precision Time Protocol alarms	PTP alarms can help you manage and monitor PTP on the switch. You can configure the PTP alarms to trigger the external alarm relay output and send system messages to a syslog server.
Layer 2 Network Address Translation	One-to-one Layer 2 NAT (Network Address Translation) is a service that allows the assignment of a unique public IP address to an existing private IP address (end device). Layer 2 NAT enables the end device to communicate on both the private and public subnets.

The following table describes the features available in Network Advantage for the Cisco Catalyst IE 9300 Switch:

Table 4: Network Advantage License

IP Routing	OSPF (V2 and V3), RIP (V1 and V2), ISIS (for IPv4 and IPv6), EIGRP (for IPv4 and IPv6), PBR (Policy Based Routing)
Virtualization	VRF-lite
Security	MACsec-256
IP Multicast	PIM sparse mode (PIM-SM), PIM dense mode (PIM-DM) and PIM Sparse dense mode
High Availability	Bidirectional Forwarding Detection (BFD) echo mode, HSRP (IPv4 and IPv6), VRRP (IPv4 and IPv6)



Important Only MACsec 256 is supported on ESS9300 as part of Network Advantage License. All other Network Advantage features do not apply to the ESS9300 at this time.

Important Notes

Accessing Hidden Commands

Hidden commands have always been present in Cisco IOS XE, but were not equipped with CLI help. This means that entering a question mark (?) at the system prompt did not display the list of available commands. Such hidden commands are only meant to assist Cisco TAC in advanced troubleshooting and are therefore not documented. For more information about CLI help, see the *Using the Command-Line Interface* → *Understanding the Help System* chapter of the Command Reference document.

This section provides information about hidden commands in Cisco IOS XE and the security measures in place, when they are accessed. Hidden commands are meant to assist Cisco TAC in advanced troubleshooting

and are therefore not documented. For more information about CLI help, see the *Using the Command-Line Interface* → *Understanding the Help System* chapter of the Command Reference document.

Hidden commands are available under:

- Category 1: Hidden commands in privileged or User EXEC mode. Begin by entering the **service internal** command to access these commands.
- Category 2: Hidden commands in one of the configuration modes (global, interface, and so on). These commands do not require the **service internal** command.

Further, the following applies to hidden commands under Category 1 and 2:

- The commands have CLI help. Entering a question mark (?) at the system prompt displays the list of available commands.



Note For Category 1, enter the **service internal** command before you enter the question mark; you do not have to do this for Category 2.

- The system generates a %PARSER-5-HIDDEN syslog message when the command is used. For example:

```
*Feb 14 10:44:37.917: %PARSER-5-HIDDEN: Warning!!! 'show processes memory old-header '
is a hidden command.
Use of this command is not recommended/supported and will be removed in future.
```

Apart from category 1 and 2, there remain internal commands that are displayed on the CLI, for which the system does NOT generate the %PARSER-5-HIDDEN syslog message.



Important We recommend that you use *any* hidden command only under TAC supervision. If you find that you are using a hidden command, open a TAC case for help with finding another way of collecting the same information as the hidden command (for a hidden EXEC mode command), or to configure the same functionality (for a hidden configuration mode command) using non-hidden commands.

Switch Model Numbers

Cisco Catalyst IE9300 Rugged Series Switches

The following table lists the supported IE9300 series hardware models and the default license levels that they are delivered with.

Model Number	Default License Level	Stacking Support	Description
IE-9310-26S2C-A	Network Advantage	No	<ul style="list-style-type: none"> • <i>Total ports:</i> 28 • <i>SFP uplinks:</i> 4x 1-Gb SFP • <i>SFP downlinks:</i> 22x 1-Gb SFP, 2x 1-Gb dual-media ports • <i>Power supplies:</i> Support for field-replaceable, redundant AC or DC power supplies.
IE-9310-26S2C-E	Network Essentials		
IE-9320-26S2C-A	Network Advantage	Yes	
IE-9320-26S2C-E	Network Essentials		

All Cisco Catalyst IE9300 Rugged Series Switches have 4 GB of DRAM, four alarm inputs, and one alarm output. Other I/O include the following:

- SD-cards socket
- Power input
- RJ-45 (RS-232) console
- Micro-USB console
- USB-A host port



Note This document uses the term IE9310 GE Fiber when referring to both IE-9310-26S2C-A and IE-9310-26S2C-E switches. This document uses the term IE9320 GE Fiber when referring to both IE-9320-26S2C-A and IE-9320-26S2C-E switches.

Cisco Catalyst ESS9300 Embedded Series Switch

The ESS9300 is a ruggedized 10G embedded platform that is designed for embedded applications for tactical, outdoor, and mobile installations requiring low power, small size, and ruggedization. Its features include:

- Single board
- Small form-factor board size (110 x 85 mm; 4.3 x 3.3 in.)
- 10 ports of 10G: Enhanced Small Form-Factor Pluggable (SFP+)
- Ethernet management port (optional)
- RS-232 and USB console
- Common +3.3VDC and +5VDC power inputs
- Low power—35W (typical)
- 4 GB DDR4 DRAM

- 8 GB onboard eMMC flash storage (2.5 GB usable space)

Starting with release 17.10.1, both the Network Essentials license and the Network Advantage license are available. The features available in the two licenses follow the IE9300 series, with the exception of MACsec-256.

Table 5: Ordering Information

Product ID	Product Description
ESS-9300-10X-E	ESS9300 board, no cooling plate, Network Essentials software.
ESS9300-NW-A=	Cisco Network Advantage license for ESS9300 Series Spare.
Network Advantage License	Description
Security	MACsec-256

Upgrading the Switch Software

This section covers the various aspects of upgrading or downgrading the device software.

Finding the Software Version

The package files for the Cisco IOS XE software can be found on the system board flash device flash (flash:) or external SDFlash (sdflash:).

You can use the **show version** privileged EXEC command to see the software version that is running on your switch.



Note Although the **show version** output always shows the software image running on the switch, the model name shown at the end of this display is the factory configuration and does not change if you upgrade the software license.

You can also use the **dir filesystem:** privileged EXEC command to see the directory names of other software images that you might have stored in flash memory.

Software Images for Cisco IOS XE Dublin 17.10.x

The following table provides the filenames for the IOS XE 17.10.x software image for Cisco Catalyst IE9300 Rugged Series Switches and the Cisco Catalyst ESS9300 Embedded Series Switch.

Release	Image Type	Filename	Switch Model
Cisco IOS XE.17.10.1	Universal	ie9k_iosxe.17.10.01.SPA.bin	IE9300
	NPE	ie9k_iosxe_npe.17.10.01.SPA.bin	IE9300
			ESS9300

Software Installation Options

The following table lists the options for the **install** command for Cisco Catalyst IE9300 Rugged Series Switches and the Cisco Catalyst ESS9300 Embedded Series Switch.

To install and activate the specified file, and to commit changes to be persistent across reloads, enter the following command: **install add file filename [activate commit]**

Option	Description
abort	Abort the current install operation.
activate	Activate an installed package.
add	Install a package file to the system.
auto-abort-timer	Install auto-abort-timer.
autoupgrade	Initiate software auto-upgrade on all incompatible switches.
commit	Commit the changes to the load path.
deactivate	Deactivate an install package.
label	Add a label name to any installation point.
remove	Remove installed packages.
rollback	Rollback to a previous installation point.

Licensing

This section provides information about the licensing packages for features available on Cisco Catalyst IE9300 Rugged Series Switches and the Cisco Catalyst ESS9300 Embedded Series Switch.

License Levels

The software features available on Cisco Catalyst IE9300 Rugged Series Switches fall under these base or add-on license levels.

Base Licenses

- Network Essentials

- Network Advantage: Includes features available with the Network Essentials license and more.

Add-on Licenses

Add-on licenses require a Network Essentials or Network Advantage as a prerequisite. The features available with add-on license levels provide Cisco innovations on the switch, and on the Cisco Digital Network Architecture Center (Cisco DNA Center).

- DNA Essentials
- DNA Advantage: Includes features available with the DNA Essentials license and more.

To find information about platform support and to know which license levels a feature is available with, use Cisco Feature Navigator. To access Cisco Feature Navigator, go to <https://cfng.cisco.com>. An account on Cisco.com is not required.

Cisco Catalyst ESS9300 Embedded Series Switch

The software features available for the Cisco Catalyst ESS9300 Embedded Series Switch fall under these base license levels.

Base Licenses

- Network Essentials
- Network Advantage: Includes features available with the Network Essentials license and more.

To find information about platform support and to know which license levels a feature is available with, use Cisco Feature Navigator. To access Cisco Feature Navigator, go to <https://cfng.cisco.com>. An account on Cisco.com is not required.

Smart Licensing Using Policy

Smart Licensing Using Policy, which is an enhanced version of Smart Licensing, is the default and the only supported method to manage licenses.

Smart Licensing using Policy provides a licensing solution that does not interrupt the operations of your network. Instead, it enables a compliance relationship to account for the hardware and software licenses you purchase and use.

With this licensing model, you do not have to complete any licensing-specific operations, such as registering or generating keys before you start using the software and the licenses that are tied to it. Only export-controlled and enforced licenses require Cisco authorization *before* use. License usage is recorded on your device with timestamps, and the required workflows can be completed later.

Multiple options are available for license usage reporting – this depends on the topology you implement. You can use the Cisco Smart Licensing Utility (CSLU) Windows application, or report usage information directly to Cisco Smart Software Manager (CSSM). A provision for offline reporting for air-gapped networks, where you download usage information and upload to CSSM, is also available.

Starting with this release, Smart Licensing Using Policy is automatically enabled on the device. This is also the case when you upgrade to this release.

By default, your Smart Account and Virtual Account in CSSM is enabled for Smart Licensing Using Policy.

Caveats

Caveats describe unexpected behavior in Cisco IOS XE releases. Caveats listed as open in a prior release are carried forward to the next release as either open or resolved.

Open Caveats

There are no open caveats for this release.

Resolved Caveats

Identifier	Description
CSCwc33322	IOX: Observing Disk space issue for Cisco Cyber Vision app installation through sensor extension.
CSCwc04550	Unable to Change PTP Profile via Web UI.
CSCwc06817	Incremental Memory leaks seen with traffic (link trigger scenarios) over rep ring.
CSCwd09742	Boot failed, due to mounting issues of perma locked device.

Troubleshooting

For the most up-to-date, detailed troubleshooting information, see the Cisco TAC website at this URL:

<https://www.cisco.com/en/US/support/index.html>

Go to **Product Support** and select your product from the list or enter the name of your product. Look under Troubleshoot and Alerts, to find information for the problem that you are experiencing.

Related Documentation

Information about Cisco IOS XE at this URL: <https://www.cisco.com/c/en/us/products/ios-nx-os-software/ios-xe/index.html>.

Information about Cisco Catalyst IE9300 Rugged Series Switches is at this URL: <https://www.cisco.com/c/en/us/products/ios-nx-os-software/ios-xe/index.html>

Information about the Cisco Catalyst ESS9300 Embedded Series Switch is at this URL: <https://www.cisco.com/c/en/us/support/switches/catalyst-ess-9300-10x-embedded-switch/model.html>

Cisco Validated Designs documents at this URL: <https://www.cisco.com/go/designzone>

To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <http://www.cisco.com/go/mibs>

Communications, Services, and Additional Information

- To receive timely, relevant information from Cisco, sign up at [Cisco Profile Manager](#).
- To get the business impact you're looking for with the technologies that matter, visit [Cisco Services](#).
- To submit a service request, visit [Cisco Support](#).
- To discover and browse secure, validated enterprise-class apps, products, solutions, and services, visit [Cisco DevNet](#).
- To obtain general networking, training, and certification titles, visit [Cisco Press](#).
- To find warranty information for a specific product or product family, access [Cisco Warranty Finder](#).

Cisco Bug Search Tool

[Cisco Bug Search Tool](#) (BST) is a gateway to the Cisco bug-tracking system, which maintains a comprehensive list of defects and vulnerabilities in Cisco products and software. The BST provides you with detailed defect information about your products and software.

Documentation Feedback

To provide feedback about Cisco technical documentation, use the feedback form available in the right pane of every online document.

