



New and Changed Information

This chapter contains the following sections:

- [New and Changed Information, on page 1](#)

New and Changed Information

This table summarizes the new and changed features for the *Cisco Nexus 3400-S NX-OS Interfaces Configuration Guide* and where they are documented.

Table 1: New and Changed Features

Feature	Description	Changed in Release	Where Documented
Hardware Profile Modes	Added support for new hardware profile port mode (160 x 10G/25G + 8 x 100G)	9.3(5)	Information about Breakout Interfaces
40G on 100G LEM	Added support for 40G to 100G LEM on Cisco Nexus 3408-S Switches	9.3(5)	Information about Breakout Interfaces
Hardware Forwarded IP/IPv6 Interface Statistics	Added support for configuring hardware forwarded IPv4/IPv6 interface statistics.	9.3(5)	Configuring Hardware Forwarded IPv4/IPv6 Interface Statistics
Subinterfaces Port Counters	Added support to additional subinterfaces port counters	9.3(4)	Monitoring the Layer 3 Interfaces Configuration Examples for Layer 3 Interfaces
Hardware Profile Modes	Added support for two hardware support modes	9.3(4)	Information about Breakout Interfaces
Native 50G support on Cisco Nexus 3432D-S switches	Cisco Nexus 3432D-S switches	9.3(3)	Information about Breakout Interfaces

