



I N D E X

A

- AAA down policy, NAC Layer 2 IP validation [1-9](#)
- abbreviating commands [2-4](#)
- ABRs [35-24](#)
- AC (command switch) [5-10](#)
- access-class command [32-19](#)
- access control entries
 - See ACEs
- access-denied response, VMPS [12-28](#)
- access groups
 - applying IPv4 ACLs to interfaces [32-20](#)
 - Layer 2 [32-20](#)
 - Layer 3 [32-20](#)
- accessing
 - clusters, switch [5-13](#)
 - command switches [5-11](#)
 - member switches [5-13](#)
 - switch clusters [5-13](#)
- access lists
 - See ACLs
- access ports
 - and Layer 2 protocol tunneling [16-11](#)
 - defined [10-3](#)
 - in switch clusters [5-9](#)
- access template [7-1](#)
- accounting
 - with 802.1x [9-32](#)
 - with IEEE 802.1x [9-8](#)
 - with RADIUS [8-28](#)
 - with TACACS+ [8-11, 8-17](#)
- ACEs
 - and QoS [33-7](#)
 - defined [32-2](#)
 - Ethernet [32-2](#)
 - IP [32-2](#)
- ACLs
 - ACEs [32-2](#)
 - any keyword [32-12](#)
 - applying
 - on bridged packets [32-38](#)
 - on multicast packets [32-39](#)
 - on routed packets [32-38](#)
 - on switched packets [32-37](#)
 - time ranges to [32-16](#)
 - to an interface [32-19, 38-7](#)
 - to IPv6 interfaces [38-7](#)
 - to QoS [33-7](#)
 - classifying traffic for QoS [33-44](#)
 - comments in [32-18](#)
 - compiling [32-21](#)
 - defined [32-1, 32-7](#)
 - examples of [32-21, 33-44](#)
 - extended IP, configuring for QoS classification [33-45](#)
 - extended IPv4
 - creating [32-10](#)
 - matching criteria [32-7](#)
 - hardware and software handling [32-21](#)
 - host keyword [32-12](#)

ACLs (continued)

IP

- creating 32-7
- fragments and QoS guidelines 33-33
- implicit deny 32-9, 32-13, 32-15
- implicit masks 32-9
- matching criteria 32-7
- undefined 32-20

IPv4

- applying to interfaces 32-19
- creating 32-7
- matching criteria 32-7
- named 32-14
- numbers 32-8
- terminal lines, setting on 32-18
- unsupported features 32-6

IPv6

- applying to interfaces 38-7
- configuring 38-3, 38-5
- displaying 38-8
- interactions with other features 38-4
- limitations 38-3
- matching criteria 38-3
- named 38-3
- precedence of 38-2
- supported 38-2
- unsupported features 38-3

Layer 4 information in 32-37

logging messages 32-8

MAC extended 32-26, 33-46

matching 32-7, 32-20, 38-3

monitoring 32-40, 38-8

named, IPv4 32-14

named, IPv6 38-3

names 38-4

number per QoS class map 33-33

port 32-2, 38-1

precedence of 32-2

QoS 33-7, 33-44

ACLs (continued)

resequencing entries 32-14

router 32-2, 38-1

router ACLs and VLAN map configuration guidelines 32-36

standard IP, configuring for QoS classification 33-44

standard IPv4

- creating 32-9

- matching criteria 32-7

support for 1-8

support in hardware 32-21

time ranges 32-16

types supported 32-2

unsupported features, IPv4 32-6

unsupported features, IPv6 38-3

using router ACLs with VLAN maps 32-36

VLAN maps

- configuration guidelines 32-29

- configuring 32-28

active links 20-2

active router 39-1

address aliasing 23-2

addresses

- displaying the MAC address table 6-26

dynamic

- accelerated aging 17-8

- changing the aging time 6-21

- default aging 17-8

- defined 6-19

- learning 6-20

- removing 6-22

MAC, discovering 6-26

multicast

- group address range 41-3

- STP address management 17-8

static

- adding and removing 6-24

- defined 6-19

address resolution 6-26, 35-8

- Address Resolution Protocol
 - See ARP
- adjacency tables, with CEF [35-72](#)
- administrative distances
 - defined [35-85](#)
 - OSPF [35-30](#)
 - routing protocol defaults [35-74](#)
- advanced IP services image [36-1](#)
- advertisements
 - CDP [25-1](#)
 - LLDP [26-2](#)
 - RIP [35-19](#)
 - VTP [12-19, 13-3](#)
- aggregatable global unicast addresses [36-3](#)
- aggregate addresses, BGP [35-57](#)
- aggregated ports
 - See EtherChannel
- aggregate policers [33-59](#)
- aggregate policing [1-10](#)
- aging, accelerating [17-8](#)
- aging time
 - accelerated
 - for MSTP [18-23](#)
 - for STP [17-8, 17-21](#)
 - MAC address table [6-21](#)
 - maximum
 - for MSTP [18-23, 18-24](#)
 - for STP [17-21, 17-22](#)
- alarms, RMON [29-3](#)
- allowed-VLAN list [12-21](#)
- application engines, redirecting traffic to [40-1](#)
- area border routers
 - See ABRs
- ARP
 - configuring [35-9](#)
 - defined [1-5, 6-26, 35-8](#)
 - encapsulation [35-10](#)
 - static cache configuration [35-9](#)
 - table
 - address resolution [6-26](#)
 - managing [6-26](#)
- ASBRs [35-24](#)
- AS-path filters, BGP [35-51](#)
- asymmetrical links, and IEEE 802.1Q tunneling [16-4](#)
- attributes, RADIUS
 - vendor-proprietary [8-31](#)
 - vendor-specific [8-29](#)
- audience [xliv](#)
- authentication
 - EIGRP [35-38](#)
 - HSRP [39-10](#)
 - local mode with AAA [8-36](#)
 - NTP associations [6-4](#)
 - RADIUS
 - key [8-21](#)
 - login [8-23](#)
 - TACACS+
 - defined [8-11](#)
 - key [8-13](#)
 - login [8-14](#)
 - See also port-based authentication
- authentication failed VLAN
 - See restricted VLAN
- authentication keys, and routing protocols [35-85](#)
- authoritative time source, described [6-2](#)
- authorization
 - with RADIUS [8-27](#)
 - with TACACS+ [8-11, 8-16](#)
- authorized ports with IEEE 802.1x [9-7](#)
- autoconfiguration [3-3](#)

- automatic discovery
 - considerations
 - beyond a noncandidate device [5-7](#)
 - brand new switches [5-9](#)
 - connectivity [5-4](#)
 - different VLANs [5-6](#)
 - management VLANs [5-7](#)
 - non-CDP-capable devices [5-6](#)
 - noncluster-capable devices [5-6](#)
 - routed ports [5-8](#)
 - in switch clusters [5-4](#)
 - See also CDP
 - automatic QoS
 - See QoS
 - automatic recovery, clusters [5-10](#)
 - See also HSRP
 - auto-MDIX
 - configuring [10-20](#)
 - described [10-20](#)
 - autonegotiation
 - duplex mode [1-3](#)
 - interface configuration guidelines [10-17](#)
 - mismatches [44-11](#)
 - autonomous system boundary routers
 - See ASBRs
 - autonomous systems, in BGP [35-45](#)
 - Auto-RP, described [41-6](#)
 - autosensing, port speed [1-3](#)
 - auxiliary VLAN
 - See voice VLAN
 - availability, features [1-6](#)
-
- B**
- BackboneFast
 - described [19-5](#)
 - disabling [19-14](#)
 - enabling [19-13](#)
 - support for [1-6](#)
 - backup interfaces
 - See Flex Links
 - backup links [20-2](#)
 - banners
 - configuring
 - login [6-19](#)
 - message-of-the-day login [6-18](#)
 - default configuration [6-17](#)
 - when displayed [6-17](#)
 - BGP
 - aggregate addresses [35-57](#)
 - aggregate routes, configuring [35-57](#)
 - CIDR [35-57](#)
 - clear commands [35-60](#)
 - community filtering [35-54](#)
 - configuring neighbors [35-55](#)
 - default configuration [35-42](#)
 - described [35-42](#)
 - enabling [35-45](#)
 - monitoring [35-60](#)
 - multipath support [35-49](#)
 - neighbors, types of [35-45](#)
 - path selection [35-49](#)
 - peers, configuring [35-55](#)
 - prefix filtering [35-53](#)
 - resetting sessions [35-48](#)
 - route dampening [35-59](#)
 - route maps [35-51](#)
 - route reflectors [35-58](#)
 - routing domain confederation [35-58](#)
 - routing session with multi-VRF CE [35-67](#)
 - show commands [35-60](#)
 - supernets [35-57](#)
 - support for [1-10](#)
 - Version 4 [35-42](#)
 - binding cluster group and HSRP group [39-11](#)

binding database

- address, DHCP server
 - See DHCP, Cisco IOS server database
- DHCP snooping
 - See DHCP snooping binding database

bindings

- address, Cisco IOS DHCP server [21-6](#)
- DHCP snooping database [21-7](#)
- IP source guard [21-15](#)

binding table, DHCP snooping

- See DHCP snooping binding database

blocking packets [24-7](#)

Boolean expressions in tracked lists [39-14](#)

booting

- boot loader, function of [3-2](#)
- boot process [3-2](#)
- manually [3-13](#)
- specific image [3-14](#)

boot loader

- accessing [3-14](#)
- described [3-2](#)
- environment variables [3-14](#)
- prompt [3-14](#)
- trap-door mechanism [3-2](#)

bootstrap router (BSR), described [41-6](#)

Border Gateway Protocol

- See BGP

BPDU

- error-disabled state [19-2](#)
- filtering [19-3](#)
- RSTP format [18-12](#)

BPDU filtering

- described [19-3](#)
- disabling [19-12](#)
- enabling [19-12](#)
- support for [1-6](#)

BPDU guard

- described [19-2](#)
- disabling [19-12](#)
- enabling [19-11](#)
- support for [1-6](#)

bridged packets, ACLs on [32-38](#)

bridge groups

- See fallback bridging

bridge protocol data unit

- See BPDU

broadcast flooding [35-16](#)

broadcast packets

- directed [35-13](#)
- flooded [35-13](#)

broadcast storm-control command [24-4](#)

broadcast storms [24-1, 35-13](#)

C

cables, monitoring for unidirectional links [27-1](#)

candidate switch

- automatic discovery [5-4](#)
- defined [5-3](#)
- requirements [5-3](#)

See also command switch, cluster standby group, and member switch

CA trustpoint

- configuring [8-45](#)
- defined [8-43](#)

caution, described [xliv](#)

CDP

- and trusted boundary [33-39](#)
- automatic discovery in switch clusters [5-4](#)
- configuring [25-2](#)
- default configuration [25-2](#)
- defined with LLDP [26-1](#)
- described [25-1](#)
- disabling for routing device [25-3 to 25-4](#)

CDP (continued)

- enabling and disabling
 - on an interface 25-4
 - on a switch 25-3
- Layer 2 protocol tunneling 16-8
- monitoring 25-4
- overview 25-1
- power negotiation extensions 10-6
- support for 1-5
- transmission timer and holdtime, setting 25-2
- updates 25-2

CEF

- defined 35-72
- enabling 35-73
- IPv6 36-14

CGMP

- as IGMP snooping learning method 23-9
- clearing cached group entries 41-51
- enabling server support 41-34
- joining multicast group 23-3
- overview 41-9
- server support only 41-9
- switch support of 1-4

CIDR 35-57**CipherSuites 8-44****Cisco 7960 IP Phone 15-1****Cisco Discovery Protocol**

See CDP

Cisco Express Forwarding

See CEF

Cisco Group Management Protocol

See CGMP

Cisco intelligent power management 10-6**Cisco IOS DHCP server**

See DHCP, Cisco IOS DHCP server

Cisco IOS File System

See IFS

Cisco Network Assistant

See Network Assistant

CiscoWorks 2000 1-4, 31-4**CIST regional root**

See MSTP

CIST root

See MSTP

classless interdomain routing

See CIDR

classless routing 35-6**class maps for QoS**

configuring 33-47

described 33-7

displaying 33-79

class of service

See CoS

clearing interfaces 10-29**CLI**

abbreviating commands 2-4

command modes 2-1

configuration logging 2-5

described 1-4

editing features

enabling and disabling 2-7

keystroke editing 2-7

wrapped lines 2-9

error messages 2-5

filtering command output 2-10

getting help 2-3

history

changing the buffer size 2-6

described 2-6

disabling 2-7

recalling commands 2-6

managing clusters 5-15

no and default forms of commands 2-4

client mode, VTP 13-3**client processes, tracking 39-12****clock**

See system clock

cluster requirements xlv

- clusters, switch
 - accessing [5-13](#)
 - automatic discovery [5-4](#)
 - automatic recovery [5-10](#)
 - benefits [1-2](#)
 - compatibility [5-4](#)
 - described [5-1](#)
 - LRE profile considerations [5-14](#)
 - managing
 - through CLI [5-15](#)
 - through SNMP [5-15](#)
 - planning [5-4](#)
 - planning considerations
 - automatic discovery [5-4](#)
 - automatic recovery [5-10](#)
 - CLI [5-15](#)
 - host names [5-13](#)
 - IP addresses [5-13](#)
 - LRE profiles [5-14](#)
 - passwords [5-14](#)
 - RADIUS [5-14](#)
 - SNMP [5-14](#), [5-15](#)
 - TACACS+ [5-14](#)
 - See also candidate switch, command switch, cluster standby group, member switch, and standby command switch
- cluster standby group
 - and HSRP group [39-11](#)
 - automatic recovery [5-12](#)
 - considerations [5-11](#)
 - defined [5-2](#)
 - requirements [5-3](#)
 - virtual IP address [5-11](#)
 - See also HSRP
- CNS [1-5](#)
 - Configuration Engine
 - configID, deviceID, hostname [4-3](#)
 - configuration service [4-2](#)
 - described [4-1](#)
 - event service [4-3](#)
 - embedded agents
 - described [4-5](#)
 - enabling automated configuration [4-6](#)
 - enabling configuration agent [4-9](#)
 - enabling event agent [4-8](#)
 - management functions [1-5](#)
- Coarse Wave Division Multiplexer
 - See CWDM SFPs
- command-line interface
 - See CLI
- command modes [2-1](#)
- commands
 - abbreviating [2-4](#)
 - no and default [2-4](#)
- commands, setting privilege levels [8-8](#)
- command switch
 - accessing [5-11](#)
 - active (AC) [5-10](#)
 - configuration conflicts [44-11](#)
 - defined [5-2](#)
 - passive (PC) [5-10](#)
 - password privilege levels [5-15](#)
 - priority [5-10](#)
 - recovery
 - from command-switch failure [5-10](#), [44-7](#)
 - from lost member connectivity [44-11](#)
 - redundant [5-10](#)
 - replacing
 - with another switch [44-9](#)
 - with cluster member [44-8](#)
 - requirements [5-3](#)
 - standby (SC) [5-10](#)

command switch (continued)

See also candidate switch, cluster standby group, member switch, and standby command switch

community list, BGP [35-54](#)

community ports [14-2](#)

community strings

configuring [5-14, 31-8](#)

for cluster switches [31-4](#)

in clusters [5-14](#)

overview [31-4](#)

SNMP [5-14](#)

community VLANs [14-2, 14-3](#)

compatibility, feature [24-11](#)

config.text [3-12](#)

configurable leave timer, IGMP [23-6](#)

configuration, initial

defaults [1-12](#)

Express Setup [1-2](#)

See also getting started guide and hardware installation guide

configuration changes, logging [30-10](#)

configuration conflicts, recovering from lost member connectivity [44-11](#)

configuration examples, network [1-15](#)

configuration files

clearing the startup configuration [B-19](#)

creating using a text editor [B-10](#)

default name [3-12](#)

deleting a stored configuration [B-19](#)

described [B-8](#)

downloading

automatically [3-12](#)

preparing [B-10, B-13, B-16](#)

reasons for [B-8](#)

using FTP [B-13](#)

using RCP [B-17](#)

using TFTP [B-11](#)

guidelines for creating and using [B-9](#)

invalid combinations when copying [B-5](#)

limiting TFTP server access [31-16](#)

configuration files (continued)

obtaining with DHCP [3-7](#)

password recovery disable considerations [8-5](#)

specifying the filename [3-12](#)

system contact and location information [31-15](#)

types and location [B-9](#)

uploading

preparing [B-10, B-13, B-16](#)

reasons for [B-8](#)

using FTP [B-14](#)

using RCP [B-18](#)

using TFTP [B-11](#)

configuration guidelines, multi-VRF CE [35-64](#)

configuration logger [30-10](#)

configuration logging [2-5](#)

configuration settings, saving [3-11](#)

configure terminal command [10-10](#)

config-vlan mode [2-2, 12-7](#)

conflicts, configuration [44-11](#)

connections, secure remote [8-38](#)

connectivity problems [44-13, 44-15, 44-16](#)

consistency checks in VTP Version 2 [13-4](#)

console port, connecting to [2-10](#)

content-routing technology

See WCCP

conventions

command [xliv](#)

for examples [xliv](#)

publication [xliv](#)

text [xliv](#)

corrupted software, recovery steps with Xmodem [44-2](#)

CoS

in Layer 2 frames [33-2](#)

override priority [15-6](#)

trust priority [15-6](#)

CoS input queue threshold map for QoS [33-16](#)

CoS output queue threshold map for QoS [33-19](#)

CoS-to-DSCP map for QoS [33-61](#)

counters, clearing interface [10-29](#)

crashinfo file [44-23](#)
 critical authentication, IEEE 802.1x [9-36](#)
 cryptographic software image
 Kerberos [8-32](#)
 SSH [8-37](#)
 SSL [8-42](#)
 customer edge devices [35-62](#)
 CWDM SFPs [1-21](#)

D

daylight saving time [6-13](#)
 debugging
 enabling all system diagnostics [44-20](#)
 enabling for a specific feature [44-19](#)
 redirecting error message output [44-20](#)
 using commands [44-19](#)
 default commands [2-4](#)
 default configuration
 802.1x [9-21](#)
 auto-QoS [33-21](#)
 banners [6-17](#)
 BGP [35-42](#)
 booting [3-12](#)
 CDP [25-2](#)
 DHCP [21-8](#)
 DHCP option 82 [21-8](#)
 DHCP snooping [21-8](#)
 DHCP snooping binding database [21-9](#)
 DNS [6-16](#)
 dynamic ARP inspection [22-5](#)
 EIGRP [35-34](#)
 EtherChannel [34-9](#)
 Ethernet interfaces [10-14](#)
 fallback bridging [43-4](#)
 Flex Links [20-4, 20-5](#)
 HSRP [39-5](#)
 IEEE 802.1Q tunneling [16-4](#)
 IGMP [41-29](#)
 default configuration (continued)
 IGMP filtering [23-25](#)
 IGMP snooping [23-7, 37-5, 37-6](#)
 IGMP throttling [23-25](#)
 initial switch information [3-3](#)
 IP addressing, IP routing [35-4](#)
 IP multicast routing [41-10](#)
 IP source guard [21-16](#)
 IPv6 [36-9](#)
 Layer 2 interfaces [10-14](#)
 Layer 2 protocol tunneling [16-11](#)
 LLDP [26-3](#)
 MAC address table [6-21](#)
 MAC address-table move update [20-5](#)
 MSDP [42-4](#)
 MSTP [18-14](#)
 multi-VRF CE [35-64](#)
 MVR [23-20](#)
 NTP [6-4](#)
 optional spanning-tree configuration [19-9](#)
 OSPF [35-25](#)
 password and privilege level [8-2](#)
 PIM [41-10](#)
 private VLANs [14-6](#)
 RADIUS [8-20](#)
 RIP [35-19](#)
 RMON [29-3](#)
 RSPAN [28-9](#)
 SDM template [7-3](#)
 SNMP [31-7](#)
 SPAN [28-9](#)
 SSL [8-44](#)
 standard QoS [33-31](#)
 STP [17-11](#)
 system message logging [30-3](#)
 system name and prompt [6-15](#)
 TACACS+ [8-13](#)
 UDLD [27-4](#)
 VLAN, Layer 2 Ethernet interfaces [12-19](#)

default configuration (continued)

VLANs 12-8

VMPS 12-29

voice VLAN 15-3

VTP 13-6

WCCP 40-5

default gateway 3-10, 35-11

default networks 35-75

default routes 35-75

default routing 35-2

deleting VLANs 12-10

denial-of-service attack 24-1

description command 10-24

designing your network, examples 1-15

destination addresses

in IPv4 ACLs 32-11

in IPv6 ACLs 38-5

destination-IP address-based forwarding,
EtherChannel 34-7

destination-MAC address forwarding, EtherChannel 34-7

detecting indirect link failures, STP 19-5

device B-19

device discovery protocol 25-1, 26-1

device manager

benefits 1-2

described 1-2, 1-4

in-band management 1-5

requirements xliv

upgrading a switch B-19

DHCP

Cisco IOS server database

configuring 21-14

default configuration 21-9

described 21-6

enabling

relay agent 21-10

server 21-10

DHCP-based autoconfiguration

client request message exchange 3-4

configuring

client side 3-3

DNS 3-6

relay device 3-6

server side 3-5

server-side 21-10

TFTP server 3-6

example 3-8

lease options

for IP address information 3-5

for receiving the configuration file 3-5

overview 3-3

relationship to BOOTP 3-4

relay support 1-5, 1-11

support for 1-5

DHCP binding database

See DHCP snooping binding database

DHCP binding table

See DHCP snooping binding database

DHCP option 82

circuit ID suboption 21-5

configuration guidelines 21-9

default configuration 21-8

displaying 21-15

forwarding address, specifying 21-11

helper address 21-11

overview 21-3

packet format, suboption

circuit ID 21-5

remote ID 21-5

remote ID suboption 21-5

- DHCP snooping
 - accepting untrusted packets form edge switch [21-3, 21-12](#)
 - and private VLANs [21-13](#)
 - binding database
 - See DHCP snooping binding database
 - configuration guidelines [21-9](#)
 - default configuration [21-8](#)
 - displaying binding tables [21-15](#)
 - message exchange process [21-4](#)
 - option 82 data insertion [21-3](#)
 - trusted interface [21-2](#)
 - untrusted interface [21-2](#)
 - untrusted messages [21-2](#)
- DHCP snooping binding database
 - adding bindings [21-14](#)
 - binding file
 - format [21-7](#)
 - location [21-7](#)
 - bindings [21-7](#)
 - clearing agent statistics [21-15](#)
 - configuration guidelines [21-10](#)
 - configuring [21-14](#)
 - default configuration [21-8, 21-9](#)
 - deleting
 - binding file [21-14](#)
 - bindings [21-15](#)
 - database agent [21-14](#)
 - described [21-7](#)
 - displaying [21-15](#)
 - binding entries [21-15](#)
 - status and statistics [21-15](#)
 - enabling [21-14](#)
 - entry [21-7](#)
 - renewing database [21-15](#)
 - resetting
 - delay value [21-14](#)
 - timeout value [21-14](#)
- DHCP snooping binding table
 - See DHCP snooping binding database
- Differentiated Services architecture, QoS [33-2](#)
- Differentiated Services Code Point [33-2](#)
- Diffusing Update Algorithm (DUAL) [35-33](#)
- directed unicast requests [1-5](#)
- directories
 - changing [B-3](#)
 - creating and removing [B-4](#)
 - displaying the working [B-3](#)
- discovery, clusters
 - See automatic discovery
- Distance Vector Multicast Routing Protocol
 - See DVMRP
- distance-vector protocols [35-3](#)
- distribute-list command [35-84](#)
- DNS
 - and DHCP-based autoconfiguration [3-6](#)
 - default configuration [6-16](#)
 - displaying the configuration [6-17](#)
 - in IPv6 [36-4](#)
 - overview [6-15](#)
 - setting up [6-16](#)
 - support for [1-5](#)
- documentation, related [xliv](#)
- document conventions [xliv](#)
- domain names
 - DNS [6-15](#)
 - VTP [13-8](#)
- Domain Name System
 - See DNS
- dot1q-tunnel switchport mode [12-18](#)
- double-tagged packets
 - IEEE 802.1Q tunneling [16-2](#)
 - Layer 2 protocol tunneling [16-10](#)

downloading

configuration files

- preparing [B-10, B-13, B-16](#)
- reasons for [B-8](#)
- using FTP [B-13](#)
- using RCP [B-17](#)
- using TFTP [B-11](#)

image files

- deleting old image [B-23](#)
- preparing [B-22, B-25, B-29](#)
- reasons for [B-19](#)
- using CMS [1-3](#)
- using FTP [B-26](#)
- using HTTP [1-3, B-19](#)
- using RCP [B-30](#)
- using TFTP [B-22](#)
- using the device manager or Network Assistant [B-19](#)

drop threshold for Layer 2 protocol packets [16-11](#)

DSCP [1-9, 33-2](#)

DSCP input queue threshold map for QoS [33-16](#)

DSCP output queue threshold map for QoS [33-19](#)

DSCP-to-CoS map for QoS [33-64](#)

DSCP-to-DSCP-mutation map for QoS [33-65](#)

DSCP transparency [33-40](#)

DTP [1-7, 12-17](#)

DUAL finite state machine, EIGRP [35-34](#)

dual IPv4 and IPv6 templates [7-2, 36-1, 36-8](#)

dual protocol stacks

- configuring [36-12](#)
- IPv4 and IPv6 [36-7](#)
- SDM templates supporting [36-8](#)

dual-purpose uplinks

- defined [10-6](#)
- LEDs [10-6](#)
- link selection [10-6](#)
- setting the type [10-16](#)

DVMRP

autosummarization

- configuring a summary address [41-48](#)
- disabling [41-50](#)

connecting PIM domain to DVMRP router [41-41](#)

enabling unicast routing [41-44](#)

interoperability

- with Cisco devices [41-39](#)
- with Cisco IOS software [41-8](#)

mrinfo requests, responding to [41-43](#)

neighbors

- advertising the default route to [41-43](#)
- discovery with Probe messages [41-39](#)
- displaying information [41-43](#)
- prevent peering with nonpruning [41-46](#)
- rejecting nonpruning [41-45](#)

overview [41-8](#)

routes

- adding a metric offset [41-50](#)
- advertising all [41-50](#)
- advertising the default route to neighbors [41-43](#)
- caching DVMRP routes learned in report messages [41-44](#)
- changing the threshold for syslog messages [41-47](#)
- deleting [41-51](#)
- displaying [41-52](#)
- favoring one over another [41-50](#)
- limiting the number injected into MBONE [41-47](#)
- limiting unicast route advertisements [41-39](#)

routing table [41-9](#)

source distribution tree, building [41-9](#)

support for [1-11](#)

tunnels

- configuring [41-41](#)
- displaying neighbor information [41-43](#)

dynamic access ports

- characteristics [12-3](#)
- configuring [12-30](#)
- defined [10-3](#)

- dynamic addresses
 - See addresses
- dynamic ARP inspection
 - ARP cache poisoning [22-1](#)
 - ARP requests, described [22-1](#)
 - ARP spoofing attack [22-1](#)
 - clearing
 - log buffer [22-15](#)
 - statistics [22-15](#)
 - configuration guidelines [22-6](#)
 - configuring
 - ACLs for non-DHCP environments [22-8](#)
 - in DHCP environments [22-7](#)
 - log buffer [22-12](#)
 - rate limit for incoming ARP packets [22-4, 22-10](#)
 - default configuration [22-5](#)
 - denial-of-service attacks, preventing [22-10](#)
 - described [22-1](#)
 - DHCP snooping binding database [22-2](#)
 - displaying
 - ARP ACLs [22-14](#)
 - configuration and operating state [22-14](#)
 - log buffer [22-15](#)
 - statistics [22-15](#)
 - trust state and rate limit [22-14](#)
 - error-disabled state for exceeding rate limit [22-4](#)
 - function of [22-2](#)
 - interface trust states [22-3](#)
 - log buffer
 - clearing [22-15](#)
 - configuring [22-12](#)
 - displaying [22-15](#)
 - logging of dropped packets, described [22-5](#)
 - man-in-the-middle attack, described [22-2](#)
 - network security issues and interface trust states [22-3](#)
 - priority of ARP ACLs and DHCP snooping entries [22-4](#)
 - dynamic ARP inspection (continued)**
 - rate limiting of ARP packets
 - configuring [22-10](#)
 - described [22-4](#)
 - error-disabled state [22-4](#)
 - statistics
 - clearing [22-15](#)
 - displaying [22-15](#)
 - validation checks, performing [22-12](#)
 - dynamic auto trunking mode [12-18](#)
 - dynamic desirable trunking mode [12-18](#)
 - Dynamic Host Configuration Protocol
 - See DHCP-based autoconfiguration
 - dynamic port VLAN membership
 - described [12-28](#)
 - reconfirming [12-31](#)
 - troubleshooting [12-33](#)
 - types of connections [12-30](#)
 - dynamic routing [35-3](#)
 - Dynamic Trunking Protocol
 - See DTP

 - E**
 - EBGP [35-41](#)
 - editing features
 - enabling and disabling [2-7](#)
 - keystrokes used [2-7](#)
 - wrapped lines [2-9](#)
 - EIGRP
 - authentication [35-38](#)
 - components [35-33](#)
 - configuring [35-36](#)
 - default configuration [35-34](#)
 - definition [35-33](#)
 - interface parameters, configuring [35-37](#)
 - monitoring [35-40](#)
 - stub routing [35-39](#)
 - support for [1-10](#)

- enable password [8-3](#)
- enable secret password [8-3](#)
- encryption, CipherSuite [8-44](#)
- encryption for passwords [8-3](#)
- Enhanced IGRP
 - See EIGRP
- enhanced object tracking
 - commands [39-12](#)
 - defined [39-12](#)
 - HSRP [39-17](#)
 - IP routing state [39-13](#)
 - line-protocol state [39-13](#)
 - tracked lists [39-14](#)
- environment variables, function of [3-15](#)
- equal-cost routing [1-10, 35-73](#)
- error-disabled state, BPDU [19-2](#)
- error messages during command entry [2-5](#)
- EtherChannel
 - automatic creation of [34-4, 34-5](#)
 - channel groups
 - binding physical and logical interfaces [34-3](#)
 - numbering of [34-3](#)
 - configuration guidelines [34-9](#)
 - configuring
 - Layer 2 interfaces [34-11](#)
 - Layer 3 physical interfaces [34-14](#)
 - Layer 3 port-channel logical interfaces [34-13](#)
 - default configuration [34-9](#)
 - described [34-2](#)
 - displaying status [34-20](#)
 - forwarding methods [34-6, 34-16](#)
 - IEEE 802.3ad, described [34-5](#)
 - interaction
 - with STP [34-9](#)
 - with VLANs [34-10](#)
- EtherChannel (continued)**
 - LACP
 - described [34-5](#)
 - displaying status [34-20](#)
 - hot-standby ports [34-18](#)
 - interaction with other features [34-6](#)
 - modes [34-5](#)
 - port priority [34-19](#)
 - system priority [34-19](#)
 - Layer 3 interface [35-3](#)
 - load balancing [34-6, 34-16](#)
 - logical interfaces, described [34-3](#)
 - PAgP
 - aggregate-port learners [34-17](#)
 - compatibility with Catalyst 1900 [34-17](#)
 - described [34-4](#)
 - displaying status [34-20](#)
 - interaction with other features [34-5](#)
 - learn method and priority configuration [34-17](#)
 - modes [34-4](#)
 - support for [1-3](#)
 - port-channel interfaces
 - described [34-3](#)
 - numbering of [34-3](#)
 - port groups [10-5](#)
 - support for [1-3](#)
- EtherChannel guard
 - described [19-7](#)
 - disabling [19-14](#)
 - enabling [19-14](#)
- Ethernet VLANs
 - adding [12-9](#)
 - defaults and ranges [12-8](#)
 - modifying [12-9](#)
- EUI [36-3](#)
- events, RMON [29-3](#)
- examples
 - conventions for [xliv](#)
 - network configuration [1-15](#)

expedite queue for QoS [33-78](#)

Express Setup [1-2](#)

- See also getting started guide

extended crashinfo file [44-23](#)

extended-range VLANs

- configuration guidelines [12-13](#)
- configuring [12-12](#)
- creating [12-13](#)
- creating with an internal VLAN ID [12-15](#)
- defined [12-1](#)

extended system ID

- MSTP [18-17](#)
- STP [17-4, 17-14](#)

extended universal identifier

- See EUI

Extensible Authentication Protocol over LAN [9-1](#)

external BGP

- See EBGp

external neighbors, BGP [35-45](#)

F

fa0 interface [1-5](#)

fallback bridging

- and protected ports [43-4](#)
- bridge groups
 - creating [43-4](#)
 - described [43-2](#)
 - displaying [43-11](#)
 - function of [43-2](#)
 - number supported [43-5](#)
 - removing [43-5](#)
- bridge table
 - clearing [43-11](#)
 - displaying [43-11](#)
- configuration guidelines [43-4](#)
- connecting interfaces with [10-9](#)
- default configuration [43-4](#)
- described [43-1](#)

fallback bridging (continued)

- frame forwarding
 - flooding packets [43-2](#)
 - forwarding packets [43-2](#)
- overview [43-1](#)
- protocol, unsupported [43-4](#)
- STP
 - disabling on an interface [43-10](#)
 - forward-delay interval [43-9](#)
 - hello BPDU interval [43-9](#)
 - interface priority [43-7](#)
 - keepalive messages [17-2](#)
 - maximum-idle interval [43-10](#)
 - path cost [43-8](#)
 - VLAN-bridge spanning-tree priority [43-6](#)
 - VLAN-bridge STP [43-2](#)
- support for [1-10](#)
- SVIs and routed ports [43-2](#)
- unsupported protocols [43-4](#)
- VLAN-bridge STP [17-10](#)

features, incompatible [24-11](#)

FIB [35-72](#)

fiber-optic, detecting unidirectional links [27-1](#)

files

- basic crashinfo
 - description [44-23](#)
 - location [44-23](#)
- copying [B-4](#)
- crashinfo, description [44-23](#)
- deleting [B-5](#)
- displaying the contents of [B-8](#)
- extended crashinfo
 - description [44-23](#)
 - location [44-23](#)
- tar
 - creating [B-6](#)
 - displaying the contents of [B-6](#)
 - extracting [B-7](#)
 - image file format [B-20](#)

file system

- displaying available file systems [B-2](#)
- displaying file information [B-3](#)
- local file system names [B-1](#)
- network file system names [B-4](#)
- setting the default [B-3](#)

filtering

- in a VLAN [32-28](#)
- IPv6 traffic [38-3, 38-7](#)
- non-IP traffic [32-26](#)
- show and more command output [2-10](#)

filtering show and more command output [2-10](#)

filters, IP

- See ACLs, IP

flash device, number of [B-1](#)

Flex Links

- configuration guidelines [20-5](#)
- configuring [20-5, 20-6](#)
- configuring preferred VLAN [20-8](#)
- configuring VLAN load balancing [20-7](#)
- default configuration [20-4](#)
- description [20-1](#)
- link load balancing [20-2](#)
- monitoring [20-11](#)
- VLANs [20-2](#)

flooded traffic, blocking [24-7](#)flow-based packet classification [1-9](#)

flowcharts

- QoS classification [33-6](#)
- QoS egress queueing and scheduling [33-17](#)
- QoS ingress queueing and scheduling [33-15](#)
- QoS policing and marking [33-10](#)

flowcontrol

- configuring [10-19](#)
- described [10-19](#)

forward-delay time

- MSTP [18-23](#)
- STP [17-21](#)

Forwarding Information Base

- See FIB

forwarding nonroutable protocols [43-1](#)

FTP

- accessing MIB files [A-3](#)
- configuration files
 - downloading [B-13](#)
 - overview [B-12](#)
 - preparing the server [B-13](#)
 - uploading [B-14](#)
- image files
 - deleting old image [B-27](#)
 - downloading [B-26](#)
 - preparing the server [B-25](#)
 - uploading [B-28](#)

G

- get-bulk-request operation [31-3](#)
- get-next-request operation [31-3, 31-5](#)
- get-request operation [31-3, 31-5](#)
- get-response operation [31-3](#)
- global configuration mode [2-2](#)
- global leave, IGMP [23-13](#)
- guest VLAN and 802.1x [9-12](#)

guide

- audience [xliv](#)
- purpose of [xliv](#)

guide mode [1-3](#)

GUIs

- See device manager and Network Assistant

H
hardware limitations and Layer 3 interfaces [10-25](#)

hello time

- MSTP [18-22](#)
- STP [17-20](#)

help, for the command line [2-3](#)

hierarchical policy maps [33-8](#)

- configuration guidelines [33-33](#)
- configuring [33-53](#)
- described [33-11](#)

history

- changing the buffer size [2-6](#)
- described [2-6](#)
- disabling [2-7](#)
- recalling commands [2-6](#)

history table, level and number of syslog messages [30-9](#)

host names, in clusters [5-13](#)

host ports

- configuring [14-11](#)
- kinds of [14-2](#)

hosts, limit on dynamic ports [12-33](#)

Hot Standby Router Protocol

- See HSRP

HP OpenView [1-4](#)

HSRP

- authentication string [39-10](#)
- automatic cluster recovery [5-12](#)
- binding to cluster group [39-11](#)
- cluster standby group considerations [5-11](#)
- command-switch redundancy [1-1, 1-6](#)
- configuring [39-4](#)
- default configuration [39-5](#)
- definition [39-1](#)
- guidelines [39-5](#)
- monitoring [39-12](#)
- object tracking [39-17](#)
- overview [39-1](#)
- priority [39-7](#)
- routing redundancy [1-10](#)
- support for ICMP redirect messages [39-11](#)
- timers [39-10](#)
- tracking [39-7](#)

See also clusters, cluster standby group, and standby command switch

HTTP over SSL

- see HTTPS

HTTPS [8-42](#)

- configuring [8-46](#)
- self-signed certificate [8-43](#)

HTTP secure server [8-42](#)

IBPG [35-41](#)

ICMP

- IPv6 [36-4](#)
- redirect messages [35-11](#)
- support for [1-11](#)
- time-exceeded messages [44-17](#)
- traceroute and [44-17](#)
- unreachable messages [32-19](#)
- unreachable messages and IPv6 [38-4](#)
- unreachables and ACLs [32-21](#)

ICMP ping

- executing [44-14](#)
- overview [44-13](#)

ICMP Router Discovery Protocol

- See IRDP

ICMPv6 [36-4](#)

IDS appliances

- and ingress RSPAN [28-20](#)
- and ingress SPAN [28-13](#)

IEEE 802.1D

- See STP

IEEE 802.1p [15-1](#)

IEEE 802.1Q

- and trunk ports [10-3](#)
- configuration limitations [12-19](#)
- encapsulation [12-16](#)
- native VLAN for untagged traffic [12-23](#)

IEEE 802.1Q (continued)

- tunneling
 - compatibility with other features [16-6](#)
 - defaults [16-4](#)
 - described [16-1](#)
- tunnel ports with other features [16-6](#)

IEEE 802.1s

See MSTP

IEEE 802.1w

See RSTP

IEEE 802.1x

See port-based authentication

IEEE 802.3ad

See EtherChannel

IEEE 802.3af

See PoE

IEEE 802.3x flow control [10-19](#)**ifIndex values, SNMP [31-6](#)****IFS [1-5](#)****IGMP**

- configurable leave timer
 - described [23-6](#)
 - enabling [23-11](#)
- configuring the switch
 - as a member of a group [41-29](#)
 - statically connected member [41-33](#)
- controlling access to groups [41-30](#)
- default configuration [41-29](#)
- deleting cache entries [41-52](#)
- displaying groups [41-52](#)
- fast switching [41-33](#)
- flooded multicast traffic
 - controlling the length of time [23-12](#)
 - disabling on an interface [23-13](#)
 - global leave [23-13](#)
 - query solicitation [23-13](#)
 - recovering from flood mode [23-13](#)
- host-query interval, modifying [41-31](#)
- joining multicast group [23-3](#)

IGMP (continued)

- join messages [23-3](#)
 - leave processing, enabling [23-11, 37-9](#)
 - leaving multicast group [23-5](#)
 - multicast reachability [41-29](#)
 - overview [41-3](#)
 - queries [23-4](#)
 - report suppression
 - described [23-6](#)
 - disabling [23-16, 37-11](#)
 - supported versions [23-3](#)
 - support for [1-4](#)
 - Version 1
 - changing to Version 2 [41-31](#)
 - described [41-3](#)
 - Version 2
 - changing to Version 1 [41-31](#)
 - described [41-3](#)
 - maximum query response time value [41-33](#)
 - pruning groups [41-33](#)
 - query timeout value [41-32](#)
- IGMP filtering**
- configuring [23-25](#)
 - default configuration [23-25](#)
 - described [23-24](#)
 - monitoring [23-29](#)
 - support for [1-4](#)
- IGMP groups**
- configuring filtering [23-28](#)
 - setting the maximum number [23-27](#)
- IGMP Immediate Leave**
- configuration guidelines [23-11](#)
 - described [23-6](#)
 - enabling [23-11](#)
- IGMP profile**
- applying [23-26](#)
 - configuration mode [23-25](#)
 - configuring [23-26](#)

- IGMP snooping
 - and address aliasing [23-2](#)
 - configuring [23-7](#)
 - default configuration [23-7, 37-5, 37-6](#)
 - definition [23-2](#)
 - enabling and disabling [23-8, 37-6](#)
 - global configuration [23-8](#)
 - Immediate Leave [23-6](#)
 - method [23-8](#)
 - monitoring [23-16, 37-11](#)
 - querier
 - configuration guidelines [23-14](#)
 - configuring [23-14](#)
 - supported versions [23-3](#)
 - support for [1-4](#)
 - VLAN configuration [23-8](#)
- IGMP throttling
 - configuring [23-28](#)
 - default configuration [23-25](#)
 - described [23-25](#)
 - displaying action [23-29](#)
- IGP [35-24](#)
- Immediate Leave, IGMP [23-6](#)
 - enabling [37-9](#)
- inaccessible authentication bypass [9-14](#)
- initial configuration
 - defaults [1-12](#)
 - Express Setup [1-2](#)
 - See also getting started guide and hardware installation guide
- interface
 - number [10-10](#)
 - range macros [10-12](#)
- interface command [10-10](#)
- interface configuration mode [2-3](#)
- interfaces
 - auto-MDIX, configuring [10-20](#)
 - configuration guidelines
 - duplex and speed [10-17](#)
 - configuring
 - for IPv4 and IPv6 [36-12](#)
 - procedure [10-10](#)
 - counters, clearing [10-29](#)
 - default configuration [10-14](#)
 - described [10-24](#)
 - descriptive name, adding [10-24](#)
 - displaying information about [10-28](#)
 - flow control [10-19](#)
 - management [1-4](#)
 - monitoring [10-28](#)
 - naming [10-24](#)
 - physical, identifying [10-10](#)
 - range of [10-11](#)
 - restarting [10-29](#)
 - shutting down [10-29](#)
 - speed and duplex, configuring [10-18](#)
 - status [10-28](#)
 - supported [10-10](#)
 - types of [10-1](#)
- interfaces range macro command [10-12](#)
- interface types [10-10](#)
- Interior Gateway Protocol
 - See IGP
- internal BGP
 - See IBGP
- internal neighbors, BGP [35-45](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- Inter-Switch Link
 - See ISL

- inter-VLAN routing [1-10, 35-2](#)
- Intrusion Detection System
 - See IDS appliances
- IP ACLs
 - for QoS classification [33-7](#)
 - implicit deny [32-9, 32-13](#)
 - implicit masks [32-9](#)
 - named [32-14](#)
 - undefined [32-20](#)
- IP addresses
 - 128-bit [36-2](#)
 - candidate or member [5-3, 5-13](#)
 - classes of [35-5](#)
 - cluster access [5-2](#)
 - command switch [5-3, 5-11, 5-13](#)
 - default configuration [35-4](#)
 - discovering [6-26](#)
 - for IP routing [35-4](#)
 - IPv6 [36-2](#)
 - MAC address association [35-8](#)
 - monitoring [35-17](#)
 - redundant clusters [5-11](#)
 - standby command switch [5-11, 5-13](#)
 - See also IP information
- IP base image [1-1](#)
- IP broadcast address [35-15](#)
- ip cef distributed command [35-72](#)
- IP directed broadcasts [35-13](#)
- ip igmp profile command [23-25](#)
- IP information
 - assigned
 - manually [3-10](#)
 - through DHCP-based autoconfiguration [3-3](#)
 - default configuration [3-3](#)
- IP multicast routing
 - addresses
 - all-hosts [41-3](#)
 - all-multicast-routers [41-3](#)
 - host group address range [41-3](#)
 - administratively-scoped boundaries, described [41-37](#)
 - and IGMP snooping [23-2](#)
 - Auto-RP
 - adding to an existing sparse-mode cloud [41-16](#)
 - benefits of [41-15](#)
 - clearing the cache [41-52](#)
 - configuration guidelines [41-11](#)
 - filtering incoming RP announcement messages [41-18](#)
 - overview [41-6](#)
 - preventing candidate RP spoofing [41-18](#)
 - preventing join messages to false RPs [41-17](#)
 - setting up in a new internetwork [41-16](#)
 - using with BSR [41-24](#)
 - bootstrap router
 - configuration guidelines [41-11](#)
 - configuring candidate BSRs [41-22](#)
 - configuring candidate RPs [41-23](#)
 - defining the IP multicast boundary [41-21](#)
 - defining the PIM domain border [41-20](#)
 - overview [41-6](#)
 - using with Auto-RP [41-24](#)
 - Cisco implementation [41-2](#)
 - configuring
 - basic multicast routing [41-11](#)
 - IP multicast boundary [41-37](#)
 - default configuration [41-10](#)
 - enabling
 - multicast forwarding [41-12](#)
 - PIM mode [41-12](#)
 - group-to-RP mappings
 - Auto-RP [41-6](#)
 - BSR [41-6](#)

IP multicast routing (continued)

MBONE

- deleting sdr cache entries 41-52
- described 41-35
- displaying sdr cache 41-53
- enabling sdr listener support 41-36
- limiting DVMRP routes advertised 41-47
- limiting sdr cache entry lifetime 41-36
- SAP packets for conference session announcement 41-35
- Session Directory (sdr) tool, described 41-35

monitoring

- packet rate loss 41-53
- peering devices 41-53
- tracing a path 41-53

multicast forwarding, described 41-7

PIMv1 and PIMv2 interoperability 41-10

protocol interaction 41-2

reverse path check (RPF) 41-7

routing table

- deleting 41-52
- displaying 41-52

RP

- assigning manually 41-14
 - configuring Auto-RP 41-15
 - configuring PIMv2 BSR 41-20
 - monitoring mapping information 41-24
 - using Auto-RP and BSR 41-24
- statistics, displaying system and network 41-52

See also CGMP

See also DVMRP

See also IGMP

See also PIM

IP phones

- and QoS 15-1
- automatic classification and queueing 33-20
- configuring 15-4
- ensuring port security with QoS 33-39
- trusted boundary for QoS 33-39

IP precedence 33-2

IP-precedence-to-DSCP map for QoS 33-62

IP protocols

- in ACLs 32-11
- routing 1-10

IP routes, monitoring 35-87

IP routing

- connecting interfaces with 10-9
- disabling 35-18
- enabling 35-18

IP services image 1-1

IP source guard

- and 802.1x 21-17
- and DHCP snooping 21-15
- and EtherChannels 21-17
- and port security 21-17
- and private VLANs 21-17
- and routed ports 21-17
- and TCAM entries 21-17
- and trunk interfaces 21-17
- and VRF 21-17

binding configuration

- automatic 21-15
- manual 21-15

binding table 21-15

configuration guidelines 21-17

default configuration 21-16

described 21-15

disabling 21-18

displaying

- bindings 21-19
- configuration 21-19

enabling 21-17

filtering

- source IP address 21-16
- source IP and MAC address 21-16
- source IP address filtering 21-16
- source IP and MAC address filtering 21-16

IP traceroute (continued)

- static bindings
 - adding 21-17
 - deleting 21-18

IP traceroute

- executing 44-17
- overview 44-16

IP unicast routing

- address resolution 35-8
- administrative distances 35-74, 35-85
- ARP 35-8
- assigning IP addresses to Layer 3 interfaces 35-5
- authentication keys 35-85
- broadcast
 - address 35-15
 - flooding 35-16
 - packets 35-13
 - storms 35-13
- classless routing 35-6
- configuring static routes 35-74
- default
 - addressing configuration 35-4
 - gateways 35-11
 - networks 35-75
 - routes 35-75
 - routing 35-2
- directed broadcasts 35-13
- disabling 35-18
- dynamic routing 35-3
- enabling 35-18
- EtherChannel Layer 3 interface 35-3
- IGP 35-24
- inter-VLAN 35-2
- IP addressing
 - classes 35-5
 - configuring 35-4

IP unicast routing (continued)

- IPv6 36-3
- IRDP 35-12
- Layer 3 interfaces 35-3
- MAC address and IP address 35-8
- passive interfaces 35-83
- protocols
 - distance-vector 35-3
 - dynamic 35-3
 - link-state 35-3
- proxy ARP 35-8
- redistribution 35-76
- reverse address resolution 35-8
- routed ports 35-3
- static routing 35-3
- steps to configure 35-4
- subnet mask 35-5
- subnet zero 35-6
- supernet 35-6
- UDP 35-15
- with SVIs 35-3
- See also BGP
- See also EIGRP
- See also OSPF
- See also RIP
- IPv4 ACLs
 - applying to interfaces 32-19
 - extended, creating 32-10
 - named 32-14
 - standard, creating 32-9
- IPv4 and IPv6
 - configuring on an interface 36-12
 - differences 36-2
 - dual protocol stacks 36-6

IPv6

ACLs

- displaying 38-8
- limitations 38-3
- matching criteria 38-3
- port 38-1
- precedence 38-2
- router 38-1
- supported 38-2

addresses 36-2

address formats 36-2

advantages 36-2

applications 36-5

assigning address 36-10

autoconfiguration 36-5

CEFv6 36-14

configuring static routes 36-15

default configuration 36-9

defined 36-1

enabling 36-10

feature limitations 36-7

features not supported 36-6

ICMP 36-4

ICMP rate limiting 36-14

monitoring 36-21

neighbor discovery 36-4

OSPF 36-19

path MTU discovery 36-4

reasons for 36-1

RIP 36-17

SDM templates 7-2, 36-7, 37-1, 38-1

supported features 36-3

switch limitations 36-7

IPv6 traffic, filtering 38-3

IRDP

configuring 35-12

definition 35-12

support for 1-11

ISL

and IPv6 36-3

and trunk ports 10-3

encapsulation 1-7, 12-16

trunking with IEEE 802.1 tunneling 16-5

isolated port 14-2

isolated VLANs 14-2, 14-3

J

join messages, IGMP 23-3

K

KDC

described 8-32

See also Kerberos

keepalive messages 17-2

Kerberos

authenticating to

boundary switch 8-34

KDC 8-34

network services 8-35

configuration examples 8-32

configuring 8-35

credentials 8-32

cryptographic software image 8-32

described 8-32

KDC 8-32

operation 8-34

realm 8-33

server 8-34

support for 1-9

switch as trusted third party 8-32

terms 8-33

TGT 8-34

tickets 8-32

key distribution center

See KDC

L

l2protocol-tunnel command 16-13

LACP

Layer 2 protocol tunneling 16-9

See EtherChannel

Layer 2 frames, classification with CoS 33-2

Layer 2 interfaces, default configuration 10-14

Layer 2 protocol tunneling

configuring 16-10

configuring for EtherChannels 16-14

default configuration 16-11

defined 16-8

guidelines 16-11

Layer 2 traceroute

and ARP 44-16

and CDP 44-15

broadcast traffic 44-15

described 44-15

IP addresses and subnets 44-16

MAC addresses and VLANs 44-15

multicast traffic 44-15

multiple devices on a port 44-16

unicast traffic 44-15

usage guidelines 44-15

Layer 3 features 1-10

Layer 3 interfaces

assigning IP addresses to 35-5

assigning IPv4 and IPv6 addresses to 36-12

assigning IPv6 addresses to 36-10

changing from Layer 2 mode 35-5

types of 35-3

Layer 3 packets, classification methods 33-2

LDAP 4-2

LEDs, switch

See hardware installation guide

lightweight directory access protocol

See LDAP

line configuration mode 2-3

Link Aggregation Control Protocol

See EtherChannel

link failure, detecting unidirectional 18-8

Link Layer Discovery Protocol

See CDP

link local unicast addresses 36-3

link redundancy

See Flex Links

links, unidirectional 27-1

link state advertisements (LSAs) 35-28

link-state protocols 35-3

link-state tracking

configuring 34-23

described 34-21

LLDP

configuring 26-3

characteristics 26-3

default configuration 26-3

disabling and enabling

globally 26-4

on an interface 26-5

monitoring and maintaining 26-7

overview 26-1

supported TLVs 26-2

switch stack considerations 26-2

transmission timer and holdtime, setting 26-3

LLDP-MED

configuring

procedures 26-3

TLVs 26-6

monitoring and maintaining 26-7

overview 26-1, 26-2

supported TLVs 26-2

LLDP Media Endpoint Discovery

See LLDP-MED

load balancing 39-3

local SPAN [28-2](#)
 logging messages, ACL [32-8](#)
 login authentication
 with RADIUS [8-23](#)
 with TACACS+ [8-14](#)
 login banners [6-17](#)
 log messages
 See system message logging
 Long-Reach Ethernet (LRE) technology [1-16](#)
 loop guard
 described [19-9](#)
 enabling [19-15](#)
 support for [1-6](#)
 LRE profiles, considerations in switch clusters [5-14](#)

M

MAB aging timer [1-7](#)
 MAB inactivity timer
 default setting [9-22](#)
 range [9-24](#)
 MAC addresses
 aging time [6-21](#)
 and VLAN association [6-20](#)
 building the address table [6-20](#)
 default configuration [6-21](#)
 discovering [6-26](#)
 displaying [6-26](#)
 displaying in the IP source binding table [21-19](#)
 dynamic
 learning [6-20](#)
 removing [6-22](#)
 in ACLs [32-26](#)
 IP address association [35-8](#)

MAC addresses (continued)

static
 adding [6-24](#)
 allowing [6-26](#)
 characteristics of [6-24](#)
 dropping [6-25](#)
 removing [6-24](#)
 MAC address notification, support for [1-11](#)
 MAC address-table move update
 configuration guidelines [20-5](#)
 configuring [20-9](#)
 default configuration [20-5](#)
 description [20-3](#)
 monitoring [20-11](#)
 MAC address-to-VLAN mapping [12-28](#)
 MAC authentication bypass
 See MAB
 MAC extended access lists
 applying to Layer 2 interfaces [32-27](#)
 configuring for QoS [33-46](#)
 creating [32-26](#)
 defined [32-26](#)
 for QoS classification [33-5](#)
 macros
 See Smartports macros
 magic packet [9-16](#)
 manageability features [1-5](#)
 management access
 in-band
 browser session [1-5](#)
 CLI session [1-5](#)
 device manager [1-5](#)
 SNMP [1-5](#)
 out-of-band console port connection [1-5](#)

- management options
 - CLI [2-1](#)
 - clustering [1-3](#)
 - CNS [4-1](#)
 - Network Assistant [1-2](#)
 - overview [1-4](#)
- management VLAN
 - considerations in switch clusters [5-7](#)
 - discovery through different management VLANs [5-7](#)
- mapping tables for QoS
 - configuring
 - CoS-to-DSCP [33-61](#)
 - DSCP [33-61](#)
 - DSCP-to-CoS [33-64](#)
 - DSCP-to-DSCP-mutation [33-65](#)
 - IP-precedence-to-DSCP [33-62](#)
 - policed-DSCP [33-63](#)
 - described [33-12](#)
- marking
 - action in policy map [33-49](#)
 - action with aggregate policers [33-59](#)
 - described [33-4](#), [33-8](#)
- matching
 - IPv6 ACLs [38-3](#)
- matching, IPv4 ACLs [32-7](#)
- maximum aging time
 - MSTP [18-23](#)
 - STP [17-21](#)
- maximum hop count, MSTP [18-24](#)
- maximum-paths command [35-49](#), [35-73](#)
- MDA
 - configuration guidelines [9-19](#)
 - described [1-8](#), [9-18](#)
 - exceptions with authentication process [9-4](#)
- membership mode, VLAN port [12-3](#)
- member switch
 - automatic discovery [5-4](#)
 - defined [5-2](#)
 - managing [5-15](#)
 - passwords [5-13](#)
 - recovering from lost connectivity [44-11](#)
 - requirements [5-3](#)
 - See also candidate switch, cluster standby group, and standby command switch
- messages, to users through banners [6-17](#)
- metrics, in BGP [35-49](#)
- metric translations, between routing protocols [35-79](#)
- metro tags [16-2](#)
- MHSRP [39-3](#)
- MIBs
 - accessing files with FTP [A-3](#)
 - location of files [A-3](#)
 - overview [31-1](#)
 - SNMP interaction with [31-4](#)
 - supported [A-1](#)
- mirroring traffic for analysis [28-1](#)
- mismatches, autonegotiation [44-11](#)
- module number [10-10](#)
- monitoring
 - access groups [32-40](#)
 - BGP [35-60](#)
 - cables for unidirectional links [27-1](#)
 - CDP [25-4](#)
 - CEF [35-73](#)
 - EIGRP [35-40](#)
 - fallback bridging [43-11](#)
 - features [1-11](#)
 - Flex Links [20-11](#)
 - HSRP [39-12](#)
 - IEEE 802.1Q tunneling [16-18](#)
 - IGMP
 - filters [23-29](#)
 - snooping [23-16](#), [37-11](#)
 - interfaces [10-28](#)

monitoring (continued)

- IP
 - address tables 35-17
 - multicast routing 41-51
 - routes 35-87
- IPv4 ACL configuration 32-40
- IPv6 36-21
- IPv6 ACL configuration 38-8
- Layer 2 protocol tunneling 16-18
- MAC address-table move update 20-11
- MSDP peers 42-18
- multicast router interfaces 23-17, 37-11
- multi-VRF CE 35-71
- MVR 23-24
- network traffic for analysis with probe 28-2
- OSPF 35-32
- port
 - blocking 24-19
 - protection 24-19
- private VLANs 14-14
- RP mapping information 41-24
- SFP status 10-28, 44-13
- source-active messages 42-18
- speed and duplex mode 10-18
- traffic flowing among switches 29-1
- traffic suppression 24-19
- tunneling 16-18
- VLAN
 - filters 32-40
 - maps 32-40
- VLANs 12-16
- VMPS 12-32
- VTP 13-16

MSDP

- benefits of 42-3
- clearing MSDP connections and statistics 42-18
- controlling source information
 - forwarded by switch 42-11
 - originated by switch 42-9
 - received by switch 42-13
- default configuration 42-4
- dense-mode regions
 - sending SA messages to 42-16
 - specifying the originating address 42-17
- filtering
 - incoming SA messages 42-14
 - SA messages to a peer 42-12
 - SA requests from a peer 42-10
- join latency, defined 42-6
- meshed groups
 - configuring 42-15
 - defined 42-15
- originating address, changing 42-17
- overview 42-1
- peer-RPF flooding 42-2
- peers
 - configuring a default 42-4
 - monitoring 42-18
 - peering relationship, overview 42-1
 - requesting source information from 42-8
 - shutting down 42-15
- source-active messages
 - caching 42-6
 - clearing cache entries 42-18
 - defined 42-2
 - filtering from a peer 42-10
 - filtering incoming 42-14
 - filtering to a peer 42-12
 - limiting data with TTL 42-13
 - monitoring 42-18
 - restricting advertised sources 42-9
- support for 1-11

MSTP

- boundary ports
 - configuration guidelines [18-15](#)
 - described [18-6](#)
- BPDU filtering
 - described [19-3](#)
 - enabling [19-12](#)
- BPDU guard
 - described [19-2](#)
 - enabling [19-11](#)
- CIST, described [18-3](#)
- CIST regional root [18-3](#)
- CIST root [18-5](#)
- configuration guidelines [18-15, 19-10](#)
- configuring
 - forward-delay time [18-23](#)
 - hello time [18-22](#)
 - link type for rapid convergence [18-24](#)
 - maximum aging time [18-23](#)
 - maximum hop count [18-24](#)
 - MST region [18-16](#)
 - neighbor type [18-25](#)
 - path cost [18-20](#)
 - port priority [18-19](#)
 - root switch [18-17](#)
 - secondary root switch [18-18](#)
 - switch priority [18-21](#)
- CST
 - defined [18-3](#)
 - operations between regions [18-4](#)
- default configuration [18-14](#)
- default optional feature configuration [19-9](#)
- displaying status [18-26](#)
- enabling the mode [18-16](#)
- EtherChannel guard
 - described [19-7](#)
 - enabling [19-14](#)

MSTP (continued)

- extended system ID
 - effects on root switch [18-17](#)
 - effects on secondary root switch [18-18](#)
 - unexpected behavior [18-17](#)
- IEEE 802.1s
 - implementation [18-6](#)
 - port role naming change [18-7](#)
 - terminology [18-5](#)
- instances supported [17-9](#)
- interface state, blocking to forwarding [19-2](#)
- interoperability and compatibility among modes [17-10](#)
- interoperability with IEEE 802.1D
 - described [18-8](#)
 - restarting migration process [18-25](#)
- IST
 - defined [18-3](#)
 - master [18-3](#)
 - operations within a region [18-3](#)
- loop guard
 - described [19-9](#)
 - enabling [19-15](#)
- mapping VLANs to MST instance [18-16](#)
- MST region
 - CIST [18-3](#)
 - configuring [18-16](#)
 - described [18-2](#)
 - hop-count mechanism [18-5](#)
 - IST [18-3](#)
 - supported spanning-tree instances [18-2](#)
- optional features supported [1-6](#)
- overview [18-2](#)
- Port Fast
 - described [19-2](#)
 - enabling [19-10](#)
- preventing root switch selection [19-8](#)

MSTP (continued)

- root guard
 - described [19-8](#)
 - enabling [19-15](#)
- root switch
 - configuring [18-17](#)
 - effects of extended system ID [18-17](#)
 - unexpected behavior [18-17](#)
- shutdown Port Fast-enabled port [19-2](#)
- status, displaying [18-26](#)
- multicast groups
 - Immediate Leave [23-6](#)
 - joining [23-3](#)
 - leaving [23-5](#)
 - static joins [23-10, 37-7](#)
- multicast packets
 - ACLs on [32-39](#)
 - blocking [24-7](#)
- multicast router interfaces, monitoring [23-17, 37-11](#)
- multicast router ports, adding [23-9, 37-8](#)
- Multicast Source Discovery Protocol
 - See MSDP
- multicast storm [24-1](#)
- multicast storm-control command [24-4](#)
- multicast television application [23-18](#)
- multicast VLAN [23-17](#)
- Multicast VLAN Registration
 - See MVR
- multidomain authentication
 - See MDA
- Multiple HSRP
 - See MHSRP
- multiple VPN routing/forwarding in customer edge devices
 - See multi-VRF CE

- multi-VRF CE
 - configuration example [35-67](#)
 - configuration guidelines [35-64](#)
 - configuring [35-63](#)
 - default configuration [35-64](#)
 - defined [35-61](#)
 - displaying [35-71](#)
 - monitoring [35-71](#)
 - network components [35-63](#)
 - packet-forwarding process [35-63](#)
 - support for [1-10](#)

MVR

- and address aliasing [23-21](#)
- and IGMPv3 [23-21](#)
- configuration guidelines [23-20](#)
- configuring interfaces [23-22](#)
- default configuration [23-20](#)
- described [23-17](#)
- example application [23-18](#)
- modes [23-21](#)
- monitoring [23-24](#)
- multicast television application [23-18](#)
- setting global parameters [23-21](#)
- support for [1-4](#)

N**NAC**

- AAA down policy [1-9](#)
- critical authentication [9-14, 9-36](#)
- IEEE 802.1x authentication using a RADIUS server [9-40](#)
- IEEE 802.1x validation using RADIUS server [9-40](#)
- inaccessible authentication bypass [1-9, 9-36](#)
- Layer 2 IEEE 802.1x validation [1-8, 9-40](#)
- Layer 2 IEEE802.1x validation [9-18](#)
- Layer 2 IP validation [1-9](#)
- named IPv4 ACLs [32-14](#)

- NameSpace Mapper
 - See NSM
- native VLAN
 - and IEEE 802.1Q tunneling 16-4
 - configuring 12-23
 - default 12-23
- neighbor discovery, IPv6 36-4
- neighbor discovery/recovery, EIGRP 35-33
- neighbors, BGP 35-55
- Network Admission Control
 - NAC
- Network Assistant
 - benefits 1-2
 - described 1-4
 - downloading image files 1-3
 - guide mode 1-3
 - management options 1-2
 - requirements xlv
 - upgrading a switch B-19
 - wizards 1-3
- network configuration examples
 - increasing network performance 1-15
 - large network 1-20
 - long-distance, high-bandwidth transport 1-21
 - providing network services 1-16
 - server aggregation and Linux server cluster 1-17
 - small to medium-sized network 1-18
- network design
 - performance 1-15
 - services 1-16
- network management
 - CDP 25-1
 - RMON 29-1
 - SNMP 31-1
- Network Time Protocol
 - See NTP
- no commands 2-4
- nonhierarchical policy maps
 - configuration guidelines 33-33
 - configuring 33-49
 - described 33-9
- non-IP traffic filtering 32-26
- nontrunking mode 12-18
- normal-range VLANs 12-4
 - configuration guidelines 12-6
 - configuration modes 12-7
 - configuring 12-4
 - defined 12-1
- no switchport command 10-4
- note, described xlv
- not-so-stubby areas
 - See NSSA
- NSM 4-3
- NSSA, OSPF 35-28
- NTP
 - associations
 - authenticating 6-4
 - defined 6-2
 - enabling broadcast messages 6-6
 - peer 6-5
 - server 6-5
 - default configuration 6-4
 - displaying the configuration 6-11
 - overview 6-2
 - restricting access
 - creating an access group 6-8
 - disabling NTP services per interface 6-10
 - source IP address, configuring 6-10
 - stratum 6-2
 - support for 1-5
 - synchronizing devices 6-5
 - time
 - services 6-2
 - synchronizing 6-2

O

object tracking, HSRP [39-17](#)

online diagnostics

overview [45-1](#)

running tests [45-3](#)

understanding [45-1](#)

Open Shortest Path First

See OSPF

optimizing system resources [7-1](#)

options, management [1-4](#)

OSPF

area parameters, configuring [35-28](#)

configuring [35-26](#)

default configuration

metrics [35-30](#)

route [35-30](#)

settings [35-25](#)

described [35-24](#)

for IPv6 [36-19](#)

interface parameters, configuring [35-27](#)

LSA group pacing [35-31](#)

monitoring [35-32](#)

router IDs [35-32](#)

route summarization [35-29](#)

support for [1-10](#)

virtual links [35-30](#)

out-of-profile markdown [1-10](#)

P

packet modification, with QoS [33-19](#)

PAGP

Layer 2 protocol tunneling [16-9](#)

See EtherChannel

parallel paths, in routing tables [35-73](#)

passive interfaces

configuring [35-83](#)

OSPF [35-30](#)

passwords

default configuration [8-2](#)

disabling recovery of [8-5](#)

encrypting [8-3](#)

for security [1-7](#)

in clusters [5-14](#)

overview [8-1](#)

recovery of [44-3](#)

setting

enable [8-3](#)

enable secret [8-3](#)

Telnet [8-6](#)

with usernames [8-6](#)

VTP domain [13-8](#)

path cost

MSTP [18-20](#)

STP [17-18](#)

path MTU discovery [36-4](#)

PBR

defined [35-79](#)

enabling [35-81](#)

fast-switched policy-based routing [35-82](#)

local policy-based routing [35-82](#)

PC (passive command switch) [5-10](#)

peers, BGP [35-55](#)

percentage thresholds in tracked lists [39-16](#)

performance, network design [1-15](#)

performance features [1-3](#)

persistent self-signed certificate [8-43](#)

per-VLAN spanning-tree plus

See PVST+

PE to CE routing, configuring [35-67](#)

physical ports [10-2](#)

PIM

default configuration [41-10](#)

dense mode

overview [41-4](#)

rendezvous point (RP), described [41-5](#)

RPF lookups [41-8](#)

PIM (continued)

- displaying neighbors [41-52](#)
- enabling a mode [41-12](#)
- overview [41-4](#)
- router-query message interval, modifying [41-28](#)
- shared tree and source tree, overview [41-25](#)
- shortest path tree, delaying the use of [41-26](#)
- sparse mode
 - join messages and shared tree [41-5](#)
 - overview [41-5](#)
 - prune messages [41-5](#)
 - RPF lookups [41-8](#)
- stub routing
 - displaying [41-52](#)
 - enabling [41-13](#)
 - overview [41-5](#)
- support for [1-11](#)
- versions
 - interoperability [41-10](#)
 - troubleshooting interoperability problems [41-25](#)
 - v2 improvements [41-4](#)

PIM-DVMRP, as snooping method [23-9](#)

ping

- character output description [44-14](#)
- executing [44-14](#)
- overview [44-13](#)

PoE

- auto mode [10-8](#)
- CDP with power consumption, described [10-6](#)
- CDP with power negotiation, described [10-6](#)
- Cisco intelligent power management [10-6](#)
- configuring [10-21](#)
- devices supported [10-6](#)
- high-power devices operating in low-power mode [10-6](#)
- IEEE power classification levels [10-7](#)
- power budgeting [10-22](#)
- power consumption [10-22](#)

PoE (continued)

- powered-device detection and initial power allocation [10-7](#)
- power management modes [10-8](#)
- power negotiation extensions to CDP [10-6](#)
- standards supported [10-6](#)
- static mode [10-8](#)
- supported watts per port [10-6](#)
- troubleshooting [44-11](#)
- policed-DSCP map for QoS [33-63](#)
- policers
 - configuring
 - for each matched traffic class [33-49](#)
 - for more than one traffic class [33-59](#)
 - described [33-4](#)
 - displaying [33-79](#)
 - number of [33-34](#)
 - types of [33-9](#)
- policing
 - described [33-4](#)
 - hierarchical
 - See hierarchical policy maps
 - token-bucket algorithm [33-9](#)
- policy-based routing
 - See PBR
- policy maps for QoS
 - characteristics of [33-49](#)
 - described [33-7](#)
 - displaying [33-80](#)
 - hierarchical [33-8](#)
 - hierarchical on SVIs
 - configuration guidelines [33-33](#)
 - configuring [33-53](#)
 - described [33-11](#)
 - nonhierarchical on physical ports
 - configuration guidelines [33-33](#)
 - configuring [33-49](#)
 - described [33-9](#)

- port ACLs
 - defined [32-2](#)
 - types of [32-3](#)
- Port Aggregation Protocol
 - See EtherChannel
- port-based authentication
 - accounting [9-8](#)
 - authentication server
 - defined [9-2](#)
 - RADIUS server [9-3](#)
 - client, defined [9-2](#)
 - configuration guidelines [9-22](#)
 - configuring
 - 802.1x authentication [9-25](#)
 - guest VLAN [9-34](#)
 - host mode [9-27](#)
 - inaccessible authentication bypass [9-36](#)
 - manual re-authentication of a client [9-29](#)
 - periodic re-authentication [9-29](#)
 - quiet period [9-30](#)
 - RADIUS server [9-27](#)
 - RADIUS server parameters on the switch [9-26](#)
 - restricted VLAN [9-35](#)
 - switch-to-client frame-retransmission number [9-31, 9-32](#)
 - switch-to-client retransmission time [9-30](#)
 - default configuration [9-21](#)
 - described [9-1](#)
 - device roles [9-2](#)
 - displaying statistics [9-44](#)
 - EAPOL-start frame [9-5](#)
 - EAP-request/identity frame [9-5](#)
 - EAP-response/identity frame [9-5](#)
 - encapsulation [9-3](#)
 - guest VLAN
 - configuration guidelines [9-12, 9-13](#)
 - described [9-12](#)
 - host mode [9-7](#)
- port-based authentication (continued)**
 - inaccessible authentication bypass
 - configuring [9-36](#)
 - described [9-14](#)
 - guidelines [9-24](#)
 - initiation and message exchange [9-5](#)
 - magic packet [9-16](#)
 - method lists [9-25](#)
 - multiple-hosts mode, described [9-8](#)
 - per-user ACLs
 - AAA authorization [9-25](#)
 - configuration tasks [9-11](#)
 - described [9-11](#)
 - RADIUS server attributes [9-11](#)
 - ports
 - authorization state and dot1x port-control command [9-7](#)
 - authorized and unauthorized [9-7](#)
 - critical [9-14](#)
 - voice VLAN [9-15](#)
 - port security
 - and voice VLAN [9-16](#)
 - described [9-15](#)
 - interactions [9-16](#)
 - multiple-hosts mode [9-8](#)
 - resetting to default values [9-44](#)
 - statistics, displaying [9-44](#)
 - switch
 - as proxy [9-3](#)
 - RADIUS client [9-3](#)
 - upgrading from a previous release [9-24, 33-26](#)
 - VLAN assignment
 - AAA authorization [9-25](#)
 - characteristics [9-10](#)
 - configuration tasks [9-10](#)
 - described [9-10](#)

port-based authentication (continued)

voice VLAN

described 9-15

PVID 9-15

VVID 9-15

wake-on-LAN, described 9-16

port blocking 1-4, 24-7

port-channel

See EtherChannel

Port Fast

described 19-2

enabling 19-10

mode, spanning tree 12-29

support for 1-6

port membership modes, VLAN 12-3

port priority

MSTP 18-19

STP 17-17

ports

access 10-3

blocking 24-7

dual-purpose uplink 10-6

dynamic access 12-3

IEEE 802.1Q tunnel 12-4

protected 24-5

routed 10-4

secure 24-8

static-access 12-3, 12-11

switch 10-2

trunks 12-3, 12-16

VLAN assignments 12-11

port security

aging 24-16

and private VLANs 24-18

and QoS trusted boundary 33-39

configuring 24-12

default configuration 24-10

described 24-8

displaying 24-19

port security (continued)

enabling 24-18

on trunk ports 24-13

sticky learning 24-9

violations 24-9

with other features 24-10

port-shutdown response, VMPS 12-28

Power over Ethernet

See PoE

preemption, default configuration 20-4

preemption delay, default configuration 20-5

preferential treatment of traffic

See QoS

prefix lists, BGP 35-53

preventing unauthorized access 8-1

primary links 20-2

primary VLANs 14-1, 14-3

priority

HSRP 39-7

overriding CoS 15-6

trusting CoS 15-6

private VLAN edge ports

See protected ports

private VLANs

across multiple switches 14-4

and SDM template 14-4

and SVIs 14-5

benefits of 14-1

community ports 14-2

community VLANs 14-2, 14-3

configuration guidelines 14-6, 14-8

configuration tasks 14-6

configuring 14-9

default configuration 14-6

end station access to 14-3

IP addressing 14-3

isolated port 14-2

isolated VLANs 14-2, 14-3

mapping 14-13

private VLANs (continued)

- monitoring [14-14](#)
 - ports
 - community [14-2](#)
 - configuration guidelines [14-8](#)
 - configuring host ports [14-11](#)
 - configuring promiscuous ports [14-12](#)
 - described [12-4](#)
 - isolated [14-2](#)
 - promiscuous [14-2](#)
 - primary VLANs [14-1, 14-3](#)
 - promiscuous ports [14-2](#)
 - secondary VLANs [14-2](#)
 - subdomains [14-1](#)
 - traffic in [14-5](#)
- privileged EXEC mode [2-2](#)
- privilege levels
- changing the default for lines [8-9](#)
 - command switch [5-15](#)
 - exiting [8-9](#)
 - logging into [8-9](#)
 - mapping on member switches [5-15](#)
 - overview [8-2, 8-7](#)
 - setting a command with [8-8](#)
- promiscuous ports
- configuring [14-12](#)
 - defined [14-2](#)
- protected ports [1-7, 24-5](#)
- protocol-dependent modules, EIGRP [35-34](#)
- Protocol-Independent Multicast Protocol
- See PIM
- provider edge devices [35-62](#)
- proxy ARP
- configuring [35-10](#)
 - definition [35-8](#)
 - with IP routing disabled [35-11](#)

- pruning, VTP
- disabling
 - in VTP domain [13-14](#)
 - on a port [12-23](#)
 - enabling
 - in VTP domain [13-14](#)
 - on a port [12-22](#)
 - examples [13-5](#)
 - overview [13-4](#)
- pruning-eligible list
- changing [12-22](#)
 - for VTP pruning [13-4](#)
 - VLANs [13-14](#)
- PVST+
- described [17-9](#)
 - IEEE 802.1Q trunking interoperability [17-10](#)
 - instances supported [17-9](#)

Q**QoS**

- and MQC commands [33-1](#)
- auto-QoS
 - categorizing traffic [33-21](#)
 - configuration and defaults display [33-30](#)
 - configuration guidelines [33-25](#)
 - described [33-20](#)
 - disabling [33-27](#)
 - displaying generated commands [33-27](#)
 - displaying the initial configuration [33-30](#)
 - effects on running configuration [33-25](#)
 - egress queue defaults [33-21](#)
 - enabling for VoIP [33-26](#)
 - example configuration [33-28](#)
 - ingress queue defaults [33-21](#)
 - list of generated commands [33-22](#)
- basic model [33-4](#)

QoS (continued)

- classification
 - class maps, described 33-7
 - defined 33-4
 - DSCP transparency, described 33-40
 - flowchart 33-6
 - forwarding treatment 33-3
 - in frames and packets 33-3
 - IP ACLs, described 33-5, 33-7
 - MAC ACLs, described 33-5, 33-7
 - options for IP traffic 33-5
 - options for non-IP traffic 33-5
 - policy maps, described 33-7
 - trust DSCP, described 33-5
 - trusted CoS, described 33-5
 - trust IP precedence, described 33-5
- class maps
 - configuring 33-47
 - displaying 33-79
- configuration guidelines
 - auto-QoS 33-25
 - standard QoS 33-33
- configuring
 - aggregate policers 33-59
 - auto-QoS 33-20
 - default port CoS value 33-38
 - DSCP maps 33-61
 - DSCP transparency 33-40
 - DSCP trust states bordering another domain 33-41
 - egress queue characteristics 33-71
 - ingress queue characteristics 33-67
 - IP extended ACLs 33-45
 - IP standard ACLs 33-44
 - MAC ACLs 33-46
 - policy maps, hierarchical 33-53
 - policy maps on physical ports 33-49
 - port trust states within the domain 33-36
 - trusted boundary 33-39

QoS (continued)

- default auto configuration 33-21
- default standard configuration 33-31
- displaying statistics 33-79
- DSCP transparency 33-40
- egress queues
 - allocating buffer space 33-72
 - buffer allocation scheme, described 33-18
 - configuring shaped weights for SRR 33-76
 - configuring shared weights for SRR 33-77
 - described 33-4
 - displaying the threshold map 33-75
 - flowchart 33-17
 - mapping DSCP or CoS values 33-74
 - scheduling, described 33-4
 - setting WTD thresholds 33-72
 - WTD, described 33-19
- enabling globally 33-35
- flowcharts
 - classification 33-6
 - egress queueing and scheduling 33-17
 - ingress queueing and scheduling 33-15
 - policing and marking 33-10
- implicit deny 33-7
- ingress queues
 - allocating bandwidth 33-69
 - allocating buffer space 33-69
 - buffer and bandwidth allocation, described 33-16
 - configuring shared weights for SRR 33-69
 - configuring the priority queue 33-70
 - described 33-4
 - displaying the threshold map 33-68
 - flowchart 33-15
 - mapping DSCP or CoS values 33-68
 - priority queue, described 33-16
 - scheduling, described 33-4
 - setting WTD thresholds 33-68
 - WTD, described 33-16

QoS (continued)

- IP phones
 - automatic classification and queueing 33-20
 - detection and trusted settings 33-20, 33-39
- limiting bandwidth on egress interface 33-78
- mapping tables
 - CoS-to-DSCP 33-61
 - displaying 33-79
 - DSCP-to-CoS 33-64
 - DSCP-to-DSCP-mutation 33-65
 - IP-precedence-to-DSCP 33-62
 - policed-DSCP 33-63
 - types of 33-12
- marked-down actions 33-51, 33-56
- marking, described 33-4, 33-8
- overview 33-2
- packet modification 33-19
- policers
 - configuring 33-51, 33-56, 33-59
 - described 33-8
 - displaying 33-79
 - number of 33-34
 - types of 33-9
- policies, attaching to an interface 33-8
- policing
 - described 33-4, 33-8
 - token bucket algorithm 33-9
- policy maps
 - characteristics of 33-49
 - displaying 33-80
 - hierarchical 33-8
 - hierarchical on SVIs 33-53
 - nonhierarchical on physical ports 33-49
- QoS label, defined 33-4

QoS (continued)

- queues
 - configuring egress characteristics 33-71
 - configuring ingress characteristics 33-67
 - high priority (expedite) 33-19, 33-78
 - location of 33-13
 - SRR, described 33-14
 - WTD, described 33-13
- rewrites 33-19
- support for 1-9
- trust states
 - bordering another domain 33-41
 - described 33-5
 - trusted device 33-39
 - within the domain 33-36
- quality of service
 - See QoS
- queries, IGMP 23-4
- query solicitation, IGMP 23-13

R**RADIUS**

- attributes
 - vendor-proprietary 8-31
 - vendor-specific 8-29
- configuring
 - accounting 8-28
 - authentication 8-23
 - authorization 8-27
 - communication, global 8-21, 8-29
 - communication, per-server 8-21
 - multiple UDP ports 8-21
- default configuration 8-20
- defining AAA server groups 8-25
- displaying the configuration 8-31

RADIUS (continued)

- identifying the server [8-21](#)
 - in clusters [5-14](#)
 - limiting the services to the user [8-27](#)
 - method list, defined [8-20](#)
 - operation of [8-19](#)
 - overview [8-18](#)
 - suggested network environments [8-18](#)
 - support for [1-9](#)
 - tracking services accessed by user [8-28](#)
- range
- macro [10-12](#)
 - of interfaces [10-11](#)
- rapid convergence [18-10](#)
- rapid per-VLAN spanning-tree plus
- See rapid PVST+
- rapid PVST+
- described [17-9](#)
 - IEEE 802.1Q trunking interoperability [17-10](#)
 - instances supported [17-9](#)
- Rapid Spanning Tree Protocol
- See RSTP
- RARP [35-8](#)
- rcommand command [5-15](#)
- RCP
- configuration files
 - downloading [B-17](#)
 - overview [B-15](#)
 - preparing the server [B-16](#)
 - uploading [B-18](#)
 - image files
 - deleting old image [B-32](#)
 - downloading [B-30](#)
 - preparing the server [B-29](#)
 - uploading [B-32](#)
- reconfirmation interval, VMPS, changing [12-31](#)
- reconfirming dynamic VLAN membership [12-31](#)
- recovery procedures [44-1](#)
- redundancy
- EtherChannel [34-3](#)
 - HSRP [39-1](#)
 - STP
 - backbone [17-8](#)
 - path cost [12-26](#)
 - port priority [12-24](#)
- redundant links and UplinkFast [19-13](#)
- reliable transport protocol, EIGRP [35-33](#)
- reloading software [3-16](#)
- Remote Authentication Dial-In User Service
- See RADIUS
- Remote Copy Protocol
- See RCP
- Remote Network Monitoring
- See RMON
- Remote SPAN
- See RSPAN
- remote SPAN [28-2](#)
- report suppression, IGMP
- described [23-6](#)
 - disabling [23-16, 37-11](#)
- requirements
- cluster [xlv](#)
 - device manager [xliv](#)
 - Network Assistant [xliv](#)
- resequencing ACL entries [32-14](#)
- resets, in BGP [35-48](#)
- resetting a UDLD-shutdown interface [27-6](#)
- restricted VLAN
- configuring [9-35](#)
 - described [9-13](#)
 - using with IEEE 802.1x [9-13](#)
- restricting access
- NTP services [6-8](#)
 - overview [8-1](#)
 - passwords and privilege levels [8-2](#)
 - RADIUS [8-18](#)
 - TACACS+ [8-10](#)

- retry count, VMPS, changing [12-32](#)
- reverse address resolution [35-8](#)
- Reverse Address Resolution Protocol
 - See RARP
- RFC
 - 1058, RIP [35-18](#)
 - 1112, IP multicast and IGMP [23-2](#)
 - 1157, SNMPv1 [31-2](#)
 - 1163, BGP [35-40](#)
 - 1166, IP addresses [35-5](#)
 - 1253, OSPF [35-24](#)
 - 1267, BGP [35-40](#)
 - 1305, NTP [6-2](#)
 - 1587, NSSAs [35-24](#)
 - 1757, RMON [29-2](#)
 - 1771, BGP [35-40](#)
 - 1901, SNMPv2C [31-2](#)
 - 1902 to 1907, SNMPv2 [31-2](#)
 - 2236, IP multicast and IGMP [23-2](#)
 - 2273-2275, SNMPv3 [31-2](#)
- RIP
 - advertisements [35-19](#)
 - authentication [35-21](#)
 - configuring [35-20](#)
 - default configuration [35-19](#)
 - described [35-19](#)
 - for IPv6 [36-17](#)
 - hop counts [35-19](#)
 - split horizon [35-22](#)
 - summary addresses [35-22](#)
 - support for [1-10](#)
- RMON
 - default configuration [29-3](#)
 - displaying status [29-6](#)
 - enabling alarms and events [29-3](#)
 - groups supported [29-2](#)
 - overview [29-1](#)
- RMON (continued)**
 - statistics
 - collecting group Ethernet [29-5](#)
 - collecting group history [29-5](#)
 - support for [1-12](#)
- root guard
 - described [19-8](#)
 - enabling [19-15](#)
 - support for [1-6](#)
- root switch
 - MSTP [18-17](#)
 - STP [17-14](#)
- route calculation timers, OSPF [35-30](#)
- route dampening, BGP [35-59](#)
- routed packets, ACLs on [32-38](#)
- routed ports
 - configuring [35-3](#)
 - defined [10-4](#)
 - in switch clusters [5-8](#)
 - IP addresses on [10-25, 35-4](#)
- route-map command [35-82](#)
- route maps
 - BGP [35-51](#)
 - policy-based routing [35-80](#)
- router ACLs
 - defined [32-2](#)
 - types of [32-4](#)
- route reflectors, BGP [35-58](#)
- router ID, OSPF [35-32](#)
- route selection, BGP [35-49](#)
- route summarization, OSPF [35-29](#)
- route targets, VPN [35-63](#)
- routing
 - default [35-2](#)
 - dynamic [35-3](#)
 - redistribution of information [35-76](#)
 - static [35-3](#)
- routing domain confederation, BGP [35-58](#)

Routing Information Protocol

See RIP

routing protocol administrative distances [35-74](#)

RSPAN

characteristics [28-8](#)

configuration guidelines [28-16](#)

default configuration [28-9](#)

defined [28-2](#)

destination ports [28-7](#)

displaying status [28-23](#)

interaction with other features [28-8](#)

monitored ports [28-5](#)

monitoring ports [28-7](#)

overview [1-11,28-1](#)

received traffic [28-4](#)

sessions

creating [28-17](#)

defined [28-3](#)

limiting source traffic to specific VLANs [28-22](#)

specifying monitored ports [28-17](#)

with ingress traffic enabled [28-20](#)

source ports [28-5](#)

transmitted traffic [28-5](#)

VLAN-based [28-6](#)

RSTP

active topology [18-9](#)

BPDU

format [18-12](#)

processing [18-13](#)

designated port, defined [18-9](#)

designated switch, defined [18-9](#)

interoperability with IEEE 802.1D

described [18-8](#)

restarting migration process [18-25](#)

topology changes [18-13](#)

overview [18-8](#)

port roles

described [18-9](#)

synchronized [18-11](#)

RSTP (continued)

proposal-agreement handshake process [18-10](#)

rapid convergence

described [18-10](#)

edge ports and Port Fast [18-10](#)

point-to-point links [18-10,18-24](#)

root ports [18-10](#)

root port, defined [18-9](#)

See also MSTP

running configuration, saving [3-11](#)

S

SC (standby command switch) [5-10](#)

scheduled reloads [3-16](#)

SDM

described [7-1](#)

templates

configuring [7-4](#)

number of [7-1](#)

SDM template

configuration guidelines [7-4](#)

configuring [7-3](#)

dual IPv4 and IPv6 [7-2](#)

types of [7-1](#)

secondary VLANs [14-2](#)

secure HTTP client

configuring [8-47](#)

displaying [8-48](#)

secure HTTP server

configuring [8-46](#)

displaying [8-48](#)

secure MAC addresses

deleting [24-15](#)

maximum number of [24-9](#)

types of [24-8](#)

secure ports, configuring [24-8](#)

secure remote connections [8-38](#)

- Secure Shell
 - See SSH
- Secure Socket Layer
 - See SSL
- security, port [24-8](#)
- security features [1-7](#)
- sequence numbers in log messages [30-7](#)
- server mode, VTP [13-3](#)
- service-provider network, MSTP and RSTP [18-1](#)
- service-provider networks
 - and customer VLANs [16-2](#)
 - and IEEE 802.1Q tunneling [16-1](#)
 - Layer 2 protocols across [16-8](#)
 - Layer 2 protocol tunneling for EtherChannels [16-9](#)
- set-request operation [31-5](#)
- setup program
 - failed command switch replacement [44-9](#)
 - replacing failed command switch [44-8](#)
- severity levels, defining in system messages [30-8](#)
- SFPs
 - monitoring status of [10-28, 44-13](#)
 - security and identification [44-12](#)
 - status, displaying [44-13](#)
- shaped round robin
 - See SRR
- show access-lists hw-summary command [32-21](#)
- show and more command output, filtering [2-10](#)
- show cdp traffic command [25-5](#)
- show cluster members command [5-15](#)
- show configuration command [10-24](#)
- show forward command [44-20](#)
- show interfaces command [10-18, 10-24](#)
- show l2protocol command [16-13, 16-15, 16-16](#)
- show lldp traffic command [26-7](#)
- show platform forward command [44-20](#)
- show running-config command
 - displaying ACLs [32-19, 32-20, 32-30, 32-33](#)
 - interface description in [10-24](#)
- shutdown command on interfaces [10-29](#)
- shutdown threshold for Layer 2 protocol packets [16-11](#)
- Simple Network Management Protocol
 - See SNMP
- Smartports macros
 - applying Cisco-default macros [11-6](#)
 - applying global parameter values [11-5, 11-6](#)
 - applying macros [11-5](#)
 - applying parameter values [11-5, 11-7](#)
 - configuration guidelines [11-3](#)
 - creating [11-4](#)
 - default configuration [11-2](#)
 - defined [11-1](#)
 - displaying [11-8](#)
 - tracing [11-3](#)
 - website [11-2](#)
- SNAP [25-1](#)
- SNMP
 - accessing MIB variables with [31-4](#)
 - agent
 - described [31-4](#)
 - disabling [31-8](#)
 - authentication level [31-11](#)
 - community strings
 - configuring [31-8](#)
 - for cluster switches [31-4](#)
 - overview [31-4](#)
 - configuration examples [31-16](#)
 - default configuration [31-7](#)
 - engine ID [31-7](#)
 - groups [31-7, 31-10](#)
 - host [31-7](#)
 - ifIndex values [31-6](#)
 - in-band management [1-5](#)
 - in clusters [5-14](#)

SNMP (continued)

- informs
 - and trap keyword [31-12](#)
 - described [31-5](#)
 - differences from traps [31-5](#)
 - disabling [31-15](#)
 - enabling [31-15](#)
- limiting access by TFTP servers [31-16](#)
- limiting system log messages to NMS [30-9](#)
- manager functions [1-4, 31-3](#)
- managing clusters with [5-15](#)
- MIBs
 - location of [A-3](#)
 - supported [A-1](#)
- notifications [31-5](#)
- overview [31-1, 31-4](#)
- security levels [31-3](#)
- status, displaying [31-17](#)
- system contact and location [31-15](#)
- trap manager, configuring [31-14](#)
- traps
 - described [31-3, 31-5](#)
 - differences from informs [31-5](#)
 - disabling [31-15](#)
 - enabling [31-12](#)
 - enabling MAC address notification [6-22](#)
 - overview [31-1, 31-5](#)
 - types of [31-12](#)
- users [31-7, 31-10](#)
- versions supported [31-2](#)
- SNMPv1 [31-2](#)
- SNMPv2C [31-2](#)
- SNMPv3 [31-2](#)
- snooping, IGMP [23-2](#)
- software images
 - location in flash [B-20](#)
 - recovery procedures [44-2](#)
 - scheduling reloads [3-16](#)
 - tar file format, described [B-20](#)
 - See also downloading and uploading
- source addresses
 - in IPv4 ACLs [32-11](#)
 - in IPv6 ACLs [38-5](#)
- source-and-destination-IP address based forwarding, EtherChannel [34-7](#)
- source-and-destination MAC address forwarding, EtherChannel [34-7](#)
- source-IP address based forwarding, EtherChannel [34-7](#)
- source-MAC address forwarding, EtherChannel [34-6](#)
- SPAN
 - configuration guidelines [28-10](#)
 - default configuration [28-9](#)
 - destination ports [28-7](#)
 - displaying status [28-23](#)
 - interaction with other features [28-8](#)
 - monitored ports [28-5](#)
 - monitoring ports [28-7](#)
 - overview [1-11, 28-1](#)
 - ports, restrictions [24-11](#)
 - received traffic [28-4](#)
 - sessions
 - configuring ingress forwarding [28-14, 28-21](#)
 - creating [28-11](#)
 - defined [28-3](#)
 - limiting source traffic to specific VLANs [28-14](#)
 - removing destination (monitoring) ports [28-12](#)
 - specifying monitored ports [28-11](#)
 - with ingress traffic enabled [28-13](#)
 - source ports [28-5](#)
 - transmitted traffic [28-5](#)
 - VLAN-based [28-6](#)
- spanning tree and native VLANs [12-19](#)

- Spanning Tree Protocol
 - See STP
- SPAN traffic [28-4](#)
- split horizon, RIP [35-22](#)
- SRR
 - configuring
 - shaped weights on egress queues [33-76](#)
 - shared weights on egress queues [33-77](#)
 - shared weights on ingress queues [33-69](#)
 - described [33-14](#)
 - shaped mode [33-14](#)
 - shared mode [33-14](#)
 - support for [1-10](#)
- SSH
 - configuring [8-39](#)
 - cryptographic software image [8-37](#)
 - described [1-5, 8-38](#)
 - encryption methods [8-38](#)
 - user authentication methods, supported [8-38](#)
- SSL
 - configuration guidelines [8-45](#)
 - configuring a secure HTTP client [8-47](#)
 - configuring a secure HTTP server [8-46](#)
 - cryptographic software image [8-42](#)
 - described [8-42](#)
 - monitoring [8-48](#)
- standby command switch
 - configuring
 - considerations [5-11](#)
 - defined [5-2](#)
 - priority [5-10](#)
 - requirements [5-3](#)
 - virtual IP address [5-11](#)
 - See also cluster standby group and HSRP
- standby group, cluster
 - See cluster standby group and HSRP
- standby ip command [39-5](#)
- standby links [20-2](#)
- standby router [39-1](#)
- standby timers, HSRP [39-10](#)
- startup configuration
 - booting
 - manually [3-13](#)
 - specific image [3-14](#)
 - clearing [B-19](#)
 - configuration file
 - automatically downloading [3-12](#)
 - specifying the filename [3-12](#)
 - default boot configuration [3-12](#)
- stateless autoconfiguration [36-5](#)
- static access ports
 - assigning to VLAN [12-11](#)
 - defined [10-3, 12-3](#)
- static addresses
 - See addresses
- static IP routing [1-10](#)
- static MAC addressing [1-7](#)
- static routes
 - configuring [35-74](#)
 - configuring for IPv6 [36-15](#)
- static routing [35-3](#)
- static VLAN membership [12-2](#)
- statistics
 - 802.1x [9-44](#)
 - CDP [25-4](#)
 - interface [10-28](#)
 - IP multicast routing [41-52](#)
 - LLDP [26-7](#)
 - LLDP-MED [26-7](#)
 - OSPF [35-32](#)
 - QoS ingress and egress [33-79](#)
 - RMON group Ethernet [29-5](#)
 - RMON group history [29-5](#)
 - SNMP input and output [31-17](#)
 - VTP [13-16](#)
- sticky learning [24-9](#)

storm control

- configuring 24-3
- described 24-1
- disabling 24-5
- displaying 24-19
- support for 1-3
- thresholds 24-1

STP

- accelerating root port selection 19-4

BackboneFast

- described 19-5
- disabling 19-14
- enabling 19-13

BPDU filtering

- described 19-3
- disabling 19-12
- enabling 19-12

BPDU guard

- described 19-2
- disabling 19-12
- enabling 19-11

- BPDU message exchange 17-3

- configuration guidelines 17-12, 19-10

configuring

- forward-delay time 17-21
- hello time 17-20
- maximum aging time 17-21
- path cost 17-18
- port priority 17-17
- root switch 17-14
- secondary root switch 17-16
- spanning-tree mode 17-13
- switch priority 17-19
- transmit hold-count 17-22

- counters, clearing 17-22

- default configuration 17-11

- default optional feature configuration 19-9

- designated port, defined 17-3

- designated switch, defined 17-3

STP (continued)

- detecting indirect link failures 19-5

- disabling 17-14

- displaying status 17-22

EtherChannel guard

- described 19-7
- disabling 19-14
- enabling 19-14

extended system ID

- effects on root switch 17-14
- effects on the secondary root switch 17-16
- overview 17-4
- unexpected behavior 17-15

- features supported 1-6

- IEEE 802.1D and bridge ID 17-4

- IEEE 802.1D and multicast addresses 17-8

- IEEE 802.1t and VLAN identifier 17-4

- inferior BPDU 17-3

- instances supported 17-9

- interface state, blocking to forwarding 19-2

interface states

- blocking 17-6
- disabled 17-7
- forwarding 17-5, 17-6
- learning 17-6
- listening 17-6
- overview 17-4

- interoperability and compatibility among modes 17-10

- keepalive messages 17-2

- Layer 2 protocol tunneling 16-8

- limitations with IEEE 802.1Q trunks 17-10

load sharing

- overview 12-24
- using path costs 12-26
- using port priorities 12-24

loop guard

- described 19-9
- enabling 19-15

STP (continued)

- modes supported 17-9
 - multicast addresses, effect of 17-8
 - optional features supported 1-6
 - overview 17-2
 - path costs 12-26
 - Port Fast
 - described 19-2
 - enabling 19-10
 - port priorities 12-25
 - preventing root switch selection 19-8
 - protocols supported 17-9
 - redundant connectivity 17-8
 - root guard
 - described 19-8
 - enabling 19-15
 - root port, defined 17-3
 - root switch
 - configuring 17-15
 - effects of extended system ID 17-4, 17-14
 - election 17-3
 - unexpected behavior 17-15
 - shutdown Port Fast-enabled port 19-2
 - status, displaying 17-22
 - superior BPDU 17-3
 - timers, described 17-20
 - UplinkFast
 - described 19-3
 - enabling 19-13
 - VLAN-bridge 17-10
- stratum, NTP 6-2
- stub areas, OSPF 35-28
- stub routing, EIGRP 35-39
- subdomains, private VLAN 14-1
- subnet mask 35-5
- subnet zero 35-6
- success response, VMPS 12-28
- summer time 6-13
- SunNet Manager 1-4
- supernet 35-6
- SVIs
 - and IP unicast routing 35-3
 - and router ACLs 32-4
 - connecting VLANs 10-9
 - defined 10-5
 - routing between VLANs 12-2
- switch clustering technology 5-1
 - See also clusters, switch
- switch console port 1-5
- Switch Database Management
 - See SDM
- switched packets, ACLs on 32-37
- Switched Port Analyzer
 - See SPAN
- switched ports 10-2
- switchport block multicast command 24-7
- switchport block unicast command 24-7
- switchport command 10-14
- switchport mode dot1q-tunnel command 16-6
- switchport protected command 24-6
- switch priority
 - MSTP 18-21
 - STP 17-19
- switch software features 1-1
- switch virtual interface
 - See SVI
- synchronization, BGP 35-45
- syslog
 - See system message logging
- system clock
 - configuring
 - daylight saving time 6-13
 - manually 6-11
 - summer time 6-13
 - time zones 6-12
 - displaying the time and date 6-12
 - overview 6-1
 - See also NTP

system message logging

- default configuration 30-3
- defining error message severity levels 30-8
- disabling 30-4
- displaying the configuration 30-13
- enabling 30-4
- facility keywords, described 30-13
- level keywords, described 30-9
- limiting messages 30-9
- message format 30-2
- overview 30-1
- sequence numbers, enabling and disabling 30-7
- setting the display destination device 30-4
- synchronizing log messages 30-5
- syslog facility 1-12
- time stamps, enabling and disabling 30-7
- UNIX syslog servers
 - configuring the daemon 30-11
 - configuring the logging facility 30-12
 - facilities supported 30-13

system MTU and IEEE 802.1Q tunneling 16-5

system name

- default configuration 6-15
- default setting 6-15
- manual configuration 6-15

See also DNS

system prompt, default setting 6-14, 6-15

system resources, optimizing 7-1

T

TACACS+

- accounting, defined 8-11
- authentication, defined 8-11
- authorization, defined 8-11

TACACS+ (continued)

- configuring
 - accounting 8-17
 - authentication key 8-13
 - authorization 8-16
 - login authentication 8-14
- default configuration 8-13
- displaying the configuration 8-17
- identifying the server 8-13
- in clusters 5-14
- limiting the services to the user 8-16
- operation of 8-12
- overview 8-10
- support for 1-9
- tracking services accessed by user 8-17

tagged packets

- IEEE 802.1Q 16-3
- Layer 2 protocol 16-8

tar files

- creating B-6
- displaying the contents of B-6
- extracting B-7
- image file format B-20

TDR 1-12

Telnet

- accessing management interfaces 2-10
- number of connections 1-5
- setting a password 8-6

templates, SDM 7-1

temporary self-signed certificate 8-43

Terminal Access Controller Access Control System Plus

See TACACS+

terminal lines, setting a password 8-6

TFTP

- configuration files
 - downloading B-11
 - preparing the server B-10
 - uploading B-11
- configuration files in base directory 3-6

TFTP (continued)

- configuring for autoconfiguration 3-6
- image files
 - deleting B-23
 - downloading B-22
 - preparing the server B-22
 - uploading B-24
- limiting access by servers 31-16

TFTP server 1-5

threshold, traffic level 24-2

time

See NTP and system clock

Time Domain Reflector

See TDR

time-range command 32-16

time ranges in ACLs 32-16

time stamps in log messages 30-7

time zones 6-12

TLVs

defined 26-2

LLDP 26-2

LLDP-MED 26-2

Token Ring VLANs

support for 12-6

VTP support 13-4

ToS 1-9

traceroute, Layer 2

and ARP 44-16

and CDP 44-15

broadcast traffic 44-15

described 44-15

IP addresses and subnets 44-16

MAC addresses and VLANs 44-15

multicast traffic 44-15

multiple devices on a port 44-16

unicast traffic 44-15

usage guidelines 44-15

traceroute command 44-17

See also IP traceroute

tracked lists

configuring 39-14

types 39-14

tracked objects

by Boolean expression 39-14

by threshold percentage 39-16

by threshold weight 39-15

tracking interface line-protocol state 39-13

tracking IP routing state 39-13

tracking objects 39-13

tracking process 39-12

traffic

blocking flooded 24-7

fragmented 32-5

fragmented IPv6 38-2

unfragmented 32-5

traffic policing 1-9

traffic suppression 24-1

transmit hold-count

see STP

transparent mode, VTP 13-3, 13-12

trap-door mechanism 3-2

traps

configuring MAC address notification 6-22

configuring managers 31-12

defined 31-3

enabling 6-22, 31-12

notification types 31-12

overview 31-1, 31-5

troubleshooting

connectivity problems 44-13, 44-15, 44-16

detecting unidirectional links 27-1

displaying crash information 44-23

PIMv1 and PIMv2 interoperability problems 41-25

setting packet forwarding 44-20

SFP security and identification 44-12

show forward command 44-20

with CiscoWorks 31-4

with debug commands 44-19

troubleshooting (continued)

- with ping 44-13
- with system message logging 30-1
- with traceroute 44-16

trunk failover

- See link-state tracking

trunking encapsulation 1-7

trunk ports

- configuring 12-20
- defined 10-3, 12-3
- encapsulation 12-20, 12-25, 12-26

trunks

- allowed-VLAN list 12-21
- configuring 12-20, 12-25, 12-26
- ISL 12-16
- load sharing
 - setting STP path costs 12-26
 - using STP port priorities 12-24, 12-25
- native VLAN for untagged traffic 12-23
- parallel 12-26
- pruning-eligible list 12-22
- to non-DTP device 12-17

trusted boundary for QoS 33-39

trusted port states

- between QoS domains 33-41
- classification options 33-5
- ensuring port security for IP phones 33-39
- support for 1-9
- within a QoS domain 33-36

trustpoints, CA 8-42

tunneling

- defined 16-1
- IEEE 802.1Q 16-1
- Layer 2 protocol 16-8

tunnel ports

- defined 12-4
- described 10-4, 16-1
- IEEE 802.1Q, configuring 16-6
- incompatibilities with other features 16-6

twisted-pair Ethernet, detecting unidirectional links 27-1

type of service

- See ToS

U

UDLD

- configuration guidelines 27-4
- default configuration 27-4
- disabling
 - globally 27-5
 - on fiber-optic interfaces 27-5
 - per interface 27-5
- echoing detection mechanism 27-2
- enabling
 - globally 27-5
 - per interface 27-5
- Layer 2 protocol tunneling 16-10
- link-detection mechanism 27-1
- neighbor database 27-2
- overview 27-1
- resetting an interface 27-6
- status, displaying 27-6
- support for 1-6

UDP, configuring 35-15

unauthorized ports with IEEE 802.1x 9-7

unicast MAC address filtering 1-5

- and adding static addresses 6-25
- and broadcast MAC addresses 6-25
- and CPU packets 6-25
- and multicast addresses 6-25
- and router MAC addresses 6-25
- configuration guidelines 6-25
- described 6-25

unicast storm 24-1

unicast storm control command 24-4

unicast traffic, blocking 24-7

UniDirectional Link Detection protocol

- See UDLD

- UNIX syslog servers
 - daemon configuration [30-11](#)
 - facilities supported [30-13](#)
 - message logging configuration [30-12](#)
 - unrecognized Type-Length-Value (TLV) support [13-4](#)
 - upgrading information
 - See release notes
 - upgrading software images
 - See downloading
 - UplinkFast
 - described [19-3](#)
 - disabling [19-13](#)
 - enabling [19-13](#)
 - support for [1-6](#)
 - uploading
 - configuration files
 - preparing [B-10](#), [B-13](#), [B-16](#)
 - reasons for [B-8](#)
 - using FTP [B-14](#)
 - using RCP [B-18](#)
 - using TFTP [B-11](#)
 - image files
 - preparing [B-22](#), [B-25](#), [B-29](#)
 - reasons for [B-20](#)
 - using FTP [B-28](#)
 - using RCP [B-32](#)
 - using TFTP [B-24](#)
 - User Datagram Protocol
 - See UDP
 - user EXEC mode [2-2](#)
 - username-based authentication [8-6](#)
-
- V
- version-dependent transparent mode [13-4](#)
 - virtual IP address
 - cluster standby group [5-11](#)
 - command switch [5-11](#)
 - Virtual Private Network
 - See VPN
 - virtual router [39-1](#), [39-2](#)
 - vlan.dat file [12-5](#)
 - VLAN 1, disabling on a trunk port [12-22](#)
 - VLAN 1 minimization [12-21](#)
 - VLAN ACLs
 - See VLAN maps
 - vlan-assignment response, VMPS [12-28](#)
 - VLAN configuration
 - at bootup [12-8](#)
 - saving [12-8](#)
 - VLAN configuration mode [2-2](#), [12-7](#)
 - VLAN database
 - and startup configuration file [12-8](#)
 - and VTP [13-1](#)
 - VLAN configuration saved in [12-7](#)
 - VLANs saved in [12-4](#)
 - vlan database command [12-7](#)
 - vlan dot1q tag native command [16-5](#)
 - VLAN filtering and SPAN [28-6](#)
 - vlan global configuration command [12-7](#)
 - VLAN ID, discovering [6-26](#)
 - VLAN load balancing on flex links [20-2](#)
 - configuration guidelines [20-5](#)
 - VLAN management domain [13-2](#)
 - VLAN Management Policy Server
 - See VMPS
 - VLAN map entries, order of [32-29](#)
 - VLAN maps
 - applying [32-33](#)
 - common uses for [32-33](#)
 - configuration guidelines [32-29](#)
 - configuring [32-28](#)
 - creating [32-30](#)
 - defined [32-2](#)
 - denying access to a server example [32-35](#)
 - denying and permitting packets [32-30](#)
 - displaying [32-40](#)

VLAN maps (continued)

- examples of ACLs and VLAN maps [32-31](#)
- removing [32-33](#)
- support for [1-8](#)
- wiring closet configuration example [32-34](#)

VLAN membership

- confirming [12-31](#)
- modes [12-3](#)

VLAN Query Protocol

- See VQP

VLANs

- adding [12-9](#)
- adding to VLAN database [12-9](#)
- aging dynamic addresses [17-9](#)
- allowed on trunk [12-21](#)
- and spanning-tree instances [12-3, 12-6, 12-13](#)
- configuration guidelines, extended-range VLANs [12-13](#)
- configuration guidelines, normal-range VLANs [12-6](#)
- configuration options [12-7](#)
- configuring [12-1](#)
- configuring IDs 1006 to 4094 [12-13](#)
- connecting through SVIs [10-9](#)
- creating in config-vlan mode [12-9](#)
- creating in VLAN configuration mode [12-10](#)
- customer numbering in service-provider networks [16-3](#)
- default configuration [12-8](#)
- deleting [12-10](#)
- described [10-2, 12-1](#)
- displaying [12-16](#)
- extended-range [12-1, 12-12](#)
- features [1-7](#)
- illustrated [12-2](#)
- internal [12-13](#)
- limiting source traffic with RSPAN [28-22](#)
- limiting source traffic with SPAN [28-14](#)
- modifying [12-9](#)
- multicast [23-17](#)

VLANs (continued)

- native, configuring [12-23](#)
 - normal-range [12-1, 12-4](#)
 - number supported [1-7](#)
 - parameters [12-5](#)
 - port membership modes [12-3](#)
 - static-access ports [12-11](#)
 - STP and IEEE 802.1Q trunks [17-10](#)
 - supported [12-2](#)
 - Token Ring [12-6](#)
 - traffic between [12-2](#)
 - VLAN-bridge STP [17-10, 43-2](#)
 - VTP modes [13-3](#)
- VLAN Trunking Protocol**
- See VTP
- VLAN trunks** [12-16](#)

VMPS

- administering [12-32](#)
 - configuration example [12-33](#)
 - configuration guidelines [12-29](#)
 - default configuration [12-29](#)
 - description [12-27](#)
 - dynamic port membership
 - described [12-28](#)
 - reconfirming [12-31](#)
 - troubleshooting [12-33](#)
 - entering server address [12-30](#)
 - mapping MAC addresses to VLANs [12-28](#)
 - monitoring [12-32](#)
 - reconfirmation interval, changing [12-31](#)
 - reconfirming membership [12-31](#)
 - retry count, changing [12-32](#)
- voice-over-IP** [15-1](#)
- voice VLAN**
- Cisco 7960 phone, port connections [15-1](#)
 - configuration guidelines [15-3](#)
 - configuring IP phones for data traffic
 - override CoS of incoming frame [15-6](#)
 - trust CoS priority of incoming frame [15-6](#)

voice VLAN (continued)

- configuring ports for voice traffic in
 - 802.1p priority tagged frames 15-5
 - 802.1Q frames 15-5
- connecting to an IP phone 15-4
- default configuration 15-3
- described 15-1
- displaying 15-7
- IP phone data traffic, described 15-2
- IP phone voice traffic, described 15-2

VPN

- configuring routing in 35-66
- forwarding 35-64
- in service provider networks 35-61
- routes 35-62

VPN routing and forwarding table

See VRF

VQP 1-7, 12-27**VRF**

- defining 35-63
- tables 35-61

VTP

- adding a client to a domain 13-14
- advertisements 12-19, 13-3
- and extended-range VLANs 13-1
- and normal-range VLANs 13-1
- client mode, configuring 13-11
- configuration
 - global configuration mode 13-7
 - guidelines 13-8
 - privileged EXEC mode 13-7
 - requirements 13-9
 - saving 13-7
 - VLAN configuration mode 13-7
- configuration mode options 13-7
- configuration requirements 13-9
- configuration revision number
 - guideline 13-14
 - resetting 13-15

VTP (continued)

- configuring
 - client mode 13-11
 - server mode 13-9
 - transparent mode 13-12
- consistency checks 13-4
- default configuration 13-6
- described 13-1
- disabling 13-12
- domain names 13-8
- domains 13-2
- Layer 2 protocol tunneling 16-8
- modes
 - client 13-3, 13-11
 - server 13-3, 13-9
 - transitions 13-3
 - transparent 13-3, 13-12
- monitoring 13-16
- passwords 13-8
- pruning
 - disabling 13-14
 - enabling 13-14
 - examples 13-5
 - overview 13-4
 - support for 1-7
- pruning-eligible list, changing 12-22
- server mode, configuring 13-9
- statistics 13-16
- support for 1-7
- Token Ring support 13-4
- transparent mode, configuring 13-12
- using 13-1
- version, guidelines 13-8
- Version 1 13-4
- Version 2
 - configuration guidelines 13-8
 - disabling 13-13
 - enabling 13-13
 - overview 13-4

W**WCCP**

- authentication [40-3](#)
- configuration guidelines [40-5](#)
- default configuration [40-5](#)
- described [40-1](#)
- displaying [40-9](#)
- dynamic service groups [40-3](#)
- enabling [40-6](#)
- features unsupported [40-4](#)
- forwarding method [40-3](#)
- Layer-2 header rewrite [40-3](#)
- MD5 security [40-3](#)
- message exchange [40-2](#)
- monitoring and maintaining [40-9](#)
- negotiation [40-3](#)
- packet redirection [40-3](#)
- packet-return method [40-3](#)
- redirecting traffic received from a client [40-6](#)
- setting the password [40-6](#)
- unsupported WCCPv2 features [40-4](#)

web authentication

- configuring [9-41 to 9-43](#)
- described [1-7, 9-20](#)
- fallback for IEEE 802.1x [9-42](#)

Web Cache Communication Protocol

See [WCCP](#)

weighted tail drop

See [WTD](#)

weight thresholds in tracked lists [39-15](#)**wizards** [1-3](#)**WTD**

- described [33-13](#)
- setting thresholds
 - egress queue-sets [33-72](#)
 - ingress queues [33-68](#)
- support for [1-10](#)

X**Xmodem protocol** [44-2](#)