



## Callback\_Disconnect\_Caller

The `Callback_Disconnect_Caller` element is responsible for disconnecting the caller's leg of the call. The IP leg of the call for Unified CVP is preserved to hold the caller's *place in line* until the callback is made back to the caller.

- [Settings, on page 1](#)
- [Element Data, on page 1](#)
- [Exit States, on page 2](#)
- [Folder and Class Information, on page 2](#)
- [Events, on page 2](#)

### Settings

Name (Label)	Type	Req'd	Single Setting Value	Substitution Allowed	Default	Notes
Probe Type	string enum	Yes	Yes	No	Disconnect Caller	The probe type can be one of: Disconnect Caller   Intercept Caller Hangup   No Intercept Caller Hangup

### Element Data

Name	Type	Notes
Result	string	The call outcome from the attempt to disconnect the caller's leg.

## Exit States

Name	Notes
done	The element is successfully run to retrieve the value.
error	The element failed to retrieve the value.

## Folder and Class Information

Studio Element Folder Name	Class Name
Cisco > Callback	com.cisco.cvp.vxml.custelem.callback.DisconnectCaller

## Events

Name (Label)	Notes
Event Type	You can select <b>Java Exception</b> , <b>VXML Event</b> , or <b>Hotlink</b> as event handler for this element.