



## CHAPTER 24

# Troubleshooting Digital Certificates

---

This chapter describes how to troubleshoot digital certificates created and maintained in the Cisco MDS 9000 Family. It includes the following sections:

- [Overview, page 24-1](#)
- [Initial Troubleshooting Checklist, page 24-3](#)
- [Digital Certificate Issues, page 24-4](#)

## Overview

Public Key Infrastructure (PKI) support provides the means for the Cisco MDS 9000 Family of switches to obtain and use digital certificates for secure communication in the network. PKI support provides manageability and scalability for IPsec/IKE and SSH.

## Digital Certificates

Digital signatures, based on public key cryptography, digitally authenticate devices and individual users. In public key cryptography, each device or user has a key pair containing both a private key and a public key. Digital certificates link the digital signature to the remote device. A digital certificate contains information to identify a user or device, such as the name, serial number, company, department, or IP address. It also contains a copy of the entity's public key. The certificate is itself signed by a certificate authority (CA), a third party that is explicitly trusted by the receiver to validate identities and to create digital certificates.

## Certificate Authorities

The trust model used in PKI support is hierarchical with multiple configurable trusted CAs. Each participating entity is configured with a list of CAs to be trusted so that the peer's certificate obtained during the security protocol exchanges can be verified, provided it has been issued by one of the locally trusted CAs. To accomplish this, the CA's self signed root certificate (or certificate chain for a subordinate CA) is locally stored. The MDS switch can also enroll with a trusted CA (trust point CA) to obtain an identity certificate (for example, for IPsec/IKE).

***Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)***

## RSA Key Pairs and Identity Certificates

You can generate one or more RSA key pairs and associate each RSA key pair with a trusted CA where the MDS switch intends to enroll to obtain an identity certificate. The MDS switch needs only one identity per CA, which consists of one key pair and one identity certificate per CA.

## Peer Certificate Verification

The peer certificate verification process involves the following steps:

- Verifies that the peer certificate is issued by one of the locally trusted CAs.
- Verifies that the peer certificate is valid (not expired) with respect to current time.
- Verifies that the peer certificate is not yet revoked by the issuing CA.

## CRLs and OCSP Support

Two methods are supported for verifying that the peer certificate has not been revoked: certificate revocation list (CRL) and Online Certificate Status Protocol (OCSP). The switch uses one or both of these methods to verify that the peer certificate has not been revoked.

CRLs are maintained by CAs to give information of prematurely revoked certificates, and the CRLs are published in a repository.

Cisco MDS SAN-OS allows the manual configuration of pre-downloaded CRLs for the trusted CAs, and then caches them in the switch bootflash (cert-store). During the verification of a peer certificate by IPsec or SSH, the issuing CA's CRL is consulted only if the CRL has already been cached locally and the revocation checking is configured to use CRL. Otherwise, CRL checking is not performed and the certificate is considered to be not revoked if no other revocation checking methods are configured.

OCSP facilitates online certificate revocation checking. You can specify an OCSP URL for each trusted CA.

## Import and Export Support for Certificates and Associated Key Pairs

As part of the CA authentication and enrollment process, the CA certificate (or the entire chain in the case of a subordinate CA) and the identity certificates can be imported in standard PEM (base64) format.

The complete identity information in a trust point can be exported to a file in the password-protected PKCS#12 standard format. The information in a PKCS#12 file consists of the RSA key pair, the identity certificate, and the CA certificate (or chain).

## PKI Enrollment Support

The PKI enrollment process for a switch involves the following steps:

1. Create a trust point and authenticate the CA to it.
1. Generate an RSA private and public key pair on the switch.
2. Associate the RSA key pair to the trust point.
3. Generate a certificate request in standard format and forward it to the CA.

## Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)

4. Might require manual intervention at the CA server by the CA administrator to approve the enrollment request when it is received by the CA.
5. Receive the issued certificate back from the CA, signed with the CA's private key.
6. Write the certificate into a nonvolatile storage area on the switch (bootflash).

Cisco MDS SAN-OS supports certificate retrieval and enrollment using a manual cut-and-paste method. Cut-and-paste enrollment literally means you must cut and paste the certificate requests and resulting certificates between the switch (using a console, Telnet, or SSH connection) and the CA, as follows:

1. Create an enrollment certificate request, which is displayed in base64-encoded text form.
2. Cut and paste the encoded certificate request text in an e-mail message or in a web form and send it to the CA.
3. Receive the issued certificate (in base64-encoded text form) from the CA in an e-mail message or in a web browser download.
4. Cut and paste the issued certificate to the switch using the certificate import facility.

## Maximum Limits

Table 24-1 lists the maximum limits for CAs and digital certificate parameters.

**Table 24-1** Maximum Limits for CA and Digital Certificate

Feature	Maximum Limit
Trust points declared on a switch	16
RSA key pairs generated on a switch	16
Identity certificates configured on a switch	16
Certificates in a CA certificate chain	10
Trust points authenticated to a specific CA	10

## Initial Troubleshooting Checklist

Begin troubleshooting digital certificates issues by checking the following issues first:

Checklist	Check off
Verify that the fully qualified domain name (FQDN) has been configured on the switch.	<input type="checkbox"/>
Verify that all the CA certificates in a CA chain for a trusted CA are added to the switch if the CA is not self-signed.	<input type="checkbox"/>
Verify that you have installed your identity certificates.	<input type="checkbox"/>
Verify that you have revoked your identity certificates if you delete the associated RSA key pairs.	<input type="checkbox"/>

## Common Troubleshooting Tools in Fabric Manager

Choose **Switches > Security > PKI** to access digital certificates.

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

## Common Troubleshooting Commands in the CLI

The following commands may be useful in troubleshooting digital certificate issues:

- `show crypto ca certificates`
- `show crypto key`
- `show crypto ca crt`
- `show crypto ca trustpoint`

## Digital Certificate Issues

This section describes troubleshooting digital certificates and includes the following topics:

- [CA Will Not Generate Identity Certificate, page 24-4](#)
- [Cannot Export Identity Certificate in PKCS#12 Format, page 24-5](#)
- [Certificate Fails at Peer, page 24-5](#)
- [PKI Fails After Reboot, page 24-10](#)
- [Cannot Import Certificate and RSA Key Pairs from Backup, page 24-10](#)

## CA Will Not Generate Identity Certificate

**Symptom** CA will not generate an identity certificate.

**Table 24-2** CA Will Not Generate Identity Certificate

Symptom	Possible Cause	Solution
CA will not generate an identity certificate.	FQDN is not configured.	Configure the host name and the IP domain name. Choose <b>Switches</b> in Fabric Manager and set the LogicalName field to the host name. Choose <b>Switches &gt; Interfaces &gt; Management &gt; DNS</b> and set the DefaultDomainName field.  Or use the <code>hostname</code> and the <code>ip domain-name</code> CLI commands.
	Empty challenge password is specified.	Specify a non-empty challenge password during enrollment.  Create exportable RSA keys. Choose <b>Switches &gt; Security &gt; PKI</b> in Fabric Manager and click the <b>Trustpoint Action</b> tab. Select <code>certreq</code> from the Command drop-down menu, fill in the URL field and enter the challenge password in the Password field. Click <b>Apply Changes</b> .  Or use the <code>crypto ca enroll</code> CLI command and enter a challenge password during enrollment.

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

## Cannot Export Identity Certificate in PKCS#12 Format

**Symptom** Cannot export identity certificate in PKCS#12 format.

**Table 24-3** *Cannot Export Identity Certificate in PKCS#12 Format*

Symptom	Possible Cause	Solution
Cannot export identity certificate in PKCS#12 format.	RSA keys not exportable.	Create exportable RSA keys. Choose <b>Switches &gt; Security &gt; PKI</b> in Fabric Manager and click <b>Create Row</b> . Check the <b>Exportable</b> check box and create an RSA key pair.  Or use the <b>crypto key generate rsa exportable</b> CLI command.

## Certificate Fails at Peer

**Symptom** Certificate fails at peer.

**Table 24-4** *Certificate Fails at Peer*

Symptom	Possible Cause	Solution
Certificate fails at peer.	FQDN changed after certificate was issued.	Revoke certificate and re-create. See the <a href="#">“Configuring Certificates on the MDS Switch Using Fabric Manager”</a> section on page 24-5 or the <a href="#">“Configuring Certificates on the MDS Switch Using the CLI”</a> section on page 24-7.
	Local and remote clocks are not synchronized.	If the clocks are not synchronized, the certificate may appear to be expired. Validate the clocks on the local and peer device.
	Peer does not recognize CA issuing the certificate.	Create a certificate for the CAs known to the peer device. See the <a href="#">“Configuring Certificates on the MDS Switch Using Fabric Manager”</a> section on page 24-5 or the <a href="#">“Configuring Certificates on the MDS Switch Using the CLI”</a> section on page 24-7.

## Configuring Certificates on the MDS Switch Using Fabric Manager

To configure certificates on an MDS switch using Fabric Manager, follow these steps:

- Step 1** Choose **Switches** and set the LogicalName field to configure the switch host name.
- Step 2** Choose **Switches > Interfaces > Management > DNS** and set the DefaultDomainName field to configure the DNS domain name for the switch.
- Step 3** Follow these steps to create an RSA key pair for the switch:
  - a. Choose **Switches > Security > PKI** and select the **RSA Key-Pair** tab.
  - b. Click **Create Row** and set the name and size field.
  - c. Check the **Exportable** check box and click **Create**.

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

- Step 4** Follow these steps to create a trust point and associate the RSA key pairs with it:
- Choose **Switches > Security > PKI** and select the **Trust Point** tab.
  - Click **Create Row** and set the TrustPointName field.
  - Select the RSA key pairs from the KeyPairName drop-down menu.
  - Select the certificates revocation method from the RevokeCheckMethods drop-down menu.
  - Click **Create**.
- Step 5** Choose **Switches > Copy Configuration** and click **Apply Changes** to copy the running-config to startup-config and save the trust point and key pair.
- Step 6** Download the CA certificate from the CA that you want to add as the trustpoint CA.
- Step 7** Follow these steps to authenticate the CA that you want to enroll to the trust point:
- In Device Manager, choose **Admin > Flash Files** and select **Copy** and then select **ftfp** from the Protocols radio button to copy the CA certificate to bootflash.
  - In Fabric Manager, choose **Switches > Security > PKI** and select the **TrustPoint Actions** tab.
  - Select **cauth** from the Command drop-down menu.
  - Click... in the URL field and select the CA certificate from bootflash.
  - Click **Apply Changes** to authenticate the CA that you want to enroll to the trust point.
  - Click the **Trust Point Actions** tab in the Information Pane.
  - Make a note of the CA certificate fingerprint displayed in the IssuerCert FingerPrint column for the trust point row in question. Compare the CA certificate fingerprint with the fingerprint already communicated by the CA (obtained from the CA web site). If the fingerprints match exactly, accept the CA by selecting the **certconfirm** trust point action. Otherwise, reject the CA by selecting the **certnoconfirm** trust point action.
  - If you selected **certconfirm** in step g, select the **Trust Point Actions** tab, select **certconfirm** from the Command drop-down menu and then click **Apply Changes**.
  - If you selected **certnoconfirm** in Step g, select the **Trust Point Actions** tab, select **certnoconfirm** from the Command drop-down menu, and then click **Apply Changes**.
- Step 8** Follow these steps to generate a certificate request for enrolling with that trust point:
- Select the **Trust Point Actions** tab in the Information pane.
  - Select **certreq** from the Command drop-down menu. This generates a PKCS#10 certificate signing request (CSR) needed for an identity certificate from the CA corresponding to this trust point entry.
  - Enter the output file name for storing the generated certificate request. It should be specified in the bootflash:filename format and will be used to store the CSR generated in PEM format.
  - Enter the challenge password to be included in the CSR. The challenge password is not saved with the configuration. This password is required in the event that your certificate needs to be revoked, so you must remember this password.
  - Click **Apply Changes** to save the changes.
- Step 9** Request an identity certificate from the CA.



**Note**

The CA may require manual verification before issuing the identity certificate.

## Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)

**Step 10** Follow these steps to import the identity certificate:

- a. In Device Manager, choose **Admin > Flash Files** and select **Copy**, then select **tftp** from the Protocol radio buttons to tftp copy the CA certificate to bootflash.
- b. In Fabric Manager, choose **Switches > Security > PKI** and select the **TrustPoint Actions** tab.
- c. Select the **certimport** option from the Command drop-down menu to import an identity certificate in this trust point.



**Note** The identity certificate should be available in PEM format in a file in bootflash.

- d. Enter the name of the certificate file that was copied to bootflash in the URL field in the bootflash:filename format.
- e. Click **Apply Changes** to save your changes.

If successful, the values of the identity certificate and its related objects, like the certificate file name, are automatically updated with the appropriate values as per the corresponding attributes in the identity certificate.

## Configuring Certificates on the MDS Switch Using the CLI

To configure certificates on an MDS switch using the CLI, follow these steps:

**Step 1** Configure the switch FQDN.

```
switch# config t
Enter configuration commands, one per line. End with CNTL/Z.
switch(config)# switchname Vegas-1
Vegas-1(config)#
```

**Step 2** Configure the DNS domain name for the switch.

```
Vegas-1(config)# ip domain-name cisco.com
Vegas-1(config)#
```

**Step 3** Create a trust point.

```
Vegas-1(config)# crypto ca trustpoint myCA
Vegas-1(config-trustpoint)# exit
Vegas-1(config)# do show crypto ca trustpoints
trustpoint: myCA; key:
revocation methods:  crl
Vegas-1(config)#
```

**Step 4** Create an RSA key pair for the switch.

```
Vegas-1(config)# crypto key generate rsa label myKey exportable modulus 1024
Vegas-1(config)# do show crypto key mypubkey rsa
key label: myKey
key size: 1024
exportable: yes
Vegas-1(config)#
```

**Step 5** Associate the RSA key pair to the trust point.

```
Vegas-1(config)# crypto ca trustpoint myCA
```

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

```
Vegas-1(config-trustpoint)# rsakeypair myKey
Vegas-1(config-trustpoint)# exit
Vegas-1(config)# do show crypto ca trustpoints
trustpoint: myCA; key: myKey
revocation methods:  crl
Vegas-1(config)#
```

**Step 6** Use the `copy running-config startup-config` command to save the trust point and key pair.

**Step 7** Download the CA certificate from the CA that you want to add as the trust point CA.

**Step 8** Authenticate the CA that you want to enroll to the trust point.

```
Vegas-1(config)# crypto ca authenticate myCA
input (cut & paste) CA certificate (chain) in PEM format;
end the input with a line containing only END OF INPUT :
-----BEGIN CERTIFICATE-----
MIIC4jCCAoygAwIBAgIQBWDSiay0GZRPSRiljK0ZejanBgkqhkiG9w0BAQUFADCB
kDEgMB4GCSqGSIb3DQEJARYRYW1hbmRrZUBjaXNjby5jb20xCzAJBgNVBAYTAk1O
MRIWEAYDVQQIEw1LYXJyYXRha2ExEjAQBGNVBAcTCUJhbmdbG9yZTEOMAwGA1UE
ChMFQ2lzy28xEzARBGNVBAsTCm5ldHN0b3JhZ2UxEjAQBGNVBAMTCUFwYXJyYSD
QTAeFw0wNTA1MDMyMjQ2MzdaFw0wNzA1MDMyMjU1MTdaMIGQMSAwHgYJKoZIhvcN
AQkBFhFhbWVjZGt1QGNpc2NvLmNvbTELMkGA1UEBHMCSU4xEjAQBGNVBAGTCUth
cm5hdGFrYTESMBAGA1UEBxMJQmFuZ2Fsb3JlMQ4wDAYDVQQKEwVDaXNjbzETMBEG
A1UECzMkbnV0c3RvcmlmZTESMBAGA1UEAxMJQXBhcm5hIENBMFwwDQYJKoZIhvcN
AQEBBQADSwAwSAJBAMW/7b3+DXJPANBsIHHzluNccNM87ypyzwuoSNZXOMpeRXXI
OzyBAGiXT2ASFuUowQ1iDM8rO/41jf8RrvYKvysCAwEAaA0BvzCBvDALBgNVHQ8E
BAMCAcYwDwYDVR0TAQH/BAUwAwEB/zAdBgNVHQ4EFgQUJyJyRoMbrCNMRU2OyRhQ
GgsWbHEwawYDVR0fBGQwYjAucCygKoYoAHR0cDovL3NzZS0wOC9DZXJ0RW5yb2xs
L0FwYXJyYXJyYTESMBNlNybdAwOC6gLIYqZmlsZTovL1xccc3N1LTA4XEN1cnRfbnJv
bGxcQXBhcm5hJTJwQ0EuY3JSMBAGCSsGAQQBgjcVAQQDAgEAMA0GCSqGSIb3DQEB
BQUAA0EAHv6UQ+8nE399Tww+KaGr0g0NIJaNgLh0AFcT0rEYuyt/WYGPzksF9EA
NBG7E0cN66zex0EOEFG1Vs6mKp1//w==
-----END CERTIFICATE-----
END OF INPUT
Fingerprint(s): MD5 Fingerprint=65:84:9A:27:D5:71:03:33:9C:12:23:92:38:6F:78:12

Do you accept this certificate? [yes/no]:y
Vegas-1(config)#
```

```
Vegas-1(config)# do show crypto ca certificates
Trustpoint: myCA
CA certificate 0:
subject= /emailAddress=amandke@cisco.com/C=IN/ST=Karnataka/L=Bangalore/O=Cisco/O
U=netstorage/CN=Aparna CA
issuer= /emailAddress=amandke@cisco.com/C=IN/ST=Karnataka/L=Bangalore/O=Cisco/OU
=netstorage/CN=Aparna CA
serial=0560D289ACB419944F4912258CAD197A
notBefore=May 3 22:46:37 2005 GMT
notAfter=May 3 22:55:17 2007 GMT
MD5 Fingerprint=65:84:9A:27:D5:71:03:33:9C:12:23:92:38:6F:78:12
purposes: sslserver sslclient ike
```

```
Vegas-1(config)#
```

**Step 9** Generate a certificate request for enrolling with that trust point.

```
Vegas-1(config)# crypto ca enroll myCA
Create the certificate request ..
Create a challenge password. You will need to verbally provide this
password to the CA Administrator in order to revoke your certificate.
For security reasons your password will not be saved in the configuration.
Please make a note of it.
Password:nbv123
The subject name in the certificate will be: Vegas-1.cisco.com
```

## Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)

```

Include the switch serial number in the subject name? [yes/no]:no
Include an IP address in the subject name [yes/no]:yes
ip address:172.22.31.162
The certificate request will be displayed...
-----BEGIN CERTIFICATE REQUEST-----
MIIBqzCCARQCAQAwhDEaMBGGA1UEAxMRVnVnYXNjby5jb20wgZ8wDQYJ
KoZlIhvcNAQEaBBAQAgY0AMIGJAoGBAL8Y1UAJ2NC7jUJ1DVaSmqNigJ2kt8r141KY
0JC6ManNy4qxk8VeMXZSiLJ4JgTzKwDxbLDkTTysnjucXGvjb+wj0hEhv/y51T9y
P2NJJ8ornqShrvFZgC7ysN/PyMwKcgzhbVpj+rargZvHtGJ91XTq4WoVksCzXv8S
VqyH0vEvAgMBAAGGtZAVBgkqhkiG9w0BCQcxCBMGbmJ2MTIzMDYGCsGSIb3DQDEJ
DjEpMCCwJQYDVROAQAQ/BBswGYIRVnVnYXNjby5jb22HBKwWH6IwDQYJ
KoZlIhvcNAQEaBBAQAgYEAkt60KER6Qo8nj0sDXZVHSfJZh6K6JtDz3Gkd99G1Fwgt
PftRncWUE/pw6HayfQ12T3ecgNwe12d15133YBF2bktExiI6U188nTOjg1XMjja8=
8a23bNDpNsM8rklwA6hWkrVL8NUZEFJxqbjfngPNTZacJCUS6ZqKCMetbKytUx0=
-----END CERTIFICATE REQUEST-----
Vegas-1(config)#

```

**Step 10** Request an identity certificate from the CA.



### Note

The CA may require manual verification before issuing the identity certificate.

**Step 11** Import the identity certificate.

```

Vegas-1(config)# crypto ca import myCA certificate
input (cut & paste) certificate in PEM format:
-----BEGIN CERTIFICATE-----
MIIEADCCA6qgAwIBAgIKCj00oQAAAAAdDANBgkqhkiG9w0BAQUFADCkDEgMB4G
CSqGSIb3DQEJARYRYW1hbmRrZUBjaXNjby5jb20xZCZAJBgNVBAYTAK1OMRlWEAYD
VQQIEwllYXJuYXRha2ExEjAQBGNVBAcTCUJhbmdbG9yZTEOMAwGA1UEChMFQ2lZ
Y28xEzARBGNVBAsTCm5ldHN0b3JhZ2UxEjAQBGNVBAMTCUFwYXJuYXNjby5jb20x
NTEeMTIwMzAyNDBaFw0wNjExMTIwMzEyNDBaMBwGjAYBgNVBAMTEVZlZ2FzLTFEu
Y2lZy28uY29tMIGfMA0GCsGSIb3DQEBAQUAA4GNADCBiQKBgQC/GNVACdjQu41C
dQ1WkjkjSICdpLfk5eJSMncQujGpzcukSZPFxjF2UoiyeCYE8ylncWyw5E08rJ47
glxr42/sI9IRIb/8udU/cj9jSSfKK56koa7xWYAu8rDfz8jmCnIM4W1aY/q2q4Gsb
x7RifdV06uFqFZEgs17/Elash9LxLwIDAQABo4ICEzCCAg8wJQYDVROAQAQ/BBsw
GYIRVnVnYXNjby5jb22HBKwWH6IwHQYDVRO0BBYEFKCLi+2sspWEfgrR
bhWmlVyo9jngMIHMBGNVHSMegcQwgcGAFCCo8kaDG6wjTEVNjSkYUBoLFmxxoYGW
pIGTMIGQMSAwHgYJKoZlIhvcNAQkBFhFhbWfuZGt1QGNpc2NvLmNvbTELMakGA1UE
BHMCSU4xEjAQBGNVBAcTCUthcm5hdGFrYTESMBAGA1UEBxMJQmFuZ2Fsb3JlMQ4w
DAYDVQQKEwVdAXNjZjEtbG9yZTEMBGA1UECXMkbnV0c3RvcnFnZTESMBAGA1UEAxMjQX
cm5hIENBAGhAFYnkjrLQZlE9JEiWmrRl6MGsGA1UdHwRkMG1wLqAsocGKkGh0dHA6
Ly9zc2UtdMDgVQ2VydEVucm9sbC9BcGFybmElMjBDQs5jcmwwMKAuoCyGkMZpbGU6
Ly9cXHNzZS0wOFxDZXJ0RW5yb2xsXEFwYXJuYXNjby5jb20xNTEeMTIwMzEyNDBa
AQEEfjB8MDSGCCsGAQUFBzAChi9odHRwOi8vc3NlLTA4L0NlcnRFbnJvbGwvc3Nl
LTA4X0FwYXJuYXNjby5jb20xNTEeMTIwMzEyNDBaAQEBAANBADbGBGsbE7GNLh9xe
OTWBNbm24U69ZSuDDcOcUZUUTgrpnTqVpPyejtsyflw
E36cIZu4WsExREqxbTk8ycx7V5o=
-----END CERTIFICATE-----
Vegas-1(config)#

Vegas-1(config)# do show crypto ca certificates
Trustpoint: myCA
certificate:
subject= /CN=Vegas-1.cisco.com
issuer= /emailAddress=amandke@cisco.com/C=IN/ST=Karnataka/L=Bangalore/O=Cisco/OU
=netstorage/CN=Aparna CA
serial=0A338EA1000000000074
notBefore=Nov 12 03:02:40 2005 GMT
notAfter=Nov 12 03:12:40 2006 GMT
MD5 Fingerprint=3D:33:62:3D:B4:D0:87:A0:70:DE:A3:87:B3:4E:24:BF
purposes: sslserver sslclient ike

```

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

```
CA certificate 0:
subject= /emailAddress=amandke@cisco.com/C=IN/ST=Karnataka/L=Bangalore/O=Cisco/O
U=netstorage/CN=Aparna CA
issuer= /emailAddress=amandke@cisco.com/C=IN/ST=Karnataka/L=Bangalore/O=Cisco/OU
=netstorage/CN=Aparna CA
serial=0560D289ACB419944F4912258CAD197A
notBefore=May 3 22:46:37 2005 GMT
notAfter=May 3 22:55:17 2007 GMT
MD5 Fingerprint=65:84:9A:27:D5:71:03:33:9C:12:23:92:38:6F:78:12
purposes: sslserver sslclient ike
```

## PKI Fails After Reboot

**Symptom** PKI fails after reboot.

**Table 24-5** *PKI Fails After Reboot*

Symptom	Possible Cause	Solution
PKI fails after a reboot.	Certificates not saved to NVRAM.	Save the running-config to startup- config to save the trust point to startup. Then reimport the certificates. See the <a href="#">“Configuring Certificates on the MDS Switch Using Fabric Manager”</a> section on page 24-5 or the <a href="#">“Configuring Certificates on the MDS Switch Using the CLI”</a> section on page 24-7.

## Cannot Import Certificate and RSA Key Pairs from Backup

**Symptom** Cannot import certificate and RSA key pairs from backup.

**Table 24-6** *Cannot Import Certificate and RSA Key Pairs from Backup*

Symptom	Possible Cause	Solution
Cannot import certificate and RSA key pairs from backup.	Configured trust point is not empty.	Delete the identity certificate, the CRL, and CA certificates, and then disassociate the RSA key pair from the trust point in that order. See the <a href="#">“Importing Certificate and RSA Key Pairs from Backup Using Fabric Manager”</a> section on page 24-11 or the <a href="#">“Importing Certificate and RSA Key Pairs from Backup Using the CLI”</a> section on page 24-11.
	An RSA key pair exists with the same name as the trust point that the import failed for.	Delete the RSA key pair. Choose <b>Switches &gt; Security &gt; PKI</b> in Fabric Manager. Right-click the RSA key pair that you want to delete and click <b>Delete Row</b> . Or use the no <b>crypto key zeroize rsa</b> CLI command

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

## Importing Certificate and RSA Key Pairs from Backup Using Fabric Manager

To import certificates and RSA key pairs from a PKCS#12 backup file using Fabric Manager, follow these steps:

- 
- Step 1** Choose **Switches > Security > PKI** and select the **TrustPointDetails** tab to verify that the trust point is empty.
- Step 2** Optionally, follow these steps to empty the trust point:
- Choose **Switches > Security > PKI** and select the **TrustPoint** tab.
  - Delete the RSA key pair from the Key Pair Name field and click **Apply Changes**.
  - Choose **Switches > Security > PKI** and select the **TrustPoint Actions** tab.
  - Select **cadelete** from the Command drop-down menu and click **Apply Changes** to delete the CA certificate.
  - Select **forcecertdelete** from the Command drop-down menu and click **Apply Changes** to delete the identity certificates.
- Step 3** In Device Manager, choose **Admin > Flash Files** and select **Copy** to copy the PKCS#12 format file to the switch bootflash.
- Step 4** In Fabric Manager, choose **Switches > Security > PKI** and select the **TrustPoint Actions** tab.
- Step 5** Select the **pkcs12import** option from the Command drop-down menu to import the key pair, identity certificate, and the CA certificate or certificate chain in PKCS#12 format to the selected trust point.
- Step 6** Enter the input in bootflash:filename format, for the PKCS#12 file.
- Step 7** Enter the required password. The password is set for decoding the PKCS#12 data. On completion, the imported data is available in bootflash in the specified file.
- Step 8** Click **Apply Changes** to save the changes.

On completion the trust point is created in the RSA key pair table corresponding to the imported key pair. The certificate information is updated in the trust point.



### Note

The trust point should be empty (no RSA key pair associated with it and no CA is associated with it using CA authentication) for the PKCS#12 import to succeed.

---

## Importing Certificate and RSA Key Pairs from Backup Using the CLI

To import certificates and RSA key pairs from a PKCS#12 backup file using the CLI, follow these steps:

- 
- Step 1** Use the **show crypto ca trustpoints** command to verify that the trust point is empty.
- Step 2** Optionally, use the **delete ca-certificate** command in trust point config submode to remove the CA certificate from the trust point.

```
switch(config)# crypto ca trustpoint myCA
switch(config-trustpoint)# delete ca-certificate
```

**Send documentation comments to [mdsfeedback-doc@cisco.com](mailto:mdsfeedback-doc@cisco.com)**

**Step 3** Optionally, use the **delete certificate force** command in trust point config submode to remove the certificates from the trust point.

```
switch(config)# crypto ca trustpoint myCA  
switch(config-trustpoint)# delete certificate force
```

**Step 4** Optionally, use the **no rsakeypair** command in the trust point config submode to remove the RSA key pairs from the trust point.

```
switch(config)# crypto ca trustpoint myCA  
switch(config-trustpoint)# no rsakeypair SwitchA
```

**Step 5** Use the **copy tftp** command to copy the PKCS#12 format file to the switch.

```
switch# copy tftp:adminid.p12 bootflash:adminid.p12
```

**Step 6** Use the **crypto ca import** command to import the certificates and RSA key pairs to the trust point.

```
switch(config)# crypto ca import admin-ca pkcs12 bootflash:adminid.p12 nbv123
```

---