



Threat Grid Appliance Setup and Configuration Guide



Version: 2.3

Updated: 8/11/2017

Cisco Systems, Inc. www.cisco.com

All contents are Copyright © 2015-2017 Cisco Systems, Inc. and/or its affiliates. All rights reserved.

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company.

Cover photo: Claret Cup cactus in bloom on a ridge high above the Arches National Park visitor's center. It takes good defenses and making the most of your resources to flourish in a harsh and hostile environment. Copyright © 2015 Mary C. Ecsedy. All rights reserved. Used with permission.

Cisco Threat Grid Appliance Administrator's Guide

All contents are Copyright © 2015-2017 Cisco Systems, Inc. and/or its affiliates. All rights reserved.

CONTENTS

CONTENTS.....	i
LIST OF FIGURES.....	iv
INTRODUCTION.....	1
Who This Guide Is For	1
Release Notes	1
What’s New.....	2
<i>Automatic License Retrieval</i>	2
<i>More Windows Changes</i>	2
<i>Backups</i>	2
<i>Windows XP Changes</i>	2
<i>Integrating with Third Party Detection and Enrichment Services</i>	3
<i>Multiple URLs for Disposition Update Service Manager</i>	3
<i>ClamAV Signatures Automatic Daily Update</i>	3
<i>LDAP Authentication</i>	3
<i>Cisco UCS C220 M4 Server</i>	3
<i>AMP for Endpoints Private Cloud Integration</i>	3
<i>Version 2.0</i>	4
Support - Contacting Threat Grid.....	4
<i>Support Mode</i>	4
<i>Start Support Mode - License Workaround Prior to Version 1.4.4</i>	4
<i>Support Servers</i>	5
<i>Support Snapshots</i>	6
PLANNING	7
User Documentation and Online Help.....	7
Browsers	7
Environmental Requirements	7
Hardware Requirements.....	7
<i>Hardware Documentation</i>	8
Network Requirements.....	8
<i>DNS Server Access</i>	9

NTP Server Access..... 9

Integrations – ESA/WSA/AMP for Endpoints etc..... 9

DHCP 9

License..... 9

Rate Limits..... 9

Organizations and Users 10

Updates..... 10

User Interfaces..... 10

TGSH Dialog..... 10

OpAdmin Portal..... 11

Threat Grid Portal..... 11

CIMC 11

Network Interfaces 11

Admin Interface..... 11

Clean Interface..... 11

Dirty Interface..... 12

CIMC Interface..... 12

Reserved Interface..... 12

Login Names and Passwords - Defaults 12

Web UI Administrator..... 12

OpAdmin and Shell user 12

CIMC (Cisco Integrated Management Controller) 13

Setup and Configuration Steps Outline 13

Time Required for Setup and Configuration..... 13

SERVER SETUP 14

Network Interface Connections Setup..... 14

C220 M3 Rack Server Setup..... 14

C220 M4 Rack Server Setup..... 16

Network Interface Setup Diagram 18

Firewall Rules Suggestions 19

Dirty Interface Outbound..... 19

Dirty Interface Inbound 19

Clean Interface Outbound 19

Clean Interface Outbound Optional..... 20

Clean Interface Inbound 20

Admin Interface Outbound Optional 20

Admin Interface Inbound 21

Dirty Interface for Non Cisco-Validated/Recommended Deployment..... 21

Power On and Boot Up 22

INITIAL NETWORK CONFIGURATION – TGSH DIALOG 24

CONFIGURATION WIZARD - OPADMIN PORTAL 30

 Configuration Workflow 30

 Login to the OpAdmin Portal 30

 Admin Password Change 32

 End User License Agreement 33

 Network Configuration Settings..... 33

Network Configuration and DHCP 34

 License Installation..... 34

 Email Host Configuration 36

 Server Notifications Configuration 36

 NTP Server Configuration..... 38

 Review and Install Configuration Settings 38

INSTALLING THREAT GRID APPLIANCE UPDATES..... 42

 Appliance Build Number 42

Build Number/Version Lookup Table 43

TEST THE APPLIANCE SETUP - SUBMIT A SAMPLE 46

APPLIANCE ADMINISTRATION 47

APPENDIX A – CIMC CONFIGURATION (RECOMMENDED) 48

INDEX 51

LIST OF FIGURES

Figure 1 - OpAdmin Start a Live Support Session	5
Figure 2 - Cisco 1000BASE-T Copper SFP (GLC-T)	7
Figure 3 - Cisco UCS C220 M3 SFF Rack Server	14
Figure 4 - Cisco UCS C220 M3 Rear View Details	15
Figure 5 - Cisco UCS C220 M4 SFF Rack Server	16
Figure 6 - Cisco UCS C220 M4 Rear View Details	17
Figure 7 - Network Interfaces Setup Diagram	18
Figure 8 - Cisco Screen During Boot Up	22
Figure 9 - TGSN Dialog	23
Figure 10 - TGSN Dialog - Network Configuration Console	24
Figure 11 - Network Configuration In-Progress (clean and dirty)	25
Figure 12 - Network Configuration In-Progress (admin)	26
Figure 13 - Network Configuration Confirmation	27
Figure 14 - Network Configuration - List of Changes Made	28
Figure 15 - IP Addresses	29
Figure 16 - OpAdmin Login	31
Figure 17 - OpAdmin Change Password	32
Figure 18 - License Page	33
Figure 19 - License Page Prior to Installation	34
Figure 20 - License Information After Successful Installation	35
Figure 21 - Notifications Configuration	36
Figure 22 - Appliance is Installing	39
Figure 23 - Successful Appliance Installation	40
Figure 24 - Appliance is Rebooting	41
Figure 25 - Appliance Is Configured	41
Figure 26 - Appliance Build Number	42
Figure 27 - Threat Grid Portal Login Page	46
Figure 28 - The Cisco screen – F8 to enter the CIMC Configuration Utility	48
Figure 29 - CIMC Configuration Utility	49
Figure 30 - Cisco Integrated Management Controller (CIMC) Interface	50

INTRODUCTION

A Cisco Threat Grid appliance provides safe and highly secure on-premises advanced malware analysis, with deep threat analytics and content. Threat Grid Appliances provide the complete Threat Grid malware analysis platform, installed on a single UCS server (Cisco UCS C220-M3 or Cisco UCS C220 M4). They empower organizations operating under various compliance and policy restrictions, to submit malware samples to the appliance.

Many organizations that handle sensitive data, such as banks, health services, etc., must follow various regulatory rules and guidelines that will not allow certain types of files, such as malware artifacts, to be sent outside of the network for malware analysis. By maintaining a Cisco Threat Grid Appliance on-premises, organizations are able to send suspicious documents and files to it to be analyzed without leaving the network.

With a Threat Grid Appliance, security teams can analyze all samples using proprietary and highly secure static and dynamic analysis techniques. The appliance correlates the analysis results with hundreds of millions of previously analyzed malware artifacts, to provide a global view of malware attacks and campaigns, and their distributions. A single sample of observed activity and characteristics can quickly be correlated against millions of other samples to fully understand its behaviors within an historical and global context. This ability helps security teams to effectively defend the organization against threats and attacks from advanced malware.

Who This Guide Is For

Before a new appliance can be used for malware analysis, it must be set up and configured for the organization's network. This guide is for the security team IT staff tasked with setting up and configuring a new Threat Grid Appliance.

This document describes how to complete the initial setup and configuration for a new Threat Grid Appliance, up to the point where malware samples can be submitted to it for analysis.

For more information, please see the Cisco Threat Grid *Appliance Administrator's Guide*, which can be found on the [Install and Upgrade page](#) on Cisco.com.

Release Notes

For detailed updates information, see the *Release Notes*, which may be found in the OpAdmin Portal:

Operations menu > **Update Appliance**

The release notes are cumulative: the most recent version contains all previous notes. Formatted PDF versions are also available online with the other Threat Grid Appliance documentation:

<http://www.cisco.com/c/en/us/support/security/amp-threat-grid-appliances/products-installation-guides-list.html>

Version Lookup Table

For a list of Threat Grid Appliance release information see the [Build Number/Version Lookup Table](#).

Note: To view the release notes for the Threat Grid Portal UI, click **Help** in the UI's navigation bar.

What's New

For a full description of new features always check the *Release Notes* and other release documentation such as Migration Notes and Data Retention Notes. Major highlights are included here.

Note: Although using IPv4LL address space (168.254.0.16) for the Dirty interface has never been documented as supported, from version 2.3.0 forward it is recognized as broken, and therefore explicitly unsupported.

Automatic License Retrieval

If an appliance is connected with the Internet, it can attempt to retrieve a license, or a replacement for an expired license, via the network. Note that automated retrieval is at present only available for licenses sold or renewed after the release of version 2.3 of the software (2017-08-11).

More Windows Changes

The 2.3 release includes the following Windows changes:

- Removes Windows XP, including from appliances that previously grandfathered it in.
- Windows 7 is now 64-bit only.
- Samples submitted to `winxp` or `win7-x86` VMs are still available. Note that any scripts or clients which hardcoded `winxp` should be changed.

Backups

The 2.2.4 release introduces a backup feature. Threat Grid appliances now support encrypted backups to NFS-backed storage; initialization of data from such storage; and reset to an empty-database state into which such a backup can be loaded.

(Note that reset is different from the wipe process used to allow an appliance to be shipped off customer premises without information leakage. The wipe process appropriate for that purpose already exists in the recovery bootloader, but is NOT suitable for preparing a system to restore a backup; reset is for backup preparation.)

We *strongly* encourage consulting the documentation prior to use. Extended documentation regarding the backup functionality is available. See the [Backup Notes and FAQ](#), and the Backup section added to the *Threat Grid Appliance Administrator's Guide*. Both documents are available on the [Threat Grid Appliance Install and Upgrade page](#) on the Cisco.com website.

Windows XP Changes

Threat Grid appliances manufactured on or after 2017-07-01 (July 1, 2017), will no longer include licensing or distribution of Windows XP, in compliance with Microsoft requirements. The 2.2.3 minor release allows new factory installations to be run without Windows XP.

Integrating with Third Party Detection and Enrichment Services

With version 2.2, OpenDNS, TitaniumCloud, and VirusTotal integrations can now be configured on the Appliance, in the new configuration page. In OpAdmin, select **Configuration > Integrations** to open this page. See the *Threat Grid Administrator's Guide* for more information.

Multiple URLs for Disposition Update Service Manager

Version 2.2 also includes the ability to configure multiple URLs for the Disposition Update Service Manager.

ClamAV Signatures Automatic Daily Update

With version 2.2 the appliance can now automatically download updates to ClamAV signatures on a daily basis, improving recognition of known malware. This feature is enabled by default, and can be disabled from the newly-added Integrations page in OpAdmin.

LDAP Authentication

LDAP Authentication has been added to the OpAdmin and TGS Dialog administrator interfaces with version 2.1.6, released on January 5, 2017, to support those customers with multiple appliance administrators who don't want them sharing the same login and password. See the *Threat Grid Administrator's Guide* for more information.

Cisco UCS C220 M4 Server

Released on November 17, 2016, the C220 M4 server includes a hardware refresh, as well as the Secure Boot feature. Please contact us at support@threatgrid.com to discuss any questions you may have about upgrading.

Note: Threat Grid will continue to provide support for M3s until after the expiration of their contracted lifespan. All the same M4 features are available as over-the-wire updates for existing M3s.

The M5 server upgrade is currently under development. We strongly encourage existing M3 and M4 customers to contact us at support@threatgrid.com to discuss any questions you may have about which server upgrade is best for your needs, as well as data migration, backups, rollout strategies, etc. Additional complexity is introduced by the migration to version 2.1.5 of the Threat Grid Appliance software, which is currently in development. We think the best approach for planning the upgrade path to the M5 is to address our customers' requirements on an individual basis.

AMP for Endpoints Private Cloud Integration

The 2.0.3 release contains features to facilitate Threat Grid Appliance integrations with Fire AMP Private Cloud (renamed as AMP for Endpoints Private Cloud), including the ability to split the DNS between the Clean and Dirty network interfaces, CA Management, and AMP for Endpoints Private Cloud Integration Configuration.

Generated SSL certificates now have the CN duplicated as a subjectAltName. This addresses an incompatibility with SSL clients, which ignore the CN field when at least one subjectAltName is present. It may be necessary to regenerate any previously appliance-generated certificates if using such tools.

Version 2.0

Version 2.0 is a major release, built upon an updated operating system. It includes enhancements that will support future hardware releases, and also brings the Threat Grid Portal UI more in line with the Cloud version. This includes significant numbers of new and updated Behavioral Indicators and other changes.

Please read the *Threat Grid Portal Release Notes* beginning with release 3.3.45 for details. (From the Portal UI Navigation bar select **Help**, then click on the link to the release notes.)

Support - Contacting Threat Grid

There are several ways to request support from a Threat Grid engineer:

- **Email.** Send email to support@threatgrid.com with your query.
- **Open a Support Case.** You will need your Cisco.com ID (or to generate one) to open a support case. You will also need your service contract number, which was included on the order invoice. Enter your support case with the [Cisco Support Case Manager](#).
- **Call.** For Cisco phone numbers and contact information see the [Cisco Contact page](#).

When requesting support from Threat Grid, please send the following information with your request:

- Appliance version: OpAdmin > Operations > Update Appliance)
- Full service status (service status from the shell)
- Network diagram or description (if applicable)
- Support Mode (Shell or Web interface)
- Support Request Details

Support Mode

If you require support from a Threat Grid engineer, they may ask you to enable "support mode", which is a live support session that gives Threat Grid support engineers remote access to the appliance. Normal operations of the appliance will not be affected. This can be done via the **OpAdmin Portal Support** menu. (You can also enable **SUPPORT MODE** from the TGSH Dialog, from the legacy Face Portal UI, and when booting up into Recovery Mode.)

To start a live support session with Threat Grid tech support:

In **OpAdmin**, select **Support > Live Support Session** and click **Start Support Session**.

Note: You can break out of the OpAdmin wizard task-flow to enable Support Mode, prior to licensing.


Start Support Mode - License Workaround Prior to Version 1.4.4

There is an issue with licenses that has been resolved in the Threat Grid Appliance v1.4.4. If your software version is prior to 1.4.4, you will need to have successfully connected to *Support Mode* servers at least once

(after November 14th, 2015), in order for your license to be accepted. The connection does not need to be ongoing or active at the time of the license validation.

Required: The Dirty network needs to be up in order for this step to work.

Figure 1 - OpAdmin Start a Live Support Session



Support Servers

Establishing a support session requires that the TG appliance reach the following servers:

- support-snapshots.threatgrid.com
- rash.threatgrid.com

Both servers should be allowed by the firewall during an active support session.

Support Snapshots

A support snapshot is basically a snapshot of the running system, which contains logs, ps output, etc., to help Support staff troubleshoot any issues.

1. Verify that SSH is specified for Support Snapshot services.
2. From the **Support** menu, select **Support Snapshots**.
3. Take the snapshot.
4. Once you take the snapshot you can either download it yourself as .tar .gz, or you can press **Submit**, which will automatically upload the snapshot to the Threat Grid snapshot server.

PLANNING

A Cisco Threat Grid Appliance is a Linux server with Threat Grid software installed by Cisco Manufacturing prior to shipping. Once a new appliance is received, it must be set up and configured for your on-premises network environment. Before you begin, there are a number of issues to consider and plan. Environmental requirements, hardware requirements, and network requirements are described below.

User Documentation and Online Help

Threat Grid Appliance - Threat Grid Appliance user documentation, including this document, the *Threat Grid Appliance Administrator's Guide*, Release Notes, integration guides, and more, can be found on the [Install and Upgrade page](#) on Cisco.com.

Threat Grid Portal UI Online Help - Threat Grid Portal user documentation, including Release Notes, "Using Threat Grid" Online Help, API documentation, and other information is available from the **Help** menu located in the navigation bar at the top of the user interface.

Browsers

Threat Grid recommends using the following browsers:

Note: Microsoft Internet Explorer is NOT recommended and not supported.

- Chrome
- Firefox
- Safari

Environmental Requirements

The Threat Grid Appliance is deployed on a UCS C220-M3 or UCS C220-M4 server. Before you set up and configure your appliance, make sure the necessary environment requirements for power, rack space, cooling, and other issues are met, according to the specification for your server.

Hardware Requirements

The form factor for the Admin interface is SFP+. If there are no SFP+ ports available on the switch, or SFP+ is not desirable, then a transceiver for 1000Base-T can be used (for example, Cisco Compatible Gigabit RJ 45 Copper SFP Transceiver Module Mini -GBIC - 10/100/1000 Base-T Copper SFP Module).

Figure 2 - Cisco 1000BASE-T Copper SFP (GLC-T)



Monitor: You can either attach a monitor to the server, or, if CIMC (Cisco Integrated Management Controller) is configured, you can use a remote KVM.

Hardware Documentation

Installation and Service Guide for Cisco UCS C220 M4 Server:

http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/hw/C220M4/install/C220M4.pdf

Installation and Service Guide for Cisco UCS C220 M3 Server:

- http://www.cisco.com/c/en/us/td/docs/unified_computing/ucs/c/hw/C220/install/C220.html

Spec Sheet for Cisco UCS C220 M3 High-Density Rack Server (Small Form Factor Disk Drive Model):

- http://www.cisco.com/c/dam/en/us/products/collateral/servers-unified-computing/ucs-c-series-rack-servers/C220M3_SFF_SpecSheet.pdf

Cisco has a power/cooling calculator, which you may also find useful:

- <https://mainstayadvisor.com/Go/Cisco/Cisco-UCS-Power-Calculator.aspx>

Network Requirements

The Threat Grid Appliance requires three networks:

ADMIN - The "*Administrative*" network. Must be configured in order to perform the appliance setup.

- OpAdmin Management Traffic (HTTPS)
- SSH
- NFSv4 (Outbound). If a NFS hostname is used instead of IP, this name will be resolved via Dirty DNS.)

CLEAN - The "*Clean*" network is used for inbound, trusted traffic to the appliance (requests). This includes integrated appliances. For example, the Cisco Email Security appliances and Web Security appliances (ESA/WSA) connect to the IP address of the Clean interface.

Note: The URL for the Clean network interface *will not work* until the OpAdmin portal configuration is complete.

The following specific, restricted kinds of network traffic can be outbound from Clean:

- Remote syslog connections

PLANNING

- Email messages sent by the Threat Grid Appliance itself
- Disposition Update Service connections to AMP for Endpoints Private Cloud devices
- DNS requests related to any of the above
- LDAP

DIRTY - The "*Dirty*" network is used for outbound traffic from the appliance (including malware traffic).

Note: We recommend using a dedicated external IP address (i.e., the "*Dirty*" interface) that is different from your corporate IP, in order to protect your internal network assets.

For network interface setup information and illustrations, see the Network Interfaces section, and the Network Interface Connections Setup sections that follow.

DNS Server Access

The DNS server used for purposes other than Disposition Update Service lookups, resolving remote syslog connections, and resolving the mail server used for notifications from the Threat Grid software itself needs to be accessible via the dirty network.

By default, DNS uses the Dirty interface. The Clean interface is used for AMP for Endpoints Private Cloud integrations. If the AMP for Endpoints Private Cloud hostname cannot be resolved over the Dirty interface, then a separate DNS server that uses the Clean interface can be configured in the OpAdmin interface.

See the *Threat Grid Appliance Administrator's Guide* for additional information.

NTP Server Access

The NTP server needs to be accessible via the Dirty network.

Integrations – ESA/WSA/AMP for Endpoints etc.

Additional planning may be required if the Threat Grid Appliance is going to be used with other Cisco products, such as ESA/WSA appliances, AMP for Endpoints Private Cloud, etc.

DHCP

If you are connected to a network configured to use DHCP, then follow the instructions provided in the **Using DHCP** section of the *Threat Grid Appliance Administrator's Guide*.

License

You will receive a license and password from Cisco Threat Grid.

For questions about licenses, please contact support@threatgrid.com.

Rate Limits

The API rate limit is global for the appliance under the terms of the license agreement. This affects API submissions **ONLY**, not manual sample submissions.

Rate limits are based on a window of rolling time, not to a calendar day. When the submission limit is exhausted, the next API submission will return a 429 error, plus a message about how long to wait before retrying. See the Threat Grid portal UI FAQ entry on rate limits for a more detailed description.

Organizations and Users

Once you have completed the appliance setup and network configuration, you will need to create the initial Threat Grid Organizations and add user account(s), so people can login and begin submitting malware samples for analysis. This task may require planning and coordination among multiple organizations and users, depending on your requirements.

Managing Threat Grid Organizations is documented in the *Threat Grid Appliance Administrator's Guide*. Managing users is documented in the Threat Grid portal Help.

Updates

The initial appliance setup and configuration steps **must be completed** before installing any Threat Grid appliance updates.

We recommend that you check for updates immediately after completing the initial configuration described in this guide.

Updates must be done in sequence. Threat Grid Appliance updates cannot be downloaded until the license is installed, and the update process requires the initial appliance configuration to be completed. Instructions for updating the appliance are located in the *Threat Grid Appliance Administrator's Guide*.

Note: Verify that SSH is specified for updates.

User Interfaces

After the server has been correctly attached to the network and powered up, there are several user interfaces available for configuring the Threat Grid Appliance. Note that LDAP authentication is available for TGS Dialog and OpAdmin with version 2.1.6.

TGS Dialog

The first interface is the **TGS Dialog**, which is used to configure the Network Interfaces. TGS Dialog is displayed when the appliance successfully boots up.

Reconnecting to the TGS Dialog

TGS Dialog will remain open on the console and can be accessed either by attaching a monitor to the appliance or, if CIMC is configured, via remote KVM.

To reconnect to the TGS Dialog, ssh into the Admin IP address as the user **'threatgrid'**.

The required password will either be the initial, randomly generated password, which is visible initially in the TGS Dialog, or the new Admin password you create during the first step of the OpAdmin Portal Configuration, which is described in the next section.

OpAdmin Portal

This is the primary Threat Grid GUI configuration tool. Much of the appliance configuration can **ONLY** be done via OpAdmin, including licenses, email host, SSL Certificates, etc.

Threat Grid Portal

The Threat Grid user interface application is available as a cloud service, and is also installed on Threat Grid Appliances. There is no communication between Threat Grid Cloud service, and the Threat Grid Portal that is included with a Threat Grid Appliance.

CIMC

Another user interface is the Cisco Integrated Management Controller ("CIMC"), which is used to manage the server.

Network Interfaces

Admin Interface

- Connect to the Admin network. **Only inbound** from Admin network.
- OpAdmin UI traffic
- SSH (inbound) for tgsh-dialog
- NFSv4 for Backups (Outbound. If a NFS hostname is used instead of IP, this name will be resolved via Dirty DNS.)

Note: The form factor for the Admin interface is SFP+. See Figure 2 - Cisco 1000BASE-T Copper SFP (GLC-T).

Clean Interface

- Connect to the Clean network. Clean must be accessible from the corporate network but requires no outbound access to the Internet.
- UI and API traffic (inbound)
- Sample Submissions
- SMTP (outbound connection to the configured mail server)
- SSH (inbound for tgsh-dialog)
- Syslog (outbound to configured syslog server)
- ESAWSA – CSA Integrations
- AMP for Endpoints Private Cloud Integration
- DNS – Optional.
- LDAP (outbound)

Dirty Interface

Connect to the Dirty network. Requires Internet access. **Outbound Only!**

- DNS
Note: If you are setting up an integration with a AMP for Endpoints Private Cloud, and the AMP for Endpoints appliance hostname cannot be resolved over the Dirty interface, then a separate DNS server that uses the Clean interface can be configured in OpAdmin.
- NTP
- Updates
- Support Session in Normal Operations Mode
- Support Snapshots
- Malware Sample-initiated Traffic
- Recovery Mode Support Session (outbound)
- OpenDNS, TitaniumCloud, Virus Total, ClamAV
- SMTP Outbound connections are redirected to a build-in honeypot

Note: Although using IPv4LL address space (168.254.0.16) for the Dirty interface has never been documented as supported, from version 2.3.0 forward it is recognized as broken, and therefore explicitly unsupported.

CIMC Interface

Recommended. If the Cisco Integrated Management Controller ("CIMC") interface is configured, it can be used for server management and maintenance. For more information see APPENDIX A – CIMC CONFIGURATION (RECOMMENDED).

Reserved Interface

The non-Admin SFP+ port is reserved for future use.

Login Names and Passwords - Defaults

Web UI Administrator

- **Login:** admin
- **Password:** "changeme"

OpAdmin and Shell user

Use the initial Threat Grid/TGSH Dialog randomly generated password, and then the new password entered during the first step of the OpAdmin configuration workflow.

If you lose the password, follow the **Lost Password** instructions located in the **Support** section of the *Threat Grid Appliance Administrator's Guide*.

CIMC (Cisco Integrated Management Controller)

- **Login:** admin
- **Password:** "password"

Setup and Configuration Steps Outline

The following setup and initial configuration steps are described in this document:

- Server Setup.
- Network Interface Connections Setup:
 - Admin
 - Clean
 - Dirty
- Initial Network Configuration - TGSH Dialog.
- Main Configuration – OpAdmin Portal.
- Install Updates.
- Test the Appliance setup: Submit a Sample for Analysis.
- Admin Configuration – Complete the remaining administrative configuration tasks (license installation, email server, SSL Certificates, etc.) in the OpAdmin Portal as documented in the *Threat Grid Appliance Administrator's Guide*.

Time Required for Setup and Configuration

You should allow yourself approximately 1 hour to complete the server setup and initial configuration steps.

Note: Please be patient during the "Apply" sections of the TGSH Dialog during the initial Appliance configuration installation steps. These steps can sometimes take more than 10 minutes to complete.

SERVER SETUP

To begin, connect both power supplies on the back of your appliance and connect the included KVM adapter to an external monitor and keyboard and plug into the KVM port located at the front of the server, as illustrated in the figure below.

If CIMC is configured, you can use a remote KVM. For CIMC configuration see **Configuring CIMC (Optional)** in the *Appendix*.


Please refer to the server product documentation for detailed hardware and environmental setup information. Links to product documentation are provided in the Hardware Documentation section, above.

Network Interface Connections Setup

Find the SFP+ ports (there are two) and the three Ethernet ports on the back of the appliance and attach the network cables as illustrated below:

C220 M3 Rack Server Setup

Figure 3 - Cisco UCS C220 M3 SFF Rack Server




The interfaces must be properly connected and configured for the appliance to operate.

Note: The details of your appliance may differ from the image above. Please contact support@threatgrid.com if you have any questions.

Note: "Reserved" is the non-Admin SFP+ port, which is reserved for future use.

See the diagram below for more information about the C220 M3 server.

Figure 4 - Cisco UCS C220 M3 Rear View Details



1	Power supplies (up to two)	6	One 10/100/1000 Ethernet dedicated management port
2	Slot 2: Low-profile PCIe slot on riser: (half-height, half-length, x16 connector, x8 lane width)	7	Dual 1-GbE ports (LAN1 and LAN2)
3	Two SFP+ Ports. Slot 1: Admin Slot 2: Reserved for backup and storage support.	8	USB ports
4	VGA video connector	9	Rear Identification button/LED
5	Serial port (RJ-45 connector) ¹	—	—

Note: For releases 1.0-1.2 a reboot may be needed if an interface was not plugged in at boot time. This is a pre-1.3 issue, except for any interface requiring an SFP, which will still needs to be plugged in at boot time post 1.3. The network cable plugged into the SFP may be hot-plugged safely.


C220 M4 Rack Server Setup

Figure 5 - Cisco UCS C220 M4 SFF Rack Server



Note: The details of your appliance may differ from the image above. Please contact support@threatgrid.com if you have any questions.

Figure 6 - Cisco UCS C220 M4 Rear View Details



1	PCIe riser 1/slot 1	7	Serial port (RJ-45 connector)
2	PCIe riser 2/slot 2	8	Dual 1-Gb Ethernet ports (LAN1 and LAN2)
3	Modular LAN-on-motherboard (mLOM) card slot	9	VGA video port (DB-15)
4	Grounding-lug hole (for DC power supplies)	10	Rear unit identification button/LED
5	USB 3.0 ports (two)	11	Power supplies (up to two, redundant as 1+1)
6	1-Gb Ethernet dedicated management port		


Connections:

- 1** Admin
- 8** (left) Clean
- 8** (right) Dirty
- 6** CIMC

Network Interface Setup Diagram

This section describes the most logical/recommended setup for an Threat Grid Appliance. However, each customer's interface setup is different. Depending on your network requirements, you may well decide to connect the Dirty interface to the inside, or the Clean interface to the outside with appropriate network security measures in place, for example.

Figure 7 - Network Interfaces Setup Diagram



Firewall Rules Suggestions

Note: Implementing a restrictive outgoing policy on the Dirty interface for ports 22 and 19791 will require tracking updates over time and spending more time maintaining the firewall, etc. See the required destinations in the configuration sections below.

Note: Although using IPv4LL address space (168.254.0.16) for the Dirty interface has never been documented as supported, from version 2.3.0 forward it is recognized as broken, and therefore explicitly unsupported.

Dirty Interface Outbound

Source	Destination	Protocol	Port	Action	Note
Dirty Interface	Internet	ANY	ANY	Allow	Allow outbound traffic from samples. (To get accurate results it is required that malware be allowed to contact its command and control server using whatever port and protocol it is designed to use.)

Dirty Interface Inbound

Source	Destination	Protocol	Port	Action	Note
ANY	Dirty Interface	ANY	ANY	Deny	Deny all incoming connections

Clean Interface Outbound

Source	Destination	Protocol	Port	Action	Note
Clean Interface	SMTP Servers	TCP	25	Allow	The appliance uses the clean interface to initiate SMTP connections to the configured mail server

Clean Interface Outbound Optional

The following depends on what services are configured.

Source	Destination	Protocol	Port	Action	Note
Clean Interface	Corporate DNS Server	TCP/UDP	53	Allow	"Optional, only required if Clean DNS is configured"
Clean Interface	AMP Private Cloud	TCP	443	Allow	"Optional, only required if AMP for Endpoints Private Cloud integration is used"
Clean Interface	Syslog Servers	UDP	514	Allow	Allow connectivity to server designated to receive Syslog messages and Threat Grid notifications
Clean Interface	LDAP Servers	TCP/UDP	389	Allow	"Optional, only required if LDAP is configured"
Clean Interface	LDAP Servers	TCP	636	Allow	"Optional, only required if LDAP is configured"

Clean Interface Inbound

Source	Destination	Protocol	Port	Action	Note
User Subnet	Clean Interface	TCP	22		Allow SSH connectivity to the tgsh-dialog
User Subnet	Clean Interface	TCP	80		Appliance API and Threat Grid user interface. This will redirect to HTTPS TCP/443
User Subnet	Clean Interface	TCP	443		Appliance API and Threat Grid user interface
User Subnet	Clean Interface	TCP	9443		Allow connectivity to the Threat Grid UI Glovebox

Admin Interface Outbound Optional

The following depends on what services are configured.

Source	Destination	Protocol	Port	Action	Note
--------	-------------	----------	------	--------	------

Threat Grid Appliance Setup and Configuration Guide

SERVER SETUP

Admin Interface	NFSv4 Server	TCP	2049	Allow	"Optional, only required if Threat Grid appliance is configured to send backups to an NFSv4 share"
-----------------	--------------	-----	------	-------	----------------------------------------------------------------------------------------------------

Admin Interface Inbound

Source	Destination	Protocol	Port	Action	Note
Admin Subnet	Admin Interface	TCP	22	Allow	Allow SSH connectivity to the TGSH Dialog
Admin Subnet	Admin Interface	TCP	80	Allow	Allow Access to the OpAdmin Portal interface. This will redirect to HTTPS TCP/443
Admin Subnet	Admin Interface	TCP	443	Allow	Allow Access to the OpAdmin Portal interface


Dirty Interface for Non Cisco-Validated/Recommended Deployment

Source	Destination	Protocol	Port	Action	Note
Dirty Interface	Internet	TCP	22	Allow	"Update, support snapshot, and licensing services"
Dirty Interface	Internet	TCP/UDP	53	Allow	Allow outbound DNS
Dirty Interface	Internet	UDP	123	Allow	Allow outbound NTP
Dirty Interface	Internet	TCP	19791	Allow	Allow connectivity to Threat Grid support
Dirty Interface	Cisco Umbrella	TCP	443	Allow	Connect with 3rd party detection and enrichment services
Dirty Interface	VirusTotal	TCP	443	Allow	Connect with 3rd party detection and enrichment services
Dirty Interface	TitaniumCloud	TCP	443	Allow	Connect with 3rd party detection and enrichment services

Power On and Boot Up

Once you have connected the server peripherals and the network interfaces (don't forget to attach the power cables and plug it in!), turn on the appliance and wait for it to boot up. The Cisco screen is displayed briefly:


Figure 8 - Cisco Screen During Boot Up



Note: If you want to configure this interface, press **F8** after the memory check is completed, and follow the instructions provided in Appendix A, Configuring CIMC.

The **TGSH Dialog** is displayed on the console when the server has successfully booted up and connected:

Figure 9 - TGS Dialog



The Admin URL shows as unavailable - the network interface connections are not yet configured and the OpAdmin Portal cannot be reached yet to perform this task.

Note: Make a note of the administrator Password into a separate text file for convenience (copy-paste) during the OpAdmin Portal configuration steps.

IMPORTANT: The **TGS Dialog** displays the initial administrator password, which will be needed in order to access and configure the OpAdmin Portal interface later in the configuration workflow steps.


INITIAL NETWORK CONFIGURATION – TGSN DIALOG

The initial network configuration is completed in the TGSN Dialog. The goal is to complete the basic configuration that will allow access to the OpAdmin interface tool to finish the remaining configuration, including the license, email host, SSL Certificates, etc.

DHCP Users: The following steps assume that you are using static IP addresses. If you are using DHCP to obtain your IPs, then please see the *Threat Grid Appliance Administrator's Guide* for more information.

1. In the TGSN Dialog interface, select **CONFIG_NETWORK**. The Network Configuration console opens:

Figure 10 - TGSN Dialog - Network Configuration Console




2. Complete the blank fields according to the settings provided by your network administrator for the Clean, Dirty, and Admin interfaces.
3. Change **DHCP Enabled** from **Y** to **N**.

Note: You need to **BACKSPACE** over the old character before you can enter the new one.


4. **DNS NAME.** If your network is using a DNS name for the Clean network, then enter the name here.
5. Leave **Configure Non-Default Routes?** set to the default of **N** (unless additional routes are needed).

Figure 11 - Network Configuration In-Progress (clean and dirty)



6. Leave the Dirty network **DNS Name** blank.

Figure 12 - Network Configuration In-Progress (admin)




7. After you finish entering all the network settings, tab down and select **Validate** to validate your entries.

If invalid values have been entered, you may see errors. If this is the case, then fix the errors and re-Validate.

After validation, the Network Configuration Confirmation displays the values you've entered:

Figure 13 - Network Configuration Confirmation




8. Select **Apply** to apply your configuration settings.

Have patience. This step may take 10 minutes or more to complete.

The console will become a blank grey box, and the screen may display scrolling configuration information as the settings are applied, and then it will list detailed information about the configuration changes that have been made:


Figure 14 - Network Configuration - List of Changes Made



9. Select **OK**.

The Network Configuration Console refreshes again and displays the IP addresses you entered:

Figure 15 - IP Addresses



You have completed the network configuration of your appliance.

Note: The URL for the Clean interface will not work until the OpAdmin portal configuration is complete.

Next Setup Step:

The next step in the appliance setup is to complete the remaining configuration tasks using the workflow in the OpAdmin portal, as described in the next section.

CONFIGURATION WIZARD - OPADMIN PORTAL

The OpAdmin Portal is the Threat Grid administrator's portal on the appliance. It is a Web user interface that can be used once an IP address has been configured on the Admin interface.

The OpAdmin Portal is the recommended tool for configuring your appliance, and in fact, much of the appliance configuration can only be done via the OpAdmin portal interface, including:

- OpAdmin Portal administrator's password
- Email servers
- DNS servers
- NTP servers
- SSL Certificates
- Other server settings
- `https://<adminIP>/` OR `https://<adminHostname>/`

Note: Not all of these settings are completed in the initial OpAdmin portal configuration wizard workflow. Some, such as SSL Certificates, are configured in separate steps, as described in the *Threat Grid Appliance Administrator's Guide*.


Configuration Workflow

The steps in the following sections should be completed in one session to reduce the chance of an interruption to the IP address during configuration.

Login to the OpAdmin Portal

1. Point your browser at the OpAdmin Portal interface (the Admin URL with the "https"). The Threat Grid OpAdmin login screen opens:

Figure 16 - OpAdmin Login




2. Enter the initial Admin Password that you copied from the TGSH Dialog and click **Login**. The *Change Password* page opens.

Continue with the next section:

Admin Password Change

The initial administrator's password was generated randomly during the pre-ship Threat Grid installation, and is visible as plain text in the TGS Dialog. You must change the initial Admin password before you may continue with the configuration workflow.

Figure 17 - OpAdmin Change Password



1. Enter the password from the TGS Dialog into the **Old Password** field. (You should have this in a text file for use at this moment.)
2. Enter and confirm a new password.
3. Click **Change Password**.

The password is updated. The *End User License Agreement* page opens.

Note: The new password will NOT be displayed in visible text in the TGS Dialog, so be sure to note it down somewhere.


If you lose the password, follow the **Lost Password** instructions located in the *Support* section of the *Threat Grid Appliance Administrator's Guide*.

Continue with the next section:

End User License Agreement

1. Review the End User License Agreement.
2. Scroll down to the end, and click **I HAVE READ AND AGREE**. The *License* page opens:

Figure 18 - License Page



We recommend that you follow the configuration workflow, and *configure the networks before you install the license*, as described in the next section, Network Configuration Settings.

Network Configuration Settings

If you configured your static network settings in the TGS Dialog, the IP addresses displayed in the Network Configuration page will reflect the values you entered in the TGS Dialog during the appliance network configuration.

Network Configuration and DHCP

If you used DHCP for your initial connection and now need to change the Clean and Dirty IP networks to static IP addresses, then follow the steps in the section: **Networking > Using DHCP**, located in the *Threat Grid Appliance Administrator's Guide*.

Continue with the next section:

License Installation

After the networks are configured, you are ready to install the Threat Grid license. (In versions older than v1.4.4, you will need to start Support Mode in order for your license to be accepted. See *Start Support Mode - License Workaround Prior to Version 1.4.4* for more information.)

Figure 19 - License Page Prior to Installation

The screenshot displays the license installation interface. It is divided into three main sections:

- Appliance ID:** A field containing the value "FCH1832V32N".
- License:** A section with the message "No license has been installed."
- Upload New License:** A section containing:
 - A "Choose File" button next to the text "No file chosen".
 - A "Passphrase" input field with a lock icon.
 - An "Upload" button.
- Retrieve License From Server:** A section with a "Retrieve" button.

1. Click on **License** in the left column. The *License* page opens as shown above. No license has been installed.
2. Under **Upload New License**, click **Chose File**, and select the license from your file manager.

Retrieve License From Server - Alternatively, the 2.3 release adds the ability to select **Retrieve**. If the appliance has network access when being installed, selecting this option will retrieve a license over the network.

3. Enter the license password you were given into the Passphrase field.
4. Click **Upload** to install. The page refreshes, and you should see your license information:

Figure 20 - License Information After Successful Installation

Appliance ID	
FCH1832V32N	

License	
Licensee	No Name Provided provision@threatgrid.com
Business	2f518e6d-dd45-4397-9533-3c6d38239c32
Validity	Fri, 22 Sep 2017 14:47:46 +0000 - Mon, 21 Sep 2020 14:47:46 +0000
Product SKU	
Daily Submissions	1500

Upload New License	
Choose File	No file chosen
<input type="password"/>	Passphrase
<input type="button" value="Upload"/>	

Retrieve License From Server	
<input type="button" value="Retrieve"/>	

Next >

Click **Next** to continue. The *Email* page opens.

Continue with the next section:

Email Host Configuration

The next step in the workflow is to configure the email host.

1. Click on **Email** in the left column. The *Email* page opens.
2. Enter the name of the **Upstream Host** (email host).
3. Change the port from 587 to **25**.
4. Leave the other settings at the defaults.
5. Click **Next**. The *Notifications* page opens.


Continue with the next section:

Server Notifications Configuration

The next step in the workflow is to configure notifications that can be delivered periodically to one or more email addresses. System notifications are displayed in the Threat Grid portal interface, but this page allows you to set up notifications that are also sent via email.

Note: Update v1.3 includes a page to configure a Syslog server to receive syslog messages and Threat Grid notifications. See the *Threat Grid Appliance Admin Guide* for more information.

Figure 21 - Notifications Configuration



1. First, set the **Critical Notification Frequency** and the **Notification Frequency** by selecting them from the dropdown lists.
2. Next, in **Notification Recipients**, enter one or more email addresses separated by commas.
3. Click **Next**. The *Date and Time* page opens.

Continue with the next section:

NTP Server Configuration

This is where you identify the NTP ("Network Time Protocol") servers.

1. Enter the **NTP Server(s)** IP or NTP name.

If there are multiple NTP Servers, separate them with a space or a comma.

2. Ignore Current System Time and Synchronize with Browser.
3. Click **Next**.

The *Review and Install* page opens with checkboxes next to all of the Configuration steps.

Continue with the next section:

Review and Install Configuration Settings


Now that you have entered your network configuration settings, you must install them as described below.

1. In the *Review and Install* page, click **Start Installation**.

Configuration scripts are installed and you see the message: "*The appliance is installing...*".


Note: Have patience. Please allow 10+ minutes for this step to complete. The screen will display configuration information as it is applied.

Figure 22 - Appliance is Installing



2. After successful installation, the State changes from the orange **Running** to a green **Successful** message confirming success. The **Reboot** button changes to green, and the configuration output is displayed:


Figure 23 - Successful Appliance Installation



3. Click **Reboot** after the successful installation. You will see the message that "*The appliance is rebooting*". Rebooting may take up to 5 minutes.


Please do not make any changes while the Appliance is rebooting.

Figure 24 - Appliance is Rebooting



Once the appliance has successfully rebooted, you will see the following confirmation that the Appliance is configured:

Figure 25 - Appliance Is Configured



Your appliance is now setup and the initial configuration is complete.

INSTALLING THREAT GRID APPLIANCE UPDATES

After you complete the initial Threat Grid Appliance setup we recommend that you install any available updates before continuing.

Threat Grid Appliance updates are applied through the **OpAdmin** Portal.

From the **Operations** menu, select **Update Appliance**. The updates page opens, displaying the current build of the appliance.

Click **Check/Download Updates**. The software checks to see if there is a more recent update/version of the Threat Grid Appliance software, and if so, it is downloaded. This may take some time.


Once the updates have been downloaded, click **Run Update** to install them.

For more information about installing updates, see the *Threat Grid Appliance Administrator's Guide*.

Appliance Build Number

The build number of an appliance can be viewed on the Updates page: OpAdmin **Operations** > **Update Appliance**:

Figure 26 - Appliance Build Number



Build Number/Version Lookup Table

The build number of an Appliance can be viewed on the Updates page (OpAdmin **Operations > Update Appliance**), as illustrated above. Appliance build numbers correspond to the following version numbers:

Build Number	Release Version	Release Date	Notes
2016.05.20170810212922.28c79852.rel	2.3	8/11/2017	Automates license download. Refreshes the portal software to 3.4.47.
2016.05.20170710175041.77c0b12f.rel	2.2.4	7/10/2017	This release introduces Backup functionality.
2016.05.20170519231807.db2f167e.rel	2.2.3	5/20/2017	This minor release allows new factory installations to be run without Windows XP.
2016.05.20170508195308.b8dc88ed.rel	2.2.2	5/8/2017	Minor release of changes to network configuration and operating-system components to support upcoming features.
2016.05.20170323020633.f82e66fe.rel	2.2.1	3/24/2017	Disables SSLv3, fixes a resource issue
2016.05.20170308211223.c92516ee.rel	2.2mfg	3/8/2017	Manufacturing-only changes. No customer impact. Not deployed via update server.
2016.05.20170303034712.1b205359.rel	2.2	3/3/2017	Storage migration, Pruning, Mask UI, Multi-disposition update
2016.05.20170105200233.32f70432.rel	2.1.6	1/7/2017	LDAP Authentication support for OpAdmin/tgsh-dialog

Threat Grid Appliance Setup and Configuration Guide

INSTALLING THREAT GRID APPLIANCE UPDATES

Build Number	Release Version	Release Date	Notes
2016.05.20161121134140.489f130d.rel	2.1.5	11/21/2016	ElasticSearch5; CSA performance fix
2016.05.20160905202824.f7792890.rel	2.1.4	9/5/2016	Primarily of interest to Manufacturing
2016.05.20160811044721.6af0fa61.rel	2.1.3	8/11/2016	Offline update support key, M4 wipe support
2016.05.20160715165510.baed88a3.rel	2.1.2	7/15/2016	
2016.05.20160706015125.b1fc50e5.rel-1	2.1.1	7/6/2016	
2016.05.20160621044600.092b23fc	2.1	6/21/2016	
2015.08.20160501161850.56631ccd	2.0.4	5/1/2016	Starting point for the 2.1 update. You must be at 2.0.4 before you can update to 2.1.
2015.08.20160315165529.599f2056	2.0.3	3/15/2016	Introduces AMP integration, CA mgmt., and split DNS
2015.08.20160217173404.ec264f73	2.0.2	2/18/2016	
2015.08.20160211192648.7e3d2e3a	2.0.1	2/12/2016	
2015.08.20160131061029.8b6bc1d6	2.0	2/11/2016	Force update to 2.0.1 from here
2014.10.20160115122111.1f09cb5f	1.4.6	1/27/2016	Starting point for the 2.0.4 update
2014.10.20151123133427.898f70c2	v1.4.5	11/25/2015	
2014.10.20151116154826.9af96403	v1.4.4		
2014.10.20151020111307.3f124cd2	v1.4.3		
2014.10.20150904134201.ef4843e7	v1.4.2		
2014.10.20150824161909.4ba773cb	v1.4.1		
2014.10.20150822201138.8934fa1d	v1.4		

Threat Grid Appliance Setup and Configuration Guide

INSTALLING THREAT GRID APPLIANCE UPDATES

Build Number	Release Version	Release Date	Notes
2014.10.20150805134744.4ce05d84	v1.3		
2014.10.20150709144003.b4d4171c	v1.2.1		
2014.10.20150326161410.44cd33f3	v1.2		
2014.10.20150203155143+hotfix1.b06f7b4f	v1.1+hotfix1		
2014.10.20150203155142.b06f7b4f	v1.1		
2014.10.20141125162160+hotfix2.8afc5e2f	v1.0+hotfix2 NOTE: The 1.0+hotfix2 is a <u>mandatory update</u> that fixes the update system itself to be able to handle large files without breaking.		
2014.10.20141125162158.8afc5e2f	v1.0		

Note: For release versions 1.0-1.2 a reboot may be needed if an interface was not plugged in at boot time. This is a pre-v1.3 issue, except for any interface requiring an SFP, which will still need to be plugged in at boot time post v1.3. The network cable plugged into the SFP may be hot-plugged safely.


Note: Updating from 1.0 to 1.0+hotfix2 takes approximately 15 minutes. Applying a full update from 1.0 to 1.3 (without data migration) takes about 30 minutes.

TEST THE APPLIANCE SETUP - SUBMIT A SAMPLE

Once the Threat Grid Appliance is updated to the current version, the final test that your appliance has been configured properly is to submit a malware sample using the Threat Grid software.

1. Sign into the Threat Grid Portal by visiting the address you configured as the Clean interface. The Threat Grid login page opens:

Figure 27 - Threat Grid Portal Login Page



2. Enter the default Login and Password: **admin/changeme**
3. Click **Login**. The main Threat Grid *Sample Analysis* page opens.
4. In the **Submit a Sample** box located in the upper-right corner, to select a sample file or enter a *URL* to submit for malware analysis.
5. Click **Upload Sample**. The Threat Grid sample analysis process is launched.

You should see your sample going through several stages of analysis. During analysis, the sample is listed in the *Submissions* section. Once analysis is completed, the results should be available in the *Samples* section, with details in the Analysis Report.

APPLIANCE ADMINISTRATION

Once the Threat Grid Appliance has been setup and initial configuration is completed, it is ready for the appliance administrator.

Release notes, Updates, SSL Certificates, adding users, and other administrator tasks and topics are documented in the *Threat Grid Appliance Administrator's Guide*.


APPENDIX A – CIMC CONFIGURATION (RECOMMENDED)

The first window displayed as the server is booting is the Cisco window, which allows you to enter the Cisco Integrated Management Controller (“CIMC”) Configuration Utility. The CIMC interface can be used for remote server management.

You will need a monitor and keyboard attached directly to the appliance.

1. Power on the server. The Cisco screen opens:

Figure 28 - The Cisco screen – F8 to enter the CIMC Configuration Utility



2. After the memory check is completed press **F8** to enter the CIMC configuration utility:

Figure 29 - CIMC Configuration Utility

```

Cisco IMC Configuration Utility Version 2.0 Cisco Systems, Inc.
*****
NIC Properties
NIC mode                               NIC redundancy
Dedicated:      [X]                   None:           [X]
Shared LOM:     [ ]                   Active-standby: [ ]
Cisco Card:     [ ]                   Active-active:  [ ]
Shared LOM Ext: [ ]

IP (Basic)
IPV4:           [X]   IPV6:  [ ]
DHCP enabled   [ ]
CIMC IP:       198.18.2.21
Prefix/Subnet: 255.255.255.0
Gateway:       198.18.2.1
Pref DNS Server: 198.18.2.1

VLAN (Advanced)
VLAN enabled:  [ ]
VLAN ID:       1
Priority:       0

*****
<Up/Down>Selection  <F10>Save  <Space>Enable/Disable  <F5>Refresh  <ESC>Exit
<F1>Additional settings
    
```


3. In the CIMC configuration utility, set up an IP address that will be used for remote server management.

When complete, Save, and then Exit.

At this point the server can be managed remotely by using a Web browser to <https://<CIMC-IP address>>

The initial user name is "admin", with a password of "password".

Figure 30 - Cisco Integrated Management Controller (CIMC) Interface



The CIMC interface can now be used to view the server health as well as open a KVM to complete the remaining setup steps remotely.

INDEX

about Threat Grid appliances	1	CIMC configuration utility	49
adding organizations	10	CIMC interface	12
adding users	10	configuring	22
Admin interface	11	Cisco Integrated Management Controller ("CIMC")	11
form factor	7	Cisco UCS C220 M4 server	3
settings	24	ClamAV	
Admin network requirements	8	Dirty interface	12
administrator password		ClamAV signatures	3
changing	32	Clean interface	11
initial	23, 31	DNS	9
administrator tasks	47	settings	24
after successful installation	39	Clean interface outbound	
reboot	40	firewall rules	19
AMP for Endpoints Private Cloud	3, 9	Clean interface outbound optional	
DNS configured on Clean	12	firewall rules	20
formerly called FireAMP Private Cloud	3	Clean network	
API		DNS Name	25
rate limits	9	Clean network requirements	8
API documentation	7	CONFIG_NETWORK	24
API traffic (inbound)	11	configuration	11
appliance		email host	11
administration	47	licenses	11
appliance build number	42	notifications	36
appliance server		SSL Certificates	11
UCS C220-M3	7	configuration changes	
UCS C220-M4	7	detailed list of	27
appliance setup		configuration settings	
testing	46	applying	27
Apply		configuration wizard	
configuration settings	27	OpAdmin	30
automatic license retrieval	2	configuration workflow	
backups	2	install license after networks are configured	33
boot up	22	NTP servers	38
browsers		review and install configuration settings	38
do not use Microsoft Internet Explorer	7	server notifications	36
recommended	7	the email host	36
build number		Configure Non-Default Routes?	25
release version lookup table	43	Configuring CIMC	22
build number	42	contacting support	4
C220 M3 rack server setup	14	creating organizations	10
C220 M4 rack server setup	16	Critical Notification Frequency	37
Change Password	32	<i>Date and Time</i> page	37
checking for updates	10	DHCP	9
Chrome	7	DHCP Enabled	24
CIMC	11	DHCP used for initial connection	
configuring	48	changing Clean and Dirty to static IP addresses	34

diagram of network interfaces	18	hardware requirements.....	7
Dirty DNS	8	Help	
Dirty interface.....	12	for Threat Grid portal UI	1, 7
Dirty interface inbound		hot-plugged	15
firewall rules.....	19	integrations	
Dirty interface outbound		CSA (ESA/WSA/etc.)	11
firewall rules.....	19	inbound traffic	8
Dirty interface settings	24	initial configuration	
Dirty network		to access OpAdmin.....	24
DNS Name	25	Upload New License	34
NTP server	9	installing the Threat Grid license	34
requirements	9	installing updates.....	10, 42
support mode.....	5	integrations.....	3, 9
Disposition Update Service connections		AMP for Endpoints Private Cloud.....	3, 9, 11
to AMP for Endpoints Private Cloud devices	9	ESA/WSA appliances	9
Disposition Update Service Manager	3	OpenDNS	3
DNS	11, 12	Titanium Cloud	3
requests	9	VirusTotal	3
server access	9	interface settings	24
DNS NAME	25	interfaces	10
documentation		IP addresses	24
appliance admin guides	7	entered.....	28
hardware guides	8	obtaining with DHCP	24
email		IPv4LL address space	
sent by the appliance	9	unsupported for Dirty interface	19
Email	36	KVM	
email host configuration.....	36	opening	50
Email page	35	remote	14
enabling support mode	4, 5	LDAP	9
encrypted backups	2	LDAP (outbound)	11
End User License Agreement.....	33	LDAP authentication	3, 10
<i>End User License Agreement page</i>	32	license	9
environmental requirements	7	installation	34
ESA/WSA appliances.....	9	password	35
establishing a support session	5	retrieve from server	34
ethernet ports	14	retrieve or replace automatically.....	2
FireAMP Private Cloud		upload new	34
renamed AMP for Endpoints Private Cloud	3	License	34
Firefox.....	7	<i>License page</i>	33, 34
firewall rules		list of configuration changes	27
Clean interface outbound	19	live support session	4
Clean interface outbound optional	20	Live Support Session	4
Dirty interface inbound	19	<i>Login page</i>	
Dirty interface outbound	19	Threat Grid portal	46
firewall rules suggestions	19	login	
form factor.....	7	OpAdmin	30
getting started	14	Login	
hardware documentation.....	8	OpAdmin	31

login names and passwords	
defaults	12
lost passwords	12
M3 rack server setup	14
M4 rack server setup	16
malware sample initiated traffic.....	12
managing multiple appliance administrators	
LDAP authentication added	3
managing organizations and users	10
Microsoft Internet Explorer	
do not use	7
monitors	8
multiple NTP Servers	38
multiple URLs.....	3
network cable plugged into the SFP	15
network cables	14
network configuration	24
settings.....	33
Network Configuration Confirmation.....	26
Network Configuration console	
opening	24
network configured to use DHCP	9
network interface connections setup.....	14
network interface setup diagram	18
network interfaces.....	11
Admin.....	11
CIMC.....	12
Clean	11
Dirty.....	12
network requirements.....	8
Admin.....	8
Clean	8
Dirty.....	9
new password.....	32
NFS-backed storage	2
NFSv4	8
NFSv4 for backups	11
Notification Frequency	37
Notification Recipients	37
notifications.....	36
<i>Notifications</i> page.....	36
NTP	12
NTP ("Network Time Protocol") server configuration	
.....	38
NTP server access	9
NTP Servers	
multiple	38
OpAdmin	
appliance administrator's portal	30
OpAdmin Portal	11
OpAdmin portal interface	
login.....	30
OpAdmin UI traffic.....	11
OpenDNS	
Dirty interface	12
OpenDNS integrations	3
opening a KVM	50
opening a support case.....	4
organizations	
managing.....	10
outbound traffic via Dirty	9
passwords	
administrator	23
administrator's initial	23
changing the initial admin.....	32
CIMC.....	13
license	35
lost	12
OpAdmin	12
Threat Grid	9
Web UI Administrator	12
periodic notifications	
configuring	36
planning.....	7
time required for setup.....	13
portal user documentation.....	7
ports	
M3	14
M4	16
power on.....	22
protecting network assets	9
rash server	5
rate limits.....	9
Reboot	
after successful installation.....	40
rebooting	40
receiving syslog messages	36
reconnecting to the TGSH Dialog.....	10
recovery mode.....	12
Release Notes	
Threat Grid appliance.....	1
Threat Grid portal UI	1
release version	
build number lookup table.....	43
remote access to the appliance	4
remote KVM	10

requirements	7	Submit a Sample	46
environmental.....	7	support	4
hardware.....	7	support mode	4
network.....	8	Dirty network.....	5
reserved interface	12	support servers.....	5
Reserved port	14	support session in normal operations mode.....	12
reset for backup preparation.....	2	support snapshots	6, 12
Retrieve License From Server	34	Support Snapshots	6
<i>Review and Install</i> page	38	Syslog (outbound).....	11
reviewing and installing configuration settings	38	syslog messages	
remote syslog connections.....	8	receiving.....	36
Safari.....	7	testing the appliance setup	46
<i>Sample Analysis</i> page	46	TGSH Dialog	10
sample submissions.....	11	network configuration, initial	24
server		opening	22
environmental requirements.....	7	reconnecting	10
server notifications		<i>The appliance is rebooting</i>	40
configuring	36	Threat Grid	
server setup	14	license	9
setup and configuration		license installation	34
basic	24	password.....	9
getting started.....	14	portal UI Help.....	7
M3 rack server	14	Portal UI	11
M4 rack server	16	support.....	4
network interface connections	14	time required	
network interface diagram	18	for setup.....	13
time required	13	to apply configuration settings	27
setup and configuration steps	13	TitaniumCloud	
SFP		Dirty interface	12
hot-plugged.....	15	TitaniumCloud integrations.....	3
SFP Transceiver Module Mini	7	turning on the appliance	22
SFP+ ports	7, 14	UCS C220 M3 server	
non-Admin	14	ports	14
non-Admin is reserved	12	UCS C220 M4 server	
SMTP.....	11	ports illustration.....	16
snapshots		UI traffic.....	11
support.....	6	Update Appliance	42
SSH		updates.....	10
for support snapshots	6	installing	42
SSH (inbound) for tgsh-dialog.....	11	updating the appliance.....	10
SSLv3 disabled	43	Upload	
Start Installation	38	license	35
Start Support Session	4	Upload Sample	46
starting a live support session	4	uploading support snapshots	6
starting support mode	4	Upstream Host	36
static IP addresses		user documentation	7
using.....	24	user interfaces	10
static network configuration	24	CIMC.....	11

OpAdmin Configuration Portal.....	11	using the CIMC interface.....	50
TGSH Dialog.....	10	VirusTotal integrations	3
Threat Grid Portal	11	win7-x86 samples	
users		still available after 2.3	2
adding	10	Windows 7	
Using DHCP	9	64-bit only in 2.3	2
using DHCP to obtain your IP addresses.....	24	Windows XP	
updates.....	12	no longer licensed or distributed	2
Validate		removed in 2.3	2
configuration settings	26	winxp samples	
version lookup table	43	still available after 2.3	2
viewing server health		wipe process.....	2