



FLOWSENSOR™ 1010

First Ship Date: 03/2015

Final Ship Date: Currently Shipping

The Stealthwatch FlowSensor 1010 has the following general configuration. Your model may look slightly different.

Front



Back



Specifications

Hardware Platform		Hardware Generation	
R220		13G	
Rack Units (Mountable)		Weight	
1U – 2 post/4 post, Static Rail, short		17.76 pounds (8.05 kg)	
Dimensions		Network	
Height: Width: Depth:	1.67 inches (4.2 cm) 17.09 inches (43.4 cm) 15.5 inches (39.4 cm)	Management Port: Monitor Ports: Console Port:	1 Cu; 10/100/1000 copper 3 Cu; 10/100/1000 copper Serial port, KVM
Shipping Dimensions		Shipping Weight	
Height: 9.75 inches (24.8 cm) Width: 23.75 inches (60.3 cm) Depth: 32.5 inches (82.6 cm)		34 pounds (15.4 kg)	
- continued -			



Power	Storage			
Single: 250 W, non-redundant	500 GB, Non-Redundant			
Humidity (Relative)	Temperature			
Operating: 10% to 80% (non-condensing) with maximum gradation of 10% per hour Storage: 5% to 95% (non-condensing)	Operating: 50° F to 95° F (10° C to 35° C) Storage: -40° F to 149° F (-40° C to 65° C)			
Heat Dissipation	Altitude			
1,040 BTUs per hour	Operating Altitude: -50 feet to 10,000 feet (-15.2 meters to 3,048 meters) Storage Altitude: -50 feet to 35,000 feet (-15.2 meters to 10,668 meters)			
Vibration (Maximum)	Shock (Maximum)			
Operating: 0.26 Grms at 5-350 Hz for 15 minutes Storage: 1.87 Grms at 10-500 Hz for 15 minutes	Operating: 1 shock pulse in the positive z axis (one pulse on each side of the system) of 31 G for up to 2.6 ms			
	Storage: 6 consecutively executed shock pulses in the positive and negative x, y, and z axes (one pulse on each side of the system) of 71 G for up to 2 ms			
Regulatory Compliance				
CE EmissionFCC Class A				

عالماله

Americas Headquarters Cisco Systems, Inc. San Jose, CA

RoHS Please call for a complete list.

> Asia Pacific Headquarters Cisco Systems (USA) Pte. Ltd. Singapore

Europe Headquarters

Cisco Systems International BV Amsterdam, The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at www.cisco.com/go/offices.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)