

# Cisco Provider Connectivity Assurance Sensor F100

Formerly Accedian Skylight Flex 100  
Performance Element

---

# Contents

Product overview	3
Features and benefits	3
Product specifications	4
Assurance Sensor F100 models	5
Power options and accessories	5
Cisco environmental sustainability	5
Cisco Services	6
Cisco Capital	6
Learn more	6

Enjoy accurate microsecond latency and reduced jitter in a compact, efficient hardware device.

## Product overview

The Cisco® Provider Connectivity Assurance Sensor F100 (formerly Accedian Skylight Flex 100 Performance Element) is a next-generation, multiport, 100 Gigabit Ethernet platform with ultra-low-latency packet forwarding and jitter.

Designed for high-bandwidth and high-availability applications requiring MEF-type service assurance, the Provider Connectivity Assurance Sensor F100 is optimized for scalable service delivery and high-precision, granular, real-time performance monitoring. It is an ideal edge, aggregation, or External Network-to-Network Interface (ENNI) unit for demanding high-bandwidth wireless backhaul, SLA-backed business services, Ethernet wholesale, and dark fiber termination applications.

The Assurance Sensor F100 provides all the tools to establish, validate, and monitor Layer 2 and Layer 3 services in a single unit. Zero-touch provisioning and IPv4/IPv6 management make these performance elements easy and secure to deploy and manage.

Fully integrated with the Cisco Provider Connectivity Assurance platform, it supports service delivery automation and scalable, real-time metrics collection and reporting—plus actionable insights delivery and machine learning for accelerated service rollout and improved operational efficiencies.

The Assurance Sensor F100 interoperates with other Provider Connectivity Assurance Sensors to deliver a scalable end-to-end and core-to-edge performance-assured networking solution tailored to your applications.

## Features and benefits

**Table 1.** Features and benefits

Feature	Benefit
<b>Line-rate Y.1564/RFC2544 Service Activation Testing (SAT)</b>	Helps measure services to ensure that they were activated and are performing as expected
<b>Wire-speed, MEF-certified Carrier Ethernet service delivery</b>	Delivers reliable network service across applications
<b>Precise, scalable Layer 2 service Operations, Administration, and Maintenance (OAM), including Y1731 and performance assurance agent</b>	Assists in the installation, monitoring, and troubleshooting of Ethernet networks
<b>Precise, scalable Layer 3 Two-Way Active Measurement Protocol (TWAMP) and real-time data transfer</b>	Measures network performance between two endpoints and provides Quality-of-Service (QoS) analysis
<b>MEF 10.3 hierarchical QoS enforcement</b>	Prioritizes network traffic and gives highest bandwidth to most critical operations
<b>Programmable, patented Field-Programmable Gate Array (FPGA)</b>	Offers flexibility for teams to configure network hardware according to their unique needs
<b>Optional synchronization module</b>	Adds high-precision timing capabilities required by next-generation services such as 5G-based applications



**Figure 1.**  
Cisco Provider Connectivity Assurance Sensor F100

## Product specifications

**Table 2.** Product specifications

Power and connectivity	
<b>Input power rating</b>	AC input: 100 to 240 VRMS, 2.5 to 1.0A, 80 Plus Platinum DC input: 36 to 72 VDC, 6.5 to 3.25A, efficiency 80% min @48V
<b>Power consumption</b>	150W nom, 230W max
<b>Maximum QSFP socket power consumption</b>	QSFP: 5.0W (max) per slots
<b>Maximum SFP+ socket power consumption</b>	SFP+: 2.0W (max) per slots
Physical	
<b>Dimensions (W x H x D)</b>	426.6 x 44.2 x 351.3 mm (16.8 x 1.74 x 13.83 in.)
<b>Weight</b>	6500 g (229 oz)
Environmental	
<b>Operating temperature</b>	0° to 50° C (32° to 122° F)
<b>Storage temperature</b>	-40° to +70° C (-40° to +158° F)
<b>Maximum altitude</b>	2000 m (6562 ft) above sea level
<b>Operating/storage humidity</b>	Operating humidity 5% to 85% RH, noncondensing Storage humidity 5% to 95% RH, noncondensing
Regulatory and standard compliance (unique ID: NG100)	
<b>Safety</b>	IEC 62368-1, EN 62368-1, UL 62368-1, CSA C22.2 No. 62368-1, AS/NZS 62368.1, J62368-1, CEI EN 62368-1, DS/EN 62368-1, SASO-IEC-62368-1
<b>EMC - Emission (Class A)</b>	CISPR 32, IEC 61000-3-2, IEC 61000-3-3, EN 55032, EN 61000-3-2, EN 61000-3-3, 47 CFR Part 15 Sub-part B, ICES-003, AS/NZS CISPR 32, VCCI-CISPR 32, KS C 9832
<b>EMC - Immunity</b>	CISPR 35, EN 55035, KS C 9835
<b>Telco</b>	NEBS Level-3: GR-63, GR-1089 (Pending)
<b>Radio</b>	EN 301 489-1/19, EN 303 413

## Power and connectivity

### Environmental

RoHS: IEC 63000:2016,EN IEC 63000:2018

## Assurance Sensor F100 models

**Table 3.** Assurance Sensor F100 models

Model	100GE QSFP interfaces	Power	Description	Cisco PID
<b>100G-AC-DC</b>	4	DC or AC hot swappable power supply	Provider Connectivity Assurance Sensor F100 quad 100 GE ports (QSFP28)	SKY-F100

## Power options and accessories

Choose between 19- and 23-in. rack-mount and wall-mount options, as well as AC power options.

## Cisco environmental sustainability

Information about Cisco’s environmental sustainability policies and initiatives for our products, solutions, operations, and extended operations or supply chain is provided in the “Environmental Sustainability” section of Cisco’s [Corporate Social Responsibility](#) (CSR) Report.

Reference links to information about key environmental sustainability topics (mentioned in the “Environmental Sustainability” section of the CSR Report) are provided in the following table:

Sustainability topic	Reference
Information on product material content laws and regulations	<a href="#">Materials</a>
Information on electronic waste laws and regulations, including products, batteries, and packaging	<a href="#">WEEE compliance</a>

Reference links **to product-specific environmental sustainability information** that is mentioned in relevant sections of this data sheet are provided in the following tables:

Sustainability topic	Reference
<b>General</b>	
Product compliance	Table 2. <a href="#">Safety and compliance information</a>
<b>Power</b>	
Power supply	Table 2. <a href="#">Product specifications: power supplies, typical and maximum power specification</a>
<b>Material</b>	
Unit weight, dimensions, and mean time between failures metrics	Table 2. <a href="#">Product specifications</a>

---

Cisco makes the packaging data available for informational purposes only. It may not reflect the most current legal developments, and Cisco does not represent, warrant, or guarantee that it is complete, accurate, or up to date. This information is subject to change without notice.

## Cisco Services

Cisco offers a wide range of services to help accelerate your success in deploying and optimizing the Cisco Provider Connectivity Assurance platform on your network. The innovative Cisco Services offerings are delivered through a unique combination of people, processes, tools, and partners and are focused on helping you increase operating efficiency and improve your data center network. Cisco Advanced Services uses an architecture-led approach to help you align your data center infrastructure with your business goals and achieve long-term value. Cisco Smart Net Total Care® Service helps you resolve mission-critical problems with direct access at any time to Cisco network experts and award-winning resources.

## Cisco Capital

### **Flexible payment solutions to help you achieve your objectives**

Cisco Capital makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more.](#)

## Learn more

For more information, on the Cisco Provider Connectivity Assurance solution, please visit [cisco.com](https://www.cisco.com).

For technical documentation, visit the [Cisco Provider Connectivity Assurance Documentation site](#).

**Americas Headquarters**  
Cisco Systems, Inc.  
San Jose, CA

**Asia Pacific Headquarters**  
Cisco Systems (USA) Pte. Ltd.  
Singapore

**Europe Headquarters**  
Cisco Systems International BV Amsterdam,  
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)