

Troubleshoot APIC NXOS Style CLI Commands

Contents

[Introduction](#)
[Prerequisites](#)
[Requirements](#)
[Background Information](#)
[NGINX](#)
[The Decoy Service](#)
[Troubleshoot the NXOS Style CLI](#)
[Trace the CLI Command through Logs](#)
[Run the CLI Command](#)
[Check decoy.log for CMD Execution](#)
[Check access.log for API Calls](#)
[Check nginx.bin.log](#)
[Re-run the Individual API Calls](#)
[Via icurl](#)
[Via moquery](#)
[Re-run the CLI Command via Python](#)
[Trace Object Modification via APIC CLI](#)
[Object Creation](#)
[Object Deletion](#)
[References & Useful links](#)

Introduction

This document describes steps to debug commands run from the APIC CLI.

Prerequisites

Requirements

Cisco recommends that you have knowledge of these topics:

- ACI REST API
- ACI Object Model

The reader must have a previous knowledge on how the works, also how the DME process logs their messages.

These documents explain in more detail about the ACI APIC and Object model:

<https://developer.cisco.com/docs/aci/>


<https://www.cisco.com/c/en/us/td/docs/switches/datacenter/aci/apic/sw/policy-model-guide/b-Cisco-ACI-Policy-Model-Guide.html>

Background Information

The Cisco Application policy Controller contains a single Northbound API which is used for Policy management.

Every policy based interaction with an APIC boils down to an HTTP/S API Request/Responded interaction. This holds true for the GUI, custom python scripts and the CLI Commands that exist on both the APICs and Switches.

This Image summarizes the way users and tools interact with the APICs API



All **show** commands run on an APIC invoke the **NXOS Style CLI**. These commands trigger a series of python scripts which build out the API requests required to gather the information requested. When a response is received, it is parsed with python then delivered to the user in a pretty format.

NGINX

NGINX is an open source web server. Each APIC runs its own NGINX process which serves the RESTful API. On an APIC, NGINX includes logging via both the `/var/log/dme/log/nginx.bin.log`

and **/var/log/dme/log/access.log** files.

The **nginx.bin.log** file shows the details of all API requests and DME interactions.

The **access.log** file logs every API request handled by NGINX.

As all API requests are HTTP requests, standard HTTP response codes can be referenced for NGINX API Call handling:

- **200** code is OK
- **4XX** codes are Client Errors
- **5XX** Codes are Server Errors, which is the APIC in this case

The Decoy Service

The Decoy service serves a special API call via a python module hosted off of NGINX.

This service:

1. Accepts the requested CLI command
2. Identifies the python scripts required to build out the REST API calls
3. Sends the API calls to the RESTful API
4. Accepts the response
5. Formats the response
6. Serves the formatted response to the user.

This service includes these log files:

- **/var/log/dme/log/decoy.log**
- **/var/log/dme/log/decoy.error.log**
- **/var/log/dme/log/decoy_server.log**

The decoy.log file registers the CLI Commands that were run.

The **access.log** file from nginx uses the “**POST /decoy/exec/cmd.cli HTTP/1.1**” format along with the HTTP code associated to the request. . The file logs the REST API calls from the command.

Note: The nginx and decoy logs mentioned are collected within the APIC 3of3 Techsupport.

Troubleshoot the NXOS Style CLI

Trace the CLI Command through Logs

Run the CLI Command

For this example, the “show controller” is issued via the APIC CLI:

```
APIC-1# show controller
Fabric Name      : ACI-POD1
```

```

Operational Size      : 2
Cluster Size        : 3
Time Difference     : 0
Fabric Security Mode : PERMISSIVE

```

ID	Pod	Address	In-Band IPv4 Version	In-Band IPv6 Flags	OOB IPv4 Serial Number	OOB Health
IPv6						
1*	1	10.0.0.1	0.0.0.0	fc00::1		192.168.1.1
4.2(6h)		crva-	XXXXXXXXXXXX	fully-fit		
2	1	10.0.0.2	0.0.0.0	fc00::1		192.168.1.1
		4.2(6h)	crva-	XXXXXXXXXXXX	fully-fit	
Flags - c:Commissioned r:Registered v:Valid Certificate a:Approved f/s:Failover						
fail/success						
(*)Current (~)Standby (+)AS						

The command returns a pretty formatted output.

Check decoy.log for CMD Execution

The **decoy.log** file can be checked to find the "**show controller**" CMD that was invoked:

```

APIC-1# tail /var/log/dme/log/decoy.log
...
...| AUTH COOKIE="XXXXXX" || ...
...||CLI: {"option": "server", "loglevel": ["disable"], "cols": 171, "mode": [["exec"]], "port": 51719, "cli": ["show", "controller"]}||...
...||port: 51719||...
...||Mode: [[u'exec']]||...
...||Command: [u'show', u'controller']||...
...||CommandCompleter: add exec||...
...||CommandCompleter: add show||...
...||CommandCompleter: add controller||...
...||last tokens: ['show', 'controller']||...
...||modeCmd: Mode: exec, fulltree: False teminal context is : {'mode-module': 'yaci._cfgroot', 'module': 'show._controllers', 'inherited': False}||.
...||('-%CMD_TERM%', {'mode-module': 'yaci._cfgroot', 'module': 'show._controllers', 'inherited': False}, {'prompt': '# ', 'mode': [[u'exec']]}, None)||...
...||terminal command module: {"mode-module": "yaci._cfgroot", "module": "show._controllers", "inherited": false}||.

```

The CLI sends this as a dictionary, we can see it from the highlighted line. The formatted version would look like this:

```
{
  "option": "server",
  "loglevel": [
    "disable" <-- Can be modified to debug the interaction further.
  ],
  "cols": 171,
  "mode": [
    <-- Command ran by admin
    [
      "exec"
    ]
  ],
  "port": 51719, <-- Random TCP port from session.
  "cli": [
    <-- Actual command
    "show",
    "controller"
  ]
}
```

}

The line with '_%CMD_TERM%' shows the command executed, along with the module used, in this example:

```
('_%CMD_TERM%', {'mode-module': 'yaci._cfgroot', 'module': 'show._controllers', 'inherited': False}, {'prompt': '# ', 'mode': [[u'exec']]}, None)
```

The CLI module must then translate it to REST API calls.

Check access.log for API Calls

The **access.log** file displays the API Calls received after decoy processes the CMD:

```
APIC-1# tail /var/log/dme/log/access.log
...
127.0.0.1 -- [24/May/2021:18:43:12 +0000] "POST /decoy/exec/cmd.cli HTTP/1.1" 200 0 "--"
"python-requests/2.7.0..."
127.0.0.1 -- [24/May/2021:18:43:19 +0000] "GET /api/mo/topology/pod-1/node-1/sys.xml HTTP/1.1"
200 1273 "--" "python-requests/2.7.0..."
127.0.0.1 -- [24/May/2021:18:43:19 +0000] "GET /api/mo/uni/fabsslcomm/ifmcertnode-1.xml
HTTP/1.1" 200 2391 "--" "python-requests/2.7.0..."
127.0.0.1 -- [24/May/2021:18:43:19 +0000] "GET /api/mo/uni/fabsslcomm/ifmcertnode-2.xml
HTTP/1.1" 200 2508 "--" "python-requests/2.7.0..."
127.0.0.1 -- [24/May/2021:18:43:19 +0000] "GET /api/mo/topology/pod-1/node-2/sys.xml HTTP/1.1"
200 1265 "--" "python-requests/2.7.0..."
```

Check nginx.bin.log

The *nginx.bin.log* file includes additional details on all API Requests handled and must include information about the payload received from various DMEs before it is sent back to the requester.

In the same file, after **decoy/exec/cmd.cli** is called, there are several API calls logged:

```
admin@APIC-1:log> cat nginx.bin.log | grep "ifmcertnode|sys.xml"
17567||2021-05-24T18:43:19.817094383+00:00||nginx||DBG4||||Request received
/api/mo/topology/pod-1/node-1/sys.xml||./common/src/rest./Rest.cc||67 bico 11.322
17567||2021-05-24T18:43:19.817184335+00:00||nginx||DBG4||||httpmethod=1; from 127.0.0.1;
url=/api/mo/topology/pod-1/node-1/sys.xml; url options=||./common/src/rest./Request.cc||133

17567||2021-05-24T18:43:19.817409193+00:00||nginx||DBG4||||Request received
/api/mo/topology/pod-1/node-2/sys.xml||./common/src/rest./Rest.cc||67
17567||2021-05-24T18:43:19.817466216+00:00||nginx||DBG4||||httpmethod=1; from 127.0.0.1;
url=/api/mo/topology/pod-1/node-2/sys.xml; url options=||./common/src/rest./Request.cc||133

17567||2021-05-24T18:43:19.817589102+00:00||nginx||DBG4||||Request received
/api/mo/uni/fabsslcomm/ifmcertnode-1.xml||./common/src/rest./Rest.cc||67
17567||2021-05-24T18:43:19.817641070+00:00||nginx||DBG4||||httpmethod=1; from 127.0.0.1;
url=/api/mo/uni/fabsslcomm/ifmcertnode-1.xml; url options=||./common/src/rest./Request.cc||133

17567||2021-05-24T18:43:19.819268449+00:00||nginx||DBG4||||Request received
/api/mo/uni/fabsslcomm/ifmcertnode-2.xml||./common/src/rest./Rest.cc||67
17567||2021-05-24T18:43:19.819340589+00:00||nginx||DBG4||||httpmethod=1; from 127.0.0.1;
url=/api/mo/uni/fabsslcomm/ifmcertnode-2.xml; url options=||./common/src/rest./Request.cc||133
...
```

Re-run the Individual API Calls

The access.logs contain a list of exactly which API calls were sent for processing.

The goal of this step is to re-run each API call to determine:

1. Is there an issue with the API call itself?
2. Is there something different about a successful API call vs a failed one?

For example, one of the API calls generated from the "show controllers" command is:

```
127.0.0.1 -- [24/May/2021:18:43:19 +0000] "GET /api/mo/topology/pod-1/node-1/sys.xml HTTP/1.1"
200 1273 "-" "python-requests/2.7.0..."
```

Via icurl

This API Request can be re-run with the use icurl on an APIC:

```
icurl 'http://localhost:7777/<API-CALL-from-ACCESS.log>'
```

Note: Port 7777 is specifically used to allow the APIC to query itself.

With the specific call as an example:

```
APIC-1# bash
admin@APIC-1:~> icurl 'http://localhost:7777/api/mo/topology/pod-1/node-1/sys.xml'

<?xml version="1.0" encoding="UTF-8"?>
<imdata totalCount="1">
<topSystem address="10.0.0.1" bootstrapState="none" childAction="" dn="topology/pod-1/node-1/sys" ... />
</imdata>
```

The amount and complexity of API calls required for each NXOS CLI command can differ greatly. In all cases, the queries can be re-played via icurl for request and response validation.

Via moquery

From the previous API calls shown, the module parses the output for the 'show controller' command with the information from the MOs requested.

```
admin@APIC-1:~> moquery -d topology/pod-1/node-1/sys -o xml
...
<topSystem address="10.0.0.1" dn="topology/pod-1/node-1/sys" fabricDomain="ACI-POD1"
id="1" inbMgmtAddr="0.0.0.0" inbMgmtAddr6=""
oobMgmtAddr="192.168.1.1" oobMgmtAddr6="" podId="1" serial="..."
state="in-service" version="4.2(6h)"/>
```

```
admin@APIC-1:~> moquery -d topology/pod-1/node-2/sys -o xml
...
<topSystem address="10.0.0.2" dn="topology/pod-1/node-2/sys" fabricDomain="ACI-POD1"
id="2" inbMgmtAddr="0.0.0.0" inbMgmtAddr6=""
oobMgmtAddr="192.168.1.2" oobMgmtAddr6="" podId="1" serial="..."
state="in-service" version="4.2(6h)"/>
```

```

admin@APIC-1:~> moquery -d uni/fabsslcomm/ifmcertnode-1 -o xml
...
<pkiFabricNodeSSLCertificate nodeId="1" serialNumber="..." subject="/serialNumber=PID:APIC-
SERVER-M2 SN:..." .../>

admin@APIC-1:~> moquery -d uni/fabsslcomm/ifmcertnode-2 -o xml
...
<pkiFabricNodeSSLCertificate nodeId="2" serialNumber="..." subject="/serialNumber=PID:APIC-
SERVER-M2 SN:..." .../>

```

Re-run the CLI Command via Python

As mentioned, all the "show" commands are actually a REST API call to a series of python scripts.

Due to this, a user can technically manually invoke the python script which runs the cmd. The goal here is to see if Python gives more information on why a specific CMD has issues.

For any "show" command that has an issue, invoke the command via Python to compare a successful vs a failed APIC:

```

apic1# ${PYTHON} -m pyclient.remote exec terminal ${COLUMNS} <some show command>
Example runs:

```

```

apic1# ${PYTHON} -m pyclient.remote exec terminal ${COLUMNS} show switch
apic1# ${PYTHON} -m pyclient.remote exec terminal ${COLUMNS} show controller

```

Example where the direct Python script gives additional debug information on a failure:

```

a-apic1# ${PYTHON} -m pyclient.remote exec terminal ${COLUMNS} show switch

Process Process-2:
Traceback (most recent call last):
File "/usr/lib64/python2.7/multiprocessing/process.py", line 267, in _bootstrap
self.run()
File "/usr/lib64/python2.7/multiprocessing/process.py", line 114, in run
self._target(*self._args, **self._kwargs)
File "/controller/yaci/execmode/show/_switch_nodes.py", line 75, in _systemQuery
mo = ctx.moDir.lookupByDn(dn)
File "/controller/ishell/cobra/mit/access.py", line 80, in lookupByDn
mos = self.query(dnQuery)
File "/controller/yaci/pyclient/local.py", line 36, in query
raise e
QueryError: Unable to deliver the message, Resolve timeout from (type/num/svc/shard) =
switch:205:4:0

ID Pod Address In-Band IPv4 In-Band IPv6 OOB IPv4 OOB IPv6 Version Flags Serial Number Name
--- --- -----
101 1 10.0.40.65 192.168.2.231 :: 192.168.1.101 :: n9000-14.2(60) aliv XXXXXXXXXXXX leaf101
...
205 ...<empty>...
al-v XXXXXXXXXXXX leaf205
206 2 10.0.156.65 192.168.2.236 :: 192.168.1.106 :: n9000-14.2(61) aliv XXXXXXXXXXXX leaf206
...

```

Flags - a:Active | l/s:Leaf/Spine | v:Valid Certificate | i:In-Service

Trace Object Modification via APIC CLI

Object Creation

The APIC utilizes **configure terminal** to modify the MIT in an NXOS-Like fashion.

The results from these operations can be seen in the **decoy.log** file.

VRF Creation Example:

```
APIC-1# configure terminal
APIC-1(config)# tenant TestTn
APIC-1(config-tenant)# vrf context Test-CTX-1
APIC-1(config-tenant-vrf)#

```

Output from **decoy.log**:

```
'18279 || 2021-05-25 22:52:11,877 || decoy || INFO || AUTH
COOKIE="eyJhbGciOiJSUzI1NiIiImtpZCI6ImgycDE1NmdjYXIXMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoiand0
In0.eyJyYmFjIjpbeijkb21haW4iOjJhbGwiLCJyb2xlclIiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQJQyIsInvz
ZXJuYW1lIjoiYWRtaW4iLCJ1c2VyaWQiojE1Mzc0LCJ1c2VyZmxhZ3MiOjQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIx
MjgyMjY2LCJzZXNzaWuaWQiojJUWW9pZGgyMFRIeUc5YldMu1hb0FnPT0ifQ.ksnCeOxrNQeuNaQnmpauUG_eja70nVta
CbamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLs41VraukWw8Fztd281eaSQPPWiT-
ieCjWxim8Sw4spYS8XBxBrBBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw
064LH7rMEpzyCTapJBXdKzUhJ-zm98fmOyloGGTTeSwp_ksH14Xq411k1ebJ83sV4tL6-
FJLhcPNIKWqYJ87fqUWwZFZb5tY4JUJxrsnahKfwyidNx5m8LCIc8pt-xbBtVihAFkAYBoxKI-
OYBrwg" ||/mgmt/opt/controller/decoy/decoy/_app.py|32'
'18279 || 2021-05-25 22:52:11,878 || decoy || INFO || CLI: {"option": "server", "loglevel": ["disable"], "cols": 100, "mode": [{"exec"}, {"configure", "terminal}], "port": 60003, "cli": [{"tenant", "TestTn}] ||/mgmt/opt/controller/decoy/apps/execserver/execapp.py|88'
'18279 || 2021-05-25 22:52:11,878 || decoy || INFO || port:
60003 ||/mgmt/opt/controller/decoy/apps/execserver/execapp.py|107'
'18279 || 2021-05-25 22:52:11,879 || decoy || INFO || Mode: [u'exec', u'configure', u'terminal'] ||/mgmt/opt/controller/decoy/apps/execserver/execapp.py|120'
'18279 || 2021-05-25 22:52:11,879 || decoy || INFO || Command: [u'tenant',
u'TestTn']] ||/mgmt/opt/controller/decoy/apps/execserver/execapp.py|121'
'18279 || 2021-05-25 22:52:11,879 || decoy || DEBUG || CommandCompleter: add
exec ||/mgmt/opt/controller/yaci/yaci/_completer.py|255'
'18279 || 2021-05-25 22:52:11,880 || decoy || DEBUG || CommandCompleter: add
configure ||/mgmt/opt/controller/yaci/yaci/_completer.py|255'
'18279 || 2021-05-25 22:52:11,880 || decoy || DEBUG || OptionKeyword: add
terminal ||/mgmt/opt/controller/yaci/yaci/_completer.py|1036'
'11818 || 2021-05-25 22:52:11,910 || decoy || DEBUG || CommandCompleter: add
tenant ||/mgmt/opt/controller/yaci/yaci/_completer.py|255'
'11818 || 2021-05-25 22:52:11,911 || decoy || DEBUG || ArgCompleter: add
TestTn ||/mgmt/opt/controller/yaci/yaci/_completer.py|531'
'11818 || 2021-05-25 22:52:11,912 || decoy || INFO || last tokens: ['tenant',
u'TestTn']] ||/mgmt/opt/controller/yaci/yaci/_ctx.py|617'
'11818 || 2021-05-25 22:52:11,912 || decoy || INFO || TID: 98 || CLI Command: 'tenant
TestTn' ||/mgmt/opt/controller/yaci/yaci/_transaction.py|67'

'11818 || 2021-05-25 22:52:14,331 || decoy || DEBUG || [commit]: <?xml version="1.0" encoding="UTF-8"?>
<fvTenant name='TestTn'
status='created,modified'></fvTenant> ||/mgmt/opt/controller/yaci/yaci/_ctx.py|1024'
'11818 || 2021-05-25 22:52:14,349 || decoy || INFO || CLIENT-HEADERS: {'APIC-Client': u'tenant TestTn',
'Cookie': 'APIC-
cookie=eyJhbGciOiJSUzI1NiIiImtpZCI6ImgycDE1NmdjYXIXMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoiand0I

```

n0.eyJyYmFjIjpbeYJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQJQyIsInVzzXJuYW1lIjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiOjQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxMjgyMjY2LCJzZXNzaW9uaWQiOjJUWW9pZGgyMFRIeUc5YldMu1hb0FnPT0ifQ.ksnCeOxrNQeuNaQnmpauUG_eja70nVtaCbamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTesBteSWP_ksH14Xq411k1ebJ83sV4tL6-FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNxT5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrg',
'Client_Name': 'APIC-CLI', 'Request-Tag':
'tag0'}||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||31'
'11818||2021-05-25 22:52:14,350||decoy||INFO||Starting new HTTP connection (1):
127.0.0.1||/mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-packages/requests/packages/urllib3/connectionpool.py||203'
'11818||2021-05-25 22:52:14,381||decoy||DEBUG||"POST /api/mo/uni/tn-TestTn.xml HTTP/1.1" 200
70||/mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-packages/requests/packages/urllib3/connectionpool.py||383'
'18279||2021-05-25 22:52:14,383||decoy||DEBUG||(None, {}, {'prompt': '(config-tenant)# ',
'mode': [[u'exec'], [u'configure'], [u'terminal'], ['tenant', u'TestTn']]],
None)||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||144'

'18280||2021-05-25 22:52:48,569||decoy||INFO||AUTH
COOKIE="eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIXMG50emx3YmR3MDfjnNv5dGEycXQzIiwidHlwIjoiand0In0.eyJyYmFjIjpbeYJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQJQyIsInVzzZXJuYW1lIjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiOjQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxMjgyMjY2LCJzZXNzaW9uaWQiOjJUWW9pZGgyMFRIeUc5YldMu1hb0FnPT0ifQ.ksnCeOxrNQeuNaQnmpauUG_eja70nVtaCbamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTesBteSWP_ksH14Xq411k1ebJ83sV4tL6-FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNxT5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrg"||/mgmt/opt/controller/decoy/decoy/_app.py||32'
'18280||2021-05-25 22:52:48,571||decoy||INFO||CLI: {"option": "server", "loglevel": ["disable"],
"cols": 100, "mode": [[["exec"], ["configure", "terminal"], ["tenant", "TestTn"]], "port": 60821,
"cli": ["vrf", "context", "Test-CTX-
1"]]}||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||88'
'18280||2021-05-25 22:52:48,571||decoy||INFO||port:
60821||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||107'
'18280||2021-05-25 22:52:48,572||decoy||INFO||Mode: [[u'exec'], [u'configure', u'terminal'],
[u'tenant', u'TestTn']]||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||120'
'18280||2021-05-25 22:52:48,572||decoy||INFO||Command: [u'vrf', u'context', u'Test-CTX-
1']||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||121'
'18280||2021-05-25 22:52:48,572||decoy||DEBUG||CommandCompleter: add
exec||/mgmt/opt/controller/yaci/yaci/_completer.py||255'
'18280||2021-05-25 22:52:48,572||decoy||DEBUG||CommandCompleter: add
configure||/mgmt/opt/controller/yaci/yaci/_completer.py||255'
'18280||2021-05-25 22:52:48,573||decoy||DEBUG||OptionKeyword: add
terminal||/mgmt/opt/controller/yaci/yaci/_completer.py||1036'
'18280||2021-05-25 22:52:48,574||decoy||DEBUG||CommandCompleter: add
tenant||/mgmt/opt/controller/yaci/yaci/_completer.py||255'
'18280||2021-05-25 22:52:48,574||decoy||DEBUG||ArgCompleter: add
TestTn||/mgmt/opt/controller/yaci/yaci/_completer.py||531'
'13482||2021-05-25 22:52:48,599||decoy||DEBUG||CommandCompleter: add
vrf||/mgmt/opt/controller/yaci/yaci/_completer.py||255'
'13482||2021-05-25 22:52:48,600||decoy||DEBUG||Keyword: add
context||/mgmt/opt/controller/yaci/yaci/_completer.py||983'
'13482||2021-05-25 22:52:48,601||decoy||DEBUG||ArgCompleter: add Test-CTX-
1||/mgmt/opt/controller/yaci/yaci/_completer.py||531'
'13482||2021-05-25 22:52:48,602||decoy||INFO||last tokens: ['vrf', 'context', u'Test-CTX-
1']||/mgmt/opt/controller/yaci/yaci/_ctx.py||617'
'13482||2021-05-25 22:52:48,602||decoy||INFO||TID: 105||CLI Command: 'vrf context Test-CTX-
1'||/mgmt/opt/controller/yaci/yaci/_transaction.py||67'

'13482||2021-05-25 22:52:51,393||decoy||DEBUG||[commit]: <?xml version="1.0" encoding="UTF-8"?>
 <fvCtx status='created,modified' name='Test-CTX-
1'></fvCtx>||/mgmt/opt/controller/yaci/yaci/_ctx.py||1024'
'13482||2021-05-25 22:52:51,405||decoy||INFO||CLIENT-HEADERS: {'APIC-Client': u'tenant TestTn';

```

vrf context Test-CTX-1', 'Cookie': 'APIC-
cookie=eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoia
n0 eyJyYmFjIjpbeJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQYIsInVzz
XJuYWlIjoiYWRtaW4iLCJ1c2VyaWQiojE1Mzc0LCJ1c2VyzmxhZ3MiojQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxM
jgyMjY2LCJzZXNzaWuaWQiojIjUWW9pZGgyMFRIeUc5YldMULhb0FnPT0ifQ.ksnCeOxrNQeuNaQnmpauUG_eja70nVtaC
bamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw
064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTessBteSWP_ksH14Xq411k1ebJ83sV4tL6-
FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrsnahKfwyidNxt5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg',
'Client_Name': 'APIC-CLI', 'Request-Tag':
'tag0'} || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 31'
'13482 | 2021-05-25 22:52:51,407 || decoy || INFO || Starting new HTTP connection (1):
127.0.0.1 || /mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py | 203'
'13482 | 2021-05-25 22:52:51,452 || decoy || DEBUG || "POST /api/mo/uni/tn-TestTn/ctx-Test-CTX-1.xml
HTTP/1.1" 200 70 || /mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py | 383'
'18280 | 2021-05-25 22:52:51,455 || decoy || DEBUG || (None, {}, {'prompt': '(config-tenant-vrf)# ',
'mode': [[u'exec'], [u'configure', u'terminal'], [u'tenant', u'TestTn'], ['vrf', 'context',
'u'Test-CTX-1']]], None) || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 144'

```

Observe the fvTenant and fvCtx objects both set with **status="created,modified"**.

Object Deletion

We can review the REST operations involved when any MO gets deleted.

VRF Deletion example:

```

APIC-1# configure terminal
APIC-1(config)# tenant TestTn
APIC-1(config-tenant)# no vrf context Test-CTX-1
APIC-1(config-tenant-vrf)#

```

Output from **decoy.log**:

```

'18279 | 2021-05-25 23:32:40,009 || decoy || INFO || AUTH
COOKIE="eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoia
n0 eyJyYmFjIjpbeJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQYIsInVzz
XJuYWlIjoiYWRtaW4iLCJ1c2VyaWQiojE1Mzc0LCJ1c2VyzmxhZ3MiojQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxM
jgyMjY2LCJzZXNzaWuaWQiojIjUWW9pZGgyMFRIeUc5YldMULhb0FnPT0ifQ.ksnCeOxrNQeuNaQnmpauUG_eja70nVtaC
bamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw
064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTessBteSWP_ksH14Xq411k1ebJ83sV4tL6-
FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrsnahKfwyidNxt5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg" || /mgmt/opt/controller/decoy/decoy/_app.py | 32'
'18279 | 2021-05-25 23:32:40,010 || decoy || INFO || CLI: {"option": "server", "loglevel": ["disable"], "cols": 100, "mode": [[["exec"], ["configure", "terminal]], "port": 32789, "cli": ["tenant", "TestTn"]]} || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 88'
'18279 | 2021-05-25 23:32:40,011 || decoy || INFO || port:
32789 || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 107'
'18279 | 2021-05-25 23:32:40,012 || decoy || INFO || Mode: [[u'exec'], [u'configure', u'terminal']] || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 120'
'18279 | 2021-05-25 23:32:40,012 || decoy || INFO || Command: [u'tenant', u'TestTn'] || /mgmt/opt/controller/decoy/apps/execserver/execapp.py | 121'
'18279 | 2021-05-25 23:32:40,012 || decoy || DEBUG || CommandCompleter: add
exec || /mgmt/opt/controller/yaci/yaci/_completer.py | 255'
'18279 | 2021-05-25 23:32:40,013 || decoy || DEBUG || CommandCompleter: add
configure || /mgmt/opt/controller/yaci/yaci/_completer.py | 255'
'18279 | 2021-05-25 23:32:40,013 || decoy || DEBUG || OptionKeyword: add

```

```
terminal || /mgmt/opt/controller/yaci/yaci/_completer.py || 1036'
'27163 || 2021-05-25 23:32:40,042 || decoy || DEBUG || CommandCompleter: add
tenant || /mgmt/opt/controller/yaci/yaci/_completer.py || 255'
'27163 || 2021-05-25 23:32:40,043 || decoy || DEBUG || ArgCompleter: add
TestTn || /mgmt/opt/controller/yaci/yaci/_completer.py || 531'
'27163 || 2021-05-25 23:32:40,043 || decoy || INFO || last tokens: ['tenant',
u'TestTn'] || /mgmt/opt/controller/yaci/yaci/_ctx.py || 617'
'27163 || 2021-05-25 23:32:40,044 || decoy || INFO || TID: 106 || CLI Command: 'tenant
TestTn' || /mgmt/opt/controller/yaci/yaci/_transaction.py || 67'

'27163 || 2021-05-25 23:32:42,467 || decoy || DEBUG || [commit]: <?xml version="1.0" encoding="UTF-8"?>
<fvTenant name='TestTn'
status='created,modified'></fvTenant> || /mgmt/opt/controller/yaci/yaci/_ctx.py || 1024'
'27163 || 2021-05-25 23:32:42,485 || decoy || INFO || CLIENT-HEADERS: {'APIC-Client': u'tenant TestTn',
'Cookie': 'APIC-'
cookie=eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoiand0In0.eyJyYmFjIjpbeJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQJQyIsInVzzXJuYW1lIjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiOjQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxMjgyMjY2LCJzZXNzaW9uaWQiOjJUWW9pZGgyMFRIeUc5YldMu1hb0FnPT0ifQ.ksnCeOxnRNQeuNaQnmpauUG_eja70nVtaCbamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-ieCjWxim8Sw4spYS8XBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw064LH7rMepzyCTapJBXdkzUhJ-zm98fmOyloGGTessBteSWP_ksH14Xq411k1ebJ83sV4tL6-FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNx5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg',
'Client_Name': 'APIC-CLI', 'Request-Tag':
'tag0'} || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 31'
'27163 || 2021-05-25 23:32:42,487 || decoy || INFO || Starting new HTTP connection (1):
127.0.0.1 || /mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-packages/requests/packages/urllib3/connectionpool.py || 203'
'27163 || 2021-05-25 23:32:42,517 || decoy || DEBUG || "POST /api/mo/uni/tn-TestTn.xml HTTP/1.1" 200
70 || /mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-packages/requests/packages/urllib3/connectionpool.py || 383'
'18279 || 2021-05-25 23:32:42,520 || decoy || DEBUG || (None, {}, {'prompt': '(config-tenant)# ',
'mode': [[u'exec'], [u'configure', u'terminal'], ['tenant', u'TestTn']]}, None) || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 144'

'18280 || 2021-05-25 23:32:53,702 || decoy || INFO || AUTH
COOKIE="eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoiand0In0.eyJyYmFjIjpbeJkb21haW4iOjJhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjJBQ0kgQVBQJQyIsInVzzXJuYW1lIjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiOjQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxMjgyMjY2LCJzZXNzaW9uaWQiOjJUWW9pZGgyMFRIeUc5YldMu1hb0FnPT0ifQ.ksnCeOxnRNQeuNaQnmpauUG_eja70nVtaCbamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWiT-ieCjWxim8Sw4spYS8XBx62tot201TIEJ8mUFHUjvXpPctDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw064LH7rMepzyCTapJBXdkzUhJ-zm98fmOyloGGTessBteSWP_ksH14Xq411k1ebJ83sV4tL6-FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNx5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg" || /mgmt/opt/controller/decoy/decoy/_app.py || 32'
'18280 || 2021-05-25 23:32:53,704 || decoy || INFO || CLI: {"option": "server", "loglevel": ["disable"], "cols": 100, "mode": [[["exec"], ["configure", "terminal"], ["tenant", "TestTn"]], {"port": 32805, "cli": ["no", "vrf", "context", "Test-CTX-1"]}] || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 88'
'18280 || 2021-05-25 23:32:53,704 || decoy || INFO || port:
32805 || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 107'
'18280 || 2021-05-25 23:32:53,705 || decoy || INFO || Mode: [[u'exec'], [u'configure', u'terminal'], [u'tenant', u'TestTn']] || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 120'
'18280 || 2021-05-25 23:32:53,705 || decoy || INFO || Command: [u'no', u'vrf', u'context', u'Test-CTX-1'] || /mgmt/opt/controller/decoy/apps/execserver/execapp.py || 121'
'18280 || 2021-05-25 23:32:53,705 || decoy || DEBUG || CommandCompleter: add
exec || /mgmt/opt/controller/yaci/yaci/_completer.py || 255'
'18280 || 2021-05-25 23:32:53,706 || decoy || DEBUG || CommandCompleter: add
configure || /mgmt/opt/controller/yaci/yaci/_completer.py || 255'
'18280 || 2021-05-25 23:32:53,706 || decoy || DEBUG || OptionKeyword: add
terminal || /mgmt/opt/controller/yaci/yaci/_completer.py || 1036'
'18280 || 2021-05-25 23:32:53,708 || decoy || DEBUG || CommandCompleter: add
tenant || /mgmt/opt/controller/yaci/yaci/_completer.py || 255'
'18280 || 2021-05-25 23:32:53,708 || decoy || DEBUG || ArgCompleter: add
```

```

TestTn||/mgmt/opt/controller/yaci/yaci/_completer.py||531'
'27771||2021-05-25 23:32:53,736||decoy||DEBUG||CommandCompleter: add
vrf||/mgmt/opt/controller/yaci/yaci/_completer.py||255'
'27771||2021-05-25 23:32:53,737||decoy||DEBUG||Keyword: add
context||/mgmt/opt/controller/yaci/yaci/_completer.py||983'
'27771||2021-05-25 23:32:53,738||decoy||DEBUG||ArgCompleter: add Test-CTX-
1||/mgmt/opt/controller/yaci/yaci/_completer.py||531'
'27771||2021-05-25 23:32:53,738||decoy||INFO||last tokens: ['no', 'vrf', 'context', u'Test-CTX-
1']||/mgmt/opt/controller/yaci/yaci/_ctx.py||617'
'27771||2021-05-25 23:32:53,738||decoy||INFO||TID: 113||CLI Command: 'no vrf context Test-CTX-
1'||/mgmt/opt/controller/yaci/yaci/_transaction.py||67'
'27771||2021-05-25 23:32:53,740||decoy||INFO||CLIENT-HEADERS: {'APIC-Client': u'tenant TestTn;
no vrf context Test-CTX-1', 'Cookie': 'APIC-
cookie=eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoia
n0.eyJyYmFjIjpbeJkb21haW4iOjIhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjBQ0kgQVBQyIsInVzz
XJuYWl1IjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiojQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxM
jgyMjY2LCJzZXNzaW9uaWQiOjUWW9pZGgymFRieUc5YldMULhb0FnPT0ifQ.ksnCeOxnRQeuNaQnmpauUG_eja70nVtaC
bamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWi-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpCtDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw
064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTeseSWP_ksH14Xq411k1ebJ83sV4tL6-
FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNx5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg',
'Client_Name': 'APIC-CLI', 'Request-Tag':
'tag0'}||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||31'
'27771||2021-05-25 23:32:53,743||decoy||INFO||Starting new HTTP connection (1):
127.0.0.1||/mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py||203'
'27771||2021-05-25 23:32:53,750||decoy||DEBUG||"GET /api/mo/uni/tn-TestTn.xml?target-subtree-
class=13extRsEctx&query-target-filter=eq(13extRsEctx.tnFvCtxName,%22Test-CTX-1%22)&query-
target=subtree HTTP/1.1" 200 70||/mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py||383'
'27771||2021-05-25 23:32:53,753||decoy||DEBUG||dnListLen:
0||/mgmt/opt/controller/yaci/lib/utils/13ext.py||97'

'27771||2021-05-25 23:32:56,375||decoy||DEBUG||[commit]: <?xml version="1.0" encoding="UTF-8"?>
<fvCtx status='deleted' name='Test-CTX-
1'></fvCtx>||/mgmt/opt/controller/yaci/yaci/_ctx.py||1024'
'27771||2021-05-25 23:32:56,386||decoy||INFO||CLIENT-HEADERS: {'APIC-Client': u'tenant TestTn;
no vrf context Test-CTX-1', 'Cookie': 'APIC-
cookie=eyJhbGciOiJSUzI1NiIsImtpZCI6ImgycDE1NmdjYXIxMG50emx3YmR3MDFjNnV5dGEycXQzIiwidHlwIjoia
n0.eyJyYmFjIjpbeJkb21haW4iOjIhbGwiLCJyb2xlc1IiOjEsInJvbGVzVyI6MX1dLCJpc3MiOjBQ0kgQVBQyIsInVzz
XJuYWl1IjoiYWRtaW4iLCJ1c2VyaWQiOjE1Mzc0LCJ1c2VyzmxhZ3MiojQsImlhdCI6MTYyMTI4MTY2NiwiZXhwIjoxNjIxM
jgyMjY2LCJzZXNzaW9uaWQiOjUWW9pZGgymFRieUc5YldMULhb0FnPT0ifQ.ksnCeOxnRQeuNaQnmpauUG_eja70nVtaC
bamxFaB1LLkMIqzJ_wk_GMN1h4eM1WLS41VraukWw8Fztd281eaSQPPWi-
ieCjWxim8Sw4spYS8XBBrBBx62tot201TIEJ8mUFHUjvXpCtDsBYi9YM51UmFxhZgYI2Lx8gg0P6sLoUydcShKKcUNgRmGw
064LH7rMEpzyCTapJBXdkzUhJ-zm98fmOy1oGGTeseSWP_ksH14Xq411k1ebJ83sV4tL6-
FJLhcPNIKwqYJ87fqUWwZFZb5tY4JUJxrSnahKfwyidNx5m8LCIc8pt-xbBtVihAFkAYBoXKI-OYBrwg',
'Client_Name': 'APIC-CLI', 'Request-Tag':
'tag0'}||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||31'
'27771||2021-05-25 23:32:56,426||decoy||DEBUG||"POST /api/mo/tn-TestTn/ctx-Test-CTX-1.xml
HTTP/1.1" 200 70||/mgmt/opt/controller/decoy/decoy-env/lib/python2.7/site-
packages/requests/packages/urllib3/connectionpool.py||383'
'18280||2021-05-25 23:32:56,428||decoy||DEBUG||(None, {}, {'prompt': '(config-tenant)# ', 'mode': [u'exec'], [u'configure', u'terminal'], [u'tenant', u'TestTn']]), None)||/mgmt/opt/controller/decoy/apps/execserver/execapp.py||144'

```

Observe the fvCtx object set with **status="deleted"**.

References & Useful links

- [ACI Programmability](#)
- [Cisco ACI Policy Model Guide](#)
- [Cisco ACI Support for NGINX Rate Limit](#)