Access Web-based Setup Page on SPA500 Series IP Phones

Objective

All devices have built-in setup pages that allows the user to customize settings and set up advanced properties in devices. The setup page allows for easy configuration of the features for the device. This document shows how to access setup page of SPA500 Series IP phones.

Applicable Devices

•SPA 500 Series IP Phones

Steps to access the setup page of SPA devices.

Note: Even though the article is also applicable for all SPA 500 Series IP Phones, the device used is SPA509G.

Note: Before accessing the SPA509G's set up page, make sure the device is connected to PoE (Power over Ethernet) enabled router or switch through its SW port.

Accessing the setup page of SPA509G

Step 1. When the IP phone is turned on, it performs Network Configurations and Setup Configurations. After it completes Network Configuration, press Setup button (paper symbol on it) as shown in figure.



Step 2. This will bring up a Setup menu with different options on IP phone's LCD.



Step 3. Press 3. This will bring up Settings menu on the LCD.



Step 4. Press 5. This will open Network Configuration menu on the LCD.

Step 5. Navigate down to option 3 or just press 3. Note that the IP address is displayed under *IP Address*.

Step 6.Go to a web browser and enter IP address.

Note: The computer and IP phone should be on the same network to access Web-based Utility.

← → C f (③ 192.168.137.162						众 公
cisco SPA509G Configuration Utility						<u>Admin Loqin</u> basic <u>advanced</u>
Voice Call History	Personal Directory	Attendant Consol	e Status			
Info System Phone	User					
						* E
System Information						
Connection Type:	DHCP			Current IP:	192.168.137.162	
Host Name:	SEP089010666F6F			Domain:	msnome.net	
Current Netmask:	200.200.200.0			Current Gateway	192.100.137.1	
Primary DNS. Secondary DNS:	192.100.137.1					
Des dust leferen efter						
Product Information Product Name:	SPA509G			Serial Number:	CBT151508BR	
Software Version:	7 4 8a			Hardware Version:	1.0.2(0001)	
MAC Address:	C89C1D6E6E6E			Client Certificate:	Installed	
Customization:	Open			Licenses:	None	
Phone Status						
Current Time:	1/1/2003 14:27:55			Elapsed Time:	02:13:56	
Broadcast Pkts Sent:	21			Broadcast Bytes Sent:	2138	
Broadcast Pkts Recv:	353			Broadcast Bytes Recv:	36800	-
		Undo All Changes	Submit All Changes			
© 2009 Cisco Systems, Inc. All Rights Reserved.						SPA509G IP Phone

Step 7. Web-based Setup utility will be displayed. If it does not show up, then the computer and IP phone may not be connected to the same network. Ping the IP address of IP phone from the computer to check the connectivity.