



Network Authentication

This document describes the Remote PHY device network authentication on the Cisco cBR Series Converged Broadband Router.

Finding Feature Information

Your software release may not support all the features that are documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. The Feature Information Table at the end of this document provides information about the documented features and lists the releases in which each feature is supported.

Use Cisco Feature Navigator to find information about the platform support and Cisco software image support. To access Cisco Feature Navigator, go to the link <http://tools.cisco.com/ITDIT/CFN/>. An account at the <http://www.cisco.com/> site is not required.

- [Hardware Compatibility Matrix for Cisco Remote PHY Device, on page 1](#)
- [Information about Network Authentication, on page 2](#)
- [How to Enable Network Authentication, on page 2](#)

Hardware Compatibility Matrix for Cisco Remote PHY Device



Note Unless otherwise specified, the hardware components introduced in a given Cisco Remote PHY Device Software Release are supported in all subsequent releases.

Table 1: Hardware Compatibility Matrix for the Cisco 2x2 Remote PHY Device

Cisco HFC Platform	Remote PHY Device
Cisco GS7000 BAU	Cisco 2x2 RPD Software 2.x and Later Releases Cisco Remote PHY Device 2x2 PID—RPD-2X2=

Information about Network Authentication

RPD must be able to operate in both authenticated and unauthenticated networks. Whether authentication is required for an RPD is determined by the network that it is connected to. In some cases, RPD is located in an untrusted network, and it must connect to devices inside the trusted network, which presents a potential security vulnerability. 802.1x is introduced to provide authentication services to eliminate the potential security issues.

802.1x is a Layer 2 protocol that uses EAP (Extensible Authentication Protocol) to provide authentication services. Following certificates are needed to use the network authentication:

- Cablelabs Root CA certificate: caRoot.pem
- CableLabs Device CA Certificate: deviceCA.pem
- RPD Certificate: rpdCert.pem, private key: rpd.key
- Cablelabs Service Provider CA Certificate: spCA.pem
- AAA Server Certificate: aaaCert.pem, private key: aaa.key

How to Enable Network Authentication

This section describes how to enable network authentication for RPD.

Installing Certificates in Radius Server

To install the certificate in Radius server, follow the steps below:

Step 1 Combine CA certificate for AAA server.

Example:

```
cat spCA.pem caRoot.pem > ca_root_srv.pem
```

Step 2 In freeRadius Server, copy "ca_root_srv.pem", "spCA.pem", "aaaCert.pem" and "aaa.key" to "/etc/freeradius/certs".

Configuring Radius Server

To install the certificate in RPD, follow the steps below:

Step 1 Define a new client in /etc/freeradius/clients.conf.

Example:

```
client rphytest_ng13 {
    ipaddr = 20.5.0.36
    secret = rphytest
    shortname = ng13_switch
}
```

```
        require_message_authenticator = yes
    }
```

The "ipaddr" is the switch's management ip address.

- Step 2** In "/etc/freeradius/eap.conf", change the following lines in "tls" to specify the server's private key file and certificate files.

Example:

```
tls {
    ...
    private_key_file = ${certdir}/aaa.key
    certificate_file = ${certdir}/aaaCert.pem
    CA_file = ${cadir}/ca_root_srv.pem
}
```

- Step 3** Start radius in radius sever.

Example:

```
sudo freeradius
```

Make sure only one freeradius instance is running.

Configuring Switch

To configure the switch, follow the steps below:



Note This procedure is for Catalyst 3750 switch, other switch may use different commands.

- Step 1** Add the following configuration in global configuration mode.

Example:

```
dot1x system-auth-control /* enable 802.1x */
aaa new-model
aaa authentication dot1x default group radius
radius-server host 10.79.41.103 auth-port 1812 key rphytest
```

- Step 2** Add the following configuration under interface which connects to RPD.

Example:

```
authentication port-control auto
dot1x pae authenticator
```

Verifying Authentication Status

To displays dot1x authentication information for RPD, use the **show dot1x** command as shown in the following example:

```
Router# show dot1x summary
```

Interface	Core-id	EAP_Received	Status
vbh0	CORE-3415960568	True	UP

```
Router# show dot1x detail
```

Interface	Core-id	EAP_Received	Status
vbh0	CORE-3415960568	True	UP

```
bssid=01:80:c2:00:00:03
```

```
freq=0
```

```
ssid=
```

```
id=0
```

```
mode=station
```

```
pairwise_cipher=NONE
```

```
group_cipher=NONE
```

```
key_mgmt=IEEE 802.1X (no WPA)
```

```
wpa_state=COMPLETED
```

```
ip_address=30.85.40.47
```

```
address=00:04:9f:00:03:73
```

```
Supplicant PAE state=AUTHENTICATED
```

```
suppPortStatus=Authorized
```

```
EAP state=SUCCESSselected
```

```
Method=13 (EAP-TLS)EAP TLS
```

```
cipher=ECDHE-RSA-AES256-SHA
```

```
tls_session_reused=0
```

```
eap_session_id=0c53798f346014cc924ac1151521ba6a14c98f91985e8c81a701b7272be7f812e7e5a75881768d74d311795a3bf0e37bfa7fff7dc4685c86f216ec59850
```

```
uuid=ab722cfb-84dc-5835-a905-edfec20f78c3
```