

# Cisco Nexus 3600 Series NX-OS Verified Scalability Guide, Release 10.3(6)M

First Published: 2024-08-23

## Introduction

This document describes the Cisco NX-OS configuration limits for Cisco Nexus 3600 Series switches.

The values provided in this guide should not be interpreted as theoretical system limits for Cisco Nexus 3600 platform hardware or Cisco NX-OS software. These limits refer to values that have been validated by Cisco. They can increase over time as more testing and validation is done.

## Verified Scalability Limits (Unidimensional)

The tables in this section list the verified scalability limits for Cisco NX-OS Release 10.3(6)M. These limits are validated with a unidimensional configuration. The values provided in these tables focus on the scalability of one particular feature at a time.

Each number is the absolute maximum currently supported by this Cisco NX-OS release for the corresponding feature. If the hardware is capable of a higher scale, future software releases might increase this verified maximum limit. Results might differ from the values listed here when trying to achieve maximum scalability with multiple features enabled.

**Table 1: Intelligent Traffic Director Verified Scalability Limits (Unidimensional)**

Feature	Supported Platforms	Verified Limit
Nodes per device group	N3K-C36180YC-R, N3K-C3636C-R	16
Buckets per ITD service	N3K-C36180YC-R, N3K-C3636C-R	64

**Table 2: Interfaces Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
DHCP servers/relay IPs per switch	5 (IPv4) + 5 (IPv6) <sup>1</sup>
MAC address - table limit per port	2,000 - (Nexus 3636C-R and 36180YC-R switches)
MAC address - table system, VLAN limit	2,000 - (Nexus 3636C-R and 36180YC-R switches)
Port channel member links	32
SVIs	3967

Feature	Verified Limit
vPCs	48

<sup>1</sup> This limit has not been tested

**Table 3: Label Switching Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
LDP sessions	200
Forwarding Equivalence Classes (FECs)	1,000
Equal-cost multipaths (ECMPs)	8
FECs ECMPs	4,000
IAS option B labels	450,000
Layer 3 VPN routes	100,000
ECMPs	2,000

**Table 4: Layer 2 Switching Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit	
MAC addresses (default template)	196,000	
MAC addresses (L2-scale template)	384,000	
MST instances	64	
MST virtual ports	218,185	
RPVST virtual ports	13,750	
VLANs	3,967	
VLANs in RPVST mode	250	
<b>Private VLANs (PVLANS)</b>		
Primary VLANs	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	7
Secondary VLANs	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	7
Ports in Community host mode	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	40
Ports in isolated host mode	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	40

Feature	Verified Limit	
Ports in isolated trunk host mode	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	40
Ports in promiscuous mode	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	40
Ports in promiscuous trunk mode	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	40
PVLANs allowed on a PVLAN port	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	7
Maximum number of VLANs (private VLAN's, native VLANs and normal VLANs) configurable on a PVLAN ports per ASIC	Nexus N3K-C36180YC-R and N3K-C3636C-R switches	4096

**Table 5: Programmability Verified Scalability Limits (Unidimensional)**

Feature	Supported Platforms	Verified Limits
<b>NX-API</b>		
See <a href="#">Guidelines and Limitations</a> for NX-API limitations.		
Maximum Number of concurrent VSH session	Nexus 3600 switches and line cards	20 concurrent VSH sessions
Number of worker processes in Nginx	Nexus 3600 switches and line cards	4 worker processes
Number of VSH sessions per worker process	Nexus 3600 switches and line cards	A maximum of 5 persistent VSH sessions are supported for each worker process
Maximum response size supported in output	Nexus 3600 switches and line cards	10 MB
Maximum number of concurrent session supported for chunk mode. See <a href="#">Configuring the Message Format and Command Type</a> to know more about chunk mode	Nexus 3600 switches and line cards	2
Maximum size of response supported in chunk mode	Nexus 3600 switches and line cards	After 10.3(1) release, the maximum size supported in chunk mode is the same as the amount of space available in volatile.

**Table 6: Layer 3 Multicast Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
IPv4 multicast routes	32,000 (Layer 3)
Outgoing interfaces (OIFs)	16 OIFs for 32K mroutes or 287 OIFs for 1000 mroutes
PIM neighbors	500
SVI	50-60
IGMP snooping groups	8000
<b>MVPN- unidimensional</b>	
Multicast VRFs	100 (N3K-C3636C-R and N3K-C36180YC-R)
Default MDT groups	100 (N3K-C3636C-R and N3K-C36180YC-R)
MVPN Peers (PIM neighbors) per device	100 (N3K-C3636C-R and N3K-C36180YC-R)

**Table 7: Security Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
IPv4 ingress access control entries (ACEs)	RACL-2000, PACL-1024 (without TCAM Carving)
IPv6 ingress access control entries (ACEs)	RACL-1000, PACL-1024 (without TCAM Carving)
ACL	12,000 (with TCAM Carving)
Egress ACLs	20,000 (N3K-C3636C-R and N3K-C36180YC-R)
RACLs	4,000 (N3K-C3636C-R and N3K-C36180YC-R)
System ACLs	4,000 TCAM entries in internal TCAM and 64,000 TCAM entries in external TCAM (N3K-C3636C-R and N3K-C36180YC-R)

**Table 8: System Management Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
<b>SPAN and ERSPAN</b>	
Configurable SPAN or ERSPAN sessions	32
Active SPAN or ERSPAN sessions	32
Active localized SPAN or ERSPAN session per line card	32 sessions across ports on single line card

Feature	Verified Limit
Active localized SPAN or ERSPAN session (Rx and Tx, Rx, or Tx)	32 sessions, 128 sources and 1 destination
Destination interfaces per SPAN session	1
Source VLANs per SPAN or ERSPAN	6

**Table 9: Layer 3 Unicast Routing Verified Scalability Limits (Unidimensional) - For Default system routing template**

Feature	Verified Limit
BFD sessions (echo mode)	288
	100 MHBFD sessions (N3K-C3636C-R and N3K-C36180YC-R)
BGP neighbors	256
HSRP groups	498
IPv4 ARP	75,000
IPv4 host routes	750,000
IPv6 host routes	62,000
IPv6 ND	32,000
IPv4 unicast routes (LPM)	192,000
IPv6 unicast routes (LPM)	62,000
OSPFv2 neighbors	1,000
OSPFv3 neighbors	1,000
OSPF/OSPFv3 LSA/LSDB size	250,000
OSPF/OSPFv3 areas	15
VRFs	3,967
<b>VRRP</b>	
VRRP groups per interface or I/O module	15

**Table 10: Layer 3 Unicast Routing Verified Scalability Limits (Unidimensional) - For Internet-peering system routing template**

Feature	Verified Limit
Routes (internet-peering mode)	852000
IPv4 routes (internet-peering mode)	781000

Feature	Verified Limit
IPv6 routes (internet-peering mode)	71000

**Table 11: HSRP Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit
Groups with default timers (3s/10s) and multiple group optimization. [There are 2 primary, one for IPv4 and the other for IPv6, and 7926 secondary]	7,928
Groups with aggressive timers (1s/3s) and multiple groups optimization. [There are 2 primary, one for IPv4 and the other for IPv6, and 7926 secondary] <sup>2</sup>	7,928
Groups per interface or I/O module	Maximum 16 (Because 16 is the unique virtual MAC address limit)

<sup>2</sup> If the user has Multi-protocol configuration, user should configure appropriate COPP policies so as to avoid any control plane traffic drops.

**Table 12: VXLAN Verified Scalability Limits (Unidimensional)**

Feature	Verified Limit <sup>3</sup>
<b>IGMP snooping over VXLAN</b>	
VXLAN VLANs	1,000
VTEP peers	256
Underlay multicast groups	128
<b>VXLAN Flood and Learn</b>	
Virtual network identifiers (VNIs) or VXLAN-mapped VLANs	Not applicable
Virtual network identifiers (VNIs) or VXLAN-mapped VLANs	Not applicable
Underlay multicast groups.	Not applicable
Overlay MAC addresses	Not applicable
Remote VXLAN tunnel endpoints (VTEPs)	Not applicable
Ingress replication peers	Not applicable
Ingress replication Layer 2 VNIs	Not applicable
MAC addresses for ingress replication	Not applicable
Port VLAN translations under an interface	Not applicable

Feature	Verified Limit <sup>3</sup>
Port VLAN translations in a switch	Not applicable
Static MAC addresses pointing to a remote VTEP	Not applicable
VXLAN VLAN logical port VP count	Not applicable
VXLAN VLANs per FEX port (host interface)	Not applicable
Layer 2 routed VNIs for vPC-centralized gateway	Not applicable
IGMP groups	Not applicable
<b>VXLAN BGP eVPN</b>	
Layer 2 VNIs	2,000
Xconnect VLANs	Not applicable
SVI with Distributed Anycast Gateway; Layer 2 VNI extended	2,000
Layer 3 VNIs / VRFs	900
Underlay multicast groups	128
VTEPs	256
MAC addresses	90,000
IPv4 host routes	350,000
IPv6 host routes	48,000
Overlay IPv4 LPM routes	180,000
Overlay IPv6 LPM routes	48,000
VXLAN VLAN logical port VP count	Not applicable
VXLAN VLANs per FEX port (host interface)	Not applicable
IGMP groups	8192
<b>VXLAN BGP eVPN Ingress Replication</b>	
Layer 2 VNIs	Not applicable
Xconnect VLANs	Not applicable
SVI with Distributed Anycast Gateway; Layer 2 VNI extended	Not applicable
Layer 3 VNIs / VRFs	Not applicable
VTEPs	Not applicable

Feature	Verified Limit <sup>3</sup>
MAC addresses	Not applicable
IPv4 host routes	Not applicable
IPv6 host routes	Not applicable
Overlay IPv4 LPM routes	Not applicable
Overlay IPv6 LPM routes	Not applicable
VXLAN VLAN logical port VP count	Not applicable
VXLAN VLANs per FEX port (host interface)	Not applicable
IGMP groups	Not applicable

<sup>3</sup> For Cisco Nexus 3636C-R and Cisco Nexus 36180YC-R switches

## Verified Scalability Limits (Multidimensional)

The tables in this section list the verified scalability limits for Cisco NX-OS Release 10.3(5)M. These limits are validated with a multidimensional configuration. The values provided in these tables focus on the scalability of one particular feature at a time.

Each number is the absolute maximum currently supported by this Cisco NX-OS release for the corresponding feature. If the hardware is capable of a higher scale, future software releases might increase this verified maximum limit. Results might differ from the values listed here when trying to achieve maximum scalability with multiple features enabled.



**Attention** These numbers are not the maximum verified values if each feature is viewed in isolation. For these numbers, see the "Verified Scalability Limits" section.

**Table 13: MSDC Profile Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
Number of 100G ports	6 36 (N3K-C3636C-R)
vPC port channels	10
ISIS IPv4 /32 unicast routes	1,291
ISIS IPv6 /128 unicast routes	1,291
Multicast IPv4 SSM	10,000
VRF IPv4/IPv6	100
PIM neighbors	100



Feature	Verified Limit
IGMP snooping database entries	240
VRRP v4 and v6	1,000 vlans
Multicast SSM	10,000
HSRP v4 and v6	1,000 vlans
SVI	100 (N3K-C3636C-R)
Sub-interfaces	100 (N3K-C3636C-R)
MAC	1000 (N3K-C3636C-R)
BGP IPv4/IPv6 VLSM routes	1000 (N3K-C3636C-R)
BGP IPv4/IPv6 Unicast routes	10,000 (N3K-C3636C-R)
ECMP	16-way Upstream (N3K-C3636C-R)
SPAN sessions	1 local SPAN session (N3K-C3636C-R)

**Table 14: MPLS Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
MPLS Layer 3 VPN	3,715
VPE	3,715
PE nodes	Nil
PE routes	Nil
ACL (IPv4)	1,100
ACL (IPv6)	440
HSRP and IPv6 VIP	3.715 each for v4 and v6
vPC uRPF	Nil
Strict uRPF	Yes
VRF	3,715
SVI	3,715
Layer 3 VPN routes IP ECMP	<500
MPLS LSR ECMP	<500
VPN IPv4 routes	65,000

Feature	Verified Limit
VPN IPv6 routes	25,000
EBGP neighbors	Nil

**Table 15: Layer 2/Layer 3 TOR Boundary Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
ECMP	16-way (Upstream)
vPC port channels	44
OSPFv2 neighbors	16
OSPFv3 neighbors	16
OSPF IPv4 /32 unicast routes	45,000
OSPF IPv4 VLSM unicast routes	1,000
OSPF IPv6 /128 unicast routes	25,000
OSPF IPv6 VLSM unicast routes	1,000
BFD sessions	230
	100 MHBFD sessions (N3K-C3636C-R and N3K-C36180YC-R)
VLAN	1,250
SVI	1,000 1250 (N3K-C3636C-R)
Sub-interfaces	250 per interface and 500 across the system (N3K-C3636C-R)
VRRP IPv4 groups	1,000 VRRS / 8 VRRPv3
VRRP IPv6 groups	1,000 VRRS / 8 VRRPv3
PIM neighbors	230
IPv4 (*,G) multicast routes	300
IPv4 (S,G) multicast routes	2,320
IGMP snooping database entries	6,300
Sflow enabled interfaces	63 45 (N3K-C3636C-R)

Feature	Verified Limit
UDLD enabled interfaces	65 48 (N3K-C3636C-R)
SPAN sessions	1 local SPAN session
MVR VLANs	250
MVR receiver ports	10
MVR multicast groups	1,000
MAC	20,000 (N3K-C3636C-R)
Q-in-Q tunnel ports	26
RSTP VLANS (tunneled over L2PT)	3,960

**Table 16: Layer 2/Layer 3 Spine Boundary (for N3K-C3636C-R) Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
Number of 100G ports	36
Number of 10G ports	36 x 4 (Breakout)
ECMP	16-way (Upstream)
vPC port channels	40
OSPFv2 neighbors	100
OSPFv3 neighbors	100
OSPF IPv4 /32 unicast routes	45,000
OSPF IPv4 VLSM unicast routes	1,000
OSPF IPv6 /128 unicast routes	25,000
OSPF IPv6 VLSM unicast routes	1,000
BFD sessions	280 100 MHBFD sessions (N3K-C3636C-R and N3K-C36180YC-R)
VLAN	3,967
SVI	3,967
Sub-interfaces	250 per interface and 511 across system
VRRP IPv4 groups	1,996 VRRS / 4 VRRPv3

Feature	Verified Limit
VRRP IPv6 groups	1,996 VRRS / 4 VRRPv3
HSRP IPv4	1,743 Secondary Groups / 7 Primary Groups
HSRP IPv6	1,743 Secondary Groups / 7 Primary Groups
PIM neighbors	230
IPv4 (*,G) multicast routes	2,000
IPv4 (S,G) multicast routes	30,000
IGMP snooping database entries	6,300
sFlow enabled interfaces	45
UDLD enabled interfaces	48
SPAN sessions	1 local SPAN session
MAC	50,000

**Table 17: Segment Routing Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
LACP	26
LACP members	1 or 4
eBGP IPv6 neighbors	25
eBGP IPv4 LU neighbors	24
IPv4 (LU) routes	1,537
IPv4 (LU) paths	6,987
IPv6 routes	1,486
IPv6 paths	6,915
SR ECMP (max)	18
MPLS HW entries	6,868

**Table 18: Segment Routing (for N3K-C3636C-R) Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
VLAN	100
SVI	100

Feature	Verified Limit
MAC entries	10,000
ARP entries	70
HSRPv4, HSRPv6 VIPs	100, 100
LACP	3
LACP members	4
eBGP IPv6 neighbors	2
eBGP IPv4 neighbors	2
IPv4 (LU) routes	6,848
IPv4 (LU) paths	8,187
IPv6 routes	6,640
IPv6 paths	7,975
SR ECMP	2
MPLS HW entries	2,682

**Table 19: VXLAN Profile Verified Scalability Limits (Multidimensional)**

Feature	Verified Limit
Number of ports	16
ECMP	8-way (Upstream)
BGP neighbors	2
BGP EVPN Layer 2 VPN host routes	60,000
BGP IPv4 VLSM unicast routes or ospf	10,000
BGP IPv6 VLSM unicast routes or ospf	2,000
BFD sessions	10
PIM neighbors	10
IPv4 (*,G) multicast routes (co-existing)	4,000
IPv4 (S,G) multicast routes (co-existing)	2,000
Layer 3 VNI	100
Layer 2 VNI	400

Feature	Verified Limit
Local VTEP	1
Remote VTEPs	205
VLAN	400
SVI	100
MAC	80,000
vPC hosts	1