



B Show Commands

- [show background](#), on page 3
- [show banner exec](#), on page 4
- [show banner motd](#), on page 5
- [show bash-shell](#), on page 6
- [show bfd clients](#), on page 7
- [show bfd neighbors](#), on page 8
- [show bgp](#), on page 12
- [show bgp](#), on page 14
- [show bgp](#), on page 17
- [show bgp](#), on page 26
- [show bgp](#), on page 34
- [show bgp](#), on page 41
- [show bgp bmp server](#), on page 44
- [show bgp community](#), on page 47
- [show bgp convergence](#), on page 54
- [show bgp dampening dampened](#), on page 56
- [show bgp dampening flap-statistics](#), on page 63
- [show bgp dampening parameters](#), on page 66
- [show bgp evi](#), on page 69
- [show bgp extcommunity](#), on page 71
- [show bgp l3vpn](#), on page 79
- [show bgp large-community](#), on page 81
- [show bgp neighbors](#), on page 88
- [show bgp neighbors](#), on page 99
- [show bgp neighbors commands](#), on page 106
- [show bgp neighbors flap-statistics](#), on page 108
- [show bgp neighbors paths](#), on page 110
- [show bgp path-attribute discard](#), on page 112
- [show bgp paths](#), on page 119
- [show bgp peer-template](#), on page 120
- [show bgp peer](#), on page 124
- [show bgp prefix-list](#), on page 126
- [show bgp private attr](#), on page 133

- [show bgp private debug history, on page 134](#)
- [show bgp process, on page 135](#)
- [show bgp received-paths, on page 141](#)
- [show bgp regexp, on page 148](#)
- [show bgp segment-routing srv6, on page 155](#)
- [show bgp self-originated, on page 156](#)
- [show bgp sessions, on page 163](#)
- [show bgp statistics, on page 165](#)
- [show bgp summary, on page 166](#)
- [show bgp summary, on page 171](#)
- [show boot, on page 176](#)
- [show boot auto-copy, on page 177](#)
- [show boot auto-copy list, on page 178](#)
- [show boot current, on page 179](#)
- [show boot mode, on page 180](#)
- [show boot order, on page 181](#)
- [show boot timings, on page 182](#)
- [show boot variables, on page 183](#)
- [show buffer-drop detail, on page 184](#)
- [show buffer-latency detail, on page 185](#)

show background

```
show background [ __readonly__ [ { TABLE_jobs <pid> <user_name> <terminal> <start> <time> <script>
<args> } ] ]
```

Syntax Description

<code>show</code>	Show running system information
<code>background</code>	show background processes (started with 'source background <file>' command)
<code>__readonly__</code>	(Optional)
<code>TABLE_jobs</code>	(Optional) All background jobs
<code>pid</code>	(Optional) Process ID of the job
<code>user_name</code>	(Optional) User name of the process
<code>terminal</code>	(Optional) Terminal where job is running
<code>start</code>	(Optional) Start time of job
<code>time</code>	(Optional) Time
<code>script</code>	(Optional) Script name
<code>args</code>	(Optional) Arguments passed to script

Command Mode

- /exec

show banner exec

```
show banner exec [ __readonly__ { banner_msg <b_msg> } ]
```

Syntax Description

show	Show running system information
banner	Show current banner message
exec	Show current exec banner message
__readonly__	(Optional)
banner_msg	(Optional) The banner message
<i>b_msg</i>	(Optional) The banner message

Command Mode

- /exec

show banner motd

```
show banner motd [ __readonly__ { banner_msg <b_msg> } ]
```

Syntax Description

show	Show running system information
banner	Show current banner message
motd	Show current motd banner message
__readonly__	(Optional)
banner_msg	(Optional) The banner message
<i>b_msg</i>	(Optional) The banner message

Command Mode

- /exec

show bash-shell

```
show bash-shell [ __readonly__ { operation_status <o_status> } ]
```

Syntax Description

show	Show running system information
bash-shell	Show bash shell status
<i>__readonly__</i>	(Optional)
<i>operation_status</i>	(Optional) Bash shell status
<i>o_status</i>	(Optional) operational status of bash shell

Command Mode

- /exec

show bfd clients

```
show bfd clients [ __readonly__ <header> [ { TABLE_bfdClients <client_name> <num_sess> } ] ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
clients	bfd client list
<i>__readonly__</i>	(Optional)
<i>header</i>	(Optional) print header
TABLE_bfdClients	(Optional) BFD Client table
<i>client_name</i>	(Optional) client name
<i>num_sess</i>	(Optional) Number of sessions

Command Mode

- /exec

show bfd neighbors

```
show bfd { [ vrf { <vrf-name> | <vrf-known-name> | all } ] } { [ <ip_type> ] } neighbors { [ multihop ] | [
module <module> ] | [ interface <intf_id> ] | [ application <bfd_cli_client_names> ] | [ { src-ip <src_ip> |
src-ipv6 <src_ipv6> } ] | [ { dest-ip <dest_ip> | dest-ipv6 <dest_ipv6> } ] | [ vrf { <vrf-name> |
<vrf-known-name> | all } ] } + [ details ] [ __readonly__ TABLE_bfdNeighbor <local_disc> [ <header> ] [
<sess_type> ] [ <vrf_name> ] [ <src_ip_addr> ] [ <src_ipv6_addr> ] [ <dest_ip_addr> ] [ <dest_ipv6_addr>
] [ <remote_disc> ] [ <local_state> ] [ <remote_state> ] [ <holddown> ] [ <cur_detect_mult> ] [ <intf> ] [
<echo> ] [ <echo_tx> ] [ <local_diag> ] [ <demand> ] [ <poll> ] [ <min_tx> ] [ <min_rx> ] [ <local_multi>
] [ <detect_timer> ] [ <tx_interval> ] [ <rx_count> ] [ <rx_avg> ] [ <rx_min> ] [ <rx_max> ] [ <last_rx> ] [
<tx_count> ] [ <tx_avg> ] [ <tx_min> ] [ <tx_max> ] [ <last_tx> ] [ <app> ] [ <up_time> ] [ <up_count> ] [
<down_count> ] [ <version> ] [ <diag> ] [ <state_bit> ] [ <demand_bit> ] [ <poll_bit> ] [ <final_bit> ] [
<multiplier> ] [ <length> ] [ <my_disc> ] [ <your_disc> ] [ <min_tx_interval> ] [ <req_min_rx> ] [
<min_echo_interval> ] [ <out_str> ] [ <host_lc> ] [ <down_reason> ] [ <no_host_reason> ] [ <parent> ] [
<per_link_str> ] [ <auth> ] [ <auth_bit> ] [ <print_details> ] ]
```

Syntax Description

show	Show running system information
bfd	BFD commands
<i>ip_type</i>	(Optional) ipv4 or ipv6
neighbors	neighbors
multihop	(Optional) Display Multihop sessions only
module	(Optional) module
<i>module</i>	(Optional) module number
interface	(Optional) interface
<i>intf_id</i>	(Optional) show bfd sessions based on interface id
application	(Optional) application
<i>bfd_cli_client_names</i>	(Optional) __nil__ Clients need to register with bfd for this list
src-ip	(Optional) Source ip
src-ipv6	(Optional) Source ip
<i>src_ip</i>	(Optional) Source ip value
dest-ip	(Optional) Destination ip
dest-ipv6	(Optional) Destination ip
<i>dest_ip</i>	(Optional) Destination ip value
vrf	(Optional) Display per-VRF information

<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
details	(Optional) details
<u>__readonly__</u>	(Optional)
TABLE_bfdNeighbor	(Optional) BFD Neighbor table
<i>header</i>	(Optional) Header
<i>sess_type</i>	(Optional) Session type
<i>vrf_name</i>	(Optional) vrf name
<i>src_ip_addr</i>	(Optional) Source IPV4 address
<i>dest_ip_addr</i>	(Optional) Destination IPV4 address
<i>local_disc</i>	(Optional) Local Discriminator
<i>remote_disc</i>	(Optional) Remote Discriminator
<i>local_state</i>	(Optional) Local State
<i>remote_state</i>	(Optional) Remote State
<i>holddown</i>	(Optional) Hold Down Time
<i>cur_detect_mult</i>	(Optional) Current Detection Multiplier
<i>intf</i>	(Optional) Interface
<i>echo</i>	(Optional) Echo enabled
<i>echo_tx</i>	(Optional) Echo Tx Interval
<i>local_diag</i>	(Optional) Local Diag
<i>demand</i>	(Optional) Demand Mode
<i>poll</i>	(Optional) Poll Bit
<i>min_tx</i>	(Optional) Local Min Tx Interval
<i>min_rx</i>	(Optional) Local Min Rx Interval
<i>local_multi</i>	(Optional) Local Detection Multiplier
<i>detect_timer</i>	(Optional) Current Detection Timer
<i>tx_interval</i>	(Optional) Tx Interval
<i>rx_count</i>	(Optional) Tx Count

<i>rx_avg</i>	(Optional) Rx Interval Avg
<i>rx_min</i>	(Optional) Rx Interval Min
<i>rx_max</i>	(Optional) Rx Interval Max
<i>last_rx</i>	(Optional) Last Rx time
<i>tx_count</i>	(Optional) Tx Count
<i>tx_avg</i>	(Optional) Tx Interval Avg
<i>tx_min</i>	(Optional) Tx Interval Min
<i>tx_max</i>	(Optional) Tx Interval Max
<i>last_tx</i>	(Optional) Last Tx time
<i>app</i>	(Optional) App name
<i>up_time</i>	(Optional) Up time
<i>up_count</i>	(Optional) Up Count
<i>down_count</i>	(Optional) Down Count
<i>version</i>	(Optional) Version in Last Packet
<i>diag</i>	(Optional) diag in Last Packet
<i>state_bit</i>	(Optional) State Bit in Last Packet
<i>demand_bit</i>	(Optional) Demand Bit in Last Packet
<i>poll_bit</i>	(Optional) Poll Bit in Last Packet
<i>final_bit</i>	(Optional) Final Bit in Last Packet
<i>multiplier</i>	(Optional) Detection Multiplier in Last Packet
<i>length</i>	(Optional) Length in Last Packet
<i>my_disc</i>	(Optional) My Discriminator in Last Packet
<i>your_disc</i>	(Optional) Your Discriminator in Last Packet
<i>min_tx_interval</i>	(Optional) Min Tx Interval in Last Packet
<i>req_min_rx</i>	(Optional) Required Rx Interval in Last Packet
<i>min_echo_interval</i>	(Optional) Min Echo Interval in Last Packet
<i>out_str</i>	(Optional) No Host LC string
<i>parent</i>	(Optional) Parent Session
<i>per_link_str</i>	(Optional) Per Link string

<i>host_lc</i>	(Optional) Host LC
<i>down_reason</i>	(Optional) Session Down Reason
<i>no_host_reason</i>	(Optional) Not Hosted Reason
<i>auth</i>	(Optional) Authentication Mode
<i>auth_bit</i>	(Optional) Auth Bit in Last Packet
<i>print_details</i>	(Optional) print details

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } flap-statistics [ <ip-prefix> | <ip-addr> [ <ip-mask> ] ] | ipv6 { unicast | multicast } flap-statistics
[ <ipv6-prefix> ] | all flap-statistics } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234
} ] [ __readonly__ TABLE_vrf <vrf-name-out> [ TABLE_afi <afi> TABLE_safi <safi> <af-name> [
TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ <dampening>
<historypaths> <dampenedpaths> ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <status>
] [ <pathtype> ] [ <peer> | <ipv6peer> ] [ <flapcount> ] [ <duration> ] [ <reuse> ] [ <penalty> ] [
<suppresslimit> ] [ <reuselimit> ] [ <best> ] ] ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
flap-statistics	Display route flap statistics
<i>ip-prefix</i>	(Optional) Display flap statistics for one prefix
<i>ip-addr</i>	(Optional) Display flap statistics for one network
<i>ip-mask</i>	(Optional) Network mask
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)

<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } policy statistics { { redistribute [ { { eigrp | isis | ospf | rip } <tag> } | static | direct | amt | lisp |
hmm | am ] } | { neighbor <neighbor-id> [ default-originate | { route-map | filter-list | prefix-list } { in | out }
] } | { dampening } | { network { <ip-addr> mask <ip-mask> | <ip-prefix> } } | { aggregate-address { <ip-addr>
<ip-mask> | <ip-prefix> } { suppress-map | advertise-map } } } | vpnv4 unicast policy statistics { neighbor
<neighbor-id> [ { route-map | filter-list | prefix-list } { in | out } ] } | ipv6 { unicast | multicast } policy statistics
{ { redistribute [ { { eigrp | isis | ospfv3 | rip } <tag> } | static | direct | amt | lisp | hmm | am ] } | { neighbor
{ <neighbor-id> | <ipv6-neighbor-id> } [ default-originate | { route-map | filter-list | prefix-list } { in | out }
] } | { dampening } | { network <ipv6-prefix> } | { aggregate-address <ipv6-prefix> { suppress-map |
advertise-map } } } } [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-polstats> [ <rpm-handle-count> ] [ { TABLE_rmap <name> <action>
<seqnum> [ { TABLE_cmd <command> <comparecount> <matchcount> } ] [ <totalacceptcount> ] [
<totalrejectcount> ] } ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
policy	Display policy related information
statistics	Display Route Filter statistics
redistribute	Statistics for redistribution
isis	(Optional) ISO IS-IS
ospf	(Optional) Open Shortest Path First
ospfv3	(Optional) Open Shortest Path First v3
rip	(Optional) Routing Information Protocol
eigrp	(Optional) Enhanced Interior Gateway Protocol

static	(Optional) Static routes
direct	(Optional) Directly connected
amt	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
lisp	(Optional) LISP EID-prefixes in the non-default VRF
hmm	(Optional) HMM prefix
am	(Optional) AM routes (learned via ARP)
<i>tag</i>	(Optional) Source protocol tag
neighbor	Show neighbor specific counters
<i>neighbor-id</i>	Neighbor IPv4 address
route-map	(Optional) Neighbor route-map
prefix-list	(Optional) Neighbor prefix-list
filter-list	(Optional) Neighbor filter-list
out	(Optional) Outbound policy
in	(Optional) Inbound policy
default-originate	(Optional) Default-originate policy
dampening	Show dampening info
network	Configured IP prefix to advertise
mask	Configured mask of the IP prefix advertised
aggregate-address	Configured BGP aggregate prefixes
suppress-map	Statistics of suppress policy
advertise-map	Statistics of advertise policy
<i>ip-addr</i>	IP network advertised
<i>ip-mask</i>	Dotted 4-octet mask
<i>ip-prefix</i>	IP prefix in CIDR format
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-polstats</i>	(Optional)
<i>rpm-handle-count</i>	(Optional)
TABLE_rmap	(Optional)

<i>name</i>	(Optional)
<i>action</i>	(Optional)
<i>seqnum</i>	(Optional)
TABLE_cmd	(Optional)
<i>command</i>	(Optional)
<i>comparecount</i>	(Optional)
<i>matchcount</i>	(Optional)
<i>totalacceptcount</i>	(Optional)
<i>totalrejectcount</i>	(Optional)

Command Mode

- /exec

show bgp

```

show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { ipv4 { unicast |
multicast } | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast
} [ <ip-addr> [ <ip-mask> [ longer-prefixes ] ] [ detail ] | <ip-prefix> [ longer-prefixes ] [ detail ] | labels |
exported | imported | detail ] | { ipv6 { unicast | multicast } | vpnv6 unicast [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast } [ <ipv6-prefix> [ longer-prefixes ] [ detail ] | labels |
exported | imported | detail ] | { ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] } [
<ip-addr> [ <ip-mask> ] | <ip-prefix> | labels | mdt-group <mdt-group> ] | { ipv4 | ipv6 } unicast [
injected-routes | origin-as validity-state [ valid | invalid | not-found ] ] | link-state [ route-type <rt-type> |
<ipv4-ls-rt> | <ipv6-ls-rt> ] | l2vpn vpls [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] [ { <ip-addr>
[ <ip-mask> ] | <ip-prefix> } | { ve-id <ve-id> block-offset <ve-bs> } ] ] | ipv4 mvpn [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ join <v4src-addr> <v4grp-addr> <src-asn> | rp
<v4src-addr> <grp-v4prefix> <pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v4prefix> | sa-ad
<v4src-addr> <v4grp-addr> | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7
} [ detail ] | join [ detail ] | sa-ad [ detail ] | i-pmsi [ detail ] | { <v4src-addr> [ <v4grp-addr> ] | <v4grp-addr>
[ <v4src-addr> ] } [ route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } ] [ detail ] ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4>
| <ext-comm-rd-aa4nn2> } [ join <v6src-addr> <v6grp-addr> <src-asn> | rp <v6src-addr> <grp-v6prefix>
<pe-addr> <rp-flags> <rp-priority> <hashlen> | sa <grp-v6prefix> | sa-ad <v6src-addr> <v6grp-addr> |
route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] ] | route-type { 1 | 2 | 3 | 4 | 5 | 6 | 7 } [ detail ] | join [ detail ] |
sa-ad [ detail ] | i-pmsi [ detail ] | { <v6src-addr> [ <v6grp-addr> ] | <v6grp-addr> [ <v6src-addr> ] } [ route-type
{ 1 | 2 | 3 | 4 | 5 | 6 | 7 } ] [ detail ] ] | l2vpn evpn [ route-type <rtype> [ etid <et> ] | detail | rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } [ route-type <rtype> [ etid <et> ] | <ipv4-evpn-rt> |
<ipv6-evpn-rt> | <mac-address> ] | vni-id <vni_id> [ route-type <rtype> | detail ] | es <es-id> [ route-type
<rtype> [ etid <et> ] ] | <ipv4-evpn-rt> | <ipv6-evpn-rt> | <mac-address> ] | all [ detail ] ] [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhlldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } { { <inlabel> <outlabel> <vpn> <hold_down> } } { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrnh> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsourcenumber> [ <originalimportsourcenumber> ] ] [
<importdestscount> ] [ TABLE_importdests <importdest> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregator> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origrsrgb_len> <psid_origrsrgb_flag> <psid_origrsrgb_base>
<psid_origrsrgb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> ] [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>

```

```

} ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]

```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>ip-addr</i>	(Optional) Display one particular network from the BRIB in detail
<i>ip-mask</i>	(Optional) Mask for one particular prefix in the BRIB
<i>ip-prefix</i>	(Optional) Display one particular prefix from the BRIB in detail
longer-prefixes	(Optional) Display route and more specific routes
labels	(Optional) Display BGP labels for prefixes
exported	(Optional) Display only exported prefixes
imported	(Optional) Display only imported prefixes
injected-routes	(Optional) Display only injected prefixes
origin-as	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
validity-state	(Optional) Display validity state of origin-as for the prefix
valid	(Optional) Display only prefixes with valid origin-as
invalid	(Optional) Display only prefixes with invalid origin-as
not-found	(Optional) Display only prefixes with not-found origin-as
mdt-group	(Optional) Display prefixes with MDT group address
<i>mdt-group</i>	(Optional) MDT group address
rd	(Optional) Display information for a route distinguisher
ve-id	(Optional) VPLS VE ID
<i>ve-id</i>	(Optional) VPLS VE ID
route-type	(Optional) EVPN Route Type number
<i>rtype</i>	(Optional) EVPN route type number
1	(Optional) Inter-AS PMSI AD

2	(Optional) Intra-AS PMSI AD
3	(Optional) SPMSI AD
4	(Optional) LEAF AD
5	(Optional) Source-Active AD
6	(Optional) Shared C-Multicast
7	(Optional) Source C-Multicast
vni-id	(Optional) EVPN VNI ID number
vni_id	(Optional) EVPN VNI ID number
rt-type	(Optional) Link-State route-type
es	(Optional) Ethernet Segment
es-id	(Optional) ESID
etid	(Optional) Ethernet Tag-ID for L2VPN EVPN route
et	(Optional) Ethernet Tag-ID
ipv4-evpn-rt	(Optional) EVPN IPv4 address
ipv4-ls-rt	(Optional) Link-State NLRI with descriptor including IPv4 address
mac-address	(Optional) MAC address
block-offset	(Optional) VPLS VE Block offset
ve-bs	(Optional) VPLS VE Block offset
ext-comm-rd-aa4nn2	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
ext-comm-rd-aa2nn4	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family

vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
join	(Optional) Display Multicast Join route
detail	(Optional) Display detailed path info for routes
sa	(Optional) Display Multicast Source Active AD route
sa-ad	(Optional) Display Multicast Source Active AD route
i-pmsi	(Optional) Display Multicast Intra-AS I-PMSI route
rp	(Optional) Display Multicast Group to RP route
v4src-addr	(Optional) Source IP Address
src-asn	(Optional) Source ASN
v4grp-addr	(Optional) Group IP Address
grp-v4prefix	(Optional) Group IP prefix
pe-addr	(Optional) PE IP Address
rp-flags	(Optional) Flags
rp-priority	(Optional) RP Priority
hashlen	(Optional) Hash mask length
l	(Optional) vrf
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional)
TABLE_afi	(Optional)
afi	(Optional)
TABLE_safi	(Optional)
safi	(Optional)
af-name	(Optional)
table-version	(Optional)

<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)

TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)

<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)

<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)

<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } { route-map {
<rmap-name> | <rmap-name> } | filter-list { <fltrlist-name> | <test_pol_name> } } | community-list {
<commlist-name> | <test_pol_name> } | large-community-list { <large-commlist-name> | <test_pol_name>
} | extcommunity-list { <extcommlist-name> | <test_pol_name> } [ exact-match ] [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [ <originalimportsource> ] ] [
<importdstscount> ] [ TABLE_importdsts <importdst> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpk_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

route-map	Display routes matching the route-map
<i>rmap-name</i>	Route-map name
<i>rmap-name</i>	Known route-map name
filter-list	Display routes matching the filter-list
<i>fltrlist-name</i>	Name of filter-list
community-list	Display routes matching the community-list
<i>commlist-name</i>	Name of community-list
large-community-list	Display routes matching the large-community-list
<i>large-commlist-name</i>	Name of large-community-list
extcommunity-list	Display routes matching the extcommunity-list
<i>extcommlist-name</i>	Name of extcommunity-list
<i>test_pol_name</i>	An existing test-list policy
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families

<i>exact-match</i>	(Optional) Exact match of the communities
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)

<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)

<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappentalty</i>	(Optional)

<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)

<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origrsrgb_len</i>	(Optional)
<i>psid_origrsrgb_flag</i>	(Optional)
<i>psid_origrsrgb_base</i>	(Optional)
<i>psid_origrsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)

<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

<i>vrf-known-name</i>	(Optional) Known VRF name
nexthop	Display routes matching the nexthop
<i>ipnexthop</i>	Nexthop address
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
evpn	Display BGP information for L2VPN EVPN address family
mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)

<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)

<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)

<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)

<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>psid</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)

<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { { { ipv4 { unicast
| multicast } | vpnv4 unicast | ipv4 mdt | link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn } nexthop-database
[ <ipnexthop> ] } | { { ipv6 { unicast | multicast } | vpnv6 unicast | ipv6 mvpn } nexthop-database [
<ipv6nexthop> ] } | { all nexthop-database } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_nhvrif <nhvrf-name-out> TABLE_nhafi <nhafi>
TABLE_nhsafi <nhsafi> <af-name> <nhcriticaldelay> <nhnoncriticaldelay> [ { TABLE_nexthop {
<ipnexthop-out> | <ipv6nexthop-out> } <refcount> <igpmetric> <multipath> <igptype> <igppref> [ {
TABLE_attachedhops { <attachedhop> | <ipv6attachedhop> } <interface> [ { TABLE_labels <index> <label>
} ] } ] <attached> <local> <reachable> <labeled> <filtered> <suppressed> <resolvetime> { <ribroute> |
<ipv6ribroute> } <pendingupdate> [ <pendingtime> ] <nextadvertise> <rnhepoch> [ <pendingrnhepoch> ]
} ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
nexthop-database	Display nexthop database
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
mdt	Display BGP information for multicast distribution tree
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families

<i>ipnexthop</i>	(Optional) Nexthop address
<i>__readonly__</i>	(Optional)
TABLE_ <i>nhvrf</i>	(Optional)
<i>nhvrf-name-out</i>	(Optional)
TABLE_ <i>nhafi</i>	(Optional)
<i>nhafi</i>	(Optional)
TABLE_ <i>nhsafi</i>	(Optional)
<i>nhsafi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>nhcriticaldelay</i>	(Optional)
<i>nhnoncriticaldelay</i>	(Optional)
TABLE_ <i>nexthop</i>	(Optional)
<i>ipnexthop-out</i>	(Optional)
<i>refcount</i>	(Optional)
<i>igpmetric</i>	(Optional)
<i>multipath</i>	(Optional)
<i>igptype</i>	(Optional)
<i>igppref</i>	(Optional)
TABLE_ <i>attachedhops</i>	(Optional)
<i>attachedhop</i>	(Optional)
<i>interface</i>	(Optional)
TABLE_ <i>labels</i>	(Optional)
<i>index</i>	(Optional)
<i>label</i>	(Optional)
<i>attached</i>	(Optional)
<i>local</i>	(Optional)
<i>reachable</i>	(Optional)
<i>labeled</i>	(Optional)
<i>filtered</i>	(Optional)

<i>suppressed</i>	(Optional)
<i>resolvetime</i>	(Optional)
<i>pendingupdate</i>	(Optional)
<i>pendingtime</i>	(Optional)
<i>ribroute</i>	(Optional)
<i>nextadvertise</i>	(Optional)
<i>rnheepoch</i>	(Optional)
<i>pendingrnheepoch</i>	(Optional)

Command Mode

- /exec

<i>refresh_interval</i>	(Optional) refresh delay for bmp server
<i>stats_interval</i>	(Optional) frequency of stat updates
<i>initiation</i>	(Optional) number of initiation messages
<i>termination</i>	(Optional) number of termination messages
<i>peer_up</i>	(Optional) number of peer up messages
<i>peer_down</i>	(Optional) number of peer down messages
<i>route_monitor</i>	(Optional) number of route monitor messages
<i>route_mirror</i>	(Optional) number of route mirror messages
<i>stats</i>	(Optional) number of stats messages
<i>messages_dropped</i>	(Optional) number of dropped messages
<i>monitored_peers</i>	(Optional) number of monitored peers for the bmp server
TABLE_peer	(Optional) monitored peer for the bmp server
<i>peer_addr</i>	(Optional) ip address of the peer
<i>refresh_interval</i>	(Optional) refresh delay for the peer
<i>peer_up</i>	(Optional) number of peer up messages for the peer
<i>peer_down</i>	(Optional) number of peer down messages for the peer
<i>route_monitor</i>	(Optional) number of route monitor messages for the peer
<i>route_mirror</i>	(Optional) number of route mirror messages for the peer
<i>stats</i>	(Optional) number of stats messages for the peer
<i>messages_dropped</i>	(Optional) number of dropped messages for the peer
<i>prefixes_denied</i>	(Optional) prefixes denied for the peer
<i>dup_pfx_advmnt</i>	(Optional) dup pfx advmnt for the peer
<i>pfx_dup_wdr_count</i>	(Optional) pfx dup wdr count for the peer
<i>cluster_list_loops</i>	(Optional) cluster list loops for the peer
<i>as_path_loops</i>	(Optional) as path loops for the peer
<i>as_confed_loops</i>	(Optional) as confed loops for the peer
<i>invalid_originator</i>	(Optional) invalid originator for the peer
<i>adj_rib_in</i>	(Optional) adj-rib-in for the peer
<i>loc-rib</i>	(Optional) loc-rib for the peer

Command Mode

- /exec

show bgp community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } community {
<regexp-str> | { <comm-id> | <wellknown-id> } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } ] [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } } { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> } [ <importsource> [ <originalimportsource> ] ] [
<importdestscount> ] [ TABLE_importdests <importdest> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenaalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher

<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
community	Display routes matching the BGP communities
<i>regexp-str</i>	Regular expression to match the communities
<i>comm-id</i>	BGP community value
<i>wellknown-id</i>	BGP wellknown community
exact-match	(Optional) Exact match of the communities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)

<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)

<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenaity</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)

<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)

<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp convergence

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFs_012345678901234 } ] convergence [ detail
] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFs_012345678901234 } ] [ __readonly__ <starttime>
<configdonetime> <juststarted> [ <initwaittime> ] [ <rpkiirsteodrcvd> ] [ <ldpconverged> ] [
<ulibconvergencesent> ] [ TABLE_vrf <vrf-name-out> <bestpathtimeout> <configuredtimeout> <updatedelay>
[ <firstpeerup> ] <timerrunning> [ <timerexpires> ] [ TABLE_afi <afi> TABLE_safi <safi> <af-name>
<total_configured_peers> <total_capable_peers> <firstbestpathsignalled> [ <firstbestpathsignalledtime> ]
<firstbestpathdone> [ <firstbestpathdonetime> [ <lastbestpathsignalledtime> <lastbestpathdonetime> ] ] [
<ribliconvergencesent> ] [ <importtimerrunning> ] [ <importtimerexpires> ] [ { TABLE_rcvdpeers [ <peer>
] [ <ipv6peer> ] [ <signalledtimepeer> ] [ <interface-parent> } ] [ { TABLE_notrcvdpeers [ <notpeer> ] [
<notipv6peer> ] [ <nokeepalive> ] [ <notsignalledtime> } ] ] ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
convergence	Display information about convergence
detail	(Optional) Display detailed information about convergence
__readonly__	(Optional)
starttime	(Optional)
configdonetime	(Optional)
juststarted	(Optional)
initwaittime	(Optional)
rpkiirsteodrcvd	(Optional)
ldpconverged	(Optional)
ulibconvergencesent	(Optional)
TABLE_vrf	(Optional)
total_configured_peers	(Optional)
total_capable_peers	(Optional)
vrf-name-out	(Optional)
bestpathtimeout	(Optional)

<i>configuredtimeout</i>	(Optional)
<i>updatedelay</i>	(Optional)
<i>firstpeerup</i>	(Optional)
<i>timerrunning</i>	(Optional)
<i>timerexpires</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>firstbestpathsignalled</i>	(Optional)
<i>firstbestpathsignalledtime</i>	(Optional)
<i>firstbestpathdone</i>	(Optional)
<i>firstbestpathdonetime</i>	(Optional)
<i>lastbestpathsignalledtime</i>	(Optional)
<i>lastbestpathdonetime</i>	(Optional)
<i>ribribconvergencesent</i>	(Optional)
<i>importtimerrunning</i>	(Optional)
<i>importtimerexpires</i>	(Optional)
TABLE_rcvdpeers	(Optional)
<i>peer</i>	(Optional)
<i>signalledtimepeer</i>	(Optional)
<i>interface-parent</i>	(Optional)
TABLE_notrcvdpeers	(Optional)
<i>notpeer</i>	(Optional)
<i>nokeepalive</i>	(Optional)
<i>notsignalledtime</i>	(Optional)

Command Mode

- /exec

show bgp dampening dampened

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening {
dampened-paths [ regexp <regexp-str> ] | history-paths [ regexp <regexp-str> ] } [ vrf { <vrf-name> |
<vrf-known-name> | ALL_VRFS_012345678901234 } ] [ _readonly_ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> } [ <importsource> [ <originalimportsource> ] ] [
<importdstscount> ] [ TABLE_importdsts <importdst> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <tpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampened-paths	Display all dampened paths

history-paths	Display all history paths
dampening	Display dampening info
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
regexp	(Optional) Display routes matching the AS path regular expression
<i>regexp-str</i>	(Optional) Regular expression to match the AS paths
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)

<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)

<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)

<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)

<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp dampening flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening
flap-statistics [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> [ TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_yniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] ] [ <dampening> <historypaths>
<dampenedpaths> ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <status> ] [ <pathtype>
] [ <peer> | <ipv6peer> ] [ <flapcount> ] [ <duration> ] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [
<reuselimit> ] [ <best> ] ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
dampening	Display dampening info
flap-statistics	Display flap statistics for routes
rd	(Optional) Display information for a route distinguisher
ext-comm-rd-aa4nn2	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
ext-comm-rd-aa2nn4	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpv4	Display BGP information for VPNv4 address family
vpv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family

link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional)
TABLE_afi	(Optional)
afi	(Optional)
TABLE_safi	(Optional)
safi	(Optional)
af-name	(Optional)
TABLE_rd	(Optional)
rd_val	(Optional)
rd_vrf	(Optional)
rd_vniid	(Optional)
rd-esi-desc	(Optional)
rd-esi	(Optional)
rd-seg-id	(Optional)
dampening	(Optional)
historypaths	(Optional)
dampenedpaths	(Optional)
TABLE_prefix	(Optional)
ipprefix	(Optional)
nonipprefix	(Optional)
status	(Optional)
best	(Optional)

<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp dampening parameters

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } dampening
parameters [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> ] [
<rd_vrf> ] [ <rd_vniid> ] [ <rpmname> ] [ TABLE_rpm <rpmindex> <rpmdamphalflife> <rpm dampsuppress>
<rpm dampreuse> <rpm dampsuppress time> <rpm dampmaxpenalty> ] [ <dampconfigured> <damp half life>
<damp suppress> <damp reuse> <damp suppress time> <damp max penalty> ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
dampening	Display dampening info
parameters	Display dampening parameters
rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family

l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional) VRF RD
<i>rd_vniid</i>	(Optional)
TABLE_rpm	(Optional)
<i>rpmname</i>	(Optional)
<i>rpmindex</i>	(Optional)
<i>rpmdamphalflife</i>	(Optional)
<i>rpmdampsuppress</i>	(Optional)
<i>rpmdampreuse</i>	(Optional)
<i>rpmdampsuppresstime</i>	(Optional)
<i>rpmdampmaxpenalty</i>	(Optional)
<i>dampconfigured</i>	(Optional)
<i>damphalflife</i>	(Optional)
<i>dampsuppress</i>	(Optional)
<i>dampreuse</i>	(Optional)

<i>dampsuppresstime</i>	(Optional)
<i>dampmaxpenalty</i>	(Optional)

Command Mode

- /exec

show bgp evi

```
show bgp evi [ <evi-id> ] [ __readonly__ [ TABLE_ctx <eid> <rd> [ <secondaryrd> ] <numlocalprefixes>
<numtotalprefixes> <created> <lastoperup> <lastoperdown> <enabled> [ <associatedvrf> ] [
TABLE_activeexportrts <exportrt> ] [ TABLE_activeimportrts <importrt> ] [ TABLE_evpnactiveexportrts
<evpnexportrt> ] [ TABLE_evpnactiveimportrts <evpnimportrt> ] [ TABLE_mvnpactiveexportrts
<mvpnexportrt> ] [ TABLE_mvnpactiveimportrts <mvpnimportrt> ] [ TABLE_activeexportrtsv6 <exportrtv6>
] [ TABLE_activeimportrtsv6 <importrtv6> ] [ TABLE_evpnactiveexportrtsv6 <evpnexportrtv6> ] [
TABLE_evpnactiveimportrtsv6 <evpnimportrtv6> ] [ TABLE_mvnpactiveexportrtsv6 <mvpnexportrtv6> ]
[ TABLE_mvnpactiveimportrtsv6 <mvpnimportrtv6> ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
evi	Display information about EVI database
<i>evi-id</i>	(Optional) EVI Id
<i>__readonly__</i>	(Optional)
<i>TABLE_ctx</i>	(Optional)
<i>eid</i>	(Optional)
<i>rd</i>	(Optional)
<i>secondaryrd</i>	(Optional)
<i>numlocalprefixes</i>	(Optional)
<i>numtotalprefixes</i>	(Optional)
<i>created</i>	(Optional)
<i>lastoperup</i>	(Optional)
<i>lastoperdown</i>	(Optional)
<i>enabled</i>	(Optional)
<i>associatedvrf</i>	(Optional)
<i>TABLE_activeexportrts</i>	(Optional)
<i>TABLE_activeimportrts</i>	(Optional)
<i>TABLE_evpnactiveexportrts</i>	(Optional)
<i>TABLE_evpnactiveimportrts</i>	(Optional)
<i>TABLE_mvnpactiveexportrts</i>	(Optional)

TABLE_mvpnactiveimportrts	(Optional)
TABLE_activeexportrtsv6	(Optional)
TABLE_activeimportrtsv6	(Optional)
TABLE_evpnactiveexportrtsv6	(Optional)
TABLE_evpnactiveimportrtsv6	(Optional)
TABLE_mvpnactiveexportrtsv6	(Optional)
TABLE_mvpnactiveimportrtsv6	(Optional)
<i>importrt</i>	(Optional)
<i>exportrt</i>	(Optional)
<i>evpnimportrt</i>	(Optional)
<i>evpnexportrt</i>	(Optional)
<i>mvpnimportrt</i>	(Optional)
<i>mvpnexportrt</i>	(Optional)
<i>importrtv6</i>	(Optional)
<i>exportrtv6</i>	(Optional)
<i>evpnimportrtv6</i>	(Optional)
<i>evpnexportrtv6</i>	(Optional)
<i>mvpnimportrtv6</i>	(Optional)
<i>mvpnexportrtv6</i>	(Optional)

Command Mode

- /exec

show bgp extcommunity

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpnv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpnv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } extcommunity
{ <regex-str> | { 4byteas-generic { transitive <ext-comm-gen-trans> | non-transitive
<ext-comm-gen-nontrans> } } + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf<vrf-name-out> TABLE_afi<afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [
<rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [
<prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync>
<locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <srv6-local-sid> ] [
<locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path<pathnr> { { <status> <best> <type> [
<origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { {
<inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] }
} } | { [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted> <pathstaled>
<pathhistory> <pathvermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [ <originalimportsource> ] ] [
<importdestscount> ] [ TABLE_importdests<importdest> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community<community> } ] [ { TABLE_largecommunity<largecommunity>
} ] [ { TABLE_extcommunity<extcommunity> } ] [ <originatorid> { TABLE_clusterlist<clusterlist> } ] [
<flappenaalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_orsgrgb_len> <psid_orsgrgb_flag> <psid_orsgrgb_base>
<psid_orsgrgb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmssi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list<path_attr_list> [ TABLE_attr<attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val<attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist<attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto<advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name

rd	(Optional) Display information for a route distinguisher
<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
labeled-unicast	Display BGP information for labeled-unicast address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
extcommunity	Display routes matching the BGP extcommunities
4byteas-generic	Generic extended community
<i>regexp-str</i>	Regular expression to match the extcommunities
transitive	Transitive extcommunity
non-transitive	Non-Transitive extcommunity
<i>ext-comm-gen-trans</i>	Extcommunity number aa4:nn format
<i>ext-comm-gen-nontrans</i>	Extcommunity number aa4:nn format
exact-match	(Optional) Exact match of the extcommunities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)

<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)

<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)

<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)

<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)

<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)

<i>rpki_origin_as_validity</i>	(Optional)
--------------------------------	------------

Command Mode

- /exec

show bgp l3vpn

```
show bgp l3vpn [ detail ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [
__readonly__ TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-rd> ] [ <vrf-state> ] [ <vrf-state-rsn> ] [
<vrf-pending-rd> ] [ { TABLE_af <af-id> [ <af-name> ] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [
<af-num-peers> ] [ <af-num-active-peers> ] [ <af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ]
[ <af-peer-aggregates> ] [ <af-export-rmap> ] [ <af-import-rmap> ] [ <af-retain-rt> ] [ TABLE_export_rt
<export-rt> ] [ TABLE_import_rt <import-rt> ] [ TABLE_evpn_export_rt <evpn-export-rt> ] [
TABLE_evpn_import_rt <evpn-import-rt> ] [ TABLE_mvpn_export_rt <mvpn-export-rt> ] [
TABLE_mvpn_import_rt <mvpn-import-rt> ] [ <af-label-mode> ] [ <af-aggregate-label> } } ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
l3vpn	BGP l3vpn information
vrf	(Optional) Virtual Router Context
detail	(Optional) Detailed information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason

<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route-target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route-target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route-target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route-target
TABLE_mvpn_export_rt	(Optional)
<i>mvpn-export-rt</i>	(Optional) Export MVPN route-target
TABLE_mvpn_import_rt	(Optional)
<i>mvpn-import-rt</i>	(Optional) Import MVPN route-target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label

Command Mode

- /exec

show bgp large-community

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } large-community
{ <regex-str> | { <large-comm-xyyzz> + [ exact-match ] } } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ _readonly_ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [
<rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [
<prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync>
<locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <srv6-local-sid> ] [
<locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> [
<origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { {
<inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] }
} } | { [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted> <pathstaled>
<pathhistory> <pathvermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [ <originalimportsource> ] ] [
<importdestscount> ] [ TABLE_importdests <importdest> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregators> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenaalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_orsgrgb_len> <psid_orsgrgb_flag> <psid_orsgrgb_base>
<psid_orsgrgb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
rd	(Optional) Display information for a route distinguisher

<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
labeled-unicast	Display BGP information for labeled-unicast address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
large-community	Display routes matching the BGP large communities
<i>regexp-str</i>	Regular expression to match the large communities
<i>large-comm-xyyyzz</i>	Large Community value in xx:yy:zz format
exact-match	(Optional) Exact match of the large communities
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)

<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)

TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)

<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)

<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)

<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp neighbors

```

show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast |
link-state | l2vpn vpls | l2vpn evpn | ipv4 mvpn | ipv6 mvpn | ipv4 labeled-unicast } neighbors [ { <neighbor-id>
| <ipv6-neighbor-id> | <neighbor-prefix-id> | <ipv6-neighbor-prefix-id> | <neighbor-interface> } ] [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ TABLE_neighbor
{ <neighbor> | <ipv6neighbor> | <templatepeer> | <ipv4prefixneighbor> | <ipv6prefixneighbor> |
<interfaceneighbor> } [ <remoteas> ] [ <localas> ] <link> [ <peertype> ] [ <index> ] [ { TABLE_conf-filter
<discard-attr> } ] [ { TABLE_filter <in-attr-type> <no-discard-attr> <dfilter-type> } ] [ { TABLE_conf-wfilter
<withdrawn-attr> } ] [ { TABLE_wfilter <in-wattr-type> <no-withdrawn-attr> <wfilter-type> } ] [ TABLE_peer
<peer> ] [ <maxprefixpeers> ] [ <configpeer> ] [ <inherit-template> ] [ <inherit-session-template> ] [ {
<prefix-parent> | <ipv6prefix-parent> | <interface-parent> } ] [ <description> ] [ <version> <remote-id>
<prevstate> <internalvpnclient> <state> <up> <vrf> [ <elapsedtime> ] [ <restarttime> ] ] [ <sourcecif> ] [
<updatesrc> ] [ <updatesrcname> ] [ <connectedif> ] [ <connectedcheck> ] [ <lowmemexempt> ] [ <bfd> ]
[ <bfdsessiontype> ] [ <bfdmintxinterval> ] [ <bfdminrxinterval> ] [ <bfdmultiplier> ] [ <bfdauthenticationtype>
] [ <ttlsecurity> ] [ <ttllimit> ] [ <dscp> ] [ <password> ] [ <passiveonly> ] [ <activepeers> <closingpeers>
<maxconcurrentpeers> ] [ <allocatedpeers> ] [ <totalpeersaccepted> ] [ <localas-inactive> ] <remove-privateas>
[ <gshut-activate> ] [ <gshut-map> ] { { [ <lastread> ] <holdtime> <keepalivetime> [ <lastwrite> ] [
<keepalive> ] <msgrecvd> <notificationsrcvd> <rcvbufbytesinq> <msgsent> <notificationssent>
<sentbytesoutstanding> <sentbytespacked> <enhancederr> <discardatrs> <connsestablished> <connsdropped>
[ <connattempts> ] [ <lastupdec> ] [ <lastupsent> ] { { [ <peerresetime> ] <peerresetreason> <errlenrcvd>
<errvalrcvd> <rstmajrcvd> <rstmincvd> [ <resetime> ] <resetreason> <errlensnt> <errvalsnt> <rstmajsent>
<rstminsnt> } | { [ <resetime> ] <resetreason> <errlensnt> <errvalsnt> <rstmajsent> <rstminsnt> [
<peerresetime> ] <peerresetreason> <errlenrcvd> <errvalrcvd> <rstmajrcvd> <rstmincvd> } } [
<capsnegotiated> <capmpadadvertised> [ <caprefreshadvertised> <capgrdynamicadvertised> ] [ <capmprecvd>
<caprefreshrcvd> <capgrdynamicrecvd> ] [ <capolddynamicadvertised> <capolddynamicrecvd>
<caprradvertised> <caprrrecvd> <capolddrradvertised> <capolddrrrecvd> <capas4advertised> <capas4recvd>
] [ { TABLE_af <af-afi> TABLE_saf <af-safi> <af-advertised> <af-recvd> <af-name> } ] [ <capgradvertised>
<capgrrecvd> ] [ { TABLE_graf <gr-afi> TABLE_grsaf <gr-safi> <gr-af-name> <gr-adv> <gr-recvd> <gr-fwd>
} ] [ <grrestarttime> <grstaletime> ] [ <grrecvdrestarttime> ] [ [ { TABLE_addpathscapaf <addpathscap-afi>
TABLE_addpathscapsaf <addpathscap-safi> <addpathscap-af-name> <addpathssendcap-adv>
<addpathsrecvcap-adv> <addpathssendcap-recv> <addpathsrecvcap-recv> } ] [ <capaddpathsadvertised>
<capaddpathsrecvd> ] ] [ <capextendednhadvertised> <capextendednhrecvd> ] [ { TABLE_capextendednhaf
<capextendednh-afi> TABLE_capextendednhsaf <capextendednh-safi> <capextendednh-af-name> } ] ] ] |
{ [ <configholdtime> <configkeepalivetime> ] } ] [ <epe> ] [ <epe-adj-sids> ] [ <epe-peer-rpc-set> ] [
<epe-peer-sid> ] [ <epe-peer-set-name> ] [ <epe-peer-set-rpc-set> ] [ <epe-peer-set-sid> ] [ { TABLE_epe-adj
{ { <epe-adj-ip-local> <epe-adj-ip-remote> } | { <epe-adj-ipv6-local> <epe-adj-ipv6-remote> } } ] [
<epe-adj-ifindex> <epe-adj-rpc-set> <epe-adj-sid> } ] ] [ <grstate> <grexpiry> ] [ <firstkeepalive> ] [
<openssent> <opensrecvd> <updatesent> <updatesrecvd> <keepalivesent> <keepaliverecvd> <rtrefreshsent>
<rtrefreshrecvd> <capabilitiesent> <capabilitiesrecvd> <bytesent> <bytesrecvd> ] [ TABLE_peraf <per-afi>
TABLE_persaf <per-safi> <per-af-name> [ <tableversion> ] [ <neighbortableversion> ] [ <pfxrecvd> ] [
<pathsrecvd> ] [ <pfxbytes> ] [ <pfxtreataswithdrawn> ] [ <pfxsent> ] [ <pathssent> ] [ <conditionmap>
<advertisemap> <advertisemapstatus> ] <insoftreconfigallowed> [ <insoftreconfigallowedalways> ] [
<sendcommunity> ] [ <sendextcommunity> ] [ { <localnexthop> | <ipv6localnexthop> } ] [ <thirdpartynexthop>
] [ <maxpfx> ] [ <maxpfx_threshold> ] [ <soo> ] [ <weight> ] [ <allowasin> ] [ <asoverride>
<peerascheckdisabled> [ <vplssignalingprotocol> ] [ { TABLE_inpolicy <inpolicynr> <inpolicytype>
<inpolicyname> [ <inpolicyhandle> } ] ] [ { TABLE_outpolicy <outpolicynr> <outpolicytype>
<outpolicyname> [ <outpolicyhandle> } ] ] <rrconfigured> <defaultoriginate> [ <defaultoriginatormap> ] [
<defaultsent> ] [ <grpathssaved> ] [ <firstoorrecvd> ] [ <firsteortime> ] [ <pathsflushed> ] [ <lastoorrecvtime>

```



```

]] [<lasteorsenttime> ] [<firstconvgttime> ] [<pfxsentfirsteor> ] [<unsuppress-map> ] [ {
TABLE_policy_template <preference> <inherit-policy-template> } ] ] [ [ <passivefd> ] [ { <localaddr> |
<ipv6localaddr> } <localport> { <remoteaddr> | <ipv6remoteaddr> } <remoteport> <fd> ] ] ] ]

```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	(Optional) Display one particular BGP neighbor
<i>neighbor-prefix-id</i>	(Optional) Display details for a prefix peering
<i>neighbor-interface</i>	(Optional) Display details for BGP interface peering
ipv4	Display BGP information for IPv4 address family
vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor</i>	(Optional)
<i>templatepeer</i>	(Optional)

<i>ipv4prefixneighbor</i>	(Optional)
<i>interfaceneighbor</i>	(Optional)
<i>remoteas</i>	(Optional)
<i>localas</i>	(Optional)
<i>link</i>	(Optional)
<i>index</i>	(Optional)
TABLE_conf-filter	(Optional)
<i>discard-attr</i>	(Optional) configured attributes those need to be discarded
TABLE_filter	(Optional)
<i>in-attr-type</i>	(Optional) matching discarded attribute
<i>no-discard-attr</i>	(Optional) number of matching attributes those are discarded
<i>dfilter-type</i>	(Optional) filter type in or out
TABLE_conf-wfilter	(Optional)
<i>withdrawn-attr</i>	(Optional) configured attributes those need to be withdrawn
TABLE_wfilter	(Optional)
<i>in-wattr-type</i>	(Optional) matching withdrawn attribute
<i>no-withdrawn-attr</i>	(Optional) number of matching attributes those are withdrawn
<i>wfilter-type</i>	(Optional) filter type in or out
TABLE_peer	(Optional)
<i>peer</i>	(Optional)
<i>maxprefixpeers</i>	(Optional)
<i>configpeer</i>	(Optional)
<i>inherit-template</i>	(Optional)
<i>inherit-session-template</i>	(Optional)
<i>prefix-parent</i>	(Optional)
<i>interface-parent</i>	(Optional)
<i>description</i>	(Optional)
<i>version</i>	(Optional)
<i>remote-id</i>	(Optional)

<i>state</i>	(Optional)
<i>prevstate</i>	(Optional)
<i>internalvpnclient</i>	(Optional)
<i>up</i>	(Optional)
<i>elapsedtime</i>	(Optional)
<i>restarttime</i>	(Optional)
<i>peertype</i>	(Optional)
<i>sourceif</i>	(Optional)
<i>updatesrc</i>	(Optional)
<i>updatesrcname</i>	(Optional)
<i>connectedif</i>	(Optional)
<i>connectedcheck</i>	(Optional)
<i>lowmemexempt</i>	(Optional)
<i>bfd</i>	(Optional)
<i>bfdsessiontype</i>	(Optional)
<i>bfdmintxinterval</i>	(Optional)
<i>bfdminrxinterval</i>	(Optional)
<i>bfdmultiplier</i>	(Optional)
<i>bfdauthenticationtype</i>	(Optional)
<i>ttlsecurity</i>	(Optional)
<i>ttllimit</i>	(Optional)
<i>dscp</i>	(Optional)
<i>localas-inactive</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>activepeers</i>	(Optional)
<i>closingpeers</i>	(Optional)
<i>maxconcurrentpeers</i>	(Optional)
<i>allocatedpeers</i>	(Optional)
<i>totalpeersaccepted</i>	(Optional)

<i>password</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>gshut-activate</i>	(Optional)
<i>gshut-map</i>	(Optional)
<i>lastread</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalivetime</i>	(Optional)
<i>lastwrite</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>notificationsrcvd</i>	(Optional)
<i>recvbufbytesinq</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>notificationssent</i>	(Optional)
<i>sentbytesoutstanding</i>	(Optional)
<i>sentbytespacked</i>	(Optional)
<i>enhancederr</i>	(Optional)
<i>discardattrs</i>	(Optional)
<i>connsestablished</i>	(Optional)
<i>connsdropped</i>	(Optional)
<i>connattempts</i>	(Optional)
<i>lastupdrecd</i>	(Optional)
<i>lastupdsent</i>	(Optional)
<i>peerresettime</i>	(Optional)
<i>peerresetreason</i>	(Optional)
<i>errlenrcvd</i>	(Optional)
<i>errvalrcvd</i>	(Optional)
<i>rstmajrcvd</i>	(Optional)
<i>rstminrcvd</i>	(Optional)

<i>errlensnt</i>	(Optional)
<i>errvalsnt</i>	(Optional)
<i>rstmajsnst</i>	(Optional)
<i>rstminsnt</i>	(Optional)
<i>resettime</i>	(Optional)
<i>resetreason</i>	(Optional)
<i>vrf</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
<i>grstate</i>	(Optional)
<i>gexpiry</i>	(Optional)
<i>firstkeepalive</i>	(Optional)
<i>epe</i>	(Optional)
<i>epe-adj-sids</i>	(Optional)
<i>epe-peer-rpc-set</i>	(Optional)
<i>epe-peer-sid</i>	(Optional)
<i>epe-peer-set-name</i>	(Optional)
<i>epe-peer-set-rpc-set</i>	(Optional)
<i>epe-peer-set-sid</i>	(Optional)
TABLE_ <i>epe-adj</i>	(Optional)
<i>epe-adj-ip-local</i>	(Optional)
<i>epe-adj-ip-remote</i>	(Optional)
<i>epe-adj-ifindex</i>	(Optional)
<i>epe-adj-rpc-set</i>	(Optional)
<i>epe-adj-sid</i>	(Optional)
<i>openssent</i>	(Optional)
<i>opensrecvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updatesrecvd</i>	(Optional)

<i>keepalivesent</i>	(Optional)
<i>keepaliverecvd</i>	(Optional)
<i>rtrefreshsent</i>	(Optional)
<i>rtrefreshrecvd</i>	(Optional)
<i>capabilitiesent</i>	(Optional)
<i>capabilitiesrecvd</i>	(Optional)
<i>bytessent</i>	(Optional)
<i>bytesrecvd</i>	(Optional)
<i>fd</i>	(Optional)
<i>passivefd</i>	(Optional)
<i>localaddr</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteaddr</i>	(Optional)
<i>remoteport</i>	(Optional)
<i>capsnegotiated</i>	(Optional)
<i>capmpadvertised</i>	(Optional)
<i>capgrdynamicadvertised</i>	(Optional)
<i>capaddpathsadvertised</i>	(Optional)
<i>caprefreshadvertised</i>	(Optional)
<i>capmprecvd</i>	(Optional)
<i>capgrdynamicrecvd</i>	(Optional)
<i>capaddpathsrecvd</i>	(Optional)
<i>caprefreshrecvd</i>	(Optional)
<i>capolddynamicadvertised</i>	(Optional)
<i>capolddynamicrecvd</i>	(Optional)
<i>caprradvertised</i>	(Optional)
<i>caprrrecvd</i>	(Optional)
<i>capoldrradvertised</i>	(Optional)
<i>capoldrrrecvd</i>	(Optional)

<i>capas4advertised</i>	(Optional)
<i>capas4recvd</i>	(Optional)
TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-advertised</i>	(Optional)
<i>af-recvd</i>	(Optional)
<i>af-name</i>	(Optional)
<i>capgradadvertised</i>	(Optional)
<i>capgrrecvd</i>	(Optional)
TABLE_graf	(Optional)
<i>gr-afi</i>	(Optional)
TABLE_grsaf	(Optional)
<i>gr-safi</i>	(Optional)
<i>gr-af-name</i>	(Optional)
<i>gr-adv</i>	(Optional)
<i>gr-recv</i>	(Optional)
<i>gr-fwd</i>	(Optional)
<i>grrestarttime</i>	(Optional)
<i>grstaletime</i>	(Optional)
<i>grrecvdrestarttime</i>	(Optional)
TABLE_addpathscapaf	(Optional)
<i>addpathscap-afi</i>	(Optional)
TABLE_addpathscapsaf	(Optional)
<i>addpathscap-safi</i>	(Optional)
<i>addpathscap-af-name</i>	(Optional)
<i>addpathssendcap-adv</i>	(Optional)
<i>addpathsrecvcap-adv</i>	(Optional)

<i>addpathssendcap-recv</i>	(Optional)
<i>addpathsrecvcap-recv</i>	(Optional)
<i>capextendednhadvertised</i>	(Optional)
<i>capextendednhrecvd</i>	(Optional)
TABLE_capextendednhaf	(Optional)
<i>capextendednh-afi</i>	(Optional)
TABLE_capextendednhsaf	(Optional)
<i>capextendednh-safi</i>	(Optional)
<i>capextendednh-af-name</i>	(Optional)
TABLE_peraf	(Optional)
<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)
<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pfxrecvd</i>	(Optional)
<i>pathsrecvd</i>	(Optional)
<i>pfxbytes</i>	(Optional)
<i>pfxtreataswithdrawn</i>	(Optional)
<i>pfxsent</i>	(Optional)
<i>pathsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)

<i>maxpfx</i>	(Optional)
<i>maxpfx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
TABLE_inpolicy	(Optional)
<i>inpolicynr</i>	(Optional)
<i>inpolicytype</i>	(Optional)
<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
TABLE_outpolicy	(Optional)
<i>outpolicynr</i>	(Optional)
<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)
<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatemap</i>	(Optional)
<i>defaultsent</i>	(Optional)
<i>grpathssaved</i>	(Optional)
<i>firsteorrecvd</i>	(Optional)
<i>firsteortime</i>	(Optional)
<i>pathsflushed</i>	(Optional)
<i>lasteorrecvtime</i>	(Optional)
<i>lasteorsenttime</i>	(Optional)
<i>firstconvgtime</i>	(Optional)
<i>pfxsentfirsteor</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)

<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vplssignalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)

Command Mode

- /exec

show bgp neighbors

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | ipv4
labeled-unicast | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } { routes [ advertised | received
| dampened ] | advertised-routes | received-routes } [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [
<rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [
<prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync>
<locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <srv6-local-sid> ] [
<locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> [
<origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { { <ipnexthop> | <ipv6nexthop> } } {
<inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] }
} } | { [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted> <pathstaled>
<pathhistory> <pathvermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [ <originalimportsource> ] ] [
<importdestscount> ] [ TABLE_importdests <importdest> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflaps> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> } } } ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family

vpn4	Display BGP information for VPNv4 address family
vpn6	Display BGP information for VPNv6 address family
labeled-unicast	Display BGP information for labeled-unicast address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
routes	Display all routes advertised/received to/from peer
advertised	(Optional) Display all routes advertised to this peer
received	(Optional) Display all routes received from this peer
advertised-routes	Display all the routes advertised to this peer
received-routes	Display all the routes received from this peer
dampened	(Optional) Display all dampened routes received from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional)
TABLE_afi	(Optional)
afi	(Optional)
TABLE_safi	(Optional)
safi	(Optional)
af-name	(Optional)
table-version	(Optional)
router-id	(Optional)
TABLE_rd	(Optional)
rd_val	(Optional)
rd_vrf	(Optional)
rd_vniid	(Optional)

<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)

<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)

<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)

<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)

<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp neighbors commands

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] } { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpv4 unicast | vpv6 unicast | l2vpn evpn } neighbors {
<neighbor-id> | <ipv6-neighbor-id> } commands [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ [ { TABLE_sesscmd <sessioncmd> <sessioncmdstatus>
[ <sessioncmdtemplate> ] } ] [ TABLE_af <af-afi> TABLE_saf <af-safi> <af-name> [ { TABLE_polcmd
<polycycmd> <polycycmdstatus> [ <polycycmdtemplate> ] } ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
neighbors	Display all configured BGP neighbors
commands	Display details on commands
<i>__readonly__</i>	(Optional)
<i>TABLE_sesscmd</i>	(Optional)
<i>sessioncmd</i>	(Optional)
<i>sessioncmdstatus</i>	(Optional)
<i>sessioncmdtemplate</i>	(Optional)

TABLE_af	(Optional)
<i>af-afi</i>	(Optional)
TABLE_saf	(Optional)
<i>af-safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_polcmd	(Optional)
<i>polycmd</i>	(Optional)
<i>polycmdstatus</i>	(Optional)
<i>polycmdtemplate</i>	(Optional)

Command Mode

- /exec

show bgp neighbors flap-statistics

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } neighbors { <neighbor-id> | <ipv6-neighbor-id> } flap-statistics
[ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf
<vrf-name-out> [ TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ <dampening> <historypaths> <dampenedpaths> ] [
TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <status> ] [ <pathtype> ] [ <peer> | <ipv6peer>
] [ <flapcount> ] [ <duration> ] [ <reuse> ] [ <penalty> ] [ <suppresslimit> ] [ <reuselimit> ] [ <best> ] ] ]
]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
all	Display BGP information for all address families
flap-statistics	Display flap statistics for routes received from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)

TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>status</i>	(Optional)
<i>best</i>	(Optional)
<i>pathtype</i>	(Optional)
<i>peer</i>	(Optional)
<i>flapcount</i>	(Optional)
<i>duration</i>	(Optional)
<i>reuse</i>	(Optional)
<i>penalty</i>	(Optional)
<i>suppresslimit</i>	(Optional)
<i>reuselimit</i>	(Optional)

Command Mode

- /exec

show bgp neighbors paths

```
show bgp { { [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] } { ipv4 { unicast
| multicast } | ipv6 { unicast | multicast } | all } } | vpnv4 unicast | vpnv6 unicast | ipv6 labeled-unicast | ipv4
labeled-unicast | link-state | l2vpn evpn } neighbors { <neighbor-id> | <ipv6-neighbor-id> } paths [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf
<vrf-name-out> TABLE_afi <afi> TABLE_safi <safi> <af-name> [ TABLE_id <id> <hashvalue> <refcount>
<metric> <aspath> ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
neighbors	Display all configured BGP neighbors
<i>neighbor-id</i>	Display one particular BGP neighbor
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
all	Display BGP information for all address families
l2vpn	Display BGP information for L2VPN address family
evpn	Display BGP information for L2VPN EVPN address family
paths	Display AS paths learned from this peer
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)

TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)

Command Mode

- /exec

<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
evpn	Display BGP information for L2VPN EVPN address family
mvpn	Display BGP information for MVPN address family
labeled-unicast	Display BGP information for labeled-unicast address family
path-attribute	path attribute on a route
discard	discard the path attribute
unknown	unknown path attribute
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)

<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)

<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)

<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)

<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgrb_len</i>	(Optional)

<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp paths

```
show [ ip ] bgp paths [ __readonly__ TABLE_id <id> <hashvalue> <refcount> <metric> <aspath> <origin> ]
```

Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
paths	Display Path information
__readonly__	(Optional)
TABLE_id	(Optional)
<i>id</i>	(Optional)
<i>hashvalue</i>	(Optional)
<i>refcount</i>	(Optional)
<i>metric</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)

Command Mode

- /exec

show bgp peer-template

```
show [ ip ] bgp peer-template [ <peer-template-name> ] [ __readonly__ { TABLE_neighbor <templatepeer>
[ <remotemas> ] [ <remoteas-type> ] [ <maxprefixpeers> ] [ <inherit-template> ] [ <inherit-session-template>
] [ { <prefix-parent> | <ipv6prefix-parent> | <interface-parent> } ] [ <description> ] [ <sourceif> ] [ <updatesrc>
] [ <updatesrcname> ] [ <connectedcheck> ] [ <lowmemexempt> ] [ <bfd> ] [ <bfdsessiontype> ] [
<bfdmintxinterval> ] [ <bfdminrxinterval> ] [ <bfdmultiplier> ] [ <bfdauthenticationtype> ] [ <ttlsecurity> ]
[ <ttllimit> ] [ <dscp> ] [ <password> ] [ <passiveonly> ] <localas-inactive> [ <remove-privateas> ] [
<gshut-activate> ] [ <gshut-map> ] [ <configholdtime> <configkeepalivetime> ] [ TABLE_peraf <per-afi>
TABLE_persaf <per-safi> <per-af-name> [ <tableversion> ] [ <neighborstableversion> ] [ <pfxrcvd> ] [
<pathsrcvd> ] [ <pfxbytes> ] [ <pfxtreataswithdrawn> ] [ <pfxsent> ] [ <pathsent> ] [ <conditionmap>
<advertisemap> <advertisemapstatus> ] [ <insoftreconfigallowed> ] [ <insoftreconfigallowedalways> ] [
<sendcommunity> ] [ <sendextcommunity> ] [ { <localnexthop> | <ipv6localnexthop> } ] [ <thirdpartynexthop>
] [ <maxpfx> ] [ <maxpfx_threshold> ] [ <soo> ] [ <weight> ] [ <allowasin> ] [ <asoverride>
<peerascheckdisabled> ] [ <vpls-signaling-protocol> ] [ { TABLE_inpolicy <inpolicynr> <inpolicytype>
<inpolicyname> [ <inpolicyhandle> } ] [ { TABLE_outpolicy <outpolicynr> <outpolicytype>
<outpolicyname> [ <outpolicyhandle> } ] ] [ <rrconfigured> <defaultoriginate> [ <defaultoriginatemap> ] [
<defaultsent> ] [ <grpatsaved> ] [ <firsteorrcvd> ] [ <firsteortime> ] [ <pathsflushed> ] [ <lasteorrcvtime>
] [ <lasteorsenttime> ] [ <firstconvgttime> ] [ <pfxsentfirsteor> ] [ <unsuppress-map> ] [ {
TABLE_policy_template <preference> <inherit-policy-template> } ] [ TABLE_vrf <vrf-name> [
TABLE_inheritingpeer <inheritingpeer> [ <interface-parent> ] ] ] ] }
```

Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-template	Display information about a peer-template
<i>peer-template-name</i>	(Optional) Peer-template name
<i>__readonly__</i>	(Optional)
<i>TABLE_neighbor</i>	(Optional)
<i>templatepeer</i>	(Optional)
<i>remotemas</i>	(Optional)
<i>remoteas-type</i>	(Optional)
<i>maxprefixpeers</i>	(Optional)
<i>inherit-template</i>	(Optional)
<i>inherit-session-template</i>	(Optional)
<i>prefix-parent</i>	(Optional)
<i>interface-parent</i>	(Optional)

<i>description</i>	(Optional)
<i>sourceif</i>	(Optional)
<i>updatesrc</i>	(Optional)
<i>updatesrcname</i>	(Optional)
<i>connectedcheck</i>	(Optional)
<i>lowmemexempt</i>	(Optional)
<i>bfd</i>	(Optional)
<i>bfdsessiontype</i>	(Optional)
<i>bfdmintxinterval</i>	(Optional)
<i>bfdminrxinterval</i>	(Optional)
<i>bfdmultiplier</i>	(Optional)
<i>bfdauthenticationtype</i>	(Optional)
<i>ttlsecurity</i>	(Optional)
<i>tllimit</i>	(Optional)
<i>dscp</i>	(Optional)
<i>passiveonly</i>	(Optional)
<i>password</i>	(Optional)
<i>localas-inactive</i>	(Optional)
<i>remove-privateas</i>	(Optional)
<i>gshut-activate</i>	(Optional)
<i>gshut-map</i>	(Optional)
<i>configholdtime</i>	(Optional)
<i>configkeepalivetime</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_inheritingpeer	(Optional)
<i>inheritingpeer</i>	(Optional)
<i>interface-parent</i>	(Optional)
TABLE_perarf	(Optional)

<i>per-afi</i>	(Optional)
TABLE_persaf	(Optional)
<i>per-safi</i>	(Optional)
<i>per-af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>pxrcvd</i>	(Optional)
<i>pathsrcvd</i>	(Optional)
<i>pxbytes</i>	(Optional)
<i>pxtreataswithdrawn</i>	(Optional)
<i>pxsent</i>	(Optional)
<i>pathsent</i>	(Optional)
<i>conditionmap</i>	(Optional)
<i>advertisemap</i>	(Optional)
<i>advertisemapstatus</i>	(Optional)
<i>insoftreconfigallowed</i>	(Optional)
<i>insoftreconfigallowedalways</i>	(Optional)
<i>sendcommunity</i>	(Optional)
<i>sendextcommunity</i>	(Optional)
<i>maxpx</i>	(Optional)
<i>maxpx_threshold</i>	(Optional)
<i>localnexthop</i>	(Optional)
TABLE_inpolicy	(Optional)
<i>inpolicynr</i>	(Optional)
<i>inpolicytype</i>	(Optional)
<i>inpolicyname</i>	(Optional)
<i>inpolicyhandle</i>	(Optional)
TABLE_outpolicy	(Optional)
<i>outpolicynr</i>	(Optional)

<i>outpolicytype</i>	(Optional)
<i>outpolicyname</i>	(Optional)
<i>outpolicyhandle</i>	(Optional)
<i>rrconfigured</i>	(Optional)
<i>defaultoriginate</i>	(Optional)
<i>defaultoriginatemap</i>	(Optional)
<i>defaultsent</i>	(Optional)
<i>grpathssaved</i>	(Optional)
<i>firsteorrecvd</i>	(Optional)
<i>firsteortime</i>	(Optional)
<i>pathsflushed</i>	(Optional)
<i>lasteorrecvtime</i>	(Optional)
<i>lasteorsenttime</i>	(Optional)
<i>firstconvgttime</i>	(Optional)
<i>pxsentfirsteor</i>	(Optional)
<i>unsuppress-map</i>	(Optional)
<i>thirdpartynexthop</i>	(Optional)
<i>soo</i>	(Optional)
<i>weight</i>	(Optional)
<i>allowasin</i>	(Optional)
<i>asoverride</i>	(Optional)
<i>peerascheckdisabled</i>	(Optional)
<i>vplssignalingprotocol</i>	(Optional)
TABLE_policy_template	(Optional)
<i>preference</i>	(Optional)
<i>inherit-policy-template</i>	(Optional)

Command Mode

- /exec

show bgp peer

```
show [ ip ] bgp { peer-session [ <session-template-name> ] | peer-policy [ <policy-template-name> ] } [
  __readonly__ TABLE_template <template> <present> [ { TABLE_command <command> [ <polarity> ] [
    <updatesource> ] [ <description> ] [ <multihop> ] [ <holdtime> ] [ <keepalive> ] [ <dscp> ] [ <routemapin>
  ] [ <routemapout> ] [ <filterlistin> ] [ <filterlistout> ] [ <prefixlistin> ] [ <prefixlistout> ] [ <maxprefixlimit>
  ] [ <defaultorigin> ] } ] [ { TABLE_vrf <vrf-name> { TABLE_peer <inheritingpeer> [ <interface-parent>
  ] } } ] ] ] ]
```

Syntax Description

show	Show running system information
ip	(Optional) Display IP information
bgp	Display BGP status and configuration
peer-session	Display information about a peer-session
peer-policy	Display information about a peer-policy
<i>session-template-name</i>	(Optional) Peer-session name
<i>policy-template-name</i>	(Optional) Peer-policy name
__readonly__	(Optional)
TABLE_template	(Optional)
<i>template</i>	(Optional)
<i>present</i>	(Optional)
TABLE_command	(Optional)
<i>command</i>	(Optional)
<i>polarity</i>	(Optional)
<i>updatesource</i>	(Optional)
<i>description</i>	(Optional)
<i>multihop</i>	(Optional)
<i>holdtime</i>	(Optional)
<i>keepalive</i>	(Optional)
<i>dscp</i>	(Optional)
<i>routemapin</i>	(Optional)
<i>routemapout</i>	(Optional)

<i>filterlistin</i>	(Optional)
<i>filterlistout</i>	(Optional)
<i>prefixlistin</i>	(Optional)
<i>prefixlistout</i>	(Optional)
<i>maxprefixlimit</i>	(Optional)
<i>defaultorigin</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name</i>	(Optional)
TABLE_peer	(Optional)
<i>inheritingpeer</i>	(Optional)
<i>interface-parent</i>	(Optional)

Command Mode

- /exec

show bgp prefix-list

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } } prefix-list { <prfxlist-name> | <test_pol_name> } [ vrf { <vrf-name>
| <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out>
TABLE_afi <afi> TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [
<rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix>
| <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [ <originalimportsource> ] ] [
<importdstscount> ] [ TABLE_importdsts <importdst> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
prefix-list	Display routes matching the prefix-list
<i>prfxlist-name</i>	Name of prefix-list
<i>test_pol_name</i>	An existing test-list policy
ipv4	Display BGP information for IPv4 address family

ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
__readonly__	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)

<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)

<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregadoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)

<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)

<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)

<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp private attr

show bgp private attr [database | as-path | nve-peer | community | large-community | extcommunity | srte-policy | prefix-sid | srv6 | attrset] [brief]

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
attr	Show BGP attributes
database	(Optional) Show attribute set table
as-path	(Optional) Show AS-PATH attribute table
nve-peer	(Optional) Show NVE peer attribute table
community	(Optional) Show community attribute table
large-community	(Optional) Show large community attribute table
extcommunity	(Optional) Show extended community attribute table
srte-policy	(Optional) Show SRTE policy attribute table
prefix-sid	(Optional) Show prefix SID attribute table
srv6	(Optional) Show SRv6 attribute table
attrset	(Optional) Show ATTRSET attribute table
brief	(Optional) Show brief info

Command Mode

- /exec

show bgp private debug history

show bgp private debug history { all | ead-es | es | mac | cloudsec }

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
private	Show BGP information intended for developer eyes only
debug	Debug
history	history
all	all
ead-es	ead-es
es	es
mac	mac
cloudsec	cloudsec

Command Mode

- /exec

show bgp process

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] process [ detail ] [
vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ [ <processid>
<protocolstartedreason> <protocoltag> <protocolasn> <protocolstate> [ <clibinarydone> <cliasciiidone> ]
<isolatemode> <gshut-aware> <gshut-activate> [ <gshut-map> ] <mmode> <memorystate> [
<mallocmemorystate> ] [ <platformmemorystate> ] [ <lowmemorytimer> ] [ <issu> ] <forwardingstatesaved>
<asformat> [ <fabricsoo> ] [ <srgbmin> <srgbmax> ] [ <epeconfiguredpeers> <epeactivepeers> ]
<attributeentries> <hwmattributeentries> <bytesused> <entriespendingdelete> <hwmentriespendingdelete>
<pathsperattribute> <aspathentries> <aspathbytes> ] TABLE_vrf <vrf-name-out> [ <vrf-id> ] [ <vrf-state>
] [ <vrf-state-rsn> ] [ <vrf-delete-pending> ] [ <vrf-evpn-mpls> ] [ <vrf-vni-id> ] [ <vrf-vni-id-valid> ] [
<vrf-topo-id> ] [ <vrf-encap-type> ] [ <vrf-vtep-ip> ] [ <vrf-vtep-virtual-ip> ] [ <vrf-vtep-vipr> ] [
<vrf-router-mac> ] [ <vrf-vip-router-mac> ] [ <vrf-vipr-router-mac> ] [ <vrf-router-id> ] [ <vrf-cfgd-id-auto>
] [ <vrf-cfgd-id> ] [ <vrf-if-router-id> ] [ <vrf-local-as> ] [ <vrf-confed-id> ] [ <vrf-cluster-id> ] [
<vrf-reconnect-interval> ] [ <vrf-peers> ] [ <vrf-pending-peers> ] [ <vrf-est-peers> ] [ <vrf-cfgd-max-as-limit>
] [ <vrf-max-as-limit> ] [ <vrf-rd-configured> ] [ <vrf-rd> ] [ <vrf-secondary-rd-configured> ] [
<vrf-secondary-rd> ] [ <vrf-pending-rd> ] [ <vrf-pending-secondary-rd> ] { TABLE_af <af-id> [ <af-name>
] [ <af-table-id> ] [ <af-state> ] [ <af-state-rsn> ] [ <af-num-peers> ] [ <af-num-active-peers> ] [
<af-peer-routes> ] [ <af-peer-paths> ] [ <af-peer-networks> ] [ <af-peer-aggregates> ] [ <af-export-rmap> ]
[ <af-import-rmap> ] [ <af-retain-rt> ] [ { TABLE_redist <protocol> <route-map> } ] <wait-igp-convergence>
[ { TABLE_add_paths_selection <route-map> } ] [ <af-retain-rt> ] [ TABLE_export_rt <export-rt> ] [
TABLE_import_rt <import-rt> ] [ TABLE_evpn_export_rt <evpn-export-rt> ] [ TABLE_evpn_import_rt
<evpn-import-rt> ] [ TABLE_mvpn_export_rt <mvpn-export-rt> ] [ TABLE_mvpn_import_rt <mvpn-import-rt>
] [ <af-label-mode> ] [ <af-aggregate-label> ] [ <af-alloc-index> ] [ <srv6-sid-locator-name> ] [
<srv6-sid-locator-id> ] [ <srv6-sid-locator-prefix> ] [ <srv6-sid-src-enc-address> ] [ <srv6-vrf-sid-alloc> ] [
<srv6-vrf-dt46-sid> ] [ <srv6-vrf-dt-sid-alloc-pending> ] [ <srv6-vrf-dt-sid-del-pending> ] [
<srv6-vrf-sid-alloc-pending-reason> ] [ <srv6-tbl-sid-alloc> ] [ <srv6-tbl-dt-type> ] [ <srv6-tbl-dt-sid> ] [
<srv6-tbl-dt-sid-alloc-pending> ] [ <srv6-tbl-dt-sid-del-pending> ] [ <srv6-tbl-dt-sid-alloc-pending-reason>
] [ <srv6-alloc-mode> ] [ <importdefault_prefixlimit> <importdefault_prefixcount> <importdefault_map>
<importdefault_advertisevpn> ] <import_vrf_advertisevpn> [ <exportdefault_prefixlimit>
<exportdefault_prefixcount> <exportdefault_map> <exportdefault_allowvpn> ] <export_vrf_allowvpn>
<af-rr> <default-information-enabled> [ <default-information-rd> <default-information-rt> ]
<nexthop-trigger-delay-critical> <nexthop-trigger-delay-non-critical> [ <nexthop-route-map> ] } ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
process	BGP global information
detail	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
<i>__readonly__</i>	(Optional) Read Only

<i>processid</i>	(Optional)
<i>protocolstartedreason</i>	(Optional)
<i>protocoltag</i>	(Optional)
<i>protocolasn</i>	(Optional)
<i>protocolstate</i>	(Optional)
<i>clibinarydone</i>	(Optional)
<i>cliasciidone</i>	(Optional)
<i>isolatemode</i>	(Optional)
<i>gshut-aware</i>	(Optional)
<i>gshut-activate</i>	(Optional)
<i>gshut-map</i>	(Optional)
<i>mmode</i>	(Optional)
<i>memorystate</i>	(Optional)
<i>mallocmemorystate</i>	(Optional)
<i>platformmemorystate</i>	(Optional)
<i>lowmemorytimer</i>	(Optional)
<i>issu</i>	(Optional)
<i>forwardingstatesaved</i>	(Optional)
<i>asformat</i>	(Optional)
<i>attributeentries</i>	(Optional)
<i>fabricsoo</i>	(Optional)
<i>srgbmin</i>	(Optional)
<i>srgbmax</i>	(Optional)
<i>epeconfiguredpeers</i>	(Optional)
<i>epeactivepeers</i>	(Optional)
<i>hwmattributeentries</i>	(Optional)
<i>bytesused</i>	(Optional)
<i>entriespendingdelete</i>	(Optional)
<i>hwmentriespendingdelete</i>	(Optional)

<i>pathsperattribute</i>	(Optional)
<i>aspathentries</i>	(Optional)
<i>aspathbytes</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional) VRF name
<i>vrf-id</i>	(Optional) VRF ID
<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-evpn-mpls</i>	(Optional) VRF EVPN L3 MPLS
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-topo-id</i>	(Optional) VRF Topo ID
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-vtep-vipr</i>	(Optional) VRF VTEP Virtual IP for Re-origination
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-vip-router-mac</i>	(Optional) VRF VIP Router MAC
<i>vrf-vipr-router-mac</i>	(Optional) VRF VIPR Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id-auto</i>	(Optional) Configured Router-ID Auto
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-if-router-id</i>	(Optional) Interface Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers

<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd-configured</i>	(Optional) VRF RD Configured
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-secondary-rd-configured</i>	(Optional) VRF Secondary RD Configured
<i>vrf-secondary-rd</i>	(Optional) VRF Secondary RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
<i>vrf-pending-secondary-rd</i>	(Optional) VRF pending secondary RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_redist	(Optional)
<i>protocol</i>	(Optional) Protocol
<i>route-map</i>	(Optional) Route Map
<i>wait-igp-convergence</i>	(Optional)

TABLE_add_paths_selection	(Optional)
<i>route-map</i>	(Optional) Route Map
<i>af-retain-rt</i>	(Optional) Retain route-target
TABLE_export_rt	(Optional)
<i>export-rt</i>	(Optional) Export route-target
TABLE_import_rt	(Optional)
<i>import-rt</i>	(Optional) Import route-target
TABLE_evpn_export_rt	(Optional)
<i>evpn-export-rt</i>	(Optional) Export EVPN route-target
TABLE_evpn_import_rt	(Optional)
<i>evpn-import-rt</i>	(Optional) Import EVPN route-target
TABLE_mvpn_export_rt	(Optional)
<i>mvpn-export-rt</i>	(Optional) Export MVPN route-target
TABLE_mvpn_import_rt	(Optional)
<i>mvpn-import-rt</i>	(Optional) Import MVPN route-target
<i>af-label-mode</i>	(Optional) Label allocation mode
<i>af-aggregate-label</i>	(Optional) Aggregate Label
<i>af-alloc-index</i>	(Optional) Allocate-Index
<i>srv6-alloc-mode</i>	(Optional) Srv6 sid allocation mode
<i>srv6-sid-locator-name</i>	(Optional) SRv6 SID Locator Name
<i>srv6-sid-locator-id</i>	(Optional) SRv6 SID Locator ID
<i>srv6-sid-src-enc-address</i>	(Optional) SRv6 Source Encap Address
<i>srv6-vrf-sid-alloc</i>	(Optional) SRv6 VRF SID Allocation Mode
<i>srv6-vrf-dt-sid-alloc-pending</i>	(Optional) Is SRv6 DT46 SID Allocation: Pending
<i>srv6-vrf-dt-sid-del-pending</i>	(Optional) Is SRv6 DT46 SID Deletion: Pending
<i>srv6-vrf-sid-alloc-pending-reason</i>	(Optional) SRv6 SID Allocation pending reason:
<i>srv6-tbl-sid-alloc</i>	(Optional) SRv6 table ctx SID allocation mode
<i>srv6-tbl-dt-type</i>	(Optional) SRv6 DT type
<i>srv6-tbl-dt-sid</i>	(Optional) SRv6 table per VRF SID :

<i>srv6-tbl-dt-sid-alloc-pending</i>	(Optional) SRv6 SID Allocation: Pending
<i>srv6-tbl-dt-sid-del-pending</i>	(Optional) SRv6 SID Deletion: Pending
<i>srv6-tbl-dt-sid-alloc-pending-reason</i>	(Optional) SRv6 SID Allocation Pending Reason
<i>importdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>importdefault_prefixcount</i>	(Optional) Current number of prefixes
<i>importdefault_map</i>	(Optional) Configured route-map
<i>importdefault_advertisevpn</i>	(Optional) Advertise-vpn is enabled
<i>import_vrf_advertisevpn</i>	(Optional) Advertise-vpn is enabled
<i>exportdefault_prefixlimit</i>	(Optional) Maximum number of prefixes allowed
<i>exportdefault_prefixcount</i>	(Optional) Current number of prefixes
<i>exportdefault_map</i>	(Optional) Configured route-map
<i>exportdefault_allowvpn</i>	(Optional) Allow-vpn is enabled
<i>export_vrf_allowvpn</i>	(Optional) Allow-vpn is enabled
<i>af-rr</i>	(Optional) Is a Route-reflector
<i>default-information-enabled</i>	(Optional) Default-information originate is enabled
<i>default-information-rd</i>	(Optional) Default-information originate RD
<i>default-information-rt</i>	(Optional) Default-information originate RT
<i>nexthop-trigger-delay-critical</i>	(Optional)
<i>nexthop-trigger-delay-non-critical</i>	(Optional)
<i>nexthop-route-map</i>	(Optional)

Command Mode

- /exec

show bgp received-paths

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | ipv4 mdt [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> }
] | vpv4 unicast [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | vpv6 unicast [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv6 labeled-unicast | link-state | l2vpn vpls [ rd {
<ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 mvpn [ rd { <ext-comm-rd-aa2nn4> |
<ext-comm-rd-aa4nn2> } ] | ipv6 mvpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | l2vpn
evpn [ rd { <ext-comm-rd-aa2nn4> | <ext-comm-rd-aa4nn2> } ] | ipv4 labeled-unicast | all } received-paths
[ private ] [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf<vrf-name-out> TABLE_afi<afi> TABLE_safi<safi> <af-name> [ <table-version> <router-id>
] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix
{ <ipprefix> | <ipv6prefix> | <nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist>
<on-xmitlist> <suppressed> <needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist>
<export-on-xmitlist> ] [ <srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path
<pathnr> { { <status> <best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> {
<ipnexthop> | <ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath>
<origin> [ <metric> ] [ <localpref> ] } } } | [ <policyincomplete> <pathvalid> <pathbest> <pathreoriginated>
<pathdeleted> <pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn>
<pathlocator> <path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> ] [ <importsource> [
<originalimportsource> ] ] [ <importdstscount> ] [ TABLE_importdsts <importdest> ] [ <existpath> ] [
<gwip> | <ipv6gwip> ] [ <aspath> <source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor>
| <ipv6neighbor> } <neighborid> <origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras>
<atomicaggregate> ] [ <inlabel> ] [ <originflag> ] [ { TABLE_community <community> } ] [ {
TABLE_largecommunity <largecommunity> } ] [ { TABLE_extcommunity <extcommunity> } ] [
<originatorid> { TABLE_clusterlist <clusterlist> } ] [ <flappenalty> <dampenedtime> <flaps> <flaptime>
<flapflags> <flapindex> <flaphalf-life> <flapreuse> <flapsuppress> <flapmax> ] [ <con_type> <con_len>
<con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len> <psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len>
<psid_sub_type> <psid_v6sid> <psid_func_len> <psid_trans_len> <psid_trans_off> ] [ <psid_origrsrgb_len>
<psid_origrsrgb_flag> <psid_origrsrgb_base> <psid_origrsrgb_end> ] ] [ <remotenh> <remotenh_encap>
<remotenh_vnid> <remotenh_mac> ] [ <pmsi> ] [ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [
<tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [ TABLE_path_attr_list <path_attr_list> [ TABLE_attr
<attr_num> <attr_code_str> <attr_code_hex> <attr_flags> <attr_len> [ TABLE_attr_val <attr_value> ] ] ] [
<attrset_origin_as> <attrset_origin> <attrset_metric> <attrset_localpref> [ <attrset_aspath> ] [
<attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist> } ] ] [ <rpki_origin_as_validity> }
} ] [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto <scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
received-paths	Display paths stored for soft-reconfig
rd	(Optional) Display information for a route distinguisher

<i>ext-comm-rd-aa4nn2</i>	(Optional) VPN route distinguisher in aa4:nn or ip:nn format
<i>ext-comm-rd-aa2nn4</i>	(Optional) VPN route distinguisher in aa:nn format
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
mdt	Display BGP information for multicast distribution tree
labeled-unicast	Display BGP information for labeled-unicast address family
link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
private	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)

<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)

<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)

<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)

<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgrb_len</i>	(Optional)

<i>psid_origsrgrb_flag</i>	(Optional)
<i>psid_origsrgrb_base</i>	(Optional)
<i>psid_origsrgrb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp regexp

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } regexp <regexp-str> [ vrf { <vrf-name> | <vrf-known-name>
| ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi>
TABLE_safi <safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [
<rd_vniid> ] [ <rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> |
<nonipprefix> } [ <prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed>
<needsresync> <locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [
<srv6-local-sid> ] [ <locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status>
<best> <type> [ <origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> |
<ipv6nexthop> } } { <inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric>
] [ <localpref> ] } } } | { <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted>
<pathstaled> <pathhistory> <pathovermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> } [ <importsource> [ <originalimportsource> ] ] [
<importdstscount> ] [ TABLE_importdsts <importdst> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flappenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family

all	Display BGP information for all address families
regexp	Display routes matching the AS path regular expression
<i>regexp-str</i>	Regular expression to match the AS paths
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)

<i>scheduledto</i>	(Optional)
<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)

<i>importdestscount</i>	(Optional)
TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregators</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)

<i>outlabel</i>	(Optional)
<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)

<i>remotenh</i>	(Optional)
<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)

<i>attrset_origin</i>	(Optional)
<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp segment-routing srv6

```
show bgp segment-routing srv6 [ __readonly__ [ <locator-name> <locator-id> <locator-prefix> ] [ TABLE_vrf
<vrf-name-out> [ <vrf-srv6-sid> ] [ TABLE_af <af-name> <af-dt> <table-srv6-sid> ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
segment-routing	Display segment-routing informstion
srv6	Display segment-routing srv6 information
__readonly__	(Optional)
<i>locator-name</i>	(Optional)
<i>locator-id</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_af	(Optional)
<i>af-name</i>	(Optional)
<i>af-dt</i>	(Optional)

Command Mode

- /exec

show bgp self-originated

```

show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] { ipv4 { unicast |
multicast } | ipv6 { unicast | multicast } | all } self-originated [ vrf { <vrf-name> | <vrf-known-name> |
ALL_VRFS_012345678901234 } ] [ __readonly__ TABLE_vrf <vrf-name-out> TABLE_afi <afi> TABLE_safi
<safi> <af-name> [ <table-version> <router-id> ] [ TABLE_rd [ <rd_val> [ <rd_vrf> ] [ <rd_vniid> ] [
<rd-esi-desc> <rd-esi> <rd-seg-id> ] ] [ TABLE_prefix { <ipprefix> | <ipv6prefix> | <nonipprefix> } [
<prefixversion> <totalpaths> <bestpathnr> [ <on-newlist> <on-xmitlist> <suppressed> <needsresync>
<locked> ] [ <table-map-filtered> ] [ <export-on-newlist> <export-on-xmitlist> ] [ <srv6-local-sid> ] [
<locallabel> ] [ <labelhldwstr> ] [ <mpath> ] ] { TABLE_path <pathnr> { { <status> <best> <type> [
<origin_as_validity_code> ] <statuscode> <bestcode> <typecode> { <ipnexthop> | <ipv6nexthop> } { {
<inlabel> <outlabel> <vpn> <hold_down> } | { <weight> <aspath> <origin> [ <metric> ] [ <localpref> ] }
} } | { <policyincomplete> <pathvalid> <pathbest> <pathreoriginated> <pathdeleted> <pathstaled>
<pathhistory> <pathvermaxaslimit> <pathmultipath> <pathnolabeledrn> <pathlocator>
<path-vpc-orphan-mac> <path-vpc-peer-orphan-mac> } [ <importsource> [ <originalimportsource> ] ] [
<importdstscount> ] [ TABLE_importdsts <importdst> ] [ <existpath> ] [ <gwip> | <ipv6gwip> ] [ <aspath>
<source> ] { <ipnexthop> | <ipv6nexthop> } <nexthopmetric> { <neighbor> | <ipv6neighbor> } <neighborid>
<origin> [ <metric> ] <localpref> <weight> [ <aggregator> <aggregatoras> <atomicaggregate> ] [ <inlabel>
] [ <originflag> ] [ { TABLE_community <community> } ] [ { TABLE_largecommunity <largecommunity>
} ] [ { TABLE_extcommunity <extcommunity> } ] [ <originatorid> { TABLE_clusterlist <clusterlist> } ] [
<flapenalty> <dampenedtime> <flaps> <flaptime> <flapflags> <flapindex> <flaphalflife> <flapreuse>
<flapsuppress> <flapmax> ] [ <con_type> <con_len> <con_rd> <con_ip> ] [ <psid_len> [ <psid_lindx_len>
<psid_lindx_flag> <psid_lindx> ] [ <psid_v6sid_len> <psid_sub_type> <psid_v6sid> <psid_func_len>
<psid_trans_len> <psid_trans_off> ] [ <psid_origsrgrb_len> <psid_origsrgrb_flag> <psid_origsrgrb_base>
<psid_origsrgrb_end> ] ] [ <remotenh> <remotenh_encap> <remotenh_vnid> <remotenh_mac> ] [ <pmsi> ]
[ <evpn-esi> ] [ <link-state-attr> <link-state-attr-len> ] [ <tunnel-encap-attr-len> ] [ <mdt_grp_addr> ] [
TABLE_path_attr_list <path_attr_list> [ TABLE_attr <attr_num> <attr_code_str> <attr_code_hex> <attr_flags>
<attr_len> [ TABLE_attr_val <attr_value> ] ] ] [ <attrset_origin_as> <attrset_origin> <attrset_metric>
<attrset_localpref> [ <attrset_aspath> ] [ <attrset_originatorid> { TABLE_attrset_clusterlist <attrset_clusterlist>
} ] ] [ <rpki_origin_as_validity> ] } } } [ TABLE_advertisedto <advertisedto> ] [ TABLE_scheduledto
<scheduledto> ] ] ] ]

```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
ipv4	Display BGP information for IPv4 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family

all	Display BGP information for all address families
self-originated	Self originated routes
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
TABLE_afi	(Optional)
<i>afi</i>	(Optional)
TABLE_safi	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>table-version</i>	(Optional)
<i>router-id</i>	(Optional)
TABLE_rd	(Optional)
<i>rd_val</i>	(Optional)
<i>rd_vrf</i>	(Optional)
<i>rd_vniid</i>	(Optional)
<i>rd-esi-desc</i>	(Optional)
<i>rd-esi</i>	(Optional)
<i>rd-seg-id</i>	(Optional)
TABLE_prefix	(Optional)
<i>ipprefix</i>	(Optional)
<i>nonipprefix</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>bestpathnr</i>	(Optional)
<i>mpath</i>	(Optional)
TABLE_advertisedto	(Optional)
<i>advertisedto</i>	(Optional)
TABLE_scheduledto	(Optional)
<i>scheduledto</i>	(Optional)

<i>prefixversion</i>	(Optional)
<i>on-newlist</i>	(Optional)
<i>on-xmitlist</i>	(Optional)
<i>suppressed</i>	(Optional)
<i>needsresync</i>	(Optional)
<i>locked</i>	(Optional)
<i>table-map-filtered</i>	(Optional)
<i>export-on-newlist</i>	(Optional)
<i>export-on-xmitlist</i>	(Optional)
<i>locallabel</i>	(Optional)
<i>labelhldwstr</i>	(Optional)
TABLE_path	(Optional)
<i>pathnr</i>	(Optional)
<i>best</i>	(Optional)
<i>status</i>	(Optional)
<i>type</i>	(Optional)
<i>origin_as_validity_code</i>	(Optional)
<i>statuscode</i>	(Optional)
<i>bestcode</i>	(Optional)
<i>typecode</i>	(Optional)
<i>ipnexthop</i>	(Optional)
<i>neighbor</i>	(Optional)
<i>neighborid</i>	(Optional)
<i>metric</i>	(Optional)
<i>localpref</i>	(Optional)
<i>weight</i>	(Optional)
<i>importsource</i>	(Optional)
<i>originalimportsource</i>	(Optional)
<i>importdestscount</i>	(Optional)

TABLE_importdests	(Optional)
<i>importdest</i>	(Optional)
<i>existpath</i>	(Optional)
<i>gwip</i>	(Optional)
<i>aspath</i>	(Optional)
<i>origin</i>	(Optional)
<i>source</i>	(Optional)
<i>policyincomplete</i>	(Optional)
<i>pathvalid</i>	(Optional)
<i>pathbest</i>	(Optional)
<i>pathreoriginated</i>	(Optional)
<i>pathdeleted</i>	(Optional)
<i>pathstaled</i>	(Optional)
<i>pathhistory</i>	(Optional)
<i>pathmultipath</i>	(Optional)
<i>pathovermaxaslimit</i>	(Optional)
<i>pathnolabeledrn</i>	(Optional)
<i>pathlocator</i>	(Optional)
<i>path-vpc-orphan-mac</i>	(Optional)
<i>path-vpc-peer-orphan-mac</i>	(Optional)
<i>nexthopmetric</i>	(Optional)
<i>aggregator</i>	(Optional)
<i>aggregatoras</i>	(Optional)
<i>atomicaggregate</i>	(Optional)
<i>inlabel</i>	(Optional)
<i>originflag</i>	(Optional)
<i>vpn</i>	(Optional)
<i>hold_down</i>	(Optional)
<i>outlabel</i>	(Optional)

<i>flappenalty</i>	(Optional)
<i>dampenedtime</i>	(Optional)
<i>flaps</i>	(Optional)
<i>flaptime</i>	(Optional)
<i>flapflags</i>	(Optional)
<i>flapindex</i>	(Optional)
<i>flaphalflife</i>	(Optional)
<i>flapreuse</i>	(Optional)
<i>flapsuppress</i>	(Optional)
<i>flapmax</i>	(Optional)
<i>con_type</i>	(Optional)
<i>con_len</i>	(Optional)
<i>con_rd</i>	(Optional)
<i>con_ip</i>	(Optional)
<i>mdt_grp_addr</i>	(Optional)
<i>evpn-esi</i>	(Optional)
<i>link-state-attr</i>	(Optional)
<i>link-state-attr-len</i>	(Optional)
<i>tunnel-encap-attr-len</i>	(Optional)
TABLE_community	(Optional)
<i>community</i>	(Optional)
TABLE_largecommunity	(Optional)
<i>largecommunity</i>	(Optional)
TABLE_extcommunity	(Optional)
<i>extcommunity</i>	(Optional)
<i>originatorid</i>	(Optional)
TABLE_clusterlist	(Optional)
<i>clusterlist</i>	(Optional)
<i>remotenh</i>	(Optional)

<i>remotenh_encap</i>	(Optional)
<i>remotenh_vnid</i>	(Optional)
<i>remotenh_mac</i>	(Optional)
<i>pmsi</i>	(Optional)
<i>psid_len</i>	(Optional)
<i>psid_lindx_len</i>	(Optional)
<i>psid_lindx_flag</i>	(Optional)
<i>psid_lindx</i>	(Optional)
<i>psid_v6sid_len</i>	(Optional)
<i>psid_sub_type</i>	(Optional)
<i>psid_func_len</i>	(Optional)
<i>psid_trans_len</i>	(Optional)
<i>psid_trans_off</i>	(Optional)
<i>psid_origsrgb_len</i>	(Optional)
<i>psid_origsrgb_flag</i>	(Optional)
<i>psid_origsrgb_base</i>	(Optional)
<i>psid_origsrgb_end</i>	(Optional)
TABLE_path_attr_list	(Optional)
<i>path_attr_list</i>	(Optional)
TABLE_attr	(Optional)
<i>attr_num</i>	(Optional)
<i>attr_code_str</i>	(Optional)
<i>attr_code_hex</i>	(Optional)
<i>attr_len</i>	(Optional)
<i>attr_flags</i>	(Optional)
TABLE_attr_val	(Optional)
<i>attr_value</i>	(Optional)
<i>attrset_origin_as</i>	(Optional)
<i>attrset_origin</i>	(Optional)

<i>attrset_metric</i>	(Optional)
<i>attrset_localpref</i>	(Optional)
<i>attrset_aspath</i>	(Optional)
<i>attrset_originatorid</i>	(Optional)
TABLE_attrset_clusterlist	(Optional)
<i>attrset_clusterlist</i>	(Optional)
<i>rpki_origin_as_validity</i>	(Optional)

Command Mode

- /exec

show bgp sessions

```
show bgp [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] sessions [ vrf {
<vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__ <totalpeers>
<totalestablishedpeers> <localas> TABLE_vrf <vrf-name-out> <local-as> <vrfpeers> <vrfestablishedpeers>
<router-id> [ TABLE_neighbor <neighbor-id> <connectionsdropped> [ <interface-parent> ] <remotetas> [
<lastflap> ] [ <lastread> ] [ <lastwrite> ] <state> <localport> <remoteport> <notificationssent>
<notificationreceived> ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
sessions	Display session information for all peers
<i>__readonly__</i>	(Optional)
TABLE_vrf	(Optional)
<i>vrf-name-out</i>	(Optional)
<i>local-as</i>	(Optional)
<i>totalpeers</i>	(Optional)
<i>totalestablishedpeers</i>	(Optional)
<i>router-id</i>	(Optional)
<i>localas</i>	(Optional)
<i>vrfpeers</i>	(Optional)
<i>vrfestablishedpeers</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighbor-id</i>	(Optional)
<i>connectionsdropped</i>	(Optional)
<i>remotetas</i>	(Optional)
<i>interface-parent</i>	(Optional)
<i>lastflap</i>	(Optional)

<i>lastread</i>	(Optional)
<i>lastwrite</i>	(Optional)
<i>state</i>	(Optional)
<i>localport</i>	(Optional)
<i>remoteport</i>	(Optional)
<i>notificationssent</i>	(Optional)
<i>notificationsreceived</i>	(Optional)

Command Mode

- /exec

show bgp statistics

```
show bgp statistics [ __readonly__ <msgsent> <msgrecvd> <bytesent> <byterecvd> <opensent> <openrecvd>
<updatesent> <updaterecvd> <kasent> <karecvd> <notifsent> <notifrecvd> <rrefreshsent> <rrefreshrecvd>
<capsent> <caprecvd> ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
statistics	BGP global statistics
<i>__readonly__</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>bytesent</i>	(Optional)
<i>byterecvd</i>	(Optional)
<i>opensent</i>	(Optional)
<i>openrecvd</i>	(Optional)
<i>updatesent</i>	(Optional)
<i>updaterecvd</i>	(Optional)
<i>kasent</i>	(Optional)
<i>karecvd</i>	(Optional)
<i>notifsent</i>	(Optional)
<i>notifrecvd</i>	(Optional)
<i>rrefreshsent</i>	(Optional)
<i>rrefreshrecvd</i>	(Optional)
<i>capsent</i>	(Optional)
<i>caprecvd</i>	(Optional)

Command Mode

- /exec

<i>vrf-state</i>	(Optional) VRF State
<i>vrf-state-rsn</i>	(Optional) VRF State Reason
<i>vrf-delete-pending</i>	(Optional) VRF delete pending
<i>vrf-evpn-mpls</i>	(Optional) VRF EVPN L3 MPLS
<i>vrf-vni-id</i>	(Optional) VRF VNI ID
<i>vrf-vni-id-valid</i>	(Optional) VRF VNI ID validity
<i>vrf-topo-id</i>	(Optional) VRF Topo ID
<i>vrf-encap-type</i>	(Optional) VRF encapsulation type
<i>vrf-vtep-ip</i>	(Optional) VRF VTEP IP
<i>vrf-vtep-virtual-ip</i>	(Optional) VRF VTEP Virtual IP
<i>vrf-vtep-vipr</i>	(Optional) VRF VTEP Virtual IP for Re-origination
<i>vrf-router-mac</i>	(Optional) VRF Router MAC
<i>vrf-vip-router-mac</i>	(Optional) VRF VIP Router MAC
<i>vrf-vipr-router-mac</i>	(Optional) VRF VIPR Router MAC
<i>vrf-router-id</i>	(Optional) Router ID
<i>vrf-cfgd-id-auto</i>	(Optional) Configured Router-ID Auto
<i>vrf-cfgd-id</i>	(Optional) Configured Router-ID
<i>vrf-if-router-id</i>	(Optional) Interface Router-ID
<i>vrf-local-as</i>	(Optional) Local AS
<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd-configured</i>	(Optional) VRF RD Configured
<i>vrf-rd</i>	(Optional) VRF RD

<i>vrf-secondary-rd-configured</i>	(Optional) VRF Secondary RD Configured
<i>vrf-secondary-rd</i>	(Optional) VRF Secondary RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
<i>vrf-pending-secondary-rd</i>	(Optional) VRF pending secondary RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT
TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)

<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)
<i>softreconfigcombopaths</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighboras</i>	(Optional)
<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)
<i>interface-parent</i>	(Optional)

Command Mode

- /exec

show bgp summary

```
show bgp { ipv4 { unicast | multicast } | ipv6 { unicast | multicast } | ipv4 mdt | vpnv4 unicast | vpnv6 unicast
| ipv6 labeled-unicast | link-state | l2vpn vpls | ipv4 mvpn | ipv6 mvpn | l2vpn evpn | ipv4 labeled-unicast | all
} summary [ vrf { <vrf-name> | <vrf-known-name> | ALL_VRFS_012345678901234 } ] [ __readonly__
TABLE_vrf <vrf-name-out> ] [ <vrf-id> ] [ <vrf-state> ] [ <vrf-state-rsn> ] [ <vrf-delete-pending> ] [
<vrf-evpn-mpls> ] [ <vrf-vni-id> ] [ <vrf-vni-id-valid> ] [ <vrf-topo-id> ] [ <vrf-encap-type> ] [ <vrf-vtep-ip>
] [ <vrf-vtep-virtual-ip> ] [ <vrf-vtep-vipr> ] [ <vrf-router-mac> ] [ <vrf-vip-router-mac> ] [
<vrf-vipr-router-mac> ] [ <vrf-router-id> ] [ <vrf-cfgd-id-auto> ] [ <vrf-cfgd-id> ] [ <vrf-if-router-id> ] [
<vrf-local-as> ] [ <vrf-confed-id> ] [ <vrf-cluster-id> ] [ <vrf-reconnect-interval> ] [ <vrf-peers> ] [
<vrf-pending-peers> ] [ <vrf-est-peers> ] [ <vrf-cfgd-max-as-limit> ] [ <vrf-max-as-limit> ] [
<vrf-rd-configured> ] [ <vrf-rd> ] [ <vrf-secondary-rd-configured> ] [ <vrf-secondary-rd> ] [ <vrf-pending-rd>
] [ <vrf-pending-secondary-rd> ] [ TABLE_af <af-id> [ <af-name> ] [ <af-table-id> ] [ <af-state> ] [
<af-state-rsn> ] [ <af-num-peers> ] [ <af-num-active-peers> ] [ <af-peer-routes> ] [ <af-peer-paths> ] [
<af-peer-networks> ] [ <af-peer-aggregates> ] [ <af-export-rmap> ] [ <af-import-rmap> ] [ <af-retain-rt> ]
TABLE_saf <safi> [ <af-name> ] [ <tableversion> ] [ <configuredpeers> ] [ <capablepeers> ] [ <totalnetworks>
] [ <totalpaths> ] [ <memoryused> ] [ <numberattrs> ] [ <bytesattrs> ] [ <numberpaths> ] [ <bytespaths> ] [
<numbercommunities> ] [ <bytescommunities> ] [ <numberclusterlist> ] [ <bytesclusterlist> ] [ <dampening>
] [ <historypaths> ] [ <dampenedpaths> ] [ <softreconfigrecvdpaths> ] [ <softreconfigidenticalpaths> ] [
<softreconfigcombopath> ] [ <softreconfigfilteredrecvd> ] [ <softreconfigbytes> ] [ TABLE_neighbor
<neighborid> [ <neighborversion> ] [ <msgrecvd> ] [ <msgsent> ] [ <neighbortableversion> ] [ <inq> ] [
<outq> ] [ <neighboras> ] [ <time> ] [ <state> ] [ <prefixreceived> ] [ <interface-parent> ] ] ] ]
```

Syntax Description

show	Show running system information
bgp	Display BGP status and configuration
vrf	(Optional) Virtual Router Context
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
summary	Display summarized information of BGP state
ipv4	Display BGP information for IPv4 address family
vpnv4	Display BGP information for VPNv4 address family
vpnv6	Display BGP information for VPNv6 address family
ipv6	Display BGP information for IPv6 address family
unicast	Display BGP information for unicast address family
multicast	Display BGP information for multicast address family
labeled-unicast	Display BGP information for labeled-unicast address family
mdt	Display BGP information for multicast distribution tree

link-state	Display BGP information for link-state address family
l2vpn	Display BGP information for L2VPN address family
vpls	Display BGP information for L2VPN VPLS address family
mvpn	Display BGP information for MVPN address family
evpn	Display BGP information for L2VPN EVPN address family
all	Display BGP information for all address families
__readonly__	(Optional)
TABLE_vrf	(Optional)
vrf-name-out	(Optional) VRF name
vrf-id	(Optional) VRF ID
vrf-state	(Optional) VRF State
vrf-state-rsn	(Optional) VRF State Reason
vrf-delete-pending	(Optional) VRF delete pending
vrf-evpn-mpls	(Optional) VRF EVPN L3 MPLS
vrf-vni-id	(Optional) VRF VNI ID
vrf-vni-id-valid	(Optional) VRF VNI ID validity
vrf-topo-id	(Optional) VRF Topo ID
vrf-encap-type	(Optional) VRF encapsulation type
vrf-vtep-ip	(Optional) VRF VTEP IP
vrf-vtep-virtual-ip	(Optional) VRF VTEP Virtual IP
vrf-vtep-vipr	(Optional) VRF VTEP Virtual IP for Re-origination
vrf-router-mac	(Optional) VRF Router MAC
vrf-vip-router-mac	(Optional) VRF VIP Router MAC
vrf-vipr-router-mac	(Optional) VRF VIPR Router MAC
vrf-router-id	(Optional) Router ID
vrf-cfgd-id-auto	(Optional) Configured Router-ID Auto
vrf-cfgd-id	(Optional) Configured Router-ID
vrf-if-router-id	(Optional) Interface Router-ID
vrf-local-as	(Optional) Local AS

<i>vrf-confed-id</i>	(Optional) Cluster-ID
<i>vrf-cluster-id</i>	(Optional) Cluster-ID
<i>vrf-reconnect-interval</i>	(Optional) VRF reconnect interval
<i>vrf-peers</i>	(Optional) No. of configured peers
<i>vrf-pending-peers</i>	(Optional) No. of pending peers
<i>vrf-est-peers</i>	(Optional) No. of established peers
<i>vrf-cfgd-max-as-limit</i>	(Optional) Configured maxas-limit
<i>vrf-max-as-limit</i>	(Optional) Active maxas-limit
<i>vrf-rd-configured</i>	(Optional) VRF RD Configured
<i>vrf-rd</i>	(Optional) VRF RD
<i>vrf-secondary-rd-configured</i>	(Optional) VRF Secondary RD Configured
<i>vrf-secondary-rd</i>	(Optional) VRF Secondary RD
<i>vrf-pending-rd</i>	(Optional) VRF pending RD
<i>vrf-pending-secondary-rd</i>	(Optional) VRF pending secondary RD
TABLE_af	(Optional)
<i>af-id</i>	(Optional) AF ID
<i>af-table-id</i>	(Optional) AF table
<i>af-name</i>	(Optional) AF table name
<i>af-state</i>	(Optional) AF table state
<i>af-state-rsn</i>	(Optional) AF table state reason
<i>af-num-peers</i>	(Optional) No. of peers
<i>af-num-active-peers</i>	(Optional) No. of active peers
<i>af-peer-routes</i>	(Optional) No. of peer routes
<i>af-peer-paths</i>	(Optional) No. of peer paths
<i>af-peer-networks</i>	(Optional) No. of peer networks
<i>af-peer-aggregates</i>	(Optional) No. of aggregates
<i>af-export-rmap</i>	(Optional) Export route-map
<i>af-import-rmap</i>	(Optional) Import route-map
<i>af-retain-rt</i>	(Optional) Retain RT

TABLE_saf	(Optional)
<i>safi</i>	(Optional)
<i>af-name</i>	(Optional)
<i>tableversion</i>	(Optional)
<i>configuredpeers</i>	(Optional)
<i>capablepeers</i>	(Optional)
<i>totalnetworks</i>	(Optional)
<i>totalpaths</i>	(Optional)
<i>memoryused</i>	(Optional)
<i>numberattrs</i>	(Optional)
<i>bytesattrs</i>	(Optional)
<i>numberpaths</i>	(Optional)
<i>bytespaths</i>	(Optional)
<i>numbercommunities</i>	(Optional)
<i>bytescommunities</i>	(Optional)
<i>numberclusterlist</i>	(Optional)
<i>bytesclusterlist</i>	(Optional)
<i>dampening</i>	(Optional)
<i>historypaths</i>	(Optional)
<i>dampenedpaths</i>	(Optional)
<i>softreconfigrecvdpaths</i>	(Optional)
<i>softreconfigidenticalpaths</i>	(Optional)
<i>softreconfigcombopaths</i>	(Optional)
<i>softreconfigfilteredrecvd</i>	(Optional)
<i>softreconfigbytes</i>	(Optional)
TABLE_neighbor	(Optional)
<i>neighborid</i>	(Optional)
<i>neighborversion</i>	(Optional)
<i>neighboras</i>	(Optional)

<i>msgrecvd</i>	(Optional)
<i>msgsent</i>	(Optional)
<i>neighbortableversion</i>	(Optional)
<i>inq</i>	(Optional)
<i>outq</i>	(Optional)
<i>time</i>	(Optional)
<i>state</i>	(Optional)
<i>prefixreceived</i>	(Optional)
<i>interface-parent</i>	(Optional)

Command Mode

- /exec

show boot

```
show boot [ __readonly__ { [ TABLE_bootvar_show <Str1> ] [ TABLE_Current_Bootvar
<current_sup_module> <current_image> [ <current_sup_module> ] [ <current_image> ] <current_poap_status>
+ [ <current_exclude_cfg> ] ] [ TABLE_Startup_Bootvar <start_sup_module> <start_image> [
<start_sup_module> ] [ <start_image> ] <start_poap_status> + [ <configured_exclude_cfg> ] ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_show	(Optional) Bootvar table
TABLE_Current_Bootvar	(Optional) Table for current boot variables
TABLE_Startup_Bootvar	(Optional) Table for boot variables on next reload
<i>Str1</i>	(Optional)
<i>current_sup_module</i>	(Optional) Current boot variable supervisor module
<i>current_image</i>	(Optional) Current image set for boot variable
<i>current_poap_status</i>	(Optional) Current status for poap
<i>current_exclude_cfg</i>	(Optional) current value of exclude_cfg
<i>start_sup_module</i>	(Optional) Next reload supervisor module
<i>start_image</i>	(Optional) Next reload boot variable
<i>start_poap_status</i>	(Optional) Next reload poap status
<i>configured_exclude_cfg</i>	(Optional) configured value of exclude_cfg in running config

Command Mode

- /exec

show boot auto-copy

```
show boot auto-copy [ __readonly__ { [ TABLE_auto_copy <Str1> <status> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autocopy is turned on
__readonly__	(Optional)
TABLE_auto_copy	(Optional) Auto copy table
<i>Str1</i>	(Optional)
<i>status</i>	(Optional) status of auto copy is enable/disable

Command Mode

- /exec

show boot auto-copy list

show boot auto-copy list [__readonly__ { [TABLE_auto_copy_list <Str1> <file>] }]

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
auto-copy	See if autcopy is turned on
list	Show the list of files to be auto-copied
__readonly__	(Optional)
TABLE_auto_copy_list	(Optional) Auto copy table
<i>Str1</i>	(Optional)
<i>file</i>	(Optional) file in the auto copy list

Command Mode

- /exec

show boot current

```
show boot current [ __readonly__ { [ TABLE_bootvar_current <Str1> ] [ TABLE_current_bootvar
<current_sup_module> <current_image> [ <current_sup_module> ] [ <current_image> ] ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
current	Show Current Bootvar Variables
__readonly__	(Optional)
TABLE_bootvar_current	(Optional) Bootvar current table
TABLE_current_bootvar	(Optional) Current booted image table
<i>Str1</i>	(Optional)
<i>current_sup_module</i>	(Optional) Current boot variable supervisor module
<i>current_image</i>	(Optional) Current image set for boot variable

Command Mode

- /exec

show boot mode

```
show boot mode [ __readonly__ { [ TABLE_mode <Str1> <current_boot_mode> [ <configured_boot_mode> ] ] } ]
```

Syntax Description

show	Show boot mode information
boot	Show boot mode
mode	See if lxc boot is turned on
<i>__readonly__</i>	(Optional)
<i>TABLE_mode</i>	(Optional) boot mode table
<i>Str1</i>	(Optional)
<i>current_boot_mode</i>	(Optional) current running boot mode
<i>configured_boot_mode</i>	(Optional) configured boot mode in running config

Command Mode

- /exec

show boot order

```
show boot order [ __readonly__ { [ TABLE_bootvar_order <Str1> ] [ TABLE_boot_order <current_order>
<next_order> ] } ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
order	Show Boot Order
__readonly__	(Optional)
TABLE_bootvar_order	(Optional) Boot order table
TABLE_boot_order	(Optional) Current boot order table
<i>Str1</i>	(Optional)
<i>current_order</i>	(Optional) order of the boot location
<i>next_order</i>	(Optional) order of the boot location

Command Mode

- /exec

show boot timings

show [system internal] boot timings [detail]

Syntax Description

show	Show running system information
system	(Optional) System-related show commands
internal	(Optional) Commands for internal use
boot	show boot information
timings	show boot timings
detail	(Optional) show detailed time statistics

Command Mode

- /exec

show boot variables

```
show boot variables [ __readonly__ { [ TABLE_boot_vars <Str1> <boot_variable> } ] ]
```

Syntax Description

show	Show running system information
boot	Show Bootvar Variables
variables	Display the list of boot variables
__readonly__	(Optional)
TABLE_boot_vars	(Optional) Show boot variables table
<i>Str1</i>	(Optional)
<i>boot_variable</i>	(Optional) available boot variable

Command Mode

- /exec

show buffer-drop detail

```
show buffer-drop detail [ __readonly__ <system-monitor-name> <monitor-name> <collector-name>
<v4-acl-name> <v6-acl-name> <queue-id> <sampler-prob-rate> <sampler-mb-rate> <sampler-mb-pkts> ]
```

Syntax Description

show	Show running system information
buffer-drop	Show Buffer Drop information
detail	Show Session Configuration
<i>__readonly__</i>	(Optional) Read only
<i>system-monitor-name</i>	(Optional) system monitor name
<i>monitor-name</i>	(Optional) monitor name
<i>collector-name</i>	(Optional) collector name
<i>v4-acl-name</i>	(Optional) v4 acl name
<i>v6-acl-name</i>	(Optional) v6 acl name
<i>queue-id</i>	(Optional) queue id
<i>sampler-prob-rate</i>	(Optional) sampler probabilistic rate
<i>sampler-mb-rate</i>	(Optional) sampler mb rate
<i>sampler-mb-pkts</i>	(Optional) sampler mb max pkts

Command Mode

- /exec

show buffer-latency detail

```
show buffer-latency detail [ __readonly__ <system-monitor-name> <monitor-name> <collector-name>
<record-name> <v4-acl-name> <v6-acl-name> <queue-id> <interface> <latency-threshold>
<sampler-prob-rate> <sampler-mb-rate> <sampler-mb-pkts> ]
```

Syntax Description

show	Show running system information
buffer-latency	Show Buffer Drop information
detail	Show Session Configuration
<i>__readonly__</i>	(Optional) Read only
<i>system-monitor-name</i>	(Optional) system monitor name
<i>monitor-name</i>	(Optional) monitor name
<i>collector-name</i>	(Optional) collector name
<i>record-name</i>	(Optional) record name
<i>v4-acl-name</i>	(Optional) v4 acl name
<i>v6-acl-name</i>	(Optional) v6 acl name
<i>queue-id</i>	(Optional) queue id
<i>interface</i>	(Optional) interface
<i>latency-threshold</i>	(Optional) latency threshold
<i>sampler-prob-rate</i>	(Optional) sampler probabilistic rate
<i>sampler-mb-rate</i>	(Optional) sampler mb rate
<i>sampler-mb-pkts</i>	(Optional) sampler mb max pkts

Command Mode

- /exec

show buffer-latency detail