



Creating SSL Certificates to Use with SD-AVC

- [Summary, on page 1](#)
- [Using a Certificate Signed by a Certification Authority, on page 2](#)
- [Using a Self-signed SSL Certificate Created with Keytool, on page 2](#)
- [Using a Self-signed SSL Certificate Created with OpenSSL, on page 4](#)

Summary

Create certificate to be signed by certification authority

	Task	Where to find...
1	Create certificate keys.	See Using a Certificate Signed by a Certification Authority, on page 2 .
2	Generate a certificate signing request (CSR).	
3	Send the CSR file to be signed by the certification authority.	
4	Install the signed certificate in the SD-AVC Dashboard.	See "Serviceability Page" in Using SD-AVC .

Create self-signed certificate

	Task	Where to find...
1	Create self-signed certificate keys.	See Using a Self-signed SSL Certificate Created with Keytool, on page 2 . See Using a Self-signed SSL Certificate Created with OpenSSL, on page 4 .
2	Install the signed certificate in the SD-AVC Dashboard.	See "Serviceability Page" in Using SD-AVC .

Using a Certificate Signed by a Certification Authority

You can use the **keytool** or **OpenSSL** command line utilities to create a certificate to be signed by a certification authority, and used with Cisco SD-AVC.

Using Keytool

1. Create certificate keys.

Example:

```
keytool -genkey -alias sdavc_alias -keyalg RSA -sigalg SHA1withRSA -keysize 2048 -keystore mykeystore.keystore
```

2. Generate a certificate signing request (CSR).

Example:

```
keytool -certreq -alias sdavc_alias -keyalg RSA -sigalg SHA1withRSA -file mycsrfile.csr -keystore mykeystore.keystore
```

The command produces a CSR file called **mycsrfile.csr**.

3. Send the CSR file to be signed by the certification authority.
4. Install the signed certificate in the SD-AVC Dashboard. See "Serviceability Page" in [Using SD-AVC](#).

Using OpenSSL

1. Create certificate keys.

Example:

```
openssl genrsa -des3 -out server.key 2048
```

2. Generate a certificate signing request (CSR).

Example:

```
openssl req -new -key server.key -sha256 -out server.csr
```

3. Send the CSR file to be signed by the certification authority.
4. Install the signed certificate in the SD-AVC Dashboard. See "Serviceability Page" in [Using SD-AVC](#).

Using a Self-signed SSL Certificate Created with Keytool

You can use the **keytool** command line utility to create a self-signed certificate, and use the certificate with Cisco SD-AVC.

This utility creates certificates in [Java KeyStore \(JKS\)](#) format.

The example shows how to create a self-signed certificate and how to display the details of the certificate. Details such as alias are required when configuring SD-AVC to use the certificate.



Note Keytool is not a Cisco product. The brief guidelines provided here are for convenience. Complete information is available online.

Creating and Installing the SSL Certificate

This example shows the command, followed by interactive input. It creates a certificate with:

- **Alias:** abc_ssl
- **Passphrase:** 123456

1. Create certificate keys.

```
keytool -genkey -keyalg RSA -alias abc_ssl -keystore my_keystore.jks -storepass 123456
-validity 360 -keysize 2048
What is your first and last name?
[Unknown]: hostname.cisco.com
What is the name of your organizational unit?
[Unknown]: dev
What is the name of your organization?
[Unknown]: cisco
What is the name of your City or Locality?
[Unknown]: san-jose
What is the name of your State or Province?
[Unknown]: ca
What is the two-letter country code for this unit?
[Unknown]: us
Is CN=hostname.cisco.com, OU=dev, O=cisco, L=san-jose, ST=ca, C=us correct? (type "yes"
or "no")
[no]: yes

Enter key password for <abc_ssl>:
(RETURN if same as keystore password):
```

2. Install the signed certificate in the SD-AVC Dashboard. See "Serviceability Page" in [Using SD-AVC](#).

Viewing the Certificate Details

View the certificate details. Note that the output includes the alias name (which may be a default value, or a specified custom alias name, as in this example), and keystore type (jks in this example).

```
1. keytool -list -v -keystore my_keystore.jks
Enter keystore password:

Keystore type: jks
Keystore provider: IBMJCE

Your keystore contains 1 entry

Alias name: abc_ssl
Creation date: Apr 30, 2019
Entry type: keyEntry
Certificate chain length: 1
Certificate[1]:
Owner: CN=hostname.cisco.com, OU=dev, O=cisco, L=san-jose, ST=ca, C=us
Issuer: CN=hostname.cisco.com, OU=dev, O=cisco, L=san-jose, ST=ca, C=us
Serial number: 5cc899de
Valid from: 4/30/19 9:54 PM until: 4/24/20 9:54 PM
```

```

Certificate fingerprints:
    MD5:  38:B7:B4:28:43:48:11:88:C5:B1:E0:47:79:26:CD:A7
    SHA1: 7C:60:01:35:26:67:40:64:65:D0:E2:B5:2B:30:1F:7D:5E:16:44:C3
    SHA256:
42:82:63:BF:CF:87:95:B7:5A:FA:38:12:45:F9:88:D5:FD:00:68:A8:96:28:63:32:0C:D4:E5:A0:86:68:25:53

    Signature algorithm name: SHA256withRSA
    Version: 3

```

Using a Self-signed SSL Certificate Created with OpenSSL

You can use the **OpenSSL** command line utility to create a self-signed certificate, and use the certificate with Cisco SD-AVC.

This utility creates certificates in numerous formats.

The example shows how to create a certificate and how to display the details of the certificate. Details such as alias/friendlyName, are required when configuring SD-AVC to use the certificate.



Note OpenSSL is not a Cisco product. The brief guidelines provided here are for convenience. Complete information is available online.

Creating and Installing the SSL Certificate

This example shows the command, followed by interactive input. It creates and exports a certificate with:

- **Alias/friendlyName:** abc_ssl
- **Output filename:** my_cakey.pem

1. Create certificate keys.

```

openssl req -newkey rsa:2048 -x509 -keyout my_cakey.pem -out my_cacert.pem -days 3650
Generating a 2048 bit RSA private key
.....+++
...+++
writing new private key to 'my_cakey.pem'
Enter PEM pass phrase:
Verifying - Enter PEM pass phrase:
-----
You are about to be asked to enter information that will be incorporated
into your certificate request.
What you are about to enter is what is called a Distinguished Name or a DN.
There are quite a few fields but you can leave some blank
For some fields there will be a default value,
If you enter '.', the field will be left blank.
-----
Country Name (2 letter code) [AU]:us
State or Province Name (full name) [Some-State]:
Locality Name (eg, city) []:city
Organization Name (eg, company) [Internet Widgits Pty Ltd]:
Organizational Unit Name (eg, section) []:
Common Name (e.g. server FQDN or YOUR name) []:hostname.cisco.com
Email Address []:anyEmail@cisco.com

openssl pkcs12 -export -in my_cacert.pem -inkey my_cakey.pem -out my_identity.p12 -name

```

```
"abc_ssl"  
Enter pass phrase for my_cakey.pem:  
Enter Export Password:  
Verifying - Enter Export Password:
```

2. Convert the format.

```
openssl pkcs12 -export -in my_cacert.pem -inkey my_cakey.pem -out my_identity.p12 -name  
"abc_ssl"  
Enter pass phrase for my_cakey.pem:  
Enter Export Password:  
Verifying - Enter Export Password:
```

3. Install the signed certificate in the SD-AVC Dashboard. See "Serviceability Page" in [Using SD-AVC](#).

Viewing the Certificate Details

View the certificate details. Note that this command provides the alias/friendlyName, which may be a default value, or a specified custom alias name, as in this example.

```
1. openssl pkcs12 -info -in my_identity.p12  
Enter Import Password:  
MAC Iteration 2048  
MAC verified OK  
PKCS7 Encrypted data: pbeWithSHA1And40BitRC2-CBC, Iteration 2048  
Certificate bag  
Bag Attributes  
    localKeyID: 2E 12 BE F7 56 D3 1D C0 39 9A 52 29 AD 18 3A 95 05 AA A5 86  
    friendlyName: abc_ssl
```

