



S through U

- [set active-probe](#), page 3
- [set backoff](#), page 6
- [set delay](#), page 8
- [set holddown](#), page 10
- [set interface \(OER\)](#), page 12
- [set jitter](#), page 14
- [set link-group](#), page 16
- [set loss](#), page 18
- [set mode](#), page 20
- [set mos](#), page 24
- [set next-hop \(OER\)](#), page 26
- [set periodic](#), page 28
- [set probe](#), page 30
- [set resolve](#), page 32
- [set traceroute reporting](#), page 35
- [set unreachable](#), page 37
- [show oer api client](#), page 39
- [show oer api provider](#), page 42
- [show oer border](#), page 45
- [show oer border active-probes](#), page 47
- [show oer border defined application](#), page 49
- [show oer border passive applications](#), page 51
- [show oer border passive cache](#), page 53
- [show oer border passive learn](#), page 56
- [show oer border passive prefixes](#), page 58
- [show oer border routes](#), page 60
- [show oer master](#), page 65
- [show oer master active-probes](#), page 68
- [show oer master appl](#), page 71
- [show oer master border](#), page 75
- [show oer master cost-minimization](#), page 80
- [show oer master defined application](#), page 83
- [show oer master learn list](#), page 85
- [show oer master link-group](#), page 87
- [show oer master nbar application](#), page 89

- [show oer master policy, page 92](#)
- [show oer master prefix, page 96](#)
- [show oer master traffic-class, page 105](#)
- [show oer master traffic-class application nbar, page 111](#)
- [show oer proxy, page 115](#)
- [shutdown \(OER\), page 117](#)
- [throughput, page 119](#)
- [traceroute probe-delay, page 121](#)
- [traffic-class access-list, page 123](#)
- [traffic-class aggregate, page 125](#)
- [traffic-class application, page 128](#)
- [traffic-class application nbar, page 132](#)
- [traffic-class filter, page 135](#)
- [traffic-class keys, page 137](#)
- [traffic-class prefix-list, page 139](#)
- [unreachable, page 141](#)

set active-probe

To configure an Optimized Edge Routing (OER) map active probe with a forced target assignment, use the **set active-probe** command in OER map configuration mode. To disable the active probe, use the **no** form of this command.

```
set active-probe probe-type ip-address [target-port number] [codec codec-name] [dscp value]
```

```
no set active-probe probe-type ip-address
```

Syntax Description

<i>probe-type</i>	Type of probe. Must be one of the following: <ul style="list-style-type: none"> • echo --Uses Internet Control Message Protocol (ICMP) echo (ping) messages. • jitter --Uses jitter messages. • tcp-conn --Uses TCP connection messages. • udp-echo --Uses User Datagram Protocol (UDP) echo messages.
<i>ip-address</i>	Target IP address of a prefix to be monitored using the specified type of probe.
target-port	(Not specified for echo probes.) Specifies the destination port number for the active probe. A remote responder must be configured on the target device with the ip sla monitor responder global configuration command. <p>Note The ip sla monitor responder command was introduced in Cisco IOS Release 12.3(14)T. This command replaces the rtr responder command.</p>
<i>number</i>	Port number in the range from 1 to 65535.
codec	(Optional) Only used with the jitter probe type. Specifies the codec value used for Mean Opinion Score (MOS) calculation.
<i>codec-name</i>	Codec value, must be one of the following: <ul style="list-style-type: none"> • g711alaw--G.711 A Law 64000 bps • g711ulaw--G.711 U Law 64000 bps • g729a--G.729 8000 bps
dscp	(Optional) Sets the Differentiated Services Code Point (DSCP) value.
<i>value</i>	DSCP value.

Command Default No active probes are configured with a forced target assignment.

Command Modes OER map configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
15.0(1)M	This command was modified. The dscp keyword and <i>value</i> argument were added.
12.2(33)SRE	This command was modified. The dscp keyword and <i>value</i> argument were added.

Usage Guidelines

Cisco IOS Release 15.0(1)M, 12.2(33)SRE, and Later Releases

If the optional **dscp** keyword and *value* argument are not specified, active probes are created using the DSCP value of the traffic class. For example, the software creates two sets of probes for the following three traffic classes. Traffic class 2 is assigned a probe with a DSCP value of “ef” and the other two traffic classes share a probe with a DSCP value of 0.

- Traffic class 1: 10.1.1.0/24, destination port 23
- Traffic class 2: 10.1.2.0/24, dscp ef
- Traffic class 3: 10.1.2.0/24, destination port 991

If the optional **dscp** keyword and *value* argument is provided, probes are created using the specified DSCP value. For example, if the DSCP value specified for the **set active-probe** command is “cs1”, only one probe is created for the three traffic classes.

Examples

The following example shows how to configure an ICMP reply (ping) message probe with a forced target assignment within an OER map. The 10.1.2.10 address is the forced target assignment. A remote responder must also be enabled on the target device.

```
Router(config)# oer-map MAP1 10
Router(config-oer-map)# match ip prefix-list LIST1
Router(config-oer-map)# set active-probe echo 10.1.2.10
```

The following example shows how to configure a TCP connection message probe with a forced target assignment within an PFR map. The 10.1.2.10 address is the forced target assignment, the target port is defined as 29, and the DSCP value is set to ef. A remote responder must be enabled on the target device. This example requires Cisco IOS Release 15.0(1)M, 12.2(33)SRE, or a later release.

```
Router(config)# pfr-map MAP2 10
Router(config-pfr-map)# match ip prefix-list LISTMAP2
Router(config-pfr-map)# set active-probe tcp-conn 10.1.2.10 target-port 29 dscp ef
```

Related Commands

Command	Description
active-probe	Configures an OER active probe for a target prefix.
ip sla monitor responder	Enables the IP SLAs Responder for general IP SLAs operations.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
show oer border active-probes	Displays connection and status information about active probes on an OER border router.
show oer master active-probes	Displays connection and status information about active probes on an OER master controller.

set backoff

To configure an Optimized Edge Routing (OER) map to set the backoff timer to adjust the time period for prefix policy decisions, use the **set backoff** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set backoff *min-timer max-timer [step-timer]*

no set backoff

Syntax Description

<i>min-timer</i>	Minimum value for the backoff timer, in seconds. The configurable time period for this argument is from 180 to 7200. The default timer value is 300.
<i>max-timer</i>	Maximum value for the backoff timer, in seconds. The configurable time period for this argument is from 180 to 7200. The default timer value is 3000.
<i>step-timer</i>	(Optional) Time period value for the step timer, in seconds. The step timer is used to add time to the out-of-policy waiting period each time the backoff timer expires and OER is unable to find an in-policy exit. The configurable time period for this argument is from 180 to 7200. The default timer value is 300.

Command Default

OER uses the following default values if this command is not configured or if the **no** form of this command is entered:

min-timer : 300 *max-timer*: 3000 *step-timer*: 300

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set backoff** command is entered on a master controller in OER map configuration mode. This command is used to configure an OER map to set the transition period that the master controller holds an out-of-policy prefix. The master controller uses a backoff timer to schedule the prefix transition period in which OER holds the out-of-policy prefix before moving the prefix to an in-policy state by selecting an in-policy exit. This command is configured with a minimum and maximum timer value and can be configured with an optional step timer.

Minimum Timer --The *min-timer* argument is used to set the minimum transition period in seconds. If the current prefix is in-policy when this timer expires, no change is made and the minimum timer is reset to the default or configured value. If the current prefix is out-of-policy, OER will move the prefix to an in-policy and reset the minimum timer to the default or configured value.

Maximum Timer --The *max-timer* argument is used to set the maximum length of time OER holds an out-of-policy prefix when there are no OER controlled in-policy prefixes. If all OER controlled prefixes are in an out-of-policy state and the value from the *max-timer* argument expires, OER will select the best available exit and reset the minimum timer to the default or configured value.

Step Timer --The *step-timer* argument allows you to optionally configure OER to add time each time the minimum timer expires until the maximum time limit has been reached. If the maximum timer expires and all OER managed exits are out-of-policy, OER will install the best available exit and reset the minimum timer.

Configuring a new timer value will immediately replace the existing value if the new value is less than the time remaining. If the new value is greater than the time remaining, the new timer value will be used when the existing timer value expires.

Examples

The following example creates an OER map named BACKOFF that sets the minimum timer to 400 seconds, the maximum timer to 4000 seconds, and the step timer to 400 seconds for traffic from the prefix list named CUSTOMER:

```
Router(config)# oer-map BACKOFF 70
Router(config-oer-map)# match ip address prefix-list CUSTOMER
Router(config-oer-map)# set backoff 400 4000 400
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
periodic (OER)	Sets the backoff timer to adjust the time period for prefix policy decisions.

set delay

To configure an Optimized Edge Routing (OER) map to configure OER to set the delay threshold, use the **set delay** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set delay {relative percentage | threshold maximum}
no set delay
```

Syntax Description

relative percentage	Sets a relative delay policy based on a comparison of short-term and long-term delay percentages. The range of values that can be configured for this argument is a number from 1 to 1000. Each increment represents one tenth of a percent.
threshold maximum	Sets the absolute maximum delay time, in milliseconds. The range of values that can be configured for this argument is from 1 to 10000.

Command Default

OER uses the following default value if this command is not configured or if the **no** form of this command is entered:

```
relative percentage : 500 (50 percent)
```

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set delay** command is entered on a master controller in OER map configuration mode. This command is configured in an OER map to set the delay threshold as a relative percentage or as an absolute value for match criteria.

The **relative** keyword is used to configure a relative delay percentage. The relative delay percentage is based on a comparison of short-term and long-term measurements. The short-term measurement reflects the delay percentage within a 5-minute time period. The long-term measurement reflects the delay percentage within a 60-minute period. The following formula is used to calculate this value:

Relative delay measurement = ((short-term measurement - long-term measurement) / long-term measurement) * 100

The master controller measures the difference between these two values as a percentage. If the percentage exceeds the user-defined or default value, the delay percentage is determined to be out-of-policy. For example, if long-term delay measurement 100 milliseconds and short-term delay measurement is 120 milliseconds, the relative delay percentage is 20 percent.

The **threshold** keyword is used to configure the absolute maximum delay period in milliseconds.

If the measured delay of the prefix is higher than the configured delay threshold, then the prefix is out-of-policy. If the short-term delay of the prefix is more than long-term delay by the percentage value configured, then the prefix is out-of-policy.

Examples

The following example creates an OER map named DELAY that sets the absolute maximum delay threshold to 2000 milliseconds for traffic from the prefix list named CUSTOMER:

```
Router(config)# oer-map DELAY 80
Router(config-oer-map)# match ip address prefix-list CUSTOMER

Router(config-oer-map)# set delay threshold 2000
```

Related Commands

Command	Description
delay	Configures configure prefix delay parameters.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set holddown

To configure an OER map to set the prefix route dampening timer for the minimum period of time in which a new exit must be used before an alternate exit can be selected, use the **set holddown** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set holddown *timer*
no set holddown

Syntax Description

<i>timer</i>	Sets the prefix route dampening time period, in seconds. The range for this argument is from 90 to 65535. The default value is 300.
--------------	---

Command Default

OER uses the following default value if this command is not configured or if the no form of this command is entered:

timer : 300 seconds

Command Modes

OER map configuration (config-oer-map)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set holddown** command is entered on a master controller in OER map configuration mode. This command is used to configure the prefix route dampening timer for the minimum period of time in which a new exit must be used before an alternate exit can be selected. The master controller puts a prefix in a holddown state during an exit change to isolate the prefix during the transition period, preventing the prefix from flapping because of rapid state changes. OER does not implement policy changes while a prefix is in the holddown state. A prefix will remain in a holddown state for the default or configured time period.

When the holddown timer expires, OER will select the best exit based on performance and policy configuration. However, an immediate route change will be triggered if the current exit for a prefix becomes unreachable.

Configuring a new timer value will immediately replace the existing value if the new value is less than the time remaining. If the new value is greater than the time remaining, the new timer value will be used when the existing timer is reset.

Examples

The following example creates an OER map named HOLDDOWN that sets the holddown timer to 120 seconds for traffic from the prefix list named CUSTOMER:

```
Router(config)# oer-map HOLDDOWN 10
Router(config-oer-map)# match ip address prefix-list CUSTOMER
Router(config-oer-map)# set holddown 120
```

Related Commands

Command	Description
holddown	Configures the prefix route dampening timer to set the minimum period of time that a new exit must be used before an alternate exit can be selected.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set interface (OER)

To configure an Optimized Edge Routing (OER) map to send packets that match prefixes in an access list on OER border routers to the null interface, use the **set interface** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set interface null0
no set interface null0
```

Syntax Description

null0	Specifies that packets will be sent to the null interface, which means that the packets are discarded.
--------------	--

Command Default

No packets are sent to the null interface.

Command Modes

OER map configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set interface** command is entered on a master controller in OER map configuration mode. This command can be used for OER black hole filtering if the border routers detect a denial-of-service (DoS) attack by directing packets to the null interface. The null interface is a virtual network interface that is similar to the loopback interface. Whereas traffic to the loopback interface is directed to the router itself, traffic sent to the null interface is discarded. This interface is always up and can never forward or receive traffic; encapsulation always fails. The null interface functions similarly to the null devices available on most operating systems. Null interfaces are used as a low-overhead method of discarding unnecessary network traffic.

Examples

The following example shows how to configure an OER map named `BLACK_HOLE_MAP` that directs packets to the null interface. To use this configuration for a DoS attack, leave the access list empty until an attack is detected and add the prefix or prefixes that are determined to be the source of the attack. Subsequent packets received from the specified prefix or prefixes will be discarded.

```
Router(config)# oer-map black-hole-map 10
```

```
Router(config-oer-map)# match ip address access-list black-hole-list
Router(config-oer-map)# set interface null0
```

Related Commands

Command	Description
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
set next-hop (OER)	Configures an OER map to send packets that match prefixes in an access list on OER border routers to the specified next hop.

set jitter

To configure an Optimized Edge Routing (OER) map to set the maximum jitter value that OER will permit for an exit link, use the **set jitter** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set jitter threshold *maximum*

no set jitter threshold *maximum*

Syntax Description

threshold	Specifies a maximum absolute threshold value for jitter. Jitter is a measure of voice quality.
<i>maximum</i>	Number (in milliseconds) in the range from 1 to 1000, where 1 represents the highest voice quality, and 1000 represents the lowest voice quality. The default value is 30.

Command Default

No jitter values are specified.

Command Modes

OER map configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set jitter** command is entered on a master controller in OER map configuration mode. This command is used to specify the maximum tolerable jitter value permitted on an exit link. Jitter is a measure of voice quality where the lower the jitter value, the higher the voice quality. If the jitter value is greater than the user-defined or the default value, OER determines that the exit link is out-of-policy and searches for an alternate exit link.

Another measure of voice quality is the estimated Mean Opinion Score (MOS). Use the **set mos** command and the **set jitter** command in an OER map to define voice quality.

Examples

The following example shows how to configure an OER map named JITTER that sets the threshold jitter value. If the jitter threshold value exceeds 20 milliseconds, the master controller searches for a new exit link.

```
Router(config)# oer-map JITTER 10
Router(config-oer-map)# set jitter threshold 20
```

Related Commands

Command	Description
jitter	Specifies the threshold jitter value that OER will permit for an exit link.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
set mos	Configures an OER map to specify the threshold and percentage Mean Opinion Score (MOS) values that OER will permit for an exit link.

set link-group

To specify a link group for traffic classes defined in an Optimized Edge Routing (OER) policy, use the **set link-group** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set link-group *link-group-name* [**fallback** *link-group-name*]

no set link-group *link-group-name*

Syntax Description

<i>link-group-name</i>	Name of link group.
fallback	(Optional) Specifies a fallback link group to be used if the primary link group is out-of-policy (OOP).

Command Default

No link groups are specified for a traffic class.

Command Modes

OER map configuration (config-*oer-map*)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **set link-group** command is entered on a master controller in OER map configuration mode. This command is used to define a link group for the traffic class matched in an OER map.

Introduced in Cisco IOS Release 12.4(15)T, link groups are used to define a group of exit links as a preferred set of links or a fallback set of links for OER to use when optimizing traffic classes specified in an OER policy. Up to three link groups can be specified for each interface. Use the **link-group** command to define the link group for an interface and use the **set link-group** command to define the primary link group and a fallback link group for a specified traffic class in an OER map.

Use the **show oer master link-group** command to view information about configured OER link groups.

Examples

The following example shows how to configure an OER map named `link_video_map` that configures OER to create a traffic class that matches an access list named `video_list`. The traffic class is configured to use a link group named `video` as the primary link group, and a fallback group named `voice`. The video link group may be a set of high bandwidth links that are preferred for video traffic.

```
Router(config)# oer-map link_video_map 10
```



```
Router(config-oer-map)# match ip address access-list video_list
Router(config-oer-map)# set link-group video fallback voice
```

Related Commands

Command	Description
link-group	Configures an OER border router exit interface as a member of a link group.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
show oer master link-group	Displays information about OER link groups.

set loss

To configure an OER map to set the relative or maximum packet loss limit that OER will permit for an exit link, use the **set loss** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set loss {relative average | threshold maximum}
no set loss
```

Syntax Description

relative <i>average</i>	Sets a relative percentage of packet loss based on a comparison of short-term and long-term packet loss percentages. The range of values that can be configured for this argument is a number from 1 to 1000. Each increment represents one tenth of a percent.
threshold <i>maximum</i>	Sets absolute packet loss based on packets per million (PPM). The range of values that can be configured for this argument is from 1 to 1000000.

Command Default

OER uses the following default value if this command is not configured or if the no form of this command is entered:

relative *average* : 100 (10 percent)

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set loss** command is entered on a master controller in OER map configuration mode. This command is used to configure an OER map to set the relative percentage or maximum number of packets that OER will permit to be lost during transmission on an exit link. If packet loss is greater than the user-defined or the default value, OER determines that the exit link is out-of-policy and searches for an alternate exit link.

The **relative** keyword is used to configure the relative packet loss percentage. The relative packet loss percentage is based on a comparison of short-term and long-term packet loss. The short-term measurement

reflects the percentage of packet loss within a 5-minute period. The long-term measurement reflects the percentage of packet loss within a 60-minute period. The following formula is used to calculate this value:

$$\text{Relative packet loss} = ((\text{short-term loss} - \text{long-term loss}) / \text{long-term loss}) * 100$$

The master controller measures the difference between these two values as a percentage. If the percentage exceeds the user-defined or default value, the exit link is determined to be out-of-policy. For example, if long-term packet loss is 200 PPM and short-term packet loss is 300 PPM, the relative loss percentage is 50 percent.

The **threshold** keyword is used to configure the absolute maximum packet loss. The maximum value is based on the actual number of PPM that have been lost.

Examples

The following example creates an OER map named LOSS that sets the relative percentage of acceptable packet loss for traffic from the prefix list named CUSTOMER to a 20 percent relative percentage. If the packet loss on the current exit link exceeds 20 percent, the master controller will search for a new exit.

```
Router(config)# oer-map LOSS 10
Router(config-oer-map)# match ip address prefix-list CUSTOMER
Router(config-oer-map)# set loss relative 200
```

Related Commands

Command	Description
loss	Sets the relative or maximum packet loss limit that OER will permit for an exit link.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set mode

To configure an Optimized Edge Routing (OER) map to configure route monitoring, route control, or exit selection for matched traffic, use the **set mode** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set mode {monitor {active [throughput] | both | fast | passive} | route {control | observe} | select-exit {best | good}}
no set mode {monitor | route {control | observe} | select-exit}
```

Syntax Description

monitor	Enables the configuration of OER monitoring settings.
active	Enables active monitoring.
throughput	(Optional) Enables active monitoring with throughput data from passive monitoring.
both	Enables both active and passive monitoring.
fast	Enables continuous active monitoring and passive monitoring.
passive	Enables passive monitoring.
route	Enables the configuration of OER route control policy settings.
control	Enables automatic route control.
observe	Configures OER to passively monitor and report without making any changes.
select-exit	Enables the exit selection based on performance or policy.
best	Configures OER to select the best available exit based on performance or policy.
good	Configures OER to select the first exit that is in-policy.

Command Default

OER uses the following default settings if this command is not configured or if the **no** form of this command is entered:

Monitoring: Both active and passive monitoring is enabled. Route control: Observe mode route control is enabled. Exit Selection: The first in-policy exit is selected.

Command Modes OER map configuration

Command History	Release	Modification
	12.3(8)T	This command was introduced.
	12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
	12.4(15)T	The fast and throughput keywords were added.

Usage Guidelines The **set mode** command is entered on a master controller in OER map configuration mode. This command is used to configure an OER map to enable and configure control mode and observe mode settings, passive monitoring and active monitoring, and exit link selection for traffic that is configured as match criteria.

Observe Mode

Observe mode monitoring is enabled by default. In observe mode, the master controller monitors prefixes and exit links based on default and user-defined policies and then reports the status of the network and the decisions that should be made but does not implement any changes. This mode allows you to verify the effectiveness of this feature before it is actively deployed.

Control Mode

In control mode, the master controller coordinates information from the border routers and makes policy decisions just as it does in observe mode. The master controller monitors prefixes and exits based on default and user-defined policies but then implements changes to optimize prefixes and to select the best exit. In this mode, the master controller gathers performance statistics from the border routers and then transmits commands to the border routers to alter routing as necessary in the OER managed network.

Passive Monitoring

The master controller passively monitors IP prefixes and TCP traffic flows. Passive monitoring is configured on the master controller. Monitoring statistics are gathered on the border routers and then reported back to the master controller. OER uses NetFlow to collect and aggregate passive monitoring statistics on a per prefix basis. No explicit NetFlow configuration is required. NetFlow support is enabled by default when passive monitoring is enabled. OER uses passive monitoring to measure the following information:

Delay --OER measures the average delay of TCP flows for a prefix. Delay is the measurement of the time between the transmission of a TCP synchronization message and receipt of the TCP acknowledgement.

Packet Loss --OER measures packet loss by tracking TCP sequence numbers for each TCP flow. OER estimates packet loss by tracking the highest TCP sequence number. If a subsequent packet is received with a lower sequence number, OER increments the packet loss counter.

Reachability --OER measures reachability by tracking TCP synchronization messages that have been sent repeatedly without receiving a TCP acknowledgement.

Throughput --OER measures outbound throughput for optimized prefixes. Throughput is measured in bits per second (bps).

**Note**

OER passively monitors TCP traffic flows for IP traffic. Passive monitoring of non-TCP sessions is not supported.

Active Monitoring

OER uses Cisco IOS IP Service Level Agreements (SLAs) to enable active monitoring. IP SLAs support is enabled by default. IP SLAs support allows OER to be configured to send active probes to target IP addresses to measure the jitter and delay, determining if a prefix is out-of-policy and if the best exit is selected. The border router collects these performance statistics from the active probe and transmits this information to the master controller. The master controller uses this information to optimize the prefix and select the best available exit based on default and user-defined policies. The **active-probe** command is used to create an active probe.

In Cisco IOS Release 12.4(15)T the **throughput** keyword was added to enable the throughput data from passive mode monitoring to be considered when optimizing UDP traffic for both performance and load-balancing. UDP traffic can be optimized only for performance (for example, delay, jitter, and loss) when active monitoring data is available. To enable load-balancing of UDP traffic, throughput data from passive monitoring is required.

Fast Failover Monitoring

In Cisco IOS Release 12.4(15)T, a new monitoring mode, fast monitoring, was introduced. Fast monitoring sets the active probes to continuously monitor all the exits (probe-all), and passive monitoring is enabled too. Fast failover monitoring can be used with all types of active probes: ICMP echo, Jitter, TCP connection, and UDP echo. When the **mode monitor fast** command is enabled, the probe frequency can be set to a lower frequency than for other monitoring modes, to allow a faster failover ability. Under fast monitoring with a lower probe frequency, route changes can be performed within 3 seconds of an out-of-policy situation. When an exit becomes OOP under fast monitoring, the select best exit is operational and the routes from the OOP exit are moved to the best in-policy exit. Fast monitoring is a very aggressive mode that incurs a lot of overhead with the continuous probing. We recommend that you use fast monitoring only for performance sensitive traffic.

Optimal Exit Link Selection

The master controller can be configured to select a new exit for an out-of-policy prefix based on performance or policy. You can configure the master controller to select the first in-policy exit by entering the **good** keyword, or you can configure the master controller to select the best exit with the **best** keyword. If the **good** keyword is used and there is no in-policy exit, the prefix is uncontrolled.

Examples

The following example creates an OER map named OBSERVE that configures OER to observe and report but not control traffic from the prefix list named CUSTOMER:

```
Router(config)# oer-map OBSERVE 80

Router(config-oer-map)# match ip address prefix-list CUSTOMER
Router(config-oer-map)# set mode route observe
```

Related Commands

Command	Description
mode (OER)	Configures route monitoring or route control on an OER master controller
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set mos

To configure an Optimized Edge Routing (OER) map to set the threshold and percentage Mean Opinion Score (MOS) values that OER will permit for an exit link, use the **set mos** command in OER map configuration mode. To reset the threshold MOS values to their default value, use the **no** form of this command.

set mos threshold *minimum percentage percent*
no set mos threshold *minimum percentage percent*

Syntax Description

threshold	Specifies a threshold MOS value that represents a minimum voice quality for exit link utilization.
<i>minimum</i>	Number (to two decimal places) in the range from 1.00 to 5.00. The number 1.00 represents the lowest voice quality, and the number 5.00 represents the highest voice quality. The default MOS value is 3.60.
percentage	Specifies a percentage value that is compared with the percentage of MOS samples that are below the MOS threshold.
<i>percent</i>	Number, as a percentage.

Command Default

The default MOS value is 3.60.

Command Modes

OER map configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set mos** command is entered on a master controller in OER map configuration mode and used to determine voice quality. The number of MOS samples over a period of time that are below the threshold MOS value are calculated. If the percentage of MOS samples below the threshold is greater than the configured percentage, OER determines that the exit link is out-of-policy and searches for an alternate exit link.

Another measure of voice quality is the jitter value. Use the **set mos** command and the **set jitter** command in an OER map to define voice quality.

Examples

The following example creates an OER map named MOS that configures the master controller to search for a new exit link if more than 30 percent of the MOS samples are below the MOS threshold of 3.80.

```
Router(config)# oer-map MOS 10

Router(config-oer-map)# match ip address prefix-list LIST1
Router(config-oer-map)# set mos threshold 3.80 percent 30
```

Related Commands

Command	Description
mos	Configures the maximum mos value that OER will permit for an exit link.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set next-hop (OER)

To configure an Optimized Edge Routing (OER) map to send packets that match prefixes in an access list on OER border routers to the specified next hop, use the **set next-hop** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set next-hop *ip-address*

no set next-hop *ip-address*

Syntax Description

ip-address

IP address of the next hop to which the packets will be sent.

Command Default

No packets are sent to the next hop.

Command Modes

OER map configuration

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

This command can be used for OER sinkhole filtering if the border routers detect a denial-of-service (DoS) attack by directing packets to the specified next hop. The packets may be saved, analyzed, or discarded at the next hop.

Examples

The following example shows how to configure an OER map named SINKHOLE_MAP that directs packets to the specified next hop. Use this configuration in preparation for a DoS attack, leave the access list empty until an attack is detected and add the prefix or prefixes that are determined to be the source of the attack. Subsequent packets received from the specified prefix or prefixes will be sent to the specified next hop.

```
Router(config)# oer-map SINKHOLE_MAP 10
Router(config-oer-map)# match ip address access-list SINKHOLE-LIST
Router(config-oer-map)# set next-hop 10.20.24.3
```

Related Commands

Command	Description
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
set interface	Configures an OER map to send packets that match prefixes in an access list on OER border routers to the null interface.

set periodic

To configure an Optimized Edge Routing (OER) map to set the time period for the periodic timer, use the **set periodic** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

set periodic *timer*

no set periodic

Syntax Description

<i>timer</i>	Length of time set for the periodic timer, in seconds. The value for the timer argument is from 180 to 7200.
--------------	--

Command Default

No default behavior or values

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set periodic** command is entered on a master controller in OER map configuration mode. This command is used to configure an OER map to configure OER to periodically select the best exit based on the periodic timer value for traffic that is configured as match criteria in an OER map. When this timer expires, OER will automatically select the best exit, regardless if the current exit is in-policy or out-of-policy. The periodic timer is reset when the new exit is selected.

Examples

The following example creates an OER map named PERIODIC that sets the periodic timer to 300 seconds for traffic from the prefix list named CUSTOMER. When the timer expires, OER will select the best exit.

```
Router(config)# oer-map PERIODIC 80

Router(config-oer-map)# match ip address prefix-list CUSTOMER
Router(config-oer-map)# set periodic 300
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
periodic (OER)	Configures OER to periodically select the best exit.

set probe

To set the frequency of an Optimized Edge Routing (OER) active probe, use the **set probe** command in OER map configuration mode. To reset the frequency of an OER active probe to its default value, use the **no** form of this command.

```
set probe {frequency seconds | packets packet-count}
```

```
no set probe {frequency seconds | packets packet-count}
```

Syntax Description

frequency	Sets the frequency of an active probe.
<i>seconds</i>	Number of seconds in the range from 4 to 60. The default is 60.
packets	Specifies the number of probe packets for a jitter probe.
<i>packet-count</i>	Number of probe packets in the range from 1 to 255. The default is 100.

Command Default

The default active probe frequency is 60 seconds.
The default number of packets probe is 100.

Command Modes

OER map configuration (config-oer-map)

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.4(15)T	The minimum number of seconds was lowered from 4 seconds to 2 second to support the fast failover monitoring mode.
12.4(24)T	This command was modified. The packets keyword and the <i>packet-count</i> argument were added.

Usage Guidelines

The **set probe** command is entered on a master controller in OER map configuration mode. This command is used within an OER map configuration to set the frequency of the active probes. Unless the default frequency of 60 seconds is used, configuring the **set probe** command will increase the frequency of the probes. Increased probe frequency results in a lower response time of OER. The frequency can be increased for a number of policies, but if all active probes are set to an increased frequency, an Intrusion Detection Service (IDS) may be triggered.

In Cisco IOS Release 12.4(15)T, a new monitoring mode, fast monitoring, was introduced. Fast monitoring sets the active probes to continuously monitor all the exits (probe-all), and passive monitoring is enabled too. Fast failover monitoring can be used with all types of active probes: ICMP echo, Jitter, TCP connection, and UDP echo. When the **set mode monitor fast** command is enabled, the probe frequency can be set to a lower frequency than for other monitoring modes, to allow a faster failover ability. The minimum number of seconds was lowered from 4 seconds to 2 second to support the fast failover monitoring mode. Under fast monitoring with a lower probe frequency, route changes can be performed within 3 seconds of an out-of-policy situation.

In Cisco IOS Release 12.4(24)T, the ability to configure the number of probe packets for jitter probes was introduced. Using the **packets** keyword and the *packet-count* argument the number of packets per jitter probe can be set. The new keyword is supported under OER map configuration mode only, not at a global level. The new keyword applies only to jitter probes and the configuration affects global probes and forced probes for all traffic classes.

Examples

The following example shows how to set the frequency of an active probe to be 10 seconds using an OER map named PROBE:

```
Router(config)# oer-map PROBE 10
Router(config-oer-map)# set probe frequency 10
```

The following example shows how to set the frequency of an active probe to be 2 seconds using an OER map named FAST after the fast failover monitoring mode is enabled:

```
Router(config)# oer-map FAST 10
Router(config-oer-map)# set mode monitor fast
Router(config-oer-map)# set probe frequency 2
```

The following example shows how to set the number of probe packets for a jitter probe at 33 packets using an OER map named JITTER:

```
Router(config)# oer-map JITTER
Router(config-oer-map)# set probe packets 33
```

Related Commands

Command	Description
active-probe	Configures an OER active probe for a target prefix.
set mode (OER)	Configures an OER map to configure route monitoring, route control, or exit selection for matched traffic.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

set resolve

To configure an OER map to set policy priority for overlapping policies, use the **set resolve** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set resolve { cost priority value | delay priority value variance percentage | jitter priority value
variance percentage | loss priority value variance percentage | mos priority value variance
percentage | range priority value | utilization priority value variance percentage }
```

```
no set resolve { cost | delay | jitter | loss | mos | range | utilization }
```

Syntax Description

cost	Specifies policy priority settings for cost optimization.
delay	Specifies policy priority settings for packet delay.
jitter	Specifies policy priority settings for jitter.
loss	Specifies policy priority settings for packet loss.
mos	Specifies policy priority settings for Mean Opinion Score (MOS).
range	Specifies policy priority settings for range.
utilization	Specifies policy priority settings for exit link utilization.
priority <i>value</i>	Sets the priority of the policy. The configurable range for this argument is from 1 to 10. The number 1 has the highest priority, and the number 10 has the lowest priority.
variance <i>percentage</i>	Sets the allowable variance for the policy, as a percentage. The configurable range of this argument is from 1 to 100.

Command Default

None

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.4(6)T	The jitter and mos keywords were added.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set resolve** command is entered on a master controller in OER map configuration mode. This command is used to set priority when multiple policies are configured for the same prefix. When this command is configured, the policy with the highest priority will be selected to determine the policy decision.

The **priority** keyword is used to specify the priority value. The number 1 assigns the highest priority to the policy. The number 10 sets the lowest priority. Each policy must be assigned a different priority number. If you try to assign the same priority number to two different policy types, an error message will be displayed on the console.

The **variance** keyword is used to set an allowable variance for a user-defined policy. This keyword configures the allowable percentage that an exit link or prefix can vary from the user-defined policy value and still be considered equivalent. For example, if exit link delay is set to 80 percent and a 10 percent variance is configured, exit links that delay values from 80 to 89 percent will be considered equal.

**Note**

Variance cannot be set for cost or range policies.

Examples

The following example creates an OER map named RESOLVE that sets the priority for delay policies to 1 for traffic learned based on highest outbound throughput. The variance is set to allow a 10 percent difference in delay statistics before a prefix is determined to be out-of-policy.

```
Router(config)# oer-map RESOLVE 10

Router(config-oer-map)# match oer learn throughput
Router(config-oer-map)# set resolve delay priority 1 variance 10
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
resolve	Sets the priority of a policy when multiple overlapping policies are configured.

set traceroute reporting

To configure an Optimized Edge Routing (OER) map to enable traceroute reporting, use the **set traceroute reporting** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set traceroute reporting [policy {delay | loss | unreachable}]
```

```
no set traceroute reporting [policy {delay | loss | unreachable}]
```

Syntax Description

policy	(Optional) Configures policy-based traceroute reporting.
delay	(Optional) Configures traceroute reporting based on delay policies.
loss	(Optional) Configures traceroute reporting based on packet loss policies.
unreachable	(Optional) Configures traceroute reporting based on reachability policies.

Command Default

Traceroute reporting is not enabled using an OER map.

Command Modes

OER map configuration

Command History

Release	Modification
12.3(14)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set traceroute reporting** command is entered on a master controller in OER map configuration mode. This command is used to enable continuous and policy-based traceroute probing. Traceroute probing allows you to monitor prefix performance on a hop-by-hop basis. Delay, loss, and reachability measurements are gathered for each hop from the probe source to the target prefix.

The following types of traceroute reporting are configured with this command:

Continuous --A traceroute probe is triggered for each new probe cycle. Entering this command without any keywords enables continuous reporting. The probe is sourced from the current exit of the prefix.

Policy based --A traceroute probe is triggered automatically when a prefix goes into an out-of-policy state. Entering this command with the **policy** keyword enables policy based traceroute reporting. Policy based traceroute probes are configured individually for delay, loss, and reachability policies. The monitored prefix is sourced from a match clause in an OER map. Policy based traceroute reporting stops when the prefix returns to an in-policy state.

The **show oer master prefix** command is used to display traceroute probe results. An on-demand traceroute probe can be initiated when entering the **show oer master prefix** command with the **current** and **now** keywords. The **set traceroute reporting** command does not have to be configured to initiate an on-demand traceroute probe.

Examples

The following example, starting in global configuration mode, enables continuous traceroute probing for prefixes that are learned based on delay:

```
Router(config)# oer-map TRACE 10
Router(config-oer-map)# match oer learn delay

Router(config-oer-map)# set traceroute reporting
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.
show oer master prefix	Displays the status of monitored prefixes.
traceroute probe-delay	Sets the time interval between traceroute probe cycles.

set unreachable

To configure an OER map to set the maximum number of unreachable hosts, use the **set unreachable** command in OER map configuration mode. To delete the set clause entry, use the **no** form of this command.

```
set unreachable {relative average | threshold maximum}
no set unreachable
```

Syntax Description

relative <i>average</i>	Sets a relative percentage of unreachable hosts based on a comparison of short-term and long-term percentages. The range of values that can be configured for this argument is a number from 1 to a 1000. Each increment represents one tenth of a percent.
threshold <i>maximum</i>	Sets the absolute maximum number of unreachable hosts based on flows per million (fpm). The range of values that can be configured for this argument is from 1 to 1000000.

Command Default

OER uses the following default value if this command is not configured or if the **no** form of this command is entered:

relative *average* : 50 (5 percent)

Command Modes

OER map configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **set unreachable** command is entered on a master controller in OER map configuration mode. This command is used to set the relative percentage or the absolute maximum number of unreachable hosts, based on flows per million, that OER will permit from an OER managed exit link. If the absolute number or relative percentage of unreachable hosts is greater than the user-defined or the default value, OER determines that the exit link is out-of-policy and searches for an alternate exit link.

The **relative** keyword is used to configure the relative percentage of unreachable hosts. The relative unreachable host percentage is based on a comparison of short-term and long-term measurements. The short-term measurement reflects the percentage of hosts that are unreachable within a 5-minute period. The long-term measurement reflects the percentage of unreachable hosts within a 60 minute period. The following formula is used to calculate this value:

$$\text{Relative percentage of unreachable hosts} = ((\text{short-term percentage} - \text{long-term percentage}) / \text{long-term percentage}) * 100$$

The master controller measures the difference between these two values as a percentage. If the percentage exceeds the user-defined or default value, the exit link is determined to be out-of-policy. For example, if 10 hosts are unreachable during the long-term measurement and 12 hosts are unreachable during short-term measurement, the relative percentage of unreachable hosts is 20 percent.

The **threshold** keyword is used to configure the absolute maximum number of unreachable hosts. The maximum value is based on the actual number of hosts that are unreachable based on fpm.

Examples

The following example creates an OER map named UNREACHABLE that configures the master controller to search for a new exit link when the difference between long and short term measurements (relative percentage) is greater than 10 percent for traffic learned based on highest delay:

```
Router(config)# oer-map UNREACHABLE 10
Router(config-oer-map)# match oer learn delay
Router(config-oer-map)# set unreachable relative 100
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
oer-map	Enters OER map configuration mode to configure an OER map to apply policies to selected IP prefixes.

show oer api client



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer api client** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.



Note

Effective with Cisco IOS Release 12.4(15)T, the **show oer api client** command is replaced by the **show oer api provider** command. See the **show oer api provider** command for more information.

To display information about Optimized Edge Routing (OER) application interface clients, use the **show oer api client** command in privileged EXEC mode.

show oer api client [detail]

Syntax Description

detail	(Optional) Displays detailed prefix information about the specified prefix or all prefixes.
---------------	---

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(6)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.4(15)T	The show oer api client command is replaced by the show oer api provider command.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer api client** command is entered on a master controller. This command is used to display the number of prefixes added by the application interface client, the sequence numbers of policies added by the application interface client, and the client ID. The **detail** keyword is used to display more detailed information about the application interface client.

Cisco IOS Release 12.4(15)T

In Cisco IOS Release 12.4(15)T and later releases, the **show oer api client** command is replaced by the **show oer api provider** command. The **show oer api client** command is currently supported for backwards compatibility, but support may be removed in a future Cisco IOS software release.

Examples

The following example shows the status of a monitored prefix:

```
Router# show oer api client
OER Prefix Stats:
  Dly: Delay in ms
  EBw: Egress Bandwidth
  IBw: Ingress Bandwidth
Prefix      State      Curr BR    CurrI/F  Dly    EBw    IBw
-----
10.1.5.0/24 INPOLICY  10.1.1.2  Et1/0    19     1     1
```

The table below describes the significant fields shown in the display.

Table 1 *show oer api client Field Descriptions*

Field	Description
Prefix	IP address and prefix length.
State	Status of the prefix.
Curr BR	Border router from which these statistics were gathered.
Curr I/F	Current exit link interface on the border router.
Dly	Delay in milliseconds.
EBw	Egress bandwidth.
IBw	Ingress bandwidth.

The following output shows the detailed status of a monitored prefix:

```
Router# show oer api client detail

Prefix: 10.1.1.0/26
  State: DEFAULT*      Time Remaining: @7
  Policy: Default
  Most recent data per exit
  Border      Interface      PasSDly  PasLDly  ActSDly  ActLDly
*10.2.1.1    Et1/0          181      181      250      250
10.2.1.2    Et2/0           0         0        351      351
10.3.1.2    Et3/0           0         0         94      943
  Latest Active Stats on Current Exit:
  Type      Target      TPort  Attem  Comps      DSum      Min      Max      Dly
echo      10.1.1.1      N       2       2         448      208     240     224
echo      10.1.1.2      N       2       2         488      228     260     244
echo      10.1.1.3      N       2       2         568      268     300     284
```



```

Prefix performance history records
Current index 2, S_avg interval(min) 5, L_avg interval(min) 60
Age      Border      Interface      OOP/RteChg Reasons
Pas: DSum Samples  DAvG  PktLoss Unreach  Ebytes  Ibytes      Pkts  Flows
Act: Dsum Attempts DAvG  Comps Unreach
00:00:03 10.1.1.1  Et1/0
          0      0      0      0      0      0      0      0
          1504     6    250     6      0

```

The table below describes the significant fields shown in the display.

Table 2 *show oer api client detail Field Descriptions*

Field	Description
Prefix	IP address and prefix length.
State	Status of the prefix.
Time Remaining	Time remaining in the current prefix learning cycle.
Policy	The state that the prefix is in. Possible values are Default, In-policy, Out-of-policy, Choose, and Holddown.
Most recent data per exit	Border router exit link statistics for the specified prefix. The asterisk (*) character indicates the exit that is being used.
Latest Active Stats on Current Exit	Active probe statistics. This field includes information about the probe type, target IP address, port number, and delay statistics.
Type	The type of active probe. Possible types are ICMP echo, TCP connect, or UDP echo. The example uses default ICMP echo probes (default TCP), so no port number is displayed.
Prefix performance history records	Displays border router historical statistics. These statistics are updated about once a minute and stored for 1 hour.

Related Commands

Command	Description
api client	Configures an OER application interface client.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer api provider

To display information about application interface providers registered with Optimized Edge Routing (OER), use the **show oer api provider** command in privileged EXEC mode.

show oer api provider [detail]

Syntax Description	detail	(Optional) Displays detailed information about application interface providers.
Command Default	Detailed information about API providers is not displayed.	
Command Modes	Privileged EXEC (#)	
Command History	Release	Modification
	12.4(15)T	This command was introduced.

Usage Guidelines

The **show oer api provider** command is entered on a master controller. This command is used to display application interface provider and host information including the ID of each configured provider, the priority of the provider and the host (if configured), and the IP addresses of each configured host device. The **detail** keyword is used to display more detailed information.

The OER application interface defines the mode of communication and messaging between applications and the network for the purpose of optimizing the traffic associated with the applications. A provider is defined as an entity outside the network in which the router configured as an OER master controller exists, for example, an ISP, or a branch office of the same company. The provider has one or more host devices running one or more applications that use the OER application interface to communicate with an OER master controller. A provider must be registered with an OER master controller before an application on a host device can interface with OER. Use the **api provider** command to register the provider, and use the **host-address** command to configure a host device. After registration, a host device in the provider network can initiate a session with an OER master controller. The OER application interface provides an automated method for networks to be aware of applications and provides application-aware performance routing.

Examples

The following example shows information about configured application interface providers and host devices:

```
Router# show oer api provider
API Version: Major 2, Minor 0
```

```

Provider id 1, priority 4000
  Host ip 172.17.1.1, priority 4001
  Host ip 10.1.2.2, priority 3001
Provider id 2, priority 20
Provider id 3, priority 10

```

The table below describes the significant fields shown in the display.

Table 3 *show oer api provider Field Descriptions*

Field	Description
API Version, Major, Minor	Version number of the application interface with major and minor releases.
Provider id	ID number of an application interface provider.
priority	The priority assigned to the policies of a provider or of a host
Host ip	IP address of a host device.

The following example shows detailed information about configured application interface providers and host devices:

```

Router# show oer api provider detail
API Version: Major 2, Minor 0
  Provider id 1001, priority 65535
    Host ip 10.3.3.3, priority 65535
      Session id 9, Version Major 2, Minor 0
      Num pfx created 2, Num policies created 2
      Last active connection time (sec) 00:00:01
      Policy ids : 101, 102,
    Host ip 10.3.3.4, priority 65535
      Session id 10, Version Major 2, Minor 0
      Num pfx created 1, Num policies created 1
      Last active connection time (sec) 00:00:03
      Policy ids : 103,
  Provider id 2001, priority 65535
    Host ip 172.19.198.57, priority 65535
      Session id 11, Version Major 2, Minor 0
      Num pfx created 0, Num policies created 0
      All Prefix report enabled
      All exit report enabled

```

The table below describes the significant fields shown in the display that are different from the table above.

Table 4 *show oer api provider detail Field Descriptions*

Field	Description
Session id	Session ID automatically allocated by OER when an application interface provider initiates a session.
Num pfx	Number of traffic classes created by the application interface provider application.
Num policies created	Number of policies dynamically created by the application interface provider application.

Field	Description
Last active connection time	Time, in seconds, since the last active connection from the application interface provider.
Policy ids	IDs assigned to each policy dynamically created by the application interface provider application.
All Prefix report enabled	Traffic class reports from the OER master controller are enabled for the application interface provider.
All exit report enabled	Exit link reports from the OER master controller are enabled for the application interface provider.

Related Commands

Command	Description
api provider	Registers an application interface provider with an OER master controller and enters OER master controller application interface provider configuration mode.
debug oer api provider	Displays OER application interface debugging information.
host-address	Configures information about a host device used by an application interface provider to communicate with an OER master controller.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display information about an Optimized Edge Routing (OER) border router connection and OER controlled interfaces, use the **show oer border** command in privileged EXEC mode.

show oer border

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border** command is entered on an OER border router. The output displays information about the border router, the status of the master controller connection, and border router interfaces.

Examples

The following example shows the status of a border router:

```
Router# show oer border
OER BR 10.1.1.3 ACTIVE, MC 10.1.1.1 UP/DOWN: UP 00:57:55,
  Auth Failures: 0
  Conn Status: SUCCESS, PORT: 3949
  Exits
```

```

Et0/0          INTERNAL
Et1/0          EXTERNAL

```

The table below describes the significant fields shown in the display.

Table 5 *show oer border Field Descriptions*

Field	Description
OER BR	Displays the IP address and the status of the local border router (ACTIVE or DISABLED).
MC	Displays the IP address of the master controller, the connection status (UP or DOWN), the length of time that connection with master controller has been active, and the number of authentication failures that have occurred between the border router and master controller.
Exits	Displays OER managed exit interfaces on the border router. This field displays the interface type, number, and OER status (EXTERNAL or INTERNAL).
Auth Failures	Displays the number of authentication failures.
Conn Status	Displays the connection status. This field displays "SUCCESS" or "FAILED".
PORT	Displays the TCP port number used to communicate with the master controller.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border active-probes



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border active-probes** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display connection status and information about active probes on an Optimized Edge Routing (OER) border router, use the **show oer border active-probes** command in privileged EXEC mode.

show oer border active-probes

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border active-probes** command is entered on a border router. This command displays the target active-probe assignment for a given prefix and the current probing status, including the border router or border routers that are executing the active probes.

Examples

The following example shows three active probes, each configured for a different prefix. The target port, source IP address, and exit interface are displayed in the output.

```
Router# show oer border active-probes
OER Border active-probes
```

```

Type      = Probe Type
Target    = Target IP Address
TPort     = Target Port
Source    = Send From Source IP Address
Interface = Exit interface
Att       = Number of Attempts
Comps    = Number of completions
N - Not applicable
Type      Target      TPort Source      Interface      Att   Comps
udp-echo  10.4.5.1           80 10.0.0.1      Et1/0          1     0
tcp-conn  10.4.7.1           33 10.0.0.1      Et1/0          1     0
echo      10.4.9.1           N  10.0.0.1      Et1/0          2     2

```

The table below describes the significant fields shown in the display.

Table 6 *show oer border active-probes Field Descriptions*

Field	Description
Type	The active probe type.
Target	The target IP address.
TPort	The target port.
Source	The source IP address.
Interface	The OER managed exit interface.
ATT	The number of attempts.
Comps	The number successfully completed attempts.

Related Commands

Command	Description
active-probe	Configures active probes to monitor an OER controlled prefixes.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border defined application

To display information about user-defined applications used in Optimized Edge Routing (OER), use the **show oer border defined application** command in privileged EXEC mode.

show oer border defined application

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **show oer border defined application** command is entered on an OER border router. This command displays all user-defined applications that are defined on the master controller. To define a custom application to be used by OER, use the **application define** command on the OER master controller.

To display the same information on the OER master controller, use the **show oer master defined application** command.

Examples

The following partial output shows information about the user-defined application definitions configured for use with OER:

```
Router# show oer border defined application
OER Defined Applications:
Name                Appl_ID Dscp Prot   SrcPort   DstPort SrcPrefix
-----
telnet              1 defa  tcp    23-23     1-65535 0.0.0.0/0
telnet              1 defa  tcp    1-65535   23-23    0.0.0.0/0
ftp                 2 defa  tcp    21-21     1-65535 0.0.0.0/0
ftp                 2 defa  tcp    1-65535   21-21    0.0.0.0/0
cuseeme             4 defa  tcp    7648-7648 1-65535 0.0.0.0/0
cuseeme             4 defa  tcp    7649-7649 1-65535 0.0.0.0/0
dhcp                5 defa  udp    68-68     67-67    0.0.0.0/0
dns                 6 defa  tcp    53-53     1-65535 0.0.0.0/0
dns                 6 defa  tcp    1-65535   53-53    0.0.0.0/0
dns                 6 defa  udp    53-53     1-65535 0.0.0.0/0
dns                 6 defa  udp    1-65535   53-53    0.0.0.0/0
finger              7 defa  tcp    79-79     1-65535 0.0.0.0/0
finger              7 defa  tcp    1-65535   79-79    0.0.0.0/0
gopher              8 defa  tcp    70-70     1-65535 0.0.0.0/0
.
.
.
```

The table below describes the significant fields shown in the display.

Table 7 *show oer border defined application Field Descriptions*

Field	Description
Name	Application Name
Appl_ID	Application ID
Dscp	Differentiated Services Code Point (DSCP) value
Prot	Protocol
SrcPort	Source port number for the traffic class
DstPort	Destination port number for the traffic class
SrcPrefix	IP address of the traffic class source

Related Commands

Command	Description
application define	Defines a user-defined application to be monitored by OER.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
show oer master defined application	Displays information about user-defined application definitions used in OER.

show oer border passive applications



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border passive applications** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display the list of application traffic classes monitored by Optimized Edge Routing (OER), use the **show oer border passive applications** command in privileged EXEC mode.

show oer border passive applications

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.4(9)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border passive applications** command is entered on a border router. This command displays a list of application traffic classes monitored by the border router using NetFlow passive monitoring.

Examples

The following example displays an application traffic class monitored by a border router:

```
Router# show oer border passive applications
OER Passive monitored Appl:
+ - monitor more specific
```

```

Prefix      /Mask  Prot  Dscp  SrcPort      DstPort      Appl_ID
10.1.3.0    /24    17    ef    [1, 65535]   [3000, 4000] 1

```

The table below describes the significant fields shown in the display.

Table 8 *show oer border passive applications Field Descriptions*

Field	Description
Prefix	IP address.
/Mask	Prefix length.
Prot	Application protocol number.
Dscp	Differentiated Services Code Point (DSCP) value.
SrcPort	Source application port number, a single port number, or a range of port numbers.
DstPort	The destination application port, a single port number, or a range of port numbers.
Appl_ID	Unique ID that identifies an application traffic class.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border passive cache



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border passive cache** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display passive measurement information collected by NetFlow for Optimized Edge Routing (OER) monitored prefixes and traffic flows, use the **show oer border passive cache** command in privileged EXEC mode.

show oer border passive cache learned [application | traffic-class]

Syntax Description

learned	Displays measurement information about monitored learned prefixes.
application	(Optional) Displays measurement information about monitored learned prefixes for an application traffic class.
traffic-class	(Optional) Displays flow cache information about monitored learned prefixes for an OER traffic class.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.4(9)T	The applications and application keywords were added.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.4(15)T	The traffic-class keyword was added.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

Release	Modification
15.0(1)M	This command was modified. The applications and prefix keywords were removed.
12.2(33)SRE	This command was modified. The applications and prefix keywords were removed.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border passive cache** command is entered on a border router. This command displays real-time prefix information collected from the border router through NetFlow passive monitoring.

Entering the **learned** keyword displays learned prefixes. A maximum of five host addresses and five ports are collected for each prefix. The output will also show the throughput in bytes and the delay in milliseconds. If the **application** keyword is entered, the output displays information about learned prefixes that match other application criteria such as Differentiated Services Code Point (DSCP) value, protocol, or port number. The **traffic-class** keyword when used with the **learned** keyword displays cache information about monitored learned prefixes for an OER traffic class.

Examples

The following example displays passive monitoring information about learned prefixes:

```
Router# show oer border passive cache learned
OER Learn Cache:
  State is enabled
  Measurement type: throughput, Duration: 2 min
  Aggregation type: prefix-length, Prefix length: 24
  4096 oer-flows per chunk,
  22 chunks allocated, 32 max chunks,
  1 allocated records, 90111 free records, 8913408 bytes allocated
Prefix      Mask      Pkts  B/Pk  Delay Samples  Active
Host1      Host2      Host3      Host4      Host5
dport1     dport2     dport3     dport4     dport5
10.1.5.0   /24       17K      46     300      2     45.1
10.1.5.2   10.1.5.3  0.0.0.0   0.0.0.0   0.0.0.0
1024      80        0         0         0         0
```

The table below describes the significant fields shown in the display.

Table 9 *show oer border passive cache learned Field Descriptions*

Field	Description
State is...	Displays OER prefix learning status. The output displays enabled or disabled.
Measurement type	Displays how the prefix is learned. The output displays throughput, delay, or both throughput and delay.
Duration	Displays the duration of the learning period in minutes.

Field	Description
Aggregation type	Displays the aggregation type. The output displays BGP, non-BGP, or prefix-length.
... oer-flows per chunk	Displays number of flow records per memory chunk.
... chunks allocated	Number of memory chunks allocated.
... allocated records	Number of records currently allocated in the learn cache.
Prefix	IP address and port of the learned prefix.
Mask	The prefix length as specified in a prefix mask.
Pkts B/Pk	The number of packets and bytes per packet.
Delay Samples	The number of delay samples that NetFlow has collected.
Active	The time for which the flow has been active.

The following example uses the **learned** and **application** keywords to display measurement information about monitored application traffic classes that have been learned by OER. In this example for voice traffic, the voice application traffic is identified by the User Datagram Protocol (UDP) protocol, a DSCP value of ef, and port numbers in the range from 3000 to 4000.

```
Router# show oer border passive cache learned application
OER Learn Cache:
  State is enabled
  Measurement type: throughput, Duration: 2 min
  Aggregation type: prefix-length, Prefix length: 24
  4096 oer-flows per chunk,
  8 chunks allocated, 32 max chunks,
  5 allocated records, 32763 free records, 4588032 bytes allocated
Prefix      Mask      Pkts  B/Pk  Delay Samples  Active
Prot  Dscp  SrcPort      DstPort
Host1      Host2      Host3      Host4      Host5
dport1      dport2      dport3      dport4      dport5
10.1.3.0    /24      873      28      0      0      13.3
17          ef [1, 65535] [3000, 4000]
10.1.3.1    0.0.0.0    0.0.0.0    0.0.0.0    0.0.0.0
3500      0          0          0          0          0
10.1.1.0    /24      7674     28      0      0      13.4
17          ef [1, 65535] [3000, 4000]
10.1.1.1    0.0.0.0    0.0.0.0    0.0.0.0    0.0.0.0
3600      0          0          0          0          0
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border passive learn



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border passive learn** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display the configured, learned parameters to be used with passive measurement information collected by NetFlow for Optimized Edge Routing (OER) learned traffic flows, use the **show oer border passive learn** command in privileged EXEC mode.

show oer border passive learn

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(9)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border passive learn** command is entered on a border router. This command displays configured parameters including filter and aggregate application information collected from the border router through NetFlow passive monitoring.

Examples

The following example displays passive monitoring information about learned traffic flows:

```
Router# show oer border passive learn
OER Border Learn Configuration :
```



```

State is enabled
Measurement type: throughput, Duration: 2 min
Aggregation type: prefix-length, Prefix length: 24
No port protocol config
Traffic Class Filter List:
List: SrcPrefix      SrcMask DstPrefix      DstMask
      Prot  DSCP  sport_opr sport_range  dport_opr dport_range  Grant
1: 0.0.0.0      0      10.1.0.0      16
      17     ef  0      [1, 65535]    0      [1, 65535]    Permit
Traffic Class Aggregate List:
List: Prot  DSCP  sport_opr sport_range  dport_opr dport_range  Grant
1: 17     ef  0      [1, 65535]    7      [3000, 4000]  Permit
Keys: protocol dscp DstPort

```

The table below describes the significant fields shown in the display.

Table 10 *show oer border passive applications Field Descriptions*

Field	Description
State is	Displays OER prefix learning status. The output displays enabled or disabled.
Measurement type	Displays how the prefix is learned. The output displays either throughput or delay.
Duration	Displays the duration of the learning period in minutes.
Aggregation type	Displays the aggregation type. The output displays BGP, non-BGP, or prefix-length.
No port protocol config	Indicates that no port protocol has been configured.
Traffic Class Filter List	Section showing the traffic class filter parameters.
Traffic Class Aggregate List	Section showing the traffic class aggregation parameters.
Keys	Parameters contained in the key list.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border passive prefixes



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border passive prefixes** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display information about passive monitored prefixes, use the **show oer border passive prefixes** command in Privileged EXEC mode.

show oer border passive prefixes

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border passive prefixes** command is entered on a border router. The output of this command displays prefixes monitored by NetFlow on the border router. The prefixes displayed in the output are monitored by the master controller.

Examples

The following example shows a prefix that is passively monitored by NetFlow:

```
Router# show oer border passive prefixes
OER Passive monitored prefixes:
```

```
Prefix      Mask      Match Type
10.1.5.0    /24       exact
```

The table below describes the significant fields shown in the display.

Table 11 *show oer border passive prefixes Field Descriptions*

Field	Description
Prefix	IP address of the learned prefix.
Mask	The prefix length as specified in a prefix mask.
Match Type	Type of prefix being monitored. The prefix can be exact or nonexact.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer border routes



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer border routes** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display information about Optimized Edge Routing (OER)-controlled routes, use the **show oer border routes** command in privileged EXEC mode.

```
show oer border routes {bgp | cce | eigrp [parent] | rwatch | static}
```

Syntax Description

bgp	Displays information for OER routes controlled by Border Gateway Protocol (BGP).
eigrp	Displays information for OER routes controlled by Enhanced Interior Gateway Routing Protocol (EIGRP).
parent	Displays information for EIGRP parent routes.
cce	Displays information for OER routes controlled by Common Classification Engine (CCE).
rwatch	Displays information for OER routes that are being watched in the Routing Information Base (RIB).
static	Displays information for OER routes controlled by static routes.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.

Release	Modification
12.4(20)T	The cee keyword was added.
12.4(24)T	The rwatch keyword was added.
15.0(1)M	This command was modified. The eigrp and parent keywords were added to support EIGRP route control.
12.2(33)SRE	This command was modified. The eigrp and parent keywords were added to support EIGRP route control.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **show oer border routes** command is entered on a border router. This command is used to display information about OER-controlled routes on a border router. You can display information about BGP or static routes.

In Cisco IOS Release 12.4(20)T, the **cee** keyword was added to display information about OER-controlled traffic classes that are identified using Network-Based Application Recognition (NBAR).

Examples

The following example displays BGP learned routes on a border router:

```
Router# show oer border routes bgp
OER BR 10.1.1.2 ACTIVE, MC 10.1.1.3 UP/DOWN: UP 00:10:08,
  Auth Failures: 0
  Conn Status: SUCCESS, PORT: 3949
BGP table version is 12, local router ID is 10.10.10.2
Status codes: s suppressed, d damped, h history, * valid, > best, i - internal,
               r RIB-failure, S Stale
Origin codes: i - IGP, e - EGP, ? - incomplete
OER Flags: C - Controlled, X - Excluded, E - Exact, N - Non-exact, I - Injected
   Network      Next Hop      OER      LocPrf Weight Path
*> 10.1.0.0/16   10.40.40.2     CE                0 400 600 i
```

The table below describes the significant fields shown in the display.

Table 12 *show oer border routes bgp Field Descriptions*

Field	Description
C-Controlled	Indicates the monitored prefix is currently under OER control.
X-Excluded	Indicates the monitored prefix is controlled by a different border router.
E - Exact	Indicates that an exact prefix indicates is controlled, but more specific routes are not.

Field	Description
N - Non-exact	Indicates that the prefix and all more specific routes are under OER control.
I - Injected	Indicates that the prefix is injected into the BGP routing table. If a less specific prefix exists in the BGP table and OER has a more specific prefix configured, then BGP will inject the new prefix and OER will flag it as I-Injected.
XN	Indicates that the prefix and all more specific prefixes are under the control of another border router, and, therefore, this prefix is excluded. (Not shown in the example output.)
CNI	Indicates that the prefix is injected, and this prefix and all more specific prefixes are under OER control.
CEI	Indicates that the specific prefix is injected and under OER control.
CN	Indicates that the prefix and all more specific prefixes are under OER control.
CE	Indicates that the specific prefix is under OER control.
Network	The IP address and prefix mask.
Next Hop	The next hop of the prefix.
OER	Type of OER control.
LocPrf	The BGP local preference value.
Weight	The weight of the route.
Path	The BGP path type.

The following example displays OER-controlled routes identified using NBAR:

```
Router# show oer border routes cce
Class-map oer-class-acl-oer_cce#2-stile-telnet, permit, sequence 0, mask 24
  Match clauses:
    ip address (access-list): oer_cce#2
    stile: telnet
  Set clauses:
    ip next-hop 10.1.3.2
    interface Ethernet2/3
  Statistic:
    Packet-matched: 60
```

The table below describes the significant fields shown in the display.

Table 13 *show oer border routes cce Field Descriptions*

Field	Description
Class-map	Indicates the name OER map used to control the OER traffic classes.
Match clauses	Indicates the match criteria being applied to the traffic classes.
ip address (access-list)	Name of access list used to match the destination prefixes of the controlled traffic classes identified using NBAR.
stile	Protocol being controlled.
Set clauses	Indicates the set criteria being applied to the matched traffic classes.
ip next-hop	IP address of the next hop to which the controlled traffic is sent. The next hop should be to a noncontrolling router.
interface	Interface name and number through which the controlled traffic is sent. If this is an ingress interface, the border router is not controlling the traffic classes. If this is an egress interface of the border router, the route is being controlled.
Statistic	Displays statistics such as number of packets matched.

The following example, available in Cisco IOS Release 15.0(10M, 12.2(33)SRE, and later releases, displays EIGRP-controlled routes on a border router with information about the parent route that exists in the EIGRP routing table. In this example, the output shows that prefix 10.1.2.0/24 is being controlled by OER. This command is used to show parent route lookup and route changes to existing parent routes when the parent route is identified from the EIGRP routing table.

```
Router# show oer border routes eigrp
Flags: C - Controlled by oer, X - Path is excluded from control,
      E - The control is exact, N - The control is non-exact
Flags Network      Parent      Tag
CE   10.1.2.0/24   10.0.0.0/8   5000
```

In this example, the **parent** keyword is used and more details are shown about the parent route lookup.

```
Router# show oer border routes eigrp parent
Network      Gateway      Intf      Flags
10.0.0.0/8   10.40.40.2   Ethernet4  1
Child Networks
Network      Flag
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master

To display information about an Optimized Edge Routing (OER) master controller, use the **show oer master** command in privileged EXEC mode.

show oer master

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.3(11)T	The protocol field was added to the output of this command under the “Learn Settings” heading.
12.3(14)T	The trace probe delay field was added to the output of this command under the “Global Settings” heading.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **show oer master** command is entered on a master controller. The output of this command displays information about the status of the OER managed network; the output includes information about the master controller, the border routers, OER managed interfaces, and default and user-defined policy settings.

Examples

The following example displays the status of an OER managed network on a master controller:

```
Router# show oer master

OER state: ENABLED and ACTIVE
  Conn Status: SUCCESS, PORT: 3949
  Number of Border routers: 2
  Number of Exits: 2
  Number of monitored prefixes: 10 (max 5000)
Border      Status   UP/DOWN   AuthFail
10.4.9.7    ACTIVE  UP        02:54:40    0
10.4.9.6    ACTIVE  UP        02:54:40    0
Global Settings:
  max-range-utilization percent 20
  mode route metric bgp local-pref 5000
  mode route metric static tag 5000
  trace probe delay 1000
```

```

logging
Default Policy Settings:
backoff 300 3000 300
delay relative 50
holddown 300
periodic 0
mode route control
mode monitor both
mode select-exit best
loss relative 10
unreachable relative 50
resolve delay priority 11 variance 20
resolve utilization priority 12 variance 20
Learn Settings:
current state : SLEEP
time remaining in current state : 4567 seconds
throughput
delay
no protocol
monitor-period 10
periodic-interval 20
aggregation-type bgp
prefixes 100
expire after time 720

```

The table below describes the significant fields shown in the display.

Table 14 *show oer master Field Descriptions*

Field	Description
OER state	Indicates the status of the master controller. The state will be either “Enabled” or “Disabled” and “Active” or “Inactive.”
Conn Status	Indicates the state of the connection between the master controller and the border router. The state is displayed as “SUCCESS” to indicate as successful connection. The state is displayed as “CLOSED” if there is no connection.
PORT:	Displays the port number that is used for communication between the master controller and the border router.
Number of Border routers:	Displays the number of border router that peer with the master controller.
Number of Exits:	Displays the number of exit interfaces under OER control.
Number of monitored prefixes:	Displays the number prefixes that are actively or passively monitored.
Border	Displays the IP address of the border router.
Status	Indicates the status of the border router. This field displays either “ACTIVE” or “INACTIVE.”

Field	Description
UP/DOWN	Displays the connection status. The output displays “DOWN” or “UP.” “UP” is followed by the length of time that the connection has been in this state.
AuthFail	Displays the number of authentication failures between the master controller and the border router.
Global Settings:	Displays the configuration of global OER master controller settings.
Default Policy Settings:	Displays default OER master controller policy settings.
Learn Settings:	Display OER learning settings.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master active-probes

To display connection and status information about active probes on an Optimized Edge Routing (OER) master controller, use the **show oer master active-probes** command in privileged EXEC mode.

show oer master active-probes [appl | forced]

Syntax Description

appl	(Optional) Filters the output display that active probes generate for application traffic configured with the OER Application-Aware Routing: PBR feature.
forced	(Optional) Filters the output display that active probes generate for voice traffic configured with a forced target assignment.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.4(2)T	Support for the appl keyword was introduced in Cisco IOS Release 12.4(2)T.
12.4(6)T	Support for the forced keyword was introduced in Cisco IOS Release 12.4(6)T.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **show oer master active-probes** command is entered on a master controller. This command is used to display the status of active probes. The output from this command displays the active probe type and destination, the border router that is the source of the active probe, the target prefixes that are used for active probing, and whether the probe was learned or configured. Entering the **appl** keyword filters the output to display information about applications optimized by the master controller. Entering the **forced** keyword filters the output to display information about voice traffic that is configured with a forced target assignment optimized by the master controller.

Examples

The following example shows the status of configured and running active probes:

```
Router# show oer master active-probes
```

```

OER Master Controller active-probes
Border = Border Router running this Probe
State = Un/Assigned to a Prefix
Prefix = Probe is assigned to this Prefix
Type = Probe Type
Target = Target Address
TPort = Target Port
How = Was the probe Learned or Configured
N - Not applicable
The following Probes exist:
State Prefix Type Target TPort How
Assigned 10.1.1.1/32 echo 10.1.1.1 N Lrnd
Assigned 10.1.4.0/24 echo 10.1.4.1 N Lrnd
Assigned 10.1.2.0/24 echo 10.1.2.1 N Lrnd
Assigned 10.1.4.0/24 udp-echo 10.1.4.1 65534 Cfgd
Assigned 10.1.3.0/24 echo 10.1.3.1 N Cfgd
Assigned 10.1.2.0/24 tcp-conn 10.1.2.1 23 Cfgd
The following Probes are running:
Border State Prefix Type Target TPort
192.168.2.3 ACTIVE 10.1.4.0/24 udp-echo 10.1.4.1 65534
172.16.1.1 ACTIVE 10.1.2.0/24 tcp-conn 10.1.2.1 23

```

The table below describes the significant fields shown in the display.

Table 15 *show oer master active-probes Field Descriptions*

Field	Description
The following Probes exist:	Displays the status of configured active probes.
State	Displays the status of the active probe. The output displays “Assigned” or “Unassigned.”
Prefix	Displays the prefix and prefix mask of the target active probe.
Type	Displays the type of active probe. The output displays “echo,” “jitter,” “tcp-conn,” or “udp-echo.”
Target	Displays the target IP address for the active probe.
TPort	Displays the target port for the active probe.
How	Displays how the active probe was created. The output will indicate the probe is configured or learned.
The following Probes are running:	Displays the status of active probes that are running.
Border	Displays the IP address of the border router.

The following example shows the status of configured and running active probes when a jitter probe has been configured:

```

Router# show oer master active-probes

OER Master Controller active-probes
Border = Border Router running this Probe
State = Un/Assigned to a Prefix
Prefix = Probe is assigned to this Prefix

```

```

Type      = Probe Type
Target    = Target Address
TPort     = Target Port
How       = Was the probe Learned or Configured
N - Not applicable
The following Probes exist:
State     Prefix           Type      Target    TPort How      codec
Assigned 10.1.1.0/24          jitter    10.1.1.10 2000 Cfgd g711ulaw
Assigned 10.1.1.0/24          echo      10.1.1.2   N Lrnd      N
The following Probes are running:
Border    State     Prefix           Type      Target    TPort
10.1.1.2  ACTIVE   10.1.1.0/24     jitter    10.1.1.10 2000
10.1.1.2  ACTIVE   10.1.1.0/24     echo      10.1.1.6   N
10.2.2.3  ACTIVE   10.1.1.0/24     jitter    10.1.1.10 2000
10.2.2.3  ACTIVE   10.1.1.0/24     echo      10.1.1.6   N
10.1.1.1  ACTIVE   10.1.1.0/24     jitter    10.1.1.10 2000
10.1.1.1  ACTIVE   10.1.1.0/24     echo      10.1.1.6   N

```

The table below describes the significant fields shown in the display that are different from those in the table above.

Table 16 *show oer master active-probes (jitter and MOS) Field Descriptions*

Field	Description
codec	Displays the codec value configured for MOS calculation. Codec values can be one of the following: g711alaw, g711ulaw, or g729a.

Related Commands

Command	Description
active-probe	Configures active probes to monitor an OER controlled prefixes.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master appl

To display information about application traffic classes monitored and controlled by an Optimized Edge Routing (OER) master controller, use the **show oer master appl** command in privileged EXEC mode.

```
{show oer master appl [access-list name] [detail] [learned [delay | throughput]] | [tcp | udp]
[protocol-number] [min-port max-port] [dst | src] [detail | policy]}
```

Syntax Description

access-list <i>name</i>	(Optional) Filters the output based on the specified named extended access list.
detail	(Optional) Displays detailed information.
learned	(Optional) Displays information about learned application traffic classes.
delay	(Optional) Displays information about applications learned using delay as the learning criterion.
throughput	(Optional) Displays information about applications learned using throughput as the learning criterion.
tcp	(Optional) Filters the output based on TCP traffic.
udp	(Optional) Filters the output based on User Datagram Protocol (UDP) traffic.
<i>protocol-number</i>	(Optional) Filters the output based on the specified protocol number.
<i>min-port max-port</i>	(Optional) Filters the output based on the specified port number or range of port numbers.
dst	(Optional) Filters the output based on the destination port number.
src	(Optional) Filters the output based on the source port number.
policy	(Optional) Displays the policy for the application or port number.

Command Modes

Privileged EXEC

Command History

Release	Modification
12.4(2)T	This command was introduced.
12.4(9)T	The learned , delay , and throughput keywords were added.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **show oer master appl** command is entered on an OER master controller. This command is used to display information about application traffic classes that are configured for monitoring and optimization.

Examples

The following example shows TCP application traffic filtered based on port 80 (HTTP):

```
Router# show oer master appl tcp 80 80 dst policy
```

Prefix	Appl Prot	Port	Port Type	Policy
10.1.0.0/16	tcp	[80, 80]	dst	20
10.1.1.0/24	tcp	[80, 80]	dst	10

The table below describes the significant fields shown in the display.

Table 17 *show oer master appl Field Descriptions*

Field	Description
Prefix	IP address of the monitored prefix that carries the application traffic.
Appl Prot	Application protocol.
Port	Application port number.
Port Type	Source or destination application port number.
Policy	Application policy number.

The following example shows information about learned application traffic classes:

```
Router# show oer master appl learned
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
Prefix          Prot Port [src][dst]/AppId          DSCP Source Prefix
                State      Time Curr BR          CurrI/F      Protocol
                PasSDly PasLDly  PasSUn  PasLUn  PasSLos  PasLLos
                ActSDly ActLDly  ActSUn  ActLUn   EBw      IBw
                ActSJit  ActPMOS
```



```

-----
100.1.0.0/16          tcp [1, 65535] [80, 80]          defa 0.0.0.0/0
                      DEFAULT*          87 U                          U
Router# show oer master appl tcp 80 80 dst
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
Prefix          Prot Port [src][dst]/ApplId      DSCP Source Prefix
                State      Time Curr BR          CurrI/F      Protocol
                PasSDly  PasLDly  PasSUn  PasLUn  PasSLos  PasLLos
                ActSDly  ActLDly  ActSUn  ActLUn  EBw      IBw
-----
100.1.0.0/16          tcp [1, 65535] [80, 80]          defa 0.0.0.0/0
                      DEFAULT*          52 U                          U

```

The table below describes the significant fields shown in the display that are different from those in the table above.

Table 18 *show oer master appl learned Field Descriptions*

Field	Description
ApplId	ID of the application.
DSCP	Differentiated Services Code Point (DSCP) value.
Source Prefix	IP address of the application source.
State	Current state of the application traffic class flow.
Time	Time, in seconds, between probe messages.
Curr BR	IP address of the border router through which the prefix associated with this application traffic class is being currently routed.
CurrI/F	Interface of the border router through which the prefix associated with this application traffic class is being currently routed.
Proto	Protocol.

The following example shows information about application traffic classes learned using delay as the learning criterion:

```

Router# show oer master appl learned delay
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
Prefix          Prot Port [src][dst]          DSCP Source Prefix
                State      Time Curr BR          CurrI/F      Proto

```

```

          PasSDly PasLDly PasSUn PasLUn PasSLos PasLLos
          ActSDly ActLDly ActSUn ActLUn PasSLos PasLLos
          ActSJit ActPMOS
-----
10.1.3.0/24      udp [1, 65535] [3000, 4000]      ef 0.0.0.0/0
                 INPOLICY*      @70 1.1.1.2      Et0/0      PBR
                 U      U      0      0      0      0
                 3      4      0      0      1      0
                 N      N

```

The following example shows information about application traffic classes learned using throughput as the learning criterion:

```

Router# show oer master appl learned throughput
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
Prefix      Prot Port [src][dst]      DSCP Source Prefix
              State      Time Curr BR      CurrI/F      Proto
          PasSDly PasLDly PasSUn PasLUn PasSLos PasLLos
          ActSDly ActLDly ActSUn ActLUn PasSLos PasLLos
          ActSJit ActPMOS
-----
10.1.1.0/24      udp [1, 65535] [3000, 4000]      ef 0.0.0.0/0
                 INPOLICY*      @70 1.1.1.2      Et0/0      PBR
                 U      U      0      0      0      0
                 11     7      0      0      1      0
                 N      N

```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master border

To display the status of connected Optimized Edge Routing (OER) border routers, use the **show oer master border** command in privileged EXEC mode.

show oer master border [*ip-address*] [**detail** | **report** | **topology**]

Syntax Description

<i>ip-address</i>	(Optional) Specifies the IP address of a single border router.
detail	(Optional) Displays detailed border router information.
report	(Optional) Displays border router related link reports.
topology	(Optional) Displays the status of the policy based routing (PBR) requirement.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.4(15)T	This command was modified. The topology keyword was added, and the show oer master border command output was enhanced to include the status of the PBR requirement.

Usage Guidelines

The **show oer master border** command and all the keywords are entered on a master controller. The output of this command shows the status of connections with border routers.

Examples

The following example displays the status of border router connections with a master controller:

```
Router# show oer master border
OER state: ENABLED and ACTIVE
Conn Status: SUCCESS, PORT: 3949
Version: 2.2
```

```

Number of Border routers: 3
Number of Exits: 3
Number of monitored prefixes: 1 (max 5000)
Max prefixes: total 5000 learn 2500
Prefix count: total 1, learn 0, cfg 1
PBR Requirements met
Nbar Status: Inactive
Border      Status  UP/DOWN      AuthFail  Version
10.165.201.5  ACTIVE  UP          00:05:29    0    2.2
10.165.201.6  ACTIVE  UP          00:05:29    0    2.2
10.165.201.7  ACTIVE  UP          00:05:29    0    2.2

```

The table below describes the significant fields shown in the display. All the other fields in the output are self-explanatory.

Table 19 *show oer master border Field Descriptions*

Field	Description
Border	Displays the IP address of the border router.
Status	Displays the status of the border router. The output displays “ACTIVE” or “INACTIVE.”
UP/DOWN	Displays the connection status and the length of time that the connection has been up. The output displays “DOWN” or “UP.” The up time is displayed in weeks, days, hours, minutes, and seconds.
AuthFail	Displays the number of authentication failures between the master controller and the border router.
Version	Displays the version for all of the border routers configured on the master controller.

The following example displays detailed information about border router connections with a master controller:

```

Router# show oer master border detail
Border      Status  UP/DOWN      AuthFail  Version
10.1.1.2    ACTIVE  UP          14:03:40    0    3.0
Et2/0      EXTERNAL UP
Et0/0      INTERNAL UP
Et1/0      EXTERNAL UP

External      Capacity  Max BW  BW Used  Load Status  Exit Id
Interface    (kbps)   (kbps)  (kbps)  (%)         -----
Et2/0        Tx        800     600     226     28 UP         2
              Rx        800     800     0       0
Et1/0        Tx        800     600     97     12 UP         1
              Rx        800     800     55     6

```

The table below describes the significant fields shown in the display.

Table 20 *show oer master border detail Field Descriptions*

Field	Description
Border	Displays the IP address of the border router.

Field	Description
Status	Displays the status of the border router. The output displays “ACTIVE” or “INACTIVE.”
UP/DOWN	Displays the connection status and the length of time that the connection has been up. The output displays “DOWN” or “UP.” The up time is displayed in weeks, days, hours, minutes, and seconds.
AuthFail	Displays the number of authentication failures between the master controller and the border router.
External Interface	Displays the external OER controlled interface.
Capacity	Displays the capacity of the interface in kilobytes per second.
Max BW	Displays the maximum usable bandwidth in kilobytes per second as configured on the interface.
BW Used	Displays the amount of bandwidth in use in kilobytes per second.
Load	Displays the amount of bandwidth in use as a percentage of the total capacity of the interface.
Status	Displays the status of the link.
Exit Id	Displays the ID number assigned by the master controller to identify the exit.
Tx	Displays the percentage of interface utilization in the outbound direction.
Rx	Displays the percentage of interface utilization in the inbound direction.

The following example displays if the PBR requirement for the application control by OER is met or not:

```

Router# show oer master border topology
LocalBR      LocalEth      RemoteBR      RemoteEth      nbar_type
-----
10.165.201.4  Ethernet0/0    10.165.202.2  Ethernet0/0    Directly Connected
10.165.201.4  Ethernet0/0    10.165.201.3  Ethernet0/0    Directly Connected
10.165.201.3  Ethernet0/0    10.165.201.4  Ethernet0/0    Directly Connected
10.165.201.3  Ethernet0/0    10.165.201.3  Ethernet0/0    Directly Connected
10.165.201.2  Ethernet0/0    10.165.201.4  Ethernet0/0    Directly Connected
10.165.201.2  Ethernet0/0    10.165.201.2  Ethernet0/0    Directly Connected
PBR Requirements met

```

The table below describes the significant fields shown in the display.

Table 21 *show oer master border topology Field Descriptions*

Field	Description
LocalBR	Displays the local border router.
LocalEth	Displays the local interface connection for the local border router.
RemoteBR	Displays the remote border router that is connected with the local border router.
RemoteEth	Displays the remote interface connection for the remote border router.
nbar_type	Displays the type of NBAR connection for each of the border routers. Three types of connection status are available: Directly Connected, One-Hop-Away Neighbor, and Not Connected.

The following example displays the border router link report:

```
Router# show oer master border report
Border      Status    UP/DOWN      AuthFail  Version
10.165.202.132  ACTIVE   UP           00:05:54    0    2.2
10.165.202.131  ACTIVE   UP           00:05:57    0    2.2
10.165.202.130  ACTIVE   UP           00:06:00    0    2.2
10.165.202.129  ACTIVE   UP           00:06:03    0    2.2
```

The table below describes the significant fields shown in the display.

Table 22 *show oer master report detail Field Descriptions*

Field	Description
Border	Displays the IP address of the border router.
Status	Displays the status of the border router. The output displays "ACTIVE" or "INACTIVE."
UP/DOWN	Displays the connection status and the length of time that the connection has been up. The output displays "DOWN" or "UP." The up time is displayed in weeks, days, hours, minutes, and seconds.
AuthFail	Displays the number of authentication failures between the master controller and the border router.
Status	Displays the status of the link.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master cost-minimization

To display the status of cost-based optimization policies, use the **show oer master cost-minimization** command in privileged EXEC mode.

```
show oer master cost-minimization { billing-history | border ip-address [interface] | nickname
name }
```

Syntax Description

billing-history	Deploys the billing history
border ip-address	Displays information for a single border router.
<i>interface</i>	(Optional) Displays information for only the specified interface.
nickname name	Displays information for the service provider. A nickname must be configured before output will be displayed.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(14)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **show oer master cost-minimization** command is entered on a master controller. The output of this command shows the status of cost-based policies.

Examples

The following example displays the billing history for cost policies:

```
Router# show oer master cost-minimization billing-history
Billing History for the past three months
   ISP2 on 10.1.1.2      Ethernet0/0
 80-percent on 10.1.1.1  Ethernet0/0
      Mon1              Mon2              Mon3
Nickname  SustUtil    Cost    SustUtil    Cost    SustUtil    Cost
-----
   ISP2      ---NA---    1737222676  1737222676      ---NA---
 80-percent      ---NA---    1737231684  1737231684      ---NA---
-----
Total Cost                                0                3474454360                0
```


The table below describes the significant fields shown in the display.

Table 23 *show oer master cost-minimization billing-history Field Descriptions*

Field	Description
Nickname	The nickname assigned to the service provider.
SustUtil	The sustained utilization of the exit link.
Cost	The financial cost of the link.
Total Cost	The total financial cost for the month.

The following example displays cost optimization information only for Ethernet 1/0:

```
Router# show oer master cost-minimization border 10.1.1.2 Ethernet1/0

Nickname : ispname           Border: 10.1.1.2           Interface: Et1/0
Calc type : Combined
Start Date: 20
Fee       : Tier Based
           Tier1 : 100, fee: 10000
           Tier2 : 90, fee: 9000
Period    : Sampling 22, Rollup 1400
Discard   : Type Percentage, Value 22
Rollup Information:
Total          Discard          Left          Collected
60             13                36             0
Current Rollup Information:
MomentaryTgtUtil: 7500 Kbps   CumRxBytes:      38669
StartingRollupTgt: 7500 Kbps   CumTxBytes:      39572
CurrentRollupTgt: 7500 Kbps   TimeRemain:      09:11:01
Rollup Utilization (Kbps):
Egress/Ingress Utilization Rollups (Descending order)
1 : 0                2 : 0
```

The table below describes the significant fields shown in the display.

Table 24 *show oer master cost-minimization border Field Descriptions*

Field	Description
Nickname	Nickname of the service provider.
Border	IP address of the border router.
Interface	Interface for which the cost policy is configured.
Calc type	Displays the configured billing method.
Start Date	Displays the starting date of the billing period.
Fee	Displays the billing type (fixed or tiered) and the billing configuration.
Period	Displays the sampling and rollup configuration.
Discard	Displays the discard configuration, type, and value.

Field	Description
Rollup Information	Displays rollup statistics.
Current Rollup Information	Displays rollup statistics for the current sampling cycle.
Rollup Utilization	Displays rollup utilization statistics in kilobytes per second.

The following example displays cost optimization information for the specified service provider:

```
Router# show oer master cost-minimization nickname ISP1

Nickname   : ISP1                Border: 10.1.1.2          Interface: Et1/0
Calc type  : Combined
Start Date : 20
Fee        : Tier Based
            Tier1 : 100, fee: 10000
            Tier2 : 90, fee: 9000
Period     : Sampling 22, Rollup 1400
Discard    : Type Percentage, Value 22
Rollup Information:
Total      Discard      Left      Collected
60         13           36         0
Current Rollup Information:
MomentaryTgtUtil:      7500 Kbps      CumRxBytes:      38979
StartingRollupTgt:    7500 Kbps      CumTxBytes:      39692
CurrentRollupTgt:    7500 Kbps      TimeRemain:      09:10:49
Rollup Utilization (Kbps):
Egress/Ingress Utilization Rollups (Descending order)
1      : 0              2      : 0
```

Related Commands

Command	Description
cost-minimization	Configures cost-based optimization policies on a master controller.
debug oer master cost-minimization	Displays debugging information for cost-based optimization policies.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master defined application

To display information about user-defined application definitions used in Optimized Edge Routing (OER), use the **show oer master defined application** command in privileged EXEC mode.

show oer master defined application

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **show oer master defined application** command is entered on an OER master controller. This command displays all applications that are user-defined. To define a custom application to be used by OER, use the **application define** command on the OER master controller.

To display the same information on an OER border router, use the **show oer border defined application** command.

Examples

The following partial example output shows information about the user-defined applications configured for use with OER:

```
Router# show oer master defined application
OER Defined Applications:
Name          Appl_ID Dscp Prot   SrcPort  DstPort SrcPrefix
-----
telnet                1 defa tcp    23-23    1-65535 0.0.0.0/0
telnet                1 defa tcp    1-65535  23-23    0.0.0.0/0
ftp                   2 defa tcp    21-21    1-65535 0.0.0.0/0
ftp                   2 defa tcp    1-65535  21-21    0.0.0.0/0
cuseeme              4 defa tcp    7648-7648 1-65535 0.0.0.0/0
cuseeme              4 defa tcp    7649-7649 1-65535 0.0.0.0/0
cuseeme              4 defa tcp    1-65535  7648-7648 0.0.0.0/0
dhcp                  5 defa udp    68-68    67-67    0.0.0.0/0
dns                    6 defa tcp    53-53    1-65535 0.0.0.0/0
dns                    6 defa tcp    1-65535  53-53    0.0.0.0/0
dns                    6 defa udp    53-53    1-65535 0.0.0.0/0
dns                    6 defa udp    1-65535  53-53    0.0.0.0/0
finger                7 defa tcp    79-79    1-65535 0.0.0.0/0
finger                7 defa tcp    1-65535  79-79    0.0.0.0/0
gopher                8 defa tcp    70-70    1-65535 0.0.0.0/0
.
.
.
```

The table below describes the significant fields shown in the display.

Table 25 *show oer master defined application Field Descriptions*

Field	Description
Name	Application Name
Appl_ID	Application ID
Dscp	Differentiated Services Code Point (DSCP) value
Prot	Protocol
SrcPort	Source port number for the traffic class
DstPort	Destination port number for the traffic class
SrcPrefix	IP address of the traffic class source

Related Commands

Command	Description
application define	Defines a user-defined application to be monitored by OER.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
show oer border defined application	Displays information about user-defined application definitions used in OER.

show oer master learn list

To display configuration information about Optimized Edge Routing (OER) learn lists, use the **show oer master learn list** command in privileged EXEC mode.

```
show oer master learn list [list-name]
```

Syntax Description

<i>list-name</i>	(Optional) Name of learn list.
------------------	--------------------------------

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **show oer master learn list** command is entered on an OER master controller. This command is used to display configuration information about learn lists. In Cisco IOS Release 12.4(15)T, the learn list configuration mode was introduced. Learn lists are a way to categorize learned traffic classes. In each learn list, different criteria for learning traffic classes including prefixes, application definitions, filters, and aggregation parameters can be configured. A traffic class is automatically learned by OER based on each learn list criteria, and each learn list is configured with a sequence number. The sequence number determines the order in which learn list criteria are applied. Learn lists allow different OER policies to be applied to each learn list; in previous releases, the traffic classes could not be divided, and an OER policy was applied to all the traffic classes profiled during one learning session.

Examples

The following example shows how to display configuration information about two learn lists, LIST1 and LIST2:

```
Router# show oer master learn list
Learn-List LIST1 10
Configuration:
  Application: ftp
  Aggregation-type: bgp
  Learn type: thruput
  Policies assigned: 8 10
Stats:
  Application Count: 0
  Application Learned:
Learn-List LIST2 20
Configuration:
  Application: telnet
  Aggregation-type: prefix-length 24
  Learn type: thruput
  Policies assigned: 5 20
Stats:
```

```

Application Count: 2
Application Learned:
  Appl Prefix 10.1.5.0/24 telnet
  Appl Prefix 10.1.5.16/28 telnet

```

The table below describes the significant fields shown in the display.

Table 26 *show oer master learn list Field Descriptions*

Field	Description
Learn-List	Identifies the OER learn list name and sequence number.
Application	Application protocol.
Aggregation-type	Type of TCF aggregation.
Learn type	Throughput or delay.
Policies assigned	Application policy number.
Application Count	Number of applications learned.
Application Learned	Type of application that is learned.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master link-group

To display information about Optimized Edge Routing (OER) link groups, use the **show oer master link-group** command in privileged EXEC mode.

```
show oer master link-group [link-group-name]
```

Syntax Description

<i>link-group-name</i>	(Optional) Name of link group.
------------------------	--------------------------------

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **show oer master link-group** command is entered on an OER master controller. This command is used to display information about link groups including the link group name, the border router and the interface on the border router that is the exit link, and the ID of the exit link.

Introduced in Cisco IOS Release 12.4(15)T, link groups are used to define a group of exit links as a preferred set of links or a fallback set of links for OER to use when optimizing a specified traffic class. Up to three link groups can be specified for each interface. Use the **link-group** command to define the link group for an interface and use the **set link-group** command to define the primary link group and a fallback link group for a specified traffic class in an OER map.

Examples

The following example displays information about all configured link groups:

```
Router# show oer master link-group
link group video
  Border          Interface      Exit id
  192.168.1.2     Serial2/0     1
link group voice
  Border          Interface      Exit id
  192.168.1.2     Serial2/0     1
  192.168.1.2     Serial3/0     2
  192.168.3.2     Serial4/0     4
link group data
  Border          Interface      Exit id
  192.168.3.2     Serial3/0     3
```

The table below describes the significant fields shown in the display.

Table 27 *show oer master link-group Field Descriptions*

Field	Description
link group	Name of the link group.
Border	IP address of the border router on which the exit link exists.
Interface	Type and number of the interface on the border router that is the exit link.
Exit id	ID number of the exit link.

The following example displays information only about the link group named voice:

```
Router# show oer master link-group voice
link group voice
  Border      Interface      Exit id
  192.168.1.2  Serial2/0      1
  192.168.1.2  Serial3/0      2
  192.168.3.2  Serial4/0      4
```

Related Commands

Command	Description
link-group	Configures an OER border router exit interface as a member of a link group.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
set link-group	Specifies a link group for traffic classes defined in an OER policy.

show oer master nbar application

To display information about the status of an application identified using Network-Based Application Recognition (NBAR) for each Optimized Edge Routing (OER) border router, use the **show oer master nbar application** command in privileged EXEC mode.

show oer master nbar application

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The **show oer master nbar application** command is entered on an OER master controller. This command is used to verify the validity of an application that is identified using NBAR at each OER border router. If the NBAR application is not supported on one or more border routers, then all the traffic classes related to that NBAR application are marked inactive and cannot be optimized using OER.

NBAR is capable of identifying applications based on the following three types of protocols:

- Non-UDP and Non-TCP IP protocols--For example, Generic Routing Encapsulation (GRE), and Internet Control Message Protocol (ICMP).
- TCP and UDP protocols that use statically assigned port numbers--For example, CU-SeeMe desktop video conference (CU-SeeMe-Server) and Post Office Protocol over Transport Layer Security (TLS) and Secure Sockets Layer (SSL) server (SPOP3-Server).
- TCP and UDP protocols that dynamically assign port numbers and require stateful inspection--For example, Real-Time Transport Protocol audio streaming (RTP-audio) and BitTorrent File Transfer Traffic (BitTorrent).

The list of applications identified using NBAR and available for profiling of OER or Performance Routing traffic classes is constantly evolving. For lists of many of the NBAR applications defined using static or dynamically assigned ports, see the Using Performance Routing to Profile the Traffic Classes module.

For more details about NBAR, see the Classifying Network Traffic Using NBAR section of the *Cisco IOS Quality of Service Solutions Configuration Guide*.

Examples

The following partial output shows information about the status of a number of applications identified using NBAR at three OER border routers. In this example, applications based on BGP, BitTorrent, and HTTP protocols are valid at all three OER border routers and traffic classes for these applications are

active. While applications such as ConnectionLess Network Service (CLNS) and KaZaA are invalid on at least one border router, all traffic classes based on these application are marked inactive.

```

Router# show oer master nbar application
NBAR Appl          10.1.1.4          10.1.1.2          10.1.1.3
-----
aarp                Invalid           Invalid           Invalid
appletalk           Invalid           Invalid           Invalid
arp                 Invalid           Invalid           Invalid
bgp                 Valid             Valid             Valid
bittorrent          Valid             Valid             Valid
bridge              Invalid           Invalid           Invalid
bstun               Invalid           Invalid           Invalid
cdp                 Invalid           Invalid           Invalid
citrix              Invalid           Invalid           Invalid
clns                Valid             Invalid           Invalid
clns_es             Invalid           Invalid           Invalid
clns_is             Invalid           Invalid           Invalid
cmns                Invalid           Invalid           Invalid
compressedtcp       Invalid           Invalid           Invalid
cuseeme             Invalid           Invalid           Invalid
decnet              Invalid           Invalid           Invalid
decnet_node         Invalid           Invalid           Invalid
decnet_router-11   Invalid           Invalid           Invalid
decnet_router-12   Invalid           Invalid           Invalid
dhcp                Invalid           Invalid           Invalid
directconnect       Invalid           Invalid           Invalid
dlsw                Invalid           Invalid           Invalid
dns                 Invalid           Invalid           Invalid
edonkey             Invalid           Invalid           Invalid
egg                 Invalid           Invalid           Invalid
eigrp               Invalid           Invalid           Invalid
exchange            Invalid           Invalid           Invalid
fasttrack           Invalid           Invalid           Invalid
finger              Invalid           Invalid           Invalid
ftp                 Invalid           Invalid           Invalid
gnutella            Invalid           Invalid           Invalid
Morpheus            Invalid           Invalid           Invalid
gopher              Invalid           Invalid           Invalid
gre                 Invalid           Invalid           Invalid
h323                Invalid           Invalid           Invalid
http                Valid             Valid             Valid
icmp                Invalid           Invalid           Invalid
imap                Invalid           Invalid           Invalid
ip                  Invalid           Invalid           Invalid
ipinip              Invalid           Invalid           Invalid
ipsec               Invalid           Invalid           Invalid
ipv6                Invalid           Invalid           Invalid
ipx                 Invalid           Invalid           Invalid
irc                 Invalid           Invalid           Invalid
kazaa2              Valid             Invalid           Valid
.
.
.

```

The table below describes the significant fields shown in the display.

Table 28 *show oer master nbar application Field Descriptions*

Field	Description
Appl	Application Name
10.1.1.4	IP address of an OER border router
10.1.1.2	IP address of an OER border router

Field	Description
10.1.1.3	IP address of an OER border router

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
show oer master traffic-class application nbar	Displays information about application traffic classes that are identified using NBAR and are monitored and controlled by an OER master controller.

show oer master policy

To display policy settings on an Optimized Edge Routing (OER) master controller, use the **show oer master policy** command in privileged EXEC mode.

show oer master policy { *sequence-number* | *policy-name* | **default** | **dynamic** }

Syntax Description

<i>sequence-number</i>	Displays only the specified OER map sequence.
<i>policy-name</i>	Displays only the specified OER map name.
default	Displays the default policy information.
dynamic	Displays dynamic policy information.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.4(6)T	The output was modified to display the active probe frequency, if configured.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.4(15)T	The dynamic keyword was added to support the OER application interface.

Usage Guidelines

The **show oer master policy** command is entered on a master controller. The output of this command displays default policy and policies configured with an OER map.

In Cisco IOS Release 12.4(15)T, an OER application interface was introduced. The OER application interface defines the mode of communication and messaging between applications and the network for the purpose of optimizing the traffic associated with the applications. A provider is defined as an entity outside the network in which the router configured as an OER master controller exists, for example, an ISP, or a branch office of the same company. The provider has one or more host devices running one or more applications that use the OER application interface to communicate with an OER master controller. The OER application interface allows applications running on a host device in the provider network to dynamically create policies to influence the existing traffic classes, or specify new traffic class criteria. The **dynamic** keyword displays the policies dynamically created by an application interface provider application.

Examples

The following example displays default policy and policies configured in an OER map named CUSTOMER. The asterisk(*) character is displayed next to policy settings that override default settings.

```
Router# show oer master policy
* Overrides Default Policy Setting
Default Policy Settings:
  backoff 300 3000 300
  delay relative 50
  holddown 300
  periodic 0
  mode route control
  mode monitor both
  mode select-exit best
  loss relative 10
  unreachable relative 50
  resolve delay priority 11 variance 20
  resolve utilization priority 12 variance 20
oer-map CUSTOMER 10
  match ip prefix-lists: NAME
  backoff 300 3000 300
  delay relative 50
  holddown 300
  periodic 0
  mode route control
  mode monitor both
  mode select-exit best
  loss relative 10
  unreachable relative 50
  *resolve utilization priority 1 variance 10
  *resolve delay priority 11 variance 20
  *probe frequency 30
oer-map CUSTOMER 20
  match ip prefix-lists:
  match oer learn delay
  backoff 300 3000 300
  delay relative 50
  holddown 300
  periodic 0
  *mode route control
  mode monitor both
  mode select-exit best
  loss relative 10
  unreachable relative 50
  resolve delay priority 11 variance 20
  resolve utilization priority 12 variance 20
```

The table below describes the significant fields shown in the display.

Table 29 *show oer master policy Field Descriptions*

Field	Description
Default Policy Settings:	Displays OER default configuration settings under this heading.
oer-map...	Displays the OER map name and sequence number. The policy settings applied in the OER map are displayed under this heading.

The following example displays dynamic policies created by applications using the OER application interface. The asterisk(*) character is displayed next to policy settings that override default settings.

```
Router# show oer master policy dynamic
Dynamic Policies:

  proxy id 10.3.3.3
  sequence no. 18446744069421203465, provider id 1001, provider priority 65535
```

```

    host priority 65535, policy priority 101, Session id 9
backoff 90 90 90
delay relative 50
holddown 90
periodic 0
probe frequency 56
mode route control
mode monitor both
mode select-exit good
loss relative 10
jitter threshold 20
mos threshold 3.60 percent 30
unreachable relative 50
next-hop not set
forwarding interface not set
resolve delay priority 11 variance 20
resolve utilization priority 12 variance 20

proxy id 10.3.3.3
sequence no. 18446744069421269001, provider id 1001, provider priority 65535
    host priority 65535, policy priority 102, Session id 9
backoff 90 90 90
delay relative 50
holddown 90
periodic 0
probe frequency 56
mode route control
mode monitor both
mode select-exit good
loss relative 10
jitter threshold 20
mos threshold 3.60 percent 30
unreachable relative 50
next-hop not set
forwarding interface not set
resolve delay priority 11 variance 20
resolve utilization priority 12 variance 20

proxy id 10.3.3.4
sequence no. 18446744069421334538, provider id 1001, provider priority 65535
    host priority 65535, policy priority 103, Session id 10
backoff 90 90 90
delay relative 50
holddown 90
periodic 0
probe frequency 56
mode route control
mode monitor both
mode select-exit good
loss relative 10
jitter threshold 20
mos threshold 3.60 percent 30
unreachable relative 50
next-hop not set
forwarding interface not set
resolve delay priority 11 variance 20
resolve utilization priority 12 variance 20

```

The table below describes the significant fields shown in the display.

Table 30 *show oer master policy dynamic Field Descriptions*

Field	Description
Dynamic Policies:	Displays OER dynamic policy configurations under this heading.
proxy id	IP address of the host application interface device that created the policy.

Field	Description
sequence no.	Number indicating the sequence in which the policy was run.
provider id	ID number of the application interface provider.
provider priority	The priority assigned to the application interface provider. If a priority has not been configured, the default priority is 65535.
host priority	The priority assigned to the host application interface device. If a priority has not been configured, the default priority is 65535.
policy priority	The priority assigned to the policy.
Session id	ID number of the application interface provider session.

Related Commands

Command	Description
api provider	Registers an application interface provider with an OER master controller and enters OER master controller application interface provider configuration mode.
host-address	Configures information about a host device used by an application interface provider to communicate with an OER master controller.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

show oer master prefix

To display the status of monitored prefixes, use the **show oer master prefix** command in privileged EXEC mode.

```
show oer master prefix [detail | inside [detail] | learned [delay | inside | throughput] | prefix
[detail | policy | report | traceroute [exit-id | border-address | current] [now]]]
```

Syntax Description

detail	(Optional) Displays detailed prefix information about the specified prefix or all prefixes.
inside	(Optional) Displays detailed prefix information about inside prefixes.
learned	(Optional) Displays information about learned prefixes.
delay	(Optional) Displays information about learned prefixes based on delay.
throughput	(Optional) Displays information about learned prefixes based on throughput.
<i>prefix</i>	(Optional) Specifies the prefix, entered as an IP address and bit length mask.
policy	(Optional) Displays policy information for the specified prefix.
report	(Optional) Displays detailed performance information and information about report requests from Optimized Edge Routing (OER) application interface providers for the specified prefix.
traceroute	(Optional) Displays path information from traceroute probes.
<i>exit-id</i>	(Optional) Displays path information based on the OER assigned exit ID.
<i>border-address</i>	(Optional) Display path information sourced from the specified border router.
current	(Optional) Displays traceroute probe statistics from the most recent traceroute probe.
now	(Optional) Initiates a new traceroute probe and displays the statistics that are returned.

Command Modes Privileged EXEC (#)

Command History	Release	Modification
	12.3(8)T	This command was introduced.
	12.3(14)T	Support for traceroute reporting was added.
	12.4(6)T	The output was modified to support jitter and MOS reporting.
	12.4(9)T	The inside keyword was added to support OER BGP inbound optimization.
	12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
	12.4(15)T	This command was modified. The report keyword was added to support the Performance Routing - Application Interface feature.
	12.4(24)T	This command was modified. The output was modified to support the Protocol Independent Route Optimization (PIRO) feature.
	15.0(1)M	This command was modified. The output was modified to support EIGRP route control.
	12.2(33)SRE	This command was modified. The output was modified to support EIGRP route control and the PIRO feature.

Usage Guidelines

The **show oer master prefix** command is entered on a master controller. This command is used to display the status of monitored prefixes. The output from this command includes information about the source border router, current exit interface, prefix delay, and egress and ingress interface bandwidth. The output can be filtered to display information for only a single prefix, learned prefixes, inside prefixes, and prefixes learned based on delay or throughput.

The **traceroute** keyword is used to display traceroute probe results. The output generated by this keyword provides hop by hop statistics to the probe target network. The output can be filtered to display information only for the exit ID (OER assigns an ID number to each exit interface) or for the specified border router. The **current** keyword displays traceroute probe results from the most recent traceroute probe. The **now** keyword initiates a new traceroute probe and displays the results.

Examples

The following example shows the status of a monitored prefix:

```
Router# show oer master prefix
OER Prefix Stats:
  Dly: Delay in ms
```

```

EBw: Egress Bandwidth
IBw: Ingress Bandwidth
Prefix      State      Curr BR   CurrI/F  Dly    EBw    IBw
-----
10.1.5.0/24 INPOLICY  10.1.1.2 Et1/0    19     1     1

```

The table below describes the significant fields shown in the display.

Table 31 *show oer master prefix Field Descriptions*

Field	Description
Prefix	IP address and prefix length.
State	Status of the prefix.
Curr BR	Border router from which these statistics were gathered.
Curr I/F	Current exit link interface on the border router.
Dly	Delay in milliseconds.
EBw	Egress bandwidth.
IBw	Ingress bandwidth.

The following output shows the detailed status of a monitored prefix:

```

Router# show oer master prefix detail

Prefix: 10.1.1.0/26
  State: DEFAULT*      Time Remaining: @7
  Policy: Default
  Most recent data per exit
  Border      Interface      PasSDly  PasLDly  ActSDly  ActLDly
*10.2.1.1    Et1/0              181      181      250      250
10.2.1.2    Et2/0               0         0        351      351
10.3.1.2    Et3/0               0         0         94      943
  Latest Active Stats on Current Exit:
  Type      Target      TPort  Attem  Comps      DSum      Min      Max      Dly
  echo     10.1.1.1      N       2      2         448      208     240     224
  echo     10.1.1.2      N       2      2         488      228     260     244
  echo     10.1.1.3      N       2      2         568      268     300     284
  Prefix performance history records
  Current index 2, S_avg interval(min) 5, L_avg interval(min) 60
  Age      Border      Interface      OOP/RteChg Reasons
  Pas: DSum  Samples  DAVg  PktLoss  Unreach  Ebytes  Ibytes  Pkts  Flows
  Act: Dsum  Attempts  DAVg  Comps  Unreach
00:00:03  10.1.1.1  Et1/0
           0         0         0         0         0         0         0         0
           1504        6      250         6         0

```

The table below describes the significant fields shown in the display.

Table 32 *show oer master prefix detail Field Descriptions*

Field	Description
Prefix	IP address and prefix length.
State	Status of the prefix.

Field	Description
Time Remaining	Time remaining in the current prefix learning cycle.
Policy	The state that the prefix is in. Possible values are Default, In-policy, Out-of-policy, Choose, and Holddown.
Most recent data per exit	Border router exit link statistics for the specified prefix. The asterisk (*) character indicates the exit that is being used.
Latest Active Stats on Current Exit	Active probe statistics. This field includes information about the probe type, target IP address, port number, and delay statistics.
Type	The type of active probe. Possible types are ICMP echo, TCP connect, or UDP echo. The example uses default ICMP echo probes (default TCP), so no port number is displayed.
Prefix performance history records	Displays border router historical statistics. These statistics are updated about once a minute and stored for 1 hour.

The following example shows prefix statistics from a traceroute probing:

```

Router# show oer master prefix 10.1.5.0/24 traceroute
* - current exit, + - control more specific
Ex - Exit ID, Delay in msec
-----
Path for Prefix: 10.1.5.0/24          Target: 10.1.5.2
Exit ID: 2, Border: 10.1.1.3        External Interface: Et1/0
Status: DONE, How Recent: 00:00:08 minutes old
Hop  Host           Time(ms) BGP
1   10.1.4.2         8        0
2   10.1.3.2         8        300
3   10.1.5.2         20       50
-----
Exit ID: 1, Border: 10.1.1.2        External Interface: Et1/0
Status: DONE, How Recent: 00:00:06 minutes old
Hop  Host           Time(ms) BGP
1   0.0.0.0          3012     0
2   10.1.3.2         12       100
3   10.1.5.2         12       50
-----

```

The table below describes the significant fields shown in the display.

Table 33 *show oer master prefix traceroute Field Descriptions*

Field	Description
Path for Prefix	Specified IP address and prefix length.
Target	Traceroute probe target.
Exit ID	OER assigned exit ID.

Field	Description
Status	Status of the traceroute probe.
How Recent	Time since last traceroute probe.
Hop	Hop number of the entry.
Host	IP address of the entry.
Time	Time, in milliseconds, for the entry.
BGP	BGP autonomous system number for the entry.

The following example shows prefix statistics including Jitter and MOS percentage values when the Jitter probe is configured for the 10.1.5.0 prefix:

```
Router# show oer master prefix 10.1.5.0/24
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter, MOS - Mean Opinion Score,
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
Prefix          State      Time Curr BR          CurrI/F      Protocol
                PasSDly  PasLDly  PasSUn  PasLUn  PasSLos  PasLLos
                ActSDly  ActLDly  ActSUn  ActLUn   EBw      IBw
                %ActSJit %ActPMOS
-----
10.1.1.0/24     DEFAULT*  @3 10.1.1.1      Et5/0        U
                U        U        0        0        0        0
                6        6  400000  400000    17       1
                1.45    25
```

The table below describes the significant fields shown in the display that are different from the show oer master prefix Field Descriptions table and the show oer master prefix detail Field Descriptions table.

Table 34 *show oer master prefix (Jitter and MOS) Field Descriptions*

Field	Description
Protocol	Protocol: U (UDP).
PasSDly	Delay, in milliseconds, in short-term statistics from passive probe monitoring. If no statistics are reported, it displays U for unknown.
PasLDly	Delay, in milliseconds, in long-term statistics from passive probe monitoring. If no statistics are reported, it displays U for unknown.
PasSUn	Number of passively monitored short-term unreachable packets in flows-per-million.
PasLUn	Number of passively monitored long-term unreachable packets in flows-per-million.

Field	Description
PasSLoS	Number of passively monitored short-term lost packets in packets-per-million.
PasLLoS	Number of passively monitored long-term lost packets in packets-per-million.
ActSDly	Number of actively monitored short-term delay packets.
ActLDly	Number of actively monitored long-term delay packets.
ActSUn	Number of actively monitored short-term unreachable packets in flows-per-million.
ActLUn	Number of actively monitored long-term unreachable packets in flows-per-million.
ActSJit	Number of actively monitored short-term jitter packets.
ActPMOS	Number of actively monitored MOS packets with a percentage below threshold.

The following example shows detailed prefix statistics when Jitter or MOS are configured as a priority:

```

Router# show oer master prefix 10.1.1.0/24 detail
Prefix: 10.1.1.0/24
  State: DEFAULT*      Time Remaining: @9
  Policy: Default
  Most recent data per exit
  Border      Interface      PasSDly  PasLDly  ActSDly  ActLDly
*10.1.1.1    Et5/0              0         0         6         6
10.2.2.3    Et2/0              0         0         7         7
10.1.1.2    Et0/0              0         0        14        14
  Most recent voice data per exit
  Border      Interface      ActSJit  ActPMOS
*10.1.1.1    Et5/0          2.00     0
10.2.2.3    Et2/0          2.01     20
10.1.1.2    Et0/0          4.56     50
  Latest Active Stats on Current Exit:
  Type      Target      TPort  Attem  Comps    DSum     Min     Max     Dly
udpJit     10.1.1.8    2000   2      2        8        4      4      4
udpJit     10.1.1.7    3000   2      2       20       4     16     10
udpJit     10.1.1.6    4000   2      2        8        4      4      4
echo       10.1.1.4    N      2      0         0        0      0      0
echo       10.1.1.3    N      2      0         0        0      0      0
  Latest Voice Stats on Current Exit:
  Type      Target      TPort  Codec  Attem  Comps  JitSum  MOS
udpJit     10.1.1.8    2000   g711alaw  2      2     2.34   4.56
udpJit     10.1.1.7    3000   g711ulaw  2      2     2.56   4.11
udpJit     10.1.1.6    4000   g729a    2      2     1.54   3.57
udpJit     10.1.1.5    4500   none     2      2     1.76   NA
  Prefix performance history records
  Current index 3, S_avg interval(min) 5, L_avg interval(min) 60
  Age      Border      Interface      OOP/RteChg  Reasons
Pas: DSum  Samples  DAvG  PktLoss  Unreach  Ebytes  Ibytes  Pkts  Flows
Act: Dsum  Attempts  DAvG  Comps  Unreach  Jitter  LoMOSCn  MOSCn
00:00:07  10.1.1.1  Et5/0
0         0         0         0         0         5920    0      148    1
          36        10        6         6         4         2        1      1
00:01:07  10.1.1.1  Et5/0

```

```

      0      0      0      0      0      12000      12384      606      16
    36      10      6      6      4      3      0      1
00:02:07 10.1.1.1      Et5/0
      0      0      0      0      0      409540      12040      867      9
    36      10      6      6      4      15      1      1

```

The table below describes the significant fields shown in the display that are different from the show oer master prefix detail Field Descriptions table.

Table 35 *show oer master prefix detail (Jitter or MOS Priority) Field Descriptions*

Field	Description
Codec	Displays the codec value configured for MOS calculation. Codec values can be one of the following: g711alaw, g711ulaw, or g729a.
JitSum	Summary of jitter.
MOS	MOS value.
Jitter	Jitter value.
LoMOSCnt	MOS-low count.

The following example shows prefix statistics including information about application interface provider report requests for the 10.1.1.0 prefix:

```

Router# show oer master prefix 10.1.1.0/24 report
Prefix Performance Report Request
  Created by: Provider 1001, Host 10.3.3.3, Session 9
  Last report sent 3 minutes ago, context 589855, frequency 4 min

Prefix Performance Report Request
  Created by: Provider 1001, Host 10.3.3.4, Session 10
  Last report sent 1 minutes ago, context 655372, frequency 3 min

OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied

Prefix              State      Time Curr BR      CurrI/F      Protocol
PasSDly PasLDly  PasSUn  PasLUn  PasSLos  PasLLos
ActSDly ActLDly  ActSUn  ActLUn  EBw      IBw
ActSJit ActPMOS  ActSLos ActLLos
-----
10.1.1.0/24        INPOLICY      0 10.3.3.3      Et4/3      BGP
                   N              N              N              N              N
                   138            145            0              0              N              N
                   N              N

```

The table below describes the significant fields shown in the display that are different from the show oer master prefix Field Descriptions, show oer master prefix detail Field Descriptions and show oer master prefix (Jitter and MOS) Field Descriptions tables.

Table 36 *show oer master prefix report Field Descriptions*

Field	Description
Provider	Application interface provider ID.
Host	IP address of a host device in the application interface provider network.
Session	Session number automatically allocated by OER when an application interface provider initiates a session.
Last report sent	The number of minutes since a report was sent to the application interface provider.
ActSLos	Number of actively monitored short-term lost packets in packets-per-million.
ActLDly	Number of actively monitored long-term lost packets in packets-per-million.

In Cisco IOS Release 12.4(24)T, 12.2(33)SRE, and later releases, PIRO introduced the ability for OER to search for a parent route--an exact matching route, or a less specific route--in any IP Routing Information Base (RIB). The following example shows that the protocol displayed for the prefix 10.1.0.0 is RIB-PBR, which means that the parent route for the traffic class exists in the RIB and policy-based routing is used to control the prefix.

```
Router# show oer master prefix 10.1.0.0
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
Prefix          State      Time Curr BR      CurrI/F      Protocol
                PasSDly PasLDly PasSUn  PasLUn  PasSLos  PasLLos
                ActSDly ActLDly ActSUn  ActLUn  EBw      IBw
                ActSJit ActPMOS ActSLos ActLLos
-----
10.1.0.0/24     INPOLICY    0 10.11.1.3     Et1/0        RIB-PBR
                129       130         0         0         214        473
                U         U           0         0         33         3
                N         N
```

In Cisco IOS Release 15.0(1)M, 12.2(33)SRE, and later releases, EIGRP route control introduced the ability for OER to search for a parent route--an exact matching route, or a less specific route--in the EIGRP routing table. In this example, the protocol displayed for the prefix 10.1.0.0 is EIGRP and this means that the parent route for the traffic class exists in the EIGRP routing table and OER is controlling the prefix.

```
Router# show oer master prefix 10.1.0.0
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
```

```

% - Force Next-Hop, ^ - Prefix is denied
Prefix          State      Time Curr BR      CurrI/F      Protocol
                PasSDly  PasLDly  PasSUn  PasLUn  PasSLos  PasLLos
                ActSDly  ActLDly  ActSUn  ActLUn  EBw      IBw
                ActSJit  ActPMOS
-----
10.1.0.0/16    DEFAULT*  @69  10.1.1.1  Gi1/22      EIGRP
                U        U        0        0        0        0
                U        U        0        0        22       8
                N        N

```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
set traceroute reporting	Configures an OER map to enable traceroute reporting.
traceroute probe-delay	Sets the time interval between traceroute probe cycles.

show oer master traffic-class

To display information about traffic classes that are monitored and controlled by an Optimized Edge Routing (OER) master controller, use the **show oer master traffic-class** command in privileged EXEC mode.

```
show oer master traffic-class [access-list access-list-name | application application-name [prefix] |
inside | learned [delay | inside | list list-name | throughput] | prefix prefix | prefix-list prefix-list-name]
[active] [passive] [status] [detail]
```

Syntax Description

access-list	(Optional) Displays information about traffic classes defined by an access list.
<i>access-list-name</i>	(Optional) Name of an access list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.
application	(Optional) Displays information about application traffic classes.
<i>application-name</i>	(Optional) Name of a predefined static application using fixed ports. See the table below.
<i>prefix</i>	(Optional) An IP address and bit length mask representing a prefix to be cleared.
inside	(Optional) Displays information about inside traffic classes.
learned	(Optional) Displays information about learned traffic classes.
delay	(Optional) Displays information about learned traffic classes defined using delay.
list	(Optional) Displays information about learned traffic classes defined in an OER learn list.
<i>list-name</i>	(Optional) Name of an OER learn list.
throughput	(Optional) Displays information about learned traffic classes defined using throughput.
prefix	(Optional) Displays information about traffic classes defined by a specified destination prefix.
prefix-list	(Optional) Displays information about traffic classes defined by a prefix list.

<i>prefix-list-name</i>	(Optional) Name of a prefix list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.
active	(Optional) Displays active performance monitoring information only.
passive	(Optional) Displays passive performance monitoring information only.
status	(Optional) Displays status information only.
detail	(Optional) Displays detailed information.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(15)T	This command was introduced.
12.2(33)SX14	This command was integrated into Cisco IOS Release 12.2(33)SX14.

Usage Guidelines

The **show oer master traffic-class** command is entered on an OER master controller. This command is used to display information about traffic classes that are configured for monitoring and optimization. In Cisco IOS Release 12.4(15)T, new **traffic-class** and **match traffic-class** commands were introduced to simplify the learning of traffic classes. In Cisco IOS Release 12.4(20)T, the ability to identify a traffic class using Network Based Application Recognition (NBAR) was introduced. Four types of traffic classes can be automatically learned using a **traffic-class** command in a learn list, or manually configured using a **match traffic-class** command in an OER map:

- Traffic classes based on destination prefixes.
- Traffic classes representing custom application definitions using access lists.
- Traffic classes based on a static application mapping name with an optional prefix list filtering to define destination prefixes.
- Traffic classes based on an NBAR-identified application mapping name with an optional prefix list filtering to define destination prefixes.

If none of the **active**, **passive**, or **status** keywords is specified, then the output will display the active, passive, and status information for the traffic classes. To restrict the amount of output, you can specify one or two of the **active**, **passive**, or **status** keywords, but the order of the keywords is important. If you specify the **active** keyword first then the **passive** or **status** keywords can be entered, if you specify the **passive** keyword first, then only the **status** keyword can be entered. The **status** keyword can be entered only by itself; the **active** and **passive** keywords are not accepted if they follow the **status** keyword. The optional **detail** keyword will display detailed output for the traffic classes.

To display information about traffic classes identified using NBAR, use the **show oer master traffic-class application nbar** command.

The table below displays the keywords that represent the application that can be configured with the **show oer master traffic-class** command. Replace the *application-name* argument with the appropriate keyword from the table.

Table 37 **Static Application List Keywords**

Keyword	Protocol	Port
cuseeme	TCP/UDP	7648 7649 7648 7649 24032
dhcp (Client)	UDP/TCP	68
dhcp (Server)	UDP/TCP	67
dns	UDP/TCP	53
finger	TCP	79
ftp	TCP	20 21
gopher	TCP/UDP	70
http	TCP/UDP	80
https	TCP	443
imap	TCP/UDP	143 220
irc	TCP/UDP	194
kerberos	TCP/UDP	88 749
l2tp	UDP	1701
ldap	TCP/UDP	389
mssql	TCP	1443
nfs	TCP/UDP	2049
nntp	TCP/UDP	119
notes	TCP/UDP	1352
ntp	TCP/UDP	123
pcany	UDP TCP	22 5632 65301 5631
pop3	TCP/UDP	110
pptp	TCP	17233
simap	TCP/UDP	585 993 (Preferred)

Keyword	Protocol	Port
sirc	TCP/UDP	994
sldap	TCP/UDP	636
smtp	TCP	25
snntp	TCP/UDP	563
spop3	TCP/UDP	123
ssh	TCP	22
telnet	TCP	23

Examples

The following example shows information about traffic classes destined for the 10.1.1.0/24 prefix:

```
Router# show oer master traffic-class
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied

DstPrefix      Appl_ID Dscp Prot      SrcPort      DstPort SrcPrefix
      Flags      State      Time      CurrBR      CurrI/F Protocol
PasSDly PasLDly PasSUn PasLUn PasSLos PasLLos      EBw      IBw
ActSDly ActLDly ActSUn ActLUn ActSJit ActPMOS ActSLos ActLLos
-----
10.1.1.0/24    N defa    N          N          N N
              #      OOPOLICY    32         10.11.1.3  Et1/0      BGP
              N      N          N          N          N N          N      IBwN
              130   134       0          0          N          N

```

The following example of the **show oer master traffic-class** command with the **inside** keyword shows information about traffic classes:

```
Router# show oer master traffic-class inside
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied

DstPrefix (inside) Appl_ID Dscp Prot      SrcPort      DstPort SrcPrefix
      Flags      State      Time      CurrBR      CurrI/F Protocol
PasSDly PasLDly PasSUn PasLUn PasSLos PasLLos      EBw      IBw
ActSDly ActLDly ActSUn ActLUn ActSJit ActPMOS ActSLos ActLLos
-----
10.0.0.0/16    N N N          N          N N
              DEFAULT*    0          U          U

```

The table below describes the significant fields shown in the display.

Table 38 *show oer master traffic-class Field Descriptions*

Field	Description
DstPrefix	Destination IP address and prefix length for the traffic class.
Appl_ID	Application ID.
Dscp	Differentiated Services Code Point (DSCP) value.
Prot	Protocol.
SrcPort	Source port number for the traffic class.
DstPort	Destination port number for the traffic class.
SrcPrefix	IP address of the traffic class source.
Flags	Special characteristics for the traffic class.
State	Current state of the traffic class.
Time	Time, in seconds, between monitoring messages.
Curr BR	IP address of the border router through which this traffic class is being currently routed.
CurrI/F	Interface of the border router through which this traffic class is being currently routed.
Protocol	Protocol. A value of U means unknown; there is no measurement data.
PasSDly	Passive monitoring short term delay in milliseconds.
PasLDly	Passive monitoring long term delay in milliseconds.
PasSUn	Number of passively monitored short-term unreachable packets in flows per million.
PasLUn	Number of passively monitored long-term unreachable packets in flows per million.
PasSLos	Number of passively monitored short-term lost packets in packets per million.
PasLLos	Number of passively monitored long-term lost packets in packets per million.
EBw	Egress bandwidth.
IBw	Ingress bandwidth.
ActSDly	Active monitoring short-term delay in milliseconds.

Field	Description
ActLDly	Active monitoring long-term delay in milliseconds.
ActSUn	Number of actively monitored short-term unreachable packets in flows per million.
ActLUn	Number of actively monitored long-term unreachable packets in flows per million.
ActSJit	Number of actively monitored short-term jitter packets.
ActPMOS	Number of actively monitored Mean Opinion Score (MOS) packets with a percentage below threshold.
ActSLos	Number of actively monitored short-term packets lost.
ActLLos	Number of actively monitored long-term packets lost.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
show oer master traffic-class application nbar	Displays information about application traffic classes that are identified using NBAR and are monitored and controlled by an OER master controller.

show oer master traffic-class application nbar

To display information about application traffic classes that are identified using Network-Based Application Recognition (NBAR) and are monitored and controlled by an Optimized Edge Routing (OER) master controller, use the **show oer master traffic-class application nbar** command in privileged EXEC mode.

```
show oer master traffic-class application nbar nbar-appl-name [prefix] [[active passive status] | detail]
```

Syntax Description

<i>nbar-appl-name</i>	Name of a dynamic application identified using NBAR. See the Usage Guidelines section for more details.
<i>prefix</i>	(Optional) An IP address and bit length mask representing a prefix.
active	(Optional) Displays active performance monitoring information only.
passive	(Optional) Displays passive performance monitoring information only.
status	(Optional) Displays status information only.
detail	(Optional) Displays detailed information.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The **show oer master traffic-class application nbar** command is entered on an OER master controller. This command is used to display information about application traffic classes that are identified using NBAR. To display information about traffic classes defined using static application mapping, use the **show oer master traffic-class** command.

The optional **detail** keyword will display detailed output for the NBAR application traffic classes. If the **detail** keyword is not specified, and if none of the **active**, **passive**, or **status** keywords is specified, then the output will display the active, passive, and status information for the traffic classes. To restrict the amount of output, specify just one or two of the **active**, **passive**, or **status** keywords. If specified, the **active**, **passive**, or **status** keywords must be specified in the order shown in the syntax.

NBAR is capable of identifying applications based on the following three types of protocols:

- Non-UDP and Non-TCP IP protocols--For example, Generic Routing Encapsulation (GRE), and Internet Control Message Protocol (ICMP).
- TCP and UDP protocols that use statically assigned port numbers--For example, CU-SeeMe desktop video conference (CU-SeeMe-Server) and Post Office Protocol over Transport Layer Security (TLS) and Secure Sockets Layer (SSL) server (SPOP3-Server).
- TCP and UDP protocols that dynamically assign port numbers and require stateful inspection--For example, Real-Time Transport Protocol audio streaming (RTP-audio) and BitTorrent File Transfer Traffic (BitTorrent).

The list of applications identified using NBAR and available for profiling OER or Performance Routing traffic classes is constantly evolving. For lists of many of the NBAR applications defined using static or dynamically assigned ports, see the Using Performance Routing to Profile the Traffic Classes module.

For more details about NBAR, see the Classifying Network Traffic Using NBAR section of the *Cisco IOS Quality of Service Solutions Configuration Guide*.

If the *prefix* argument is specified, only the OER-controlled traffic class that matches the application specified by the *nbar-appl-name* argument and the destination prefix specified by the *prefix* argument are displayed. If the *prefix* argument is not specified, all OER-controlled traffic classes that match the application specified by the *nbar-appl-name* argument, regardless of the destination prefix, are displayed.

Examples

The following example shows information about traffic classes consisting of Real-time Transport Protocol streaming audio (RTP-audio) traffic:

```
Router# show oer master traffic-class application nbar rtp-audio
OER Prefix Statistics:
Pas - Passive, Act - Active, S - Short term, L - Long term, Dly - Delay (ms),
P - Percentage below threshold, Jit - Jitter (ms),
MOS - Mean Opinion Score
Los - Packet Loss (packets-per-million), Un - Unreachable (flows-per-million),
E - Egress, I - Ingress, Bw - Bandwidth (kbps), N - Not applicable
U - unknown, * - uncontrolled, + - control more specific, @ - active probe all
# - Prefix monitor mode is Special, & - Blackholed Prefix
% - Force Next-Hop, ^ - Prefix is denied
-----
DstPrefix      Appl_ID Dscp Prot      SrcPort      DstPort      SrcPrefix
Flags          State      Time          EBw           CurrBR      CurrI/F Protocol
PasSDly      PasLDly    PasSUn    PasLUn        EBw         IBw
ActSDly      ActLDly    ActSUn    ActLUn        ActSJit     ActPMOS
-----
100.1.1.0/28   RTP-Audio defa  N           N             N 0.0.0.0/0
                DEFAULT*    461         101.1.1.2    Et1/0      U
                U           0           1           2
                150        130        0           0           15         0
100.1.1.16/28 RTP-Audio defa  N           N             N 0.0.0.0/0
                DEFAULT*    461         101.1.1.2    Et1/0      U
                U           0           1           2
                250        200        0           0           30         0
```

The table below describes the significant fields shown in the display.

Table 39 show oer master traffic-class Field Descriptions

Field	Description
DstPrefix	Destination IP address and prefix length for the traffic class.

Field	Description
Appl_ID	Application ID. The application can be a static application or an NBAR identified application.
Dscp	Differentiated Services Code Point (DSCP) value.
Prot	Protocol.
SrcPort	Source port number for the traffic class.
DstPort	Destination port number for the traffic class.
SrcPrefix	IP address of the traffic class source.
Flags	Special characteristics for the traffic class, see the key above for details.
State	Current state of the traffic class.
Time	Time, in seconds, between monitoring messages.
Curr BR	IP address of the border router through which this traffic class is being currently routed.
CurrI/F	Interface of the border router through which this traffic class is being currently routed.
Protocol	Protocol. If the traffic class is being controlled by OER this field displays one of the following: BGP, STATIC, or CCE. A value of U means unknown; OER is not controlling the traffic class.
PasSDly	Passive monitoring short term delay in milliseconds.
PasLDly	Passive monitoring long term delay in milliseconds.
PasSUn	Number of passively monitored short term unreachable packets in flows-per-million.
PasLUn	Number of passively monitored long term unreachable packets in flows-per-million.
PasSLos	Number of passively monitored short term lost packets in packets-per-million.
PasLLos	Number of passively monitored long term lost packets in packets-per-million.
EBw	Egress bandwidth.
IBw	Ingress bandwidth.
ActSDly	Active monitoring short term delay in milliseconds.

Field	Description
ActLDly	Active monitoring long term delay in milliseconds.
ActSUn	Number of actively monitored short term unreachable packets in flows-per-million.
ActLUn	Number of actively monitored long term unreachable packets in flows-per-million.
ActSJit	Number of actively monitored short term jitter packets.
ActPMOS	Number of actively monitored Mean Opinion Score (MOS) packets with a percentage below threshold.

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
show oer master traffic-class	Displays information about traffic classes that are monitored and controlled by an OER master controller.

show oer proxy



Note

Effective with Cisco IOS Release 15.0(1)SY, the **show oer proxy** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To display Optimized Edge Routing (OER) proxy information, use the **show oer proxy** command in privileged EXEC mode.

show oer proxy

Syntax Description

This command has no arguments or keywords.

Command Modes

Privileged EXEC (#)

Command History

Release	Modification
12.2(33)SRB	This command was introduced.
12.2(33)SXI	This command was integrated into Cisco IOS Release 12.2(33)SXI.
12.4(24)T	This command was integrated into Cisco IOS Release 12.4(24)T.
15.0(1)SY	This command was modified. This command was hidden.

Examples

The following is sample output from the **show oer proxy** command:

```
Router# show oer proxy
OER PROXY 0.0.0.0 DISABLED, MC 0.0.0.0 UP/DOWN: DOWN
Conn Status: NOT OPEN, Port 3949
```

The table below describes the significant fields shown in the display.

Table 40 *show oer proxy Field Descriptions*

Field	Description
OER PROXY	Displays the IP address and the status of the OER proxy.
MC	Displays the IP address of the master controller (MC).
UP/DOWN	Displays the connection status: UP or DOWN.
Conn Status	Displays the connection status: OPEN or NOT OPEN.
Port	Displays the TCP port number used to communicate with the master controller.

Related Commands

Command	Description
show oer api	Displays information about OER application interface clients.

shutdown (OER)



Note

Effective with Cisco IOS Release 15.0(1)SY, the **shutdown** command is hidden. Although this command is still available in Cisco IOS software, the CLI interactive Help does not display it if you attempt to view it by entering a question mark at the command line. This command will be completely removed in a future release.

To stop an Optimized Edge Routing (OER) master controller or OER border router process without removing the OER process configuration, use the **shutdown** command in OER master controller or OER border router configuration mode. To start a stopped OER process, use the **no** form of this command.

shutdown

no shutdown

Syntax Description

This command has no arguments or keywords.

Command Default

No master controller or border router is stopped.

Command Modes

OER border router configuration (config-oer-br) OER master controller configuration (config-oer-mc)

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
12.2SX	This command is supported in the Cisco IOS Release 12.2SX train. Support in a specific 12.2SX release of this train depends on your feature set, platform, and platform hardware.
15.0(1)SY	This command was modified. This command was hidden.

Usage Guidelines

The **shutdown** command is entered on a master controller or border router. Entering the **shutdown** command stops an active master controller or border router process but does not remove any configuration parameters. The **shutdown** command is displayed in the running configuration file when enabled. To disable a master controller or border router and completely remove the process configuration from the

running configuration file, use the **no oer master** or **no oer border** command in global configuration mode.

Cisco IOS Release 12.2(33)SXH

This command is supported only in OER border router configuration mode.

Examples

The following example stops an active OER border router session:

```
Router(config)# oer border
Router(config-oer-br)# shutdown
```

The following example starts an inactive OER master controller session:

```
Router(config)# oer master
Router(config-oer-mc)# no shutdown
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

throughput

To configure Optimized Edge Routing (OER) to learn the top prefixes based on the highest outbound throughput, use the **throughput** command in Top Talker and Top Delay learning configuration mode or learn list configuration mode. To disable learning based on outbound throughput, use the **no** form of this command.

throughput
no throughput

Syntax Description This command has no arguments or keywords.

Command Default None

Command Modes Learn list configuration (config-oer-mc-learn-list) Top Talker and Top Delay learning configuration (config-oer-mc-learn)

Command History	Release	Modification
	12.3(8)T	This command was introduced.
	12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.
	12.4(15)T	Support for the learn list configuration mode was added to this command.

Usage Guidelines The **throughput** command is entered on a master controller. The master controller creates a list of prefixes based on the highest outbound throughput. This command is used to configure a master controller to learn prefixes based on the highest outbound packet throughput. When this command is enabled, OER will learn the top prefixes across all border routers according to the highest outbound throughput.

Examples

Top Talker and Top Delay Learning Configuration Mode

The following example shows how to configure a master controller to learn the top prefixes based on the highest outbound throughput:

```
Router(config)# oer master
```

```
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# throughput
```

Learn List Configuration Mode

The following example shows how to configure a master controller to learn top prefixes based on the highest throughput for a learn list named LEARN_REMOTE_LOGIN_TC that learns Telnet and Secure Shell (SSH) application TCF entries:

```
Router(config)# oer master
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# list seq 10 refname LEARN_REMOTE_LOGIN_TC
Router(config-oer-mc-learn-list)# traffic-class application telnet ssh
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
```

Related Commands

Command	Description
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
list (OER)	Creates an OER learn list to specify criteria for learning traffic classes and enters learn list configuration mode.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

traceroute probe-delay

To set the time interval between traceroute probe cycles, use the **traceroute probe-delay** command in Optimized Edge Routing (OER) master controller configuration mode. To set the interval between probes to the default value, use the **no** form of this command.

traceroute probe-delay *milliseconds*

no traceroute probe-delay *milliseconds*

Syntax Description

milliseconds

Configures the time interval, in milliseconds, between traceroute probes. The configurable range for this argument is a number from 0 to 65535.

Command Default

The following value is used when this command is not configured or the **no** form is entered:
milliseconds : 1000

Command Modes

OER master controller configuration

Command History

Release	Modification
12.3(14)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **traceroute probe-delay** command is entered on a master controller. This command is used to set the delay interval between traceroute probes.

Continuous and policy based traceroute reporting is configured with the **set traceroute reporting** OER map configuration mode command. The time interval between traceroute probes is configured with the **traceroute probe-delay** command in OER master controller configuration mode. On-demand traceroute probes are triggered by entering the **show oer master prefix** command with the **current** and **now** keywords.

Examples

The following example, which starts in global configuration mode, sets the delay interval between tracertoute probes to 10000 milliseconds:

```
Router(config)# oer master
Router(config-oer-mc)# tracertoute probe-delay 10000
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
set tracertoute reporting	Configures an OER map to enable tracertoute reporting.
show oer master prefix	Displays the status of monitored prefixes.

traffic-class access-list

To define an Optimized Edge Routing (OER) application traffic class using an access list applied to learned traffic flows, use the **traffic-class access-list** command in learn list configuration mode. To disable the definition of OER learned traffic flows into application traffic classes using an access list, use the **no** form of this command.

traffic-class access-list *access-list-name* [**filter** *prefix-list-name*]

no traffic-class access-list

Syntax Description

<i>access-list-name</i>	Name of an access list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.
filter	(Optional) Specifies that the traffic flows are filtered on the basis of a prefix list.
<i>prefix-list-name</i>	(Optional) Name of a prefix list (created using the ip prefix-list command).

Command Default

OER application traffic classes are not defined using an access list.

Command Modes

Learn list configuration (config-oer-mc-learn-list)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **traffic-class access-list** command is used to configure the master controller to automatically learn application traffic defined in an access list. Only one access list can be specified, but the access list may contain many access list entries (ACEs) to help define the traffic class parameters.

In Cisco IOS Release 12.4(15)T, the learn list configuration mode was introduced. Learn lists are a way to categorize learned traffic classes. In each learn list, different criteria for learning traffic classes including prefixes, application definitions, filters, and aggregation parameters can be configured. A traffic class is automatically learned by OER based on each learn list criteria, and each learn list is configured with a sequence number. The sequence number determines the order in which learn list criteria are applied. Learn lists allow different OER policies to be applied to each learn list; in previous releases the traffic classes could not be divided, and an OER policy was applied to all the traffic classes.

**Note**

The **traffic-class access-list** command, the **traffic-class application** command, and the **traffic-class prefix-list** commands are all mutually exclusive in an OER learn list. Only one of these commands can be specified per OER learn list.

Examples

The following example, starting in global configuration mode, shows how to define a custom application traffic class using an access list. Every entry in the access list defines one application, and the destination network of the traffic class is determined by the specified aggregation method. After the access list is configured, the master controller automatically learns the defined application traffic based on highest throughput. A prefix list may be used to filter the traffic flows by destination prefix.

```
Router(config)# ip access-list extended USER_DEFINED_TC
Router(config-ext-nacl)# permit tcp any any 500
Router(config-ext-nacl)# permit tcp any any range 700 750
Router(config-ext-nacl)# permit udp 10.1.1.1 0.0.0.0 any
Router(config-ext-nacl)# permit ip any any dscp ef
Router(config-ext-nacl)# exit
Router(config)# oer master
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# list seq 10 refname LEARN_USER_DEFINED_TC
Router(config-oer-mc-learn-list)# traffic-class access-list USER_DEFINED_TC
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
list (OER)	Creates an OER learn list to specify criteria for learning traffic classes and enters learn list configuration mode.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

traffic-class aggregate

To aggregate Optimized Edge Routing (OER) learned traffic flows into application traffic classes using an access list, use the **traffic-class aggregate** command in OER Top Talker and Top Delay learning configuration mode. To disable the aggregation of OER learned traffic flows into application traffic classes using an access list, use the **no** form of this command.

traffic-class aggregate access-list *access-list-name*

no traffic-class aggregate access-list *access-list-name*

Syntax Description

access-list	Specifies that an IP access list is to be used to aggregate the OER learned traffic flows into application traffic classes.
<i>access-list-name</i>	Name of the access list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.

Command Default

OER learned traffic flows are not aggregated into application traffic classes using an access list.

Command Modes

OER Top Talker and Top Delay learning configuration

Command History

Release	Modification
12.4(9)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **traffic-class aggregate** command can be used with the **traffic-class filter** and **traffic-class keys** commands to configure the master controller to automatically learn defined application traffic. Only one access list can be specified, but the access list may contain many access list entries (ACEs) to help define the traffic class parameters.

**Note**

The **traffic-class aggregate** command is different from the **aggregation-type** command that aggregates learned prefixes based on the type of traffic flow. The **traffic-class aggregate** command introduces the ability to use an access list to aggregate learned traffic flows to create an application traffic class. Both commands can be used in the same configuration.

Examples

The following example, starting in global configuration mode, configures the master controller to automatically learn defined application traffic. In this example, two access lists are created to identify and define voice traffic in the network. Using the **traffic-class aggregate** and the **traffic-class filter** commands with the access lists, only voice traffic with a Differentiated Services Code Point (DSCP) bit set to ef, a User Datagram Protocol (UDP), and a destination port in the range of 3000 to 4000 is learned and added to the OER application database on the master controller.

```
Router(config)# ip access-list extended voice-filter-acl
Router(config-ext-nacl)# permit udp any 10.1.0.0 0.0.255.255 dscp ef

Router(config-ext-nacl)# exit
Router(config)# ip access-list extended voice-agg-acl
Router(config-ext-nacl)# permit udp any any range 3000 4000 dscp ef

Router(config-ext-nacl)# exit
Router(config)# oer master

Router(config-oer-master)# learn

Router(config-oer-master-learn)# aggregation-type prefix-length 24

Router(config-oer-master-learn)# throughput

Router(config-oer-master-learn)# traffic-class filter access-list voice-filter-acl

Router(config-oer-master-learn)# traffic-class aggregate access-list voice-agg-acl
Router(config-oer-master-learn)# traffic-class keys protocol dport dscp
Router(config-oer-master-learn)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
traffic-class filter	Filters uninteresting traffic from OER learned traffic flows using an access list.

Command	Description
traffic-class keys	Specifies a key list used by an OER border router to aggregate the traffic flows into learned application classes.

traffic-class application

To define an Optimized Edge Routing (OER) traffic class using a predefined static application, use the **traffic-class application** command in learn list configuration mode. To remove the definition of an OER learned traffic class using a predefined static application, use the **no** form of this command.

traffic-class application *application-name* [**filter** *prefix-list-name*]

no traffic-class application *application-name* [**filter** *prefix-list-name*]

Syntax Description

<i>application-name</i>	Name of a predefined static application using fixed ports. See the table below.
filter	(Optional) Specifies that the traffic flows are filtered on the basis of a prefix list.
<i>prefix-list-name</i>	(Optional) Name of a prefix list (created using the ip prefix-list command).

Command Default

OER traffic classes are not defined using a static application mapping.

Command Modes

Learn list configuration (config-oer-mc-learn-list)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **traffic-class application** command is used to configure the master controller to automatically learn traffic using a keyword that represents an application. OER maps the application keyword to a protocol--TCP or UDP, or both--and one or more ports and this mapping is shown in the table below. More than one application can be configured as part of the traffic class.

In Cisco IOS Release 12.4(15)T, the learn list configuration mode was introduced. Learn lists are a way to categorize learned traffic classes. In each learn list, different criteria for learning traffic classes including prefixes, application definitions, filters, and aggregation parameters can be configured. A traffic class is automatically learned by OER based on each learn list criteria, and each learn list is configured with a sequence number. The sequence number determines the order in which learn list criteria are applied. Learn lists allow different OER policies to be applied to each learn list; in previous releases, the traffic classes could not be divided, and an OER policy was applied to all the traffic classes.

**Note**

The **traffic-class access-list** command, the **traffic-class application** command, the **traffic-class application nbar** command, and the **traffic-class prefix-list** commands are all mutually exclusive in an OER learn list. Only one of these commands can be specified per OER learn list.

The table below displays the keywords that represent the application that can be configured with the **traffic-class application** command. Replace the *application-name* argument with the appropriate keyword from the table.

Table 41 **Static Application List Keywords**

Keyword	Protocol	Port
cuseeme	TCP UDP	7648 7649 7648 7649 24032
dhcp (Client)	UDP/TCP	68
dhcp (Server)	UDP/TCP	67
dns	UDP/TCP	53
finger	TCP	79
ftp	TCP	20 21
gopher	TCP/UDP	70
http	TCP/UDP	80
https	TCP	443
imap	TCP/UDP	143 220
irc	TCP/UDP	194
kerberos	TCP/UDP	88 749
l2tp	UDP	1701
ldap	TCP/UDP	389
mssql	TCP	1443
nfs	TCP/UDP	2049
nntp	TCP/UDP	119
notes	TCP/UDP	1352
ntp	TCP/UDP	123
pcany	UDP TCP	22 5632 65301 5631
pop3	TCP/UDP	110

Keyword	Protocol	Port
pptp	TCP	17233
simap	TCP/UDP	585 993 (Preferred)
sirc	TCP/UDP	994
sldap	TCP/UDP	636
sntp	TCP	25
snntp	TCP/UDP	563
spop3	TCP/UDP	123
ssh	TCP	22
telnet	TCP	23

Examples

The following example, starting in global configuration mode, shows how to define application traffic classes using two OER learn lists, LEARN_REMOTE_LOGIN_TC and LEARN_FILE_TRANSFER_TC. The number of traffic classes to be learned in both learn list sessions is set to 50, and the maximum number of traffic classes to be learned for all sessions of the learn list is set to 90. The remote login traffic class is configured using keywords representing Telnet and Secure Shell (SSH) traffic and the resulting prefixes are aggregated to a prefix length of 24. The file transfer traffic class is configured using a keyword that represents FTP and is also aggregated to a prefix length of 24. A prefix-list is applied to the file transfer traffic class to permit traffic from the 10.0.0.0/8 prefix. The master controller is configured to learn the top prefixes based on highest outbound throughput for the filtered traffic and the resulting traffic classes are added to the OER application database to be passively and actively monitored.

```
Router(config)# ip prefix-list INCLUDE_10_NET 10.0.0.0/8
Router(config)# oer master
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# list seq 10 refname LEARN_REMOTE_LOGIN_TC
Router(config-oer-mc-learn-list)# count 50 max 90
Router(config-oer-mc-learn-list)# traffic-class application telnet ssh
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# exit
Router(config-oer-mc-learn)# list seq 20 refname LEARN_FILE_TRANSFER_TC
Router(config-oer-mc-learn-list)# count 50 max 90
Router(config-oer-mc-learn-list)# traffic-class application ftp filter INCLUDE_10_NET
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.

Command	Description
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
list (OER)	Creates an OER learn list to specify criteria for learning traffic classes and enters learn list configuration mode.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
traffic-class application nbar	Defines an OER traffic class using an NBAR application mapping.

traffic-class application nbar

To define an Optimized Edge Routing (OER) traffic class using an Network-Based Application Recognition (NBAR) application mapping, use the **traffic-class application nbar** command in learn list configuration mode. To remove the definition of an OER learned traffic class using an application identified using NBAR, use the **no** form of this command.

traffic-class application nbar *nbar-appl-name* [*nbar-appl-name* ...] [**filter** *prefix-list-name*]

no traffic-class application nbar [*nbar-appl-name* ...]

Syntax Description

<i>nbar-appl-name</i>	Keyword representing the name of a dynamic application identified using NBAR. One application must be specified, but the ellipses show that more than one application keyword can be specified, up to a maximum of ten. See the Usage Guidelines section for more details.
filter	(Optional) Specifies that the traffic flows are filtered on the basis of a prefix list.
<i>prefix-list-name</i>	(Optional) Name of a prefix list (created using the ip prefix-list command).

Command Default

OER traffic classes are not defined using an NBAR application mapping.

Command Modes

Learn list configuration (config-oer-mc-learn-list)

Command History

Release	Modification
12.4(20)T	This command was introduced.

Usage Guidelines

The **traffic-class application nbar** command is used to configure the master controller to automatically learn traffic using a keyword that represents an application that can be identified using NBAR. More than one application can be configured as part of the traffic class with a maximum of ten applications entered per command line. Enter multiple **traffic-class application nbar** command statements if you need to specify more than ten applications.

NBAR is capable of identifying applications based on the following three types of protocols:

- Non-UDP and Non-TCP IP protocols--For example, Generic Routing Encapsulation (GRE), and Internet Control Message Protocol (ICMP).

- TCP and UDP protocols that use statically assigned port numbers--For example, CU-SeeMe desktop video conference (CU-SeeMe-Server) and Post Office Protocol over Transport Layer Security (TLS) and Secure Sockets Layer (SSL) server (SPOP3-Server).
- TCP and UDP protocols that dynamically assign port numbers and require stateful inspection--For example, Real-Time Transport Protocol audio streaming (RTP-audio) and BitTorrent File Transfer Traffic (BitTorrent).

Use the **traffic-class application nbar ?** command to determine if an application can be identified using NBAR and replace the *nbar-appl-name* argument with the appropriate keyword from the screen display.

The list of applications identified using NBAR and available for profiling of OER or Performance Routing traffic classes is constantly evolving. For lists of many of the NBAR applications defined using static or dynamically assigned ports, see the Using Performance Routing to Profile the Traffic Classes module.

For more details about NBAR, see the Classifying Network Traffic Using NBAR section of the *Cisco IOS Quality of Service Solutions Configuration Guide* .

In Cisco IOS Release 12.4(15)T, the learn list configuration mode was introduced. Learn lists are a way to categorize learned traffic classes. In each learn list, different criteria for learning traffic classes including prefixes, application definitions, filters, and aggregation parameters can be configured. A traffic class is automatically learned by OER based on each learn list criteria, and each learn list is configured with a sequence number. The sequence number determines the order in which learn list criteria are applied. Learn lists allow different OER policies to be applied to each learn list; in previous releases, the traffic classes could not be divided, and an OER policy was applied to all the traffic classes.



Note

The **traffic-class access-list** command, the **traffic-class application** command, the **traffic-class application nbar** command, and the **traffic-class prefix-list** commands are all mutually exclusive in an OER learn list. Only one of these commands can be specified per OER learn list.

Examples

The following example, starting in global configuration mode, shows how to define application traffic classes identified by using NBAR and two OER learn lists, LEARN_VOICE_TC and LEARN_VIDEO_TC. The number of traffic classes to be learned in both learn list sessions is 50, and the maximum number of traffic classes to be learned for all sessions of the learn list is 90.

The Voice over IP (VoIP) traffic class is configured using keywords representing RTP-Audio and the resulting prefixes are aggregated to a prefix length of 24. The video traffic class is configured using a keyword that represents RTP-video and is also aggregated to a prefix length of 24. A prefix list is applied to the video traffic class to match traffic for the destination prefix of 10.0.0.0/8. The master controller is configured to learn the top prefixes based on highest outbound throughput for the learned traffic, and the resulting traffic classes are added to the OER application database.

The traffic streams that the learn list profiles for both the RTP-audio and the RTP-video applications are:

```
10.1.1.1
10.1.2.1
20.1.1.1
20.1.2.1
```

The traffic classes that are learned for each application are:

```
10.1.1.0/24 rtp-audio
10.1.2.0/24 rtp-audio
20.1.1.0/24 rtp-audio
20.1.2.0/24 rtp-audio
```

```
10.1.1.0/24 rtp-video
10.1.2.0/24 rtp-video
```

The difference in traffic classes learned is due to the optional INCLUDE_10_NET prefix list that only includes RTP-video application traffic with a destination prefix that matches the prefix 10.0.0.0/8.

```
Router(config)# ip prefix-list INCLUDE_10_NET 10.0.0.0/8
Router(config)# oer master
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# list seq 10 refname LEARN_VOICE_TC
Router(config-oer-mc-learn-list)# count 50 max 90
Router(config-oer-mc-learn-list)# traffic-class application nbar rtp-audio
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# exit
Router(config-oer-mc-learn)# list seq 20 refname LEARN_VIDEO_TC
Router(config-oer-mc-learn-list)# count 50 max 90
Router(config-oer-mc-learn-list)# traffic-class application nbar rtp-video
filter INCLUDE_10_NET
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
list (OER)	Creates an OER learn list to specify criteria for learning traffic classes and enters learn list configuration mode.
match traffic-class application nbar	Defines a match clause using an NBAR application mapping in an OER map to create a traffic class.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

traffic-class filter

To filter uninteresting traffic from Optimized Edge Routing (OER) learned traffic flows using an access list, use the **traffic-class filter** command in OER Top Talker and Top Delay learning configuration mode. To disable the filtering of OER learned traffic flows using an access list, use the **no** form of this command.

traffic-class filter access-list *access-list-name*

no traffic-class filter access-list *access-list-name*

Syntax Description

access-list	Specifies that an IP access list is to be used to filter uninteresting traffic from OER learned traffic flows.
<i>access-list-name</i>	Name of the access list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.

Command Default

Uninteresting traffic is not filtered from OER traffic flows using an access list.

Command Modes

OER Top Talker and Top Delay learning configuration

Command History

Release	Modification
12.4(9)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

OER is used to optimize the performance of selected traffic flows in your network. While defining the selected traffic flows, this command is used to filter out traffic that you are not interested in optimizing.

The **traffic-class filter** command can be used with the **traffic-class aggregate** and **traffic-class keys** commands to configure the master controller to automatically learn defined application traffic. Only one access list can be specified, but the access list may contain many access list entries (ACEs) to help define the traffic class parameters.

Examples

The following example, starting in global configuration mode, configures the master controller to automatically learn defined application traffic. In this example, two access lists are created to identify and define voice traffic in the network. Using the **traffic-class aggregate** and the **traffic-class filter** commands with the access lists, only voice traffic with a Differentiated Services Code Point (DSCP) bit set to ef, a User Datagram Protocol (UDP), and a destination port in the range of 3000 to 4000 is learned and added to the OER application database on the master controller.

```
Router(config)# ip access-list extended voice-filter-acl
Router(config-ext-nacl)# permit udp any 10.1.0.0 0.0.255.255 dscp ef

Router(config-ext-nacl)# exit
Router(config)# ip access-list extended voice-agg-acl
Router(config-ext-nacl)# permit udp any any range 3000 4000 dscp ef

Router(config-ext-nacl)# exit
Router(config)# oer master

Router(config-oer-master)# learn

Router(config-oer-master-learn)# aggregation-type prefix-length 24

Router(config-oer-master-learn)# throughput

Router(config-oer-master-learn)# traffic-class filter access-list voice-filter-acl

Router(config-oer-master-learn)# traffic-class aggregate access-list voice-agg-acl
Router(config-oer-master-learn)# traffic-class keys dscp protocol dport
Router(config-oer-master-learn)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
traffic-class aggregate	Aggregates OER learned traffic flows into application traffic classes using an access list.
traffic-class keys	Specifies a key list used by an OER border router to aggregate the traffic flows into learned application classes.

traffic-class keys

To specify a key list of fields in the traffic flows that an Optimized Edge Routing (OER) border router uses to aggregate traffic flows into application traffic classes, use the **traffic-class keys** command in OER Top Talker and Top Delay learning configuration mode. To remove the key list, use the **no** form of this command.

```
traffic-class keys [default | [dscp] [protocol [dport] [sport]]]
```

```
no traffic-class keys [default | [dscp] [protocol [dport] [sport]]]
```

Syntax Description

default	(Optional) Aggregates the traffic flows into application traffic classes on the basis of protocol and destination port.
dscp	(Optional) Aggregates the traffic flows into application traffic classes on the basis of Differentiated Services Code Point (DSCP) value.
protocol	(Optional) Aggregates the traffic flows into application traffic classes on the basis of the protocol.
dport	(Optional) Aggregates the traffic flows into application traffic classes on the basis of the destination port.
sport	(Optional) Aggregates the traffic flows into application traffic classes on the basis of the source port.

Command Default

No OER traffic class key lists are created.

Command Modes

OER Top Talker and Top Delay learning configuration

Command History

Release	Modification
12.4(9)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **traffic-class keys** command can be used with the **traffic-class filter** and **traffic-class aggregate** commands to configure the master controller to automatically learn defined application traffic. This command is used only if the **traffic-class aggregate** command is not configured or returns no matches.

Examples

In this following task, the **traffic-class filter** command references an access list that is used to filter out unwanted traffic, and an access list with aggregation criteria aggregates the traffic into subsets of traffic classes using the **traffic-class aggregate** command. Traffic class keys are specified with the **traffic-class keys** command, but they will be used only if the traffic class aggregation access list does not have any matches. Usually traffic class keys are specified when there is no traffic class aggregation. In this example, only voice traffic with a DSCP bit set to ef, a User Datagram Protocol (UDP), and a destination port in the range of 3000 to 4000 is learned and added to the OER application database on the master controller.

```
Router(config)# ip access-list extended voice-filter-acl
Router(config-ext-nacl)# permit udp any 10.1.0.0 0.0.255.255 dscp ef

Router(config-ext-nacl)# exit
Router(config)# ip access-list extended voice-agg-acl
Router(config-ext-nacl)# permit udp any any range 3000 4000 dscp ef

Router(config-ext-nacl)# exit
Router(config)# oer master

Router(config-oer-master)# learn

Router(config-oer-master-learn)# aggregation-type prefix-length 24

Router(config-oer-master-learn)# throughput

Router(config-oer-master-learn)# traffic-class filter access-list voice-filter-acl

Router(config-oer-master-learn)# traffic-class aggregate access-list voice-agg-acl
Router(config-oer-master-learn)# traffic-class keys dscp protocol dport
Router(config-oer-master-learn)# end
```

Related Commands

Command	Description
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.
traffic-class aggregate	Aggregates OER learned traffic flows into application traffic classes using an access list.
traffic-class filter	Filters uninteresting traffic from OER learned traffic flows using an access list.

traffic-class prefix-list

To define an Optimized Edge Routing (OER) traffic class using a prefix list applied to learned traffic classes, use the **traffic-class prefix-list** command in learn list configuration mode. To disable the definition of OER learned traffic flows into traffic classes using a prefix list, use the **no** form of this command.

traffic-class prefix-list *prefix-list-name* [**inside**]

no traffic-class prefix-list

Syntax Description

<i>prefix-list-name</i>	Name of a prefix list. Names cannot contain either a space or quotation marks and must begin with an alphabetic character to distinguish them from numbered access lists.
inside	(Optional) Specifies that the prefix list contains inside prefixes.

Command Default

OER application traffic classes are not defined using a prefix list.

Command Modes

Learn list configuration (config-oer-mc-learn-list)

Command History

Release	Modification
12.4(15)T	This command was introduced.

Usage Guidelines

The **traffic-class prefix-list** command is used to configure the master controller to automatically learn traffic based only on destination prefixes. Use the optional **inside** keyword to specify prefixes that are within the internal network.

In Cisco IOS Release 12.4(15)T, the learn list configuration mode was introduced. Learn lists are a way to categorize learned traffic classes. In each learn list, different criteria for learning traffic classes including prefixes, application definitions, filters, and aggregation parameters can be configured. A traffic class is automatically learned by OER based on each learn list criteria, and each learn list is configured with a sequence number. The sequence number determines the order in which learn list criteria are applied. Learn lists allow different OER policies to be applied to each learn list; in previous releases the traffic classes could not be divided, and an OER policy was applied to all the traffic classes.

**Note**

The **traffic-class prefix-list** command, the **traffic-class application** command, and the **traffic-class access-list** commands are all mutually exclusive in an OER learn list. Only one of these commands can be specified per OER learn list.

Examples

The following example, starting in global configuration mode, shows how to define traffic classes based only on destination prefixes for a learn list named LEARN_PREFIX_TC. The traffic classes are created using the prefix list, LEARN_LIST1, in which every entry in the prefix list defines one destination network of a traffic class. After the prefix list is configured, the master controller automatically learns the traffic classes based on the highest throughput.

```
Router(config)# ip prefix-list LEARN_LIST1 permit seq 10 10.0.0.0/8
Router(config)# ip prefix-list LEARN_LIST1 permit seq 20 172.16.0.0/16
Router(config)# oer master
Router(config-oer-mc)# learn
Router(config-oer-mc-learn)# list seq 10 refname LEARN_PREFIX_TC
Router(config-oer-mc-learn-list)# aggregation-type prefix-length 24
Router(config-oer-mc-learn-list)# traffic-class prefix-list LEARN_LIST1
Router(config-oer-mc-learn-list)# throughput
Router(config-oer-mc-learn-list)# end
```

Related Commands

Command	Description
aggregation-type	Configures an OER master controller to aggregate learned prefixes based on the type of traffic flow.
learn	Enters OER Top Talker and Top Delay learning configuration mode to configure prefixes for OER to learn.
list (OER)	Creates an OER learn list to specify criteria for learning traffic classes and enters learn list configuration mode.
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

unreachable

To set the relative percentage or maximum number of unreachable hosts that Optimized Edge Routing (OER) permits from an OER-managed exit link, use the **unreachable** command in OER master controller configuration mode. To return the maximum number of unreachable hosts to the default value, use the **no** form of this command.

```
unreachable { relative average | threshold maximum }
no unreachable
```

Syntax Description

relative <i>average</i>	Sets a relative percentage of unreachable hosts based on a comparison of short-term and long-term percentages. The range of values that can be configured for this argument is a number from 1 to a 1000. Each increment represents one tenth of a percent.
threshold <i>maximum</i>	Sets the absolute maximum number of unreachable hosts based on flows per million (fpm). The range of values that can be configured for this argument is from 1 to 1000000.

Command Default

OER uses the following default value if this command is not configured or if the no form of this command is entered:

relative *average* : 50 (5 percent)

Command Modes

OER master controller configuration

Command History

Release	Modification
12.3(8)T	This command was introduced.
12.2(33)SRB	This command was integrated into Cisco IOS Release 12.2(33)SRB.

Usage Guidelines

The **unreachable** command entered on a master controller. This command is used to specify the relative percentage or the absolute maximum number of unreachable hosts, based on fpm, that OER will permit from an OER-managed exit link. If the absolute number or relative percentage of unreachable hosts is greater than the user-defined or the default value, OER determines that the exit link is out-of-policy and searches for an alternate exit link.

The **relative** keyword is used to configure the relative percentage of unreachable hosts. The relative unreachable host percentage is based on a comparison of short-term and long-term measurements. The short-term measurement reflects the percentage of hosts that are unreachable within a 5-minute period. The long-term measurement reflects the percentage of unreachable hosts within a 60-minute period. The following formula is used to calculate this value:

$$\text{Relative percentage of unreachable hosts} = ((\text{short-term percentage} - \text{long-term percentage}) / \text{long-term percentage}) * 100$$

The master controller measures the difference between these two values as a percentage. If the percentage exceeds the user-defined or default value, the exit link is determined to be out-of-policy. For example, if 10 hosts are unreachable during the long-term measurement and 12 hosts are unreachable during short-term measurement, the relative percentage of unreachable hosts is 20 percent.

The **threshold** keyword is used to configure the absolute maximum number of unreachable hosts. The maximum value is based on the actual number of hosts that are unreachable based on fpm.

Examples

The following example configures the master controller to search for a new exit link when the difference between long- and short-term measurements (relative percentage) is greater than 10 percent:

```
Router(config)# oer master
Router(config-oer-mc)# unreachable relative 100
```

The following example configures OER to search for a new exit link when 10,000 hosts are unreachable:

```
Router(config)# oer master
Router(config-oer-mc)# unreachable threshold 10000
```

Related Commands

Command	Description
oer	Enables an OER process and configures a router as an OER border router or as an OER master controller.

© 2007-2012 Cisco Systems, Inc. All rights reserved.