



Enabling Protocol Discovery

Network-Based Application Recognition (NBAR) includes a feature called Protocol Discovery. Protocol Discovery provides an easy way to discover the application protocols that are operating on an interface. When you configure NBAR, the first task is to enable Protocol Discovery.

This module contains concepts and tasks for enabling the Protocol Discovery feature.

- [Prerequisites for Enabling Protocol Discovery, on page 1](#)
- [Information About Protocol Discovery, on page 1](#)
- [How to Configure Protocol Discovery, on page 2](#)
- [Configuration Examples for Enabling Protocol Discovery, on page 4](#)
- [Where to Go Next, on page 5](#)
- [Additional References, on page 5](#)
- [Feature Information for Enabling Protocol Discovery, on page 6](#)

Prerequisites for Enabling Protocol Discovery

Before enabling Protocol Discovery, read the information in the "Classifying Network Traffic Using NBAR" module.

Information About Protocol Discovery

Protocol Discovery Functionality

NBAR determines which protocols and applications are currently running on your network. NBAR includes a feature called Protocol Discovery. Protocol Discovery provides an easy way of discovering the application protocols that are operating on an interface so that appropriate quality of service (QoS) features can be applied. With Protocol Discovery, you can discover any protocol traffic that is supported by NBAR and obtain statistics that are associated with that protocol.

Protocol Discovery maintains the following per-protocol statistics for enabled interfaces:

- Total number of input packets and bytes
- Total number of output packets and bytes
- Input bit rates

- Output bit rates

The statistics can then be used when you later define classes and traffic policies (sometimes known as policy maps) for each traffic class. The traffic policies (policy maps) are used to apply specific QoS features and functionality to the traffic classes.

How to Configure Protocol Discovery

Enabling Protocol Discovery on an Interface

The **ip nbar protocol-discovery** command is used to enable Protocol Discovery on an interface. With Cisco IOS Release 12.2(18)ZYA, intended for use on the Cisco 6500 series switch that is equipped with a Supervisor 32/PISA, the **ip nbar protocol-discovery** command is supported on both Layer 2 and Layer 3 Etherchannels.

To enable Protocol Discovery on an interface, perform the following steps.

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **interface** *type number* [*name-tag*]
4. **ip nbar protocol-discovery**
5. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3	interface <i>type number</i> [<i>name-tag</i>] Example: Router(config)# interface ethernet 2/4	Configures an interface type and enters interface configuration mode. <ul style="list-style-type: none"> • Enter the interface type and the interface number.
Step 4	ip nbar protocol-discovery Example: Router(config-if)# ip nbar protocol-discovery	Configures NBAR to discover traffic for all protocols known to NBAR on a particular interface.

	Command or Action	Purpose
Step 5	end Example: <pre>Router(config-if)# end</pre>	(Optional) Exits interface configuration mode.

Reporting Protocol Discovery Statistics

To display a report of the Protocol Discovery statistics per interface, perform the following steps.

SUMMARY STEPS

1. **enable**
2. **show policy-map interface** *type number*
3. **show ip nbar protocol-discovery** [**interface** *type number*] [**stats** {**byte-count** | **bit-rate** | **packet-count** | **max-bit-rate**}] [**protocol** *protocol-name* | **top-n** *number*]
4. **exit**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	show policy-map interface <i>type number</i> Example: <pre>Router# show policy-map interface Fastethernet 6/0</pre>	(Optional) Displays the packet and class statistics for all policy maps on the specified interface. <ul style="list-style-type: none"> • Enter the interface type and the interface number.
Step 3	show ip nbar protocol-discovery [interface <i>type number</i>] [stats { byte-count bit-rate packet-count max-bit-rate }] [protocol <i>protocol-name</i> top-n <i>number</i>] Example: <pre>Router# show ip nbar protocol-discovery interface Fastethernet 6/0</pre>	Displays the statistics gathered by the NBAR Protocol Discovery feature. <ul style="list-style-type: none"> • (Optional) Enter keywords and arguments to fine-tune the statistics displayed.
Step 4	exit Example: <pre>Router# exit</pre>	(Optional) Exits privileged EXEC mode.

Configuration Examples for Enabling Protocol Discovery

Example Enabling Protocol Discovery on an Interface

In the following sample configuration, Protocol Discovery is enabled on Ethernet interface 2/4.

```
Router> enable

Router# configure terminal

Router(config)# interface ethernet 2/4

Router(config-if)# ip nbar protocol-discovery

Router(config-if)# end
```

Example Reporting Protocol Discovery Statistics

The following example displays output from the `show ip nbar protocol-discovery` command for the five most active protocols on an Ethernet interface:

```
Router# show ip nbar protocol-discovery top-n 5

Ethernet2/0
```

Protocol	Input		Output	
	Packet Count	Byte Count	Packet Count	Byte Count
rtp	3272685		3272685	
		242050604		242050604
gnutella	768000		768000	
	2002000		2002000	
ftp	513574		513574	
	118779716		118779716	
http	383000		383000	
	987000		987000	
netbios	482183		482183	
	37606237		37606237	
unknown	121000		121000	
	312000		312000	

	534038683	534038683
	2754000	2754000
	4405000	4405000
Total	6298724	6298724
	989303872	989303872
	4213000	4213000
	8177000	8177000

Where to Go Next

After you enable Protocol Discovery, you have the option to configure NBAR using the Modular Quality of Service (QoS) Command-Line Interface (CLI) (MQC). To configure NBAR using the MQC, see the "Configuring NBAR Using the MQC" module.

Additional References

The following sections provide references related to enabling Protocol Discovery.

Related Documents

Related Topic	Document Title
QoS commands: complete command syntax, command modes, command history, defaults, usage guidelines, and examples	<i>Cisco IOS Quality of Service Solutions Command Reference</i>
Concepts and information about NBAR	"Classifying Network Traffic Using NBAR" module
Configuring NBAR using the MQC	"Configuring NBAR Using the MQC" module
Adding application recognition modules (also known as PDLMs)	"Adding Application Recognition Modules" module
Creating a custom protocol	"Creating a Custom Protocol" module

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Feature Information for Enabling Protocol Discovery

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for Enabling Protocol Discovery

Feature Name	Releases	Feature Information
NBAR--Network-Based Application Recognition	12.2(18)ZYA	Integrates NBAR and Firewall Service Module (FWSM) functionality on the Catalyst 6500 series switch that is equipped with a Supervisor 32/programmable intelligent services accelerator (PISA). The following commands were modified: ip nbar protocol-discovery , show ip nbar protocol-discovery .