

GETVPN GDOI Bypass

The GETVPN GDOI Bypass feature supports enabling and disabling the default Group Domain of Interpretation (GDOI) bypass crypto policy. It also supports hardening of the default GDOI bypass crypto policy once it is enabled.

- Finding Feature Information, on page 1
- Restrictions for GETVPN GDOI Bypass, on page 1
- Information About GETVPN GDOI Bypass, on page 2
- How to Configure GETVPN GDOI Bypass, on page 3
- Configuration Examples for GETVPN GDOI Bypass, on page 5
- Additional References for GETVPN GDOI Bypass, on page 6
- Feature Information for GETVPN GDOI Bypass, on page 7

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Restrictions for GETVPN GD0I Bypass

When a key server (KS) is placed behind a group member (GM), the local deny Access Control List (ACL) must be configured explicitly to allow traffic using UDP as the transport protocol and port 848 as either the source or destination (UDP 848 traffic) to pass through.

Information About GETVPN GDOI Bypass

GDOI Bypass Crypto Policy

The Cisco IOS Group Encrypted Transport VPN (GETVPN) uses Group Domain of Interpretation (GDOI) as the key management protocol.

A group member (GM) is a device responsible for encryption and decryption, that is, a device responsible for handling the GET VPN data plane.

A key server (KS) is a device responsible for creating and maintaining the GET VPN control plane. All encryption policies, such as traffic, encryption protocols, security association, rekey timers, and so on, are centrally defined on the KS and are pushed down to all GMs at registration time.

Enabling and Disabling the Default GDOI Bypass Crypto Policy

A new group member (GM) configuration allows users to disable the Group Domain of Interpretation (GDOI) bypass crypto policy and to control traffic exceptions by explicitly configuring the GM local access control list (ACL).

Hardening of the Default GDOI Bypass Crypto Policy

To improve security, the following changes have been enforced while applying the default Group Domain of Interpretation (GDOI) bypass crypto policy:

- The default GDOI bypass crypto policy is installed only on Group Encrypted Transport VPN (GETVPN)-protected interfaces (interfaces at which GDOI crypto map is applied). Only UDP848 traffic that is destined for the group member's (GM) address used for registration or rekey is allowed.
- If the GM VRF-aware feature is used to specify that the GDOI data plane and control plane are in different VRFs, auto-insertion of the default GDOI bypass crypto policy is not applied to the GDOI-protected interface.
- If traffic using UDP as the transport protocol and port 848 as either the source or destination (UDP 848 traffic) is expected to arrive at other non-GDOI-protected interfaces (but with other crypto maps applied), exceptions for the non-GDOI crypto map must be explicitly configured.
- If a crypto map set with multiple groups is configured, the overall GDOI bypass crypto policy installed
 is the union of all the GDOI bypass crypto policies for each group within the security association database
 (SADB).

Any of the conditions mentioned below triggers a recompute of the default GDOI bypass crypto policy applied to a GETVPN-protected interface:

- Removing client bypass-policy configuration using the no client bypass-policy command.
- Applying or removing the GDOI bypass crypto map from an interface.
- Applying or removing the GDOI bypass crypto map from crypto map sets.
- Changing the IP address of the GDOI-protected interface (if **no client registration interface** is used)

- If **client registration interface** is used, the following cases trigger a recompute of the default GDOI bypass crypto policy applied to a GETVPN-protected interface:
 - Changes from no client registration interface to client registration interface
 - Changes to the client registration interface (for example, from loopback 0 to loopback 1)
 - Changes to the client registration interface address

How to Configure GETVPN GDOI Bypass

Enabling the Default GDOI Bypass Crypto Policy

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- 3. crypto gdoi group group-name
- 4. client bypass-policy
- 5. end

DETAILED STEPS

	Command or Action	Purpose	
Step 1	enable	Enables privileged EXEC mode.	
	Example:	• Enter your password if prompted.	
	Device> enable		
Step 2	configure terminal	Enters global configuration mode.	
	Example:		
	Device# configure terminal		
Step 3	crypto gdoi group group-name	Identifies a GDOI group and enters GDOI group	
	Example:	configuration mode.	
	Device(config)# crypto gdoi group GETVPN		
Step 4	client bypass-policy	Enables the default GDOI bypass crypto policy.	
	Example:		
	Device(config-gdoi-group)# client bypass-policy		
Step 5	end	Exits GDOI group configuration mode and returns to privileged EXEC mode.	
	Example:		
	Device(config-gdoi-group)# end		

Disabling the Default GDOI Bypass Crypto Policy

SUMMARY STEPS

- 1. enable
- 2. configure terminal
- 3. crypto gdoi group group-name
- 4. no client bypass-policy
- 5. end

DETAILED STEPS

	Command or Action	Purpose	
Step 1	enable	Enables privileged EXEC mode.	
	Example:	• Enter your password if prompted.	
	Device> enable		
Step 2	configure terminal	Enters global configuration mode.	
	Example:		
	Device# configure terminal		
Step 3	crypto gdoi group group-name	Identifies a GDOI group and enters GDOI group	
	Example:	configuration mode.	
	Device(config)# crypto gdoi group GETVPN		
Step 4	no client bypass-policy	Disables the default GDOI bypass crypto policy.	
	Example:		
	Device(config-gdoi-group)# no client bypass-policy	,	
Step 5	end	Exits GDOI group configuration mode and returns to privileged EXEC mode.	
	Example:		
	Device(config-gdoi-group)# end		

Verifying Enablement and Disablement of the Default GDOI Bypass Crypto Policy

SUMMARY STEPS

- 1. enable
- 2. show crypto gdoi gm acl
- 3. show crypto gdoi gm acl

DETAILED STEPS

Step 1 enable

Enables privileged EXEC mode.

• Enter your password if prompted.

Example:

Device> enable

Step 2 show crypto gdoi gm acl

Verifies the enablement of the default GDOI bypass crypto policy.

Note VRF will be displayed only if it is non-global.

Example:

```
Device# show crypto gdoi gm acl

Group Name: GETVPN

ACL Downloaded From KS 10.0.0.2:
   access-list deny eigrp any any
   access-list permit ip any any

ACL Configured Locally:

ACL of default GDOI bypass policy:
   Ethernet1/0: deny udp host 10.0.0.9 eq 848 any eq 848 vrf RED*
```

Step 3 show crypto gdoi gm acl

Verifies the disablement of the default GDOI bypass crypto policy.

Example:

```
Group Name: GETVPN

ACL Downloaded From KS 10.0.0.2:
   access-list deny eigrp any any
   access-list permit ip any any

ACL Configured Locally:

ACL of default GDOI bypass policy: Disabled
```

Device# show crypto qdoi qm acl

Configuration Examples for GETVPN GDOI Bypass

Example: Enabling the Default GDOI Bypass Crypto Policy

```
Device> enable
Device# configure terminal
Device(config)# crypto gdoi group getvpn
Device(config-gdoi-group)# client bypass-policy
Device(config-gdoi-group)# end
```

Example: Disabling the Default GDOI Bypass Crypto Policy

Device> enable
Device# configure terminal
Device(config)# crypto gdoi group getvpn
Device(config-gdoi-group)# no client bypass-policy
Device(config-gdoi-group)# end

Additional References for GETVPN GDOI Bypass

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
Cisco IOS security commands	Cisco IOS Security Command References
Basic deployment guidelines for enabling GET VPN in an enterprise network	Cisco IOS GET VPN Solutions Deployment Guide
Designing and implementing a GET VPN network	Group Encrypted Transport VPN (GETVPN) Design and Implementation Guide

Standards and RFCs

Standard/RFC	Title
RFC 6407	The Group Domain of Interpretation

Technical Assistance

Description	Link
The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.	http://www.cisco.com/cisco/web/support/index.html
To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.	
Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.	

Feature Information for GETVPN GDOI Bypass

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Table 1: Feature Information for GETVPN GDOI Bypass

Feature Name	Releases	Feature Information
GETVPN GDOI Bypass	15.4(3)M	The GETVPN GDOI Bypass feature supports enabling and disabling the default Group Domain of Interpretation (GDOI) bypass crypto policy. It also supports hardening of the default GDOI bypass crypto policy once it is enabled. The following commands were introduced: client bypass-policy and show crypto gdoi gm acl.

Feature Information for GETVPN GDOI Bypass