

### **Preface**

Published: December 18, 2006, OL-8824-01

Revised: October 26, 2012

#### **Contents**

This document describes how to install, configure, and use Intrusion Prevention System Device Manager (IDM) for IPS 6.0. It includes a glossary that contains expanded acronyms and pertinent IPS terms. It is part of the documentation set for Cisco Intrusion Prevention System 6.0. Use this guide with the documents listed in Related Documentation, page xxiv. This preface contains the following topics:

- Audience, page xxiii
- Conventions, page xxiii
- Related Documentation, page xxiv
- Obtaining Documentation and Submitting a Service Request, page xxv

### **Audience**

This guide is for administrators who need to do the following:

- Install and configure the IDM.
- Secure their networks with IPS sensors.
- Prevent intrusion on their networks and monitor subsequent alerts.

## **Conventions**

This document uses the following conventions:

Convention	Indication
<b>bold</b> font	Commands and keywords and user-entered text appear in <b>bold</b> font.
italic font	Document titles, new or emphasized terms, and arguments for which you supply values are in <i>italic</i> font.
[ ]	Elements in square brackets are optional.

{x   y   z }	Required alternative keywords are grouped in braces and separated by vertical bars.
[x y z]	Optional alternative keywords are grouped in brackets and separated by vertical bars.
string	A nonquoted set of characters. Do not use quotation marks around the string or the string will include the quotation marks.
courier font	Terminal sessions and information the system displays appear in courier font.
< >	Nonprinting characters such as passwords are in angle brackets.
[ ]	Default responses to system prompts are in square brackets.
!, #	An exclamation point (!) or a pound sign (#) at the beginning of a line of code indicates a comment line.



Means reader take note.



Tip

Means the following information will help you solve a problem.



Means *reader be careful*. In this situation, you might perform an action that could result in equipment damage or loss of data.



**Timesave** 

Means the described action saves time. You can save time by performing the action described in the paragraph.



Means reader be warned. In this situation, you might perform an action that could result in bodily injury.

### **Related Documentation**

For more information on Cisco IPS, refer to the following documentation found at this URL: http://www.cisco.com/en/US/products/hw/vpndevc/ps4077/tsd\_products\_support\_series\_home.html

- Documentation Roadmap for Cisco Intrusion Prevention System
- Release Notes for Cisco Intrusion Prevention System
- Cisco Intrusion Prevention System Manager Express Configuration Guide
- Cisco Intrusion Prevention System Command Reference
- Cisco Intrusion Prevention System Sensor CLI Configuration Guide
- Cisco Intrusion Prevention System Appliance and Module Installation Guide

- Installling and Removing Interface Cards in Cisco IPS-4260 and IPS 4270-20
- Regulatory Compliance and Safety Information for the Cisco Intrusion Detection and Prevention System 4200 Series Appliance Sensor

# **Obtaining Documentation and Submitting a Service Request**

For information on obtaining documentation, submitting a service request, and gathering additional information, see the monthly *What's New in Cisco Product Documentation*, which also lists all new and revised Cisco technical documentation, at:

http://www.cisco.com/en/US/docs/general/whatsnew/whatsnew.html

Subscribe to the *What's New in Cisco Product Documentation* as a Really Simple Syndication (RSS) feed and set content to be delivered directly to your desktop using a reader application. The RSS feeds are a free service and Cisco currently supports RSS Version 2.0.

Obtaining Documentation and Submitting a Service Request