

# **L Commands**

This chapter describes the Cisco Nexus Cloud Services Platform commands that begin with the letter L.

## line console

To enter console configuration mode, use the **line console** command. To exit console configuration mode, use the **no** form of this command.

line console

no line console

**Syntax Description** 

This command has no arguments or keywords.

**Defaults** 

None

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### **Examples**

This example shows how to enter console configuration mode:

n1010# configure terminal
n1010(config)# line console
n1010(config-console)#

# line vty

To enter line configuration mode, use the **line vty** command. To exit line configuration mode, use the **no** form of this command.

line vty

no line vty

**Syntax Description** 

This command has no arguments or keywords.

Defaults

None

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### Examples

This example shows how to enter line configuration mode:

n1010# configure terminal
n1010(config)# line vty
n1010(config-line)#

Command	Description	
exit	Exits a configuration mode.	
line console	Enters console configuration mode.	

## logging console

To enable logging messages to the console session, use the **logging console** command. To disable logging messages to the console session, use the **no** form of this command.

logging console [severity-level]

no logging console

### **Syntax Description**

severity-level

Severity level at which you want messages to be logged. When you set a severity level, such as 4, then messages at that severity level and higher (0 through 4) are logged.

Severity levels are as follows:

Level	Designation	Definition
0	Emergency	System unusable
1	Alert	Immediate action needed
2	Critical	Critical condition—default level
3	Error	Error condition
4	Warning	Warning condition
5	Notification	Normal but significant condition
6	Informational	Informational message only
7	Debugging	Condition that appears during debugging only



Level 0 is the highest severity level.

Defaults

None

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

#### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### **Examples**

This example shows how to enable logging messages with a severity level of 4 (warning) or higher to the console session:

n1010# configure terminal

n1010(config)# logging console 4 n1010(config)#

Command	Description	
logging event	Logs interface events.	
logging level	Enables the logging of messages from named facilities and for specified severity levels.	
logging logfile	Configures the log file used to store system messages.	
logging module	Starts logging of module messages to the log file.	
logging server	Designate and configure a remote server for logging system messages.	
logging timestamp	Set the unit of measure for the system messages timestamp.	
show logging logfile	Displays the contents of the log file.	

# logging event

To log interface events, use the **logging event** command. To disable logging of events, use the **no** version of this command.

logging event {link-status | trunk-status} {enable | default}

no logging event {link-status | trunk-status} {enable | default}

### **Syntax Description**

link-status	Logs all up/down and change status messages.	
trunk-status	Logs all trunk status messages.	
default	Specifies that the default logging configuration is used.	
enable	Enables interface logging to override the port level logging configuration.	

Defaults

None

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### **Examples**

This example shows how to log interface events:

n1010# configure terminal
n1010(config)# logging event link-status default
n1010(config)#

Command	Description	
logging console	Enables logging messages to the console session.	
logging level	Enables the logging of messages from named facilities and for specified severity levels.	
logging logfile	Configures the log file used to store system messages.	
logging module	Starts logging of module messages to the log file.	
logging server	Designate and configure a remote server for logging system messages.	
logging timestamp	Set the unit of measure for the system messages timestamp.	
show logging logfile	Displays the contents of the log file.	

# logging level

To enable the logging of messages from a named facility and for specified severity levels, use the **logging level** command. To disable the logging of messages, use the **no** form of this command.

logging level facility severity-level

no logging level facility severity-level

### **Syntax Description**

facility	Facility name.	
severity-level	Severity level at which you want messages to be logged. When you set a severity level, for example 4, then messages at that severity level and higher (0 through 4) are logged.	
	Severity levels are as follows:	

Level	Designation	Definition
0	Emergency	System unusable
1	Alert	Immediate action needed
2	Critical	Critical condition—default level
3	Error	Error condition
4	Warning	Warning condition
5	Notification	Normal but significant condition
6	Informational	Informational message only
7	Debugging	Condition that appears during debugging only



Level 0 is the highest severity level.

Defaults

None

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### **Usage Guidelines**

To apply the same severity level to all facilities, use the following command:

• logging level all level\_number

To list the available facilities for which messages can be logged, use the following command:

logging level?

### **Examples**

This example shows how to enable logging messages from the AAA facility that have a severity level of 0 through 2:

```
n1010# configure terminal
n1010(config)# logging level aaa 2
n1010(config)#
```

This example shows how to enable logging messages from the license facility with a severity level of 0 through 4 and then display the license logging configuration:

```
n1010# configure terminal
n1010(config)# logging level license 4
n1010(config)# show logging level license
             Default Severity
Facility
                                Current Session Severity
              -----
licmgr
                      6
0 (emergencies)
                      1(alerts)
                                     2(critical)
                                     5(notifications)
3 (errors)
                      4(warnings)
6(information)
                      7(debugging)
n1010(config)#
```

Command	Description
logging console	Enables logging messages to the console session.
logging event	Logs interface events.
logging logfile	Configures the log file used to store system messages.
logging module	Starts logging of module messages to the log file.
logging server	Designate and configure a remote server for logging system messages.
logging timestamp	Set the unit of measure for the system messages timestamp.
show logging logfile	Displays the contents of the log file.

# logging logfile

To configure the log file used to store system messages, use the **logging logfile** command. To remove a configuration, use the **no** form of this command.

Name of the log file that stores system messages.

**logging logfile** logfile-name severity-level [size bytes]

**no logging logfile** [logfile-name severity-level [size bytes]]]

### **Syntax Description**

severity-level	level, for (0 throug	•	vant messages to be logged. When you set a severity essages at that severity level and higher
	Level	Designation	Definition
	0	Emergency	System unusable
	1	Alert	Immediate action needed
	2	Critical	Critical condition—default level
	3	Error	Error condition
	4	Warning	Warning condition
	5	Notification	Normal but significant condition
	6	Informational	Informational message only
	7	Debugging	Condition that appears during debugging only
size bytes	` -	l) Specifies the log f	ile size in bytes, from 4096 to 10485760 bytes. The



Level 0 is the highest severity level.

Defaults

None

logfile-name

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### Examples

This example shows how to configure a log file named LogFile to store system messages and set its severity level to 4:

```
n1010# configure terminal
n1010(config)# logging logfile LogFile 4
n1010(config)#
```

Command	Description
logging console	Enables logging messages to the console session.
logging event	Logs interface events.
logging level	Enables the logging of messages from named facilities and for specified severity levels.
logging module	Starts logging of module messages to the log file.
logging server	Designate and configure a remote server for logging system messages.
logging timestamp	Set the unit of measure for the system messages timestamp.
show logging logfile	Displays the contents of the log file.

## logging module

To start logging of module messages to the log file, use the **logging module** command. To stop module log messages, use the **no** form of this command.

**logging module** [severity-level]

no logging module [severity-level]

### **Syntax Description**

severity-level

Severity level at which you want messages to be logged. If you do not specify a severity level, the default is used. When you set a severity level, for example 4, then messages at that severity level and higher (0 through 4) are logged.

Severity levels are as follows:

Level	Designation	Definition
0	Emergency	System unusable
1	Alert	Immediate action needed
2	Critical	Critical condition—default level
3	Error	Error condition
4	Warning	Warning condition
5	Notification	Normal but significant condition (the default)
6	Informational	Informational message only
7	Debugging	Condition that appears during debugging only



Level 0 is the highest severity level.

#### Defaults

Disabled

If you start logging of module messages, and do not specify a severity, then the default, Notification (5), is used.

#### **Command Modes**

Global configuration (config)

### **SupportedUserRoles**

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### **Examples**

This example shows how to start logging module messages to the log file at the default severity level (severity 4):

```
n1010# configure terminal
n1010(config)# logging module
n1010(config)#
```

This example shows how to stop logging module messages to the log file:

```
n1010# configure terminal
n1010(config)# no logging module
n1010#
```

Command	Description
logging console	Enables logging messages to the console session.
logging event	Logs interface events.
logging level	Enables the logging of messages from named facilities and for specified severity levels.
logging logfile	Configures the log file used to store system messages.
logging server	Designate and configure a remote server for logging system messages.
logging timestamp	Set the unit of measure for the system messages timestamp.
show logging logfile	Displays the contents of the log file.

# logging server

To designate and configure a remote server for logging system messages, use the **logging server** command. Use the **no** form of this command to remove or change the configuration.

logging server hostname [indicator [use-vrf name [facility {auth | authpriv | cron | daemon | ftp | kernel | local0 | local1 | local2 | local3 | local4 | local5 | local6 | local7 | lpr | mail | news | syslog | user | uucp}]]]

no logging server hostname [indicator [use-vrf name [facility {auth | authpriv | cron | daemon | ftp | kernel | local0 | local1 | local2 | local3 | local4 | local5 | local6 | local7 | lpr | mail | news | syslog | user | uucp}]]]

### **Syntax Description**

hostname	Hostname/IPv4/IPv6 address of the remote syslog server.
indicator	(Optional) One of the following indicators: 0-emerg, 1-alert, 2-crit, 3-err, 4-warn, 5-notif, 6-inform, 7-debug.
use-vrf name	(Optional) Specifies the VRF name. The default is management.
facility	(Optional) Specifies the facility to use when forwarding to the server.
auth	Specifies the auth facility.
authpriv	Specifies the authpriv facility.
cron	Specifies the Cron/at facility.
daemon	Specifies the daemon facility.
ftp	Specifies the file transfer system facility.
kernel	Specifies the kernel facility.
local0	Specifies the local0 facility.
local1	Specifies the local1 facility.
local2	Specifies the local2 facility.
local3	Specifies the local3 facility.
local4	Specifies the local4 facility.
local5	Specifies the local5 facility.
local6	Specifies the local6 facility.
local7	Specifies the local7 facility.
lpr	Specifies the lpr facility.
mail	Specifies the mail facility.
news	Specifies the USENET news facility.
syslog	Specifies the syslog facility.
user	Specifies the user facility.
uucp	Specifies the UNIX-to-UNIX copy system facility.

**Defaults** None

**Command Modes** Global configuration (config)

### SupportedUserRoles network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### Examples

This example shows how to configure a remote syslog server at a specified IPv4 address using the default outgoing facility:

```
n1010# configure terminal
n1010(config)# logging server 172.28.254.253
n1010(config)#
```

This example shows how to configure a remote syslog server at a specified host name with severity level 5 or higher:

```
n1010# configure terminal
n1010(config)# logging server syslogA 5
n1010(config)#
```

Command	Description
logging console	Enables logging messages to the console session.
logging event	Logs interface events.
logging level	Enables the logging of messages from named facilities and for specified severity levels.
logging logfile	Configures the log file used to store system messages.
logging module	Starts logging of module messages to the log file.
logging timestamp	Set the unit of measure for the system messages timestamp.
show logging logfile	Displays the contents of the log file.

# logging timestamp

To set the unit of measure for the system message time stamp, use the **logging timestamp** command. To restore the default unit of measure, use the **no** form of this command.

logging timestamp {microseconds | milliseconds | seconds}

no logging timestamp {microseconds | milliseconds | seconds}

### **Syntax Description**

microseconds	Specifies the time stamp in microseconds.
milliseconds	Specifies the time stamp in milliseconds.
seconds	Specifies the time stamp in seconds (default).

Defaults

Seconds

**Command Modes** 

Global configuration (config)

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.0(4)SP1(1)	This command was introduced.

### Examples

This example shows how to set microseconds as the unit of measure for the system message time stamp:

n1010# configure terminal
n1010(config)# logging timestamp microseconds
n1010(config)#

Command	Description	
logging console	Enables logging messages to the console session.	
logging event	Logs interface events.	
logging level	Enables the logging of messages from named facilities and for specified severity levels.	
logging logfile	Configures the log file used to store system messages.	
logging module	Starts logging of module messages to the log file.	
logging server	Designate and configure a remote server for logging system messages.	
show logging logfile	Displays the contents of the log file.	

# login virtual-service-blade

To log in to a Virtual Service Blade (VSB), use the login virtual-service-blade command.

login virtual-service-blade name [primary | secondary]

### **Syntax Description**

name	Name of an existing virtual service blade.	
primary	(Optional) The Cisco Nexus Cloud Services Platform that was assigned the primary role.	
secondary	(Optional) The Cisco Nexus Cloud Services Platform that was assigned the secondary role.	

Defaults

None

**Command Modes** 

**EXEC** 

**SupportedUserRoles** 

network-admin

### **Command History**

Release	Modification
4.2(1)SP1(2)	The optional <b>primary</b> and <b>secondary</b> keywords were added.
4.0(4)SP1(1)	This command was introduced.

### **Usage Guidelines**

This command gives serial command access to a virtual service blade.

### **Examples**

This example shows how to log into the Cisco Nexus 1000V CLI for the VSB named VSB-1 which is on the primary Cisco Nexus Cloud Services Platform.

n1010# login virtual-service-blade VSB-1 primary n1010#

Command	Description
description	Adds a description to the virtual service.
enable	Initiates the configuration of the virtual service and then enables it.
show virtual-service-blade	Displays information about the virtual service blades.
show virtual-service-blade	Displays information about a virtual service.
name	
show virtual-service-blade-type	Displays a summary of all virtual service configurations by the type
summary	name.

Command	Description
virtual-service-blade	Creates the named virtual service and places you into the configuration mode for that service.
virtual-service-blade-type	Specifies the type and name of the software image file to add to this virtual service.