



K Commands

- [key](#), on page 2
- [key-string 0](#), on page 3
- [key-string 7](#), on page 4
- [key chain](#), on page 5
- [key config-key](#), on page 6
- [kill-everyone](#), on page 7
- [kill background](#), on page 8

key

[no] key *keyid*

Syntax Description

no Negate a command or set its defaults

key Configure a key

keyid Type: integer

min: 0 max: 65535

Key identifier

Command Modes

- /exec/configure/keychain

key-string 0

key-string [0] *keystring*|**no** **key-string**

Syntax Description	
no	Negate a command or set its defaults
key-string	Set key string
0	Encryption Type - No Encryption(default)
<i>keystring</i>	Type: remainder key string
Command Modes	<ul style="list-style-type: none"> • /exec/configure/keychain-key

key-string 7

key-string 7 *keysting*

Syntax Description

key-string Set key string

7 Encryption Type -
Proprietary

keysting Type: remainder
key string

Command Modes

- /exec/configure/keychain-key

key chain

[no] **key chain** *keychain*

Syntax Description	
no	Negate a command or set its defaults
key	Key Management
chain	Keychain Management
<i>keychain</i>	Type: string pattern: [!~]* antipattern: mode decrypt length: 63 key-chain name
Command Modes	• /exec/configure

key config-key

[no] key config-key {hex|ascii} [*master-key*]

Syntax Description

no	Negate a command or set its defaults
key	Encryption key for strong encryption
config-key	Master-key for strong encryption of secrets in config
hex	Key followed should be in hex format
ascii	Key followed should be in ascii format
<i>master-key</i>	Type: string Enter the Master-key

Command Modes

- /exec

kill-everyone

[no] [eigrp] kill-everyone

Syntax Description	no	Negate a command or set its defaults
	eigrp	EIGRP router configuration commands
	kill-everyone	Kill all adjacencies on SIA

Command Modes	<ul style="list-style-type: none">• /exec/configure/router-eigrp/router-eigrp-vrf-common• /exec/configure/router-eigrp/router-eigrp-af-common
----------------------	--

kill background

`kill background pid`

Syntax Description

kill terminate processes

background kill background processes (started with 'source background <file>' command)

pid Type: string

background script to terminate, by process-id or just a regex matching any line from 'show background' command

Command Modes

• /exec