

New and Changed Information

This chapter provides release-specific information for each new and changed feature in the *Cisco Nexus 9000 Series NX-OS High Availability and Redundancy Guide* .

• New and Changed Information, on page 1

New and Changed Information

This table summarizes the new and changed features for the Cisco Nexus 9000 Series NX-OS High Availability and Redundancy Guide, Release 9.3(x) and where they are documented.

Table 1: New and Changed Features

Feature	Description	Changed in Release	Where Documented
• NXA-PHV-350W	Added support for these AC and DC power supplies for the Cisco Nexus N9K-C9348GC-FXP switch.	9.3 (6)	Power Supply Redundancy
• N9K-C93180YC-FX3	Introduced this switch.	9.3 (5)	Physical Redundancy
• NXA-PHV-500W • NXA-PHV-500W-B	Added support for these AC and DC power supplies for the Cisco Nexus N9K-C92348GC-X switch.	9.3 (5)	Power Supply Redundancy
• N2200-PDC-400W • N2200-PDC-350W-B	Added support for these DC power supplies for the Cisco Nexus N9K-C92348GC-X switch.	9.3 (4)	Power Supply Redundancy

Feature	Description	Changed in Release	Where Documented
N9K-C9316D-GXN9K-C93600CD-GXN9K-C9364C-GX	Introduced these switches.	9.3 (3)	Physical Redundancy
• N9K-C93360YC-FX2 • N9K-C92348GC-X	Introduced these switches.	9.3 (1)	Physical Redundancy