



## Configuring IPv6 First Hop Security

- [Prerequisites for First Hop Security in IPv6, on page 1](#)
- [Restrictions for First Hop Security in IPv6, on page 1](#)
- [Information about First Hop Security in IPv6, on page 2](#)
- [How to Configure an IPv6 Snooping Policy, on page 4](#)
- [How to Attach an IPv6 Snooping Policy to an Interface, on page 6](#)
- [How to Attach an IPv6 Snooping Policy to a Layer 2 EtherChannel Interface, on page 7](#)
- [How to Attach an IPv6 Snooping Policy to VLANs Globally , on page 8](#)
- [How to Configure the IPv6 Binding Table Content , on page 9](#)
- [How to Configure an IPv6 Neighbor Discovery Inspection Policy, on page 10](#)
- [How to Configure an IPv6 Router Advertisement Guard Policy, on page 14](#)
- [How to Configure an IPv6 DHCP Guard Policy , on page 19](#)
- [How to Configure IPv6 Source Guard, on page 24](#)
- [How to Configure IPv6 Prefix Guard, on page 26](#)
- [Configuration Examples for IPv6 First Hop Security, on page 29](#)

### Prerequisites for First Hop Security in IPv6

- You have configured the necessary IPv6 enabled SDM template.
- You should be familiar with the IPv6 neighbor discovery feature.

### Restrictions for First Hop Security in IPv6

- The following restrictions apply when applying FHS policies to EtherChannel interfaces (Port Channels):
  - A physical port with an FHS policy attached cannot join an EtherChannel group.
  - An FHS policy cannot be attached to a physical port when it is a member of an EtherChannel group.
- By default, a snooping policy has a security-level of guard. When such a snooping policy is configured on an access switch, external IPv6 Router Advertisement (RA) or Dynamic Host Configuration Protocol for IPv6 (DHCPv6) server packets are blocked, even though the uplink port facing the router or DHCP

server/relay is configured as a trusted port. To allow IPv6 RA or DHCPv6 server messages, do the following:

- Apply an IPv6 RA-guard policy (for RA) or IPv6 DHCP-guard policy (for DHCP server messages) on the uplink port.
- Configure a snooping policy with a lower security-level, for example `glean` or `inspect`. However, configuring a lower security level is not recommended with such a snooping policy, because benefits of First Hop security features are not effective.

## Information about First Hop Security in IPv6

First Hop Security in IPv6 (FHS IPv6) is a set of IPv6 security features, the policies of which can be attached to a physical interface, an EtherChannel interface, or a VLAN. An IPv6 software policy database service stores and accesses these policies. When a policy is configured or modified, the attributes of the policy are stored or updated in the software policy database, then applied as was specified. The following IPv6 policies are currently supported:

- **IPv6 Snooping Policy**—IPv6 Snooping Policy acts as a container policy that enables most of the features available with FHS in IPv6.
- **IPv6 FHS Binding Table Content**—A database table of IPv6 neighbors connected to the switch is created from information sources such as Neighbor Discovery (ND) protocol snooping. This database, or binding, table is used by various IPv6 guard features (such as IPv6 ND Inspection) to validate the link-layer address (LLA), the IPv4 or IPv6 address, and prefix binding of the neighbors to prevent spoofing and redirect attacks.
- **IPv6 Neighbor Discovery Inspection**—IPv6 ND inspection learns and secures bindings for stateless autoconfiguration addresses in Layer 2 neighbor tables. IPv6 ND inspection analyzes neighbor discovery messages in order to build a trusted binding table database and IPv6 neighbor discovery messages that do not conform are dropped. An ND message is considered trustworthy if its IPv6-to-Media Access Control (MAC) mapping is verifiable.

This feature mitigates some of the inherent vulnerabilities of the ND mechanism, such as attacks on DAD, address resolution, router discovery, and the neighbor cache.




---

**Note** Effective Cisco IOS XE Release 16.3.1, ND Inspection functionality, IPv6 Snooping Policy, and IPv6 FHS Binding Table Content are supported through Switch Integrated Security Feature (SISF)-based Device Tracking. For more information, see *Configuring SISF based device tracking* section of the Software Configuration Guide.

---

- **IPv6 Router Advertisement Guard**—The IPv6 Router Advertisement (RA) guard feature enables the network administrator to block or reject unwanted or rogue RA guard messages that arrive at the network switch platform. RAs are used by routers to announce themselves on the link. The RA Guard feature analyzes the RAs and filters out bogus RAs sent by unauthorized routers. In host mode, all router advertisement and router redirect messages are disallowed on the port. The RA guard feature compares configuration information on the Layer 2 device with the information found in the received RA frame. Once the Layer 2 device has validated the content of the RA frame and router redirect frame against the

configuration, it forwards the RA to its unicast or multicast destination. If the RA frame content is not validated, the RA is dropped.

- IPv6 DHCP Guard—The IPv6 DHCP Guard feature blocks reply and advertisement messages that come from unauthorized DHCPv6 servers and relay agents. IPv6 DHCP guard can prevent forged messages from being entered in the binding table and block DHCPv6 server messages when they are received on ports that are not explicitly configured as facing a DHCPv6 server or DHCP relay. To use this feature, configure a policy and attach it to an interface or a VLAN. To debug DHCP guard packets, use the **debug ipv6 snooping dhcp-guard** privileged EXEC command.
- IPv6 Source Guard—Like IPv4 Source Guard, IPv6 Source Guard validates the source address or prefix to prevent source address spoofing.

A source guard programs the hardware to allow or deny traffic based on source or destination addresses. It deals exclusively with data packet traffic.

The IPv6 source guard feature provides the ability to store entries in the hardware TCAM table to prevent a host from sending packets with an invalid IPv6 source address.

To debug source-guard packets, use the `debug ipv6 snooping source-guard` privileged EXEC command.



---

**Note** The IPv6 source guard and prefix guard features are supported only in the ingress direction; it is not supported in the egress direction.

---

The following restrictions apply:

- An FHS policy cannot be attached to an physical port when it is a member of an EtherChannel group.
- When IPv6 source guard is enabled on a switch port, NDP or DHCP snooping must be enabled on the interface to which the switch port belongs. Otherwise, all data traffic from this port will be blocked.
- An IPv6 source guard policy cannot be attached to a VLAN. It is supported only at the interface level.
- When you configure IPv4 and IPv6 source guard together on an interface, it is recommended to use **ip verify source mac-check** instead of **ip verify source**. IPv4 connectivity on a given port might break due to two different filtering rules set — one for IPv4 (IP-filter) and the other for IPv6 (IP-MAC filter).
- You cannot use IPv6 Source Guard and Prefix Guard together. When you attach the policy to an interface, it should be "validate address" or "validate prefix" but not both.
- PVLAN and Source/Prefix Guard cannot be applied together.
- IPv6 Source Guard and Prefix Guard is supported on EtherChannels

For more information on IPv6 Source Guard, see the [IPv6 Source Guard](#) chapter of the Cisco IOS IPv6 Configuration Guide Library on Cisco.com.

- IPv6 Prefix Guard—The IPv6 prefix guard feature works within the IPv6 source guard feature, to enable the device to deny traffic originated from non-topologically correct addresses. IPv6 prefix guard is often used when IPv6 prefixes are delegated to devices (for example, home gateways) using DHCP prefix

delegation. The feature discovers ranges of addresses assigned to the link and blocks any traffic sourced with an address outside this range.

For more information on IPv6 Prefix Guard, see the [IPv6 Prefix Guard](#) chapter of the Cisco IOS IPv6 Configuration Guide Library on Cisco.com.

- **IPv6 Destination Guard**—The IPv6 destination guard feature works with IPv6 neighbor discovery to ensure that the device performs address resolution only for those addresses that are known to be active on the link. It relies on the address glean functionality to populate all destinations active on the link into the binding table and then blocks resolutions before they happen when the destination is not found in the binding table.



**Note** IPv6 Destination Guard is recommended to apply on Layer 2 VLAN with an SVI configured

For more information about IPv6 Destination Guard, see the [IPv6 Destination Guard](#) chapter of the Cisco IOS IPv6 Configuration Guide Library on Cisco.com.

## How to Configure an IPv6 Snooping Policy

The IPv6 Snooping Policy feature is deprecated starting from Cisco IOS XE Denali 16.3.1. Although the commands are visible on the CLI and you can configure them, we recommend that you use the Switch Integrated Security Feature (SISF)-based Device Tracking feature instead.

Beginning in privileged EXEC mode, follow these steps to configure IPv6 Snooping Policy :

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <b>configure terminal</b><br><br><b>Example:</b><br>Device# <code>configure terminal</code>  | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>ipv6 snooping policy <i>policy-name</i></b><br><br><b>Example:</b><br>Device(config)# <code>ipv6 snooping policy example_policy</code>  | Creates a snooping policy and enters IPv6 Snooping Policy Configuration mode.   |
| <b>Step 3</b> | <code>{[default ]   [device-role {node   switch}]   [limit address-count <i>value</i>]   [no]   [protocol {dhcp   ndp}]   [security-level {glean   guard   inspect}]   [tracking {disable [stale-lifetime <i>seconds</i>]   infinite]   enable [reachable-lifetime <i>seconds</i>]   infinite}]   [trusted-port ] }</code><br><br><b>Example:</b><br>Device (config-ipv6-snooping) # <code>security-level inspect</code> | Enables data address gleaning, validates messages against various criteria, specifies the security level for messages. <ul style="list-style-type: none"> <li>• (Optional) <b>default</b>—Sets all to default options.</li> <li>• (Optional) <b>device-role {node}   switch</b>—Specifies the role of the device attached to the port. Default is <b>node</b>.</li> </ul> |

|                      | Command or Action  | Purpose  |
|----------------------|--|--|
|                      | <p><b>Example:</b><br/>                     Device (config-ipv6-snooping) #<br/>                     trusted-port</p>                                      | <ul style="list-style-type: none"> <li>• (Optional) <b>limit address-count value</b>—Limits the number of addresses allowed per target.</li> <li>• (Optional) <b>no</b>—Negates a command or sets it to defaults.</li> <li>• (Optional) <b>protocol {dhcp   ndp}</b>—Specifies which protocol should be redirected to the snooping feature for analysis. The default, is <b>dhcp</b> and <b>ndp</b>. To change the default, use the <b>no protocol</b> command.</li> <li>• (Optional) <b>security-level {glean guard inspect}</b>—Specifies the level of security enforced by the feature. Default is <b>guard</b>.                             <ul style="list-style-type: none"> <li><b>glean</b>—Glens addresses from messages and populates the binding table without any verification.</li> <li><b>guard</b>—Glens addresses and inspects messages. In addition, it rejects RA and DHCP server messages. This is the default option.</li> <li><b>inspect</b>—Glens addresses, validates messages for consistency and conformance, and enforces address ownership.</li> </ul> </li> <li>• (Optional) <b>tracking {disable   enable}</b>—Overrides the default tracking behavior and specifies a tracking option.</li> <li>• (Optional) <b>trusted-port</b>—Sets up a trusted port. It disables the guard on applicable targets. Bindings learned through a trusted port have preference over bindings learned through any other port. A trusted port is given preference in case of a collision while making an entry in the table.</li> </ul> |
| <p><b>Step 4</b></p> | <p><b>end</b></p> <p><b>Example:</b><br/>                     Device (config-ipv6-snooping) # <b>exit</b></p>  | <p>Exits configuration modes to Privileged EXEC mode.</p>  |
| <p><b>Step 5</b></p> | <p><b>show ipv6 snooping policy policy-name</b></p> <p><b>Example:</b><br/>                     Device#<b>show ipv6 snooping policy example_policy</b></p> | <p>Displays the snooping policy configuration.</p>   |

**What to do next**

Attach an IPv6 Snooping policy to interfaces or VLANs.

## How to Attach an IPv6 Snooping Policy to an Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Snooping policy on an interface or VLAN:

**Procedure**

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>interface</b> Interface_type <i>stack/module/port</i><br><b>Example:</b><br>Device (config)# <b>interface</b><br><b>gigabitethernet 1/1/4</b>   | Specifies an interface type and identifier; enters the interface configuration mode.  |
| <b>Step 3</b> | <b>switchport</b><br><b>Example:</b><br>Device (config-if)# <b>switchport</b>  | Enters the Switchport mode.<br><br><b>Note</b> To configure Layer 2 parameters, if the interface is in Layer 3 mode, you must enter the switchport interface configuration command without any parameters to put the interface into Layer 2 mode. This shuts down the interface and then re-enables it, which might generate messages on the device to which the interface is connected. When you put an interface that is in Layer 3 mode into Layer 2 mode, the previous configuration information related to the affected interface might be lost, and the interface is returned to its default configuration. The command prompt displays as (config-if)# in Switchport configuration mode. |
| <b>Step 4</b> | <b>ipv6 snooping</b> [ <b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> { <i>vlan_id</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i> }]   <b>vlan</b> { <i>vlan_id</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ] | Attaches a custom ipv6 snooping policy to the interface or the specified VLANs on the interface. To attach the default policy to the interface, use the <b>ipv6 snooping</b> command without the <b>attach-policy</b> keyword. To attach  |

|               | Command or Action  | Purpose   |
|---------------|--|---|
|               | <p><b>Example:</b></p> <pre>Device(config-if)# ipv6 snooping</pre> <p>or</p> <pre>Device(config-if)# ipv6 snooping attach-policy example_policy</pre> <p>or</p> <pre>Device(config-if)# ipv6 snooping vlan 111,112</pre> <p>or</p> <pre>Device(config-if)# ipv6 snooping attach-policy example_policy vlan 111,112</pre> | <p>the default policy to VLANs on the interface, use the <b>ipv6 snooping vlan</b> command. The default policy is, security-level <b>guard</b>, device-role <b>node</b>, protocol <b>ndp</b> and <b>dhcp</b>.</p> |
| <b>Step 5</b> | <p><b>do show running-config</b></p> <p><b>Example:</b></p> <pre>Device#(config-if)# do show running-config</pre>  | <p>Verifies that the policy is attached to the specified interface without exiting the interface configuration mode.</p>  |

## How to Attach an IPv6 Snooping Policy to a Layer 2 EtherChannel Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Snooping policy on an EtherChannel interface or VLAN:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>  | <p>Enters the global configuration mode.</p>  |
| <b>Step 2</b> | <p><b>interface range</b> <i>Interface_name</i></p> <p><b>Example:</b></p> <pre>Device(config)# interface range Po11</pre>           | <p>Specify the port-channel interface name assigned when the EtherChannel was created. Enters the interface range configuration mode.</p> <p><b>Tip</b> Enter the <b>do show interfaces summary</b> command for quick reference to interface names and types.</p> |
| <b>Step 3</b> | <p><b>ipv6 snooping</b> [<b>attach-policy</b> <i>policy_name</i> [<b>vlan</b> <i>{vlan_ids   add vlan_ids   except vlan_ids}</i></p> | <p>Attaches the IPv6 Snooping policy to the interface or the specified VLANs on that</p>  |

|               | Command or Action   | Purpose   |
|---------------|---|---|
|               | <pre>  none   remove vlan_ids   all } ]   vlan [ {vlan_ids   add vlan_ids   exceptvlan_ids   none   remove vlan_ids   all} ]</pre> <p><b>Example:</b></p> <pre>Device(config-if-range)# ipv6 snooping attach-policy example_policy</pre> <p>or</p> <pre>Device(config-if-range)# ipv6 snooping attach-policy example_policy vlan 222,223,224</pre> <p>or</p> <pre>Device(config-if-range)#ipv6 snooping vlan 222, 223,224</pre> | interface. The default policy is attached if the <b>attach-policy</b> option is not used.               |
| <b>Step 4</b> | <p><b>do show running-config interfaceportchannel_interface_name</b></p> <p><b>Example:</b></p> <pre>Device#(config-if-range)# do show running-config int poll</pre>  | Confirms that the policy is attached to the specified interface without exiting the configuration mode. |

## How to Attach an IPv6 Snooping Policy to VLANs Globally

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Snooping Policy to VLANs across multiple interfaces:

### Procedure

|               | Command or Action   | Purpose   |
|---------------|---|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>   | Enters the global configuration mode.   |
| <b>Step 2</b> | <p><b>vlan configuration vlan_list</b></p> <p><b>Example:</b></p> <pre>Device(config)# vlan configuration 333</pre>   | Specifies the VLANs to which the IPv6 Snooping policy will be attached ; enters the VLAN interface configuration mode.  |
| <b>Step 3</b> | <p><b>ipv6 snooping [attach-policy policy_name]</b></p> <p><b>Example:</b></p> <pre>Device(config-vlan-config)#ipv6 snooping attach-policy example_policy</pre> | Attaches the IPv6 Snooping policy to the specified VLANs across all switch and stack interfaces. The default policy is attached if the <b>attach-policy</b> option is not used. The default |



|               | Command or Action   | Purpose   |
|---------------|---|---|
|               |   | policy is, security-level <b>guard</b> , device-role <b>node</b> , protocol <b>ndp</b> and <b>dhcp</b> .      |
| <b>Step 4</b> | <b>do show running-config</b><br><br><b>Example:</b><br>Device#(config-if)# <b>do show running-config</b> | Verifies that the policy is attached to the specified VLANs without exiting the interface configuration mode. |

## How to Configure the IPv6 Binding Table Content

Beginning in privileged EXEC mode, follow these steps to configure IPv6 Binding Table Content :

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <b>configure terminal</b><br><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>[no] ipv6 neighbor binding [vlan vlan-id {ipv6-address interface interface_type stack/module/port hw_address [reachable-lifetimevalue [seconds   default   infinite]   [tracking { default   disable } [reachable-lifetimevalue [seconds   default   infinite]   [enable [reachable-lifetimevalue [seconds   default   infinite]   [retry-interval {seconds} default [reachable-lifetimevalue [seconds   default   infinite] } ]</b><br><br><b>Example:</b><br>Device(config)# <b>ipv6 neighbor binding</b> | Adds a static entry to the binding table database.  |
| <b>Step 3</b> | <b>[no] ipv6 neighbor binding max-entries number [mac-limit number   port-limit number [mac-limit number]   vlan-limit number [mac-limit number]   port-limit number [mac-limit number] ] ]</b><br><br><b>Example:</b><br>Device(config)# <b>ipv6 neighbor binding max-entries 30000</b>   | Specifies the maximum number of entries that are allowed to be inserted in the binding table cache. |
| <b>Step 4</b> | <b>ipv6 neighbor binding logging</b><br><br><b>Example:</b><br>Device(config)# <b>ipv6 neighbor binding logging</b>  | Enables the logging of binding table main events.   |

|               | Command or Action   | Purpose   |
|---------------|---|---|
| <b>Step 5</b> | <b>exit</b><br><b>Example:</b><br>Device(config)# <b>exit</b>                                     | Exits global configuration mode, and places the router in privileged EXEC mode. |
| <b>Step 6</b> | <b>show ipv6 neighbor binding</b><br><b>Example:</b><br>Device# <b>show ipv6 neighbor binding</b> | Displays contents of a binding table.   |

## How to Configure an IPv6 Neighbor Discovery Inspection Policy

Beginning in privileged EXEC mode, follow these steps to configure an IPv6 ND Inspection Policy:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>[no]ipv6 nd inspection policy <i>policy-name</i></b><br><b>Example:</b><br>Device(config)# <b>ipv6 nd inspection policy example_policy</b>  | Specifies the ND inspection policy name and enters ND Inspection Policy configuration mode. |
| <b>Step 3</b> | <b>device-role {host   switch}</b><br><b>Example:</b><br>Device(config-nd-inspection)# <b>device-role switch</b>   | Specifies the role of the device attached to the port. The default is <b>host</b> .         |
| <b>Step 4</b> | <b>limit address-count <i>value</i></b><br><b>Example:</b><br>Device(config-nd-inspection)# <b>limit address-count 1000</b>  | Enter 1–10,000.   |
| <b>Step 5</b> | <b>tracking {enable [reachable-lifetime {<i>value</i>   infinite}]   disable [stale-lifetime {<i>value</i>   infinite}]}</b><br><b>Example:</b><br>Device(config-nd-inspection)# <b>tracking disable stale-lifetime infinite</b> | Overrides the default tracking policy on a port.  |
| <b>Step 6</b> | <b>trusted-port</b><br><b>Example:</b>   | Configures a port to become a trusted port.   |

|                | Command or Action   | Purpose  |
|----------------|---|--|
|                | Device (config-nd-inspection) #<br><b>trusted-port</b>  |  |
| <b>Step 7</b>  | <b>validate source-mac</b><br><br><b>Example:</b><br>Device (config-nd-inspection) # <b>validate source-mac</b>   | Checks the source media access control (MAC) address against the link-layer address.       |
| <b>Step 8</b>  | <b>no {device-role   limit address-count   tracking   trusted-port   validate source-mac}</b><br><br><b>Example:</b><br>Device (config-nd-inspection) # <b>no validate source-mac</b>           | Remove the current configuration of a parameter with the <b>no</b> form of the command.    |
| <b>Step 9</b>  | <b>default {device-role   limit address-count   tracking   trusted-port   validate source-mac}</b><br><br><b>Example:</b><br>Device (config-nd-inspection) # <b>default limit address-count</b> | Restores configuration to the default values.  |
| <b>Step 10</b> | <b>do show ipv6 nd inspection policy policy_name</b><br><br><b>Example:</b><br>Device (config-nd-inspection) # <b>do show ipv6 nd inspection policy example_policy</b>                          | Verifies the ND Inspection Configuration without exiting ND inspection configuration mode. |

## How to Attach an IPv6 Neighbor Discovery Inspection Policy to an Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 ND Inspection policy to an interface or VLANs on an interface :

### Procedure

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>configure terminal</b><br><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.  |
| <b>Step 2</b> | <b>interface Interface_type stack/module/port</b><br><br><b>Example:</b><br>Device (config) # <b>interface gigabitethernet 1/1/4</b> | Specifies an interface type and identifier; enters the interface configuration mode. |

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 3</b> | <p><b>ipv6 nd inspection</b> [<b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b>} ]   <b>vlan</b> [ {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b>} ]</p> <p><b>Example:</b></p> <pre>Device(config-if)# ipv6 nd inspection attach-policy example_policy  or  Device(config-if)# ipv6 nd inspection attach-policy example_policy vlan 222,223,224  or  Device(config-if)# ipv6 nd inspection vlan 222, 223,224</pre> | Attaches the Neighbor Discovery Inspection policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 4</b> | <p><b>do show running-config</b></p> <p><b>Example:</b></p> <pre>Device#(config-if)# do show running-config</pre>  | Verifies that the policy is attached to the specified interface without exiting the interface configuration mode.   |

## How to Attach an IPv6 Neighbor Discovery Inspection Policy to a Layer 2 EtherChannel Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Neighbor Discovery Inspection policy on an EtherChannel interface or VLAN:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>                        | Enters the global configuration mode.   |
| <b>Step 2</b> | <p><b>interface range</b> <i>Interface_name</i></p> <p><b>Example:</b></p> <pre>Device(config)# interface Po11</pre> | <p>Specify the port-channel interface name assigned when the EtherChannel was created. Enters the interface range configuration mode.</p> <p><b>Tip</b> Enter the <b>do show interfaces summary</b> command for quick reference to interface names and types.</p> |

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 3</b> | <p><b>ipv6 nd inspection</b> [<b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]   <b>vlan</b> [ {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]</p> <p><b>Example:</b></p> <pre>Device(config-if-range)# ipv6 nd inspection attach-policy example_policy  or  Device(config-if-range)# ipv6 nd inspection attach-policy example_policy vlan 222,223,224  or  Device(config-if-range)#ipv6 nd inspection vlan 222, 223,224</pre> | <p>Attaches the ND Inspection policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used.</p> |
| <b>Step 4</b> | <p><b>do show running-config interface</b> <i>portchannel_interface_name</i></p> <p><b>Example:</b></p> <pre>Device#(config-if-range)# do show running-config int poll</pre>  | <p>Confirms that the policy is attached to the specified interface without exiting the configuration mode.</p>   |

## How to Attach an IPv6 Neighbor Discovery Inspection Policy to VLANs Globally

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 ND Inspection policy to VLANs across multiple interfaces:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>                              | <p>Enters the global configuration mode.</p>  |
| <b>Step 2</b> | <p><b>vlan configuration</b> <i>vlan_list</i></p> <p><b>Example:</b></p> <pre>Device(config)# vlan configuration 334</pre> | <p>Specifies the VLANs to which the IPv6 Snooping policy will be attached ; enters the VLAN interface configuration mode.</p> |
| <b>Step 3</b> | <p><b>ipv6 nd inspection</b> [<b>attach-policy</b> <i>policy_name</i>]</p>   | <p>Attaches the IPv6 Neighbor Discovery policy to the specified VLANs across all switch and</p>                               |

|               | Command or Action   | Purpose  |
|---------------|---|--|
|               | <b>Example:</b><br>Device(config-vlan-config)# <b>ipv6 nd inspection attach-policy example_policy</b>     | stack interfaces. The default policy is attached if the <b>attach-policy</b> option is not used.<br><br>The default policy is, device-role <b>host</b> , no drop-unsecure, limit address-count disabled, sec-level minimum is disabled, tracking is disabled, no trusted-port, no validate source-mac. |
| <b>Step 4</b> | <b>do show running-config</b><br><br><b>Example:</b><br>Device#(config-if)# <b>do show running-config</b> | Confirms that the policy is attached to the specified VLANs without exiting the configuration mode.  |

## How to Configure an IPv6 Router Advertisement Guard Policy

Beginning in privileged EXEC mode, follow these steps to configure an IPv6 Router Advertisement policy :

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <b>configure terminal</b><br><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>[no]ipv6 nd raguard policy policy-name</b><br><br><b>Example:</b><br>Device(config)# <b>ipv6 nd raguard policy example_policy</b>     | Specifies the RA Guard policy name and enters RA Guard Policy configuration mode.   |
| <b>Step 3</b> | <b>[no]device-role {host   monitor   router   switch}</b><br><br><b>Example:</b><br>Device(config-nd-raguard)# <b>device-role switch</b> | Specifies the role of the device attached to the port. The default is <b>host</b> .<br><br><b>Note</b> For a network with both host-facing ports and router-facing ports, along with a RA guard policy configured with <b>device-role host</b> on host-facing ports or vlan, it is mandatory to configure a RA guard policy with <b>device-role router</b> on router-facing ports to allow the RA Guard feature to work properly. |

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 4</b> | <p><b>[no]hop-limit {maximum   minimum} value</b></p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard) # hop-limit maximum 33</pre>                                | <p>(1–255) Range for Maximum and Minimum Hop Limit values.</p> <p>Enables filtering of Router Advertisement messages by the Hop Limit value. A rogue RA message may have a low Hop Limit value (equivalent to the IPv4 Time to Live) that when accepted by the host, prevents the host from generating traffic to destinations beyond the rogue RA message generator. An RA message with an unspecified Hop Limit value is blocked.</p> <p>If not configured, this filter is disabled. Configure <b>minimum</b> to block RA messages with Hop Limit values lower than the value you specify. Configure <b>maximum</b> to block RA messages with Hop Limit values greater than the value you specify.</p> |
| <b>Step 5</b> | <p><b>[no]managed-config-flag {off   on}</b></p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard) # managed-config-flag on</pre>                                   | <p>Enables filtering of Router Advertisement messages by the Managed Address Configuration, or "M" flag field. A rogue RA message with an M field of 1 can cause a host to use a rogue DHCPv6 server. If not configured, this filter is disabled.</p> <p><b>On</b>—Accepts and forwards RA messages with an M value of 1, blocks those with 0.</p> <p><b>Off</b>—Accepts and forwards RA messages with an M value of 0, blocks those with 1.</p>   |
| <b>Step 6</b> | <p><b>[no]match {ipv6 access-list list   ra prefix-list list}</b></p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard) # match ipv6 access-list example_list</pre> | <p>Matches a specified prefix list or access list.</p>   |
| <b>Step 7</b> | <p><b>[no]other-config-flag {on   off}</b></p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard) # other-config-flag on</pre>                                       | <p>Enables filtering of Router Advertisement messages by the Other Configuration, or "O" flag field. A rogue RA message with an O field of 1 can cause a host to use a rogue DHCPv6 server. If not configured, this filter is disabled.</p> <p><b>On</b>—Accepts and forwards RA messages with an O value of 1, blocks those with 0.</p> <p><b>Off</b>—Accepts and forwards RA messages with an O value of 0, blocks those with 1.</p>   |

|                | Command or Action   | Purpose  |
|----------------|---|--|
| <b>Step 8</b>  | <p>[no]router-preference maximum {high   medium   low}</p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard)# router-preference maximum high</pre>  | <p>Enables filtering of Router Advertisement messages by the Router Preference flag. If not configured, this filter is disabled.</p> <ul style="list-style-type: none"> <li>• <b>high</b>—Accepts RA messages with the Router Preference set to high, medium, or low.</li> <li>• <b>medium</b>—Blocks RA messages with the Router Preference set to high.</li> <li>• <b>low</b>—Blocks RA messages with the Router Preference set to medium and high.</li> </ul> |
| <b>Step 9</b>  | <p>[no]trusted-port</p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard)# trusted-port</pre>   | <p>When configured as a trusted port, all attached devices are trusted, and no further message verification is performed.</p>  |
| <b>Step 10</b> | <p>default {device-role   hop-limit {maximum   minimum}   managed-config-flag   match {ipv6 access-list   ra prefix-list }   other-config-flag   router-preference maximum   trusted-port}</p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard)# default hop-limit</pre> | <p>Restores a command to its default value.</p>  |
| <b>Step 11</b> | <p>do show ipv6 nd raguard policy <i>policy_name</i></p> <p><b>Example:</b></p> <pre>Device(config-nd-raguard)# do show ipv6 nd raguard policy example_policy</pre>   | <p>(Optional)—Displays the ND Guard Policy configuration without exiting the RA Guard policy configuration mode.</p>   |

## How to Attach an IPv6 Router Advertisement Guard Policy to an Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Router Advertisement policy to an interface or to VLANs on the interface :

### Procedure

|               | Command or Action  | Purpose                                      |
|---------------|--|--|
| <b>Step 1</b> | <p>configure terminal</p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre> | <p>Enters the global configuration mode.</p> |



|               | Command or Action   | Purpose   |
|---------------|---|---|
| <b>Step 2</b> | <b>interface</b> Interface_type <i>stack/module/port</i><br><b>Example:</b><br>Device(config)# <b>interface</b><br><b>gigabitethernet 1/1/4</b>   | Specifies an interface type and identifier; enters the interface configuration mode.  |
| <b>Step 3</b> | <b>ipv6 nd rguard</b> [ <b>attach-policy</b> <i>policy_name</i><br>[ <b>vlan</b> { <i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b><br><i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]   <b>vlan</b><br>[ { <i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>  <br><b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ] ]<br><b>Example:</b><br>Device(config-if)# <b>ipv6 nd rguard</b><br><b>attach-policy example_policy</b><br><br>or<br>Device(config-if)# <b>ipv6 nd rguard</b><br><b>attach-policy example_policy vlan</b><br><b>222,223,224</b><br><br>or<br>Device(config-if)# <b>ipv6 nd rguard vlan</b><br><b>222, 223,224</b> | Attaches the Neighbor Discovery Inspection policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 4</b> | <b>do show running-config</b><br><b>Example:</b><br>Device#(config-if)# <b>do show</b><br><b>running-config</b>   | Confirms that the policy is attached to the specified interface without exiting the configuration mode.   |

## How to Attach an IPv6 Router Advertisement Guard Policy to a Layer 2 EtherChannel Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Router Advertisement Guard Policy on an EtherChannel interface or VLAN:

### Procedure

|               | Command or Action   | Purpose                               |
|---------------|---|---------------------------------------|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b> | Enters the global configuration mode. |

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 2</b> | <b>interface range</b> <i>Interface_name</i><br><b>Example:</b><br>Device(config)# <b>interface</b> Po11  | Specify the port-channel interface name assigned when the EtherChannel was created. Enters the interface range configuration mode.<br><br><b>Tip</b> Enter the <b>do show interfaces summary</b> command for quick reference to interface names and types. |
| <b>Step 3</b> | <b>ipv6 nd raguard</b> [ <b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> { <i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]   <b>vlan</b> [ { <i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ] ]<br><b>Example:</b><br>Device(config-if-range)# <b>ipv6 nd raguard attach-policy example_policy</b><br><br>or<br><br>Device(config-if-range)# <b>ipv6 nd raguard attach-policy example_policy vlan 222,223,224</b><br><br>or<br><br>Device(config-if-range)# <b>ipv6 nd raguard vlan 222, 223,224</b> | Attaches the RA Guard policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used.   |
| <b>Step 4</b> | <b>do show running-config interfaceportchannel_interface_name</b><br><b>Example:</b><br>Device#(config-if-range)# <b>do show running-config int poll</b>  | Confirms that the policy is attached to the specified interface without exiting the configuration mode.  |

## How to Attach an IPv6 Router Advertisement Guard Policy to VLANs Globally

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 Router Advertisement policy to VLANs regardless of interface:

### Procedure

|               | Command or Action   | Purpose                           |
|---------------|---|-----------------------------------|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b> | Enters global configuration mode. |

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 2</b> | <b>vlan configuration</b> <i>vlan_list</i><br><b>Example:</b><br>Device(config)# <b>vlan configuration 335</b>   | Specifies the VLANs to which the IPv6 RA Guard policy will be attached ; enters the VLAN interface configuration mode.  |
| <b>Step 3</b> | <b>ipv6 dhcp guard</b> [ <b>attach-policy</b> <i>policy_name</i> ]<br><b>Example:</b><br>Device(config-vlan-config)# <b>ipv6 nd raguard attach-policy example_policy</b> | Attaches the IPv6 RA Guard policy to the specified VLANs across all switch and stack interfaces. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 4</b> | <b>do show running-config</b><br><b>Example:</b><br>Device#(config-if)# <b>do show running-config</b>  | Confirms that the policy is attached to the specified VLANs without exiting the configuration mode.   |

## How to Configure an IPv6 DHCP Guard Policy

Beginning in privileged EXEC mode, follow these steps to configure an IPv6 DHCP (DHCPv6) Guard policy:

### Procedure

|               | Command or Action   | Purpose   |
|---------------|---|---|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>   | Enters the global configuration mode.   |
| <b>Step 2</b> | <b>[no]ipv6 dhcp guard policy</b> <i>policy-name</i><br><b>Example:</b><br>Device(config)# <b>ipv6 dhcp guard policy example_policy</b> | Specifies the DHCPv6 Guard policy name and enters DHCPv6 Guard Policy configuration mode.   |
| <b>Step 3</b> | <b>[no]device-role</b> { <b>client</b>   <b>server</b> }<br><b>Example:</b><br>Device(config-dhcp-guard)# <b>device-role server</b>     | (Optional) Filters out DHCPv6 replies and DHCPv6 advertisements on the port that are not from a device of the specified role. Default is <b>client</b> . <ul style="list-style-type: none"> <li>• <b>client</b>—Default value, specifies that the attached device is a client. Server messages are dropped on this port.</li> <li>• <b>server</b>—Specifies that the attached device is a DHCPv6 server. Server messages are allowed on this port.</li> </ul> |

|        | Command or Action   | Purpose   |
|--------|---|---|
| Step 4 | <p><b>[no] match server access-list</b><br/><i>ipv6-access-list-name</i></p> <p><b>Example:</b></p> <pre>;;Assume a preconfigured IPv6 Access List as follows: Device(config)# ipv6 access-list my_acls Device(config-ipv6-acl)# permit host FE80::A8BB:CCFF:FE01:F700 any  ;;configure DCHPv6 Guard to match approved access list. Device(config-dhcp-guard)# match server access-list my_acls</pre> | <p>(Optional). Enables verification that the advertised DHCPv6 server or relay address is from an authorized server access list (The destination address in the access list is 'any'). If not configured, this check will be bypassed. An empty access list is treated as a permit all.</p>   |
| Step 5 | <p><b>[no] match reply prefix-list</b><br/><i>ipv6-prefix-list-name</i></p> <p><b>Example:</b></p> <pre>;;Assume a preconfigured IPv6 prefix list as follows: Device(config)# ipv6 prefix-list my_prefix permit 2001:0DB8::/64 le 128  ;; Configure DCHPv6 Guard to match prefix Device(config-dhcp-guard)# match reply prefix-list my_prefix</pre>   | <p>(Optional) Enables verification of the advertised prefixes in DHCPv6 reply messages from the configured authorized prefix list. If not configured, this check will be bypassed. An empty prefix list is treated as a permit.</p>   |
| Step 6 | <p><b>[no]preference{ max limit   min limit }</b></p> <p><b>Example:</b></p> <pre>Device (config-dhcp-guard) # preference max 250 Device (config-dhcp-guard) #preference min 150</pre>  | <p>Configure <b>max</b> and <b>min</b> when <b>device-role</b> is <b>server</b> to filter DHCPv6 server advertisements by the server preference value. The defaults permit all advertisements.</p> <p><b>max limit</b>—(0 to 255) (Optional) Enables verification that the advertised preference (in preference option) is less than the specified limit. Default is 255. If not specified, this check will be bypassed.</p> <p><b>min limit</b>—(0 to 255) (Optional) Enables verification that the advertised preference (in preference option) is greater than the specified limit. Default is 0. If not specified, this check will be bypassed.</p> |
| Step 7 | <p><b>[no] trusted-port</b></p> <p><b>Example:</b></p> <pre>Device (config-dhcp-guard) # trusted-port</pre>   | <p>(Optional) <b>trusted-port</b>—Sets the port to a trusted mode. No further policing takes place on the port.</p> <p><b>Note</b> If you configure a trusted port then the device-role option is not available.</p>  |

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 8</b> | <b>default {device-role   trusted-port}</b><br><b>Example:</b><br>Device(config-dhcp-guard) # <b>default device-role</b>                                 | (Optional) <b>default</b> —Sets a command to its defaults.  |
| <b>Step 9</b> | <b>do show ipv6 dhcp guard policy policy_name</b><br><b>Example:</b><br>Device(config-dhcp-guard) # <b>do show ipv6 dhcp guard policy example_policy</b> | (Optional) Displays the configuration of the IPv6 DHCP guard policy without leaving the configuration submode. Omitting the <i>policy_name</i> variable displays all DHCPv6 policies. |

**Example of DHCPv6 Guard Configuration**

```
enable
configure terminal
ipv6 access-list acl1
 permit host FE80::A8BB:CCFF:FE01:F700 any
ipv6 prefix-list abc permit 2001:0DB8::/64 le 128
ipv6 dhcp guard policy poll1
 device-role server
 match server access-list acl1
 match reply prefix-list abc
 preference min 0
 preference max 255
 trusted-port
interface GigabitEthernet 0/2/0
 switchport
 ipv6 dhcp guard attach-policy poll1 vlan add 1
 vlan 1
  ipv6 dhcp guard attach-policy poll1
show ipv6 dhcp guard policy poll1
```

## How to Attach an IPv6 DHCP Guard Policy to an Interface or a VLAN on an Interface

Beginning in privileged EXEC mode, follow these steps to configure IPv6 Binding Table Content :

**Procedure**

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.  |
| <b>Step 2</b> | <b>interface Interface_type stack/module/port</b><br><b>Example:</b><br>Device(config)# <b>interface gigabitethernet 1/1/4</b> | Specifies an interface type and identifier; enters the interface configuration mode. |

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 3</b> | <p><b>ipv6 dhcp guard</b> [<b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b>} ] ]   <b>vlan</b> [ {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b>} ]</p> <p><b>Example:</b></p> <pre>Device(config-if)# ipv6 dhcp guard attach-policy example_policy  or  Device(config-if)# ipv6 dhcp guard attach-policy example_policy vlan 222,223,224  or  Device(config-if)# ipv6 dhcp guard vlan 222, 223,224</pre> | Attaches the DHCP Guard policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 4</b> | <p><b>do show running-config interface</b> <i>Interface_type stack/module/port</i></p> <p><b>Example:</b></p> <pre>Device#(config-if)# do show running-config gig 1/1/4</pre>  | Confirms that the policy is attached to the specified interface without exiting the configuration mode.  |

## How to Attach an IPv6 DHCP Guard Policy to a Layer 2 EtherChannel Interface

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 DHCP Guard policy on an EtherChannel interface or VLAN:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>                        | Enters the global configuration mode.   |
| <b>Step 2</b> | <p><b>interface range</b> <i>Interface_name</i></p> <p><b>Example:</b></p> <pre>Device(config)# interface Po11</pre> | <p>Specify the port-channel interface name assigned when the EtherChannel was created. Enters the interface range configuration mode.</p> <p><b>Tip</b> Enter the <b>do show interfaces summary</b> command for quick reference to interface names and types.</p> |

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 3</b> | <p><b>ipv6 dhcp guard</b> [<b>attach-policy</b> <i>policy_name</i> [ <b>vlan</b> {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]   <b>vlan</b> [ {<i>vlan_ids</i>   <b>add</b> <i>vlan_ids</i>   <b>except</b> <i>vlan_ids</i>   <b>none</b>   <b>remove</b> <i>vlan_ids</i>   <b>all</b> } ]</p> <p><b>Example:</b></p> <pre>Device(config-if-range)# ipv6 dhcp guard attach-policy example_policy</pre> <p>or</p> <pre>Device(config-if-range)# ipv6 dhcp guard attach-policy example_policy vlan 222,223,224</pre> <p>or</p> <pre>Device(config-if-range)#ipv6 dhcp guard vlan 222, 223,224</pre> | Attaches the DHCP Guard policy to the interface or the specified VLANs on that interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 4</b> | <p><b>do show running-config</b> <i>interface portchannel_interface_name</i></p> <p><b>Example:</b></p> <pre>Device#(config-if-range)# do show running-config int poll</pre>  | Confirms that the policy is attached to the specified interface without exiting the configuration mode.  |

## How to Attach an IPv6 DHCP Guard Policy to VLANs Globally

Beginning in privileged EXEC mode, follow these steps to attach an IPv6 DHCP Guard policy to VLANs across multiple interfaces:

### Procedure

|               | Command or Action  | Purpose   |
|---------------|--|---|
| <b>Step 1</b> | <p><b>configure terminal</b></p> <p><b>Example:</b></p> <pre>Device# configure terminal</pre>                              | Enters the global configuration mode.   |
| <b>Step 2</b> | <p><b>vlan configuration</b> <i>vlan_list</i></p> <p><b>Example:</b></p> <pre>Device(config)# vlan configuration 334</pre> | Specifies the VLANs to which the IPv6 Snooping policy will be attached ; enters the VLAN interface configuration mode.                    |
| <b>Step 3</b> | <p><b>ipv6 dhcp guard</b> [<b>attach-policy</b> <i>policy_name</i>]</p> <p><b>Example:</b></p>                             | Attaches the IPv6 Neighbor Discovery policy to the specified VLANs across all switch and stack interfaces. The default policy is attached |

|               | Command or Action   | Purpose  |
|---------------|---|--|
|               | Device(config-vlan-config)# <b>ipv6 dhcp guard attach-policy example_policy</b>                           | if the <b>attach-policy</b> option is not used. The default policy is, device-role <b>client</b> , <b>no</b> trusted-port. |
| <b>Step 4</b> | <b>do show running-config</b><br><br><b>Example:</b><br>Device#(config-if)# <b>do show running-config</b> | Confirms that the policy is attached to the specified VLANs without exiting the configuration mode.                        |

## How to Configure IPv6 Source Guard

### Procedure

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>enable</b><br><br><b>Example:</b><br><br>Device> <b>enable</b>  | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>   |
| <b>Step 2</b> | <b>configure terminal</b><br><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.  |
| <b>Step 3</b> | <b>[no] ipv6 source-guard policy policy_name</b><br><br><b>Example:</b><br>Device(config)# <b>ipv6 source-guard policy example_policy</b>                                | Specifies the IPv6 Source Guard policy name and enters IPv6 Source Guard policy configuration mode.  |
| <b>Step 4</b> | <b>[deny global-autoconf] [permit link-local] [default{...}] [exit] [no{...}]</b><br><br><b>Example:</b><br>Device(config-sisf-sourceguard)# <b>deny global-autoconf</b> | (Optional) Defines the IPv6 Source Guard policy. <ul style="list-style-type: none"> <li>• <b>deny global-autoconf</b>—Denies data traffic from auto-configured global addresses. This is useful when all global addresses on a link are DHCP-assigned and the administrator wants to block hosts with self-configured addresses to send traffic.</li> <li>• <b>permit link-local</b>—Allows all data traffic that is sourced by a link-local address.</li> </ul> <p><b>Note</b> Trusted option under source guard policy is not supported.</p> |



|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 5</b> | <b>end</b><br><b>Example:</b><br>Device(config-sisf-sourceguard)# <b>end</b>  | Exits out of IPv6 Source Guard policy configuration mode.                          |
| <b>Step 6</b> | <b>show ipv6 source-guard policy <i>policy_name</i></b><br><b>Example:</b><br>Device# <b>show ipv6 source-guard policy example_policy</b> | Shows the policy configuration and all the interfaces where the policy is applied. |

**What to do next**

Apply the IPv6 Source Guard policy to an interface.

## How to Attach an IPv6 Source Guard Policy to an Interface

**Procedure**

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>enable</b><br><b>Example:</b><br>Device> <b>enable</b>  | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>                     |
| <b>Step 2</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.  |
| <b>Step 3</b> | <b>interface</b> Interface_type <i>stack/module/port</i><br><b>Example:</b><br>Device(config)# <b>interface gigabitethernet 1/1/4</b>                        | Specifies an interface type and identifier; enters the interface configuration mode.   |
| <b>Step 4</b> | <b>ipv6 source-guard [attach-policy &lt;policy_name&gt; ]</b><br><b>Example:</b><br>Device(config-if)# <b>ipv6 source-guard attach-policy example_policy</b> | Attaches the IPv6 Source Guard policy to the interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 5</b> | <b>show ipv6 source-guard policy <i>policy_name</i></b><br><b>Example:</b><br>Device#(config-if)# <b>show ipv6 source-guard policy example_policy</b>        | Shows the policy configuration and all the interfaces where the policy is applied.   |

## How to attach an IPv6 Source Guard Policy to a Layer 2 EtherChannel Interface

### Procedure

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>enable</b><br><b>Example:</b><br>Device> <b>enable</b>  | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>                     |
| <b>Step 2</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>  | Enters the global configuration mode.  |
| <b>Step 3</b> | <b>interface port-channel</b> <i>port-channel-number</i><br><b>Example:</b><br>Device (config)# <b>interface Po4</b>   | Specifies an interface type and port number and places the switch in the port channel configuration mode.                              |
| <b>Step 4</b> | <b>ipv6 source-guard</b> [ <b>attach-policy</b> <i>&lt;policy_name&gt;</i> ]<br><b>Example:</b><br>Device(config-if) # <b>ipv6 source-guard attach-policy example_policy</b> | Attaches the IPv6 Source Guard policy to the interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 5</b> | <b>show ipv6 source-guard policy</b> <i>policy_name</i><br><b>Example:</b><br>Device(config-if) # <b>show ipv6 source-guard policy example_policy</b>                        | Shows the policy configuration and all the interfaces where the policy is applied.   |

## How to Configure IPv6 Prefix Guard



**Note** To allow routing protocol control packets sourced by a link-local address when prefix guard is applied, enable the permit link-local command in the source-guard policy configuration mode.

### Procedure

|               | Command or Action                | Purpose  |
|---------------|----------------------------------|--|
| <b>Step 1</b> | <b>enable</b><br><b>Example:</b> | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul> |

|               | Command or Action   | Purpose   |
|---------------|---|---|
|               | Device> <b>enable</b>   |   |
| <b>Step 2</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <b>configure terminal</b>   | Enters global configuration mode.   |
| <b>Step 3</b> | <b>[ no ] ipv6 source-guard policy</b><br><i>source-guard-policy</i><br><b>Example:</b><br>Device(config)# <b>ipv6 source-guard policy</b><br><b>my_snooping_policy</b> | Defines an IPv6 source-guard policy name and enters switch integrated security features source-guard policy configuration mode. |
| <b>Step 4</b> | <b>[ no ] validate address</b><br><b>Example:</b><br>Device(config-sisf-sourceguard)# <b>no</b><br><b>validate address</b>  | Disables the validate address feature and enables the IPv6 prefix guard feature to be configured.                               |
| <b>Step 5</b> | <b>validate prefix</b><br><b>Example:</b><br>Device(config-sisf-sourceguard)# <b>validate</b><br><b>prefix</b>  | Enables IPv6 source guard to perform the IPv6 prefix-guard operation.   |
| <b>Step 6</b> | <b>exit</b><br><b>Example:</b><br>Device(config-sisf-sourceguard)# <b>exit</b>  | Exits switch integrated security features source-guard policy configuration mode and returns to privileged EXEC mode.           |
| <b>Step 7</b> | <b>show ipv6 source-guard policy</b><br><i>[source-guard-policy]</i><br><b>Example:</b><br>Device# <b>show ipv6 source-guard policy</b><br><b>policy1</b>               | Displays the IPv6 source-guard policy configuration.  |

## How to Attach an IPv6 Prefix Guard Policy to an Interface

### Procedure

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 1</b> | <b>enable</b><br><b>Example:</b><br>Device> <b>enable</b> | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul> |

|               | Command or Action   | Purpose  |
|---------------|---|--|
| <b>Step 2</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <code>configure terminal</code>   | Enters the global configuration mode.  |
| <b>Step 3</b> | <b>interface</b> <i>Interface_type stack/module/port</i><br><b>Example:</b><br>Device (config)# <code>interface gigabitethernet 1/1/4</code>                    | Specifies an interface type and identifier; enters the interface configuration mode.   |
| <b>Step 4</b> | <b>ipv6 source-guard attach-policy</b> <i>policy_name</i><br><b>Example:</b><br>Device (config-if)# <code>ipv6 source-guard attach-policy example_policy</code> | Attaches the IPv6 Source Guard policy to the interface. The default policy is attached if the <b>attach-policy</b> option is not used. |
| <b>Step 5</b> | <b>show ipv6 source-guard policy</b> <i>policy_name</i><br><b>Example:</b><br>Device (config-if)# <code>show ipv6 source-guard policy example_policy</code>     | Shows the policy configuration and all the interfaces where the policy is applied.   |

## How to attach an IPv6 Prefix Guard Policy to a Layer 2 EtherChannel Interface

### Procedure

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 1</b> | <b>enable</b><br><b>Example:</b><br>Device> <code>enable</code>  | Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>                     |
| <b>Step 2</b> | <b>configure terminal</b><br><b>Example:</b><br>Device# <code>configure terminal</code>  | Enters the global configuration mode.  |
| <b>Step 3</b> | <b>interface port-channel</b> <i>port-channel-number</i><br><b>Example:</b><br>Device (config)# <code>interface Po4</code>   | Specifies an interface type and port number and places the switch in the port channel configuration mode.                              |
| <b>Step 4</b> | <b>ipv6 source-guard</b> [ <b>attach-policy</b> <i>&lt;policy_name&gt;</i> ]<br><b>Example:</b><br>Device (config-if)# <code>ipv6 source-guard attach-policy example_policy</code> | Attaches the IPv6 Source Guard policy to the interface. The default policy is attached if the <b>attach-policy</b> option is not used. |

|               | Command or Action  | Purpose  |
|---------------|--|--|
| <b>Step 5</b> | <b>show ipv6 source-guard policy <i>policy_name</i></b><br><br><b>Example:</b><br>Device(config-if)# <b>show ipv6 source-guard policy example_policy</b> | Shows the policy configuration and all the interfaces where the policy is applied. |

## Configuration Examples for IPv6 First Hop Security

### Examples: How to attach an IPv6 Source Guard Policy to a Layer 2 EtherChannel Interface

The following example shows how to attach an IPv6 Source Guard Policy to a Layer 2 EtherChannel Interface:

```
Switch# configure terminal
Switch(config)# ipv6 source-guard policy POL
Switch(config-sisf-sourceguard) # validate address
switch(config-sisf-sourceguard)# exit
Switch(config)# interface Po4
Switch(config)# ipv6 snooping
Switch(config-if)# ipv6 source-guard attach-policy POL
Switch(config-if)# exit
switch(config)#
```

### Examples: How to attach an IPv6 Prefix Guard Policy to a Layer 2 EtherChannel Interface

The following example shows how to attach an IPv6 Prefix Guard Policy to a Layer 2 EtherChannel Interface:

```
Switch# configure terminal
Switch(config)# ipv6 source-guard policy POL
Switch (config-sisf-sourceguard)# no validate address
Switch((config-sisf-sourceguard)# validate prefix
Switch(config)# interface Po4
Switch(config-if)# ipv6 snooping
Switch(config-if)# ipv6 source-guard attach-policy POL
```

