



Configuring VideoStream

- [Finding Feature Information, page 1](#)
- [Prerequisites for VideoStream, page 1](#)
- [Restrictions for Configuring VideoStream, page 2](#)
- [Information about VideoStream, page 2](#)
- [How to Configure VideoStream, page 2](#)
- [Monitoring Media Streams, page 7](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to <http://www.cisco.com/go/cfn>. An account on Cisco.com is not required.

Prerequisites for VideoStream

Make sure that the multicast feature is enabled. We recommend configuring IP multicast on the controller with multicast-multicast mode.

Check for the IP address on the client machine. The machine should have an IP address from the respective VLAN.

Verify that the access points have joined the controllers.

Restrictions for Configuring VideoStream

Information about VideoStream

The IEEE 802.11 wireless multicast delivery mechanism does not provide a reliable way to acknowledge lost or corrupted packets. As a result, if any multicast packet is lost in the air, it is not sent again which may cause an IP multicast stream unviewable.

The VideoStream feature makes the IP multicast stream delivery reliable over the air, by converting the multicast frame to a unicast frame over the air. Each VideoStream client acknowledges receiving a video IP multicast stream.

How to Configure VideoStream

Configuring Multicast-Direct Globally for Media-Stream

SUMMARY STEPS

1. **configure terminal**
2. **wireless multicast**
3. **IP igmp snooping**
4. **IP igmp snooping querier**
5. **wireless media-stream multicast-direct**
6. **wireless media-stream message**
7. **wireless media-stream group<name><startIp><endIp>**
8. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example: Switch# configure terminal	
Step 2	wireless multicast	Enables multicast for wireless forwarding.
Step 3	IP igmp snooping	Enables IGMP snooping on a per-VLAN basis. If the global setting is disabled, then all VLANs are treated as disabled, whether they are enabled or not.

	Command or Action	Purpose
Step 4	IP igmp snooping querier	Configures a snooping querier on an interface when there is no multicast router in the VLAN to generate queries.
Step 5	wireless media-stream multicast-direct Example: Switch(config)#wireless media-stream multicast-direct	Configures the global multicast-direct feature for the controller.
Step 6	wireless media-stream message Example: Switch(config)#wireless media-stream message ? Email Configure Session Announcement Email Notes Configure Session Announcement notes URL Configure Session Announcement URL phone Configure Session Announcement Phone number <cr>	Configures various message configuration parameters like phone, URL, email and notes. That is, when a media stream is refused (due to bandwidth constraints), a message can be sent to the user. These parameters configure the messages to send IT support email address, notes (message to display explaining why the stream was refused), URL to which the user can be redirected and the phone number that the user can call about the refused stream.
Step 7	wireless media-stream group<name><startIp><endIp> Example: Switch(config)#wireless media-stream group grp1 231.1.1.1 239.1.1.3 Switch(config-media-stream)#? avg-packet-size Configures average packet size default Set a command to its defaults exit Exit sub-mode max-bandwidth Configures maximum Expected Stream Bandwidth in Kbps no Negate a command or set its defaults policy Configure media stream admission policy qos Configure Over the AIR QoS class, <'video'> ONLY <cr>	configures each media stream and its parameters like expected multicast destination addresses, stream bandwidth consumption and stream priority parameters.
Step 8	end Example: Switch(config) # end	Returns to privileged EXEC mode. Alternatively, you can also press Ctrl-Z to exit global configuration mode.

Configuring Media-Stream for 802.11 bands

SUMMARY STEPS

1. configure terminal
2. ap dot11 24ghz | 5ghz media-stream multicast-direct
3. ap dot11 24ghz | 5ghz media-stream video-redirect
4. ap dot11 24ghz | 5ghz media-stream multicast-direct admission-besteffort
5. ap dot11 24ghz | 5ghz media-stream multicast-direct client-maximum [<value>]
6. ap dot11 24ghz | 5ghz media-stream multicast-direct radio-maximum 20
7. ap dot11 24ghz | 5ghz cac multimedia max-bandwidth [<bandwidth>]
8. ap dot11 24ghz | 5ghz cac media-stream multicast-direct min_client_rate [<dot11_rate>]
9. ap dot11 5ghz cac media-stream
10. ap dot11 5ghz cac multimedia
11. ap dot11 5ghz cac video
12. ap dot11 5ghz cac voice
13. end

DETAILED STEPS

	Command or Action	Purpose
Step 1	configure terminal	Enters global configuration mode.
	Example: Switch# configure terminal	
Step 2	ap dot11 24ghz 5ghz media-stream multicast-direct	Configures if media stream (mc2uc) is allowed for 802.11 band
	Example: Switch(config)# ap dot11 24ghz media-stream multicast-direct	
Step 3	ap dot11 24ghz 5ghz media-stream video-redirect	Configures to redirect unicast video traffic to best effort queue.
	Example: Switch(config)# ap dot11 24ghz media-stream video-redirect	
Step 4	ap dot11 24ghz 5ghz media-stream multicast-direct admission-besteffort	Configures the media stream to still be sent through the best effort queue if a media stream cannot be prioritized due to bandwidth availability limitations. Add no in the command to drop the stream if the media stream cannot be prioritized due to bandwidth availability limitations.
	Example: Switch(config)# ap dot11 24ghz media-stream multicast-direct admission-besteffort	

	Command or Action	Purpose
Step 5	ap dot11 24ghz 5ghz media-stream multicast-direct client-maximum [<value>] Example: Switch(config) #ap dot11 24ghz media-stream multicast-direct client-max 15	Configures maximum number of allowed media streams per individual client. The maximum is 15 and the default is 0. Value 0 denotes unlimited streams.
Step 6	ap dot11 24ghz 5ghz media-stream multicast-direct radio-maximum 20	Configures maximum number of radio streams. The range is from 1 to 20. Default is 0. Value 0 denotes unlimited streams.
Step 7	ap dot11 24ghz 5ghz cac multimedia max-bandwidth [<bandwidth>] Example: Switch(config) #ap dot11 24ghz cac multimedia max-bandwidth 60	Configure maximum media (voice + video) bandwidth in %. The range is between 5% and 85%.
Step 8	ap dot11 24ghz 5ghz cac media-stream multicast-direct min_client_rate [<dot11_rate>] Example: Switch(config) #ap dot11 24ghz cac media-stream multicast-direct min_client_rate	Configures the minimum PHY rate needed for a client to send media-stream as unicast. Clients communicating below this rate will not receive the media stream as a unicast flow. Typically, this PHY rate is equal to or higher than the rate at which multicast frames are sent.
Step 9	ap dot11 5ghz cac media-stream	Configures CAC parameters for media stream access category.
Step 10	ap dot11 5ghz cac multimedia	Configures CAC parameters for media access category, used for voice and video.
Step 11	ap dot11 5ghz cac video	Configures CAC parameters for video access category, used for voice signaling.
Step 12	ap dot11 5ghz cac voice	Configures CAC parameters for voice access category.
Step 13	end Example: Switch(config) # end	Returns to privileged EXEC mode. Alternatively, you can also press Ctrl-Z to exit global configuration mode.

Configuring WLAN to Stream Video

SUMMARY STEPS

1. **configure terminal**
2. **wlan wlan_name**
3. **shutdown**
4. **media-stream multicast-direct**
5. **no shutdown**
6. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	configure terminal Example: Switch# configure terminal	Enters global configuration mode.
Step 2	wlan wlan_name Example: Switch(config)# wlan wlan50	Enters the WLAN configuration mode.
Step 3	shutdown Example: Switch(config-wlan)# shutdown	Disables the WLAN for configuring its parameters.
Step 4	media-stream multicast-direct Example: Switch(config)# media-stream multicast-direct	Configures the multicast-direct feature on media-stream for the WLAN.
Step 5	no shutdown Example: Switch(config-wlan)# no shutdown	Enables the WLAN.
Step 6	end Example: Switch(config)# end	Returns to privileged EXEC mode. Alternatively, you can also press Ctrl-Z to exit global configuration mode.

Deleting a Media-Stream

Before You Begin

The media-stream should be enabled and configured for it to be deleted.

SUMMARY STEPS

1. **configure terminal**
2. **no wireless media-stream group media_stream_name**
3. **end**

DETAILED STEPS

	Command or Action	Purpose
Step 1	configure terminal Example: Switch# configure terminal	Enters global configuration mode.
Step 2	no wireless media-stream group media_stream_name Example: Switch(config)# no wireless media-stream grp1	Deletes the media-stream which bears the name mentioned in the command.
Step 3	end Example: Switch(config)# end	Returns to privileged EXEC mode. Alternatively, you can also press Ctrl-Z to exit global configuration mode.

Monitoring Media Streams

Table 1: Commands for monitoring media streams

Commands	Description
show wireless media-stream client detail <i>group name</i>	Displays media stream client details of the particular group.
show wireless media-stream client summary	Displays the media stream information of all the clients.
show wireless media-stream group detail <i>group name</i>	Displays the media stream configuration details of the particular group.

Commands	Description
show wireless media-stream group summary	Displays the media stream configuration details of all the groups.
show wireless media-stream message details	Displays the session announcement message details.
show wireless multicast	Displays the multicast-direct configuration state.
show ap dot11 24ghz 5ghz media-stream rrc	Displays 802.11 media Resource-Reservation-Control configurations.