



Link Configuration Mode Commands

Command Modes

The Link configuration mode defines the MTP3 link parameters for a specific link in a linkset of an SS7 routing domain instance.

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id) #
```



Important

The commands or keywords/variables that are available are dependent on platform type, product version, and installed license(s).

- [arbitration](#), on page 2
- [do show](#), on page 3
- [end](#), on page 3
- [exit](#), on page 3
- [mtp2-aerm-emergency-threshold](#), on page 4
- [mtp2-aerm-normal-threshold](#), on page 4
- [mtp2-eim-decrement](#), on page 5
- [mtp2-eim-increment](#), on page 6
- [mtp2-eim-threshold](#), on page 6
- [mtp2-error-correction](#), on page 7
- [mtp2-lssu-len](#), on page 8
- [mtp2-max-outstand-frames](#), on page 9
- [mtp2-suerm-threshold](#), on page 10
- [mtp3-discard-priority](#), on page 10
- [mtp3-max-slt-try](#), on page 11
- [mtp3-msg-priority](#), on page 12
- [mtp3-msg-size](#), on page 12
- [mtp3-p1-qlen](#), on page 13
- [mtp3-p2-qlen](#), on page 14
- [mtp3-p3-qlen](#), on page 15

- [mtp3-test-pattern](#), on page 15
- [priority](#), on page 16
- [signaling-link-code](#), on page 17
- [sscf-nni-n1](#), on page 17
- [sscop-max-cc](#), on page 18
- [sscop-max-pd](#), on page 19
- [sscop-max-stat](#), on page 20
- [timeout](#), on page 20

arbitration

This command configures link arbitration.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
arbitration { active | passive }  
no arbitration
```

no

Removes the arbitration configuration for the link.

active

The SSCOP initiates the transmission of PDUs.

passive

The SSCOP waits to receive PDUs.

Usage Guidelines

Sets the configuration to initiate transmission of PDUs.

Example

```
arbitration active
```

do show

Executes all **show** commands while in Configuration mode.

Product

All

Privilege

Security Administrator, Administrator

Syntax Description

do show

Usage Guidelines

Use this command to run all Exec mode **show** commands while in Configuration mode. It is not necessary to exit the Config mode to run a **show** command.

The pipe character | is only available if the command is valid in the Exec mode.



Caution

There are some Exec mode **show** commands which are too resource intensive to run from Config mode. These include: **do show support collection**, **do show support details**, **do show support record** and **do show support summary**. If there is a restriction on a specific **show** command, the following error message is displayed:

```
Failure: Cannot execute 'do show support' command from Config mode.
```

end

Exits the current configuration mode and returns to the Exec mode.

Product

All

Privilege

Security Administrator, Administrator

Syntax Description

end

Usage Guidelines

Use this command to return to the Exec mode.

exit

Exits the current mode and returns to the parent configuration mode.

Product

All

Privilege

Security Administrator, Administrator

Syntax Description

exit

Usage Guidelines

Use this command to return to the parent configuration mode.

mtp2-aerm-emergency-threshold

Configure the alignment error rate monitor (AERM) emergency threshold value. This command is only available for a lowspeed-narrowband link-type.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description **mtp2-aerm-emergency-threshold** *value*
default **mtp2-aerm-emergency-threshold**

default

Resets the parameter to the default value of 1.

value

value : Enter an integer from 1 to 50. Default: 1.

Usage Guidelines This command sets the emergency threshold for the MTP2 alignment error rate monitor.

Example

Set the emergency AERM threshold to 17:

```
mtp2-aerm-emergency-threshold 17
```

mtp2-aerm-normal-threshold

Configure the alignment error rate monitor (AERM) normal threshold value. This command is only available for a lowspeed-narrowband link-type.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp2-aerm-normal-threshold *value*
default mtp2-aerm-normal-threshold

default

Resets the parameter to the default value of 4.

value

value : Enter an integer from 4 to 100. Default: 4.

Usage Guidelines

This command sets the normal threshold for the MTP2 alignment error rate monitor.

Example

Set the normal AERM threshold to 55:

```
mtp2-aerm-normal-threshold 55
```

mtp2-eim-decrement

Configure the errored interval monitor (EIM) emergency decrement value. This command is only available for a highspeed-narrowband link-type.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp2-eim-decrement *value*
default mtp2-eim-decrement

default

Resets the parameter to the default value of 11.

value

value : Enter an integer from 1 to 63. Default: 11.

Usage Guidelines

This command sets the emergency decrement value for the EIM.

Example

Reset the EIM emergency decrement to 1:

```
default mtp2-eim-decrement
```

mtp2-eim-increment

Configure the errored interval monitor (EIM) emergency increment value. This command is only available for a highspeed-narrowband link-type.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

```
configure > ss7-routing-domain domain_id variant var_type > linkset id linkset_id > link id link_id
```

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
mtp2-eim-increment value
default mtp2-eim-increment
```

default

Resets the parameter to the default value of 198.

value

value : Enter an integer from 1 to 1023. Default: 198.

Usage Guidelines

This command sets the emergency increment value for the EIM.

Example

Set the EIM emergency increment to 2:

```
mtp2-eim-increment 2
```

mtp2-eim-threshold

Configure the errored interval monitor (EIM) emergency threshold value. This command is only available for a highspeed-narrowband link-type.

Product

SGSN

Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain <i>domain_id</i> variant <i>var_type</i> > linkset id <i>linkset_id</i> > link id <i>link_id</i> Entering the above command sequence results in the following prompt: <pre>[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#</pre>
Syntax Description	mtp2-eim-threshold <i>value</i> default mtp2-eim-threshold default Resets the parameter to the default value of 794. value <i>value</i> : Enter an integer from 1 to 65535. Default: 794.
Usage Guidelines	This command sets the emergency threshold value for the EIM. Example Set the EIM emergency threshold to 154: <pre>mtp2-eim-threshold 154</pre>

mtp2-error-correction

Configure the error correction method to be used. This command is only available for lowspeed or highspeed narrowband link-types.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain <i>domain_id</i> variant <i>var_type</i> > linkset id <i>linkset_id</i> > link id <i>link_id</i> Entering the above command sequence results in the following prompt: <pre>[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#</pre>
Syntax Description	mtp2-error-correction { basic preventive-cyclic-retransmission } default mtp2-error-correction default Resets the parameter to the default value.

basic

Basic error correction (BEC) is a positive / negative acknowledgement method that uses backwards retransmission. This method is best for links with less than 30 ms one-way propagation delays.

preventive-cyclic-retransmission

PCR is recommended for links with 125 ms, or higher, propagation delays.

Usage Guidelines

Set the method of MTP2 layer error correct to be used on the link.

Example

Set error correction for a link with 15 ms propagaion delay::

```
mtp2-error-correction basic
```

mtp2-lssu-len

This command sets the length of the link status signal unit (LSSU) which carries link status information used to manage link alignment and indicate the status of the signaling points to each other. This command is only available for lowspeed or highspeed narrowband link-types.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

```
configure > ss7-routing-domain domain_id variant var_type > linkset id linkset_id > link id link_id
```

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
mtp2-lssu-len #_octets
default mtp2-lssu-len
```

default

Using this keyword with the command resets the length to the default of 1 octet.

#_octets

Sets the number of octets for the length of the LSSU.

#_octets: Must be either 1 or 2.

Usage Guidelines

Use this command to define the maximum amount of link status information that is to be shared between signaling points.

Example

You can use the following command to set the LSSU length to 2 octets - the maximum length:

```
mtp2-lssu-len 2
```

mtp2-max-outstand-frames

This command sets the maximum number of outstanding packets to be sent by the link manager (linkmgr) - applicable for both high speed (HSL) and low speed (LSL) narrowband links.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain <i>domain_id</i> variant <i>var_type</i> > linkset id <i>linkset_id</i> > link id <i>link_id</i> Entering the above command sequence results in the following prompt: [local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#

Syntax Description **mtp2-max-outstand-frames** #_bytes
default mtp2-max-outstand-frames

default

Using this keyword with the command resets number of packets to the default of 7 bytes.

#_bytes

Sets the maximum number of packets sent by the linkmgr that can be allowed to be outstanding.

#_bytes: Must be an integer from 5 to 10.

Usage Guidelines

The linkmgr (MTP2) sends data at a higher rate, than the narrowband (NB) E1 link speed, when in congestion and performing retransmission. This can lead to more congestion leading to more time taken for the link to come out of congestion. If using a value of 10 during congestion, then linkmgr pumps data at a rate higher than 2.5 mbps. To avoid this problem, a lower value is usually considered optimal. This configuration holds good for both HSL and LSL.

Example

Use the following command to reset the default number of outstanding packets sent by the LinkMgr:

```
default mtp2-max-outstand-frames
```

Set the maximum number of outstanding packets the linkmgr can send to 6:

```
mtp2-max-outstand-frames 6
```

mtp2-suerm-threshold

Configure the signal unit error rate monitor (SUERM) threshold. This command is only available for lowspeed-narrowband link-types.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description **mtp2-suerm-threshold** *value*
default mtp2-suerm-threshold

default

Resets the parameter to the default value.

value

Defines the threshold for number of bad frames

value: Enter an integer from 64 to 1023. Default is 64.

Usage Guidelines Sets the threshold for link monitoring of bad frames.

Example

Set a new link monitoring bad frames (SEURM) threshold of 256:

```
mtp2-suerm-threshold 256
```

mtp3-discard-priority

Configure MTP3 message discard priority.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp3-discard-priority *priority*
default mtp3-discard-priority

default

Resets the priority to the default value.

priority

priority: must be an integer between 0 and 3.

Default is 0.

Usage Guidelines

Use this command to manage MTP3 messaging.

Example

```
mtp3-discard-priority 2
```

mtp3-max-slt-try

Configure maximum number of times to retry SLT (signaling link test).

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > ss7-routing-domain *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp3-max-slt-try *retries*
default mtp3-max-slt-try

default

Resets the number of retries to the default value.

retries

retries: must be an integer between 1 to 65535.

Default is 10.

Usage Guidelines Use this command to troubleshoot MTP3 link mismatch.

Example

```
mtp3-max-slt-try 35
```

mtp3-msg-priority

Configures the priority for sending MTP3 management messages.

Product SGSN

Privilege Security Administrator, Administrator

Command Modes Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

```
configure > ss7-routing-domain domain_id variant var_type > linkset id linkset_id > link id link_id
```

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description **mtp3-msg-priority** *priority*
default mtp3-msg-priority

default

Resets the number of priority to the default value.

priority

priority: must be an integer from 0 to 3.

Default: 0

Usage Guidelines Use this command to set the priority for sending MTP3 management messages.

Example

Use the following to set the message priority to 3:

```
mtp3-msg-priority 3
```

mtp3-msg-size

Configures the size of messages from layer 3 to layer 2.

Product SGSN

Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain <i>domain_id</i> variant <i>var_type</i> > linkset id <i>linkset_id</i> > link id <i>link_id</i> Entering the above command sequence results in the following prompt: [local] <i>host_name</i> (config-ss7-rd-linkset-linkset_id-link-link_id)#
Syntax Description	mtp3-msg-size <i>size</i> default mtp3-msg-size default Resets the the size to the default value which is 4096 (for q.2140) or 272 (for MTP2) size <i>size</i> : must be an integer from 1 to 272 for high-speed or low-speed narrowband SS7 links. <i>size</i> : must be an integer from 1 to 4096 for ATM broadband links.
Usage Guidelines	Use this command to set the maximum message size, in bytes.

Example

Use this command to set the MTP3 message size to 4096 bytes:

```
mtp3-msg-size 4096
```

mtp3-p1-qlen

Configure the size for the MTP3 p1 queue length.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain <i>domain_id</i> variant <i>var_type</i> > linkset id <i>linkset_id</i> > link id <i>link_id</i> Entering the above command sequence results in the following prompt: [local] <i>host_name</i> (config-ss7-rd-linkset-linkset_id-link-link_id)#
Syntax Description	mtp3-p1-qlen <i>size</i> default mtp3-p1-qlen

default

Resets the number of size of the priority 1 queue to the default value.

size

size: integer from 1 to 65535. Size should be less than MTP3 p2 qlen and p3 qlen.

Default: 1024

Usage Guidelines

Use this command to configure the queue length threshold for raising the congestion priority to level 1.

Example

Use this command to set the queue length priority to 128:

```
mtp3-p1-qlen 128
```

mtp3-p2-qlen

Configure the size of the priority 2 queue.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
mtp3-p2-qlen size  
default mtp3-p2-qlen
```

default

Resets the number of size of the priority 2 queue to the default value.

size

size: integer from 1 to 65535. Size should be less than MTP3 p3 qlen and greater than p1 qlen.

Default: 1024

Usage Guidelines

Use this command to configure the queue length threshold for raising the congestion priority to level 2.

Example

Use this command to set the queue length threshold to 256:

mtp3-p2-qlen 256

mtp3-p3-qlen

Configure the size of the priority 3 queue.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp3-p3-qlen *size*
default **mtp3-p3-qlen**

default

Resets the number of size of the priority 3 queue to the default value.

size

size: integer from 1 to 65535. Size should be greater than MTP3 p1 qlen and p2 qlen .

Default: 1024

Usage Guidelines

Use this command to configure the queue length threshold for raising the congestion priority to level 3.

Example

```
mtp3-p3-qlen 1024
```

mtp3-test-pattern

Configures the character string for the test message.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

mtp3-test-pattern *pattern*
default mtp3-test-pattern

default

Resets the pattern to the default value.

pattern

pattern: 1 to 15 alphanumeric characters.

Default: SGSN-ORIGINATED

Usage Guidelines

Use this command to define a test pattern string for the signalling link test match (SLTM).

Example

```
mtp3-test-pattern TEST1-HomeOffice
```

priority

Configures the MTP3 Link Priority.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

priority *pri_value*
no priority

no

Removes the priority configuration.

pri_value

pri_value: 0 represents highest priority and 15 represents the lowest priority.

Usage Guidelines

Use this command to configure the link priority within the MTP3 link set.

Example

```
priority 2
```

signaling-link-code

Configures the signaling link code (SLC).

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration configure > ss7-routing-domain domain_id variant var_type > linkset id linkset_id > link id link_id Entering the above command sequence results in the following prompt: <pre>[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#</pre>
Syntax Description	<p>signaling-link-code code no signaling-link-code</p> <p>no Removes the SLC configuration.</p> <p>code <i>code</i>: integer from 0 to 15.</p>
Usage Guidelines	Use this command to uniquely identify the signaling link to be used for MTP3 management messages.

Example

```
signaling-link-code 4
```

sscf-nni-n1

Configures the SSCF NNI N1. This command is only available for ATM-broadband link-types.

Product	SGSN
Privilege	Security Administrator, Administrator
Command Modes	Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

sscf-nni-n1 *value*
no sscf-nni-n1

default

Removes the sscf-nni-n1 configuration.

value

value: integer from 1 to 65535.

Default: 1000

Usage Guidelines

Use this command to identify the network-to-node interface (NNI) between the MTP3 and SSCOP layers.

Example

```
sscf-nni-n1 4064
```

sscop-max-cc

Configure the maximum value for the SSCOP connection control (CC) state variable. This command is only available for ATM-broadband link-types.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

sscop-max-cc *value*
no sscop-max-cc

default

Removes the sscop-max-cc configuration.

value

value: integer from 1 to 65535.

Default: 4

Usage Guidelines

Use this command as part of the configuration responsible for managing the SSCOP connection. This command sets the number of times retries.

Example

```
sscop-max-cc 256
```

sscop-max-pd

Configures the maximum acceptable value for the SSCOP state variable VT(PD). This command is only available for ATM-broadband link-types.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

```
configure > ss7-routing-domain domain_id variant var_type > linkset id linkset_id > link id link_id
```

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
sscop-max-pd value
no sscop-max-pd
```

default

Removes the **sscop-max-pd** configuration.

value

value: integer from 1 to 65535.

Default: 500

Usage Guidelines

Use this command to define the maximum number of data PDUs transmitted between POLL PDUs.

Example

```
sscop-max-pd 2500
```

sscop-max-stat

Configures the maximum number of elements included in a status PDU. This command is only available for ATM-broadband link-types.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

sscop-max-stat *value*
no sscop-max-stat

default

Removes the **sscop-max-stat** configuration.

value

value: integer from 3 to 65535. This parameter should be an odd integer greater than or equal to 3.

Default: 67

Usage Guidelines

Received in response to a POLL PDU, the STAT PDU includes information about the number of SD PDUs that have been received.

Example

```
sscop-max-stat 56000
```

timeout

This command enables configuration of an array of signaling and flow control timers - for MTP, SSCF, and SSCOP.

Product

SGSN

Privilege

Security Administrator, Administrator

Command Modes

Exec > Global Configuration > SS7 Routing Domain Configuration > Linkset Configuration > Link Configuration

configure > **ss7-routing-domain** *domain_id* **variant** *var_type* > **linkset id** *linkset_id* > **link id** *link_id*

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-ss7-rd-linkset-linkset_id-link-link_id)#
```

Syntax Description

```
[ no ] timeout timer timer_value
```

no

Adding **no** to the **timeout** command removes the timer configuration.

timer timer_value

Select the timer and enter a value from the range.

For timers having different ranges for highspeed and lowspeed links or for different variants, the appropriate ranges will be displayed based on the link-type configured.



Important

Currently, the China variant uses ITU values.

Timer	Link Type & Variant	Range of Times Granularity = 100ms	Default Time
mtp2-tmr-t1 Alignment ready timer	Highspeed; ITU	160..3500 (16 - 350 seconds)	3000 (300 seconds)
	Lowspeed; ITU	120 - 500 (12 - 50 seconds)	400 (40 seconds)
	Highspeed; ANSI	160 - 3500 (16 to 350 seconds)	1700 (170 seconds)
	Lowspeed; ANSI	120 - 500 (12 - 50 seconds)	130 (13 seconds)
mtp2-tmr-t2 Not aligned timer	Highspeed; ITU	50 - 1500 (5 - 150 seconds)	50 (5 seconds)
	Lowspeed; ITU	50 - 150 (5 - 15 seconds)	50 (5 seconds)
	Highspeed; ANSI	50 - 1500 (5 - 150 seconds)	230 (23 seconds)
	Lowspeed; ANSI	50 - 150 (5 - 15 seconds)	115 (11.5 seconds)
mtp2-tmr-t3 Aligned timer	Highspeed/Lowspeed; ITU	10 - 140 (1 - 14 seconds)	15 (1.5 seconds)
	Highspeed/Lowspeed; ANSI	10 - 140 (1 - 14 seconds)	115 (11.5 seconds)

Timer	Link Type & Variant	Range of Times Granularity = 100ms	Default Time
mtp2-tmr-t4e Emergency proving period timer	Highspeed; ITU	4 - 60 (400 milliseconds - 6 seconds)	5 (500 milliseconds)
	Lowspeed; ITU	4 - 6 (400 - 600 milliseconds)	5 (500 milliseconds)
	Highspeed; ANSI	4 - 60 (400 milliseconds - 6 seconds)	50 (5 seconds)
	Lowspeed; ANSI	4 - 6 (400 - 600 milliseconds)	6 (600 milliseconds)
mtp2-tmr-t4n Normal proving period timer Once set this timer can be reset but it can not be disabled.	Highspeed; ITU	30 - 700 (3 to 70 seconds)	3 (30 seconds)
	Lowspeed; ITU	20 - 95 (2 - 9.5 seconds)	82 (8.2 seconds)
	Highspeed; ANSI	30 - 700 (3 to 70 seconds)	3 (30 seconds)
	Lowspeed; ANSI	20 - 95 (2 - 9.5 seconds)	23 (2.3 seconds)
mtp2-tmr-t5 Sending status indication busy (SIB) timer	Highspeed/Lowspeed ITU/ANSI	1 - 2 (100 - 200 milliseconds)	1 (100 milliseconds)
mtp2-tmr-t6 Remote congestion timer	Highspeed/Lowspeed ITU/ANSI	10 - 60 (1 to 6 seconds)	30 (3 seconds)
mtp2-tmr-t7 Excessive delay of acknowledgement timer	Highspeed/Lowspeed ITU/ANSI	5 - 20 (500 milliseconds - 2 seconds)	10 (1 second)
mtp2-tmr-t8 Interval timer for error interval monitor timer	Highspeed ITU/ANSI	1 - 2 (100 - 200 milliseconds)	1 (100 milliseconds)
mtp3-tmr-t1 Delay to avoid mis-sequencing on changeover timer	Highspeed/Lowspeed ITU/ANSI	5 - 12 (500 - 1200 milliseconds)	5 (500 milliseconds)

Timer	Link Type & Variant	Range of Times Granularity = 100ms	Default Time
mtp3-tmr-t12 Waiting for uninhibit acknowledgement timer	Highspeed/Lowspeed ITU/ANSI	8 - 15 (800 - 1500 milliseconds)	8 (800 milliseconds)
mtp3-tmr-t13 Waiting for force uninhibit timer	Highspeed/Lowspeed ITU/ANSI	8 - 15 (800 - 1500 milliseconds)	8 (800 milliseconds)
mtp3-tmr-t14 Waiting for inhibition acknowledgement timer	Highspeed/Lowspeed ITU/ANSI	20 - 30 (2000 - 3000 milliseconds)	20 (2000 milliseconds)
mtp3-tmr-t17 Delay to avoid oscillation of initial alignment failure and link restart	Highspeed/Lowspeed ITU/ANSI	8 - 15 (800 - 1500 milliseconds)	8 (800 milliseconds)
mtp3-tmr-t2 Waiting for changeover acknowledgement	Highspeed/Lowspeed ITU/ANSI	7 - 20 (700 - 2000 milliseconds)	7 (700 milliseconds)
mtp3-tmr-t22 Local inhibit test timer	Highspeed/Lowspeed ITU/ANSI	1800 - 3000 (180 - 300 seconds)	1800 (180 seconds)
mtp3-tmr-t23 Remote inhibit test timer	Highspeed/Lowspeed ITU/ANSI	1800 - 3000 (180 - 300 seconds)	1800 (180 seconds)
mtp3-tmr-t24 Stabilising timer after removal of local processor outage, used in LPO latching to RPO (national option)	Highspeed/Lowspeed ITU/ANSI	5 - 15 (500 - 1500 milliseconds)	5 (500 milliseconds)
mtp3-tmr-t3 Time controlled diversion-delay to avoid mis-sequencing on changeback	Highspeed/Lowspeed ITU/ANSI	5 - 12 (500 - 1200 milliseconds)	5 (500 milliseconds)
mtp3-tmr-t31 BSN requested timer	Highspeed/Lowspeed ITU/ANSI	50 - 100 (5 to 10 seconds)	50 (5 seconds)

Timer	Link Type & Variant	Range of Times Granularity = 100ms	Default Time
mtp3-tmr-t32 SLT timer	Highspeed/Lowspeed ITU/ANSI	40 - 120 (4 - 12 seconds)	100 (10 seconds)
mtp3-tmr-t33 Connecting timer	Highspeed/Lowspeed ITU/ANSI	50 - 100 (5 to 10 seconds)	50 (5 seconds)
mtp3-tmr-t34 Periodic signalling link test timer	Highspeed/Lowspeed ITU/ANSI	300 - 900 (30 to 90 seconds)	600 (60 seconds)
mtp3-tmr-t4 Waiting for changeback acknowledgement (first attempt)	Highspeed/Lowspeed ITU/ANSI	5 - 12 (500 to 1200 milliseconds)	5 (500 milliseconds)
mtp3-tmr-t5 Waiting for changeback acknowledgement (second attempt)	Highspeed/Lowspeed ITU/ANSI	5 - 12 (500 to 1200 milliseconds)	5 (500 milliseconds)
mtp3-tmr-t7 Waiting for signalling data link connection acknowledgement	Highspeed/Lowspeed ITU/ANSI	10 - 20 (1000 - 2000 milliseconds)	10 (1000 milliseconds)

Timer	Link type & Variant	Range of Times	Default Time
sscf-nni-tmr-t1	ATM Broadband ITU/ANSI	1 - 65535 (10 - 655350 milliseconds) Granularity = 10 ms	500 (5 seconds)
sscf-nni-tmr-t2	ATM Broadband ITU/ANSI	1 - 65535 (10 - 655350 milliseconds) Granularity = 10 ms	3000 (30 seconds)
sscf-nni-tmr-t3	ATM Broadband ITU/ANSI	1 - 65535 (10 - 655350 milliseconds) Granularity = 10 ms	1 (10 milliseconds)
sscop-tmr-cc SSCOP CC timer	ATM Broadband ITU/ANSI	1 - 65535 (100 - 6553500 milliseconds) Granularity = 100 ms	2 (200 milliseconds)

Timer	Link type & Variant	Range of Times	Default Time
sscop-tmr-idle SSCOP idle timer (UNI 3.1 only)	ATM Broadband ITU/ANSI	1 - 65535 (100 - 6553500 milliseconds) Granularity = 100 ms	1 (100 milliseconds)
sscop-tmr-keep-alive SSCOP keep alive timer For stability purposes, tmrKeepAlive >= tmrPoll and tmrKeepAlive < tmrNoResponse.	ATM Broadband ITU/ANSI	1 - 65535 (100 - 6553500 milliseconds) Granularity = 100 ms	1 (100 milliseconds)
sscop-tmr-no-rsp SSCOP no response timer For stability purposes, tmrNoResponse > tmrKeepAlive.	ATM Broadband ITU/ANSI	1 - 65535 (100 - 6553500 milliseconds) Granularity = 100 ms	15 (1.5 seconds)
sscop-tmr-poll SSCOP poll timer For stability purposes, tmrPoll <= tmrKeepAlive.	ATM Broadband ITU/ANSI	1 - 65535 (100 - 6553500 milliseconds) Granularity = 100 ms	1 (100 milliseconds)

Usage Guidelines

For a single link and specified link-type (highspeed or lowspeed), this command sets the timer values listed above. The SS7 variant is determined when the SS7 routing domain is first defined from the Global Configuration mode.

Repeat the **timeout** command (one timer and value per entry) as needed to configure all required timers.



Important

Currently, the China variant uses the same timers, values, and defaults as the ITU variant.

Example

```
timeout timer timer_value
```

■ timeout