



# PVC Configuration Mode Commands

---

## Command Modes

The Permanent Virtual Connection (PVC) configuration mode commands bind IP interfaces or SS7-Frame Relay links a PVC as well as configure PVC operational parameters for a specific port.

Exec > Global Configuration > ATM Port Configuration > PVC Configuration

**configure > port atm slot\_number/port\_number > pvc vpi vpi\_number vci vci\_number**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-port-slot_number/port_number-pvc-pvc_number/vci_number) #
```



---

**Important**

The commands or keywords/variables that are available are dependent on platform type, version, and installed license(s).



---

**Important**

For information on common commands available in this configuration mode, refer to the [Common Commands](#) chapter.

- [bind, on page 1](#)
- [encapsulation aal5, on page 2](#)
- [shaping, on page 3](#)
- [shutdown, on page 4](#)

## bind

This command binds an IP interface or an SS7 link to the PVC.



---

**Important**

Prior to attempting the binding, the interface and context or the SS7 routing information and link must have been configured.

---

**Product**

SGSN

---

**Privilege**

Security Administrator, Administrator

encapsulation aal5

<b>Command Modes</b>	Exec > Global Configuration > ATM Port Configuration > PVC Configuration <b>configure &gt; port atm slot_number/port_number &gt; pvc vpi vpi_number vci vci_number</b>
	Entering the above command sequence results in the following prompt: [local]host_name(config-port-slot_number/port_number-pvc-pvc_number/vci_number) #
<b>Syntax Description</b>	<b>[ no ] bind { interface interface_name context_name   link ss7-routing-domain rd_id linkset-id id link-id id }</b>
	<b>no</b> Removes the binding from the configuration.
	<b>interface_name</b> Defines the name of the virtual interface to be bound to the PVC. <i>interface_name</i> : Must be a unique string consisting of 1 to 79 alphanumeric characters.
	<b>context_name</b> Specifies the name of the context to be bound to the virtual interface. <i>context_name</i> : Must be a unique string consisting of 1 to 79 alphanumeric characters.
	<b>ss7-routing-domain rd_id</b> Identifies a specific SS7 routing domain. <i>rd_id</i> must be an integer from 1 to 12
	<b>linkset-id id</b> Identifies a specific linkset within the routing domain. <i>id</i> : must be an integer from 1 to 33
	<b>link-id id</b> Identifies a specific link within the linkset. <i>id</i> : must be an integer value 1 - 16

**Usage Guidelines** Use this command to bind the PVC to an interface or a specific link.**Example**

Use a command similar to the following to bind a PVC to a link ID #2:

**bind ss7-routing-domain 1 linkset-id 23 link-id 2**

## encapsulation aal5

Specify the data encapsulation type for the ATM adaptation layer 5 (AAL5) frames for the PVC.

**Product** SGSN**Privilege** Security Administrator, Administrator

**Command Modes**

Exec > Global Configuration > ATM Port Configuration > PVC Configuration

**configure > port atm slot\_number/port\_number > pvc vpi vpi\_number vci vci\_number**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-port-slot_number/port_number-pvc-pvc_number/vci_number) #
```

**Syntax Description**

**encapsulation aal5 { llc-snap | vc-mux }**

**llc-snap**

Frames protocol is identified in the AAL5 using logical link control (LLC) encapsulation.

**vc-mux**

Frames are not encapsulated and use virtual circuit multiplexing (VC-MUX) to identify the protocols used for the AAL5 frames.

**Usage Guidelines**

Use this command to identify the protocol type for the circuit.

**Example**

```
encapsulation aal5 vc-mux
```

# shaping

Specify the type of traffic shaping (rates) for this PVC.

**Product**

SGSN

**Privilege**

Security Administrator, Administrator

**Command Modes**

Exec > Global Configuration > ATM Port Configuration > PVC Configuration

**configure > port atm slot\_number/port\_number > pvc vpi vpi\_number vci vci\_number**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-port-slot_number/port_number-pvc-pvc_number/vci_number) #
```

**Syntax Description**

**shaping { cbr pcr prc\_num | ubr pcr prc\_num | ubrt+ pcr prc\_num mrc mrc\_num | vbr pcr prc\_num scr src\_num mbs mbs\_num }**

**cbr**

Constant bit rate

pcr - peak cell rate = cells per second

*prc\_num*: Must be an integer from 75 to 1412830

**shutdown****ubr**

Unspecified Bit Rate

pcr - peak cell rate = cells per second

*prc\_num*: Must be an integer from 75 to 1412830**ubr+**

Unspecified Bit Rate with Minimum Cell Rate.

The PCR and MCR values should be set to maintain the following relationship: PCR &gt;= (MCR + minRate), where the current recommend minRate is 75.

pcr - peak cell rate = cells per second

*prc\_num*: Must be an integer from 75 to 1412830

mcr - minimum cell rate

*mrc\_num*: Must be an integer from 75 to 1412830**vbr**

Variable Bit Rate, NRT (not real time) type.

The PCR and MCR values should be set to maintain the following relationship: PCR &gt;= (MCR + minRate), where the current recommend minRate is 75.

pcr - peak cell rate = cells per second

*prc\_num* must be an integer from 75 to 1412830

scr - sustained cell rate

*src\_num* must be an integer from 75 to 1412830

mbs - maximum burst size

*mbs\_num* must be an integer from 75 to 1412830**Usage Guidelines**

Use this command to configure the shaping for egress traffic on this PVC.

**Example****shaping cbr pcr 56000****shutdown**

Disables/enables traffic over the current VLAN.

**Product** SGSN**Privilege** Security Administrator, Administrator**Command Modes** Exec > Global Configuration > ATM Port Configuration > PVC Configuration

**configure > port atm slot\_number/port\_number > pvc vpi vpi\_number vci vci\_number**

Entering the above command sequence results in the following prompt:

```
[local]host_name(config-port-slot_number/port_number-pvc-pvc_number/vci_number) #
```

---

**Syntax Description**

**shutdown**  
**no shutdown**

**no**

Enables the VLAN. When omitted the VLAN is non-functional.

---

**Usage Guidelines**

Enables/ Disables specified VLAN.

This command is necessary to bring a VLAN into service by enabling it via the **no** keyword.

**Example**

To disable a VLAN from sending or receiving network traffic use the following command:

**shutdown**

To enable a VLAN use the following command:

**no shutdown**

shutdown