



CPS Commands



Note If you want to save the output of any command on any of the CPS VMs, then the output should be redirected to a file.

- [about.sh](#), on page 2
- [adduser.sh](#), on page 2
- [auditrpm.sh](#), on page 3
- [build_all.sh](#), on page 3
- [build_etc.sh](#), on page 5
- [build_set.sh](#), on page 5
- [capture_env.sh](#), on page 6
- [change_passwd.sh](#), on page 7
- [cleanup_license.sh](#), on page 7
- [component_alarm_reports.py](#), on page 7
- [copytoall.sh](#), on page 8
- [diagnostics.sh](#), on page 9
- [dump_utility.py](#), on page 12
- [list_installed_features.sh](#), on page 16
- [reinit.sh](#), on page 18
- [restartall.sh](#), on page 18
- [restartqns.sh](#), on page 19
- [runonall.sh](#), on page 19
- [service](#), on page 20
- [session_cache_ops.sh](#), on page 20
- [set_priority.sh](#), on page 24
- [startall.sh](#), on page 26
- [startqns.sh](#), on page 26
- [statusall.sh](#), on page 27
- [stopall.sh](#), on page 28
- [stopqns.sh](#), on page 29
- [summaryall.sh](#), on page 29
- [sync_times.sh](#), on page 43
- [syncconfig.sh](#), on page 43

- [terminatesessions](#), on page 44
- [top_qps.sh](#), on page 46
- [vm-init.sh](#), on page 48

about.sh

This command displays:

- Core version
- Patch installed
- ISO version
- Feature version
- URLs to the various interfaces
- APIs for the deployment

Syntax

```
/var/qps/bin/diag/about.sh [-h]
```

Executable on VMs

- Cluster Manager
- pcrfclient01/02

adduser.sh

This utility adds a new user to the specified nodes that are part of the CPS deployment. These accounts will be provisioned without shell access and, as such, they're only useful for authenticating against the various web-based GUIs used to administrate CPS.

The hosts that get provisioned with these new accounts can be selected using the 'node-regex' option. The default regular expression used by the script is:

```
node-regex ::= ^(pcrfclient|qns|lb[0-9]+|sessionmgr)
```

Syntax

```
/var/qps/bin/support/adduser.sh [-h] [node-regex]
```

When prompted for the user's group, set 'qns-svn' for read-write permissions or 'qns-ro' for read-only permissions.

To add a user with 'read/write' access to Control Center, their group should be 'qns'.

- To check if a user already exists, login in as root and enter 'su <username>'.
• To check a user's 'groups', enter 'groups <username>'.

Executable on VMs

All

Example

```
[root@host ~]# /var/qps/bin/support/adduser.sh
Enter username: username
Enter group for the user: groupname
Enter password: password
Re-enter password: password
The above example adds username to all the VMs in the cluster.
```

auditrpms.sh

This script runs in background on all VMs except Cluster Manager. This script/daemon should be always running and is monitored via monit. No intervention from end user is required. Corresponding logs are generated at individual nodes in `/var/log/broadhop/audit/audit_rpms.log`.



Note All successful attempts i.e. installation or removal are tracked in this file. In case package is upgraded there would be two entries seen in log file, one for removal of old package and one for installation of new package.

Executable on VMs

On all VMs except Cluster Manager

Example

```
[root@lb01 ~]# monsum | grep auditrpms
Process 'auditrpms.sh' Running
```

build_all.sh

This command is executed from Cluster Manager to rebuild CPS package.

Syntax

- `/var/qps/install/current/scripts/build_all.sh`
- `/var/qps/install/current/scripts/build/build_all.sh`

Executable on VMs

Cluster Manager

Example

```
[root@host ~]# /var/qps/install/current/scripts/build_all.sh
Building /etc/broadhop...
Copying to /var/qps/images/etc.tar.gz...
```

```

Creating MD5 Checksum...
Copying /etc/puppet to /var/qps/images/puppet.tar.gz...
Creating MD5 Checksum...
Copying Policy Builder configuration (/var/qps/current_config/pb_config) to
/var/qps/images/svn.tar.gz...
Creating MD5 Checksum...
Updating tar from: /var/qps/env_config/ to /var/www/html/images/
Creating MD5 Checksum...
Building /var/qps/bin...
Copying /var/qps/bin to /var/qps/images/scripts_bin.tar.gz...
Creating MD5 Checksum...
Building images...
Building image: /var/qps/images/controlcenter.tar.gz
Installing from:
    file:///var/qps/.tmp/release
Installing features:
    com.broadhop.controlcenter.feature.feature.group
    com.broadhop.faultmanagement.service.feature.feature.group
    com.broadhop.infrastructure.feature.feature.group
    com.broadhop.server.runtime.product
    com.broadhop.snmp.feature.feature.group
Creating MD5 Checksum... /var/qps/images/controlcenter.tar.gz.md5chksum
Building image: /var/qps/images/diameter_endpoint.tar.gz
Installing from:
    file:///var/qps/.tmp/release
Installing features:
    com.broadhop.diameter2.service.feature.feature.group
    com.broadhop.server.runtime.product
    com.broadhop.snmp.feature.feature.group
Creating MD5 Checksum... /var/qps/images/diameter_endpoint.tar.gz.md5chksum
Building image: /var/qps/images/iomanager01.tar.gz
Installing from:
    file:///var/qps/.tmp/release
Installing features:
    com.broadhop.iomanager.feature.feature.group
    com.broadhop.notifications.service.feature.feature.group
    com.broadhop.server.runtime.product
    com.broadhop.snmp.feature.feature.group
Creating MD5 Checksum... /var/qps/images/iomanager01.tar.gz.md5chksum
Building image: /var/qps/images/iomanager02.tar.gz
Installing from:
    file:///var/qps/.tmp/release
Installing features:
    com.broadhop.iomanager.feature.feature.group
    com.broadhop.notifications.service.feature.feature.group
    com.broadhop.server.runtime.product
    com.broadhop.snmp.feature.feature.group
Creating MD5 Checksum... /var/qps/images/iomanager02.tar.gz.md5chksum
Building image: /var/qps/images/pb.tar.gz
Installing from:
    file:///var/qps/.tmp/release
Installing features:
    com.broadhop.client.feature.audit.feature.group
    com.broadhop.client.feature.balance.feature.group
    com.broadhop.client.feature.custrefdata.feature.group
    com.broadhop.client.feature.diameter2.feature.group
    com.broadhop.client.feature.notifications.feature.group
    com.broadhop.client.feature.spr.feature.group
    com.broadhop.client.feature.unifiedapi.feature.group
    com.broadhop.client.feature.vouchers.feature.group
    com.broadhop.client.feature.ws.feature.group
    com.broadhop.client.product
Creating MD5 Checksum... /var/qps/images/pb.tar.gz.md5chksum
Building image: /var/qps/images/pcrf.tar.gz

```

```

Installing from:
  file:///var/qps/.tmp/release
Installing features:
  com.broadhop.audit.service.feature.feature.group
  com.broadhop.balance.service.feature.feature.group
  com.broadhop.balance.spr.feature.feature.group
  com.broadhop.custrefdata.service.feature.feature.group
  com.broadhop.diameter2.local.feature.feature.group
  com.broadhop.externaldatacache.memcache.feature.feature.group
  com.broadhop.notifications.local.feature.feature.group
  com.broadhop.policy.feature.feature.group
  com.broadhop.server.runtime.product
  com.broadhop.snmp.feature.feature.group
  com.broadhop.spr.dao.mongo.feature.feature.group
  com.broadhop.spr.feature.feature.group
  com.broadhop.ui.controlcenter.feature.feature.group
  com.broadhop.unifiedapi.interface.feature.feature.group
  com.broadhop.unifiedapi.ws.service.feature.feature.group
  com.broadhop.vouchers.service.feature.feature.group
  com.broadhop.ws.service.feature.feature.group
Creating MD5 Checksum... /var/qps/images/pcrf.tar.gz.md5chksum
Copying portal default database to /var/qps/images/portal_dump.tar.gz
Creating MD5 Checksum for portal dump...
Copying portal to /var/qps/images/portal.tar.gz
Creating MD5 Checksum for portal.tar.gz...
Copying wispr.war to /var/qps/images/wispr.war
Output images to /var/qps/images/

```

build_etc.sh

This command is executed from Cluster Manager to rebuild etc.tar.gz in /etc/broadhop/ directory.

Syntax

```
/var/qps/install/current/scripts/build/build_etc.sh
```

Executable on VMs

Cluster Manager

Example

```

[root@host /]# /var/qps/install/current/scripts/build/build_etc.sh
Building /etc/broadhop...
Copying to /var/qps/images/etc.tar.gz...
Creating MD5 Checksum...

```

build_set.sh

This command is used to rebuild replica sets. This command is normally only run the first time the environment starts, but can be used if CPS databases must be rebuilt.

Syntax

```
/var/qps/bin/support/mongo/build_set.sh [--help]
```

Executable on VMs

All

Example

To create replica-sets for SPR:

```
[root@host /]# /var/qps/bin/support/mongo/build_set.sh --spr --create
Starting Replica-Set Creation
Please select your choice: replica sets sharded (1) or non-sharded (2):
2
```

capture_env.sh

This command collects most of the debug logs to debug an issue.

Syntax

```
/var/qps/bin/support/env/capture_env.sh
```

Executable on VMs

pcrfclient01/02

Output

This command provides the following information to collect logs:

- -h|--help: Show usage
- -q|--qns: For capturing qns logs (default is to skip qns logs)
- -t|--trap: For capturing trap logs (default is to skip trap logs)
- -m|--mongo: For capturing mongo logs (default is to skip mongo logs)
- -v|--var-log: For capturing /var/log/messages (default is to skip the log)
- -a|--age: Should be followed by maximum age of log based on last modification time (defaults to 1 day)
- -n|--host: Should be followed by common separated list of hostnames for capturing logs (defaults to all hosts)

Example

```
[root@host /]# /var/qps/bin/support/env/capture_env.sh
Creating archive of QPS environment information...
-----
Capturing /etc/broadhop...
Capturing logs...
Capturing Policy Builder data...
Capturing installed software versions...
```

change_passwd.sh

Change the Control Center user's (Linux user) password on Cluster Manager VM or OAM (pcrfclient) VM.

Syntax

```
/var/qps/bin/support/change_passwd.sh [-h]
```

Executable on VMs

All

Example

```
Enter username whose password needs to be changed: root
Enter new password:
Re-enter new password:

Done.
Disconnecting from pcrfclient02... done.
```



Note It is recommended not to use \$ character in the password.

cleanup_license.sh

Cleans up the records related to license in the licensedfeats collection in the sharding database. This command must be run as root user when license file is updated on the OAM (pcrfclient) machine.

Syntax

```
/var/qps/bin/support/mongo/cleanup_license.sh [-h]
```

Executable on VMs

- Cluster Manager
- pcrfclient01/02

component_alarm_reports.py

This command is used to store or retrieve the open/active component alarms in CPS.

- For clear alarms, it removes the alarms matching the clear alarm.
- For active alarms, it clears old alarms if any and adds the latest alarm.

Syntax

```
component_alarm_reports.py -h
usage: component_alarm_reports.py [-h] --action {update,report}
                                   [--eventhost EVENTHOST] [--date DATE]
                                   [--name NAME] [--facility FACILITY]
                                   [--severity SEVERITY] [--info INFO]
```

CPS Update/Report Component Alarm(s) to/from Mongo DB

optional arguments:

```
-h, --help            show this help message and exit
--action {update,report}, -a {update,report}
                    Action value update : Update an alarm. report : Report
                    active alarms
--eventhost EVENTHOST, -e EVENTHOST
                    Event Host Name
--date DATE, -d DATE  Date of event
--name NAME, -n NAME  Name of alarm
--facility FACILITY, -f FACILITY
                    Facility of alarm
--severity SEVERITY, -s SEVERITY
                    Severity of alarm
--info INFO, -i INFO  Info of alarm
```



Attention The `--action update` parameter is for Cisco Internal Use Only.

Path:

On Cluster Manager: `/var/qps/install/current/scripts/modules/component_alarm_reports.py`

On pcrfclient and policy director VMs:

`/var/qps/bin/install/current/scripts/modules/component_alarm_reports.py`

Executable on VMs

Cluster Manager, Policy Director and OAM (pcrfclient) nodes

Examples

To retrieve the active alarms:

```
component_alarm_reports.py -a report
event_host=lb02 name=ProcessDown severity=critical facility=operatingsystem
date=2017-22-11,10:13:49,310329511,+00:00 info=corosync process is down
```

copytoall.sh

Prior to 7.0.5 release, in order to propagate the changes done in Cluster Manager, user used to execute `reinit.sh` which in turn triggers each CPS VM to download and install the updated VM images from the Cluster Manager and it time consuming process.

In CPS 7.0.5 and higher releases, if minor changes are made to any file in Cluster Manager, instead of executing `reinit.sh` script, use this command to synchronize the modified files from Cluster Manager to all other VMs.

Syntax

```
copytoall.sh
```

Executable on VMs

Cluster Manager



Note In case executing `copytoall.sh` command from `qns-admin`, prefix `sudo` before the command.

Example

1. If the user updated `/etc/broadhop/logback.xml` file in Cluster Manager.
2. Build etc directory on each cluster by executing `build_all.sh` from Cluster Manager to rebuild CPS package script.

```
/var/qps/install/current/scripts/build_all.sh
```

3. Execute the following command to copy the file:

```
SSHUSER_PREFERROOT=true copytoall.sh /etc/broadhop/logback.xml /etc/broadhop/logback.xml
```

diagnostics.sh

Runs a set of diagnostics and displays the current state of the system. If any components are not running, red failure messages are displayed.



Note RADIUS-based policy control is no longer supported in CPS 14.0.0 and later releases as 3GPP Gx Diameter interface has become the industry-standard policy control interface.

Syntax

```
/var/qps/bin/diag/diagnostics.sh -h
Usage: /var/qps/bin/diag/diagnostics.sh [options]
This script runs checks (i.e. diagnostics) against the various access, monitoring, and
configuration points of a running CPS system.
In HA/GR environments, the script always does a ping check for all VMs prior to any other
checks and adds any that fail the ping test to the IGNORED_HOSTS variable. This helps reduce
the possibility for script function errors.
NOTE: See /var/qps/bin/diag/diagnostics.ini to disable certain checks for the HA/GR env
persistently. The use of a flag will override the diagnostics.ini value.
Examples:
    /var/qps/bin/diag/diagnostics.sh -q
    /var/qps/bin/diag/diagnostics.sh --basic_ports --clock_skew -v
--ignored_hosts='portal01,portal02'
```

Options:

```
--basic_ports : Run basic port checks
    For AIO: 80, 11211, 27017, 27749, 7070, 8080, 8090, 8182, 9091, 9092
    For HA/GR: 80, 11211, 7070, 8080, 8081, 8090, 8182, 9091, 9092, and Mongo DB ports
based on /etc/broadhop/mongoConfig.cfg
```

```

--clock_skew : Check clock skew between lb01 and all vms (Multi-Node Environment only)
--diskspace : Check diskspace
--get_active_alarms : Get the active alarms in the CPS

--get_replica_status : Get the status of the replica-sets present in environment.
(Multi-Node Environment only)
--get_shard_health : Get the status of the sharded database information present in
environment. (Multi-Node Environment only)
--get_sharding_status : Get the status of the sharding information present in environment.
(Multi-Node Environment only)

--get_peer_status: Get the diameter peers present in the environment.
--get_sharded_replica_status : Get the status of the shards present in environment.
(Multi-Node Environment only)
--ha_proxy : Connect to HAProxy to check operation and performance statistics, and ports
(Multi-Node Environment only)
    http://lbvip01:5540/haproxy?stats
    http://lbvip01:5540/haproxy-diam?stats
--help -h : Help - displays this help
--hostnames : Check hostnames are valid (no underscores, resolvable, in
/etc/broadhop/servers) (AIO only)
--ignored_hosts : Ignore the comma separated list of hosts. For example
--ignored_hosts='portal01,portal02'
    Default is 'portal01,portal02,portallb01,portallb02' (Multi-Node Environment only)
--ping_check : Check ping status for all VM

--lwr_diagnostics : Retrieve diagnostics from CPS LWR kafka processes
--qns_diagnostics : Retrieve diagnostics from CPS java processes
--qns_login : Check qns user passwordless login
--quiet -q : Quiet output - display only failed diagnostics
--radius : Run radius specific checks
--redis : Run redis specific checks
--whisper : Run whisper specific checks
--aido : Run Aido specific checks
--svn : Check svn sync status between pcrfclient01 & pcrfclient02 (Multi-Node Environment
only)
--tacacs : Check Tacacs server reachability
--swapspace : Check swap space
--verbose -v : Verbose output - display *all* diagnostics (by default, some are grouped
for readability)
--virtual_ips : Ensure Virtual IP Addresses are operational (Multi-Node Environment
only)
--vm_allocation : Ensure VM Memory and CPUs have been allocated according to
recommendations

```

The test for swap memory usage must have the following criteria :

- The test passes if the swap space used is less than 200 MB.
- The script issues a warning if the swap space used is between 200 MB and 1000 MB.
- The status fails if the swap memory used exceeds 1000 MB.

Executable on VMs

Cluster Manager and OAM (pcrfclient) nodes

Example

```

[root@pcrfclient01 ~]# diagnostics.sh
QNS Diagnostics
Checking basic ports (80, 7070, 27017, 27717-27720, 27749, 8080, 9091)...[PASS]
Checking qns passwordless logins on all boxes...[PASS]

```

```

Validating hostnames...[PASS]
Checking disk space for all VMs...[PASS]
Checking swap space for all VMs...[PASS]
Checking for clock skew...[PASS]
Retrieving QNS diagnostics from qns01:9045...[PASS]
Retrieving QNS diagnostics from qns02:9045...[PASS]
Checking HAProxy status...[PASS]
Checking VM CPU and memory allocation for all VMs...[PASS]
Checking Virtual IPs are up...[PASS]
[root@pcrfclient01 ~]#

```

List of Active Alarms

To get the list of active alarms, execute the `diagnostics.sh --get_active_alarms` command. Here is a sample output:

```

#diagnostics.sh --get_active_alarms

CPS Diagnostics HA Multi-Node Environment
-----
Active Application Alarm Status
-----
id=1000 sub_id=3001 event_host=lb02 status=down date=2017-11-22,
10:47:34,051+0000 msg="3001:Host: site-host-gx Realm: site-gx-client.com is down"
id=1000 sub_id=3001 event_host=lb02 status=down date=2017-11-22,
10:47:34,048+0000 msg="3001:Host: site-host-sd Realm: site-sd-client.com is down"
id=1000 sub_id=3001 event_host=lb01 status=down date=2017-11-22,
10:45:17,927+0000 msg="3001:Host: site-server Realm: site-server.com is down"
id=1000 sub_id=3001 event_host=lb02 status=down date=2017-11-22,
10:47:34,091+0000 msg="3001:Host: site-host-rx Realm: site-rx-client.com is down"
id=1000 sub_id=3002 event_host=lb02 status=down date=2017-11-22,
10:47:34,111+0000 msg="3002:Realm: site-server.com:applicationId: 7:all peers are down"
Active Component Alarm Status
-----
event_host=lb02 name=ProcessDown severity=critical facility=operatingsystem
date=2017-22-11,10:13:49,310329511,+00:00 info=corosync process is down

```



Attention

- Due to the limitation of architecture of the CPS SNMP implementation, if the SNMP daemon or policy server (QNS) process on pcrfclient VM restarts, there can be gap between active alarms displayed by the `diagnostics.sh` and active alarms in NMS.
- The date printed for application alarm status is when the alarm was seen at pcrfclient VM. The time for the alarm at NMS is the time before the alarm is received from Policy Director (LB) VM. So there can be a difference in the dates for the same alarm reported in `diagnostics.sh` and in NMS.

The following table list the type of SNMP alarms:

Table 1: IDs - Type of SNMP Alarms

Alarm ID	Type
1000	Application Alarm
7100	Database Alarm
7200	Failover Alarm

Alarm ID	Type
7300	Process Alarm
7400	VM Alarm
7700	GR Alarm

For more information on SNMP alarms, refer to *CPS SNMP, Alarms and Clearing Procedures Guide*.

Sample Output of --get_sharding_status

```

diagnostics.sh --get_sharding_status
CPS Diagnostics HA Multi-Node Environment
-----
|-----|
|                                     SHARDING STATUS INFORMATION
| Date : 2019-01-08 01:01:05          |
|-----|
|
| Shard Id   Mongo DB                               State   Backup DB   Removed   Session
| Count
|
| 1          sessionmgr01:27717/session_cache      online  false       false     0
|
| Rebalance Status: Rebalanced
|
|-----|

```

dump_utility.py

This collection utility is used to collect standard information from the CPS system in case of issues (system, application, database). This utility collects such information from VM, depending on type of information and VMs selected in the input.

This utility can be executed from anywhere from the terminal. Logs are printed on terminal and written to a log file: `/var/tmp/dumputility-<date_time_when_executed>.log`.



Important Warning messages related to the files that does not exist in the system will not be displayed on the terminal but will be logged only to the log file (`/var/tmp/dumputility-<date_time_when_executed>.log`).



Caution Running the dump utility can be CPU intensive.



Important The dump utility should be run from the Cluster Manager wherever possible.

The following types of information can be collected:

- **Common Information:** This information is common for all type of issues. Information is collected from percliient01 VM. If percliient01 is down, information is collected from percliient02 VM. If both VMs are down, information is collected from Cluster Manager VM. The following information can be fetched:
 - `about.sh` output
 - `diagnostics.sh` output
 - `list_installed_features.sh` output
 - Facter output
 - Consolidated logs
 - Bulkstats files
 - SVN dump from PB config

- **System Information:** This information is useful in troubleshooting system related issues. The following information can be fetched:
 - `sysctl -a` output
 - Information about processes running
 - Firewall configuration
 - Netstat statistics
 - Complete lsof output
 - Total number of open files
 - `ifconfig` output
 - Routing table information
 - Disk usage
 - Monit status
 - Monit summary
 - System logs
 - Sar logs
 - Dmesg logs
 - Secure logs
 - Yum logs
 - Whisper logs
 - Puppet logs

- **Application Information:** This information is useful in troubleshooting application-related issues. The following information can be fetched:

- Contents of `/etc/broadhop` directory
 - `/var/log/broadhop` logs
 - monit status
 - monit summary
- **Database Information:** This information is useful in troubleshooting database related issues. The following information can be fetched:
- MongoDB logs
 - Mongostat output
 - `rs.status()` output
 - `rs.conf()` output
 - `/var/qps/bin/support/mongo/session_cache_ops.sh -count` output
 - `top_qps.sh` output for 10 seconds
 - `mongotop` output for 3 seconds
- **OAM (PCRFCLIENT) Specific Data:** The following information can be fetched from OAM (pcrfclient) VMs:
- carbon logs
 - httpd logs
 - `pcs resource show` output
- **Policy Director (Ib) Specific Data:** The following information can be fetched from policy director (load balancer) VMs:
- SNMP trap logs
 - HAproxy logs
 - `pcs resource show` output
- **Policy Server (QNS) Specific Data:** The following information can be fetched from policy server (QNS) VMs:
- Thread level CPU/memory usage of java process
 - `jstack` output of java process
 - Policy Server (QNS) logs
 - Policy Server service logs

Syntax

`dump_utility.py`

The following options are supported:

- `-v, --vm-type`: Specifies type of VM or single VM name from which information has to be fetched. Multiple VMs are separated by colon. For example, `--vm-type qns:sessionmgr01`.
- `-i, --info-type`: Specifies type of information to be collected. Possible values are application, db, system, vm_specific. Multiple values are separated by colon. For example, `--info-type application:system`.
- `-o, --output-file-name`: Name of the tar file to store fetched information.
- `-h, --help`: Displays help.

Executable on VMs

- Cluster Manager
- pcrfclient01/02

Example

- To fetch system information from Policy Director (lb) VMs:

```
dump_utility.py --info-type system --vm-type lb
```

- To fetch application and VM specific information from qns01:

```
dump_utility.py --info-type application:vm_specific --vm-type qns01
```

OR

```
dump_utility.py --info-type application:vm_specific --vm-type sav-qns01
```

where, `sav-qns01` is hostname of qns01 VM.

- To fetch database specific information from all replica sets:

```
dump_utility.py --info-type db --vm-type pcrfclient:sessionmgr
```

Sample output:

```
dump_utility.py --info-type application --vm-type sav-qns01
Logs are also getting stored in /var/tmp/dumputility-07-06-2016-04-07-47.log
*****
Collecting information, please wait...
*****
Fetching common information like about.sh/list_installed_features/diagnostics etc from
pcrfclient01
This step takes time, please wait...
Fetching command outputs from pcrfclient01
Fetching files hosts file from pcrfclient01
Fetching files consolidated logs from pcrfclient01
Fetching files Bulkstats file from pcrfclient01
Fetching command outputs from qns01
Fetching files Broadhop dir from qns01
Fetching files Broadhop logs from qns01
*****
Information is collected at : /var/tmp/07-06-2016-04-07-47.tar.gz
*****
Disconnecting from pcrfclient01... done.
```



Important For non-root users, certain CPS scripts (`about.sh`, `diagnostics.sh` and so on) expects sudo password. For such scripts, output is displayed on terminal and is saved in the file. Also for some data which can only be accessed by root user, permission denied related warning is displayed.

list_installed_features.sh

Displays the features and versions of the features that are installed on each VM in the environment.

Syntax

```
/var/qps/bin/diag/list_installed_features.sh
```

Executable on VMs

All

Example

```
[root@host /]# /var/qps/bin/diag/list_installed_features.sh
Features installed on lb01:9045
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.iomanager.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
Features installed on lb02:9045
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.iomanager.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
Features installed on qns01:9045
com.broadhop.balance.service.feature=3.4.2.r071203
com.broadhop.balance.spr.feature=3.4.2.r071203
com.broadhop.custrefdata.service.feature=2.4.2.r072158
com.broadhop.diameter2.local.feature=3.4.2.r072694
com.broadhop.externaldatacache.memcache.feature=7.0.2.r072627
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.policy.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
com.broadhop.spr.dao.mongo.feature=2.3.2.r071887
com.broadhop.spr.feature=2.3.2.r071887
com.broadhop.ui.controlcenter.feature=3.4.2.r070445
com.broadhop.unifiedapi.interface.feature=2.3.2.r072695
com.broadhop.unifiedapi.ws.service.feature=2.3.2.r072695
com.broadhop.vouchers.service.feature=3.4.2.r071203
com.broadhop.ws.service.feature=1.5.2.r071537
Features installed on qns02:9045
com.broadhop.balance.service.feature=3.4.2.r071203
com.broadhop.balance.spr.feature=3.4.2.r071203
com.broadhop.custrefdata.service.feature=2.4.2.r072158
com.broadhop.diameter2.local.feature=3.4.2.r072694
com.broadhop.externaldatacache.memcache.feature=7.0.2.r072627
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.policy.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
```



```
com.broadhop.snmp.feature=7.0.2.r072627
com.broadhop.spr.dao.mongo.feature=2.3.2.r071887
com.broadhop.spr.feature=2.3.2.r071887
com.broadhop.ui.controlcenter.feature=3.4.2.r070445
com.broadhop.unifiedapi.interface.feature=2.3.2.r072695
com.broadhop.unifiedapi.ws.service.feature=2.3.2.r072695
com.broadhop.vouchers.service.feature=3.4.2.r071203
com.broadhop.ws.service.feature=1.5.2.r071537
Features installed on qns03:9045
com.broadhop.balance.service.feature=3.4.2.r071203
com.broadhop.balance.spr.feature=3.4.2.r071203
com.broadhop.custrefdata.service.feature=2.4.2.r072158
com.broadhop.diameter2.local.feature=3.4.2.r072694
com.broadhop.externaldatacache.memcache.feature=7.0.2.r072627
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.policy.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
com.broadhop.spr.dao.mongo.feature=2.3.2.r071887
com.broadhop.spr.feature=2.3.2.r071887
com.broadhop.ui.controlcenter.feature=3.4.2.r070445
com.broadhop.unifiedapi.interface.feature=2.3.2.r072695
com.broadhop.unifiedapi.ws.service.feature=2.3.2.r072695
com.broadhop.vouchers.service.feature=3.4.2.r071203
com.broadhop.ws.service.feature=1.5.2.r071537
Features installed on qns04:9045
com.broadhop.balance.service.feature=3.4.2.r071203
com.broadhop.balance.spr.feature=3.4.2.r071203
com.broadhop.custrefdata.service.feature=2.4.2.r072158
com.broadhop.diameter2.local.feature=3.4.2.r072694
com.broadhop.externaldatacache.memcache.feature=7.0.2.r072627
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.policy.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
com.broadhop.spr.dao.mongo.feature=2.3.2.r071887
com.broadhop.spr.feature=2.3.2.r071887
com.broadhop.ui.controlcenter.feature=3.4.2.r070445
com.broadhop.unifiedapi.interface.feature=2.3.2.r072695
com.broadhop.unifiedapi.ws.service.feature=2.3.2.r072695
com.broadhop.vouchers.service.feature=3.4.2.r071203
com.broadhop.ws.service.feature=1.5.2.r071537
Features installed on pcrfclient01:9045
com.broadhop.controlcenter.feature=7.0.2.r072627
com.broadhop.faultmanagement.service.feature=1.0.2.r071534
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
Features installed on pcrfclient02:9045
com.broadhop.controlcenter.feature=7.0.2.r072627
com.broadhop.faultmanagement.service.feature=1.0.2.r071534
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
Features installed on all (combined)
com.broadhop.balance.service.feature=3.4.2.r071203
com.broadhop.balance.spr.feature=3.4.2.r071203
com.broadhop.controlcenter.feature=7.0.2.r072627
com.broadhop.custrefdata.service.feature=2.4.2.r072158
com.broadhop.diameter2.local.feature=3.4.2.r072694
com.broadhop.externaldatacache.memcache.feature=7.0.2.r072627
com.broadhop.faultmanagement.service.feature=1.0.2.r071534
com.broadhop.infrastructure.feature=7.0.2.r072627
com.broadhop.iomanager.feature=7.0.2.r072627
```

```

com.broadhop.policy.feature=7.0.2.r072627
com.broadhop.server.runtime.product=7.0.2.r072627
com.broadhop.snmp.feature=7.0.2.r072627
com.broadhop.spr.dao.mongo.feature=2.3.2.r071887
com.broadhop.spr.feature=2.3.2.r071887
com.broadhop.ui.controlcenter.feature=3.4.2.r070445
com.broadhop.unifiedapi.interface.feature=2.3.2.r072695
com.broadhop.unifiedapi.ws.service.feature=2.3.2.r072695
com.broadhop.vouchers.service.feature=3.4.2.r071203
com.broadhop.ws.service.feature=1.5.2.r071537

```

reinit.sh

This command is executed from Cluster Manager. It SSHs to all the CPS VMs and triggers the `/etc/init.d/vm-init.sh` script on each VM to download all the Puppet scripts, CPS softwares, `/etc/hosts` files and updates the VM with the new software from Cluster Manager to the VM.

Refer to [vm-init.sh, on page 48](#), to trigger this process for a single VM as opposed to all VMs.

Syntax

```
/var/qps/install/current/scripts/upgrade/reinit.sh
```

Executable on VMs

Cluster Manager

Example

```

[root@host /]# /var/qps/install/current/scripts/upgrade/reinit.sh
Running pupdate on lab
Updating /etc/hosts file from installer VM...
Updating /etc/facter/facts.d/bxb1-lb01...
Updating /etc/puppet from installer VM...

```

restartall.sh

This command is executed from Cluster Manager. It stops and restarts all of the Policy Server (QNS) services on all VMs in the CPS cluster. This command is also executed when new software is installed on VMs.

Refer to [restartqns.sh, on page 19](#) to restart Policy Server (QNS) services on a specific VM as opposed to all VMs.

Syntax

```
/var/qps/bin/control/restartall.sh
```

Executable on VMs

Cluster Manager



Note When executing `restartall.sh` command from `qns-admin`, prefix `sudo` before the command.



Caution Executing `restartall.sh` will cause messages to be dropped.

Example

```
/var/qps/bin/control/restartall.sh  
Currently active LB: lb01
```

This process will restart all QPS software on the nodes in this order:

```
lb02 pcrfclient02 qns01 qns02 pcrfclient01 lb01
```

restartqns.sh

This command stops and restarts all Policy Server (QNS) services on the target VM.

Syntax

```
/var/qps/bin/control/restartqns.sh hostname
```

Executable on VMs

Cluster Manager



Note When executing `restartqns.sh` command from `qns-admin`, prefix `sudo` before the command.

Example

```
/var/qps/bin/control/restartqns.sh qns01  
/var/qps/bin/control/restartqns.sh pcrfclient01
```

runonall.sh

Executes a command, as provided as an argument, on all of the VMs listed in the `servers` file. These commands must be run as the `CPS` user on the remote VMs, or they will fail to execute properly.

Syntax

```
/var/qps/bin/control/runonall.sh <executable command>
```

Executable on VMs

All



Note In case executing runonall.sh command from qns-admin, prefix sudo before the command.

Example

```
/var/qps/bin/control/runonall.sh ntpdate -u
```

service

This command is used to control individual services on each VM.

Syntax

```
service < option > | --status-all | [ service_name [ command | --full-restart ] ]
```



Caution Do not use this command for any services managed by the monit service. Use the monit summary command to view the list of services managed by monit. The list of services managed by monit is different on each CPS VM.

session_cache_ops.sh

This command provides information about, and performs operations on the session database.

Syntax

```
/var/qps/bin/support/mongo/session_cache_ops.sh <Argument1> <Argument2>
<Argument1>: --count or --remove
--count
--remove
--statistics-count
--add-shard
--add-ringset
--db-shrink
<Argument2>: site1 or site2 or site3 ... siten
This argument for GR only, in GR setup user need to pass the site number (site1 or site2 ...) as second argument
```

Options

--count

This option prints the count of sessions present in all available session_cache* databases.

The session count is the number of allocated entries in the database for unique subscriber sessions on the network. Each allocated entry may have related nested sub-sessions with other session types such as Sy/Rx.

- A session count is incremented when a Gx CCR-I arrives and an entry (Mongo data structure called a document) is allocated.
- If there are other types of sessions related to that unique subscriber during the life of the Gx session (or Sy/Rx) these are nested within the "document".
- If these "other" types of sessions are terminated, they are removed from the document and those counter types are decremented immediately.
- When the Gx CCR-T arrives it is decremented immediately from the Gx Type count.
- Up to 30 seconds later the unique session entry/document is removed, and the Session Total count is decremented.

The other session types should not be used in validating the number of total sessions as this varies greatly between call models and time. These are simply specific totals drawn from each entry.

It is typical for the session_total_count will be slightly more than the Gx_TYPE count due to the 30 second delay. The reason for this delay is that the entry (document) needs to wait for any other related (nested) sessions to close.

On occasion there may be small variance of data between what the perfclient01 and perfclient02 report, although they are querying the same database. These are, however, comparable.

The counters processing order is that the total session count is performed first and the detailed session (types) are done second. Slight discrepancies/variance in the numbers may occur.

Example

```
# session_cache_ops.sh --count
Session cache operation script
Tue Dec 22 02:26:49 MST 2015
-----
Session Replica-set SESSION-SET1
-----
Session Database      : Session Count
-----
session_cache         : 14
session_cache_2       : 15
session_cache_3       : 12
session_cache_4       : 10
-----
No of Sessions in SET1 : 51
-----
Total Number of Sessions : 51
```

--remove

This option removes sessions from all available session_cache* databases.



Warning

You will be prompted to confirm this action after running this command. If you proceed, this will remove existing sessions in the replica-set.

Example

```
# session_cache_ops.sh --remove
Session cache operation script
Tue Dec 22 02:29:42 MST 2015
-----
```

```

Session Replica-set SESSION-SET1
-----
WARNING: Continuing will remove existing sessions in
        replica-set : SESSION-SET1
CAUTION: This result into loss of session data
Are you sure you want to continue (y/yes or n/no)? : y
Removing sessions from session_cache db
connecting to: sessionmgr04:27717/session_cache
WriteResult({ "nRemoved" : 1 })
Remove sessions operation completed on session_cache db.
Removing sessions from session_cache_2 db
connecting to: sessionmgr04:27717/session_cache_2
WriteResult({ "nRemoved" : 0 })
Remove sessions operation completed on session_cache_2 db.
Removing sessions from session_cache_3 db
connecting to: sessionmgr04:27717/session_cache_3
WriteResult({ "nRemoved" : 0 })
Remove sessions operation completed on session_cache_3 db.
Removing sessions from session_cache_4 db
connecting to: sessionmgr04:27717/session_cache_4
WriteResult({ "nRemoved" : 0 })
Remove sessions operation completed on session_cache_4 db.
-----

```

--statistics-count

This option prints statistics count of the sessions (types if the session Gx, Rx, and so on) in all available session_cache* databases.

Example

```

# session_cache_ops.sh --statistics-count
Session cache operation script
Tue Dec 22 02:28:38 MST 2015
-----
Sessions statistic counter on General
-----
  Session Type          : Session Count
-----
ADMIN-SET1
  EDR                   : 5
  GX_SCE                 : 10
-----

```

--add-shard

Adds session shards to the session database, either normal shards or hot standby shards.

Example

```

# session_cache_ops.sh --add-shard
Session cache operation script
Tue Dec 22 02:22:24 MST 2015
      Session Sharding
-----
Select type of session shard  Default      [*]
                               Hot Standby   [ ]

Sessionmgr pairs : sessionmgr01:sessionmgr02:27717

Session shards per pair : 4

Creating Session sharding [ Done ]

```

```
-----
Note :
- Press 'y' to select the shard type
- If sharding needed for multiple sessionmgr vms with port
  please provide sessionmgr vm with port separated by ':',
  and pair separated by ', '
(Ex: sessionmgr01:sessionmgr02:27717,sessionmgr03:sessionmgr04:27717)
```



Note If sharding is required for GR setup, then add *site_id* at end of sessionmgr VM and port, separated by colon (:), in sessionmgr pairs parameter.

For example, sessionmgr01:sessionmgr02:27717:SITE1

--add-ringset

This option adds a new set to the ring.

Example

```
# session_cache_ops.sh --add-ringset
Session cache operation script
Wed Jun  8 18:23:15 EDT 2016
Session cache operation script: addRingSet
The progress of this script can be monitored in the following log:
/var/log/broadhop/scripts/session_cache_ops_08062016_182315.log
Note :
Please provide sessionmgr vm separated by ':' and pair separated by ', '

(Ex HA: sessionmgr01-lab:sessionmgr02-lab)
(Ex GR: sessionmgr01-site1:sessionmgr02-site1,sessionmgr01-site2:sessionmgr02-site2)
Enter cache servers: sessionmgr01,sessionmgr02
Verifying Qnoses processes is running
Adding set sessionmgr01,sessionmgr02 to ring
Executing OSGI Command> setSkRingSet 1 4 sessionmgr01:11211,
Executing OSGI Command> setSkRingSet 1 4 sessionmgr02:11211,
Executing OSGI Command> rebuildSkRing 1
Ringset added successfully
```

--db-shrink

This option is used after clean of all sessions from CPS mongo database. It performs a synchronization operation by removing session cache database files and copying data files from primary member. This reduces the database size and compact database files and/or reclaim disk space. Currently, this operation does not support specific to replica-set.



Note This option must be performed in maintenance window (if required in production) and when there is no session data.

Example

```
# session_cache_ops.sh --db-shrink
Session cache operation script
Fri May 13 06:17:42 EDT 2016
-----
```

```

Session DB Shrink Replica-set
-----
CAUTION: This option must performed in maintenance window and no session data
Are you sure you want to continue (y/yes or n/no)? : yes
Verify log /var/log/broadhop/scripts/session_cache_ops_13052016_061742.log

DB Shrink operation completed successfully for set - SESSION-SET1
  DB File count before Shrink: 36
  DB File count after  Shrink: 16
  DB Size before Shrink: 4.2G
  DB Size after  Shrink: 256M

DB Shrink operation completed successfully for set - SESSION-SET2
  DB File count before Shrink: 28
  DB File count after  Shrink: 8
  DB Size before Shrink: 4.0G
  DB Size after  Shrink: 128M

```

Executable on VMs

perfclient01/02

set_priority.sh

This command sets the priorities of replica-sets, and replica-set members for High Availability (HA) or Geo-Redundant (GR) CPS deployments.

By default, priority of mongo databases, replica-sets, and members are set in order (with higher priority) as defined in the Mongo Config (mongoConfig.cfg).

Use the `diagnostics.sh --get_replica_status` command to view the status and current priorities of all databases replica-sets.



Note If a member is shown in an unknown state, it is likely that the member is not accessible from one of other members, mostly an arbiter. In that case, you must go to that member and check its connectivity with other members.

Also, you can login to mongo on that member and check its actual status.

Syntax

```
/var/qps/bin/support/mongo/set_priority.sh
```

The following options are supported:

- **Mandatory Options:**

```
--db <db_name>
      [all|session|spr|admin|balance|report|portal|audit|bindings]
```

The `set_priority --db all` command would set the priority of all replica-sets listed in `mongoConfig.cfg` in descending order. The member that is listed first in the configuration would be assigned the highest priority.

The `set_priority --db session` command would set the priority of all replica-sets of db type SESSION. By default, priorities are set in descending order.

• **General Options:**

```
--h [ --help ]           show syntax and usage information for this script
--version                show version information of this script
--asc                   Set priority in ascending order (default is descending)
--dsc                   Set priority in descending order
--priority <0|1000>     Set specific priority
--force [false|true]    forces the new priority to be applied (default is false).
```



Note The `--priority <0|1000>` option is not currently supported. Do not use.



Caution Do not use the `--force` option unless instructed by a Cisco representative. By default, the `set_priority.sh` script will only attempt to set the priorities when all members of a replica set are in a healthy state. The `--force` option can be used when the members are NOT in a healthy state.

• **Specific Replica-set Options:**

```
--replSet <setname>      specifies the replica-set name
```

This option enables you to specify priority for a particular replica-set. You must provide the `<setname>`.

• **Geo-Redundancy Options:**

```
--sitename [site1|site2] specifies the GR site to which the operation applies
```

This option enables you to specify a GR site. The `mongoConfig.cfg` must have relevant start and end tags (like `#SITE1_START` and `#SITE1_END`).

Executable on VMs

Cluster Manager

Examples

High Availability Options:

```
set_priority.sh --db all
set_priority.sh --db session
set_priority.sh --db session --asc
set_priority.sh --db session --replSet set01
```

Geo-Redundancy Options:

```
set_priority.sh --db session --replSet set01 --sitename <site1|site2>
set_priority.sh --db session --replSet set01 --sitename <site1|site2>
set_priority.sh --db session --replSet set01 --sitename <site1|site2> --force true
```

startall.sh

This command is executed from Cluster Manager. It starts all Policy Server (QNS) services on all VMs in the CPS cluster. This command is also executed when a new software is installed on VMs.

Refer to [startqns.sh, on page 26](#) to start services on a specific VM as opposed to all VMs.

Syntax

```
/var/qps/bin/control/startall.sh
```



Note When executing startall.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

Cluster Manager

Example

```
/var/qps/bin/control/startall.sh
```

startqns.sh

This command is executed from Cluster Manager. It starts all Policy Server (QNS) services on the specified VM.

Syntax

```
/var/qps/bin/control/startqns.sh hostname
```



Note When executing startqns.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

Cluster Manager

Example

```
/var/qps/bin/control/startqns.sh qns01  
/var/qps/bin/control/startqns.sh pcrfclient01
```

statusall.sh

This command displays whether the services managed by monit are stopped or running on all VMs. This script can be executed from Cluster Manager or OAM (pcrfclient).

Syntax

```
/var/qps/bin/control/statusall.sh
```



Note When executing statusall.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

- Cluster Manager
- pcrfclient01/02

Output

For each process or program, the command displays:

- **Status**
 - Running – the process/Program is healthy and running
 - Does not exist – the process id specified in the /var/run/processname-pid does not exist. This is a cause for concern if recurring.
 - Waiting – This is normal for a program /process monitored by monit
 - Status ok – This is normal for a program monitored by monit
- **Monitoring Status**
 - Monitored – The process/program is being monitored
 - Not Monitored – The process/program is not under the control of monit
 - Waiting – A transient state which reports as waiting depending upon when the statusall.sh command is run which internally uses monit status command.



Note For more details, see: <https://bitbucket.org/tildeslash/monit/issue/114/>.

- **Uptime**

The number of days, hours, and minutes the process or program has been running.

Example

```
[root@host /]# /var/qps/bin/control/statusall.sh
Executing 'sudo /usr/bin/monit status' on all QNS Servers
The Monit daemon 5.5 uptime: 2h 12m
Process 'snmptrapd'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'snmpd'
  status          Running
  monitoring status Monitored
  uptime          2h 12m
Process 'sessionmgr-27017'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'qns-2'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'qns-1'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'memcached'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'logstash'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'elasticsearch'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'collectd'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'carbon-cache'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
Process 'carbon-aggregator'
  status          Running
  monitoring status Monitored
  uptime          15h 33m
System 'lab'
  status          Running
  monitoring status Monitored
Connection to 127.0.0.1 closed.
```

stopall.sh

This command is executed from Cluster Manager. It stops the Policy Server (QNS) services on each VMs in the CPS cluster.

Refer to [stopqns.sh, on page 29](#) to stop Policy Server (QNS) services on a specific VM as opposed to all VMs.

Syntax

```
/var/qps/bin/control/stopall.sh
```



Note When executing stopall.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

Cluster Manager

Example

```
/var/qps/bin/control/stopall.sh
```

stopqns.sh

This command is executed from Cluster Manager. It stops all Policy Server (QNS) services on the specified VM.

Syntax

```
/var/qps/bin/control/stopqns.sh hostname
```



Note When executing stopqns.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

Cluster Manager

Example

```
/var/qps/bin/control/stopqns.sh qns01
```

summaryall.sh

This command provides a brief status of the services managed by monit on all VMs in the CPS cluster.

Syntax

```
/var/qps/bin/control/summaryall.sh
```



Note When executing summaryall.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

Cluster Manager

Example

```

/var/qps/bin/control/summaryall.sh
The Monit daemon 5.14 uptime: 6d 10h 51m

Process 'whisper'                Running
Process 'snmptrapd'              Running
Process 'snmpd'                  Running
Program 'vip_trap'                Status ok
Program 'gr_site_status_trap'    Status ok
Process 'redis-2'                Running
Process 'redis-1'                Running
Process 'redis'                  Running
Process 'qns-4'                  Running
Process 'qns-3'                  Running
Process 'qns-2'                  Running
Process 'qns-1'                  Running
Process 'corosync'               Running
File 'monitor-qns-4'             Accessible
File 'monitor-qns-3'             Accessible
File 'monitor-qns-2'             Accessible
File 'monitor-qns-1'             Accessible
Process 'memcached'              Running
Process 'irqbalance'             Running
Process 'haproxy-diameter'       Running
Process 'haproxy'                Running
Process 'cutter'                 Running
Program 'cpu_load_monitor'       Status ok
Program 'cpu_load_trap'          Status ok
Program 'gen_low_mem_trap'       Status ok
Process 'collectd'               Running
Process 'auditrpmsh.sh'          Running
System 'lb01'                    Running
The Monit daemon 5.14 uptime: 6d 10h 51m

Process 'whisper'                Running
Process 'snmptrapd'              Running
Process 'snmpd'                  Running
Program 'vip_trap'                Status ok
Program 'gr_site_status_trap'    Status ok
Process 'redis-2'                Running
Process 'redis-1'                Running
Process 'redis'                  Running
Process 'qns-4'                  Running
Process 'qns-3'                  Running
Process 'qns-2'                  Running
Process 'qns-1'                  Running
Process 'corosync'               Running
File 'monitor-qns-4'             Accessible
File 'monitor-qns-3'             Accessible
File 'monitor-qns-2'             Accessible
File 'monitor-qns-1'             Accessible
Process 'memcached'              Running
Process 'irqbalance'             Running
Process 'haproxy-diameter'       Running
Process 'haproxy'                Running
Process 'cutter'                 Running
Program 'cpu_load_monitor'       Status ok
Program 'cpu_load_trap'          Status ok
Program 'gen_low_mem_trap'       Status ok

```

```

Process 'collectd'           Running
Process 'auditrpms.sh'      Running
System 'lb02'               Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'memcached'         Running
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'sessionmgr01'      Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'memcached'         Running
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'sessionmgr02'      Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'       Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'qns01'              Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'       Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'qns02'              Running
The Monit daemon 5.14 uptime: 5d 19h 19m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Program 'kpi_trap'          Status ok
Program 'db_trap'           Status ok
Program 'failover_trap'     Status ok
Program 'qps_process_trap'  Status ok
Program 'admin_login_trap'  Status ok
Program 'vm_trap'           Status ok
Program 'qps_message_trap'  Status ok
Program 'ldap_message_trap' Status ok
Process 'qns-2'             Running
Process 'qns-1'             Running
Process 'corosync'          Running

```

```

Program 'monitor_replica'      Status ok
File 'monitor-qns-2'          Accessible
File 'monitor-qns-1'          Accessible
Process 'logstash'            Running
Program 'mon_db_for_lb_failover' Status ok
Program 'mon_db_for_callmodel' Status ok
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'carbon-cache'        Running
Process 'carbon-aggregator'    Running
Process 'auditrpm.sh'          Running
System 'pcrfclient01'         Running
The Monit daemon 5.14 uptime: 5d 19h 52m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Program 'kpi_trap'            Status ok
Program 'db_trap'             Status ok
Program 'failover_trap'        Status ok
Program 'qps_process_trap'     Status ok
Program 'admin_login_trap'     Status ok
Program 'vm_trap'             Status ok
Program 'qps_message_trap'     Status ok
Program 'ldap_message_trap'    Status ok
Process 'qns-2'               Running
Process 'qns-1'               Running
Process 'corosync'            Running
Program 'monitor_replica'      Status ok
File 'monitor-qns-2'          Accessible
File 'monitor-qns-1'          Accessible
Process 'logstash'            Running
Program 'mon_db_for_lb_failover' Status ok
Program 'mon_db_for_callmodel' Status ok
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'carbon-cache'        Running
Process 'carbon-aggregator'    Running
Process 'auditrpm.sh'          Running
System 'pcrfclient02'         Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'qns-1'               Running
File 'monitor-qns-1'          Accessible
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpm.sh'          Running
System 'qns03'                 Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'qns-1'               Running
File 'monitor-qns-1'          Accessible
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'     Status ok

```



```

Process 'collectd'           Running
Process 'auditrpms.sh'      Running
System 'qns04'              Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'memcached'         Running
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'          Running
Process 'auditrpms.sh'      Running
System 'sessionmgr03'       Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'memcached'         Running
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'          Running
Process 'auditrpms.sh'      Running
System 'sessionmgr04'       Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'        Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'          Running
Process 'auditrpms.sh'      Running
System 'qns05'              Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'        Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'          Running
Process 'auditrpms.sh'      Running
System 'qns06'              Running
The Monit daemon 5.14 uptime: 6d 10h 52m

```

```

Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'        Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'     Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'          Running
Process 'auditrpms.sh'      Running
System 'qns07'              Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'           Running

```

```

Process 'snmpd'           Running
Process 'qns-1'          Running
File 'monitor-qns-1'     Accessible
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok
Program 'gen_low_mem_trap' Status ok
Process 'collectd'       Running
Process 'auditrpm.sh'    Running
System 'qns08'           Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'        Running
Process 'snmpd'          Running
Process 'qns-1'          Running
File 'monitor-qns-1'     Accessible
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok
Program 'gen_low_mem_trap' Status ok
Process 'collectd'       Running
Process 'auditrpm.sh'    Running
System 'qns09'           Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'        Running
Process 'snmpd'          Running
Process 'qns-1'          Running
File 'monitor-qns-1'     Accessible
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok
Program 'gen_low_mem_trap' Status ok
Process 'collectd'       Running
Process 'auditrpm.sh'    Running
System 'qns10'           Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'        Running
Process 'snmpd'          Running
Process 'qns-1'          Running
File 'monitor-qns-1'     Accessible
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok
Program 'gen_low_mem_trap' Status ok
Process 'collectd'       Running
Process 'auditrpm.sh'    Running
System 'qns11'           Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'        Running
Process 'snmpd'          Running
Process 'qns-1'          Running
File 'monitor-qns-1'     Accessible
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok
Program 'gen_low_mem_trap' Status ok
Process 'collectd'       Running
Process 'auditrpm.sh'    Running
System 'qns12'           Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'        Running
Process 'snmpd'          Running
Process 'memcached'      Running
Program 'cpu_load_monitor' Status ok
Program 'cpu_load_trap'   Status ok

```

```

Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr05'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'memcached'            Running
Program 'cpu_load_monitor'      Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr06'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'memcached'            Running
Program 'cpu_load_monitor'      Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr07'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'memcached'            Running
Program 'cpu_load_monitor'      Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr08'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'memcached'            Running
Program 'cpu_load_monitor'      Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr13'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'memcached'            Running
Program 'cpu_load_monitor'      Status ok
Program 'cpu_load_trap'        Status ok
Program 'gen_low_mem_trap'      Status ok
Process 'collectd'              Running
Process 'auditrpms.sh'         Running
System 'sessionmgr14'          Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'              Running
Process 'snmpd'                 Running
Process 'qns-1'                 Running

```

```

File 'monitor-qns-1'           Accessible
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'qns13'                Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'memcached'           Running
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'sessionmgr09'         Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'qns-1'                Running
File 'monitor-qns-1'           Accessible
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'qns14'                Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'memcached'           Running
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'sessionmgr10'         Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'qns-1'                Running
File 'monitor-qns-1'           Accessible
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'qns15'                Running
The Monit daemon 5.14 uptime: 6d 10h 51m

```

```

Process 'whisper'             Running
Process 'snmpd'               Running
Process 'memcached'           Running
Program 'cpu_load_monitor'     Status ok
Program 'cpu_load_trap'       Status ok
Program 'gen_low_mem_trap'     Status ok
Process 'collectd'            Running
Process 'auditrpmsh.sh'       Running
System 'sessionmgr11'         Running

```

The Monit daemon 5.14 uptime: 6d 10h 52m

```
Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'       Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'    Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'qns16'             Running
The Monit daemon 5.14 uptime: 6d 10h 51m
```

```
Process 'whisper'           Running
Process 'snmpd'             Running
Process 'memcached'        Running
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'    Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'sessionmgr12'      Running
The Monit daemon 5.14 uptime: 6d 10h 51m
```

```
Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'       Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'    Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'qns17'             Running
The Monit daemon 5.14 uptime: 6d 10h 51m
```

```
Process 'whisper'           Running
Process 'snmpd'             Running
Process 'qns-1'             Running
File 'monitor-qns-1'       Accessible
Program 'cpu_load_monitor'  Status ok
Program 'cpu_load_trap'    Status ok
Program 'gen_low_mem_trap'  Status ok
Process 'collectd'         Running
Process 'auditrpms.sh'     Running
System 'qns18'             Running
```

- qns-1.service - CPS Application Start Script
 - Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
 - Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
 - Process: 29532 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)
 - Process: 4919 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited, status=0/SUCCESS)
 - Main PID: 4937 (java)
 - CGroup: /system.slice/qns-1.service
 - └─4937 /usr/bin/java -server -XX:+PrintGCDetails -XX:+PrintGCTimeStamps -XX:+PrintGCDateStamps -XX:+PrintTenuringDistribution -XX...
- qns-2.service - CPS Application Start Script
 - Loaded: loaded (/etc/systemd/system/qns-2.service; static; vendor preset: disabled)
 - Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
 - Process: 29426 ExecStop=/var/qps/bin/support/startqps stop 2 (code=exited, status=0/SUCCESS)

```

Process: 4860 ExecStart=/var/qps/bin/support/startqps start 2 (code=exited,
status=0/SUCCESS)
Main PID: 4876 (java)
  CGroup: /system.slice/qns-2.service
          └─4876 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSize...
● qns-3.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-3.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 29846 ExecStop=/var/qps/bin/support/startqps stop 3 (code=exited, status=0/SUCCESS)

Process: 4804 ExecStart=/var/qps/bin/support/startqps start 3 (code=exited,
status=0/SUCCESS)
Main PID: 4820 (java)
  CGroup: /system.slice/qns-3.service
          └─4820 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSize...
● qns-4.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-4.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 29697 ExecStop=/var/qps/bin/support/startqps stop 4 (code=exited, status=0/SUCCESS)

Process: 4749 ExecStart=/var/qps/bin/support/startqps start 4 (code=exited,
status=0/SUCCESS)
Main PID: 4765 (java)
  CGroup: /system.slice/qns-4.service
          └─4765 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSize...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 17896 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 11745 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 11761 (java)
  CGroup: /system.slice/qns-1.service
          └─11761 /usr/bin/java -server -XX:+PrintGCDetails -XX:+PrintGCTimeStamps
-XX:+PrintGCDateStamps -XX:+PrintTenuringDistribution -X...
● qns-2.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-2.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 16763 ExecStop=/var/qps/bin/support/startqps stop 2 (code=exited, status=0/SUCCESS)

Process: 11690 ExecStart=/var/qps/bin/support/startqps start 2 (code=exited,
status=0/SUCCESS)
Main PID: 11706 (java)
  CGroup: /system.slice/qns-2.service
          └─11706 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSiz...
● qns-3.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-3.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 15817 ExecStop=/var/qps/bin/support/startqps stop 3 (code=exited, status=0/SUCCESS)

Process: 11888 ExecStart=/var/qps/bin/support/startqps start 3 (code=exited,
status=0/SUCCESS)
Main PID: 11906 (java)
  CGroup: /system.slice/qns-3.service
          └─11906 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSiz...
● qns-4.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-4.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago

```

```

Process: 14704 ExecStop=/var/qps/bin/support/startqps stop 4 (code=exited, status=0/SUCCESS)

Process: 11812 ExecStart=/var/qps/bin/support/startqps start 4 (code=exited,
status=0/SUCCESS)
Main PID: 11848 (java)
  CGroup: /system.slice/qns-4.service
          └─11848 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:ReservedCodeCacheSiz...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:49 IST; 4 days ago
Process: 30239 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 805 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited, status=0/SUCCESS)

Main PID: 821 (java)
  CGroup: /system.slice/qns-1.service
          └─821 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -Xm...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:47 IST; 4 days ago
Process: 10934 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 13549 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 13565 (java)
  CGroup: /system.slice/qns-1.service
          └─13565 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 9805 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 29166 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 29204 (java)
  CGroup: /system.slice/qns-1.service
          └─29204 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-Xms512m -Xmx1024m -javaagent:/opt/broadhop/qns...
● qns-2.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-2.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 9787 ExecStop=/var/qps/bin/support/startqps stop 2 (code=exited, status=0/SUCCESS)

Process: 28958 ExecStart=/var/qps/bin/support/startqps start 2 (code=exited,
status=0/SUCCESS)
Main PID: 29007 (java)
  CGroup: /system.slice/qns-2.service
          └─29007 /usr/java/default/bin/java -server -XX:+UnlockDiagnosticVMOptions
-XX:+UnsyncloadClass -Xms2048m -Xmx2048m -javaagent:/op...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 16610 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 18158 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 18185 (java)
  CGroup: /system.slice/qns-1.service
          └─18185 /usr/bin/java -server -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-Xms512m -Xmx1024m -javaagent:/opt/broadhop/qns...
● qns-2.service - CPS Application Start Script

```

```

Loaded: loaded (/etc/systemd/system/qns-2.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 16592 ExecStop=/var/qps/bin/support/startqps stop 2 (code=exited, status=0/SUCCESS)

Process: 17959 ExecStart=/var/qps/bin/support/startqps start 2 (code=exited,
status=0/SUCCESS)
Main PID: 17977 (java)
CGroup: /system.slice/qns-2.service
└─17977 /usr/java/default/bin/java -server -XX:+UnlockDiagnosticVMOptions
-XX:+UnsyncloadClass -Xms2048m -Xmx2048m -javaagent:/op...
● qns-1.service - CPS Application Start Script
Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:49 IST; 4 days ago
Process: 9733 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 12732 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 12748 (java)
CGroup: /system.slice/qns-1.service
└─12748 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -...
● qns-1.service - CPS Application Start Script
Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:47 IST; 4 days ago
Process: 8925 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 11537 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 11554 (java)
CGroup: /system.slice/qns-1.service
└─11554 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -...
● qns-1.service - CPS Application Start Script
Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:47 IST; 4 days ago
Process: 8352 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 11089 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 11111 (java)
CGroup: /system.slice/qns-1.service
└─11111 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -...
● qns-1.service - CPS Application Start Script
Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 6327 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 9157 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 9174 (java)
CGroup: /system.slice/qns-1.service
└─9174 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
Process: 596 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 3623 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 3639 (java)
CGroup: /system.slice/qns-1.service
└─3639 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass

```



```

-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 6463 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 9160 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 9176 (java)
  CGroup: /system.slice/qns-1.service
    └─9176 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:47 IST; 4 days ago
  Process: 2125 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 4861 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 4877 (java)
  CGroup: /system.slice/qns-1.service
    └─4877 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 3601 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 6350 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 6372 (java)
  CGroup: /system.slice/qns-1.service
    └─6372 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 32517 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 3098 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 3114 (java)
  CGroup: /system.slice/qns-1.service
    └─3114 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 6986 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 9788 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 9808 (java)
  CGroup: /system.slice/qns-1.service
    └─9808 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:49 IST; 4 days ago
  Process: 2578 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

  Process: 5592 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
  Main PID: 5609 (java)

```

```

CGroup: /system.slice/qns-1.service
└─5609 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 6041 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 8728 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 8746 (java)
CGroup: /system.slice/qns-1.service
└─8746 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:47 IST; 4 days ago
  Process: 32142 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 2435 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 2458 (java)
CGroup: /system.slice/qns-1.service
└─2458 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 2369 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 5110 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 5129 (java)
CGroup: /system.slice/qns-1.service
└─5129 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 2900 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 5889 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 5905 (java)
CGroup: /system.slice/qns-1.service
└─5905 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -X...
● qns-1.service - CPS Application Start Script
  Loaded: loaded (/etc/systemd/system/qns-1.service; static; vendor preset: disabled)
  Active: active (running) since Wed 2018-04-18 18:18:46 IST; 4 days ago
  Process: 27907 ExecStop=/var/qps/bin/support/startqps stop 1 (code=exited, status=0/SUCCESS)

Process: 30489 ExecStart=/var/qps/bin/support/startqps start 1 (code=exited,
status=0/SUCCESS)
Main PID: 30505 (java)
CGroup: /system.slice/qns-1.service
└─30505 /usr/bin/java -XX:+UnlockDiagnosticVMOptions -XX:+UnsyncloadClass
-XX:+TieredCompilation -XX:+DisableExplicitGC -server -...
[root@installer ~]#

```

sync_times.sh

This command synchronizes the time between all CPS VMs.

Syntax

For High Availability deployments:

```
/var/qps/bin/support/sync_times.sh ha
```

For Geographic Redundancy deployments:

```
/var/qps/bin/support/sync_times.sh gr
```

Executable on VMs

Cluster Manager

To check the current clock skew of the system, execute the following command:

```
diagnostics.sh --clock_skew -v
```

The output numbers are in seconds. Refer to the following sample output:

```
CPS Diagnostics Multi-Node Environment
-----
Checking for clock skew...
Clock skew not detected between qns01 and lb01. Skew: 1...[PASS]
Clock skew not detected between qns02 and lb01. Skew: 0...[PASS]
Clock skew not detected between lb01 and lb01. Skew: 0...[PASS]
Clock skew not detected between lb02 and lb01. Skew: 0...[PASS]
Clock skew not detected between sessionmgr01 and lb01. Skew: 0...[PASS]
Clock skew not detected between sessionmgr02 and lb01. Skew: 0...[PASS]
Clock skew not detected between pcrfclient01 and lb01. Skew: 0...[PASS]
Clock skew not detected between pcrfclient02 and lb01. Skew: 0...[PASS]
```

syncconfig.sh

This command is executed to synchronize the changes to the VM nodes. The files in the `/var/qps/current_config/etc/broadhop` are zipped to a file and stored in `/var/www/html`. The Puppet scripts in VM downloads the file to the VM and applies the changes to the VM.

Syntax

```
/var/qps/bin/update/syncconfig.sh
/var/qps/install/currentfolder/scripts/bin/update/syncconfig.sh
```

where, `currentfolder` is version of the current installation.

For example, for CPS 7.0.5, it is 7.0.5.

```
/var/qps/install/7.0.5/scripts/bin/update/syncconfig.sh
```

Executable on VMs

All

Example

```
[root@host /]# /var/qps/bin/update/synconfig.sh
Building /etc/broadhop...
Copying to /var/qps/images/etc.tar.gz...
Creating MD5 Checksum...
```

terminatesessions

This utility submits bulk session terminate requests.

**Note**

For fresh installations of CPS 10.1.0, this feature is enabled by default. However, for upgrades from systems prior to CPS 10.1.0, this feature needs to be enabled as follows:

In the `/etc/broadhop/pcrf/features` file, add **com.broadhop.policy.command.feature**. For more information, refer to "Customize Features" in the "Deployment" section in *CPS Installation Guide for VMware*

**Important**

To eliminate the impact of TPS and session count in the system, add the following entry in the `/etc/broadhop/qns.conf` file on the Cluster Manager VM:

```
-Ddistribution.blocked.duration=1800000
```

The entry value is in milliseconds, which converts to 30 minutes. The recommended value is multiples of 30 minutes.

After configuring the above values, run the following commands:

```
copytoall.sh /etc/broadhop/qns.conf
stopall.sh
startall.sh
```

Syntax

```
/var/qps/bin/support/command --username <USERNAME> --password <PASSWORD> terminatesessions
--criteria <criteria> [--disable_signaling <y/n - default n>] [--rate <throttling rate -
default 100>]
```

Where,

- `--username` and `--password` are the user's Control Center credentials.
- `--criteria`: Identifies the session. Following are some examples:
 - ALL
 - APN eq SOS
 - APN except SOS
 - IMSIRANGE A-B



Remember For the termination of sessions without any criteria (ALL) and termination of sessions with IMSI range as criteria (IMSIRANGE A-B), CPS must be configured to create sessions with **tags** field having **ImsiKey:imsi:<imsivalue>** as element. If this element is not configured, the command does not terminate sessions for ALL and IMSI range as criteria.

- `--disable_signaling`: Disables signaling on external interface.
- `--rate`: Defines the throttling rate.

`/var/qps/bin/support/command terminatesessions -h` shows help related to the command option.

Executable on VMs

pcrfclient01/02

Example

```
/var/qps/bin/support/command -u testuser -p cisco123 terminatesessions -c "ALL" -d y
Do you want to proceed with delete command? [y]|n: y
deleteBulkSession testuser "ALL" false 100
User is : testuser
Criterion is : ALL
Command Criteria type   : ALL
Command Criteria value  : null
Signalling is set to   : false
Rate-Limiter value is set to : 100
CommandId submitted successfully : 1471941788159
```

show

This utility shows the status of the submitted command(s).

Syntax

```
/var/qps/bin/support/command --username <USERNAME> --password <PASSWORD> show [--all <All>]
[--id <ID>]
```

Where,

- `--username` and `--password` are the user's Control Center credentials.
- `--all`: Shows the status of all the command requests submitted.
- `--id`: Shows the status of the submitted command.

Executable on VMs

pcrfclient01/02

Example

```
/var/qps/bin/support/command -u testuser -p cisco123 show
getCommands
```

```

BulkTerminateCommand(1471492548449)- state: COMPLETED submitted: Thu Aug 18 09:25:48 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]
BulkTerminateCommand(1471492739896)- state: COMPLETED submitted: Thu Aug 18 09:28:59 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]
BulkTerminateCommand(1471493146320)- state: COMPLETED submitted: Thu Aug 18 09:35:46 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]
BulkTerminateCommand(1471494348267)- state: COMPLETED submitted: Thu Aug 18 09:55:48 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]
BulkTerminateCommand(1471494588431)- state: COMPLETED submitted: Thu Aug 18 09:59:48 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]

/var/qps/bin/support/command -u testuser -p cisco123 show --id 1471494588431
getCommand 1471494588431
BulkTerminateCommand(1471494588431)- state: COMPLETED submitted: Thu Aug 18 09:59:48 IST
2016 status:
[Eligible for Deletion = 1, Submitted For Deletion = 1, Not Submitted Due To Later Creation
= 0]

```

cancel

This utility cancels the further execution of the submitted command.

Syntax

```
/var/qps/bin/support/command --username <USERNAME --password <PASSWORD> cancel --id <ID>
```

Where,

- --username and --password are the user's Control Center credentials.
- --id: ID of the submitted command.

Executable on VMs

pcrfclient01/02

Example

```

/var/qps/bin/support/command -u testuser -p cisco123 cancel --id 1471941788159
Do you want to proceed with cancel command? [y]|n: y
cancelCommand 1471941788159
Command Already completed: 1471941788159

```

top_qps.sh

This command displays performance statistics of CPS VMs.

Syntax

```
/var/qps/bin/control/top_qps.sh <time>
```

where <time> is the number of seconds for which the statistics are to be captured.



Note When executing top_qps.sh command from qns-admin, prefix sudo before the command.

Executable on VMs

perfclient01/02

Output

- Average time in ms.
- Number of message transactions processed during n seconds, where n is an integer value in seconds.
- Transactions per second (TPS) is messages/n.
- Error shows any error occurred during execution on the Policy Server (QNS) VM. It could be database error, authentication failure and so on. Details of the error can be seen in the consolidated engine or in the consolidated Policy Server (QNS) log.
- Times used is how much total time it took to process the message.

Example

Figure 1: Example for top_qps.sh

```
-----
Host Detail:
qns03,qns01,qns07,qns06,qns08,qns05,qns04
qns02
Measurement timer: 5   QNS Count: 8
-----
```

Average	Success	TPS	Error	Time Used	Messages
31.3868	31706	6341.2000	0	995.1514	diameter_Gx_CCR-U
32.4724	4490	898.0000	0	145.8012	diameter_Rx_AAR
31.1475	4630	926.0000	0	144.2129	diameter_Gx_CCR-I
29.8733	4697	939.4000	0	140.3147	diameter_Syp_AAA
31.7974	4037	807.4000	36	128.3662	diameter_Rx_STR
30.5017	3722	744.4000	0	113.5272	diameter_Gx_CCR-T
30.1642	415	83.0000	0	12.5181	diameter_Syp_STA
33.1618	221	44.2000	0	7.3288	diameter_Gx_RAA
27.6945	120	24.0000	0	3.3233	class com.broadhop.cache.TimerExpired
6.0920	1	0.2000	0	0.0061	diameter_Rx_ASA

Average	Success	TPS	Error	Time Used	Actions
13.6113	82620	16524.0000	0	1124.5640	com.broadhop.locking.impl.LockSessionAction
4.4117	54757	10951.4000	0	241.5705	com.broadhop.cache.impl.actions.GetSessionAction
2.2590	50002	10000.4000	36	112.9528	com.broadhop.session.UpdateEntry
0.9880	54760	10952.0000	0	54.1017	com.broadhop.spr.impl.actions.GetSubscriberActionImpl
0.8557	36553	7310.6000	0	31.2784	com.broadhop.balance.service.actions.OCSSLoadBalanceState
2.4404	4691	938.2000	0	11.4480	com.broadhop.session.CreateEntry
0.0674	15322	3064.4000	0	1.8321	com.broadhop.balance.service.actions.OCSSGetReservationStatusRequest
0.0174	54734	10946.8000	0	0.9521	com.broadhop.policyintel.impl.actions.StartPolicyReporting
0.0138	54758	10951.6000	0	0.7581	com.broadhop.policy.impl.service.AddSubscriberService
0.0183	32091	6418.2000	0	0.5866	send.diameter_Gx_CCA-U
0.0284	13374	2674.8000	0	0.3795	diameter.create.remote.session.Syp
0.0283	8649	1729.8000	0	0.2447	send.diameter_Gx_RAR
0.0316	4691	938.2000	0	0.1484	send.diameter_Gx_CCA-I
0.0026	54747	10949.4000	0	0.1407	com.broadhop.policyintel.impl.actions.StopPolicyReporting
0.0279	4691	938.2000	0	0.1309	send.diameter_Syp_AAR
0.0007	163853	32770.6000	0	0.1194	com.broadhop.policy.impl.actions.LogMessage
0.0231	3998	799.6000	0	0.0922	send.diameter_Syp_STR
0.0197	4540	908.0000	0	0.0896	send.diameter_Rx_AAA
0.0183	4091	818.2000	0	0.0749	send.diameter_Rx_STA
0.0166	3776	755.2000	0	0.0626	send.diameter_Gx_CCA-T
1.0123	15	3.0000	0	0.0152	com.broadhop.session.DeleteEntry
0.0191	102	20.4000	0	0.0020	send.diameter_Rx_ASR

```
-----
Fri May 1 01:48:21 IST 2015
*** End-of-Collection ***
-----
```

215906

Diameter Synchronization Message Behavior

Some Diameter messages (like UDR) are synchronous Diameter calls, which means that the Policy Server (QNS) will be waiting for a response after sending the Diameter request.

Response of these Diameter message is not captured in `top_qps` as those message are not processed in policy engine separately.

Average time 3.3676 shown below is round trip time (from UDR sent to UDA received)

Sample Top_Qns

Average	Success	TPS	Error	Time Used	Messages
9.7211	2910	727.5000	0	28.2883	diameter_Gx_CCR-I

Average	Success	TPS	Error	Time Used	Actions
3.6854	2924	731.0000	0	10.7761	
3.3676	2922	730.5000	0	9.8400	com.broadhop.cache.impl.actions.GetSessionAction
0.7908	2919	729.7500	0	2.3083	send.sync.diameter_Sh_UDR
0.1981	2924	731.0000	0	0.5793	com.broadhop.session.CreateEntry
0.0480	2919	729.7500	0	0.1400	com.broadhop.locking.impl.LockSessionAction
0.0126	2924	731.0000	0	0.0370	send.diameter_Gx_CCA-I
					diameter.create.remote.session.Sh

Average time is not applicable for these response messages. However, number of response messages (UDA) received can be seen from Grafana.

vm-init.sh

This command is executed from the VM nodes from `/etc/init.d`, (starts up automatically if VM reboots too). It downloads all the Puppet script, CPS software, `/etc/hosts` files and updates the VM with the new software.

This command only updates the software and does not restart the CPS software. The new software will be run only after process restart (for example, by executing `/var/qps/bin/control/restartall.sh` script from Cluster Manager).



Caution Executing `restartall.sh` will cause messages to be dropped.

Syntax

```
/etc/init.d/vm-init.sh
```

Executable on VMs

Any CPS VM

Example

```
/etc/init.d/vm-init.sh
```