

# **ADC for Dynamic Rules**

**Table 1: Feature History** 

Feature Name	Release Information	Description
ADC Dynamic Rules over Gx	2024.02.0	UPF leverages the dynamic ADC rules for traffic matching and charging. This feature allows the service providers to manage IoT devices, such as connected cars, and charge their subscribers based on the traffic flows classified by SMF or UPF. With this traffic classification, the service providers enable service monetization. In summary, SMF first processes the dynamic ADC rules received from PCF with TDF-App-Identifier, Service ID, and Rating group. SMF then sends this information to UPF to classify ruledefs and perform charging. <b>Default Setting</b> : Enabled – Always-on

- Feature Description, on page 1
- How it Works, on page 1
- Limitations, on page 2
- OAM Support, on page 2

# **Feature Description**

UPF processes N4 messages received from SMF and installs, removes, and modifies the message entities (PDR/URR/FAR/QER) of dynamic ADC rules.

UPF matches the configured ruledef with the TDF-App-Identifier AVP received in the dynamic ADC rule as part of PDR installation from SMF. If matched, UPF classifies the packets and charges the subscribers as per the Rating Group and Service ID of the Dynamic rule PDR.

## **How it Works**

PCRF installs a dynamic ADC rule with charging rule definition on SMF. UPF receives the N4 messages from SMF containing the dynamic ADC rule-related PDRs, URRs, QERs, and FARs. The dynamic ADC rule

PDR contains the Application ID corresponding to the TDF-App-Identifier received from the PCRF and the Mute notification. UPF does not enable any Application Start/Stop triggers as Mute is enabled.

Upon receiving the N4 message, UPF matches the ruledef pointed using the Application ID/TDF-App-Identifier. UPF then charges the packets matching to this ruledef against the URR received and applies bandwidth policing based on the QER received for the dynamic ADC rule PDR.

UPF supports the following three use cases to support dynamic ADC rules:

• Installing a Dynamic ADC Rule per Subscription: Upon receiving the dynamic ADC rule from PCRF, SMF installs the rule and sends an N4 Session Establishment Request to UPF to create PDR, QER, FAR, and URR. The Create PDR Request for this dynamic ADC rule contains the TDF-App-Identifier and Mute AVP enabled for all dynamic ADC rules.

UPF matches the configured ruledef with the TDF-App-Identifier and charges the packets according to the RG/SI received in the Dynamic ADC rule. UPF does not generate the N4 Session report for APP-START/STOP, as Mute notifications are enabled from PCRF on SMF during rule install.

• Modifying a Dynamic ADC Rule from PCRF/SMF: PCRF sends a Re-authorization request (RAR) to SMF along with a Dynamic ADC Rule Modification request. SMF then sends a Session Modification Request to UPF to update QER containing the updated gate status and MBR values.

UPF performs modifications of the AVPs and sends a N4 Session Modification Response to SMF. UPF also allows enabling or disabling the offline/online charging and modification of the QoS through RAR in mid-session.

• **Removing a Dynamic ADC Rule from PCRF/SMF**: UPF receives an N4 Modify Request with Remove PDRs and QERs corresponding to the dynamic ADC rule. UPF also receives Remove URRs occasionally, if it is the last rule for that Rating-Group/Service-ID.

Upon receiving the N4 Modify Request, UPF stops matching the rule for the ruledef pointed by the TDF-App-Identifier from the Session Modification Request.

For detailed information on dynamic ADC rules, see the UCC 5G SMF Configuration and Administration Guide applicable for the release.

## Limitations

Following is the known limitation of this feature:

• Default bearer URR does not display usage for the subscriber when offline charging is enabled using the RAR on mid-session for the dynamic ADC rule.

# **OAM** Support

This section describes operations, administration, and maintenance support for this feature.

### Show Command Output

This section describes the show commands supported in this feature.

#### show subscribers user-plane-only full all

The output of the show command **show subscribers user-plane-only full all** has been enhanced to display the number of associated ADC PDRs.

[local]UPF1# show subscribers user-plane-only full all : [0x000400000000002] 1125899906842626 Local SEID Remote SEID : [0x0000004bebf6665] 20380083813 State : Connected : Wed Apr 3 12:45:51 2024 : 00h00m07s Connect Time Idle time Access Type: uplane-ipv4v6 Network Type: IP user-plane-service-name: user-plane-service active-service-scheme-name: Callid: 00004e23 Rulebase: adc1 Interface Type: N4 eMPS Session: No eMPS Session Priority: 0 Session-Type: normal Precedence-order: 0 Data Queue: 0 Card/Cpu: 1/0 Sessmgr Instance: 1 IP address: 2001:cb0:0:3::4e:2301,11.11.0.4 Next Hop Ip Address: N/A, Source context: EPC2-UP Destination context: ISP PDN-Instance: cnpgw User-plane-Sx-addr: 20.20.20.106 Control-plane-Sx-addr: 20.20.20.3 Number of associated PDRs : 4 Number of associated ADC PDRs : 2 Number of associated FARs : 4 Number of associated OERs : 3 Number of associated BARs : 0 Number of associated URRs : 5 Number of associated BLIs : 1 Uplink APN AMBR (bps) : 100000 Downlink APN AMBR (bps) : 100000 active input acl: n/a active output acl: n/a active input ipv6 acl: n/a active output ipv6 acl: n/a Bandwidth Policy: n/a FW-and-NAT Policy: n/a FW-and-NAT Policy ID: n/a Firewall Policy IPv4: n/a Firewall Policy IPv6: n/a NAT Policy NAT44: n/a NAT Policy NAT64: n/a Converged Session: No Converged Peer Callid: n/a Visited Call: No Subscriber Parameters: IMSI: 123456781300001 IMEI: 123456781312381 MSISDN: 22331101101010 Rat Type: 6 Old Rat Type: n/a MCC MNC: 123456 SGSN Address: 20.20.20.15 ULI: TAI+ECGI=2163540015216354000000d00 CF Policy ID: n/a GX CF Policy ID: n/a S-NSSAI: 0x01000002 Roaming Status: Homer Old Roaming Status: n/a input pkts: 5 output pkts: 5

input bytes: 5200 input bytes dropped: 0 input pkts dropped: 0 CF Buffered Uplink Packets: 0 CF Buffered Uplink Bytes: 0 Uplink Packets in Buffer: 0 Buff Over-limit Uplink Pkts: 0 DDN buffered pkts : 0 DDN buffer overflow drop pkts : 0 pk rate from user(bps): 0 ave rate from user(bps): 0 sust rate from user(bps): 0 pk rate from user(pps): 0 ave rate from user(pps): 0 sust rate from user(pps): 0 ipv4 bad hdr: 0 ipv4 fragments sent: 0 ipv4 bad length trim: 0 input pkts dropped (0 mbr): 0 ipv4 input acl drop: 0 ipv6 input acl drop: 0 ip source violations: 0 ipv6 bad hdr: 0 ipv4 icmp packets dropped: 0 APN AMBR Uplink Pkts Drop: 0 APN AMBR Uplink Bytes Drop: 0 APN AMBR Uplink Pkts IP pref lowered: 0 0 APN AMBR Uplink Bytes IP pref lowered: 0 0 ITC Uplink Pkts Drop: 0 ITC Uplink Bytes Drop: 0 ITC Uplink Pkts IP pref lowered: 0 ITC Uplink Bytes IP pref lowered: 0 ITC Terminated Flows:: 0 Flow Action Terminated Flows: 0 ToS marked Uplink Pkts: 0 CC Dropped Uplink Pkts: 0 CC Dropped Uplink bytes: 0 Uplink Inflight Pkts: 0 QFI Mismatch Uplink Pkts Drop: 0 Total QoS-Group(s) Active: 0 DNS-to-EDNS Uplink Pkts: 0 EDNS Response Received: 0 Flow information: Current Active Flows: TCP: 1 UDP: 0

```
output bytes: 200
 output bytes dropped: 0
 output pkts dropped: 0
 CF Buffered Downlink Packets: 0
 CF Buffered Downlink Bytes: 0
 Downlink Packets in Buffer: 0
 Buff Over-limit Downlink Pkts: 0
DDN buffered bytes : 0
DDN buffer overflow drop bytes : 0
pk rate to user(bps): 0
 ave rate to user(bps): 0
 sust rate to user(bps): 0
 pk rate to user(pps): 0
 ave rate to user(pps): 0
 sust rate to user(pps): 0
 ipv4 ttl exceeded: 0
 ipv4 could not fragment: 0
 output pkts dropped (0 mbr): 0
 ipv4 output acl drop: 0
 ipv6 output acl drop: 0
 ipv4 output no-flow drop: 0
  ipv6 bad length trim: 0
 APN AMBR Downlink Pkts Drop: 0
  APN AMBR Downlink Bytes Drop: 0
  APN AMBR Downlink Pkts IP pref lowered:
 APN AMBR Downlink Bytes IP pref lowered:
  ITC Downlink Pkts Drop: 0
  ITC Downlink Bytes Drop: 0
  ITC Downlink Pkts IP pref lowered: 0
  ITC Downlink Bytes IP pref lowered: 0
 ITC Redirected Flows: 0
 Flow Action Redirected Flows: 0
  ToS marked Downlink Pkts: 0
  CC Dropped Downlink Pkts: 0
  CC Dropped Downlink Bytes: 0
  Downlink Inflight Pkts: 0
  QFI Mismatch Downlink Pkts Drop: 0
DNS-to-EDNS Uplink Bytes: 0
```

show subscribers user-plane-only callid callid pdr full all

The output of the show command **show subscribers user-plane-only callid** *callid* **pdr full all**has been modified to display the following new fields:

TDF App Id

Total Flows: TCP: 1 UDP: 0 FP: 1

TDF Notifications

#### Total ADC PDRs found

[local]UPF1# show subscribers user-plane-only callid 00004e21 pdr full all Callid: 00004e21 Interface Type: N4 IP address: 2001:cb0:0:3::4e:2301,11.11.0.4 0x0003 PDR-ID: Rule Name: port-2000 TDF App Id: port-2000 TDF Notifications: Disabled Hits: 1 Match Bypassed: 4 Matched Bytes: 200 Matched Packets: 5 55 Precedence: Source Interface: Core Source Interface Type: N/A SDF Filter(s): No SDF filters present Local F-TEID: 0x0 Local F-TEID IP Addr: IPv4: N/A IPv6: N/A Application ID: N/A ' TATT. 0x80000001 Outer header removal: Destination Interface: Access Apply Action: FORWARD Outer Header Creation: GTP-U/UDP/IPv4 Remote TEID: 0x3000000 Transport Level Marking: N/A Transport Level Marking Options: Copy Inner: No Copy Outer: No Inner Packet Marking: N/A Remote IP Address: 20.20.20.15 Remote Port: N/A 2 Associated QERIDs: OER-TDS Correlation-ID 0x0000003 n/a 0x00000001 Associated URRIDs: 4 Parent URR-ID 0x000000E 0x00000011 0x80000002 n/a 0x0000027 0x80000002 n/a 0x80000009 n/a N/A Activation Time: Deactivation Time: N/A Bearer Level Info-id: 1 5QI: 5 ARP: 20 Charging Id: 4 PDR-ID: 0x0004 port-2000 Rule Name: port-2000 TDF App Id: TDF Notifications: Disabled 1 Match Bypassed: Hits: 4 Matched Bytes: 5200 Matched Packets: 5 55 Precedence: Source Interface: Access Source Interface Type: S5U(1) SDF Filter(s): No SDF filters present

Local F-TEID: 0x8001 Local F-TEID IP Addr: IPv4: 20.20.20.46 IPv6: N/A Outer header removal: GTP-U/UDP/IPv4 Application ID: N/A 0x80000002 Associated FARID: Destination Interface: Core Apply Action: FORWARD Outer Header Creation: Remote TEID: 0x0 Transport Level Marking: N/A Transport Level Marking Options: Copy Inner: No Copy Outer: No Inner Packet Marking: N/A Remote IP Address: N/A Remote Port: Associated QERIDs: 2 
 uxuu0000003
 n/a

 uxu0000001
 0x0000000

 Associated URRIDs:
 4

 URR-IDs
 Parent URR-ID

 0x00000011
 0x8000002

 0x00000027
 ~' 

 0x80000027
 ~' QER-IDs Correlation-ID 0x000000E n/a 0x80000002 0x80000009 n/a Deactivation Time: N/A Bearer L Bearer Level Info-id: 1 50I: 5 ARP: 20 Charging Id: 4 PDR-ID: 0x0005 Rule Name: ipv6rsradl TDF App Id: N/A N/A TDF Notifications: Hits: 3 Match Bypassed: Matched Bytes: 312 Matched Packets: Precedence: 1 Source Interface:CP-function Source Interface Type: N/A SDF Filter(s): No SDF filters present 0x8000a001 Local F-TEID: Local F-TEID IP Addr: 20.20.20.46 TPv4: IPv6: N/A Outer header removal: GTP-U/UDP/IPv4 Application ID: N/A Associated FARID: 0x0003 Destination Interface: Access Apply Action: FORWARD Outer Header Creation: GTP-U/UDP/IPv4 Remote TEID: 0x300000 Transport Level Marking: N/A Transport Level Marking Options: Copy Inner: No Copy Outer: No Inner Packet Marking: N/A Remote IP Address: 20.20.20.15

N/A

0 3

Remote Port:

0

0

Associated QERIDs: 1 Correlation-ID OER-IDS 0x00000002 n/a Associated URRIDs: Ο Activation Time: N/A Deactivation Time: N/A Bearer Level Info-id: N/A PDR-ID: 0x0006 Rule Name: ipv6rsraul TDF App Id: N/A TDF Notifications: N/A 0 Match Bypassed: Hits: Matched Bytes: 0 Matched Packets: Precedence: 1 Source Interface: Access Source Interface Type: S5U(1) SDF Filter(s): Filter 1 Protocol: ICMPV6 Src IP Addr: ANY ANY Src Port: Dst IP Addr: ff05::2/128 Dst Port: ANY SPI: 0 Filter 2 ICMPV6 Protocol: Src IP Addr: ANY Src Port: ANY Dst IP Addr: ff02::2/128 Dst Port: ANY SPI: 0 Filter 3 Protocol: ICMPV6 Src IP Addr: ANY Src Port: ANY Dst IP Addr: ff01::2/128 Dst Port: ANY SPI: 0 0x8001 Local F-TEID: Local F-TEID IP Addr: IPv4: 20.20.20.46 IPv6: N/A Outer header removal: GTP-U/UDP/IPv4 Application ID: N/A 0x0004 Associated FARID: Destination Interface: CP-function Apply Action: FORWARD Outer Header Creation: GTP-U/UDP/IPv4 Remote TEID: 0x4 Transport Level Marking: N/A Transport Level Marking Options: Copy Inner: No Copy Outer: No Inner Packet Marking: N/A Remote IP Address: 20.20.20.3 Remote Port: N/A Associated QERIDs: 0 Associated URRIDs: 0 Activation Time: N/A Deactivation Time: N/A Bearer Level Info-id: N/A

Total ADC PDRs found:2Total PDRs found:4