



L3, L4, and L7 Rule Combination in Ruledef

- [Revision History](#), on page 1
- [Feature Description](#), on page 1
- [How it Works](#), on page 2
- [Configuring the L3, L4, and L7 Rule Combination in Ruledef Feature](#), on page 3
- [Monitoring and Troubleshooting](#), on page 4

Revision History



Note Revision history details are not provided for features introduced before release 21.24.

Revision Details	Release
Added support for CLI commands as part of the enhanced ACS feature.	21.27
First introduced.	Pre 21.24

Feature Description

The L3, L4, and L7 Rule Combination in Ruledef feature allows you to categorize traffic into specific Rating Group (RG) for:

- Specific IP addresses
- Ports
- Uniform Resource Locators (URLs)

The scalability of the host pool is increased from 256 to 512. This feature allows and defines the **url-sni-pool** configuration with 256 entries in a single pool. The entries can be a combination of URL and Server Name Indication (SNI) values. The system-wide limit of URL-SNI pools is 384 entries.

How it Works

The feature enables you to define a list of URLs or SNIs for the **url-sni-pool** configuration. The system uses a pool of URLs or SNIs as an L7 filter within a ruledef. A ruledef can contain a combination of hostpool, portmap, and url-sni pool match. The system matches the url-sni-pool configuration along with the other rule lines criteria without occupying any of the 32 existing rule lines.

Enhanced ACS Feature

The feature supports the following ECS constructs on Config Manager:

- Ruledef
- Host Pool
- PortMap
- IMSI Pool
- Group of Ruledef
- Charging Action
- URL-SNI Pool
- Rulebase
- Action-priority Lines
- Routing Ruledef
- Bandwidth Policy
- Monitoring Key
- Xheader
- ACS-level Config

The following are the new limits on ECSv2 constructs:

Construct	Limits
Ruledef	5000
Rule-lines per Ruledef	32
Group-of-Ruledef	512
Ruledef inside a Group-of-Ruledef	512
Host-Pool	1200
IP/IP ranges per Host-Pool	256
PortMap	800
Port/Port range per PortMap	20

Construct	Limits
URL-SNI-Pool	1200
URL/SNI per URL-SNI-Pool	256
IP/IP ranges per GW node	30,000
URL/SNI per GW node	30,000
Port/Port range per GW node	3000
Action-Priority line per Rulebase	3000
Action-Priority line per GW node	50,000
Routing-Priority line per GW node	5000

Enabling Enhanced ACS Feature

Use the following configuration to enable the enhanced ACS mode.

On CP:

```
configure
  require enhanced-acs-config control-plane
```

On UP:

```
configure
  require enhanced-acs-config user-plane
```



Note These two configurations takes effect only after reboot. So, you must add them in Day-0 configuration.

Configuring the L3, L4, and L7 Rule Combination in Ruledef Feature

The new URL-SNI Pool Configuration mode is available under ACS Configuration mode. Use the following configuration to enable the feature.

```
configure
  active-charging service service_name
    url-sni-pool pool_name
      http url { contains | starts-with | ends-with | = | !contains |
!starts-with | !ends-with | != } url_name
      tls sni { contains | starts-with | ends-with | = | !contains |
!starts-with | !ends-with | != } sni_identity
    ruledef ruledef_name
      ip server-ip-address host_poolname
      tcp either-port port-map port_mapname
      http-tls url-sni-pool pool_name
    end
```

**Note**

- The system configures the ruledef with the default all-lines AND option or **multi-line-or-all-lines** option.
- When the **url-sni-pool** rule line is configured, the URL or SNI value is always matched regardless of the AND or OR match operation.
- When the AND operation is configured, all the other rule lines is matched in addition to the URL or SNI value in the pool.
 - The AND operation is the default configuration.
- After configuring the OR operation, the system matches the following values for the rule action to take effect:
 - Any one of the other rule lines.
 - URL or SNI

Verifying the L3, L4, and L7 Rule Combination in Ruledef Feature Configuration

Use the following show CLI commands to verify the url-sni-pool configuration.

- On Control Plane: **show configuration active-charging service name** *service_name*

For example, the following is a partial output of the show CLI command:

```
url-sni-pool url_pool1
    http url contains google.com
    tls sni contains gmail.com
```

- On User Plane: **show user-plane-service url-sni-pool name** *pool_name*

For example, the following is a partial output of the show CLI command:

```
url-sni-pool url_pool1
    http url contains google.com
    tls sni contains gmail.com
```

```
Total url-pool(s) found: 1
```

Monitoring and Troubleshooting

Show commands and Outputs

This section provides information about the show CLI commands available in support of the feature.

show configuration active-charging service name <service_name>

Use this CLI command in Control Plane to display the url-sni-pool attachment to the ruledef.

The following is a partial sample output:

```
ruledef special_charging_group1
  ip server-ip-address range host-pool IP_FREE_MUSIC
  tcp either-port range port-map PORT_FREE_MUSIC
  http-tls url-sni-pool url_pool1
```

show user-plane-service ruledef name <ruledef_name>

Use this show CLI command in User Plane to display the url-sni-pool attachment to the ruledef.

The following is a partial sample output:

```
Ruledef Name: special_charging_group1
  ip server-ip-address range host-pool IP_FREE_MUSIC
  tcp either-port range port-map PORT_FREE_MUSIC
  Rule Application Type: Charging
  Copy Packet to Log: Disabled
  Tethered Flow Check: Disabled
  Attached Url-Sni-Pool: url_pool1
  Multi-line OR: Disabled
```

