



Appendix A: Post-Upgrade Checklist

First Published: March 6, 2013 Revised: June 10, 2013

The following checklist is useful after you upgrade your software on a Cisco StadiumVision Director server.

Checkoff **List Item** 1. Complete any specific verification steps documented for your particular upgrade. 2. Clear the browser cache. 3. Verify that the Control Panel shows the Cisco Stadium Vision Director version and build number that you installed. **4.** If you are using phone control, verify that the phones work. 5. If using IP phones for local TV control, verify that channels can be successfully changed. **6.** Verify that channel names and favorites are properly set. 7. If using suite commerce integration, verify that an order can be successfully placed using the IP phone. **8.** Verify that all devices are properly in the nonevent_group. 9. Go to the Services Alert window in the Management Dashboard and make sure that all relevant services are green. Tip You might need to click the refresh button to be sure that all services are re-polled for status. If needed, you can Disable services that are not part of your installation 10. Verify that all DMPs and TVs in the Management Dashboard are This step is for upgrades from Release 3.0 only. Note 11. Verify success of the content migration. See the "Validating the Content Migration" section on page 8.

| List Item | | Checkoff |
|--|--|----------|
| Note This step is for upgrades from Release 3.0 only. | | |
| 12. | Clean up and remove legacy VDM files. See the "Cleaning Up Legacy Video Files After Migration" section on page 9. | |
| 13. | Start an existing event script and validate that screens display the expected content. | |
| 14. | Stop the event script and validate that screens are powered off. | |
| 15. | Make a minor edit to the event script and make sure it can be saved. | |
| 16. | Verify that you can push a new video file in the CMS to the DMPs. | |
| 17. | If using dynamic menu boards, make a change to a menu item and verify that the change is reflected on the menu board. | |
| 18. | If using external content integration, be sure to re-enable your data sources in the Control Panel and restart the External Content Integration application from the Management Dashboard. | |
| 19. | Perform a server backup for the upgrade configuration. | |
| 20. | After satisfying your site's testing and event requirements, failback to the primary server and upgrade it to the same version of software that you validated on your secondary server. | |
| | For more information, see the "Configuring Failover Between Redundant Cisco Stadium Vision Director Servers" module in the Cisco Stadium Vision Director Server Administration Guide. | |
| 21. | After you perform failback, be sure that you reconfigure your backup and restore environment using the Text Utility Interface (TUI). | |
| 22. | (As needed for sites with a large volume of video content) Reduce the number of backups that are retained by the system. | |
| | For more information, see the "Backing Up and Restoring Cisco Stadium Vision Director Servers" module in the <i>Cisco Stadium Vision Director Server Administration Guide</i> . | |