



Managing Configuration Files

Last Updated: November 29, 2011

Creating, loading, and maintaining configuration files enable you to generate a set of user-configured commands to customize the functionality of your Cisco routing device. For a complete description of the configuration file management commands, refer to the *Cisco IOS Configuration Fundamentals Command Reference*.

- [Finding Feature Information, page 1](#)
- [Prerequisites for Managing Configuration Files, page 1](#)
- [Restrictions for Managing Configuration Files, page 2](#)
- [Information About Managing Configuration Files, page 2](#)
- [How to Manage Configuration File Information, page 9](#)
- [Additional References, page 45](#)

Finding Feature Information

Your software release may not support all the features documented in this module. For the latest feature information and caveats, see the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the Feature Information Table at the end of this document.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to www.cisco.com/go/cfn. An account on Cisco.com is not required.

Prerequisites for Managing Configuration Files

- You should have at least a basic familiarity with the Cisco IOS environment and the command-line interface.
- You should have at least a minimal configuration running on your system. You can create a basic configuration file using the **setup** command (see Using Setup Mode to Configure a Cisco Networking Device for details).



Americas Headquarters:
Cisco Systems, Inc., 170 West Tasman Drive, San Jose, CA 95134-1706 USA

Restrictions for Managing Configuration Files

- Many of the Cisco IOS commands described in this document are available and function only in certain configuration modes on the router.
- Some of the Cisco IOS configuration commands are only available on certain router platforms, and the command syntax may vary on different platforms.

Information About Managing Configuration Files

- [Types of Configuration Files](#), page 2
- [Configuration Mode and Selecting a Configuration Source](#), page 3
- [Configuration File Changes Using the CLI](#), page 3
- [Location of Configuration Files](#), page 3
- [Copy Configuration Files from a Network Server to the Router](#), page 3
- [Configuration Files Larger than NVRAM](#), page 7
- [Control of the Parser Cache](#), page 8
- [Configure the Router to Download Configuration Files](#), page 8

Types of Configuration Files

Configuration files contain the Cisco IOS software commands used to customize the functionality of your Cisco routing device (router, access server, switch, and so on). Commands are parsed (translated and executed) by the Cisco IOS software when the system is booted (from the startup-config file) or when you enter commands at the CLI in a configuration mode.

Startup configuration files (startup-config) are used during system startup to configure the software. Running configuration files (running-config) contain the current configuration of the software. The two configuration files can be different. For example, you may want to change the configuration for a short time period rather than permanently. In this case, you would change the running configuration using the **configureterminal EXEC** command but not save the configuration using the **copyrunning-configstartup-config EXEC** command.

To change the running configuration, use the **configureterminal** command, as described in the “Modifying the Configuration File at the CLI” section. As you use the Cisco IOS configuration modes, commands generally are executed immediately and are saved to the running configuration file either immediately after you enter them or when you exit a configuration mode.

To change the startup configuration file, you can either save the running configuration file to the startup configuration using the **copyrunning-configstartup-config EXEC** command or copy a configuration file from a file server to the startup configuration (see the “Copying a Configuration File from a TFTP Server to the Router” section for more information).

Configuration Mode and Selecting a Configuration Source

To enter configuration mode on the router, enter the **configure** command at the privileged EXEC prompt. The Cisco IOS software responds with the following prompt asking you to specify the terminal, memory, or a file stored on a network server (network) as the source of configuration commands:

```
Configuring from terminal, memory, or network [terminal]?
```

Configuring from the terminal allows you to enter configuration commands at the command line, as described in the following section. Configuring from memory loads the startup configuration file. See the “Reexecuting the Configuration Commands in the Startup Configuration File” section for more information. Configuring from the network allows you to load and execute configuration commands over the network. See the “Copying a Configuration File from a TFTP Server to the Router” section for more information.

Configuration File Changes Using the CLI

The Cisco IOS software accepts one configuration command per line. You can enter as many configuration commands as you want. You can add comments to a configuration file describing the commands you have entered. Precede a comment with an exclamation point (!). Because comments are *not* stored in NVRAM or in the active copy of the configuration file, comments do not appear when you list the active configuration with the **show running-config** EXEC command. Comments do not display when you list the startup configuration with the **show startup-config** or **more nvram:startup-config** EXEC mode command. Comments are stripped out of the configuration file when it is loaded onto the router. However, you can list the comments in configuration files stored on a File Transfer Protocol (FTP), remote copy protocol (rcp), or Trivial File Transfer Protocol (TFTP) server. When you configure the software using the CLI, the software executes the commands as you enter them.

Location of Configuration Files

Configuration files are stored in the following locations:

- The running configuration is stored in RAM.
- On all platforms except the Class A Flash file system platforms, the startup configuration is stored in nonvolatile random-access memory (NVRAM).
- On Class A Flash file system platforms, the startup configuration is stored in the location specified by the CONFIG_FILE environment variable (see the “Specifying the CONFIG_FILE Environment Variable on Class A Flash File Systems” section). The CONFIG_FILE variable defaults to NVRAM and can be a file in the following file systems:
 - **nvram:** (NVRAM)
 - **bootflash:** (internal Flash memory)
 - **slot0:** (first PCMCIA slot)
 - **slot1:** (second PCMCIA slot)

Copy Configuration Files from a Network Server to the Router

You can copy configuration files from a TFTP, rcp, or FTP server to the running configuration or startup configuration of the router. You may want to perform this function for one of the following reasons:

- To restore a backed-up configuration file.

- To use the configuration file for another router. For example, you may add another router to your network and want it to have a similar configuration to the original router. By copying the file to the new router, you can change the relevant parts rather than re-creating the whole file.
- To load the same configuration commands on to all the routers in your network so that all the routers have similar configurations.

The `copy{ftp|rcp:tftp:system:running-configEXEC}` command loads the configuration files into the router as if you were typing the commands in at the command line. The router does not erase the existing running configuration before adding the commands. If a command in the copied configuration file replaces a command in the existing configuration file, the existing command will be erased. For example, if the copied configuration file contains a different IP address in a particular command than the existing configuration, the IP address in the copied configuration will be used. However, some commands in the existing configuration may not be replaced or negated. In this case, the resulting configuration file will be a mixture of the existing configuration file and the copied configuration file, with the copied configuration file having precedence.

In order to restore a configuration file to an exact copy of a file stored on a server, you need to copy the configuration file directly to the startup configuration (using the `copyftp|rcp:tftp:} nvram:startup-config` command) and reload the router.

To copy configuration files from a server to a router, perform the tasks described in the following sections:

The protocol you use depends on which type of server you are using. The FTP and rcp transport mechanisms provide faster performance and more reliable delivery of data than TFTP. These improvements are possible because the FTP and rcp transport mechanisms are built on and use the TCP/IP stack, which is connection-oriented.

- [Copy a Configuration File from the Router to a TFTP Server, page 4](#)
- [Copy a Configuration File from the Router to an rcp Server, page 4](#)
- [Copy a Configuration File from the Router to an FTP Server, page 6](#)

Copy a Configuration File from the Router to a TFTP Server

In some implementations of TFTP, you must create a dummy file on the TFTP server and give it read, write, and execute permissions before copying a file over it. Refer to your TFTP documentation for more information.

Copy a Configuration File from the Router to an rcp Server

You can copy configuration file from the router to an rcp server.

One of the first attempts to use the network as a resource in the UNIX community resulted in the design and implementation of the remote shell protocol, which included the remote shell (rsh) and remote copy (rcp) functions. Rsh and rcp give users the ability to execute commands remotely and copy files to and from a file system residing on a remote host or server on the network. The Cisco implementation of rsh and rcp interoperates with standard implementations.

The rcp `copy` commands rely on the rsh server (or daemon) on the remote system. To copy files using rcp, you need not create a server for file distribution, as you do with TFTP. You need only to have access to a server that supports the remote shell (rsh). (Most UNIX systems support rsh.) Because you are copying a file from one place to another, you must have read permission on the source file and write permission on the destination file. If the destination file does not exist, rcp creates it for you.

Although the Cisco rcp implementation emulates the functions of the UNIX rcp implementation--copying files among systems on the network--the Cisco command syntax differs from the UNIX rcp command syntax. The Cisco rcp support offers a set of `copy` commands that use rcp as the transport mechanism.

These `rcp copy` commands are similar in style to the Cisco TFTP `copy` commands, but they offer an alternative that provides faster performance and reliable delivery of data. These improvements are possible because the `rcp` transport mechanism is built on and uses the TCP/IP stack, which is connection-oriented. You can use `rcp` commands to copy system images and configuration files from the router to a network server and vice versa.

You also can enable `rcp` support to allow users on remote systems to copy files to and from the router.

To configure the Cisco IOS software to allow remote users to copy files to and from the router, use the `iprcmdrcp-enable` global configuration command.

- [Restrictions, page 5](#)
- [Requirements for the rcp Username, page 5](#)

Restrictions

The `rcp` protocol requires a client to send a remote username on each `rcp` request to a server. When you copy a configuration file from the router to a server using `rcp`, the Cisco IOS software sends the first valid username it encounters in the following sequence:

- 1 The username specified in the `copy EXEC` command, if a username is specified.
- 2 The username set by the `iprcmdremote-username` global configuration command, if the command is configured.
- 3 The remote username associated with the current `tty` (terminal) process. For example, if the user is connected to the router through Telnet and was authenticated through the `username` command, the router software sends the Telnet username as the remote username.
- 4 The router host name.

For the `rcp copy` request to execute successfully, an account must be defined on the network server for the remote username. If the server has a directory structure, the configuration file or image is written to or copied from the directory associated with the remote username on the server. For example, if the system image resides in the home directory of a user on the server, you can specify that user name as the remote username.

Use the `iprcmdremote-username` command to specify a username for all copies. (`Rcmd` is a UNIX routine used at the super-user level to execute commands on a remote machine using an authentication scheme based on reserved port numbers. `Rcmd` stands for “remote command”). Include the username in the `copy` command if you want to specify a username for that copy operation only.

If you are writing to the server, the `rcp` server must be properly configured to accept the `rcp` write request from the user on the router. For UNIX systems, you must add an entry to the `.rhosts` file for the remote user on the `rcp` server. For example, suppose the router contains the following configuration lines:

```
hostname Rtr1
ip rcmd remote-username User0
```

If the router IP address translates to `Router1.company.com`, then the `.rhosts` file for `User0` on the `rcp` server should contain the following line:

```
Router1.company.com Rtr1
```

Requirements for the rcp Username

The `rcp` protocol requires a client to send a remote username on each `rcp` request to a server. When you copy a configuration file from the router to a server using `rcp`, the Cisco IOS software sends the first valid username it encounters in the following sequence:

- 1 The username specified in the **copy EXEC** command, if a username is specified.
- 2 The username set by the **iprcmdremote-username** global configuration command, if the command is configured.
- 3 The remote username associated with the current tty (terminal) process. For example, if the user is connected to the router through Telnet and was authenticated through the **username** command, the router software sends the Telnet username as the remote username.
- 4 The router host name.

For the rcp copy request to execute, an account must be defined on the network server for the remote username. If the server has a directory structure, the configuration file or image is written to or copied from the directory associated with the remote username on the server. For example, if the system image resides in the home directory of a user on the server, specify that user name as the remote username.

Refer to the documentation for your rcp server for more information.

Copy a Configuration File from the Router to an FTP Server

You can copy a configuration file from the router to an FTP server.

- [Understanding the FTP Username and Password, page 6](#)

Understanding the FTP Username and Password

The FTP protocol requires a client to send a remote username and password on each FTP request to a server. When you copy a configuration file from the router to a server using FTP, the Cisco IOS software sends the first valid username it encounters in the following sequence:

- 1 The username specified in the **copy EXEC** command, if a username is specified.
- 2 The username set by the **ipftpusername** global configuration command, if the command is configured.
- 3 Anonymous.

The router sends the first valid password it encounters in the following sequence:

- 1 The password specified in the **copy** command, if a password is specified.
- 2 The password set by the **ipftppassword** command, if the command is configured.
- 3 The router forms a password *username @routename .domain* . The variable *username* is the username associated with the current session, *routename* is the configured host name, and *domain* is the domain of the router.

The username and password must be associated with an account on the FTP server. If you are writing to the server, the FTP server must be properly configured to accept the FTP write request from the user on the router.

If the server has a directory structure, the configuration file or image is written to or copied from the directory associated with the username on the server. For example, if the system image resides in the home directory of a user on the server, specify that user name as the remote username.

Refer to the documentation for your FTP server for more information.

Use the **ipftpusername** and **ipftppassword** global configuration commands to specify a username and password for all copies. Include the username in the **copy EXEC** command if you want to specify a username for that copy operation only.

Configuration Files Larger than NVRAM

To maintain a configuration file that exceeds size of NVRAM, you should be aware of the information in the following sections:

- [Compressing the Configuration File, page 7](#)
- [Storing the Configuration in Flash Memory on Class A Flash File Systems, page 7](#)
- [Loading the Configuration Commands from the Network, page 7](#)

Compressing the Configuration File

The **servicecompress-config** global configuration command specifies that the configuration file be stored compressed in NVRAM. Once the configuration file has been compressed, the router functions normally. When the system is booted, it recognizes that the configuration file is compressed, expands it, and proceeds normally. The **morenvram:startup-config** EXEC command expands the configuration before displaying it.

Before you compress configuration files, refer to the appropriate hardware installation and maintenance publication. Verify that your system's ROMs support file compression. If not, you can install new ROMs that support file compression.

The size of the configuration must not exceed three times the NVRAM size. For a 128-KB size NVRAM, the largest expanded configuration file size is 384 KB.

The **servicecompress-config** global configuration command works only if you have Cisco IOS software Release 10 or later release boot ROMs. Installing new ROMs is a one-time operation and is necessary only if you do not already have Cisco IOS Release 10 in ROM. If the boot ROMs do not recognize a compressed configuration, the following message is displayed:

```
Boot ROMs do not support NVRAM compression Config NOT written to NVRAM
```

Storing the Configuration in Flash Memory on Class A Flash File Systems

On Class A Flash file system routers, you can store the startup configuration in Flash memory by setting the CONFIG_FILE environment variable to a file in internal Flash memory or Flash memory in a PCMCIA slot.

See the "Specifying the CONFIG_FILE Environment Variable on Class A Flash File Systems" section for more information.

Care must be taken when editing or changing a large configuration. Flash memory space is used every time a **copysystem:running-confignvram:startup-config** EXEC command is issued. Because file management for Flash memory, such as optimizing free space, is not done automatically, you must pay close attention to available Flash memory. Use the **squeeze** command to reclaim used space. We recommend that you use a large-capacity Flash card of at least 20 MB.

Loading the Configuration Commands from the Network

You can also store large configurations on FTP, rcp, or TFTP servers and download them at system startup. To use a network server to store large configurations, see the "Copying a Configuration File from the Router to a TFTP Server" and "Configure the Router to Download Configuration Files" sections for more information on these commands.

Control of the Parser Cache

The Cisco IOS command-line parser in the Cisco IOS software performs the translation and execution (parsing) of command lines. The Parser Cache feature was developed to rapidly process large configuration files, thereby dramatically improving load time.

The Parser Cache feature allows the rapid recognition and translation of configuration lines in a configuration file that differ slightly from previously used configuration lines (for example, pvc 0/100, pvc 0/101, and so on) by dynamically creating, caching, and reusing simplified parse graphs. This improvement is useful primarily for configuration files that repeat similar commands hundreds or thousands of times, such as cases in which thousands of virtual circuits must be configured for subinterfaces, or hundreds of access lists must be configured. Performance will improve the most for those files in which the same commands are used repeatedly but the numerical arguments change from command to command.

The Parser Cache is enabled by default on all platforms using Cisco IOS Release 12.1(5)T and later releases. However, users with Cisco devices that do not require large configuration files may want to disable the Parser Cache to free the resources used by this feature. (Memory used by this feature depends on the size of the configuration files parsed, but is generally less than 512 KB.)

There are several ways to control the parser cache (these are all optional):

- Clearing the Parser Cache--To free resources or to reset the parser cache memory, you may wish to clear the parse entries and hit/miss statistics stored by the Parser Cache feature
- Disabling the Parser Cache--The Parser Cache feature is enabled by default. To disable the Parser Cache feature, use the `no parser cache` command in global configuration mode. When the parser cache is disabled, the `no parser cache` command line is written to the running configuration file. If you wish to disable the parser cache to free system resources, you should clear the parser cache before issuing the `no parser cache` command. You will not be able to clear the parser cache after disabling it.
- Reenabling the Parser Cache--To reenabling the Parser Cache feature after disabling it, use the `parser cache` command in global configuration mode
- Monitoring the Parser--Statistics about the last configuration file parsed are kept in the system memory, along with hit/miss statistics on the commands parsed by the Parser Cache feature. "Hits" and "misses" refer to the matches that the parser cache was able to make to similar commands used previously in the configuration session. Those commands that are matched ("hits") be parsed more efficiently. The parser cache cannot improve the parse time for those commands it was unable to match ("misses").

Configure the Router to Download Configuration Files

You can configure the router to load one or two configuration files at system startup. The configuration files are loaded into memory and read in as if you were typing the commands at the command line. Thus, the configuration for the router will be a mixture of the original startup configuration and the one or two downloaded configuration files.

- [Network Versus Host Configuration Files, page 8](#)

Network Versus Host Configuration Files

For historical reasons, the first file the router downloads is called the network configuration file. The second file the router downloads is called the host configuration file. Two configuration files can be used when all of the routers on a network use many of the same commands. The network configuration file contains the standard commands used to configure all of the routers. The host configuration files contain the commands specific to one particular host. If you are loading two configuration files, the host

configuration file should be the configuration file you want to have precedence over the other file. Both the network and host configuration files must reside on a network server reachable via TFTP, rcp, or FTP, and must be readable.

How to Manage Configuration File Information

- [Displaying Configuration File Information, page 9](#)
- [Modifying the Configuration File at the CLI, page 10](#)
- [Copying a Configuration File from the Router to a TFTP Server, page 12](#)
- [Copying a Configuration File from the Router to an rcp Server, page 13](#)
- [Copying a Configuration File from the Router to the FTP Server, page 16](#)
- [Copying a Configuration File from a TFTP Server to the Router, page 18](#)
- [Copying a Configuration File from the rcp Server to the Router, page 19](#)
- [Copying a Configuration File from an FTP Server to the Router, page 22](#)
- [Maintaining Configuration Files Larger than NVRAM, page 24](#)
- [Managing the Parser Cache, page 29](#)
- [Copying Configuration Files from Flash Memory to the Startup or Running Configuration, page 32](#)
- [Copying Configuration Files Between Flash Memory File Systems, page 32](#)
- [Copying a Configuration File from an FTP Server to Flash Memory Devices, page 34](#)
- [Copying a Configuration File from an rcp Server to Flash Memory Devices, page 35](#)
- [Copying a Configuration File from a TFTP Server to Flash Memory Devices, page 37](#)
- [Reexecuting the Configuration Commands in the Startup Configuration File, page 37](#)
- [Clearing the Startup Configuration, page 38](#)
- [Deleting a Specified Configuration File, page 39](#)
- [Specifying the CONFIG_FILE Environment Variable on Class A Flash File Systems, page 39](#)
- [Configuring the Router to Download Configuration Files, page 41](#)

Displaying Configuration File Information

To display information about configuration files, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **show bootvar**
3. **more *file-url***
4. **show running-config**
5. **show startup-config**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>show bootvar</code></p> <p>Example:</p> <pre>Router# show bootvar</pre>	<p>Lists the contents of the BOOT environment variable, the name of the configuration file pointed to by the CONFIG_FILE environment variable, and the contents of the BOOTLDR environment variable.</p>
<p>Step 3 <code>more file-url</code></p> <p>Example:</p> <pre>Router# more 10.1.1.1</pre>	<p>Displays the contents of a specified file.</p>
<p>Step 4 <code>show running-config</code></p> <p>Example:</p> <pre>Router# show running-config</pre>	<p>Displays the contents of the running configuration file. (Command alias for themoresystem:running-config command.)</p>
<p>Step 5 <code>show startup-config</code></p> <p>Example:</p> <pre>Router# show startup-config</pre>	<p>Displays the contents of the startup configuration file. (Command alias for the morenvram:startup-config command.)</p> <p>On all platforms except the Class A Flash file system platforms, the default startup-config file usually is stored in NVRAM. On the Class A Flash file system platforms, the CONFIG_FILE environment variable points to the default startup-config file. The CONFIG_FILE variable defaults to NVRAM.</p>

Modifying the Configuration File at the CLI

The Cisco IOS software accepts one configuration command per line. You can enter as many configuration commands as you want. You can add comments to a configuration file describing the commands you have entered. Precede a comment with an exclamation point (!). Because comments are *not* stored in NVRAM or in the active copy of the configuration file, comments do not appear when you list the active configuration with the **showrunning-config** or **moresystem:running-config** EXEC command. Comments do not display when you list the startup configuration with the **showstartup-config** or **morenvram:startup-config** EXEC mode command. Comments are stripped out of the configuration file when it is loaded onto the router. However, you can list the comments in configuration files stored on a File Transfer Protocol (FTP), remote copy protocol (rcp), or Trivial File Transfer Protocol (TFTP) server. When you configure the software using the CLI, the software executes the commands as you enter them. To configure the software using the CLI, use the following commands beginning in privileged EXEC mode:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **configuration command**
4. Do one of the following:
 - **end**
 - **^Z**
5. **copy system:running-config nvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3 configuration command Example: Router(config)# configuration command	Enter the necessary configuration commands. The Cisco IOS documentation set describes configuration commands organized by technology.
Step 4 Do one of the following: <ul style="list-style-type: none"> • end • ^Z Example: Router(config)# end	Ends the configuration session and exits to EXEC mode. Note When you press the Ctrl and Z keys simultaneously, ^Z is displayed to the screen.

Command or Action	Purpose
<p>Step 5 <code>copy system:running-config nvram:startup-config</code></p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	<p>Saves the running configuration file as the startup configuration file.</p> <p>You may also use the <code>copyrunning-configstartup-config</code> command alias, but you should be aware that this command is less precise. On most platforms, this command saves the configuration to NVRAM. On the Class A Flash file system platforms, this step saves the configuration to the location specified by the <code>CONFIG_FILE</code> environment variable (the default <code>CONFIG_FILE</code> variable specifies that the file should be saved to NVRAM).</p>

Examples

In the following example, the router prompt name of the router is configured. The comment line, indicated by the exclamation mark (!), does not execute any command. The `hostname` command is used to change the router name from Router to `new_name`. By pressing Ctrl-Z (^Z) or entering the `end` command, the user quits configuration mode. The `copysystem:running-confignvram:startup-config` command saves the current configuration to the startup configuration.

```
Router# configure terminal
Router(config)# !The following command provides the router host name.
Router(config)# hostname new_name
new_name(config)# end
new_name# copy system:running-config nvram:startup-config
```

When the startup configuration is NVRAM, it stores the current configuration information in text format as configuration commands, recording only nondefault settings. The memory is checksummed to guard against corrupted data.



Note

Some specific commands might not get saved to NVRAM. You will need to enter these commands again if you reboot the machine. These commands are noted in the documentation. We recommend that you keep a list of these settings so that you can quickly reconfigure your router after rebooting.

Copying a Configuration File from the Router to a TFTP Server

To copy configuration information on a TFTP network server, complete the tasks in this section:

SUMMARY STEPS

1. `enable`
2. `copy system:running-config tftp: [[[//location]/directory]/filename]`
3. `copy nvram:startup-config tftp: [[[//location]/directory]/filename]`

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>copy system:running-config tftp: [[[//location]/directory]/filename]</code></p> <p>Example:</p> <pre>Router# copy system:running-config tftp: //server1/topdir/file10</pre>	<p>Copies the running configuration file to a TFTP server.</p>
<p>Step 3 <code>copy nvram:startup-config tftp: [[[//location]/directory]/filename]</code></p> <p>Example:</p> <pre>Router# copy nvram:startup-config tftp: //server1/1stidir/file10</pre>	<p>Copies the startup configuration file to a TFTP server.</p>

Examples

The following example copies a configuration file from a router to a TFTP server:

```
Tokyo# copy system:running-config tftp://172.16.2.155/tokyo-config
Write file tokyo-config on host 172.16.2.155? [confirm] y
Writing tokyo-config!!! [OK]
```

- [What to Do Next, page 13](#)

What to Do Next

After you have issued the **copy** command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the **copy** command and the current setting of the **fileprompt** global configuration command.

Copying a Configuration File from the Router to an rcp Server

To copy a startup configuration file or a running configuration file from the router to an rcp server, use the following commands beginning in privileged EXEC mode:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip rcmd remote-username *username***
4. **end**
5. Do one of the following:
 - **copy system:running-config rcp: [[[/[/[*username*@]*location*]/*directory*]/*filename*]**
 - **copy nvram:sta rtup-config rcp :[[[/[/[*username*@]*location*]/*directory*]/*filename*]**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 ip rcmd remote-username <i>username</i></p> <p>Example:</p> <pre>Router(config)# ip rcmd remote-username user1</pre>	<p>(Optional) Changes the default remote username.</p>
<p>Step 4 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>(Optional) Exits global configuration mode.</p>

Command or Action	Purpose
<p>Step 5 Do one of the following:</p> <ul style="list-style-type: none"> • copy system:running-config rcp: [[[//[username@]location]/directory]/filename] • copy nvram:startup-config rcp : [[[//[username@]location]/directory]/filename] <p>Example:</p> <pre>Router# copy system:running-config rcp: //user1@company.com/ dir-files/file1</pre>	<p>Specifies that the router running configuration file be stored on an rcp server.</p> <p>or</p> <p>Specifies that the router startup configuration file be stored on an rcp server.</p>

- [Examples, page 15](#)
- [What to Do Next, page 15](#)

Examples

- [Storing a Running Configuration File on an rcp Server, page 15](#)
- [Storing a Startup Configuration File on an rcp Server, page 15](#)

Storing a Running Configuration File on an rcp Server

The following example copies the running configuration file named rtr2-config to the netadmin1 directory on the remote host with an IP address of 172.16.101.101:

```
Router# copy system:running-config rcp://netadmin1@172.16.101.101/Rtr2-config
Write file rtr2-config on host 172.16.101.101?[confirm]
Building configuration...[OK]
Connected to 172.16.101.101
Router#
```

Storing a Startup Configuration File on an rcp Server

The following example shows how to store a startup configuration file on a server by using rcp to copy the file:

```
Rtr2# configure terminal
Rtr2(config)# ip rcmd remote-username netadmin2
Rtr2(config)# end
Rtr2# copy nvram:startup-config rcp:
Remote host[]? 172.16.101.101
Name of configuration file to write [rtr2-config]?
Write file rtr2-config on host 172.16.101.101?[confirm]
![OK]
```

What to Do Next

After you have issued the **copy EXEC** command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the **copy** command and the current setting of the **fileprompt** global configuration command.

Copying a Configuration File from the Router to the FTP Server

To copy a startup configuration file or a running configuration file from the router to an FTP server, complete the following tasks:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip ftp username *username***
4. **ip ftp password *password***
5. **end**
6. Do one of the following:
 - **copy system:running-config ftp:** [[[/*username* [:*password*]@]*location/directory*]/*filename*]
 -
 -
 - **copy nvram:startup-config ftp:** [[[/*username* [:*password*]@]*location/directory*]/*filename*]

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 configure terminal Example: Router# configure terminal	Enters global configuration mode.
Step 3 ip ftp username <i>username</i> Example: Router(config)# ip ftp username user1	(Optional) Specifies the default remote username.

Command or Action	Purpose
<p>Step 4 <code>ip ftp password <i>password</i></code></p> <p>Example:</p> <pre>Router(config)# ip ftp username guessme</pre>	(Optional) Specifies the default password.
<p>Step 5 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	(Optional) Exits global configuration mode. This step is required only if you override the default remote username or password (see Steps 2 and 3).
<p>Step 6 Do one of the following:</p> <ul style="list-style-type: none"> • copy system:running-config ftp: <code>[[[//[<i>username</i>][:<i>password</i>]@]<i>location/directory</i>]/<i>filename</i>]</code> • • copy nvram:startup-config ftp: <code>[[[//[<i>username</i>][:<i>password</i>]@]<i>location/directory</i>]/<i>filename</i>]</code> <p>Example:</p> <pre>Router# copy system:running-config ftp: // user1:guessme@company.com /dir10/file1</pre>	Copies the running configuration or startup configuration file to an FTP server.

- [Examples, page 17](#)
- [What to Do Next, page 18](#)

Examples

- [Storing a Running Configuration File on an FTP Server, page 17](#)
- [Storing a Startup Configuration File on an FTP Server, page 17](#)

Storing a Running Configuration File on an FTP Server

The following example copies the running configuration file named rtr2-confg to the netadmin1 directory on the remote host with an IP address of 172.16.101.101:

```
Router# copy system:running-config ftp://netadmin1:mypass@172.16.101.101/Rtr2-confg
Write file rtr2-confg on host 172.16.101.101?[confirm]
Building configuration...[OK]
Connected to 172.16.101.101
Router#
```

Storing a Startup Configuration File on an FTP Server

The following example shows how to store a startup configuration file on a server by using FTP to copy the file:

```
Rtr2# configure terminal
Rtr2(config)# ip ftp username netadmin2
Rtr2(config)# ip ftp password mypass
Rtr2(config)# end
Rtr2# copy nvram:startup-config ftp:
Remote host[]? 172.16.101.101
Name of configuration file to write [rtr2-config]?
Write file rtr2-config on host 172.16.101?[confirm]
![OK]
```

What to Do Next

After you have issued the **copy EXEC** command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the **copy** command and the current setting of the **fileprompt** global configuration command.

Copying a Configuration File from a TFTP Server to the Router

To copy a configuration file from a TFTP server to the router, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **copy tftp: [[[location]/directory]/filename] system:running-config**
3. **copy tftp: [[[location]/directory]/filename] nvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 copy tftp: [[[location]/directory]/filename] system:running-config Example: Router# copy tftp://server1/dir10/datasource system:running-config	Copies a configuration file from a TFTP server to the running configuration.

Command or Action	Purpose
<p>Step 3 <code>copy tftp: [location]/directory]/filename] nvram:startup-config</code></p> <p>Example:</p> <pre>Router# copy tftp://server1/dir10/datasource nvram:startup-config</pre>	<p>Copies a configuration file from a TFTP server to the startup configuration.</p>

Examples

In the following example, the software is configured from the file named tokyo-config at IP address 172.16.2.155:

```
Router1# copy tftp://172.16.2.155/tokyo-config system:running-config
Configure using tokyo-config from 172.16.2.155? [confirm] y
Booting tokyo-config from 172.16.2.155:!!! [OK - 874/16000 bytes]
```

- [What to Do Next, page 19](#)

What to Do Next

After you have issued the **copy EXEC** command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the **copy** command and the current setting of the **fileprompt** global configuration command.

Copying a Configuration File from the rcp Server to the Router

To copy a configuration file from an rcp server to the running configuration or startup configuration, complete the following tasks:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip rcmd remote-username** *username*
4. **end**
5. **copy rep:** [][username@]location]/directory]/filename]system:running-config

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>(Optional) Enters configuration mode from the terminal. This step is required only if you override the default remote username (see Step 3).</p>
<p>Step 3 <code>ip rcmd remote-username <i>username</i></code></p> <p>Example:</p> <pre>Router(config)# ip rcmd remote-username user1</pre>	<p>(Optional) Specifies the remote username.</p>
<p>Step 4 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>(Optional) Exits global configuration mode. This step is required only if you override the default remote username (see Step 2).</p>

Command or Action	Purpose
<p>Step 5 <code>copy rcp: [[[//[username@]location]/directory]/filename]system:running-config</code></p> <p>Example:</p> <p>Example:</p> <p>or</p> <p>Example:</p> <pre> copy rcp:[[[//[username@]location]/directory]/filename] nvram:startup-config </pre> <p>Example:</p> <pre> Router# copy rcp://[user1@company.com/dir10/fileone] nvram:s tartup-config </pre>	<p>Copies the configuration file from a rcp server to the running configuration or startup configuration.</p>

- [Examples, page 21](#)
- [What to Do Next, page 22](#)

Examples

- [Copy rcp Running-Config, page 21](#)
- [Copy rcp Startup-Config, page 21](#)

Copy rcp Running-Config

The following example copies a configuration file named host1-config from the netadmin1 directory on the remote server with an IP address of 172.16.101.101, and loads and runs those commands on the router:

```

Router# copy rcp://netadmin1@172.16.101.101/host1-config system:running-config
Configure using host1-config from 172.16.101.101? [confirm]
Connected to 172.16.101.101
Loading 1112 byte file host1-config:[OK]
Router#
%SYS-5-CONFIG: Configured from host1-config by rcp from 172.16.101.101
                    
```

Copy rcp Startup-Config

The following example specifies a remote username of `netadmin1`. Then it copies the configuration file named `host2-config` from the `netadmin1` directory on the remote server with an IP address of `172.16.101.101` to the startup configuration.

```
Rtr2# configure terminal
Rtr2(config)# ip rcmd remote-username netadmin1
Rtr2(config)# end
Rtr2# copy rcp: nvram:startup-config
Address of remote host [255.255.255.255]? 172.16.101.101
Name of configuration file[rtr2-config]? host2-config
Configure using host2-config from 172.16.101.101?[confirm]
Connected to 172.16.101.101
Loading 1112 byte file host2-config:[OK]
[OK]
Rtr2#
%SYS-5-CONFIG_NV:Non-volatile store configured from host2-config by rcp from
172.16.101.101
```

What to Do Next

After you have issued the `copy EXEC` command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the `copy` command and the current setting of the `fileprompt` global configuration command.

Copying a Configuration File from an FTP Server to the Router

To copy a configuration file from an FTP server to the running configuration or startup configuration, complete the tasks in this section:

SUMMARY STEPS

1. `enable`
2. `configure terminal`
3. `ip ftp username username`
4. `ip ftp password password`
5. `end`
6. `copy ftp: [[[/username [:password]@]location]/directory]/filename]system:running-config`

DETAILED STEPS

Command or Action	Purpose
Step 1 <code>enable</code> Example: Router> <code>enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 <code>configure terminal</code> Example: Router# <code>configure terminal</code>	(Optional) Allows you to enter global configuration mode. This step is required only if you want to override the default remote username or password (see Steps 2 and 3).

Command or Action	Purpose
<p>Step 3 <code>ip ftp username <i>username</i></code></p> <p>Example:</p> <pre>Router(config)# ip ftp username user1</pre>	(Optional) Specifies the default remote username.
<p>Step 4 <code>ip ftp password <i>password</i></code></p> <p>Example:</p> <pre>Router(config)# ip ftp password guessme</pre>	(Optional) Specifies the default password.
<p>Step 5 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	(Optional) Exits global configuration mode. This step is required only if you override the default remote username or password (see Steps 2 and 3).
<p>Step 6 <code>copy ftp: [[[/[<i>username</i> [:<i>password</i>]@]<i>location</i>]/<i>directory</i>]/<i>filename</i>]system:running-config</code></p> <p>Example:</p> <p>Example:</p> <p>or</p> <p>Example:</p> <pre>copy ftp:[[/[<i>username</i> [:<i>password</i>]@]<i>location/directory</i>]/<i>filename</i>] nvram:startup-config</pre> <p>Example:</p> <pre>Router# copy ftp://user1:guessme@company.com /dir10/ datasource nvram:startup-config</pre>	Using FTP, copies the configuration file from a network server to running memory or the startup configuration.

- [Examples, page 23](#)
- [What to Do Next, page 24](#)

Examples

- [Copy FTP Running-Config, page 24](#)
- [Copy FTP Startup-Config, page 24](#)

Copy FTP Running-Config

The following example copies a host configuration file named `host1-config` from the `netadmin1` directory on the remote server with an IP address of `172.16.101.101`, and loads and runs those commands on the router:

```
Router# copy rcp://netadmin1:mypass@172.16.101.101/host1-config system:running-config

Configure using host1-config from 172.16.101.101? [confirm]
Connected to 172.16.101.101
Loading 1112 byte file host1-config:[OK]
Router#
%SYS-5-CONFIG: Configured from host1-config by ftp from 172.16.101.101
```

Copy FTP Startup-Config

The following example specifies a remote username of `netadmin1`. Then it copies the configuration file named `host2-config` from the `netadmin1` directory on the remote server with an IP address of `172.16.101.101` to the startup configuration.

```
Rtr2# configure terminal
Rtr2(config)# ip ftp username
netadmin1
Rtr2(config)# ip ftp password
mypass
Rtr2(config)# end
Rtr2# copy ftp: nvram:startup-config
Address of remote host [255.255.255.255]? 172.16.101.101
Name of configuration file[rtr2-config]? host2-config
Configure using host2-config from 172.16.101.101?[confirm]
Connected to 172.16.101.101
Loading 1112 byte file host2-config:[OK]
[OK]
Rtr2#
%SYS-5-CONFIG_NV:Non-volatile store configured from host2-config by ftp from
172.16.101.101
```

What to Do Next

After you have issued the `copy EXEC` command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the `copy` command and the current setting of the `fileprompt` global configuration command.

Maintaining Configuration Files Larger than NVRAM

To maintain a configuration file that exceeds size of NVRAM, perform the tasks described in the following sections:

- [Compressing the Configuration File, page 24](#)
- [Storing the Configuration in Flash Memory on Class A Flash File Systems, page 26](#)
- [Loading the Configuration Commands from the Network, page 28](#)

Compressing the Configuration File

To compress configuration files, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **service compress-config**
4. **end**
5. Do one of the following:
 - Use FTP, rcp, or TFTP to copy the new configuration.
 - **configure terminal**
6. **copy system:running-config nvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 service compress-config</p> <p>Example:</p> <pre>Router(config)# service compress-config</pre>	<p>Specifies that the configuration file be compressed.</p>
<p>Step 4 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode.</p>
<p>Step 5 Do one of the following:</p> <ul style="list-style-type: none"> • Use FTP, rcp, or TFTP to copy the new configuration. • configure terminal <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters the new configuration:</p> <ul style="list-style-type: none"> • If you try to load a configuration that is more than three times larger than the NVRAM size, the following error message is displayed: <p>“[buffer overflow - <i>file-size</i> /<i>buffer-size</i> bytes].”</p>

Command or Action	Purpose
Step 6 <code>copy system:running-config nvram:startup-config</code> Example: <pre>Router(config)# copy system:running-config nvram:startup-config</pre>	When you have finished changing the running-configuration, saves the new configuration.

Examples

The following example compresses a 129-KB configuration file to 11 KB:

```
Router# configure terminal
Router(config)# service compress-config
Router(config)# end
Router# copy tftp://172.16.2.15/tokyo-config system:running-config
Configure using tokyo-config from 172.16.2.155? [confirm] y
Booting tokyo-config from 172.16.2.155:!!! [OK - 874/16000 bytes]
Router# copy system:running-config nvram:startup-config

Building configuration...
Compressing configuration from 129648 bytes to 11077 bytes
[OK]
```

Storing the Configuration in Flash Memory on Class A Flash File Systems

To store the startup configuration in Flash memory, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **copy nvram:startup-config** *flash-filesystem:filename*
3. **configure terminal**
4. **boot config flash-filesystem:** *filename*
5. **end**
6. Do one of the following:
 - Use FTP, rcp, or TFTP to copy the new configuration. If you try to load a configuration that is more than three times larger than the NVRAM size, the following error message is displayed:
 - “[buffer overflow - *file-size* /*buffer-size* bytes] . ”
 - **configure terminal**
7. **copy system:running-config nvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>copy nvram:startup-config flash-filesystem:filename</code></p> <p>Example:</p> <pre>Router# copy nvram:startup-config slot0:router-config</pre>	<p>Copies the current startup configuration to the new location to create the configuration file.</p>
<p>Step 3 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 4 <code>boot config flash-filesystem: filename</code></p> <p>Example:</p> <pre>Router(config)# boot config slot0:router-config</pre>	<p>Specifies that the startup configuration file be stored in Flash memory by setting the CONFIG_FILE variable.</p>
<p>Step 5 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode.</p>
<p>Step 6 Do one of the following:</p> <ul style="list-style-type: none"> • Use FTP, rcp, or TFTP to copy the new configuration. If you try to load a configuration that is more than three times larger than the NVRAM size, the following error message is displayed: • “[buffer overflow - file-size /buffer-size bytes] .” • configure terminal <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters the new configuration.</p>

Command or Action	Purpose
Step 7 <code>copy system:running-config nvram:startup-config</code> Example: <pre>Router(config)# copy system:running-config nvram:startup-config</pre>	When you have finished changing the running-configuration, saves the new configuration.

Examples

The following example stores the configuration file in slot 0:

```
Router# copy nvram:startup-config slot0:router-config
Router# configure terminal
Router(config)# boot config slot0:router-config
Router(config)# end
Router# copy system:running-config nvram:startup-config
```

Loading the Configuration Commands from the Network

To use a network server to store large configurations, complete the tasks in this section:

SUMMARY STEPS

1. `enable`
2. `copy system:running-config {ftp: | rcp: | tftp:}`
3. `configure terminal`
4. `boot network {ftp:[[//][username [:password]@]location]/directory]/filename] | rcp:[[//][username@]location]/directory]/filename] | tftp:[[//location]/directory]/filename }`
5. `service config`
6. `end`
7. `copy system:running-config nvram:startup-config`

DETAILED STEPS

Command or Action	Purpose
Step 1 <code>enable</code> Example: <pre>Router> enable</pre>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.

Command or Action	Purpose
<p>Step 2 <code>copy system:running-config {ftp: rcp: tftp: }</code></p> <p>Example:</p> <pre>Router# copy system:running-config ftp:</pre>	Saves the running configuration to an FTP, rcp, or TFTP server.
<p>Step 3 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	Enters global configuration mode.
<p>Step 4 <code>boot network {ftp:[[/[username [:password]@]location]/directory]/filename] rcp:[[/[username@]location]/directory]/filename] tftp:[[/[location]/directory]/filename]}</code></p> <p>Example:</p> <pre>Router(config)# boot network ftp://user1:guessme@company.com/dir10/file1</pre>	Specifies that the startup configuration file be loaded from the network server at startup.
<p>Step 5 <code>service config</code></p> <p>Example:</p> <pre>Router(config)# service config</pre>	Enables the router to download configuration files at system startup.
<p>Step 6 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	Exits global configuration mode.
<p>Step 7 <code>copy system:running-config nvram:startup-config</code></p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	Saves the configuration.

Managing the Parser Cache

To control the Parser Cache feature, perform the tasks described in the following sections. All of these tasks are optional:

- [Clearing the Parser Cache, page 30](#)
- [Disabling the Parser Cache, page 30](#)
- [Reenabling the Parser Cache, page 31](#)

- [What to Do Next, page 31](#)

Clearing the Parser Cache

To clear the information stored by the Parser Cache feature, complete the task in this section:

SUMMARY STEPS

1. `enable`
2. `clear parser cache`

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <code>Router> enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	clear parser cache Example: <code>Router# clear parser cache</code>	Clears the parse cache entries and hit/miss statistics stored for the Parser Cache feature.

Disabling the Parser Cache

The Parser Cache feature is enabled by default. To disable the Parser Cache feature, complete the task in this section:

SUMMARY STEPS

1. `enable`
2. `no parser cache`

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: <code>Router> enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.

Command or Action	Purpose
<p>Step 2 <code>no parser cache</code></p> <p>Example:</p> <pre>Router# no parser cache</pre>	<p>Disables the Parser Cache feature:</p> <ul style="list-style-type: none"> • When the parser cache is disabled, the no parser cache command line is written to the running configuration file. • If you wish to disable the parser cache to free system resources, you should clear the parser cache before issuing the no parser cache command. You will not be able to clear the parser cache after disabling it.

Reenabling the Parser Cache

To reenble the Parser Cache feature after disabling it, complete the task in this section:

SUMMARY STEPS

1. `enable`
2. `parser cache`

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 <code>enable</code></p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 <code>parser cache</code></p> <p>Example:</p> <pre>Router# parser cache</pre>	<p>Enables the Parser Cache feature.</p>

What to Do Next

The `show parser statistics` command displays two sets of data, as follows:

- The number of commands in the configuration file that was last copied into the running configuration, and the time it took for the system to parse them (a configuration file can be loaded into the running configuration at system startup, or by issuing commands such as the **copy source running-config EXEC** command).
- The status of the parser cache (enabled or disabled) and the number of command matches (hits or misses) since the system was started or since the parser cache was cleared.

Copying Configuration Files from Flash Memory to the Startup or Running Configuration

To copy a configuration file from Flash memory directly to your startup configuration in NVRAM or your running configuration, enter one of the commands in Step 2:

SUMMARY STEPS

1. **enable**
2. Do one of the following:
 - **copy filesystem : [partition-number:][filename] nvram:startup-config**
 - **copy filesystem : [partition-number:][filename] system:running-config**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 Do one of the following: <ul style="list-style-type: none"> • copy filesystem : [partition-number:][filename] nvram:startup-config • copy filesystem : [partition-number:][filename] system:running-config Example: Router# copy slot0:4:ios-upgrade-1 nvram:startup-config	Loads a configuration file directly into NVRAM. or Copies a configuration file to your running configuration.

Examples

The following example copies the file named ios-upgrade-1 from partition 4 of the Flash memory PC Card in slot 0 to the router startup configurations:

```
Router# copy slot0:4:ios-upgrade-1 nvram:startup-config

Copy '
ios-upgrade-1
' from flash device
  as 'startup-config' ? [yes/no] yes

[OK]
```

Copying Configuration Files Between Flash Memory File Systems

On platforms with multiple Flash memory file systems, you can copy files from one Flash memory file system, such as internal Flash memory or a Flash memory card in a PCMCIA slot, to another Flash

memory file system. Copying files to different Flash memory file systems lets you create backup copies of working configurations and duplicate configurations for other routers. To copy a configuration file between Flash memory file systems, use the following commands in EXEC mode:

SUMMARY STEPS

1. **enable**
2. **show source-filesystem :**
3. **copy source-filesystem : [partition-number:][filename] dest-filesystem:[partition-number:][filename]**
4. **verify dest-filesystem : [partition-number:][filename]**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 show source-filesystem :</p> <p>Example:</p> <pre>Router# copy slot0:4:ios-upgrade-1 nvram:startup-config</pre>	<p>Displays the layout and contents of Flash memory to verify the filename.</p>
<p>Step 3 copy source-filesystem : [partition-number:][filename] dest-filesystem:[partition-number:][filename]</p> <p>Example:</p> <pre>Router# copy flash: slot1:</pre>	<p>Copies a configuration file between Flash memory devices.</p> <ul style="list-style-type: none"> • The source device and the destination device cannot be the same. For example, the copyslot1:slot1: command is invalid.
<p>Step 4 verify dest-filesystem : [partition-number:][filename]</p> <p>Example:</p> <pre>Router# verify flash: slot1:</pre>	<p>Verifies the checksum of the file you copied.</p>

Example

The following example copies the file named running-config from partition 1 of internal Flash memory to partition 1 of slot 1 on a Cisco 3600 series router. In this example, the source partition is not specified, so the router prompts for the partition number.

```
Router# copy flash: slot1:

System flash
Partition  Size  Used   Free   Bank-Size  State      Copy Mode
1          4096K  3070K  1025K  4096K      Read/Write Direct
```

```

 2          16384K  1671K   14712K    8192K      Read/Write   Direct
[Type ?<no> for partition directory; ? for full directory; q to abort]
Which partition? [default = 1]
System flash directory, partition 1:
File Length Name/status
 1  3142748 dirt/network/mars-test/c3600-j-mz.latest
 2    850   running-config
[3143728 bytes used, 1050576 available, 4194304 total]
PCMCIA Slot1 flash directory:
File Length Name/status
 1  1711088 dirt/gate/c3600-i-mz
 2    850   running-config
[1712068 bytes used, 2482236 available, 4194304 total]
Source file name? running-config

Destination file name [running-config]?
Verifying checksum for 'running-config' (file # 2)... OK
Erase flash device before writing? [confirm]
Flash contains files. Are you sure you want to erase? [confirm]
Copy 'running-config' from flash: device
  as 'running-config' into slot1: device WITH erase? [yes/no] yes

Erasing device...
eeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeeee ..erased
!
[OK - 850/4194304 bytes]
Flash device copy took 00:00:30 [hh:mm:ss]
Verifying checksum... OK (0x16)

```

Copying a Configuration File from an FTP Server to Flash Memory Devices

To copy a configuration file from an FTP server to a Flash memory device, complete the task in this section:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip ftp username *username***
4. **ip ftp password *password***
5. **end**
6. **copy ftp: [[[//[*username*:*password*@][*location*]/*directory*]/*filename*] flash-filesystem:[*partition-number*]:][*filename*]**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.

Command or Action	Purpose
<p>Step 2 <code>configure terminal</code></p> <p>Example:</p> <pre>Router# configure terminal</pre>	(Optional) Enters global configuration mode. This step is required only if you override the default remote username or password (see Steps 3 and 4).
<p>Step 3 <code>ip ftp username <i>username</i></code></p> <p>Example:</p> <pre>Router(config)# ip ftp username user1</pre>	(Optional) Specifies the remote username.
<p>Step 4 <code>ip ftp password <i>password</i></code></p> <p>Example:</p> <pre>Router(config)# ip ftp password guessme</pre>	(Optional) Specifies the remote password.
<p>Step 5 <code>end</code></p> <p>Example:</p> <pre>Router(config)# end</pre>	(Optional) Exits configuration mode. This step is required only if you override the default remote username (see Steps 3 and 4).
<p>Step 6 <code>copy ftp: [[[/[<i>username:password@</i>]<i>location</i>]/<i>directory</i>]/<i>filename</i>] flash-filesystem:[<i>partition-number</i>:[<i>filename</i>]</code></p> <p>Example:</p> <pre>Router> copy ftp:router-config slot0:new-config</pre>	Copies the configuration file from a network server to the Flash memory device using FTP.

- [What to Do Next, page 35](#)

What to Do Next

After you have issued the **copy EXEC** command, you may be prompted for additional information or for confirmation of the action. The prompting will depend on how much information you provide in the **copy** command and the current setting of the **fileprompt** global configuration command.

Copying a Configuration File from an rcp Server to Flash Memory Devices

To copy a configuration file from an rcp server to a Flash memory device, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **ip rcmd remote-username** *username*
4. **end**
5. **copy rcp:** [[[/[*username@*]/*location*]/*directory*]/*filename*]*flash-filesystem:[partition-number:]*
[*filename*]

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> • Enter your password if prompted.
<p>Step 2 configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>(Optional) Enters global configuration mode. This step is required only if you override the default remote username or password (see Steps 3 and 4).</p>
<p>Step 3 ip rcmd remote-username <i>username</i></p> <p>Example:</p> <pre>Router(config)# ip rcmd remote-username user1</pre>	<p>(Optional) Specifies the remote username.</p>
<p>Step 4 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>(Optional) Exits configuration mode. This step is required only if you override the default remote username or password (see Steps 3 and 4).</p>
<p>Step 5 copy rcp: [[[/[<i>username@</i>]/<i>location</i>]/<i>directory</i>]/<i>filename</i>]<i>flash-filesystem:[partition-number:]</i> [<i>filename</i>]</p> <p>Example:</p> <pre>Router# copy rcp:router-config slot0:new-config</pre>	<p>Copies the configuration file from a network server to the Flash memory device using rcp. Reply to any router prompts for additional information or confirmation. The prompting will depend on how much information you provide in the copy command and the current setting of the fileprompt command.</p>

Copying a Configuration File from a TFTP Server to Flash Memory Devices

To copy a configuration file from a TFTP server to a Flash memory device, complete the task in this section:

SUMMARY STEPS

1. **enable**
2. **copy tftp:** [[[//location]/directory]/filename] flash-filesystem:[partition-number:][filename]

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 copy tftp: [[[//location]/directory]/filename] flash-filesystem:[partition-number:][filename] Example: Router# copy tftp:router-config slot0:new-config	Copies the file from a TFTP server to the Flash memory device. Reply to any router prompts for additional information or confirmation. The prompting will depending on how much information you provide in the copy command and the current setting of the fileprompt command.

Examples

The following example shows the copying of the configuration file named router-config from a TFTP server to the Flash memory card inserted in slot 0 of the Network Processing Engine (NPE) or Route Switch Processor (RSP) card of a Cisco 7500 series router. The copied file is renamed new-config.

```
Router# copy tftp:router-config slot0:new-config
```

Reexecuting the Configuration Commands in the Startup Configuration File

To reexecute the commands located in the startup configuration file, complete the task in this section:

SUMMARY STEPS

1. **enable**
2. **configure memory**

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	configure memory Example: Router# configure memory	Reexecutes the configuration commands located in the startup configuration file .

Clearing the Startup Configuration

You can clear the configuration information from the startup configuration. If you reboot the router with no startup configuration, the router will enter the Setup command facility so that you can configure the router from scratch. To clear the contents of your startup configuration, complete the task in this section:

SUMMARY STEPS

1. enable
2. erase nvram

DETAILED STEPS

	Command or Action	Purpose
Step 1	enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2	erase nvram Example: Router# erase nvram	Clears the contents of your startup configuration. <p>Note For all platforms except the Class A Flash file system platforms, this command erases NVRAM. The startup configuration file cannot be restored once it has been deleted. On Class A Flash file system platforms, when you use the erasestartup-configEXEC command, the router erases or deletes the configuration pointed to by CONFIG_FILE environment variable. If this variable points to NVRAM, the router erases NVRAM. If the CONFIG_FILE environment variable specifies a Flash memory device and configuration filename, the router deletes the configuration file. That is, the router marks the file as “deleted,” rather than erasing it. This feature allows you to recover a deleted file.</p>

Deleting a Specified Configuration File

To delete a specified configuration on a specific Flash device, complete the task in this section:

SUMMARY STEPS

1. **enable**
2. **delete** *flash-filesystem : filename*

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 delete <i>flash-filesystem : filename</i> Example: Router# delete slot0:myconfig	Deletes a specified configuration file on a specified Flash device. Note On Class A and B Flash file systems, when you delete a specific file in Flash memory, the system marks the file as deleted, allowing you to later recover a deleted file using the undelete EXEC command. Erased files cannot be recovered. To permanently erase the configuration file, use the squeeze EXEC command. On Class C Flash file systems, you cannot recover a file that has been deleted. If you attempt to erase or delete the configuration file specified by the CONFIG_FILE environment variable, the system prompts you to confirm the deletion.

Specifying the CONFIG_FILE Environment Variable on Class A Flash File Systems

On Class A Flash file systems, you can configure the Cisco IOS software to load the startup configuration file specified by the CONFIG_FILE environment variable. The CONFIG_FILE variable defaults to NVRAM. To change the CONFIG_FILE environment variable, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **copy** [*flash-url* | *ftp-url* | *rcp-url* | *tftp-url* | **system:running-config** | **nvram:startup-config**] *dest-flash-url*
3. **configure terminal**
4. **boot config** *dest-flash-url*
5. **end**
6. **copy** **system:running-config** **nvram:startup-config**
7. **show bootvar**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.
<p>Step 2 copy [flash-url ftp-url rcp-url tftp-url system:running-config nvram:startup-config] dest-flash-url</p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	<p>Copies the configuration file to the Flash file system from which the router will load the file upon restart.</p>
<p>Step 3 configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 4 boot config dest-flash-url</p> <p>Example:</p> <pre>Router(config)# boot config 172.16.1.1</pre>	<p>Sets the CONFIG_FILE environment variable. This step modifies the runtime CONFIG_FILE environment variable.</p>
<p>Step 5 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode.</p>
<p>Step 6 copy system:running-config nvram:startup-config</p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	<p>Saves the configuration performed in Step 3 to the startup configuration.</p>
<p>Step 7 show bootvar</p> <p>Example:</p> <pre>Router# show bootvar</pre>	<p>(Optional) Allows you to verify the contents of the CONFIG_FILE environment variable.</p>

Examples

The following example copies the running configuration file to the first PCMCIA slot of the RSP card in a Cisco 7500 series router. This configuration is then used as the startup configuration when the system is restarted.

```
Router# copy system:running-config slot0:config2
Router# configure terminal
Router(config)# boot config slot0:config2
Router(config)# end
Router# copy system:running-config nvram:startup-config
[ok]
Router# show bootvar
BOOT variable = slot0:rsp-boot-m
CONFIG_FILE variable = nvram:
Current CONFIG_FILE variable = slot0:config2
Configuration register is 0x010F
```

- [What to Do Next, page 41](#)

What to Do Next

After you specify a location for the startup configuration file, the **nvram:startup-config** command is aliased to the new location of the startup configuration file. The **morenvram:startup-config EXEC** command will display the startup configuration, regardless of its location. The **erasenvram:startup-config EXEC** command will erase the contents of NVRAM and delete the file pointed to by the CONFIG_FILE environment variable.

When you save the configuration using the **copysystem:running-confignvram:startup-config** command, the router saves a complete version of the configuration file to the location specified by the CONFIG_FILE environment variable and a distilled version to NVRAM. A distilled version is one that does not contain access list information. If NVRAM contains a complete configuration file, the router prompts you to confirm your overwrite of the complete version with the distilled version. If NVRAM contains a distilled configuration, the router does not prompt you for confirmation and proceeds with overwriting the existing distilled configuration file in NVRAM.



Note

If you specify a file in a Flash device as the CONFIG_FILE environment variable, every time you save your configuration file with the **copysystem:running-confignvram:startup-config** command, the old configuration file is marked as “deleted,” and the new configuration file is saved to that device. Eventually, Flash memory will be full, because the old configuration files still take up memory. Use the **squeeze EXEC** command to permanently delete the old configuration files and reclaim the space.

Configuring the Router to Download Configuration Files

You can specify an ordered list of network configuration and host configuration filenames. The Cisco IOS XE software scans this list until it loads the appropriate network or host configuration file.

To configure the router to download configuration files at system startup, perform at least one of the tasks described in the following sections:

- "Configuring the Router to Download the Network Configuration File"
- "Configuring the Router to Download the Host Configuration File"

If the router fails to load a configuration file during startup, it tries again every 10 minutes (the default setting) until a host provides the requested files. With each failed attempt, the router displays the following message on the console terminal:

```
Booting host-config... [timed out]
```

If there are any problems with the startup configuration file, or if the configuration register is set to ignore NVRAM, the router enters the Setup command facility.

- [Configuring the Router to Download the Network Configuration File, page 42](#)
- [Configuring the Router to Download the Host Configuration File, page 43](#)

Configuring the Router to Download the Network Configuration File

To configure the Cisco IOS software to download a network configuration file from a server at startup, complete the tasks in this section:

SUMMARY STEPS

1. **enable**
2. **configure terminal**
3. **boot network** {ftp:[[/[/username [:password]@]location]/directory]/filename] | rcp:[[/[/username@]location]/directory]/filename] | tftp:[[/[/location]/directory]/filename]}
4. **service config**
5. **end**
6. Router#**copysystem:running-confignvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
Step 1 enable Example: Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> • Enter your password if prompted.
Step 2 configure terminal Example: Router# configure terminal	Enters global configuration mode.

Command or Action	Purpose
<p>Step 3 boot network {ftp:[[/[username [:password]@]location]/directory]/filename] rcp:[[/[username@]location]/directory]/filename] tftp:[[/location]/directory]/filename }</p> <p>Example:</p> <pre>Router(config)# boot network tftp:hostfile1</pre>	<p>Specifies the network configuration file to download at startup, and the protocol to be used (TFTP, rcp, or FTP).</p> <ul style="list-style-type: none"> If you do not specify a network configuration filename, the Cisco IOS software uses the default filename network-config. If you omit the address, the router uses the broadcast address. You can specify more than one network configuration file. The software tries them in order entered until it loads one. This procedure can be useful for keeping files with different configuration information loaded on a network server.
<p>Step 4 service config</p> <p>Example:</p> <pre>Router(config)# service config</pre>	<p>Enables the system to automatically load the network file upon restart.</p>
<p>Step 5 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode.</p>
<p>Step 6 Router#copy system:running-config nvram:startup-config</p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	<p>Saves the running configuration to the startup configuration file.</p>

Configuring the Router to Download the Host Configuration File

To configure the Cisco IOS software to download a host configuration file from a server at startup, complete the tasks in this section:

SUMMARY STEPS

- enable
- configure terminal
- boot host** {ftp:[[/[username [:password]@]location]/directory]/filename] | rcp:[[/[username@]location]/directory]/filename] | tftp:[[/location]/directory]/filename }
- service config**
- end**
- copy system:running-config nvram:startup-config**

DETAILED STEPS

Command or Action	Purpose
<p>Step 1 enable</p> <p>Example:</p> <pre>Router> enable</pre>	<p>Enables privileged EXEC mode.</p> <ul style="list-style-type: none"> Enter your password if prompted.
<p>Step 2 configure terminal</p> <p>Example:</p> <pre>Router# configure terminal</pre>	<p>Enters global configuration mode.</p>
<p>Step 3 boot host {ftp:[[/username [:password]@]location]/directory]/filename] rcp:[[/username@]location]/directory]/ filename] tftp:[[/location]/directory]/ filename] }</p> <p>Example:</p> <pre>Router(config)# boot host tftp:hostfile1</pre>	<p>Specifies the host configuration file to download at startup, and the protocol to be used (FTP, rcp, or TFTP):</p> <ul style="list-style-type: none"> If you do not specify a host configuration filename, the router uses its own name to form a host configuration filename by converting the name to all lowercase letters, removing all domain information, and appending “-config.” If no host name information is available, the software uses the default host configuration filename router-config. If you omit the address, the router uses the broadcast address. You can specify more than one host configuration file. The Cisco IOS software tries them in order entered until it loads one. This procedure can be useful for keeping files with different configuration information loaded on a network server.
<p>Step 4 service config</p> <p>Example:</p> <pre>Router(config)# service config</pre>	<p>Enables the system to automatically load the host file upon restart.</p>
<p>Step 5 end</p> <p>Example:</p> <pre>Router(config)# end</pre>	<p>Exits global configuration mode.</p>

Command or Action	Purpose
<p>Step 6 <code>copy system:running-config nvram:startup-config</code></p> <p>Example:</p> <pre>Router# copy system:running-config nvram:startup-config</pre>	<p>Saves the running configuration to the startup configuration file.</p>

Examples

In the following example, a router is configured to download the host configuration file named `hostfile1` and the network configuration file named `networkfile1`. The router uses TFTP and the broadcast address to obtain the file.

```
Router# configure terminal
Router(config)# boot host tftp:hostfile1
Router(config)# boot network tftp:networkfile1
Router(config)# service config
Router(config)# end
Router# copy system:running-config nvram:startup-config
```

Additional References

Related Documents

Related Topic	Document Title
Cisco IOS commands	Cisco IOS Master Commands List, All Releases
Cisco IOS configuration commands	<i>Cisco IOS Configuration Fundamentals Command Reference</i>

Standards

Standard	Title
No new or modified standards are supported, and support for existing standards has not been modified	--

MIBs

MIB	MIBs Link
<ul style="list-style-type: none"> No new or modified MIBs are supported, and support for existing MIBs has not been modified. 	To locate and download MIBs for selected platforms, Cisco software releases, and feature sets, use Cisco MIB Locator found at the following URL: http://www.cisco.com/go/mibs

RFCs

RFC	Title
No new or modified RFCs are supported, and support for existing RFCs has not been modified.	--

Technical Assistance

Description	Link
The Cisco Support and Documentation website provides online resources to download documentation, software, and tools. Use these resources to install and configure the software and to troubleshoot and resolve technical issues with Cisco products and technologies. Access to most tools on the Cisco Support and Documentation website requires a Cisco.com user ID and password.	http://www.cisco.com/cisco/web/support/index.html

Cisco and the Cisco Logo are trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and other countries. A listing of Cisco's trademarks can be found at www.cisco.com/go/trademarks. Third party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1005R)

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: www.cisco.com/go/trademarks. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

© 2011 Cisco Systems, Inc. All rights reserved.