



## RFC-2867 RADIUS Tunnel Accounting

---

The RFC-2867 RADIUS Tunnel Accounting introduces six new RADIUS accounting types that are used with the RADIUS accounting attribute Acct-Status-Type (attribute 40), which indicates whether an accounting request marks the beginning of user service (start) or the end (stop).

This feature also introduces two virtual private virtual private dialup network (VPDN) commands that help users better troubleshoot VPDN session events.

Without RADIUS tunnel accounting support, VPDN with network accounting, which allows users to determine tunnel-link status changes, did not report all possible attributes to the accounting record file. Now that all possible attributes can be displayed, users can better verify accounting records with their Internet Service Providers (ISPs).

- [Finding Feature Information, page 1](#)
- [Restrictions for RFC-2867 RADIUS Tunnel Accounting, page 2](#)
- [Information About RFC-2867 RADIUS Tunnel Accounting, page 2](#)
- [How to Configure RADIUS Tunnel Accounting, page 8](#)
- [Configuration Examples for RADIUS Tunnel Accounting, page 11](#)
- [Additional References, page 14](#)
- [Feature Information for RFC-2867 RADIUS Tunnel Accounting, page 15](#)

## Finding Feature Information

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see [Bug Search Tool](#) and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

# Restrictions for RFC-2867 RADIUS Tunnel Accounting

RADIUS tunnel accounting works only with L2TP tunnel support.

## Information About RFC-2867 RADIUS Tunnel Accounting

### RADIUS Attributes Support for RADIUS Tunnel Accounting

The table below outlines the new RADIUS accounting types that are designed to support the provision of compulsory tunneling in dialup networks; that is, these attribute types allow you to better track tunnel status changes.


**Note**

The accounting types are divided into two separate tunnel types so users can decide if they want tunnel type, tunnel-link type, or both types of accounting.

**Table 1: RADIUS Accounting Types for the Acct-Status-Type Attribute**

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
Tunnel-Start	9	Marks the beginning of a tunnel setup with another node.	<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> </ul>

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
Tunnel-Stop	10	Marks the end of a tunnel connection to or from another node.	<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Acct-Input-Octets (42)--from AAA</li> <li>• Acct-Output-Octets (43)--from AAA</li> <li>• Acct-Session-Id (44)--from AAA</li> <li>• Acct-Session-Time (46)--from AAA</li> <li>• Acct-Input-Packets (47)--from AAA</li> <li>• Acct-Output-Packets (48)--from AAA</li> <li>• Acct-Terminate-Cause (49)--from AAA</li> <li>• Acct-Multi-Session-Id (51)--from AAA</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> <li>• Acct-Tunnel-Packets-Lost (86)--from client</li> </ul>

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
Tunnel-Reject	11	Marks the rejection of a tunnel setup with another node.	<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Acct-Terminate-Cause (49)--from client</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> </ul>

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
Tunnel-Link-Start	12	Marks the creation of a tunnel link. Only some tunnel types (Layer 2 Transport Protocol [L2TP]) support the multiple links per tunnel; this value should be included only in accounting packets for tunnel types that support multiple links per tunnel.	<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• NAS-Port (5)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> </ul>

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
Tunnel-Link-Stop	13	Marks the end of a tunnel link. Only some tunnel types (L2TP) support the multiple links per tunnel; this value should be included only in accounting packets for tunnel types that support multiple links per tunnel.	

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
			<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• NAS-Port (5)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Acct-Input-Octets (42)--from AAA</li> <li>• Acct-Output-Octets (43)--from AAA</li> <li>• Acct-Session-Id (44)--from AAA</li> <li>• Acct-Session-Time (46)--from AAA</li> <li>• Acct-Input-Packets (47)--from AAA</li> <li>• Acct-Output-Packets (48)--from AAA</li> <li>• Acct-Terminate-Cause (49)--from AAA</li> <li>• Acct-Multi-Session-Id (51)--from AAA</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• NAS-Port-Type (61)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> <li>• Acct-Tunnel-Packets-Lost</li> </ul>

Type-Name	Number	Description	Additional Attributes <sup>1</sup>
			(86)--from client
Tunnel-Link-Reject	14	Marks the rejection of a tunnel setup for a new link in an existing tunnel. Only some tunnel types (L2TP) support the multiple links per tunnel; this value should be included only in accounting packets for tunnel types that support multiple links per tunnel.	<ul style="list-style-type: none"> <li>• User-Name (1)--from client</li> <li>• NAS-IP-Address (4)--from AAA</li> <li>• Acct-Delay-Time (41)--from AAA</li> <li>• Acct-Terminate-Cause (49)--from AAA</li> <li>• Event-Timestamp (55)--from AAA</li> <li>• Tunnel-Type (64)--from client</li> <li>• Tunnel-Medium-Type (65)--from client</li> <li>• Tunnel-Client-Endpoint (66)--from client</li> <li>• Tunnel-Server-Endpoint (67)--from client</li> <li>• Acct-Tunnel-Connection (68)--from client</li> </ul>

<sup>1</sup> If the specified tunnel type is used, these attributes should also be included in the accounting request packet.

## How to Configure RADIUS Tunnel Accounting

### Enabling Tunnel Type Accounting Records

Use this task to configure your LAC to send tunnel and tunnel-link accounting records to be sent to the RADIUS server.

Two new command line interfaces (CLIs)--vpdn session accounting network(tunnel-link-type records)and vpdn tunnel accounting network(tunnel-type records)--are supported to help identify the following events:

- A VPDN tunnel is brought up or destroyed
- A request to create a VPDN tunnel is rejected
- A user session within a VPDN tunnel is brought up or brought down



- A user session create request is rejected

**Note**

The first two events are tunnel-type accounting records: authentication, authorization, and accounting (AAA) sends Tunnel-Start, Tunnel-Stop, or Tunnel-Reject accounting records to the RADIUS server. The next two events are tunnel-link-type accounting records: AAA sends Tunnel-Link-Start, Tunnel-Link-Stop, or Tunnel-Link-Reject accounting records to the RADIUS server.

**SUMMARY STEPS**

1. **enable**
2. **configure terminal**
3. Router(config)# **aaa accounting network default** *list-name* {**start-stop** | **stop-only** | **wait-start** | **none** **group** *groupname*
4. Router(config)# **vpdn enable**
5. Router(config)# **vpdn tunnel accounting network** *list-name*
6. Router(config)# **vpdn session accounting network** *list-name*

**DETAILED STEPS**

	Command or Action	Purpose
<b>Step 1</b>	<b>enable</b>  <b>Example:</b> Router> enable	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<b>Step 2</b>	<b>configure terminal</b>  <b>Example:</b> Router# configure terminal	Enters global configuration mode.
<b>Step 3</b>	Router(config)# <b>aaa accounting network default</b> <i>list-name</i> { <b>start-stop</b>   <b>stop-only</b>   <b>wait-start</b>   <b>none</b> <b>group</b> <i>groupname</i>	Enables network accounting. <ul style="list-style-type: none"> <li>• <b>default</b> --If the default network accounting method-list is configured and no additional accounting configurations are enabled on the interface, network accounting is enabled by default.</li> </ul> <p>If either the <b>vpdn session accounting network</b> command or the <b>vpdn tunnel accounting network</b> command is linked to the <b>default</b> method-list, all tunnel and tunnel-link accounting records are enabled for those sessions.</p> <ul style="list-style-type: none"> <li>• <i>list-name</i> --The <i>list-name</i> defined in the <b>aaa accounting</b> command must be the same as the <i>list-name</i> defined in the VPDN command; otherwise, accounting will not occur.</li> </ul>

	Command or Action	Purpose
<b>Step 4</b>	Router(config)# <b>vpdn enable</b>	Enables virtual private dialup networking on the router and informs the router to look for tunnel definitions in a local database and on a remote authorization server (if applicable).
<b>Step 5</b>	Router(config)# <b>vpdn tunnel accounting network</b> <i>list-name</i>	Enables Tunnel-Start, Tunnel-Stop, and Tunnel-Reject accounting records. <ul style="list-style-type: none"> <li>• <i>list-name</i> --The <i>list-name</i> must match the <i>list-name</i> defined in the <b>aaa accounting</b> command; otherwise, network accounting will not occur.</li> </ul>
<b>Step 6</b>	Router(config)# <b>vpdn session accounting network</b> <i>list-name</i>	Enables Tunnel-Link-Start, Tunnel-Link-Stop, and Tunnel-Link-Reject accounting records. <ul style="list-style-type: none"> <li>• <i>list-name</i> --The <i>list-name</i> must match the <i>list-name</i> defined in the <b>aaa accounting</b> command; otherwise, network accounting will not occur.</li> </ul>

## What To Do Next

After you have enabled RADIUS tunnel accounting, you can verify your configuration via the following optional task “Verifying RADIUS Tunnel Accounting.”

## Verifying RADIUS Tunnel Accounting

Use either one or both of the following optional steps to verify your RADIUS tunnel accounting configuration.

### SUMMARY STEPS

1. **enable**
2. Router# **show accounting**
3. Router# **show vpdn [session] [tunnel]**

### DETAILED STEPS

	Command or Action	Purpose
<b>Step 1</b>	<b>enable</b>  <b>Example:</b> Router> <code>enable</code>	Enables privileged EXEC mode. <ul style="list-style-type: none"> <li>• Enter your password if prompted.</li> </ul>
<b>Step 2</b>	Router# <b>show accounting</b>	Displays the active accountable events on the network and helps collect information in the event of a data loss on the accounting server.

	Command or Action	Purpose
Step 3	Router# <code>show vpdn [session] [tunnel]</code>	<p>Displays information about active L2TP tunnel and message identifiers in a VPDN.</p> <ul style="list-style-type: none"> <li>• <b>session</b> --Displays a summary of the status of all active tunnels.</li> <li>• <b>tunnel</b> --Displays information about all active L2TP tunnels in summary-style format.</li> </ul>

## Configuration Examples for RADIUS Tunnel Accounting

### Configuring RADIUS Tunnel Accounting on LAC Example

The following example shows how to configure your L2TP access concentrator (LAC) to send tunnel and tunnel-link accounting records to the RADIUS server:

```

aaa new-model
!
!
aaa authentication ppp default group radius
aaa authorization network default local
aaa accounting network m1 start-stop group radius
aaa accounting network m2 stop-only group radius
aaa session-id common
enable secret 5 $1$IDjH$iL7puCja1RMlyOM.JAeuf/
enable password lab
!
username ISP_LAC password 0 tunnelpass
!
!
resource-pool disable
!
!
ip subnet-zero
ip cef
no ip domain-lookup
ip host dirt 171.69.1.129
!
vpdn enable
vpdn tunnel accounting network m1
vpdn session accounting network m1
vpdn search-order domain dnis
!
vpdn-group 1
 request-dialin
  protocol l2tp
  domain cisco.com
  initiate-to ip 10.1.26.71
  local name ISP_LAC
!
isdn switch-type primary-5ess
!
!
fax interface-type fax-mail
mta receive maximum-recipients 0
!

```

```

controller T1 7/4
  framing esf
  linecode b8zs
  pri-group timeslots 1-24
  !
  !
  !
interface FastEthernet0/0
  ip address 10.1.27.74 255.255.255.0
  no ip mroute-cache
  duplex half
  speed auto
  no cdp enable
  !
interface FastEthernet0/1
  no ip address
  no ip mroute-cache
  shutdown
  duplex auto
  speed auto
  no cdp enable
  !
interface Serial7/4:23
  ip address 60.0.0.2 255.255.255.0
  encapsulation ppp
  dialer string 2000
  dialer-group 1
  isdn switch-type primary-5ess
  ppp authentication chap
  !
interface Group-Async0
  no ip address
  shutdown
  group-range 1/00 3/107
  !
ip default-gateway 10.1.27.254
ip classless
ip route 0.0.0.0 0.0.0.0 10.1.27.254
no ip http server
ip pim bidir-enable
  !
  !
dialer-list 1 protocol ip permit
no cdp run
  !
  !
radius-server host 172.19.192.26 auth-port 1645 acct-port 1646 key rad123
radius-server retransmit 3
call rsvp-sync
  !

```

## Configuring RADIUS Tunnel Accounting on LNS Example

The following example shows how to configure your L2TP network server (LNS) to send tunnel and tunnel-link accounting records to the RADIUS server:

```

aaa new-model
  !
  !
aaa accounting network m1 start-stop group radius
aaa accounting network m2 stop-only group radius
aaa session-id common
enable secret 5 $1$ftf.$wE6Q5Yv6hmQiwL9pizPCg1
  !
username ENT_LNS password 0 tunnelpass
username user1@cisco.com password 0 lab
username user2@cisco.com password 0 lab
spe 1/0 1/7
  firmware location system:/ucode/mica_port_firmware

```



```
dialer-list 1 protocol ip permit
no cdp run
!
!
radius-server host 172.19.192.80 auth-port 1645 acct-port 1646 key rad123
radius-server retransmit 3
call rsvp-sync
```

## Additional References

The following sections provide references related to RFC-2867 RADIUS Tunnel Accounting.

### Related Documents

Related Topic	Document Title
RADIUS attributes	“ RADIUS Attributes ” feature module.
VPDN	<i>Cisco IOS VPDN Configuration Guide , Release 12.4T.</i>
Network accounting	“ Configuring Accounting ” feature module.

### Standards

Standards	Title
None	--

### MIBs

MIBs	MIBs Link
None	To locate and download MIBs for selected platforms, Cisco IOS releases, and feature sets, use Cisco MIB Locator found at the following URL: <a href="http://www.cisco.com/go/mibs">http://www.cisco.com/go/mibs</a>

### RFCs

RFCs	Title
RFC 2867	<i>RADIUS Accounting Modifications for Tunnel Protocol Support</i>

**Technical Assistance**

Description	Link
<p>The Cisco Support website provides extensive online resources, including documentation and tools for troubleshooting and resolving technical issues with Cisco products and technologies.</p> <p>To receive security and technical information about your products, you can subscribe to various services, such as the Product Alert Tool (accessed from Field Notices), the Cisco Technical Services Newsletter, and Really Simple Syndication (RSS) Feeds.</p> <p>Access to most tools on the Cisco Support website requires a Cisco.com user ID and password.</p>	<p><a href="http://www.cisco.com/techsupport">http://www.cisco.com/techsupport</a></p>

## Feature Information for RFC-2867 RADIUS Tunnel Accounting

The following table provides release information about the feature or features described in this module. This table lists only the software release that introduced support for a given feature in a given software release train. Unless noted otherwise, subsequent releases of that software release train also support that feature.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to [www.cisco.com/go/cfn](http://www.cisco.com/go/cfn). An account on Cisco.com is not required.

**Table 2: Feature Information for RFC-2867 RADIUS Tunnel Accounting**

Feature Name	Releases	Feature Information
RFC-2867 RADIUS Tunnel Accounting	12.2(15)B 12.3(4)T	<p>The RFC-2867 RADIUS Tunnel Accounting introduces six new RADIUS accounting types that are used with the RADIUS accounting attribute Acct-Status-Type (attribute 40), which indicates whether an accounting request marks the beginning of user service (start) or the end (stop).</p> <p>This feature also introduces two virtual private virtual private dialup network (VPDN) commands that help users better troubleshoot VPDN session events.</p> <p>In 12.2(15)B, this feature was introduced on the Cisco 6400 series, Cisco 7200 series, and the Cisco 7400 series routers.</p> <p>This feature was integrated into Cisco IOS Release 12.3(4)T.</p> <p>The following commands were introduced or modified: <b>aaa accounting</b>, <b>vpdn session accounting network</b>, <b>vpdn tunnel accounting network</b>.</p>