



## Cisco Unified Border Element H.323-to-SIP Internetworking Configuration Guide, Cisco IOS Release 15M&T

Last Modified: November 25, 2015

### **Americas Headquarters**

Cisco Systems, Inc. 170 West Tasman Drive San Jose, CA 95134-1706 USA http://www.cisco.com Tel: 408 526-4000

800 553-NETS (6387)

Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <a href="http://www.cisco.com/go/trademarks">http://www.cisco.com/go/trademarks</a>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)

© 2015 Cisco Systems, Inc. All rights reserved.



### CONTENTS

#### CHAPTER 1 Cisco Unified Border

### Cisco Unified Border Element H.323-to-SIP Interworking 1

Finding Feature Information 1

Cisco Unified Border Element H.323-to-SIP Interworking Features 1

### CHAPTER 2 Session Border Controller Enhancements 3

Prerequisites for Session Border Controller Enhancements 3

Feature Information for Session Border Controller Enhancements 4

Contents



# **Cisco Unified Border Element H.323-to-SIP Interworking**

This Cisco Unified Border Element is a special Cisco IOS software image that provides a network-to-network interface point for billing, security, call admission control, quality of service, and signaling interworking. This chapter describes basic gateway functionality, software images, topology, and summarizes supported features.



Cisco Product Authorization Key (PAK)--A Product Authorization Key (PAK) is required to configure some of the features described in this guide. Before you start the configuration process, please register your products and activate your PAK at the following URL <a href="http://www.cisco.com/go/license">http://www.cisco.com/go/license</a>.

- Finding Feature Information, page 1
- Cisco Unified Border Element H.323-to-SIP Interworking Features, page 1

### **Finding Feature Information**

Your software release may not support all the features documented in this module. For the latest caveats and feature information, see Bug Search Tool and the release notes for your platform and software release. To find information about the features documented in this module, and to see a list of the releases in which each feature is supported, see the feature information table at the end of this module.

Use Cisco Feature Navigator to find information about platform support and Cisco software image support. To access Cisco Feature Navigator, go to <a href="https://www.cisco.com/go/cfn">www.cisco.com/go/cfn</a>. An account on Cisco.com is not required.

## Cisco Unified Border Element H.323-to-SIP Interworking Features

This chapter contains the following configuration topics:

### **Cisco UBE Prerequisites and Restrictions**

- Prerequisites for Cisco Unified Border Element (Enterprise)
- Restrictions for Cisco Unified Border Element (Enterprise)

### **H.323-SIP Protocol Handling and Supplementary Services**

- H.323-to-SIP Supplementary Feature Interworking for Session Border Controller
  - H323-to-SIP Back-to-Back Support



### **Session Border Controller Enhancements**

The H.323-SIP and SIP-SIP Supplementary Services, Transcoding Optimization, and Firewall Integration feature provides enhancements for H.323-to-SIP Supplementary Services--specifically, mapping ECS to ReINVITE and ECS to REFER and for SIP-to-SIP Supplementary Services mapping ReINVITE to ReINVITE on the Cisco Session Border Controller. This feature also provides enhancements in Transcoding Performance and support for Universal Transcoding Support as well as integration of Cisco IOS Firewall with the Session Border Controller. Feature highlights include the following:

- Call Admission Control (based on CPU, memory, and total calls)
- · Delayed Media Call
- ENUM support
- Configuring SIP Error Message Pass Through
- Interoperability with Cisco Unified Communications Manager 5.0 and BroadSoft
- · Lawful Intercept
- · Media Inactivity
- · Modem passthrough
- TCP and UDP interworking
- Tcl scripts with SIP NOTIFY VoiceXML with SIP-to-SIP
- Transport Layer Security (TLS)
- Prerequisites for Session Border Controller Enhancements, page 3
- Feature Information for Session Border Controller Enhancements, page 4

## **Prerequisites for Session Border Controller Enhancements**

#### **Cisco Unified Border Element**

 Cisco IOS Release 12.4(11)XW or a later release must be installed and running on your Cisco Unified Border Element.

### **Cisco Unified Border Element (Enterprise)**

• Cisco IOS XE Release 3.1S or a later release must be installed and running on your Cisco ASR 1000 Series Router.

## **FeatureInformationforSessionBorderControllerEnhancements**

Feature Name	Releases	Feature Information
Session Border Controller Enhancements for H.323-SIP and SIP-SIP Supplementary Services, Transcoding Optimization, and Firewall Integration	12.4(11)XW 12.4(20)T	The H.323-to-SIP and SIP-to-SIP Supplementary Services, Transcoding Optimization, and Firewall Integration feature provides enhancements for H.323-SIP Supplementary Services on the Cisco Session Border Controller. This feature also provides enhancements in Transcoding Performance and support for Universal Transcoding Support as well as integration of Cisco IOS Firewall with the Session Border Controller.  In Cisco IOS Release 12.4(11)XW, this feature was implemented on the Cisco Unified Border Element
Session Border Controller Enhancements for H.323-SIP and SIP-SIP Supplementary Services, Transcoding Optimization, and Firewall Integration	Cisco IOS XE Release 3.1S	The H.323-to-SIP and SIP-to-SIP Supplementary Services, Transcoding Optimization, and Firewall Integration feature provides enhancements for H.323-SIP Supplementary Services on the Cisco Session Border Controller. This feature also provides enhancements in Transcoding Performance and support for Universal Transcoding Support as well as integration of Cisco IOS Firewall with the Session Border Controller. In Cisco IOS XE Release 3.1S, this feature was implemented on the Cisco Unified Border Element (Enterprise)