



DISC Commands

This chapter provides DISC (disconnect) commands for the Cisco ONS 15454, ONS 15327 and ONS 15600.

9.1 DISC-TACC

Disconnect Test Access

Usage Guidelines

Cisco ONS 15454, ONS 15327, ONS 15600

This command disconnects the TAP and puts the connection back to its original state (no splits). For more information on TACC, refer to the *Cisco ONS SONET TL1 Reference Guide*.

For this command to be applicable, you must first create the TAP using the ED-<MOD_PATH> command.



If you send this command to an already disconnected TAP connection, an SADC error message is returned.



If the system cannot release TAP, an SRTN error message is returned.

Category

Troubleshooting and Test Access

Security

Maintenance

Related Commands

CHG-ACCMD-<MOD_TACC>	OPR-LPBK-<MOD2>	RTRV-PTHTRC-<PATH>
CONN-TACC-<MOD_TACC>	RLS-LPBK-<MOD2>	RTRV-TACC
EX-SW-<OCN_BLSR>		

Input Format

DISC-TACC:[<TID>]:<TAP>:<CTAG>;

9.1 DISC-TACC

Input Example DISC-TACC:CISCO:8:123;

Input Parameters**Table 9-1** *DISC-TACC Input Parameters*

Parameter and Values	Description
TAP	The Test Access Path number. TAP number must be an integer with a range of 1 to 999. String Note This command only supports disconnecting one TAP at a time