



Add and Remove Cards and Nodes

This chapter provides procedures for adding and removing dense wavelength division multiplexing (DWDM) cards and nodes.



Note

Unless otherwise specified, “ONS 15454” refers to both ANSI and ETSI shelf assemblies.

Before You Begin

Before performing any of the following procedures, investigate all alarms and clear any trouble conditions. Refer to the *Cisco ONS 15454 DWDM Troubleshooting Guide* as necessary for general troubleshooting information and alarm or error descriptions.

This section lists the chapter procedures (NTPs). Turn to a procedure to view its tasks (DLPs).

1. [NTP-G107 Permanently Remove or Remove and Replace DWDM Cards, page 12-2](#)—Complete as needed.
2. [NTP-G127 Add an AD-xC-xx.x Card to an OADM Node, page 12-5](#)—Complete as needed.
3. [NTP-G129 Add a DWDM Node, page 12-8](#)—Complete as needed.
4. [NTP-G130 Remove a DWDM Node, page 12-10](#)—Complete as needed.
5. [NTP-G146 Add a Rack and/or Shelf to a Multishelf Node, page 12-12](#)—Complete as needed.
6. [NTP-G147 Delete a Shelf and/or Rack from a Multishelf Node, page 12-13](#)—Complete as needed.

NTP-G107 Permanently Remove or Remove and Replace DWDM Cards

Purpose	This procedure permanently removes or removes and replaces DWDM cards installed in the ONS 15454 shelf and rack.
Tools/Equipment	None
Prerequisite Procedures	NTP-G30 Install the DWDM Cards, page 3-44 NTP-G32 Install the Transponder and Muxponder Cards, page 3-50
Required/As Needed	As needed
Onsite/Remote	Onsite
Security Level	Provisioning or higher

**Caution**

Removing and replacing cards can be traffic affecting.

**Caution**

Do not use this procedure to replace a TCC2 or TCC2P card. To replace a TCC2/TCC2P card, refer to the *Cisco ONS 15454 DWDM Troubleshooting Guide*.

Step 1 Complete the [“DLP-G46 Log into CTC” task on page 2-25](#).

**Note**

If you cannot log into Cisco Transport Controller (CTC) and you need to remove a card, remove the card as described in [Step 6](#). After you log into CTC, troubleshoot the mismatched equipment alarm (MEA) with the *Cisco ONS 15454 DWDM Troubleshooting Guide*.

Step 2 Click the **Alarms** tab.

- a. Verify that the alarm filter is not on. See the [“DLP-G128 Disable Alarm Filtering” task on page 8-28](#) as necessary.
- b. Verify that no unexplained alarms appear on the network. If alarms appear, investigate and resolve them before continuing. Refer to the *Cisco ONS 15454 DWDM Troubleshooting Guide* for procedures.

Step 3 If you are removing and replacing a card, go to [Step 5](#).

Step 4 If you are permanently removing a card, go to [Step 11](#).

Step 5 To remove and replace a card, complete the following tasks, as needed:

- The circuits traversing through the card that needs to be replaced (for example, an amplifier) need to be protection switched. For instance, if the card you want to replace is an active transponder (TXP) or muxponder (MXP) in a Y-cable protection group, complete the [“DLP-G179 Apply a Force Y-Cable or Splitter Protection Switch” task on page 10-38](#) to force traffic away from the TXP or MXP that you will remove. If the card you want to replace is the standby TXP or MXP in a Y-cable protection group, complete the [“DLP-G182 Apply a Lockout” task on page 10-40](#) to prevent traffic from switching to the TXP or MXP that you will remove.
- If the card is used as a node timing reference, complete the [“NTP-G112 Change the Node Timing Reference” procedure on page 13-17](#) to change the timing reference to a card that will not be removed.

- If the card is an OSCM or OSC-CSM with an optical service channel (OSC) or TXP, MXP cards with generic communications channel (GCC) termination, complete the “[NTP-G85 Modify or Delete OSC Terminations, DCC/GCC Terminations, and Provisionable Patchcords](#)” procedure on [page 10-42](#) to delete the termination and recreate it on a card that will not be removed.



Note If you delete a card in CTC but do not remove it from the shelf, it will reboot and reappear in CTC.

- Step 6** Physically remove the card:
- Disconnect any cables.
 - Open the card latches/ejectors.
 - Use the latches/ejectors to pull the card forward and away from the shelf.
- Step 7** Insert the new card using one of the following procedures as applicable:
- [NTP-G30 Install the DWDM Cards, page 3-44](#)
 - [NTP-G32 Install the Transponder and Muxponder Cards, page 3-50](#)
- Step 8** Continue with the “[NTP-G34 Install Fiber-Optic Cables on DWDM Cards and DCUs](#)” procedure on [page 3-56](#).
- Step 9** Complete the following tasks or procedures, as needed:
- If you switched a Y-cable protection group in [Step 5](#), complete the “[DLP-G180 Clear a Manual or Force Y-Cable or Splitter Protection Switch](#)” task on [page 10-39](#).
 - If you deleted circuits in [Step 5](#), complete the “[DLP-G105 Provision Optical Channel Network Connections](#)” task on [page 7-11](#).
 - If you switched the timing reference in [Step 5](#), complete the “[NTP-G112 Change the Node Timing Reference](#)” procedure on [page 13-17](#) to change the reference back to the new card.
 - If you deleted an OSC or GCC termination in [Step 5](#), complete the “[NTP-G38 Provision OSC Terminations](#)” procedure on [page 3-83](#) or the “[DLP-G76 Provision DCC/GCC Terminations](#)” task on [page 7-22](#).
- Step 10** Go to [Step 13](#).
- Step 11** To permanently remove a card, complete the following tasks:
- Delete the circuits associated with the card being removed. Complete the “[DLP-G106 Delete Optical Channel Network Connections](#)” task on [page 7-13](#), and the “[DLP-G347 Delete Optical Channel Client Connections](#)” task on [page 7-8](#) as needed.
 - Physically remove the card:
 - Disconnect any cables.
 - Open the card latches/ejectors.
 - Use the latches/ejectors to pull the card forward and away from the shelf.
- Step 12** If the card you are removing is an OSCM, OSC-CSM, DWDM Amplifier, or Filter card, complete the following tasks; otherwise, go to [Step 13](#).
- Reconfigure the circuits (OCHCC, OCHNC, Trails) as needed. Complete the “[DLP-G105 Provision Optical Channel Network Connections](#)” task on [page 7-11](#), and the “[DLP-G346 Provision Optical Channel Client Connections](#)” task on [page 7-4](#) as needed.
 - Reload ANS provisioning. Complete the “[NTP-G143 Import the Cisco MetroPlanner NE Update Configuration File](#)” task on [page 3-38](#).

- Relaunch ANS. Complete the “[NTP-G37 Run Automatic Node Setup](#)” task on page 3-82.

Step 13 Click the **Alarms** tab.

- Verify that the alarm filter is not on. See the “[DLP-G128 Disable Alarm Filtering](#)” task on page 8-28 as necessary.
- Verify that no unexplained alarms appear on the network. If alarms appear, investigate and resolve them. Refer to the *Cisco ONS 15454 DWDM Troubleshooting Guide* for procedures.

Stop. You have completed this procedure.

DLP-G254 Place OPT-BST, OPT-BST-E, OPT-BST-L, and OPT-PRE Ports Out of Service

Purpose	This task places OPT-BST, OPT-BST-E, OPT-BST-L, and OPT-PRE card ports out of service in preparation for card removal.
Tools/Equipment	None
Prerequisite Procedures	DLP-G46 Log into CTC, page 2-25
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

- Step 1** On the shelf graphic in CTC, double-click the OPT-BST, OPT-BST-E, OPT-BST-L, or OPT-PRE card with the ports that you want to put out of service.
 - Step 2** Click the **Provisioning > Optical Line > Parameters** tabs.
 - Step 3** In the Admin State column for the card’s ports, choose **OOS,DSBLD** (ANSI) or **Locked,disabled** (ETSI) for each port that does not have an OOS-MA,DSBLD or Locked-enabled,disabled service state.
 - Step 4** Click **Apply**.
 - Step 5** In the confirmation dialog box, click **Yes**.
 - Step 6** Click the **Provisioning > Opt Apli Line > Parameters** tabs.
 - Step 7** In the Admin State column for the card’s ports, choose **OOS,DSBLD** or **Locked,disabled** (ETSI) for each port that does not have an OOS-MA,DSBLD or Locked,disabled service state.
 - Step 8** Click **Apply**.
 - Step 9** In the confirmation dialog box, click **Yes**.
 - Step 10** Return to your originating procedure (NTP).
-

DLP-G318 Place OPT-BST, OPT-BST-E, OPT-BST-L, and OPT-PRE Ports In Service

Purpose	This task places OPT-BST, OPT-BST-E, OPT-BST-L, and OPT-PRE card ports in service.
Tools/Equipment	None
Prerequisite Procedures	DLP-G46 Log into CTC, page 2-25
Required/As Needed	As needed
Onsite/Remote	Onsite or remote
Security Level	Provisioning or higher

-
- Step 1** On the shelf graphic in CTC, double-click the OPT-BST, OPT-BST-E, OPT-BST-L, or OPT-PRE card with the ports that you want to put in service.
- Step 2** Click the **Provisioning > Optical Line > Parameters** tabs.
- Step 3** In the Admin State column for the card's ports, choose **IS,AINS** (ANSI) or **Unlocked-automaticInService** (ETSI) for Port 1 (COM-RX) of the OPT-PRE or Ports 2 (OSC-RX) and 3 (COM-TX) of the OPT-BST, OPT-BST-E, or OPT-BST-L cards.
- Step 4** Click **Apply**.
- Step 5** In the confirmation dialog box, click **Yes**.
- Step 6** Return to your originating procedure (NTP).
-

NTP-G127 Add an AD-xC-xx.x Card to an OADM Node

Purpose	This procedure adds an AD-xC-xx.x card to an optical add/drop multiplexing (OADM) node.
Tools/Equipment	None
Prerequisite Procedures	Chapter 3, "Turn Up a Node" A Cisco MetroPlanner OADM site plan recalculated for the new OADM card
Required/As Needed	As needed
Onsite/Remote	Onsite
Security Level	Provisioning or higher



Note Do not begin this procedure until the Cisco MetroPlanner site plan has been recalculated with the new AD-xC-xx.x card added to the OADM node.



Note During this procedure, you will use TL1 commands to delete and recreate optical channel network connection (OCHNC) cross-connects. You might need to refer to the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.



Caution This procedure will affect the service of unprotected circuits that pass through the OADM node.

- Step 1** Complete the “[DLP-G46 Log into CTC](#)” task on page 2-25 at a node on the OADM network.
- Step 2** In node view (single-shelf mode) or multishelf view (multishelf mode), display the OADM node where you will add the card.
- Step 3** Click the **Circuits** tab.
- Step 4** Make a list of all OCHNCs and/or OCHCCs that are carried on the express path for both the east-to-west (E > W) and west-to-east (W > E) directions.
- Step 5** For OCHNCs and/or OCHCCs identified in [Step 4](#) that are routed on the active path of a splitter or Y-cable protection group, force the traffic to the protect path in the opposite side of the ring using the “[DLP-G179 Apply a Force Y-Cable or Splitter Protection Switch](#)” task on page 10-38.
- Step 6** Click the **Circuits** tab.
- Step 7** Complete the following steps for all OCHNCs and/or OCHCCs carried on the express path that were identified in [Step 4](#):
- Choose the OCHNC or OCHCC circuit(s) and click **Edit**. (To choose multiple circuits, press the Shift key while you click the circuits.)
 - In the Edit Circuit dialog box, click the **State** tab.
 - In the State field on the right, choose **OOS,DSBLD** (ANSI) or **Locked,disabled** (ETSI) from the drop-down list.
 - Click **Apply**.
 - Repeat Steps [a](#) through [d](#) for each OCHNC or OCHCC circuit.
- Step 8** From the Tools menu, choose **Open TL1 Connection**.
- Step 9** In the Select Node dialog box, choose the OADM node where you will add the AD-xC-xx.x card and click **OK**.
- Step 10** In the TL1 dialog box, use the **DLT-OCHNC** command to delete the OCHNC cross-connects for the express path OCHNC and/or the relative OCH-TRAIL for the OCHCCs listed in [Step 4](#), as follows:
`DLT-OCHNC:[<TID>]:<SRC>,<DST>:<CTAG>:::[CKTID=<CKTID>],[CMDMDE=<CMDMDE>];`
 where:
- <SRC> is the Source access identifier from the “CHANNEL” section. In 2-way wavelength connection sources both directions need to be indicated.
 - <DST> is the Destination access identifier from the “LINE” section. In 2-way wavelength connection sources both directions need to be indicated.
 - <CKTID> is the cross-connect ID. The default is Blank or None. String of ASCII characters. Maximum length is 48. If CKTID is empty or null the CKTID field will not be displayed.
 - <CMDMDE> is the command execution mode.
- For additional information, including valid command values, refer to the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.
- Step 11** Click **Close** to close the TL1 dialog box.
- Step 12** In node view (single-shelf mode) or multishelf view (multishelf mode), click the **Provisioning > WDM-ANS > Internal Patchcords** tabs.

- Step 13** Highlight the two express connections that carry the deleted circuits passing through the node. (The express connections are the only ones connecting an EXP_TX port on the last west-side OADM card, W > E, with an EXP_RX port on the first east-side OADM card, W > E.)
- Step 14** Click **Delete**.
- Step 15** Remove the physical express cables between the EXP_TX and EXP_RX ports specified in [Step 13](#).
- Step 16** Insert the new AD-xC-xx.x card in the slot identified by your Cisco MetroPlanner site plan.
- Step 17** Complete the “[NTP-G34 Install Fiber-Optic Cables on DWDM Cards and DCUs](#)” procedure on [page 3-56](#) for the OADM node, following the new internal connections table generated by Cisco MetroPlanner.
- Step 18** Complete the “[NTP-G152 Create and Verify Internal Patchcords](#)” procedure on [page 3-80](#).
- Step 19** Import the recalculated OADM site parameters. See the “[NTP-G143 Import the Cisco MetroPlanner NE Update Configuration File](#)” task on [page 3-38](#).
- Step 20** In node view (single-shelf mode) or multishelf view (multishelf mode), click the **Provisioning > WDM-ANS > Port Status** tabs.
- Step 21** Click **Launch ANS**.
- Step 22** From the Tools menu, choose **Open TL1 Connection**.
- Step 23** In the Select Node dialog box, choose the OADM node and click **OK**.
- Step 24** In the TL1 dialog box, use the **ENT-OCHNC** command to create the OCHNC or relative OCH-Trail of the OCHCC cross-connects that were deleted in [Step 10](#), as follows:
- ```
ENT-OCHNC:[<TID>]:<SRC>,<DST>:<CTAG>::[<WCT>]:[CKTID=<CKTID>],
[CMDMDE=<CMDMDE>]:[<PST>[,<SST>]];
```
- where:
- <SRC> is the Source access identifier from the “CHANNEL” section. In 2-way wavelength connection sources both directions need to be indicated.
  - <DST> is the Destination access identifier from the “LINE” section. In 2-way wavelength connection sources both directions need to be indicated.
  - <WCT> Wavelength connection type, either 1WAY or 2WAY. The default is 1WAY.
  - <CKTID> is the cross-connect ID. The default is Blank or None. String of ASCII characters. Maximum length is 48. If CKTID is empty or null the CKTID field will not be displayed.
  - <CMDMDE> is the command execution mode.
  - <PST> is the primary state, either IS or OOS.
  - <SST> is the secondary state.
- For additional information and a list of valid command values, see the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.
- Step 25** Click **Close** to close the TL1 dialog box.
- Step 26** In node view (single-shelf mode) or multishelf view (multishelf mode), click the **Circuits** tab.
- Step 27** Complete the following steps for all OCHNCs and/or OCHCCs set to OOS,DSBLD (ANSI) or Locked,disabled (ETSI) in [Step 7](#):
- a. Choose the OCHNC or OCHCC circuit(s) and click **Edit**. To choose multiple circuits, press the Shift key while you click the circuits.
  - b. In the Edit Circuit dialog box, click the **State** tab.

- c. In the State field on the right, choose **IS,AINS** (ANSI) or **Unlocked,automaticInService** (ETSI) from the drop-down list.
- d. Click **Apply**, and then click **OK**.

**Step 28** Complete the “[DLP-G180 Clear a Manual or Force Y-Cable or Splitter Protection Switch](#)” task on [page 10-39](#) for OCHNCs and/or OCHCCs that were switched to the opposite side of the ring as part of a splitter or Y-cable protection group to return the traffic to its condition before the card was added.

**Stop. You have completed this procedure.**

---

## NTP-G129 Add a DWDM Node

|                                |                                                                                                                |
|--------------------------------|----------------------------------------------------------------------------------------------------------------|
| <b>Purpose</b>                 | This procedure adds a DWDM node to an existing Multi-Service Transport Platform (MSTP) network.                |
| <b>Tools/Equipment</b>         | None                                                                                                           |
| <b>Prerequisite Procedures</b> | <a href="#">Chapter 3, “Turn Up a Node”</a><br>A Cisco MetroPlanner network plan recalculated for the new node |
| <b>Required/As Needed</b>      | As needed                                                                                                      |
| <b>Onsite/Remote</b>           | Onsite                                                                                                         |
| <b>Security Level</b>          | Provisioning or higher                                                                                         |



### Note

Do not begin this procedure until the Cisco MetroPlanner network plan has been updated and recalculated with the new DWDM node.

---



### Note

This procedure assumes all turn-up procedures provided in [Chapter 3, “Turn Up a Node,”](#) have been completed at the node that will be added. If this has not been completed, do not continue. Complete the turn up procedures at the new node before you complete this procedure.

---



### Note

During this procedure, you will use TL1 commands to delete and recreate OCHNC and OCHCC cross-connects. You might need to refer to the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.

---



### Caution

To complete this procedure, a span will be disconnected where the new node is added. This will affect the service of any unprotected circuits that pass through that span.

---

**Step 1** At the node that will be added, complete the “[NTP-G51 Verify DWDM Node Turn-Up](#)” procedure on [page 6-2](#). If the node has not been turned up, do not continue. Complete procedures in [Chapter 3, “Turn Up a Node,”](#) and [Chapter 4, “Perform Node Acceptance Tests,”](#) then begin this procedure again.

**Step 2** If the Cisco MetroPlanner network design has not been updated and recalculated for the new node and client services, update and recalculate it now, following the procedures in the Cisco MetroPlanner documentation.



- Step 3** Identify the fiber spans that must be disconnected to insert the new node.
- Step 4** Complete the “[DLP-G46 Log into CTC](#)” task on page 2-25 at a DWDM node that is active on the network where you want to add the new DWDM node.
- Step 5** In network view, click the **Circuits** tab.
- Step 6** Identify the OCHCCs and/or OCHNCs that are carried on the fiber span express path that you identified in [Step 3](#) in both the east-to-west and west-to-east directions.
- Step 7** If the OCHCC and/or OCHNC circuit is on the active path and is protected by a splitter or Y-cable protection group, complete the “[DLP-G179 Apply a Force Y-Cable or Splitter Protection Switch](#)” task on page 10-38 to force traffic away from the span where the node will be added. If not, continue with [Step 8](#).
- Step 8** For each circuit identified in [Step 6](#) that was not switched in [Step 7](#) (unprotected circuits), complete the following steps:
- In network view, select the OCHNC and/or OCHCC circuit and click **Edit**.
  - In the Edit Circuit dialog box, click the **State** tab.
  - In the State field on the right, choose **OOS,DSBLD** (ANSI) or **Locked,disabled** (ETSI) from the drop-down list.
  - Click **Apply**, then click **OK**.
- Step 9** Remove the fibers from the cards at the adjacent nodes that will connect to the new node.
- Step 10** Install the fibers from the adjacent nodes that will connect to the new node using the “[NTP-G34 Install Fiber-Optic Cables on DWDM Cards and DCUs](#)” procedure on page 3-56.
- Step 11** Create cross-connects on the new node for all circuits identified in [Step 6](#):
- From the Tools menu, choose **Open TL1 Connection**.
  - In the Select Node dialog box, choose the new node and click **OK**.
  - In the TL1 dialog box, use the **ENT-OCHNC** command to create the OCHNC and/or OCHCC cross-connects for each unprotected pass-through circuit as follows:  

```
ENT-OCHNC:[<TID>]:<SRC>,<DST>:<CTAG>::[<WCT>]:[CKTID=<CKTID>],
[CMDMDE=<CMDMDE>]:[<PST>[,<SST>]];
```

where:

    - <SRC> is the Source access identifier from the “CHANNEL” section. In 2-way wavelength connection sources both directions need to be indicated.
    - <DST> is the Destination access identifier from the “LINE” section. In 2-way wavelength connection sources both directions need to be indicated.
    - <WCT> Wavelength connection type, either 1WAY or 2WAY. The default is 1WAY.
    - <CKTID> is the cross-connect ID. The default is Blank or None. String of ASCII characters. Maximum length is 48. If CKTID is empty or null the CKTID field will not be displayed.
    - <CMDMDE> is the command execution mode.
    - <PST> is the primary state, either IS or OOS.
    - <SST> is the secondary state.

For additional information and a list of valid command values, see the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.
  - Click **Close** to close the TL1 dialog box.

- e. Repeat [Step 8](#) to change the circuits placed in OOS,DSBLD (ANSI) or Locked,disabled (ETSI) back in service by choosing IS-AINS (ANSI) or Unlocked,automaticInService (ETSI) in the State drop-down list.
- Step 12** Complete the “[DLP-G180 Clear a Manual or Force Y-Cable or Splitter Protection Switch](#)” task on [page 10-39](#) for the circuits that were switched in [Step 7](#) to return the traffic to its original paths.
- Step 13** Complete the “[DLP-G106 Delete Optical Channel Network Connections](#)” task on [page 7-13](#) for circuits identified in [Step 6](#) that will not be part of the traffic matrix after the node is added.
- Step 14** Divide the circuits that existed previously into two groups: those that will terminate in the new node and those that will pass through it.
- Step 15** For circuits that will terminate in the new node, complete the “[DLP-G106 Delete Optical Channel Network Connections](#)” task on [page 7-13](#) and then the “[DLP-G105 Provision Optical Channel Network Connections](#)” task on [page 7-11](#).
- Step 16** Complete the “[DLP-G105 Provision Optical Channel Network Connections](#)” task on [page 7-11](#) to create new circuits.

**Stop. You have completed this procedure.**

---

## NTP-G130 Remove a DWDM Node

|                                |                                                                      |
|--------------------------------|----------------------------------------------------------------------|
| <b>Purpose</b>                 | This procedure removes a node from a DWDM network.                   |
| <b>Tools/Equipment</b>         | None                                                                 |
| <b>Prerequisite Procedures</b> | A Cisco MetroPlanner network plan recalculated for the new topology. |
| <b>Required/As Needed</b>      | As needed                                                            |
| <b>Onsite/Remote</b>           | Onsite                                                               |
| <b>Security Level</b>          | Provisioning or higher                                               |



### Note

During this procedure, you will use TL1 commands to delete and recreate OCHNC or OCHCC cross-connects. You might need to refer to the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH TL1 Command Guide*.



### Caution

This procedure will affect the service of unprotected circuits that pass through the span where the node will be removed.

- Step 1** If the Cisco MetroPlanner network design has not been updated and recalculated with the node removed, update and recalculate the design now by following the procedures in the Cisco MetroPlanner documentation.
- Step 2** Complete the “[NTP-G21 Log into the ONS 15454 GUI](#)” task on [page 2-23](#) at the DWDM target node that will be removed.
- Step 3** Click the **Circuits** tab.
- Step 4** Identify all the OCHNCs and/or OCHCCs that are passing through or are added and dropped at the node that will be removed.

**Step 5** Delete the OCHNCs and OCHCCs identified in [Step 4](#) that terminate (add/drop) on the target DWDM node. See the “[DLP-G347 Delete Optical Channel Client Connections](#)” task on [page 7-8](#) and the “[DLP-G106 Delete Optical Channel Network Connections](#)” task on [page 7-13](#) to delete to delete OCHCCs and OCHNCs, respectively.

**Step 6** For the protected pass through circuits on the target node, perform [Step 7](#). Else, go to [Step 10](#).




---

**Note** Non-protected pass through circuits need not be modified or deleted.

---

**Step 7** If the OCHNC and OCHCC circuits pass through the target node on the active path and are protected by a splitter or Y-cable protection group, navigate to an adjacent node connected to the target node and complete the “[DLP-G179 Apply a Force Y-Cable or Splitter Protection Switch](#)” task on [page 10-38](#) to force the traffic away from the node that will be deleted. Otherwise, continue with [Step 8](#).

**Step 8** Complete the following steps for the protected pass through circuits:

- a. Select the OCHNCs or OCHCCs and click **Edit**.
- b. In the Edit Circuit dialog box, click the **State** tab.
- c. In the State field, choose **OOS,DSBLD** (ANSI) or **Locked,disabled** (ETSI) from the drop-down list.
- d. Click **Apply**, then click **OK**.

**Step 9** Complete the following steps to delete the cross-connects on the target node for each circuit placed in the OOS,DSBLD (ANSI) or Locked,disabled (ETSI) state in [Step 8](#):

- a. From the Tools menu, choose **Open TL1 Connection**.
- b. In the Select Node dialog box, select the new node and click **OK**.
- c. In the TL1 dialog box, use the **DLT-OCHNC** command to delete the OCHNC cross-connects for each unprotected pass-through circuit as follows:

```
DLT-OCHNC:[<TID>]:<SRC>,<DST>:<CTAG>:::[CKTID=<CKTID>],
[CMDMDE=<CMDMDE>];
```

where:

- <SRC> is the source access identifier from the Channel section in a two-way wavelength.
- <DST> is the destination access identifier from the LINEWL section in a two-way wavelength.
- <CKTID> is the cross-connect ID. The default is Blank or None. CKTD is a string of ASCII characters. The maximum length is 48. If CKTID is empty or null, the CKTID field will not be displayed.
- <CMDMDE> is the command execution mode. NORM mode is the default behavior for all commands but you can specify FRCD to force the system to override a state in which the command would normally be denied.

For additional information, including valid command values, refer to the *Cisco ONS SONET TL1 Command Guide* or the *Cisco ONS 15454 SDH and Cisco ONS 15600 SDH TL1 Command Guide*.

- d. Click **Close** to close the TL1 dialog box.

**Step 10** Remove the fibers from the target node, and reconnect the fibers to the adjacent nodes. Note that once the fibers are rerouted, the non-protected pass through circuits will go to OOS-PARTIAL (ANSI) or Locked-partial (ETSI) state.

**Step 11** Complete the following steps to update the ANS parameters at the adjacent nodes:

- a. Display an adjacent node in node view.

- b. Complete the “[NTP-G143 Import the Cisco MetroPlanner NE Update Configuration File](#)” procedure on page 3-38 to load the new NE Update file onto the node.
  - c. Complete the “[NTP-G37 Run Automatic Node Setup](#)” procedure on page 3-82 to recalculate the ANS parameters at the node.
  - d. Display the next adjacent node in node view.
  - e. Repeat Steps b and c for the second adjacent node.
- Step 12** Repeat [Step 8](#) to change the circuits placed in OOS,DSBLD (ANSI) or Locked,disabled (ETSI) back in service by changing the Target Circuit Admin State field to **IS-AINS** (ANSI) or **Unlocked,AutomaticInService** (ETSI).
- Step 13** Complete the “[DLP-G180 Clear a Manual or Force Y-Cable or Splitter Protection Switch](#)” task on page 10-39 for the OCHNCs and OCHCCs that were switched in [Step 7](#).
- Step 14** To discover the non-protected pass through circuits that are in the OOS-PARTIAL (ANSI) or Locked-partial (ETSI) state after completing [Step 10](#), select the circuit and choose **Tools > Circuits > Reconfigure Circuits** from the menu bar. The Reconfigure Circuits dialog box is displayed; click **Yes**. **Stop. You have completed this procedure.**
- 

## NTP-G146 Add a Rack and/or Shelf to a Multishelf Node

|                                |                                                                                                                                                                                                                                                                                                                                                                |
|--------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Purpose</b>                 | This procedure adds a rack and/or subtending shelf to a multishelf node.                                                                                                                                                                                                                                                                                       |
| <b>Tools/Equipment</b>         | None                                                                                                                                                                                                                                                                                                                                                           |
| <b>Prerequisite Procedures</b> | One of the following: <ul style="list-style-type: none"> <li>• <a href="#">NTP-G145 Connect a Multishelf Node and Subtending Shelves to an MS-ISC-100T Card</a>, page 1-78, or</li> <li>• <a href="#">NTP-G158 Connect a Multishelf Node and Subtending Shelves to a Cisco Catalyst 2950</a>, page 1-80</li> </ul> <a href="#">Chapter 3, “Turn Up a Node”</a> |
| <b>Required/As Needed</b>      | As needed                                                                                                                                                                                                                                                                                                                                                      |
| <b>Onsite/Remote</b>           | Onsite                                                                                                                                                                                                                                                                                                                                                         |
| <b>Security Level</b>          | Provisioning or higher                                                                                                                                                                                                                                                                                                                                         |



### Note

Each shelf you want to add to a multishelf configuration must have network connectivity. For more information, see [Chapter 2, “Connect the PC and Log into the GUI.”](#)

---

- Step 1** Complete the “[DLP-G46 Log into CTC](#)” task on page 2-25 at the multishelf DWDM node where you want to add a shelf.
- Step 2** To add a rack, in multishelf view, right click the gray area and choose **Add Rack**. If you do not need to add a rack, continue with [Step 3](#).
- Step 3** To add a shelf, in multishelf view, right-click the white space inside the rack and choose **Add Shelf**.
- Step 4** In the Shelf ID Selection dialog box, choose a shelf ID from the drop-down list.
- Step 5** Click **OK**. The shelf appears in the multishelf view.

- Step 6** Complete the “[DLP-G46 Log into CTC](#)” task on page 2-25 at the subtending shelf.
- Step 7** In multishelf view, click the **Provisioning > General > Multishelf Config** tabs.
- Step 8** Click **Enable as Subtended Shelf**.
- Step 9** From the Shelf ID drop-down list, choose the shelf ID that you created in [Step 4](#).
- Step 10** Click **Apply**.
- Step 11** In the confirmation dialog box, click **Yes** to reboot the shelf. The CTC view changes to network view and the node icon changes to gray. (This might take several minutes.)
- Step 12** If you are connecting the new subtending shelf to the EAP patch panel, complete the following steps. If not, continue with [Step 13](#).
- Using a cross-over (CAT 5) LAN cable, plug one connector into the front panel of the subtending shelf TCC2/TCC2P card in Slot 7 and plug the other end into the SSC port on the left patch panel.
  - Using a cross-over (CAT 5) LAN cable, plug one connector into the front panel of the subtending shelf TCC2/TCC2P card in Slot 11 and plug the other end into the SSC port on the right patch panel.
- Step 13** If you are connecting the subtending shelf to the Catalyst 2950 switch, complete the following steps. If not, continue with [Step 14](#).
- Plug one end of a cross-over (CAT-5) LAN cable into the front panel of the subtending shelf TCC2/TCC2P card in Slot 7 and plug the other end into Port 2 of the first Catalyst 2950.
  - Plug one end of a cross-over (CAT-5) LAN cable into the front panel of the subtending shelf TCC2/TCC2P card in Slot 11 and plug the other end into Port 2 of the backup Catalyst 2950.
- Step 14** Repeat Steps [3](#) through [12](#) for each subtending shelf in the multishelf configuration.
- Stop. You have completed this procedure.**

## NTP-G147 Delete a Shelf and/or Rack from a Multishelf Node

|                                |                                                                                                                                                                                                                                                                                                                                                            |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Purpose</b>                 | This procedure deletes a shelf and/or rack from a multishelf node in the CTC window.                                                                                                                                                                                                                                                                       |
| <b>Tools/Equipment</b>         | None                                                                                                                                                                                                                                                                                                                                                       |
| <b>Prerequisite Procedures</b> | One of the following: <ul style="list-style-type: none"> <li><a href="#">NTP-G145 Connect a Multishelf Node and Subtending Shelves to an MS-ISC-100T Card, page 1-78</a>, or</li> <li><a href="#">NTP-G158 Connect a Multishelf Node and Subtending Shelves to a Cisco Catalyst 2950, page 1-80</a></li> </ul> <a href="#">Chapter 3, “Turn Up a Node”</a> |
| <b>Required/As Needed</b>      | As needed                                                                                                                                                                                                                                                                                                                                                  |
| <b>Onsite/Remote</b>           | Onsite                                                                                                                                                                                                                                                                                                                                                     |
| <b>Security Level</b>          | Provisioning or higher                                                                                                                                                                                                                                                                                                                                     |



### Note

You cannot delete a node controller shelf from a multishelf node configuration.

- 
- Step 1** Complete the “[DLP-G46 Log into CTC](#)” task on page 2-25 at the multishelf DWDM node where you want to delete a shelf or rack. If you want to delete a shelf, continue with [Step 2](#). If you want to delete a rack only, go to [Step 9](#).
- Step 2** Complete the following tasks, as needed:
- If cards on the shelf carry unprotected circuits, you must delete the circuits. Complete the “[DLP-G106 Delete Optical Channel Network Connections](#)” task on page 7-13 or the or the “[DLP-G347 Delete Optical Channel Client Connections](#)” task on page 7-8.
  - If cards use internal patchcords, complete the “[DLP-G355 Delete an Internal Patchcord](#)” task on page 3-82.
  - If cards on the shelf are an OSCM or OSC-CSM with an OSC or GCC termination, complete the “[NTP-G85 Modify or Delete OSC Terminations, DCC/GCC Terminations, and Provisionable Patchcords](#)” procedure on page 10-42.
  - Put all ports in the Out-of-Service and Management, Disabled (OOS-MA,DSBLD) (ANSI) or Locked-enabled,disabled (ETSI) service state. For more information, see [Chapter 11, “Change DWDM Card Settings.”](#)




---

**Note** It is not necessary to delete the cards from the shelf before deleting a shelf.

---

- Step 3** From the View menu, choose **Go to Parent View** to return to multishelf view.
- Step 4** Right-click on the shelf in the rack for the subtending shelf you want to delete and choose **Delete Shelf**.
- Step 5** In the confirmation dialog box, click **Yes**.
- Step 6** To return the deleted shelf to a single-shelf node, you must use the LCD panel:
- a. Repeatedly press the **Status** button until Shelf Status appears.
  - b. Repeatedly press the **Port** button until Controller Status=MS Config appears.
  - c. Press **Status** again and press **Port** to set multishelf mode to MS=N.
  - d. Press **Status** to choose Done.
  - e. Repeatedly press **Status** until “Save and Reboot?” appears, and then press **Slot** to choose Apply. This reboots the shelf. A “Saving changes; TCC may reboot” message appears on the LCD.
- Step 7** After the TCC2/TCC2P reboot is complete, complete the following steps to disconnect the removed subtending shelf from the patch panel or Catalyst 2950.
- a. Remove the cross-over (CAT 5) LAN cable from the front panel of the TCC2/TCC2P card in Slot 7.
  - b. Remove the cross-over (CAT 5) LAN cable from the front panel of the TCC2/TCC2P card in Slot 11.
- Step 8** Reconnect the shelf to the LAN either on the backplane or one of the front panel TCC2/TCC2Ps. For more information, see [Chapter 2, “Connect the PC and Log into the GUI.”](#)
- Step 9** To delete an empty rack from the CTC window, right-click in the gray area on the rack graphic and choose **Delete Rack**.

**Stop. You have completed this procedure.**

---