



## **IPv4 Routing Configuration Guide, Cisco IOS XE 17 (Cisco NCS 520 Series)**

**First Published:** 2019-11-26

**Last Modified:** 2020-01-12

### **Americas Headquarters**

Cisco Systems, Inc.  
170 West Tasman Drive  
San Jose, CA 95134-1706  
USA  
<http://www.cisco.com>  
Tel: 408 526-4000  
800 553-NETS (6387)  
Fax: 408 527-0883

THE SPECIFICATIONS AND INFORMATION REGARDING THE PRODUCTS IN THIS MANUAL ARE SUBJECT TO CHANGE WITHOUT NOTICE. ALL STATEMENTS, INFORMATION, AND RECOMMENDATIONS IN THIS MANUAL ARE BELIEVED TO BE ACCURATE BUT ARE PRESENTED WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED. USERS MUST TAKE FULL RESPONSIBILITY FOR THEIR APPLICATION OF ANY PRODUCTS.

THE SOFTWARE LICENSE AND LIMITED WARRANTY FOR THE ACCOMPANYING PRODUCT ARE SET FORTH IN THE INFORMATION PACKET THAT SHIPPED WITH THE PRODUCT AND ARE INCORPORATED HEREIN BY THIS REFERENCE. IF YOU ARE UNABLE TO LOCATE THE SOFTWARE LICENSE OR LIMITED WARRANTY, CONTACT YOUR CISCO REPRESENTATIVE FOR A COPY.

The Cisco implementation of TCP header compression is an adaptation of a program developed by the University of California, Berkeley (UCB) as part of UCB's public domain version of the UNIX operating system. All rights reserved. Copyright © 1981, Regents of the University of California.

NOTWITHSTANDING ANY OTHER WARRANTY HEREIN, ALL DOCUMENT FILES AND SOFTWARE OF THESE SUPPLIERS ARE PROVIDED "AS IS" WITH ALL FAULTS. CISCO AND THE ABOVE-NAMED SUPPLIERS DISCLAIM ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, THOSE OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NON-INFRINGEMENT OR ARISING FROM A COURSE OF DEALING, USAGE, OR TRADE PRACTICE.

IN NO EVENT SHALL CISCO OR ITS SUPPLIERS BE LIABLE FOR ANY INDIRECT, SPECIAL, CONSEQUENTIAL, OR INCIDENTAL DAMAGES, INCLUDING, WITHOUT LIMITATION, LOST PROFITS OR LOSS OR DAMAGE TO DATA ARISING OUT OF THE USE OR INABILITY TO USE THIS MANUAL, EVEN IF CISCO OR ITS SUPPLIERS HAVE BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Any Internet Protocol (IP) addresses and phone numbers used in this document are not intended to be actual addresses and phone numbers. Any examples, command display output, network topology diagrams, and other figures included in the document are shown for illustrative purposes only. Any use of actual IP addresses or phone numbers in illustrative content is unintentional and coincidental.

All printed copies and duplicate soft copies of this document are considered uncontrolled. See the current online version for the latest version.

Cisco has more than 200 offices worldwide. Addresses and phone numbers are listed on the Cisco website at [www.cisco.com/go/offices](http://www.cisco.com/go/offices).

The documentation set for this product strives to use bias-free language. For purposes of this documentation set, bias-free is defined as language that does not imply discrimination based on age, disability, gender, racial identity, ethnic identity, sexual orientation, socioeconomic status, and intersectionality. Exceptions may be present in the documentation due to language that is hardcoded in the user interfaces of the product software, language used based on standards documentation, or language that is used by a referenced third-party product.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/c/en/us/about/legal/trademarks.html>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1721R)

© 2020 Cisco Systems, Inc. All rights reserved.



## CONTENTS

---

### CHAPTER 1

#### **IPv4 Routing 1**

- Limitations for IPv4 Routing 1
- Configuring IP Address on BDI Interface 2
- Verifying IPv4 Routing 2

---

### CHAPTER 2

#### **Configuring OSPF 5**

- Cisco OSPF Implementation 5
- Route Distribution for OSPF 5
- Router Coordination for OSPF 6
- Limitation for OSPF 6
- How to Configure OSPF 6
  - Enabling OSPF 6
  - Configuring OSPF on BDI 6
  - Configuring Loopback on OSPF Interface 6
  - Configuration Examples for OSPF 7

---

### CHAPTER 3

#### **Configuring IS-IS 9**

- IS-IS Overview 9
- How to Configure IS-IS 9
  - Enabling IS-IS 9
  - Configuring IS-IS on BDI Interface 9
  - Configuring Loopback on IS-IS Interface 10
  - Configuration Examples for IS-IS 10

---

### CHAPTER 4

#### **Configuring BGP 11**

- BGP Overview 11

- Limitations for BGP 11
- How to Configure BGP 12
  - Configuring BGP on BDI 12
  - Verifying BGP Configuration 12
  - Configuration Examples for BGP 12

---

**CHAPTER 5**

- Configuring EIGRP 13**
  - EIGRP Features 13
  - How to Configure EIGRP 14
    - Configuring EIGRP 14
    - Configuration Examples for EIGRP 14

---

**CHAPTER 6**

- Configuring Static Route 15**
  - Static Route Overview 15
  - How to Configure Static Route 15
    - Configuring Static Route on BDI Interface 15
    - Verifying Static Route Configuration 15

---

**CHAPTER 7**

- Configuring IPv4 Unicast Routing ECMP 17**
  - IPv4 Unicast Routing ECMP 17
  - Limitation for IPv4 Unicast Routing ECMP 17
  - How to Configure IPv4 Unicast Routing ECMP 17
    - Configuring IPv4 Unicast Routing ECMP 17
    - Verifying IPv4 Unicast Routing ECMP Configuration 18



# CHAPTER 1

## IPv4 Routing

The IPv4 routing is supported only on BDI interfaces. The device supports Layer 3 functionality, where packets are routed across various bridge domain interfaces.

- [Limitations for IPv4 Routing, on page 1](#)
- [Configuring IP Address on BDI Interface, on page 2](#)
- [Verifying IPv4 Routing, on page 2](#)

## Limitations for IPv4 Routing

- The IPv4 routing is supported only on BDI interfaces, and not supported on physical interfaces (1G, 10G) and port channel interfaces.
- IP addresses cannot be configured on the physical and the port channel interface.
- The maximum number of IPv4 routes that can be learnt is 12,000.
- BDI level IP ACLs are not supported.
- VRRP and HSRP protocols are not supported.



---

**Note** Effective Cisco IOS XE Gibraltar 16.12.1 and later, VRRP and HSRP protocols are supported on the Cisco NCS 520 router.

---

- The maximum number of VRF lite sessions supported are 128.
- BDI statistics is supported only for CPU bounded traffic, for data traffic going over BDI interface will be shown on respective underlying EFP statistics.
- For adding static ARP, it is mandatory that you specify the static MAC address. For example, to configure static ARP, specify the following commands:
  - `arp<ip-add> <mac-add> arpa` under the **config** mode.
  - `mac static address <mac>` under the **config-if-srv** mode.
- The router sends Gratuitous ARP only when the BDI interface is brought up, and processes the Gratuitous ARP if it is of the request type.

- IPv6 is not supported.




---

**Note** Effective Cisco IOS XE Dublin 17.11.1, IPv6 configurations are supported on the management interface.

---

Starting from Cisco IOS XE Dublin 17.12.1, the IPv6 configuration for access-list, neighbor, route, and unicast routing are supported in the global configuration mode.

- IPv4 multicast is not supported.
- IPv4 MIBs are not supported.
- IP-FRR, LFA, segment routing, and policy-based routing are not supported.
- BFD is not supported.
- IP unnumbered is not supported.
- MPLS is not supported.

## Configuring IP Address on BDI Interface

To configure IP address on BDI interface, enter the following commands:

```
interface BDI10
ip address 192.0.2.0 255.255.255.0
end
```

## Verifying IPv4 Routing

Use the **show ip route** and **show ip route summary** commands to verify IP address on BDI interface:

```
router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
       n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       H - NHRP, G - NHRP registered, g - NHRP registration summary
       o - ODR, P - periodic downloaded static route, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    10.0.0.0/32 is subnetted, 1 subnets
O       10.0.0.1 [110/2] via 192.168.13.4, 1d01h, BDI210
         [110/2] via 192.0.2.4, 1d01h, BDI111
    10.0.0.1/32 is subnetted, 1 subnets
C       10.6.6.6 is directly connected, Loopback0
```

```

10.0.0.2/32 is subnetted, 1 subnets
O   10.8.8.8 [110/2] via 192.168.13.1, 1d01h, BDI210
    [110/2] via 192.0.2.1, 1d00h, BDI111
10.0.0.0/32 is subnetted, 1 subnets
O   192.0.2.0 [110/2] via 192.168.13.2, 03:20:31, BDI210
    [110/2] via 192.0.2.2, 03:20:29, BDI111
192.0.2.0/24 is variably subnetted, 2 subnets, 2 masks
C   192.0.2.0/24 is directly connected, BDI111
L   192.0.2.3/32 is directly connected, BDI111
192.168.13.0/24 is variably subnetted, 2 subnets, 2 masks
C   192.168.13.0/24 is directly connected, BDI210
L   192.168.13.3/32 is directly connected, BDI210

```

```
router#show ip route summary
```

```
IP routing table name is default (0x0)
```

```
IP routing table maximum-paths is 32
```

Route Source	Networks	Subnets	Replicates	Overhead	Memory (bytes)
application	0	0	0	0	0
connected	0	5	0	560	1560
static	0	0	0	0	0
ospf 30	0	3	0	576	948
Intra-area: 3 Inter-area: 0 External-1: 0 External-2: 0					
NSSA External-1: 0 NSSA External-2: 0					
isis 1	0	0	0	0	0
Level 1: 0 Level 2: 0 Inter-area: 0					
bgp 1	0	0	0	0	0
External: 0 Internal: 0 Local: 0					
internal	6				2792
Total	6	8	0	1136	5300







## CHAPTER 2

# Configuring OSPF

---

- [Cisco OSPF Implementation](#), on page 5
- [Route Distribution for OSPF](#), on page 5
- [Router Coordination for OSPF](#), on page 6
- [Limitation for OSPF](#), on page 6
- [How to Configure OSPF](#), on page 6

## Cisco OSPF Implementation

The Cisco implementation conforms to the OSPF Version 2 specifications detailed in the Internet RFC 2328. The following list outlines key features supported in the Cisco OSPF implementation:

- Stub areas
- Route redistribution
- Authentication
- Routing interface parameters
- Virtual links
- Not-so-stubby area (NSSA)
- OSPF over demand circuit

For more information on each key OSPF features, see [https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute\\_ospf/configuration/xs-3s/iro-xe-3s-book/iro-cfg.html#GUID-A999A739-6B1D-4E5E-9396-F7531469D805](https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute_ospf/configuration/xs-3s/iro-xe-3s-book/iro-cfg.html#GUID-A999A739-6B1D-4E5E-9396-F7531469D805).

## Route Distribution for OSPF

You can specify route redistribution. For more information on how to configure route redistribution, see [https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute\\_ospf/configuration/xs-3s/iro-xe-3s-book/iro-cfg.html#GUID-369415D9-E481-41AE-9387-ECEDFE461361](https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute_ospf/configuration/xs-3s/iro-xe-3s-book/iro-cfg.html#GUID-369415D9-E481-41AE-9387-ECEDFE461361).

# Router Coordination for OSPF

OSPF typically requires coordination among many internal routers: Area Border Routers (ABRs), which are routers connected to multiple areas, and Autonomous System Boundary Routers (ASBRs). For more information, see [https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute\\_ospf/configuration/xr-3s/iro-xe-3s-book/iro-cfg.html#GUID-CFFB7E62-5D56-4036-8DF7-F5BFC75ADF53](https://www.cisco.com/c/en/us/td/docs/ios-xml/ios/iproute_ospf/configuration/xr-3s/iro-xe-3s-book/iro-cfg.html#GUID-CFFB7E62-5D56-4036-8DF7-F5BFC75ADF53).

## Limitation for OSPF

- OSPFv3 is not supported.

## How to Configure OSPF

### Enabling OSPF

Before configuring, you need to enable OSPF.

To enable OSPF at the global configuration mode, enter the following commands:

```
enable
configure terminal
router ospf process-id
router-id <loopback ip-address>
network ip-address wildcard-mask area area-id
end
```

### Configuring OSPF on BDI

Before configuring, you need to enable OSPF.

To enable OSPF on the BDI interface, enter the following commands:

```
enable
configure terminal
interface BDI <bdi-no>
ip address <ip-address > <subnet-mask>
ip ospf <process-id> area <area-id>
end
```

For more information, see [How to Configure OSPF](#).

### Configuring Loopback on OSPF Interface

To configure loopback on OSPF interface, enter the following commands:

```
interface loopback<loopback-no>
ip address <ip-address > <subnet-mask>
```

```
ip ospf <process-id> area <area-id>
```

## Configuration Examples for OSPF

Refer the following [examples](#) on various configurations for OSPF.





## CHAPTER 3

# Configuring IS-IS

---

- [IS-IS Overview](#), on page 9
- [How to Configure IS-IS](#), on page 9

## IS-IS Overview

Intermediate System-to-Intermediate System (IS-IS) routing protocol is a link-state Interior Gateway Protocol (IGP). Link-state protocols are characterized by the propagation of the information required to build a complete network connectivity map on each participating device. That map is then used to calculate the shortest path to destinations.

The IS-IS protocol was developed in the late 1980s by Digital Equipment Corporation (DEC) and was standardized by the International Standards Organization (ISO) in ISO/IEC 10589. The current version of this standard is ISO/IEC 10589:2002.

For more information, refer [Information About IS-IS](#).

## How to Configure IS-IS

### Enabling IS-IS

To configure IS-IS, you need to enable IS-IS on the device and interface.

To enable IS-IS as an IP routing protocol on the device at the global configuration mode, enter the following commands:

```
enable
configure terminal
router isis [area-tag]
net network-entity-title
end
```

### Configuring IS-IS on BDI Interface

To enable IS-IS as an IP routing protocol on the BDI interface, enter the following commands:

```
enable
```

```
configure terminal
interface BDI<bdi-no>
ip address ip-address mask
ip router isis [area-tag]
end
```

For more information, see [Configuring IS-IS](#).

## Configuring Loopback on IS-IS Interface

To configure loopback on IS-IS interface, enter the following commands:

```
interface loopback<loopback-no>
ip address <ip-address > <subnet-mask>
ip router isis area <area-tag>
end
```

## Configuration Examples for IS-IS

Refer the examples described in the [Configuration Examples for IS-IS](#).



## CHAPTER 4

# Configuring BGP

---

- [BGP Overview, on page 11](#)
- [Limitations for BGP, on page 11](#)
- [How to Configure BGP, on page 12](#)

## BGP Overview

Border Gateway Protocol (BGP) is an interdomain routing protocol designed to provide loop-free routing between separate routing domains that contain independent routing policies (autonomous systems). The Cisco software implementation of BGP version 4 includes support for 4-byte autonomous system numbers and multiprotocol extensions to allow BGP to carry routing information for IP multicast routes and multiple Layer 3 protocol address families including IP Version 4 (IPv4), IP Version 6 (IPv6), Virtual Private Networks Version 4 (VPNv4), Connectionless Network Services (CLNS), and Layer 2 VPN (L2VPN). This module contains conceptual material to help you understand how BGP is implemented in Cisco software.

For more information, see [Information About Cisco BGP](#).

## Limitations for BGP

- BGP-PIC is not supported.

But by default, BGP-PIC is enabled on all the Cisco IOS XE platforms, hence the BGP-PIC must be disabled using the **cef table output-chain build favor memory-utilization** command under configuration mode. If the BGP-PIC is not disabled, then the route update failure might occur.

- When you configure BGP with graceful restart and remove the BGP configuration using **no router bgp** command, the graceful restart timer starts. As a result, the stale entry is present in the BGP routing table and it is only removed after the BGP graceful restart timer is over.

# How to Configure BGP

## Configuring BGP on BDI

Configuring a basic BGP network consists of a few required tasks and many optional tasks. A BGP routing process must be configured and BGP peers must be configured, preferably using the address family configuration model. If the BGP peers are part of a VPN network, the BGP peers must be configured using the IPv4 VRF address family task.

For more information, see [Configuring BGP](#).

## Verifying BGP Configuration

Use the following **show** command to verify the BGP configuration:

```
router#show run int lo0
Building configuration...

Current configuration : 86 bytes
!
interface Loopback0
ip address 192.0.2.0 255.255.255.255
ip ospf 30 area 0
end

RTR10-Dom3(config)#do sh run | sec router bgp
router bgp 1
  bgp router-id 10.10.10.10
  bgp log-neighbor-changes
  redistribute connected
  neighbor 10.1.1.1 remote-as 1
  neighbor 10.1.1.1 update-source Loopback0
  neighbor 10.6.6.6 remote-as 1
  neighbor 10.6.6.6 update-source Loopback0
  neighbor 10.8.8.8 remote-as 1
  neighbor 10.8.8.8 update-source Loopback0
```

## Configuration Examples for BGP

Refer the examples described in the [Configuration Examples for a Basic BGP Network](#).





## CHAPTER 5

# Configuring EIGRP

Perform this task to enable EIGRP and create an EIGRP routing process. EIGRP sends updates to interfaces in specified networks. If you do not specify the network of an interface, the interface will not be advertised in any EIGRP update.

Configuring the `router eigrp autonomous-system-number` command creates an EIGRP autonomous system configuration that creates an EIGRP routing instance, which can be used for tagging routing information.

```
enable
configure terminal
router eigrp <autonomous-system-number>
network <network-number>
end
```

For more information on configuring EIGRP, refer [How to Configure EIGRP](#).

- [EIGRP Features, on page 13](#)
- [How to Configure EIGRP, on page 14](#)

## EIGRP Features

- Increased network width—With IP Routing Information Protocol (RIP), the largest possible width of your network is 15 hops. When EIGRP is enabled, the largest possible width is increased to 100 hops, and the EIGRP metric is large enough to support thousands of hops.
- Fast convergence—The DUAL algorithm allows routing information to converge as quickly as any currently available routing protocol.
- Partial updates—EIGRP sends incremental updates when the state of a destination changes, instead of sending the entire contents of the routing table. This feature minimizes the bandwidth required for EIGRP packets.
- Neighbor discovery mechanism—This simple protocol-independent hello mechanism is used to learn about neighboring devices.
- Scaling—EIGRP scales to large networks.

For more information, refer [Information About Configuring EIGRP](#).

# How to Configure EIGRP

## Configuring EIGRP

Perform this task to enable EIGRP and create an EIGRP routing process. EIGRP sends updates to interfaces in specified networks. If you do not specify the network of an interface, the interface will not be advertised in any EIGRP update.

Configuring the `router eigrp autonomous-system-number` command creates an EIGRP autonomous system configuration that creates an EIGRP routing instance, which can be used for tagging routing information.

```
enable
configure terminal
router eigrp <autonomous-system-number>
network <network-number>
end
```

For more information on configuring EIGRP, refer [How to Configure EIGRP](#).

## Configuration Examples for EIGRP

Refer the examples described in the [Configuration Examples for EIGRP](#).



## CHAPTER 6

# Configuring Static Route

- [Static Route Overview, on page 15](#)
- [How to Configure Static Route, on page 15](#)

## Static Route Overview

Static routes are entirely user configurable and can point to a next-hop interface, next-hop IP address, or both. In Cisco IOS XR software, if an interface was specified, then the static route is installed in the Routing Information Base (RIB) if the interface is reachable. If an interface was not specified, the route is installed if the next-hop address is reachable. The only exception to this configuration is when a static route is configured with the permanent attribute, in which case it is installed in RIB regardless of reachability.

## How to Configure Static Route

### Configuring Static Route on BDI Interface

You can configure static route to point to an IP address on a network. The static route enables traffic going to the network through the specified forwarding IP address.

the router to send all the traffic going out of the router which sends

To configure static route on the BDI interface, enter the following commands:

```
router(config)#ip route <Destination prefix> <Destination prefix mask> <Forwarding router's address>
```

The following example shows how to configure static route on the BDI interface:

```
router(config)#ip route 10.10.23.0 255.255.255.0 10.10.11.2
```

## Verifying Static Route Configuration

You can verify the static route configured on the BDI interface using the **show ip route** command.





## CHAPTER 7

# Configuring IPv4 Unicast Routing ECMP

By default ECMP is enabled on the host if protocols such as OSPF or IS-IS are configured on the BDI interface. There is no specific CLI to configure ECMP. ECMP based on Source IP (SIP), Destination IP (DIP), Source Port (SP), and Destination port (DP).

- [IPv4 Unicast Routing ECMP, on page 17](#)
- [Limitation for IPv4 Unicast Routing ECMP, on page 17](#)
- [How to Configure IPv4 Unicast Routing ECMP, on page 17](#)

## IPv4 Unicast Routing ECMP

IPv4 unicast routing equal-cost multi-path (ECMP) feature enables to forward traffic to destination over multiple best paths.

If there are more than one next hop is available to reach the same next network or host, then an ECMP group is created associating all the available next hop options. When a route entry is added for the ECMP destination, the ECMP interface is associated with the route entry. This ensures that all the packets destined to this particular host is load balanced to all the available next hop options.

## Limitation for IPv4 Unicast Routing ECMP

ECMP supports a maximum of four paths.

## How to Configure IPv4 Unicast Routing ECMP

### Configuring IPv4 Unicast Routing ECMP

By default ECMP is enabled on the host if protocols such as OSPF or IS-IS are configured on the BDI interface. There is no specific CLI to configure ECMP. ECMP based on Source IP (SIP), Destination IP (DIP), Source Port (SP), and Destination port (DP).

## Verifying IPv4 Unicast Routing ECMP Configuration

Use the following show commands to verify the IPv4 unicast routing ECMP configuration:

- **show ip route**
- **Show ip cef**

```
router#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2, m - OMP
       n - NAT, Ni - NAT inside, No - NAT outside, Nd - NAT DIA
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       H - NHRP, G - NHRP registered, g - NHRP registration summary
       o - ODR, P - periodic downloaded static route, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR

Gateway of last resort is not set

    10.0.0.0/32 is subnetted, 1 subnets
O       10.0.0.1 [110/2] via 192.168.13.4, 1d01h, BDI210
        [110/2] via 192.0.2.4, 1d01h, BDI111
    10.0.0.1/32 is subnetted, 1 subnets
C       10.6.6.6 is directly connected, Loopback0
    10.0.0.2/32 is subnetted, 1 subnets
O       10.8.8.8 [110/2] via 192.168.13.1, 1d01h, BDI210
        [110/2] via 192.0.2.1, 1d00h, BDI111
    10.0.0.0/32 is subnetted, 1 subnets
O       192.0.2.0 [110/2] via 192.168.13.2, 03:20:31, BDI210
        [110/2] via 192.0.2.2, 03:20:29, BDI111
    192.0.2.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.0.2.0/24 is directly connected, BDI111
L       192.0.2.3/32 is directly connected, BDI111
    192.168.13.0/24 is variably subnetted, 2 subnets, 2 masks
C       192.168.13.0/24 is directly connected, BDI210
L       192.168.13.3/32 is directly connected, BDI210
```