



INDEX

A

audience [iv-vii](#)
automatic synchronization
 about [3-3](#)

C

conventions [iv-viii](#)

D

documentation
 additional publications [iv-ix](#)
 related documents [iv-viii](#)

F

failure, switchover [3-9](#)

H

HA policy
 description [2-2](#)
 maximum retries [2-2](#)
 minimum lifetime [2-3](#)
high availability
 description [1-1](#)
 displaying status [3-18](#)
 network level [1-3](#)
 supervisor module switchover mechanism [3-4](#)
 switchover characteristics [3-4](#)
 system level [1-3](#)

M

maximum retries. See HA policy
message and transaction service. See MTS
minimum lifetime. See HA policy
MTS
 description [2-2](#)

P

persistent storage service. See PSS
policy. See HA policy
primary role, VSM [3-5](#)
processes
 restartability [2-3](#)
PSS
 description [2-2](#)
 global and local synchronization [2-2](#)
 private and shared [2-2](#)

R

related documents [iv-ix](#)
restart
 stateful, description [2-4](#)
 stateless, description [2-4](#)
restartability
 infrastructure [2-1](#)
 process [2-3](#)
restarts
 troubleshooting [2-5](#)
role, VSM
 primary [3-5](#)

Send document comments to nexus1k-docfeedback@cisco.com.

secondary 3-5

standalone 3-5

S

secondary role, VSM 3-5

services

restartability 2-3

standalone role, VSM 3-5

stateful restart

description 2-4

stateless restart

description 2-4

supervisor module

role

secondary 3-5

supervisor modules

changing the domain ID 3-16

replacing standby supervisor 3-15, 3-16

role

primary 3-5

standalone 3-5

switchover mechanisms 3-4

switchovers 3-9

characteristics 3-4

guidelines 3-7

System Manager 2-2

description 2-2

V

VEMs 1-1

virtual Ethernet modules. See VEMs

virtual machines. See VMs

virtual service modules. See VSMs

VMs 1-1

VSMs 1-1

manual switchover 3-9