



## O Show Commands

---

- [show object-group, on page 2](#)
- [show openflow hardware capabilities, on page 3](#)
- [show openflow switch, on page 4](#)
- [show openflow switch flows, on page 5](#)
- [show ospfv3, on page 6](#)
- [show ospfv3 border-routers, on page 11](#)
- [show ospfv3 database, on page 13](#)
- [show ospfv3 database database-summary, on page 16](#)
- [show ospfv3 database detail, on page 18](#)
- [show ospfv3 interface, on page 23](#)
- [show ospfv3 interface brief, on page 26](#)
- [show ospfv3 neighbors, on page 28](#)
- [show ospfv3 neighbors detail, on page 30](#)
- [show ospfv3 neighbors summary, on page 33](#)
- [show ospfv3 request-list, on page 35](#)
- [show ospfv3 retransmission-list, on page 37](#)
- [show ospfv3 route, on page 39](#)
- [show ospfv3 route summary, on page 41](#)
- [show ospfv3 statistics, on page 43](#)
- [show ospfv3 summary-address, on page 47](#)
- [show ospfv3 traffic, on page 48](#)
- [show ospfv3 virtual-links, on page 52](#)
- [show ospfv3 virtual-links brief, on page 56](#)
- [show otv, on page 57](#)

# show object-group

```
show object-group [ <name> ] [ __readonly__ TABLE_ogroup <group_type> <group_name> [ TABLE_seqno
<seqno> { <_port_op> <port0_num> | <_port_range> <port1_num> <port2_num> | <hostaddr> | <net_ip> |
<mask_ip_addr> <mask_ip_mask> | <hostipv6> | <net_ipv6> | <mask_ipv6_addr> <mask_ipv6_mask> } ]
]
```

## Syntax Description

show	Show running system information
object-group	Show configured ACL object groups
<i>name</i>	(Optional) object-group name
<i>__readonly__</i>	(Optional)
<i>group_type</i>	(Optional) Object group type
<i>group_name</i>	(Optional) Object group name
<i>seqno</i>	(Optional) Sequence number
TABLE_ogroup	(Optional)
TABLE_seqno	(Optional)
<i>_port_op</i>	(Optional) Port operator
<i>_port_range</i>	(Optional) Port range
<i>port0_num</i>	(Optional) Port number
<i>port1_num</i>	(Optional) Port number
<i>port2_num</i>	(Optional) Port number
<i>net_ip</i>	(Optional) A.B.C.D Network address of object-group member
<i>hostaddr</i>	(Optional) A.B.C.D Host address
<i>mask_ip_addr</i>	(Optional) A.B.C.D IP address
<i>mask_ip_mask</i>	(Optional) A.B.C.D IP address mask

## Command Mode

- /exec

# show openflow hardware capabilities

show openflow hardware capabilities [ pipeline <pipeline-id> ]

## Syntax Description

show	Show running system information
openflow	Show OpenFlow information
hardware	Hardware
capabilities	Capabilities
pipeline	(Optional) Pipeline id
<i>pipeline-id</i>	(Optional) Pipeline id

## Command Mode

- /exec

# show openflow switch

```
show openflow switch <switch-id> [ { controllers [ stats | { role { master | slave | equal } } ] | ports } ] [
__readonly__ <cli_output> <ctrlv4> <ctrlport> ]
```

## Syntax Description

show	Show running system information
openflow	Show OpenFlow information
switch	Logical switch id
<i>switch-id</i>	Logical switch-id to enter
controllers	(Optional) Controllers
stats	(Optional) Stats
ports	(Optional) Ports
role	(Optional) Controller role
master	(Optional) Master
slave	(Optional) Slave
equal	(Optional) Equal
<i>__readonly__</i>	(Optional)
<i>cli_output</i>	(Optional)
<i>ctrlv4</i>	(Optional)
<i>ctrlport</i>	(Optional)

## Command Mode

- /exec

# show openflow switch flows

```
show openflow switch <switch-id> flows [ [ table-id <table-id> ] [ [ pending | pending-del | controller |
configured | default | fixed ] [ brief | list | summary ] ] | stats | compare statistics { snapshot | report [ brief |
list ] } ]
```

## Syntax Description

show	Show running system information
openflow	Show OpenFlow information
switch	Logical switch id
<i>switch-id</i>	Logical switch-id to enter
flows	Flows
brief	(Optional) Brief
summary	(Optional) Summary
pending	(Optional) Pending
pending-del	(Optional) Pending delete
controller	(Optional) Controller
configured	(Optional) Configured
default	(Optional) Default
fixed	(Optional) Fixed
stats	(Optional) Stats
compare	(Optional) Compare Flow Statistics
statistics	(Optional) Flow Statistics
snapshot	(Optional) Create a reference point to compare flow stats counters
report	(Optional) Dump difference of flow stats counters from snapshot
table-id	(Optional) Table-id for the pipeline
list	(Optional) List
<i>table-id</i>	(Optional) Table ID

## Command Mode

- /exec

# show ospfv3

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx
<ptag> <instance_number> <cname> <rid> <stateful_ha> <gr_ha> [ [ <gr_planned_only> ] [ <gr_grace_period>
] [ <gr_state> ] [ <gr_last_status> ] ] [ <gr_helper_mode> ] <support_tos0_only> <support_opaque_lsa> [
<low_mem_cond> ] <is_abr> <is_asbr> [ <max_lsa_non_self_number> ] [ <max_lsa_state> ] [
<max_lsa_warning_only> ] [ <max_lsa_current_non_self_lsa_number> ] [ <max_lsa_threshold_pct> ] [
<max_lsa_ignore_time> ] [ <max_lsa_reset_time> ] [ <max_lsa_ignore_count> ] [
<max_lsa_current_ignore_count> ] [ <max_lsa_ignore_time_left> ] [ <max_lsa_reset_time_left> ] [
<max_lsa_permanent_ignore> ] [ { TABLE_redist <proto> [ <max_lsas> ] [ <warning> ] [ <threshold> ] [
<current_count> ] } ] <admin_dist> <ref_bw> <spf_start_time> <spf_hold_time> <spf_max_time>
<lsa_start_time> <lsa_hold_time> <lsa_max_time> <min_lsa_arr_time> <lsa_aging_pace> <spf_max_paths>
<max_metric_adver> [ [ <max_metric_time_left> ] [ <max_metric_wait_bgp> ] [ <max_metric_timeout> ]
[ <max_metric_always> ] [ <max_metric_sum_lsa> ] [ <max_metric_ext_lsa> ] ] <asext_lsa_cnt>
<asext_lsa_crc> <area_total> <area_normal> <area_stub> <area_nssa> <act_area_total> <act_area_normal>
<act_area_stub> <act_area_nssa> [ <name_lookup> ] <no_discard_rt_ext> <no_discard_rt_int> [ <passive_dflt>
] [ <bfd_enabled> ] [ <ipsec_sa_type> ] [ <ipsec_sa_algorithm> ] [ <ipsec_sa_spi> ] [ { TABLE_area <aname>
[ <backbone_active> ] [ <active> ] <age> <total_intf> <act_intf> <passive_intf> <loopback_intf> [
<gr_nbr_cnt> ] <stub> [ <stub_def_cost> ] <nssa> [ <no_redist> ] [ <nssa_trans> ] <no_summary> [
<ipsec_sa_type> ] [ <ipsec_sa_algorithm> ] [ <ipsec_sa_spi> ] <spf_runs> <last_spf_run_time> [
TABLE_range <addr> <masklen> <state> <nets> <advertise> [ <cost> ] ] [ <filter_in> ] [ <filter_out> ]
<lsa_cnt> <lsa_crc> } ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
instance_number	(Optional)
cname	(Optional)
rid	(Optional)

<i>stateful_ha</i>	(Optional)
<i>gr_ha</i>	(Optional)
<i>gr_planned_only</i>	(Optional)
<i>gr_grace_period</i>	(Optional)
<i>gr_state</i>	(Optional)
<i>gr_last_status</i>	(Optional)
<i>gr_helper_mode</i>	(Optional)
<i>support_tos0_only</i>	(Optional)
<i>support_opaque_lsa</i>	(Optional)
<i>low_mem_cond</i>	(Optional)
<i>is_abr</i>	(Optional)
<i>is_asbr</i>	(Optional)
<i>max_lsa_non_self_number</i>	(Optional)
<i>max_lsa_state</i>	(Optional)
<i>max_lsa_warning_only</i>	(Optional)
<i>max_lsa_current_non_self_lsa_number</i>	(Optional)
<i>max_lsa_threshold_pct</i>	(Optional)
<i>max_lsa_ignore_time</i>	(Optional)
<i>max_lsa_reset_time</i>	(Optional)
<i>max_lsa_ignore_count</i>	(Optional)
<i>max_lsa_current_ignore_count</i>	(Optional)
<i>max_lsa_ignore_time_left</i>	(Optional)
<i>max_lsa_reset_time_left</i>	(Optional)
<i>max_lsa_permanent_ignore</i>	(Optional)
TABLE_redist	(Optional)
<i>proto</i>	(Optional)
<i>max_lsas</i>	(Optional)
<i>warning</i>	(Optional)
<i>threshold</i>	(Optional)

<i>current_count</i>	(Optional)
<i>admin_dist</i>	(Optional)
<i>ref_bw</i>	(Optional)
<i>spf_start_time</i>	(Optional)
<i>spf_hold_time</i>	(Optional)
<i>spf_max_time</i>	(Optional)
<i>lsa_start_time</i>	(Optional)
<i>lsa_hold_time</i>	(Optional)
<i>lsa_max_time</i>	(Optional)
<i>min_lsa_arr_time</i>	(Optional)
<i>lsa_aging_pace</i>	(Optional)
<i>spf_max_paths</i>	(Optional)
<i>max_metric_adver</i>	(Optional)
<i>max_metric_time_left</i>	(Optional)
<i>max_metric_wait_bgp</i>	(Optional)
<i>max_metric_timeout</i>	(Optional)
<i>max_metric_always</i>	(Optional)
<i>max_metric_sum_lsa</i>	(Optional)
<i>max_metric_ext_lsa</i>	(Optional)
<i>asext_lsa_cnt</i>	(Optional)
<i>asext_lsa_crc</i>	(Optional)
<i>area_total</i>	(Optional)
<i>area_normal</i>	(Optional)
<i>area_stub</i>	(Optional)
<i>area_nssa</i>	(Optional)
<i>act_area_total</i>	(Optional)
<i>act_area_normal</i>	(Optional)
<i>act_area_stub</i>	(Optional)
<i>act_area_nssa</i>	(Optional)



<i>name_lookup</i>	(Optional)
<i>no_discard_rt_ext</i>	(Optional)
<i>no_discard_rt_int</i>	(Optional)
<i>passive_dflt</i>	(Optional)
<i>bfd_enabled</i>	(Optional)
<i>ipsec_sa_type</i>	(Optional) IPsec SA Type
<i>ipsec_sa_algorithm</i>	(Optional) IPsec SA Algorithm name
<i>ipsec_sa_spi</i>	(Optional) IPsec SA SPI Value
TABLE_area	(Optional)
<i>aname</i>	(Optional)
<i>backbone_active</i>	(Optional)
<i>active</i>	(Optional)
<i>age</i>	(Optional)
<i>total_intf</i>	(Optional)
<i>act_intf</i>	(Optional)
<i>passive_intf</i>	(Optional)
<i>loopback_intf</i>	(Optional)
<i>gr_nbr_cnt</i>	(Optional)
<i>stub</i>	(Optional)
<i>stub_def_cost</i>	(Optional)
<i>nssa</i>	(Optional)
<i>no_redist</i>	(Optional)
<i>nssa_trans</i>	(Optional)
<i>no_summary</i>	(Optional)
<i>ipsec_sa_type</i>	(Optional) IPsec SA Type
<i>ipsec_sa_algorithm</i>	(Optional) IPsec SA Algorithm name
<i>ipsec_sa_spi</i>	(Optional) IPsec SA SPI Value
<i>spf_runs</i>	(Optional)
<i>last_spf_run_time</i>	(Optional)

TABLE_range	(Optional)
<i>masklen</i>	(Optional)
<i>state</i>	(Optional)
<i>nets</i>	(Optional)
<i>advertise</i>	(Optional)
<i>cost</i>	(Optional)
<i>filter_in</i>	(Optional)
<i>filter_out</i>	(Optional)
<i>lsa_cnt</i>	(Optional)
<i>lsa_crc</i>	(Optional)

**Command Mode**

- /exec

# show ospfv3 border-routers

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] border-routers [ all_routes ] [
vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag> <cname> [ TABLE_br
<type> <addr> <cost> <asbr> <abr> <area> <spf_inst> [ <vlink_unresolved> ] [ TABLE_br_ubest_nh [
<ubest_nh_addr> ] [ <ubest_nh_intf> ] ] [ TABLE_br_mbest_nh [ <mbest_nh_addr> ] [ <mbest_nh_intf> ]
] ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
border-routers	Border routers
all_routes	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_br	(Optional)
type	(Optional)
addr	(Optional)
cost	(Optional)
asbr	(Optional)
abr	(Optional)
area	(Optional)
spf_inst	(Optional)
vlink_unresolved	(Optional)

TABLE_br_ubest_nh	(Optional)
<i>ubest_nh_intf</i>	(Optional)
TABLE_br_mbest_nh	(Optional)
<i>mbest_nh_intf</i>	(Optional)

**Command Mode**

- /exec

## show ospfv3 database

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] database [ [ [ router | network | intra-area-prefix | inter-area { irouter | iprefix } | nssa-external | area-unknown | [ [ { link | link-unknown | grace } [ <interface> ] ] ] ] [ area <area-id-ip> ] ] | external [ tag <tag_val> ] | as-unknown ] [ <lsid> ] [ self-originated | adv-router <adv-id> | adv-router-name <adv-name> ] ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <rid> <ptag> <cname> [ TABLE_db3_lsa [ <name> ] [ <area> ] [ <id> ] [ <advrtr> ] [ <age> ] [ <seqno> ] [ <corrupt> ] [ <rtr_num_links> ] [ <net_num_rtr> ] [ <prefix> ] [ <inter_rid> ] [ <link_if> ] [ <intra_ref_type> ] [ <intra_ref_lsid> ] ] ] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
router	(Optional) Display router LSAs
network	(Optional) Display network LSAs
inter-area	(Optional) Display inter-area LSAs
iprefix	(Optional) Display Inter-Area-Prefix LSAs
irouter	(Optional) Display Inter-Area-Router LSAs
nssa-external	(Optional) Display NSSA-external LSAs
area-unknown	(Optional) Display area-scope unknown LSAs
external	(Optional) Display AS-external LSAs
as-unknown	(Optional) Display as-scope unknown LSAs
grace	(Optional) Display Grace LSAs
link	(Optional) Display Link LSAs
link-unknown	(Optional) Display link-scope unknown LSAs
<i>interface</i>	(Optional) OSPF enabled interface

<i>intra-area-prefix</i>	(Optional) Display Intra-Area-Prefix LSAs
<i>self-originated</i>	(Optional) Display only self-originated LSAs
<i>lsid</i>	(Optional) Restrict display by link state ID
<i>adv-router</i>	(Optional) Restrict display by Advertising router
<i>advid</i>	(Optional) Advertising router ID
<i>adv-router-name</i>	(Optional) Restrict display by Advertising router name
<i>adv-name</i>	(Optional) DNS Name of the Advertising router
<i>area</i>	(Optional) Display only LSA's in this area
<i>area-id-ip</i>	(Optional) Area Id as an integer or ip address
<i>tag</i>	(Optional) Restrict display by tag
<i>tag_val</i>	(Optional) 32-bit tag value
<i>__readonly__</i>	(Optional)
<i>TABLE_ctx</i>	(Optional)
<i>rid</i>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>TABLE_db3_lsa</i>	(Optional)
<i>name</i>	(Optional)
<i>area</i>	(Optional)
<i>id</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>age</i>	(Optional)
<i>seqno</i>	(Optional)
<i>corrupt</i>	(Optional)
<i>rtr_num_links</i>	(Optional)
<i>net_num_rtr</i>	(Optional)
<i>inter_rid</i>	(Optional)
<i>link_if</i>	(Optional)
<i>intra_ref_type</i>	(Optional)

<i>intra_ref_lsid</i>	(Optional)
-----------------------	------------

**Command Mode**

- /exec

# show ospfv3 database database-summary

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] database database-summary
[ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <rid> <ptag> <cname> [
TABLE_dbsum [ TABLE_dbsum_area <area> [ TABLE_dbsum_area_lsa <area_lsa_name> <area_lsa_count>
] <area_lsa_total> ] [ TABLE_dbsum_all [ TABLE_dbsum_lsa_all <lsa_name> <lsa_count> ]
<non_self_lsa_total> <lsa_total> ] ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
database-summary	Summary of database
__readonly__	(Optional)
TABLE_ctx	(Optional)
rid	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_dbsum	(Optional)
TABLE_dbsum_area	(Optional)
area	(Optional)
TABLE_dbsum_area_lsa	(Optional)
area_lsa_name	(Optional)
area_lsa_count	(Optional)
area_lsa_total	(Optional)
TABLE_dbsum_all	(Optional)



TABLE_dbsum_lsa_all	(Optional)
<i>lsa_name</i>	(Optional)
<i>lsa_count</i>	(Optional)
<i>non_self_lsa_total</i>	(Optional)
<i>lsa_total</i>	(Optional)

**Command Mode**

- /exec

## show ospfv3 database detail

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] database [ [ [ router | network
| intra-area-prefix | inter-area { irouter | iprefix } | nssa-external | area-unknown | [ [ { link | link-unknown |
grace } [ <interface> ] ] ] ] area <area-id-ip> ] | external [ tag <tag_val> ] | as-unknown [ <lsid> ] [
self-originated | adv-router <adv-id> | adv-router-name <adv-name> ] detail [ vrf { <vrf-name> |
<vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <rid> <ptag> <cname> [ TABLE_db3_lsa [ <name>
] [ <area> ] [ TABLE_lsd <age> <maxage> <wrapping> <dummy> <flush_pending> <type> [ <intf> ] <id>
<advrtr> <seqno> <cksum> <len> [ <corrupt> ] [ <rtr_abr> ] [ <rtr_asbr> ] [ <rtr_translate> ] [ <rtr_vlink_end>
] [ <rtr_options> ] [ <rtr_num_links> ] [ TABLE_rlsa [ <rtr_link_type> ] [ <rtr_link_metric> ] [ <rtr_link_ifid>
] [ <rtr_link_nbr_ifid> ] [ <rtr_link_nbr_rid> ] ] [ <net_options> ] [ TABLE_nlsa [ <net_rtr> ] ] [ <ia_prefix>
] [ <ia_prefix_options> ] [ <ia_prefix_metric> ] [ <ia_rtr_options> ] [ <ia_rtr_metric> ] [ <ia_rtr_rid> ] [
<asext_prefix> ] [ <asext_options> ] [ <asext_metric_type2> ] [ <asext_metric> ] [ <asext_fwd_addr> ] [
<asext_tag> ] [ <asext_ref_lstype> ] [ <asext_ref_lsid> ] [ <link_priority> ] [ <link_options> ] [ <link_laddr>
] [ <link_num_prefix> ] [ TABLE_linklsa [ <link_prefix> ] [ <link_prefix_options> ] ] [ <intra_num_prefix>
] [ <intra_ref_lstype> ] [ <intra_ref_lsid> ] [ <intra_ref_advtr> ] [ TABLE_iaplsa [ <intra_prefix> ] [
<intra_prefix_options> ] [ <intra_prefix_metric> ] [ <corrupted_length> ] ] [ <tlv_type> ] [ <tlv_len> ] [
<tlv_data> ] [ <tlv_unknown> ] [ <gr_interval> ] [ <gr_reason> ] [ <unknown> ] [ <data_len> ] [ <data> ] ]
] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
database	Link-state Database Summary
router	(Optional) Display router LSAs
network	(Optional) Display network LSAs
inter-area	(Optional) Display inter-area LSAs
iprefix	(Optional) Display Inter-Area-Prefix LSAs
irouter	(Optional) Display Inter-Area-Router LSAs
nssa-external	(Optional) Display NSSA-external LSAs
area-unknown	(Optional) Display area-scope unknown LSAs

external	(Optional) Display AS-external LSAs
as-unknown	(Optional) Display as-scope unknown LSAs
grace	(Optional) Display Grace LSAs
link	(Optional) Display Link LSAs
link-unknown	(Optional) Display link-scope unknown LSAs
<i>interface</i>	(Optional) OSPF enabled interface
intra-area-prefix	(Optional) Display Intra-Area-Prefix LSAs
self-originated	(Optional) Display only self-originated LSAs
<i>lsid</i>	(Optional) Restrict display by link state ID
adv-router	(Optional) Restrict display by Advertising router
<i>advid</i>	(Optional) Advertising router ID
adv-router-name	(Optional) Restrict display by Advertising router name
<i>adv-name</i>	(Optional) DNS Name of the Advertising router
area	(Optional) Display only LSA's in this area
<i>area-id-ip</i>	(Optional) Area Id as an integer or ip address
tag	(Optional) Restrict display by tag
<i>tag_val</i>	(Optional) 32-bit tag value
detail	Display LSA in detail
__readonly__	(Optional)
TABLE_ctx	(Optional)
<i>rid</i>	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_db3_lsa	(Optional)
<i>name</i>	(Optional)
<i>area</i>	(Optional)
TABLE_lsdb	(Optional)
<i>age</i>	(Optional)
<i>maxage</i>	(Optional)

<i>wrapping</i>	(Optional)
<i>dummy</i>	(Optional)
<i>flush_pending</i>	(Optional)
<i>type</i>	(Optional)
<i>intf</i>	(Optional)
<i>id</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>len</i>	(Optional)
<i>corrupt</i>	(Optional)
<i>rtr_abr</i>	(Optional)
<i>rtr_asbr</i>	(Optional)
<i>rtr_translate</i>	(Optional)
<i>rtr_vlink_end</i>	(Optional)
<i>rtr_options</i>	(Optional)
<i>rtr_num_links</i>	(Optional)
TABLE_rlsa	(Optional)
<i>rtr_link_type</i>	(Optional)
<i>rtr_link_metric</i>	(Optional)
<i>rtr_link_ifid</i>	(Optional)
<i>rtr_link_nbr_ifid</i>	(Optional)
<i>rtr_link_nbr_rid</i>	(Optional)
<i>net_options</i>	(Optional)
TABLE_nlsa	(Optional)
<i>net_rtr</i>	(Optional)
<i>ia_prefix_options</i>	(Optional)
<i>ia_prefix_metric</i>	(Optional)
<i>ia_rtr_options</i>	(Optional)

<i>ia_rtr_metric</i>	(Optional)
<i>ia_rtr_rid</i>	(Optional)
<i>asext_options</i>	(Optional)
<i>asext_metric_type2</i>	(Optional)
<i>asext_metric</i>	(Optional)
<i>asext_tag</i>	(Optional)
<i>asext_ref_lstype</i>	(Optional)
<i>asext_ref_lsid</i>	(Optional)
<i>link_priority</i>	(Optional)
<i>link_options</i>	(Optional)
<i>link_num_prefix</i>	(Optional)
TABLE_linklsa	(Optional)
<i>link_prefix_options</i>	(Optional)
<i>intra_num_prefix</i>	(Optional)
<i>intra_ref_lstype</i>	(Optional)
<i>intra_ref_lsid</i>	(Optional)
<i>intra_ref_advrtr</i>	(Optional)
TABLE_iaplsa	(Optional)
<i>intra_prefix_options</i>	(Optional)
<i>intra_prefix_metric</i>	(Optional)
<i>corrupted_length</i>	(Optional)
<i>tlv_type</i>	(Optional)
<i>tlv_len</i>	(Optional)
<i>tlv_data</i>	(Optional)
<i>tlv_unknown</i>	(Optional)
<i>gr_interval</i>	(Optional)
<i>gr_reason</i>	(Optional)
<i>unknown</i>	(Optional)
<i>data_len</i>	(Optional)

<i>data</i>	(Optional)
-------------	------------

**Command Mode**

- /exec

# show ospfv3 interface

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] interface [ <interface> | vrf {
<vrf-name> | <vrf-known-name> | all } ] [ private ] [ __readonly__ TABLE_ctx <ptag> <cname> [ TABLE_intf
<ifname> <admin_status> <proto_status> <addr> [ <masklen> ] [ <inst_id> ] <area> [ <if_cfg> ] <state_str>
<type_str> <cost> [ <ipsec_sa_type> ] [ <ipsec_sa_algorithm> ] [ <ipsec_sa_spi> ] [ <bfd_enabled> ] <index>
[ <passive> ] [ <mpls> ] [ <transmit_delay> ] [ <if_priority> ] [ <dr_rid> ] [ <dr_addr> ] [ <bdr_rid> ] [
<bdr_addr> ] [ <nbr_total> ] [ <nbr_flood> ] [ <nbr_adjs> ] [ <gr_nbr> ] [ <hello_interval> ] [ <dead_interval>
] [ <wait_interval> ] [ <rxmt_interval> ] [ <hello_timer> ] [ <wait_timer> ] [ <lsu_timer> ] [ <lsack_timer>
] [ <link_lsa_cnt> ] [ <link_lsa_crc> ] [ <multi_area_cnt> ] [ <multi_area_adj> ] ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
interface	OSPF enabled interface
interface	(Optional) OSPF enabled interface
private	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_intf	(Optional)
ifname	(Optional)
admin_status	(Optional)
proto_status	(Optional)
masklen	(Optional)
inst_id	(Optional)

<i>area</i>	(Optional)
<i>if_cfg</i>	(Optional)
<i>state_str</i>	(Optional)
<i>type_str</i>	(Optional)
<i>cost</i>	(Optional)
<i>ipsec_sa_type</i>	(Optional) IPsec SA Type
<i>ipsec_sa_algorithm</i>	(Optional) IPsec SA Algorithm name
<i>ipsec_sa_spi</i>	(Optional) IPsec SA SPI Value
<i>bfd_enabled</i>	(Optional)
<i>index</i>	(Optional)
<i>passive</i>	(Optional)
<i>mpls</i>	(Optional)
<i>transmit_delay</i>	(Optional)
<i>if_priority</i>	(Optional)
<i>dr_rid</i>	(Optional)
<i>bdr_rid</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>nbr_flood</i>	(Optional)
<i>nbr_adj</i>	(Optional)
<i>gr_nbr</i>	(Optional)
<i>hello_interval</i>	(Optional)
<i>dead_interval</i>	(Optional)
<i>wait_interval</i>	(Optional)
<i>rxmt_interval</i>	(Optional)
<i>hello_timer</i>	(Optional)
<i>wait_timer</i>	(Optional)
<i>lsu_timer</i>	(Optional)
<i>lsack_timer</i>	(Optional)
<i>link_lsa_cnt</i>	(Optional)



<i>link_lsa_crc</i>	(Optional)
<i>multi_area_cnt</i>	(Optional)
<i>multi_area_adj</i>	(Optional)

**Command Mode**

- /exec

# show ospfv3 interface brief

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] interface brief [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag> <cname> <intf_count> TABLE_intf <ifname> <index> <area> <cost> <state_str> <nbr_total> <admin_status> ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
interface	OSPF enabled interface
brief	Display summary of OSPFv3 interfaces
<i>__readonly__</i>	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>intf_count</i>	(Optional)
TABLE_intf	(Optional)
<i>ifname</i>	(Optional)
<i>index</i>	(Optional)
<i>area</i>	(Optional)
<i>cost</i>	(Optional)
<i>state_str</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>admin_status</i>	(Optional)

## Command Mode

- /exec

# show ospfv3 neighbors

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] neighbors [ { { <interface> [ <neighbor> | <neighbor-name> ] } | { [ <neighbor> | <neighbor-name> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] } } ] [ __readonly__ TABLE_ctx <ptag> <cname> <nbrcount> [ TABLE_nbr <rid> <priority> <state> <drstate> <uptime> <ifid> <intf> [ <multiarea> ] <addr> ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
interface	(Optional) OSPF enabled interface
neighbor	(Optional) Router ID of neighbor
neighbor-name	(Optional) DNS Name of the neighbor
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
nbrcount	(Optional)
TABLE_nbr	(Optional)
rid	(Optional)
priority	(Optional)
state	(Optional)
drstate	(Optional)
uptime	(Optional)

<i>ifid</i>	(Optional)
<i>intf</i>	(Optional)
<i>multiarea</i>	(Optional)

**Command Mode**

- /exec

## show ospfv3 neighbors detail

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] neighbors [ <interface> ] [
<neighbor> ] detail [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ private ] [ __readonly__ TABLE_ctx
<ptag> <cname> [ TABLE_nbr <rid> <addr> <area> <intf> <state> <transition> <lastchange> [ <bfd_state>
] [ <priority> ] [ <ifid> ] [ <dr> ] [ <bdr> ] [ <master> ] [ <seqno> ] [ <dbdallsentacked> ] [ <dbdallsent> ] [
<dbdallacked> ] [ <lsaonreqlist> ] [ <lsafromlastreq> ] [ <lsreqrxmts> ] <helloptions> <dbdoptions>
<lastnonhello> [ <deadtimer> ] [ <pacingtimer> ] [ <dbdrxmtimer> ] [ <reqrxmtimer> ] [ <lsutimer> ] [
<rerxmtimer> ] [ <fastrerxmtimer> ] [ <lsacktimer> ] [ <grtimer> ] [ <helpermode> ] [ <helpercand> ] [
<helperterm> ] [ <senddbd> ] [ <sendlsreq> ] [ <sendlsu> ] [ <sendlsurxmt> ] [ <sendlsack> ] [
<sendlsreqreply> ] [ <sradsid> ] [ <sradjflags> ] ] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
interface	(Optional) OSPF enabled interface
neighbor	(Optional) Router ID of neighbor
detail	Show detailed neighbor display
private	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_nbr	(Optional)
rid	(Optional)
area	(Optional)

<i>intf</i>	(Optional)
<i>state</i>	(Optional)
<i>transition</i>	(Optional)
<i>lastchange</i>	(Optional)
<i>bfd_state</i>	(Optional)
<i>priority</i>	(Optional)
<i>ifid</i>	(Optional)
<i>dr</i>	(Optional)
<i>bdr</i>	(Optional)
<i>master</i>	(Optional)
<i>seqno</i>	(Optional)
<i>dbdallsentacked</i>	(Optional)
<i>dbdallsent</i>	(Optional)
<i>dbdallacked</i>	(Optional)
<i>lsaonreqlist</i>	(Optional)
<i>lsafromlastreq</i>	(Optional)
<i>lsregrxmts</i>	(Optional)
<i>helloptions</i>	(Optional)
<i>dbdoptions</i>	(Optional)
<i>lastnonhello</i>	(Optional)
<i>deadtimer</i>	(Optional)
<i>pacingtimer</i>	(Optional)
<i>dbdrxmtimer</i>	(Optional)
<i>regrxmtimer</i>	(Optional)
<i>lsutimer</i>	(Optional)
<i>rerxmtimer</i>	(Optional)
<i>fastrerxmtimer</i>	(Optional)
<i>lsacktimer</i>	(Optional)
<i>grtimer</i>	(Optional)

<i>helpermode</i>	(Optional)
<i>helpercand</i>	(Optional)
<i>helperterm</i>	(Optional)
<i>senddbd</i>	(Optional)
<i>sendlsreq</i>	(Optional)
<i>sendlsu</i>	(Optional)
<i>sendlsurxmt</i>	(Optional)
<i>sendlsack</i>	(Optional)
<i>sendlsreqreply</i>	(Optional)
<i>sradjsid</i>	(Optional)
<i>sradjflags</i>	(Optional)

**Command Mode**

- /exec



## show ospfv3 neighbors summary

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] neighbors [ <interface> ]
summary [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag> <cname>
TABLE_intf { <ifname> | <total> } <down> <attempt> <init> <twoway> <exstart> <exchange> <loading>
<full> <if_total> ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
neighbors	Neighbor list
<i>interface</i>	(Optional) OSPF enabled interface
summary	Summary of neighbors
<i>__readonly__</i>	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_intf	(Optional)
<i>ifname</i>	(Optional)
<i>total</i>	(Optional)
<i>down</i>	(Optional)
<i>attempt</i>	(Optional)
<i>init</i>	(Optional)
<i>twoway</i>	(Optional)
<i>exstart</i>	(Optional)

<i>exchange</i>	(Optional)
<i>loading</i>	(Optional)
<i>full</i>	(Optional)
<i>if_total</i>	(Optional)

**Command Mode**

- /exec



- /exec

## show ospfv3 retransmission-list

```
show [ ipv6 ] ospfv3 [ <tag> ] retransmission-list { <routerid> | <router-name> } <interface> [ __readonly__
[ TABLE_ctx <ptag> <cname> [ TABLE_rxmit <nbr_rid> <intf> <nbr_addr> [ <timer_running> ] [
<timer_due> ] [ TABLE_lsa [ <type> ] [ <lsid> ] [ <advrtr> ] [ <seqno> ] [ <cksum> ] [ <age> ] ] ] ] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
retransmission-list	Link state retransmission list
<i>routerid</i>	Neighbor router ID
<i>router-name</i>	DNS Name of the router
<i>interface</i>	OSPF enabled interface
<i>__readonly__</i>	(Optional)
TABLE_ctx	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
TABLE_rxmit	(Optional)
<i>nbr_rid</i>	(Optional)
<i>intf</i>	(Optional)
<i>timer_running</i>	(Optional)
<i>timer_due</i>	(Optional)
TABLE_lsa	(Optional)
<i>type</i>	(Optional)
<i>lsid</i>	(Optional)
<i>advrtr</i>	(Optional)
<i>seqno</i>	(Optional)
<i>cksum</i>	(Optional)
<i>age</i>	(Optional)

**Command Mode**

- /exec



<i>direct</i>	(Optional)
<i>area</i>	(Optional)
<i>vlink_unresolved</i>	(Optional)
TABLE_route_ubest_nh	(Optional)
<i>ubest_nh_intf</i>	(Optional)
<i>ubest_cost</i>	(Optional)
<i>distance</i>	(Optional)
<i>ubest_nh_direct</i>	(Optional)
<i>ubest_nh_sham_link</i>	(Optional)
<i>ubest_nh_te_tun</i>	(Optional)
<i>ubest_nh_in_rib</i>	(Optional)
TABLE_route_mbest_nh	(Optional)
<i>mbest_nh_intf</i>	(Optional)
<i>mbest_cost</i>	(Optional)
<i>mbest_nh_direct</i>	(Optional)
<i>mbest_nh_in_rib</i>	(Optional)

**Command Mode**

- /exec



# show ospfv3 route summary

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] route [ <ipv6-prefix> [
longer-prefixes ] ] summary [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx
<ptag> <cname> [ TABLE_route <total_routes> <total_paths> [ TABLE_route_type <path_type>
<path_routes> <path_paths> ] [ TABLE_route_masklen <masklen> <masklen_routes> <masklen_paths> ] ]
]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
route	Internal OSPF routes
longer-prefixes	(Optional) Show exact match and more specific routes
summary	Show route counts
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_route	(Optional)
total_routes	(Optional)
total_paths	(Optional)
TABLE_route_type	(Optional)
path_type	(Optional)
path_routes	(Optional)
path_paths	(Optional)
TABLE_route_masklen	(Optional)

<i>masklen</i>	(Optional)
<i>masklen_routes</i>	(Optional)
<i>masklen_paths</i>	(Optional)

**Command Mode**

- /exec

# show ospfv3 statistics

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] statistics [ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_stats <ptag> <cname> <last_clear> <rid_change> <dr_elections> <older_lsa_rcv> <nbr_state_change> <nbr_dead_postpone> <nbr_dead_expire> <nbr_bad_lsreq> <nbr_seqno_mismatch> <spf_full> <spf_summary> <spf_external> <spf_extsummary> <rtr_generate> <rtr_refresh> <rtr_flush> <rtr_other_flush> <net_generate> <net_refresh> <net_flush> <net_other_flush> <inter_prefix_generate> <inter_prefix_refresh> <inter_prefix_flush> <inter_prefix_other_flush> <inter_router_generate> <inter_router_refresh> <inter_router_flush> <inter_router_other_flush> <asext_generate> <asext_refresh> <asext_flush> <asext_other_flush> <link_generate> <link_refresh> <link_flush> <link_other_flush> <intra_prefix_generate> <intra_prefix_refresh> <intra_prefix_flush> <intra_prefix_other_flush> <unknown_generate> <unknown_refresh> <unknown_flush> <unknown_other_flush> <limbo_lsa_count> <limbo_lsa_hwm> <limbo_lsa_deleted> <limbo_lsa_revived> <limbo_runs> <limbo_lsa_last_time_hwm> [ <limbo_timer> ] <helloq_size> <helloq_max_size> <helloq_hwm> <helloq_drops> <helloq_last_hwm_time> <floodq_size> <floodq_max_size> <floodq_hwm> <floodq_drops> <floodq_last_hwm_time> <lsdb_add_fail> [ TABLE_buffer_detail [ <buf_size> ] [ <buf_size_huge> ] <buf_in_use> <buf_hwm> <buf_perm> <buf_alloc> <buf_free> ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
statistics	Event counters
__readonly__	(Optional)
TABLE_stats	(Optional)
ptag	(Optional)
cname	(Optional)
last_clear	(Optional)
rid_change	(Optional)
dr_elections	(Optional)
older_lsa_rcv	(Optional)

<i>nbr_state_change</i>	(Optional)
<i>nbr_dead_postpone</i>	(Optional)
<i>nbr_dead_expire</i>	(Optional)
<i>nbr_bad_lsreq</i>	(Optional)
<i>nbr_seqno_mismatch</i>	(Optional)
<i>spf_full</i>	(Optional)
<i>spf_summary</i>	(Optional)
<i>spf_external</i>	(Optional)
<i>spf_extsummary</i>	(Optional)
<i>rtr_generate</i>	(Optional)
<i>rtr_refresh</i>	(Optional)
<i>rtr_flush</i>	(Optional)
<i>rtr_other_flush</i>	(Optional)
<i>net_generate</i>	(Optional)
<i>net_refresh</i>	(Optional)
<i>net_flush</i>	(Optional)
<i>net_other_flush</i>	(Optional)
<i>inter_prefix_generate</i>	(Optional)
<i>inter_prefix_refresh</i>	(Optional)
<i>inter_prefix_flush</i>	(Optional)
<i>inter_prefix_other_flush</i>	(Optional)
<i>inter_router_generate</i>	(Optional)
<i>inter_router_refresh</i>	(Optional)
<i>inter_router_flush</i>	(Optional)
<i>inter_router_other_flush</i>	(Optional)
<i>asext_generate</i>	(Optional)
<i>asext_refresh</i>	(Optional)
<i>asext_flush</i>	(Optional)
<i>asext_other_flush</i>	(Optional)

<i>link_generate</i>	(Optional)
<i>link_refresh</i>	(Optional)
<i>link_flush</i>	(Optional)
<i>link_other_flush</i>	(Optional)
<i>intra_prefix_generate</i>	(Optional)
<i>intra_prefix_refresh</i>	(Optional)
<i>intra_prefix_flush</i>	(Optional)
<i>intra_prefix_other_flush</i>	(Optional)
<i>unknown_generate</i>	(Optional)
<i>unknown_refresh</i>	(Optional)
<i>unknown_flush</i>	(Optional)
<i>unknown_other_flush</i>	(Optional)
<i>limbo_lsa_count</i>	(Optional)
<i>limbo_lsa_hwm</i>	(Optional)
<i>limbo_lsa_deleted</i>	(Optional)
<i>limbo_lsa_revived</i>	(Optional)
<i>limbo_runs</i>	(Optional)
<i>limbo_lsa_last_time_hwm</i>	(Optional)
<i>limbo_timer</i>	(Optional)
<i>helloq_size</i>	(Optional)
<i>helloq_max_size</i>	(Optional)
<i>helloq_hwm</i>	(Optional)
<i>helloq_drops</i>	(Optional)
<i>helloq_last_hwm_time</i>	(Optional)
<i>floodq_size</i>	(Optional)
<i>floodq_max_size</i>	(Optional)
<i>floodq_hwm</i>	(Optional)
<i>floodq_drops</i>	(Optional)
<i>floodq_last_hwm_time</i>	(Optional)

<i>lsdb_add_fail</i>	(Optional)
TABLE_buffer_detail	(Optional)
<i>buf_size</i>	(Optional)
<i>buf_size_huge</i>	(Optional)
<i>buf_in_use</i>	(Optional)
<i>buf_hwm</i>	(Optional)
<i>buf_perm</i>	(Optional)
<i>buf_alloc</i>	(Optional)
<i>buf_free</i>	(Optional)

**Command Mode**

- /exec

# show ospfv3 summary-address

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] summary-address [ private ]
[ vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ [ TABLE_ctx <ptag> <cname> <rid> [
TABLE_sum <addr> <masklen> [ <metric> ] [ <tag> ] [ <pending> ] ] ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
summary-address	Summary-address redistribution information
private	THIS KEYWORD OR VARIABLE IS NOT SUPPORTED
tag	(Optional)
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
rid	(Optional)
TABLE_sum	(Optional)
masklen	(Optional)
metric	(Optional)
pending	(Optional)

## Command Mode

- /exec

## show ospfv3 traffic

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] traffic [ <interface> [ detail ]
| [ detail ] | [ detail ] vrf { <vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_traf <ptag>
<cname> <last_clear> [ <ifname> ] <pkt_in> <pkt_out> <lsu_first_trans> <lsu_retrans> <lsu_for_lsreq>
<lsu_nbr_trans> <throttle_out> <throttle_out_token> <throttle_out_ip> <lsa_ignored> <lsa_dropped_spf>
<lsa_dropped_gr> <pkt_drops_in> <pkt_drops_out> <pkt_errors_in> <pkt_errors_out> <hello_errors_in>
<dbds_errors_in> <lsreqs_errors_in> <lsus_errors_in> <lsacks_errors_in> <pkt_unknown_in>
<pkt_unknown_out> <pkt_no_ospf_intf> <bad_version> <bad_crc> <dup_rtr_id> <dup_src_addr>
<invalid_src_addr> <invalid_dst_addr> <non_existing_nbr> <pkt_passive_intf> <wrong_area>
<invalid_pkt_len> <nbr_changed_routerid_ipaddr> <nbr_changed_interfaceid> [ <bad_auth> ] [
<bad_reserved> ] [ <pkt_no_vrf> ] <hellos_in> <dbds_in> <lsreqs_in> <lsus_in> <lsacks_in> <hellos_out>
<dbds_out> <lsreqs_out> <lsus_out> <lsacks_out> [ <hellos_in_hq> <dbds_in_hq> <lsreqs_in_flq>
<lsus_in_flq> <lsacks_in_flq> <lsas_in_dbds_in> <lsas_in_lsreqs_in> <lsas_in_lsus_in> <lsas_in_lsacks_in>
<lsas_in_dbds_out> <lsas_in_lsreqs_out> <lsas_in_lsus_out> <lsas_in_lsacks_out> <lsas_in_rxmt_lsus_out>
] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
<i>tag</i>	(Optional) Process tag
<i>interface</i>	(Optional) OSPF enabled interface
detail	(Optional) Display detailed information
vrf	(Optional) Display per-VRF information
<i>vrf-name</i>	(Optional) VRF name
<i>vrf-known-name</i>	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
traffic	Packet counters
<i>__readonly__</i>	(Optional)
TABLE_traf	(Optional)
<i>ptag</i>	(Optional)
<i>cname</i>	(Optional)
<i>last_clear</i>	(Optional)
<i>ifname</i>	(Optional)
<i>pkt_in</i>	(Optional)



<i>pkt_out</i>	(Optional)
<i>lsu_first_trans</i>	(Optional)
<i>lsu_retrans</i>	(Optional)
<i>lsu_for_lsreq</i>	(Optional)
<i>lsu_nbr_trans</i>	(Optional)
<i>throttle_out</i>	(Optional)
<i>throttle_out_token</i>	(Optional)
<i>throttle_out_ip</i>	(Optional)
<i>lsa_ignored</i>	(Optional)
<i>lsa_dropped_spf</i>	(Optional)
<i>lsa_dropped_gr</i>	(Optional)
<i>pkt_drops_in</i>	(Optional)
<i>pkt_drops_out</i>	(Optional)
<i>pkt_errors_in</i>	(Optional)
<i>pkt_errors_out</i>	(Optional)
<i>hello_errors_in</i>	(Optional)
<i>dbds_errors_in</i>	(Optional)
<i>lsreqs_errors_in</i>	(Optional)
<i>lsus_errors_in</i>	(Optional)
<i>lsacks_errors_in</i>	(Optional)
<i>pkt_unknown_in</i>	(Optional)
<i>pkt_unknown_out</i>	(Optional)
<i>pkt_no_ospf_intf</i>	(Optional)
<i>bad_version</i>	(Optional)
<i>bad_crc</i>	(Optional)
<i>dup_rtr_id</i>	(Optional)
<i>dup_src_addr</i>	(Optional)
<i>invalid_src_addr</i>	(Optional)
<i>invalid_dst_addr</i>	(Optional)

<i>non_existing_nbr</i>	(Optional)
<i>pkt_passive_intf</i>	(Optional)
<i>wrong_area</i>	(Optional)
<i>invalid_pkt_len</i>	(Optional)
<i>nbr_changed_routerid_ipaddr</i>	(Optional)
<i>nbr_changed_interfaceid</i>	(Optional)
<i>bad_auth</i>	(Optional)
<i>bad_reserved</i>	(Optional)
<i>pkt_no_vrf</i>	(Optional)
<i>hellos_in</i>	(Optional)
<i>dbds_in</i>	(Optional)
<i>lsreqs_in</i>	(Optional)
<i>lsus_in</i>	(Optional)
<i>lsacks_in</i>	(Optional)
<i>hellos_out</i>	(Optional)
<i>dbds_out</i>	(Optional)
<i>lsreqs_out</i>	(Optional)
<i>lsus_out</i>	(Optional)
<i>lsacks_out</i>	(Optional)
<i>hellos_in_hq</i>	(Optional)
<i>dbds_in_hq</i>	(Optional)
<i>lsreqs_in_flq</i>	(Optional)
<i>lsus_in_flq</i>	(Optional)
<i>lsacks_in_flq</i>	(Optional)
<i>lsas_in_dbds_in</i>	(Optional)
<i>lsas_in_lsreqs_in</i>	(Optional)
<i>lsas_in_lsus_in</i>	(Optional)
<i>lsas_in_lsacks_in</i>	(Optional)
<i>lsas_in_dbds_out</i>	(Optional)

<i>lsas_in_lsreqs_out</i>	(Optional)
<i>lsas_in_lsus_out</i>	(Optional)
<i>lsas_in_lsacks_out</i>	(Optional)
<i>lsas_in_rxmt_lsus_out</i>	(Optional)

**Command Mode**

- /exec

## show ospfv3 virtual-links

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] virtual-links [ vrf { <vrf-name>
| <vrf-known-name> | all } ] [ _readonly_ TABLE_ctx <ptag> <cname> [ TABLE_vlink <name> <nbr_rid>
<if_state> <transit_area> <nh_intf> <nbr_addr> [ <transit_area_stub> ] [ <transit_area_nssa> ] <addr> [
<masklen> ] <inst_id> <area> [ <if_cfg> ] <state_str> <type_str> <cost> <index> [ <passive> ] [ <mpls> ]
[ <transmit_delay> ] [ <if_priority> ] [ <dr_rid> ] [ <dr_addr> ] [ <bdr_rid> ] [ <bdr_addr> ] [ <nbr_total> ]
[ <nbr_flood> ] [ <nbr_adj> ] [ <gr_nbr> ] [ <hello_interval> ] [ <dead_interval> ] [ <wait_interval> ] [
<rxmt_interval> ] [ <hello_timer> ] [ <wait_timer> ] [ <pacing_timer> ] [ <lsu_timer> ] [ <lsack_timer> ] [
<netlsa_throt_timer> ] [ <link_lsa_cnt> ] [ <link_lsa_crc> ] [ <state> ] [ <transition> ] [ <lastchange> ] [
<priority> ] [ <ifid> ] [ <dr> ] [ <bdr> ] [ <master> ] [ <seqno> ] [ <dbdallsentacked> ] [ <dbdallsent> ] [
<dbdallacked> ] [ <lsaonreqlist> ] [ <lsafromlastreq> ] [ <lsreqrxmts> ] [ <helloptions> ] [ <dbdoptions> ] [
<lastnonhello> ] [ <deadtimer> ] [ <pacingtimer> ] [ <dbdrxmtimer> ] [ <reqrxmtimer> ] [ <lsutimer> ] [
<rerxmtimer> ] [ <fastrerxmtimer> ] [ <lsacktimer> ] [ <grtimer> ] [ <helpermode> ] [ <helpercand> ] [
<helperterm> ] [ <senddbd> ] [ <sendlsreq> ] [ <sendlsu> ] [ <sendlsurxmt> ] [ <sendlsack> ] [
<sendlsreqreply> ] [ <ipsec_sa_type> ] [ <ipsec_sa_algorithm> ] [ <ipsec_sa_spi> ] ] ]
```

### Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
virtual-links	Virtual link information
_readonly_	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
TABLE_vlink	(Optional)
name	(Optional)
nbr_rid	(Optional)
if_state	(Optional)
transit_area	(Optional)

<i>nh_intf</i>	(Optional)
<i>transit_area_stub</i>	(Optional)
<i>transit_area_nssa</i>	(Optional)
<i>masklen</i>	(Optional)
<i>inst_id</i>	(Optional)
<i>area</i>	(Optional)
<i>if_cfg</i>	(Optional)
<i>state_str</i>	(Optional)
<i>type_str</i>	(Optional)
<i>cost</i>	(Optional)
<i>index</i>	(Optional)
<i>passive</i>	(Optional)
<i>mpls</i>	(Optional)
<i>transmit_delay</i>	(Optional)
<i>if_priority</i>	(Optional)
<i>dr_rid</i>	(Optional)
<i>bdr_rid</i>	(Optional)
<i>nbr_total</i>	(Optional)
<i>nbr_flood</i>	(Optional)
<i>nbr_adj</i>	(Optional)
<i>gr_nbr</i>	(Optional)
<i>hello_interval</i>	(Optional)
<i>dead_interval</i>	(Optional)
<i>wait_interval</i>	(Optional)
<i>rxmt_interval</i>	(Optional)
<i>hello_timer</i>	(Optional)
<i>wait_timer</i>	(Optional)
<i>pacing_timer</i>	(Optional)
<i>lsu_timer</i>	(Optional)

<i>lsack_timer</i>	(Optional)
<i>netlsa_throt_timer</i>	(Optional)
<i>link_lsa_cnt</i>	(Optional)
<i>link_lsa_crc</i>	(Optional)
<i>state</i>	(Optional)
<i>transition</i>	(Optional)
<i>lastchange</i>	(Optional)
<i>priority</i>	(Optional)
<i>ifid</i>	(Optional)
<i>dr</i>	(Optional)
<i>bdr</i>	(Optional)
<i>master</i>	(Optional)
<i>seqno</i>	(Optional)
<i>dbdallsentacked</i>	(Optional)
<i>dbdallsent</i>	(Optional)
<i>dbdallacked</i>	(Optional)
<i>lsaonreqlist</i>	(Optional)
<i>lsafromlastreq</i>	(Optional)
<i>lsreqrxmts</i>	(Optional)
<i>helloptions</i>	(Optional)
<i>dbdoptions</i>	(Optional)
<i>lastnonhello</i>	(Optional)
<i>deadtimer</i>	(Optional)
<i>pacingtimer</i>	(Optional)
<i>dbdrxmtimer</i>	(Optional)
<i>reqrxmtimer</i>	(Optional)
<i>lsutimer</i>	(Optional)
<i>rerxmtimer</i>	(Optional)
<i>fastrerxmtimer</i>	(Optional)

<i>lsacktimer</i>	(Optional)
<i>grtimer</i>	(Optional)
<i>helpermode</i>	(Optional)
<i>helpercand</i>	(Optional)
<i>helperterm</i>	(Optional)
<i>senddbd</i>	(Optional)
<i>sendlsreq</i>	(Optional)
<i>sendlsu</i>	(Optional)
<i>sendlsurxmt</i>	(Optional)
<i>sendlsack</i>	(Optional)
<i>sendlsreqreply</i>	(Optional)
<i>ipsec_sa_type</i>	(Optional) IPsec SA Type
<i>ipsec_sa_algorithm</i>	(Optional) IPsec SA Algorithm name
<i>ipsec_sa_spi</i>	(Optional) IPsec SA SPI Value

**Command Mode**

- /exec

# show ospfv3 virtual-links brief

```
show [ ipv6 ] ospfv3 [ <tag> ] [ vrf { <vrf-name> | <vrf-known-name> | all } ] virtual-links brief [ vrf {
<vrf-name> | <vrf-known-name> | all } ] [ __readonly__ TABLE_ctx <ptag> <cname> <vlink_count> [
TABLE_vlink <nbr_rid> <vlink_num> <transit_area> <cost> <if_state> ] ]
```

## Syntax Description

show	Show running system information
ipv6	(Optional) Display IPv6 information
ospfv3	Display OSPFv3 status and configuration
tag	(Optional) Process tag
vrf	(Optional) Display per-VRF information
vrf-name	(Optional) VRF name
vrf-known-name	(Optional) Known VRF name
all	(Optional) Display information for all VRFs
virtual-links	Virtual link information
brief	Display summary of OSPFv3 virtual links
__readonly__	(Optional)
TABLE_ctx	(Optional)
ptag	(Optional)
cname	(Optional)
vlink_count	(Optional)
TABLE_vlink	(Optional)
nbr_rid	(Optional)
vlink_num	(Optional)
transit_area	(Optional)
cost	(Optional)
if_state	(Optional)

## Command Mode

- /exec



# show otv

```
show otv [ <overlay-if> [ vpn <vpn-name> ] ]
```

## Syntax Description

show	Display OTV information
otv	Configure OTV information
<i>overlay-if</i>	(Optional) Overlay interface
vpn	(Optional) Overlay VPN name
<i>vpn-name</i>	(Optional) OTV VPN Name

## Command Mode

- /exec

