



U Commands

- [unsuppress-map](#), on page 2

unsuppress-map

To unsuppress routes that are suppressed by using the aggregate-address command, use the **unsuppress-map** command.

unsuppress-map *map-name*

Syntax Description

<i>map-name</i>	Map name.
-----------------	-----------

Command Default

None

Command Modes

config-router-neighbor-af mode

Command History

Release	Modification
6.2(2)	This command was introduced.

Usage Guidelines

This command requires the Enterprise Services license.

Examples

This example shows how to unsuppress routes that are suppressed by using the aggregate-address command:

```
switch# configure terminal
switch(config)# ip prefix-list IPLIST seq 5 permit 10.1.1.0/24
switch(config)# route-map UNSUPPRESS_MAP permit 10
switch(config-route-map)# match ip address prefix-list IPLIST
switch(config-route-map)# exit
switch(config)# router bgp 100
switch(config-router)# address-family ipv4 unicast
switch(config-router-af)# aggregate-address 10.1.1.0/16 summary-only
switch(config-router-af)# exit
switch(config-router)# neighbor 10.2.3.4 remote-as 300
switch(config-router-neighbor)# address-family ipv4 unicast
switch(config-router-neighbor-af)# unsuppress-map UNSUPPRESS_MAP
switch(config-router-neighbor-af)#
```

Related Commands

Command	Description
address-family ipv4 unicast	Enters IPv4 unicast address family mode.