



## Unsupported Commands in Cisco IOS Release 12.2(55)SE

---

This appendix lists some of the command-line interface (CLI) commands that appear when you enter the question mark (?) at the Catalyst 2960 or 2960-S switch prompt but are not supported in this release, either because they are not tested or because of switch hardware limitations. This is not a complete list. These unsupported commands are listed by software feature and command mode:

- [Access Control Lists, page 1-1](#)
- [Boot Loader Commands, page 1-2](#)
- [Debug Commands, page 1-2](#)
- [IGMP Snooping Commands, page 1-2](#)
- [Interface Commands, page 1-3](#)
- [MAC Address Commands, page 1-3](#)
- [Miscellaneous, page 1-4](#)
- [Network Address Translation \(NAT\) Commands, page 1-4](#)
- [QoS, page 1-4](#)
- [RADIUS, page 1-5](#)
- [SNMP, page 1-5](#)
- [SNMPv3, page 1-6](#)
- [Spanning Tree, page 1-6](#)
- [VLAN, page 1-6](#)
- [VTP, page 1-7](#)

### Access Control Lists

### Unsupported Privileged EXEC Commands

**access-enable** [host] [timeout *minutes*]

**access-template** [access-list-number | name] [dynamic-name] [source] [destination] [timeout *minutes*]

**clear access-template** [access-list-number | name] [dynamic-name] [source] [destination].

```
show access-lists rate-limit [destination]
show accounting
show ip accounting [checkpoint] [output-packets | access violations]
show ip cache [prefix-mask] [type number]
```

## Unsupported Global Configuration Commands

```
access-list rate-limit acl-index {precedence | mask prec-mask}
access-list dynamic extended
```

## Unsupported Route-Map Configuration Commands

```
match ip address prefix-list prefix-list-name [prefix-list-name...]
```

## Boot Loader Commands

## Unsupported Global Configuration Commands

```
boot buffersize
```

## Debug Commands

## Unsupported Privileged EXEC Commands

```
debug platform cli-redirection main
debug platform configuration
```

## IGMP Snooping Commands

## Unsupported Global Configuration Commands

```
ip igmp snooping tcn
```

# Interface Commands

## Unsupported Privileged EXEC Commands

```
show interfaces [interface-id | vlan vlan-id] [crb | fair-queue | irb | mac-accounting | precedence | irb | random-detect | rate-limit | shape]
```

## Unsupported Global Configuration Commands

```
interface tunnel
```

## Unsupported Interface Configuration Commands

```
transmit-interface type number
```

# MAC Address Commands

## Unsupported Privileged EXEC Commands

```
show mac-address-table  
show mac-address-table address  
show mac-address-table aging-time  
show mac-address-table count  
show mac-address-table dynamic  
show mac-address-table interface  
show mac-address-table multicast  
show mac-address-table notification  
show mac-address-table static  
show mac-address-table vlan  
show mac address-table multicast
```



**Note** Use the **show ip igmp snooping groups** privileged EXEC command to display Layer 2 multicast address-table entries for a VLAN.

## Unsupported Global Configuration Commands

```
mac-address-table aging-time  
mac-address-table notification
```

mac-address-table static

## Miscellaneous

### Unsupported User EXEC Commands

verify

### Unsupported Privileged EXEC Commands

file verify auto

show cable-diagnostics prbs

test cable-diagnostics prbs

### Unsupported Global Configuration Commands

errdisable recovery cause unicast flood

l2protocol-tunnel global drop-threshold

memory reserve critical

service compress-config

stack-mac persistent timer

## Network Address Translation (NAT) Commands

### Unsupported Privileged EXEC Commands

show ip nat statistics

show ip nat translations

## QoS

### Unsupported Global Configuration Command

priority-list

## Unsupported Interface Configuration Commands

**priority-group**  
**rate-limit**

## Unsupported Policy-Map Configuration Command

**class class-default** where **class-default** is the *class-map-name*.

## RADIUS

### Unsupported Global Configuration Commands

**aaa nas port extended**  
**aaa authentication *feature* default enable**  
**aaa authentication *feature* default line**  
**aaa nas port extended**  
**authentication command bounce-port ignore** (only on switches running the LAN Lite image)  
**authentication command disable-port ignore** (only on switches running the LAN Lite image)  
**radius-server attribute nas-port**  
**radius-server configure**  
**radius-server extended-portnames**

## SNMP

### Unsupported Global Configuration Commands

**no monitor session all** (only on switches running the LAN Lite image)  
**snmp-server enable informs**  
**snmp-server enable traps hsrp**  
**snmp-server enable traps rtr** (only on switches running the LAN Lite image)  
**snmp-server ifindex persist**

## SNMPv3

### Unsupported 3DES Encryption Commands

All

## Spanning Tree

### Unsupported Global Configuration Command

spanning-tree pathcost method {long | short}

### Unsupported Interface Configuration Command

spanning-tree stack-port

## VLAN

### Unsupported Global Configuration Command

vlan internal allocation policy {ascending | descending}

### Unsupported vlan-config Command

private-vlan

### Unsupported User EXEC Commands

show running-config vlan

show vlan ifindex

vlan database

### Unsupported vlan-config Command

private-vlan

## Unsupported VLAN Database Commands

```
ntp  
vlan  
show vlan private-vlan
```

## VTP

### Unsupported Privileged EXEC Commands

```
vtp {password password | pruning | version number}
```



Note

---

This command has been replaced by the **vtp** global configuration command.

---

