



INDEX

ACLs
 applying IPv6 ACLs to a Layer 3 interface **42-16**

Numerics

10/100 autonegotiation feature, forced **7-11**
10-Gigabit Ethernet or Gigabit Ethernet ports
 deploy on WS-X4606-10GE-E and Sup 6-E **7-7**
10-Gigabit Ethernet port
 deploy with Gigabit Ethernet SFP ports **7-7**
1400 W DC Power supply
 special considerations **10-16**
1400 W DC SP Triple Input power supply
 special considerations **10-17**
802.10 SAID (default) **12-5**
802.1Q
 trunks **16-6**
802.1Q VLANs
 encapsulation **14-3**
 trunk restrictions **14-5**
802.1s
 See MST
802.1w
 See MST
802.1X
 See port-based authentication
802.1X authentication
 for Critical Authentication **36-13**
 for guest VLANs **36-10**
 for MAC Authentication Bypass **36-11**
 for Wake-on-LAN **36-14**
 web-based authentication **36-13**

with port security **36-16**
with VLAN assignment **36-9**
with voice VLAN ports **36-19**
802.1X Host Mode **36-6**
 multiauthentication mode **36-8**
 multidomain authentication mode **36-7**
 single-host **36-7**
802.3ad
 See LACP

A

AAA **39-1**
AAA (authentication, authorization, and accounting). See also port-based authentication. **37-1**
abbreviating commands **2-5**
access control entries
 See ACEs
access control entries and lists **39-1**
access-group mode, configuring on Layer 2 interface **42-30**
access-group mode, using PACL with **42-29**
access list filtering, SPAN enhancement **46-13**
access ports
 configure port security **38-7, 38-22**
 configuring **14-8**
 access VLANs **14-6**
 accounting
 with TACACS+ **3-16, 3-21**
ACEs
 ACLs **42-2**
 IP **42-2**
 Layer 4 operation restrictions **42-9**
ACEs and ACLs **39-1**

- ACL assignments, port-based authentication **36-17**
- ACL assignments and redirect URLs, configure **36-32**
- ACLs
 - ACEs **42-2**
 - and SPAN **46-5**
 - and TCAM programming for Sup II-Plus thru V-10GE **42-6**
 - applying on routed packets **42-26**
 - applying on switched packets **42-25**
 - compatibility on the same switch **42-3**
 - configuring with VLAN maps **42-25**
 - CPU impact **42-11**
 - downloadable **37-7**
 - hardware and software support **42-5**
 - IP, matching criteria for port ACLs **42-4**
 - MAC extended **42-12**
 - matching criteria for router ACLs **42-3**
 - port
 - and voice VLAN **42-4**
 - defined **42-3**
 - limitations **42-5**
 - processing **42-11**
 - selecting mode of capturing control packets **42-7**
 - troubleshooting high CPU **42-6**
 - types supported **42-3**
 - understanding **42-2**
 - VLAN maps **42-5**
- ACLs and VLAN maps, examples **42-19**
- acronyms, list of **A-1**
- action drivers, marking **33-19**
- active queue management **33-9**
- active queue management via DBL, QoS on Sup 6-E **33-32**
- active traffic monitoring, IP SLAs **50-1**
- addresses
 - displaying the MAC address table **4-30**
 - dynamic
 - changing the aging time **4-21**
 - defined **4-19**
- learning **4-20**
- removing **4-22**
- IPv6 **43-2**
- MAC, discovering **4-30**
- See MAC addresses
- static
 - adding and removing **4-27**
 - defined **4-19**
- address resolution **4-30**
- adjacency tables
 - description **27-2**
 - displaying statistics **27-9**
- advertisements
 - LLDP **1-4, 23-2**
- advertisements, VTP
 - See VTP advertisements
- aggregation switch, enabling DHCP snooping **40-9**
- aging time
 - MAC address table **4-21**
- All Auth manager sessions, displaying summary **36-68**
- All Auth manager sessions on the switch authorized for a specified authentication method **36-68**
- applying IPv6 ACLs to a Layer 3 interface **42-16**
- AQM via DBL, QoS on Sup 6-E **33-32**
- ARP
 - defined **4-30**
 - table
 - address resolution **4-30**
 - managing **4-30**
- authentication
 - NTP associations **4-4**
 - See also port-based authentication
- TACACS+
 - defined **3-16**
 - key **3-18**
 - login **3-19**
- Authentication, Authorization, and Accounting (AAA) **39-1**
- Authentication Failed VLAN assignment

- configure with 802.1X **36-53**
 - Authentication methods registered with the Auth manager, determining **36-67**
 - authentication open command **36-8**
 - authentication proxy web pages **37-4**
 - authentication server
 - defined **36-3**
 - RADIUS server **36-3**
 - Auth manager session for an interface, verifying **36-68**
 - Auth manager summary, displaying **36-67**
 - authoritative time source, described **4-2**
 - authorization
 - with TACACS+ **3-16, 3-21**
 - authorized and unauthorized ports **36-4**
 - authorized ports with 802.1X **36-4**
 - autoconfiguration **3-2**
 - Auto-MDIX on a port
 - configuring **7-22**
 - displaying the configuration **7-22**
 - overview **7-21**
 - autonegotiation feature
 - forced 10/100Mbps **7-11**
 - auto-sync command **5-8**
-
- B**
 - Baby Giants
 - interacting with **7-20**
 - BackboneFast
 - adding a switch (figure) **18-4**
 - and MST **16-23**
 - configuring **18-16**
 - link failure (figure) **18-14, 18-15**
 - not supported MST **16-23**
 - understanding **18-14**
 - See also STP
 - banners
 - configuring
 - login **4-19**
 - message-of-the-day login **4-18**
 - default configuration **4-18**
 - when displayed **4-17**
 - b command **54-3**
 - BGP **1-11**
 - routing session with multi-VRF CE **31-11**
 - blocking packets **44-1**
 - blocking state (STP)
 - RSTP comparisons (table) **16-24**
 - boot bootldr command **3-31**
 - boot command **3-28**
 - boot commands **54-3**
 - boot fields
 - See configuration register boot fields
 - boot system command **3-26, 3-31**
 - boot system flash command **3-28**
 - Border Gateway Protocol
 - See BGP
 - boundary ports
 - description **16-27**
 - BPDU Guard
 - and MST **16-23**
 - configuring **18-16**
 - overview **18-8**
 - BPDUs
 - and media speed **16-2**
 - pseudobridges and **16-25**
 - what they contain **16-3**
 - bridge ID
 - See STP bridge ID
 - bridge priority (STP) **16-16**
 - bridge protocol data units
 - See BPDUs
 - Broadcast Storm Control
 - disabling **45-5**
 - enabling **45-3**

C

Call Home

- description **1-16, 52-1**
- message format options **52-2**
- messages
 - format options **52-2**
- call home **52-1**
 - alert groups **52-6**
 - configuring e-mail options **52-9**
 - contact information **52-4**
 - default settings **52-18**
 - destination profiles **52-5**
 - displaying information **52-14**
 - mail-server priority **52-10**
 - pattern matching **52-9**
 - periodic notification **52-8**
 - rate limit messages **52-9**
 - severity threshold **52-8**
 - smart call home feature **52-2**
 - SMTP server **52-9**
 - testing communications **52-10**

call home alert groups

- configuring **52-6**
- description **52-6**
- subscribing **52-7**

call home contacts

- assigning information **52-4**

call home destination profiles

- attributes **52-5**
- configuring **52-5**
- description **52-5**
- displaying **52-16**

call home notifications

- full-txt format for syslog **52-25**
- XML format for syslog **52-34**

Capturing control packets

- selecting mode **42-7**

cautions

Unicast RPF

- BGP optional attributes **28-5**

cautions for passwords

- encrypting **3-22**

CDP

- configuration **20-2**
- defined with LLDP **23-1**
- displaying configuration **20-3**
- enabling on interfaces **20-3**
- host presence detection **36-8**
- maintaining **20-3**
- monitoring **20-3**
- overview **1-2, 20-1**
- cdp enable command** **20-3**

CEF

- adjacency tables **27-2**
- and NSF with SSO **9-4**
- configuring load balancing **27-7**
- displaying statistics **27-8**
- enabling **27-6, 53-2**
- hardware switching **27-4**
- load balancing **27-6**
- overview **27-2**
- software switching **27-4**

certificate authority (CA) **52-3**

CGMP

- overview **21-1**

channel-group group command **19-8, 19-10**

Cisco 7600 series Internet router

- enabling SNMP **55-4, 55-5**

Cisco Discovery Protocol

- See CDP

Cisco Express Forwarding

- See CEF

Cisco Group Management Protocol

- See CGMP

Cisco IOS IP SLAs **50-2**

Cisco IOS NSF-aware

- support **9-2**

Cisco IOS NSF-capable support **9-2**

Cisco IP Phones

- configuring **34-3**
- sound quality **34-1**

CiscoWorks 2000 **49-4**

CIST

- description **16-22**

civic location **23-3**

class level, configure in a service policy **33-29**

class of service

- See CoS

clear cdp counters command **20-4**

clear cdp table command **20-3**

clear counters command **7-25**

clearing

- IP multicast table entries **29-26**

clear ip eigrp neighbors command **26-17**

CLI

- accessing **2-2**
- backing out one level **2-5**
- getting commands **2-5**
- history substitution **2-4**
- modes **2-5**
- monitoring environments **46-1**
- ROM monitor **2-7**
- software basics **2-4**

clients

- in 802.1X authentication **36-3**

clock

- See system clock

command-line processing **2-3**

command modes **2-5**

commands

- b **54-3**
- boot **54-3**
- dev **54-3**
- dir device **54-3**
- i **54-3**
- listing **2-5**

reset **54-3**

ROM monitor **54-2 to ??**

SNMP **55-4**

common and internal spanning tree

- See CIST

common spanning tree

- See CST

community ports **35-4**

community strings

- configuring **49-7**
- overview **49-4**

community VLANs **35-3, 35-4**

- and SPAN features **35-12**
- configure as a PVLAN **35-13**

compiling MIBs **55-4**

config-register command **3-29**

config terminal command **3-9**

configurable leave timer,IGMP **21-4**

configuration examples

- SNMP **49-16**

configuration files

- limiting TFTP server access **49-15**
- obtaining with DHCP **3-6**
- saving **3-10**
- system contact and location information **49-15**

configuration guidelines

- SNMP **49-6**

configuration register

- boot fields
 - listing value **3-29**
 - modifying **3-28**
- changing from ROM monitor **54-3**
- changing settings **3-28 to 3-29**
- configuring **3-26**
- settings at startup **3-27**

configure class-level queue-limit in a service policy **33-29**

configure terminal command **3-29, 7-2**

configuring access-group mode on Layer 2 interface **42-30**

- configuring flow control **7-14**
 - configuring interface link and trunk status events **7-26**
 - configuring named IPv6 ACLs **42-15**
 - configuring named MAC extended ACLs **42-12, 42-14**
 - configuring unicast MAC address filtering **42-12**
 - configuring VLAN maps **42-17**
 - console configuration mode **2-5**
 - console port
 - disconnecting user sessions **8-7**
 - monitoring user sessions **8-6**
 - contact information
 - assigning for call home **52-4**
 - control plane policing
 - See CoPP
 - control protocol, IP SLAs **50-4**
 - CoPP
 - applying QoS service policy to control plane **39-3**
 - configuring
 - ACLs to match traffic **39-3**
 - enabling MLS QoS **39-3**
 - packet classification criteria **39-3**
 - service-policy map **39-3**
 - control plane configuration mode
 - entering **39-3**
 - displaying
 - dynamic information **39-7**
 - number of conforming bytes and packets **39-7**
 - rate information **39-7**
 - entering control plane configuration mode **39-3**
 - monitoring statistics **39-7**
 - overview **39-2**
 - copy running-config startup-config command **3-10**
 - copy system:running-config nvram:startup-config command **3-31**
 - CoS
 - definition **33-3**
 - figure **33-2**
 - overriding on Cisco IP Phones **34-5**
 - priority **34-5**
 - counters
 - clearing MFIB **29-26**
 - clearing on interfaces **7-25**
 - CPU, impact of ACL processing **42-11**
 - CPU port sniffing **46-10**
 - crashinfo
 - kernel file **3-34**
 - process core dump file **3-34**
 - process file **3-33**
 - crashinfo, configuring
 - commands **3-35**
 - default **3-35**
 - determining the process that crashed **3-39**
 - enabling generation of process core dump **3-38**
 - saving files to a secondary device **3-39**
 - show commands **3-36**
 - Critical Authentication
 - configure with 802.1X **36-50**
 - CST
 - description **16-25**
 - IST and **16-22**
 - MST and **16-22**
 - customer edge devices **31-2**
-
- ## D
- database agent
 - configuration examples **40-15**
 - enabling the DHCP Snooping **40-12**
 - daylight saving time **4-13**
 - default configuration
 - 802.1X **36-23**
 - banners **4-18**
 - DNS **4-16**
 - IGMP filtering **21-20**
 - IGMP snooping **22-5, 22-6**
 - IP SLAs **50-7**
 - IPv6 **43-7**
 - LLDP **23-3**

- MAC address table **4-21**
- multi-VRF CE **31-3**
- NTP **4-4**
- private VLANs **35-11**
- resetting the interface **7-28**
- RMON **51-3**
- SNMP **49-5**
- SPAN and RSPAN **46-6**
- system message logging **47-3**
- TACACS+ **3-18**
- default gateway
 - configuring **3-11**
 - verifying configuration **3-11**
- default settings, erase command **3-32**
- default web-based authentication configuration
 - 802.1X **37-6**
- denial-of-service attacks
 - IP address spoofing, mitigating **28-5**
 - Unicast RPF, deploying **28-5**
- denying access to a server on another VLAN **42-23**
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports **7-7**
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports on WS-X4606-10GE-E and Sup 6-E **7-7**
- description command **7-14**
- detecting unidirectional links **24-1**
- dev command **54-3**
- device discovery protocol **23-1**
- device IDs
 - call home format **52-21, 52-22**
- DHCP
 - configuring
 - rate limit for incoming packets **40-13**
 - denial-of-service attacks, preventing **40-13**
 - rate limiting of packets
 - configuring **40-13**
 - DHCP-based autoconfiguration
 - client request message exchange **3-3**
 - configuring
 - client side **3-3**
 - DNS **3-5**
 - relay device **3-5**
 - server-side **3-4**
 - TFTP server **3-4**
 - example **3-7**
 - lease options
 - for IP address information **3-4**
 - for receiving the configuration file **3-4**
 - overview **3-2**
 - relationship to BOOTP **3-3**
 - DHCP option 82
 - overview **40-4**
 - DHCP Snooping
 - enabling, and Option 82 **40-10**
 - DHCP snooping
 - accepting untrusted packets from edge switch **40-10**
 - configuring **40-6**
 - default configuration **40-7**
 - displaying binding tables **40-18**
 - displaying configuration **40-19**
 - displaying information **40-18**
 - enabling **40-7**
 - enabling on private VLAN **40-11**
 - enabling on the aggregation switch **40-9**
 - enabling the database agent **40-12**
 - message exchange process **40-4**
 - monitoring **40-23**
 - option 82 data insertion **40-4**
 - overview **40-1**
 - Snooping database agent **40-2**
 - DHCP Snooping Database Agent
 - adding to the database (example) **40-18**
 - enabling (example) **40-15**
 - overview **40-2**
 - reading from a TFTP file (example) **40-16**
 - Diagnostics
 - online **53-1**
 - troubleshooting **53-7**

- Power-On-Self-Test
 - causes of failure [53-20](#)
 - how it works [53-9](#)
 - overview [53-9](#)
- Power-On-Self-Test for Supervisor Engine V-10GE [53-14](#)
- Differentiated Services Code Point values
 - See DSCP values
- DiffServ architecture, QoS [33-2](#)
- Digital optical monitoring transceiver support [7-10](#)
- Digital Signing [54-6](#)
- dir device command [54-3](#)
- disabled state
 - RSTP comparisons (table) [16-24](#)
 - disabling
 - broadcast storm control [45-5](#)
 - disabling multicast storm control [45-6](#)
 - disconnect command [8-7](#)
 - displaying
 - Auth Manager summary for an interface [36-67](#)
 - MAB details [36-70](#)
 - summary of all Auth manager sessions [36-68](#)
 - summary of all Auth manager sessions on the switch authorized for a specified authentication method [36-68](#)
 - displaying EtherChannel to a Virtual Switch System [19-14](#)
 - displaying storm control [45-6](#)
 - display PoE consumed by a module [11-7](#)
- DNS
 - and DHCP-based autoconfiguration [3-5](#)
 - default configuration [4-16](#)
 - displaying the configuration [4-17](#)
 - overview [4-15](#)
 - setting up [4-16](#)
- domain names
 - DNS [4-15](#)
- Domain Name System
 - See DNS
- downloading MIBs [55-2, 55-3, 55-4](#)
- DSCP values
 - definition [33-4](#)
 - IP precedence [33-2](#)
- DTP
 - VLAN trunks and [14-3](#)
 - duplex command [7-13](#)
 - duplex mode
 - configuring interface [7-11](#)
 - dynamic ARP inspection
 - ARP cache poisoning [41-2](#)
 - configuring
 - ACLs for non-DHCP environments [41-11](#)
 - in DHCP environments [41-5](#)
 - log buffer [41-14](#)
 - rate limit for incoming ARP packets [41-16](#)
 - denial-of-service attacks, preventing [41-16](#)
 - interface trust state, security coverage [41-3](#)
 - log buffer
 - configuring [41-14](#)
 - logging of dropped packets [41-4](#)
 - overview [41-1](#)
 - port channels, their behavior [41-5](#)
 - priority of static bindings [41-4](#)
 - purpose of [41-2](#)
 - rate limiting of ARP packets [41-4](#)
 - configuring [41-16](#)
 - validation checks, performing [41-19](#)
 - Dynamic Host Configuration Protocol snooping
 - See DHCP snooping
 - dynamic port VLAN membership
 - example [12-29](#)
 - limit on hosts [12-29](#)
 - reconfirming [12-26](#)
 - troubleshooting [12-29](#)
 - Dynamic Trunking Protocol
 - See DTP

E

EAP frames

- changing retransmission time **36-63**
- exchanging (figure) **36-4, 36-6, 36-12**
- request/identity **36-3**
- response/identity **36-3**
- setting retransmission number **36-64**

EAPOL frames

- 802.1X authentication and **36-3**
- OTP authentication, example (figure) **36-4, 36-12**
- start **36-4**

edge ports

- description **16-27**

EGP

- overview **1-11**

EIGRP

- configuration examples **26-18**
- monitoring and maintaining **26-17**

EIGRP (Enhanced IGRP)

- stub routing
 - benefits **26-16**
 - configuration tasks **26-16**
 - configuring **26-12**
 - overview **26-12**
 - restrictions **26-16**
 - verifying **26-17**

EIGRP (enhanced IGRP)

- overview **1-12**

eigrp stub command **26-17**EIGRP stub routing, configuring **26-11**ELIN location **23-3**

e-mail addresses

- assigning for call home **52-4**

e-mail notifications

- Call Home **1-16, 52-1**

Embedded CiscoView

- displaying information **4-33**
- installing and configuring **4-31**

overview **4-31**

emergency alarms on Sup Engine 6-E systems **10-3**

enable command **3-9, 3-28**

enable mode **2-5**

enabling SNMP **55-4, 55-5**

encapsulation types **14-3**

Enhanced Interior Gateway Routing Protocol

 See EIGRP

Enhanced PoE support on E-series **11-15**

environmental monitoring

 using CLI commands **10-1**

EPM logging **36-70**

EtherChannel

 channel-group group command **19-8, 19-10**

 configuration guidelines **19-5**

 configuring **19-6 to 19-14**

 configuring Layer 2 **19-9**

 configuring Layer 3 **19-6**

 displaying to a virtual switch system **19-14**

 interface port-channel command **19-7**

 lacp system-priority

 command example **19-12**

 modes **19-3**

 overview **19-1**

 PAgP

 Understanding **19-3**

 physical interface configuration **19-7**

 port-channel interfaces **19-2**

 port-channel load-balance command **19-13**

 removing **19-14**

 removing interfaces **19-13**

EtherChannel guard

 disabling **18-7**

 enabling **18-6**

 overview **18-6**

explicit host tracking

 enabling **21-11**

extended range VLANs

 See VLANs

Extensible Authentication Protocol over LAN **36-2**

Exterior Gateway Protocol

See EGP

F

Fallback Authentication

configure with 802.1X **36-57**

FastDrop

overview **29-10**

FIB

description **27-2**

See also MFIB

Filter-ID ACL and Per-User ACL, configureport-based authentication

configure Per-User ACL and Filter-ID ACL **36-38**

filtering

in a VLAN **42-17**

non-IP traffic **42-12, 42-14**

flags **29-11**

Flash memory

configuring router to boot from **3-31**

loading system images from **3-30**

security precautions **3-31**

Flexible NetFlow

caveats **32-1**

defined **1-2, 32-1**

flooded traffic, blocking **44-2**

flowchart, traffic marking procedure **33-19**

flow control, configuring **7-14**

For **11-13**

forward-delay time (STP)

configuring **16-18**

forwarding information base

See FIB

G

gateway

See default gateway

get-bulk-request operation **49-3**

get-next-request operation **49-3, 49-4**

get-request operation **49-3, 49-4**

get-response operation **49-3**

Gigabit Ethernet SFP ports

deploy with 10-Gigabit Ethernet **7-7**

global configuration mode **2-5**

Guest-VLANs

configure with 802.1X **36-46, 36-54**

H

hardware and software ACL support **42-5**

hardware switching **27-5**

hello time (STP)

configuring **16-17**

high CPU due to ACLs, troubleshooting **42-6**

history

CLI **2-4**

history table, level and number of syslog messages **47-9**

hop counts

configuring MST bridges **16-28**

host

limit on dynamic port **12-29**

host ports

kinds of **35-4**

host presence CDP message **36-8**

Hot Standby Routing Protocol

See HSRP

HSRP

description **1-10**

http

http://www.cisco.com/en/US/docs/ios/12_4/ip_sla/configuration/guide/hsla_c.html **50-1, 50-4**

- //www.cisco.com/en/US/docs/ios/fnetflow/configuration/guide/12_4t/fnf_12_4t_book.html **32-1**
- //www.cisco.com/en/US/docs/ios/fundamentals/command reference/cf_book.html **47-1, 49-1, 51-1**
- hw-module module num power command **10-18**
-
- I**
- ICMP
- enabling **8-12**
 - ping **8-7**
 - running IP traceroute **8-9**
 - time exceeded messages **8-9**
- ICMP Echo operation
- configuring **50-12**
 - IP SLAs **50-11**
- i command **54-3**
- IDS
- using with SPAN and RSPAN **46-3**
- IEEE 802.1s
- See MST
- IEEE 802.1w
- See MST
- IEEE 802.3ad
- See LACP
- IGMP
- configurable-leave timer **21-4**
 - description **29-3**
 - enabling **29-13**
 - explicit host tracking **21-4**
 - immediate-leave processing **21-3**
 - leave processing, enabling **22-8**
 - overview **21-1**
 - report suppression
 - disabling **22-10**
- IGMP filtering
- configuring **21-21**
 - default configuration **21-20**
 - described **21-20**
- IGMP groups
- monitoring **21-24**
 - setting the maximum number **21-23**
- IGMP Immediate Leave
- configuration guidelines **21-9**
- IGMP profile
- applying **21-22**
 - configuration mode **21-21**
 - configuring **21-21**
- IGMP Snooping
- configure
 - leave timer **21-9**
 - configuring
 - Learning Methods **21-7**
 - static connection to a multicast router **21-8**
 - configuring host statically **21-11**
 - enabling
 - Immediate-Leave processing
 - explicit host tracking **21-11**
 - suppressing multicast flooding **21-12**
 - IGMP snooping
 - configuration guidelines **21-5**
 - default configuration **22-5, 22-6**
 - enabling
 - globally **21-6**
 - on a VLAN **21-6**
 - enabling and disabling **22-6**
 - IP multicast and **29-4**
 - monitoring **21-14, 22-11**
 - overview **21-1**
 - IGMP Snooping, displaying
 - group **21-16**
 - hot membership **21-15**
 - how to **21-15**
 - MAC address entries **21-18**
 - multicast router interfaces **21-17**
 - on a VLAN interface **21-18**
 - Querier information **21-19**
 - IGMPSnooping Querier, configuring **21-10**

- Immediate Leave, IGMP
enabling **22-8**
- immediate-leave processing
enabling **21-8**
- IGMP
See fast-leave processing
- ingress packets, SPAN enhancement **46-12**
- inline power
configuring on Cisco IP phones **34-5**
- Intelligent Power Management **11-4**
- interacting with Baby Giants **7-20**
- interface command **3-9, 7-2**
- interface link and trunk status events
configuring **7-26**
- interface port-channel command **19-7**
- interface range command **7-5**
- interface range macro command **7-6**
- interfaces
adding descriptive name **7-13**
clearing counters **7-25**
configuring **7-2**
configuring ranges **7-4**
displaying information about **7-24**
Layer 2 modes **14-4**
maintaining **7-24**
monitoring **7-24**
naming **7-13**
numbers **7-2**
overview **7-2**
restarting **7-25**
See also Layer 2 interfaces
- Internet Control Message Protocol
See ICMP
- Internet Group Management Protocol
See IGMP
- Internet Protocol version 6
See IPv6
- Inter-Switch Link encapsulation
See ISL encapsulation
- Intrusion Detection System
See IDS
- inventory management TLV **23-2, 23-7**
- IP
configuring default gateway **3-11**
configuring static routes **3-11**
displaying statistics **27-8**
- IP addresses
128-bit **43-2**
discovering **4-30**
IPv6 **43-2**
ip cef command **27-6, 53-2**
- IP Enhanced IGRP
interfaces, displaying **26-17**
- ip icmp rate-limit unreachable command **8-12**
- ip igmp profile command **21-21**
- ip igmp snooping tcn flood command **21-13**
- ip igmp snooping tcn flood query count command **21-14**
- ip igmp snooping tcn query solicit command **21-14**
- IP information
assigned
through DHCP-based autoconfiguration **3-2**
- ip load-sharing per-destination command **27-7**
- ip local policy route-map command **30-8**
- ip mask-reply command **8-13**
- IP MTU sizes, configuring **26-8**
- IP MTU sizes, configuring **26-8**
- IP multicast
clearing table entries **29-26**
configuring **29-12**
default configuration **29-12**
displaying PIM information **29-21**
displaying the routing table information **29-22**
enabling dense-mode PIM **29-14**
enabling sparse-mode **29-14**
features not supported **29-12**
hardware forwarding **29-8**
IGMP snooping and **21-5, 29-4**
overview **29-1**

- routing protocols **29-2**
- software forwarding **29-8**
- See also Auto-RP; IGMP; PIM; RP; RPF
- IP multicast routing
 - enabling **29-13**
 - monitoring and maintaining **29-21**
- ip multicast-routing command **29-13**
- IP phones
 - configuring voice ports **34-3**
 - See Cisco IP Phones **34-1**
- ip pim command **29-14**
- ip pim dense-mode command **29-14**
- ip pim sparse-dense-mode command **29-15**
- ip policy route-map command **30-7**
- ip redirects command **8-13**
- IP routing tables
 - deleting entries **29-26**
- IP Service Level Agreements
 - See IP SLAs
- IP service levels, analyzing **50-1**
- IP SLAs
 - benefits **50-3**
 - Control Protocol **50-4**
 - default configuration **50-7**
 - definition **50-1**
 - ICMP echo operation **50-11**
 - measuring network performance **50-3**
 - monitoring **50-13**
 - multioperations scheduling **50-6**
 - operation **50-4**
 - responder
 - described **50-4**
 - enabling **50-8**
 - response time **50-5**
 - scheduling **50-6**
 - SNMP support **50-3**
 - supported metrics **50-3**
 - threshold monitoring **50-6**
 - UDP jitter operation **50-9**
- IP Source Guard
 - configuring **40-20**
 - configuring on private VLANs **40-22**
 - displaying **40-22, 40-23**
 - overview **40-19**
- IP statistics
 - displaying **27-8**
- IP traceroute
 - executing **8-9**
 - overview **8-9**
- IP unicast
 - displaying statistics **27-8**
- IP Unnumbered support
 - configuring on a range of Ethernet VLANs **13-6**
 - configuring on LAN and VLAN interfaces **13-5**
 - configuring with connected host polling **13-7**
 - DHCP Option 82 **13-3**
 - displaying settings **13-8**
 - format of agent remote ID suboptions **13-3**
 - troubleshooting **13-9**
 - with connected host polling **13-4**
 - with DHCP server and Relay agent **13-2**
- ip unreachable command **8-12**
- IPv6
 - addresses **43-2**
 - default configuration **43-7**
 - defined **43-1**
 - Enhanced Interior Gateway Routing Protocol (EIGRP)
 - IPv6 **43-6**
 - Router ID **43-6**
 - OSPF **43-5**
- IPX
 - redistribution of route information with EIGRP **1-12**
- ISL
 - encapsulation **14-3**
 - isolated port **35-4**
 - isolated VLANs **35-3, 35-4**
- ISSU
 - compatibility matrix **6-13**

compatibility verification using Cisco Feature Navigator **6-14**

NSF overview **6-3**

perform the process

 aborting a software upgrade **6-31**

 configuring the rollback timer as a safeguard **6-32**

 displaying a compatibility matrix **6-34**

 loading the new software on the new standby **6-24**

 stopping the rollback timer **6-23**

 switching to the standby **6-21**

 verify the ISSU state **6-17**

 verify the redundancy mode **6-16**

 verify the software installation **6-15**

 vload the new software on standby **6-18**

prerequisites **6-2**

process overview **6-6**

restrictions **6-2**

SNMP support **6-14**

SSO overview **6-3**

IST

and MST regions **16-22**

description **16-22**

master **16-27**

J

jumbo frames

 and ethernet ports **7-18**

 configuring MTU sizes for **7-19**

 ports and linecards that support **7-16**

 understanding MTUs **7-17**

 understanding support **7-17**

 VLAN interfaces **7-18**

K

keyboard shortcuts **2-3**

L

labels, definition **33-3**

LACP

 system ID **19-4**

Layer 2 access ports **14-8**

Layer 2 frames

 classification with CoS **33-2**

Layer 2 interface, configuring access-mode mode on **42-30**

Layer 2 interfaces

 assigning VLANs **12-7**

 configuring **14-5**

 configuring as PVLAN host ports **35-17**

 configuring as PVLAN promiscuous ports **35-16**

 configuring as PVLAN trunk ports **35-18**

 defaults **14-5**

 disabling configuration **14-9**

 modes **14-4**

 show interfaces command **14-7**

Layer 2 interface type

 resetting **35-22**

 setting **35-22**

Layer 2 switching

 overview **14-1**

Layer 2 Traceroute

 and ARP **8-11**

 and CDP **8-10**

 host-to-host paths **8-10**

 IP addresses and subnets **8-11**

 MAC addresses and VLANs **8-10**

 multicast traffic **8-10**

 multiple devices on a port **8-11**

 unicast traffic **1-24, 8-10**

 usage guidelines **8-10**

Layer 2 trunks

 configuring **14-6**

 overview **14-3**

Layer 3 interface, applying IPv6 ACLs **42-16**

Layer 3 interface counters,configuring **26-9**
 Layer 3 interface counters,understanding **26-3**
 Layer 3 interfaces
 changing from Layer 2 mode **31-7**
 configuration guidelines **26-4**
 overview **26-1**
 logical **26-2**
 physical **26-2**
 VLANs as interfaces **26-6**
 Layer 3 packets
 classification methods **33-2**
 Layer 4 port operations
 configuration guidelines **42-10**
 restrictions **42-9**
 Leave timer, enabling **21-9**
 link and trunk status events
 configuring interface **7-26**
 Link Layer Discovery Protocol
 See CDP
 listening state (STP)
 RSTP comparisons (table) **16-24**
 LLDP
 configuring **23-3**
 characteristics **23-4**
 default configuration **23-3**
 disabling and enabling
 globally **23-5**
 on an interface **23-6**
 monitoring and maintaining **23-10**
 overview **23-1**
 transmission timer and holdtime, setting **23-4**
 LLDP-MED
 configuring
 procedures **23-3**
 TLVs **23-7, 23-8**
 monitoring and maintaining **23-10**
 overview **23-1**
 supported TLVs **23-2**
 load balancing
 configuring for CEF **27-7**
 configuring for EtherChannel **19-12**
 overview **19-5, 27-6**
 per-destination **27-7**
 location service
 configuring **23-9**
 location TLV **23-3, 23-7**
 logging, EPM **36-70**
 Logical Layer 3 interfaces
 configuring **26-5**
 login authentication
 with TACACS+ **3-19**
 login banners **4-17**
 login timer
 changing **8-6**
 logout warning command **8-6**
 loop guard
 and MST **16-23**
 configuring **18-5**
 overview **18-3**

M

MAC/PHY configuration status TLV **23-2**
 MAC addresses
 aging time **4-21**
 allocating **16-5**
 and VLAN association **4-20**
 building tables **4-20, 14-2**
 convert dynamic to sticky secure **38-5**
 default configuration **4-21**
 discovering **4-30**
 displaying **4-30, 8-3**
 displaying in DHCP snooping binding table **40-19**
 dynamic
 learning **4-20**
 removing **4-22**
 in ACLs **42-12**
 static

- adding **4-28**
- allowing **4-29**
- characteristics of **4-27**
- dropping **4-29**
- removing **4-28**
- sticky **38-4**
- sticky secure, adding **38-5**
- MAC Authentication Bypass
 - configure with 802.1X **36-48**
- MAC details, displaying **36-70**
- MAC extended access lists **42-12**
- macros
 - See Smartports macros
- main-cpu command **5-8**
- management address TLV **23-2**
- management options
 - SNMP **49-1**
- marking
 - hardware capabilities **33-21**
 - marking action drivers **33-19**
 - marking network traffic **33-16**
 - marking support, multi-attribute **33-20**
 - match ip address command **30-6**
 - maximum aging time (STP)
 - configuring **16-18**
- MDA
 - configuration guidelines **36-20 to 36-21**
 - described **36-20**
 - messages, to users through banners **4-17**
- MFIB
 - CEF **29-5**
 - overview **29-11**
- MFIB, IP
 - displaying **29-24**
- MIBs
 - compiling **55-4**
 - downloading **55-2, 55-3, 55-4**
 - overview **49-1**
 - SNMP interaction with **49-4**
- MLD Done messages and Immediate-leave **22-4**
- MLD messages **22-2**
- MLD queries **22-3**
- MLD reports **22-4**
- MLD Snooping
 - MLD Done messages and Immediate-leave **22-4**
 - MLD messages **22-2**
 - MLD queries **22-3**
 - MLD reports **22-4**
 - Multicast client aging robustness **22-3**
 - Multicast router discovery **22-3**
 - overview **22-1**
- Mode of capturing control packets, selecting **42-7**
- modules
 - checking status **8-2**
 - monitoring
 - ACL information **42-34**
 - IGMP
 - snooping **22-11**
 - IGMP filters **21-24**
 - IGMP snooping **21-14**
 - IP SLAs operations **50-13**
 - multicast router interfaces **22-11**
 - multi-VRF CE **31-17**
 - traffic flowing among switches **51-1**
 - VLAN filters **42-24**
 - VLAN maps **42-24**
 - M-record **16-22**
 - MST
 - and multiple spanning trees **1-5, 16-22**
 - boundary ports **16-27**
 - BPDUs **16-22**
 - configuration parameters **16-26**
 - configuring **16-29**
 - displaying configurations **16-33**
 - edge ports **16-27**
 - enabling **16-29**
 - hop count **16-28**
 - instances

- configuring parameters **16-32**
 - description **16-22**
 - number supported **16-26**
 - interoperability with PVST+ **16-23**
 - link type **16-28**
 - master **16-27**
 - message age **16-28**
 - regions **16-26**
 - restrictions **16-29**
 - to-SST interoperability **16-24**
 - MSTP
 - EtherChannel guard
 - enabling **18-6**
 - M-record **16-22**
 - M-tree **16-22**
 - M-tree **16-22**
 - MTUS
 - understanding **7-17**
 - MTU size
 - configuring **7-19, 7-20, 7-26, 7-27**
 - default **12-5**
 - multiauthentication mode **36-8**
 - multicast
 - See IP multicast
 - Multicast client aging robustness **22-3**
 - multicast groups
 - static joins **22-7**
 - multicast packets
 - blocking **44-2**
 - Multicast router discovery **22-3**
 - multicast router interfaces, displaying **21-17**
 - multicast router interfaces, monitoring **22-11**
 - multicast router ports, adding **22-7**
 - multicast routers
 - flood suppression **21-12**
 - multicast router table
 - displaying **29-22**
 - Multicast Storm Control
 - enabling **45-4**
 - disabling **45-6**
 - multidomain authentication
 - See MDA
 - multidomain authentication mode **36-7**
 - multioperations scheduling, IP SLAs **50-6**
 - Multiple Authentication
 - described **36-20**
 - Multiple AuthorizationAuthentication
 - configuring **36-29**
 - Multiple Domain Authentication **36-29**
 - multiple forwarding paths **1-5, 16-22**
 - multiple-hosts mode **36-7**
 - Multiple Spanning Tree
 - See MST
 - multiple VPN routing/forwarding
 - See multi-VRF CE
 - multi-VRF CE
 - components **31-3**
 - configuration example **31-12**
 - default configuration **31-3**
 - defined **31-1**
 - displaying **31-17**
 - monitoring **31-17**
 - network components **31-3**
 - packet-forwarding process **31-3**
-
- N**
- named IPv6 ACLs, configuring
 - ACLs
 - configuring named IPv6 ACLs **42-15**
 - named MAC extended ACLs
 - ACLs
 - configuring named MAC extended **42-12, 42-14**
 - native VLAN
 - specifying **14-6**
 - network fault tolerance **1-5, 16-22**
 - network management

- configuring **20-1**
 - RMON **51-1**
 - SNMP **49-1**
 - network performance, measuring with IP SLAs **50-3**
 - network policy TLV **23-2, 23-7**
 - Network Time Protocol
 - See NTP
 - network traffic, marking **33-16**
 - New Software Features in Release 7.7
 - TDR **8-3**
 - Next Hop Resolution Protocol
 - See NHRP
 - NHRP
 - support **1-12**
 - non-IP traffic filtering **42-12, 42-14**
 - non-RPF traffic
 - description **29-9**
 - in redundant configurations (figure) **29-10**
 - Nonstop Forwarding
 - See NSF
 - nonvolatile random-access memory
 - See NVRAM
 - normal-range VLANs
 - See VLANs
 - NSF
 - defined **9-1**
 - guidelines and restrictions **9-7**
 - operation **9-4**
 - NSF-aware
 - support **9-2**
 - NSF-capable
 - supervisor engines **9-2**
 - support **9-2**
 - NSF with SSO supervisor engine redundancy
 - and CEF **9-4**
 - overview **9-3**
 - SSO operation **9-3**
 - NTP
 - associations
 - authenticating **4-4**
 - defined **4-2**
 - enabling broadcast messages **4-7**
 - peer **4-6**
 - server **4-6**
 - default configuration **4-4**
 - displaying the configuration **4-11**
 - overview **4-2**
 - restricting access
 - creating an access group **4-9**
 - disabling NTP services per interface **4-10**
 - source IP address, configuring **4-10**
 - stratum **4-2**
 - synchronizing devices **4-6**
 - time
 - services **4-2**
 - synchronizing **4-2**
 - NVRAM
 - saving settings **3-10**
-
- ## O
- OIR
 - overview **7-23**
 - Online Diagnostics **53-1**
 - online insertion and removal
 - See OIR
 - Open Shortest Path First
 - See OSPF
 - operating system images
 - See system images
 - Option 82
 - enabling DHCP Snooping **40-10**
 - OSPF
 - area concept **1-13**
 - description **1-13**
 - for IPv6 **43-5**

P

packets

- modifying [33-9](#)

packet type filtering

- overview [46-14](#)

- SPAN enhancement [46-14](#)

PACL, using with access-group mode [42-29](#)

PACL with VLAN maps and router ACLs [42-31](#)

PAgP

- understanding [19-3](#)

passwords

- configuring enable password [3-14](#)

- configuring enable secret password [3-14](#)

- encrypting [3-22](#)

- recovering lost enable password [3-25](#)

- setting line password [3-14](#)

PBR (policy-based routing)

- configuration (example) [30-8](#)

- enabling [30-6](#)

- features [30-2](#)

- overview [30-1](#)

- route-map processing logic [30-3](#)

- route-map processing logic example [30-4](#)

- route maps [30-2](#)

- when to use [30-5](#)

per-port and VLAN Access Control List [40-19](#)

per-port per-VLAN QoS

- enabling [33-33](#)

- overview [33-10](#)

Per-User ACL and Filter-ID ACL, configure [36-38](#)

Per-VLAN Rapid Spanning Tree [16-6](#)

- enabling [16-20](#)

- overview [16-6](#)

PE to CE routing, configuring [31-11](#)

Physical Layer 3 interfaces, configuring [26-10](#)

PIM

- configuring dense mode [29-14](#)

- configuring sparse mode [29-14](#)

displaying information [29-21](#)

displaying statistics [29-25](#)

enabling sparse-dense mode [29-14, 29-15](#)

overview [29-3](#)

PIM-DM [29-3](#)

PIM on an interface, enabling [29-13](#)

PIM-SM [29-4](#)

PIM-SSM mapping, enabling [29-16](#)

ping

- executing [8-8](#)

- overview [8-7](#)

ping command [8-8, 29-21](#)

PoE [11-7](#)

- configuring power consumption for single device [11-5](#)

- Enhanced PoE support on E-series [11-15](#)

- policing and monitoring [11-11](#)

- power consumption for powered devices

- Intelligent Power Management [11-4](#)

- power management modes [11-3](#)

- show interface status [11-6](#)

PoE policing

- configuring errdisable recovery [11-14](#)

- configuring on an interface [11-12](#)

- displaying on an interface [11-13](#)

- power modes [11-12](#)

point-to-point

- in 802.1X authentication (figure) [36-2](#)

policing

- how to implement [33-15](#)

- See QoS policing

policing, PoE [11-11](#)

policy associations, QoS on Sup 6-E [33-37](#)

policy-map command [33-14](#)

policy map marking action, configuring [33-21](#)

port ACLs

- and voice VLAN [42-4](#)

- defined [42-3](#)

- limitations [42-5](#)

- Port Aggregation Protocol
 - see PAgP
- port-based authentication
 - 802.1X with voice VLAN **36-19**
 - authentication server
 - defined **37-2**
 - changing the quiet period **36-63**
 - client, defined **36-3, 37-2**
 - configuration guidelines **36-24, 37-6**
 - configure ACL assignments and redirect URLs **36-32**
 - configure switch-to-RADIUS server communication **36-27**
 - configure with Authentication Failed VLAN assignment **36-53**
 - configure with Critical Authentication **36-50**
 - configure with Guest-VLANs **36-46, 36-54**
 - configure with MAC Authentication Bypass **36-48**
 - configure with Wake-on-LAN **36-52**
 - configuring
 - Multiple Domain Authentication and Multiple Authorization **36-29**
 - RADIUS server **37-10**
 - RADIUS server parameters on the switch **37-8**
 - configuring Fallback Authentication **36-57**
 - configuring Guest-VLAN **36-27**
 - configuring manual re-authentication of a client **36-66**
 - controlling authorization state **36-5**
 - default configuration **36-23, 37-6**
 - described **36-1**
 - device roles **36-2, 37-2**
 - displaying statistics **36-67, 37-13**
 - enabling **36-24**
 - 802.1X authentication **37-8**
 - enabling multiple hosts **36-62**
 - enabling periodic re-authentication **36-61**
 - encapsulation **36-3**
 - host mode **36-6**
 - how 802.1X fails on a port **36-21**
 - initiation and message exchange **36-3**
 - method lists **36-24**
 - modes **36-6**
 - multidomain authentication **36-20**
 - multiple-hosts mode, described **36-7**
 - port security
 - multiple-hosts mode **36-7**
 - ports not supported **36-4**
 - pre-authentication open access **36-8**
 - resetting to default values **36-66**
 - setting retransmission number **36-64**
 - setting retransmission time **36-63**
 - switch
 - as proxy **37-2**
 - topologies, supported **36-21**
 - using with ACL assignments and redirect URLs **36-17**
 - using with port security **36-16**
 - with Critical Authentication **36-13**
 - with Guest VLANs **36-10**
 - with MAC Authentication Bypass **36-11**
 - with VLAN assignment **36-9**
 - port-channel interfaces
 - See also EtherChannel
 - creating **19-7**
 - overview **19-2**
 - port-channel load-balance
 - command **19-12**
 - command example **19-12**
 - port-channel load-balance command **19-13**
 - port cost (STP)
 - configuring **16-15**
 - port description TLV **23-2**
 - PortFast
 - and MST **16-23**
 - BPDU filter, configuring **18-10**
 - configuring or enabling **18-16**
 - overview **18-7**
 - PortFast BPDU filtering
 - and MST **16-23**

- enabling [18-10](#)
- overview [18-9](#)
- port numbering with TwinGig Convertors [7-7](#)
- port priority
 - configuring MST instances [16-32](#)
 - configuring STP [16-13](#)
- ports
 - blocking [44-1](#)
 - checking status [8-2](#)
 - dynamic VLAN membership
 - example [12-29](#)
 - reconfirming [12-26](#)
 - forwarding, resuming [44-3](#)
 - See also interfaces
- port security
 - aging [38-5](#)
 - configuring [38-7](#)
 - displaying [38-28](#)
 - guidelines and restrictions [38-33](#)
 - on access ports [38-7, 38-22](#)
 - on private VLAN [38-14](#)
 - host [38-14](#)
 - promiscuous [38-16](#)
 - topology [38-15, 38-18, 38-32](#)
 - on trunk port [38-17](#)
 - guidelines and restrictions [38-15, 38-18, 38-21, 38-32](#)
 - port mode changes [38-22](#)
 - on voice ports [38-22](#)
 - sticky learning [38-5](#)
 - using with 802.1X [36-16](#)
 - violations [38-6](#)
 - with 802.1X Authentication [38-32](#)
 - with DHCP and IP Source Guard [38-31](#)
 - with other features [38-33](#)
- port states
 - description [16-5](#)
- port VLAN ID TLV [23-2](#)
- power
 - inline [34-5](#)
 - power dc input command [10-17](#)
 - power handling for Supervisor Engine II-TS [11-11](#)
 - power inline command [11-3](#)
 - power inline consumption command [11-5](#)
 - power management
 - Catalyst 4500 series [10-5](#)
 - Catalyst 4500 Switch power supplies [10-12](#)
 - configuring combined mode [10-11](#)
 - configuring redundant mode [10-10](#)
 - overview [10-1](#)
 - redundancy [10-5](#)
 - power management for Catalyst 4500 Switch
 - combined mode [10-7](#)
 - redundant mode [10-7](#)
 - power management limitations in Catalyst 4500 Switch [10-8](#)
 - power management mode
 - selecting [10-7](#)
 - power management TLV [23-2, 23-7](#)
 - power negotiation
 - through LLDP [23-8](#)
 - Power-On-Self-Test diagnostics [53-9, 53-20](#)
 - Power-On-Self-Test for Supervisor Engine V-10GE [53-14](#)
 - power redundancy-mode command [10-10](#)
 - power supplies
 - available power for Catalyst 4500 Switch [10-12](#)
 - fixed [10-6](#)
 - variable [10-6](#)
 - pre-authentication open access [36-8](#)
 - pre-authentication open access. See port-based authentication.
 - primary VLANs [35-3, 35-5](#)
 - associating with secondary VLANs [35-14](#)
 - configuring as a P VLAN [35-13](#)
 - priority
 - overriding CoS of incoming frames [34-5](#)
 - priority queuing, QoS on Sup 6-E [33-28](#)
 - private VLAN
 - configure port security [38-14, 38-15](#)

enabling DHCP Snooping [40-11](#)
 private VLANs
 across multiple switches [35-5](#)
 and SVIs [35-10](#)
 benefits of [35-3](#)
 community ports [35-4](#)
 community VLANs [35-3, 35-4](#)
 default configuration [35-11](#)
 end station access to [35-3](#)
 isolated port [35-4](#)
 isolated VLANs [35-3, 35-4](#)
 ports
 community [35-4](#)
 isolated [35-4](#)
 promiscuous [35-5](#)
 primary VLANs [35-3, 35-5](#)
 promiscuous ports [35-5](#)
 secondary VLANs [35-3](#)
 subdomains [35-3](#)
 traffic in [35-9](#)
 privileged EXEC mode [2-5](#)
 privileges
 changing default [3-23](#)
 configuring levels [3-23](#)
 exiting [3-24](#)
 logging in [3-24](#)
 promiscuous ports
 configuring PVLAN [35-16](#)
 defined [35-5](#)
 setting mode [35-22](#)
 protocol timers [16-4](#)
 provider edge devices [31-2](#)
 pruning, VTP
 See VTP pruning
 pseudobridges
 description [16-25](#)
 PVACL [40-19](#)
 PVID (port VLAN ID)
 and 802.1X with voice VLAN ports [36-19](#)

PVLAN promiscuous trunk port
 configuring [35-2, 35-16, 35-19](#)
 PVLANs
 802.1q support [35-13](#)
 across multiple switches [35-5](#)
 configuration guidelines [35-11](#)
 configure port security [38-14, 38-16, 38-18](#)
 configure port security in a wireless setting [38-32](#)
 configuring [35-10](#)
 configuring a VLAN [35-13](#)
 configuring promiscuous ports [35-16](#)
 host ports
 configuring a Layer 2 interface [35-17](#)
 setting [35-22](#)
 overview [35-1](#)
 permitting routing, example [35-21](#)
 promiscuous mode
 setting [35-22](#)
 setting
 interface mode [35-22](#)

Q

QoS
 classification [33-6 to ??](#)
 definitions [33-3](#)
 enabling per-port per-VLAN [33-33](#)
 overview [33-1](#)
 overview of per-port per-VLAN [33-10](#)
 packet modification [33-9](#)
 traffic shaping [33-9](#)
 See also COS; DSCP values; transmit queues
 QoS active queue management
 tracking queue length [33-9](#)
 QoS labels
 definition [33-3](#)
 QoS marking
 description [33-5](#)
 QoS on Sup 6-E

- Active Queue management via DBL **33-32**
active queue management via DBL **33-25, 33-32**
classification **33-13**
configuring **33-11**
configuring the policy map marking action **33-21**
hardware capabilities for marking **33-21**
how to implement policing **33-15**
marking action drivers **33-19**
marking network traffic **33-16**
MQC-based QoS configuration **33-11**
multi-attribute marking support **33-20**
platform hardware capabilities **33-12**
platform restrictions **33-16**
platform-supported classification criteria and QoS features **33-11**
policing **33-14**
policy associations **33-37**
prerequisites for applying a service policy **33-13**
priority queuing **33-28**
queue-limiting **33-29**
restrictions for applying a service policy **33-13**
shaping **33-23**
sharing(bandwidth) **33-25**
sharing(bandwidth), shaping, and priority queuing **33-23**
software QoS **33-38**
traffic marking procedure flowchart **33-19**
- QoS policing
definition **33-5**
described **33-8**
- QoS policy
attaching to interfaces **33-8**
- QoS service policy
prerequisites **33-13**
restrictions for applying **33-13**
- QoS transmit queues
burst **33-9**
maximum rate **33-9**
sharing link bandwidth **33-9**
- Quality of service
See QoS
queueing **33-8**
queue-limiting, QoS on Sup 6-E **33-29**
-
- R**
- RADIUS server
configure to-Switch communication **36-27**
configuring settings **36-29**
parameters on the switch **36-27**
- range command **7-5**
range macros
defining **7-6**
ranges of interfaces
configuring **7-4**
- Rapid Spanning Tree
See RSTP
- re-authentication of a client
configuring manual **36-66**
enabling periodic **36-61**
- redirect URLs, port-based authentication **36-17**
- reduced MAC address **16-2**
- redundancy
configuring **5-7**
guidelines and restrictions **5-6**
changes made through SNMP **5-11**
- NSF-aware support **9-2**
NSF-capable support **9-2**
overview **5-2**
redundancy command **5-8**
understanding synchronization **5-5**
- redundancy (NSF) **9-1**
configuring
BGP **9-9**
CEF **9-8**
EIGRP **9-12**
OSPF **9-11**
routing protocols **9-5**

- redundancy (RPR)
- route processor redundancy **5-3**
 - synchronization **5-5**
- redundancy (SSO)
- redundancy command **9-8**
 - route processor redundancy **5-3**
 - synchronization **5-6**
- reload command **3-28, 3-29, 3-40**
- Remote Network Monitoring
- See RMON
- rendezvous point, configuring **29-16**
- rendezvous point, configuring single static **29-19**
- replication
- description **29-8**
- report suppression, IGMP
- disabling **22-10**
- reserved-range VLANs
- See VLANs
- reset command **54-3**
- resetting an interface to default configuration **7-28**
- resetting a switch to defaults **3-32**
- responder, IP SLAs
- described **50-4**
 - enabling **50-8**
- response time, measuring with IP SLAs **50-5**
- restricting access
- NTP services **4-8**
 - TACACS+ **3-15**
- retransmission number
- setting in 802.1X authentication **36-64**
- retransmission time
- changing in 802.1X authentication **36-63**
- RFC
- 1157, SNMPv1 **49-2**
 - 1305, NTP **4-2**
 - 1757, RMON **51-2**
 - 1901, SNMPv2C **49-2**
 - 1902 to 1907, SNMPv2 **49-2**
 - 2273-2275, SNMPv3 **49-2**
- RIP
- description **1-13**
 - for IPv6 **43-5**
- RMON
- default configuration **51-3**
 - displaying status **51-6**
 - enabling alarms and events **51-3**
 - groups supported **51-2**
 - overview **51-1**
- ROM monitor
- boot process and **3-26**
 - CLI **2-7**
 - commands **54-2 to ??**
 - exiting **54-5**
- root bridge
- configuring **16-9**
 - selecting in MST **16-22**
- root guard
- and MST **16-23**
 - enabling **18-2**
 - overview **18-2**
- routed packets
- ACLs **42-26**
- route-map (IP) command **30-6**
- route maps
- defining **30-6**
 - PBR **30-2**
- router ACLs
- description **42-3**
 - using with VLAN maps **42-25**
- router ACLs, using PACL with VLAN maps **42-31**
- route targets
- VPN **31-3**
- Routing Information Protocol
- See RIP
- RPF
- <Emphasis>See Unicast RPF
- RSPAN
- configuration guidelines **46-16**

- destination ports **46-5**
 IDS **46-3**
 monitored ports **46-4**
 monitoring ports **46-5**
 received traffic **46-3**
 sessions
 creating **46-17**
 defined **46-3**
 limiting source traffic to specific VLANs **46-23**
 monitoring VLANs **46-22**
 removing source (monitored) ports **46-21**
 specifying monitored ports **46-17**
 source ports **46-4**
 transmitted traffic **46-4**
 VLAN-based **46-5**
- RSTP
 compatibility **16-23**
 description **16-22**
 port roles **16-23**
 port states **16-24**
-
- S**
- SAID
 See 802.10 SAID
 scheduling **33-8**
 scheduling, IP SLAs operations **50-6**
 secondary root switch **16-12**
 secondary VLANs **35-3**
 associating with primary **35-14**
 permitting routing **35-21**
 security
 configuring **39-1**
 Security Association Identifier
 See 802.10 SAID
 selecting a power management mode **10-7**
 selecting X2/TwinGig Convertor Mode **7-8**
 sequence numbers in log messages **47-7**
 server IDs
 description **52-23**
 service policy, configure class-level queue-limit **33-29**
 service-policy input command **25-2**
 set default interface command **30-7**
 set interface command **30-7**
 set ip default next-hop command **30-7**
 set ip next-hop command **30-6**
 set-request operation **49-4**
 severity levels, defining in system messages **47-8**
 shaping, QoS on Sup 6-E **33-23**
 sharing(bandwidth), QoS on Sup 6-E **33-25**
 show adjacency command **27-9**
 show boot command **3-31**
 show catalyst4000 chassis-mac-address command **16-3**
 show cdp command **20-2, 20-3**
 show cdp entry command **20-3**
 show cdp interface command **20-3**
 show cdp neighbors command **20-4**
 show cdp traffic command **20-4**
 show ciscoview package command **4-33**
 show ciscoview version command **4-33**
 show configuration command **7-13**
 show debugging command **20-4**
 show environment command **10-2**
 show history command **2-4**
 show interfaces command **7-19, 7-20, 7-24, 7-26, 7-27**
 show interfaces status command **8-2**
 show ip cef command **27-8**
 show ip eigrp interfaces command **26-17**
 show ip eigrp neighbors command **26-17**
 show ip eigrp topology command **26-17**
 show ip eigrp traffic command **26-17**
 show ip interface command **29-21**
 show ip local policy command **30-8**
 show ip mroute command **29-21**
 show ip pim interface command **29-21**
 show lldp traffic command **23-10**
 show mac-address-table address command **8-3**
 show mac-address-table interface command **8-3**

- show mls entry command **27-8**
- show module command **8-2, 16-5**
- show PoE consumed **11-7**
- show power inline command **11-6**
- show power supplies command **10-10**
- show protocols command **7-24**
- show running-config command
 - adding description for an interface **7-13**
 - checking your settings **3-9**
 - displaying ACLs **42-19, 42-21, 42-28, 42-29, 42-30**
- show startup-config command **3-10**
- show users command **8-6**
- show version command **3-29**
- shutdown, command **7-25**
- shutting down
 - interfaces **7-25**
- Simple Network Management Protocol
 - See SNMP
- single-host mode **36-7**
- single spanning tree
 - See SST
- single static RP, configuring **29-19**
- slot numbers, description **7-2**
- smart call home **52-1**
 - description **52-2**
 - destination profile (note) **52-5**
 - registration requirements **52-3**
 - service contract requirements **52-3**
 - Transport Gateway (TG) aggregation point **52-2**
- SMARTnet
 - smart call home registration **52-3**
- Smartports macros
 - applying global parameter values **15-8**
 - applying macros **15-8**
 - applying parameter values **15-8**
 - configuration guidelines **15-6**
 - configuring **15-2**
 - creating **15-7**
 - default configuration **15-3**
- defined **15-1**
- displaying **15-12**
- tracing **15-6**
- SNMP
 - accessing MIB variables with **49-4**
 - agent
 - described **49-4**
 - disabling **49-7**
 - and IP SLAs **50-3**
 - authentication level **49-10**
 - community strings
 - configuring **49-7**
 - overview **49-4**
 - configuration examples **49-16**
 - configuration guidelines **49-6**
 - default configuration **49-5**
 - enabling **55-4, 55-5**
 - engine ID **49-6**
 - groups **49-6, 49-9**
 - host **49-6**
 - informs
 - and trap keyword **49-11**
 - described **49-5**
 - differences from traps **49-5**
 - enabling **49-15**
 - limiting access by TFTP servers **49-15**
 - limiting system log messages to NMS **47-9**
 - manager functions **49-3**
 - notifications **49-5**
 - overview **49-1, 49-4**
 - status, displaying **49-17**
 - system contact and location **49-15**
 - trap manager, configuring **49-13**
 - traps
 - described **49-3, 49-5**
 - differences from informs **49-5**
 - enabling **49-11**
 - enabling MAC address notification **4-22**
 - enabling MAC move notification **4-24**

- enabling MAC threshold notification **4-26**
- overview **49-1, 49-4**
- types of **49-11**
- users **49-6, 49-9**
- versions supported **49-2**
- SNMP commands **55-4**
- SNMPv1 **49-2**
- SNMPv2C **49-2**
- SNMPv3 **49-2**
- software
 - upgrading **5-13**
- software configuration register **3-26**
- software QoS, on Sup 6-E **33-38**
- software switching
 - description **27-5**
 - interfaces **27-6**
 - key data structures used **29-7**
- source IDs
 - call home event format **52-22**
- SPAN
 - and ACLs **46-5**
 - configuration guidelines **46-7**
 - configuring **46-7 to 46-10**
 - destination ports **46-5**
 - IDS **46-3**
 - monitored port, defined **46-4**
 - monitoring port, defined **46-5**
 - received traffic **46-3**
 - sessions
 - defined **46-3**
 - source ports **46-4**
 - transmitted traffic **46-4**
 - VLAN-based **46-5**
- SPAN and RSPAN
 - concepts and terminology **46-3**
 - default configuration **46-6**
 - displaying status **46-24**
 - overview **46-2**
 - session limits **46-6**
- SPAN enhancements
 - access list filtering **46-13**
 - configuration example **46-15**
 - CPU port sniffing **46-10**
 - encapsulation configuration **46-12**
 - ingress packets **46-12**
 - packet type filtering **46-14**
 - spanning-tree backbonefast command **18-16**
 - spanning-tree cost command **16-15**
 - spanning-tree guard root command **18-2**
 - spanning-tree portfast bpdu-guard command **18-9**
 - spanning-tree portfast command **18-7**
 - spanning-tree port-priority command **16-13**
 - spanning-tree uplinkfast command **18-13**
 - spanning-tree vlan
 - command **16-9**
 - command example **16-9**
 - spanning-tree vlan command **16-8**
 - spanning-tree vlan cost command **16-15**
 - spanning-tree vlan forward-time command **16-19**
 - spanning-tree vlan hello-time command **16-17**
 - spanning-tree vlan max-age command **16-18**
 - spanning-tree vlan port-priority command **16-13**
 - spanning-tree vlan priority command **16-17**
 - spanning-tree vlan root primary command **16-10**
 - spanning-tree vlan root secondary command **16-12**
 - speed
 - configuring interface **7-11**
 - speed command **7-12**
 - SSO
 - configuring **9-8**
 - SSO operation **9-3**
 - SST
 - description **16-22**
 - interoperability **16-24**
 - static addresses
 - See addresses
 - static routes
 - configuring **3-11**

- verifying **3-12**
- statistics
 - 802.1X **37-13**
 - displaying 802.1X **36-67**
 - displaying PIM **29-25**
 - LLDP **23-10**
 - LLDP-MED **23-10**
 - SNMP input and output **49-17**
- sticky learning
 - configuration file **38-5**
 - defined **38-5**
 - disabling **38-5**
 - enabling **38-5**
 - saving addresses **38-5**
- sticky MAC addresses
 - configuring **38-7**
 - defined **38-4**
- Storm Control
 - displaying **45-6**
 - enabling Broadcast **45-3**
 - enabling Multicast **45-4**
 - hardware-based, implementing **45-2**
 - overview **45-1**
 - software-based, implementing **45-2**
- STP
 - bridge ID **16-2**
 - configuring **16-7 to 16-20**
 - creating topology **16-4**
 - defaults **16-6**
 - disabling **16-19**
 - enabling **16-7**
 - enabling extended system ID **16-8**
 - enabling Per-VLAN Rapid Spanning Tree **16-20**
 - EtherChannel guard
 - disabling **18-7**
 - forward-delay time **16-18**
 - hello time **16-17**
 - maximum aging time **16-18**
 - overview **16-1, 16-3**
- per-VLAN rapid spanning tree **16-6**
- port cost **16-15**
- port priority **16-13**
- root bridge **16-9**
- stratum, NTP **4-2**
- stub routing (EIGRP)
 - benefits **26-16**
 - configuration tasks **26-16**
 - configuring **26-12**
 - overview **26-11, 26-12**
 - restrictions **26-16**
 - verifying **26-17**
- subdomains, private VLAN **35-3**
- summer time **4-13**
- supervisor engine
 - accessing the redundant **5-14**
 - configuring **3-8 to 3-13**
 - copying files to standby **5-14**
 - default configuration **3-1**
 - default gateways **3-11**
 - environmental monitoring **10-1**
 - redundancy **9-1**
 - ROM monitor **3-26**
 - startup configuration **3-25**
 - static routes **3-11**
 - synchronizing configurations **5-11**
- Supervisor Engine II-TS
 - insufficient inline power handling **11-11**
- SVI Autostate Exclude
 - understanding **26-3**
- SVI Autostate exclude
 - configuring **26-6**
- switch **43-2**
 - switched packets
 - and ACLs **42-25**
- Switched Port Analyzer
 - See SPAN
- switchport
 - show interfaces **7-19, 7-20, 7-26, 7-27**

- switchport access vlan command **14-6, 14-8**
 - switchport block multicast command **44-2**
 - switchport block unicast command **44-2**
 - switchport mode access command **14-8**
 - switchport mode dynamic command **14-6**
 - switchport mode trunk command **14-6**
 - switch ports
 - See access ports
 - switchport trunk allowed vlan command **14-6**
 - switchport trunk encapsulation command **14-6**
 - switchport trunk encapsulation dot1q command **14-3**
 - switchport trunk encapsulation isl command **14-3**
 - switchport trunk encapsulation negotiate command **14-3**
 - switchport trunk native vlan command **14-6**
 - switchport trunk pruning vlan command **14-7**
 - switch-to-RADIUS server communication
 - configuring **36-27**
 - system
 - reviewing configuration **3-10**
 - settings at startup **3-27**
 - system alarms
 - on Sup 2+ to V-10GE **10-4**
 - overview **10-4**
 - system and network statistics, displaying **29-21**
 - system capabilities TLV **23-2**
 - system clock
 - configuring
 - daylight saving time **4-13**
 - manually **4-11**
 - summer time **4-13**
 - time zones **4-12**
 - displaying the time and date **4-12**
 - overview **4-2**
 - See also NTP
 - system description TLV **23-2**
 - system images
 - loading from Flash memory **3-30**
 - modifying boot field **3-27**
 - specifying **3-30**
 - system message logging
 - default configuration **47-3**
 - defining error message severity levels **47-8**
 - disabling **47-4**
 - displaying the configuration **47-12**
 - enabling **47-4**
 - facility keywords, described **47-12**
 - level keywords, described **47-9**
 - limiting messages **47-9**
 - message format **47-2**
 - overview **47-1**
 - sequence numbers, enabling and disabling **47-7**
 - setting the display destination device **47-5**
 - synchronizing log messages **47-6**
 - timestamps, enabling and disabling **47-7**
 - UNIX syslog servers
 - configuring the daemon **47-10**
 - configuring the logging facility **47-11**
 - facilities supported **47-12**
 - system name
 - manual configuration **4-15**
 - See also DNS
 - system name TLV **23-2**
 - system prompt, default setting **4-14**
-
- T**
- TACACS+
 - accounting, defined **3-16**
 - authentication, defined **3-16**
 - authorization, defined **3-16**
 - configuring
 - accounting **3-21**
 - authentication key **3-18**
 - authorization **3-21**
 - login authentication **3-19**
 - default configuration **3-18**
 - displaying the configuration **3-22**
 - identifying the server **3-18**

- limiting the services to the user **3-21**
- operation of **3-17**
- overview **3-15**
- tracking services accessed by user **3-21**
- TCAM programming and ACLs **42-7**
 - for Sup II-Plus/-thru V-10GE **42-6**
- TDR
 - checking cable connectivity **8-3**
 - enabling and disabling test **8-3**
 - guidelines **8-3**
- Telnet
 - accessing CLI **2-2**
 - disconnecting user sessions **8-7**
 - executing **8-5**
 - monitoring user sessions **8-6**
 - telnet command **8-6**
- Terminal Access Controller Access Control System Plus
 - See TACACS+
- TFTP
 - configuration files in base directory **3-5**
 - configuring for autoconfiguration **3-4**
 - limiting access by servers **49-15**
- threshold monitoring, IP SLAs **50-6**
- time
 - See NTP and system clock
- Time Domain Reflectometer
 - See TDR
- time exceeded messages **8-9**
- timer
 - See login timer
- timestamps in log messages **47-7**
- time zones **4-12**
- TLV
 - host presence detection **36-8**
- TLVs
 - defined **1-4, 23-2**
 - LLDP-MED **23-2**
- Token Ring
 - media not supported (note) **12-5, 12-9**
- Topology change notification processing
 - MLD Snooping
 - Topology change notification processing **22-4**
- TOS
 - description **33-4**
 - trace command **8-9**
- traceroute
 - See IP traceroute
 - See Layer 2 Traceroute
- traceroute mac command **8-11**
- traceroute mac ip command **8-11**
- traffic
 - blocking flooded **44-2**
- traffic control
 - using ACLs (figure) **42-4**
 - using VLAN maps (figure) **42-5**
- traffic marking procedure flowchart **33-19**
- traffic shaping **33-9**
- translational bridge numbers (defaults) **12-5**
- traps
 - configuring MAC address notification **4-22**
 - configuring MAC move notification **4-24**
 - configuring MAC threshold notification **4-26**
 - configuring managers **49-11**
 - defined **49-3**
 - enabling **4-22, 4-24, 4-26, 49-11**
 - notification types **49-11**
 - overview **49-1, 49-4**
- troubleshooting
 - with CiscoWorks **49-4**
 - with system message logging **47-1**
 - with traceroute **8-9**
- troubleshooting high CPU due to ACLs **42-6**
- trunk ports
 - configure port security **38-17**
 - configuring P VLAN **35-18 to 35-19**
- trunks
 - 802.1Q restrictions **14-5**
 - configuring **14-6**

- configuring access VLANs **14-6**
 - configuring allowed VLANs **14-6**
 - default interface configuration **14-6**
 - different VTP domains **14-3**
 - enabling to non-DTP device **14-4**
 - encapsulation **14-3**
 - specifying native VLAN **14-6**
 - understanding **14-3**
 - trustpoint **52-3**
 - TwinGig Convertors
 - port numbering **7-7**
 - selecting X2/TwinGig Convertor mode **7-8**
 - type length value
 - See TLV
 - type of service
 - See TOS
-
- U**
 - UDLD
 - default configuration **24-2**
 - disabling **24-5**
 - enabling **24-4**
 - overview **24-1**
 - UDP jitter, configuring **50-9**
 - UDP jitter operation, IP SLAs **50-9**
 - unauthorized ports with 802.1X **36-4**
 - unicast
 - See IP unicast
 - unicast flood blocking
 - configuring **44-1**
 - unicast MAC address filtering
 - and adding static addresses **4-29**
 - and broadcast MAC addresses **4-28**
 - and CPU packets **4-29**
 - and multicast addresses **4-28**
 - and router MAC addresses **4-28**
 - configuration guidelines **4-28**
 - described **4-28**
 - unicast MAC address filtering, configuring
 - ACLs
 - configuring unicast MAC address filtering **42-12**
 - Unicast RPF (Unicast Reverse Path Forwarding)
 - applying **28-5**
 - BGP attributes
 - caution **28-5**
 - CEF
 - requirement **28-2**
 - tables **28-7**
 - configuring **28-9**
 - (examples) **?? to 28-12**
 - BOOTP **28-8**
 - DHCP **28-8**
 - enterprise network (figure) **28-6**
 - prerequisites **28-9**
 - routing table requirements **28-7**
 - tasks **28-9**
 - verifying **28-10**
 - deploying **28-5**
 - description **1-15, 28-2**
 - disabling **28-11**
 - enterprise network (figure) **28-6**
 - FIB **28-2**
 - implementing **28-4**
 - maintaining **28-11**
 - monitoring **28-11**
 - packets, dropping (figure) **28-4**
 - prerequisites **28-9**
 - restrictions
 - basic **28-8**
 - routing asymmetry **28-7**
 - routing asymmetry (figure) **28-8**
 - routing table requirements **28-7**
 - security policy
 - applying **28-5**
 - attacks, mitigating **28-5**
 - deploying **28-5**
 - tunneling **28-5**

- source addresses, validating **28-3**
 - (figure) **28-3, 28-4**
 - failure **28-3**
 - traffic filtering **28-5**
 - tunneling **28-5**
 - validation
 - failure **28-3, 28-4**
 - packets, dropping **28-3**
 - source addresses **28-3**
 - verifying **28-10**
 - unicast traffic
 - blocking **44-2**
 - unidirectional ethernet
 - enabling **25-2**
 - example of setting **25-2**
 - overview **25-1**
 - UniDirectional Link Detection Protocol
 - See UDLD
 - UNIX syslog servers
 - daemon configuration **47-10**
 - facilities supported **47-12**
 - message logging configuration **47-11**
 - UplinkFast
 - and MST **16-23**
 - enabling **18-16**
 - MST and **16-23**
 - overview **18-11**
 - user EXEC mode **2-5**
 - user sessions
 - disconnecting **8-7**
 - monitoring **8-6**
 - using PACL with access-group mode **42-29**
-
- V**
 - VACLs
 - Layer 4 port operations **42-9**
 - virtual configuration register **54-3**
 - virtual LANs
 - See VLANs
 - Virtual Private Network
 - See VPN
 - Virtual Switch System(VSS), displaying EtherChannel to **19-14**
 - VLAN ACLs
 - See VLAN maps
 - vlan command **12-6**
 - VLAN ID, discovering **4-30**
 - VLAN Management Policy Server
 - See VMPS
 - VLAN maps
 - applying to a VLAN **42-21**
 - configuration example **42-22**
 - configuration guidelines **42-18**
 - configuring **42-17**
 - creating and deleting entries **42-19**
 - defined **42-3**
 - denying access example **42-23**
 - denying packets **42-19**
 - displaying **42-24**
 - order of entries **42-18**
 - permitting packets **42-19**
 - router ACLs and **42-25**
 - using (figure) **42-5**
 - using in your network **42-22**
 - VLAN maps, PACL and Router ACLs **42-31**
 - VLANs
 - allowed on trunk **14-6**
 - configuration guidelines **12-3**
 - configuring **12-5**
 - default configuration **12-4**
 - description **1-7**
 - extended range **12-3**
 - IDs (default) **12-4**
 - interface assignment **12-7**
 - limiting source traffic with RSPAN **46-23**
 - monitoring with RSPAN **46-22**
 - name (default) **12-4**

- normal range **12-3**
- overview **12-1**
- reserved range **12-3**
- See also PVLANS
- VLAN Trunking Protocol
 - See VTP
- VLAN trunks
 - overview **14-3**
- VMPS
 - configuration file example **12-32**
 - configuring dynamic access ports on client **12-25**
 - configuring retry interval **12-27**
 - database configuration file **12-32**
 - dynamic port membership
 - example **12-29**
 - reconfirming **12-26**
 - reconfirming assignments **12-26**
 - reconfirming membership interval **12-26**
 - server overview **12-21**
- VMPS client
 - administering and monitoring **12-28**
 - configure switch
 - configure reconfirmation interval **12-26**
 - dynamic ports **12-25**
 - entering IP VMPS address **12-24**
 - reconfirmation interval **12-27**
 - reconfirm VLAN membership **12-26**
 - default configuration **12-24**
 - dynamic VLAN membership overview **12-23**
 - troubleshooting dynamic port VLAN membership **12-29**
- VMPS server
 - fall-back VLAN **12-23**
 - illegal VMPS client requests **12-23**
 - overview **12-21**
 - security modes
 - multiple **12-22**
 - open **12-22**
 - secure **12-22**
- voice interfaces
 - configuring **34-1**
- Voice over IP
 - configuring **34-1**
- voice ports
 - configuring VVID **34-3**
- voice traffic **11-2, 34-5**
- voice VLAN
 - IP phone data traffic, described **34-2**
 - IP phone voice traffic, described **34-2**
- voice VLAN ports
 - using 802.1X **36-19**
- VPN
 - configuring routing in **31-11**
 - forwarding **31-3**
 - in service provider networks **31-1**
 - routes **31-2**
 - routing and forwarding table
 - See VRF
- VRF
 - defining **31-3**
 - tables **31-1**
- VRF-aware services
 - ARP **31-6, 31-9**
 - configuring **31-6**
 - ftp **31-8**
 - ping **31-7**
 - SNMP **31-7**
 - syslog **31-8**
 - tftp **31-8**
 - traceroute **31-8**
 - uRPF **31-7**
- VTP
 - client, configuring **12-16**
 - configuration guidelines **12-12**
 - default configuration **12-13**
 - disabling **12-16**
 - monitoring **12-19**
 - overview **12-7**

pruning
 configuring **12-15**
See also VTP version 2
server, configuring **12-16**
statistics **12-19**
transparent mode, configuring **12-16**
version 2
 enabling **12-15**
VTP advertisements
 description **12-9**
VTP domains
 description **12-8**
VTP modes **12-8**
VTP pruning
 overview **12-11**
VTP versions 2 and 3
 overview **12-9**
 See also VTP
VVID (voice VLAN ID)
 and 802.1X authentication **36-19**
 configuring **34-3**

W

Wake-on-LAN
 configure with 802.1X **36-52**
web-based authentication
 authentication proxy web pages **37-4**
 description **1-25, 36-13, 37-1**
web-based authentication, interactions with other
features **37-4**