



INDEX

ACLs

applying IPv6 ACLs to a Layer 3 interface **39-22**

Numerics

10/100 autonegotiation feature, forced **6-11**

10-Gigabit Ethernet or Gigabit Ethernet ports

 deploy on WS-X4606-10GE-E and Sup 6-E **6-7**

10-Gigabit Ethernet port

 deploy with Gigabit Ethernet SFP ports **6-6**

1400 W DC Power supply

 special considerations **10-16**

1400 W DC SP Triple Input power supply

 special considerations **10-17**

802.10 SAID (default) **13-4**

802.1Q

 trunks **17-6**

 tunneling

 compatibility with other features **22-5**

 defaults **22-4**

 described **22-2**

 tunnel ports with other features **22-6**

802.1Q VLANs

 encapsulation **15-3**

 trunk restrictions **15-5**

802.1s

 See MST

802.1w

 See MST

802.1X

 See port-based authentication

802.1X authentication

for Critical Authentication **34-12**

for guest VLANs **34-8**

for MAC Authentication Bypass **34-9**

for Wake-on-LAN **34-12**

RADIUS accounting **34-16**

with port security **34-15**

with VLAN assignment **34-7**

with voice VLAN ports **34-18**

802.3ad

 See LACP

A

AAA **36-1**

abbreviating commands **2-5**

access control entries

 See ACEs

access control entries and lists **36-1**

access-group mode, configuring on Layer 2 interface **39-35**

access-group mode, using PACL with **39-35**

access list filtering, SPAN enhancement **43-13**

access lists

 using with WCCP **49-7**

access ports

 and Layer 2 protocol tunneling **22-9**

 configure port security **35-6, 35-21**

 configuring **15-8**

 access VLANs **15-6**

 accounting

 configuring for 802.1X **34-32**

 with TACACS+ **3-16, 3-21**

ACEs

- ACLs **39-2**
 - IP **39-2**
 - Layer 4 operation restrictions **39-15**
 - ACEs and ACLs **36-1**
 - ACLS
 - ACEs **39-2**
 - and SPAN **43-5**
 - and TCAM programming for Sup 6-E **39-15**
 - and TCAM programming for Sup II-Plus thru V-10GE **39-6**
 - applying on routed packets **39-32**
 - applying on switched packets **39-31**
 - chaning the TCAM programming algorithm **39-9**
 - compatibility on the same switch **39-3**
 - configuring with VLAN maps **39-31**
 - CPU impact **39-17**
 - hardware and software support **39-5**
 - IP, matching criteria for port ACLs **39-4**
 - MAC extended **39-19**
 - matching criteria for router ACLs **39-3**
 - port
 - and voice VLAN **39-4**
 - defined **39-3**
 - limitations **39-5**
 - processing **39-17**
 - resize the TCAM regions **39-10**
 - selecting mode of capturing control packets **39-12**
 - TCAM programming algorithm **39-7**
 - troubleshooting high CPU **39-12**
 - types supported **39-3**
 - understanding **39-2**
 - VLAN maps **39-5**
 - ACLs and VLAN maps, examples **39-25**
 - acronyms, list of **A-1**
 - action drivers, marking **32-75**
 - active queue management **32-14**
 - active queue management via DBL, QoS on Sup 6-E **32-85**
 - adding members to a community **12-8**
 - addresses
 - displaying the MAC address table **4-30**
 - dynamic
 - changing the aging time **4-21**
 - defined **4-19**
 - learning **4-20**
 - removing **4-22**
 - MAC, discovering **4-30**
 - See MAC addresses
 - static
 - adding and removing **4-27**
 - defined **4-19**
 - address resolution **4-30**
 - adjacency tables
 - description **27-2**
 - displaying statistics **27-9**
 - advertisements, VTP
 - See VTP advertisements
 - aggregation switch, enabling DHCP snooping **37-9**
 - aging time
 - MAC address table **4-21**
 - applying IPv6 ACLs to a Layer 3 interface **39-22**
 - AQM via DBL, QoS on Sup 6-E **32-85**
 - ARP
 - defined **4-30**
 - table
 - address resolution **4-30**
 - managing **4-30**
 - asymmetrical links, and 802.1Q tunneling **22-4**
 - audience **xxxvii**
 - authentication
 - NTP associations **4-4**
 - See also port-based authentication
 - TACACS+
 - defined **3-16**
 - key **3-18**
 - login **3-19**
 - Authentication, Authorization, and Accounting (AAA) **36-1**

- Authentication Failed VLAN assignment
 - configure with 802.1X **34-40**
 - authentication server
 - defined **34-3**
 - RADIUS server **34-3**
 - authoritative time source, described **4-2**
 - authorization
 - with TACACS+ **3-16, 3-21**
 - authorized and unauthorized ports **34-4**
 - authorized ports with 802.1X **34-4**
 - autoconfiguration **3-2**
 - automatic discovery
 - considerations **12-7**
 - automatic QoS
 - See QoS
 - Auto-MDIX on a port
 - configuring **6-20**
 - displaying the configuration **6-21**
 - overview **6-19**
 - autonegotiation feature
 - forced 10/100Mbps **6-11**
 - Auto-QoS
 - configuring **32-17**
 - auto-sync command **8-8**
-
- B**
 - Baby Giants
 - interacting with **6-19**
 - BackboneFast
 - adding a switch (figure) **18-3**
 - and MST **17-23**
 - configuring **18-16**
 - link failure (figure) **18-14, 18-15**
 - not supported MST **17-23**
 - understanding **18-13**
 - See also STP
 - banners
 - configuring
 - login **4-19**
 - message-of-the-day login **4-18**
 - default configuration **4-18**
 - when displayed **4-17**
 - b command **51-3**
 - b flash command **51-3**
 - BGP **1-7**
 - routing session with multi-VRF CE **31-7**
 - blocking packets **41-1**
 - blocking state (STP)
 - RSTP comparisons (table) **17-24**
 - boot bootldr command **3-31**
 - boot command **3-28**
 - boot commands **51-3**
 - boot fields
 - See configuration register boot fields
 - bootstrap program
 - See ROM monitor
 - boot system command **3-26, 3-31**
 - boot system flash command **3-28**
 - Border Gateway Protocol
 - See BGP
 - boundary ports
 - description **17-27**
 - BPDU Guard
 - and MST **17-23**
 - configuring **18-16**
 - overview **18-8**
 - BPDUs
 - and media speed **17-2**
 - pseudobridges and **17-25**
 - what they contain **17-3**
 - bridge ID
 - See STP bridge ID
 - bridge priority (STP) **17-16**
 - bridge protocol data units
 - See BPDUs
 - Broadcast Storm Control
 - disabling **42-6**

enabling [42-3](#)

BSR

 configuration example [29-21](#)

burst rate [32-56](#)

burst size [32-31](#)

C

cache engine clusters [xxxix, 49-1](#)

cache engines [xxxix, 49-1](#)

cache farms

 See cache engine clusters

candidates

 automatic discovery [12-7](#)

candidate switch, cluster

 defined [12-12](#)

 requirements [12-12](#)

Capturing control packets

 selecting mode [39-12](#)

cautions

 Unicast RPF

 BGP optional attributes [28-4](#)

cautions for passwords

 encrypting [3-22](#)

CDP

 and trusted boundary [32-26](#)

 automatic discovery in communities [12-7](#)

 configuration [23-2](#)

 displaying configuration [23-3](#)

 enabling on interfaces [23-3](#)

 Layer 2 protocol tunneling [22-7](#)

 maintaining [23-3](#)

 monitoring [23-3](#)

 overview [1-2, 23-1](#)

cdp enable command [23-3](#)

CEF

 adjacency tables [27-2](#)

 and NSF with SSO [9-5](#)

 configuring load balancing [27-7](#)

displaying statistics [27-8](#)

enabling [27-6](#)

hardware switching [27-4](#)

load balancing [27-6](#)

overview [27-1](#)

software switching [27-4](#)

CGMP

 overview [20-1](#)

channel-group group command [19-7, 19-10](#)

Cisco 7600 series Internet router

 enabling SNMP [50-16](#)

Cisco Discovery Protocol

 See CDP

Cisco Express Forwarding

 See CEF

Cisco Group Management Protocol

 See CGMP

Cisco IOS NSF-aware

 support [9-2](#)

Cisco IOS NSF-capable support [9-2](#)

Cisco IP Phones

 configuring [33-2](#)

 sound quality [33-1](#)

CiscoWorks 2000 [45-4](#)

CIST

 description [17-22](#)

class-map command [32-33](#)

class of service

 See CoS

clear cdp counters command [23-4](#)

clear cdp table command [23-3](#)

clear counters command [6-23](#)

clearing

 IP multicast table entries [29-20](#)

clear ip eigrp neighbors command [26-18](#)

clear ip flow stats command [46-9](#)

CLI

 accessing [2-1](#)

 backing out one level [2-5](#)

getting commands **2-5**
 history substitution **2-3**
 managing clusters **12-12**
 modes **2-5**
 monitoring environments **43-1**
 ROM monitor **2-7**
 software basics **2-4**

clients
 in 802.1X authentication **34-2**

clock
 See system clock

clustering switches
 command switch characteristics **12-11, 12-12**
 and VTY **12-11**
 convert to a community **12-9**
 managing
 through CLI **12-12**
 overview **12-10**
 planning considerations
 CLI **12-12**
 passwords **12-8**

command-line processing **2-3**

command modes **2-5**

commands
b 51-3
b flash 51-3
boot 51-3
confreg 51-3
dev 51-3
dir device 51-3
frame 51-5
i 51-3
listing 2-5
meminfo 51-5
reset 51-3
ROM monitor 51-2 to 51-3
ROM monitor debugging 51-5
SNMP 50-16
sysret 51-5

command switch, cluster
 requirements **12-11**
 common and internal spanning tree
 See CIST
 common spanning tree
 See CST
 community of switches
 access modes in Network Assistant **12-8**
 adding devices **12-8**
 candidate characterisits **12-6**
 communication protocols **12-8**
 community name **12-7**
 configuration information **12-8**
 converting from a cluster **12-9**
 host name **12-7**
 passwords **12-8**
 community ports **40-4**
 community strings
 configuring **45-7**
 overview **45-4**
 community VLANs **40-3, 40-4**
 and SPAN features **40-12**
 configure as a PVLAN **40-13**
 compiling MIBs **50-16**
 config-register command **3-29**
 config terminal command **3-9**
 configurable leave timer,IGMP **20-3**
 configuration examples
 SNMP **45-16**
 configuration files
 limiting TFTP server access **45-15**
 obtaining with DHCP **3-6**
 saving **3-10**
 system contact and location information **45-15**
 configuration guidelines
 SNMP **45-6**
 configuration register
 boot fields
 listing value **3-29**

- modifying **3-28**
 - changing from ROM monitor **51-3**
 - changing settings **3-28 to 3-29**
 - configuring **3-26**
 - settings at startup **3-27**
 - configure terminal command **3-28, 6-2**
 - configuring access-group mode on Layer 2 interface **39-35**
 - configuring flow control **6-14**
 - configuring interface link and trunk status events **6-24**
 - configuring named IPv6 ACLs **39-20**
 - configuring named MAC extended ACLs **39-19**
 - configuring unicast MAC address filtering **39-19**
 - configuring VLAN maps **39-23**
 - confreg command **51-3**
 - console configuration mode **2-5**
 - console download **51-4 to 51-5**
 - console port
 - disconnecting user sessions **7-6**
 - monitoring user sessions **7-6**
 - control plane policing
 - See CoPP
 - CoPP
 - applying QoS service policy to control plane **36-3**
 - configuring
 - ACLs to match traffic **36-3**
 - enabling MLS QoS **36-3**
 - packet classification criteria **36-3**
 - service-policy map **36-3**
 - control plane configuration mode
 - entering **36-3**
 - displaying
 - dynamic information **36-7**
 - number of conforming bytes and packets **36-7**
 - rate information **36-7**
 - entering control plane configuration mode **36-3**
 - monitoring statistics **36-7**
 - overview **36-1**
 - copy running-config startup-config command **3-10**
 - copy system:running-config nvram:startup-config command **3-31**
 - CoS
 - definition **32-3**
 - figure **32-2**
 - overriding on Cisco IP Phones **33-4**
 - priority **33-4**
 - CoS Mutation
 - configuring **32-40**
 - CoS-to-DSCP maps **32-57**
 - CoS value, configuring for an interface **32-53**
 - counters
 - clearing MFIB **29-21**
 - clearing on interfaces **6-23**
 - CPU, impact of ACL processing **39-17**
 - CPU port sniffing **43-10**
 - Critical Authentication
 - configure with 802.1X **34-36, 34-37**
 - CST
 - description **17-25**
 - IST and **17-22**
 - MST and **17-22**
 - customer edge devices **31-2**
-
- ## D
- database agent
 - configuration examples **37-12**
 - enabling the DHCP Snooping **37-12**
 - daylight saving time **4-13**
 - debug commands, ROM monitor **51-5**
 - default configuration
 - 802.1X **34-22**
 - auto-QoS **32-17**
 - banners **4-18**
 - DNS **4-16**
 - IGMP filtering **20-18**
 - IGMP snooping **21-5, 21-6**
 - Layer 2 protocol tunneling **22-9**

- MAC address table [4-21](#)
- multi-VRF CE [31-4](#)
- NTP [4-4](#)
- private VLANs [40-11](#)
- resetting the interface [6-26](#)
- RMON [47-3](#)
- SNMP [45-6](#)
- SPAN and RSPAN [43-6](#)
- system message logging [44-3](#)
- system name and prompt [4-15](#)
- TACACS+ [3-18](#)
- default gateway
 - configuring [3-11](#)
 - verifying configuration [3-11](#)
- default settings, erase command [3-31](#)
- denial-of-service attacks
 - IP address spoofing, mitigating [28-5](#)
 - Unicast RPF, deploying [28-5](#)
- denying access to a server on another VLAN [39-29](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports [6-6](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports on WS-X4606-10GE-E and Sup 6-E [6-7](#)
- description command [6-13](#)
- detecting unidirectional links [24-1](#)
- dev command [51-3](#)
- DHCP-based autoconfiguration
 - client request message exchange [3-3](#)
 - configuring
 - client side [3-2](#)
 - DNS [3-5](#)
 - relay device [3-5](#)
 - server-side [3-3](#)
 - TFTP server [3-4](#)
 - example [3-7](#)
 - lease options
 - for IP address information [3-3](#)
 - for receiving the configuration file [3-4](#)
 - overview [3-2](#)
- relationship to BOOTP [3-2](#)
- DHCP option 82
 - overview [37-3](#)
- DHCP Snooping
 - enabling, and Option 82 [37-9](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [37-10](#)
 - configuring [37-6](#)
 - default configuration [37-7](#)
 - displaying binding tables [37-16](#)
 - displaying configuration [37-16](#)
 - displaying information [37-15](#)
 - enabling [37-7](#)
 - enabling on private VLAN [37-11](#)
 - enabling on the aggregation switch [37-9](#)
 - enabling the database agent [37-12](#)
 - message exchange process [37-4](#)
 - monitoring [37-20](#)
 - option 82 data insertion [37-3](#)
 - overview [37-1](#)
 - Snooping database agent [37-2](#)
- DHCP Snooping Database Agent
 - adding to the database (example) [37-15](#)
 - enabling (example) [37-12](#)
 - overview [37-2](#)
 - reading from a TFTP file (example) [37-14](#)
- Diagnostics
 - online [48-1](#)
 - troubleshooting [48-2](#)
 - Power-On-Self-Test
 - causes of failure [48-14](#)
 - how it works [48-3](#)
 - overview [48-3](#)
 - Power-On-Self-Test for Supervisor Engine V-10GE [48-8](#)
- Differentiated Services Code Point values
 - See DSCP values
- DiffServ architecture, QoS [32-2](#)
- Digital optical monitoring transceiver support [6-10](#)

- dir device command **51-3**
- disabled state
 - RSTP comparisons (table) **17-24**
- disabling
 - broadcast storm control **42-6**
 - disabling multicast storm control **42-7**
 - disconnect command **7-6**
 - discovery, clusters
 - See automatic discovery
 - displaying storm control **42-7**
- DNS
 - and DHCP-based autoconfiguration **3-5**
 - default configuration **4-16**
 - displaying the configuration **4-17**
 - overview **4-15**
 - setting up **4-16**
- documentation
 - organization **xxxvii**
 - related **xl**
- domain names
 - DNS **4-15**
- Domain Name System
 - See DNS
- double-tagged packets
 - 802.1Q tunneling **22-2**
 - Layer 2 protocol tunneling **22-9**
- downloading MIBs **50-14, 50-15**
- drop threshold for Layer 2 protocol packets **22-10**
- DSCP maps **32-57**
- DSCP-to-CoS maps
 - configuring **32-59**
- DSCP values
 - configuring maps **32-57**
 - definition **32-4**
 - IP precedence **32-2**
 - mapping markdown **32-24**
 - mapping to transmit queues **32-55**
- DSCP values, configuring port value **32-54**
- DTP
 - VLAN trunks and **15-3**
 - duplex command **6-12**
 - duplex mode
 - configuring interface **6-11**
 - dynamic ARP inspection
 - ARP cache poisoning **38-2**
 - configuring
 - ACLs for non-DHCP environments **38-11**
 - in DHCP environments **38-5**
 - log buffer **38-14**
 - rate limit for incoming ARP packets **38-16**
 - denial-of-service attacks, preventing **38-16**
 - interface trust state, security coverage **38-3**
 - log buffer
 - configuring **38-14**
 - logging of dropped packets **38-4**
 - overview **38-1**
 - port channels, their behavior **38-5**
 - priority of static bindings **38-4**
 - purpose of **38-2**
 - rate limiting of ARP packets **38-4**
 - configuring **38-16**
 - validation checks, performing **38-19**
 - dynamic buffer limiting
 - globally **32-27**
 - on specific CoS values **32-29**
 - on specific IP DSCP values **32-28**
 - Dynamic Host Configuration Protocol snooping
 - See DHCP snooping
 - dynamic port VLAN membership
 - example **13-25**
 - limit on hosts **13-24**
 - reconfirming **13-22**
 - troubleshooting **13-24**
 - Dynamic Trunking Protocol
 - See DTP

E

EAP frames

- changing retransmission time **34-45**
- exchanging (figure) **34-4, 34-6, 34-11**
- request/identity **34-3**
- response/identity **34-3**
- setting retransmission number **34-46**

EAPOL frames

- 802.1X authentication and **34-3**
- OTP authentication, example (figure) **34-4, 34-11**
- start **34-3**

edge ports

- description **17-27**

EGP

- overview **1-7**

EIGRP

- configuration examples **26-19**
- monitoring and maintaining **26-18**

EIGRP (Enhanced IGRP)

- stub routing
 - benefits **26-17**
 - configuration tasks **26-17**
 - configuring **26-13**
 - overview **26-13**
 - restrictions **26-17**
 - verifying **26-18**

EIGRP (enhanced IGRP)

- overview **1-8**

eigrp stub command **26-18**

EIGRP stub routing, configuring **26-12**

Embedded CiscoView

- displaying information **4-33**
- installing and configuring **4-31**
- overview **4-31**

emergency alarms on Sup Engine 6-E systems **10-3**

enable command **3-9, 3-28**

enable mode **2-5**

enabling or disabling QOS on an interface **32-50**

enabling SNMP **50-16**

encapsulation types **15-3**

Enhanced Interior Gateway Routing Protocol

 See EIGRP

environmental conditions

 Sup Engine 6-E **10-2**

 Sup Engines II-Plus to V-10GE **10-2**

environmental monitoring

 using CLI commands **10-1**

EtherChannel

 channel-group group command **19-7, 19-10**

 configuration guidelines **19-5**

 configuring **19-6 to 19-14**

 configuring Layer 2 **19-9**

 configuring Layer 3 **19-6**

 interface port-channel command **19-7**

 lacp system-priority

 command example **19-12**

 modes **19-3**

 overview **19-1**

 PAgP

 Understanding **19-3**

 physical interface configuration **19-7**

 port-channel interfaces **19-2**

 port-channel load-balance command **19-13**

 removing **19-14**

 removing interfaces **19-14**

EtherChannel guard

 disabling **18-6**

 enabling **18-6**

 overview **18-6**

explicit host tracking

 enabling **20-10**

extended range VLANs

 See VLANs

Extensible Authentication Protocol over LAN **34-1**

Exterior Gateway Protocol

 See EGP

F

FastDrop
 clearing entries **29-20**
 displaying entries **29-19**
 overview **29-10**

FIB
 description **27-2**
 See also MFIB

filtering
 in a VLAN **39-23**
 non-IP traffic **39-19**

flags **29-11**

Flash memory
 configuring router to boot from **3-30**
 loading system images from **3-30**
 security precautions **3-30**
 flooded traffic, blocking **41-2**
 flowchart, traffic marking procedure **32-75**
 flow control, configuring **6-14**
 forward-delay time (STP)
 configuring **17-18**
 forwarding information base
 See FIB

frame command **51-5**

G

gateway
 See default gateway
 get-bulk-request operation **45-3**
 get-next-request operation **45-3, 45-4**
 get-request operation **45-3, 45-4**
 get-response operation **45-3**
 Gigabit Ethernet SFP ports
 deploy with 10-Gigabit Ethernet **6-6**
 global configuration mode **2-5**
 Guest-VLANs
 configure with 802.1X **34-32, 34-41**

H

hardware and software ACL support **39-5**
 hardware switching **27-5**
 hello time (STP)
 configuring **17-17**
 hierarchical policers, configuring **32-46**
 hierarchical policies, QoS on Sup 6-E **32-87**
 high CPU due to ACLs, troubleshooting **39-12**
 history
 CLI **2-3**
 history table, level and number of syslog messages **44-9**
 hop counts
 configuring MST bridges **17-28**
 host
 configuring host statically **20-10**
 limit on dynamic port **13-24**
 host ports
 kinds of **40-4**
 Hot Standby Routing Protocol
 See HSRP
 HSRP
 description **1-7**
 http
[//www.cisco.com/en/US/docs/ios/fundamentals/com
mand reference/cf_book.html](http://www.cisco.com/en/US/docs/ios/fundamentals/command_reference/cf_book.html) **44-1, 47-1**
 hw-module module num power command **10-20**

I

ICMP
 enabling **7-11**
 ping **7-7**
 running IP traceroute **7-8**
 time exceeded messages **7-8**
 i command **51-3**
 IDS
 using with SPAN and RSPAN **43-2**
 IEEE 802.1s

See MST

IEEE 802.1w

 See MST

IEEE 802.3ad

 See LACP

IGMP

- configurable leave timer
- enabling **20-8**
- configurable-leave timer **20-3**
- description **29-3**
- enabling **29-13**
- explicit host tracking **20-4, 20-10**
- immediate-leave processing **20-3**
- leave processing, enabling **21-8**
- overview **20-1**
- report suppression
 - disabling **21-11**

IGMP filtering

- configuring **20-18**
- default configuration **20-18**
- described **20-18**
- monitoring **20-21**

IGMP groups

- setting the maximum number **20-20**

IGMP Immediate Leave

- configuration guidelines **20-8**

IGMP profile

- applying **20-19**
- configuration mode **20-18**
- configuring **20-19**

IGMP snooping

- configuration guidelines **20-4**
- default configuration **21-5, 21-6**
- enabling **20-5, 20-6**
- enabling and disabling **21-6**
- IP multicast and **29-4**
- monitoring **20-13, 21-11**
- overview **20-1**

IGRP

 description **1-8**

 Immediate Leave, IGMP

- enabling **21-8**

 immediate-leave processing

- enabling **20-8**

 IGMP

- See fast-leave processing

 ingress packets, SPAN enhancement **43-12**

 inline power

- configuring on Cisco IP phones **33-5**

 insufficient inline power handling for Supervisor Engine II-TS **10-18**

 Intelligent Power Management **11-4**

 interacting with Baby Giants **6-19**

 interface command **3-9, 6-1**

 interface link and trunk status events

- configuring **6-24**

 interface port-channel command **19-7**

 interface range command **6-4**

 interface range macro command **6-5**

 interfaces

- adding descriptive name **6-13**
- clearing counters **6-23**
- configuring **6-2**
- configuring ranges **6-4**
- displaying information about **6-23**
- Layer 2 modes **15-4**
- maintaining **6-22**
- monitoring **6-22**
- naming **6-13**
- numbers **6-2**
- overview **6-1**
- restarting **6-24**
- See also Layer 2 interfaces

 Interior Gateway Routing Protocol

- See IGRP

 Internet Control Message Protocol

- See ICMP

 Internet Group Management Protocol

- See IGMP
- Inter-Switch Link encapsulation
 - See ISL encapsulation
- Intrusion Detection System
 - See IDS
- IP
 - configuring default gateway **3-11**
 - configuring static routes **3-11**
 - displaying statistics **27-8**
 - flow switching cache **46-9**
- IP addresses
 - cluster candidate or member **12-12**
 - cluster command switch **12-11**
 - discovering **4-30**
- ip cef command **27-6**
- IP Enhanced IGRP
 - interfaces, displaying **26-18**
- ip flow-aggregation cache destination-prefix command **46-11**
- ip flow-aggregation cache prefix command **46-11**
- ip flow-aggregation cache source-prefix command **46-12**
- ip flow-export command **46-9**
- ip icmp rate-limit unreachable command **7-12**
- ip igmp profile command **20-18**
- ip igmp snooping tcn flood command **20-12**
- ip igmp snooping tcn flood query count command **20-12**
- ip igmp snooping tcn query solicit command **20-13**
- IP information
 - assigned
 - through DHCP-based autoconfiguration **3-2**
- ip load-sharing per-destination command **27-7**
- ip local policy route-map command **30-5**
- ip mask-reply command **7-13**
- IP MTU sizes, configuring **26-8**
- IP MTU sizes, configuring **26-8**
- IP multicast
 - clearing table entries **29-20**
 - configuring **29-12**
 - default configuration **29-13**
 - displaying PIM information **29-16**
 - displaying the routing table information **29-16**
 - enabling **29-13**
 - enabling dense-mode PIM **29-14**
 - enabling sparse-mode **29-14**
 - features not supported **29-12**
 - hardware forwarding **29-8**
 - IGMP snooping and **20-4, 29-4**
 - monitoring **29-15**
 - overview **29-1**
 - routing protocols **29-2**
 - software forwarding **29-8**
 - See also Auto-RP; IGMP; PIM; RP; RPF
- ip multicast-routing command **29-13**
- IP phones
 - automatic classification and queueing **32-17**
 - configuring voice ports **33-3**
 - See Cisco IP Phones **33-1**
 - trusted boundary for QoS **32-26**
- ip pim command **29-14**
- ip pim dense-mode command **29-14**
- ip pim sparse-dense-mode command **29-15**
- ip policy route-map command **30-4**
- IP Port Security for Static Hosts
 - on a Layer 2 access port **37-21**
 - on a PVLAN host port **37-24**
 - overview **37-21**
- ip redirects command **7-12**
- ip route-cache flow command **46-7**
- IP routing tables
 - deleting entries **29-20**
- IP Source Guard
 - configuring **37-17**
 - configuring on private VLANs **37-19**
 - displaying **37-19, 37-20**
 - overview **37-16**
- IP statistics
 - displaying **27-8**
- IP traceroute

- executing **7-8**
- overview **7-8**
- IP unicast
 - displaying statistics **27-8**
- IP Unnumbered support
 - configuring on a range of Ethernet VLANs **14-5**
 - configuring on LAN and VLAN interfaces **14-4**
 - configuring with connected host polling **14-6**
 - DHCP Option 82 **14-2**
 - displaying settings **14-7**
 - format of agent remote ID suboptions **14-3**
 - troubleshooting **14-8**
 - with connected host polling **14-3**
 - with DHCP server and Relay agent **14-2**
- ip unreachable command **7-11**
- IPX
 - redistribution of route information with EIGRP **1-8**
- ISL
 - encapsulation **15-3**
 - trunking with 802.1Q tunneling **22-4**
- isolated port **40-4**
- isolated VLANs **40-3, 40-4**
- ISSU
 - compatibility matrix **5-13**
 - compatibility verification using Cisco Feature Navigator **5-14**
 - NSF overview **5-4**
 - perform the process
 - aborting a software upgrade **5-26**
 - configuring the rollback timer as a safeguard **5-27**
 - displaying a compatibility matrix **5-29**
 - loading the new software on the new standby **5-24**
 - stopping the rollback timer **5-23**
 - switching to the standby **5-20**
 - verify the ISSU state **5-16**
 - verify the redundancy mode **5-15**
 - verify the software installation **5-14**
 - upload the new software on standby **5-17**
- prerequisites **5-2**
- process overview **5-7**
- restrictions **5-2**
- SNMP support **5-13**
- SSO overview **5-4**
- versioning capability in software to support **5-12**
- IST
 - and MST regions **17-22**
 - description **17-22**
 - master **17-27**

- J**
- jumbo frames
 - and ethernet ports **6-18**
 - configuring MTU sizes for **6-18**
 - ports and linecards that support **6-16**
 - understanding MTUs **6-17**
 - understanding support **6-17**
 - VLAN interfaces **6-18**

- K**
- keyboard shortcuts **2-3**

- L**
- l2protocol-tunnel command **22-11**
- labels, definition **32-3**
- LACP
 - system ID **19-4**
- Layer 2 access ports **15-8**
- Layer 2 Control Packet QoS
 - feature interaction **32-64**
 - overview **32-60**
 - usage guidelines **32-64**
- Layer 2 frames
 - classification with CoS **32-2**

- Layer 2 interface, configuring access-mode mode on **39-35**
- Layer 2 interfaces
- assigning VLANs **13-7**
 - configuring **15-5**
 - configuring as PVLAN host ports **40-16**
 - configuring as PVLAN promiscuous ports **40-15**
 - configuring as PVLAN trunk ports **40-17**
 - defaults **15-5**
 - disabling configuration **15-9**
 - modes **15-4**
 - show interfaces command **15-7**
- Layer 2 interface type
- resetting **40-22**
 - setting **40-22**
- Layer 2 protocol tunneling
- default configuration **22-9**
 - guidelines **22-10**
- Layer 2 switching
- overview **15-1**
- Layer 2 Traceroute
- and ARP **7-10**
 - and CDP **7-9**
 - host-to-host paths **7-9**
 - IP addresses and subnets **7-10**
 - MAC addresses and VLANs **7-10**
 - multicast traffic **7-10**
 - multiple devices on a port **7-10**
 - unicast traffic **1-20, 7-9**
 - usage guidelines **7-9**
- Layer 2 trunks
- configuring **15-6**
 - overview **15-3**
- Layer 3 interface, applying IPv6 ACLs **39-22**
- Layer 3 interface counters,configuring **26-10**
- Layer 3 interface counters,understanding **26-4**
- Layer 3 interfaces
- configuration guidelines **26-5**
 - overview **26-1**
- logical **26-2**
 - physical **26-2**
 - VLANs as interfaces **26-7**
- Layer 3 packets
- classification methods **32-2**
- Layer 4 port operations
- configuration guidelines **39-16**
 - restrictions **39-15**
 - limitations on using a TwinGig Convertor **6-8**
 - link and trunk status events
 - configuring interface **6-24** - listening state (STP)
 - RSTP comparisons (table) **17-24** - load balancing
 - configuring for CEF **27-7**
 - configuring for EtherChannel **19-13**
 - overview **19-4, 27-6**
 - per-destination **27-7**
- Logical Layer 3 interfaces
- configuring **26-5**
- login authentication
- with TACACS+ **3-19**
- login banners **4-17**
- login timer
- changing **7-5**
- logoutwarning command **7-6**
- loop guard
- and MST **17-23**
 - configuring **18-4**
 - overview **18-3**
-
- M**
- MAC addresses
- aging time **4-21**
 - allocating **17-5**
 - and VLAN association **4-20**
 - building tables **4-20, 15-2**
 - convert dynamic to sticky secure **35-5**

- default configuration [4-21](#)
- discovering [4-30](#)
- displaying [4-30, 7-3](#)
- displaying in DHCP snooping binding table [37-16](#)
- dynamic
 - learning [4-20](#)
 - removing [4-22](#)
- in ACLs [39-19](#)
- static
 - adding [4-28](#)
 - allowing [4-29](#)
 - characteristics of [4-27](#)
 - dropping [4-29](#)
 - removing [4-28](#)
- sticky [35-4](#)
- sticky secure, adding [35-5](#)
- MAC Authentication Bypass
 - configure with 802.1X [34-35](#)
- MAC extended access lists [39-19](#)
- macros
 - See Smartports macros
- main-cpu command [8-8](#)
- management options
 - SNMP [45-1](#)
- mapping
 - DSCP markdown values [32-24](#)
 - DSCP values to transmit queues [32-55](#)
- mapping tables
 - configuring DSCP [32-57](#)
 - described [32-14](#)
- marking
 - hardware capabilities [32-77](#)
- marking action drivers [32-75](#)
- marking network traffic [32-72](#)
- marking support, multi-attribute [32-76](#)
- mask destination command [46-11](#)
- mask source command [46-11, 46-12](#)
- Match CoS for non-IPV4 traffic
 - configuring [32-35](#)
- match ip address command [30-3](#)
- maximum aging time (STP)
 - configuring [17-18](#)
- MDA
 - configuration guidelines [34-19 to 34-20](#)
 - described [34-19](#)
- members
 - automatic discovery [12-7](#)
- member switch
 - managing [12-12](#)
- member switch, cluster
 - defined [12-11](#)
 - requirements [12-12](#)
- meminfo command [51-5](#)
- messages, to users through banners [4-17](#)
- metro tags [22-2](#)
- MFIB
 - CEF [29-5](#)
 - displaying [29-18](#)
 - overview [29-11](#)
- MIBs
 - compiling [50-16](#)
 - downloading [50-14, 50-15](#)
 - overview [45-1](#)
 - related information [50-15](#)
 - SNMP interaction with [45-4](#)
- MLD Done messages and Immediate-leave [21-4](#)
- MLD messages [21-2](#)
- MLD queries [21-3](#)
- MLD reports [21-4](#)
- MLD Snooping
 - MLD Done messages and Immediate-leave [21-4](#)
 - MLD messages [21-2](#)
 - MLD queries [21-3](#)
 - MLD reports [21-4](#)
 - Multicast client aging robustness [21-3](#)
 - Multicast router discovery [21-3](#)
 - overview [21-1](#)
- Mode of capturing control packets, selecting [39-12](#)

- modules
 - checking status **7-1**
 - powering down **10-20**
- monitoring
 - 802.1Q tunneling **22-12**
 - ACL information **39-39**
 - IGMP
 - snooping **21-11**
 - IGMP filters **20-21**
 - IGMP snooping **20-13**
 - Layer 2 protocol tunneling **22-12**
 - multicast router interfaces **21-11**
 - multi-VRF CE **31-12**
 - traffic flowing among switches **47-1**
 - tunneling **22-12**
 - VLAN filters **39-30**
 - VLAN maps **39-30**
 - M-record **17-23**
- MST
 - and multiple spanning trees **1-3, 17-22**
 - boundary ports **17-27**
 - BPDUs **17-23**
 - configuration parameters **17-26**
 - configuring **17-29**
 - displaying configurations **17-33**
 - edge ports **17-27**
 - enabling **17-29**
 - hop count **17-28**
 - instances
 - configuring parameters **17-32**
 - description **17-22**
 - number supported **17-26**
 - interoperability with PVST+ **17-23**
 - link type **17-28**
 - master **17-27**
 - message age **17-28**
 - regions **17-26**
 - restrictions **17-29**
 - to-SST interoperability **17-24**
- MSTP
 - EtherChannel guard
 - enabling **18-6**
 - M-record **17-23**
 - M-tree **17-23**
 - M-tree **17-23**
 - MTUS
 - understanding **6-17**
 - MTU size
 - configuring **6-18, 6-25**
 - default **13-4**
 - multicast
 - See IP multicast
 - Multicast client aging robustness **21-3**
 - multicast groups
 - static joins **21-7**
 - multicast packets
 - blocking **41-2**
 - Multicast router discovery **21-3**
 - multicast router interfaces, monitoring **21-11**
 - multicast router ports, adding **21-8**
 - multicast routers
 - displaying routing tables **29-16**
 - flood suppression **20-10**
 - Multicast Storm Control
 - enabling **42-4**
 - disabling **42-7**
 - suppression on Sup 6-E **42-4**
 - suppression on WS-X4014 **42-5**
 - suppression on WS-X4016 **42-5**
 - WS-X4515, WS-X4014, and WS-X4013+ Sup Engs **42-5**
 - WS-X4516 Sup Eng **42-5**
 - multidomain authentication
 - See MDA
 - Multiple Domain Authentication
 - configuring **34-28**
 - overview of Host Mode **34-6**

multiple forwarding paths **1-3, 17-22**

Multiple Spanning Tree

 See MST

multiple VPN routing/forwarding

 See multi-VRF CE

multi-VRF CE

 components **31-4**

 configuration example **31-8**

 default configuration **31-4**

 defined **31-1**

 displaying **31-12**

 monitoring **31-12**

 network components **31-4**

 packet-forwarding process **31-4**

N

named aggregate policers, creating **32-31**

named IPv6 ACLs, configuring

 ACLs

 configuring named IPv6 ACLs **39-20**

named MAC extended ACLs

 ACLs

 configuring named MAC extended **39-19**

native VLAN

 and 802.1Q tunneling **22-4**

 specifying **15-6**

NetFlow

 aggregation

 minimum mask, default value **46-11**

 destination-prefix aggregation

 configuration (example) **46-16**

 minimum mask, configuring **46-11**

IP

 flow switching cache **46-9**

prefix aggregation

 configuration (example) **46-14**

 minimum mask, configuring **46-11**

source-prefix aggregation

minimum mask, configuring **46-11**

switching

 checking for required hardware **46-6**

 configuration (example) **46-13**

 configuring switched IP flows **46-8**

 enabling Collection **46-7**

 exporting cache entries **46-9**

 statistics **46-9**

NetFlow statistics

 caveats on supervisor **46-6**

 checking for required hardware **46-6**

 configuring collection **46-6**

 enabling Collection **46-7**

 exporting cache entries **46-9**

 overview of collection **46-1**

 switched/bridged IP flows **46-8**

Network Assistant

 and VTY **12-11**

configure

 enable communication with switch **12-13, 12-17**

default configuration **12-2**

overview of CLI commands **12-2**

network fault tolerance **1-3, 17-22**

network management

 configuring **23-1**

 RMON **47-1**

 SNMP **45-1**

Network Time Protocol

 See NTP

network traffic, marking **32-72**

New Software Features in Release 7.7

 TDR **7-3**

Next Hop Resolution Protocol

 See NHRP

NFFC/NFFC II

 IGMP snooping and **20-4**

NHRP

 support **1-8**

non-IP traffic filtering **39-19**

- non-RPF traffic
 description **29-9**
 in redundant configurations (figure) **29-10**
- Nonstop Forwarding
 See NSF
- nonvolatile random-access memory
 See NVRAM
- normal-range VLANs
 See VLANs
- NSF
 defined **9-1**
 guidelines and restrictions **9-9**
 operation **9-4**
- NSF-aware
 supervisor engines **9-3**
 support **9-2**
- NSF-capable
 supervisor engines **9-3**
 support **9-2**
- NSF with SSO supervisor engine redundancy
 and CEF **9-5**
 overview **9-3**
 SSO operation **9-4**
- NTP
 associations
 authenticating **4-4**
 defined **4-2**
 enabling broadcast messages **4-7**
 peer **4-6**
 server **4-6**
 default configuration **4-4**
 displaying the configuration **4-11**
 overview **4-2**
 restricting access
 creating an access group **4-9**
 disabling NTP services per interface **4-10**
 source IP address, configuring **4-10**
 stratum **4-2**
 synchronizing devices **4-6**
- time
 services **4-2**
 synchronizing **4-2**
- NVRAM
 saving settings **3-10**
-
- O**
- OIR
 overview **6-22**
- Online Diagnostics **48-1**
- online insertion and removal
 See OIR
- Open Shortest Path First
 See OSPF
- operating system images
 See system images
- Option 82
 enabling DHCP Snooping **37-9**
- OSPF
 area concept **1-9**
 description **1-9**
-
- P**
- packets
 modifying **32-16**
 software processed
 and QoS **32-16**
- packet type filtering
 overview **43-15**
 SPAN enhancement **43-15**
- PACL, using with access-group mode **39-35**
- PACL with VLAN maps and router ACLs **39-37**
- PAgP
 understanding **19-3**
- passwords
 configuring enable password **3-13**

- configuring enable secret password **3-13**
- encrypting **3-22**
- in clusters **12-8**
- recovering lost enable password **3-25**
- setting line password **3-14**
- PBR (policy-based routing)
 - configuration (example) **30-5**
 - enabling **30-3**
 - features **30-2**
 - overview **30-1**
 - route maps **30-2**
 - when to use **30-2**
- per-port and VLAN Access Control List **37-16**
- per-port per-VLAN QoS
 - enabling **32-48**
 - overview **32-16**
- Per-VLAN Rapid Spanning Tree **17-6**
 - enabling **17-20**
 - overview **17-6**
- PE to CE routing, configuring **31-7**
- Physical Layer 3 interfaces, configuring **26-11**
- PIM
 - configuring dense mode **29-14**
 - configuring sparse mode **29-14**
 - displaying information **29-15**
 - displaying statistics **29-20**
 - enabling sparse-dense mode **29-14, 29-15**
 - overview **29-3**
- PIM-DM **29-3**
- PIM-SM **29-3**
- ping
 - executing **7-7**
 - overview **7-7**
- ping command **7-7, 29-16**
- PoE **11-7**
 - configuring power consumption for single device **11-5**
 - configuring power consumption for switch **11-4**
 - power consumption for powered devices
- Intelligent Power Management **11-4**
- powering down a module **10-20**
- power management modes **11-2**
- show interface status **11-6**
- point-to-point
 - in 802.1X authentication (figure) **34-2, 34-17**
- police command **32-37**
- policed-DSCP map **32-58**
- policers
 - description **32-5**
 - types of **32-10**
- policies
 - See QoS policies
- policing
 - how to implement **32-72**
 - See QoS policing
- policy associations, QoS on Sup 6-E **32-89**
- policy-map command **32-33, 32-36**
- policy map marking action, configuring **32-77**
- policy maps
 - attaching to interfaces **32-40**
 - configuring **32-35**
- port ACLs
 - and voice VLAN **39-4**
 - defined **39-3**
 - limitations **39-5**
- Port Aggregation Protocol
 - see PAgP
- port-based authentication
 - 802.1X with voice VLAN **34-18**
 - changing the quiet period **34-44**
 - client, defined **34-2**
 - configuration guidelines **34-23**
 - configure 802.1X accounting **34-32**
 - configure switch-to-RADIUS server communication **34-26**
 - configure with Authentication Failed VLAN assignment **34-40**
 - configure with Critical Authentication **34-36, 34-37**

- configure with Guest-VLANs [34-32, 34-41](#)
- configure with MAC Authentication Bypass [34-35](#)
- configure with Wake-on-LAN [34-39](#)
- configuring
 - Multiple Domain Authentication [34-28](#)
- configuring Guest-VLAN [34-26](#)
- configuring manual re-authentication of a client [34-47](#)
- controlling authorization state [34-4](#)
- default configuration [34-22](#)
- described [34-1](#)
- device roles [34-2](#)
- displaying statistics [34-48](#)
- enabling [34-23](#)
- enabling multiple hosts [34-43](#)
- enabling periodic re-authentication [34-42](#)
- encapsulation [34-3](#)
- host mode [34-6](#)
- initiation and message exchange [34-3](#)
- method lists [34-23](#)
- multidomain authentication [34-19](#)
- multiple-hosts mode, described [34-6](#)
- port security
 - multiple-hosts mode [34-7](#)
- ports not supported [34-4](#)
- resetting to default values [34-48](#)
- setting retransmission number [34-46](#)
- setting retransmission time [34-45](#)
- topologies, supported [34-21](#)
- using with port security [34-15](#)
- with Critical Authentication [34-12](#)
- with Guest VLANs [34-8](#)
- with MAC Authentication Bypass [34-9](#)
- with VLAN assignment [34-7](#)
- port-based QoS features
 - See QoS
- port-channel interfaces
 - See also EtherChannel
 - creating [19-6](#)
- overview [19-2](#)
- port-channel load-balance
 - command [19-12](#)
 - command example [19-12](#)
- port-channel load-balance command [19-13](#)
- port cost (STP)
 - configuring [17-15](#)
- PortFast
 - and MST [17-23](#)
 - BPDU filter, configuring [18-9](#)
 - configuring or enabling [18-16](#)
 - overview [18-6](#)
- PortFast BPDU filtering
 - and MST [17-23](#)
 - enabling [18-9](#)
 - overview [18-9](#)
- port numbering with TwinGig Convertors [6-8](#)
- port priority
 - configuring MST instances [17-32](#)
 - configuring STP [17-13](#)
- ports
 - blocking [41-1](#)
 - checking status [7-2](#)
 - dynamic VLAN membership
 - example [13-25](#)
 - reconfirming [13-22](#)
 - forwarding, resuming [41-3](#)
 - See also interfaces
- port security
 - aging [35-5](#)
 - and QoS trusted boundary [32-26](#)
 - configuring [35-7](#)
 - displaying [35-26](#)
 - guidelines and restrictions [35-31](#)
 - on access ports [35-6, 35-21](#)
 - on private VLAN [35-13](#)
 - host [35-14](#)
 - over Layer 2 EtherChannel [35-31](#)
 - promiscuous [35-15](#)

- topology **35-14, 35-17, 35-31**
- on trunk port **35-16**
 - guidelines and restrictions **35-14, 35-17, 35-20, 35-31**
 - port mode changes **35-21**
- on voice ports **35-21**
- RADIUS accounting **34-16**
- sticky learning **35-5**
- using with 802.1X **34-15**
- violations **35-5**
- with 802.1X Authentication **35-30**
- with DHCP and IP Source Guard **35-30**
- with other features **35-31**
- port states
 - description **17-5**
- port trust state
 - See trust states
- power
 - inline **33-5**
- power dc input command **10-17**
- power handling for Supervisor Engine II-TS **11-11**
- power inline command **11-3**
- power inline consumption command **11-4, 11-5**
- power management
 - Catalyst 4500 series **10-6**
 - Catalyst 4500 Switch power supplies **10-13**
 - Catalyst 4948 series **10-20**
 - configuring combined mode **10-12**
 - configuring redundant mode **10-11**
 - overview **10-1**
 - redundancy **10-6**
- power management for Catalyst 4500 Switch
 - combined mode **10-8**
 - redundant mode **10-8**
- power management limitations in Catalyst 4500 Switch **10-9**
- power management mode
 - selecting **10-8**
- Power-On-Self-Test diagnostics **48-3, 48-14**
- Power-On-Self-Test for Supervisor Engine V-10GE **48-8**
- power redundancy-mode command **10-11**
- power supplies
 - available power for Catalyst 4500 Switch **10-13**
 - fixed **10-7**
 - variable **10-7, 10-20**
- primary VLANs **40-2, 40-5**
 - associating with secondary VLANs **40-14**
 - configuring as a PVLAN **40-13**
- priority
 - overriding CoS of incoming frames **33-4**
- priority queuing, QoS on Sup 6-E **32-84**
- private VLAN
 - configure port security **35-14**
 - enabling DHCP Snooping **37-11**
- private VLANs
 - across multiple switches **40-5**
 - and SVIs **40-10**
 - benefits of **40-2**
 - community ports **40-4**
 - community VLANs **40-3, 40-4**
 - default configuration **40-11**
 - end station access to **40-3**
 - isolated port **40-4**
 - isolated VLANs **40-3, 40-4**
 - ports
 - community **40-4**
 - isolated **40-4**
 - promiscuous **40-5**
 - primary VLANs **40-2, 40-5**
 - promiscuous ports **40-5**
 - secondary VLANs **40-3**
 - subdomains **40-2**
 - traffic in **40-9**
- privileged EXEC mode **2-5**
- privileges
 - changing default **3-23**
 - configuring levels **3-23**
 - exiting **3-24**
 - logging in **3-24**

- promiscuous ports
- configuring PVLAN [40-15](#)
 - defined [40-5](#)
 - setting mode [40-22](#)
- protocol timers [17-4](#)
- provider edge devices [31-2](#)
- pruning, VTP
- See VTP pruning
- pseudobridges
- description [17-25](#)
- PVACL [37-16](#)
- PVID (port VLAN ID)
- and 802.1X with voice VLAN ports [34-18](#)
- PVLAN promiscuous trunk port
- configuring [40-2, 40-15, 40-19](#)
- PVLANS
- 802.1q support [40-12](#)
 - across multiple switches [40-5](#)
 - configuration guidelines [40-11](#)
 - configure port security [35-13, 35-15, 35-17](#)
 - configure port security in a wireless setting [35-31](#)
 - configure port security over Layer 2 EtherChannel [35-31](#)
 - configuring [40-10](#)
 - configuring a VLAN [40-13](#)
 - configuring promiscuous ports [40-15](#)
 - host ports
 - configuring a Layer 2 interface [40-16](#)
 - setting [40-22](#)
 - overview [40-1](#)
 - permitting routing, example [40-21](#)
 - promiscuous mode
 - setting [40-22](#)
 - setting
 - interface mode [40-22](#)

Q**QoS**

- allocating bandwidth [32-56](#)
- and software processed packets [32-16](#)
- auto-QoS
 - configuration and defaults display [32-20](#)
 - configuration guidelines [32-19](#)
 - described [32-17](#)
 - displaying [32-20](#)
 - effects on NVRAM configuration [32-19](#)
 - enabling for VoIP [32-19](#)
 - basic model [32-5](#)
 - burst size [32-31](#)
 - classification [32-6 to 32-10](#)
 - configuration guidelines [32-25](#)
 - auto-QoS [32-19](#)
 - configuring
 - auto-QoS [32-17](#)
 - DSCP maps [32-57](#)
 - dynamic buffer limiting [32-27](#)
 - traffic shaping [32-56](#)
 - trusted boundary [32-26](#)
 - configuring Layer 2 Control Packet QoS, feature interaction [32-64](#)
 - configuring Layer 2 Control Packet QoS, guidelines [32-64](#)
 - configuring Layer 2 Control Packet QoS, overview [32-60](#)
 - configuring UBRL [32-42](#)
 - configuring VLAN-based on Layer 2 interfaces [32-51](#)
 - creating named aggregate policers [32-31](#)
 - creating policing rules [32-32](#)
 - default auto configuration [32-17](#)
 - default configuration [32-23](#)
 - definitions [32-3](#)
 - disabling on interfaces [32-40](#)
 - enabling and disabling [32-50](#)
 - enabling hierarchical policers [32-46](#)
 - enabling on interfaces [32-40](#)
 - enabling per-port per-VLAN [32-48](#)
 - flowcharts [32-8, 32-12](#)
 - IP phones

- automatic classification and queueing **32-17**
- detection and trusted settings **32-17, 32-26**
- overview **32-1**
- overview of per-port per-VLAN **32-16**
- packet modification **32-16**
- port-based **32-51**
- priority **32-15**
- traffic shaping **32-16**
- transmit rate **32-56**
- trust states
 - trusted device **32-26**
- VLAN-based **32-51**
- See also COS; DSCP values; transmit queues
- QoS active queue management**
 - tracking queue length **32-14**
- QoS labels**
 - definition **32-3**
- QoS mapping tables**
 - CoS-to-DSCP **32-57**
 - DSCP-to-CoS **32-59**
 - policed-DSCP **32-58**
 - types **32-14**
- QoS marking**
 - description **32-5**
- QoS on Sup 6-E**
 - Active Queue management via DBL **32-85**
 - active queue management via DBL **32-81, 32-85**
 - classification **32-71**
 - configuring **32-67**
 - configuring the policy map marking action **32-77**
 - hardware capabilities for marking **32-77**
 - hierarchical policies **32-87**
 - how to implement policing **32-72**
 - marking action drivers **32-75**
 - marking network traffic **32-72**
 - MQC-based QoS configuration **32-68**
 - multi-attribute marking support **32-76**
 - platform hardware capabilities **32-70**
 - platform restrictions **32-72**
- platform-supported classification criteria and QoS features **32-68, 32-69**
- policing **32-71**
- policy associations **32-89**
- prerequisites for applying a service policy **32-70**
- priority queuing **32-84**
- restrictions for applying a service policy **32-70**
- shaping **32-79**
- sharing(bandwidth) **32-81**
- sharing(blandwidth), shapring, and priority queuing **32-79**
- software QoS **32-89**
- traffic marking procedure flowchart **32-75**
- QoS policers**
 - burst size **32-31**
 - types of **32-10**
- QoS policing**
 - definition **32-5**
 - described **32-5, 32-10**
- QoS policy**
 - attaching to interfaces **32-11**
 - overview of configuration **32-33**
- QoS service policy**
 - prerequisites **32-70**
 - restrictions for applying **32-70**
- QoS transmit queues**
 - allocating bandwidth **32-56**
 - burst **32-16**
 - configuring traffic shaping **32-56**
 - mapping DHCP values to **32-55**
 - maximum rate **32-16**
 - overview **32-14**
 - sharing link bandwidth **32-15**
- QoS transmit queues, configuring** **32-54**
- Quality of service**
 - See QoS
- queueing** **32-6, 32-14**

R

- RADIUS server
 configure to-Switch communication **34-26**
 configuring settings **34-28**
 parameters on the switch **34-26**
- range command **6-4**
- range macros
 defining **6-5**
- ranges of interfaces
 configuring **6-4**
- Rapid Spanning Tree
 See RSTP
- rcommand command **12-12**
- re-authentication of a client
 configuring manual **34-47**
 enabling periodic **34-42**
- reduced MAC address **17-2**
- redundancy
 configuring **8-7**
 guidelines and restrictions **8-6**
 changes made through SNMP **8-11**
 NSF-aware support **9-2**
 NSF-capable support **9-2**
 overview **8-2**
 redundancy command **8-8**
 understanding synchronization **8-5**
- redundancy (NSF) **9-1**
 configuring
 BGP **9-11**
 CEF **9-11**
 EIGRP **9-16**
 IS-IS **9-14**
 OSPF **9-13**
 routing protocols **9-5**
- redundancy (RPR)
 route processor redundancy **8-3**
 synchronization **8-5**
- redundancy (SSO)
- redundancy command **9-10**
 route processor redundancy **8-3**
 synchronization **8-5**
- related documentation **xl**
- reload command **3-28, 3-29**
- Remote Network Monitoring
 See RMON
- replication
 description **29-8**
- report suppression, IGMP
 disabling **21-11**
- reserved-range VLANs
 See VLANs
- reset command **51-3**
- resetting an interface to default configuration **6-26**
- resetting a switch to defaults **3-31**
- restricting access
 NTP services **4-8**
 TACACS+ **3-15**
- retransmission number
 setting in 802.1X authentication **34-46**
- retransmission time
 changing in 802.1X authentication **34-45**
- RFC
 1157, SNMPv1 **45-2**
 1305, NTP **4-2**
 1757, RMON **47-2**
 1901, SNMPv2C **45-2**
 1902 to 1907, SNMPv2 **45-2**
 2273-2275, SNMPv3 **45-2**
- RIP
 description **1-9**
- RMON
 default configuration **47-3**
 displaying status **47-7**
 enabling alarms and events **47-4**
 groups supported **47-2**
 overview **47-1**
- ROM monitor

- boot process and **3-26**
- CLI **2-7**
- commands **51-2 to 51-3**
- debug commands **51-5**
- entering **51-2**
- exiting **51-6**
- overview **51-1**
- root bridge
 - configuring **17-9**
 - selecting in MST **17-22**
- root guard
 - and MST **17-23**
 - enabling **18-2**
 - overview **18-2**
- routed packets
 - ACLs **39-32**
- route-map (IP) command **30-3**
- route maps
 - defining **30-3**
 - PBR **30-2**
- router ACLs
 - description **39-3**
 - using with VLAN maps **39-31**
- router ACLs, using PACL with VLAN maps **39-37**
- route targets
 - VPN **31-4**
- Routing Information Protocol
 - See RIP
- RPF
 - <Emphasis>See Unicast RPF
- RSPAN
 - configuration guidelines **43-16**
 - destination ports **43-5**
 - IDS **43-2**
 - monitored ports **43-4**
 - monitoring ports **43-5**
 - received traffic **43-3**
 - sessions
 - creating **43-17**
- defined **43-3**
- limiting source traffic to specific VLANs **43-23**
- monitoring VLANs **43-22**
- removing source (monitored) ports **43-21**
- specifying monitored ports **43-17**
- source ports **43-4**
- transmitted traffic **43-4**
- VLAN-based **43-5**
- RSTP
 - compatibility **17-23**
 - description **17-22**
 - port roles **17-24**
 - port states **17-24**

- S**
- SAID
 - See 802.10 SAID
- scheduling **32-14**
 - defined **32-5**
 - overview **32-6**
- secondary root switch **17-12**
- secondary VLANs **40-3**
 - associating with primary **40-14**
 - permitting routing **40-21**
- security
 - configuring **36-1**
- Security Association Identifier
 - See 802.10 SAID
- selecting a power management mode **10-8**
- selecting X2/TwinGig Convertor Mode **6-8**
- sequence numbers in log messages **44-7**
- servers, VTP
 - See VTP servers
- service-policy command **32-33**
- service-policy input command **25-2, 32-40**
- service-provider networks
 - and customer VLANs **22-2**
- set default interface command **30-4**

- set interface command **30-3**
 set ip default next-hop command **30-4**
 set ip next-hop command **30-3**
 set-request operation **45-4**
 severity levels, defining in system messages **44-8**
 shaping, QoS on Sup 6-E **32-79**
 sharing(bandwidth), QoS on Sup 6-E **32-81**
 show adjacency command **27-9**
 show boot command **3-31**
 show catalyst4000 chassis-mac-address command **17-3**
 show cdp command **23-2, 23-3**
 show cdp entry command **23-4**
 show cdp interface command **23-3**
 show cdp neighbors command **23-4**
 show cdp traffic command **23-4**
 show ciscoview package command **4-33**
 show ciscoview version command **4-33**
 show cluster members command **12-12**
 show configuration command **6-13**
 show debugging command **23-4**
 show environment command **10-2**
 show history command **2-4**
 show interfaces command **6-18, 6-23, 6-25**
 show interfaces status command **7-2**
 show ip cache flow aggregation destination-prefix
command **46-12**
 show ip cache flow aggregation prefix command **46-12**
 show ip cache flow aggregation source-prefix
command **46-12**
 show ip cache flow command **46-9**
 show ip cef command **27-8**
 show ip eigrp interfaces command **26-18**
 show ip eigrp neighbors command **26-18**
 show ip eigrp topology command **26-18**
 show ip eigrp traffic command **26-18**
 show ip interface command **29-16**
 show ip local policy command **30-5**
 show ip mroute command **29-16**
 show ip pim interface command **29-16**
 show l2protocol command **22-12**
 show mac-address-table address command **7-3**
 show mac-address-table interface command **7-3**
 show mls entry command **27-8**
 show module command **7-1, 17-5**
 show PoE consumed **11-7**
 show power inline command **11-6**
 show power inline consumption command **11-5**
 show power supplies command **10-11**
 show protocols command **6-23**
 show running-config command
 adding description for an interface **6-13**
 checking your settings **3-9**
 displaying ACLs **39-24, 39-27, 39-34, 39-35**
 show startup-config command **3-10**
 show users command **7-6**
 show version command **3-29**
 shutdown, command **6-24**
 shutdown threshold for Layer 2 protocol packets **22-9**
 shutting down
 interfaces **6-24**
 Simple Network Management Protocol
 See SNMP
 single spanning tree
 See SST
 slot numbers, description **6-2**
 Smartports macros
 applying global parameter values **16-8**
 applying macros **16-8**
 applying parameter values **16-8**
 configuration guidelines **16-5**
 configuring **16-2**
 creating **16-7**
 default configuration **16-3**
 defined **16-1**
 displaying **16-13**
 tracing **16-6**
 SNMP
 accessing MIB variables with **45-4**

agent
 described **45-4**
 disabling **45-7**
 authentication level **45-10**
 community strings
 configuring **45-7**
 overview **45-4**
 configuration examples **45-16**
 configuration guidelines **45-6**
 default configuration **45-6**
 enabling **50-16**
 engine ID **45-6**
 groups **45-6, 45-9**
 host **45-6**
 informs
 and trap keyword **45-11**
 described **45-5**
 differences from traps **45-5**
 enabling **45-14**
 limiting access by TFTP servers **45-15**
 limiting system log messages to NMS **44-9**
 manager functions **45-3**
 notifications **45-5**
 overview **45-1, 45-4**
 status, displaying **45-17**
 system contact and location **45-15**
 trap manager, configuring **45-13**
 traps
 described **45-3, 45-5**
 differences from informs **45-5**
 enabling **45-11**
 enabling MAC address notification **4-22**
 enabling MAC move notification **4-24**
 enabling MAC threshold notification **4-26**
 overview **45-1, 45-4**
 types of **45-11**
 users **45-6, 45-9**
 versions supported **45-2**
 SNMP commands **50-16**

SNMPv1 **45-2**
 SNMPv2C **45-2**
 SNMPv3 **45-2**
 software
 upgrading **8-13**
 software configuration register **3-26**
 software QoS, on Sup 6-E **32-89**
 software switching
 description **27-5**
 interfaces **27-6**
 key data structures used **29-7**
 SPAN
 and ACLs **43-5**
 configuration guidelines **43-7**
 configuring **43-6 to 43-10**
 destination ports **43-5**
 IDS **43-2**
 monitored port, defined **43-4**
 monitoring port, defined **43-5**
 received traffic **43-3**
 sessions
 defined **43-3**
 source ports **43-4**
 transmitted traffic **43-4**
 VLAN-based **43-5**
 SPAN and RSPAN
 concepts and terminology **43-3**
 default configuration **43-6**
 displaying status **43-25**
 overview **43-1**
 session limits **43-6**
 SPAN enhancements
 access list filtering **43-13**
 configuration example **43-16**
 CPU port sniffing **43-10**
 encapsulation configuration **43-12**
 ingress packets **43-12**
 packet type filtering **43-15**
 spanning-tree backbonefast command **18-16**

- spanning-tree cost command **17-15**
- spanning-tree guard root command **18-2**
- spanning-tree portfast bpdu-guard command **18-8**
- spanning-tree portfast command **18-7**
- spanning-tree port-priority command **17-13**
- spanning-tree uplinkfast command **18-12**
- spanning-tree vlan
 - command **17-9**
 - command example **17-9**
- spanning-tree vlan command **17-8**
- spanning-tree vlan cost command **17-15**
- spanning-tree vlan forward-time command **17-19**
- spanning-tree vlan hello-time command **17-17**
- spanning-tree vlan max-age command **17-18**
- spanning-tree vlan port-priority command **17-13**
- spanning-tree vlan priority command **17-17**
- spanning-tree vlan root primary command **17-10**
- spanning-tree vlan root secondary command **17-12**
- speed
 - configuring interface **6-11**
- speed command **6-11**
- SSO
 - configuring **9-10**
- SSO operation **9-4**
- SST
 - description **17-22**
 - interoperability **17-24**
- static addresses
 - See addresses
- static routes
 - configuring **3-11**
 - verifying **3-12**
- statistics
 - displaying 802.1X **34-48**
 - displaying PIM **29-20**
 - NetFlow accounting **46-9**
 - SNMP input and output **45-17**
- sticky learning
 - configuration file **35-5**
- defined **35-5**
- disabling **35-5**
- enabling **35-5**
- saving addresses **35-5**
- sticky MAC addresses
 - configuring **35-7**
 - defined **35-4**
- Storm Control
 - displaying **42-7**
 - enabling Broadcast **42-3**
 - enabling Multicast **42-4**
 - hardware-based, implementing **42-2**
 - overview **42-1**
 - software-based, implementing **42-2**
- STP
 - bridge ID **17-2**
 - configuring **17-7 to 17-20**
 - creating topology **17-4**
 - defaults **17-6**
 - disabling **17-19**
 - enabling **17-7**
 - enabling extended system ID **17-8**
 - enabling Per-VLAN Rapid Spanning Tree **17-20**
 - EtherChannel guard
 - disabling **18-6**
 - forward-delay time **17-18**
 - hello time **17-17**
 - Layer 2 protocol tunneling **22-7**
 - maximum aging time **17-18**
 - overview **17-1, 17-3**
 - per-VLAN rapid spanning tree **17-6**
 - port cost **17-15**
 - port priority **17-13**
 - root bridge **17-9**
 - stratum, NTP **4-2**
 - stub routing (EIGRP)
 - benefits **26-17**
 - configuration tasks **26-17**
 - configuring **26-13**

overview **26-12, 26-13**
 restrictions **26-17**
 verifying **26-18**
 subdomains, private VLAN **40-2**
 summer time **4-13**
 supervisor engine
 accessing the redundant **8-15**
 configuring **3-8 to 3-13**
 copying files to standby **8-15**
 default configuration **3-1**
 default gateways **3-11**
 environmental monitoring **10-1**
 redundancy **9-1**
 ROM monitor **3-26**
 startup configuration **3-25**
 static routes **3-11**
 synchronizing configurations **8-11**
 Supervisor Engine II-TS
 insufficient inline power handling **10-18, 11-11**
 SVI Autostate Exclude
 understanding **26-3**
 SVI Autostate exclude
 configuring **26-7**
 switched packets
 and ACLs **39-31**
 Switched Port Analyzer
 See SPAN
 switching, NetFlow
 checking for required hardware **46-6**
 configuration (example) **46-13**
 configuring switched IP flows **46-8**
 enabling Collection **46-7**
 exporting cache entries **46-9**
 switchport
 show interfaces **6-18, 6-25**
 switchport access vlan command **15-6, 15-8**
 switchport block multicast command **41-2**
 switchport block unicast command **41-2**
 switchport mode access command **15-8**
 switchport mode dot1q-tunnel command **22-6**
 switchport mode dynamic command **15-6**
 switchport mode trunk command **15-6**
 switch ports
 See access ports
 switchport trunk allowed vlan command **15-6**
 switchport trunk encapsulation command **15-6**
 switchport trunk encapsulation dot1q command **15-3**
 switchport trunk encapsulation isl command **15-3**
 switchport trunk encapsulation negotiate command **15-3**
 switchport trunk native vlan command **15-6**
 switchport trunk pruning vlan command **15-7**
 switch-to-RADIUS server communication
 configuring **34-26**
 sysret command **51-5**
 system
 reviewing configuration **3-10**
 settings at startup **3-27**
 system alarms
 on Sup 2+ to V-10GE **10-5**
 on Sup 6-E **10-5**
 overview **10-4**
 system clock
 configuring
 daylight saving time **4-13**
 manually **4-11**
 summer time **4-13**
 time zones **4-12**
 displaying the time and date **4-12**
 overview **4-2**
 See also NTP
 system images
 loading from Flash memory **3-30**
 modifying boot field **3-27**
 specifying **3-30**
 system message logging
 default configuration **44-3**
 defining error message severity levels **44-8**
 disabling **44-4**

- displaying the configuration [44-12](#)
 enabling [44-4](#)
 facility keywords, described [44-11](#)
 level keywords, described [44-8](#)
 limiting messages [44-9](#)
 message format [44-2](#)
 overview [44-1](#)
 sequence numbers, enabling and disabling [44-7](#)
 setting the display destination device [44-4](#)
 synchronizing log messages [44-5](#)
 timestamps, enabling and disabling [44-7](#)
 UNIX syslog servers
 configuring the daemon [44-10](#)
 configuring the logging facility [44-11](#)
 facilities supported [44-11](#)
 system MTU
 802.1Q tunneling [22-5](#)
 maximums [22-5](#)
 system name
 default configuration [4-15](#)
 default setting [4-15](#)
 manual configuration [4-15](#)
 See also DNS
 system prompt, default setting [4-14, 4-15](#)
-
- T**
- TACACS+ [36-1](#)
 accounting, defined [3-16](#)
 authentication, defined [3-16](#)
 authorization, defined [3-16](#)
 configuring
 accounting [3-21](#)
 authentication key [3-18](#)
 authorization [3-21](#)
 login authentication [3-19](#)
 default configuration [3-18](#)
 displaying the configuration [3-22](#)
 identifying the server [3-18](#)
- limiting the services to the user [3-21](#)
 operation of [3-17](#)
 overview [3-15](#)
 tracking services accessed by user [3-21](#)
- tagged packets
 802.1Q [22-3](#)
 Layer 2 protocol [22-7](#)
- TCAM programming algorithm
 changing [39-9](#)
 TCAM programming algorithm, overview [39-7](#)
 TCAM programming and ACLs [39-10, 39-12](#)
 for Sup II-Plus thru V-10GE [39-6](#)
 TCAM programming and ACLs for Sup 6-E [39-15](#)
 TCAM region, changing the algorithm [39-9](#)
 TCAM region, resizing [39-10](#)
- TDR
 checking cable connectivity [7-3](#)
 enabling and disabling test [7-3](#)
 guidelines [7-3](#)
- Telnet
 accessing CLI [2-2](#)
 disconnecting user sessions [7-6](#)
 executing [7-5](#)
 monitoring user sessions [7-6](#)
 telnet command [7-5](#)
- Terminal Access Controller Access Control System Plus
 See TACACS+
- TFTP
 configuration files in base directory [3-4](#)
 configuring for autoconfiguration [3-4](#)
 limiting access by servers [45-15](#)
- TFTP download
 See also console download
- time
 See NTP and system clock
- Time Domain Reflectometer
 See TDR
- time exceeded messages [7-8](#)
- timer

See login timer
 timestamps in log messages **44-7**
 time zones **4-12**
 Token Ring
 media not supported (note) **13-5, 13-9**
 Topology change notification processing
 MLD Snooping
 Topology change notification processing **21-5**
 TOS
 description **32-4**
 trace command **7-9**
 traceroute
 See IP traceroute
 See Layer 2 Traceroute
 traceroute mac command **7-10**
 traceroute mac ip command **7-10**
 traffic
 blocking flooded **41-2**
 traffic control
 using ACLs (figure) **39-4**
 using VLAN maps (figure) **39-5**
 traffic marking procedure flowchart **32-75**
 traffic shaping **32-16**
 translational bridge numbers (defaults) **13-4**
 transmit queues
 See QoS transmit queues
 transmit rate **32-56**
 traps
 configuring MAC address notification **4-22**
 configuring MAC move notification **4-24**
 configuring MAC threshold notification **4-26**
 configuring managers **45-11**
 defined **45-3**
 enabling **4-22, 4-24, 4-26, 45-11**
 notification types **45-11**
 overview **45-1, 45-4**
 troubleshooting
 with CiscoWorks **45-4**
 with system message logging **44-1**
 with traceroute **7-8**
 troubleshooting high CPU due to ACLs **39-12**
 trunk ports
 configure port security **35-16**
 configuring PVLAN **40-17 to 40-19**
 trunks
 802.1Q restrictions **15-5**
 configuring **15-6**
 configuring access VLANs **15-6**
 configuring allowed VLANs **15-6**
 default interface configuration **15-6**
 different VTP domains **15-3**
 enabling to non-DTP device **15-4**
 encapsulation **15-3**
 specifying native VLAN **15-6**
 understanding **15-3**
 trusted boundary for QoS **32-26**
 Trust State of interfaces, configuring
 trust states
 configuring **32-52**
 tunneling
 defined **22-1**
 tunnel ports
 802.1Q, configuring **22-6**
 described **22-2**
 incompatibilities with other features **22-5**
 TwinGig Convertors
 limitations on using **6-8**
 port numbering **6-8**
 selecting X2/TwinGig Converter mode **6-8**
 type of service
 See TOS

U

UDLD
 default configuration **24-2**
 disabling **24-3**
 enabling **24-3**

- overview **24-1**
- unauthorized ports with 802.1X **34-4**
- unicast
 - See IP unicast
 - unicast flood blocking
 - configuring **41-1**
 - unicast MAC address filtering
 - and adding static addresses **4-29**
 - and broadcast MAC addresses **4-28**
 - and CPU packets **4-29**
 - and multicast addresses **4-28**
 - and router MAC addresses **4-28**
 - configuration guidelines **4-28**
 - described **4-28**
 - unicast MAC address filtering, configuring
 - ACLs
 - configuring unicast MAC address filtering **39-19**
 - Unicast RPF (Unicast Reverse Path Forwarding)
 - applying **28-5**
 - BGP attributes
 - caution **28-4**
 - CEF
 - requirement **28-2**
 - tables **28-7**
 - configuring **28-9**
 - (examples) **?? to 28-12**
 - BOOTP **28-8**
 - DHCP **28-8**
 - enterprise network (figure) **28-6**
 - prerequisites **28-9**
 - routing table requirements **28-7**
 - tasks **28-9**
 - verifying **28-10**
 - deploying **28-5**
 - description **28-2**
 - disabling **28-11**
 - enterprise network (figure) **28-6**
 - FIB **28-2**
 - implementing **28-4**
 - maintaining **28-10**
 - monitoring **28-10**
 - packets, dropping (figure) **28-4**
 - prerequisites **28-9**
 - restrictions
 - basic **28-8**
 - routing asymmetry **28-7**
 - routing asymmetry (figure) **28-8**
 - routing table requirements **28-7**
 - security policy
 - applying **28-5**
 - attacks, mitigating **28-5**
 - deploying **28-5**
 - tunneling **28-5**
 - source addresses, validating **28-3**
 - (figure) **28-3, 28-4**
 - failure **28-3**
 - traffic filtering **28-5**
 - tunneling **28-5**
 - validation
 - failure **28-3, 28-4**
 - packets, dropping **28-3**
 - source addresses **28-3**
 - verifying **28-10**
 - unicast traffic
 - blocking **41-2**
 - unidirectional ethernet
 - enabling **25-2**
 - example of setting **25-2**
 - overview **25-1**
 - UniDirectional Link Detection Protocol
 - See UDLD
 - UNIX syslog servers
 - daemon configuration **44-10**
 - facilities supported **44-11**
 - message logging configuration **44-11**
 - UplinkFast
 - and MST **17-23**
 - enabling **18-16**

- MST and **17-23**
overview **18-11**
- User Based Rate Limiting
configuring **32-42**
overview **32-42**
- user EXEC mode **2-5**
- user sessions
disconnecting **7-6**
monitoring **7-6**
- using PACL with access-group mode **39-35**
-
- V**
- VACLs
Layer 4 port operations **39-15**
- virtual configuration register **51-3**
- virtual LANs
See VLANs
- Virtual Private Network
See VPN
- VLAN ACLs
See VLAN maps
- VLAN-based QoS on Layer 2 interfaces,
configuring **32-51**
- vlan command **13-6**
- vlan dot1q tag native command **22-4**
- VLAN ID, discovering **4-30**
- VLAN Management Policy Server
See VMPS
- VLAN maps
applying to a VLAN **39-27**
configuration example **39-28**
configuration guidelines **39-23**
configuring **39-23**
creating and deleting entries **39-24**
defined **39-3**
denying access example **39-29**
denying packets **39-24**
displaying **39-30**
- order of entries **39-24**
permitting packets **39-24**
router ACLs and **39-31**
using (figure) **39-5**
using in your network **39-27**
- VLAN maps, PACL and Router ACLs **39-37**
- VLANs
allowed on trunk **15-6**
configuration guidelines **13-3**
configuring **13-5**
customer numbering in service-provider
networks **22-3**
default configuration **13-4**
description **1-5**
extended range **13-3**
IDs (default) **13-4**
interface assignment **13-7**
limiting source traffic with RSPAN **43-23**
monitoring with RSPAN **43-22**
name (default) **13-4**
normal range **13-3**
overview **13-1**
reserved range **13-3**
See also PVLANS
- VLAN Trunking Protocol
See VTP
- VLAN trunks
overview **15-3**
- VMPS
configuration file example **13-28**
configuring dynamic access ports on client **13-21**
configuring retry interval **13-23**
database configuration file **13-28**
dynamic port membership
example **13-25**
reconfirming **13-22**
reconfirming assignments **13-22**
reconfirming membership interval **13-22**
server overview **13-17**

- VMPS client
- administering and monitoring [13-23](#)
 - configure switch
 - configure reconfirmation interval [13-22](#)
 - dynamic ports [13-21](#)
 - entering IP VMPS address [13-20](#)
 - reconfirmation interval [13-23](#)
 - reconfirm VLAM membership [13-22](#)
 - default configuration [13-20](#)
 - dynamic VLAN membership overview [13-19](#)
 - troubleshooting dynamic port VLAN membership [13-24](#)
- VMPS server
- fall-back VLAN [13-18](#)
 - illegal VMPS client requests [13-19](#)
 - overview [13-17](#)
 - security modes
 - multiple [13-18](#)
 - open [13-17](#)
 - secure [13-18](#)
 - voice interfaces
 - configuring [33-1](#)
 - Voice over IP
 - configuring [33-1](#)
 - voice ports
 - configuring VVID [33-3](#)
 - voice traffic [11-2, 33-5](#)
 - voice VLAN
 - IP phone data traffic, described [33-2](#)
 - IP phone voice traffic, described [33-2](#)
 - voice VLAN ports
 - using 802.1X [34-18](#)
- VPN
- configuring routing in [31-6](#)
 - forwarding [31-4](#)
 - in service provider networks [31-1](#)
 - routes [31-2](#)
 - routing and forwarding table
 - See VRF
- VRF
- defining [31-4](#)
 - tables [31-1](#)
- VTP
- configuration guidelines [13-11](#)
 - configuring [13-12 to 13-16](#)
 - configuring transparent mode [13-15](#)
 - default configuration [13-12](#)
 - disabling [13-15](#)
 - Layer 2 protocol tunneling [22-7](#)
 - monitoring [13-16](#)
 - overview [13-7](#)
 - See also VTP version 2
- VTP advertisements
- description [13-9](#)
- VTP clients
- configuring [13-14](#)
- VTP domains
- description [13-8](#)
- VTP modes [13-8](#)
- VTP pruning
- enabling [13-13](#)
 - overview [13-10](#)
- VTP servers
- configuring [13-14](#)
- VTP statistics
- displaying [13-16](#)
- VTP version 2
- enabling [13-13](#)
 - overview [13-9](#)
 - See also VTP
- VTY and Network Assistant [12-11](#)
- VVID (voice VLAN ID)
- and 802.1X authentication [34-18](#)
 - configuring [33-3](#)
-
- W**
- Wake-on-LAN

configure with 802.1X [34-39](#)

WCCP

configuration examples [49-9](#)

configuring on a router [49-2, 49-10](#)

features [49-4](#)

restrictions [49-5](#)

service groups [49-6](#)

Web Cache Communication Protocol

See WCCP [xxxix, 49-1](#)

web caches

See cache engines

web cache services

description [49-4](#)

web caching

See web cache services

See also WCCP

web scaling [49-1](#)

