



INDEX

Numerics

- 10/100 autonegotiation feature, forced [8-21](#)
- 10-Gigabit Ethernet or Gigabit Ethernet ports
 - deploy on WS-X4606-10GE-E and Sup 6-E [8-13](#)
- 10-Gigabit Ethernet port
 - deploy with Gigabit Ethernet SFP ports [8-12](#), [8-13](#)
- 10-slot chassis, support for WS-X46490-CSFP-E [8-17](#)
- 1400 W DC Power supply
 - special considerations [14-21](#)
- 1400 W DC SP Triple Input power supply
 - special considerations [14-22](#)
- 802.10 SAID (default) [17-5](#)
- 802.1AE
 - standard [45-2](#)
- 802.1Q
 - trunks [22-6](#)
 - tunneling
 - compatibility with other features [29-5](#)
 - defaults [29-3](#)
 - described [29-2](#)
 - tunnel ports with other features [29-6](#)
- 802.1Q VLANs
 - trunk restrictions [19-4](#)
- 802.1s
 - See MST
- 802.1w
 - See MST
- 802.1X
 - See port-based authentication
- 802.1X authentication
 - Authentication Failed VLAN assignment [46-17](#)
 - for Critical Authentication [46-14](#)

- for guest VLANs [46-11](#)
- for MAC Authentication Bypass [46-12](#)
- for Unidirectional Controlled Port [46-15](#)
- VLAN User Distribution [46-16](#)
- web-based authentication [46-14](#)
- with port security [46-19](#)
- with VLAN assignment [46-10](#)
- with voice VLAN ports [46-22](#)
- 802.1X Host Mode [46-6](#)
 - multiauthentication mode [46-8](#)
 - multidomain authentication mode [46-7](#)
 - single-host [46-7](#)
- 802.1x-REV [45-2](#)
- 802.3ad
 - See LACP
- 9000W AC, displaying OBFL [14-4](#)

A

- AAA [50-1](#)
- AAA (authentication, authorization, and accounting). See also port-based authentication. [48-2](#)
- abbreviating commands [2-5](#)
- about Wireshark [58-5](#)
- access control entries
 - See ACEs
- access control entries and lists [50-1](#)
- access-group mode, configuring on Layer 2 interface [53-31](#)
- access-group mode, using PACL with [53-30](#)
- access list filtering, SPAN enhancement [57-13](#)
- access lists
 - using with WCCP [71-8](#)
- access ports

- and Layer 2 protocol tunneling [29-15](#)
- configure port security [49-7, 49-22](#)
- configuring [19-7](#)
- access VLANs [19-5](#)
- accounting
 - with RADIUS [46-111](#)
 - with TACACS+ [3-16, 3-21](#)
- ACEs
 - ACLs [53-2](#)
 - IP [1-41, 53-2](#)
 - Layer 4 operation restrictions [53-10](#)
- ACEs and ACLs [50-1](#)
- ACL assignments, port-based authentication [46-20](#)
- ACL assignments and redirect URLs, configure [46-38](#)
- ACL configuration, displaying a Layer 2 interface [53-32](#)
- ACLs
 - ACEs [53-2](#)
 - and SPAN [57-5](#)
 - and TCAM programming for Sup 6-E [53-10](#)
 - and TCAM programming for Sup II-Plus thru V-10GE [53-6](#)
 - applying IPv6 ACLs to a Layer 3 interface [53-17](#)
 - applying on routed packets [53-26](#)
 - applying on switched packets [53-25](#)
 - compatibility on the same switch [53-3](#)
 - configuring with VLAN maps [53-25](#)
 - CPU impact [53-12](#)
 - downloadable [48-7](#)
 - hardware and software support [53-6](#)
 - IP, matching criteria for port ACLs [53-4](#)
 - MAC extended [53-14](#)
 - matching criteria for router ACLs [53-3](#)
 - port
 - and voice VLAN [53-4](#)
 - defined [53-3](#)
 - processing [53-12](#)
 - selecting mode of capturing control packets [53-7](#)
 - troubleshooting high CPU [53-6](#)
 - types supported [53-3](#)
 - understanding [53-2](#)
 - VLAN maps [53-5](#)
- ACLs, applying to a Layer 2 interface [53-31](#)
- ACLs and VLAN maps, examples [53-19](#)
- acronyms, list of [1-1](#)
- action drivers, marking [42-21, 42-55](#)
- activating and deactivating a capture point, Wireshark [58-13](#)
- activating and deactivating Wiresharkcapture points, conceptual, Wireshark [58-9](#)
- active queue management [42-9](#)
- active queue management via DBL, QoS on Sup 6-E [42-34, 42-68](#)
- active traffic monitoring, IP SLAs [68-1](#)
- adding members to a community [16-9](#)
- addresses
 - displaying the MAC table [4-44](#)
 - dynamic
 - changing the aging time [4-30](#)
 - defined [4-28](#)
 - learning [4-29](#)
 - removing [4-31](#)
 - IPv6 [54-2](#)
 - MAC, discovering [4-44](#)
 - See MAC addresses
 - static
 - adding and removing [4-36](#)
 - defined [4-28](#)
- address resolution [4-44](#)
- adjacency tables
 - description [35-2](#)
 - displaying statistics [35-9](#)
- administrative VLAN
 - REP, configuring [24-9](#)
- administrative VLAN, REP [24-8](#)
- advertisements
 - LLDP [1-7, 31-2](#)
- advertisements, VTP
 - See VTP advertisements
- aggregation switch, enabling DHCP snooping [52-9](#)

- aging time
 - MAC address table [4-30](#)
- All Auth manager sessions, displaying summary [46-126](#)
- All Auth manager sessions on the switch authorized for a specified authentication method [46-126](#)
- ANCP client
 - enabling and configuring [38-2](#)
 - guidelines and restrictions [38-5](#)
 - identify a port with DHCP option 82 [38-4](#)
 - identify a port with protocol [38-2](#)
 - overview [38-1](#)
- ANCP protocol
 - identifying a port with [38-2](#)
- applying IPv6 ACLs to a Layer 3 interface [53-17](#)
- AQM via DBL, QoS on Sup 6-E [42-34, 42-68](#)
- archiving crashfiles information [2-8](#)
- ARP
 - defined [4-44](#)
 - table
 - address resolution [4-44](#)
 - managing [4-44](#)
- asymmetrical links, and 802.1Q tunneling [29-3](#)
- attachment points, Wireshark [58-6](#)
- attributes, RADIUS
 - vendor-proprietary [46-114](#)
 - vendor-specific [46-112](#)
- authentication
 - NTP associations [4-4](#)
 - RADIUS
 - key [46-104](#)
 - login [46-106](#)
 - See also port-based authentication
 - TACACS+
 - defined [3-16](#)
 - key [3-18](#)
 - login [3-19](#)
- Authentication, Authorization, and Accounting (AAA) [50-1](#)
- Authentication Failed, configuring 80.1X [46-70](#)
- Authentication methods registered with the Auth manager, determining [46-125](#)
- authentication open comand [46-8](#)
- authentication proxy web pages [48-4](#)
- authentication server
 - defined [46-3](#)
 - RADIUS server [46-3](#)
- Auth manager session for an interface, verifying [46-126](#)
- Auth manager summary, displaying [46-126](#)
- authoritative time source, described [4-2](#)
- authorization
 - with RADIUS [46-110](#)
 - with TACACS+ [3-16, 3-21](#)
- authorized and unauthorized ports [46-5](#)
- authorized ports with 802.1X [46-5](#)
- autoconfiguration [3-2](#)
- automatic discovery
 - considerations [16-7](#)
- Auto-MDIX on a port
 - configuring [8-31](#)
 - displaying the configuration [8-32](#)
 - overview [8-30](#)
- autonegotiation feature
 - forced 10/100Mbps [8-21](#)
- Auto SmartPorts built-in macros
 - configuring parameters [21-6](#)
- Auto SmartPorts macros
 - built-in macros [21-5](#)
 - configuration guidelines [21-5](#)
 - default configuration [21-4](#)
 - defined [21-1](#)
 - displaying [21-13](#)
 - enabling [21-4](#)
 - IOS shell [21-2, 21-10](#)
- Auto Smartports macros
 - defined [1-2](#)
- Auto SmartPorts user-defined macros
 - configuring [21-10](#)
- auto-sync command [11-8, 12-7](#)

Auto SmartPorts macros

See also SmartPorts macros

Auto Smartports macros

See also Smartports macros

B

Baby Giants

interacting with [8-29](#)

BackboneFast

adding a switch (figure) [25-3](#)

and MST [22-23](#)

configuring [25-15](#)

link failure (figure) [25-14, 25-15](#)

not supported MST [22-23](#)

understanding [25-13](#)

See also STP

banners

configuring

login [4-27](#)

message-of-the-day login [4-24](#)

default configuration [4-24](#)

when displayed [4-24](#)

b command [73-3](#)

BFD

and hardware support [39-7](#)

configuration example

BFD in a BGP network [39-25](#)

BFD in an EIGRP network with echo mode enabled by default [39-17](#)

BFD in an OSPF network [39-22](#)

support for static routing [39-27](#)

configuring

Echo mode [39-15](#)

session parameters on the interface [39-8](#)

Slow timer [39-16](#)

support for BGP [39-9](#)

support for dynamic routing protocols [39-9](#)

support for EIGRP [39-10](#)

support for OSPF [39-11](#)

support for static routing [39-13](#)

disabling echo mode without asymmetry [39-16](#)

monitoring and troubleshooting [39-17](#)

neighbor relationships [39-3](#)

operation [39-3](#)

prerequisites [39-2](#)

restrictions [39-2](#)

b flash command [73-3](#)

BGP [1-17](#)

routing session with multi-VRF CE [41-9](#)

blocking packets [55-1](#)

blocking state (STP)

RSTP comparisons (table) [22-24](#)

Boolean expressions in tracked lists [59-4](#)

boot bootldr command [3-31](#)

boot command [3-28](#)

boot commands [73-3](#)

boot fields

See configuration register boot fields

bootstrap program

See ROM monitor

boot system command [3-26, 3-31](#)

boot system flash command [3-28](#)

Border Gateway Protocol

See BGP

boundary ports

description [22-27](#)

BPDU Guard

and MST [22-23](#)

configuring [25-15](#)

overview [25-8](#)

BPDU's

and media speed [22-2](#)

pseudobridges and [22-25](#)

what they contain [22-3](#)

bridge ID

See STP bridge ID

bridge priority (STP) [22-17](#)

bridge protocol data units

See BPDUs

Broadcast Storm Control

disabling [56-5](#)

enabling [56-3](#)

Built-in macros and user-defined triggers, configuring mapping [21-9](#)

C

cache engine clusters [71-1](#)

cache engines [71-1](#)

cache farms

See cache engine clusters

Call Home

description [1-24, 67-2](#)

message format options [67-2](#)

messages

format options [67-2](#)

call home [67-1](#)

alert groups [67-6](#)

configuring e-mail options [67-9](#)

contact information [67-4](#)

default settings [67-18](#)

destination profiles [67-5](#)

displaying information [67-14](#)

mail-server priority [67-10](#)

pattern matching [67-9](#)

periodic notification [67-8](#)

rate limit messages [67-9](#)

severity threshold [67-8](#)

smart call home feature [67-2](#)

SMTP server [67-9](#)

testing communications [67-10](#)

call home alert groups

configuring [67-6](#)

description [67-6](#)

subscribing [67-7](#)

call home contacts

assigning information [67-4](#)

call home destination profiles

attributes [67-5](#)

configuring [67-5](#)

description [67-5](#)

displaying [67-16](#)

call home notifications

full-txt format for syslog [67-25](#)

XML format for syslog [67-28](#)

candidates

automatic discovery [16-7](#)

candidate switch, cluster

defined [16-12](#)

capture filter, Wireshark [58-7](#)

capture points, Wireshark [58-6](#)

Capturing control packets

selecting mode [53-7](#)

cautions

Unicast RPF

BGP optional attributes [36-4](#)

cautions for passwords

encrypting [3-22](#)

CDP

automatic discovery in communities [16-7](#)

configuration [30-2](#)

defined with LLDP [31-1](#)

displaying configuration [30-3](#)

enabling on interfaces [30-3](#)

host presence detection [46-8](#)

Layer 2 protocol tunneling [29-13](#)

maintaining [30-3](#)

monitoring [30-3](#)

overview [1-3, 30-1](#)

cdp enable command [30-3](#)

CEF

adjacency tables [35-2](#)

and NSF with SSO [13-5](#)

configuring load balancing [35-7](#)

displaying statistics [35-8](#)

- enabling [35-6, 70-2](#)
- hardware switching [35-4](#)
- load balancing [35-6](#)
- overview [35-1](#)
- software switching [35-4](#)
- certificate authority (CA) [67-3](#)
- CFM
 - and Ethernet OAM, configuring [65-51](#)
 - and Ethernet OAM interaction [65-51](#)
 - clearing [65-31](#)
 - configuration guidelines [65-7, 66-4](#)
 - configuring crosscheck for VLANs [65-11](#)
 - configuring fault alarms [65-16](#)
 - configuring port MEP [65-14](#)
 - configuring static remote MEP [65-13, 65-16, 65-18](#)
 - crosscheck [65-5](#)
 - defined [65-2](#)
 - EtherChannel support [65-7, 66-4](#)
 - fault alarms
 - configuring [65-16](#)
 - IP SLAs support for [65-6](#)
 - IP SLAs with endpoint discovers [65-21](#)
 - maintenance domain [65-2](#)
 - manually configuring IP SLAs ping or jitter [65-19](#)
 - measuring network performance [65-6](#)
 - monitoring [65-32, 65-33](#)
 - port MEP, configuring [65-14](#)
 - remote MEPs [65-5](#)
 - static RMEP, configuring [65-13, 65-16, 65-18](#)
 - static RMEP check [65-5](#)
 - Y.1731
 - described [65-27](#)
- CGMP
 - overview [27-2](#)
- Change of Authorization, RADIUS [46-97](#)
- channel-group group command [5-46, 26-8, 26-10](#)
- Cisco 7600 series Internet router
 - enabling SNMP [72-4, 72-5](#)
- Cisco Discovery Protocol
 - See CDP
- Cisco Express Forwarding
 - See CEF
- Cisco Group Management Protocol
 - See CGMP
- Cisco IOS IP SLAs [68-2](#)
- Cisco IOS NSF-aware
 - support [13-2](#)
- Cisco IOS NSF-capable support [13-2](#)
- Cisco IP Phones
 - configuring [43-3](#)
 - sound quality [43-1](#)
- Cisco TrustSec
 - credentials [45-10](#)
 - switch-to-switch security
 - 802.1x mode [45-11](#)
 - configuration example [45-14](#)
 - manual mode [45-12](#)
- Cisco TrustSec Network Device Admission Control
 - See NDAC
- CiscoWorks 2000 [62-4](#)
- CIST
 - description [22-22](#)
- civic location [31-3](#)
- class level, configure in a service policy [42-31, 42-65](#)
- class of service
 - See CoS
- clear cdp counters command [30-4](#)
- clear cdp table command [30-3](#)
- clear counters command [8-36](#)
- clearing
 - Ethernet CFM [65-31](#)
 - IP multicast table entries [37-28](#)
- clear ip eigrp neighbors command [34-19](#)
- CLI
 - accessing [2-2](#)
 - backing out one level [2-5](#)
 - getting commands [2-5](#)
 - history substitution [2-4](#)

- managing clusters [16-13](#)
- modes [2-5](#)
- monitoring environments [57-1](#)
- ROM monitor [2-7](#)
- software basics [2-4](#)
- client processes, tracking [59-1](#)
- clients
 - in 802.1X authentication [46-3](#)
- clock
 - See system clock
- clustering switches
 - command switch characteristics and VTY [16-12](#)
 - convert to a community [16-10](#)
 - managing
 - through CLI [16-13](#)
 - overview [16-2](#)
 - planning considerations
 - CLI [16-13](#)
 - passwords [16-8](#)
- CoA Request Commands [46-100](#)
- command-line processing [2-3](#)
- command modes [2-5](#)
- commands
 - b [73-3](#)
 - b flash [73-3](#)
 - boot [73-3](#)
 - confreg [73-3](#)
 - dev [73-3](#)
 - dir device [73-3](#)
 - frame [73-5](#)
 - i [73-3](#)
 - listing [2-5](#)
 - meminfo [73-5](#)
 - reset [73-3](#)
 - ROM monitor [73-2 to 73-3](#)
 - ROM monitor debugging [73-5](#)
 - SNMP [72-4](#)
 - sysret [73-5](#)
- command switch, cluster
 - requirements [16-11](#)
- common and internal spanning tree
 - See CIST
- common spanning tree
 - See CST
- community of switches
 - access modes in Network Assistant [16-9](#)
 - adding devices [16-9](#)
 - communication protocols [16-8](#)
 - community name [16-8](#)
 - configuration information [16-9](#)
 - converting from a cluster [16-10](#)
 - host name [16-8](#)
 - passwords [16-8](#)
- community ports [44-3](#)
- community strings
 - configuring [62-7](#)
 - overview [62-4](#)
- community VLANs [44-2, 44-3](#)
 - configure as a PVLAN [44-15](#)
- compiling MIBs [72-4](#)
- config-register command [3-29](#)
- config terminal command [3-9](#)
- configurable leave timer,IGMP [27-4](#)
- configuration examples
 - SNMP [62-15](#)
- configuration files
 - limiting TFTP server access [62-15](#)
 - obtaining with DHCP [3-6](#)
 - saving [3-10](#)
 - system contact and location information [62-14](#)
- configuration guidelines
 - CFM [65-7, 66-4](#)
 - Ethernet OAM [65-35](#)
 - REP [24-7](#)
 - SNMP [62-6](#)
 - VLAN mapping [29-10](#)
- configuration register

- boot fields
 - listing value [3-29](#)
 - modifying [3-28](#)
 - changing from ROM monitor [73-3](#)
 - changing settings [3-28 to 3-29](#)
 - configuring [3-26](#)
 - settings at startup [3-27](#)
 - configure class-level queue-limit in a service policy [42-31, 42-65](#)
 - configure terminal command [3-29, 8-2](#)
 - configuring access-group mode on Layer 2 interface [53-31](#)
 - configuring flow control [8-23](#)
 - configuring interface link and trunk status events [8-37](#)
 - configuring named IPv6 ACLs [53-16](#)
 - configuring named MAC extended ACLs [53-14, 53-15](#)
 - configuring unicast MAC address filtering [53-13](#)
 - configuring VLAN maps [53-17](#)
 - confreg command [73-3](#)
 - Connectivity Fault Management
 - See CFM
 - console configuration mode [2-5](#)
 - console download [73-4 to 73-5](#)
 - console port
 - disconnecting user sessions [9-7](#)
 - monitoring user sessions [9-6](#)
 - contact information
 - assigning for call home [67-4](#)
 - controlling switch access with RADIUS [46-95](#)
 - Control Plane Policing
 - and Layer 2 Control packet QoS, configuration example [50-14](#)
 - configuration guidelines and restrictions [50-8](#)
 - configuring for control plane traffic [50-4](#)
 - configuring for data plane and management plan traffic [50-5](#)
 - defaults [50-4](#)
 - general guidelines [50-3](#)
 - monitoring [50-9](#)
 - understanding [50-2](#)
 - control protocol, IP SLAs [68-4](#)
 - convergence
 - REP [24-4](#)
 - copy running-config startup-config command [3-10](#)
 - copy system:running-config nvram:startup-config command [3-32](#)
 - core system filter, Wireshark [58-6](#)
 - CoS
 - definition [42-3](#)
 - figure [42-2](#)
 - overriding on Cisco IP Phones [43-5](#)
 - priority [43-5](#)
 - counters
 - clearing MFIB [37-28](#)
 - clearing on interfaces [8-36](#)
 - CPU, impact of ACL processing [53-12](#)
 - CPU port sniffing [57-10](#)
 - crashfiles information, archiving [2-8](#)
 - Critical Authentication
 - configure with 802.1X [46-62](#)
 - crosscheck, CFM [65-5, 65-11](#)
 - CST
 - description [22-25](#)
 - IST and [22-22](#)
 - MST and [22-22](#)
 - customer edge devices [41-2](#)
 - C-VLAN [1-2, 29-7](#)
-
- ## D
- database agent
 - configuration examples [52-15](#)
 - enabling the DHCP Snooping [52-13](#)
 - daylight saving time [4-13](#)
 - debug commands, ROM monitor [73-5](#)
 - decoding and displaying packets, Wireshark [58-9](#)
 - default configuration
 - 802.1X [46-27](#)
 - banners [4-24](#)

- DNS [4-23](#)
- Ethernet OAM [65-35](#)
- IGMP filtering [27-30](#)
- IGMP snooping [28-5, 28-6](#)
- IP SLAs [68-6](#)
- IPv6 [54-7](#)
- Layer 2 protocol tunneling [29-16](#)
- LLDP [31-5](#)
- MAC address table [4-30](#)
- MVR [27-23](#)
- NTP [4-4](#)
- private VLANs [44-12](#)
- RADIUS [46-103](#)
- REP [24-7](#)
- resetting the interface [8-40](#)
- RMON [69-3](#)
- SNMP [62-5](#)
- SPAN and RSPAN [57-6](#)
- system message logging [60-3](#)
- TACACS+ [3-18](#)
- VLAN mapping [29-9](#)
- Y.1731 [65-29](#)
- default gateway
 - configuring [3-11](#)
 - verifying configuration [3-11](#)
- default settings, erase command [3-32](#)
- default web-based authentication configuration
 - 802.1X [48-6](#)
- defining/modifying/deleting a capture point, Wireshark [58-12](#)
- denial-of-service attacks
 - IP address spoofing, mitigating [36-5](#)
 - Unicast RPF, deploying [36-5](#)
- denying access to a server on another VLAN [53-23](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports [8-12, 8-13](#)
- deploying 10-Gigabit Ethernet and a Gigabit Ethernet SFP ports on WS-X4606-10GE-E and Sup 6-E [8-13](#)
- description command [8-23](#)
- dev command [73-3](#)
- device discovery protocol [31-1](#)
- device IDs
 - call home format [67-21, 67-22](#)
- device sensor
 - configuring [46-118](#)
- DHCP
 - configuring
 - rate limit for incoming packets [52-13](#)
 - denial-of-service attacks, preventing [52-13](#)
 - rate limiting of packets
 - configuring [52-13](#)
- DHCP-based autoconfiguration
 - client request message exchange [3-3](#)
 - configuring
 - client side [3-3](#)
 - DNS [3-5](#)
 - relay device [3-5](#)
 - server-side [3-4](#)
 - TFTP server [3-4](#)
 - example [3-7](#)
 - lease options
 - for IP address information [3-4](#)
 - for receiving the configuration file [3-4](#)
 - overview [3-2](#)
 - relationship to BOOTP [3-3](#)
- DHCP option 82
 - identifying a port with [38-4](#)
 - overview [52-4](#)
- DHCP Snooping
 - enabling, and Option 82 [52-10](#)
- DHCP snooping
 - accepting untrusted packets from edge switch [52-10](#)
 - configuring [52-6](#)
 - default configuration [52-7](#)
 - displaying binding tables [52-19](#)
 - displaying configuration [52-19](#)
 - displaying information [52-18](#)
 - enabling [52-7](#)
 - enabling on private VLAN [52-12](#)

- enabling on the aggregation switch [52-9](#)
- enabling the database agent [52-13](#)
- message exchange process [52-4](#)
- monitoring [52-23](#)
- option 82 data insertion [52-4](#)
- overview [52-1](#)
- Snooping database agent [52-2](#)
- DHCP Snooping Database Agent
 - adding to the database (example) [52-18](#)
 - enabling (example) [52-15](#)
 - overview [52-2](#)
 - reading from a TFTP file (example) [52-17](#)
- Diagnostics
 - online [70-1](#)
 - Power-On-Self-Test
 - causes of failure [70-20](#)
 - how it works [70-10](#)
 - overview [70-10](#)
 - Power-On-Self-Test for Supervisor Engine V-10GE [70-13](#)
- Differentiated Services Code Point values
 - See DSCP values
- DiffServ architecture, QoS [42-2](#)
- Digital optical monitoring transceiver support [8-19](#)
- dir device command [73-3](#)
- disabled state
 - RSTP comparisons (table) [22-24](#)
- disabling
 - broadcast storm control [56-5](#)
- disabling multicast storm control [56-5](#)
- disconnect command [9-7](#)
- discovery, clusters
 - See automatic discovery
- discovery, Ethernet OAM [65-34](#)
- display dection and removal events [15-7](#)
- display filter, Wireshark [58-7](#)
- displaying
 - Auth Manager summary for an interface [46-126](#)
 - MAB details [46-128](#)
 - summary of all Auth manager sessions [46-126](#)
 - summary of all Auth manager sessions on the switch authorized for a specified authentication method [46-126](#)
 - displaying EtherChannel to a Virtual Switch System [26-16](#)
 - displaying storm control [56-6](#)
 - displaying Wireshark information [58-14](#)
 - display PoE consumed by a module [15-8](#)
 - display PoE detection and removal events [15-7](#)
- DNS
 - and DHCP-based autoconfiguration [3-5](#)
 - default configuration [4-23](#)
 - displaying the configuration [4-24](#)
 - overview [4-22](#)
 - setting up [4-23](#)
- domain names
 - DNS [4-22](#)
- Domain Name System
 - See DNS
- double-tagged packets
 - 802.1Q tunneling [29-2](#)
 - Layer 2 protocol tunneling [29-15](#)
- downloading MIBs [72-3, 72-4](#)
- drop threshold for Layer 2 protocol packets [29-16](#)
- DSCP values
 - definition [42-4](#)
 - IP precedence [42-2](#)
- Dual_Active Detection
 - using Enhanced PAgP [5-23](#)
- Dual-Active Detection, using Fast-Hello [5-24](#)
- duplex command [8-22](#)
- duplex mode
 - configuring interface [8-20](#)
- dynamic ARP inspection
 - ARP cache poisoning [51-2](#)
 - configuring
 - ACLs for non-DHCP environments [51-11](#)
 - in DHCP environments [51-5](#)
 - log buffer [51-14](#)

- rate limit for incoming ARP packets [51-16](#)
- denial-of-service attacks, preventing [51-16](#)
- interface trust state, security coverage [51-3](#)
- log buffer
 - configuring [51-14](#)
- logging of dropped packets [51-4](#)
- overview [51-1](#)
- port channels, their behavior [51-5](#)
- priority of static bindings [51-4](#)
- purpose of [51-2](#)
- rate limiting of ARP packets [51-4](#)
 - configuring [51-16](#)
- validation checks, performing [51-19](#)

Dynamic Host Configuration Protocol snooping

- See DHCP snooping

dynamic port VLAN membership

- example [17-29](#)
- limit on hosts [17-28](#)
- reconfirming [17-26](#)
- troubleshooting [17-28](#)

E

EAP frames

- changing retransmission time [46-85](#)
- exchanging (figure) [46-4](#), [46-6](#), [46-13](#)
- request/identity [46-4](#)
- response/identity [46-4](#)
- setting retransmission number [46-86](#)

EAPOL frames

- 802.1X authentication and [46-3](#)
- OTP authentication, example (figure) [46-4](#), [46-13](#)
- start [46-4](#)

Echo mode, configuring BFD [39-15](#)

edge ports

- description [22-27](#)

EGP

- overview [1-17](#)

EIGRP

- configuration examples [34-19](#)
- monitoring and maintaining [34-19](#)

EIGRP (Enhanced IGRP)

- stub routing
 - benefits [34-17](#)
 - configuration tasks [34-18](#)
 - configuring [34-14](#)
 - overview [34-14](#)
 - restrictions [34-17](#)
 - verifying [34-18](#)

EIGRP (enhanced IGRP)

- overview [1-17](#)

eigrp stub command [34-18](#)

EIGRP stub routing, configuring [34-13](#)

ELIN location [31-3](#)

e-mail addresses

- assigning for call home [67-4](#)

e-mail notifications

- Call Home [1-24](#), [67-2](#)

Embedded CiscoView

- displaying information [4-48](#)
- installing and configuring [4-45](#)
- overview [4-45](#)

emergency alarms on Sup Engine 6-E systems [14-5](#)

enable command [3-9](#), [3-28](#)

enable mode [2-5](#)

enabling SNMP [72-4](#), [72-5](#)

encryption keying [45-2](#)

encryption keys, MKA [45-2](#)

Enhanced Interior Gateway Routing Protocol

- See EIGRP

enhanced object tracking

- defined [59-1](#)
- IP routing state [59-2](#)
- line-protocol state [59-2](#)
- tracked lists [59-3](#)

Enhanced PoE support on E-series [15-15](#)

Enhanced PoE support on E-series, configuring Universal PoE [15-16](#)

- environmental monitoring
 - using CLI commands [14-1](#)
 - EPM logging [46-129](#)
 - errdisable recovery
 - configuring [15-14](#)
 - EtherChannel
 - channel-group group command [5-46, 26-8, 26-10](#)
 - configuration guidelines [5-30, 26-5](#)
 - configuring [26-6 to 26-16](#)
 - configuring (tasks) [5-30](#)
 - configuring Layer 2 [26-10](#)
 - configuring Layer 3 [26-7](#)
 - DFC restriction, see CSCdt27074 in the Release Notes
 - displaying to a virtual switch system [26-16](#)
 - interface port-channel command [26-7](#)
 - lACP system-priority
 - command example [26-13](#)
 - modes [26-3](#)
 - overview [26-2](#)
 - PAgP
 - Understanding [26-4](#)
 - physical interface configuration [5-46, 26-7](#)
 - port-channel interfaces [26-2](#)
 - port-channel load-balance command [26-14](#)
 - removing [26-15](#)
 - removing interfaces [26-15](#)
 - understanding [5-2](#)
 - EtherChannel guard
 - disabling [25-6](#)
 - enabling [25-6](#)
 - overview [25-6](#)
 - Ethernet management port
 - and routing [8-6](#)
 - and routing protocols [8-6](#)
 - configuring [8-10](#)
 - default setting [8-6](#)
 - described [1-29, 8-6](#)
 - for network management [1-29, 8-6](#)
 - specifying [8-10](#)
 - supported features [8-10](#)
 - unsupported features [8-10](#)
 - Ethernet management port, internal
 - and routing protocols [8-6](#)
 - Ethernet Management Port, using [8-6](#)
 - Ethernet OAM [65-34](#)
 - and CFM interaction [65-51](#)
 - configuration guidelines [65-35](#)
 - configuring with CFM [65-51](#)
 - default configuration [65-35](#)
 - discovery [65-34](#)
 - enabling [65-36, 65-52](#)
 - link monitoring [65-34, 65-38](#)
 - messages [65-34](#)
 - protocol
 - defined [65-33](#)
 - monitoring [65-49](#)
 - remote failure indications [65-34](#)
 - remote loopback [65-34, 65-37](#)
 - templates [65-45](#)
 - Ethernet OAM protocol CFM notifications [65-51](#)
 - Ethernet Remote Defect Indication (ETH-RDI) [65-28](#)
 - event triggers, user-defined
 - configuring, 802.1X-based [21-8](#)
 - configuring, MAC address-based [21-9](#)
 - explicit host tracking
 - enabling [27-11](#)
 - extended range VLANs
 - See VLANs
 - Extensible Authentication Protocol over LAN [46-2](#)
 - Exterior Gateway Protocol
 - See EGP
-
- ## F
- Fa0 port
 - See Ethernet management port
 - Failure detection, using BFD [39-7](#)
 - Fallback Authentication

- configure with 802.1X [46-77](#)
- FastDrop
 - overview [37-11](#)
- fastethernet0 port
 - See Ethernet management port
- Fast-Hello
 - dual-active detection [5-24](#)
- Fast-Hello dual-active detection, configuring [5-50](#)
- fast link notification
 - on VSL failure [5-14](#)
- Fast UDLD
 - configuring probe message interval [32-8](#)
 - default configuration [32-4](#)
 - displaying link status [32-9](#)
 - enabling globally [32-5](#)
 - enabling on individual interface [32-7](#)
 - enabling per-interface [32-6](#)
 - modes of operation [32-3](#)
 - resetting disabled LAN interfaces [32-8](#)
 - use case [32-2](#)
- Fast UDLD, overview [32-1](#)
- feature interactions, Wireshark [58-10](#)
- FIB
 - description [35-2](#)
 - See also MFIB
- fiber-optics interfaces
 - disabling UDLD [32-7](#)
- Filter-ID ACL and Per-User ACL, configureport-based authentication
 - configure Per-User ACL and Filter-ID ACL [46-45](#)
- filtering
 - in a VLAN [53-18](#)
 - non-IP traffic [53-14](#), [53-15](#)
- filters, Wireshark [58-6](#)
- flags [37-12](#)
- Flash memory
 - configuring router to boot from [3-31](#)
 - loading system images from [3-30](#)

- security precautions [3-31](#)
- Flexible NetFlow
 - caveats [64-1](#), [64-7](#)
 - defined [1-4](#), [64-1](#)
- Flex Links
 - configuration guidelines [23-6](#)
 - configuring [23-6](#), [23-7](#)
 - configuring preferred VLAN [23-9](#)
 - configuring VLAN load balancing [23-8](#)
 - monitoring [23-12](#)
- flooded traffic, blocking [55-2](#)
- flowchart, traffic marking procedure [42-21](#), [42-55](#)
- flow control, configuring [8-23](#)
- For [15-13](#)
- forward-delay time (STP)
 - configuring [22-19](#)
- forwarding information base
 - See FIB
- frame command [73-5](#)

G

- gateway
 - See default gateway
- get-bulk-request operation [62-3](#)
- get-next-request operation [62-3](#), [62-4](#)
- get-request operation [62-3](#), [62-4](#)
- get-response operation [62-3](#)
- Gigabit Ethernet SFP ports
 - deploy with 10-Gigabit Ethernet [8-12](#), [8-13](#)
- GLBP, introduction [1-15](#)
- global configuration mode [2-5](#)
- Guest-VLANs
 - configure with 802.1X [46-57](#)

H

- hardware and software ACL support [53-6](#)
- hardware switching [35-5](#)

- hello time (STP)
 - configuring [22-17](#)
 - high CPU due to ACLs, troubleshooting [53-6](#)
 - history
 - CLI [2-4](#)
 - history table, level and number of syslog messages [60-9](#)
 - hop counts
 - configuring MST bridges [22-28](#)
 - host
 - limit on dynamic port [17-28](#)
 - host modes, MACsec [45-3](#)
 - host ports
 - kinds of [44-4](#)
 - host presence CDP message [46-8](#)
 - Hot Standby Routing Protocol
 - See HSRP
 - HSRP
 - description [1-16](#)
 - HSRP, introduction [1-16](#)
 - hw-module module num power command [14-22](#)
-
- ICMP
 - enabling [9-12](#)
 - ping [9-7](#)
 - running IP traceroute [9-9](#)
 - time exceeded messages [9-9](#)
 - ICMP Echo operation
 - configuring [68-11](#)
 - IP SLAs [68-11](#)
 - i command [73-3](#)
 - IDS
 - using with SPAN and RSPAN [57-2](#)
 - IEEE 802.1ag [65-2](#)
 - IEEE 802.1s
 - See MST
 - IEEE 802.1w
 - See MST
 - IEEE 802.3ad
 - See LACP
 - IGMP
 - configurable-leave timer [27-4](#)
 - description [37-3](#)
 - enabling [37-14](#)
 - explicit host tracking [27-4](#)
 - immediate-leave processing [27-3](#)
 - leave processing, enabling [28-8](#)
 - overview [27-2](#)
 - report suppression
 - disabling [28-10](#)
 - IGMP filtering
 - configuring [27-31](#)
 - default configuration [27-30](#)
 - described [27-30](#)
 - monitoring [27-34](#)
 - IGMP groups
 - setting the maximum number [27-33](#)
 - IGMP Immediate Leave
 - configuration guidelines [27-9](#)
 - IGMP profile
 - applying [27-32](#)
 - configuration mode [27-31](#)
 - configuring [27-31](#)
 - IGMP Snooping
 - configure
 - leave timer [27-9](#)
 - configuring
 - Learning Methods [27-7](#)
 - static connection to a multicast router [27-8](#)
 - configuring host statically [27-11](#)
 - enabling
 - Immediate-Leave processing
 - explicit host tracking [27-11](#)
 - suppressing multicast flooding [27-12](#)
 - IGMP snooping
 - configuration guidelines [27-5](#)
 - default configuration [28-5, 28-6](#)

- enabling
 - globally [27-6](#)
 - on a VLAN [27-6](#)
- enabling and disabling [28-6](#)
- IP multicast and [37-4](#)
- monitoring [27-14, 28-10](#)
- overview [27-2](#)
- IGMP Snooping, displaying
 - group [27-16](#)
 - hot membership [27-15](#)
 - how to [27-15](#)
 - MAC address entries [27-18](#)
 - multicast router interfaces [27-17](#)
 - on a VLAN interface [27-18](#)
 - Querier information [27-19](#)
- IGMPSnooping Querier, configuring [27-10](#)
- Immediate Leave, IGMP
 - enabling [28-8](#)
- immediate-leave processing
 - enabling [27-8](#)
 - IGMP
 - See fast-leave processing
- ingress packets, SPAN enhancement [57-12](#)
- inline power
 - configuring on Cisco IP phones [43-5](#)
- insufficient inline power handling for Supervisor Engine II-TS [14-22](#)
- Intelligent Power Management [15-4](#)
- interacting with Baby Giants [8-29](#)
- interface
 - displaying operational status [15-6](#)
- interface command [3-9, 8-2](#)
- interface configuration
 - REP [24-10](#)
- interface link and trunk status events
 - configuring [8-37](#)
- interface port-channel command [5-45, 26-7](#)
- interface range command [8-4](#)
- interface range macro command [8-11](#)
- interfaces
 - adding descriptive name [8-23](#)
 - clearing counters [8-36](#)
 - configuring [8-2](#)
 - configuring ranges [8-4](#)
 - displaying information about [8-36](#)
 - Layer 2 modes [19-3](#)
 - maintaining [8-35](#)
 - monitoring [8-35](#)
 - naming [8-23](#)
 - numbers [8-2](#)
 - overview [8-2](#)
 - restarting [8-37](#)
 - See also Layer 2 interfaces
 - using the Ethernet Management Port [8-6](#)
- Internet Control Message Protocol
 - See ICMP
- Internet Group Management Protocol
 - See IGMP
- Internet Protocol version 6
 - See IPv6
- introduction
 - 802.1X Identity-Based Network Security, list of supported features [1-34](#)
 - Bidirectional Forwarding Detection [1-14](#)
 - Cisco Call Home [1-24](#)
 - Cisco Energy Wise [1-24](#)
 - Cisco Express Forwarding [1-14](#)
 - Cisco IOS IP Service Level Agreements [1-24](#)
 - Cisco IOS Mediatrace and Performance Monitor [1-26](#)
 - Cisco Medianet AutoQoS [1-25](#)
 - Cisco Medianet Flow Metadata [1-26](#)
 - Cisco Media Services Proxy [1-25](#)
 - Cisco TrustSec MACsec Encryption [1-35](#)
 - Cisco TrustSec Security Architecture [1-36](#)
 - Debugging Features (platform and debug platform) [1-43](#)
 - Device Sensor [1-14](#)
 - Dynamic Host Control Protocol [1-28](#)

- Easy Virtual Network [1-28](#)
- EIGRP Stub routing [1-14](#)
- Embedded Event Manager [1-29](#)
- Enhanced Object Tracking [1-15](#)
- EtherChannel bundles [1-3](#)
- Ethernet CFM [1-3](#)
- Ethernet Management Port [1-29](#)
- Ethernet OAM Protocol [1-3](#)
- FAT File Management System (Sup 60-E, 6L-E, 4948E, and 4900M) [1-30](#)
- File System Management (Sup 7-E and 7L-E) [1-29](#)
- Flexible Netflow (Sup 7-E and 7L-E) [1-4](#)
- Flex Link and MAC Address-Table Move Update [1-4](#)
- GLBP [1-15](#)
- hard-based Control Plane Policing [1-37](#)
- HSRP [1-16](#)
- In Service Software Upgrade [1-19](#)
- Intelligent Power Management [1-30](#)
- Internet Group Management Protocol (IGMP) Snooping [1-4](#)
- IP Routing protocols [1-17](#)
- IP Source Guard [1-38](#)
- IP Source Guard or Static Hosts [1-38](#)
- IPv6 [1-19](#)
- IPv6 First Hop Security [1-39](#)
- IPv6 Multicast BSR and BSR Scoped Zone Support, introduction [1-5](#)
- IPv6 Multicast Listen Discovery (MLD) and Multicast Listen Discovery Snooping [1-6](#)
- IS-IS [1-18](#)
- Jumbo Frame [1-6](#)
- Layer 2 traceroute [1-43](#)
- Link Aggregation Control Protocol [1-7](#)
- MAC Address Notification [1-30](#)
- NAC
 - Layer 2 802.1X authentication [1-40](#)
 - Layer 2 IP validation [1-40](#)
- NetFlow-lite [1-30](#)
- Network Security with ACLs (IP ACLs, MAC ACLs, Port ACLs, Router, ACLs, and VLAN ACLs) [1-41](#)
- NSF with SSO [1-20](#)
- OSPF [1-18](#)
- OSPF for Routed Access [1-21](#)
- Port Security [1-41](#)
- Power over Ethernet [1-31](#)
- RIP [1-19](#)
- Simple Network Management Protocol [1-31](#)
- SPAN and RSPAN [1-32](#)
- Time Domain Reflectometry [1-43](#)
- Unicast Reverse Path Forwarding [1-22](#)
- Universal Power over Ethernet [1-32](#)
- Virtual Router Redundancy Protocol [1-22](#)
- VRF-lite [1-22](#)
- Web-based Authentication [1-43](#)
- Web Content Coordination Protocol [1-32](#)
- Wireshark [1-33](#)
- XML-PI [1-33](#)
- Intrusion Detection System
 - See IDS
- inventory management TLV [31-3, 31-9](#)
- IOS shell
 - See Auto SmartPorts macros
- IP
 - configuring default gateway [3-11](#)
 - configuring static routes [3-11](#)
 - displaying statistics [35-8](#)
- IP addresses
 - 128-bit [54-2](#)
 - cluster candidate or member [16-12](#)
 - cluster command switch [16-11](#)
 - discovering [4-44](#)
 - IPv6 [54-2](#)
- ip cef command [35-6, 70-2](#)
- IP Enhanced IGRP
 - interfaces, displaying [34-19](#)
- ip icmp rate-limit unreachable command [9-12](#)
- ip igmp profile command [27-31](#)
- ip igmp snooping tcn flood command [27-13](#)
- ip igmp snooping tcn flood query count command [27-14](#)

- ip igmp snooping tcn query solicit command [27-14](#)
- IP information
 - assigned
 - through DHCP-based autoconfiguration [3-2](#)
- ip load-sharing per-destination command [35-7](#)
- ip local policy route-map command [40-8](#)
- ip mask-reply command [9-13](#)
- IP MTU sizes,configuring [34-9](#)
- IP multicast
 - clearing table entries [37-28](#)
 - configuring [37-13](#)
 - default configuration [37-13](#)
 - displaying PIM information [37-23](#)
 - displaying the routing table information [37-24](#)
 - enabling dense-mode PIM [37-15](#)
 - enabling sparse-mode [37-15](#)
 - features not supported [37-13](#)
 - hardware forwarding [37-9](#)
 - IGMP snooping and [27-5, 37-4](#)
 - overview [37-1](#)
 - routing protocols [37-2](#)
 - software forwarding [37-9](#)
 - See also Auto-RP; IGMP; PIM; RP; RPF
- IP multicast routing
 - enabling [37-14](#)
 - monitoring and maintaining [37-23](#)
- ip multicast-routing command [37-14](#)
- IP multicast traffic, load splitting [37-22](#)
- IP phones
 - configuring voice ports [43-3](#)
 - See Cisco IP Phones [43-1](#)
- ip pim command [37-15](#)
- ip pim dense-mode command [37-15](#)
- ip pim sparse-dense-mode command [37-16](#)
- ip policy route-map command [40-7](#)
- IP Port Security for Static Hosts
 - on a Layer 2 access port [52-25](#)
 - on a PVLAN host port [52-28](#)
 - overview [52-24](#)
- ip redirects command [9-13](#)
- IP routing tables
 - deleting entries [37-28](#)
- IPsec VPN, introduction [1-38](#)
- IP Service Level Agreements
 - See IP SLAs
- IP service levels, analyzing [68-1](#)
- IP SLAs
 - benefits [68-2](#)
 - CFM endpoint discovery [65-21](#)
 - configuration guidelines [68-7](#)
 - Control Protocol [68-4](#)
 - default configuration [68-6](#)
 - definition [68-1](#)
 - ICMP echo operation [68-11](#)
 - manually configuring CFM ping or jitter [65-19](#)
 - measuring network performance [68-3](#)
 - multioperations scheduling [68-5](#)
 - operation [68-3](#)
 - reachability tracking [59-9](#)
 - responder
 - described [68-4](#)
 - enabling [68-7](#)
 - response time [68-4](#)
 - scheduling [68-5](#)
 - SNMP support [68-2](#)
 - supported metrics [68-2](#)
 - threshold monitoring [68-6](#)
 - track state [59-9](#)
 - UDP jitter operation [68-8](#)
- IP Source Guard
 - configuring [52-20](#)
 - configuring on private VLANs [52-22](#)
 - displaying [52-22, 52-23](#)
 - overview [52-23](#)
- IP statistics
 - displaying [35-8](#)
- IP traceroute
 - executing [9-9](#)

- overview [9-8](#)
 - IP unicast
 - displaying statistics [35-8](#)
 - IP Unnumbered support
 - configuring on a range of Ethernet VLANs [18-5](#)
 - configuring on LAN and VLAN interfaces [18-4](#)
 - configuring with connected host polling [18-6](#)
 - DHCP Option 82 [18-2](#)
 - displaying settings [18-7](#)
 - format of agent remote ID suboptions [18-2](#)
 - troubleshooting [18-8](#)
 - with connected host polling [18-3](#)
 - with DHCP server and Relay agent [18-2](#)
 - ip unreachable command [9-12](#)
 - IPv4, IPv6, and MAC ACLs, configuring on a Layer 2 interface [53-29](#)
 - IPv6
 - addresses [54-2](#)
 - default configuration [54-7](#)
 - defined [1-19, 54-1](#)
 - Enhanced Interior Gateway Routing Protocol (EIGRP) IPv6 [54-6](#)
 - Router ID [54-6](#)
 - OSPF [54-6](#)
 - IPv6 control traffic, policing [50-16](#)
 - IPv6 First Hop Security, introduction [1-39](#)
 - IPX
 - redistribution of route information with EIGRP [1-17](#)
 - is [29-19](#)
 - IS-IS, introduction [1-18](#)
 - ISL
 - trunking with 802.1Q tunneling [29-4](#)
 - isolated port [44-4](#)
 - isolated VLANs [44-2, 44-3, 44-4](#)
 - ISSU
 - compatibility matrix [5-59, 6-14, 7-13](#)
 - compatibility verification using Cisco Feature Navigator [5-60, 6-15, 7-14](#)
 - NSF overview [6-3, 7-3](#)
 - perform the process
 - aborting a software upgrade [5-76, 6-34, 7-33](#)
 - configuring the rollback timer as a safeguard [5-77, 6-35, 7-35](#)
 - displaying a compatibility matrix [5-79, 6-36, 6-40, 7-36](#)
 - loading the new software on the new standby [5-69, 6-27, 7-26](#)
 - stopping the rollback timer [5-68, 6-26, 7-25](#)
 - switching to the standby [5-66, 6-24, 7-23](#)
 - verify the ISSU state [5-63, 6-20, 7-20](#)
 - verify the redundancy mode [5-62, 6-19, 7-19](#)
 - verify the software installation [5-61, 6-18, 7-18](#)
 - vload the new software on standby [5-65, 6-21, 7-21](#)
 - prerequisites [5-55, 6-2, 7-2](#)
 - process overview [6-6, 7-6](#)
 - restrictions [5-55, 6-2, 7-2](#)
 - SNMP support [6-15, 7-14](#)
 - SSO overview [6-3, 7-3](#)
 - versioning capability in software to support [6-13](#)
 - IST
 - and MST regions [22-22](#)
 - description [22-22](#)
 - master [22-27](#)
 - ITU-T Y.1731
 - See Y.1731
-
- ## J
-
- jumbo frames
 - and ethernet ports [8-27](#)
 - configuring MTU sizes for [8-28](#)
 - ports and linecards that support [8-26](#)
 - understanding MTUs [8-26](#)
 - understanding support [8-26](#)
 - VLAN interfaces [8-28](#)
-
- ## K
-
- keyboard shortcuts [2-3](#)

- L**
- l2protocol-tunnel command [29-17](#)
 - labels, definition [42-3](#)
 - LACP
 - system ID [26-4](#)
 - Layer 2 access ports [19-7](#)
 - Layer 2 Control Packet QoS
 - and CoPP configuration example [50-14](#)
 - default configuration [50-11](#)
 - disabling [50-13](#)
 - enabling [50-12](#)
 - guideline and restrictions [50-16](#)
 - understanding [50-11](#)
 - Layer 2 frames
 - classification with CoS [42-2](#)
 - Layer 2 interface
 - applying ACLs [53-31](#)
 - configuring access-mode mode on [53-31](#)
 - configuring IPv4, IPv6, and MAC ACLs [53-29](#)
 - displaying an ACL configuration [53-32](#)
 - Layer 2 interfaces
 - assigning VLANs [17-7](#)
 - configuring [19-5](#)
 - configuring as PVLAN host ports [44-18](#)
 - configuring as PVLAN promiscuous ports [44-17](#)
 - configuring as PVLAN trunk ports [44-19](#)
 - defaults [19-4](#)
 - disabling configuration [19-8](#)
 - modes [19-3](#)
 - show interfaces command [19-6](#)
 - Layer 2 interface type
 - resetting [44-24](#)
 - setting [44-24](#)
 - Layer 2 protocol tunneling
 - default configuration [29-16](#)
 - guidelines [29-16](#)
 - Layer 2 switching
 - overview [19-1](#)
 - Layer 2 Traceroute
 - and ARP [9-10](#)
 - and CDP [9-10](#)
 - host-to-host paths [9-10](#)
 - IP addresses and subnets [9-10](#)
 - MAC addresses and VLANs [9-10](#)
 - multicast traffic [9-10](#)
 - multiple devices on a port [9-10](#)
 - unicast traffic [1-43, 9-9](#)
 - usage guidelines [9-10](#)
 - Layer 2 trunks
 - configuring [19-5](#)
 - overview [19-3](#)
 - Layer 3 interface, applying IPv6 ACLs [53-17](#)
 - Layer 3 interface counters,configuring [34-10](#)
 - Layer 3 interface counters,understanding [34-3](#)
 - Layer 3 interfaces
 - changing from Layer 2 mode [41-16](#)
 - configuration guidelines [34-5](#)
 - configuring VLANs as interfaces [34-7](#)
 - overview [34-1](#)
 - counters [34-3](#)
 - logical [34-2](#)
 - physical [34-2](#)
 - SVI autostate exclude [34-3](#)
 - Layer 3 packets
 - classification methods [42-2](#)
 - Layer 4 port operations
 - configuration guidelines [53-11](#)
 - restrictions [53-10](#)
 - Leave timer, enabling [27-9](#)
 - licenses, managing with PRTU [4-14](#)
 - limitations on using a TwinGig Convertor [8-14](#)
 - Link Aggregation Control Protocol, introduction [1-7](#)
 - link and trunk status events
 - configuring interface [8-37](#)
 - link integrity, verifying with REP [24-4](#)
 - Link Layer Discovery Protocol
 - See CDP

link monitoring, Ethernet OAM [65-34, 65-38](#)

link-state tracking

configuration guidelines [26-21](#)

default configuration [26-21](#)

described [26-18](#)

displaying status [26-22](#)

generic configuration procedure [26-21](#)

link status, displaying UDLD [32-9](#)

listening state (STP)

RSTP comparisons (table) [22-24](#)

LLDP

configuring [31-4](#)

characteristics [31-5](#)

default configuration [31-5](#)

disabling and enabling

globally [31-6](#)

on an interface [31-7](#)

monitoring and maintaining [31-14](#)

overview [31-1](#)

transmission timer and holdtime, setting [31-5](#)

LLDP-MED

configuring

procedures [31-4](#)

TLVs [31-9, 31-11](#)

monitoring and maintaining [31-14](#)

overview [31-1](#)

supported TLVs [31-2](#)

LLDP Media Endpoint Discovery

See LLDP-MED

load balancing

configuring for CEF [35-7](#)

configuring for EtherChannel [26-14](#)

overview [26-5, 35-6](#)

per-destination [35-7](#)

load splitting IP multicast traffic [37-22](#)

Location Service

overview [31-1](#)

location service

configuring [31-12](#)

understanding [31-3](#)

location TLV [31-3, 31-9](#)

logging, EPM [46-129](#)

Logical Layer 3 interfaces

configuring [34-6](#)

logical layer 3 VLAN interfaces [34-2](#)

login authentication

with RADIUS [46-106](#)

with TACACS+ [3-19](#)

login banners [4-24](#)

login timer

changing [9-6](#)

logoutwarning command [9-6](#)

loop guard

and MST [22-23](#)

configuring [25-4](#)

overview [25-3](#)

M

MAC/PHY configuration status TLV [31-2](#)

MAC addresses

aging time [4-30](#)

allocating [22-6](#)

and VLAN association [4-29](#)

building tables [4-28, 19-2](#)

convert dynamic to sticky secure [49-5](#)

default configuration [4-30](#)

disabling learning on a VLAN [4-39](#)

discovering [4-44](#)

displaying [9-3](#)

displaying in DHCP snooping binding table [52-19](#)

dynamic

learning [4-29](#)

removing [4-31](#)

in ACLs [53-14](#)

static

adding [4-37](#)

allowing [4-38](#)

- characteristics of [4-36](#)
 - dropping [4-38](#)
 - removing [4-37](#)
- sticky [49-4](#)
- sticky secure, adding [49-5](#)
- MAC address learning, disabling on a VLAN [4-39](#)
 - configuring [4-39](#)
 - deployment scenarios [4-40](#)
 - feature compatibility [4-42](#)
 - feature incompatibility [4-43](#)
 - feature inompatibility [4-43](#)
 - usage guidelines [4-40](#)
- MAC address table
 - displaying [4-44](#)
- MAC address-table move update
 - configuration guidelines [23-10](#)
 - configuring [23-10](#)
 - monitoring [23-12](#)
- MAC Authentication Bypass
 - configure with 802.1X [46-60](#)
- MAC details, displaying [46-128](#)
- MAC extended access lists [53-14](#)
- macl [53-14](#)
- macros
 - See Auto SmartPorts macros
 - See Auto Smartports macros
 - See Smartports macros
- MACSec
 - 802.1AE Tagging [45-9](#)
- MACsec [45-2](#)
 - configuring on an interface [45-7](#)
 - defined [45-1, 45-2](#)
 - switch-to-switch security [45-1](#)
- MACsec Key Agreement Protocol
 - See MKA
- main-cpu command [11-8, 12-7](#)
- management address TLV [31-2](#)
- management options
 - SNMP [62-1](#)
- Management Port, Ethernet [8-6](#)
- managing software licenses, using PRTU [4-14](#)
- manual preemption, REP, configuring [24-13](#)
- marking
 - hardware capabilities [42-23, 42-57](#)
- marking action drivers [42-21, 42-55](#)
- marking network traffic [42-18, 42-52](#)
- marking support, multi-attribute [42-22, 42-56](#)
- match ip address command [40-6](#)
- maximum aging time (STP)
 - configuring [22-18](#)
- MDA
 - configuration guidelines [46-23 to ??](#)
 - described [46-23](#)
- MEC
 - configuration [5-45](#)
 - described [5-14](#)
 - failure [5-15](#)
- Media Access Control Security
 - See MACsec
- members
 - automatic discovery [16-7](#)
- member switch
 - managing [16-13](#)
- member switch, cluster
 - defined [16-2](#)
- meminfo command [73-5](#)
- messages, Ethernet OAM [65-34](#)
- messages, to users through banners [4-24](#)
- Metro features
 - Y.1731 (AIS and RDI), introduction [1-12](#)
- metro tags [29-2](#)
- MFIB
 - CEF [37-6](#)
 - overview [37-12](#)
- MFIB, IP
 - displaying [37-26](#)
- MIBs
 - compiling [72-4](#)

- downloading [72-3, 72-4](#)
 - overview [62-1](#)
 - related information [72-3](#)
 - SNMP interaction with [62-4](#)
- MKA
 - configuring policies [45-6](#)
 - defined [45-2](#)
 - policies [45-2](#)
 - replay protection [45-3](#)
 - statistics [45-4](#)
 - virtual ports [45-3](#)
- MLD Done messages and Immediate-leave [28-4](#)
- MLD messages [28-2](#)
- MLD queries [28-3](#)
- MLD reports [28-4](#)
- MLD Snooping
 - MLD Done messages and Immediate-leave [28-4](#)
 - MLD messages [28-2](#)
 - MLD queries [28-3](#)
 - MLD reports [28-4](#)
 - Multicast client aging robustness [28-3](#)
 - Multicast router discovery [28-3](#)
 - overview [28-1](#)
- Mode of capturing control packets, selecting [53-7](#)
- modules
 - checking status [9-1](#)
 - powering down [14-22](#)
- monitoring
 - 802.1Q tunneling [29-18](#)
 - ACL information [53-35](#)
 - Ethernet CFM [65-32, 65-33](#)
 - Ethernet OAM [65-49](#)
 - Ethernet OAM protocol [65-49](#)
 - Flex Links [23-12](#)
 - IGMP
 - snooping [28-10](#)
 - IGMP filters [27-34](#)
 - IGMP snooping [27-14](#)
 - Layer 2 protocol tunneling [29-18](#)
 - MAC address-table move update [23-12](#)
 - multicast router interfaces [28-11](#)
 - multi-VRF CE [41-14, 41-21, 41-22](#)
 - MVR [27-29](#)
 - object tracking [59-12](#)
 - REP [24-14](#)
 - traffic flowing among switches [69-1](#)
 - tunneling [29-18](#)
 - VLAN filters [53-24](#)
 - VLAN maps [53-24](#)
- monitoring and troubleshooting
 - BFD [39-17](#)
- M-record [22-23](#)
- MST
 - and multiple spanning trees [1-8, 22-22](#)
 - boundary ports [22-27](#)
 - BPDUUs [22-23](#)
 - configuration parameters [22-26](#)
 - configuring [22-29](#)
 - displaying configurations [22-33](#)
 - edge ports [22-27](#)
 - enabling [22-29](#)
 - hop count [22-28](#)
 - instances
 - configuring parameters [22-32](#)
 - description [22-23](#)
 - number supported [22-26](#)
 - interoperability with PVST+ [22-23](#)
 - link type [22-28](#)
 - master [22-27](#)
 - message age [22-28](#)
 - regions [22-26](#)
 - restrictions [22-29](#)
 - to-SST interoperability [22-24](#)
- MSTP
 - EtherChannel guard
 - enabling [25-6](#)
 - M-record [22-23](#)
 - M-tree [22-23](#)

- M-tree [22-23](#)
- MTUS
 - understanding [8-26](#)
- MTU size
 - configuring [8-28, 8-29, 8-38](#)
 - default [17-5](#)
- Multi-authentication
 - described [46-23](#)
- multiauthentication mode [46-8](#)
- multicast
 - See IP multicast
- Multicast client aging robustness [28-3](#)
- multicast Ethernet loopback, using [65-31](#)
- multicast Ethernet loopback (ETH-LB) [65-29](#)
- Multicast Forwarding Information Base (MFIB) [37-12](#)
- multicast groups
 - static joins [28-7](#)
- Multicast HA [37-13](#)
- Multicast implementation
 - HA [37-13](#)
 - MFIB [37-12](#)
 - S/M, 224/4 [37-13](#)
- multicast packets
 - blocking [55-2](#)
- Multicast router discovery [28-3](#)
- multicast router interfaces, displaying [27-17](#)
- multicast router interfaces, monitoring [28-11](#)
- multicast router ports, adding [28-7](#)
- multicast routers
 - flood suppression [27-12](#)
- multicast router table
 - displaying [37-24](#)
- Multicast Storm Control
 - enabling [56-4](#)
 - disabling [56-5](#)
- multicast television application, using MVR [27-21](#)
- Multicast VLAN Registration
 - See MVR
- multichassis EtherChannel
 - see MEC [5-14](#)
- multidomain authentication
 - See MDA
- multidomain authentication mode [46-7](#)
- multioperations scheduling, IP SLAs [68-5](#)
- Multiple AuthorizationAuthentication
 - configuring [46-34](#)
- Multiple Domain Authentication [46-34](#)
- multiple forwarding paths [1-8, 22-22](#)
- multiple-hosts mode [46-7](#)
- Multiple Spanning Tree
 - See MST
- multiple VPN routing/forwarding
 - See multi-VRF CE
- multi-VRF CE
 - components [41-3](#)
 - configuration example [41-17](#)
 - defined [41-1](#)
 - displaying [41-14, 41-21, 41-22](#)
 - monitoring [41-14, 41-21, 41-22](#)
 - network components [41-3](#)
 - packet-forwarding process [41-3](#)
- MVR
 - configuration guidelines and limitations [27-23](#)
 - configuring global parameters [27-24](#)
 - configuring on access ports [27-26](#)
 - configuring on a trunk port [27-27](#)
 - default configuration [27-23](#)
 - displaying information [27-29](#)
 - in a multicast television application [27-21](#)
 - monitoring [27-29](#)
 - setting global parameters [27-24](#)

N

- NAC Layer 2 802.1X authentication, intro [1-40](#)
- NAC Layer 2 IP validation, intro [1-40](#)
- named IPv6 ACLs, configuring

- ACLs
 - configuring named IPv6 ACLs [53-16](#)
- named MAC extended ACLs
 - ACLs
 - configuring named MAC extended [53-14, 53-15](#)
- native VLAN
 - and 802.1Q tunneling [29-4](#)
 - specifying [19-5](#)
- NDAC [45-9](#)
 - defined [45-9](#)
 - MACsec [45-1](#)
- NEAT
 - configuring [46-88](#)
 - overview [46-24](#)
- neighbor offset numbers, REP [24-5](#)
- NetFlow-lite
 - clear commands [63-9](#)
 - display commands [63-8](#)
- NetFlow packet sampling
 - about [63-2](#)
- Network Assistant
 - and VTY [16-12](#)
 - configure
 - enable communication with switch [16-13, 16-17](#)
 - default configuration [16-3](#)
 - overview of CLI commands [16-3](#)
- Network Device Admission Control (NDAC) [45-9](#)
- Network Edge Access Topology
 - See NEAT
- network fault tolerance [1-8, 22-22](#)
- network management
 - configuring [30-1](#)
 - RMON [69-1](#)
 - SNMP [62-1](#)
- network performance, measuring with IP SLAs [68-3](#)
- network policy TLV [31-2, 31-9](#)
- Network Time Protocol
 - See NTP
- network traffic, marking [42-18, 42-52](#)
- New Software Features in Release 7.7
 - TDR [9-3](#)
- Next Hop Resolution Protocol
 - See NHRP
- NHRP
 - support [1-18](#)
- non-fiber-optics interfaces
 - disabling UDLD [32-7](#)
- non-IP traffic filtering [53-14, 53-15](#)
- non-RPF traffic
 - description [37-10](#)
 - in redundant configurations (figure) [37-11](#)
- Nonstop Forwarding
 - See NSF
- nonvolatile random-access memory
 - See NVRAM
- normal-range VLANs
 - See VLANs
- NSF
 - defined [13-1](#)
 - guidelines and restrictions [13-9](#)
 - operation [13-4](#)
- NSF-aware
 - supervisor engines [13-3](#)
 - support [13-2](#)
- NSF-capable
 - supervisor engines [13-3](#)
 - support [13-2](#)
- NSF with SSO supervisor engine redundancy
 - and CEF [13-5](#)
 - overview [13-3](#)
 - SSO operation [13-4](#)
- NTP
 - associations
 - authenticating [4-4](#)
 - defined [4-2](#)
 - enabling broadcast messages [4-7](#)
 - peer [4-6](#)
 - server [4-6](#)

- default configuration [4-4](#)
- displaying the configuration [4-11](#)
- overview [4-2](#)
- restricting access
 - creating an access group [4-9](#)
 - disabling NTP services per interface [4-10](#)
- source IP address, configuring [4-10](#)
- stratum [4-2](#)
- synchronizing devices [4-6](#)
- time
 - services [4-2](#)
 - synchronizing [4-2](#)

Introduction

- PPPoE Intermediate Agent [1-41](#)
- Storm Control [1-42](#)
- uRPF Strict Mode [1-42](#)

NVRAM

- saving settings [3-10](#)

O

OAM

- client [65-34](#)
- features [65-34](#)
- sublayer [65-34](#)

OAM manager

- configuring [65-52](#)
- with CFM and Ethernet OAM [65-51](#)

OAM PDUs [65-35](#)

OAM protocol data units [65-33](#)

OBFL, displaying for the 9000W AC [14-4](#)

object tracking

- monitoring [59-12](#)

OIR

- overview [8-33](#)

on-demand online diagnostics [70-2](#)

online diagnostic

- troubleshooting [70-8](#)

Online Diagnostics [70-1](#)

online diagnostics

- configuring on-demand [70-2](#)
- data path, displaying test results [70-7](#)
- displaying tests and test results [70-4](#)
- linecard [70-8](#)
- scheduling [70-2](#)
- starting and stopping tests [70-3](#)

online insertion and removal

- See OIR

Open Shortest Path First

- See OSPF

operating system images

- See system images

Option 82

- enabling DHCP Snooping [52-10](#)

OSPF

- area concept [1-18](#)
- description [1-18](#)
- for IPv6 [54-6](#)

OSPF, introduction [1-18](#)

OSPF for Routed Access, introduction [1-21](#)

P

packets

- modifying [42-9](#)

packet type filtering

- overview [57-14](#)
- SPAN enhancement [57-14](#)

PACL

- using with access-group mode [53-30](#)

PACL configuration guidelines [53-28](#)

PACL with VLAN maps and router ACLs [53-32](#)

PAgP

- understanding [26-4](#)

PAgP, dual-active detection [5-23](#)

passwords

- configuring enable password [3-14](#)
- configuring enable secret password [3-14](#)

- encrypting [3-22](#)
- in clusters [16-8](#)
- recovering lost enable password [3-25](#)
- setting line password [3-14](#)
- PBR (policy-based routing)
 - configuration (example) [40-8](#)
 - enabling [40-6](#)
 - features [40-2](#)
 - overview [40-1](#)
 - route-map processing logic [40-3](#)
 - route-map processing logic example [40-4](#)
 - route maps [40-2](#)
 - when to use [40-5](#)
- percentage thresholds in tracked lists [59-6](#)
- Permanent Right-To_Use [4-14](#)
- per-port and VLAN Access Control List [52-19](#)
- per-port per-VLAN QoS
 - enabling [42-36, 42-70](#)
 - overview [42-10](#)
- Per-User ACL and Filter-ID ACL, configure [46-45](#)
- Per-VLAN Rapid Spanning Tree [22-6](#)
 - enabling [22-20](#)
 - overview [22-6](#)
- PE to CE routing, configuring [41-9](#)
- physical layer 3 interfaces [34-2](#)
- Physical Layer 3 interfaces, configuring [34-12](#)
- PIM
 - configuring dense mode [37-15](#)
 - configuring sparse mode [37-15](#)
 - displaying information [37-23](#)
 - displaying statistics [37-27](#)
 - enabling sparse-dense mode [37-15, 37-16](#)
 - overview [37-3](#)
- PIM-DM [37-3](#)
- PIM on an interface, enabling [37-14](#)
- PIM-SM [37-3](#)
- PIM-SSM mapping, enabling [37-17](#)
- ping
 - executing [9-8](#)
 - overview [9-7](#)
 - ping command [9-8, 37-23](#)
- PoE [15-7, 15-8](#)
 - configuring power consumption, powered devices [15-5](#)
 - configuring power consumption for single device [15-5, 15-16](#)
 - displaying operational status for an interface [15-6](#)
 - Enhanced PoE support on E-series [15-15](#)
 - policing and monitoring [15-12](#)
 - power consumption for powered devices
 - Intelligent Power Management [15-4](#)
 - powering down a module [14-22](#)
 - power management modes [15-2](#)
- PoE policing
 - configuring errdisable recovery [15-14](#)
 - configuring on an interface [15-13](#)
 - displaying on an interface [15-14](#)
 - power modes [15-12](#)
- point-to-point
 - in 802.1X authentication (figure) [46-3](#)
- policing
 - how to implement [42-18, 42-52](#)
 - See QoS policing
- policing, PoE [15-12](#)
- policing IPv6 control traffic [50-16](#)
- policy associations, QoS on Sup 6-E [42-39, 42-73](#)
- policy-map command [42-16, 42-51](#)
- policy map marking action, configuring [42-23, 42-57](#)
- port ACLs
 - and voice VLAN [53-4](#)
 - defined [53-3](#)
- Port Aggregation Protocol
 - see PAgP
- port-based authentication
 - 802.1X with voice VLAN [46-22](#)
 - Authentication Failed VLAN assignment [46-17](#)
 - authentication server
 - defined [48-2](#)

- changing the quiet period [46-84](#)
- client, defined [46-3, 48-2](#)
- configuration guidelines [46-29, 48-6](#)
- configure ACL assignments and redirect URLs [46-38](#)
- configure switch-to-RADIUS server communication [46-32](#)
- configure with Authentication Failed [46-70](#)
- configure with Critical Authentication [46-62](#)
- configure with Guest-VLANs [46-57](#)
- configure with MAC Authentication Bypass [46-60](#)
- configure with VLAN User Distribution [46-68](#)
- configure with Voice VLAN [46-72](#)
- configuring
 - Multiple Domain Authentication and Multiple Authorization [46-34](#)
 - RADIUS server [48-10](#)
 - RADIUS server parameters on the switch [48-9](#)
- configuring Fallback Authentication [46-77](#)
- configuring Guest-VLAN [46-32](#)
- configuring manual re-authentication of a client [46-94](#)
- configuring with Unidirectional Controlled Port [46-66](#)
- controlling authorization state [46-5](#)
- default configuration [46-27, 48-6](#)
- described [46-1](#)
- device roles [46-2, 48-2](#)
- displaying statistics [46-125, 48-14](#)
- enabling [46-29](#)
 - 802.1X authentication [48-9](#)
- enabling multiple hosts [46-83](#)
- enabling periodic re-authentication [46-81](#)
- encapsulation [46-3](#)
- host mode [46-6](#)
- how 802.1X fails on a port [46-25](#)
- initiation and message exchange [46-4](#)
- method lists [46-29](#)
- modes [46-6](#)
- multidomain authentication [46-23](#)
- multiple-hosts mode, described [46-7](#)
- port security
 - multiple-hosts mode [46-7](#)
- ports not supported [46-5](#)
- pre-authentication open access [46-8](#)
- resetting to default values [46-95](#)
- setting retransmission number [46-86](#)
- setting retransmission time [46-85](#)
- switch
 - as proxy [48-2](#)
- switch supplicant
 - configuring [46-88](#)
 - overview [46-24](#)
- topologies, supported [46-26](#)
- using with ACL assignments and redirect URLs [46-20](#)
- using with port security [46-19](#)
- voice aware 802.1x security
 - configuring [46-74](#)
 - described [46-22, 46-73](#)
 - with Critical Authentication [46-14](#)
 - with Guest VLANs [46-11](#)
 - with MAC Authentication Bypass [46-12](#)
 - with Unidirectional Controlled Port [46-15](#)
 - with VLAN assignment [46-10](#)
 - with VLAN User Distribution [46-16](#)
- port-channel
 - see EtherChannel
- port-channel interfaces
 - See also EtherChannel
 - creating [5-45, 26-7](#)
 - overview [26-2](#)
- port-channel load-balance
 - command [26-13](#)
 - command example [26-13](#)
- port-channel load-balance command [26-14](#)
- port cost (STP)
 - configuring [22-15](#)
- port description TLV [31-2](#)
- PortFast

- and MST [22-23](#)
- BPDU filter, configuring [25-9](#)
- configuring or enabling [25-15](#)
- overview [25-6](#)
- PortFast BPDU filtering
 - and MST [22-23](#)
 - enabling [25-9](#)
 - overview [25-9](#)
- port numbering with TwinGig Convertors [8-13](#)
- port priority
 - configuring MST instances [22-32](#)
 - configuring STP [22-13](#)
- ports
 - blocking [55-1](#)
 - checking status [9-2](#)
 - dynamic VLAN membership
 - example [17-29](#)
 - reconfirming [17-26](#)
 - forwarding, resuming [55-3](#)
 - REP [24-6](#)
 - See also interfaces
- port security
 - aging [49-5](#)
 - configuring [49-7](#)
 - displaying [49-28](#)
 - guidelines and restrictions [49-33](#)
 - on access ports [49-7, 49-22](#)
 - on private VLAN [49-14](#)
 - host [49-14](#)
 - promiscuous [49-16](#)
 - topology [49-15, 49-18, 49-32](#)
 - on trunk port [49-17](#)
 - guidelines and restrictions [49-15, 49-18, 49-32](#)
 - port mode changes [49-22](#)
 - on voice ports [49-22](#)
 - sticky learning [49-5](#)
 - using with 802.1X [46-19](#)
 - violations [49-6](#)
 - with 802.1X Authentication [49-32](#)
 - with DHCP and IP Source Guard [49-31](#)
 - with other features [49-33](#)
- port states
 - description [22-5](#)
- port VLAN ID TLV [31-2](#)
- power
 - inline [43-5](#)
 - power dc input command [14-21](#)
 - powered devices, configuring power consumption [15-5](#)
 - power handling for Supervisor Engine II-TS [15-12](#)
 - power inline command [15-3](#)
 - power inline consumption command [15-5](#)
 - power management
 - Catalyst 4500 series [14-7](#)
 - Catalyst 4500 Switch power supplies [14-14](#)
 - Catalyst 4948 series [14-23](#)
 - configuring combined mode [14-13](#)
 - configuring redundant mode [14-12](#)
 - overview [14-1](#)
 - redundancy [14-7](#)
 - power management for Catalyst 4500 Switch
 - combined mode [14-9](#)
 - redundant mode [14-9](#)
 - power management limitations in Catalyst 4500 Switch [14-10](#)
 - power management mode
 - selecting [14-10](#)
 - power management TLV [31-2, 31-3, 31-9](#)
 - power negotiation
 - through LLDP [31-11](#)
 - Power-On-Self-Test diagnostics [70-10, 70-20](#)
 - Power-On-Self-Test for Supervisor Engine V-10GE [70-13](#)
 - power policing, displaying on an interface [15-14](#)
 - power redundancy-mode command [14-13](#)
 - power supplies
 - available power for Catalyst 4500 Switch [14-14](#)
 - fixed [14-8](#)
 - variable [14-8, 14-23](#)

- pre-authentication open access [46-8](#)
 - pre-authentication open access. See port-based authentication.
 - preempt delay time, REP [24-5](#)
 - primary edge port, REP [24-4](#)
 - primary VLANs [44-2, 44-4](#)
 - associating with secondary VLANs [44-16](#)
 - configuring as a PVLAN [44-15](#)
 - priority
 - overriding CoS of incoming frames [43-5](#)
 - priority queuing, QoS on Sup 6-E [42-30, 42-64](#)
 - private VLAN
 - configure port security [49-14, 49-15](#)
 - enabling DHCP Snooping [52-12](#)
 - private VLANs
 - across multiple switches [44-5](#)
 - and SVIs [44-10](#)
 - benefits of [44-2](#)
 - community ports [44-3](#)
 - community VLANs [44-2, 44-3](#)
 - default configuration [44-12](#)
 - end station access to [44-3](#)
 - isolated port [44-4](#)
 - isolated VLANs [44-2, 44-3, 44-4](#)
 - ports
 - community [44-3](#)
 - isolated [44-4](#)
 - promiscuous [44-4](#)
 - primary VLANs [44-2, 44-4](#)
 - promiscuous ports [44-4](#)
 - secondary VLANs [44-2](#)
 - subdomains [44-2](#)
 - traffic in [44-9](#)
 - privileged EXEC mode [2-5](#)
 - privileges
 - changing default [3-23](#)
 - configuring levels [3-23](#)
 - exiting [3-24](#)
 - logging in [3-24](#)
 - promiscuous ports
 - configuring PVLAN [44-17](#)
 - defined [44-4](#)
 - setting mode [44-24](#)
 - protocol timers [22-4](#)
 - provider edge devices [41-2](#)
 - PRTU, managing software licenses [4-14](#)
 - pruning, VTP
 - See VTP pruning
 - pseudobridges
 - description [22-25](#)
 - PVACL [52-19](#)
 - PVID (port VLAN ID)
 - and 802.1X with voice VLAN ports [46-22](#)
 - PVLAN promiscuous trunk port
 - configuring [44-11, 44-17, 44-21](#)
 - PVLANS
 - 802.1q support [44-14](#)
 - across multiple switches [44-5](#)
 - configuration guidelines [44-12](#)
 - configure port security [49-14, 49-16, 49-18](#)
 - configure port security in a wireless setting [49-32](#)
 - configuring [44-11](#)
 - configuring a VLAN [44-15](#)
 - configuring promiscuous ports [44-17](#)
 - host ports
 - configuring a Layer 2 interface [44-18](#)
 - setting [44-24](#)
 - overview [44-1](#)
 - permitting routing, example [44-23](#)
 - promiscuous mode
 - setting [44-24](#)
 - setting
 - interface mode [44-24](#)
-
- Q**
- QoS
 - classification [42-6 to ??](#)

- definitions [42-3](#)
 - enabling per-port per-VLAN [42-36, 42-70](#)
 - overview [42-1](#)
 - overview of per-port per-VLAN [42-10](#)
 - packet modification [42-9](#)
 - traffic shaping [42-9](#)
 - See also COS; DSCP values; transmit queues
 - QoS active queue management
 - tracking queue length [42-9](#)
 - QoS labels
 - definition [42-3](#)
 - QoS marking
 - description [42-5](#)
 - QoS on Sup 6-E
 - Active Queue management via DBL [42-34, 42-68](#)
 - active queue management via DBL [42-27, 42-34, 42-61, 42-68](#)
 - classification [42-16, 42-50](#)
 - configuring [42-13, 42-47](#)
 - configuring CoS mutation [42-45, 42-79](#)
 - configuring the policy map marking action [42-23, 42-57](#)
 - hardware capabilities for marking [42-23, 42-57](#)
 - how to implement policing [42-18, 42-52](#)
 - marking action drivers [42-21, 42-55](#)
 - marking network traffic [42-18, 42-52](#)
 - MQC-based QoS configuration [42-13, 42-48](#)
 - multi-attribute marking support [42-22, 42-56](#)
 - platform hardware capabilities [42-15, 42-49](#)
 - platform restrictions [42-18, 42-52](#)
 - platform-supported classification criteria and QoS features [42-13, 42-14, 42-48](#)
 - policing [42-17, 42-51](#)
 - policy associations [42-39, 42-73](#)
 - prerequisites for applying a service policy [42-15, 42-49](#)
 - priority queuing [42-30, 42-64](#)
 - queue-limiting [42-31, 42-65](#)
 - restrictions for applying a service policy [42-15, 42-50](#)
 - shaping [42-25, 42-59](#)
 - sharing(bandwidth) [42-27, 42-61](#)
 - sharing(bandwidth), shapring, and priority queuing [42-25, 42-59](#)
 - software QoS [42-40, 42-74](#)
 - traffic marking procedure flowchart [42-21, 42-55](#)
 - QoS policing
 - definition [42-5](#)
 - described [42-8](#)
 - QoS policy
 - attaching to interfaces [42-8](#)
 - QoS service policy
 - prerequisites [42-15, 42-49](#)
 - restrictions for applying [42-15, 42-50](#)
 - QoS transmit queues
 - burst [42-9](#)
 - maximum rate [42-9](#)
 - sharing link bandwidth [42-9](#)
 - quad-supervisor
 - uplink forwarding [5-6](#)
 - Quality of service
 - See QoS
 - queueing [42-8](#)
 - queue-limiting, QoS on Sup 6-E [42-31, 42-65](#)
-
- ## R
- ### RADIUS
- attributes
 - vendor-proprietary [46-114](#)
 - vendor-specific [46-112](#)
 - change of authorization [46-97](#)
 - configuring
 - accounting [46-111](#)
 - authentication [46-106](#)
 - authorization [46-110](#)
 - communication, global [46-104, 46-112](#)
 - communication, per-server [46-103, 46-104](#)
 - multiple UDP ports [46-104](#)
 - default configuration [46-103](#)
 - defining AAA server groups [46-108](#)

- displaying the configuration [46-116](#)
- identifying the server [46-103](#)
- limiting the services to the user [46-110](#)
- method list, defined [46-103](#)
- operation of [46-97](#)
- server load balancing [46-116](#)
- suggested network environments [46-96](#)
- tracking services accessed by user [46-111](#)
- understanding [46-96](#)
- RADIUS, controlling switch access with [46-95](#)
- RADIUS Change of Authorization [46-97](#)
- RADIUS server
 - configure to-Switch communication [46-32](#)
 - configuring settings [46-34](#)
 - parameters on the switch [46-32](#)
- RA Guard
 - configuring [53-36](#)
 - deployment [53-36](#)
 - examples [53-37](#)
 - introduction [53-35](#)
 - usage guidelines [53-38](#)
- range command [8-4](#)
- range macros
 - defining [8-11](#)
- ranges of interfaces
 - configuring [8-4](#)
- Rapid Spanning Tree
 - See RSTP
- rcommand command [16-13](#)
- reachability, tracking IP SLAs IP host [59-9](#)
- re-authentication of a client
 - configuring manual [46-94](#)
 - enabling periodic [46-81](#)
- redirect URLs, port-based authentication [46-20](#)
- reduced MAC address [22-2](#)
- redundancy
 - configuring [11-7, 12-7](#)
 - guidelines and restrictions [11-5, 12-5](#)
 - changes made through SNMP [11-11, 12-11](#)
 - NSF-aware support [13-2](#)
 - NSF-capable support [13-2](#)
 - overview [11-2, 12-2](#)
 - redundancy command [11-8, 12-7](#)
 - understanding synchronization [11-4, 12-5](#)
- redundancy (NSF) [13-1](#)
 - configuring
 - BGP [13-11](#)
 - CEF [13-10](#)
 - EIGRP [13-16](#)
 - IS-IS [13-13](#)
 - OSPF [13-12](#)
 - routing protocols [13-5](#)
- redundancy (RPR)
 - route processor redundancy [11-2, 12-3](#)
 - synchronization [11-5, 12-5](#)
- redundancy (SSO)
 - redundancy command [13-10](#)
 - route processor redundancy [11-3, 12-3](#)
 - synchronization [11-5, 12-5](#)
- reload command [3-28, 3-29](#)
- Remote Authentication Dial-In User Service
 - See RADIUS
- remote failure indications [65-34](#)
- remote loopback, Ethernet OAM [65-34, 65-37](#)
- Remote Network Monitoring
 - See RMON
- rendezvous point, configuring [37-17](#)
- rendezvous point, configuring single static [37-20](#)
- REP
 - administrative VLAN [24-8](#)
 - administrative VLAN, configuring [24-9](#)
 - and STP [24-6](#)
 - configuration guidelines [24-7](#)
 - configuring interfaces [24-10](#)
 - convergence [24-4](#)
 - default configuration [24-7](#)
 - manual preemption, configuring [24-13](#)
 - monitoring [24-14](#)

- neighbor offset numbers [24-5](#)
- open segment [24-2](#)
- ports [24-6](#)
- preempt delay time [24-5](#)
- primary edge port [24-4](#)
- ring segment [24-2](#)
- secondary edge port [24-4](#)
- segments [24-1](#)
 - characteristics [24-2](#)
- SNMP traps, configuring [24-14](#)
- supported interfaces [24-1](#)
- triggering VLAN load balancing [24-6](#)
- verifying link integrity [24-4](#)
- VLAN blocking [24-13](#)
- VLAN load balancing [24-4](#)
- replication
 - description [37-9](#)
- report suppression, IGMP
 - disabling [28-10](#)
- reserved-range VLANs
 - See VLANs
- reset command [73-3](#)
- resetting an interface to default configuration [8-40](#)
- resetting a switch to defaults [3-32](#)
- Resilient Ethernet ProtocolSee REP
- responder, IP SLAs
 - described [68-4](#)
 - enabling [68-7](#)
- response time, measuring with IP SLAs [68-4](#)
- restricting access
 - NTP services [4-8](#)
 - RADIUS [46-95](#)
 - TACACS+ [3-15](#)
- retransmission number
 - setting in 802.1X authentication [46-86](#)
- retransmission time
 - changing in 802.1X authentication [46-85](#)
- RFC
 - 1157, SNMPv1 [62-2](#)
 - 1305, NTP [4-2](#)
 - 1757, RMON [69-2](#)
 - 1901, SNMPv2C [62-2](#)
 - 1902 to 1907, SNMPv2 [62-2](#)
 - 2273-2275, SNMPv3 [62-2](#)
- RFC 5176 Compliance [46-98](#)
- RIP
 - description [1-19](#)
 - for IPv6 [54-5](#)
- RIP, introduction [1-19](#)
- RMON
 - default configuration [69-3](#)
 - displaying status [69-6](#)
 - enabling alarms and events [69-3](#)
 - groups supported [69-2](#)
 - overview [69-1](#)
- ROM monitor
 - boot process and [3-26](#)
 - CLI [2-7](#)
 - commands [73-2 to 73-3](#)
 - debug commands [73-5](#)
 - entering [73-1](#)
 - exiting [73-6](#)
 - overview [73-1](#)
- root bridge
 - configuring [22-9](#)
 - selecting in MST [22-22](#)
- root guard
 - and MST [22-23](#)
 - enabling [25-2](#)
 - overview [25-2](#)
- routed packets
 - ACLs [53-26](#)
- route-map (IP) command [40-6](#)
- route maps
 - defining [40-6](#)
 - PBR [40-2](#)
- router ACLs
 - description [1-41, 53-3](#)

- using with VLAN maps [53-25](#)
 - router ACLs, using PACL with VLAN maps [53-32](#)
 - route targets
 - VPN [41-3](#)
 - Routing Information Protocol
 - See RIP
 - RPF
 - See Unicast RPF
 - RSPAN
 - configuration guidelines [57-16](#)
 - destination ports [57-5](#)
 - IDS [57-2](#)
 - monitored ports [57-4](#)
 - monitoring ports [57-5](#)
 - received traffic [57-3](#)
 - sessions
 - creating [57-17](#)
 - defined [57-3](#)
 - limiting source traffic to specific VLANs [57-23](#)
 - monitoring VLANs [57-21](#)
 - removing source (monitored) ports [57-20](#)
 - specifying monitored ports [57-17](#)
 - source ports [57-4](#)
 - transmitted traffic [57-4](#)
 - VLAN-based [57-5](#)
 - RSTP
 - compatibility [22-23](#)
 - description [22-22](#)
 - port roles [22-24](#)
 - port states [22-24](#)
- S**
-
- S/M, 224/4 [37-13](#)
 - SAID
 - See 802.10 SAID
 - SAP
 - defined [45-9](#)
 - negotiation [45-9](#)
 - support [45-1](#)
 - scheduling [42-8](#)
 - scheduling, IP SLAs operations [68-5](#)
 - secondary edge port, REP [24-4](#)
 - secondary root switch [22-12](#)
 - secondary VLANs [44-2](#)
 - associating with primary [44-16](#)
 - permitting routing [44-23](#)
 - security
 - configuring [50-1](#)
 - Security Association Identifier
 - See 802.10 SAID
 - Security Exchange Protocol
 - See SXP
 - Security Exchange Protocol
 - See SAP
 - selecting a power management mode [14-10](#)
 - selecting X2/TwinGig Convertor Mode [8-14](#)
 - sequence numbers in log messages [60-7](#)
 - server IDs
 - description [67-23](#)
 - service policy, configure class-level queue-limit [42-31](#), [42-65](#)
 - service-policy input command [33-2](#)
 - service-provider networks
 - and customer VLANs [29-2](#)
 - session keys, MKA [45-2](#)
 - set default interface command [40-7](#)
 - set interface command [40-7](#)
 - set ip default next-hop command [40-7](#)
 - set ip next-hop command [40-6](#)
 - set-request operation [62-4](#)
 - severity levels, defining in system messages [60-8](#)
 - shaping, QoS on Sup 6-E [42-25](#), [42-59](#)
 - sharing(bandwidth), QoS on Sup 6-E [42-27](#), [42-61](#)
 - Shell functions
 - See Auto SmartPorts macros
 - See Auto Smartports macros
 - Shell triggers

- See Auto SmartPorts macros
- See Auto Smartports macros
- show adjacency command [35-9](#)
- show boot command [3-32](#)
- show catalyst4000 chassis-mac-address command [22-3](#)
- show cdp command [30-2, 30-3](#)
- show cdp entry command [30-4](#)
- show cdp interface command [30-3](#)
- show cdp neighbors command [30-4](#)
- show cdp traffic command [30-4](#)
- show ciscoview package command [4-48](#)
- show ciscoview version command [4-48](#)
- show cluster members command [16-13](#)
- show configuration command [8-23](#)
- show debugging command [30-4](#)
- show environment command [14-2](#)
- show history command [2-4](#)
- show interfaces command [8-28, 8-29, 8-36, 8-38](#)
- show interfaces status command [9-2](#)
- show ip cef command [35-8](#)
- show ip eigrp interfaces command [34-19](#)
- show ip eigrp neighbors command [34-19](#)
- show ip eigrp topology command [34-19](#)
- show ip eigrp traffic command [34-19](#)
- show ip interface command [37-23](#)
- show ip local policy command [40-8](#)
- show ip mroute command [37-23](#)
- show ip pim interface command [37-23](#)
- show l2protocol command [29-18](#)
- show lldp traffic command [31-15](#)
- show mac-address-table address command [9-3](#)
- show mac-address-table interface command [9-3](#)
- show mls entry command [35-8](#)
- show module command [9-1, 22-6](#)
- show PoE consumed [15-8](#)
- show power inline command [15-6](#)
- show power supplies command [14-13](#)
- show protocols command [8-36](#)
- show running-config command
 - adding description for an interface [8-23](#)
 - checking your settings [3-9](#)
 - displaying ACLs [53-19, 53-21, 53-30, 53-31](#)
- show startup-config command [3-10](#)
- show users command [9-6](#)
- show version command [3-29](#)
- shutdown, command [8-37](#)
- shutdown threshold for Layer 2 protocol packets [29-16](#)
- shutting down
 - interfaces [8-37](#)
- Simple Network Management Protocol
 - See SNMP
- single-host mode [46-7](#)
- single spanning tree
 - See SST
- single static RP, configuring [37-20](#)
- slot numbers, description [8-2](#)
- Slow timer, configuring BFD [39-16](#)
- smart call home [67-1](#)
 - description [67-2](#)
 - destination profile (note) [67-5](#)
 - registration requirements [67-3](#)
 - service contract requirements [67-3](#)
 - Transport Gateway (TG) aggregation point [67-2](#)
- SMARTnet
 - smart call home registration [67-3](#)
- Smartports macros
 - applying global parameter values [20-8, 20-15](#)
 - applying macros [20-8](#)
 - applying parameter values [20-9](#)
 - configuration guidelines [20-6, 20-14](#)
 - configuring [20-2](#)
 - creating [20-8](#)
 - default configuration [20-4, 20-13](#)
 - defined [1-10, 20-1](#)
 - displaying [20-13](#)
 - tracing [20-7, 20-14](#)
- SNMP
 - accessing MIB variables with [62-4](#)

- agent
 - described [62-4](#)
 - disabling [62-7](#)
- and IP SLAs [68-2](#)
- authentication level [62-10](#)
- community strings
 - configuring [62-7](#)
 - overview [62-4](#)
- configuration examples [62-15](#)
- configuration guidelines [62-6](#)
- default configuration [62-5](#)
- enabling [72-4, 72-5](#)
- engine ID [62-6](#)
- groups [62-6, 62-9](#)
- host [62-6](#)
- informs
 - and trap keyword [62-11](#)
 - described [62-5](#)
 - differences from traps [62-5](#)
 - enabling [62-14](#)
- limiting access by TFTP servers [62-15](#)
- limiting system log messages to NMS [60-9](#)
- manager functions [62-3](#)
- notifications [62-5](#)
- overview [62-1, 62-4](#)
- status, displaying [62-16](#)
- system contact and location [62-14](#)
- trap manager, configuring [62-13](#)
- traps
 - described [62-3, 62-5](#)
 - differences from informs [62-5](#)
 - enabling [62-11](#)
 - enabling MAC address notification [4-31](#)
 - enabling MAC move notification [4-33](#)
 - enabling MAC threshold notification [4-35](#)
 - overview [62-1, 62-4](#)
 - types of [62-11](#)
- users [62-6, 62-9](#)
- versions supported [62-2](#)
- SNMP commands [72-4](#)
- SNMP traps
 - REP [24-14](#)
- SNMPv1 [62-2](#)
- SNMPv2C [62-2](#)
- SNMPv3 [62-2](#)
- software
 - upgrading [11-13, 12-12](#)
- software configuration register [3-26](#)
- software QoS, on Sup 6-E [42-40, 42-74](#)
- software switching
 - description [35-5](#)
 - interfaces [35-6](#)
 - key data structures used [37-8](#)
- source IDs
 - call home event format [67-22](#)
- SPAN
 - and ACLs [57-5](#)
 - configuration guidelines [57-7](#)
 - configuring [57-6 to 57-10](#)
 - destination ports [57-5](#)
 - IDS [57-2](#)
 - monitored port, defined [57-4](#)
 - monitoring port, defined [57-5](#)
 - received traffic [57-3](#)
 - sessions
 - defined [57-3](#)
 - source ports [57-4](#)
 - transmitted traffic [57-4](#)
 - VLAN-based [57-5](#)
- SPAN and RSPAN
 - concepts and terminology [57-3](#)
 - default configuration [57-6](#)
 - displaying status [57-24](#)
 - overview [57-1](#)
 - session limits [57-6](#)
- SPAN enhancements
 - access list filtering [57-13](#)
 - configuration example [57-15](#)

- CPU port sniffing [57-10](#)
- encapsulation configuration [57-12](#)
- ingress packets [57-12](#)
- packet type filtering [57-14](#)
- spanning-tree backbonefast command [25-16](#)
- spanning-tree cost command [22-15](#)
- spanning-tree guard root command [25-2](#)
- spanning-tree portfast bpduguard command [25-8](#)
- spanning-tree portfast command [25-7](#)
- spanning-tree port-priority command [22-13](#)
- spanning-tree uplinkfast command [25-12](#)
- spanning-tree vlan
 - command [22-9](#)
 - command example [22-9](#)
- spanning-tree vlan command [22-8](#)
- spanning-tree vlan cost command [22-16](#)
- spanning-tree vlan forward-time command [22-19](#)
- spanning-tree vlan hello-time command [22-18](#)
- spanning-tree vlan max-age command [22-18](#)
- spanning-tree vlan port-priority command [22-13](#)
- spanning-tree vlan priority command [22-17](#)
- spanning-tree vlan root primary command [22-10](#)
- spanning-tree vlan root secondary command [22-12](#)
- speed
 - configuring interface [8-20](#)
- speed command [8-21](#)
- SSO
 - configuring [13-10](#)
- SSO operation [13-4](#)
- SST
 - description [22-22](#)
 - interoperability [22-24](#)
- static ACL, removing the requirement [53-28](#)
- static addresses
 - See addresses
- static routes
 - configuring [3-11](#)
 - verifying [3-12](#)
- statistics
 - 802.1X [48-14](#)
 - displaying 802.1X [46-125](#)
 - displaying PIM [37-27](#)
 - LLDP [31-14](#)
 - LLDP-MED [31-14](#)
 - MKA [45-4](#)
 - SNMP input and output [62-16](#)
- sticky learning
 - configuration file [49-6](#)
 - defined [49-5](#)
 - disabling [49-6](#)
 - enabling [49-5](#)
 - saving addresses [49-6](#)
- sticky MAC addresses
 - configuring [49-7](#)
 - defined [49-4](#)
- storing captured packets to a .pcap file, Wireshark [58-8](#)
- Storm Control
 - displaying [56-6](#)
 - enabling Broadcast [56-3](#)
 - enabling Multicast [56-4](#)
 - hardware-based, implementing [56-2](#)
 - overview [56-1](#)
 - software-based, implementing [56-2](#)
- STP
 - and REP [24-6](#)
 - bridge ID [22-2](#)
 - configuring [22-7 to 22-20](#)
 - creating topology [22-5](#)
 - defaults [22-7](#)
 - disabling [22-20](#)
 - enabling [22-8](#)
 - enabling extended system ID [22-9](#)
 - enabling Per-VLAN Rapid Spanning Tree [22-20](#)
 - EtherChannel guard
 - disabling [25-6](#)
 - forward-delay time [22-19](#)
 - hello time [22-17](#)
 - Layer 2 protocol tunneling [29-13](#)

- maximum aging time [22-18](#)
 - overview [22-1, 22-3](#)
 - per-VLAN rapid spanning tree [22-6](#)
 - port cost [22-15](#)
 - port priority [22-13](#)
 - root bridge [22-9](#)
- stratum, NTP [4-2](#)
- stub routing (EIGRP)
 - benefits [34-17](#)
 - configuration tasks [34-18](#)
 - configuring [34-14](#)
 - overview [34-13, 34-14](#)
 - restrictions [34-17](#)
 - verifying [34-18](#)
- subdomains, private VLAN [44-2](#)
- summer time [4-13](#)
- supervisor engine
 - accessing the redundant [11-14, 12-14](#)
 - configuring [3-8 to 3-13](#)
 - copying files to standby [11-14, 12-14](#)
 - default configuration [3-1](#)
 - default gateways [3-11](#)
 - environmental monitoring [14-1](#)
 - redundancy [13-1](#)
 - ROM monitor [3-26](#)
 - startup configuration [3-25](#)
 - static routes [3-11](#)
 - synchronizing configurations [11-11, 12-10](#)
- Supervisor Engine 7L-E, selecting the uplink port [8-18](#)
- Supervisor Engine II-TS
 - insufficient inline power handling [14-22, 15-12](#)
- Smartports macros
 - See also Auto Smartports macros
- SVI Autostate Exclude
 - understanding [34-3](#)
- SVI Autostate exclude
 - configuring [34-7](#)
- S-VLAN [1-2, 29-7](#)
- switch [54-2](#)
 - switch access with RADIUS, controlling [46-95](#)
 - switched packets
 - and ACLs [53-25](#)
 - Switched Port Analyzer
 - See SPAN
 - switchport
 - show interfaces [8-28, 8-29, 8-38](#)
 - switchport access vlan command [19-5, 19-7](#)
 - switchport block multicast command [55-2](#)
 - switchport block unicast command [55-2](#)
 - switchport mode access command [19-7](#)
 - switchport mode dot1q-tunnel command [29-6](#)
 - switchport mode dynamic command [19-5](#)
 - switchport mode trunk command [19-5](#)
- switch ports
 - See access ports
- switchport trunk allowed vlan command [19-5](#)
- switchport trunk encapsulation command [19-5](#)
- switchport trunk native vlan command [19-5](#)
- switchport trunk pruning vlan command [19-6](#)
- switch-to-RADIUS server communication
 - configuring [46-32](#)
- sysret command [73-5](#)
- system
 - reviewing configuration [3-10](#)
 - settings at startup [3-27](#)
- system alarms
 - overview [14-6](#)
- system and network statistics, displaying [37-23](#)
- system capabilities TLV [31-2](#)
- system clock
 - configuring
 - daylight saving time [4-13](#)
 - manually [4-11](#)
 - summer time [4-13](#)
 - time zones [4-12](#)
 - displaying the time and date [4-12](#)
 - overview [4-2](#)
 - See also NTP

- system description TLV [31-2](#)
 - system images
 - loading from Flash memory [3-30](#)
 - modifying boot field [3-27](#)
 - specifying [3-30](#)
 - system message logging
 - default configuration [60-3](#)
 - defining error message severity levels [60-8](#)
 - disabling [60-4](#)
 - displaying the configuration [60-12](#)
 - enabling [60-4](#)
 - facility keywords, described [60-12](#)
 - level keywords, described [60-9](#)
 - limiting messages [60-9](#)
 - message format [60-2](#)
 - overview [60-1](#)
 - sequence numbers, enabling and disabling [60-7](#)
 - setting the display destination device [60-5](#)
 - synchronizing log messages [60-6](#)
 - timestamps, enabling and disabling [60-7](#)
 - UNIX syslog servers
 - configuring the daemon [60-10](#)
 - configuring the logging facility [60-11](#)
 - facilities supported [60-12](#)
 - system MTU
 - 802.1Q tunneling [29-5](#)
 - maximums [29-5](#)
 - system name
 - manual configuration [4-22](#)
 - See also DNS
 - system name TLV [31-2](#)
 - system prompt, default setting [4-21](#)
- T**
- TACACS+ [50-1](#)
 - accounting, defined [3-16](#)
 - authentication, defined [3-16](#)
 - authorization, defined [3-16](#)
 - configuring
 - accounting [3-21](#)
 - authentication key [3-18](#)
 - authorization [3-21](#)
 - login authentication [3-19](#)
 - default configuration [3-18](#)
 - displaying the configuration [3-22](#)
 - identifying the server [3-18](#)
 - limiting the services to the user [3-21](#)
 - operation of [3-17](#)
 - overview [3-15](#)
 - tracking services accessed by user [3-21](#)
- tagged packets
 - 802.1Q [29-3](#)
 - Layer 2 protocol [29-13](#)
 - TCAM programming and ACLs [53-7](#)
 - for Sup II-Plust thru V-10GE [53-6](#)
 - TCAM programming and ACLs for Sup 6-E [53-10](#)
 - TDR
 - checking cable connectivity [9-3](#)
 - enabling and disabling test [9-3](#)
 - guidelines [9-3](#)
 - Telnet
 - accessing CLI [2-2](#)
 - disconnecting user sessions [9-7](#)
 - executing [9-5](#)
 - monitoring user sessions [9-6](#)
 - telnet command [9-6](#)
 - templates, Ethernet OAM [65-45](#)
 - Terminal Access Controller Access Control System Plus
 - See TACACS+
 - TFTP
 - configuration files in base directory [3-5](#)
 - configuring for autoconfiguration [3-4](#)
 - limiting access by servers [62-15](#)
 - TFTP download
 - See also console download
 - threshold monitoring, IP SLAs [68-6](#)
 - time

- See NTP and system clock
- Time Domain Reflectometer
 - See TDR
- time exceeded messages [9-9](#)
- timer
 - See login timer
- timestamps in log messages [60-7](#)
- time zones [4-12](#)
- TLV
 - host presence detection [46-8](#)
- TLVs
 - defined [1-7, 31-2](#)
 - LLDP-MED [31-2](#)
- Token Ring
 - media not supported (note) [17-5, 17-10](#)
- Topology change notification processing
 - MLD Snooping
 - Topology change notification processing [28-4](#)
- TOS
 - description [42-4](#)
- trace command [9-9](#)
- traceroute
 - See IP traceroute
 - See Layer 2 Traceroute
- traceroute mac command [9-11](#)
- traceroute mac ip command [9-11](#)
- tracked lists
 - configuring [59-3](#)
 - types [59-3](#)
- tracked objects
 - by Boolean expression [59-4](#)
 - by threshold percentage [59-6](#)
 - by threshold weight [59-5](#)
- tracking interface line-protocol state [59-2](#)
- tracking IP routing state [59-2](#)
- tracking objects [59-1](#)
- tracking process [59-1](#)
- track state, tracking IP SLAs [59-9](#)
- traffic
 - blocking flooded [55-2](#)
- traffic control
 - using ACLs (figure) [53-4](#)
 - using VLAN maps (figure) [53-5](#)
- traffic marking procedure flowchart [42-21, 42-55](#)
- traffic shaping [42-9](#)
- translational bridge numbers (defaults) [17-5](#)
- traps
 - configuring MAC address notification [4-31](#)
 - configuring MAC move notification [4-33](#)
 - configuring MAC threshold notification [4-35](#)
 - configuring managers [62-11](#)
 - defined [62-3](#)
 - enabling [4-31, 4-33, 4-35, 62-11](#)
 - notification types [62-11](#)
 - overview [62-1, 62-4](#)
- troubleshooting
 - with CiscoWorks [62-4](#)
 - with system message logging [60-1](#)
 - with traceroute [9-8](#)
- troubleshooting high CPU due to ACLs [53-6](#)
- trunk failover
 - See link-state tracking
- trunk ports
 - configure port security [49-17](#)
 - configuring PVLAN [44-19 to 44-21](#)
- trunks
 - 802.1Q restrictions [19-4](#)
 - configuring [19-5](#)
 - configuring access VLANs [19-5](#)
 - configuring allowed VLANs [19-5](#)
 - default interface configuration [19-5](#)
 - enabling to non-DTP device [19-3](#)
 - specifying native VLAN [19-5](#)
 - understanding [19-3](#)
- trustpoint [67-3](#)
- tunneling
 - defined [29-1](#)
- tunnel ports

- 802.1Q, configuring [29-6](#)
 - described [29-2](#)
 - incompatibilities with other features [29-5](#)
 - TwinGig Convertors
 - limitations on using [8-14](#)
 - port numbering [8-13](#)
 - selecting X2/TwinGig Convertor mode [8-14](#)
 - type length value
 - See TLV
 - type of service
 - See TOS
-
- ## U
- UDLD
 - configuring probe message interval per-interface [32-8](#)
 - default configuration [32-4](#)
 - disabling on fiber-optic interfaces [32-7](#)
 - disabling on non-fiber-optic interfaces [32-7](#)
 - displaying link status [32-9](#)
 - enabling globally [32-5](#)
 - enabling per-interface [32-6](#)
 - modes of operation [32-3](#)
 - resetting disabled LAN interfaces [32-8](#)
 - use case [32-2](#)
 - UDLD, overview [32-1](#)
 - UDP jitter, configuring [68-9](#)
 - UDP jitter operation, IP SLAs [68-8](#)
 - unauthorized ports with 802.1X [46-5](#)
 - unicast
 - See IP unicast
 - unicast flood blocking
 - configuring [55-1](#)
 - unicast MAC address filtering
 - and adding static addresses [4-38](#)
 - and broadcast MAC addresses [4-37](#)
 - and CPU packets [4-37](#)
 - and multicast addresses [4-37](#)
 - and router MAC addresses [4-37](#)
 - configuration guidelines [4-37](#)
 - described [4-37](#)
 - unicast MAC address filtering, configuring
 - ACLs
 - configuring unicast MAC address filtering [53-13](#)
 - Unicast RPF (Unicast Reverse Path Forwarding)
 - applying [36-5](#)
 - BGP attributes
 - caution [36-4](#)
 - CEF
 - requirement [36-2](#)
 - tables [36-7](#)
 - configuring [36-9](#)
 - (examples) [?? to 36-12](#)
 - BOOTP [36-8](#)
 - DHCP [36-8](#)
 - enterprise network (figure) [36-6](#)
 - prerequisites [36-9](#)
 - routing table requirements [36-7](#)
 - tasks [36-9](#)
 - verifying [36-10](#)
 - deploying [36-5](#)
 - description [1-22, 36-1](#)
 - disabling [36-11](#)
 - enterprise network (figure) [36-6](#)
 - FIB [36-2](#)
 - implementing [36-4](#)
 - packets, dropping (figure) [36-4](#)
 - prerequisites [36-9](#)
 - restrictions
 - basic [36-8](#)
 - routing asymmetry [36-7](#)
 - routing asymmetry (figure) [36-8](#)
 - routing table requirements [36-7](#)
 - security policy
 - applying [36-5](#)
 - attacks, mitigating [36-5](#)
 - deploying [36-5](#)

- tunneling [36-5](#)
- source addresses, validating [36-3](#)
 - (figure) [36-3, 36-4](#)
 - failure [36-3](#)
- traffic filtering [36-5](#)
- tunneling [36-5](#)
- validation
 - failure [36-3, 36-4](#)
 - packets, dropping [36-3](#)
 - source addresses [36-3](#)
- verifying [36-10](#)
- unicast traffic
 - blocking [55-2](#)
- Unidirectional Controlled Port, configuring 802.1X [46-66](#)
- unidirectional ethernet
 - enabling [33-2](#)
 - example of setting [33-2](#)
 - overview [33-1](#)
- UniDirectional Link Detection Protocol
 - See UDLD
- Universal PoE, configuring [15-16](#)
- UNIX syslog servers
 - daemon configuration [60-10](#)
 - facilities supported [60-12](#)
 - message logging configuration [60-11](#)
- UplinkFast
 - and MST [22-23](#)
 - enabling [25-15](#)
 - MST and [22-23](#)
 - overview [25-11](#)
- uplink forwarding
 - quad-supervisor [5-6](#)
- uplink mode, selecting on supervisor engine 6-E [8-16](#)
- uplink port, selecting on a supervisor engine 7L-E [8-18](#)
- usage examples, Wireshark [58-18](#)
- user-defined event triggers
 - configuring, 802.1X-based [21-8](#)
 - configuring, MAC address-based [21-9](#)

- User-defined triggers and built-in macros, configuring mapping [21-9](#)
- user EXEC mode [2-5](#)
- user sessions
 - disconnecting [9-7](#)
 - monitoring [9-6](#)

V

- VACLs
 - Layer 4 port operations [53-10](#)
- virtual configuration register [73-3](#)
- virtual LANs
 - See VLANs
- virtual ports, MKA [45-3](#)
- Virtual Router Redundancy Protocol, introduction [1-22](#)
- Virtual Switch System(VSS), displaying EtherChannel to [26-16](#)
- VLAN ACLs
 - See VLAN maps
- VLAN blocking, REP [24-13](#)
- vlan command [17-6](#)
- vlan dot1q tag native command [29-4](#)
- VLAN ID
 - service provider [29-9](#)
- VLAN ID, discovering [4-44](#)
- VLAN ID translation
 - See VLAN mapping
- VLAN load balancing
 - REP [24-4](#)
- VLAN load balancing, triggering [24-6](#)
- VLAN load balancing on flex links [23-2](#)
 - configuration guidelines [23-6](#)
- VLAN Management Policy Server
 - See VMPS
- VLAN mapping
 - 1-to-1 [29-8](#)
 - 1-to-1, configuring [29-11](#)
 - configuration guidelines [29-10](#)

- configuring [29-11](#)
 - configuring on a trunk port [29-11](#)
 - default [29-9](#)
 - described [1-2, 29-7](#)
 - selective QinQ [29-8](#)
 - selective Q-in-Q, configuring [29-12](#)
 - traditional QinQ [29-8](#)
 - traditional Q-in-Q, configuring [29-12](#)
 - types of [29-8](#)
- VLAN maps
- applying to a VLAN [53-21](#)
 - configuration example [53-22](#)
 - configuration guidelines [53-18](#)
 - configuring [53-17](#)
 - creating and deleting entries [53-19](#)
 - defined [1-41](#)
 - denying access example [53-23](#)
 - denying packets [53-19](#)
 - displaying [53-24](#)
 - order of entries [53-18](#)
 - permitting packets [53-19](#)
 - router ACLs and [53-25](#)
 - using (figure) [53-5](#)
 - using in your network [53-22](#)
- VLAN maps, PACL and Router ACLs [53-32](#)
- VLANs
- allowed on trunk [19-5](#)
 - configuration guidelines [17-3](#)
 - configuring [17-5](#)
 - configuring as Layer 3 interfaces [34-7](#)
 - customer numbering in service-provider networks [29-3](#)
 - default configuration [17-4](#)
 - description [1-11](#)
 - extended range [17-3](#)
 - IDs (default) [17-5](#)
 - interface assignment [17-7](#)
 - limiting source traffic with RSPAN [57-23](#)
 - monitoring with RSPAN [57-21](#)
 - name (default) [17-5](#)
 - normal range [17-3](#)
 - overview [17-1](#)
 - reserved range [17-3](#)
 - See also PVLANS
- VLAN Trunking Protocol
- See VTP
- VLAN trunks
- overview [19-3](#)
- VLAN User Distribution, configuring 802.1X [46-68](#)
- VMPS
- configuration file example [17-32](#)
 - configuring dynamic access ports on client [17-25](#)
 - configuring retry interval [17-27](#)
 - database configuration file [17-32](#)
 - dynamic port membership
 - example [17-29](#)
 - reconfirming [17-26](#)
 - reconfirming assignments [17-26](#)
 - reconfirming membership interval [17-26](#)
 - server overview [17-21](#)
- VMPS client
- administering and monitoring [17-27](#)
 - configure switch
 - configure reconfirmation interval [17-26](#)
 - dynamic ports [17-25](#)
 - entering IP VMPS address [17-24](#)
 - reconfirmation interval [17-27](#)
 - reconfirm VLAM membership [17-26](#)
 - default configuration [17-24](#)
 - dynamic VLAN membership overview [17-23](#)
 - troubleshooting dynamic port VLAN membership [17-28](#)
- VMPS server
- fall-back VLAN [17-22](#)
 - illegal VMPS client requests [17-23](#)
 - overview [17-21](#)
 - security modes
 - multiple [17-22](#)

- open [17-21](#)
 - secure [17-22](#)
- voice aware 802.1x security
 - port-based authentication
 - configuring [46-74](#)
 - described [46-22, 46-73](#)
- voice interfaces
 - configuring [43-1](#)
- Voice over IP
 - configuring [43-1](#)
- voice ports
 - configuring VVID [43-3](#)
- voice traffic [15-2, 43-5](#)
- voice VLAN
 - IP phone data traffic, described [43-2](#)
 - IP phone voice traffic, described [43-2](#)
- Voice VLAN, configure 802.1X [46-72](#)
- voice VLAN ports
 - using 802.1X [46-22](#)
- VPN
 - configuring routing in [41-8](#)
 - forwarding [41-3](#)
 - routes [41-2](#)
 - routing and forwarding table
 - See VRF
- VRF
 - defining [41-3](#)
 - tables [41-1](#)
- VRF-aware services
 - ARP [41-6, 41-15, 41-17](#)
 - configuring [41-6, 41-15](#)
 - ftp [41-16](#)
 - ping [41-15](#)
 - tftp [41-16](#)
 - traceroute [41-16](#)
 - uRPF [41-16](#)
- VRF-lite
 - description [1-22](#)
- VSS
 - dual-active detection
 - displaying [5-51](#)
 - Enhanced PAgP, advantages [5-23](#)
 - enhanced PAgP, configuring [5-49](#)
 - Enhanced PAgP, description [5-23](#)
 - fast-hello, configuring [5-50](#)
- VTP
 - client, configuring [17-16](#)
 - configuration guidelines [17-12](#)
 - default configuration [17-13](#)
 - disabling [17-16](#)
 - Layer 2 protocol tunneling [29-14](#)
 - monitoring [17-19](#)
 - overview [17-8](#)
 - pruning
 - configuring [17-15](#)
 - See also VTP version 2
 - server, configuring [17-16](#)
 - statistics [17-19](#)
 - transparent mode, configuring [17-16](#)
 - version 2
 - enabling [17-15](#)
- VTP advertisements
 - description [17-9](#)
- VTP domains
 - description [17-8](#)
- VTP modes [17-9](#)
- VTP pruning
 - overview [17-11](#)
- VTP versions 2 and 3
 - overview [17-9](#)
 - See also VTP
- VTY and Network Assistant [16-12](#)
- VVID (voice VLAN ID)
 - and 802.1X authentication [46-22](#)
 - configuring [43-3](#)

W**WCCP**

- configuration examples [71-10](#)
- configuring on a router [71-2, 71-11](#)
- features [71-4](#)
- restrictions [71-5](#)
- service groups [71-6](#)

web-based authentication

- authentication proxy web pages [48-4](#)
- description [1-43, 46-14, 48-1](#)

web-based authentication, interactions with other features [48-4](#)**Web Cache Communication Protocol**

- See WCCP [71-1](#)

web caches

- See cache engines

web cache services

- description [71-4](#)

web caching

- See web cache services
- See also WCCP

web scaling [71-1](#)**weight thresholds in tracked lists** [59-5](#)**Wireshark**

- activating and deactivating, capture points, conceptual [58-9](#)
- attachment points [58-6](#)
- capture filter [58-7](#)
- capture points [58-6](#)
- core system filter [58-6](#)
- decoding and displaying packets [58-9](#)
- display filter [58-7](#)
- feature interactions [58-10](#)
- filters [58-6](#)
- storing captured packets to a .pcap filter [58-8](#)
- usage examples [58-18](#)

Wireshark, about [58-5](#)**Wireshark, activating and deactivating a capture point** [58-13](#)**Wireshark, defining/modifying/deleting a capture point** [58-12](#)**Wireshark, displaying information** [58-14](#)**WS-X46490-CSFP-E, support on a 10-slot chassis** [8-17](#)**Y****Y.1731****default configuration** [65-29](#)**described** [65-27](#)**ETH-AIS****Ethernet Alarm Signal function (ETH-AIS)**[65-28](#)**ETH-RDI** [65-28](#)**multicast Ethernet loopback** [65-31](#)**multicast ETH-LB** [65-29](#)**terminology** [65-27](#)