



New and Changed Information

- [New and Changed Information for This Release, on page 1](#)

New and Changed Information for This Release

The following table provides an overview of the significant changes to this guide for this current release. The table does not provide an exhaustive list of all changes made to this guide or of all new features in this release.

Table 1: New Features and Changed Behavior in Cisco UCS Manager, Release 3.2(3)

Feature	Description	Where Documented
6G-12G Mixed Mode	6G-12G Mixed Mode is available for SAS Expander Configuration Policy .	Creating Sas Expander Configuration Policy
Single Path support for UCS S3260 Dual Pass Through (UCS-S3260-DHBA) controller	In Cisco UCS S3260 M5 servers, Cisco UCS Manager enables single path access to disks by configuring a single DiskPort per disk slot.	Disk Zoning Policies

Table 2: New Features and Changed Behavior in Cisco UCS Manager, Release 3.2(2)

Feature	Description	Where Documented
FlexFlash Removable State now has a No Change option.	This new option is for hypervisors that do not have a FlexFlash non-removable state requirement before installation.	Enabling FlexFlash SD Card Support
Extended support for Cisco UCS C480 M5 Server and Cisco UCS B480 M5 Server.	Cisco UCS Manager support for the UCS C480 M5 rack-mount server and B480 M5 blade server.	Creating a Storage Profile PCH Controller Definition

