

New and Changed Information

- New and Changed Information for Firmware Release 14.2(1), on page 1
- New and Changed Information for Firmware Release 14.1(1), on page 1
- New and Changed Information for Firmware Release 14.0(1), on page 2
- New and Changed Information for Firmware Release 12.8(1), on page 2
- New and Changed Information for Firmware Release 12.7(1), on page 2
- New and Changed Information for Firmware Release 12.6(1), on page 2
- New and Changed Information for Firmware Release 12.5(1)SR3, on page 2
- New and Changed Information for Firmware Release 12.5(1)SR2, on page 3
- New and Changed Information for Firmware Release 12.5(1)SR1, on page 3
- New and Changed Information for Firmware Release 12.5(1), on page 3
- New and Changed Information for Firmware Release 12.1(1), on page 4

New and Changed Information for Firmware Release 14.2(1)

The following information is new or changed for Firmware Release 14.2(1).

Feature	New or Changed
Support for SIP OAuth on SRST	Security Enhancements for Your Phone Network

New and Changed Information for Firmware Release 14.1(1)

The following information is new or changed for Firmware Release 14.1(1).

Feature	New or Changed
SIP OAuth for Proxy TFTP support	Security Enhancements for Your Phone Network
Phone Migration without Transition Load	Migration of your Phone to a Multiplatform Phone Directly

New and Changed Information for Firmware Release 14.0(1)

Table 1: New and Changed Information

Feature	New or Changed
Call Park Monitoring Enhancement	Product Specific Configuration
SIP OAuth Enhancements	Security Enhancements for Your Phone Network
OAuth Enhancements for MRA	Mobile and Remote Access Through Expressway
User Interface Enhancements	Survivable Remote Site Telephony

As of Firmware Release 14.0, the phones support DTLS 1.2. DTLS 1.2 requires Cisco Adaptive Security Appliance (ASA) Release 9.10 or later. You configure the minimum DTLS version for a VPN connection in ASA. For more information, see *ASDM Book 3: Cisco ASA Series VPN ASDM Configuration Guide* at https://www.cisco.com/c/en/us/support/security/asa-5500-series-next-generation-firewalls/products-installation-and-configuration-guides-list.html

New and Changed Information for Firmware Release 12.8(1)

The following information is new or changed for Firmware Release 12.8(1).

Feature	New or Changed Content
Phone Data Migration	Change a User's Phone Model
Add additional information about the Web Access field	Product Specific Configuration

New and Changed Information for Firmware Release 12.7(1)

No administration guide updates were required for Firmware Release 12.7(1).

New and Changed Information for Firmware Release 12.6(1)

No administration guide updates were required for Firmware Release 12.6(1).

New and Changed Information for Firmware Release 12.5(1)SR3

All references to the Cisco Unified Communications Manager documentation have been updated to support all Cisco Unified Communications Manager releases.

Table 2: Cisco IP Phone 8832 Administration Guide Revisions for Firmware Release 12.5(1)SR3

Revision	Updated Section
Support for Activation Code Onboarding and Mobile and Remote Access	Activation Code Onboarding and Mobile and Remote Access
Support for the Problem Report Tool use from Cisco Unified Communications Manager.	Create a Phone Problem Report from Cisco Unified Communications Manager

New and Changed Information for Firmware Release 12.5(1)SR2

No administration guide updates were required for Firmware Release 12.5(1)SR2.

Firmware Release 12.5(1)SR2 replaces Firmware Release 12.5(1) and Firmware 12.5(1)SR1. Firmware Release 12.5(1) and Firmware Release 12.5(1)SR2.

New and Changed Information for Firmware Release 12.5(1)SR1

The following table lists the changes made to the *Cisco IP Conference Phone 8832 Administration Guide for Cisco Unified Communications Manager* to support Firmware Release 12.5(1)SR1.

Table 3: Cisco IP Conference Phone 8832 Administration Guide Revisions for Firmware Release 12.5(1)SR1

Revision	New or Updated Section
Support for Elliptic Curve	Supported Security Features

New and Changed Information for Firmware Release 12.5(1)

The following table lists the changes made to the *Cisco IP Conference Phone 8832 Administration Guide for Cisco Unified Communications Manager* to support Firmware Release 12.5(1).

Table 4: Cisco IP Conference Phone 8832 Administration Guide Revisions for Firmware Release 12.5(1)

Revision	New or Updated Section
Support for Whisper Paging on Cisco Unified Communications Manager Express	Cisco Unified Communications Manager Express Interaction
Support for Disable TLS Ciphers	Product Specific Configuration
Support for Enbloc Dialing for Inter-Digit Timer T.302 Enhancement.	Product Specific Configuration

New and Changed Information for Firmware Release 12.1(1)

The following table describes changes to the *Cisco IP Conference Phone 8832 Administration Guide for Cisco Unified Communications Manager* to support Firmware Release 12.1(1).

Revision	New or Updated Section
Support for Cisco IP Conference Phone 8832 PoE Injector	Phone Power Requirements
	Ways to Provide Power to Your Conference Phone
	• Install the Conference Phone
Support for Wireless Microphones	Cisco IP Conference Phone 8832
	• Wireless Expansion Microphone (8832 Only)
	• Install the Wireless Expansion Microphones
	Install the Wireless Microphone Charging Cradle
Support for Daisy Chain	Cisco IP Conference Phone 8832
	Daisy Chain Mode
	• Install the Conference Phone in Daisy Chain Mode
	One Phone in Daisy Chain Mode Doesn't Work
Support for Cisco IP Conference Phone 8832 Non-PoE Ethernet Injector	Install the Conference Phone
	Ways to Provide Power to Your Conference Phone
Support for Wi-Fi	Install the Conference Phone
	Ways to Provide Power to Your Conference Phone
	Set Domain Name Field
	• Enable Wireless LAN from the Phone
	Set Up the Wireless LAN from Cisco Unified Communications Manager
	• Set Up Wireless LAN from the Phone
	Set the Number of WLAN Authentication Attempts
	Enable WLAN Prompt Mode
	• Set Up a Wi-Fi Profile using Cisco Unified Communications Manager
	Set Up a Wi-Fi Group using Cisco Unified Communications Manager

Revision	New or Updated Section
Support for Mobile and Remote Access Through Expressway	Mobile and Remote Access Through Expressway
	Deployment Scenarios
	Configure User Credentials Persistent for Expressway Sign-In
Support for enabling or disabling TLS 1.2 for web server access.	Product Specific Configuration
Support for G722.2 AMR-WB audio codec	Cisco IP Conference Phone 8832
	Call Statistics Fields

New and Changed Information for Firmware Release 12.1(1)