



Database Schema

This manual describes how data is organized in the Cisco Unified CCX database. The Unified CCX database stores the data in the following two types of databases:

- `db_cra` – Used to store information for historical and real-time reports, including Unified CCX configuration information, stored procedures, and call statistics.
- `db_cra_repository` - Used to store information related to prompts, grammars, scripts, and documents.

All the tables described in this document are in the above two databases.



Note

SQL is case-insensitive and the queries written against the database can be in any case. However, you might have to change the case for the column names depending on the third-party tool that you use for querying the database. Refer to the documentation for these third-party tools for more information.

The following sections include these topics:

- [General Database Concepts](#) , on page 1
- [Database Table Details](#), on page 2

General Database Concepts

This section provides an overview of some basic database concepts.

Tables, Columns, and Rows

A database contains one or more tables of data. Each table in a database defines a set of columns, which are called *fields*. Within each table, the database stores data in rows, which are called *records*. Each record (row) contains one value for each field (column) of the table.

Database tables and the number and names of their fields are constant. The number of records in a table and the data that those records contain will vary according your system.

Table Relationships

Related tables in a database share one or more common fields. For example, both the Skill and the SkillGroup tables include the skillID field. Each record in the Skill table is related to each record in the SkillGroup table that shares the same skillID value.

Relationships between tables can be one-to-one or one-to-many. For example, because one skill can be associated with many skill groups, the relationship between the Skill and SkillGroup tables is one-to-many. On the other hand, each call or call leg has its own set of data about the agent who handled the call and other information. Therefore, the relationship between the AgentConnectionDetail and ContactCallDetail table is one-to-one.

Each database table description in this manual is followed by a Related Tables section. These sections show the fields by which a table is related to other tables. If the fields have different names in each table, these sections show the mapping.

Database Table Details

Each description provides the following information:

- Database Table Name—Name of the Unified CCX database table.
- Field Name—Name of a field as it appears in the database table.
- Description—Description of the field, including valid values where appropriate.
- Storage—Information about the data in each field as follows:
 - Data type used for the field in the database.



Note For storage characteristics and limitations of the data types used for the fields in the databases refer to "IBM Informix SQL Reference Guide". The date and time in the database fields are stored in Coordinated Universal Time (UTC).

- Whether the NULL value is valid for the field. "NULL" if the NULL value is or "NOT NULL" if the NULL value is not valid.



Note If the NULL value is valid, the database will record a value of -1 for a numeric field and an empty string for other fields.

- "Primary Key" if the field is a primary key, or part of a primary key, in the database table.

Overview of Tables

The following tables are described in this guide:

- [AgentConnectionDetail](#), on page 5, contains records written for calls that are connected to an agent.

- [AgentStateDetail](#), on page 8, contains records written when an agent changes state.
- [AgentCallDetailSnapshot](#), on page 9, contains records of agent call details in a day.
- [AgentStateDetailSnapshot](#), on page 10, contains records of agent state change details in a day.
- [AuditReskill](#), on page 12, contains records written when the resource is added or removed from the CSQ because of the changes that are made to the resource or CSQ skills.
- [AuditSkillGroup](#), on page 14, contains records written when the resource skills or competency level changes are made to the resource or CSQ.
- [AreaCode](#), on page 11, contains the area code and time zone information used for outbound calls.
- [Campaign](#), on page 15, contains records with campaign configuration information.
- [CampaignCSQMap](#), on page 18, provides a relationship between campaigns and Contact Service Queues (CSQs).
- [CampaignSupervisorMap](#), on page 19, provides a relationship between campaigns and supervisors.
- [CampaignData](#), on page 20, contains records with the campaign data information.
- [ChatProblemStatement](#), on page 24, contains the associated problem statements and tag ids for each chat widget.
- [ChatTriggerPoint](#), on page 26, contains the chat CSQ tag information.
- [ChatUserForm](#), on page 27, contains the user form fields included in each chat widget along with the order of the fields in the widget.
- [ChatWidget](#), on page 28, contains the chat widget information.
- [ChatBubble](#), on page 29, contains the chat bubble information.
- [ContactCallDetail](#), on page 31, contains records written for every incoming, outgoing, or internal call.
- [ContactQueueDetail](#), on page 38, contains records written for calls that are queued for CSQs; one record for each CSQ is queued.
- [ContactRoutingDetail](#), on page 40, contains records written for calls that are queued for CSQs; one record for each call.
- [ContactServiceQueue](#), on page 41, contains records written for CSQs configured on the Unified CCX Administration user interface.
- [CrsApplication](#), on page 45, contains records about applications that are uniquely identified by application name.
- [CrsGroup](#), on page 48, contains records about groups that are identified by a combination of group class name and group ID.
- [CrsTrigger](#), on page 49, contains records about triggers that are uniquely identified by trigger name.
- [DialingList](#), on page 53, contains records with outbound contacts that need to be dialed for a particular campaign.
- [MonitoredResourceDetail](#), on page 63, contains records written for agents who are monitored by a Supervisor.

- [ProfileIDMapping](#), on page 65, contains records written for profiles defined on the Unified CCX Administration user interface.
- [PurgeHistory](#), on page 66, contains records written for tracking of the history of purge information for both Manual and Scheduled purge.
- [RemoteMonitoringDetail](#), on page 68, contains records written for remote monitoring calls made by a Supervisor.
- [Resource](#), on page 70, contains records written for resources (agents) that are configured on the Cisco Unified Communications Manager (Unified CM) Administration user interface.
- [ResourceGroup](#), on page 73, contains records written for resource groups configured on the Unified CCX Administration user interface.
- [ResourceSkillMapping](#), on page 73, is a relationship table between resources and skills.
- [RmonCSQConfig](#), on page 74, contains records written for CSQs configured for a Supervisor's remote monitoring allowed list on the Unified CCX Administration user interface.
- [RmonResConfig](#), on page 75, contains records written for resources configured for a Supervisor's remote monitoring allowed list on the Unified CCX Administration user interface.
- [RmonUser](#), on page 76, contains records written for remote monitoring Supervisors configured on the Unified CCX Administration user interface.
- [RtCSQsSummary](#), on page 76, contains real-time statistics for configured CSQs.
- [RtICDStatistics](#), on page 78, contains Unified CCX summary statistics.
- [Skill](#), on page 80, contains records written for skills configured on the Unified CCX Administration user interface.
- [SkillGroup](#), on page 81, is a relationship table between skills and CSQs.
- [Supervisor](#), on page 82, contains records written for Supervisors configured on the Unified CCX Administration user interface.
- [SupervisorCampaignMap](#), on page 83, contains records for the list of campaigns that can be associated with no or more campaigns to a Supervisor and managed by the Supervisor.
- [SupervisorApplicationMap](#), on page 84, contains records for the list of applications that can be associated to a Supervisor and managed by the Supervisor.
- [Team](#), on page 85, contains records written for teams configured on the Unified CCX Administration user interface.
- [TeamCSQMapping](#), on page 86, is a relationship table between teams and CSQs.
- [TextAgentConnectionDetail](#), on page 87, contains information relating to the agent who handled the contact or leg.
- [TextAgentStateDetails](#), on page 89, contains information about the chat agent and about the event that caused the chat agent state change.
- [TextContactDetail](#), on page 90, contains detailed information about the contact or leg.
- [TextContactQueueDetail](#), on page 93, is a relationship table between teams and CSQs.

- [TextCustomerDetails](#), on page 94, contains customer-related information corresponding to the chat contact.
- [WorkflowTask](#), on page 96, contains records written for workflow tasks that are executed.

AgentConnectionDetail

Database table name: AgentConnectionDetail

The Unified CCX system creates a new record in the AgentConnectionDetail table when an agent disconnects a call or a leg by hanging up or by transferring the call. (A new call leg starts each time that a call is transferred, except when a call is transferred from a Cisco Computer Telephony Interface [CTI] port to an agent.)

An AgentConnectionDetail record contains information relating to the agent who handled the call or call leg.

Table 1: AgentConnectionDetail Table Fields

Field Name	Description	Storage
sessionID	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call.	decimal(18, 0) NOT NULL Primary Key
sessionSeqNum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
nodeID	Unique identifier assigned to each Unified CCX server in the cluster.	smallint NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceID	Identifier of the agent who handled the call.	int NOT NULL Primary Key
startDateTime	Date and time that the call or the leg started ringing at the device of an agent.	datetime year to fraction (3) NOT NULL Primary Key
endDateTime	Date and time that the call or the leg was transferred or disconnected.	datetime year to fraction (3) NOT NULL

Field Name	Description	Storage
qIndex	A new qIndex is created whenever a Unified CCX call is conferenced to a Unified CCX route point.	smallint NOT NULL Primary Key
gmtOffset	Offset, in minutes, between the local time of the Unified CCX server and Greenwich Mean Time. As the time information is stored in GMT, this field will always be zero.	smallint NOT NULL
ringTime	Amount of time, in seconds, between the time the call or the leg first rang at the extension of an agent and one of the following events: <ul style="list-style-type: none"> • The agent answered the call or the leg • The caller hung up before the call or the leg was answered • The system retrieved the call or the leg before the call or the leg was answered 	smallint NULL
talkTime	Amount of time, in seconds, that passed from the time an agent answered the call or the leg to the time the call or the leg was disconnected or transferred, not including hold time.	smallint NULL
holdTime	Amount of time, in seconds, that the call or the leg spent on hold.	smallint NULL
workTime	Amount of time, in seconds, that an agent spent in Work State after the call or the leg.	smallint NULL
callWrapupData	After-call information that the agent enters through the Agent Desktop user interface while the agent is in the work state.	varchar(40) NULL

Field Name	Description	Storage
callResult	<p>Outcome of the outbound dialer call.</p> <p>1 = Voice (Customer answered and was connected to agent)</p> <p>2 = Fax/Modem (Fax machine detected)</p> <p>3 = Answering Machine (answering machine detected)</p> <p>4 = Invalid (Number reported as invalid by the network)</p> <p>5 = Do Not Call (customer does not want to be called again)</p> <p>6 = Wrong Number (number successfully contacted but wrong number)</p> <p>7 = Customer Not Home (number successfully contacted but reached the wrong person)</p> <p>8 = Callback (customer requested regular callback)</p> <p>9 = Agent Rejected (Agent has skipped or rejected a preview call)</p> <p>10 = Agent Closed (Agent has skipped or rejected a preview call with the close option)</p> <p>11 = Busy (busy signal detected)</p> <p>12 = RNA (the agent lets the call go ring-no-answer)</p> <p>20 = OB_XFER is default (the agent transfers or conferences the outbound call to another agent.</p>	<p>smallint</p> <p>NULL</p>
dialinglistid	<p>Unique identifier of a contact that is dialed for an outbound campaign. Links with DialingList.dialingListID</p>	<p>int</p> <p>NULL</p>
rna	<p>Specifies if the call or the leg hasn't been answered by an agent within the configured ring time. This equates to 't' if the call hasn't been answered.</p>	<p>Boolean</p>

Related Topics

- [ContactCallDetail](#), on page 31
- [ContactRoutingDetail](#) , on page 40
- [DialingList](#) , on page 53
- [MonitoredResourceDetail](#), on page 63
- [ProfileIDMapping](#), on page 65
- [PurgeHistory](#), on page 66
- [Resource](#) , on page 70

AgentStateDetail

Database table name: AgentStateDetail

The Unified CCX system creates a new record in the AgentStateDetail table each time the state of an agent changes. An AgentStateDetail record contains information about the agent and about the event that caused the agent state change.

Table 2: AgentStateDetail Table Fields

Field Name	Description	Storage
agentID	Identifier of the agent whose state has changed.	int NOT NULL Primary Key
eventDateTime	Date and time that the agent state changed.	datetime year to fraction (3) NOT NULL Primary Key
gmtOffset	Offset, in minutes, between the local time of the Unified CCX server and Greenwich Mean Time. As the time information is stored in GMT, this field will always be zero.	smallint NOT NULL
eventType	Event that triggered the agent state change: 1—Log In 2—Not Ready 3—Ready 4—Reserved 5—Talking 6—Work 7—Log Out	smallint NOT NULL Primary Key
reasonCode	Code, as set up in the Cisco Desktop Administrator, for the reason that the agent changed to Not Ready State or to Log Out State. Null if a reason code is not configured.	smallint NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Related Topics

[ProfileIDMapping](#), on page 65

[Resource](#) , on page 70

AgentCallDetailSnapshot

Database table name: AgentCallDetailSnapshot

The Unified CCX system stores the records of agent call details in a day in the AgentCallDetailSnapshot table. All previous day records will be purged as part of the scheduled purge at mid-night.

Table 3: AgentCallDetailSnapshot Table Fields

Field Name	Description	Storage
contactid	Alphanumeric identifier for the contact.	int NOT NULL Primary Key
sessionseqnum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
agentID	Identifier of the agent whose ACD call details are stored.	int NOT NULL Primary Key
calltype	Identifier of the type of all incoming and outgoing calls of agents' ACD line extension.	int NOT NULL
startdatetime	Start date and time of the agent call details that are to be stored.	BIG INT NOT NULL Primary Key
phonenumber	Identifier of the phone number of the calls that were handled by the agent.	varchar (30) NOT NULL
disposition	Identifier of the contact disposition.	int NULL
wrapupdata	Information that the agents enter in the desktop user interface after a call, while the agents are still in the work state.	lvarchar (804) NULL
csqname	Identifier of the CSQ name that the agent was assigned to.	nvarchar (50) NULL
enddatetime	End date and time of the agent call details that are to be stored.	BIG INT NOT NULL

Related Topics

[Resource](#) , on page 70

AgentStateDetailSnapshot

Database table name: AgentStateDetailSnapshot

The Unified CCX system stores the records of agent state change details in a day in the AgentStateDetailSnapshot table. All previous day records will be purged as part of the scheduled purge at mid-night.

Table 4: AgentStateDetailSnapshot Table Fields

Field Name	Description	Storage
agentID	Identifier of the agent whose state has changed.	int NOT NULL Primary Key
eventDateTime	Date and time that the agent state changed.	BIG INT NOT NULL Primary Key
eventType	Event that triggered the agent state change: 1—Log In 2—Not Ready 3—Ready 4—Reserved 5—Talking 6—Work 7—Log Out	smallint NOT NULL Primary Key
reasonCode	Code, as set up in the Cisco Desktop Administrator, for the reason that the agent changed to Not Ready State or to Log Out State. Null if a reason code is not configured.	smallint NOT NULL Primary Key
wrapupData	After-call information that the agent enters through the Agent Desktop user interface while the agent is in the work state.	Ivarchar (804) NULL

Related Tables

- [Resource](#) , on page 70 (agentID maps to resourceID and via profileID)

Related Topics

[Resource](#) , on page 70

AreaCode

Database table name: AreaCode

The AreaCode table contains a mapping of area codes and their time zones. This table is used as a reference for populating the `gmtPhone` and `dstPhone` columns of the `DialingList` table. This table is pre-populated by the Unified CCX system with the data for North America during the installation process, using a SQL script that the installer invokes. If the Unified CCX is installed in a different location, administrators can enter the area code and time zone information for that region using Unified CCX Administration, and the data is stored in this table.

Table 5: AreaCode Table Fields

Field Name	Description	Storage
<code>profileid</code>	Identifier of the profile.	int NOT NULL Primary Key
<code>createdatetime</code>	Default -CURRENT_TIMESTAMP	datetime year to second NOT NULL
<code>recordid</code>	Unique identifier for the record	int NOT NULL Primary Key
<code>areacode</code>	The area code of the call.	nvarchar(10) NOT NULL Primary Key
<code>regioncode</code>	Uses the same data as that of <code>gmtzone</code> .	nvarchar(10) NULL
<code>daylightsavingsenabled</code>	Indicates whether daylight savings time is observed. <ul style="list-style-type: none"> • N = Daylight savings time is not observed. • Y = Daylight savings time is observed. 	char(1) NOT NULL
<code>gmtzone</code>	Stores identifiers that internally maps to the GMT offset corresponding to the area code.	int NULL
<code>privatedata</code>	Any fields which are to be used internally only.	BLOB NULL

Field Name	Description	Storage
active	Whether the record is active in the system. A record becomes inactive if the team is deleted from the system. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date this record was deleted.	datetime year to second NULL

Related Topics

[ProfileIDMapping](#), on page 65

[DialingList](#), on page 53

AuditReskill

Database table name: audit_reskill

The Unified CCX system creates a new record in the audit_reskill table for addition, deletion, and increase or decrease in the competency level of resources or CSQ skills.

Supervisors can revert the changes that are made to the resource skills either manually or through the Auto-Removal option from the Supervisor desktop.

Table 6: audit_reskill Table Fields

Field Name	Description	Storage
recordID	Numeric identifier of the record.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceLoginID	User ID in the Unified CM configuration.	nvarchar(50,0) NOT NULL
csqID	Numeric identifier for the CSQ.	int NOT NULL

Field Name	Description	Storage
operation	The type of operation performed on the resource or CSQ: <ul style="list-style-type: none"> • Resource_Modified(1) • Csq_Modified(2) • Csq_Added(3) • Csq_Deleted(4) • Skill_Deleted(5) 	smallint NOT NULL
result	The resultant action because of type of operation performed on the resource: <ul style="list-style-type: none"> • Added_to_csq(1) • Removed_from_csq(2) 	smallint NOT NULL
skillgrouprecordid	The record ID corresponding to the skill group from the audit_skillgroup table for a CSQ.	int NOT NULL
reskiller	Login ID of the user.	nvarchar(100,0) NOT NULL
reskiller_type	Resource is reskilled by: <ul style="list-style-type: none"> • Supervisor(1) • Admin(2) • System(3) <p>Note If the resource is reskilled by the Auto-Removal option, the reskiller_type is System.</p>	smallint NOT NULL
reskilledtimestamp	Date and Time this record was changed.	datetime year to fraction(3) NOT NULL
active	Indicates whether the record is active based on the values in the "result" field in the audit_reskill table. <ul style="list-style-type: none"> • True=The record is active when a resource is added to a CSQ and the value of the "result" field is "Added_to_csq". • False =The record is inactive when the resource is removed from the CSQ and the value of the "result" field is "Removed_from_csq". If an active record exists for the same resource and the same CSQ, then this record is also marked inactive. 	boolean NOT NULL

Related Topics

[AuditSkillGroup](#), on page 14

AuditSkillGroup

Database table name: audit_skillgroup

The Unified CCX system creates a new record in the audit_skillgroup table when resources are added or removed from a CSQ. This record is created when addition, deletion, or increase or decrease in the competency level of a resource skill.

Table 7: audit_skillgroup Table Fields

Field Name	Description	Storage
recordID	Numeric identifier of the record.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
skillID	Numeric identifier of the skill.	int NOT NULL Primary Key
fromcompetency	Existing skill level of the agents. Values range from 1 (lowest) to 10 (highest).	int NOT NULL
tocompetency	Modified skill level of the agents. Values range from 1 (lowest) to 10 (highest).	int NOT NULL
operation	The type of operation performed on the skill: <ul style="list-style-type: none"> • Skill Add(1) • Skill Removed(2) • Competency Increased(3) • Competency Decreased(4) 	smallint NOT NULL

Related Topics

[AuditReskill](#), on page 12

CalendarAssociation

Database table name: CalendarAssociation

The calendar and application association is persisted in the CalendarAssociation table.

Table 8: CalendarAssociation Table Fields

Field Name	Description	Storage
recordid	Unique identifier of the record.	serial NOT NULL Primary Key
calendarid	A unique identifier for the calendar.	int NOT NULL
entity	Application name or the chat widget ID associated with the calendar.	nvarchar(50) NOT NULL
entitytype	Indicates whether the calendar is associated with an application or a chat widget.	smallint NOT NULL
active	Indicates wheather the record is deleted.	boolean NOT NULL
dateinactive	Date and time when the record was deleted.	datetime year to second

Campaign

Database table name: Campaign

The campaign configuration information is stored in this table. A campaign is associated with one or more CSQs. This mapping of Campaigns and CSQs is stored separately in CampaignCSQMap table.

Table 9: Campaign Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key
campaignid	A unique identifier for the campaign.	int NOT NULL Primary Key
profileid	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Field Name	Description	Storage
createdatetime	Default -CURRENT_TIMESTAMP	datetime year to second NOT NULL
campaignname	Name of the campaign. Must be unique.	nvarchar(10) NULL
enabled	<ul style="list-style-type: none"> • 0 = campaign is enabled • 1 = campaign is disabled 	smallint NOT NULL
description	A description of the campaign.	varchar(50) NULL
starttime	When the campaign starts (based on server time). This is stored in minutes.	int NOT NULL
endtime	When the campaign ends (based on server time). This is stored in minutes.	int NOT NULL
cache size	Number of contacts to be retrieved in a batch for dialing for this campaign.	int NOT NULL
maxattempts	Maximum number of attempts made to dial a contact for this campaign.	int NOT NULL
ansmachineretry	<p>0 = Dialer should try dialing a contact again if it reached an answering machine</p> <p>1 = Dialer should not try dialing a contact again if it reached an answering machine</p>	smallint NOT NULL
callbacktimelimit	The amount of time in minutes before and after the scheduled callback time, during which the Dialer attempts a callback.	int NULL
missedcallbackaction	<p>Indicates what the Dialer should do if a callback could not be placed at the scheduled time:</p> <p>0 = reschedule callback to same time the next business day</p> <p>1 = make an ordinary retry</p> <p>2 = close record</p>	int NULL
privatedata	Any fields which are used internally only can be stored in this column in a blob.	BLOB NULL

Field Name	Description	Storage
active	Indicates whether the record is active in the system. A record becomes inactive if the campaign is deleted from the system. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date this record was deleted.	datetime year to second NULL
dialertype	The type of the dialer used for the campaign. The dialer can be any one of the following three types - Predictive, Progressive or Preview Outbound. 0 - Direct Preview Dialer 1 - IVR based Predictive Dialer 2 - IVR based Progressive Dialer Default value = 0	smallint NOT NULL
campaignType	The campaign type can be IVR-based or ICD-based. 0 - IVR based campaign 1 - Agent based campaign Default value = 1	smallint NOT NULL
campaignCallingNum	The campaign calling number that is displayed to the contact. This number is used by the outbound IVR dialer. Note This field will have value only if you have an Outbound IVR license on top of Unified CCX premium license in your Unified CCX and the dialer type is progressive or predictive.	BLOB NULL
applicationTrigger	This is the JTAPI trigger associated with this campaign. Note This field will have value only if you have an Outbound IVR license on top of Unified CCX premium license in your Unified CCX and the dialer type is progressive or predictive.	BLOB NULL

Field Name	Description	Storage
applicationName	<p>The name of the application associated with the above-mentioned JTAPI trigger.</p> <p>Note This field will have value only if you have an Outbound IVR license on top of Unified CCX premium license in your Unified CCX and the dialer type is progressive or predictive.</p>	BLOB NULL

Related Topics

[CampaignCSQMap](#), on page 18

[ContactCallDetail](#), on page 31

[ProfileIDMapping](#), on page 65

[DialingList](#), on page 53

CampaignCSQMap

Database table name: CampaignCSQMap

The CampaignCSQMap table shows the relationship between campaigns and contact service queues (CSQs). A new record is created in the CampaignCSQMap table when a campaign is associated with a CSQ in Unified CCX Administration.

Table 10: CampaignCSQMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record	int NOT NULL Primary Key
campaignid	A unique identifier for the campaign, from the Campaign table.	int NOT NULL Primary Key
csqid	A unique identifier for the CSQ, from the ContactServiceQueue table.	int NOT NULL Primary Key
active	<p>Indicates whether the record is active in the system. A record becomes inactive if the campaign is deleted from the system.</p> <p>f = Inactive t = Active</p>	smallint NULL

Field Name	Description	Storage
createdatetime	Default, CURRENT_TIME_STAMP	datetime year to second NULL
dateinactive	Date this record was deleted.	datetime year to second NULL

Related Topics

[Campaign](#), on page 15

[ContactServiceQueue](#) , on page 41

CampaignSupervisorMap

Database table name: CampaignSupervisorMap

The CampaignSupervisorMap table shows the relationship between campaign and supervisor associated with that campaign. A new record is created in the CampaignSupervisorMap table when a campaign is associated with a supervisor in Unified CCX Administration.

Table 11: CampaignSupervisorMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record	int NOT NULL Primary Key
campaignid	A unique identifier for the campaign, from the Campaign table.	int NOT NULL Primary Key
supervisorid	A unique identifier for the supervisor, based on the supervisor's resourceloginid.	nvarchar(50,0) NOT NULL Primary Key
active	Indicates whether the record is active in the system. A record becomes inactive if the campaign is deleted from the system. f = Inactive t = Active	boolean NOT NULL
createdatetime	Default, CURRENT_TIME_STAMP	datetime year to second NOT NULL

Field Name	Description	Storage
dateinactive	Date this record was deleted.	datetime year to second NULL

Related Topics

[Campaign](#), on page 15

[Supervisor](#), on page 82

CampaignData

Database table name: CampaignData

If you have configured a campaign as an outbound IVR campaign and have chosen Predictive dialer type, the number of lines per port along with the other parameters are stored in the CampaignData table every half hour.

Table 12: CampaignCSQMap Table Fields

Field Name	Description	Storage
recordId	A unique identifier for the record	int NOT NULL Primary Key
campaignId	The campaign for which the data is recorded	int NOT NULL Primary Key
startDate	Start date and time of the interval	datetime year to fraction NOT NULL
endDate	End date and time of the interval	datetime year to fraction NOT NULL
attemptedCalls	The number of attempted calls in the interval	int NOT NULL
abandonedCalls	The number of abandoned calls in the interval	int NOT NULL
voiceCalls	The number of voice calls in the interval	int NOT NULL

Field Name	Description	Storage
linesPerPort	Lines Per Port value computed depending on the abandoned calls/voice calls	decimal(8, 3) NOT NULL
active	Indicates whether the data stored is for an active campaign or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	The date on which this campaign was deleted	datetime year to fraction

Related Topics

[Campaign](#), on page 15

CCCalendar

Database table name: CCCalendar

This table stores the calendar information.

Table 13: CCCalendar Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	serial NOT NULL Primary Key
calid	A unique identifier for the calendar.	int NOT NULL
name	Name of the calendar.	lvarchar (30) NOT NULL
description	The description of the calendar that is configured in the Unified CCX Administration Calendar Management.	lvarchar (70) NULL
timezone	The time zone of the calendar.	nvarchar (50) NOT NULL
caltype	Indicates the type of calendar. <ul style="list-style-type: none"> • 1—Full time • 2—Flexible 	smallint NOT NULL

Field Name	Description	Storage
hasspecialdays	Indicates the availability of the special days.	boolean NOT NULL
hasholidays	Indicates the availability of the holidays.	boolean NOT NULL
active	Indicates whether the record is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date and time of the record when it is marked as inactive.	DATETIME year to second NULL

CCHolidays

Database table name: CCHolidays

This table stores the configured business holidays of a calendar.

Table 14: CCHolidays Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	serial NOT NULL Primary Key
calid	A unique identifier for the calendar.	int NOT NULL
name	Name of the calendar.	nvarchar (50) NOT NULL
caldate	Date of the special day.	DATETIME YEAR TO DAY NOT NULL
active	Indicates whether the record is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date and time of the record when it is marked as inactive.	DATETIME year to second NULL

ChannelProvider

Database table name: ChannelProvider

This table contains the channel provider configurations, including the type of channel, and server details with fully qualified domain name (FQDN), protocol, and port. Channel providers enable the use of non-interactive media channels such as email with Unified CCX.

Table 15: ChannelProvider Table Fields

Field Name	Description	Storage
Id	Unique identifier of the channel provider. Server ID is the foreign key that associates this table with the ContactServiceQueue table.	int NOT NULL Primary Key
channelType	Type of contact channel.	varchar (20, 0) NOT NULL
sendserverfqdn	FQDN of the channel provider for sending the channel type.	Varchar(255, 0) NOT NULL
sendprotocol	Sending protocol that is used to communicate with the channel provider.	Varchar(20, 0) NOT NULL
sendserverport	16-bit port number that is used to communicate with the channel provider for sending the channel type.	int NOT NULL
receiveserverfqdn	FQDN of the channel provider for receiving the channel type.	Varchar(255, 0) NOT NULL
receiveprotocol	Receiving protocol that is used to communicate with the channel provider.	Varchar(20, 0) NOT NULL
receiveserverport	16-bit port number that is used to communicate with the channel provider for receiving the channel type.	int NOT NULL
description	Description of the channel provider.	Lvarchar(400)
active	Indicates whether the record is currently active or not. A record becomes inactive if the record is deleted or updated from the system. f = Inactive t = Active	Boolean NOT NULL
dateinactive	If the active field is "f", this field indicates the date and time that the record became inactive.	datetime year to second

Field Name	Description	Storage
proxytype	Indicates whether Enable/Disable option is selected for SOCKS Proxy in Mail server configuration page.	Lvarchar(25)
mailservertype	Indicates the mail server type. The default is microsoft.	Lvarchar(50)

Related Topics

[ContactServiceQueue](#) , on page 41

ChatProblemStatement

Database table name: ChatProblemStatement

This table contains the associated problem statements and tag ids for each chat widget. Chat widget is the widget that enables the Unified CCX Administrator to create a chat interface for the end user.

Table 16: ChatProblemStatement Table Fields

Field Name	Description	Storage
wdID	Unique ID for each chat widget. It is the foreign key which associates this table with the chatwidget table.	int NOT NULL Primary Key
tagID	The tagID for the csq associated with the problem statement.	nvarchar(50) NOT NULL
problemStmt	The definition of the problem.	lvarchar (256) NOT NULL
psOrder	Order of the problem statement in the chat widget.	int NOT NULL Primary Key

Related Topics

[ChatWidget](#), on page 28

ChatScheduledHours

Database table name: ChatScheduledHours

This table stores the custom weekly business hours configured by administrator.

Table 17: ChatScheduledHours Table Fields

Field Name	Description	Storage
profileId	A unique identifier for the record.	int NOT NULL Primary Key
wdID	A unique ID for each widget.	int NOT NULL Primary Key
scheduledDay	Scheduled working days in a week.	LVARCHAR(3) NOT NULL
fromTime	Start time of business hours.	int NOT NULL
toTime	End time of business hours.	int NOT NULL
active	Indicates whether the widget is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	The date and time when the record became inactive.	datetime year to second

ChatScheduledSpecialDays

Database table name: ChatScheduledSpecialDays

This table stores the business holidays and specially extended hours for specific days.

Table 18: ChatScheduledSpecialDays Table Fields

Field Name	Description	Storage
profileId	A unique identifier for the record.	int NOT NULL Primary Key
wdID	A unique ID for each widget.	int NOT NULL Primary Key

Field Name	Description	Storage
customType	Scheduled business holiday or the special day.	small int NOT NULL
name	Name of the business holiday or the special day.	LVARCHAR(256) NOT NULL
dateConfigured	Date of the business holiday or the special day.	datetime year to second NOT NULL
fromTime	Start time of business hours.	int
toTime	End time of business hours.	int
active	Indicates whether the widget is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	The date and time when the record became inactive.	datetime year to second

ChatTriggerPoint

Database table name: ChatTriggerPoint

This table describes chat CSQ tag information. A ChatTriggerPoint is uniquely identified by a csqID and a chattriggerpointname. Chat contacts inserted into Unified CCX are queued to respective CSQs based on the chattriggerpointname present in the contact. When a chat CSQ is created, a new record is inserted into this table. When a CSQ is modified, the old record is marked as inactive, and a new record is inserted into the table with a the new csqID. When a CSQ is deleted, the corresponding record is marked as inactive.

Table 19: ChatTriggerPoint Table Fields

Field Name	Description	Storage
csqID	Numeric identifier for the CSQ.	int NOT NULL
chattriggerpointname	Name of fields present in the chat trigger point.	Ivarchar(256) NOT NULL
active	Indicates whether the record is currently active. f = Inactive t = Active	boolean NOT NULL

Field Name	Description	Storage
dateinactive	If the active field is “f”, date and time that the record became inactive.	Datetime year to fraction(3) NULL

Related Topics

[ChatUserForm](#), on page 27

ChatUserForm

Database table name: ChatUserForm

This table contains the user form fields included in each chat widget along with the order of the fields in the widget.

Table 20: ChatUserForm Table Fields

Field Name	Description	Storage
wdID	Unique ID for each chat widget. It is the foreign key which associates this table with the chatwidget table.	int NOT NULL Primary Key
fieldName	Name of fields present in the user form.	lvarchar (200) NOT NULL
fieldID	ID of fields present in the user form.	int NOT NULL Primary Key
fieldOrder	Order of the field in the widget.	smallint NOT NULL
active	Indicates whether the record is currently active or not. f = Inactive t = Active	Boolean NOT NULL
lastmodifieddate	The date and time when the user form details were last modified.	datetime year to fraction (3)

Related Topics

[ChatWidget](#), on page 28

ChatWidget

Database table name: ChatWidget

This table stores the chat widget information.

Table 21: ChatWidget Table Fields

Field Name	Description	Storage
wdID	A unique ID for each widget.	int NOT NULL Primary Key
wdName	Name of the widget.	Ivarchar (50) NOT NULL
wdDescription	The description of the widget that is configured in the Unified CCX Administration.	Ivarchar (256) NULL
wdWelcome	The welcome message that is displayed when the customer joins the chat sessions.	Ivarchar (256) NULL
wdLogo	The Location of the logo file that is displayed in the customer facing chat widget.	Ivarchar (256) NULL
wdError	The message that is displayed to the customer when the chat is unavailable.	Ivarchar (360)
wdJoinTimeout	The message that is displayed to the customer when a chat request is not handled within the set time.	Ivarchar (256) NULL
wdCode	Blob data to store the HTML code generated for the widget.	BLOB NULL
active	Indicates whether the widget is currently active or not. f = Inactive t = Active	boolean NOT NULL
lastModifiedDate	The date and time on which the widget details were last modified.	datetime year to fraction (3) NULL
wdContextServiceFieldsets	The context service specific field sets used to capture information that are related to the contact being served over the chat session.	Ivarchar(1024) NULL

Field Name	Description	Storage
offHoursMessage	A message to be displayed off the scheduled business hours.	lvarchar (256) NULL
wdType	Indicates the type of widget: <ul style="list-style-type: none"> • 0- Chat Bubble 	small int NOT NULL Default 0

Related Topics

[ChatProblemStatement](#), on page 24

[ChatUserForm](#), on page 27

[ChatBubble](#), on page 29

ChatBubble

Database table name: ChatBubble

This table stores the chat bubble information.

Table 22: ChatBubble Table Fields

Field Name	Description	Storage
recordId	A unique ID for a set of chat bubble properties.	int NOT NULL Primary Key
wdId	The ID of the chat widget record that contains the chat bubble record. It is the foreign key which associates this table with the chatwidget table.	int NOT NULL Primary Key
titleText	Title text of the chat bubble.	lvarchar (96) NOT NULL
titleTextColor	Text color of the chat bubble title in hex code.	lvarchar (7) NOT NULL
titleBackgroundColor	Background color of the chat bubble title text in hex code.	lvarchar (7) NOT NULL Default #EBEBEC
buttonText	The text of the chat button.	lvarchar (60) NOT NULL

Field Name	Description	Storage
buttonTextColor	Color of the chat button text in hex code.	Ivarchar (7) NOT NULL
buttonBackgroundColor	Background color of the chat button in hex code.	Ivarchar (7) NOT NULL
afterResumeNewChatMsg	Text on the chat window that demarks new chat messages from old ones.	Ivarchar (60) NOT NULL
agentMessageTextColor	Color of the agent message text in hex code.	Ivarchar (7) NOT NULL
agentMessageBackgroundColor	Background color of the agent message in hex code.	Ivarchar(7) NOT NULL
fontTypeFace	Font family used for the text in the chat web form and chat window.	Ivarchar (120) NOT NULL
problemStmntCaption	Label that asks the user to choose a problem statement.	Ivarchar (120) NOT NULL
ratingEnabled	Whether post-chat rating is available for the chat.	boolean NOT NULL
active	Indicates whether the entry is active or inactive. f= Inactive t= Active	boolean NOT NULL
dateInactive	Date when the record became inactive.	datetime year to second

ChatBubbleMessage

Database table name: ChatBubbleMessage

This table stores information about chat bubble messages.

Table 23: ChatBubbleMessage Table Fields

Field Name	Description	Storage
recordId	A unique ID for a set of chat bubble message properties.	int NOT NULL Primary Key

Field Name	Description	Storage
wdId	The ID of the chat widget record that contains the chat bubble message record. It is the foreign key which associates this table with the chatwidget table.	int NOT NULL Primary Key
messageTitle	The title of the chat bubble message field.	lvarchar (50) NOT NULL
messageValue	The value entered for the field.	lvarchar (360) NOT NULL

ContactCallDetail

Database table name: ContactCallDetail

The Unified CCX system creates a new record in the ContactCallDetail table for each call or call leg processed by the system. A new call leg starts each time that a call is transferred or redirected, except when a call is transferred from a Cisco CTI port to an agent.

A ContactCallDetail record contains detailed information about the call or leg. A minimum of one such record will exist for each call.

Table 24: ContactQueueDetail Table Fields

Field Name	Description	Storage
sessionID	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call.	decimal(18,0) NOT NULL Primary Key
sessionSeqNum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
nodeID	Unique identifier assigned to each server in the cluster.	smallint NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Field Name	Description	Storage
contactType	<p>Contact type of the call or the leg:</p> <ul style="list-style-type: none"> • 1—Incoming. Outside call received by the Unified CCX system. • 2—Outgoing. Call originated by the Unified CCX system, other than a call made within the system. • 3—Internal. Call transferred or conferenced between agents, or a call made within the system. • 4—Redirect in • 5—Transfer in • 6—Preview Outbound • 7—IVR Outbound • 8—Agent Outbound • 9—Agent Outbound call transferred to IVR 	<p>smallint NOT NULL</p>
contactDisposition	<p>Disposition of the call or the leg.</p> <ul style="list-style-type: none"> • 1—Abandoned • 2—Handled • 3—Do not care • 4—Aborted¹ • 5-22—Rejected • 99—Cleared 	<p>smallint NOT NULL</p>
dispositionReason	<p>Reason why the call is aborted or rejected by the system.</p>	<p>varchar(100,0) NULL</p>
originatorType	<p>Originator of the call or the leg:</p> <ul style="list-style-type: none"> • 1—Agent. Call originated by an agent. • 2—Device. Call originated by a simulated caller (used for testing) and an agent phone where the agent is not currently logged in. • 3—Unknown. Call originated by an outside caller through a gateway or by an unknown device. 	<p>smallint NOT NULL</p>

Field Name	Description	Storage
originatorID	Numeric identifier of the agent who originated the call or the leg. Used only if originatorType is 1.	int NULL
originatorDN	If originatorType is 1 and the call was placed by the agent using the non-IPCC extension then this field contains the non-IPCC extension, else it contains an empty character ("). If originatorType is 2, this field shows the CTI port number. If originatorType is 3, this field shows the telephone number of the caller as received by the Unified CM, if available. An empty character (") if originatorType is 1. This is not applicable for agent based progressive and predictive outbound calls.	nvarchar(30,0) NULL
destinationType	Destination of the call or the leg: <ul style="list-style-type: none"> • 1—Agent. Call presented to an agent. • 2—Device. Call presented to a route point. • 3—Unknown. Call presented to an outside destination through a gateway or to an unknown device. • Null if no destination. 	smallint NULL
destinationID	Numeric identifier of the agent who received the call or the leg. Used only if destinationType is 1.	int NULL
destinationDN	If the destinationType is 1 and the call was received by an agent using the non-IPCC extension, then this field contains the non-IPCC extension, else it contains an empty character ("). If destinationType is 2, this field shows the CTI port number. If destinationType is 3, this field shows the telephone number called, if available. An empty character (") if destinationType is 1.	nvarchar(30) NULL

Field Name	Description	Storage
startDateTime	<p>For an incoming call or a leg, date and time that the call or the leg started to ring in the system.</p> <p>For an internal call or for an outgoing call, date and time that the call originated.</p> <p>For a transferred call or a leg, endDateTime of the transferring call or leg.</p>	<p>datetime year to fraction (3)</p> <p>NOT NULL</p>
endDateTime	Date and time that this call or the leg was transferred or was disconnected.	<p>datetime year to fraction (3)</p> <p>NOT NULL</p>
gmtOffset	Offset, in minutes, between the local time of the Unified CCX server and Greenwich Mean Time. As the time information is stored in GMT, this field will always be zero.	<p>smallint</p> <p>NOT NULL</p>
calledNumber	<p>Telephone number of the device to which the call or leg was presented.</p> <p>If the call or leg was placed to a Unified CCX Route Point, this field shows the directory number configured in the Unified CM for that Route Point.</p> <p>If the call was placed to an external party, this field shows the telephone number dialed by the caller.</p>	<p>nvarchar(30)</p> <p>NULL</p>
origCalledNumber	<p>Telephone number dialed by the caller if the call was placed from an IP phone.</p> <p>The Unified CM directory number to which the VoIP gateway routed the call if the call was placed from outside the VoIP² network (for example, from the PSTN³ or a TDM⁴ PBX⁵).</p> <p>Null if the caller picked up the phone but did not dial any digits.</p>	<p>nvarchar(30)</p> <p>NULL</p>
applicationTaskID	<p>Identifier of the Unified CCX or Cisco Unified IP IVR⁶(Unified IP IVR) application task that is associated with the call or the leg.</p> <p>Null for a call that does not have an application associated with it.</p>	<p>decimal(18,0)</p> <p>NULL</p>
applicationID	<p>Identifier of the Unified CCX or Unified IP IVR application that processed the call or the leg.</p> <p>Null for a call or a leg that does not have an application associated with it.</p>	<p>int</p> <p>NULL</p>

Field Name	Description	Storage
applicationName	Name of the Unified CCX or Unified IP IVR application associated with the call. Null for a call or a leg that does not have an application associated with it.	nvarchar(30) NULL
connectTime	Amount of time, in seconds, between the start time of the call or the leg and the end time of the call or the leg.	smallint NULL
customVariable1	Contents of the variable _ccdrVar1, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable2	Contents of the variable _ccdrVar2, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable3	Contents of the variable _ccdrVar3, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable4	Contents of the variable _ccdrVar4, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable5	Contents of the variable _ccdrVar5, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL

Field Name	Description	Storage
customVariable6	Contents of the variable _ccdrVar6, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable7	Contents of the variable _ccdrVar7, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable8	Contents of the variable _ccdrVar8, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable9	Contents of the variable _ccdrVar9, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
customVariable10	Contents of the variable _ccdrVar10, if this variable is set by the Set Enterprise Call step in the script that the Unified CCX or Unified IP IVR application associated with this call or this leg invoked. Null if this variable is not set.	varchar(40) NULL
accountNumber	Account number entered by the caller.	varchar(40) NULL
callerEnteredDigits	Phone number entered by the caller.	varchar(40) NULL
badCallTag	Tag for a bad call. Default = N	char(1) NULL

Field Name	Description	Storage
transfer	Was this call leg transferring the call: t = transfer f = no	boolean NULL
redirect	Was this call leg redirecting the call: t = redirect f = no	boolean NULL
conference	Was this call leg conferencing the call: t = conference f = no	boolean NULL
flowout	When this flag is set, it means this call leg is sent to another application or destination outside the system.	boolean NULL
metServiceLevel	Did the call meet the service level: t = met service level f = no Note: Reserved for future use.	boolean NULL
campaignID	Unique identifier of the campaign that generated this call.	int NULL
OrigProtocolCallRef	Unique identifier to identify a call leg that enters the Unified CCX system. This is used to trace a call which has traversed from some product to the Unified CCX.	Varchar(32) NULL
DestProtocolCallRef	Unique Identifier to identify a call leg that exits the Unified CCX system. This is used to trace a call which has traversed from Unified CCX to some other product.	Varchar(32) NULL
CallResult	The result of an IVR based or agent based progressive or predictive outbound call.	smallint NULL
dialingListID	Unique identifier of a contact that is dialed for an outbound campaign. Links with DialingList.dialingListID.	int NULL

¹ For aborted calls, the corresponding value in ContactQueueDetail.disposition = 1 (abandoned)

² VoIP = Voice over Internet Protocol

³ PSTN = Public Switched Telephone Network

⁴ TDM = Time-Division Multiplexing

⁵ Private Branch Exchange

⁶ Interactive Voice Response

Related Topics

- [AgentConnectionDetail](#), on page 5
- [Campaign](#), on page 15
- [ContactQueueDetail](#), on page 38
- [ContactRoutingDetail](#), on page 40
- [MonitoredResourceDetail](#), on page 63
- [ProfileIDMapping](#), on page 65
- [PurgeHistory](#), on page 66
- [Resource](#), on page 70

ContactQueueDetail

Database table name: ContactQueueDetail

The Unified CCX system writes the record when the call is queued for CSQs; then one of the following happens:

- Call is abandoned while queued for CSQs
- Call is being dequeued
- Caller is connected to an agent

Table 25: ContactQueueDetail Table Fields

Field Name	Description	Storage
sessionID	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call.	decimal(18,0) NOT NULL Primary Key
sessionSeqNum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
nodeID	Unique identifier assigned to each server in the cluster.	smallint NOT NULL Primary Key

Field Name	Description	Storage
targetID	Numeric ID of the CSQ or the agent depending upon the targetType. Numeric ID of the CSQ or the agent depending upon the targetType. <ul style="list-style-type: none"> • 0—Numeric record ID of the CSQ. (See record ID description in the Contact Service Queue Table) • 1—Numeric agent ID (see resourceID description in the Resource Table) 	int NOT NULL Primary Key
targetType	Indicates whether the call was queued for a CSQ or for an agent. <ul style="list-style-type: none"> • 0 = CSQ • 1 = Agent 	smallint NOT NULL Primary Key
qIndex	A new qIndex is created whenever the Unified CCX call is conferenced to a Unified CCX route point.	smallint NOT NULL Primary Key
queueOrder	The order of the call in the queue.	smallint NOT NULL
disposition	Disposition for this leg of the call for this CSQ. <ul style="list-style-type: none"> • Abandoned = 1⁷ • Handled by CSQ = 2 • Dequeued from CSQ = 3 • Handled by script = 4 • Handled by another CSQ = 5 	smallint NULL
metServiceLevel	Call answered within the configured number of seconds of queue time for this CSQ. <ul style="list-style-type: none"> • Yes = t • No = f 	boolean NULL
queueTime	Number of seconds the caller spent in queue for this CSQ and this leg of the call.	smallint NULL

⁷ For aborted calls, ContactQueueDetail.disposition = 1 and the corresponding ContactCallDetail.contactDisposition = 4 (aborted).

Related Topics

- [AgentConnectionDetail](#), on page 5
- [ContactCallDetail](#), on page 31
- [ContactRoutingDetail](#) , on page 40
- [MonitoredResourceDetail](#), on page 63
- [ProfileIDMapping](#), on page 65
- [RemoteMonitoringDetail](#) , on page 68
- [Resource](#) , on page 70

ContactRoutingDetail

Database table name: ContactRoutingDetail

The Unified CCX system creates a new record in the ContactRoutingDetail table for each Unified CCX call or call leg that is queued for one or more CSQs. A new call leg starts each time that a call is transferred or redirected, except when a call is transferred from a Cisco CTI port to an agent. The system also creates a new record in the ContactRoutingDetail table if a call is conferenced to a Unified CCX script.

A ContactRoutingDetail record contains information about call priority and accumulated queue time. This differs from the ContactQueueDetail record which shows individual queue time for each CSQ.

Table 26: ContactRoutingDetail Table Fields

Field Name	Description	Storage
sessionID	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call.	decimal(18, 0) NOT NULL Primary Key
sessionSeqNum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
nodeID	Unique identifier assigned to each server in the cluster.	smallint NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
qIndex	A new qIndex is created whenever the Unified CCX call is conferenced to a Unified CCX route point.	smallint NOT NULL Primary Key

Field Name	Description	Storage
origPriority	Priority level assigned to the call or the leg when it was first queued. Null if a priority was not assigned.	smallint NULL
finalPriority	Priority level of the call or the leg when it ended. Null if a priority was not assigned.	smallint NULL
queueTime	Time, in seconds, that the call or the leg was queued before an agent picked up the call or the leg. This is the accumulated queue time perceived by the caller if the call is queued for more than one CSQ; in contrast, the ContactQueueDetail record records queue time for each individual CSQ.	smallint NULL
startDateTime	For an incoming call or a leg, date and time that the call or the leg was queued for the first CSQ.	datetime year to fraction (3) NOT NULL

Related Topics

- [AgentConnectionDetail](#), on page 5
- [ContactCallDetail](#), on page 31
- [ContactQueueDetail](#), on page 38
- [MonitoredResourceDetail](#), on page 63
- [ProfileIDMapping](#), on page 65
- [PurgeHistory](#), on page 66

ContactServiceQueue

Database table name: ContactServiceQueue

The Unified CCX system creates a new record in the ContactServiceQueue table when a CSQ is set up in Unified CCX Administration.

A ContactServiceQueue record contains information about the CSQ. One such record exists for each active and inactive CSQ. When a CSQ is deleted (deactivated), its record still remains in the database marked as inactive; that is, the active field value is “F”.

Table 27: ContactServiceQueue Table Fields

Field Name	Description	Storage
contactServiceQueueID	Numeric identifier of the CSQ. This ID does not change when CSQ attributes are changed through the Unified CCX Administration user interface.	int NOT NULL
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL

Field Name	Description	Storage
CSQName	Name of the CSQ as set up in Unified CCX Administration.	nvarchar(50,0) NOT NULL
resourcePoolType	Type of resource pool that is set up in Unified CCX Administration: 1—Resource groups 2—Resource skills	smallint NOT NULL
resourceGroupID	If resourcePoolType is 1, unique identifier used to locate the associated resource group in the Resource Group table. Not used if resourcePoolType is 2.	int NULL
selectionCriteria	Resource pool selection model that is set up in the Unified CCX Administration.	nvarchar(30,0) NOT NULL
skillGroupID	If resourcePoolType is 2, unique identifier used to locate the associated skill group in the SkillGroup table. Not used if resourcePoolType is 1.	int NULL
serviceLevel	Goal, in seconds, for the maximum time that a caller spends in the queue before the call is answered by an agent, as set up in Unified CCX Administration.	int NOT NULL
serviceLevelPercentage	Goal for the percentage of calls that meet the service level that is shown in the serviceLevel field, as set up in Unified CCX Administration.	smallint NOT NULL
active	Indicates whether the record is active: f = Inactive t = Active A record becomes inactive if the CSQ is deleted from the system or if the attributes are changed through the Unified CCX Administration user interface. When an attribute is changed, the record is marked inactive; that is, the active field is changed to “f”, and a new record is created.	boolean NOT NULL
autoWork	Whether an agent goes to Work State after handling a call from this CSQ: f—No t—Yes	boolean NOT NULL

Field Name	Description	Storage
dateInactive	If the active field is “F”, date and time that the record became inactive.	datetime year to fraction (3) NULL
queueAlgorithm	Criterion that specifies how contacts are queued, as set up in Unified CCX Administration.	nvarchar(30,0) NOT NULL
recordID	Identifier of this record. When any CSQ attribute, such as service level, is changed through the Unified CCX Administration user interface, the record is marked inactive; that is, the value of the active field changes to “F”, and a new record is created with a new record ID; the contactServiceQueueID stays the same for that CSQ.	int NOT NULL Primary Key
orderList	Reserved for future use.	int NULL
wrapupTime	Time in seconds that agent is placed in Work state. Possible values: 1 – 7200 0 – disabled	smallint NULL
prompt	The prompt value is used for remote monitoring. The customer can record the name of the CSQ and store it in a WAV file. This field contains the name of the WAV file.	nvarchar (256) NOT NULL
privateData	Any fields which are used internally only can be stored in this column in a blob.	BLOB NULL
queueType	A type of the CSQ. Possible values: 0 – voice CSQ 1 – email CSQ 2 – chat CSQ	smallint NOT NULL
queueTypeName	The name displayed for the CSQ type. Possible values: <ul style="list-style-type: none"> • Vioce • Chat • Email 	nvarchar(30,0) NULL

Field Name	Description	Storage
accountuserId	The userid of the email account mapped to an email CSQ.	nvarchar(255,0) NULL
channelproviderId	The unique identifier for the channel provider.	int NULL
reviewQueueId	Reserved.	int NULL
routingType	The type of routing: <ul style="list-style-type: none"> • Interactive • Noninteractive 	nvarchar(30,0) NULL
folderName	The name of the email folder that needs to be polled for mails on the mail server.	nvarchar(255,0) NULL
pollingInterval	The time (in seconds) on how frequently the email server is polled for any new emails.	int NULL
snapshotAge	The time (in minutes) to indicate how far to go back to fetch emails on startup.	int NULL
feedId	The unique identifier for the feeds from SocialMiner.	nvarchar(30,0) NULL

Related Topics

- [ContactQueueDetail](#), on page 38
- [ProfileIDMapping](#), on page 65
- [RemoteMonitoringDetail](#), on page 68
- [ResourceGroup](#), on page 73
- [SkillGroup](#), on page 81
- [TeamCSQMapping](#), on page 86

ContactWrapupData

Database table name: ContactWrapupData

The Unified CCX system creates a new record in the contactwrapupdata table each time the agent selects a Wrap-Up reason.

Table 28: ContactWrapupData Table Fields

Field Name	Description	Storage
sessionID	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call.	decimal (18) NOT NULL Primary Key
sessionSeqNum	Session sequence number that the system assigned to the call or the leg. Each leg of a call is assigned a new sequence number.	smallint NOT NULL Primary Key
resourceID	Numeric identifier of the resource.	int NOT NULL Primary Key
wrapupData	Call related information that the agent enters through the Agent Desktop user interface while the agent is in the talking/work state.	varchar (160) NOT NULL Primary Key
nodeid	Unique identifier assigned to each Unified CCX server in the cluster.	smallint Primary Key
qindex	A new qIndex is created whenever a Unified CCX call is conferenced to a Unified CCX route point.	smallint Primary Key
startDateTime	Date and time that the call or the leg started ringing at the device of an agent.	datetime year to fraction Primary Key
wrapupindex	Unique number of wrapup reasons for a particular call. A call can have maximum of five wrapup reasons.	smallint

CrsApplication

Database table name: CrsApplication

The CrsApplication table records application information. An application is uniquely identified by applicationName. When an application is created, a new record is inserted into this table. When an application is modified, the old record is marked as inactive, and a new record is inserted into the table with a new recordID. When an application is deleted, the corresponding record is marked as inactive.

Table 29: CrsApplication Table Fields

Field Name	Description	Storage
record ID	Unique numeric ID for each record. Introduced for historical reporting purposes. Possible values: 1, 2, 3....	int NOT NULL Primary Key
profileID	The indentifier of the profile	int NOT NULL Primary Key
applicationID	Configurable application identifier. Not unique for an application. Exposed for Cisco Unified Intelligent Contact Management Enterprise (Unified ICME) integration. Configured on Unified CCX Administration, modifiable. Possible values: -1, 1, 2, 3...	int NOT NULL
configClass	Represents application configuration class. Possible values: <ul style="list-style-type: none"> • com.cisco.app.ApplicationConfig • ApplicationConfig.class 	Ivarchar(512) NOT NULL
version	Specifies internal configuration schema version. Possible values: 1	int NOT NULL
configImplClass	Represents application configuration implementation class. Possible value: com.cisco.crs.app.ScriptApplicationConfig	Ivarchar(512) NOT NULL
applicationName	Name that uniquely identifies the application	nvarchar(50,0) NOT NULL

Field Name	Description	Storage
applicationType	The type of application. Possible values: <ul style="list-style-type: none"> • Busy • Ring-No-Answer • Cisco Script Application • Simulation Script • Unified ICME Post-Routing • Unified ICME Translation Routing 	nvarchar(128,0) NOT NULL
applicationEnabled	Whether or not the application is enabled. Possible values: <ul style="list-style-type: none"> • f = disabled • t = enabled 	boolean NOT NULL
numOfSessions	Maximum number of sessions	int NOT NULL
description	The description of the application that is configured in the Unified CCX Administration.	nvarchar(128,0) NULL
privateData	Internal data not exposed to customers.	BLOB NULL
createDateTime	The time when the record is created or updated. Default value: Current year to second	datetime year to second NOT NULL
active	Whether this record is active. Possible values: <ul style="list-style-type: none"> • f = inactive • t = active 	boolean NOT NULL
dateInactive	If active = f, the time when this record became inactive.	datetime year to second NULL

Related Topics

[ProfileIDMapping](#), on page 65

CrsGroup

Database table name: CrsGroup table

The CrsGroup table describes group information. A group is uniquely identified by the combination of groupClassName and groupID. When a group is created, a new record is inserted into this table. When a group is modified, the old record is marked as inactive, and a new record is inserted into the table with a new recordID. When a group is deleted, the corresponding record is marked as inactive.

Table 30: CrsGroup Table Fields

Field Name	Description	Storage
recordID	A unique numeric ID for each record. Introduced for historical reporting purposes.	int NOT NULL Primary Key
profileID	Identifier of the profile Possible values: 1, 2, 3...	int NOT NULL Primary Key
configClass	Represents Group configuration class. Possible values: GroupConfig.class	Ivarchar(512) NOT NULL
version	Specifies internal configuration schema version. Possible values: 2	int NOT NULL
configImplClass	Represents group configuration implementation class. Possible values: <ul style="list-style-type: none"> • com.cisco.crs.email. • CiscoEmailControlGroupConfig. 	Ivarchar(512) NOT NULL
groupClass	Uniquely identifies a group together with the groupID. The class of channels being managed by the group.	Ivarchar(400) NOT NULL
groupID	Uniquely identifies a group together with groupClassName. Group identifier unique for a give class of channels.	int NOT NULL
groupType	Type of the group, corresponding to type of the channels managed by the group as defined since CRS 3.0.	nvarchar(128,0) NOT NULL

Field Name	Description	Storage
groupEnabled	Whether the group is enabled. Possible values: f = disabled t = enabled	boolean NOT NULL
numOfChannels	Number of channels defined in the group.	int NOT NULL
description	Description of the group.	nvarchar(128,0) NULL
privateData	Internal data not exposed to customers.	BLOB NULL
createDateTime	When the group was created. Default value: Current year to second	datetime year to second NOT NULL
active	Whether this record is active. Possible values: f = inactive t = active	boolean NOT NULL
dateInactive	If active = f, the time when the record became inactive.	datetime year to second NULL

CrsTrigger

Database table name: CrsTrigger

The CrsTrigger table describes trigger information. A trigger is uniquely identified by a trigger name (triggerName). When a trigger is created, a new record is inserted into this table. When a trigger is modified, the old record is marked as inactive, and a new record is inserted into the table with a new recordID. When a trigger is deleted, the corresponding record will be marked as inactive.

Table 31: CrsTrigger Table Fields

Field Name	Description	Storage
recordID	Unique numeric ID for each record. Introduced for historical reporting purposes.	int NOT NULL Primary Key

Field Name	Description	Storage
profileID	Identifier of the profile Possible values: 1, 2, 3....	int NOT NULL Primary Key
configClass	Represents trigger configuration class. Possible values: ApplicationTriggerConfig.class	Ivarchar(512) NOT NULL
version	Specifies internal configuration schema version. Possible values: 3	int NOT NULL
configImplClass	Represents trigger configuration implementation class. Possible values: <ul style="list-style-type: none"> • com.cisco.crs.email. • CiscoEmailControlGroupConfig. 	Ivarchar(512) NOT NULL
triggerName	Uniquely identifies a trigger. Available from CRS 4.5 onwards. The API does limit the string length. Go back and revisit the length.	nvarchar(50,0) NOT NULL
triggerType	Hard coded. Possible values: <ul style="list-style-type: none"> • Cisco Http Trigger • Cisco JTAPI Trigger 	nvarchar(128,0) NOT NULL
applicationName	Application name being triggered by the trigger.	nvarchar(50,0) NOT NULL
triggerEnabled	Whether the trigger is enabled Possible values: <ul style="list-style-type: none"> • f = disabled • t = enabled 	boolean NOT NULL
numOfSessions	Maximum number of sessions Possible values: 0, 1, 2...	int NOT NULL
idleTimeout	Idle time out in milliseconds	int NOT NULL

Field Name	Description	Storage
triggerLocale	Default locale for the trigger. Possible values: <ul style="list-style-type: none"> • system.default (the currently configured system default locale) • accept.trigger (the locale provided by the incoming event) 	nvarchar(50,0) NOT NULL
description	Description of the trigger	nvarchar(128,0) NULL
misc1	For HTTP trigger, this field contains the URL. For JTAPI and call triggers, this is the dialed number (DN).	lvarchar(256) NULL
misc2	For JTAPI trigger, this is the partition.	lvarchar(256) NULL
privateData	Internal data not exposed to customers, such as parameters or groups associated with a trigger.	BLOB NULL
createDateTime	When the trigger was created. Default value: Current year to second	datetime year to second Not NULL
active	Whether this record is active. Possible values: f = inactive t = active	boolean NOT NULL
dateInactive	If active = f, the time when the record became inactive.	datetime year to second NULL

Related Topics

[ProfileIDMapping](#), on page 65

DateShiftMap

Database table name: DateShiftMap

This table stores the special business days configured for calendars.

Table 32: DateShiftMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	serial NOT NULL Primary Key
calid	A unique identifier for the calendar.	int NOT NULL
name	Name of the calendar.	nvarchar (50) NOT NULL
caldate	Date of the special day.	DATETIME YEAR TO DAY NOT NULL
shiftname	The shift name configured for the specific day of the week.	nvarchar (25) NOT NULL
shifttype	Type of the shift.	smallint NOT NULL
fromtime	Shift start time.	int NOT NULL
totime	Shift end time.	int NOT NULL
active	Indicates whether the record is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date and time of the record when it is marked as inactive.	DATETIME year to second NULL

DayShiftMap

Database Table Name: DayShiftMap

This table stores the custom weekly business days configured for calendars.

Table 33: DayShiftMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	serial NOT NULL Primary Key
calid	A unique identifier for the calendar.	int NOT NULL
dow	Day of the week.	nvarchar (3) NOT NULL
shiftname	The shift name configured for the specific day of the week.	nvarchar (25) NOT NULL
shifttype	Type of the shift.	NOT NULL smallint
fromtime	Shift start time in 24 hour format.	int NOT NULL
totime	Shift end time in 24 hour format.	int NOT NULL
active	Indicates whether the record is currently active or not. f = Inactive t = Active	boolean NOT NULL
dateinactive	Date and time of the record when it is marked as inactive.	DATETIME year to second NULL

DialingList

Database table name: DialingList

The DialingList table contains the outbound contacts that need to be dialed for a particular campaign. This table is populated when a text file containing the outbound contacts is imported from the Campaigns configuration page in the Unified CCX Administration.

When the outbound contacts are imported into the database from the Unified CCX Administration, the callStatus field has the default value of 1 (Pending); that is, the contacts are yet to be dialed.

Table 34: DialingList Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key
dialinglistid	A unique identifier for a contact.	int NOT NULL Primary Key
profileid	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
campaignid	Campaign identifier	int NULL
createdatetime	Default -CURRENT_TIMESTAMP	datetime year to second NULL
accountnumber	The account number of the contact (from the imported file). This field is sent to the agent desktop.	nvarchar(25, 0) NULL
firstname	The first name of the contact (from the imported file).	nvarchar(50, 0) NULL
lastname	The last name of the contact (from the imported file).	nvarchar(50,0) NULL
phone01	Primary phone number of the contact (from the imported file).	varchar(28,0) NOT NULL
phone02	Additional number of the contact (from the imported file). The number is dialed when the agent selects Skip-Next for the preview call.	varchar(28,0) NULL
phone03	Additional number of the contact (from the imported file). This number is dialed if attempts to dial the first two numbers are unsuccessful.	varchar(28,0) NULL
gmtzonephone01	The time zone for the first phone number of the contact.	smallint NOT NULL

Field Name	Description	Storage
dstphone01	0 = Daylight Savings Time (DST) is observed at this phone number. 1 = DST is not observed at this phone number	smallint NOT NULL
gmtzonephone02	The time zone for the second phone number of the contact.	smallint NOT NULL
dstphone02	0 = DST is observed at this phone number. 1 = DST is not observed at this phone number.	smallint NOT NULL
gmtzonephone03	The time zone for the third phone number of the contact.	smallint NOT NULL
dstphone03	0 = DST is observed at this phone number. 1 = DST is not observed at this phone number.	smallint NOT NULL
callbacknumber	Phone number to be used for callback (can be supplied by the agent).	varchar(28,0) NULL
callbackdatetime	Customer requested callback time.	datetime year to second NULL
callstatus	The status of the contact record: 1 = Pending. The call is pending. 2 = Active. The record is sent (active) to the Outbound subsystem for dialing. 3 = Closed. The record is closed. 4 = Callback. The record is marked for a callback. 5 = Max Calls. Maximum attempts have been reached for this record (considered closed). 6 = Retry. The call is redialed immediately whenever there is any miss. 7 = Unknown. If the Outbound subsystem was restarted with records in the Active (2) state, the records are moved to this state. 8 = Retries with delay. The call is redialed as it was either busy, no answer, customer abandoned or system abandoned. Retry time is set as per the corresponding configuration in the Unified CCX Application Administration web interface.	smallint NOT NULL

Field Name	Description	Storage
callresult	<p>The call result from the last call placed for this record.</p> <p>1 = Voice. Customer answered and was connected to agent.</p> <p>2 = Fax. Fax machine reached.</p> <p>3 = Answering machine. Answering machine reached.</p> <p>4 = Invalid. Number reported as invalid by the network or by the agent.</p> <p>5 = Do Not Call. Customer does not want to be called again.</p> <p>6 = Wrong Number. Number successfully contacted but wrong number.</p> <p>7 = Wrong Person. Number successfully contacted but reached the wrong person.</p> <p>8 = Callback. Customer requested regular callback.</p> <p>9 = Skip/Reject. Agent skipped or rejected a preview call.</p> <p>10 = Skip-Close/Reject-Close. Agent skipped or rejected a preview call with the close option.</p> <p>11 = Busy. Busy signal detected or marked busy by agent.</p> <p>12 = Agent did not respond to the preview call within the timeout duration.</p> <p>13 = Callback Failed - this value is not written to the database; this is for internal use only.</p> <p>14 = Callback missed and marked for Retry.</p> <p>15 = Customer's phone timed out either due to Ring No Answer (RNA) or Gateway failure.</p> <p>16 = Call was abandoned because IVR port was unavailable or Unified CCX failed to transfer the call to the IVR port.</p> <p>17 = Call failed due any one of the reasons.</p> <p>18 = Customer abandoned as customer or agent disconnected the call within the time limit as configured in "Abandoned Call Wait Time" in Unified CCX Application Administration web interface.</p>	<p>smallint</p> <p>NOT NULL</p>

Field Name	Description	Storage
callresult01	The call result from the last time phone01 was called. Values are the same as for callResult.	smallint NULL
callresult02	The call result from the last time phone02 was called. Values are the same as for callResult.	smallint NULL
callresult03	The call result from the last time phone03 was called. Values are the same as for callResult.	smallint NULL
lastnumberdialed	The last number dialed. 1 = phone01 2 = phone02 3 = phone03	smallint NULL
callsmadetophone01	The number of call attempts made to phone01. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
callsmadetophone02	The number of call attempts made to phone02. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
callsmadetophone03	The number of call attempts made to phone03. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
retry	Indicates whether the contact has to be retried.	boolean NULL
active	Contacts becomes inactive for a campaign in the following scenarios: 1 = delete a campaign 2 = delete all the contacts for a campaign f = Inactive t = Active	boolean NOT NULL
dateinactive	The date when record became inactive.	datetime year to second NULL
numMissedCallback	Number of missed callbacks.	smallint NULL

Related Topics

[AgentConnectionDetail](#), on page 5

[AreaCode](#), on page 11

[Campaign](#), on page 15

[ContactCallDetail](#), on page 31

[DialingList](#), on page 53

[ProfileIDMapping](#), on page 65

DialingListHistory

Database table name: DialingList

The DialingList table contains the outbound contacts that need to be dialed for a particular campaign. This table is populated when a text file containing the outbound contacts is imported from the Campaigns configuration page in the Unified CCX Administration.

When the outbound contacts are imported into the database from the Unified CCX Administration, the callStatus field has the default value of 1 (Pending); that is, the contacts are yet to be dialed.

Table 35: DialingList Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key
dialinglistid	A unique identifier for a contact.	int NOT NULL Primary Key
profileid	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
campaignid	Campaign identifier	int NULL
createdatetime	Default -CURRENT_TIMESTAMP	datetime year to second NULL
accountnumber	The account number of the contact (from the imported file). This field is sent to the agent desktop.	nvarchar(25,0) NULL
firstname	The first name of the contact (from the imported file).	nvarchar(50,0) NULL

Field Name	Description	Storage
lastname	The last name of the contact (from the imported file).	nvarchar(50,0) NULL
phone01	Primary phone number of the contact (from the imported file).	varchar(28,0) NULL
phone02	Additional number of the contact (from the imported file). The number is dialed when the agent selects Skip-Next for the preview call.	varchar(28,0) NULL
phone03	Additional number of the contact (from the imported file). This number is dialed if attempts to dial the first two numbers are unsuccessful.	varchar(28,0) NULL
gmtzonephone01	The time zone for the first phone number of the contact.	smallint NULL
dstphone01	0 = Daylight Savings Time (DST) is observed at this phone number. 1 = DST is not observed at this phone number	smallint NULL
gmtzonephone02	The time zone for the second phone number of the contact.	smallint NULL
dstphone02	0 = DST is observed at this phone number. 1 = DST is not observed at this phone number.	smallint NULL
gmtzonephone03	The time zone for the third phone number of the contact.	smallint NULL
dstphone03	0 = DST is observed at this phone number. 1 = DST is not observed at this phone number.	smallint NULL
callbacknumber	Phone number to be used for callback (can be supplied by the agent).	varchar(28) NULL
callbackdatetime	Customer requested callback time.	datetime year to second NULL

Field Name	Description	Storage
callstatus	<p>The status of the contact record:</p> <p>1 = Pending. The call is pending.</p> <p>2 = Active. The record is sent (active) to the Outbound subsystem for dialing.</p> <p>3 = Closed. The record is closed.</p> <p>4 = Callback. The record is marked for a callback.</p> <p>5 = Max Calls. Maximum attempts have been reached for this record (considered closed).</p> <p>6 = Retry. The call is redialed immediately whenever there is any miss.</p> <p>7 = Unknown. If the Outbound subsystem was restarted with records in the Active (2) state, the records are moved to this state.</p> <p>8 = Retries with delay. The call is redialed as it was either busy, no answer, customer abandoned or system abandoned. Retry time is set as per the corresponding configuration in the Unified CCX Application Administration web interface.</p>	<p>smallint</p> <p>NULL</p>

Field Name	Description	Storage
callresult	<p>The call result from the last call placed for this record.</p> <p>1 = Voice. Customer answered and was connected to agent.</p> <p>2 = Fax. Fax machine reached.</p> <p>3 = Answering machine. Answering machine reached.</p> <p>4 = Invalid. Number reported as invalid by the network or by the agent.</p> <p>5 = Do Not Call. Customer does not want to be called again.</p> <p>6 = Wrong Number. Number successfully contacted but wrong number.</p> <p>7 = Wrong Person. Number successfully contacted but reached the wrong person.</p> <p>8 = Callback. Customer requested regular callback.</p> <p>9 = Skip/Reject. Agent skipped or rejected a preview call.</p> <p>10 = Skip-Close/Reject-Close. Agent skipped or rejected a preview call with the close option.</p> <p>11 = Busy. Busy signal detected or marked busy by agent.</p> <p>12 = Agent did not respond to the preview call within the timeout duration.</p> <p>13 = Callback Failed - this value is not written to the database; this is for internal use only.</p> <p>14 = Callback missed and marked for Retry.</p> <p>15 = Customer's phone timed out either due to Ring No Answer (RNA) or Gateway failure.</p> <p>16 = Call was abandoned because IVR port was unavailable or Unified CCX failed to transfer the call to the IVR port.</p> <p>17 = Call failed due any one of the reasons.</p> <p>18 = Customer abandoned as customer or agent disconnected the call within the time limit as configured in "Abandoned Call Wait Time" in Unified CCX Application Administration web interface.</p>	<p>smallint</p> <p>NULL</p>

Field Name	Description	Storage
callresult01	The call result from the last time phone01 was called. Values are the same as for callResult.	smallint NULL
callresult02	The call result from the last time phone02 was called. Values are the same as for callResult.	smallint NULL
callresult03	The call result from the last time phone03 was called. Values are the same as for callResult.	smallint NULL
lastnumberdialed	The last number dialed. 1 = phone01 2 = phone02 3 = phone03	smallint NULL
callsmadetophone01	The number of call attempts made to phone01. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
callsmadetophone02	The number of call attempts made to phone02. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
callsmadetophone03	The number of call attempts made to phone03. If there is an error in an attempt to call this number, the attempt is not counted here.	smallint NULL
retry	Indicates whether the contact has to be retried.	boolean NULL
active	Contacts becomes inactive for a campaign in the following scenarios: 1 = delete a campaign 2 = delete all the contacts for a campaign 3 = when callStatus becomes 3 (closed) or 5 (max calls) f = Inactive t = Active	boolean NULL
dateinactive	The date when record became inactive.	datetime year to second NULL

Field Name	Description	Storage
numMissedCallback	Number of missed callbacks.	smallint NULL

Related Topics

[AgentConnectionDetail](#), on page 5

[AreaCode](#), on page 11

[Campaign](#), on page 15

[ContactCallDetail](#), on page 31

[DialingList](#), on page 53

[ProfileIDMapping](#), on page 65

MonitoredResourceDetail

Database table name: MonitoredResourceDetail

The MonitoredResourceDetail table records the actual agents who are monitored. The RemoteMonitoringDetail table records the original agent or the CSQ that the supervisor plans to monitor. Monitoring a CSQ involves monitoring the agents who handle calls for that CSQ. So the actual agents (which can be more than one) that are monitored will be recorded in the MonitoredResourceDetail table.

Table 36: MonitoredResourceDetail Table Fields

Field Name	Description	Storage
sessionid	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call. It is the sessionID of the IVR call; that is, when the supervisor starts monitoring, the monitoring call itself is an IVR call. The supervisor monitors one or more Unified CCX calls.	decimal(18) NOT NULL Primary Key
startmonitoringreqtime	The time and date that the remote supervisor attempted to monitor the agent.	datetime year to fraction (3) NOT NULL
startmonitoringcalltime	The time and date that the supervisor began monitoring the call.	datetime year to fraction (3) NOT NULL Primary Key
monitoredrsrcid	Identifier of the resource being monitored.	int NOT NULL
monitoredsessionseqnum	The session sequence number of the Unified CCX call that is being monitored.	smallint NOT NULL

Field Name	Description	Storage
profileid	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
gmtoffset	Offset, in minutes, between the local time of the Unified CCX server and Greenwich Mean Time. As the time information is stored in GMT, this field will always be zero.	int NOT NULL
nodeid	Unique identifier assigned to each server in the cluster.	smallint NOT NULL Primary Key

Related Topics

- [AgentConnectionDetail](#), on page 5
- [ContactCallDetail](#), on page 31
- [ContactQueueDetail](#), on page 38
- [ContactRoutingDetail](#), on page 40
- [RemoteMonitoringDetail](#), on page 68
- [Resource](#), on page 70

MediaCustomerDataMapping

Database table name: MediaCustomerDataMapping

The MediaCustomerDataMapping table contains mapping between the customer data fields for a specific media (such as email and other media types) and the order of fields stored in the TextCustomerDetail table.



Note Do not edit this table directly. It is for internal use only

Table 37: MediaCustomerDataMapping Table Fields

Field Name	Description	Storage
recordId	Unique identifier for the record.	int NOT NULL Primary Key
mediaType	Type of the media such as email and other media types.	varchar(30,0) NOT NULL Primary Key

Field Name	Description	Storage
fieldName	Name of the field in the customer data.	varchar(50,0) NOT NULL
columnId	Field ID in the TextCustomerDetail where this field is stored.	int NOT NULL

Related Topics

- [AgentConnectionDetail](#), on page 5
- [AgentStateDetail](#), on page 8
- [AreaCode](#), on page 11
- [Campaign](#), on page 15
- [ContactCallDetail](#), on page 31
- [ContactQueueDetail](#), on page 38
- [ContactRoutingDetail](#), on page 40
- [ContactServiceQueue](#), on page 41
- [DialingList](#), on page 53
- [MonitoredResourceDetail](#), on page 63
- [RemoteMonitoringDetail](#), on page 68
- [Resource](#), on page 70
- [ResourceGroup](#), on page 73
- [ResourceSkillMapping](#), on page 73
- [RmonCSQConfig](#), on page 74
- [RmonResConfig](#), on page 75
- [RmonUser](#), on page 76
- [Skill](#), on page 80
- [SkillGroup](#), on page 81
- [Supervisor](#), on page 82
- [Team](#), on page 85
- [TeamCSQMapping](#), on page 86

ProfileIDMapping

Database table name: ProfileIDMapping

The Unified CCX system creates a new record in the ProfileIDMapping table when a new profile is set up in the Unified CCX Administration.

A ProfileIDMapping record shows the mapping of the profile name to its unique identifier.

Table 38: ProfileIDMapping Table Fields

Field Name	Description	Storage
profileName	Name of the profile, as set up in the Unified CCX Administration.	nvarchar(50,0) NOT NULL Primary Key
profileID	Identifier of the profile.	int NOT NULL

PurgeHistory

Database table name: PurgeHistory

PurgeHistory is mainly to keep track of the history of purge information for both Manual and Scheduled purge.

Table 39: PurgeHistory Table Fields

Field Name	Description	Storage
nodeId	Unique identifier assigned to each server in the cluster.	int NOT NULL Primary Key
purgeHistoryId	Sequence numbers.	int NOT NULL Primary Key
purgeType	PurgeType MANUAL or SCHEDULED.	nvarchar(10,0) NOT NULL
purgeState	PurgeState can be any one of, RUNNING, COMPLETED_SUCCESSFULLY, COMPLETED_WITH_ERRORS, UNKNOWN.	nvarchar(30,0) NOT NULL
purgeStartedDateTime	Purge start time.	datetime year to fraction(3) NOT NULL
hrDbSizeBeforePurge	Historical db size before purge which will have the value using store procedure getDbSize with column name as "used".	int NULL
configDbSizeBeforePurge	Config db size before purge which will have the value using store procedure getDBspaceUsage('db_cra') with column name as "used".	int NULL

Field Name	Description	Storage
oldestRecDateTimeBeforePurge	Oldest record date and time before purge.	datetime year to fraction(3) NULL
purgeCompletedDateTime	Purge completion time.	datetime year to fraction(3) NULL
hrDbSizeAfterPurge	Historical db size after purge which will have the value using store procedure getDbSize with column name as "used".	int NULL
configDbSizeAfterPurge	Config db size after purge which will have the value using store procedure getDBspaceUsage('db_cra') with column name as "used".	int NULL
oldestRecDateTimeAfterPurge	Oldest record date time after purge.	datetime year to fraction(3) NULL
purgeRunTime	Purge run time in minutes which is the difference between purgeCompletedDateTime and purgeStartedDateTime.	int NULL

ReasoncodeLabelMap

Database table name: ReasoncodeLabelMap

Unified CCX System maintains a reason code and label for Logout and Not Ready states, that are available in Cisco Finesse Administration.

This table holds the mapping between reason code and label.

Table 40: ReasoncodeLabelMap

Field Name	Description	Storage
code	Reason code, as configured in Finesse Administration.	Smallint NOT NULL Primary Key
label	Reason label, as configured in Finesse Administration.	NVARCHAR(40,0) NOT NULL

Field Name	Description	Storage
category	Type of reason code, label: NOT_READY LOGOUT	NVARCHAR(15,0) NOT NULL Primary Key
active	Whether the record is active in the system. A record becomes Inactive if reason code label is deleted from Finesse Administration and this field will be marked "FALSE".	boolean NULL
dateinactive	Date and time this record was added, modified, or deleted from Cisco Finesse Administration.	Date time year to second NULL

RemoteMonitoringDetail

Database table name: RemoteMonitoringDetail

The Remote Monitoring Detail Record provides information about sessions where remote monitoring is used.

Table 41: RemoteMonitoringDetail Table Fields

Field Name	Description	Storage
sessionid	Identifier that the system assigned to the call. This identifier remains the same for all legs of the call. This is the sessionID of the IVR call; that is, the call that the supervisor makes to monitor other Unified CCX calls.	decimal(18) NOT NULL Primary Key
startmonitoringreqtime	The time and date that the remote supervisor attempted to monitor the agent.	datetime year to fraction (3) NOT NULL Primary Key
remoteloginid	The numeric ID the supervisor enters before starting to monitor a call	varchar(50,0) NULL
rmonid	Numeric ID of the supervisor who does the monitoring.	int NOT NULL
endmonitoringtime	The date and time the monitoring ended.	datetime year to fraction (3) NOT NULL

Field Name	Description	Storage
origmonitoredid	If origMonitoredIDType is: <ul style="list-style-type: none"> • 1 (agent), this field contains the extension of the agent being monitored. • 2 (CSQ), this field contains the CSQ ID of the CSQ being monitored. 	int NOT NULL
origmonitoredidtype	Indicates an agent or a CSQ. <ul style="list-style-type: none"> • 1 = agent • 2 = CSQ 	smallint NOT NULL
cause	The termination cause of a monitoring session: <ul style="list-style-type: none"> • 3 = Normal (Monitored) • 100 = Normal (Agent RNA) • 0 = Error (Other) • -9 = Error (Unable to Stop Monitoring) • -8 = Error (Unable to Monitor New Call) • -7 = Error (Agent Logged Off) • -6 = Error (Network Problem) • -5 = Error (VoIP Server unable to communicate) • -4 = Error (Monitoring not allowed) • -3 = Error (Agent not logged in) • -2 = Error (Invalid input) • -1 = Error (Other) 	smallint NULL
sessionSeqNum	The sequence number for the IVR call; that is, the call the supervisor makes to monitor other Unified CCX calls.	smallint NOT NULL
monitoredSessionID	The sessionID of the monitored Unified CCX call.	decimal(18) NOT NULL
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Field Name	Description	Storage
gmtOffset	Offset, in minutes, between the local time of the Unified CCX server and Greenwich Mean Time. As the time information is stored in GMT, this field will always be zero.	int NULL
nodeID	Unique identifier assigned to each server in the cluster.	smallint NOT NULL Primary Key

Related Topics

- [AgentConnectionDetail](#), on page 5
- [ContactCallDetail](#), on page 31
- [ContactQueueDetail](#), on page 38
- [ContactRoutingDetail](#), on page 40
- [ContactServiceQueue](#), on page 41
- [MonitoredResourceDetail](#), on page 63
- [RmonUser](#), on page 76

Resource

Database table name: Resource

The Unified CCX system creates a new record in the Resource table when the Unified CCX system retrieves agent information from the Unified CM.

A Resource record contains information about the resource (agent). One such record exists for each active and inactive resource. When a resource is deleted, the old record is flagged as inactive; when a resource is updated, a new record is created and the old one is flagged as inactive.

Table 42: Resource Table Fields

Field Name	Description	Storage
resourceID	Numeric identifier of the resource.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceLoginID	The login name assigned to the resource in the Unified CM.	nvarchar(50,0) NOT NULL
resourceName	The first name and the last name of the resource.	nvarchar(50,0) NOT NULL

Field Name	Description	Storage
resourceGroupID	Resource group to which the resource belongs. Null if no resource group is assigned to the resource.	int NULL
resourceType	Type of the resource: 1—Agent 2—Supervisor 3—Administrator	smallint NOT NULL
active	Whether this record is active: f—Inactive t—Active A record becomes inactive if the resource is deleted or updated.	boolean NOT NULL
au toAvail	Determines whether the resource goes to Ready State after handling a Unified CCX call: f—No t—Yes	boolean NOT NULL
extension	The Unified CCX extension of the resource.	nvarchar(50,0) NOT NULL
orderInRG	Order in which the resource resides within the resource group. Null if no resource group is assigned to the resource.	int NULL
dateInactive	If the active field is “f”, date and time that the record became inactive.	datetime year to fraction(3) NULL
resourceSkillMapID	Identifier used to locate the associated skill set of the resource in the ResourceSkillMapping table. The ResourceSkillMapping table can contain multiple records for one resource.	int NOT NULL
assignedTeamID	Identifier of the resource’s assigned team.	int NOT NULL
resourceFirstName	The resource’s first name.	nvarchar(50,0) NOT NULL

Field Name	Description	Storage
resourceLastName	The resource's last name.	nvarchar(50,0) NOT NULL
resourceAlias	The resource's alias name.	nvarchar(50,0) NULL
capabilities	Advanced Supervisor Capabilities for the resource.	smallint NOT NULL

Related Tables

- [AgentConnectionDetail](#), on page 5 (via resourceID, profileID)
- [AgentStateDetail](#), on page 8 (resourceID maps to agentID, via profileID)
- [ContactCallDetail](#), on page 31 (resourceID maps originatorID/destinationID when originatorType/destinageType is 1, via profileID)
- [ContactQueueDetail](#), on page 38 (resourceID maps to targetID when targetType is 1, via profileID)
- [MonitoredResourceDetail](#), on page 63 (resourceID maps to monitoredRsrcID, via profileID)
- [ProfileIDMapping](#), on page 65 (via profileID)
- [RemoteMonitoringDetail](#), on page 68 (resourceID maps to origMonitoredID when origMonitoredIDType is 1, via profileID)
- [ResourceGroup](#), on page 73 (via resourceGroupID, profileID)
- [ResourceSkillMapping](#), on page 73 (via resourceSkillMapID, profileID)
- [Supervisor](#), on page 82 (via resourceLoginID, profileID)
- [Team](#), on page 85 (assignedTeamID maps to teamID, via profileID)

Related Topics

- [AgentConnectionDetail](#), on page 5
- [AgentStateDetail](#), on page 8
- [ContactCallDetail](#), on page 31
- [ContactQueueDetail](#), on page 38
- [MonitoredResourceDetail](#), on page 63
- [ProfileIDMapping](#), on page 65
- [RemoteMonitoringDetail](#), on page 68
- [ResourceGroup](#), on page 73
- [ResourceSkillMapping](#), on page 73
- [Supervisor](#), on page 82
- [Team](#), on page 85

ResourceGroup

Database table name: ResourceGroup

The Unified CCX system creates a new record in the ResourceGroup table when a resource group is set up in the Unified CCX Administration.

A ResourceGroup record contains information about the resource group. One such record exists for each active and inactive resource group.

Table 43: Resource Group Table Fields

Field Name	Description	Storage
resourceGroupID	Numeric identifier of the resource group.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceGroupName	Name of the resource group, as set up in the Unified CCX Administration.	nvarchar(50,0) NULL
active	Whether the record is active in the Unified CCX system: f—Inactive t—Active A record becomes inactive if the resource group is deleted or updated.	boolean NOT NULL
dateInactive	If the active field is “f”, date and time that the record became inactive.	datetime year to fraction(3) NULL

Related Topics

[ContactServiceQueue](#) , on page 41

[ProfileIDMapping](#), on page 65

[Resource](#) , on page 70

ResourceSkillMapping

Database table name: ResourceSkillMapping

The Unified CCX system creates a new record in the ResourceSkillMapping table when an agent is associated with a skill in the Unified CCX Administration.

A ResourceSkillMapping record contains information about all of the skills that are assigned to resources.

Table 44: ResourceSkillMapping Table Fields

Field Name	Description	Storage
resourceSkillMapID	Identifier of the skill set that is associated with a resource.	int NOT NULL Primary Key
skillID	Identifier of the skill that is associated with a resource.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
competenceLevel	Competence level associated with the skill, as set up in the Unified CCX Administration. Values range from 1 (lowest) to 10 (highest).	smallint NOT NULL
active	Whether the record is active in the Unified CCX system: f—Inactive t—Active A record becomes inactive if the resource group is deleted or updated.	boolean NOT NULL

Related Topics

[ProfileIDMapping](#), on page 65

[Resource](#), on page 70

[Skill](#), on page 80

RmonCSQConfig

Database table name: RmonCSQConfig

The Remote Monitoring Contact Service Queue Configuration table contains the CSQs that a remote monitoring supervisor is allowed to monitor (the supervisor's allowed list). This table is updated when you configure the Unified CCX system through the Unified CCX Administration pages.

Table 45: RmonCSQConfig Table Fields

Field Name	Description	Storage
rmonID	Numeric identifier of the remote supervisor.	int NOT NULL Primary Key

Field Name	Description	Storage
contactServiceQueueID	The numeric identifier of the CSQ, relating to contactServiceQueueID in the ContactServiceQueue table.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Related Topics

[ContactServiceQueue](#) , on page 41

[RmonResConfig](#), on page 75

[RmonUser](#) , on page 76

RmonResConfig

Database table name: RmonResConfig

The Remote Monitoring Resource Configuration table contains the list of the agents (resources) that a remote monitoring supervisor is allowed to monitor (the supervisor's allowed list). This table is updated when you configure the system through the Unified CCX Administration pages.

Table 46: RmonResConfig Table Fields

Field Name	Description	Storage
rmonID	Numeric identifier of the remote supervisor.	int NOT NULL Primary Key
resourceLoginID	The login ID of the resource that the remote supervisor is allowed to monitor.	nvarchar(50,0) NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Related Topics

[ProfileIDMapping](#), on page 65

[Resource](#) , on page 70

[RmonCSQConfig](#) , on page 74

[RmonUser](#) , on page 76

RmonUser

Database table name: RmonUser

The Remote Monitoring User table provides information about the supervisor who is logged in to remotely monitor agents.

Table 47: RmonUser Table Fields

Field Name	Description	Storage
rmonID	Numeric identifier of the remote supervisor.	int NOT NULL Primary Key
LoginID	User login name of the remote supervisor.	nvarchar(50,0) NOT NULL
name	Name of the supervisor.	nvarchar(50,0) NOT NULL
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
type	The type of supervisor: 0 = regular supervisor 1 = remote monitoring supervisor	int NOT NULL
active	Determines whether the remote supervisor is active. f = inactive t = active	boolean NOT NULL
dateInactive	Date and time the remote supervisor became inactive.	datetime year to second NULL

Related Topics

[RmonResConfig](#), on page 75

[RemoteMonitoringDetail](#), on page 68

[RmonCSQConfig](#), on page 74

RtCSQsSummary

Database table name: RtCSQsSummary

The rtcsqsummary table contains real-time statistics about all configured Contact Service Queues in the system. This table gets updated automatically when real-time snapshot data writing for this table is enabled through the Unified CCX Administration pages (**Tools > Real-time snapshot configuration** menu option). The updating frequency is based on the configured data writing interval.

Table 48: RtCSQsSummary Table Fields

Field Name	Description	Storage
csqname	Name of the contact service queue.	nvarchar(50,0) NOT NULL Primary Key
loggedinagents	Number agents who are logged in.	int NULL
availableagents	Number of available (idle) agents.	int NULL
unavailableagents	Number of unavailable agents.	int NULL
totalcalls	Total number of calls.	int NULL
oldestcontact	Oldest contact in the queue.	int NULL
callshandled	Number of calls handled.	int NULL
callsabandoned	Number of calls abandoned.	int NULL
callsdequeued	Number of calls dequeued.	int NULL
avgtalkduration	Average talk duration.	int NULL
avgwaitduration	Average wait duration.	int NULL
longesttalkduration	Longest talk duration.	int NULL

Field Name	Description	Storage
longestwaitduration	Longest wait duration.	int NULL
callswaiting	Number of calls waiting.	int NULL
enddatetime	The date and time that this table data was last updated.	datetime year to second NULL
workingagents	Number of agents who are in the working state.	int NULL
talkingagents	Number of agents who are in the talking state.	int NULL
reservedagents	Number of agents who are in the reserved state.	int NULL
startdatetime	The date and time that this table's statistics get collected.	datetime year to second NULL
convavgtalkduration	Average talk duration in HH:MM:SS format.	varchar(25,0) NULL
convavgwaitduration	Average wait duration in HH:MM:SS format.	varchar(25,0) NULL
convlongesttalkduration	Longest talk duration in HH:MM:SS format.	varchar(25,0) NULL
convlongestwaitduration	Longest wait duration in HH:MM:SS format.	varchar(25,0) NULL
convoldestcontact	Oldest call in the queue in HH:MM:SS format.	varchar(25,0) NULL

RtICDStatistics

Database table name: RtICDStatistics

The RtICDStatistics table contains real-time summary statistics about Unified CCX. This table gets updated automatically when real-time snapshot data writing for this table is enabled through the Unified CCX

Administration pages (**Tools > Real-time snapshot configuration** menu option). The updating frequency is based on the configured data writing interval.

Table 49: RtICDStatistics Table Fields

Field Name	Description	Storage
type	Contact Service Queue type that identifies the contact type it services. It can be either voice or e-mail.	nvarchar(50,0) NOT NULL Primary Key
totalcsqs	Number of CSQs configured.	int NULL
loggedinagents	Number of agents who are logged in.	int NULL
workingagents	Number of agents who are in the working state.	int NULL
reservedagents	Number of agents who are in the reserved state.	int NULL
talkingagents	Number of agents who are in the talking state.	int NULL
availableagents	Number of available (idle) agents.	int NULL
unavailableagents	Number of unavailable agents.	int NULL
totalcalls	Total number of calls.	int NULL
callswaiting	Number of calls waiting.	int NULL
callshandled	Number of calls handled.	int NULL
callsabandoned	Number of calls abandoned.	int NULL
avgtalkduration	Average talk duration.	int NULL

Field Name	Description	Storage
avgwaitduration	Average wait duration.	int NULL
longesttalkduration	Longest talk duration.	int NULL
longestwaitduration	Longest wait duration.	int NULL
oldestcontact	Oldest contact in the queue.	int NULL
startdatetime	Data collection starting time.	datetime year to second NULL
enddatetime	Date and time this table was last updated.	datetime year to second NULL
convavgtalkduration	Average talk duration in HH:MM:SS format.	varchar(25,0) NULL
convavgwaitduration	Average wait duration in HH:MM:SS format.	varchar(25,0) NULL
convlongesttalkduration	Longest talk duration in HH:MM:SS format.	varchar(25,0) NULL
convlongestwaitduration	Longest wait duration in HH:MM:SS format.	varchar(25,0) NULL
convoldestcontact	Oldest call in the queue in HH:MM:SS format.	varchar(25,0) NULL

Skill

Database table name: Skill

The Unified CCX system creates a new record in the Skill table when a skill is set up in the Unified CCX Administration.

A Skill record contains information about a skill. One such record exists for each configured skill.

Table 50: Skill Table Fields

Field Name	Description	Storage
skillID	Numeric identifier of the skill.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
skillName	Name of the skill, as set up in the Unified CCX Administration.	nvarchar(50,0) NOT NULL
active	Determines whether the record is active in the Unified CCX system: f—Inactive t—Active A record becomes inactive if the skill is deleted or updated.	boolean NOT NULL
dateInactive	If the active field is “f”, date and time that the record became inactive.	datetime year to fraction(3) NULL

Related Topics

[ProfileIDMapping](#), on page 65

[ResourceSkillMapping](#), on page 73

[SkillGroup](#), on page 81

SkillGroup

Database table name: SkillGroup

The Unified CCX system creates a new record in the SkillGroup table when skills are associated with a CSQ in the Unified CCX Administration.

A SkillGroup record describes each skill that is associated with the CSQ.

Table 51: Skill Group Table Fields

Field Name	Description	Storage
skillGroupID	Numeric identifier of the skill group.	int NOT NULL Primary Key

Field Name	Description	Storage
skillID	Numeric identifier of the skill.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
competenceLevel	Minimum acceptable skill level for agents with this skill, as set up in the Unified CCX Administration. Values range from 1 (lowest) to 10 (highest).	smallint NOT NULL
active	Determines whether the record is active in the CSQ: f—Inactive t—Active A record becomes inactive if the new skill group is deleted or updated.	boolean NOT NULL
skillWeight	Skills within a CSQ can be assigned weights. This field is used in the weighted skill calculation of the skill-based resource selection algorithm. Default value is 1.	int NOT NULL
skillOrder	Skills within a CSQ can be ordered. This field is used in the order skill calculation of the skill-based resource selection algorithm. Default value is 1.	int NOT NULL

Related Topics

[ContactServiceQueue](#) , on page 41

[ProfileIDMapping](#), on page 65

[Skill](#) , on page 80

Supervisor

Database table name: Supervisor

The Supervisor table contains the information about supervisors.

Table 52: Supervisor Table Fields

Field Name	Description	Storage
recordID	Numeric identifier of this supervisor.	int NOT NULL Primary Key
resourceLoginID	User ID in the Unified CM configuration.	nvarchar(50,0) NOT NULL
managedTeamID	Team identifier of the managed team.	int NOT NULL
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
supervisorType	Type of supervisor for this team 0 = Primary 1 = Secondary	smallint NOT NULL
active	Indicates whether the record is active in the Unified CCX system. A record becomes inactive if a team is deleted or updated. f = Inactive t = Active	boolean NOT NULL
dateInactive	Date this record was deleted.	datetime year to second NULL

Related Topics

[Resource](#) , on page 70

[ProfileIDMapping](#), on page 65

[Team](#), on page 85

SupervisorCampaignMap

Database table name: SupervisorCampaignMap

This table provides the list of campaigns that are managed by Supervisors. A Supervisor can be associated with one or more campaigns to manage.

Table 53: SupervisorCampaignMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key
profileid	An identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceloginid	The login name assigned to the resource in the Unified CM.	nvarchar(50,0) NOT NULL
campaignid	A unique identifier for the campaign.	int NOT NULL
active	Indicates whether the record is active.	boolean NOT NULL
dateinactive	Date this record is deleted.	datetime year to second NULL

Related Topics

[ProfileIDMapping](#), on page 65

[Campaign](#), on page 15

[Resource](#) , on page 70

SupervisorApplicationMap

Database table name: SupervisorApplicationMap

This table provides the list of applications that are managed by Supervisors. A Supervisor can be associated with one or more applications to manage.

Table 54: SupervisorApplicationMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key

Field Name	Description	Storage
profileid	An identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
resourceloginid	The login name assigned to the resource in the Unified CM.	nvarchar(50,0) NOT NULL
applicationid	A unique identifier for the application.	int NOT NULL
active	Indicates whether the record is active.	boolean NOT NULL
dateinactive	Date this record is deleted.	datetime year to second NULL

Related Topics

[ProfileIDMapping](#), on page 65

[CrsApplication](#), on page 45

[Resource](#), on page 70

Team

Database table name: Team

The Team table contains information about specific teams.

Table 55: Team Table Fields

Field Name	Description	Storage
teamID	Numeric identifier for this team.	int NOT NULL Primary Key
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
teamName	Name of this team.	nvarchar(50,0) NOT NULL

Field Name	Description	Storage
active	Indicates whether the record is active in the Unified CCX system. A record becomes inactive if a team is deleted or updated. f = Inactive t = Active	boolean NOT NULL
dateInactive	Date this record was deleted.	datetime year to fraction(3) NULL

Related Topics

[ProfileIDMapping](#), on page 65

[Resource](#), on page 70

[Supervisor](#), on page 82

[TeamCSQMapping](#), on page 86

TeamCSQMapping

Database table name: TeamCSQMapping

The TeamCSQMapping table shows the relationship between Teams and CSQs; for example, Team 1 is CSQ3, Team 4 is CSQ10.

Table 56: TeamCSQMapping Table Fields

Field Name	Description	Storage
recordID	Numeric identifier for this record.	int NOT NULL Primary Key
csqID	Numeric identifier for the CSQ.	int NOT NULL
teamID	Numeric identifier for the team.	int NOT NULL
profileID	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key

Field Name	Description	Storage
active	Indicates whether the record is active in the Unified CCX system. A record becomes inactive if a team is deleted or updated. f = Inactive t = Active	boolean NOT NULL
dateInactive	Date this record was deleted.	datetime year to second NULL

Related Tables

- [ContactServiceQueue](#) , on page 41 (csqID maps to contactServiceQueueID, and via profileID)
- [ProfileIDMapping](#), on page 65 (via ProfileID)
- [Team](#), on page 85 (via teamID and profileID)

Related Topics

[ContactServiceQueue](#) , on page 41

[ProfileIDMapping](#), on page 65

[Team](#), on page 85

TextAgentConnectionDetail

Database table name: TextAgentConnectionDetail

The Unified CCX system creates a new record in the TextAgentConnectionDetail table when an agent disconnects a contact or a leg by hanging up or by transferring the contact. A new contact or leg starts each time that a contact is transferred.

The TextAgentConnectionDetail record contains information relating to the agent who handled the contact or leg.

Table 57: TextAgentConnectionDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for the contact.	varchar (64,0) NOT NULL Primary Key
ContactSeqNum	Contact sequence number that the system assigned to the contact or the leg. Each leg of a contact is assigned a new contact sequence number. To be used later.	smallint NOT NULL Primary Key

Field Name	Description	Storage
nodeID	Numeric identifier for the node.	smallint NOT NULL
resourceID	Numeric identifier for the resource.	int NOT NULL Primary Key
startDateTime	Date and time that the contact or leg entered the system.	datetime year to fraction (3) NOT NULL Primary Key
endDateTime	Date and time that the contact or the leg was transferred or disconnected.	datetime year to fraction (3) NOT NULL
qIndex	A new qIndex is created whenever a Unified CCX contact is conferenced to a Unified CCX route point. To be used later.	smallint NOT NULL
acceptTime	Amount of time, in seconds, that passed from the time a contact or leg was presented to an agent and the agent answered the contact.	smallint NULL
talkTime	Amount of time, in seconds, that passed from the time an agent answered the contact or the leg to the time the contact or the leg was disconnected or transferred, not including hold time.	smallint NULL
workTime	Amount of time, in seconds, that an agent spent in Work State after the contact or the leg. To be used later.	smallint NULL
WrapupData	The contact information that the agent enters after the contact is handled through the Agent Desktop user interface.	varchar(40,0) NULL
contactdisposition	Disposition of the contact.	smallint NOT NULL Default: 0

Related Topics

[TextContactDetail](#) , on page 90

[TextContactQueueDetail](#), on page 93

TextAgentStateDetails

Database table name: TextAgentStateDetail

The Unified CCX system creates a new record in the TextAgentStateDetail table each time the state of the agent changes while the agent is handling chat and email. The TextAgentStateDetail record contains information about the agent and about the event that caused the agent state to change.

Table 58: TextCustomerDetail Table Fields

Field Name	Description	Storage
agentID	Identifier of the agent whose state has changed.	int NOT NULL Primary Key
stateChangeDatetime	Date and time that the chat agent state changed.	datetime year to fraction (3) NOT NULL Primary Key
agentStateID	Event that triggered the chat agent state change: 0—Logon 1—Log off 2—Not available 3—Available 4—Busy 5—Unknown 6—Partial busy 7—Reserved	smallint NOT NULL Primary Key
reasonCode	Code, as written to the database, for the reason that the chat agent changed to Not Ready state or to Log Out state. 32750—Non chat agent 32755—Contact ended 32757—Media handler failure 32760—Login 32763—Contact not accepted 32764—CCX failure 32765—Connection down	smallint NOT NULL Primary Key

Field Name	Description	Storage
routingType	Routing type of the contact or leg: 1—Interactive 2—Non Interactive	smallint NOT NULL Primary Key

TextAgentWrapupDetail

Database table name: TextAgentWrapupDetail

The Unified CCX system creates a new record in the TextAgentWrapupDetail table each time the agent enters a Wrap-Up detail.

Table 59: TextAgentWrapupDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for the contact.	varchar (64,0) NOT NULL Primary Key
resourceID	Numeric identifier for the resource.	int NOT NULL Primary Key
reasonID	Numeric identifier for the reason.	int NOT NULL
wrapupTime	Date and time that the Wrap-Up is applied.	datetime year to fraction (3) NOT NULL Primary Key
MediaType	Type of the media such as email and other media types. 1—Chat 3—Email	smallint NULL

TextContactDetail

Database table name: TextContactDetail

The Unified CCX system creates a new record in the TextContactDetail table for each chat and email contact or leg processed by the system. A new contact or leg starts each time a contact is transferred or redirected.

A TextContactDetail record contains detailed information about the contact or leg. At least one such record will exist for each contact or leg.

Table 60: TextContactDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for this record.	varchar (64,0) NOT NULL Primary Key
ContactSeqNum	Contact sequence number that the system assigned to the contact or the leg. Each leg of a contact is assigned a new contact sequence number. To be used later.	smallint NOT NULL Primary Key
nodeID	Numeric identifier for the node.	smallint NOT NULL
contactType	Type of contact or leg: 1—Incoming. Outside contact received by the Unified CCX system.	smallint NOT NULL
mediaType	Type of the media such as email and other media types. 1—Chat 3—Email	smallint NOT NULL
contactDisposition	Disposition of the contact or the leg. 1—Abandoned 2—Handled 3—Do not care 4—Aborted ⁸ 5—Rejected 6—Cleared 7—Unknown	smallint NOT NULL

Field Name	Description	Storage
dispositionReason	Reason why the contact is aborted or rejected by the system. <ul style="list-style-type: none"> • Unknown • Chat_agent_ended • Chat_customer_ended • Chat_agent_aborted • Chat_agent_abandoned • Chat_customer_abandoned • Chat_abandoned_timeout • Chat_customer_abandoned • Chat_customer_waited • Chat_system_failure • Chat_system_failure_before_agent_joined • Chat_agent_connection_failure • Chat_agent_end_before_in_chatroom 	varchar(100,0) NULL
originatorType	Originator of the contact or the leg: 1—Agent. Contact originated by an agent. 2—Unknown. Contact originated from outside.	smallint NOT NULL
originator	Numeric identifier of the agent who originated the contact or the leg. Used only if originatorType is 1.	nvarchar(50,0) int NULL
destinationType	Destination of the contact or the leg: 1—Agent. Contact presented to an agent. Null if no destination.	smallint NOT NULL
destination	Numeric identifier of the agent who received the contact or the leg. Used only if destinationType is 1.	nvarchar(50,0) int NULL
startDateTime	Date and the time that the contact or the leg is presented to the agent.	datetime year to fraction (3) NOT NULL

Field Name	Description	Storage
endDateTime	Date and time that the contact or the leg is transferred or disconnected.	datetime year to fraction (3) NOT NULL
tagID	The string with which the contact or the leg is tagged.	nvarchar(50,0) NULL
source	Source from which the contact originated. 1—Bubble Chat 2—Fb Messenger -1—Others	smallint

⁸ For aborted calls, the corresponding value in ContactQueueDetail.disposition = 1 (abandoned).

Related Topics

[TextAgentConnectionDetail](#) , on page 87

[TextContactQueueDetail](#), on page 93

TextContactQueueDetail

Database table name: TextContactQueueDetail

The Unified CCX system writes the record when the contact is queued for chat and email CSQs; then one of the following happens:

- Contact or leg is abandoned while queued for chat and email CSQs
- Contact or leg is being dequeued
- Contact or leg is connected to an agent

Table 61: TextContactQueueDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for the contact.	varchar (64,0) NOT NULL Primary Key
ContactSeqNum	Contact sequence number that the system assigned to the contact or the leg. Each leg of a call is assigned a new contact sequence number. To be used later.	smallint NOT NULL Primary Key
nodeID	Numeric identifier for the node.	smallint NOT NULL

Field Name	Description	Storage
csqRecordID	Numeric identifier for the chat and email CSQ.	int NOT NULL Primary Key
qIndex	A new qIndex is created whenever a Unified CCX contact is conferenced to a Unified CCX route point. To be used later.	smallint NOT NULL Primary Key
disposition	Disposition for this leg of the contact for this CSQ. <ul style="list-style-type: none"> • Abandoned = 1⁹ • Handled by CSQ = 2 • Dequeued from CSQ = 3 • Handled by another CSQ = 4 	smallint NULL
metServiceLevel	Contact answered within the configured number of seconds of queue time for this CSQ. <ul style="list-style-type: none"> • Yes = t • No = f To be used later.	boolean NULL
queueTime	Number of seconds the contact spent in queue for this CSQ and this leg of the contact.	int NULL

⁹ For aborted calls, ContactQueueDetail.disposition = 1 and the corresponding ContactCallDetail.contactDisposition = 4 (aborted).

Related Topics

[TextAgentConnectionDetail](#) , on page 87

[TextContactDetail](#) , on page 90

[ContactServiceQueue](#) , on page 41

TextCustomerDetails

Database table name: TextCustomerDetail

The Unified CCX system creates a new record in the TextCustomerDetails table when a chat and email agent receives the contact.

The TextCustomerDetail table captures customer related information corresponding to the chat and email contact. Maximum 10 customer fields can be persisted in the table. The chat and email customer is advised to limit each field value as per the details mentioned in the below table so that the data truncation will not

happen while storing the customer data into the database. Customer can write custom reports on top of this historical reporting table and use the persisted data.

Table 62: TextCustomerDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for this record.	nvarchar (64,0) NOT NULL Primary Key
FieldID1 to FieldID10	The unique field IDs corresponding to the field names in the non-voice contact or MediaCustomerDataMapping table. In actual table schema there are 10 individual columns named FieldID1 through FieldID10.	int NOT NULL
FieldValue1 to FieldValue5 FieldValue9 to FieldValue10	Indicates the field values provided for the corresponding field names in the non-voice contact or MediaCustomerDataMapping table. In actual table schema there are 10 individual columns named FieldValue1 through FieldValue10.	lvarchar (600) NOT NULL
FieldValue6 to FieldValue8	Indicates the field values provided for the corresponding field names in the non-voice contact or MediaCustomerDataMapping table. In case of email contact the field values 6 to 8 are used for the Agent added email addresses in the CC, BCC and To fields respectively.	lvarchar (5080) NULL
InsertionDate	Indicates the date and time of insertion.	datetime year to fraction(3) NOT NULL

Related Topics

[ChatUserForm](#), on page 27

[TextContactDetail](#), on page 90

[MediaCustomerDataMapping](#), on page 64

TextRatingDetail

Database table name: TextRatingDetail

The Unified CCX system creates a new record in the TextRatingDetail table each time the customer rates a chat experience.

Table 63: TextRatingDetail Table Fields

Field Name	Description	Storage
ContactID	Alphanumeric identifier for this record.	varchar (64) NOT NULL Primary Key
Rating	The rating given by the customer.	smallint NOT NULL
RatingTime	Date and time the customer assigned the rating.	datetime year to fraction (3) NOT NULL

Related Topics

[TextAgentStateDetails](#), on page 89

[TextCustomerDetails](#), on page 94

[TextContactQueueDetail](#), on page 93

[TextAgentWrapupDetail](#), on page 90

[TextContactDetail](#) , on page 90

[TextAgentConnectionDetail](#) , on page 87

WorkflowTask

Database table name: WorkflowTask

A WorkflowTask record contains information about a task or a subtask that runs on the Unified CCX system.

Table 64: WorkflowTask Table Fields

Field Name	Description	Storage
taskID	Identifier of the task.	decimal(18,0) NOT NULL Primary Key
parentTaskID	Identifier of the parent task, if the task is a subtask.	decimal(18,0) NULL
startDateTime	Date and the time that the task started executing.	datetime year to second NULL
endDateTime	Date and the time that the task completed executing.	datetime year to second NULL

Field Name	Description	Storage
applicationServerID	Unique identifier assigned to each Unified CCX server in the cluster.	smallint NOT NULL Primary Key

Related Topics

[AgentConnectionDetail](#), on page 5

[ContactCallDetail](#), on page 31

[ContactQueueDetail](#), on page 38

[ContactRoutingDetail](#), on page 40

[MonitoredResourceDetail](#), on page 63

[RemoteMonitoringDetail](#), on page 68

WrapupCategory

Database table name: WrapupCategory

Wrap-Up reason category information is stored in this table. A Wrap-Up Reason is associated with one or more CSQs. This mapping of Wrap-Up Reasons and CSQs is stored separately in wrapupCsqMap table.

Table 65: WrapupCategory Table Fields

Field Name	Description	Storage
categoryid	A unique identifier for the Wrap-Up category.	int NOT NULL Primary Key
profileid	Identifier of the Unified CCX profile that is associated with this record.	int NOT NULL Primary Key
recordid	A unique identifier for the record.	int NOT NULL Primary Key
name	The name of the Wrap-Up category.	nvarchar(160,0) NOT NULL
type	The type of interaction for which the Wrap-Up reason is applied. For example, Non-Voice.	lvarchar(40) NOT NULL
global	Indicates whether the Wrap-Up category is tagged at global or CSQ level.	boolean NOT NULL

Field Name	Description	Storage
active	Indicates whether the record is currently active.	boolean NOT NULL
dateinactive	The date and time when the record became inactive.	datetime year to second NULL
createdatetime	The date and time that the record is created. Default value: Current year to second.	bigint NULL

WrapupReasons

Database table name: WrapupReasons

This table stores the details about the Wrap-Up reasons that are configured by the administrator.

Table 66: WrapupReasons Table Fields

Field Name	Description	Storage
reasonid	A unique identifier for the Wrap-Up reason.	int NOT NULL Primary Key
categoryid	A unique identifier for the Wrap-Up category.	int NOT NULL
reason	The name of the Wrap-Up reason.	nvarchar(160,0) NOT NULL
active	Indicates whether the record is currently active.	boolean NOT NULL
dateinactive	The date and time when the record became inactive.	datetime year to second NULL
createdatetime	The date and time that the record is created. Default value: Current year to second.	bigint NULL

WrapupCsqMap

Database table name: WrapupCsqMap

The mapping of Wrap-Up Reasons and CSQs is stored in this table.

Table 67: WrapupCsqMap Table Fields

Field Name	Description	Storage
recordid	A unique identifier for the record.	int NOT NULL Primary Key
categoryid	A unique identifier for the Wrap-up Category.	int NOT NULL
csqid	A unique identifier for the CSQ from the ContactServiceQueue table.	int NOT NULL
active	Indicates whether the record is currently active.	boolean NOT NULL
dateinactive	The date and time when the record became inactive.	datetime year to second NULL
createdatetime	The date and time that the record is created. Default value: Current year to second.	bigint NULL

