

About this Guide

Note The ASR 5000 hardware platform has reached end of life and is not supported in this release. Any references to the ASR 5000 (specific or implied) or its components in this document are coincidental. Full details on the ASR 5000 hardware platform end of life are available at:

https://www.cisco.com/c/en/us/products/collateral/wireless/asr-5000-series/eos-eol-notice-c51-735573.html.

This preface describes the Command Line Interface Reference and its document conventions.

This reference describes how to use the command line interface (CLI) to interact with the products supported by the StarOSTM. The CLI commands are organized by command modes in the code and in this reference. The command modes are presented alphabetically. The description of each command states the command's function, describes its syntax, presents limitations when applicable, and offers an example of its usage.

- CLI Command Sections, on page i
- Conventions Used, on page ii
- Supported Documents and Resources, on page iv
- Contacting Customer Support, on page v

CLI Command Sections

The following table describes the individual sections in the command descriptions presented in this reference.

Section	Description
Product	The product(s) supporting the CLI command.
Privilege	The user privilege levels having access to the CLI command.
	For more information on user types and user privileges, refer to the <i>CLI Administrative Users</i> section in the <i>Command Line Interface Overview</i> chapter.

Section	Description
Mode	The command and configuration mode sequences to the CLI configuration mode for the CLI command.
	For more information on command modes, refer to the <i>CLI Command Modes</i> section in the <i>Command</i> <i>Line Interface Overview</i> chapter.
Syntax	The command's syntax.
	For more information on CLI command syntax, refer to the <i>CLI Command Syntax</i> section in the <i>Command</i> <i>Line Interface Overview</i> chapter.
	Description of the keyword(s) and variable(s) in the command.
Usage	Information about the command's usage including dependencies and limitations, if any.
Example	Example(s) of the command.

Conventions Used

The following tables describe the conventions used throughout this documentation.

Notice Type	Description
Information Note	Provides information about important features or instructions.
Caution	Alerts you of potential damage to a program, device, or system.
Warning	Alerts you of potential personal injury or fatality. May also alert you of potential electrical hazards.
Typeface Conventions	Description
Text represented as a screen display	This typeface represents displays that appear on your terminal screen, for example: Login:
Text represented as commands	This typeface represents commands that you enter, for example:
	show ip access-list
	This document always gives the full form of a command in lowercase letters. Commands are not case sensitive.

Typeface Conventions	Description
Text represented as a command <i>variable</i>	This typeface represents a variable that is part of a command, for example:
	<pre>show card slot_number</pre>
	<i>slot_number</i> is a variable representing the desired chassis slot number.
Text represented as menu or sub-menu names	This typeface represents menus and sub-menus that you access within a software application, for example:
	Click the File menu, then click New
Command Syntax Conventions	Description
{ keyword or variable }	Required keyword options and variables are those components that are required to be entered as part of the command syntax.
	Required keyword options and variables are surrounded by grouped braces { }. For example:
	<pre>sctp-max-data-chunks { limit max_chunks</pre>
	If a keyword or variable is not enclosed in braces or brackets, it is mandatory. For example:
	snmp trap link-status
[keyword or variable]	Optional keywords or variables, or those that a user may or may not choose to use, are surrounded by brackets.
	Some commands support multiple options. These are documented within braces or brackets by separating each option with a vertical bar.
	These options can be used in conjunction with required or optional keywords or variables. For example:
	<pre>action activate-flow-detection { intitiation termination }</pre>
	or
	<pre>ip address [count number_of_packets size number_of_bytes]</pre>

Supported Documents and Resources

Related Common Documentation

The following common documents are available:

- AAA Interface Administration Reference
- GTPP Interface Administration Reference
- Installation Guide (platform dependant)
- Release Change Reference
- SNMP MIB Reference
- Statistics and Counters Reference
- System Administration Guide (platform dependant)
- Thresholding Configuration Guide

Related Product Documentation

The most up-to-date information for related products is available in the product Release Notes provided with each product release.

The following related product documents are also available:

- ADC Administration Guide
- CF Administration Guide
- ECS Administration Guide
- ePDG Administration Guide
- GGSN Administration Guide
- HA Administration Guide
- HSGW Administration Guide
- IPSec Reference
- IPSG Administration Guide
- MME Administration Guide
- MURAL Software Installation Guide
- MURAL User Guide
- NAT Administration Guide
- PDSN Administration Guide
- PSF Administration Guide
- P-GW Administration Guide
- SAEGW Administration Guide
- SaMOG Administration Guide
- SecGW Administration Guide
- SGSN Administration Guide
- S-GW Administration Guide

Obtaining Documentation

The most current Cisco documentation is available on the following website:

L

http://www.cisco.com/cisco/web/psa/default.html

Use the following path selections to access this documentation:

Products > Wireless > Mobile Internet> Platforms > Cisco ASR 5000 Series > Cisco ASR 5000

Contacting Customer Support

Use the information in this section to contact customer support.

Refer to the support area of http://www.cisco.com for up-to-date product documentation or to submit a service request. A valid username and password are required to access this site. Please contact your Cisco sales or service representative for additional information.